
HPX Documentation

2.0.0

The STE || AR Group

July 05, 2026

USER DOCUMENTATION

Welcome to the *HPX* documentation!

If you're new to *HPX* you can get started with the *Quick start* guide. Don't forget to read the *Terminology* section to learn about the most important concepts in *HPX*. The *Examples* give you a feel for how it is to write real *HPX* applications and the *Manual* contains detailed information about everything from building *HPX* to debugging it. There are links to blog posts and videos about *HPX* in *Additional material*.

You can find a comprehensive list of contact options on [Support for deploying and using HPX¹](#). Do not hesitate to contact us if you can't find what you are looking for in the documentation!

See *Citing HPX* for details on how to cite *HPX* in publications. See *HPX users* for a list of institutions and projects using *HPX*.

There are also available a [PDF](#) version of this documentation as well as a [Single HTML Page](#).

¹ <https://github.com/TheHPXProject/hpx/blob/master/.github/SUPPORT.md>

WHAT IS *HPX*?

HPX is a C++ Standard Library for Concurrency and Parallelism. It implements all of the corresponding facilities as defined by the C++ Standard. Additionally, in *HPX* we implement functionalities proposed as part of the ongoing C++ standardization process. We also extend the C++ Standard APIs to the distributed case. *HPX* is developed by the STE||AR group (see *People*).

The goal of *HPX* is to create a high quality, freely available, open source implementation of a new programming model for conventional systems, such as classic Linux based Beowulf clusters or multi-socket highly parallel SMP nodes. At the same time, we want to have a very modular and well designed runtime system architecture which would allow us to port our implementation onto new computer system architectures. We want to use real-world applications to drive the development of the runtime system, coining out required functionalities and converging onto a stable API which will provide a smooth migration path for developers.

The API exposed by *HPX* is not only modeled after the interfaces defined by the C++11/14/17/20 ISO standard. It also adheres to the programming guidelines used by the Boost collection of C++ libraries. We aim to improve the scalability of today's applications and to expose new levels of parallelism which are necessary to take advantage of the exascale systems of the future.

HPX is a member of the High-Performance Software Foundation ([HPSF](https://hpsf.io)²) network, which signals its commitment to the open-source, high-performance computing (HPC) community. By joining [HPSF](https://hpsf.io)³ - and, concurrently, the Linux Foundation - *HPX* gains access to a broader collaborative ecosystem that promotes shared standards, interoperable tools, and joint research initiatives, all of which accelerates the development of scalable parallel applications. This dual affiliation enhances *HPX*'s credibility, attracting contributors and industry partners who value the rigorous governance and transparent development practices upheld by both organizations. Consequently, *HPX* can more effectively influence the direction of future HPC frameworks while benefiting from the collective expertise, resources, and industry backing provided by [HPSF](https://hpsf.io)⁴ and the Linux Foundation.

² <https://hpsf.io/projects/hpx/>

³ <https://hpsf.io/projects/hpx/>

⁴ <https://hpsf.io/projects/hpx/>

WHAT'S SO SPECIAL ABOUT *HPX*?

- *HPX* exposes a uniform, standards-oriented API for ease of programming parallel and distributed applications.
- It enables programmers to write fully asynchronous code using hundreds of millions of threads.
- *HPX* provides unified syntax and semantics for local and remote operations.
- *HPX* makes concurrency manageable with dataflow and future based synchronization.
- It implements a rich set of runtime services supporting a broad range of use cases.
- *HPX* exposes a uniform, flexible, and extendable performance counter framework which can enable runtime adaptivity
- It is designed to solve problems conventionally considered to be scaling-impaired.
- *HPX* has been designed and developed for systems of any scale, from hand-held devices to very large scale systems.
- It is the first fully functional implementation of the ParalleX execution model.
- *HPX* is published under a liberal open-source license and has an open, active, and thriving developer community.

2.1 Quick start

The following steps will help you get started with *HPX*. Before getting started, make sure you have all the necessary prerequisites, which are listed in `_prerequisites`. After *Installing HPX*, you can check how to run a simple example *Hello, World!*. *Writing task-based applications* explains how you can get started with *HPX*. You can refer to our *Migration guide* if you use other APIs for parallelism (like OpenMP, MPI or Intel Threading Building Blocks (TBB)) and you would like to convert your code to *HPX* code.

2.1.1 Installing *HPX*

The easiest way to install *HPX* on your system is by choosing one of the steps below:

1. **vcpkg**

You can download and install *HPX* using the `vcpkg`⁵ dependency manager:

```
$ vcpkg install hpx
```

2. **Spack**

Another way to install *HPX* is using `Spack`⁶:

⁵ <https://github.com/Microsoft/vcpkg>

⁶ <https://spack.readthedocs.io/en/latest/>

```
$ spack install hpx
```

3. Conan

You can also use the [Conan](https://conan.io/)⁷ package manager to build and use *HPX* in your projects. First, export the *HPX* recipe from the *HPX* repository to your local Conan cache:

```
$ git clone https://github.com/TheHPXProject/hpx.git
$ cd hpx
$ conan create . --build=missing
```

This builds *HPX* and makes it available in your local Conan cache. You can then use it in your Conan-based projects by adding it to your `conanfile.txt`:

```
[requires]
hpx/2.0.0

[generators]
CMakeDeps
CMakeToolchain
```

Then use `find_package(HPX REQUIRED)` in your `CMakeLists.txt` as usual. Conan will automatically handle building *HPX* with your chosen configuration options and provide the necessary CMake integration files.

4. Fedora

Installation can be done with [Fedora](https://fedoraproject.org/wiki/DNF)⁸ as well:

```
$ dnf install hpx*
```

5. Arch Linux

HPX is available in the [Arch User Repository \(AUR\)](https://wiki.archlinux.org/title/Arch_User_Repository)⁹ as `hpx` too.

More information or alternatives regarding the installation can be found in the *Building HPX*, a detailed guide with thorough explanation of ways to build and use *HPX*.

2.1.2 Hello, World!

To get started with this minimal example you need to create a new project directory and a file `CMakeLists.txt` with the contents below in order to build an executable using [CMake](https://www.cmake.org)¹⁰ and *HPX*:

```
cmake_minimum_required(VERSION 3.19)
project(my_hpx_project CXX)
find_package(HPX REQUIRED)
add_executable(my_hpx_program main.cpp)
target_link_libraries(my_hpx_program HPX::hpx HPX::wrap_main hpx::iostreams_component)
```

The next step is to create a `main.cpp` with the contents below:

⁷ <https://conan.io/>

⁸ <https://fedoraproject.org/wiki/DNF>

⁹ https://wiki.archlinux.org/title/Arch_User_Repository

¹⁰ <https://www.cmake.org>

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Then, in your project directory run the following:

```
$ mkdir build && cd build
$ cmake -DHPX_DIR=</path/to/hpx/installation> ..
$ make all
$ ./my_hpx_program
```

```
$ ./my_hpx_program
Hello World!
```

The program looks almost like a regular C++ hello world with the exception of the two includes and `hpx::cout`.

- When you include `hpx_main.hpp` *HPX* makes sure that `main` actually gets launched on the *HPX* runtime. So while it looks almost the same you can now use futures, `async`, parallel algorithms and more which make use of the *HPX* runtime with lightweight threads.
- `hpx::cout` is a replacement for `std::cout` to make sure printing never blocks a lightweight thread. You can read more about `hpx::cout` in *The HPX I/O-streams component*.

Note:

- You will most likely have more than one `main.cpp` file in your project. See the section on *Using HPX with CMake-based projects* for more details on how to use `add_hpx_executable`.
- `HPX::wrap_main` is required if you are implicitly using `main()` as the runtime entry point. See *Re-use the main() function as the main HPX entry point* for more information.
- `hpx::iostreams_component` is optional for a minimal project but lets us use the *HPX* equivalent of `std::cout`, i.e., the *HPX The HPX I/O-streams component* functionality in our application.
- You do not have to let *HPX* take over your main function like in the example. See *Starting the HPX runtime* for more details on how to initialize and run the *HPX* runtime.

Caution: Ensure that *HPX* is installed with `HPX_WITH_DISTRIBUTED_RUNTIME=ON` to prevent encountering an error indicating that the `HPX::iostreams_component` target is not found.

When including `hpx_main.hpp` the user-defined `main` gets renamed and the real `main` function is defined by *HPX*. This means that the user-defined `main` must include a return statement, unlike the real `main`. If you do not include the return statement, you may end up with confusing compile time errors mentioning `user_main` or even runtime errors.

2.1.3 Writing task-based applications

So far we haven't done anything that can't be done using the C++ standard library. In this section we will give a short overview of what you can do with *HPX* on a single node. The essence is to avoid global synchronization and break up your application into small, composable tasks whose dependencies control the flow of your application. Remember, however, that *HPX* allows you to write distributed applications similarly to how you would write applications for a single node (see *Why HPX?* and *Writing distributed applications*).

If you are already familiar with `async` and `future` from the C++ standard library, the same functionality is available in *HPX*.

The following terminology is essential when talking about task-based C++ programs:

- **lightweight thread**: Essential for good performance with task-based programs. Lightweight refers to smaller stacks and faster context switching compared to OS threads. Smaller overheads allow the program to be broken up into smaller tasks, which in turns helps the runtime fully utilize all processing units.
- **async**: The most basic way of launching tasks asynchronously. Returns a `future<T>`.
- **future<T>**: Represents a value of type `T` that will be ready in the future. The value can be retrieved with `get` (blocking) and one can check if the value is ready with `is_ready` (non-blocking).
- **shared_future<T>**: Same as `future<T>` but can be copied (similar to `std::unique_ptr` vs `std::shared_ptr`).
- **continuation**: A function that is to be run after a previous task has run (represented by a future). `then` is a method of `future<T>` that takes a function to run next. Used to build up dataflow DAGs (directed acyclic graphs). `shared_futures` help you split up nodes in the DAG and functions like `when_all` help you join nodes in the DAG.

The following example is a collection of the most commonly used functionality in *HPX*:

```
#include <hpx/algorithm.hpp>
#include <hpx/future.hpp>
#include <hpx/init.hpp>

#include <iostream>
#include <random>
#include <vector>

void final_task(hpx::future<hpx::tuple<hpx::future<double>, hpx::future<void>>>>)
{
    std::cout << "in final_task" << std::endl;
}

int hpx_main()
{
    // A function can be launched asynchronously. The program will not block
    // here until the result is available.
    hpx::future<int> f = hpx::async([]() { return 42; });
    std::cout << "Just launched a task!" << std::endl;

    // Use get to retrieve the value from the future. This will block this task
    // until the future is ready, but the HPX runtime will schedule other tasks
    // if there are tasks available.
    std::cout << "f contains " << f.get() << std::endl;
```

(continues on next page)

(continued from previous page)

```

// Let's launch another task.
hpx::future<double> g = hpx::async([]() { return 3.14; });

// Tasks can be chained using the then method. The continuation takes the
// future as an argument.
hpx::future<double> result = g.then([](hpx::future<double>&& gg) {
    // This function will be called once g is ready. gg is g moved
    // into the continuation.
    return gg.get() * 42.0 * 42.0;
});

// You can check if a future is ready with the is_ready method.
std::cout << "Result is ready? " << result.is_ready() << std::endl;

// You can launch other work in the meantime. Let's sort a vector.
std::vector<int> v(1000000);

// We fill the vector synchronously and sequentially.
hpx::generate(hpx::execution::seq, std::begin(v), std::end(v), &std::rand);

// We can launch the sort in parallel and asynchronously.
hpx::future<void> done_sorting =
    hpx::sort(hpx::execution::par(           // In parallel.
              hpx::execution::task),        // Asynchronously.
              std::begin(v), std::end(v));

// We launch the final task when the vector has been sorted and result is
// ready using when_all.
auto all = hpx::when_all(result, done_sorting).then(&final_task);

// We can wait for all to be ready.
all.wait();

// all must be ready at this point because we waited for it to be ready.
std::cout << (all.is_ready() ? "all is ready!" : "all is not ready...")
          << std::endl;

return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

Try copying the contents to your `main.cpp` file and look at the output. It can be a good idea to go through the program step by step with a debugger. You can also try changing the types or adding new arguments to functions to make sure you can get the types to match. The type of the `then` method can be especially tricky to get right (the continuation needs to take the future as an argument).

Note: HPX programs accept command line arguments. The most important one is `--hpx:threads=N` to set the number of OS threads used by HPX. HPX uses one thread per core by default. Play around with the example above

and see what difference the number of threads makes on the `sort` function. See *Launching and configuring HPX applications* for more details on how and what options you can pass to *HPX*.

Tip: The example above used the construction `hpx::when_all(...).then(...)`. For convenience and performance it is a good idea to replace uses of `hpx::when_all(...).then(...)` with `dataflow`. See *Dataflow* for more details on `dataflow`.

Tip: If possible, try to use the provided parallel algorithms instead of writing your own implementation. This can save you time and the resulting program is often faster.

2.1.4 Next steps

If you haven't done so already, reading the *Terminology* section will help you get familiar with the terms used in *HPX*.

The *Examples* section contains small, self-contained walkthroughs of example *HPX* programs. The *Local to remote* example is a thorough, realistic example starting from a single node implementation and going stepwise to a distributed implementation.

The *Manual* contains detailed information on writing, building and running *HPX* applications.

2.2 Tutorials

This section provides structured, video-based learning resources for *HPX*. The tutorials complement the reference documentation with guided, example-driven explanations of core concepts and advanced features.

Each tutorial introduces the relevant concepts and then applies them step by step through practical code examples. The focus is on demonstrating how to design, implement, and reason about parallel and distributed applications using *HPX*. While the main documentation emphasizes API descriptions and detailed reference material, the tutorial series adopts a practical, code-oriented approach.

The tutorials are intended for a broad audience: from beginners setting up *HPX* for the first time to advanced users exploring performance tuning, custom executors, and SIMD vectorization. Together, they form a structured learning path that lowers the entry barrier while progressively introducing more advanced features.

The complete video series is available on YouTube:

[HPX Tutorial Playlist](#)¹¹

The code is available on Github:

HPX Tutorial Code <https://github.com/STELLAR-GROUP/HPX_Tutorials_Code>

¹¹ <https://www.youtube.com/watch?v=OZWTmrIWUF0&list=PL7vEgTL3FalZkvNqssEP9-tXQ5rEwZy2l&index=1>

2.2.1 Available Modules

- **Introduction to |hpx|**

Foundational overview of *HPX*, including its architecture, design principles, and key capabilities in the context of high-performance computing.

- **Building |hpx| on Windows/Unix**

Step-by-step guidance on installing *HPX* and setting up the environment based on your operating system.

- **Running |hpx| applications**

Demonstration on how to build and run a simple Hello World example using *HPX*.

- **Algorithms in |hpx|**

Overview of the parallel algorithms provided by *HPX* and explanation on how execution policies unlock high-performance C++ computing.

- **Vectorization and SIMD in |hpx|**

Introduction to data-parallel programming, SIMD execution policies, and vectorization techniques relevant to modern C++ and HPC workloads.

- **Futures and Asynchronous Programming**

Explanation of the asynchronous programming model in *HPX*, including futures, *async*, and dataflow-based execution patterns.

- **Performance Analysis and Optimization**

Guidance on profiling *HPX* applications, analyzing performance counters, identifying bottlenecks, and applying optimization strategies.

- **Task Scheduling and Custom Executors**

Detailed discussion of the execution model in *HPX*, built-in executors, and mechanisms for defining custom execution strategies.

- **Migration Guides**

Best practices and recommendations for transitioning from other HPC frameworks to *HPX*.

- **HPX in Practice**

Examples of open-source libraries and applications using *HPX*, illustrating real-world usage patterns and ecosystem integration.

2.3 Examples

The following sections analyze some examples to help you get familiar with the *HPX* style of programming. We start off with simple examples that utilize basic *HPX* elements and then begin to expose the reader to the more complex and powerful *HPX* concepts. Section *Building tests and examples* shows how you can build the examples.

2.3.1 Asynchronous execution

The Fibonacci sequence is a sequence of numbers starting with 0 and 1 where every subsequent number is the sum of the previous two numbers. In this example, we will use *HPX* to calculate the value of the *n*-th element of the Fibonacci sequence. In order to compute this problem in parallel, we will use a facility known as a future.

As shown in the Fig. ?? below, a future encapsulates a delayed computation. It acts as a proxy for a result initially not known, most of the time because the computation of the result has not completed yet. The future synchronizes the access of this value by optionally suspending any *HPX*-threads requesting the result until the value is available. When a future is created, it spawns a new *HPX*-thread (either remotely with a *parcel* or locally by placing it into the thread

queue) which, when run, will execute the function associated with the future. The arguments of the function are bound when the future is created.




Fig. 2.1: Schematic of a future execution.

Once the function has finished executing, a write operation is performed on the future. The write operation marks the future as completed, and optionally stores data returned by the function. When the result of the delayed computation is needed, a read operation is performed on the future. If the future's function hasn't completed when a read operation is performed on it, the reader *HPX*-thread is suspended until the future is ready. The future facility allows *HPX* to schedule work early in a program so that when the function value is needed it will already be calculated and available. We use this property in our Fibonacci example below to enable its parallel execution.

Setup

The source code for this example can be found here: `fibonacci_local.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.fibonacci_local
```

To run the program type:

```
$ ./bin/fibonacci_local
```

This should print (time should be approximate):

```
fibonacci(10) == 55
elapsed time: 0.002430 [s]
```

This run used the default settings, which calculate the tenth element of the Fibonacci sequence. To declare which Fibonacci value you want to calculate, use the `--n-value` option. Additionally you can use the `--hpx:threads` option to declare how many OS-threads you wish to use when running the program. For instance, running:


```
$ ./bin/fibonacci --n-value 20 --hpx:threads 4
```

Will yield:

```
fibonacci(20) == 6765
elapsed time: 0.062854 [s]
```

Walkthrough

Now that you have compiled and run the code, let's look at how the code works. Since this code is written in C++, we will begin with the `main()` function. Here you can see that in *HPX*, `main()` is only used to initialize the runtime system. It is important to note that application-specific command line options are defined here. *HPX* uses [Boost.Program_options](https://www.boost.org/doc/html/program_options.html)¹² for command line processing. You can see that our programs `--n-value` option is set by calling the `add_options()` method on an instance of `hpx::program_options::options_description`. The default value of the variable is set to 10. This is why when we ran the program for the first time without using the `--n-value` option the program returned the 10th value of the Fibonacci sequence. The constructor argument of the description is the text that appears when a user uses the `--hpx:help` option to see what command line options are available. `HPX_APPLICATION_STRING` is a macro that expands to a string constant containing the name of the *HPX* application currently being compiled.

In *HPX* `main()` is used to initialize the runtime system and pass the command line arguments to the program. If you wish to add command line options to your program you would add them here using the instance of the Boost class `options_description`, and invoking the public member function `.add_options()` (see [Boost Documentation](https://www.boost.org/doc/)¹³ for more details). `hpx::init` calls `hpx_main()` after setting up *HPX*, which is where the logic of our program is encoded.

```
int main(int argc, char* argv[])
{
    // Configure application-specific options
    hpx::program_options::options_description desc_commandline(
        "Usage: " HPX_APPLICATION_STRING " [options]");

    // clang-format off
    desc_commandline.add_options()
        ("n-value",
         hpx::program_options::value<std::uint64_t>()->default_value(10),
         "n value for the Fibonacci function")
        ;
    // clang-format on

    // Initialize and run HPX
    hpx::local::init_params init_args;
    init_args.desc_cmdline = desc_commandline;

    return hpx::local::init(hpx_main, argc, argv, init_args);
}
```

The `hpx::init` function in `main()` starts the runtime system, and invokes `hpx_main()` as the first *HPX*-thread. Below we can see that the basic program is simple. The command line option `--n-value` is read in, a timer (`hpx::chrono::high_resolution_timer`) is set up to record the time it takes to do the computation, the `fibonacci` function is invoked synchronously, and the answer is printed out.

¹² https://www.boost.org/doc/html/program_options.html

¹³ <https://www.boost.org/doc/>

```
int hpx_main(hpx::program_options::variables_map& vm)
{
    hpx::threads::add_scheduler_mode(
        hpx::threads::policies::scheduler_mode::fast_idle_mode);

    // extract command line argument, i.e. fib(N)
    std::uint64_t n = vm["n-value"].as<std::uint64_t>();

    {
        // Keep track of the time required to execute.
        hpx::chrono::high_resolution_timer t;

        std::uint64_t r = fibonacci(n);

        char const* fmt = "fibonacci({1}) == {2}\\nelapsed time: {3} [s]\\n";
        hpx::util::format_to(std::cout, fmt, n, r, t.elapsed());
    }

    return hpx::local::finalize();    // Handles HPX shutdown
}
```

The `fibonacci` function itself is synchronous as the work done inside is asynchronous. To understand what is happening we have to look inside the `fibonacci` function:

```
std::uint64_t fibonacci(std::uint64_t n)
{
    if (n < 2)
        return n;

    hpx::future<std::uint64_t> n1 = hpx::async(fibonacci, n - 1);
    std::uint64_t n2 = fibonacci(n - 2);

    return n1.get() + n2;    // wait for the Future to return their values
}
```

This block of code looks similar to regular C++ code. First, if `(n < 2)`, meaning `n` is 0 or 1, then we return 0 or 1 (recall the first element of the Fibonacci sequence is 0 and the second is 1). If `n` is larger than 1 we spawn two new tasks whose results are contained in `n1` and `n2`. This is done using `hpx::async` which takes as arguments a function (function pointer, object or lambda) and the arguments to the function. Instead of returning a `std::uint64_t` like `fibonacci` does, `hpx::async` returns a future of a `std::uint64_t`, i.e. `hpx::future<std::uint64_t>`. Each of these futures represents an asynchronous, recursive call to `fibonacci`. After we've created the futures, we wait for both of them to finish computing, we add them together, and return that value as our result. We get the values from the futures using the `get` method. The recursive call tree will continue until `n` is equal to 0 or 1, at which point the value can be returned because it is implicitly known. When this termination condition is reached, the futures can then be added up, producing the `n`-th value of the Fibonacci sequence.

Note that calling `get` potentially blocks the calling `HPX`-thread, and lets other `HPX`-threads run in the meantime. There are, however, more efficient ways of doing this. `examples/quickstart/fibonacci_futures.cpp` contains many more variations of locally computing the Fibonacci numbers, where each method makes different tradeoffs in where asynchrony and parallelism is applied. To get started, however, the method above is sufficient and optimizations can be applied once you are more familiar with `HPX`. The example *Dataflow* presents dataflow, which is a way to more efficiently chain together multiple tasks.

2.3.2 Parallel algorithms

This program will perform a matrix multiplication in parallel. The output will look something like this:

```
Matrix A is :
4 9 6
1 9 8

Matrix B is :
4 9
6 1
9 8

Resultant Matrix is :
124 93
130 82
```

Setup

The source code for this example can be found here: `matrix_multiplication.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.matrix_multiplication
```

To run the program type:

```
$ ./bin/matrix_multiplication
```

or:

```
$ ./bin/matrix_multiplication --n 2 --m 3 --k 2 --s 100 --l 0 --u 10
```

where the first matrix is $n \times m$ and the second $m \times k$, s is the seed for creating the random values of the matrices and the range of these values is $[l, u]$

This should print:

```
Matrix A is :
4 9 6
1 9 8

Matrix B is :
4 9
6 1
9 8

Resultant Matrix is :
124 93
130 82
```

Notice that the numbers may be different because of the random initialization of the matrices.

Walkthrough

Now that you have compiled and run the code, let's look at how the code works.

First, `main()` is used to initialize the runtime system and pass the command line arguments to the program. `hpx::init` calls `hpx_main()` after setting up HPX, which is where our program is implemented.

```
int main(int argc, char* argv[])
{
    using namespace hpx::program_options;
    options_description cmdline("usage: " HPX_APPLICATION_STRING " [options]");
    // clang-format off
    cmdline.add_options()
        ("n",
         hpx::program_options::value<std::size_t>()->default_value(2),
         "Number of rows of first matrix")
        ("m",
         hpx::program_options::value<std::size_t>()->default_value(3),
         "Number of columns of first matrix (equal to the number of rows of "
         "second matrix)")
        ("k",
         hpx::program_options::value<std::size_t>()->default_value(2),
         "Number of columns of second matrix")
        ("seed,s",
         hpx::program_options::value<unsigned int>(),
         "The random number generator seed to use for this run")
        ("l",
         hpx::program_options::value<int>()->default_value(0),
         "Lower limit of range of values")
        ("u",
         hpx::program_options::value<int>()->default_value(10),
         "Upper limit of range of values");
    // clang-format on
    hpx::local::init_params init_args;
    init_args.desc_cmdline = cmdline;

    return hpx::local::init(hpx_main, argc, argv, init_args);
}
```

Proceeding to the `hpx_main()` function, we can see that matrix multiplication can be done very easily.

```
int hpx_main(hpx::program_options::variables_map& vm)
{
    using element_type = int;

    // Define matrix sizes
    std::size_t const rowsA = vm["n"].as<std::size_t>();
    std::size_t const colsA = vm["m"].as<std::size_t>();
    std::size_t const rowsB = colsA;
    std::size_t const colsB = vm["k"].as<std::size_t>();
    std::size_t const rowsR = rowsA;
    std::size_t const colsR = colsB;

    // Initialize matrices A and B
```

(continues on next page)

(continued from previous page)

```

std::vector<int> A(rowsA * colsA);
std::vector<int> B(rowsB * colsB);
std::vector<int> R(rowsR * colsR);

// Define seed
unsigned int seed = std::random_device{}();
if (vm.count("seed"))
    seed = vm["seed"].as<unsigned int>();

gen.seed(seed);
std::cout << "using seed: " << seed << std::endl;

// Define range of values
int const lower = vm["l"].as<int>();
int const upper = vm["u"].as<int>();

// Matrices have random values in the range [lower, upper]
std::uniform_int_distribution<element_type> dis(lower, upper);
auto generator = std::bind(dis, gen);
hpx::ranges::generate(A, generator);
hpx::ranges::generate(B, generator);

// Perform matrix multiplication
hpx::experimental::for_loop(hpx::execution::par, 0, rowsA, [&](auto i) {
    hpx::experimental::for_loop(0, colsB, [&](auto j) {
        R[i * colsR + j] = 0;
        hpx::experimental::for_loop(0, rowsB, [&](auto k) {
            R[i * colsR + j] += A[i * colsA + k] * B[k * colsB + j];
        });
    });
});

// Print all 3 matrices
print_matrix(A, rowsA, colsA, "A");
print_matrix(B, rowsB, colsB, "B");
print_matrix(R, rowsR, colsR, "R");

return hpx::local::finalize();
}

```

First, the dimensions of the matrices are defined. If they were not given as command-line arguments, their default values are 2 x 3 for the first matrix and 3 x 2 for the second. We use standard vectors to define the matrices to be multiplied as well as the resultant matrix.

To give some random initial values to our matrices, we use `std::uniform_int_distribution`¹⁴. Then, `std::bind()` is used along with `hpx::ranges::generate()` to yield two matrices A and B, which contain values in the range of [0, 10] or in the range defined by the user at the command-line arguments. The seed to generate the values can also be defined by the user.

The next step is to perform the matrix multiplication in parallel. This can be done by just using an `hpx::experimental::for_loop` combined with a parallel execution policy `hpx::execution::par` as the outer loop of the multiplication. Note that the execution of `hpx::experimental::for_loop` without specifying an execu-

¹⁴ https://en.cppreference.com/w/cpp/numeric/random/uniform_int_distribution

tion policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Finally, the matrices A, B that are multiplied as well as the resultant matrix R are printed using the following function.

```
void print_matrix(std::vector<int> const& M, std::size_t rows, std::size_t cols,
    char const* message)
{
    std::cout << "\nMatrix " << message << " is:" << std::endl;
    for (std::size_t i = 0; i < rows; i++)
    {
        for (std::size_t j = 0; j < cols; j++)
            std::cout << M[i * cols + j] << " ";
        std::cout << "\n";
    }
}
```

2.3.3 Asynchronous execution with actions

This example extends the *previous example* by introducing *actions*: functions that can be run remotely. In this example, however, we will still only run the action locally. The mechanism to execute *actions* stays the same: `hpx::async`. Later examples will demonstrate running actions on remote *localities* (e.g. *Remote execution with actions*).

Setup

The source code for this example can be found here: `fibonacci.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.fibonacci
```

To run the program type:

```
$ ./bin/fibonacci
```

This should print (time should be approximate):

```
fibonacci(10) == 55
elapsed time: 0.00186288 [s]
```

This run used the default settings, which calculate the tenth element of the Fibonacci sequence. To declare which Fibonacci value you want to calculate, use the `--n-value` option. Additionally you can use the `--hpx:threads` option to declare how many OS-threads you wish to use when running the program. For instance, running:

```
$ ./bin/fibonacci --n-value 20 --hpx:threads 4
```

Will yield:

```
fibonacci(20) == 6765
elapsed time: 0.233827 [s]
```

Walkthrough

The code needed to initialize the *HPX* runtime is the same as in the *previous example*:

```
int main(int argc, char* argv[])
{
    // Configure application-specific options
    hpx::program_options::options_description desc_commandline(
        "Usage: " HPX_APPLICATION_STRING " [options]");

    desc_commandline.add_options()("n-value",
        hpx::program_options::value<std::uint64_t>()->default_value(10),
        "n value for the Fibonacci function");

    // Initialize and run HPX
    hpx::init_params init_args;
    init_args.desc_cmdline = desc_commandline;

    return hpx::init(argc, argv, init_args);
}
```

The `hpx::init` function in `main()` starts the runtime system, and invokes `hpx_main()` as the first *HPX*-thread. The command line option `--n-value` is read in, a timer (`hpx::chrono::high_resolution_timer`) is set up to record the time it takes to do the computation, the *fibonacci action* is invoked synchronously, and the answer is printed out.

```
int hpx_main(hpx::program_options::variables_map& vm)
{
    // extract command line argument, i.e. fib(N)
    std::uint64_t n = vm["n-value"].as<std::uint64_t>();

    {
        // Keep track of the time required to execute.
        hpx::chrono::high_resolution_timer t;

        // Wait for fib() to return the value
        fibonacci_action fib;
        std::uint64_t r = fib(hpx::find_here(), n);

        char const* fmt = "fibonacci({1}) == {2}\\nelapsed time: {3} [s]\\n";
        hpx::util::format_to(std::cout, fmt, n, r, t.elapsed());
    }

    return hpx::finalize();    // Handles HPX shutdown
}
```

Upon a closer look we see that we've created a `std::uint64_t` to store the result of invoking our *fibonacci_action* `fib`. This *action* will launch synchronously (as the work done inside of the *action* will be asynchronous itself) and return the result of the Fibonacci sequence. But wait, what is an *action*? And what is this *fibonacci_action*? For starters, an *action* is a wrapper for a function. By wrapping functions, *HPX* can send packets of work to different processing units. These vehicles allow users to calculate work now, later, or on certain nodes. The first argument to our *action* is the location where the *action* should be run. In this case, we just want to run the *action* on the machine that we are currently on, so we use `hpx::find_here`. To further understand this we turn to the code to find where *fibonacci_action* was defined:

```
// forward declaration of the Fibonacci function
std::uint64_t fibonacci(std::uint64_t n);

// This is to generate the required boilerplate we need for the remote
// invocation to work.
HPX_PLAIN_ACTION(fibonacci, fibonacci_action)
```

A plain *action* is the most basic form of *action*. Plain *actions* wrap simple global functions which are not associated with any particular object (we will discuss other types of *actions* in *Components and actions*). In this block of code the function `fibonacci()` is declared. After the declaration, the function is wrapped in an *action* in the declaration `HPX_PLAIN_ACTION`. This function takes two arguments: the name of the function that is to be wrapped and the name of the *action* that you are creating.

This picture should now start making sense. The function `fibonacci()` is wrapped in an *action* `fibonacci_action`, which was run synchronously but created asynchronous work, then returns a `std::uint64_t` representing the result of the function `fibonacci()`. Now, let's look at the function `fibonacci()`:

```
std::uint64_t fibonacci(std::uint64_t n)
{
    if (n < 2)
        return n;

    // We restrict ourselves to execute the Fibonacci function locally.
    hpx::id_type const locality_id = hpx::find_here();

    // Invoking the Fibonacci algorithm twice is inefficient.
    // However, we intentionally demonstrate it this way to create some
    // heavy workload.

    fibonacci_action fib;
    hpx::future<std::uint64_t> n1 = hpx::async(fib, locality_id, n - 1);
    hpx::future<std::uint64_t> n2 = hpx::async(fib, locality_id, n - 2);

    return n1.get() +
        n2.get();    // wait for the Futures to return their values
}
```

This block of code is much more straightforward and should look familiar from the *previous example*. First, if `(n < 2)`, meaning `n` is 0 or 1, then we return 0 or 1 (recall the first element of the Fibonacci sequence is 0 and the second is 1). If `n` is larger than 1 we spawn two tasks using `hpx::async`. Each of these futures represents an asynchronous, recursive call to `fibonacci`. As previously we wait for both futures to finish computing, get the results, add them together, and return that value as our result. The recursive call tree will continue until `n` is equal to 0 or 1, at which point the value can be returned because it is implicitly known. When this termination condition is reached, the futures can then be added up, producing the `n`-th value of the Fibonacci sequence.

2.3.4 Remote execution with actions

This program will print out a hello world message on every OS-thread on every *locality*. The output will look something like this:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 1 on locality 1
hello world from OS-thread 0 on locality 0
hello world from OS-thread 0 on locality 1
```

Setup

The source code for this example can be found here: `hello_world_distributed.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.hello_world_distributed
```

To run the program type:

```
$ ./bin/hello_world_distributed
```

This should print:

```
hello world from OS-thread 0 on locality 0
```

To use more OS-threads use the command line option `--hpx:threads` and type the number of threads that you wish to use. For example, typing:

```
$ ./bin/hello_world_distributed --hpx:threads 2
```

will yield:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
```

Notice how the ordering of the two print statements will change with subsequent runs. To run this program on multiple localities please see the section *How to use HPX applications with PBS*.

Walkthrough

Now that you have compiled and run the code, let's look at how the code works, beginning with `main()`:

```
// Here is the main entry point. By using the include 'hpx/hpx_main.hpp' HPX
// will invoke the plain old C-main() as its first HPX thread.
int main()
{
    // Get a list of all available localities.
    std::vector<hpx::id_type> localities = hpx::find_all_localities();

    // Reserve storage space for futures, one for each locality.
    std::vector<hpx::future<void>> futures;
```

(continues on next page)

(continued from previous page)

```

futures.reserve(localities.size());

for (hpx::id_type const& node : localities)
{
    // Asynchronously start a new task. The task is encapsulated in a
    // future, which we can query to determine if the task has
    // completed.
    typedef hello_world_foreman_action action_type;
    futures.push_back(hpx::async<action_type>(node));
}

// The non-callback version of hpx::wait_all takes a single parameter,
// a vector of futures to wait on. hpx::wait_all only returns when
// all of the futures have finished.
hpx::wait_all(futures);
return 0;
}

```

In this excerpt of the code we again see the use of futures. This time the futures are stored in a vector so that they can easily be accessed. `hpx::wait_all` is a family of functions that wait on for an `std::vector<>` of futures to become ready. In this piece of code, we are using the synchronous version of `hpx::wait_all`, which takes one argument (the `std::vector<>` of futures to wait on). This function will not return until all the futures in the vector have been executed.

In *Asynchronous execution with actions* we used `hpx::find_here` to specify the target of our actions. Here, we instead use `hpx::find_all_localities`, which returns an `std::vector<>` containing the identifiers of all the machines in the system, including the one that we are on.

As in *Asynchronous execution with actions* our futures are set using `hpx::async<>`. The `hello_world_foreman_action` is declared here:

```

// Define the boilerplate code necessary for the function 'hello_world_foreman'
// to be invoked as an HPX action.
HPX_PLAIN_ACTION(hello_world_foreman, hello_world_foreman_action)

```

Another way of thinking about this wrapping technique is as follows: functions (the work to be done) are wrapped in actions, and actions can be executed locally or remotely (e.g. on another machine participating in the computation).

Now it is time to look at the `hello_world_foreman()` function which was wrapped in the action above:

```

void hello_world_foreman()
{
    // Get the number of worker OS-threads in use by this locality.
    std::size_t const os_threads = hpx::get_os_thread_count();

    // Populate a set with the OS-thread numbers of all OS-threads on this
    // locality. When the hello world message has been printed on a particular
    // OS-thread, we will remove it from the set.
    std::set<std::size_t> attendance;
    for (std::size_t os_thread = 0; os_thread < os_threads; ++os_thread)
        attendance.insert(os_thread);

    // As long as there are still elements in the set, we must keep scheduling
    // HPX-threads. Because HPX features work-stealing task schedulers, we have

```

(continues on next page)

(continued from previous page)

```

// no way of enforcing which worker OS-thread will actually execute
// each HPX-thread.
while (!attendance.empty())
{
    // Each iteration, we create a task for each element in the set of
    // OS-threads that have not said "Hello world". Each of these tasks
    // is encapsulated in a future.
    std::vector<hpx::future<std::size_t>> futures;
    futures.reserve(attendance.size());

    for (std::size_t worker : attendance)
    {
        // Asynchronously start a new task. The task is encapsulated in a
        // future that we can query to determine if the task has completed.
        //
        // We give the task a hint to run on a particular worker thread
        // (core) and suggest binding the scheduled thread to the given
        // core, but no guarantees are given by the scheduler that the task
        // will actually run on that worker thread. It will however try as
        // hard as possible to place the new task on the given worker
        // thread.
        hpx::execution::parallel_executor exec(
            hpx::threads::thread_priority::bound);

        hpx::threads::thread_schedule_hint hint(
            hpx::threads::thread_schedule_hint_mode::thread,
            static_cast<std::int16_t>(worker));

        // Annotate the created threads with the given thread name
        hpx::execution::experimental::annotating_executor annotating_exec(
            hpx::execution::experimental::with_hint(exec, hint),
            std::string("hello_world_worker#") + std::to_string(worker));

        futures.push_back(
            hpx::async(annotating_exec, hello_world_worker, worker));
    }

    // Wait for all of the futures to finish. The callback version of the
    // hpx::wait_each function takes two arguments: a vector of futures,
    // and a binary callback. The callback takes two arguments; the first
    // is the index of the future in the vector, and the second is the
    // return value of the future. hpx::wait_each doesn't return until
    // all the futures in the vector have returned.
    hpx::spinlock mtx;
    hpx::wait_each(hpx::unwrapping([&](std::size_t t) {
        if (std::size_t(-1) != t)
        {
            std::lock_guard<hpx::spinlock> lk(mtx);
            attendance.erase(t);
        }
    })),
    futures);

```

(continues on next page)

(continued from previous page)

```

    }
}

```

Now, before we discuss `hello_world_foreman()`, let's talk about the `hpx::wait_each` function. The version of `hpx::wait_each` invokes a callback function provided by the user, supplying the callback function with the result of the future.

In `hello_world_foreman()`, an `std::set<>` called `attendance` keeps track of which OS-threads have printed out the hello world message. When the OS-thread prints out the statement, the future is marked as ready, and `hpx::wait_each` in `hello_world_foreman()`. If it is not executing on the correct OS-thread, it returns a value of -1, which causes `hello_world_foreman()` to leave the OS-thread id in `attendance`.

```

std::size_t hello_world_worker(std::size_t desired)
{
    // Returns the OS-thread number of the worker that is running this
    // HPX-thread.
    std::size_t current = hpx::get_worker_thread_num();
    if (current == desired)
    {
        // The HPX-thread has been run on the desired OS-thread.
        char const* msg = "hello world from OS-thread {1} on locality {2}\n";

        hpx::util::format_to(hpx::cout, msg, desired, hpx::get_locality_id())
            << std::flush;

        return desired;
    }

    // This HPX-thread has been run by the wrong OS-thread, make the foreman
    // try again by rescheduling it.
    return std::size_t(-1);
}

```

Because *HPX* features work stealing task schedulers, there is no way to guarantee that an action will be scheduled on a particular OS-thread. This is why we must use a guess-and-check approach.

2.3.5 Components and actions

The accumulator examples demonstrate the use of components. Components are C++ classes that expose methods as a type of *HPX* action. These actions are called component actions. There are three examples: - accumulator - template accumulator - template function accumulator

Components are globally named, meaning that a component action can be called remotely (e.g., from another machine). There are two accumulator examples in *HPX*.

In the *Asynchronous execution with actions* and the *Remote execution with actions*, we introduced plain actions, which wrapped global functions. The target of a plain action is an identifier which refers to a particular machine involved in the computation. For plain actions, the target is the machine where the action will be executed.

Component actions, however, do not target machines. Instead, they target component instances. The instance may live on the machine that we've invoked the component action from, or it may live on another machine.

The components in these examples expose three different functions:

- `reset()` - Resets the accumulator value to 0.

- `add(arg)` - Adds `arg` to the accumulators value.
- `query()` - Queries the value of the accumulator.

These examples create an instance of the (template or template function) accumulator, and then allow the user to enter commands at a prompt, which subsequently invoke actions on the accumulator instance.

Accumulator

Setup

The source code for this example can be found here: `accumulator_client.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.accumulators.accumulator
```

To run the program type:

```
$ ./bin/accumulator_client
```

Once the program starts running, it will print the following prompt and then wait for input. An example session is given below:

```
commands: reset, add [amount], query, help, quit
> add 5
> add 10
> query
15
> add 2
> query
17
> reset
> add 1
> query
1
> quit
```

Walkthrough

Now, let's take a look at the source code of the accumulator example. This example consists of two parts: an *HPX* component library (a library that exposes an *HPX* component) and a client application which uses the library. This walkthrough will cover the *HPX* component library. The code for the client application can be found here: `accumulator_client.cpp`.

An *HPX* component is represented by two C++ classes:

- **A server class** - The implementation of the component's functionality.
- **A client class** - A high-level interface that acts as a proxy for an instance of the component.

Typically, these two classes both have the same name, but the server class usually lives in different sub-namespaces (server). For example, the full names of the two classes in accumulator are:

- `examples::server::accumulator` (server class)

- `examples::accumulator` (client class)

The server class

The following code is from `server/accumulator.hpp`¹⁵.

All *HPX* component server classes must inherit publicly from the *HPX* component base class: `hpx::components::component_base`

The accumulator component inherits from `hpx::components::locking_hook`. This allows the runtime system to ensure that all action invocations are serialized. That means that the system ensures that no two actions are invoked at the same time on a given component instance. This makes the component thread safe and no additional locking has to be implemented by the user. Moreover, an accumulator component is a component because it also inherits from `hpx::components::component_base` (the template argument passed to `locking_hook` is used as its base class). The following snippet shows the corresponding code:

```
class accumulator
: public hpx::components::locking_hook<
    hpx::components::component_base<accumulator>>
```

Our accumulator class will need a data member to store its value in, so let's declare a data member:

```
argument_type value_;
```

The constructor for this class simply initializes `value_` to 0:

```
accumulator()
: value_(0)
{
}
```

Next, let's look at the three methods of this component that we will be exposing as component actions:

Here are the action types. These types wrap the methods we're exposing. The wrapping technique is very similar to the one used in the *Asynchronous execution with actions* and the *Remote execution with actions*:

```
HPX_DEFINE_COMPONENT_ACTION(accumulator, reset)
HPX_DEFINE_COMPONENT_ACTION(accumulator, add)
HPX_DEFINE_COMPONENT_ACTION(accumulator, query)
```

The last piece of code in the server class header is the declaration of the action type registration code:

```
HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::reset_action, accumulator_reset_action)

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::add_action, accumulator_add_action)

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::query_action, accumulator_query_action)
```

Note: The code above must be placed in the global namespace.

¹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/server/accumulator.hpp>

The rest of the registration code is in `accumulator.cpp`¹⁶

```

////////////////////////////////////
// Add factory registration functionality.
HPX_REGISTER_COMPONENT_MODULE()

////////////////////////////////////
typedef hpx::components::component<examples::server::accumulator>
    accumulator_type;

HPX_REGISTER_COMPONENT(accumulator_type, accumulator)

////////////////////////////////////
// Serialization support for accumulator actions.
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::reset_action, accumulator_reset_action)
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::add_action, accumulator_add_action)
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::query_action, accumulator_query_action)

```

Note: The code above must be placed in the global namespace.

The client class

The following code is from `accumulator.hpp`¹⁷

The client class is the primary interface to a component instance. Client classes are used to create components:

```

// Create a component on this locality.
examples::accumulator c = hpx::new_<examples::accumulator>(hpx::find_here());

```

and to invoke component actions:

```
c.add(hpx::launch::apply, 4);
```

Clients, like servers, need to inherit from a base class, this time, `hpx::components::client_base`:

```

class accumulator
: public hpx::components::client_base<accumulator, server::accumulator>

```

For readability, we typedef the base class like so:

```

typedef hpx::components::client_base<accumulator, server::accumulator>
    base_type;

```

Here are examples of how to expose actions through a client class:

There are a few different ways of invoking actions:

¹⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/accumulator.cpp>

¹⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/accumulator.hpp>

- **Non-blocking:** For actions that don't have return types, or when we do not care about the result of an action, we can invoke the action using fire-and-forget semantics. This means that once we have asked *HPX* to compute the action, we forget about it completely and continue with our computation. We use `hpx::post` to invoke an action in a non-blocking fashion.

```
void reset(hpx::launch::apply_policy)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::reset_action action_type;
    hpx::post(action_type(), this->get_id());
}
```

- **Asynchronous:** Futures, as demonstrated in *Asynchronous execution*, *Asynchronous execution with actions*, and the *Remote execution with actions*, enable asynchronous action invocation. Here's an example from the accumulator client class:

```
hpx::future<argument_type> query(hpx::launch::async_policy)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::query_action action_type;
    return hpx::async(action_type(), this->get_id());
}
```

- **Synchronous:** To invoke an action in a fully synchronous manner, we can simply call `hpx::sync` which is semantically equivalent to `hpx::async().get()` (i.e., create a future and immediately wait on it to be ready). Here's an example from the accumulator client class:

```
void add(argument_type arg)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::add_action action_type;
    action_type()(this->get_id(), arg);
}
```

Note that `this->get_id()` references a data member of the `hpx::components::client_base` base class which identifies the server accumulator instance.

`hpx::id_type` is a type which represents a global identifier in *HPX*. This type specifies the target of an action. This is the type that is returned by `hpx::find_here` in which case it represents the *locality* the code is running on.

Template accumulator

Walkthrough

The server class

The following code is from `server/template_accumulator.hpp`¹⁸.

¹⁸ http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/server/template_accumulator.hpp

Similarly to the accumulator example, the component server class inherits publicly from `hpx::components::component_base` and from `hpx::components::locking_hook` ensuring thread-safe method invocations.

```
template <typename T>
class template_accumulator
: public hpx::components::locking_hook<
    hpx::components::component_base<template_accumulator<T>>>
```

The body of the template accumulator class remains mainly the same as the accumulator with the difference that it uses templates in the data types.

```
typedef T argument_type;

template_accumulator()
: value_(0)
{
}

////////////////////////////////////
// Exposed functionality of this component.

/// Reset the components value to 0.
void reset()
{
    // set value_ to 0.
    value_ = 0;
}

/// Add the given number to the accumulator.
void add(argument_type arg)
{
    // add value_ to arg, and store the result in value_.
    value_ += arg;
}

/// Return the current value to the caller.
argument_type query() const
{
    // Get the value of value_.
    return value_;
}

////////////////////////////////////
// Each of the exposed functions needs to be encapsulated into an
// action type, generating all required boilerplate code for threads,
// serialization, etc.
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, reset)
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, add)
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, query)
```

The last piece of code in the server class header is the declaration of the action type registration code. `REGISTER_TEMPLATE_ACCUMULATOR_DECLARATION(type)` declares actions for the specified type, while `REGISTER_TEMPLATE_ACCUMULATOR(type)` registers the actions and the component for the specified type, using macros

to handle boilerplate code.

```
#define REGISTER_TEMPLATE_ACCUMULATOR_DECLARATION(type)      \
    HPX_REGISTER_ACTION_DECLARATION(                          \
        examples::server::template_accumulator<type>::reset_action, \
        HPX_PP_CAT(__template_accumulator_reset_action_, type)) \
                                                                    \
    HPX_REGISTER_ACTION_DECLARATION(                          \
        examples::server::template_accumulator<type>::add_action, \
        HPX_PP_CAT(__template_accumulator_add_action_, type)) \
                                                                    \
    HPX_REGISTER_ACTION_DECLARATION(                          \
        examples::server::template_accumulator<type>::query_action, \
        HPX_PP_CAT(__template_accumulator_query_action_, type)) \
                                                                    \
    /**/

#define REGISTER_TEMPLATE_ACCUMULATOR(type)                  \
    HPX_REGISTER_ACTION(                                       \
        examples::server::template_accumulator<type>::reset_action, \
        HPX_PP_CAT(__template_accumulator_reset_action_, type)) \
                                                                    \
    HPX_REGISTER_ACTION(                                       \
        examples::server::template_accumulator<type>::add_action, \
        HPX_PP_CAT(__template_accumulator_add_action_, type)) \
                                                                    \
    HPX_REGISTER_ACTION(                                       \
        examples::server::template_accumulator<type>::query_action, \
        HPX_PP_CAT(__template_accumulator_query_action_, type)) \
                                                                    \
    typedef ::hpx::components::component<                    \
        examples::server::template_accumulator<type>>         \
        HPX_PP_CAT(__template_accumulator_, type);           \
    HPX_REGISTER_COMPONENT(HPX_PP_CAT(__template_accumulator_, type)) \
                                                                    \
    /**/
```

Note: The code above must be placed in the global namespace.

Finally, `HPX_REGISTER_COMPONENT_MODULE()` in file `server/template_accumulator.cpp`¹⁹ adds the factory registration functionality.

The client class

The client class of the template accumulator can be found in `template_accumulator.hpp`²⁰ and is very similar to the client class of the accumulator with the only difference that it uses templates and hence can work with different types.

¹⁹ http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/server/template_accumulator.cpp

²⁰ http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/template_accumulator.hpp

Template function accumulator

Walkthrough

The server class

The following code is from `server/template_function_accumulator.hpp`²¹.

The component server class inherits publicly from `hpx::components::component_base`.

```
class template_function_accumulator
: public hpx::components::component_base<template_function_accumulator>
```

`typedef hpx::spinlock mutex_type` defines a `mutex_type` as `hpx::spinlock` for thread safety, while the code that follows exposes the functionality of this component.

```
////////////////////////////////////
// Exposed functionality of this component.

/// Reset the value to 0.
void reset()
{
    // Atomically set value_ to 0.
    std::lock_guard<mutex_type> l(mtx_);
    value_ = 0;
}

/// Add the given number to the accumulator.
template <typename T>
void add(T arg)
{
    // Atomically add value_ to arg, and store the result in value_.
    std::lock_guard<mutex_type> l(mtx_);
    value_ += static_cast<double>(arg);
}

/// Return the current value to the caller.
double query() const
{
    // Get the value of value_.
    std::lock_guard<mutex_type> l(mtx_);
    return value_;
}
```

- `reset()`: Resets the accumulator value to 0 in a thread-safe manner using `std::lock_guard`.
- `add()`: Adds a value to the accumulator, allowing any type `T` that can be cast to double.
- `query()`: Returns the current value of the accumulator in a thread-safe manner.

To define the actions for `reset()` and `query()` we can use the macro `HPX_DEFINE_COMPONENT_ACTION`. However, actions with template arguments require special type definitions. Therefore, we use `make_action()` to define `add()`.

²¹ http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/server/template_function_accumulator.hpp

```
////////////////////////////////////  
// Each of the exposed functions needs to be encapsulated into an  
// action type, generating all required boilerplate code for threads,  
// serialization, etc.  
  
HPX_DEFINE_COMPONENT_ACTION(template_function_accumulator, reset)  
HPX_DEFINE_COMPONENT_ACTION(template_function_accumulator, query)  
  
// Actions with template arguments (see add<>() above) require special  
// type definitions. The simplest way to define such an action type is  
// by deriving from the HPX facility make_action.  
template <typename T>  
struct add_action  
    : hpx::actions::make_action<void (template_function_accumulator::*)(  
        T),  
        &template_function_accumulator::template add<T>,  
        add_action<T>::type  
    {  
};
```

The last piece of code in the server class header is the action registration:

```
HPX_REGISTER_ACTION_DECLARATION(  
    examples::server::template_function_accumulator::reset_action,  
    managed_accumulator_reset_action)  
  
HPX_REGISTER_ACTION_DECLARATION(  
    examples::server::template_function_accumulator::query_action,  
    managed_accumulator_query_action)
```

Note: The code above must be placed in the global namespace.

The rest of the registration code is in `accumulator.cpp`²²

```
////////////////////////////////////  
// Add factory registration functionality.  
HPX_REGISTER_COMPONENT_MODULE()  
  
////////////////////////////////////  
typedef hpx::components::component<  
    examples::server::template_function_accumulator>  
    accumulator_type;  
  
HPX_REGISTER_COMPONENT(accumulator_type, template_function_accumulator)  
  
////////////////////////////////////  
// Serialization support for managed_accumulator actions.  
HPX_REGISTER_ACTION(accumulator_type::wrapped_type::reset_action,  
    managed_accumulator_reset_action)  
HPX_REGISTER_ACTION(accumulator_type::wrapped_type::query_action,
```

(continues on next page)

²² <http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/accumulator.cpp>

(continued from previous page)

```
managed_accumulator_query_action)
```

Note: The code above must be placed in the global namespace.

The client class

The client class of the template accumulator can be found in `template_function_accumulator.hpp`²³ and is very similar to the client class of the accumulator with the only difference that it uses templates and hence can work with different types.

2.3.6 Dataflow

HPX provides its users with several different tools to simply express parallel concepts. One of these tools is a *local control object (LCO)* called dataflow. An *LCO* is a type of component that can spawn a new thread when triggered. They are also distinguished from other components by a standard interface that allow users to understand and use them easily. A Dataflow, being an *LCO*, is triggered when the values it depends on become available. For instance, if you have a calculation X that depends on the results of three other calculations, you could set up a dataflow that would begin the calculation X as soon as the other three calculations have returned their values. Dataflows are set up to depend on other dataflows. It is this property that makes dataflow a powerful parallelization tool. If you understand the dependencies of your calculation, you can devise a simple algorithm that sets up a dependency tree to be executed. In this example, we calculate compound interest. To calculate compound interest, one must calculate the interest made in each compound period, and then add that interest back to the principal before calculating the interest made in the next period. A practical person would, of course, use the formula for compound interest:

$$F = P(1 + i)^n$$

where F is the future value, P is the principal value, i is the interest rate, and n is the number of compound periods.

However, for the sake of this example, we have chosen to manually calculate the future value by iterating:

$$I = Pi$$

and

$$P = P + I$$

Setup

The source code for this example can be found here: `interest_calculator.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.interest_calculator
```

To run the program type:

²³ http://github.com/TheHPXProject/hpx/blob/unknown/examples/accumulators/template_function_accumulator.hpp

```
$ ./bin/interest_calculator --principal 100 --rate 5 --cp 6 --time 36
Final amount: 134.01
Amount made: 34.0096
```

Walkthrough

Let us begin with `main`. Here we can see that we again are using `Boost.Program_options` to set our command line variables (see *Asynchronous execution with actions* for more details). These options set the principal, rate, compound period, and time. It is important to note that the units of time for `cp` and `time` must be the same.

```
int main(int argc, char** argv)
{
    options_description cmdline("Usage: " HPX_APPLICATION_STRING " [options]");

    cmdline.add_options()("principal", value<double>()->default_value(1000),
        "The principal [$]")("rate", value<double>()->default_value(7),
        "The interest rate [%]")("cp", value<int>()->default_value(12),
        "The compound period [months]")("time",
        value<int>()->default_value(12 * 30),
        "The time money is invested [months]");

    hpx::init_params init_args;
    init_args.desc_cmdline = cmdline;

    return hpx::init(argc, argv, init_args);
}
```

Next we look at `hpx_main`.

```
int hpx_main(variables_map& vm)
{
    {
        using hpx::dataflow;
        using hpx::make_ready_future;
        using hpx::shared_future;
        using hpx::unwrapping;
        hpx::id_type here = hpx::find_here();

        double init_principal =
            vm["principal"].as<double>();           //Initial principal
        double init_rate = vm["rate"].as<double>(); //Interest rate
        int cp = vm["cp"].as<int>();                //Length of a compound period
        int t = vm["time"].as<int>();               //Length of time money is invested

        init_rate /= 100;    //Rate is a % and must be converted
        t /= cp;             //Determine how many times to iterate interest calculation:
        //How many full compound periods can fit in the time invested

        // In non-dataflow terms the implemented algorithm would look like:
        //
        // int t = 5;         // number of time periods to use
        // double principal = init_principal;
```

(continues on next page)

(continued from previous page)

```

// double rate = init_rate;
//
// for (int i = 0; i < t; ++i)
// {
//     double interest = calc(principal, rate);
//     principal = add(principal, interest);
// }
//
// Please note the similarity with the code below!

shared_future<double> principal = make_ready_future(init_principal);
shared_future<double> rate = make_ready_future(init_rate);

for (int i = 0; i < t; ++i)
{
    shared_future<double> interest =
        dataflow(unwrapping(calc), principal, rate);
    principal = dataflow(unwrapping(add), principal, interest);
}

// wait for the dataflow execution graph to be finished calculating our
// overall interest
double result = principal.get();

std::cout << "Final amount: " << result << std::endl;
std::cout << "Amount made: " << result - init_principal << std::endl;
}

return hpx::finalize();
}

```

Here we find our command line variables read in, the rate is converted from a percent to a decimal, the number of calculation iterations is determined, and then our shared_futures are set up. Notice that we first place our principal and rate into shares futures by passing the variables `init_principal` and `init_rate` using `hpx::make_ready_future`.

In this way `hpx::shared_future<double> principal` and `rate` will be initialized to `init_principal` and `init_rate` when `hpx::make_ready_future<double>` returns a future containing those initial values. These shared futures then enter the for loop and are passed to `interest`. Next `principal` and `interest` are passed to the reassignment of `principal` using a `hpx::dataflow`. A dataflow will first wait for its arguments to be ready before launching any callbacks, so `add` in this case will not begin until both `principal` and `interest` are ready. This loop continues for each compound period that must be calculated. To see how `interest` and `principal` are calculated in the loop, let us look at `calc_action` and `add_action`:

```

// Calculate interest for one period
double calc(double principal, double rate)
{
    return principal * rate;
}

////////////////////////////////////
// Add the amount made to the principal
double add(double principal, double interest)
{

```

(continues on next page)

(continued from previous page)

```

    return principal + interest;
}

```

After the shared future dependencies have been defined in `hpx_main`, we see the following statement:

```
double result = principal.get();
```

This statement calls `hpx::future::get` on the shared future `principal` which had its value calculated by our for loop. The program will wait here until the entire dataflow tree has been calculated and the value assigned to `result`. The program then prints out the final value of the investment and the amount of interest made by subtracting the final value of the investment from the initial value of the investment.

2.3.7 Local to remote

When developers write code they typically begin with a simple serial code and build upon it until all of the required functionality is present. The following set of examples were developed to demonstrate this iterative process of evolving a simple serial program to an efficient, fully-distributed *HPX* application. For this demonstration, we implemented a 1D heat distribution problem. This calculation simulates the diffusion of heat across a ring from an initialized state to some user-defined point in the future. It does this by breaking each portion of the ring into discrete segments and using the current segment's temperature and the temperature of the surrounding segments to calculate the temperature of the current segment in the next timestep as shown by Fig. ?? below.




Fig. 2.2: Heat diffusion example program flow.

We parallelize this code over the following eight examples:

- Example 1
- Example 2
- Example 3
- Example 4
- Example 5
- Example 6
- Example 7
- Example 8

The first example is straight serial code. In this code we instantiate a vector `U` that contains two vectors of doubles as seen in the structure `stepper`.


```

struct stepper
{
    // Our partition type
    typedef double partition;

    // Our data for one time step
    typedef std::vector<partition> space;

    // Our operator
    static double heat(double left, double middle, double right)
    {
        return middle + (k * dt / (dx * dx)) * (left - 2 * middle + right);
    }

    // do all the work on 'nx' data points for 'nt' time steps
    space do_work(std::size_t nx, std::size_t nt)
    {
        // U[t][i] is the state of position i at time t.
        std::vector<space> U(2);
        for (space& s : U)
            s.resize(nx);

        // Initial conditions: f(0, i) = i
        for (std::size_t i = 0; i != nx; ++i)
            U[0][i] = double(i);

        // Actual time step loop
        for (std::size_t t = 0; t != nt; ++t)
        {
            space const& current = U[t % 2];
            space& next = U[(t + 1) % 2];

            next[0] = heat(current[nx - 1], current[0], current[1]);

            for (std::size_t i = 1; i != nx - 1; ++i)
                next[i] = heat(current[i - 1], current[i], current[i + 1]);

            next[nx - 1] = heat(current[nx - 2], current[nx - 1], current[0]);
        }

        // Return the solution at time-step 'nt'.
        return U[nt % 2];
    }
};

```

Each element in the vector of doubles represents a single grid point. To calculate the change in heat distribution, the temperature of each grid point, along with its neighbors, is passed to the function `heat`. In order to improve readability, references named `current` and `next` are created which, depending on the time step, point to the first and second vector of doubles. The first vector of doubles is initialized with a simple heat ramp. After calling the heat function with the data in the `current` vector, the results are placed into the `next` vector.

In example 2 we employ a technique called futurization. Futurization is a method by which we can easily transform a code that is serially executed into a code that creates asynchronous threads. In the simplest case this involves replacing a variable with a future to a variable, a function with a future to a function, and adding a `.get()` at the point where a

value is actually needed. The code below shows how this technique was applied to the struct `stepper`.

```
struct stepper
{
    // Our partition type
    typedef hpx::shared_future<double> partition;

    // Our data for one time step
    typedef std::vector<partition> space;

    // Our operator
    static double heat(double left, double middle, double right)
    {
        return middle + (k * dt / (dx * dx)) * (left - 2 * middle + right);
    }

    // do all the work on 'nx' data points for 'nt' time steps
    hpx::future<space> do_work(std::size_t nx, std::size_t nt)
    {
        using hpx::dataflow;
        using hpx::unwrapping;

        // U[t][i] is the state of position i at time t.
        std::vector<space> U(2);
        for (space& s : U)
            s.resize(nx);

        // Initial conditions: f(0, i) = i
        for (std::size_t i = 0; i != nx; ++i)
            U[0][i] = hpx::make_ready_future(double(i));

        auto Op = unwrapping(&stepper::heat);

        // Actual time step loop
        for (std::size_t t = 0; t != nt; ++t)
        {
            space const& current = U[t % 2];
            space& next = U[(t + 1) % 2];

            // WHEN U[t][i-1], U[t][i], and U[t][i+1] have been computed, THEN we
            // can compute U[t+1][i]
            for (std::size_t i = 0; i != nx; ++i)
            {
                next[i] =
                    dataflow(hpx::launch::async, Op, current[idx(i, -1, nx)],
                        current[i], current[idx(i, +1, nx)]);
            }
        }

        // Now the asynchronous computation is running; the above for-loop does not
        // wait on anything. There is no implicit waiting at the end of each timestep;
        // the computation of each U[t][i] will begin as soon as its dependencies
        // are ready and hardware is available.
    }
};
```

(continues on next page)

(continued from previous page)

```

    // Return the solution at time-step 'nt'.
    return hpx::when_all(U[nt % 2]);
}
};

```

In example 2, we redefine our partition type as a `shared_future` and, in `main`, create the object `result`, which is a future to a vector of partitions. We use `result` to represent the last vector in a string of vectors created for each timestep. In order to move to the next timestep, the values of a partition and its neighbors must be passed to `heat` once the futures that contain them are ready. In *HPX*, we have an LCO (Local Control Object) named `Dataflow` that assists the programmer in expressing this dependency. `Dataflow` allows us to pass the results of a set of futures to a specified function when the futures are ready. `Dataflow` takes three types of arguments, one which instructs the dataflow on how to perform the function call (`async` or `sync`), the function to call (in this case `Op`), and futures to the arguments that will be passed to the function. When called, `dataflow` immediately returns a future to the result of the specified function. This allows users to string dataflows together and construct an execution tree.

After the values of the futures in `dataflow` are ready, the values must be pulled out of the future container to be passed to the function `heat`. In order to do this, we use the *HPX* facility `unwrapping`, which underneath calls `.get()` on each of the futures so that the function `heat` will be passed doubles and not futures to doubles.

By setting up the algorithm this way, the program will be able to execute as quickly as the dependencies of each future are met. Unfortunately, this example runs terribly slow. This increase in execution time is caused by the overheads needed to create a future for each data point. Because the work done within each call to `heat` is very small, the overhead of creating and scheduling each of the three futures is greater than that of the actual useful work! In order to amortize the overheads of our synchronization techniques, we need to be able to control the amount of work that will be done with each future. We call this amount of work per overhead grain size.

In example 3, we return to our serial code to figure out how to control the grain size of our program. The strategy that we employ is to create “partitions” of data points. The user can define how many partitions are created and how many data points are contained in each partition. This is accomplished by creating the `struct partition`, which contains a member object `data_`, a vector of doubles that holds the data points assigned to a particular instance of `partition`.

In example 4, we take advantage of the partition setup by redefining `space` to be a vector of `shared_futures` with each future representing a partition. In this manner, each future represents several data points. Because the user can define how many data points are in each partition, and, therefore, how many data points are represented by one future, a user can control the grainsize of the simulation. The rest of the code is then futurized in the same manner as example 2. It should be noted how strikingly similar example 4 is to example 2.

Example 4 finally shows good results. This code scales equivalently to the OpenMP version. While these results are promising, there are more opportunities to improve the application’s scalability. Currently, this code only runs on one *locality*, but to get the full benefit of *HPX*, we need to be able to distribute the work to other machines in a cluster. We begin to add this functionality in example 5.

In order to run on a distributed system, a large amount of boilerplate code must be added. Fortunately, *HPX* provides us with the concept of a *component*, which saves us from having to write quite as much code. A component is an object that can be remotely accessed using its global address. Components are made of two parts: a server and a client class. While the client class is not required, abstracting the server behind a client allows us to ensure type safety instead of having to pass around pointers to global objects. Example 5 renames example 4’s `struct partition` to `partition_data` and adds serialization support. Next, we add the server side representation of the data in the structure `partition_server`. `Partition_server` inherits from `hpx::components::component_base`, which contains a server-side component boilerplate. The boilerplate code allows a component’s public members to be accessible anywhere on the machine via its Global Identifier (GID). To encapsulate the component, we create a client side helper class. This object allows us to create new instances of our component and access its members without having to know its GID. In addition, we are using the client class to assist us with managing our asynchrony. For example, our client class `partition`’s member function `get_data()` returns a future to `partition_data get_data()`. This struct inherits its boilerplate code from `hpx::components::client_base`.

In the structure `stepper`, we have also had to make some changes to accommodate a distributed environment. In order to get the data from a particular neighboring partition, which could be remote, we must retrieve the data from all of the neighboring partitions. These retrievals are asynchronous and the function `heat_part_data`, which, amongst other things, calls `heat`, should not be called unless the data from the neighboring partitions have arrived. Therefore, it should come as no surprise that we synchronize this operation with another instance of `dataflow` (found in `heat_part`). This `dataflow` receives futures to the data in the current and surrounding partitions by calling `get_data()` on each respective partition. When these futures are ready, `dataflow` passes them to the `unwrapping` function, which extracts the `shared_array` of doubles and passes them to the `lambda`. The `lambda` calls `heat_part_data` on the `locality`, which the middle partition is on.

Although this example could run distributed, it only runs on one `locality`, as it always uses `hpx::find_here()` as the target for the functions to run on.

In example 6, we begin to distribute the partition data on different nodes. This is accomplished in `stepper::do_work()` by passing the GID of the `locality` where we wish to create the partition to the partition constructor.

```
for (std::size_t i = 0; i != np; ++i)
    U[0][i] = partition(localities[locidx(i, np, nl)], nx, double(i));
```

We distribute the partitions evenly based on the number of localities used, which is described in the function `locidx`. Because some of the data needed to update the partition in `heat_part` could now be on a new `locality`, we must devise a way of moving data to the `locality` of the middle partition. We accomplished this by adding a switch in the function `get_data()` that returns the end element of the buffer `data_` if it is from the left partition or the first element of the buffer if the data is from the right partition. In this way only the necessary elements, not the whole buffer, are exchanged between nodes. The reader should be reminded that this exchange of end elements occurs in the function `get_data()` and, therefore, is executed asynchronously.

Now that we have the code running in distributed, it is time to make some optimizations. The function `heat_part` spends most of its time on two tasks: retrieving remote data and working on the data in the middle partition. Because we know that the data for the middle partition is local, we can overlap the work on the middle partition with that of the possibly remote call of `get_data()`. This algorithmic change, which was implemented in example 7, can be seen below:

```
// The partitioned operator, it invokes the heat operator above on all elements
// of a partition.
static partition heat_part(
    partition const& left, partition const& middle, partition const& right)
{
    using hpx::dataflow;
    using hpx::unwrapping;

    hpx::shared_future<partition_data> middle_data =
        middle.get_data(partition_server::middle_partition);

    hpx::future<partition_data> next_middle = middle_data.then(
        unwrapping([middle](partition_data const& m) -> partition_data {
            HPX_UNUSED(middle);

            // All local operations are performed once the middle data of
            // the previous time step becomes available.
            std::size_t size = m.size();
            partition_data next(size);
            for (std::size_t i = 1; i != size - 1; ++i)
                next[i] = heat(m[i - 1], m[i], m[i + 1]);
```

(continues on next page)

(continued from previous page)

```

        return next;
    }));

    return dataflow(hpx::launch::async,
        unwrapping([left, middle, right](partition_data next,
            partition_data const& l, partition_data const& m,
            partition_data const& r) -> partition {
                HPX_UNUSED(left);
                HPX_UNUSED(right);

                // Calculate the missing boundary elements once the
                // corresponding data has become available.
                std::size_t size = m.size();
                next[0] = heat(l[size - 1], m[0], m[1]);
                next[size - 1] = heat(m[size - 2], m[size - 1], r[0]);

                // The new partition_data will be allocated on the same locality
                // as 'middle'.
                return partition(middle.get_id(), std::move(next));
            }),
        std::move(next_middle),
        left.get_data(partition_server::left_partition), middle_data,
        right.get_data(partition_server::right_partition));
}

```

Example 8 completes the futurization process and utilizes the full potential of *HPX* by distributing the program flow to multiple localities, usually defined as nodes in a cluster. It accomplishes this task by running an instance of *HPX* main on each *locality*. In order to coordinate the execution of the program, the `struct stepper` is wrapped into a component. In this way, each *locality* contains an instance of `stepper` that executes its own instance of the function `do_work()`. This scheme does create an interesting synchronization problem that must be solved. When the program flow was being coordinated on the head node, the GID of each component was known. However, when we distribute the program flow, each partition has no notion of the GID of its neighbor if the next partition is on another *locality*. In order to make the GIDs of neighboring partitions visible to each other, we created two buffers to store the GIDs of the remote neighboring partitions on the left and right respectively. These buffers are filled by sending the GID of newly created edge partitions to the right and left buffers of the neighboring localities.

In order to finish the simulation, the solution vectors named `result` are then gathered together on *locality* 0 and added into a vector of spaces `overall_result` using the *HPX* functions `gather_id` and `gather_here`.

Example 8 completes this example series, which takes the serial code of example 1 and incrementally morphs it into a fully distributed parallel code. This evolution was guided by the simple principles of futurization, the knowledge of grainsize, and utilization of components. Applying these techniques easily facilitates the scalable parallelization of most applications.

2.3.8 Serializing user-defined types

In order to facilitate the sending and receiving of complex datatypes HPX provides a serialization abstraction.

Just like boost, hpx allows users to serialize user-defined types by either providing the serializer as a member function or defining the serialization as a free function.

Unlike Boost HPX doesn't acknowledge second unsigned int parameter, it is solely there to preserve API compatibility with Boost Serialization

This tutorial was heavily inspired by [Boost's serialization concepts](#)²⁴.

Setup

The source code for this example can be found here: `custom_serialization.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.custom_serialization
```

To run the program type:

```
$ ./bin/custom_serialization
```

This should print:

```
Rectangle(Point(x=0,y=0),Point(x=0,y=5))  
gravity.g = 9.81%
```

Serialization Requirements

In order to serialize objects in HPX, at least one of the following criteria must be met:

In the case of default constructible objects:

- The object is an empty type.
- Has a serialization function as shown in this tutorial.
- All members are accessible publicly and they can be used in structured binding contexts.

Otherwise:

- They need to have special serialization support.

²⁴ https://www.boost.org/doc/libs/1_79_0/libs/serialization/doc/serialization.html

Member function serialization

```

struct point_member_serialization
{
    int x{0};
    int y{0};

    // Required when defining the serialization function as private
    // In this case it isn't
    // Provides serialization access to HPX
    friend class hpx::serialization::access;

    // Second argument exists solely for compatibility with boost serialize
    // it is NOT processed by HPX in any way.
    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & x & y;
        // clang-format on
    }
};

// Allow bitwise serialization
HPX_IS_BITWISE_SERIALIZABLE(point_member_serialization)

```

Notice that `point_member_serialization` is defined as bitwise serializable (see *Bitwise serialization for bitwise copyable data* for more details). HPX is also able to recursively serialize composite classes and structs given that its members are serializable.

```

struct rectangle_member_serialization
{
    point_member_serialization top_left;
    point_member_serialization lower_right;

    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & top_left & lower_right;
        // clang-format on
    }
};

```

Free function serialization

In order to decouple your models from HPX, HPX also allows for the definition of free function serializers.

```
struct rectangle_free
{
    point_member_serialization top_left;
    point_member_serialization lower_right;
};

template <typename Archive>
void serialize(Archive& ar, rectangle_free& pt, unsigned int const)
{
    // clang-format off
    ar & pt.lower_right & pt.top_left;
    // clang-format on
}
```

Even if you can't modify a class to befriend it, you can still be able to serialize your class provided that your class is default constructable and you are able to reconstruct it yourself.

```
class point_class
{
public:
    point_class(int x, int y)
        : x(x)
        , y(y)
    {
    }

    point_class() = default;

    [[nodiscard]] int get_x() const noexcept
    {
        return x;
    }

    [[nodiscard]] int get_y() const noexcept
    {
        return y;
    }

private:
    int x;
    int y;
};

template <typename Archive>
void load(Archive& ar, point_class& pt, unsigned int const)
{
    int x, y;
    ar >> x >> y;
    pt = point_class(x, y);
}
```

(continues on next page)

(continued from previous page)

```

}

template <typename Archive>
void save(Archive& ar, point_class const& pt, unsigned int const)
{
    ar << pt.get_x() << pt.get_y();
}

// This tells HPX that you have spilt your serialize function into
// load and save
HPX_SERIALIZATION_SPLIT_FREE(point_class)

```

Serializing non default constructable classes

Some classes don't provide any default constructor.

```

class planet_weight_calculator
{
public:
    explicit planet_weight_calculator(double g)
        : g(g)
    {
    }

    template <class Archive>
    friend void save_construct_data(
        Archive&, planet_weight_calculator const*, unsigned int);

    [[nodiscard]] double get_g() const
    {
        return g;
    }

private:
    // Provides serialization access to HPX
    friend class hpx::serialization::access;
    template <class Archive>
    void serialize(Archive&, unsigned int const)
    {
        // Serialization will be done in the save_construct_data
        // Still needs to be defined
    }

    double g;
};

```

In this case you have to define a `save_construct_data` and `load_construct_data` in which you do the serialization yourself.

```

template <class Archive>
inline void save_construct_data(Archive& ar,

```

(continues on next page)

(continued from previous page)

```

    planet_weight_calculator const* weight_calc, unsigned int const)
{
    ar << weight_calc->g;    // Do all of your serialization here
}

template <class Archive>
inline void load_construct_data(
    Archive& ar, planet_weight_calculator* weight_calc, unsigned int const)
{
    double g;
    ar >> g;

    // ::new(ptr) construct new object at given address
    hpx::construct_at(weight_calc, g);
}

```

Bitwise serialization for bitwise copyable data

When sending non arithmetic types not defined by `std::is_arithmetic`²⁵, HPX has to (de)serialize each object separately. However, if the class you are trying to send consists only of bitwise copyable datatypes, you may mark your class as such. Then HPX will serialize your object bitwise instead of element wise. This has enormous benefits, especially when sending a vector/array of your class. To define your class as such you need to call `HPX_IS_BITWISE_SERIALIZABLE(T)` with your desired custom class.

```

struct point_member_serialization
{
    int x{0};
    int y{0};

    // Required when defining the serialization function as private
    // In this case it isn't
    // Provides serialization access to HPX
    friend class hpx::serialization::access;

    // Second argument exists solely for compatibility with boost serialize
    // it is NOT processed by HPX in any way.
    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & x & y;
        // clang-format on
    }
};

// Allow bitwise serialization
HPX_IS_BITWISE_SERIALIZABLE(point_member_serialization)

```

²⁵ https://en.cppreference.com/w/cpp/types/is_arithmetic

2.3.9 Termination detection

This example demonstrates how to use *HPX*'s termination detection API to ensure all asynchronous work has completed before shutting down the runtime. This is particularly useful when you need to guarantee that all posted tasks have finished execution before the application exits.

Overview

The termination detection API provides a way to wait for all local *HPX*-threads to complete their work. This is essential in scenarios where you spawn asynchronous tasks using *hpx::post* or *hpx::async* and need to ensure they all finish before the runtime shuts down.

The API supports several use cases:

- **Basic usage:** Wait indefinitely for all tasks to complete
- **Timeout:** Wait for a specified duration
- **Deadline:** Wait until a specific time point
- **Cancellation:** Support for cancellation tokens to interrupt the wait

Setup

The source code for this example can be found here: `termination_detection.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.termination_detection
```

To run the program type:

```
$ ./bin/termination_detection
```

This will execute all four examples demonstrating different usage patterns of the termination detection API.

Walkthrough

The example demonstrates four different usage patterns of the termination detection API. Let's examine each one:

Basic usage

The simplest form waits indefinitely for all local threads to complete:

This is useful when you want to ensure all work is done before shutting down, and you don't have time constraints.

Timeout usage

You can specify a maximum duration to wait:

The function returns `true` if all threads completed within the timeout, or `false` if the timeout elapsed. This is useful when you want to give tasks a reasonable amount of time to complete but don't want to wait indefinitely.

Deadline usage

Similar to timeout, but you specify an absolute time point:

This is useful when you have a specific deadline by which all work must be completed.

Cancellation support

The most flexible form supports cancellation tokens:

This allows external control over the wait operation. You can request cancellation from another thread, which is useful in scenarios like graceful shutdown with user interruption support.

API Reference

The termination detection API is available in the `hpx::local` namespace:

`void hpx::local::termination_detection()`

Wait indefinitely for all local *HPX*-threads to complete.

`bool hpx::local::termination_detection(hpx::chrono::steady_duration const &timeout)`

Wait for all local *HPX*-threads to complete, with a timeout.

Parameters

timeout – Maximum duration to wait

Returns

`true` if all threads completed, `false` if timeout elapsed

`bool hpx::local::termination_detection(hpx::chrono::steady_time_point const &deadline)`

Wait for all local *HPX*-threads to complete, until a deadline.

Parameters

deadline – Absolute time point to wait until

Returns

`true` if all threads completed, `false` if deadline passed

`bool hpx::local::termination_detection(hpx::stop_token stop_token, hpx::chrono::steady_duration const &timeout)`

Wait for all local *HPX*-threads to complete, with cancellation support.

Parameters

- **stop_token** – Token that can be used to request cancellation
- **timeout** – Maximum duration to wait (defaults to maximum duration)

Returns

`true` if all threads completed, `false` if timeout elapsed or stop was requested

Use cases

The termination detection API is particularly useful in the following scenarios:

- **Graceful shutdown:** Ensure all background tasks complete before exiting
- **Testing:** Verify that all spawned tasks have finished in unit tests
- **Batch processing:** Wait for all work items in a batch to complete
- **Resource cleanup:** Ensure all tasks using shared resources have finished before cleanup

See also

- `hpx::post` - Fire-and-forget asynchronous execution
- `hpx::async` - Asynchronous execution with a future
- `hpx::finalize` - Shut down the *HPX* runtime

2.4 Manual

The manual is your comprehensive guide to *HPX*. It contains detailed information on how to build and use *HPX* in different scenarios.

2.4.1 Prerequisites

Supported platforms

At this time, *HPX* supports the following platforms. Other platforms may work, but we do not test *HPX* with other platforms, so please be warned.

Table 2.1: Supported Platforms for *HPX*

Name	Minimum Version	Architectures
Linux	2.6	x86-32, x86-64, k1om
BlueGeneQ	V1R2M0	PowerPC A2
Windows	Any Windows system	x86-32, x86-64
Mac OSX	Any OSX system	x86-64
ARM	Any ARM system	Any architecture
RISC-V	Any RISC-V system	Any architecture

Supported compilers

The table below shows the supported compilers for *HPX*.

Table 2.2: Supported Compilers for *HPX*

Name	Minimum Version	Latest tested
GNU Compiler Collection (g++) ²⁶	12.0	15.0
clang: a C language family frontend for LLVM ²⁷	16.0	20.0
Visual C++ ²⁸ (x64)	2022	2022

Software and libraries

The table below presents all the necessary prerequisites for building *HPX*.

Table 2.3: Software prerequisites for *HPX*

	Name	Minimum Version	Latest tested
Build System	CMake ²⁹	3.20	4.1
Required Libraries	Boost ³⁰	1.71.0	1.88.0
	Portable Hardware Locality (HWLOC) ³¹	1.5	2.4

The most important dependencies are [Boost](#)³² and [Portable Hardware Locality \(HWLOC\)](#)³³. The installation of Boost is described in detail in Boost's [Getting Started](#)³⁴ document. A recent version of hwloc is required in order to support thread pinning and NUMA awareness and can be found in [Hwloc Downloads](#)³⁵.

HPX is written in 99.99% Standard C++ (the remaining 0.01% is platform specific assembly code). As such, *HPX* is compilable with almost any standards compliant C++ compiler. The code base takes advantage of C++ language and standard library features when available.

Note: When building Boost using gcc, please note that it is required to specify a `cxxflags=-std=c++20` command line argument to b2 (bjam).

Note: In most configurations, *HPX* depends only on header-only Boost. Boost.Filesystem is required if the standard library does not support filesystem. The following are not needed by default, but are required in certain configurations: Boost.Chrono, Boost.DateTime, Boost.Log, Boost.LogSetup, Boost.Regex, and Boost.Thread.

Depending on the options you chose while building and installing *HPX*, you will find that *HPX* may depend on several other libraries such as those listed below.

Note: In order to use a high speed parcellport, we currently recommend configuring *HPX* to use MPI so that MPI can be used for communication between different localities. Please set the CMake variable `MPI_CXX_COMPILER` to your MPI C++ compiler wrapper if not detected automatically.

Table 2.4: Optional software prerequisites for *HPX*

Name	Minimum version
google-perftools ³⁶	1.7.1
jemalloc ³⁷	2.1.0
mi-malloc ³⁸	1.0.0
Performance Application Programming Interface (PAPI)	

²⁶ <https://gcc.gnu.org>

²⁷ <https://clang.llvm.org/>

²⁸ <https://msdn.microsoft.com/en-us/visualc/default.aspx>

²⁹ <https://www.cmake.org>

³⁰ <https://www.boost.org/>

³¹ <https://www.open-mpi.org/projects/hwloc/>

³² <https://www.boost.org/>

³³ <https://www.open-mpi.org/projects/hwloc/>

³⁴ https://www.boost.org/more/getting_started/index.html

³⁵ <https://www.open-mpi.org/software/hwloc/v1.11>

2.4.2 Getting HPX

Download a tarball of the latest release from [HPX Downloads](#)³⁹ and unpack it or clone the repository directly using git:

```
$ git clone https://github.com/TheHPXProject/hpx.git
```

It is also recommended that you check out the latest stable tag:

```
$ cd hpx
```

```
$ git checkout v2.0.0
```

2.4.3 Building HPX

Basic information

The build system for HPX is based on CMake⁴⁰, a cross-platform build-generator tool which is not responsible for building the project but rather generates the files needed by your build tool (GNU make, Visual Studio, etc.) for building HPX. If CMake is not already installed in your system, you can download it and install it here: [CMake Downloads](#)⁴¹.

Once CMake⁴² has been run, the build process can be started. The build process consists of the following parts:

- The HPX core libraries (target `core`): This forms the basic set of HPX libraries.
- HPX Examples (target `examples`): This target is enabled by default and builds all HPX examples (disable by setting `HPX_WITH_EXAMPLES:BOOL=Off`). HPX examples are part of the `all` target and are included in the installation if enabled.
- HPX Tests (target `tests`): This target builds the HPX test suite and is enabled by default (disable by setting `HPX_WITH_TESTS:BOOL=Off`). They are not built by the `all` target and have to be built separately.
- HPX Documentation (target `docs`): This target builds the documentation, and is not enabled by default (enable by setting `HPX_WITH_DOCUMENTATION:BOOL=On`. For more information see *Documentation*.

The HPX build process is highly configurable through CMake⁴³, and various CMake⁴⁴ variables influence the build process. A list with the most important CMake⁴⁵ variables can be found in the section that follows, while the complete list of available CMake⁴⁶ variables is in *CMake options*. These variables can be used to refine the recipes that can be found at *Platform specific build recipes*, a section that shows some basic steps on how to build HPX for a specific platform.

In order to use HPX, only the core libraries are required. In order to use the optional libraries, you need to specify them as link dependencies in your build (See *Creating HPX projects*).

³⁶ <https://code.google.com/p/gperftools>

³⁷ <http://jemalloc.net>

³⁸ <http://microsoft.github.io/mimalloc/>

³⁹ <https://hpx.stellar-group.org/downloads/>

⁴⁰ <https://www.cmake.org>

⁴¹ <https://www.cmake.org/cmake/resources/software.html>

⁴² <https://www.cmake.org>

⁴³ <https://www.cmake.org>

⁴⁴ <https://www.cmake.org>

⁴⁵ <https://www.cmake.org>

⁴⁶ <https://www.cmake.org>

Most important CMake options

While building *HPX*, you are provided with multiple CMake options which correspond to different configurations. Below, there is a set of the most important and frequently used CMake options.

HPX_WITH_MALLOC

Use a custom allocator. Using a custom allocator tuned for multithreaded applications is very important for the performance of *HPX* applications. When debugging applications, it's useful to set this to `system`, as custom allocators can hide some memory-related bugs. Note that setting this to something other than `system` requires an external dependency.

HPX_WITH_CUDA

Enable support for CUDA. Use `CMAKE_CUDA_COMPILER` to set the CUDA compiler. This is a standard CMake⁴⁷ variable, like `CMAKE_CXX_COMPILER`.

HPX_WITH_PARCELPORTR_MPI

Enable the MPI parcellport. This enables the use of MPI for the networking operations in the *HPX* runtime. The default value is `OFF` because it's not available on all systems and/or requires another dependency. However, it is the recommended parcellport.

HPX_WITH_PARCELPORTR_TCP

Enable the TCP parcellport. Enables the use of TCP for networking in the runtime. The default value is `ON`. However, it's only recommended for debugging purposes, as it is slower than the MPI parcellport.

HPX_WITH_PARCELPORTR_LCI

Enable the LCI parcellport. This enables the use of LCI for the networking operations in the *HPX* runtime. The default value is `OFF` because it's not available on all systems and/or requires another dependency. However, this experimental parcellport may provide better performance than the MPI parcellport. Please refer to *Using the LCI parcellport* for more information about the LCI parcellport.

HPX_WITH_APEX

Enable APEX integration. [APEX](https://uo-oaciss.github.io/apex/quickstarthpx/)⁴⁸ can be used to profile *HPX* applications. In particular, it provides information about individual tasks in the *HPX* runtime.

HPX_WITH_GENERIC_CONTEXT_COROUTINES

Enable Boost. Context for task context switching. It must be enabled for non-x86 architectures such as ARM and Power.

HPX_WITH_MAX_CPU_COUNT

Set the maximum CPU count supported by *HPX*. The default value is 64, and should be set to a number at least as high as the number of cores on a system including virtual cores such as hyperthreads.

HPX_WITH_CXX_STANDARD

Set a specific C++ standard version e.g. `HPX_WITH_CXX_STANDARD=23`. The default and minimum value is 20. Possible values are 20, 23, or 26.

HPX_WITH_EXAMPLES

Build examples.

HPX_WITH_TESTS

Build tests.

⁴⁷ <https://www.cmake.org>

⁴⁸ <https://uo-oaciss.github.io/apex/quickstarthpx/>

HPX_WITH_DEBUG_POSTFIX

Set the postfix for debug libraries. The default is `d`. This variable is used to set `CMAKE_DEBUG_POSTFIX` and is only relevant for Debug builds or multi-configuration generators. The default rarely needs to be changed. It ensures that generated debug binaries have a different name than release binaries, which is important to avoid ABI problems when both debug and release binaries are installed on the same system.

For a complete list of available [CMake](#)⁴⁹ variables that influence the build of *HPX*, see *CMake options*.

Build types

[CMake](#)⁵⁰ can be configured to generate project files suitable for builds that have enabled debugging support or for an optimized build (without debugging support). The [CMake](#)⁵¹ variable used to set the build type is `CMAKE_BUILD_TYPE` (for more information see the [CMake Documentation](#)⁵²). Available build types are:

- **Debug:** Full debug symbols are available as well as additional assertions to help debugging. To enable the debug build type for the *HPX* API, the C++ Macro `HPX_DEBUG` is defined.
- **RelWithDebInfo:** Release build with debugging symbols. This is most useful for profiling applications
- **Release:** Release build. This disables assertions and enables default compiler optimizations.
- **RelMinSize:** Release build with optimizations for small binary sizes.

Important: We currently don't guarantee ABI compatibility between Debug and Release builds. Please make sure that applications built against *HPX* use the same build type as you used to build *HPX*. For CMake builds, this means that the `CMAKE_BUILD_TYPE` variables have to match and for projects not using [CMake](#)⁵³, the `HPX_DEBUG` macro has to be set in debug mode.

Using CMake Presets

HPX provides a `CMakePresets.json` file which includes a variety of pre-defined build configurations. These presets allow you to easily configure the build for common scenarios without needing to manually specify multiple CMake variables.

To use a preset, you can use the `--preset` option with CMake:

```
$ cmake --preset <preset-name>
$ cmake --build --preset <preset-name>
```

Some of the available presets include:

- **default:** Standard release build with tests and examples enabled.
- **minimal:** Minimal build with only core features (no tests, examples, or tools).
- **full:** Full build with all standard features enabled.
- **debug:** Debug build with symbols and debug-optimized settings.
- **performance:** Build optimized for performance analysis with APEX profiling.
- **cuda:** Build with CUDA support (requires CUDA toolkit).

⁴⁹ <https://www.cmake.org>

⁵⁰ <https://www.cmake.org>

⁵¹ <https://www.cmake.org>

⁵² https://cmake.org/cmake/help/latest/variable/CMAKE_BUILD_TYPE.html

⁵³ <https://www.cmake.org>

- `sycl`: Build with SYCL support (requires compatible compiler).
- `sanitizer-address`: Build with AddressSanitizer enabled.

For a full list of available presets, you can run:

```
$ cmake --list-presets
```

Platform specific build recipes

Unix variants

Once you have the source code and the dependencies and assuming all your dependencies are in paths known to `CMake`⁵⁴, the following gets you started:

1. First, set up a separate build directory to configure the project:

```
$ mkdir build && cd build
```

2. To configure the project you have the following options:

- To build the core *HPX* libraries and examples, and install them to your chosen location (recommended):

```
$ cmake -DCMAKE_INSTALL_PREFIX=/install/path ..
```

Tip: If you want to change `CMake`⁵⁵ variables for your build, it is usually a good idea to start with a clean build directory to avoid configuration problems. It is especially important that you use a clean build directory when changing between Release and Debug modes.

- To install *HPX* to the default system folders, simply leave out the `CMAKE_INSTALL_PREFIX` option:

```
$ cmake ..
```

- If your dependencies are in custom locations, you may need to tell `CMake`⁵⁶ where to find them by passing one or more options to `CMake`⁵⁷ as shown below:

```
$ cmake -DBoost_ROOT=/path/to/boost
      -DHWloc_ROOT=/path/to/hwloc
      -DTcmalloc_ROOT=/path/to/tcmalloc
      -DJemalloc_ROOT=/path/to/jemalloc
      [other CMake variable definitions]
      /path/to/source/tree
```

For instance:

```
$ cmake -DBoost_ROOT=/packages/boost -DHWloc_ROOT=/packages/hwloc -DCMAKE_
INSTALL_PREFIX=/packages/hpx ~/downloads/hpx_1.5.1
```

- If you want to try *HPX* without using a custom allocator pass `-DHPX_WITH_MALLOC=system` to `CMake`⁵⁸:

⁵⁴ <https://www.cmake.org>

⁵⁵ <https://www.cmake.org>

⁵⁶ <https://www.cmake.org>

⁵⁷ <https://www.cmake.org>

⁵⁸ <https://www.cmake.org>

```
$ cmake -DCMAKE_INSTALL_PREFIX=/install/path -DHPX_WITH_MALLOC=system ..
```

Note: Please pay special attention to the section about *HPX_WITH_MALLOC:STRING* as this is crucial for getting decent performance.

Important: If you are building *HPX* for a system with more than 64 processing units, you must change the *CMake*⁵⁹ variable *HPX_WITH_MAX_CPU_COUNT* (to a value at least as big as the number of (virtual) cores on your system). Note that the default value is 64.

Caution: Compiling and linking *HPX* needs a considerable amount of memory. It is advisable that at least 2 GB of memory per parallel process is available.

3. Once the configuration is complete, to build the project you run:

```
$ cmake --build . --target install
```

Windows

Note: The following build recipes are mostly user-contributed and may be outdated. We always welcome updated and new build recipes.

To build *HPX* under Windows 10 x64 with Visual Studio 2015:

- Download the CMake V3.19 installer (or latest version) from [here](#)⁶⁰
- Download the hwloc V1.11.0 (or the latest version) from [here](#)⁶¹ and unpack it.
- Download the latest Boost libraries from [here](#)⁶² and unpack them.
- Build the Boost DLLs and LIBs by using these commands from Command Line (or PowerShell). Open CMD/PowerShell inside the Boost dir and type in:

```
.\bootstrap.bat
```

This batch file will set up everything needed to create a successful build. Now execute:

```
.\b2.exe link=shared variant=release,debug architecture=x86 address-model=64  
↪threading=multi --build-type=complete install
```

This command will start a (very long) build of all available Boost libraries. Please, be patient.

- Open CMake-GUI.exe and set up your source directory (input field 'Where is the source code') to the *base directory* of the source code you downloaded from *HPX*'s GitHub pages. Here's an example of CMake path settings, which point to the Documents/GitHub/hpx folder:

⁵⁹ <https://www.cmake.org>

⁶⁰ <https://blog.kitware.com/cmake-3-19-0-available-for-download/>

⁶¹ <https://www.open-mpi.org/software/hwloc/v2.11/>

⁶² <https://www.boost.org/users/download/>




Fig. 2.3: Example CMake path settings.

Inside ‘Where is the source-code’ enter the base directory of your *HPX* source directory (do not enter the “src” sub-directory!). Inside ‘Where to build the binaries’ you should put in the path where all the building processes will happen. This is important because the building machinery will do an “out-of-tree” build. CMake will not touch or change the original source files in any way. Instead, it will generate Visual Studio Solution Files, which will build *HPX* packages out of the *HPX* source tree.

- Set new configuration variables (in CMake, not in Windows environment): `Boost_ROOT`, `Hwloc_ROOT`, `Asio_ROOT`, `CMAKE_INSTALL_PREFIX`. The meaning of these variables is as follows:
 - `Boost_ROOT` the *HPX* root directory of the unpacked Boost headers/cpp files.
 - `Hwloc_ROOT` the *HPX* root directory of the unpacked Portable Hardware Locality files.
 - `Asio_ROOT` the *HPX* root directory of the unpacked ASIO files. Alternatively use `HPX_WITH_FETCH_ASIO` with value `True`.
 - `CMAKE_INSTALL_PREFIX` the *HPX* root directory where the future builds of *HPX* should be installed.

Note: *HPX* is a very large software collection, so it is not recommended to use the default `C:\Program Files\hpx`. Many users may prefer to use simpler paths *without* whitespace, like `C:\bin\hpx` or `D:\bin\hpx` etc.

To insert new env-vars click on “Add Entry” and then insert the name inside “Name”, select `PATH` as Type and put the path-name in the “Path” text field. Repeat this for the first three variables.

This is how variable insertion will look:




Fig. 2.4: Example CMake adding entry.

Alternatively, users could provide `Boost_LIBRARYDIR` instead of `Boost_ROOT`; the difference is that `Boost_LIBRARYDIR` should point to the subdirectory inside Boost root where all the compiled DLLs/LIBs are. For example, `Boost_LIBRARYDIR` may point to the `bin.v2` subdirectory under the Boost rootdir. It is important to keep the meanings of these two variables separated from each other: `Boost_DIR` points to the ROOT folder of the Boost library. `Boost_LIBRARYDIR` points to the subdir inside the Boost root folder where the compiled binaries are.

- Click the ‘Configure’ button of CMake-GUI. You will be immediately presented with a small window where you can select the C++ compiler to be used within Visual Studio. This has been tested using the latest v14 (a.k.a C++ 2015) but older versions should be sufficient too. Make sure to select the 64Bit compiler.
- After the generate process has finished successfully, click the ‘Generate’ button. Now, CMake will put new VS Solution files into the BUILD folder you selected at the beginning.
- Open Visual Studio and load the `HPX.sln` from your build folder.
- Go to `CMakePredefinedTargets` and build the `INSTALL` project:





Fig. 2.5: Visual Studio `INSTALL` target.

It will take some time to compile everything, and in the end you should see an output similar to this one:

2.4.4 CMake options

In order to configure *HPX*, you can set a variety of options to allow CMake to generate your specific makefiles/project files. A list of the most important CMake options can be found in *Most important CMake options*, while this section includes the comprehensive list.



```
Output
Show output from: Build
116> -- Installing: C:/bin/HPX/bin/1d_stencil_2.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_3.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_4.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_4_parallel.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_5.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_6.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_7.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_8.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_1_omp.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_3_omp.exe
116> -- Installing: C:/bin/HPX/bin/simple_central_tuplespace_client.exe
116> -- Installing: C:/bin/HPX/lib/hpx_simple_central_tuplespaced.lib
116> -- Installing: C:/bin/HPX/lib/hpx_simple_central_tuplespaced.dll
116> -- Installing: C:/bin/HPX/bin/transpose_serial.exe
116> -- Installing: C:/bin/HPX/bin/transpose_serial_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_smp.exe
116> -- Installing: C:/bin/HPX/bin/transpose_smp_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_serial_vector.exe
116> -- Installing: C:/bin/HPX/bin/hpx_runtime.exe
===== Build: 116 succeeded, 0 failed, 0 up-to-date, 0 skipped =====
```

Fig. 2.6: Visual Studio build output.

Variables that influence how *HPX* is built

The options are split into these categories:

- *Generic options*
- *Build Targets options*
- *Thread Manager options*
- *AGAS options*
- *Parcelport options*
- *Profiling options*
- *Debugging options*
- *Modules options*

Generic options

- `HPX_WITH_AUTOMATIC_SERIALIZATION_REGISTRATION:BOOL`
- `HPX_WITH_BUILD_BINARY_PACKAGE:BOOL`
- `HPX_WITH_CHECK_MODULE_DEPENDENCIES:BOOL`
- `HPX_WITH_COMPILER_WARNINGS:BOOL`
- `HPX_WITH_COMPILER_WARNINGS_AS_ERRORS:BOOL`
- `HPX_WITH_COMPRESSION_BZIP2:BOOL`
- `HPX_WITH_COMPRESSION_SNAPPY:BOOL`
- `HPX_WITH_COMPRESSION_ZLIB:BOOL`
- `HPX_WITH_CONTRACTS_MODE:STRING`
- `HPX_WITH_CUDA:BOOL`
- `HPX_WITH_CXX20_STD_EXECUTION_POLICES:INTERNAL`
- `HPX_WITH_CXX_MODULES:BOOL`
- `HPX_WITH_CXX_STANDARD:STRING`
- `HPX_WITH_DATAPAR_BACKEND:STRING`
- `HPX_WITH_DEPRECATION_WARNINGS:BOOL`
- `HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL`
- `HPX_WITH_DYNAMIC_HPX_MAIN:BOOL`
- `HPX_WITH_FAULT_TOLERANCE:BOOL`
- `HPX_WITH_FULL_RPATH:BOOL`
- `HPX_WITH_GCC_VERSION_CHECK:BOOL`
- `HPX_WITH_GENERIC_CONTEXT_COROUTINES:BOOL`
- `HPX_WITH_HIDDEN_VISIBILITY:BOOL`
- `HPX_WITH_HIP:BOOL`
- `HPX_WITH_HIPSYCL:BOOL`
- `HPX_WITH_IGNORE_COMPILER_COMPATIBILITY:BOOL`
- `HPX_WITH_LOGGING:BOOL`
- `HPX_WITH_MALLOC:STRING`
- `HPX_WITH_MODULES_AS_STATIC_LIBRARIES:BOOL`
- `HPX_WITH_MODULE_COMPATIBILITY_HEADERS:BOOL`
- `HPX_WITH_NICE_THREADLEVEL:BOOL`
- `HPX_WITH_PARCEL_COALESCING:BOOL`
- `HPX_WITH_PKGCONFIG:BOOL`
- `HPX_WITH_PRECOMPILED_HEADERS:BOOL`
- `HPX_WITH_PSEUDO_DEPENDENCIES:BOOL`
- `HPX_WITH_RUN_MAIN_EVERYWHERE:BOOL`

- *HPX_WITH_STACKOVERFLOW_DETECTION:BOOL*
- *HPX_WITH_STATIC_LINKING:BOOL*
- *HPX_WITH_SUPPORT_NO_UNIQUE_ADDRESS_ATTRIBUTE:BOOL*
- *HPX_WITH_SYCL:BOOL*
- *HPX_WITH_SYCL_FLAGS:STRING*
- *HPX_WITH_UNITY_BUILD:BOOL*
- *HPX_WITH_VIM_YCM:BOOL*
- *HPX_WITH_ZERO_COPY_SERIALIZATION_THRESHOLD:STRING*

HPX_WITH_AUTOMATIC_SERIALIZATION_REGISTRATION:BOOL

Use automatic serialization registration for actions and functions. This affects compatibility between HPX applications compiled with different compilers (default ON)

HPX_WITH_BUILD_BINARY_PACKAGE:BOOL

Build HPX on the build infrastructure on any LINUX distribution (default: OFF).

HPX_WITH_CHECK_MODULE_DEPENDENCIES:BOOL

Verify that no modules are cross-referenced from a different module category (default: OFF)

HPX_WITH_COMPILER_WARNINGS:BOOL

Enable compiler warnings (default: ON)

HPX_WITH_COMPILER_WARNINGS_AS_ERRORS:BOOL

Turn compiler warnings into errors (default: OFF)

HPX_WITH_COMPRESSION_BZIP2:BOOL

Enable bzip2 compression for parcel data (default: OFF).

HPX_WITH_COMPRESSION_SNAPPY:BOOL

Enable snappy compression for parcel data (default: OFF).

HPX_WITH_COMPRESSION_ZLIB:BOOL

Enable zlib compression for parcel data (default: OFF).

HPX_WITH_CONTRACTS_MODE:STRING

Contract evaluation mode for pre-C++26 compilers, options are: ENFORCE, QUICK_ENFORCE, OBSERVE, IGNORE

HPX_WITH_CUDA:BOOL

Enable support for CUDA (default: OFF)

HPX_WITH_CXX20_STD_EXECUTION_POLICES:INTERNAL**HPX_WITH_CXX_MODULES:BOOL**

Enable exposing C++20 modules (default: OFF).

HPX_WITH_CXX_STANDARD:STRING

Set the C++ standard to use when compiling HPX itself. (default: 20)

HPX_WITH_DATAPAR_BACKEND:STRING

Define which vectorization library should be used. Options are: VC, EVE, STD_EXPERIMENTAL_SIMD, SVE, EMULATE, NONE

HPX_WITH_DEPRECATED_WARNINGS:BOOL

Enable warnings for deprecated facilities (default: ON).

HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL

Disables the mechanism that produces debug output for caught signals and unhandled exceptions (default: OFF)

HPX_WITH_DYNAMIC_HPX_MAIN:BOOL

Enable dynamic overload of system main() (Linux and Apple only, default: ON)

HPX_WITH_FAULT_TOLERANCE:BOOL

Build HPX to tolerate failures of nodes, i.e. ignore errors in active communication channels (default: OFF)

HPX_WITH_FULL_RPATH:BOOL

Build and link HPX libraries and executables with full RPATHs (default: ON)

HPX_WITH_GCC_VERSION_CHECK:BOOL

Don't ignore version reported by gcc (default: ON)

HPX_WITH_GENERIC_CONTEXT_COROUTINES:BOOL

Use Boost.Context as the underlying coroutines context switch implementation.

HPX_WITH_HIDDEN_VISIBILITY:BOOL

Use -fvisibility=hidden for builds on platforms which support it (default OFF)

HPX_WITH_HIP:BOOL

Enable compilation with HIPCC (default: OFF)

HPX_WITH_HIPSYCL:BOOL

Use hipsycl cmake integration (default: OFF)

HPX_WITH_IGNORE_COMPILER_COMPATIBILITY:BOOL

Ignore compiler incompatibility in dependent projects (default: ON).

HPX_WITH_LOGGING:BOOL

Build HPX with logging enabled (default: ON).

HPX_WITH_MALLOC:STRING

Define which allocator should be linked in. Options are: system, tcmalloc, jemalloc, mimalloc, tbbmalloc, and custom (default is: tcmalloc)

HPX_WITH_MODULES_AS_STATIC_LIBRARIES:BOOL

Compile HPX modules as STATIC (whole-archive) libraries instead of OBJECT libraries (Default: ON)

HPX_WITH_MODULE_COMPATIBILITY_HEADERS:BOOL

Generate backwards-compatibility headers for HPX Modules (default: OFF)

HPX_WITH_NICE_THREADLEVEL:BOOL

Set HPX worker threads to have high NICE level (may impact performance) (default: OFF)

HPX_WITH_PARCEL_COALESCING:BOOL

Enable the parcel coalescing plugin (default: ON).

HPX_WITH_PKGCONFIG:BOOL

Enable generation of pkgconfig files (default: ON on Linux without CUDA/HIP, otherwise OFF)

HPX_WITH_PRECOMPILED_HEADERS:BOOL

Enable precompiled headers for certain build targets (experimental) (default OFF)

HPX_WITH_PSEUDO_DEPENDENCIES:BOOL

Turn compiler warnings into errors (default: ON)

HPX_WITH_RUN_MAIN_EVERYWHERE:BOOL

Run `hpx_main` by default on all localities (default: OFF, deprecated, will be removed).

HPX_WITH_STACKOVERFLOW_DETECTION:BOOL

Enable stackoverflow detection for HPX threads/coroutines (default: OFF, debug: ON).

HPX_WITH_STATIC_LINKING:BOOL

Compile HPX statically linked libraries (Default: OFF)

HPX_WITH_SUPPORT_NO_UNIQUE_ADDRESS_ATTRIBUTE:BOOL

Enable the use of the `[[no_unique_address]]` attribute (default: ON)

HPX_WITH_SYCL:BOOL

Enable support for Sycl (default: OFF)

HPX_WITH_SYCL_FLAGS:STRING

Sycl compile flags for selecting specific targets (default: empty)

HPX_WITH_UNITY_BUILD:BOOL

Enable unity build for certain build targets (default OFF)

HPX_WITH_VIM_YCM:BOOL

Generate HPX completion file for VIM YouCompleteMe plugin

HPX_WITH_ZERO_COPY_SERIALIZATION_THRESHOLD:STRING

The threshold in bytes to when perform zero copy optimizations (default: 8192)

Build Targets options

- *HPX_WITH_ASIO_TAG:STRING*
- *HPX_WITH_COMPILE_ONLY_TESTS:BOOL*
- *HPX_WITH_DISTRIBUTED_RUNTIME:BOOL*
- *HPX_WITH_DOCUMENTATION:BOOL*
- *HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS:STRING*
- *HPX_WITH_EXAMPLES:BOOL*
- *HPX_WITH_EXAMPLES_HDF5:BOOL*
- *HPX_WITH_EXAMPLES_OPENMP:BOOL*
- *HPX_WITH_EXAMPLES_QT4:BOOL*
- *HPX_WITH_EXAMPLES_QTHREADS:BOOL*
- *HPX_WITH_EXAMPLES_TBB:BOOL*
- *HPX_WITH_EXECUTABLE_PREFIX:STRING*
- *HPX_WITH_FAIL_COMPILE_TESTS:BOOL*
- *HPX_WITH_FETCH_APEX:BOOL*
- *HPX_WITH_FETCH_ASIO:BOOL*
- *HPX_WITH_FETCH_BOOST:BOOL*

- *HPX_WITH_FETCH_GASNET:BOOL*
- *HPX_WITH_FETCH_HWLOC:BOOL*
- *HPX_WITH_FETCH_LCI:BOOL*
- *HPX_WITH_FETCH_LCW:BOOL*
- *HPX_WITH_IO_COUNTERS:BOOL*
- *HPX_WITH_LCI_BOOTSTRAP_MPI:BOOL*
- *HPX_WITH_LCI_TAG:STRING*
- *HPX_WITH_LCW_TAG:STRING*
- *HPX_WITH_NANOBENCH:BOOL*
- *HPX_WITH_PARALLEL_LINK_JOBS:STRING*
- *HPX_WITH_TESTS:BOOL*
- *HPX_WITH_TESTS_BENCHMARKS:BOOL*
- *HPX_WITH_TESTS_EXAMPLES:BOOL*
- *HPX_WITH_TESTS_EXTERNAL_BUILD:BOOL*
- *HPX_WITH_TESTS_HEADERS:BOOL*
- *HPX_WITH_TESTS_REGRESSIONS:BOOL*
- *HPX_WITH_TESTS_UNIT:BOOL*
- *HPX_WITH_THRUST:BOOL*
- *HPX_WITH_TOOLS:BOOL*

HPX_WITH_ASIO_TAG:STRING

Asio repository tag or branch

HPX_WITH_COMPILE_ONLY_TESTS:BOOL

Create build system support for compile time only HPX tests (default ON)

HPX_WITH_DISTRIBUTED_RUNTIME:BOOL

Enable the distributed runtime (default: ON). Turning off the distributed runtime completely disallows the creation and use of components and actions. Turning this option off is experimental!

HPX_WITH_DOCUMENTATION:BOOL

Build the HPX documentation (default OFF).

HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS:STRING

List of documentation output formats to generate. Valid options are html;singlehtml;latexpdf;man. Multiple values can be separated with semicolons. (default html).

HPX_WITH_EXAMPLES:BOOL

Build the HPX examples (default ON)

HPX_WITH_EXAMPLES_HDF5:BOOL

Enable examples requiring HDF5 support (default: OFF).

HPX_WITH_EXAMPLES_OPENMP:BOOL

Enable examples requiring OpenMP support (default: OFF).

HPX_WITH_EXAMPLES_QT4:BOOL

Enable examples requiring Qt4 support (default: OFF).

HPX_WITH_EXAMPLES_QTHREADS:BOOL

Enable examples requiring QThreads support (default: OFF).

HPX_WITH_EXAMPLES_TBB:BOOL

Enable examples requiring TBB support (default: OFF).

HPX_WITH_EXECUTABLE_PREFIX:STRING

Executable prefix (default none), '**hpx_**' useful for system install.

HPX_WITH_FAIL_COMPILE_TESTS:BOOL

Create build system support for fail compile HPX tests (default ON)

HPX_WITH_FETCH_APEX:BOOL

Use FetchContent to fetch APEX. By default an installed APEX will be used. (default: OFF)

HPX_WITH_FETCH_ASIO:BOOL

Use FetchContent to fetch Asio. By default an installed Asio will be used. (default: OFF)

HPX_WITH_FETCH_BOOST:BOOL

Use FetchContent to fetch Boost. By default an installed Boost will be used. (default: OFF)

HPX_WITH_FETCH_GASNET:BOOL

Use FetchContent to fetch GASNET. By default an installed GASNET will be used. (default: OFF).

HPX_WITH_FETCH_HWLOC:BOOL

Use FetchContent to fetch Hwloc. By default an installed Hwloc will be used. (default: OFF)

HPX_WITH_FETCH_LCI:BOOL

Use FetchContent to fetch LCI. By default an installed LCI will be used. (default: OFF)

HPX_WITH_FETCH_LCW:BOOL

Use FetchContent to fetch LCW. By default an installed LCW will be used. (default: OFF)

HPX_WITH_IO_COUNTERS:BOOL

Enable IO counters (default: ON)

HPX_WITH_LCI_BOOTSTRAP_MPI:BOOL

Configure the autofetched LCI with mpi bootstrap support (default: OFF)

HPX_WITH_LCI_TAG:STRING

LCI repository tag or branch

HPX_WITH_LCW_TAG:STRING

LCW repository tag or branch

HPX_WITH_NANOBENCH:BOOL

Use Nanobench for performance tests. Nanobench will be fetched using FetchContent (default: OFF)

HPX_WITH_PARALLEL_LINK_JOBS:STRING

Number of Parallel link jobs while building hpx (only for Ninja as generator) (default 2)

HPX_WITH_TESTS:BOOL

Build the HPX tests (default ON)

HPX_WITH_TESTS_BENCHMARKS:BOOL

Build HPX benchmark tests (default: ON)

HPX_WITH_TESTS_EXAMPLES:BOOL

Add HPX examples as tests (default: ON)

HPX_WITH_TESTS_EXTERNAL_BUILD:BOOL

Build external cmake build tests (default: ON)

HPX_WITH_TESTS_HEADERS:BOOL

Build HPX header tests (default: OFF)

HPX_WITH_TESTS_REGRESSIONS:BOOL

Build HPX regression tests (default: ON)

HPX_WITH_TESTS_UNIT:BOOL

Build HPX unit tests (default: ON)

HPX_WITH_THRUST:BOOL

Enable support for NVIDIA Thrust integration (default: ON when CUDA is enabled, OFF otherwise)

HPX_WITH_TOOLS:BOOL

Build HPX tools (default: OFF)

Thread Manager options

- *HPX_COROUTINES_WITH_SWAP_CONTEXT_EMULATION:BOOL*
- *HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD:BOOL*
- *HPX_WITH_COROUTINE_COUNTERS:BOOL*
- *HPX_WITH_IO_POOL:BOOL*
- *HPX_WITH_MAX_CPU_COUNT:STRING*
- *HPX_WITH_MAX_NUMA_DOMAIN_COUNT:STRING*
- *HPX_WITH_SCHEDULER_LOCAL_STORAGE:BOOL*
- *HPX_WITH_SPINLOCK_DEADLOCK_DETECTION:BOOL*
- *HPX_WITH_SPINLOCK_POOL_NUM:STRING*
- *HPX_WITH_STACKTRACES:BOOL*
- *HPX_WITH_STACKTRACES_DEMANGLE_SYMBOLS:BOOL*
- *HPX_WITH_STACKTRACES_STATIC_SYMBOLS:BOOL*
- *HPX_WITH_THREAD_BACKTRACE_DEPTH:STRING*
- *HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION:BOOL*
- *HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES:BOOL*
- *HPX_WITH_THREAD_CUMULATIVE_COUNTS:BOOL*
- *HPX_WITH_THREAD_IDLE_RATES:BOOL*
- *HPX_WITH_THREAD_LOCAL_STORAGE:BOOL*
- *HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF:BOOL*

- *HPX_WITH_THREAD_QUEUE_WAITTIME:BOOL*
- *HPX_WITH_THREAD_STACK_MMAP:BOOL*
- *HPX_WITH_THREAD_STEALING_COUNTS:BOOL*
- *HPX_WITH_THREAD_TARGET_ADDRESS:BOOL*
- *HPX_WITH_TIMER_POOL:BOOL*
- *HPX_WITH_WORK_REQUESTING_SCHEDULERS:BOOL*

HPX_COROUTINES_WITH_SWAP_CONTEXT_EMULATION:BOOL

Emulate SwapContext API for coroutines (Windows only, default: OFF)

HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD:BOOL

Futures attempt to run associated threads directly if those have not been started (default: OFF)

HPX_WITH_COROUTINE_COUNTERS:BOOL

Enable keeping track of coroutine creation and rebind counts (default: OFF)

HPX_WITH_IO_POOL:BOOL

Disable internal IO thread pool, do not change if not absolutely necessary (default: ON)

HPX_WITH_MAX_CPU_COUNT:STRING

HPX applications will not use more than this number of OS-Threads (empty string means dynamic) (default: "")

HPX_WITH_MAX_NUMA_DOMAIN_COUNT:STRING

HPX applications will not run on machines with more NUMA domains (default: 8)

HPX_WITH_SCHEDULER_LOCAL_STORAGE:BOOL

Enable scheduler local storage for all HPX schedulers (default: OFF)

HPX_WITH_SPINLOCK_DEADLOCK_DETECTION:BOOL

Enable spinlock deadlock detection (default: OFF)

HPX_WITH_SPINLOCK_POOL_NUM:STRING

Number of elements a spinlock pool manages (default: 128)

HPX_WITH_STACKTRACES:BOOL

Attach backtraces to HPX exceptions (default: ON)

HPX_WITH_STACKTRACES_DEMANGLE_SYMBOLS:BOOL

Thread stack back trace symbols will be demangled (default: ON)

HPX_WITH_STACKTRACES_STATIC_SYMBOLS:BOOL

Thread stack back trace will resolve static symbols (default: OFF)

HPX_WITH_THREAD_BACKTRACE_DEPTH:STRING

Thread stack back trace depth being captured (default: 20)

HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION:BOOL

Enable thread stack back trace being captured on suspension (default: OFF)

HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES:BOOL

Enable measuring thread creation and cleanup times (default: OFF)

HPX_WITH_THREAD_CUMULATIVE_COUNTS:BOOL

Enable keeping track of cumulative thread counts in the schedulers (default: ON)

HPX_WITH_THREAD_IDLE_RATES:BOOL

Enable measuring the percentage of overhead times spent in the scheduler (default: OFF)

HPX_WITH_THREAD_LOCAL_STORAGE:BOOL

Enable thread local storage for all HPX threads (default: OFF)

HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF:BOOL

HPX scheduler threads do exponential backoff on idle queues (default: ON)

HPX_WITH_THREAD_QUEUE_WAITTIME:BOOL

Enable collecting queue wait times for threads (default: OFF)

HPX_WITH_THREAD_STACK_MMAP:BOOL

Use mmap for stack allocation on appropriate platforms

HPX_WITH_THREAD_STEALING_COUNTS:BOOL

Enable keeping track of counts of thread stealing incidents in the schedulers (default: OFF)

HPX_WITH_THREAD_TARGET_ADDRESS:BOOL

Enable storing target address in thread for NUMA awareness (default: OFF)

HPX_WITH_TIMER_POOL:BOOL

Disable internal timer thread pool, do not change if not absolutely necessary (default: ON)

HPX_WITH_WORK_REQUESTING_SCHEDULERS:BOOL

Enable work requesting scheduler (default: ON)

AGAS options

- *HPX_WITH_AGAS_DUMP_REFCNT_ENTRIES:BOOL*

HPX_WITH_AGAS_DUMP_REFCNT_ENTRIES:BOOL

Enable dumps of the AGAS refcnt tables to logs (default: OFF)

Parcelport options

- *HPX_WITH_NETWORKING:BOOL*
- *HPX_WITH_PARCELPORTR_ACTION_COUNTERS:BOOL*
- *HPX_WITH_PARCELPORTR_COUNTERS:BOOL*
- *HPX_WITH_PARCELPORTR_GASNET:BOOL*
- *HPX_WITH_PARCELPORTR_LCI:BOOL*
- *HPX_WITH_PARCELPORTR_LCI_LOG:STRING*
- *HPX_WITH_PARCELPORTR_LCI_PCOUNTER:STRING*
- *HPX_WITH_PARCELPORTR_LCW:BOOL*
- *HPX_WITH_PARCELPORTR_LCW_LOG:STRING*
- *HPX_WITH_PARCELPORTR_LCW_PCOUNTER:STRING*
- *HPX_WITH_PARCELPORTR_LIBFABRIC:BOOL*
- *HPX_WITH_PARCELPORTR_MPI:BOOL*
- *HPX_WITH_PARCELPORTR_TCP:BOOL*

- *HPX_WITH_PARCEL_PROFILING:BOOL*

HPX_WITH_NETWORKING:BOOL

Enable support for networking and multi-node runs (default: ON)

HPX_WITH_PARCELPART_ACTION_COUNTERS:BOOL

Enable performance counters reporting parcellport statistics on a per-action basis.

HPX_WITH_PARCELPART_COUNTERS:BOOL

Enable performance counters reporting parcellport statistics.

HPX_WITH_PARCELPART_GASNET:BOOL

Enable the GASNET based parcellport.

HPX_WITH_PARCELPART_LCI:BOOL

Enable the LCI based parcellport.

HPX_WITH_PARCELPART_LCI_LOG:STRING

Enable the LCI-parcellport-specific logger

HPX_WITH_PARCELPART_LCI_PCOUNTER:STRING

Enable the LCI-parcellport-specific performance counter

HPX_WITH_PARCELPART_LCW:BOOL

Enable the LCW based parcellport.

HPX_WITH_PARCELPART_LCW_LOG:STRING

Enable the LCW-parcellport-specific logger

HPX_WITH_PARCELPART_LCW_PCOUNTER:STRING

Enable the LCW-parcellport-specific performance counter

HPX_WITH_PARCELPART_LIBFABRIC:BOOL

Enable the libfabric based parcellport. This is currently an experimental feature

HPX_WITH_PARCELPART_MPI:BOOL

Enable the MPI based parcellport.

HPX_WITH_PARCELPART_TCP:BOOL

Enable the TCP based parcellport.

HPX_WITH_PARCEL_PROFILING:BOOL

Enable profiling data for parcels

Profiling options

- *HPX_LIKWID_WITH_LIKWID:BOOL*
- *HPX_WITH_APEX:BOOL*
- *HPX_WITH_ITTNOTIFY:BOOL*
- *HPX_WITH_PAPI:BOOL*
- *HPX_WITH_TRACY:BOOL*

HPX_LIKWID_WITH_LIKWID:BOOL

Enable Likwid instrumentation support.

HPX_WITH_APEX:BOOL

Enable APEX instrumentation support.

HPX_WITH_ITTNOTIFY:BOOL

Enable Amplifier (ITT) instrumentation support.

HPX_WITH_PAPI:BOOL

Enable the PAPI based performance counter.

HPX_WITH_TRACY:BOOL

Enable Tracy instrumentation support.

Debugging options

- *HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS:BOOL*
- *HPX_WITH_ATTACH_DEBUGGER_ON_TEST_FAILURE:BOOL*
- *HPX_WITH_CONTRACTS:BOOL*
- *HPX_WITH_PARALLEL_TESTS_BIND_NONE:BOOL*
- *HPX_WITH_SANITIZERS:BOOL*
- *HPX_WITH_TESTS_COMMAND_LINE:STRING*
- *HPX_WITH_TESTS_DEBUG_LOG:BOOL*
- *HPX_WITH_TESTS_DEBUG_LOG_DESTINATION:STRING*
- *HPX_WITH_TESTS_MAX_THREADS_PER_LOCALITY:STRING*
- *HPX_WITH_THREAD_DEBUG_INFO:BOOL*
- *HPX_WITH_THREAD_DESCRIPTION_FULL:BOOL*
- *HPX_WITH_THREAD_GUARD_PAGE:BOOL*
- *HPX_WITH_VALGRIND:BOOL*
- *HPX_WITH_VERIFY_LOCKS:BOOL*
- *HPX_WITH_VERIFY_LOCKS_BACKTRACE:BOOL*

HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS:BOOL

Swap `hpx_assert` with `hpx_contract_assert`

HPX_WITH_ATTACH_DEBUGGER_ON_TEST_FAILURE:BOOL

Break the debugger if a test has failed (default: OFF)

HPX_WITH_CONTRACTS:BOOL

Enable C++ contracts support in HPX

HPX_WITH_PARALLEL_TESTS_BIND_NONE:BOOL

Pass `-hpx:bind=none` to tests that may run in parallel (cmake `-j` flag) (default: OFF)

HPX_WITH_SANITIZERS:BOOL

Configure with sanitizer instrumentation support.

HPX_WITH_TESTS_COMMAND_LINE:STRING

Add given command line options to all tests run

HPX_WITH_TESTS_DEBUG_LOG:BOOL

Turn on debug logs (`-hpx:debug-hpx-log`) for tests (default: OFF)

HPX_WITH_TESTS_DEBUG_LOG_DESTINATION:STRING

Destination for test debug logs (default: `cout`)

HPX_WITH_TESTS_MAX_THREADS_PER_LOCALITY:STRING

Maximum number of threads to use for tests (default: 0, use the number of threads specified by the test)

HPX_WITH_THREAD_DEBUG_INFO:BOOL

Enable thread debugging information (default: OFF, implicitly enabled in debug builds)

HPX_WITH_THREAD_DESCRIPTION_FULL:BOOL

Use function address for thread description (default: OFF)

HPX_WITH_THREAD_GUARD_PAGE:BOOL

Enable thread guard page (default: ON)

HPX_WITH_VALGRIND:BOOL

Enable Valgrind instrumentation support.

HPX_WITH_VERIFY_LOCKS:BOOL

Enable lock verification code (default: OFF, enabled in debug builds)

HPX_WITH_VERIFY_LOCKS_BACKTRACE:BOOL

Enable thread stack back trace being captured on lock registration (to be used in combination with `HPX_WITH_VERIFY_LOCKS=ON`, default: OFF)

Modules options

- *HPX_ALLOCATOR_SUPPORT_WITH_CACHING:BOOL*
- *HPX_COMMAND_LINE_HANDLING_LOCAL_WITH_JSON_CONFIGURATION_FILES:BOOL*
- *HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE:BOOL*
- *HPX_DATASTRUCTURES_WITH_ADAPT_STD_VARIANT:BOOL*
- *HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY:BOOL*
- *HPX_FUNCTIONAL_WITH_BOOST_PLACEHOLDERS:BOOL*
- *HPX_IOSTREAM_WITH_WIDE_STREAMS:BOOL*
- *HPX_ITERATOR_SUPPORT_WITH_BOOST_ITERATOR_TRAVERSAL_TAG_COMPATIBILITY:BOOL*
- *HPX_LOGGING_WITH_SEPARATE_DESTINATIONS:BOOL*
- *HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS:BOOL*
- *HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION:BOOL*
- *HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE:BOOL*
- *HPX_SERIALIZATION_WITH_BOOST_TYPES:BOOL*
- *HPX_SERIALIZATION_WITH_SUPPORTS_ENDIANESS:BOOL*
- *HPX_TOPOLOGY_WITH_ADDITIONAL_HWLOC_TESTING:BOOL*
- *HPX_WITH_POWER_COUNTER:BOOL*

HPX_ALLOCATOR_SUPPORT_WITH_CACHING:BOOL

Enable caching allocator. (default: ON)

HPX_COMMAND_LINE_HANDLING_LOCAL_WITH_JSON_CONFIGURATION_FILES:BOOL

Enable reading JSON formatted configuration files on the command line.

(default: OFF)

HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE:BOOL

Enable compatibility of `hpx::get` with `std::tuple`. (default: ON)

HPX_DATASTRUCTURES_WITH_ADAPT_STD_VARIANT:BOOL

Enable compatibility of `hpx::get` with `std::variant`.

(default: OFF)

HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY:BOOL

Enable `Boost.FileSystem` compatibility. (default: OFF)

HPX_FUNCTIONAL_WITH_BOOST_PLACEHOLDERS:BOOL

Enable support for Boost placeholder types. (default: OFF)

HPX_Iostream_WITH_WIDE_STREAMS:BOOL

Enable wide IO streams. (default: OFF)

HPX_ITERATOR_SUPPORT_WITH_BOOST_ITERATOR_TRAVERSAL_TAG_COMPATIBILITY:BOOL

Enable `Boost.Iterator` traversal tag compatibility. (default: OFF)

HPX_LOGGING_WITH_SEPARATE_DESTINATIONS:BOOL

Enable separate logging channels for AGAS, timing, and parcel transport. (default: ON)

HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS:BOOL

Enable serializing `std::tuple` with `const` members. (default: OFF)

HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION:BOOL

Enable serializing raw pointers. (default: OFF)

HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE:BOOL

Assume all types are bitwise serializable. (default: OFF)

HPX_SERIALIZATION_WITH_BOOST_TYPES:BOOL

Enable serialization of certain Boost types. (default: OFF)

HPX_SERIALIZATION_WITH_SUPPORTS_ENDIANESS:BOOL

Support endian conversion on input and output archives. (default: OFF)

HPX_TOPOLOGY_WITH_ADDITIONAL_HWLOC_TESTING:BOOL

Enable HWLOC filtering that makes it report no cores, this is purely an option supporting better testing - do not enable under normal circumstances. (default: OFF)

HPX_WITH_POWER_COUNTER:BOOL

Enable use of performance counters based on `pwr` library (default: OFF)

Additional tools and libraries used by HPX

Here is a list of additional libraries and tools that are either optionally supported by the build system or are optionally required for certain examples or tests. These libraries and tools can be detected by the *HPX* build system.

Each of the tools or libraries listed here will be automatically detected if they are installed in some standard location. If a tool or library is installed in a different location, you can specify its base directory by appending `_ROOT` to the variable name as listed below. For instance, to configure a custom directory for Boost, specify `Boost_ROOT=/custom/boost/root`.

Boost_ROOT:PATH

Specifies where to look for the Boost installation to be used for compiling *HPX*. Set this if CMake is not able to locate a suitable version of Boost. The directory specified here can be either the root of an installed Boost distribution or the directory where you unpacked and built Boost without installing it (with staged libraries).

Hwloc_ROOT:PATH

Specifies where to look for the hwloc library. Set this if CMake is not able to locate a suitable version of hwloc. Hwloc provides platform-independent support for extracting information about the used hardware architecture (number of cores, number of NUMA domains, hyperthreading, etc.). *HPX* utilizes this information if available.

Papi_ROOT:PATH

Specifies where to look for the PAPI library. The PAPI library is needed to compile a special component exposing PAPI hardware events and counters as *HPX* performance counters. This is not available on the Windows platform.

Amplifier_ROOT:PATH

Specifies where to look for one of the tools of the Intel Parallel Studio product, either Intel Amplifier or Intel Inspector. This should be set if the CMake variable `HPX_USE_ITT_NOTIFY` is set to ON. Enabling ITT support in *HPX* will integrate any application with the mentioned Intel tools, which customizes the generated information for your application and improves the generated diagnostics.

In addition, some of the examples may need the following variables:

Hdf5_ROOT:PATH

Specifies where to look for the Hierarchical Data Format V5 (HDF5) include files and libraries.

2.4.5 Using HPX on Compiler Explorer

Compiler Explorer⁶³ (CE) is a browser-based tool that compiles C++ code in real time and shows assembly, program output, and optimization results side by side. It is widely used for quick experiments, conference demos, and sharing reproducible snippets. This page explains how to build *HPX* for CE, how to link against its static libraries from a raw compiler command, and how to use the *sandbox header* that *HPX* ships specifically for constrained environments.

Sandbox environment constraints

CE executes compiled programs inside a Linux container (nsjail) with no network access and limited resources. The constraints that matter most for *HPX* are:

- No network namespace — sockets cannot be opened. Any attempt to initialise the distributed runtime will fail with `EACCES` at startup.
- A small PID budget (typically 32 PIDs) — *HPX* starts cleanly within this limit when the worker thread count is kept low.

⁶³ <https://godbolt.org>

- A short execution timeout — CE’s public instance allows roughly 10 seconds. An *HPX* fork or self-hosted instance can relax this to 30 seconds, which is enough for benchmarks on problem sizes of one million elements or more.
- Static linking is required — the sandbox does not augment `LD_LIBRARY_PATH`, so shared *HPX* libraries are not found at runtime.

Building *HPX* for Compiler Explorer

HPX ships a `godbolt-minimal` configure preset in `CMakePresets.json` that encodes all the flags needed for a CE-compatible build:

```
$ cmake --preset godbolt-minimal
$ cmake --build --preset godbolt-minimal
```

This preset enables:

- `HPX_WITH_STATIC_LINKING=ON` — bundles everything into the `.a` archives that CE links against.
- `HPX_WITH_NETWORKING=OFF` — disables the parcelset so *HPX* never attempts to open a network socket.
- `HPX_WITH_FETCH_ASIO=ON` — downloads Asio via FetchContent, removing the need for a system-level Asio installation.
- `HPX_WITH_MALLOC=system` — uses the system allocator; avoids a `jemalloc` or `tcmalloc` dependency.
- `HPX_WITH_TESTS=OFF`, `HPX_WITH_EXAMPLES=OFF`, `HPX_WITH_DOCUMENTATION=OFF` — skips everything that CE does not need.

The preset produces four static libraries under `build/godbolt-minimal/lib/`:

```
libhpx_wrap.a
libhpx_init.a
libhpx.a
libhpx_core.a
```

These are the only artifacts that CE consumes.

Note: The `HPX_WITH_CXX_STANDARD` variable pins the C++ standard for the build (e.g. `-DHPX_WITH_CXX_STANDARD=20`). This is *HPX*’s own cache variable and is distinct from `CMAKE_CXX_STANDARD`, which *HPX* rejects unless `HPX_USE_CMAKE_CXX_STANDARD` is also set.

Linking without CMake

CE’s backend compiles user code with a raw `g++` or `clang++` invocation. The complete set of flags needed is:

```
$ g++ -std=c++20 -O2 -o my_program my_program.cpp \
    -isystem /path/to/hpx/include \
    -isystem /path/to/boost/include \
    -L/path/to/hpx/lib \
    -DHPX_APPLICATION_EXPORTS \
    -Wl,-wrap=main \
    -lhpx_wrap -lhpx_init -lhpx -lhpx_core \
    -lpthread -ldl -lrt
```

Two details here are easy to get wrong:

Library link order. The order `hpx_wrap` → `hpx_init` → `hpx` → `hpx_core` must be preserved. Reversing it produces undefined-reference errors because `hpx_wrap` depends on symbols in `hpx_init`, which depends on the full runtime in `hpx`, which in turn depends on the core library.

The `-Wl, -wrap=main` flag. Including `hpx/hpx_main.hpp` (see *Re-use the `main()` function as the main HPX entry point*) works by re-routing control through HPX's own entry point before the user's `main` is called. On Linux this is implemented via the linker's `--wrap` option; the flag must therefore appear on the *linker* command line, not merely in the compile flags. Without it, the HPX runtime is never initialised and all API calls crash at startup. See *Linux implementation* for a detailed explanation of the mechanism.

Important: `-DHPX_APPLICATION_EXPORTS` must be passed as a preprocessor definition when compiling application code against the static libraries. Omitting it causes link failures related to HPX's symbol visibility macros.

Writing HPX code for Compiler Explorer

The simplest way to write an HPX program for CE is to include `hpx/hpx_main.hpp`. This header arranges for the HPX runtime to be initialised before `main` runs, so the body of `main` can call any HPX API function directly:

```
#include <hpx/hpx_main.hpp>
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

#include <iostream>
#include <numeric>
#include <vector>

int main()
{
    std::vector<int> v(1'000'000);
    std::iota(v.begin(), v.end(), 0);

    long long sum = hpx::transform_reduce(
        hpx::execution::par, v.begin(), v.end(), 0LL,
        std::plus<>{}, [](int x) { return static_cast<long long>(x); });

    std::cout << "sum = " << sum << "\n";
}
```

Caution: Include `hpx/hpx_main.hpp` in exactly one translation unit — the file that contains `main`. Including it in more than one file causes a multiple definition error for the `include_libhpx_wrap` variable that controls runtime initialisation.

The `hpx/experimental/sandbox.hpp` header

HPX ships a header-only toolkit at `hpx/experimental/sandbox.hpp` designed specifically for code running in constrained environments. It provides:

- **Environment introspection** — `hpx::experimental::sandbox::detect_environment()` returns an `environment_info` struct describing the number of physical cores, processing units, NUMA domains, and active HPX worker threads. The `is_sandbox` flag is set when the `COMPILER_EXPLORER` or `HPX_SANDBOX` environment variable is present, letting code adapt its behaviour automatically.
- **Timing** — `hpx::experimental::sandbox::measure(fn, iterations)` runs a callable `fn` for `iterations` repetitions (with one warmup pass) and returns the mean execution time in milliseconds.
- **Comparative benchmarking** — `hpx::experimental::sandbox::benchmark(label, seq_fn, par_fn, iterations)` measures both a sequential and a parallel version of the same computation, computes speedup and parallel efficiency, and returns a `benchmark_report` struct. Calling `report.print(std::cout)` produces a fixed-width table that renders cleanly in CE's output pane.

A typical usage pattern looks like this:

```
#include <hpx/hpx_main.hpp>
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>
#include <hpx/experimental/sandbox.hpp>

#include <algorithm>
#include <iostream>
#include <numeric>
#include <vector>

int main()
{
    namespace sb = hpx::experimental::sandbox;

    sb::describe_environment(std::cout);

    std::vector<int> data(500'000);
    std::iota(data.begin(), data.end(), 0);

    auto report = sb::benchmark(
        "transform_reduce",
        [&]() {
            hpx::transform_reduce(
                hpx::execution::seq,
                data.begin(), data.end(), 0LL,
                std::plus<>{}, [](int x) { return (long long)x; });
        },
        [&]() {
            hpx::transform_reduce(
                hpx::execution::par,
                data.begin(), data.end(), 0LL,
                std::plus<>{}, [](int x) { return (long long)x; });
        });

    report.print(std::cout);
}
```


The output includes sequential and parallel mean times, speedup, parallel efficiency, and a verdict (Excellent scaling, Good scaling, Moderate scaling, Limited scaling, or No speedup).

Note: All functions in `hpx/experimental/sandbox.hpp` must be called from within a running *HPX* runtime, i.e., from an *HPX* thread. Calling them before `hpx::init` or after `hpx::finalize` is undefined behaviour. When using `hpx/hpx_main.hpp`, the body of `main` satisfies this requirement automatically.

Known limitations in sandboxed environments

- **Single locality only.** The distributed runtime can be compiled in (`HPX_WITH_DISTRIBUTED_RUNTIME=ON`) and actions on locality 0 work normally, but there is no way to launch a second locality from within CE's sandbox. Code that calls `hpx::find_all_localities()` or `hpx::get_num_localities()` will always see exactly one locality.
- **Networking is disabled.** `HPX_WITH_NETWORKING=OFF` means all parcelport-dependent functionality (remote actions, distributed data structures) is unavailable regardless of what the code requests.
- **Thread count is limited by the sandbox's CPU allocation.** CE's public instance typically exposes two cores. Use `--hpx:threads=N` on the command line or `hpx::init_params::cfg` in code to set the worker count explicitly rather than relying on hardware detection. See *Launching and configuring HPX applications* for details.
- **macOS link flag differs.** The `-Wl, -wrap=main` flag is Linux-specific. On macOS the linker uses `-Wl, -e, _initialize_main` instead. CE runs Linux containers, so this only matters when building the CE integration locally on macOS for testing.

2.4.6 Migration guide

The Migration Guide serves as a valuable resource for developers seeking to transition their parallel computing applications from different APIs (i.e. OpenMP, Intel Threading Building Blocks (TBB), MPI) to *HPX*. *HPX*, an advanced C++ library, offers a versatile and high-performance platform for parallel and distributed computing, providing a wide range of features and capabilities. This guide aims to assist developers in understanding the key differences between different APIs and *HPX*, and it provides step-by-step instructions for converting code to *HPX* code effectively.

Some general steps that can be used to migrate code to *HPX* code are the following:

1. Install *HPX* using the *Quick start* guide.
2. Include the *HPX* header files:

Add the necessary header files for *HPX* at the beginning of your code, such as:

```
#include <hpx/init.hpp>
```

3. Replace your code with *HPX* code using the guide that follows.
4. Use *HPX*-specific features and APIs:

HPX provides additional features and APIs that can be used to take advantage of the library's capabilities. For example, you can use the *HPX* asynchronous execution to express fine-grained tasks and dependencies, or utilize *HPX*'s distributed computing features for distributed memory systems.

5. Compile and run the *HPX* code:

Compile the converted code with the *HPX* library and run it using the appropriate *HPX* runtime environment.

OpenMP

The OpenMP API supports multi-platform shared-memory parallel programming in C/C++. Typically it is used for loop-level parallelism, but it also supports function-level parallelism. Below are some examples on how to convert OpenMP to *HPX* code:

OpenMP parallel for loop

Parallel for loop

OpenMP code:

```
#pragma omp parallel for
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    // loop body
});
```

In the above code, the OpenMP `#pragma omp parallel for` directive is replaced with `hpx::experimental::for_loop` from the *HPX* library. The loop body within the lambda function will be executed in parallel for each iteration.

Private variables

OpenMP code:

```
int x = 0;

#pragma omp parallel for private(x)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    int x = 0; // Declare 'x' as a local variable inside the loop body
    // loop body
});
```

The variable `x` is declared as a local variable inside the loop body, ensuring that it is private to each thread.

Shared variables

OpenMP code:

```
int x = 0;

#pragma omp parallel for shared(x)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

std::atomic<int> x = 0; // Declare 'x' as a shared variable outside the loop

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    // loop body
});
```

To ensure variable *x* is shared among all threads, you simply have to declare it as an atomic variable outside the *for_loop*.

Number of threads

OpenMP code:

```
#pragma omp parallel for num_threads(2)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

hpx::execution::experimental::num_cores nc(2);

hpx::experimental::for_loop(hpx::execution::par.with(nc), 0, n, [&](int i) {
    // loop body
});
```

To declare the number of threads to be used for the parallel region, you can use *hpx::execution::experimental::num_cores* and pass the number of cores (*nc*) to *hpx::experimental::for_loop* using *hpx::execution::par.with(nc)*. This example uses 2 threads for the parallel loop.

Reduction

OpenMP code:

```
int s = 0;

#pragma omp parallel for reduction(+: s)
for (int i = 0; i < n; ++i) {
    s += i;
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

int s = 0;

hpx::experimental::for_loop(hpx::execution::par, 0, n, reduction(s, 0, plus<>()), [&
↪](int i, int& accum) {
    accum += i;
    // loop body
});
```

The reduction clause specifies that the variable *s* should be reduced across iterations using the *plus<>* operation. It initializes *s* to 0 at the beginning of the loop and accumulates the values of *s* from each iteration using the + operator. The lambda function representing the loop body takes two parameters: *i*, which represents the loop index, and *accum*, which is the reduction variable *s*. The lambda function is executed for each iteration of the loop. The reduction ensures that the *accum* value is correctly accumulated across different iterations and threads.

Schedule

OpenMP code:

```
int s = 0;

// static scheduling with chunk size 1000
#pragma omp parallel for schedule(static, 1000)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

hpx::execution::experimental::static_chunk_size cs(1000);

hpx::experimental::for_loop(hpx::execution::par.with(cs), 0, n, [&](int i) {
    // loop body
});
```

To define the scheduling type, you can use the corresponding execution policy from `hpx::execution::experimental`, define the chunk size (cs, here declared as 1000) and pass it to the `hpx::experimental::for_loop` using `hpx::execution::par.with(cs)`.

Accordingly, other types of scheduling are available and can be used in a similar manner:

```
#include <hpx/execution.hpp>
hpx::execution::experimental::dynamic_chunk_size cs(1000);
```

```
#include <hpx/execution.hpp>
hpx::execution::experimental::guided_chunk_size cs(1000);
```

```
#include <hpx/execution.hpp>
hpx::execution::experimental::auto_chunk_size cs(1000);
```

OpenMP single thread

OpenMP code:

```
{ // parallel code
  #pragma omp single
  {
    // single-threaded code
  }
  // more parallel code
}
```

HPX equivalent:

```
#include <hpx/mutex.hpp>

hpx::mutex mtx;

{ // parallel code
  { // single-threaded code
    std::scoped_lock l(mtx);
  }
  // more parallel code
}
```

To make sure that only one thread accesses a specific code within a parallel section you can use `hpx::mutex` and `std::scoped_lock` to take ownership of the given mutex `mtx`. For more information about mutexes please refer to *Mutex*.

OpenMP tasks

Simple tasks

OpenMP code:

```
// executed asynchronously by any available thread
#pragma omp task
{
    // task code
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

auto future = hpx::async([](){
    // task code
});
```

or

```
#include <hpx/future.hpp>

hpx::post([](){
    // task code
}); // fire and forget
```

The tasks in *HPX* can be defined simply by using the `async` function and passing as argument the code you wish to run asynchronously. Another alternative is to use `post` which is a fire-and-forget method.

Tip: If you think you will like to synchronize your tasks later on, we suggest you use `hpx::async` which provides synchronization options, while `hpx::post` explicitly states that there is no return value or way to synchronize with the function execution. Synchronization options are listed below.

Task wait

OpenMP code:

```
#pragma omp task
{
    // task code
}

#pragma omp taskwait
// code after completion of task
```

HPX equivalent:

```
#include <hpx/future.hpp>
```

(continues on next page)

(continued from previous page)

```

hpx::async([]){
    // task code
}.get(); // wait for the task to complete

// code after completion of task

```

The `get()` function can be used to ensure that the task created with `hpx::async` is completed before the code continues executing beyond that point.

Multiple tasks synchronization

OpenMP code:

```

#pragma omp task
{
    // task 1 code
}

#pragma omp task
{
    // task 2 code
}

#pragma omp taskwait
// code after completion of both tasks 1 and 2

```

HPX equivalent:

```

#include <hpx/future.hpp>

auto future1 = hpx::async([](){
    // task 1 code
});

auto future2 = hpx::async([](){
    // task 2 code
});

auto future = hpx::when_all(future1, future2).then([](auto&&){
    // code after completion of both tasks 1 and 2
});

```

If you would like to synchronize multiple tasks, you can use the `hpx::when_all` function to define which futures have to be ready and the `then()` function to declare what should be executed once these futures are ready.

Dependencies

OpenMP code:

```
int a = 10;
int b = 20;
int c = 0;

#pragma omp task depend(in: a, b) depend(out: c)
{
    // task code
    c = 100;
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

int a = 10;
int b = 20;
int c = 0;

// Create a future representing 'a'
auto future_a = hpx::make_ready_future(a);

// Create a future representing 'b'
auto future_b = hpx::make_ready_future(b);

// Create a task that depends on 'a' and 'b' and executes 'task_code'
auto future_c = hpx::dataflow(
    []() {
        // task code
        return 100;
    },
    future_a, future_b);

c = future_c.get();
```

If one of the arguments of `hpx::dataflow` is a future, then it will wait for the future to be ready to launch the thread. Hence, to define the dependencies of tasks you have to create futures representing the variables that create dependencies and pass them as arguments to `hpx::dataflow`. `get()` is used to save the result of the future to the desired variable.

Nested tasks

OpenMP code:

```
#pragma omp task
{
    // Outer task code
    #pragma omp task
    {
        // Inner task code
    }
}
```

(continues on next page)

(continued from previous page)

```

    }
}

```

HPX equivalent:

```

#include <hpx/future.hpp>

auto future_outer = hpx::async([](){
    // Outer task code

    hpx::async([](){
        // Inner task code
    });
});

```

or

```

#include <hpx/future.hpp>

auto future_outer = hpx::post([](){ // fire and forget
    // Outer task code

    hpx::post([](){ // fire and forget
        // Inner task code
    });
});

```

If you have nested tasks, you can simply use nested `hpx::async` or `hpx::post` calls. The implementation is similar if you want to take care of synchronization:

OpenMP code:

```

#pragma omp taskwait
{
    // Outer task code
    #pragma omp taskwait
    {
        // Inner task code
    }
}

```

HPX equivalent:

```

#include <hpx/future.hpp>

auto future_outer = hpx::async([]() {
    // Outer task code

    hpx::async([]() {
        // Inner task code
    }).get();    // Wait for the inner task to complete
});

future_outer.get();    // Wait for the outer task to complete

```

Task yield

OpenMP code:

```
#pragma omp task
{
    // code before yielding
    #pragma omp taskyield
    // code after yielding
}
```

HPX equivalent:

```
#include <hpx/future.hpp>
#include <hpx/thread.hpp>

auto future = hpx::async([](){
    // code before yielding
});

// yield execution to potentially allow other tasks to run
hpx::this_thread::yield();

// code after yielding
```

After creating a task using `hpx::async`, `hpx::this_thread::yield` can be used to reschedule the execution of threads, allowing other threads to run.

Task group

OpenMP code:

```
#pragma omp taskgroup
{
    #pragma omp task
    {
        // task 1 code
    }

    #pragma omp task
    {
        // task 2 code
    }
}
```

HPX equivalent:

```
#include <hpx/task_group.hpp>

// Declare a task group
hpx::experimental::task_group tg;

// Run the tasks
```

(continues on next page)

(continued from previous page)

```

tg.run([]){
    // task 1 code
};
tg.run(
    // task 2 code
);

// Wait for the task group
tg.wait();

```

To create task groups, you can use `hpx::experimental::task_group`. The function `run()` can be used to run each task within the task group, while `wait()` can be used to achieve synchronization. If you do not care about waiting for the task group to complete its execution, you can simply remove the `wait()` function.

OpenMP sections

OpenMP code:

```

#pragma omp sections
{
    #pragma omp section
    // section 1 code
    #pragma omp section
    // section 2 code
} // implicit synchronization

```

HPX equivalent:

```

#include <hpx/future.hpp>

auto future_section1 = hpx::async([](){
    // section 1 code
});
auto future_section2 = hpx::async([](){
    // section 2 code
});

// synchronization: wait for both sections to complete
hpx::wait_all(future_section1, future_section2);

```

Unlike tasks, there is an implicit synchronization barrier at the end of each `sections` directive in OpenMP. This synchronization is achieved using `hpx::wait_all` function.

Note: If the `nowait` clause is used in the `sections` directive, then you can just remove the `hpx::wait_all` function while keeping the rest of the code as it is.

Intel Threading Building Blocks (TBB)

Intel Threading Building Blocks (TBB) provides a high-level interface for parallelism and concurrent programming using standard ISO C++ code. Below are some examples on how to convert Intel Threading Building Blocks (TBB) to *HPX* code:

parallel_for

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>(10000);

tbb::parallel_for( tbb::blocked_range<int>(0, values.size()),
                  [&](tbb::blocked_range<int> r)
{
    for (int i=r.begin(); i<r.end(); ++i)
    {
        // loop body
    }
});
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

auto values = std::vector<double>(10000);

hpx::experimental::for_loop(hpx::execution::par, 0, values.size(), [&](int i) {
    // loop body
});
```

In the above code, *tbb::parallel_for* is replaced with *hpx::experimental::for_loop* from the *HPX* library. The loop body within the lambda function will be executed in parallel for each iteration.

parallel_for_each

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>(10000);

tbb::parallel_for_each(values.begin(), values.end(), [&]() {
    // loop body
});
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

auto values = std::vector<double>(10000);

hpx::for_each(hpx::execution::par, values.begin(), values.end(), [&]() {
```

(continues on next page)

(continued from previous page)

```
// loop body
});
```

By utilizing `hpx::for_each` and specifying a parallel execution policy with `hpx::execution::par`, it is possible to transform `tbb::parallel_for_each` into its equivalent counterpart in HPX.

parallel_invoke

Intel Threading Building Blocks (TBB) code:

```
tbb::parallel_invoke(task1, task2, task3);
```

HPX equivalent:

```
#include <hpx/future.hpp>

hpx::wait_all(hpx::async(task1), hpx::async(task2), hpx::async(task3));
```

To convert `tbb::parallel_invoke` to HPX, we use `hpx::async` to asynchronously execute each task, which returns a future representing the result of each task. We then pass these futures to `hpx::when_all`, which waits for all the futures to complete before returning.

parallel_pipeline

Intel Threading Building Blocks (TBB) code:

```
tbb::parallel_pipeline(4,
    tbb::make_filter<void, int>(tbb::filter::serial_in_order,
        [](tbb::flow_control& fc) -> int {
            // Generate numbers from 1 to 10
            static int i = 1;
            if (i <= 10) {
                return i++;
            }
            else {
                fc.stop();
                return 0;
            }
        }) &
    tbb::make_filter<int, int>(tbb::filter::parallel,
        [](int num) -> int {
            // Multiply each number by 2
            return num * 2;
        }) &
    tbb::make_filter<int, void>(tbb::filter::serial_in_order,
        [](int num) {
            // Print the results
            std::cout << num << " ";
        })
);
```

HPX equivalent:

```
#include <iostream>
#include <vector>
#include <ranges>
#include <hpx/algorithm.hpp>

// generate the values
auto range = std::views::iota(1) | std::views::take(10);

// materialize the output vector
std::vector<int> results(10);

// in parallel execution of pipeline and transformation
hpx::ranges::transform(
    hpx::execution::par, range, result.begin(), [](int i) { return 2 * i; });

// print the modified vector
for (int i : result)
{
    std::cout << i << " ";
}
std::cout << std::endl;
```

The line `auto range = std::views::iota(1) | std::views::take(10);` generates a range of values using the `std::views::iota` function. It starts from the value 1 and generates an infinite sequence of incrementing values. The `std::views::take(10)` function is then applied to limit the sequence to the first 10 values. The result is stored in the `range` variable.

Hint: A view is a lightweight object that represents a particular view of a sequence or range. It acts as a read-only interface to the original data, providing a way to query and traverse the elements without making any copies or modifications.

Views can be composed and chained together to form complex pipelines of operations. These operations are evaluated lazily, meaning that the actual computation is performed only when the result is needed or consumed.

Since views perform lazy evaluation, we use `std::vector<int> results(10);` to materialize the vector that will store the transformed values. The `hpx::ranges::transform` function is then used to perform a parallel transformation on the range. The transformed values will be written to the `results` vector.

Hint: Ranges enable loop fusion by combining multiple operations into a single parallel loop, eliminating waiting time and reducing overhead. Using ranges, you can express these operations as a pipeline of transformations on a sequence of elements. This pipeline is evaluated in a single pass, performing all the desired operations in parallel without the need to wait between them.

In addition, *HPX* enhances the benefits of range fusion by offering parallel execution policies, which can be used to optimize the execution of the fused loop across multiple threads.

parallel_reduce

Reduction

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto total = tbb::parallel_reduce(
    tbb::blocked_range<int>(0, values.size()),
    0.0,
    [&](tbb::blocked_range<int> r, double running_total)
    {
        for (int i=r.begin(); i<r.end(); ++i)
        {
            running_total += values[i];
        }

        return running_total;
    },
    std::plus<double>());
```

HPX equivalent:

```
#include <hpx/numeric.hpp>

auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto total = hpx::reduce(
    hpx::execution::par, values.begin(), values.end(), 0, std::plus{});
```

By utilizing `hpx::reduce` and specifying a parallel execution policy with `hpx::execution::par`, it is possible to transform `tbb::parallel_reduce` into its equivalent counterpart in *HPX*. As demonstrated in the previous example, the management of intermediate results is seamlessly handled internally by *HPX*, eliminating the need for explicit consideration.

Transformation & Reduction

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto transform_function(double current_value){
    // transformation code
}

auto total = tbb::parallel_reduce(
    tbb::blocked_range<int>(0, values.size()),
    0.0,
    [&](tbb::blocked_range<int> r, double transformed_val)
    {
        for (int i=r.begin(); i<r.end(); ++i)
```

(continues on next page)

(continued from previous page)

```

        {
            transformed_val += transform_function(values[i]);
        }
        return transformed_val;
    },
    std::plus<double>());

```

HPX equivalent:

```

#include <hpx/numeric.hpp>

auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto transform_function(double current_value)
{
    // transformation code
}

auto total = hpx::transform_reduce(hpx::execution::par, values.begin(),
    values.end(), 0, std::plus{},
    [&](double current_value) { return transform_function(current_value); });

```

In situations where certain values require transformation before the reduction process, *HPX* provides a straightforward solution through `hpx::transform_reduce`. The `transform_function()` allows for the application of the desired transformation to each value.

parallel_scan

Intel Threading Building Blocks (TBB) code:

```

tbb::parallel_scan(tbb::blocked_range<size_t>(0, input.size()),
    0,
    [&input, &output](const tbb::blocked_range<size_t>& range, int& partial_sum, bool is_
    ↪final_scan) {
        for (size_t i = range.begin(); i != range.end(); ++i) {
            partial_sum += input[i];
            if (is_final_scan) {
                output[i] = partial_sum;
            }
        }
        return partial_sum;
    },
    [](int left_sum, int right_sum) {
        return left_sum + right_sum;
    }
);

```

HPX equivalent:

```

#include <hpx/numeric.hpp>

hpx::inclusive_scan(hpx::execution::par, input.begin(), input.end(),

```

(continues on next page)

(continued from previous page)

```
output.begin(),
[](const int& left, const int& right) { return left + right; });
```

hpx::inclusive_scan with *hpx::execution::par* as execution policy can be used to perform a prefix scan in parallel. The management of intermediate results is seamlessly handled internally by *HPX*, eliminating the need for explicit consideration. *input.begin()* and *input.end()* refer to the beginning and end of the sequence of elements the algorithm will be applied to respectively. *output.begin()* refers to the beginning of the destination, while the last argument specifies the function which will be invoked for each of the values of the input sequence.

Apart from *hpx::inclusive_scan*, *HPX* provides its users with *hpx::exclusive_scan*. The key difference between inclusive scan and exclusive scan lies in the treatment of the current element during the scan operation. In an inclusive scan, each element in the output sequence includes the contribution of the corresponding element in the input sequence, while in an exclusive scan, the current element in the input sequence does not contribute to the corresponding element in the output sequence.

parallel_sort

Intel Threading Building Blocks (TBB) code:

```
std::vector<int> numbers = {9, 2, 7, 1, 5, 3};

tbb::parallel_sort(numbers.begin(), numbers.end());
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

std::vector<int> numbers = {9, 2, 7, 1, 5, 3};

hpx::sort(hpx::execution::par, numbers.begin(), numbers.end());
```

hpx::sort provides an equivalent functionality to *tbb::parallel_sort*. When given a parallel execution policy with *hpx::execution::par*, the algorithm employs parallel execution, allowing for efficient sorting across available threads.

task_group

Intel Threading Building Blocks (TBB) code:

```
// Declare a task group
tbb::task_group tg;

// Run the tasks
tg.run(task1);
tg.run(task2);

// Wait for the task group
tg.wait();
```

HPX equivalent:

```
#include <hpx/task_group.hpp>

// Declare a task group
hpx::experimental::task_group tg;

// Run the tasks
tg.run(task1);
tg.run(task2);

// Wait for the task group
tg.wait();
```

HPX drew inspiration from Intel Threading Building Blocks (TBB) to introduce the `hpx::experimental::task_group` feature. Therefore, utilizing `hpx::experimental::task_group` provides an equivalent functionality to `tbb::task_group`.

MPI

MPI is a standardized communication protocol and library that allows multiple processes or nodes in a parallel computing system to exchange data and coordinate their execution.

List of MPI-HPX functions

MPI function	HPX equivalent
<i>MPI_Allgather</i>	<code>hpx::collectives::all_gather</code>
<i>MPI_Allreduce</i>	<code>hpx::collectives::all_reduce</code>
<i>MPI_Alltoall</i>	<code>hpx::collectives::all_to_all</code>
<i>MPI_Barrier</i>	<code>hpx::distributed::barrier</code>
<i>MPI_Bcast</i>	<code>hpx::collectives::broadcast_to()</code> and <code>hpx::collectives::broadcast_from()</code> used with <code>get()</code>
<i>MPI_Comm_size</i>	<code>hpx::get_num_localities</code>
<i>MPI_Comm_rank</i>	<code>hpx::get_locality_id()</code>
<i>MPI_Exscan</i>	<code>hpx::collectives::exclusive_scan()</code> used with <code>get()</code>
<i>MPI_Gather</i>	<code>hpx::collectives::gather_here()</code> and <code>hpx::collectives::gather_there()</code> used with <code>get()</code>
<i>MPI_Irecv</i>	<code>hpx::collectives::get()</code>
<i>MPI_Isend</i>	<code>hpx::collectives::set()</code>
<i>MPI_Reduce</i>	<code>hpx::collectives::reduce_here</code> and <code>hpx::collectives::reduce_there</code> used with <code>get()</code>
<i>MPI_Scan</i>	<code>hpx::collectives::inclusive_scan()</code> used with <code>get()</code>
<i>MPI_Scatter</i>	<code>hpx::collectives::scatter_to()</code> and <code>hpx::collectives::scatter_from()</code>
<i>MPI_Wait</i>	<code>hpx::collectives::get()</code> used with a future i.e. <code>setf.get()</code>

MPI_Send & MPI_Recv

Let's assume we have the following simple message passing code where each process sends a message to the next process in a circular manner. The exchanged message is modified and printed to the console.

MPI code:

```
#include <cstdint>
#include <cstdint>
#include <iostream>
#include <mpi.h>
#include <vector>

constexpr int times = 2;

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int this_locality;
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    int next_locality = (this_locality + 1) % num_localities;
    std::vector<int> msg_vec = {0, 1};

    int cnt = 0;
    int msg = msg_vec[this_locality];

    int recv_msg;
    MPI_Request request_send, request_recv;
    MPI_Status status;

    while (cnt < times) {
        cnt += 1;

        MPI_Isend(&msg, 1, MPI_INT, next_locality, cnt, MPI_COMM_WORLD,
                 &request_send);
        MPI_Irecv(&recv_msg, 1, MPI_INT, next_locality, cnt, MPI_COMM_WORLD,
                 &request_recv);

        MPI_Wait(&request_send, &status);
        MPI_Wait(&request_recv, &status);

        std::cout << "Time: " << cnt << ", Locality " << this_locality
                  << " received msg: " << recv_msg << "\n";

        recv_msg += 10;
        msg = recv_msg;
    }

    MPI_Finalize();
}
```

(continues on next page)

(continued from previous page)

```
return 0;
}
```

HPX equivalent:

```
#include <hpx/config.hpp>

#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/algorithm.hpp>
#include <hpx/hpx_init.hpp>
#include <hpx/modules/collectives.hpp>

#include <cstdint>
#include <cstdlib>
#include <iostream>
#include <utility>
#include <vector>

using namespace hpx::collectives;

constexpr char const* channel_communicator_name =
    "/example/channel_communicator/";

// the number of times
constexpr int times = 2;

int hpx_main()
{
    std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
    std::uint32_t this_locality = hpx::get_locality_id();

    // allocate channel communicator
    // NOTE: The communicator object must be kept alive until all
    // participating sites have successfully connected. Destroying it
    // prematurely may cause other sites to hang. Consider using a barrier
    // after creation if the communicator would otherwise go out of scope.
    auto comm = create_channel_communicator(hpx::launch::sync,
        channel_communicator_name, num_sites_arg(num_localities),
        this_site_arg(this_locality));

    std::uint32_t next_locality = (this_locality + 1) % num_localities;
    std::vector<int> msg_vec = {0, 1};

    int cnt = 0;
    int msg = msg_vec[this_locality];

    // send values to another locality
    auto setf = set(comm, that_site_arg(next_locality), msg, tag_arg(cnt));
    auto got_msg = get<int>(comm, that_site_arg(next_locality), tag_arg(cnt));

    setf.get();
}
```

(continues on next page)

(continued from previous page)

```

while (cnt < times)
{
    cnt += 1;

    auto done_msg = got_msg.then([&](auto&& f) {
        int rec_msg = f.get();
        std::cout << "Time: " << cnt << ", Locality " << this_locality
                    << " received msg: " << rec_msg << "\n";

        // change msg by adding 10
        rec_msg += 10;

        // start next round
        setf =
            set(comm, that_site_arg(next_locality), rec_msg, tag_arg(cnt));
        got_msg =
            get<int>(comm, that_site_arg(next_locality), tag_arg(cnt));
        setf.get();
    });

    done_msg.get();
}

return hpx::finalize();
}
#endif

int main(int argc, char* argv[])
{
#ifdef HPX_COMPUTE_DEVICE_CODE
    hpx::init_params params;
    params.cfg = {"--hpx:run-hpx-main"};
    return hpx::init(argc, argv, params);
#else
    (void) argc;
    (void) argv;
    return 0;
#endif
}

```

To perform message passing between different processes in *HPX* we can use a channel communicator. To understand this example, let's focus on the *hpx_main()* function:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- *create_channel_communicator* function is used to create a channel to serve the communication. This function takes several arguments, including the launch policy (*hpx::launch::sync*), the name of the communicator (*channel_communicator_name*), the number of localities, and the ID of the current locality.
- The communication follows a ring pattern, where each process (or locality) sends a message to its neighbor in a circular manner. This means that the messages circulate around the localities, ensuring that the communication wraps around when reaching the end of the locality sequence. To achieve this, the *next_locality* variable is calculated as the ID of the next locality in the ring.

- The initial values for the communication are set (*msg_vec*, *cnt*, *msg*).
- The *set()* function is called to send the message to the next locality in the ring. The message is sent asynchronously and is associated with a tag (*cnt*).
- The *get()* function is called to receive a message from the next locality. It is also associated with the same tag as the *set()* operation.
- The *setf.get()* call blocks until the message sending operation is complete.
- A continuation is set up using the function *then()* to handle the received message. Inside the continuation:
 - The received message value (*rec_msg*) is retrieved using *f.get()*.
 - The received message is printed to the console and then modified by adding 10.
 - The *set()* and *get()* operations are repeated to send and receive the modified message to the next locality.
 - The *setf.get()* call blocks until the new message sending operation is complete.
- The *done_msg.get()* call blocks until the continuation is complete for the current loop iteration.

Having said that, we conclude to the following table:

MPI_Gather

The following code gathers data from all processes to the root process and verifies the gathered data in the root process.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities, this_locality;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    std::vector<int> local_data; // Data to be gathered

    if (this_locality == 0) {
        local_data.resize(num_localities); // Resize the vector on the root process
    }

    // Each process calculates its local data value
    int my_data = 42 + this_locality;

    for (std::uint32_t i = 0; i != 10; ++i) {

        // Gather data from all processes to the root process (process 0)
        MPI_Gather(&my_data, 1, MPI_INT, local_data.data(), 1, MPI_INT, 0,
                  MPI_COMM_WORLD);

        // Only the root process (process 0) will print the gathered data
```

(continues on next page)

(continued from previous page)

```

    if (this_locality == 0) {
        std::cout << "Gathered data on the root: ";
        for (int i = 0; i < num_localities; ++i) {
            std::cout << local_data[i] << " ";
        }
        std::cout << std::endl;
    }
    std::cout << std::endl;

    MPI_Finalize();
    return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

// test functionality based on immediate local result value
auto gather_direct_client = create_communicator(gather_direct_basename,
    num_sites_arg(num_localities), this_site_arg(this_locality));

for (std::uint32_t i = 0; i != 10; ++i)
{
    if (this_locality == 0)
    {
        hpx::future<std::vector<std::uint32_t>> overall_result =
            gather_here(gather_direct_client, std::uint32_t(42));

        std::vector<std::uint32_t> sol = overall_result.get();
        std::cout << "Gathered data on the root:";

        for (std::size_t j = 0; j != sol.size(); ++j)
        {
            HPX_TEST(j + 42 == sol[j]);
            std::cout << " " << sol[j];
        }
        std::cout << std::endl;
    }
    else
    {
        hpx::future<void> overall_result =
            gather_there(gather_direct_client, this_locality + 42);
        overall_result.get();
    }
}

```

This code will print 10 times the following message:

```
Gathered data on the root: 42 43
```

HPX uses two functions to implement the functionality of *MPI_Gather*: *gather_here* and *gather_there*. *gather_here* is gathering data from all localities to the locality with ID 0 (root locality). *gather_there* allows non-root localities to participate in the gather operation by sending data to the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *gather_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The *gather_here* function is used to perform the gather operation. It collects data from all other localities into the *overall_result* future object. The function arguments provide the necessary information, such as the base name for the gather operation (*gather_direct_basename*), the value to be gathered (*value*), the number of localities (*num_localities*), the current locality ID (*this_locality*), and the generation number (related to the gather operation).
 - The *get()* member function of the *overall_result* future is used to retrieve the gathered data.
 - The next *for* loop is used to verify the correctness of the gathered data (*sol*). *HPX_TEST* is a macro provided by the HPX testing utilities to perform similar testing with the Standard C++ macro *assert*.
- If the current locality is not the root:
 - The *gather_there* function is used to participate in the gather operation initiated by the root locality. It sends the data (in this case, the value *this_locality + 42*) to the root locality, indicating that it should be included in the gathering.
 - The *get()* member function of the *overall_result* future is used to wait for the gather operation to complete for this locality.

MPI_Scatter

The following code gathers data from all processes to the root process and verifies the gathered data in the root process.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities, this_locality;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    int num_localities = num_localities;
    std::vector<int> data(num_localities);

    if (this_locality == 0) {
        // Fill the data vector on the root locality (locality 0)
        for (int i = 0; i < num_localities; ++i) {
            data[i] = 42 + i;
        }
    }
}
```

(continues on next page)

(continued from previous page)

```

    int local_data; // Variable to store the received data

    // Scatter data from the root locality to all other localities
    MPI_Scatter(&data[0], 1, MPI_INT, &local_data, 1, MPI_INT, 0, MPI_COMM_WORLD);

    // Now, each locality has its own local_data

    // Print the local_data on each locality
    std::cout << "Locality " << this_locality << " received " << local_data
                << std::endl;

    MPI_Finalize();
    return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
HPX_TEST_LTE(std::uint32_t(2), num_localities);

std::uint32_t this_locality = hpx::get_locality_id();

auto scatter_direct_client =
    hpx::collectives::create_communicator(scatter_direct_basename,
        num_sites_arg(num_localities), this_site_arg(this_locality));

// test functionality based on immediate local result value
for (std::uint32_t i = 0; i != 10; ++i)
{
    if (this_locality == 0)
    {
        std::vector<std::uint32_t> data(num_localities);
        std::iota(data.begin(), data.end(), 42 + i);

        hpx::future<std::uint32_t> result =
            scatter_to(scatter_direct_client, std::move(data));

        HPX_TEST_EQ(i + 42 + this_locality, result.get());
    }
    else
    {
        hpx::future<std::uint32_t> result =
            scatter_from<std::uint32_t>(scatter_direct_client);

        HPX_TEST_EQ(i + 42 + this_locality, result.get());

        std::cout << "Locality " << this_locality << " received "
                    << i + 42 + this_locality << std::endl;
    }
}

```

For num_localities = 2 and since we run for 10 iterations this code will print the following message:

```

Locality 1 received 43
Locality 1 received 44
Locality 1 received 45
Locality 1 received 46
Locality 1 received 47
Locality 1 received 48
Locality 1 received 49
Locality 1 received 50
Locality 1 received 51
Locality 1 received 52

```

HPX uses two functions to implement the functionality of *MPI_Scatter*: *hpx::scatter_to* and *hpx::scatter_from*. *hpx::scatter_to* is distributing the data from the locality with ID 0 (root locality) to all other localities. *hpx::scatter_from* allows non-root localities to receive the data from the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *hpx::collectives::create_communicator()* is used to create a communicator called *scatter_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The data vector is filled with values ranging from $42 + i$ to $42 + i + \text{num_localities} - 1$.
 - The *hpx::scatter_to* function is used to perform the scatter operation using the communicator *scatter_direct_client*. This scatters the data vector to other localities and returns a future representing the result.
 - *HPX_TEST_EQ* is a macro provided by the HPX testing utilities to test the distributed values.
- If the current locality is not the root:
 - The *hpx::scatter_from* function is used to collect the data by the root locality.
 - *HPX_TEST_EQ* is a macro provided by the HPX testing utilities to test the collected values.

MPI_Allgather

The following code gathers data from all processes and sends the data to all processes.

MPI code:

```

#include <cstdint>
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes
    int num_localities = size;

```

(continues on next page)

(continued from previous page)

```

// Get the MPI process rank
int here = rank;

std::uint32_t value = here;

std::vector<std::uint32_t> r(num_localities);

// Perform an all-gather operation to gather values from all processes.
MPI_Allgather(&value, 1, MPI_UINT32_T, r.data(), 1, MPI_UINT32_T,
              MPI_COMM_WORLD);

// Print the result.
std::cout << "Locality " << here << " has values:";
for (size_t j = 0; j < r.size(); ++j) {
    std::cout << " " << r[j];
}
std::cout << std::endl;

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

// test functionality based on immediate local result value
auto all_gather_direct_client =
    create_communicator(all_gather_direct_basename,
                        num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::vector<std::uint32_t>> overall_result =
    all_gather(all_gather_direct_client, value);

std::vector<std::uint32_t> r = overall_result.get();

std::cout << "Locality " << here << " has values:";
for (std::size_t j = 0; j != r.size(); ++j)
{
    std::cout << " " << j;
}
std::cout << std::endl;

```

For num_localities = 2 this code will print the following message:

```

Locality 0 has values: 0 1
Locality 1 has values: 0 1

```

HPX uses the function `all_gather` to implement the functionality of `MPI_Allgather`. In more detail:

- `hpx::get_num_localities(hpx::launch::sync)` retrieves the number of localities, while `hpx::get_locality_id()` re-

turns the ID of the current locality.

- The function `hpx::collectives::create_communicator()` is used to create a communicator called `all_gather_direct_client`.
- The values that the localities exchange with each other are equal to each locality's ID.
- The gather operation is performed using `all_gather`. The result is stored in an `hpx::future` object called `over_all_result`, which represents a future result that can be retrieved later when needed.
- The `get()` function waits until the result is available and then stores it in the vector called `r`.

MPI_Allreduce

The following code combines values from all processes and distributes the result back to all processes.

MPI code:

```
#include <cstdint>
#include <iostream>
#include <mpi.h>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes
    int num_localities = size;

    // Get the MPI process rank
    int here = rank;

    // Create a communicator for the all reduce operation.
    MPI_Comm all_reduce_direct_client;
    MPI_Comm_split(MPI_COMM_WORLD, 0, rank, &all_reduce_direct_client);

    // Perform the all reduce operation to calculate the sum of 'here' values.
    std::uint32_t value = here;
    std::uint32_t res = 0;
    MPI_Allreduce(&value, &res, 1, MPI_UINT32_T, MPI_SUM,
                  all_reduce_direct_client);

    std::cout << "Locality " << rank << " has value: " << res << std::endl;

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t const num_localities =
    hpx::get_num_localities(hpx::launch::sync);
```

(continues on next page)

(continued from previous page)

```

std::uint32_t const here = hpx::get_locality_id();

auto const all_reduce_direct_client =
    create_communicator(all_reduce_direct_basename,
        num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result =
    all_reduce(all_reduce_direct_client, value, std::plus<std::uint32_t>{});

std::uint32_t res = overall_result.get();
std::cout << "Locality " << here << " has value: " << res << std::endl;

```

For num_localities = 2 this code will print the following message:

```

Locality 0 has value: 1
Locality 1 has value: 1

```

HPX uses the function *all_reduce* to implement the functionality of *MPI_Allreduce*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *hpx::collectives::create_communicator()* is used to create a communicator called *all_reduce_direct_client*.
- The value of each locality is equal to its ID.
- The reduce operation is performed using *all_reduce*. The result is stored in an *hpx::future* object called *overall_result*, which represents a future result that can be retrieved later when needed.
- The *get()* function waits until the result is available and then stores it in the variable *res*.

MPI_Alltoall

The following code gathers data from and scatters data to all processes.

MPI code:

```

#include <algorithm>
#include <cstdint>
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes

```

(continues on next page)

(continued from previous page)

```

int num_localities = size;

// Get the MPI process rank
int this_locality = rank;

// Create a communicator for all-to-all operation.
MPI_Comm all_to_all_direct_client;
MPI_Comm_split(MPI_COMM_WORLD, 0, rank, &all_to_all_direct_client);

std::vector<std::uint32_t> values(num_localities);
std::fill(values.begin(), values.end(), this_locality);

// Create vectors to store received values.
std::vector<std::uint32_t> r(num_localities);

// Perform an all-to-all operation to exchange values with other localities.
MPI_Alltoall(values.data(), 1, MPI_UINT32_T, r.data(), 1, MPI_UINT32_T,
             all_to_all_direct_client);

// Print the results.
std::cout << "Locality " << this_locality << " has values:";
for (std::size_t j = 0; j != r.size(); ++j) {
    std::cout << " " << r[j];
}
std::cout << std::endl;

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

auto all_to_all_direct_client =
    create_communicator(all_to_all_direct_basename,
                        num_sites_arg(num_localities), this_site_arg(this_locality));

std::vector<std::uint32_t> values(num_localities);
std::fill(values.begin(), values.end(), this_locality);

hpx::future<std::vector<std::uint32_t>> overall_result =
    all_to_all(all_to_all_direct_client, std::move(values));

std::vector<std::uint32_t> r = overall_result.get();
std::cout << "Locality " << this_locality << " has values:";

for (std::size_t j = 0; j != r.size(); ++j)
{
    std::cout << " " << r[j];
}

```

(continues on next page)

(continued from previous page)

```
std::cout << std::endl;
```

For `num_localities = 2` this code will print the following message:

```
Locality 0 has values: 0 1
Locality 1 has values: 0 1
```

HPX uses the function *all_to_all* to implement the functionality of *MPI_Alltoall*. In more detail:

- `hpx::get_num_localities(hpx::launch::sync)` retrieves the number of localities, while `hpx::get_locality_id()` returns the ID of the current locality.
- The function `hpx::collectives::create_communicator()` is used to create a communicator called *all_to_all_direct_client*.
- The value each locality sends is equal to its ID.
- The all-to-all operation is performed using *all_to_all*. The result is stored in an `hpx::future` object called *overall_result*, which represents a future result that can be retrieved later when needed.
- The `get()` function waits until the result is available and then stores it in the variable *r*.

MPI_Barrier

The following code shows how barrier is used to synchronize multiple processes.

MPI code:

```
#include <cstdlib>
#include <iostream>
#include <mpi.h>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    std::size_t iterations = 5;

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    for (std::size_t i = 0; i != iterations; ++i) {
        MPI_Barrier(MPI_COMM_WORLD);
        if (rank == 0) {
            std::cout << "Iteration " << i << " completed." << std::endl;
        }
    }

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::size_t iterations = 5;
std::uint32_t this_locality = hpx::get_locality_id();

char const* const barrier_test_name = "/test/barrier/multiple";

hpx::distributed::barrier b(barrier_test_name);
for (std::size_t i = 0; i != iterations; ++i)
{
    b.wait();
    if (this_locality == 0)
    {
        std::cout << "Iteration " << i << " completed." << std::endl;
    }
}
```

This code will print the following message:

```
Iteration 0 completed.
Iteration 1 completed.
Iteration 2 completed.
Iteration 3 completed.
Iteration 4 completed.
```

HPX uses the function *barrier* to implement the functionality of *MPI_Barrier*. In more detail:

- After defining the number of iterations, we use *hpx::get_locality_id()* to get the ID of the current locality.
- *char const* const barrier_test_name = "/test/barrier/multiple"*: This line defines a constant character array as the name of the barrier. This name is used to identify the barrier across different localities. All participating threads that use this name will synchronize at this barrier.
- Using *hpx::distributed::barrier b(barrier_test_name)*, we create an instance of the distributed barrier with the previously defined name. This barrier will be used to synchronize the execution of threads across different localities.
- Running for all the desired iterations, we use *b.wait()* to synchronize the threads. Each thread waits until all other threads also reach this point before any of them can proceed further.

MPI_Bcast

The following code broadcasts data from one process to all other processes.

MPI code:

```
#include <iostream>
#include <mpi.h>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
```

(continues on next page)

(continued from previous page)

```

MPI_Comm_rank(MPI_COMM_WORLD, &here);

int value;

for (int i = 0; i < 5; ++i) {
    if (here == 0) {
        value = i + 42;
    }

    // Broadcast the value from process 0 to all other processes
    MPI_Bcast(&value, 1, MPI_INT, 0, MPI_COMM_WORLD);

    if (here != 0) {
        std::cout << "Locality " << here << " received " << value << std::endl;
    }
}

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);

std::uint32_t here = hpx::get_locality_id();

auto broadcast_direct_client =
    create_communicator(broadcast_direct_basename,
        num_sites_arg(num_localities), this_site_arg(here));

// test functionality based on immediate local result value
for (std::uint32_t i = 0; i != 5; ++i)
{
    if (here == 0)
    {
        hpx::future<std::uint32_t> result =
            broadcast_to(broadcast_direct_client, i + 42);

        result.get();
    }
    else
    {
        hpx::future<std::uint32_t> result =
            hpx::collectives::broadcast_from<std::uint32_t>(
                broadcast_direct_client);

        uint32_t r = result.get();

        std::cout << "Locality " << here << " received " << r << std::endl;
    }
}

```

(continues on next page)

(continued from previous page)

}

For `num_localities = 2` this code will print the following message:

```
Locality 1 received 42
Locality 1 received 43
Locality 1 received 44
Locality 1 received 45
Locality 1 received 46
```

HPX uses two functions to implement the functionality of *MPI_Bcast*: *broadcast_to* and *broadcast_from*. *broadcast_to* is broadcasting the data from the root locality to all other localities. *broadcast_from* allows non-root localities to collect the data sent by the root locality. In more detail:

- `hpx::get_num_localities(hpx::launch::sync)` retrieves the number of localities, while `hpx::get_locality_id()` returns the ID of the current locality.
- The function `create_communicator()` is used to create a communicator called *broadcast_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The *broadcast_to* function is used to perform the broadcast operation using the communicator *broadcast_direct_client*. This sends the data to other localities and returns a future representing the result.
 - The `get()` member function of the *result* future is used to wait for and retrieve the result.
- If the current locality is not the root:
 - The *broadcast_from* function is used to collect the data by the root locality.
 - The `get()` member function of the *result* future is used to wait for the result.

MPI_Exscan

The following code computes the exclusive scan (partial reductions) of data on a collection of processes.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
    MPI_Comm_rank(MPI_COMM_WORLD, &here);

    // Calculate the value for this locality (here)
    int value = here;

    // Perform an exclusive scan
```

(continues on next page)

(continued from previous page)

```

std::vector<int> result(num_localities);
MPI_Exscan(&value, &result[0], 1, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

if (here != 0) {
    int r = result[here - 1]; // Result is in the previous rank's slot

    std::cout << "Locality " << here << " has value " << r << std::endl;
}

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

auto exclusive_scan_client = create_communicator(exclusive_scan_basename,
    num_sites_arg(num_localities), this_site_arg(here));

// test functionality based on immediate local result value
std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result = exclusive_scan(
    exclusive_scan_client, value, std::plus<std::uint32_t>{});

uint32_t r = overall_result.get();

if (here != 0)
{
    std::cout << "Locality " << here << " has value " << r << std::endl;
}

```

For num_localities = 2 this code will print the following message:

```
Locality 1 has value 0
```

HPX uses the function *exclusive_scan* to implement *MPI_Exscan*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *exclusive_scan_client*.
- The *exclusive_scan* function is used to perform the exclusive scan operation using the communicator *exclusive_scan_client*. *std::plus<std::uint32_t>{}* specifies the binary associative operator to use for the scan. In this case, it's addition for summing values.
- The *get()* member function of the *overall_result* future is used to wait for the result.

MPI_Scan

The following code Computes the inclusive scan (partial reductions) of data on a collection of processes.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
    MPI_Comm_rank(MPI_COMM_WORLD, &here);

    // Calculate the value for this locality (here)
    int value = here;

    std::vector<int> result(num_localities);

    MPI_Scan(&value, &result[0], 1, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

    std::cout << "Locality " << here << " has value " << result[0] << std::endl;

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

auto inclusive_scan_client = create_communicator(inclusive_scan_basename,
    num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result = inclusive_scan(
    inclusive_scan_client, value, std::plus<std::uint32_t>{});

uint32_t r = overall_result.get();

std::cout << "Locality " << here << " has value " << r << std::endl;
```

For num_localities = 2 this code will print the following message:

```
Locality 0 has value 0
Locality 1 has value 1
```

HPX uses the function *inclusive_scan* to implement *MPI_Scan*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *inclusive_scan_client*.
- The *inclusive_scan* function is used to perform the exclusive scan operation using the communicator *inclusive_scan_client*. *std::plus<std::uint32_t>{}* specifies the binary associative operator to use for the scan. In this case, it's addition for summing values.
- The *get()* member function of the *overall_result* future is used to wait for the result.

MPI_Reduce

The following code performs a global reduce operation across all processes.

MPI code:

```
#include <iostream>
#include <mpi.h>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_processes;
    MPI_Comm_size(MPI_COMM_WORLD, &num_processes);

    int this_rank;
    MPI_Comm_rank(MPI_COMM_WORLD, &this_rank);

    int value = this_rank;

    int result = 0;

    // Perform the reduction operation
    MPI_Reduce(&value, &result, 1, MPI_INT, MPI_SUM, 0, MPI_COMM_WORLD);

    // Print the result for the root process (process 0)
    if (this_rank == 0) {
        std::cout << "Locality " << this_rank << " has value " << result
                  << std::endl;
    }

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

auto reduce_direct_client = create_communicator(reduce_direct_basename,
        num_sites_arg(num_localities), this_site_arg(this_locality));
```

(continues on next page)

(continued from previous page)

```

std::uint32_t value = hpx::get_locality_id();

if (this_locality == 0)
{
    hpx::future<std::uint32_t> overall_result = reduce_here(
        reduce_direct_client, value, std::plus<std::uint32_t>{});

    uint32_t r = overall_result.get();

    std::cout << "Locality " << this_locality << " has value " << r
        << std::endl;
}
else
{
    hpx::future<void> overall_result =
        reduce_there(reduce_direct_client, std::move(value));
    overall_result.get();
}

```

This code will print the following message:

```
Locality 0 has value 1
```

HPX uses two functions to implement the functionality of *MPI_Reduce*: *reduce_here* and *reduce_there*. *reduce_here* is gathering data from all localities to the locality with ID 0 (root locality) and then performs the defined reduction operation. *reduce_there* allows non-root localities to participate in the reduction operation by sending data to the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *reduce_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The *reduce_here* function initiates a reduction operation with addition (*std::plus*) as the reduction operator. The result is stored in *overall_result*.
 - The *get()* member function of the *overall_result* future is used to wait for the result.
- If the current locality is not the root:
 - The *reduce_there* initiates a remote reduction operation.
 - The *get()* member function of the *overall_result* future is used to wait for the remote reduction operation to complete. This is done to ensure synchronization among localities.

2.4.7 Building tests and examples

Tests

To build the tests:

```
$ cmake --build . --target tests
```

To control which tests to run use `ctest`:

- To run single tests, for example a test for `for_loop`:

```
$ ctest --output-on-failure -R tests.unit.modules.algorithms.algorithms.for_loop
```

- To run a whole group of tests:

```
$ ctest --output-on-failure -R tests.unit
```

Examples

- To build (and install) all examples invoke:

```
$ cmake -DHPX_WITH_EXAMPLES=On .
$ make examples
$ make install
```

- To build the `hello_world_1` example run:

```
$ make hello_world_1
```

HPX executables end up in the `bin` directory in your build directory. You can now run `hello_world_1` and should see the following output:

```
$ ./bin/hello_world_1
Hello World!
```

You've just run an example which prints `Hello World!` from the *HPX* runtime. The source for the example is in `examples/quickstart/hello_world_1.cpp`. The `hello_world_distributed` example (also available in the `examples/quickstart` directory) is a distributed hello world program, which is described in *Remote execution with actions*. It provides a gentle introduction to the distributed aspects of *HPX*.

Tip: Most build targets in *HPX* have two names: a simple name and a hierarchical name corresponding to what type of example or test the target is. If you are developing *HPX* it is often helpful to run `make help` to get a list of available targets. For example, `make help | grep hello_world` outputs the following:

```
... examples.quickstart.hello_world_2
... hello_world_2
... examples.quickstart.hello_world_1
... hello_world_1
... examples.quickstart.hello_world_distributed
... hello_world_distributed
```

It is also possible to build, for instance, all quickstart examples using `make examples.quickstart`.

2.4.8 Creating *HPX* projects

Using *HPX* with pkg-config

How to build *HPX* applications with pkg-config

After you are done installing *HPX*, you should be able to build the following program. It prints `Hello World!` on the *locality* you run it on.

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Copy the text of this program into a file called `hello_world.cpp`.

Now, in the directory where you put `hello_world.cpp`, issue the following commands (where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used while building *HPX*):

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig
$ c++ -o hello_world hello_world.cpp \
    `pkg-config --cflags --libs hpx_application` \
    -lhpx_iostreams -DHPX_APPLICATION_NAME=hello_world
```

Important: When using `pkg-config` with *HPX*, the `pkg-config` flags must go after the `-o` flag.

Note: *HPX* libraries have different names in debug and release mode. If you want to link against a debug *HPX* library, you need to use the `_debug` suffix for the `pkg-config` name. That means instead of `hpx_application` or `hpx_component`, you will have to use `hpx_application_debug` or `hpx_component_debug`. Moreover, all referenced *HPX* components need to have an appended `d` suffix. For example, instead of `-lhpx_iostreams` you will need to specify `-lhpx_iostreamsd`.

Important: If the *HPX* libraries are in a path that is not found by the dynamic linker, you will need to add the path `$HPX_LOCATION/lib` to your linker search path (for example `LD_LIBRARY_PATH` on Linux).

To test the program, type:

```
$ ./hello_world
```

which should print `Hello World!` and exit.

How to build HPX components with pkg-config

Let's try a more complex example involving an *HPX* component. An *HPX* component is a class that exposes *HPX* actions. *HPX* components are compiled into dynamically loaded modules called component libraries. Here's the source code:

hello_world_component.cpp

```
#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/iostream.hpp>
#include "hello_world_component.hpp"

#include <iostream>

namespace examples { namespace server {
    void hello_world::invoke()
    {
        hpx::cout << "Hello HPX World!" << std::endl;
    }
}} // namespace examples::server

HPX_REGISTER_COMPONENT_MODULE()

typedef hpx::components::component<examples::server::hello_world>
    hello_world_type;

HPX_REGISTER_COMPONENT(hello_world_type, hello_world)

HPX_REGISTER_ACTION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)
#endif
```

hello_world_component.hpp

```
#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/actions.hpp>
#include <hpx/include/components.hpp>
#include <hpx/include/lcos.hpp>
#include <hpx/serialization.hpp>

#include <utility>

namespace examples { namespace server {
    struct HPX_COMPONENT_EXPORT hello_world
        : hpx::components::component_base<hello_world>
    {
        void invoke();
        HPX_DEFINE_COMPONENT_ACTION(hello_world, invoke)
    };
}
```

(continues on next page)

(continued from previous page)

```

}}    // namespace examples::server

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)

namespace examples {
    struct hello_world
    : hpx::components::client_base<hello_world, server::hello_world>
    {
        typedef hpx::components::client_base<hello_world, server::hello_world>
            base_type;

        hello_world(hpx::future<hpx::id_type>&& f)
            : base_type(std::move(f))
        {
        }

        hello_world(hpx::id_type&& f)
            : base_type(std::move(f))
        {
        }

        void invoke()
        {
            hpx::async<server::hello_world::invoke_action>(this->get_id())
                .get();
        }
    };
}    // namespace examples

#endif

```

hello_world_client.cpp

```

#include <hpx/config.hpp>
#if defined(HPX_COMPUTE_HOST_CODE)
#include <hpx/wrap_main.hpp>

#include "hello_world_component.hpp"

int main()
{
    {
        // Create a single instance of the component on this locality.
        examples::hello_world client =
            hpx::new_<examples::hello_world>(hpx::find_here());

        // Invoke the component's action, which will print "Hello World!".
        client.invoke();
    }

    return 0;
}

```

(continues on next page)

(continued from previous page)

```
}
#endif
```

Copy the three source files above into three files (called `hello_world_component.cpp`, `hello_world_component.hpp` and `hello_world_client.cpp`, respectively).

Now, in the directory where you put the files, run the following command to build the component library. (where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used while building *HPX*):

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig
$ c++ -o libhpx_hello_world.so hello_world_component.cpp \
  `pkg-config --cflags --libs hpx_component` \
  -lhpx_iostreams -DHPX_COMPONENT_NAME=hpx_hello_world
```

Now pick a directory in which to install your *HPX* component libraries. For this example, we'll choose a directory named `my_hpx_libs`:

```
$ mkdir ~/my_hpx_libs
$ mv libhpx_hello_world.so ~/my_hpx_libs
```

Note: *HPX* libraries have different names in debug and release mode. If you want to link against a debug *HPX* library, you need to use the `_debug` suffix for the `pkg-config` name. That means instead of `hpx_application` or `hpx_component` you will have to use `hpx_application_debug` or `hpx_component_debug`. Moreover, all referenced *HPX* components need to have a appended `d` suffix, e.g. instead of `-lhpx_iostreams` you will need to specify `-lhpx_iostreamsd`.

Important: If the *HPX* libraries are in a path that is not found by the dynamic linker. You need to add the path `$HPX_LOCATION/lib` to your linker search path (for example `LD_LIBRARY_PATH` on Linux).

Now, to build the application that uses this component (`hello_world_client.cpp`), we do:

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig
$ c++ -o hello_world_client hello_world_client.cpp \
  `pkg-config --cflags --libs hpx_application` \
  -L${HOME}/my_hpx_libs -lhpx_hello_world -lhpx_iostreams
```

Important: When using `pkg-config` with *HPX*, the `pkg-config` flags must go after the `-o` flag.

Finally, you'll need to set your `LD_LIBRARY_PATH` before you can run the program. To run the program, type:

```
$ export LD_LIBRARY_PATH="$LD_LIBRARY_PATH:$HOME/my_hpx_libs"
$ ./hello_world_client
```

which should print `Hello HPX World!` and exit.

Using HPX with CMake-based projects

In addition to the pkg-config support discussed on the previous pages, *HPX* comes with full CMake support. In order to integrate *HPX* into existing or new CMakeLists.txt, you can leverage the `find_package`⁶⁴ command integrated into CMake. Following, is a Hello World component example using CMake.

Let's revisit what we have. We have three files that compose our example application:

- `hello_world_component.hpp`
- `hello_world_component.cpp`
- `hello_world_client.hpp`

The basic structure to include *HPX* into your CMakeLists.txt is shown here:

```
# Require a recent version of cmake
cmake_minimum_required(VERSION 3.18 FATAL_ERROR)

# This project is C++ based.
project(your_app CXX)

# Instruct cmake to find the HPX settings
find_package(HPX)
```

In order to have CMake find *HPX*, it needs to be told where to look for the `HPXConfig.cmake` file that is generated when *HPX* is built or installed. It is used by `find_package(HPX)` to set up all the necessary macros needed to use *HPX* in your project. The ways to achieve this are:

- Set the `HPX_DIR` CMake variable to point to the directory containing the `HPXConfig.cmake` script on the command line when you invoke CMake:

```
$ cmake -DHPX_DIR=$HPX_LOCATION/lib/cmake/HPX ...
```

where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used when building/configuring *HPX*.

- Set the `CMAKE_PREFIX_PATH` variable to the root directory of your *HPX* build or install location on the command line when you invoke CMake:

```
$ cmake -DCMAKE_PREFIX_PATH=$HPX_LOCATION ...
```

The difference between `CMAKE_PREFIX_PATH` and `HPX_DIR` is that CMake will add common postfixes, such as `lib/cmake/<project`, to the `CMAKE_PREFIX_PATH` and search in these locations too. Note that if your project uses *HPX* as well as other CMake-managed projects, the paths to the locations of these multiple projects may be concatenated in the `CMAKE_PREFIX_PATH`.

- The variables above may be set in the CMake GUI or curses `ccmake` interface instead of the command line.

Additionally, if you wish to require *HPX* for your project, replace the `find_package(HPX)` line with `find_package(HPX REQUIRED)`.

You can check if *HPX* was successfully found with the `HPX_FOUND` CMake variable.

⁶⁴ https://www.cmake.org/cmake/help/latest/command/find_package.html

Using CMake targets

The recommended way of setting up your targets to use *HPX* is to link to the `HPX::hpx CMake65` target:

```
target_link_libraries(hello_world_component PUBLIC HPX::hpx)
```

This requires that you have already created the target like this:

```
add_library(hello_world_component SHARED hello_world_component.cpp)
target_include_directories(hello_world_component PUBLIC ${CMAKE_CURRENT_SOURCE_DIR})
```

When you link your library to the `HPX::hpx CMake66` target, you will be able use *HPX* functionality in your library. To use `main()` as the implicit entry point in your application you must additionally link your application to the CMake target `HPX::wrap_main`. This target is automatically linked to executables if you are using the macros described below (*Using macros to create new targets*). See *Re-use the `main()` function as the main *HPX* entry point* for more information on implicitly using `main()` as the entry point. If you want the same wrapping behavior without including `hpx/hpx_main.hpp67`, link to the `HPX::auto_wrap_main` target instead. This enables the runtime initialization around `main()` unconditionally and is useful for codebases where adding the header to `main.cpp` is impractical

Note: The use of `HPX::auto_wrap_main` is not supported when using the native Windows MSVC toolchain.

If you want to use the facilities exposed by `hpx::runtime_manager` in binaries that were not linked as executables (e.g., in shared libraries), you will need make your cmake target explicitly depend on the `HPX::init` target:

```
add_library(hello_world_component SHARED hello_world_component.cpp)
target_link_libraries(hello_world_component PRIVATE HPX::init)
```

Otherwise you may see compilation errors complaining about the header file `hpx/runtime_manager.hpp` not being found.

Creating a component requires setting two additional compile definitions:

```
target_compile_options(hello_world_component
    HPX_COMPONENT_NAME=hello_world
    HPX_COMPONENT_EXPORTS)
```

Instead of setting these definitions manually you may link to the `HPX::component` target, which sets `HPX_COMPONENT_NAME` to `hpx_<target_name>`, where `<target_name>` is the target name of your library. Note that these definitions should be `PRIVATE` to make sure these definitions are not propagated transitively to dependent targets.

In addition to making your library a component you can make it a plugin. To do so link to the `HPX::plugin` target. Similarly to `HPX::component` this will set `HPX_PLUGIN_NAME` to `hpx_<target_name>`. This definition should also be `PRIVATE`. Unlike regular shared libraries, plugins are loaded at runtime from certain directories and will not be found without additional configuration. Plugins should be installed into a directory containing only plugins. For example, the plugins created by *HPX* itself are installed into the `hpx` subdirectory in the library install directory (typically `lib` or `lib64`). When using the `HPX::plugin` target you need to install your plugins into an appropriate directory. You may also want to set the location of your plugin in the build directory with the `*_OUTPUT_DIRECTORY*` CMake target properties to be able to load the plugins in the build directory. Once you've set the install or output directory of your plugin you need to tell your executable where to find it at runtime. You can do this either by setting the environment variable `HPX_COMPONENT_PATHS` or the ini setting `hpx.component_paths` (see `--hpx:ini`) to the directory containing your plugin.

⁶⁵ <https://www.cmake.org>

⁶⁶ <https://www.cmake.org>

⁶⁷ http://github.com/TheHPXProject/hpx/blob/unknown/wrap/include/hpx/hpx_main.hpp

Using macros to create new targets

In addition to the targets described above, *HPX* provides convenience macros to hide optional boilerplate code that may be useful for your project. The link to the targets described above. We recommend that you use the targets directly whenever possible as they tend to compose better with other targets.

The macro for adding an *HPX* component is `add_hpx_component`. It can be used in your `CMakeLists.txt` file like this:

```
# build your application using HPX
add_hpx_component(hello_world
  SOURCES hello_world_component.cpp
  HEADERS hello_world_component.hpp
  COMPONENT_DEPENDENCIES iostreams)
```

Note: `add_hpx_component` adds a `_component` suffix to the target name. In the example above, a `hello_world_component` target will be created.

The available options to `add_hpx_component` are:

- `SOURCES`: The source files for that component
- `HEADERS`: The header files for that component
- `DEPENDENCIES`: Other libraries or targets this component depends on
- `COMPONENT_DEPENDENCIES`: The components this component depends on
- `PLUGIN`: Treats this component as a plugin-able library
- `COMPILE_FLAGS`: Additional compiler flags
- `LINK_FLAGS`: Additional linker flags
- `FOLDER`: Adds the headers and source files to this Source Group folder
- `EXCLUDE_FROM_ALL`: Do not build this component as part of the `all` target

After adding the component, the way you add the executable is as follows:

```
# build your application using HPX
add_hpx_executable(hello_world
  SOURCES hello_world_client.cpp
  COMPONENT_DEPENDENCIES hello_world)
```

Note: `add_hpx_executable` automatically adds a `_component` suffix to dependencies specified in `COMPONENT_DEPENDENCIES`, meaning you can directly use the name given when adding a component using `add_hpx_component`.

When you configure your application, all you need to do is set the `HPX_DIR` variable to point to the installation of *HPX*.

Note: All library targets built with *HPX* are exported and readily available to be used as arguments to `target_link_libraries`⁶⁸ in your targets. The *HPX* include directories are available with the `HPX_INCLUDE_DIRS` CMake variable.

⁶⁸ https://www.cmake.org/cmake/help/latest/command/target_link_libraries.html

Using the HPX compiler wrapper `hpxcxx`

The `hpxcxx` compiler wrapper helps to compile a *HPX* component, application, or object file, based on the arguments passed to it.

```
$ hpxcxx [--exe=<APPLICATION_NAME> | --comp=<COMPONENT_NAME> | -c] FLAGS FILES
```

The `hpxcxx` command **requires** that either an application or a component is built or `-c` flag is specified. If the build is against a debug build, the `-g` is to be specified while building.

Optional FLAGS

- `-l <LIBRARY>` | `-l<LIBRARY>`: Links `<LIBRARY>` to the build
- `-g`: Specifies that the application or component build is against a debug build
- `-rd`: Sets `release-with-debug-info` option
- `-mr`: Sets `minsize-release` option

All other flags (like `-o OUTPUT_FILE`) are directly passed to the underlying C++ compiler.

Using macros to set up existing targets to use *HPX*

In addition to the `add_hpx_component` and `add_hpx_executable`, you can use the `hpx_setup_target` macro to have an already existing target to be used with the *HPX* libraries:

```
hpx_setup_target(target)
```

Optional parameters are:

- `EXPORT`: Adds it to the CMake export list `HPXTargets`
- `INSTALL`: Generates an install rule for the target
- `PLUGIN`: Treats this component as a plugin-able library
- `TYPE`: The type can be: `EXECUTABLE`, `LIBRARY` or `COMPONENT`
- `DEPENDENCIES`: Other libraries or targets this component depends on
- `COMPONENT_DEPENDENCIES`: The components this component depends on
- `COMPILE_FLAGS`: Additional compiler flags
- `LINK_FLAGS`: Additional linker flags

If you do not use CMake, you can still build against *HPX*, but you should refer to the section on *How to build HPX components with pkg-config*.

Note: Since *HPX* relies on dynamic libraries, the dynamic linker needs to know where to look for them. If *HPX* isn't installed into a path that is configured as a linker search path, external projects need to either set `RPATH` or adapt `LD_LIBRARY_PATH` to point to where the *HPX* libraries reside. In order to set `RPATHs`, you can include `HPX_SetFullRPATH` in your project after all libraries you want to link against have been added. Please also consult the CMake documentation [here](https://gitlab.kitware.com/cmake/community/wikis/doc/cmake/RPATH-handling)⁶⁹.

⁶⁹ <https://gitlab.kitware.com/cmake/community/wikis/doc/cmake/RPATH-handling>

Using HPX with Makefile

A basic project building with *HPX* is through creating makefiles. The process of creating one can get complex depending upon the use of cmake parameter `HPX_WITH_HPX_MAIN` (which defaults to ON).

How to build *HPX* applications with makefile

If *HPX* is installed correctly, you should be able to build and run a simple Hello World program. It prints Hello World! on the *locality* you run it on.

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Copy the content of this program into a file called `hello_world.cpp`.

Now, in the directory where you put `hello_world.cpp`, create a Makefile. Add the following code:

```
CXX=(CXX)  # Add your favourite compiler here or let makefile choose default.

CXXFLAGS=-O3 -std=c++17

Boost_ROOT=/path/to/boost
Hwloc_ROOT=/path/to/hwloc
Tcmalloc_ROOT=/path/to/tcmalloc
HPX_ROOT=/path/to/hpx

INCLUDE_DIRECTIVES=$(HPX_ROOT)/include $(Boost_ROOT)/include $(Hwloc_ROOT)/include

LIBRARY_DIRECTIVES=-L$(HPX_ROOT)/lib $(HPX_ROOT)/lib/libhpx_init.a $(HPX_ROOT)/lib/
↳ libhpx.so $(Boost_ROOT)/lib/libboost_atomic-mt.so $(Boost_ROOT)/lib/libboost_
↳ filesystem-mt.so $(Boost_ROOT)/lib/libboost_program_options-mt.so $(Boost_ROOT)/lib/
↳ libboost_regex-mt.so $(Boost_ROOT)/lib/libboost_system-mt.so -lpthread $(Tcmalloc_
↳ ROOT)/libtcmalloc_minimal.so $(Hwloc_ROOT)/libhwloc.so -ldl -lrt

LINK_FLAGS=$(HPX_ROOT)/lib/libhpx_wrap.a -Wl,-wrap=main  # should be left empty for HPX_
↳ WITH_HPX_MAIN=OFF

hello_world: hello_world.o
    $(CXX) $(CXXFLAGS) -o hello_world hello_world.o $(LIBRARY_DIRECTIVES) $(LINK_FLAGS)

hello_world.o:
    $(CXX) $(CXXFLAGS) -c -o hello_world.o hello_world.cpp $(INCLUDE_DIRECTIVES)
```

Important: `LINK_FLAGS` should be left empty if `HPX_WITH_HPX_MAIN` is set to OFF. Boost in the above example

is build with `--layout=tagged`. Actual Boost flags may vary on your build of Boost.

To build the program, type:

```
$ make
```

A successful build should result in `hello_world` binary. To test, type:

```
$ ./hello_world
```

How to build *HPX* components with makefile

Let's try a more complex example involving an *HPX* component. An *HPX* component is a class that exposes *HPX* actions. *HPX* components are compiled into dynamically-loaded modules called component libraries. Here's the source code:

hello_world_component.cpp

```
#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/iostream.hpp>
#include "hello_world_component.hpp"

#include <iostream>

namespace examples { namespace server {
    void hello_world::invoke()
    {
        hpx::cout << "Hello HPX World!" << std::endl;
    }
}} // namespace examples::server

HPX_REGISTER_COMPONENT_MODULE()

typedef hpx::components::component<examples::server::hello_world>
    hello_world_type;

HPX_REGISTER_COMPONENT(hello_world_type, hello_world)

HPX_REGISTER_ACTION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)
#endif
```

hello_world_component.hpp

```
#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/actions.hpp>
#include <hpx/include/components.hpp>
```

(continues on next page)

(continued from previous page)

```

#include <hpx/include/lcos.hpp>
#include <hpx/serialization.hpp>

#include <utility>

namespace examples { namespace server {
    struct HPX_COMPONENT_EXPORT hello_world
        : hpx::components::component_base<hello_world>
    {
        void invoke();
        HPX_DEFINE_COMPONENT_ACTION(hello_world, invoke)
    };
}} // namespace examples::server

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)

namespace examples {
    struct hello_world
        : hpx::components::client_base<hello_world, server::hello_world>
    {
        typedef hpx::components::client_base<hello_world, server::hello_world>
            base_type;

        hello_world(hpx::future<hpx::id_type>&& f)
            : base_type(std::move(f))
        {
        }

        hello_world(hpx::id_type&& f)
            : base_type(std::move(f))
        {
        }

        void invoke()
        {
            hpx::async<server::hello_world::invoke_action>(this->get_id())
                .get();
        }
    };
} // namespace examples

#endif

```

hello_world_client.cpp

```

#include <hpx/config.hpp>
#if defined(HPX_COMPUTE_HOST_CODE)
#include <hpx/wrap_main.hpp>

#include "hello_world_component.hpp"

```

(continues on next page)

(continued from previous page)

```

int main()
{
    {
        // Create a single instance of the component on this locality.
        examples::hello_world client =
            hpx::new_<examples::hello_world>(hpx::find_here());

        // Invoke the component's action, which will print "Hello World!".
        client.invoke();
    }

    return 0;
}
#endif

```

Now, in the directory, create a Makefile. Add the following code:

```

CXX=(CXX) # Add your favourite compiler here or let makefile choose default.

CXXFLAGS=-O3 -std=c++17

Boost_ROOT=/path/to/boost
Hwloc_ROOT=/path/to/hwloc
Tcmalloc_ROOT=/path/to/tcmalloc
HPX_ROOT=/path/to/hpx

INCLUDE_DIRECTIVES=$(HPX_ROOT)/include $(Boost_ROOT)/include $(Hwloc_ROOT)/include

LIBRARY_DIRECTIVES=-L$(HPX_ROOT)/lib $(HPX_ROOT)/lib/libhpx_init.a $(HPX_ROOT)/lib/
↳ libhpx.so $(Boost_ROOT)/lib/libboost_atomic-mt.so $(Boost_ROOT)/lib/libboost_
↳ filesystem-mt.so $(Boost_ROOT)/lib/libboost_program_options-mt.so $(Boost_ROOT)/lib/
↳ libboost_regex-mt.so $(Boost_ROOT)/lib/libboost_system-mt.so -lpthread $(Tcmalloc_
↳ ROOT)/libtcmalloc_minimal.so $(Hwloc_ROOT)/libhwloc.so -ldl -lrt

LINK_FLAGS=$(HPX_ROOT)/lib/libhpx_wrap.a -Wl,-wrap=main # should be left empty for HPX_
↳ WITH_HPX_MAIN=OFF

hello_world_client: libhpx_hello_world hello_world_client.o
    $(CXX) $(CXXFLAGS) -o hello_world_client $(LIBRARY_DIRECTIVES) libhpx_hello_world
↳ $(LINK_FLAGS)

hello_world_client.o: hello_world_client.cpp
    $(CXX) $(CXXFLAGS) -o hello_world_client.o hello_world_client.cpp $(INCLUDE_DIRECTIVES)

libhpx_hello_world: hello_world_component.o
    $(CXX) $(CXXFLAGS) -o libhpx_hello_world hello_world_component.o $(LIBRARY_DIRECTIVES)

hello_world_component.o: hello_world_component.cpp
    $(CXX) $(CXXFLAGS) -c -o hello_world_component.o hello_world_component.cpp $(INCLUDE_
↳ DIRECTIVES)

```

To build the program, type:

```
$ make
```

A successful build should result in `hello_world` binary. To test, type:

```
$ ./hello_world
```

Note: Due to high variations in CMake flags and library dependencies, it is recommended to build *HPX* applications and components with `pkg-config` or `CMakeLists.txt`. Writing `Makefile` may result in broken builds if due care is not taken. `pkg-config` files and CMake systems are configured with CMake build of *HPX*. Hence, they are stable when used together and provide better support overall.

2.4.9 Starting the *HPX* runtime

In order to write an application that uses services from the *HPX* runtime system, you need to initialize the *HPX* library by inserting certain calls into the code of your application. Depending on your use case, this can be done in 3 different ways:

- *Minimally invasive:* Re-use the `main()` function as the main *HPX* entry point.
- *Balanced use case:* Supply your own main *HPX* entry point while blocking the main thread.
- *Most flexibility:* Supply your own main *HPX* entry point while avoiding blocking the main thread.
- *Suspend and resume:* As above but suspend and resume the *HPX* runtime to allow for other runtimes to be used.

Re-use the `main()` function as the main *HPX* entry point

This method is the least intrusive to your code. However, it provides you with the smallest flexibility in terms of initializing the *HPX* runtime system. The following code snippet shows what a minimal *HPX* application using this technique looks like:

```
#include <hpx/hpx_main.hpp>

int main(int argc, char* argv[])
{
    return 0;
}
```

The only change to your code you have to make is to include the file `hpx/hpx_main.hpp`. In this case the function `main()` will be invoked as the first *HPX* thread of the application. The runtime system will be initialized behind the scenes before the function `main()` is executed and will automatically stop after `main()` has returned. For this method to work you must link your application to the CMake⁷⁰ target `HPX::wrap_main`. This is done automatically if you are using the provided macros (*Using macros to create new targets*) to set up your application, but must be done explicitly if you are using targets directly (*Using CMake targets*). All *HPX* API functions can be used from within the `main()` function now. If you cannot or do not want to include `hpx/hpx_main.hpp` in `main.cpp`, you can instead link against `HPX::auto_wrap_main`. That target enables the same runtime startup path without needing the header-triggered option.

Note: The use of `HPX::auto_wrap_main` is not supported when using the native Windows MSVC toolchain.

⁷⁰ <https://www.cmake.org>

Note: The function `main()` does not need to expect receiving `argc` and `argv` as shown above, but could expose the signature `int main()`. This is consistent with the usually allowed prototypes for the function `main()` in C++ applications.

All command line arguments specific to *HPX* will still be processed by the *HPX* runtime system as usual. However, those command line options will be removed from the list of values passed to `argc/argv` of the function `main()`. The list of values passed to `main()` will hold only the commandline options that are not recognized by the *HPX* runtime system (see the section *HPX Command Line Options* for more details on what options are recognized by *HPX*).

Note: In this mode all one-letter shortcuts that are normally available on the *HPX* command line are disabled (such as `-t` or `-l` see *HPX Command Line Options*). This is done to minimize any possible interaction between the command line options recognized by the *HPX* runtime system and any command line options defined by the application.

The value returned from the function `main()` as shown above will be returned to the operating system as usual.

Important: To achieve this seamless integration, the header file `hpx/hpx_main.hpp` defines a macro:

```
#define main hpx_startup::user_main
```

which could result in unexpected behavior.

Important: To achieve this seamless integration, we use different implementations for different operating systems. In case of Linux or macOS, the code present in `hpx_wrap.cpp` is put into action. We hook into the system function in case of Linux and provide alternate entry point in case of macOS. For other operating systems we rely on a macro:

```
#define main hpx_startup::user_main
```

provided in the header file `hpx/hpx_main.hpp`. This implementation can result in unexpected behavior.

Caution: We make use of an *override* variable `include_libhpx_wrap` in the header file `hpx/hpx_main.hpp` to swiftly choose the function call stack at runtime. Therefore, the header file should *only* be included in the main executable. Including it in the components will result in multiple definition of the variable.

Supply your own main *HPX* entry point while blocking the main thread

With this method you need to provide an explicit main-thread function named `hpx_main` at global scope. This function will be invoked as the main entry point of your *HPX* application on the console *locality* only (this function will be invoked as the first *HPX* thread of your application). All *HPX* API functions can be used from within this function.

The thread executing the function `hpx::init` will block waiting for the runtime system to exit. The value returned from `hpx_main` will be returned from `hpx::init` after the runtime system has stopped.

The function `hpx::finalize` has to be called on one of the *HPX* localities in order to signal that all work has been scheduled and the runtime system should be stopped after the scheduled work has been executed.

This method of invoking *HPX* has the advantage of the user being able to decide which version of `hpx::init` to call. This allows to pass additional configuration parameters while initializing the *HPX* runtime system.

```
#include <hpx/hpx_init.hpp>

int hpx_main(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    // Initialize HPX, run hpx_main as the first HPX thread, and
    // wait for hpx::finalize being called.
    return hpx::init(argc, argv);
}
```

Note: The function `hpx_main` does not need to expect receiving `argc/argv` as shown above, but could expose one of the following signatures:

```
int hpx_main();
int hpx_main(int argc, char* argv[]);
int hpx_main(hpx::program_options::variables_map& vm);
```

This is consistent with (and extends) the usually allowed prototypes for the function `main()` in C++ applications.

The header file to include for this method of using *HPX* is `hpx/hpx_init.hpp`.

There are many additional overloads of `hpx::init` available, such as the ability to provide your own entry-point function instead of `hpx_main`. Please refer to the function documentation for more details (see: `hpx/hpx_init.hpp`).

Supply your own main *HPX* entry point while avoiding blocking the main thread

With this method you need to provide an explicit main thread function named `hpx_main` at global scope. This function will be invoked as the main entry point of your *HPX* application on the console *locality* only (this function will be invoked as the first *HPX* thread of your application). All *HPX* API functions can be used from within this function.

The thread executing the function `hpx::start` will *not* block waiting for the runtime system to exit, but will return immediately. The function `hpx::finalize` has to be called on one of the *HPX* localities in order to signal that all work has been scheduled and the runtime system should be stopped after the scheduled work has been executed.

This method of invoking *HPX* is useful for applications where the main thread is used for special operations, such as GUIs. The function `hpx::stop` can be used to wait for the *HPX* runtime system to exit and should at least be used as the last function called in `main()`. The value returned from `hpx_main` will be returned from `hpx::stop` after the runtime system has stopped.

```
#include <hpx/hpx_start.hpp>

int hpx_main(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}
```

(continues on next page)

(continued from previous page)

```

int main(int argc, char* argv[])
{
    // Initialize HPX, run hpx_main.
    hpx::start(argc, argv);

    // ...Execute other code here...

    // Wait for hpx::finalize being called.
    return hpx::stop();
}

```

Note: The function `hpx_main` does not need to expect receiving `argc/argv` as shown above, but could expose one of the following signatures:

```

int hpx_main();
int hpx_main(int argc, char* argv[]);
int hpx_main(hpx::program_options::variables_map& vm);

```

This is consistent with (and extends) the usually allowed prototypes for the function `main()` in C++ applications.

The header file to include for this method of using *HPX* is `hpx/hpx_start.hpp`.

There are many additional overloads of `hpx::start` available, such as the option for users to provide their own entry point function instead of `hpx_main`. Please refer to the function documentation for more details (see: `hpx/hpx_start.hpp`).

Supply your own explicit startup function as the main *HPX* entry point

There is also a way to specify any function (besides `hpx_main`) to be used as the main entry point for your *HPX* application:

```

#include <hpx/hpx_init.hpp>

int application_entry_point(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    // Initialize HPX, run application_entry_point as the first HPX thread,
    // and wait for hpx::finalize being called.
    return hpx::init(&application_entry_point, argc, argv);
}

```

Note: The function supplied to `hpx::init` must have one of the following prototypes:

```

int application_entry_point(int argc, char* argv[]);
int application_entry_point(hpx::program_options::variables_map&
vm);

```

Note: If `nullptr` is used as the function argument, *HPX* will not run any startup function on this locality.

Suspending and resuming the *HPX* runtime

In some applications it is required to combine *HPX* with other runtimes. To support this use case, *HPX* provides two functions: `hpx::suspend` and `hpx::resume`. `hpx::suspend` is a blocking call which will wait for all scheduled tasks to finish executing and then put the thread pool OS threads to sleep. `hpx::resume` simply wakes up the sleeping threads so that they are ready to accept new work. `hpx::suspend` and `hpx::resume` can be found in the header `hpx/hpx_suspend.hpp`.

```
#include <hpx/hpx_start.hpp>
#include <hpx/hpx_suspend.hpp>

int main(int argc, char* argv[])
{
    // Initialize HPX, don't run hpx_main
    hpx::start(nullptr, argc, argv);

    // Schedule a function on the HPX runtime
    hpx::post(&my_function, ...);

    // Wait for all tasks to finish, and suspend the HPX runtime
    hpx::suspend();

    // Execute non-HPX code here

    // Resume the HPX runtime
    hpx::resume();

    // Schedule more work on the HPX runtime

    // hpx::finalize has to be called from the HPX runtime before hpx::stop
    hpx::post([]() { hpx::finalize(); });
    return hpx::stop();
}
```

Note: `hpx::suspend` does not wait for `hpx::finalize` to be called. Only call `hpx::finalize` when you wish to fully stop the *HPX* runtime.

Warning:

`hpx::suspend` only waits for local tasks, i.e. tasks on the
current locality, to finish executing. When using `hpx::suspend` in a multi-locality scenario the user is responsible for ensuring that any work required from other localities has also finished.

HPX also supports suspending individual thread pools and threads. For details on how to do that, see the documentation

for `hpx::threads::thread_pool_base`.

Automatically suspending worker threads

The previous method guarantees that the worker threads are suspended when you ask for it and that they stay suspended. An alternative way to achieve the same effect is to tweak how quickly *HPX* suspends its worker threads when they run out of work. The following configuration values make sure that *HPX* idles very quickly:

```
hpx.max_idle_backoff_time = 1000
hpx.max_idle_loop_count = 0
```

They can be set on the command line using `--hpx:ini=hpx.max_idle_backoff_time=1000` and `--hpx:ini=hpx.max_idle_loop_count=0`. See *Launching and configuring HPX applications* for more details on how to set configuration parameters.

After setting idling parameters the previous example could now be written like this instead:

```
#include <hpx/hpx_start.hpp>

int main(int argc, char* argv[])
{
    // Initialize HPX, don't run hpx_main
    hpx::start(nullptr, argc, argv);

    // Schedule some functions on the HPX runtime
    // NOTE: run_as_hpx_thread blocks until completion.
    hpx::run_as_hpx_thread(&my_function, ...);
    hpx::run_as_hpx_thread(&my_other_function, ...);

    // hpx::finalize has to be called from the HPX runtime before hpx::stop
    hpx::post([]() { hpx::finalize(); });
    return hpx::stop();
}
```

In this example each call to `hpx::run_as_hpx_thread` acts as a “parallel region”.

Working of `hpx_main.hpp`

In order to initialize *HPX* from `main()`, we make use of linker tricks.

It is implemented differently for different operating systems. The method of implementation is as follows:

- *Linux*: Using linker `--wrap` option.
- *Mac OSX*: Using the linker `-e` option.
- *Windows*: Using `#define main hpx_startup::user_main`

Linux implementation

We make use of the Linux linker `ld`'s `--wrap` option to wrap the `main()` function. This way any calls to `main()` are redirected to our own implementation of `main`. It is here that we check for the existence of `hpx_main.hpp` by making use of a shadow variable `include_libhpx_wrap`. The value of this variable determines the function stack at runtime.

The implementation can be found in `libhpx_wrap.a`.

Important: It is necessary that `hpx_main.hpp` be not included more than once. Multiple inclusions can result in multiple definition of `include_libhpx_wrap`.

Mac OSX implementation

Here we make use of yet another linker option `-e` to change the entry point to our custom entry function `initialize_main`. We initialize the *HPX* runtime system from this function and call `main` from the initialized system. We determine the function stack at runtime by making use of the shadow variable `include_libhpx_wrap`.

The implementation can be found in `libhpx_wrap.a`.

Important: It is necessary that `hpx_main.hpp` be not included more than once. Multiple inclusions can result in multiple definition of `include_libhpx_wrap`.

Windows implementation

We make use of a macro `#define main hpx_startup::user_main` to take care of the initializations.

This implementation could result in unexpected behaviors.

2.4.10 Launching and configuring *HPX* applications

Configuring *HPX* applications

All *HPX* applications can be configured using special command line options and/or using special configuration files. This section describes the available options, the configuration file format, and the algorithm used to locate possible predefined configuration files. Additionally, this section describes the defaults assumed if no external configuration information is supplied.

During startup any *HPX* application applies a predefined search pattern to locate one or more configuration files. All found files will be read and merged in the sequence they are found into one single internal database holding all configuration properties. This database is used during the execution of the application to configure different aspects of the runtime system.

In addition to the ini files, any application can supply its own configuration files, which will be merged with the configuration database as well. Moreover, the user can specify additional configuration parameters on the command line when executing an application. The *HPX* runtime system will merge all command line configuration options (see the description of the `--hpx:ini`, `--hpx:config`, and `--hpx:app-config` command line options).

The HPX ini file format

All HPX applications can be configured using a special file format that is similar to the well-known [Windows INI file format](#)⁷¹. This is a structured text format that allows users to group key/value pairs (properties) into sections. The basic element contained in an ini file is the property. Every property has a name and a value, delimited by an equal sign '='. The name appears to the left of the equal sign:

```
name=value
```

The value may contain equal signs as only the first '=' character is interpreted as the delimiter between name and value. Whitespace before the name, after the value and immediately before and after the delimiting equal sign is ignored. Whitespace inside the value is retained.

Properties may be grouped into arbitrarily named sections. The section name appears on a line by itself, in square brackets. All properties after the section declaration are associated with that section. There is no explicit “end of section” delimiter; sections end at the next section declaration or the end of the file:

```
[section]
```

In HPX sections can be nested. A nested section has a name composed of all section names it is embedded in. The section names are concatenated using a dot '.':

```
[outer_section.inner_section]
```

Here, `inner_section` is logically nested within `outer_section`.

It is possible to use the full section name concatenated with the property name to refer to a particular property. For example, in:

```
[a.b.c]
d = e
```

the property value of `d` can be referred to as `a.b.c.d=e`.

In HPX ini files can contain comments. Hash signs '#' at the beginning of a line indicate a comment. All characters starting with '#' until the end of the line are ignored.

If a property with the same name is reused inside a section, the second occurrence of this property name will override the first occurrence (discard the first value). Duplicate sections simply merge their properties together, as if they occurred contiguously.

In HPX ini files a property value `${FOO:default}` will use the environmental variable `FOO` to extract the actual value if it is set and `default` otherwise. No default has to be specified. Therefore, `${FOO}` refers to the environmental variable `FOO`. If `FOO` is not set or empty, the overall expression will evaluate to an empty string. A property value `$(section.key:default)` refers to the value held by the property `section.key` if it exists and `default` otherwise. No default has to be specified. Therefore `$(section.key)` refers to the property `section.key`. If the property `section.key` is not set or empty, the overall expression will evaluate to an empty string.

Note: Any property `$(section.key:default)` is evaluated whenever it is queried and not when the configuration data is initialized. This allows for lazy evaluation and relaxes initialization order of different sections. The only exception are recursive property values, e.g., values referring to the very key they are associated with. Those property values are evaluated at initialization time to avoid infinite recursion.

⁷¹ https://en.wikipedia.org/wiki/INI_file

Built-in default configuration settings

During startup any *HPX* application applies a predefined search pattern to locate one or more configuration files. All found files will be read and merged in the sequence they are found into one single internal data structure holding all configuration properties.

As a first step the internal configuration database is filled with a set of default configuration properties. Those settings are described on a section by section basis below.

Note: You can print the default configuration settings used for an executable by specifying the command line option `--hpx:dump-config`.

The system configuration section

```
[system]
pid = <process-id>
prefix = <current prefix path of core HPX library>
executable = <current prefix path of executable>
```

Property	Description
system.pid	This is initialized to store the current OS-process id of the application instance.
system.prefix	This is initialized to the base directory <i>HPX</i> has been loaded from.
system.executable_prefix	This is initialized to the base directory the current executable has been loaded from.

The *HPX* configuration section

```
[hpx]
location = ${HPX_LOCATION:${system.prefix}}
component_path = [hpx.location]/lib/hpx:${system.executable_prefix}/lib/hpx:${system.
↳executable_prefix}/../lib/hpx
master_ini_path = [hpx.location]/share/hpx-<version>:${system.executable_prefix}/share/
↳hpx-<version>:${system.executable_prefix}/../share/hpx-<version>
ini_path = [hpx.master_ini_path]/ini
os_threads = 1
cores = all
localities = 1
program_name =
cmd_line =
lock_detection = ${HPX_LOCK_DETECTION:0}
throw_on_held_lock = ${HPX_THROW_ON_HELD_LOCK:1}
minimal_deadlock_detection = <debug>
spinlock_deadlock_detection = <debug>
spinlock_deadlock_detection_limit = ${HPX_SPINLOCK_DEADLOCK_DETECTION_LIMIT:1000000}
max_background_threads = ${HPX_MAX_BACKGROUND_THREADS:[hpx.os_threads]}
max_idle_loop_count = ${HPX_MAX_IDLE_LOOP_COUNT:<hpx_idle_loop_count_max>}
max_busy_loop_count = ${HPX_MAX_BUSY_LOOP_COUNT:<hpx_busy_loop_count_max>}
max_idle_backoff_time = ${HPX_MAX_IDLE_BACKOFF_TIME:<hpx_idle_backoff_time_max>}
```

(continues on next page)

(continued from previous page)

```
exception_verbosity = ${HPX_EXCEPTION_VERBOSITY:2}
trace_depth = ${HPX_TRACE_DEPTH:20}
handle_signals = ${HPX_HANDLE_SIGNALS:1}
handle_failed_new = ${HPX_HANDLE_FAILED_NEW:1}



### [hpx.stacks]


small_size = ${HPX_SMALL_STACK_SIZE:<hpx_small_stack_size>}
medium_size = ${HPX_MEDIUM_STACK_SIZE:<hpx_medium_stack_size>}
large_size = ${HPX_LARGE_STACK_SIZE:<hpx_large_stack_size>}
huge_size = ${HPX_HUGE_STACK_SIZE:<hpx_huge_stack_size>}
use_guard_pages = ${HPX_THREAD_GUARD_PAGE:1}
```


Property	Description
<code>hpx.location</code>	This is initialized to the id of the <i>locality</i> this application instance is running on.
<code>hpx.component_path</code>	Duplicates are discarded. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
<code>hpx.master_ini_path</code>	This is initialized to the list of default paths of the main <code>hpx.ini</code> configuration files. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or using ';' (Windows).
<code>hpx.ini_path</code>	This is initialized to the default path where <i>HPX</i> will look for more ini configuration files. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or using ';' (Windows).
<code>hpx.os_threads</code>	This setting reflects the number of OS threads used for running <i>HPX</i> threads. Defaults to number of detected cores (not hyperthreads/PUs).
<code>hpx.cores</code>	This setting reflects the number of cores used for running <i>HPX</i> threads. Defaults to number of detected cores (not hyperthreads/PUs).
<code>hpx.localities</code>	This setting reflects the number of localities the application is running on. Defaults to 1.
<code>hpx.program_name</code>	This setting reflects the program name of the application instance. Initialized from the command line <code>argv[0]</code> .
<code>hpx.cmd_line</code>	This setting reflects the actual command line used to launch this application instance.
<code>hpx.lock_detection</code>	This setting verifies that no locks are being held while a <i>HPX</i> thread is suspended. This setting is applicable only if <code>HPX_WITH_VERIFY_LOCKS</code> is set during configuration in CMake.
<code>hpx.throw_on_hold</code>	This setting causes an exception if during lock detection at least one lock is being held while a <i>HPX</i> thread is suspended. This setting is applicable only if <code>HPX_WITH_VERIFY_LOCKS</code> is set during configuration in CMake. This setting has no effect if <code>hpx.lock_detection=0</code> .
<code>hpx.minimal_deadlock_detection</code>	This setting enables support for minimal deadlock detection for <i>HPX</i> threads. By default this is set to 1 (for Debug builds) or to 0 (for Release, RelWithDebInfo, RelMinSize builds). This setting is effective only if <code>HPX_WITH_THREAD_DEADLOCK_DETECTION</code> is set during configuration in CMake.
<code>hpx.spinlock_deadlock_detection</code>	This setting verifies that spinlocks don't spin longer than specified using the <code>spinlock_deadlock_detection_limit</code> . This setting is applicable only if <code>HPX_WITH_SPINLOCK_DEADLOCK_DETECTION</code> is set during configuration in CMake. By default this is set to 1 (for Debug builds) or to 0 (for Release, RelWithDebInfo, RelMinSize builds).
<code>hpx.spinlock_deadlock_detection_limit</code>	This setting specifies the upper limit of the allowed number of spins that spinlocks are allowed to perform. This setting is applicable only if <code>HPX_WITH_SPINLOCK_DEADLOCK_DETECTION</code> is set during configuration in CMake. By default this is set to 1000000.
<code>hpx.max_background_threads</code>	This setting defines the number of threads in the scheduler, which are used to execute background work. By default this is the same as the number of cores used for the scheduler.
<code>hpx.max_idle_loop_count</code>	By default this is defined by the preprocessor constant <code>HPX_IDLE_LOOP_COUNT_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.max_busy_loop_count</code>	This setting defines the maximum value of the busy-loop counter in the scheduler. By default this is defined by the preprocessor constant <code>HPX_BUSY_LOOP_COUNT_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.max_idle_backoff_time</code>	This setting defines the maximum time (in milliseconds) for the scheduler to sleep after <code>hpx.max_idle_loop_count</code> iterations. This setting is applicable only if <code>HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF</code> is set during configuration in CMake ⁷² . By default this is defined by the preprocessor constant <code>HPX_IDLE_BACKOFF_TIME_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.exception_verbosity</code>	This setting defines the verbosity of exceptions. Valid values are integers. A setting of 2 or higher prints all available information. A setting of 1 leaves out the build configuration and environment variables. A setting of 0 or lower prints only the description of the thrown exception and the file name, function, and line number where the exception was thrown. The default value is 2 or the value of the environment variable <code>HPX_EXCEPTION_VERBOSITY</code> .
<code>hpx.trace_depth</code>	This setting defines the number of stack-levels printed in generated stack backtraces. This defaults to 20, but can be changed using the cmake <code>HPX_WITH_THREAD_BACKTRACE_DEPTH</code> configuration setting.

2.4. Manual

<code>hpx.handle_signals</code>	This setting defines whether <i>HPX</i> will register signal handlers that will print the configuration information (stack backtrace, system information, etc.) whenever a signal is raised. The default is 1. Setting this value to 0 can be useful in cases when generating a core-dump on segmentation faults or similar signals is desired.
---------------------------------	---

The `hpx.threadpools` configuration section

```
[hpx.threadpools]
io_pool_size = ${HPX_NUM_IO_POOL_SIZE:2}
parcel_pool_size = ${HPX_NUM_PARCEL_POOL_SIZE:2}
timer_pool_size = ${HPX_NUM_TIMER_POOL_SIZE:2}
```

Property	Description
<code>hpx.threadpools.io_pool_size</code>	The value of this property defines the number of OS threads created for the internal I/O thread pool.
<code>hpx.threadpools.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool.
<code>hpx.threadpools.timer_pool_size</code>	The value of this property defines the number of OS threads created for the internal timer thread pool.

The `hpx.thread_queue` configuration section

Important: These are the setting control internal values used by the thread scheduling queues in the *HPX* scheduler. You should not modify these settings unless you know exactly what you are doing.

```
[hpx.thread_queue]
min_tasks_to_steal_pending = ${HPX_THREAD_QUEUE_MIN_TASKS_TO_STEAL_PENDING:0}
min_tasks_to_steal_staged = ${HPX_THREAD_QUEUE_MIN_TASKS_TO_STEAL_STAGED:0}
min_add_new_count = ${HPX_THREAD_QUEUE_MIN_ADD_NEW_COUNT:10}
max_add_new_count = ${HPX_THREAD_QUEUE_MAX_ADD_NEW_COUNT:10}
max_delete_count = ${HPX_THREAD_QUEUE_MAX_DELETE_COUNT:1000}
```

Property	Description
<code>hpx.thread_queue.min_tasks_to_steal_pending</code>	The value of this property defines the number of pending <i>HPX</i> threads that have to be available before neighboring cores are allowed to steal work. The default is to allow stealing always.
<code>hpx.thread_queue.min_tasks_to_steal_staged</code>	The value of this property defines the number of staged <i>HPX</i> tasks that need to be available before neighboring cores are allowed to steal work. The default is to allow stealing always.
<code>hpx.thread_queue.min_add_new_count</code>	The value of this property defines the minimal number of tasks to be converted into <i>HPX</i> threads whenever the thread queues for a core have run empty.
<code>hpx.thread_queue.max_add_new_count</code>	The value of this property defines the maximal number of tasks to be converted into <i>HPX</i> threads whenever the thread queues for a core have run empty.
<code>hpx.thread_queue.max_delete_count</code>	The value of this property defines the number of terminated <i>HPX</i> threads to discard during each invocation of the corresponding function.

⁷² <https://www.cmake.org>

The `hpx.components` configuration section

```
[hpx.components]
load_external = ${HPX_LOAD_EXTERNAL_COMPONENTS:1}
```

Property	Description
<code>hpx.components.load_external</code>	This entry defines whether external components will be loaded on this <i>locality</i> . This entry is normally set to 1, and usually there is no need to directly change this value. It is automatically set to 0 for a dedicated AGAS server <i>locality</i> .

Additionally, the section `hpx.components` will be populated with the information gathered from all found components. The information loaded for each of the components will contain at least the following properties:

```
[hpx.components.<component_instance_name>]
name = <component_name>
path = <full_path_of_the_component_module>
enabled = ${hpx.components.load_external}
```

Property	Description
<code>hpx.components.<component_instance_name>.name</code>	This is the name of a component, usually the same as the second argument to the macro used while registering the component with <code>HPX_REGISTER_COMPONENT</code> . Set by the component factory.
<code>hpx.components.<component_instance_name>.path</code>	This is either the full path file name of the component module or the directory the component module is located in. In this case, the component module name will be derived from the property <code>hpx.components.<component_instance_name>.name</code> . Set by the component factory.
<code>hpx.components.<component_instance_name>.enabled</code>	This setting explicitly enables or disables the component. This is an optional property. <code>HPX_COMPONENTS_ENABLED</code> that the component is enabled if it is not defined.

The value for `<component_instance_name>` is usually the same as for the corresponding `name` property. However, generally it can be defined to any arbitrary instance name. It is used to distinguish between different ini sections, one for each component.

The `hpx.parcel` configuration section

```
[hpx.parcel]
address = ${HPX_PARCEL_SERVER_ADDRESS:<hpx_initial_ip_address>}
port = ${HPX_PARCEL_SERVER_PORT:<hpx_initial_ip_port>}
bootstrap = ${HPX_PARCEL_BOOTSTRAP:<hpx_parcel_bootstrap>}
max_connections = ${HPX_PARCEL_MAX_CONNECTIONS:<hpx_parcel_max_connections>}
max_connections_per_locality = ${HPX_PARCEL_MAX_CONNECTIONS_PER_LOCALITY:<hpx_parcel_max_
↳connections_per_locality>}
max_message_size = ${HPX_PARCEL_MAX_MESSAGE_SIZE:<hpx_parcel_max_message_size>}
max_outbound_message_size = ${HPX_PARCEL_MAX_OUTBOUND_MESSAGE_SIZE:<hpx_parcel_max_
↳outbound_message_size>}
array_optimization = ${HPX_PARCEL_ARRAY_OPTIMIZATION:1}
zero_copy_optimization = ${HPX_PARCEL_ZERO_COPY_OPTIMIZATION:${hpx.parcel.array_
↳optimization}}
```

(continues on next page)

(continued from previous page)

```

zero_copy_receive_optimization = ${HPX_PARCEL_ZERO_COPY_RECEIVE_OPTIMIZATION:${hpx.
↪parcel.array_optimization}}
async_serialization = ${HPX_PARCEL_ASYNC_SERIALIZATION:1}
message_handlers = ${HPX_PARCEL_MESSAGE_HANDLERS:0}

```

Property	Description
<code>hpx.parcel.address</code>	This property defines the default IP address to be used for the <i>parcel</i> layer to listen to. This IP address will be used as long as no other values are specified (for instance, using the <code>--hpx:hpx</code> command line option). The expected format is any valid IP address or domain name format that can be resolved into an IP address. The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_ADDRESS</code> ("127.0.0.1").
<code>hpx.parcel.port</code>	This property defines the default IP port to be used for the <i>parcel</i> layer to listen to. This IP port will be used as long as no other values are specified (for instance using the <code>--hpx:hpx</code> command line option). The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_PORT</code> (7910).
<code>hpx.parcel.bootstrap</code>	This property defines which <i>parcelpport</i> type should be used during application bootstrap. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_BOOTSTRAP</code> ("tcp").
<code>hpx.parcel.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_CONNECTIONS</code> (512).
<code>hpx.parcel.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_CONNECTIONS_PER_LOCALITY</code> (4).
<code>hpx.parcel.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_MESSAGE_SIZE</code> (1000000000 bytes).
<code>hpx.parcel.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_OUTBOUND_MESSAGE_SIZE</code> (1000000 bytes).
<code>hpx.parcel.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations during serialization of <i>parcel</i> data. The default is 1.
<code>hpx.parcel.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero-copy optimizations for serialized entities. The default value is defined by the preprocessor constant <code>HPX_ZERO_COPY_SERIALIZATION_THRESHOLD</code> .
<code>hpx.parcel.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization (this is both for encoding and decoding parcels). The default is 1.
<code>hpx.parcel.message_handlers</code>	This property defines whether message handlers are loaded. The default is 0.
<code>hpx.parcel.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is -1 (all cores).

The following settings relate to the TCP/IP parcelport.

```
[hpx.parcel.tcp]
enable = ${HPX_HAVE_PARCELPORT_TCP:${hpx.parcel.enabled}}
array_optimization = ${HPX_PARCEL_TCP_ARRAY_OPTIMIZATION:${hpx.parcel.array_
↳optimization}}
zero_copy_optimization = ${HPX_PARCEL_TCP_ZERO_COPY_OPTIMIZATION:${hpx.parcel.zero_copy_
↳optimization}}
zero_copy_receive_optimization = ${HPX_PARCEL_TCP_ZERO_COPY_RECEIVE_OPTIMIZATION:${hpx.
↳parcel.zero_copy_receive_optimization}}
zero_copy_serialization_threshold = ${HPX_PARCEL_TCP_ZERO_COPY_SERIALIZATION_THRESHOLD:
↳${hpx.parcel.zero_copy_serialization_threshold}}
async_serialization = ${HPX_PARCEL_TCP_ASYNC_SERIALIZATION:${hpx.parcel.async_
↳serialization}}
parcel_pool_size = ${HPX_PARCEL_TCP_PARCEL_POOL_SIZE:${hpx.threadpools.parcel_pool_size}}
max_connections = ${HPX_PARCEL_TCP_MAX_CONNECTIONS:${hpx.parcel.max_connections}}
max_connections_per_locality = ${HPX_PARCEL_TCP_MAX_CONNECTIONS_PER_LOCALITY:${hpx.
↳parcel.max_connections_per_locality}}
max_message_size = ${HPX_PARCEL_TCP_MAX_MESSAGE_SIZE:${hpx.parcel.max_message_size}}
max_outbound_message_size = ${HPX_PARCEL_TCP_MAX_OUTBOUND_MESSAGE_SIZE:${hpx.parcel.max_
↳outbound_message_size}}
max_background_threads = ${HPX_PARCEL_TCP_MAX_BACKGROUND_THREADS:${hpx.parcel.max_
↳background_threads}}
```

Property	Description
<code>hpx.parcel.tcp.enable</code>	Enables the use of the default TCP parcelport. Note that the initial bootstrap of the overall <i>HPX</i> application will be performed using the default TCP connections. This parcelport is enabled by default. This will be disabled only if MPI is enabled (see below).
<code>hpx.parcel.tcp.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations in the TCP/IP parcelport during serialization of parcel data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations during serialization of parcel data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end in the TCP/IP parcelport during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero copy optimizations for serialized entities. The default is the same value as set for <code>hpx.parcel.zero_copy_serialization_threshold</code> .
<code>hpx.parcel.tcp.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization in the TCP/IP parcelport (this is both for encoding and decoding parcels). The default is the same value as set for <code>hpx.parcel.async_serialization</code> .
<code>hpx.parcel.tcp.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool of the TCP <i>parcel</i> port. The default is taken from <code>hpx.threadpools.parcel_pool_size</code> .
<code>hpx.parcel.tcp.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections</code> .
<code>hpx.parcel.tcp.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections_per_locality</code> .
<code>hpx.parcel.tcp.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_message_size</code> .
<code>hpx.parcel.tcp.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_outbound_connections</code> .
<code>hpx.parcel.tcp.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is taken from <code>hpx.parcel.max_background_threads</code> .

The following settings relate to the MPI parcelport. These settings take effect only if the compile time constant `HPX_HAVE_PARCELPOR_T_MPI` is set (the equivalent CMake variable is `HPX_WITH_PARCELPOR_T_MPI` and has to be set to ON).

```
[hpx.parcel.mpi]
enable = ${HPX_HAVE_PARCELPOR_T_MPI:[hpx.parcel.enabled]}
env = ${HPX_HAVE_PARCELPOR_T_MPI_ENV:MV2_COMM_WORLD_RANK,PMI_RANK,OMPI_COMM_WORLD_SIZE,
↪ALPS_APP_PE,PALS_NODEID}
multithreaded = ${HPX_HAVE_PARCELPOR_T_MPI_MULTITHREADED:1}
rank = <MPI_rank>
processor_name = <MPI_processor_name>
array_optimization = ${HPX_HAVE_PARCEL_MPI_ARRAY_OPTIMIZATION:[hpx.parcel.array_
↪optimization]}
zero_copy_optimization = ${HPX_HAVE_PARCEL_MPI_ZERO_COPY_OPTIMIZATION:[hpx.parcel.zero_
↪copy_optimization]}
zero_copy_receive_optimization = ${HPX_HAVE_PARCEL_MPI_ZERO_COPY_RECEIVE_OPTIMIZATION:
↪[hpx.parcel.zero_copy_receive_optimization]}
```

(continues on next page)

(continued from previous page)

```
zero_copy_serialization_threshold = ${HPX_PARCEL_MPI_ZERO_COPY_SERIALIZATION_THRESHOLD:
↳[hpx.parcel.zero_copy_serialization_threshold]}
use_io_pool = ${HPX_HAVE_PARCEL_MPI_USE_IO_POOL:$1}
async_serialization = ${HPX_HAVE_PARCEL_MPI_ASYNC_SERIALIZATION:[hpx.parcel.async_
↳serialization]}
parcel_pool_size = ${HPX_HAVE_PARCEL_MPI_PARCEL_POOL_SIZE:[hpx.threadpools.parcel_pool_
↳size]}
max_connections = ${HPX_HAVE_PARCEL_MPI_MAX_CONNECTIONS:[hpx.parcel.max_connections]}
max_connections_per_locality = ${HPX_HAVE_PARCEL_MPI_MAX_CONNECTIONS_PER_LOCALITY:[hpx.
↳parcel.max_connections_per_locality]}
max_message_size = ${HPX_HAVE_PARCEL_MPI_MAX_MESSAGE_SIZE:[hpx.parcel.max_message_
↳size]}
max_outbound_message_size = ${HPX_HAVE_PARCEL_MPI_MAX_OUTBOUND_MESSAGE_SIZE:[hpx.
↳parcel.max_outbound_message_size]}
max_background_threads = ${HPX_PARCEL_MPI_MAX_BACKGROUND_THREADS:[hpx.parcel.max_
↳background_threads]}
```

Property	Description
<code>hpx.parcel.mpi.enable</code>	Enables the use of the MPI parcelport. <i>HPX</i> tries to detect if the application was started within a parallel MPI environment. If the detection was successful, the MPI parcelport is enabled by default. To explicitly disable the MPI parcelport, set to 0. Note that the initial bootstrap of the overall <i>HPX</i> application will be performed using MPI as well.
<code>hpx.parcel.mpi.env</code>	This property influences which environment variables (separated by commas) will be analyzed to find out whether the application was invoked by MPI.
<code>hpx.parcel.mpi.multithreaded</code>	This property is used to determine what threading mode to use when initializing MPI. If this setting is 0, <i>HPX</i> will initialize MPI with <code>MPI_THREAD_SINGLE</code> . If the value is not equal to 0, <i>HPX</i> will initialize MPI with <code>MPI_THREAD_MULTII</code> .
<code>hpx.parcel.mpi.rank</code>	This property will be initialized to the MPI rank of the <i>locality</i> .
<code>hpx.parcel.mpi.processor_name</code>	This property will be initialized to the MPI processor name of the <i>locality</i> .
<code>hpx.parcel.mpi.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations in the MPI parcelport during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations in the MPI parcelport during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end in the MPI parcelport during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero-copy optimizations for serialized entities. The default is the same value as set for <code>hpx.parcel.zero_copy_serialization_threshold</code> .
<code>hpx.parcel.mpi.use_io_pool</code>	This property can be set to run the progress thread inside of <i>HPX</i> threads instead of a separate thread pool. The default is 1.
<code>hpx.parcel.mpi.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization in the MPI parcelport (this is both for encoding and decoding parcels). The default is the same value as set for <code>hpx.parcel.async_serialization</code> .
<code>hpx.parcel.mpi.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool of the MPI <i>parcel</i> port. The default is taken from <code>hpx.threadpools.parcel_pool_size</code> .
<code>hpx.parcel.mpi.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections</code> .
<code>hpx.parcel.mpi.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections_per_locality</code> .
<code>hpx.parcel.mpi.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_message_size</code> .
<code>hpx.parcel.mpi.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_outbound_message_size</code> .
<code>hpx.parcel.mpi.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is taken from <code>hpx.parcel.max_background_threads</code> .

The `hpx.agas` configuration section

```
[hpx.agas]
address = ${HPX_AGAS_SERVER_ADDRESS:<hpx_initial_ip_address>}
port = ${HPX_AGAS_SERVER_PORT:<hpx_initial_ip_port>}
service_mode = hosted
dedicated_server = 0
max_pending_refcnt_requests = ${HPX_AGAS_MAX_PENDING_REFCNT_REQUESTS:<hpx_initial_agas_
↪max_pending_refcnt_requests>}
use_caching = ${HPX_AGAS_USE_CACHING:1}
use_range_caching = ${HPX_AGAS_USE_RANGE_CACHING:1}
local_cache_size = ${HPX_AGAS_LOCAL_CACHE_SIZE:<hpx_agas_local_cache_size>}
```

Property	Description
<code>hpx.agas.address</code>	This property defines the default IP address to be used for the AGAS root server. This IP address will be used as long as no other values are specified (for instance, using the <code>--hpx:agas</code> command line option). The expected format is any valid IP address or domain name format that can be resolved into an IP address. The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_ADDRESS</code> ("127.0.0.1").
<code>hpx.agas.port</code>	This property defines the default IP port to be used for the AGAS root server. This IP port will be used as long as no other values are specified (for instance, using the <code>--hpx:agas</code> command line option). The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_PORT</code> (7009).
<code>hpx.agas.service_mode</code>	This property specifies what type of AGAS service is running on this <i>locality</i> . Currently, two modes exist. The <i>locality</i> that acts as the AGAS server runs in <code>bootstrap</code> mode. All other localities are in <code>hosted</code> mode.
<code>hpx.agas.dedicated_server</code>	This property specifies whether the AGAS server is exclusively running AGAS services and not hosting any application components. It is a boolean value. Set to 1 if <code>--hpx:run-agas-server-only</code> is present.
<code>hpx.agas.max_pending_refcnt_requests</code>	This property defines the number of reference counting requests (increments or decrements) to buffer. The default depends on the compile time preprocessor constant <code>HPX_AGAS_MAX_PENDING_REFCNT_REQUESTS</code> (4096).
<code>hpx.agas.use_caching</code>	This property specifies whether a software address translation cache is used. It is a boolean value. Defaults to 1.
<code>hpx.agas.use_range_caching</code>	This property specifies whether range-based caching is used by the software address translation cache. This property is ignored if <code>hpx.agas.use_caching</code> is false. It is a boolean value. Defaults to 1.
<code>hpx.agas.local_cache_size</code>	This property defines the size of the software address translation cache for AGAS services. This property is ignored if <code>hpx.agas.use_caching</code> is false. Note that if <code>hpx.agas.use_range_caching</code> is true, this size will refer to the maximum number of ranges stored in the cache, not the number of entries spanned by the cache. The default depends on the compile time preprocessor constant <code>HPX_AGAS_LOCAL_CACHE_SIZE</code> (4096).

The `hpx.commandline` configuration section

The following table lists the definition of all pre-defined command line option shortcuts. For more information about commandline options, see the section *HPX Command Line Options*.

```
[hpx.commandline]
aliasing = ${HPX_COMMANDLINE_ALIASING:1}
allow_unknown = ${HPX_COMMANDLINE_ALLOW_UNKNOWN:0}

[hpx.commandline.aliases]
-a = --hpx:agas
-c = --hpx:console
-h = --hpx:help
-I = --hpx:ini
-l = --hpx:localities
-p = --hpx:app-config
-q = --hpx:queuing
-r = --hpx:run-agas-server
-t = --hpx:threads
-v = --hpx:version
-w = --hpx:worker
-x = --hpx:hpx
-0 = --hpx:node=0
-1 = --hpx:node=1
-2 = --hpx:node=2
-3 = --hpx:node=3
-4 = --hpx:node=4
-5 = --hpx:node=5
-6 = --hpx:node=6
-7 = --hpx:node=7
-8 = --hpx:node=8
-9 = --hpx:node=9
```

Note: The short options listed above are disabled by default if the application is built using `#include <hpx/hpx_main.hpp>`. See *Re-use the `main()` function as the main HPX entry point* for more information. The rationale behind this is that in this case the user's application may handle its own command line options, since *HPX* passes all unknown options to `main()`. Short options like `-t` are prone to create ambiguities regarding what the application will support. Hence, the user should instead rely on the corresponding long options like `--hpx:threads` in such a case.

Property	Description
<code>hpx.commandline.aliases</code>	Enable command line aliases as defined in the section <code>hpx.commandline.aliases</code> (see below). Defaults to 1.
<code>hpx.commandline.allow_unknown</code>	Allow for unknown command line options to be passed through to <code>hpx_main()</code> Defaults to 0.
<code>hpx.commandline.aliases.-a</code>	On the commandline <code>-a</code> expands to: <code>--hpx:agas</code> .
<code>hpx.commandline.aliases.-c</code>	On the commandline <code>-c</code> expands to: <code>--hpx:console</code> .
<code>hpx.commandline.aliases.-h</code>	On the commandline <code>-h</code> expands to: <code>--hpx:help</code> .
<code>hpx.commandline.aliases.--help</code>	On the commandline <code>--help</code> expands to: <code>--hpx:help</code> .
<code>hpx.commandline.aliases.-I</code>	On the commandline <code>-I</code> expands to: <code>--hpx:ini</code> .
<code>hpx.commandline.aliases.-l</code>	On the commandline <code>-l</code> expands to: <code>--hpx:localities</code> .
<code>hpx.commandline.aliases.-p</code>	On the commandline <code>-p</code> expands to: <code>--hpx:app-config</code> .
<code>hpx.commandline.aliases.-q</code>	On the commandline <code>-q</code> expands to: <code>--hpx:queuing</code> .
<code>hpx.commandline.aliases.-r</code>	On the commandline <code>-r</code> expands to: <code>--hpx:run-agas-server</code> .
<code>hpx.commandline.aliases.-t</code>	On the commandline <code>-t</code> expands to: <code>--hpx:threads</code> .
<code>hpx.commandline.aliases.-v</code>	On the commandline <code>-v</code> expands to: <code>--hpx:version</code> .
<code>hpx.commandline.aliases.--version</code>	On the commandline <code>--version</code> expands to: <code>--hpx:version</code> .
<code>hpx.commandline.aliases.-w</code>	On the commandline <code>-w</code> expands to: <code>--hpx:worker</code> .
<code>hpx.commandline.aliases.-x</code>	On the commandline <code>-x</code> expands to: <code>--hpx:hpx</code> .
<code>hpx.commandline.aliases.-0</code>	On the commandline <code>-0</code> expands to: <code>--hpx:node=0</code> .
<code>hpx.commandline.aliases.-1</code>	On the commandline <code>-1</code> expands to: <code>--hpx:node=1</code> .
<code>hpx.commandline.aliases.-2</code>	On the commandline <code>-2</code> expands to: <code>--hpx:node=2</code> .
<code>hpx.commandline.aliases.-3</code>	On the commandline <code>-3</code> expands to: <code>--hpx:node=3</code> .
<code>hpx.commandline.aliases.-4</code>	On the commandline <code>-4</code> expands to: <code>--hpx:node=4</code> .
<code>hpx.commandline.aliases.-5</code>	On the commandline <code>-5</code> expands to: <code>--hpx:node=5</code> .
<code>hpx.commandline.aliases.-6</code>	On the commandline <code>-6</code> expands to: <code>--hpx:node=6</code> .
<code>hpx.commandline.aliases.-7</code>	On the commandline <code>-7</code> expands to: <code>--hpx:node=7</code> .
<code>hpx.commandline.aliases.-8</code>	On the commandline <code>-8</code> expands to: <code>--hpx:node=8</code> .
<code>hpx.commandline.aliases.-9</code>	On the commandline <code>-9</code> expands to: <code>--hpx:node=9</code> .

Loading INI files

During startup and after the internal database has been initialized as described in the section *Built-in default configuration settings*, HPX will try to locate and load additional ini files to be used as a source for configuration properties. This allows for a wide spectrum of additional customization possibilities by the user and system administrators. The sequence of locations where HPX will try loading the ini files is well defined and documented in this section. All ini files found are merged into the internal configuration database. The merge operation itself conforms to the rules as described in the section *The HPX ini file format*.

1. Load all component shared libraries found in the directories specified by the property `hpx.component_path` and retrieve their default configuration information (see section *Loading components* for more details). This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
2. Load all files named `hpx.ini` in the directories referenced by the property `hpx.master_ini_path`. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
3. Load a file named `.hpx.ini` in the current working directory, e.g., the directory the application was invoked from.
4. Load a file referenced by the environment variable `HPX_INI`. This variable is expected to provide the full path name of the ini configuration file (if any).
5. Load a file named `/etc/hpx.ini`. This lookup is done on non-Windows systems only.
6. Load a file named `.hpx.ini` in the home directory of the current user, e.g., the directory referenced by the environment variable `HOME`.
7. Load a file named `.hpx.ini` in the directory referenced by the environment variable `PWD`.
8. Load the file specified on the command line using the option `--hpx:config`.
9. Load all properties specified on the command line using the option `--hpx:ini`. The properties will be added to the database in the same sequence as they are specified on the command line. The format for those options is, for instance, `--hpx:ini=hpx.default_stack_size=0x4000`. In addition to the explicit command line options, this will set the following properties as implied from other settings:
 - `hpx.parcel.address` and `hpx.parcel.port` as set by `--hpx:hpx`
 - `hpx.agas.address`, `hpx.agas.port` and `hpx.agas.service_mode` as set by `--hpx:agas`
 - `hpx.program_name` and `hpx.cmd_line` will be derived from the actual command line
 - **`hpx.os_threads` and `hpx.localities` as set by**
 `--hpx:threads` and `--hpx:localities`
 - `hpx.runtime_mode` will be derived from any explicit `--hpx:console`, `--hpx:worker`, or `--hpx:connect`, or it will be derived from other settings, such as `--hpx:node=0`, which implies `--hpx:console`.
10. Load files based on the pattern `*.ini` in all directories listed by the property `hpx.ini_path`. All files found during this search will be merged. The property `hpx.ini_path` can hold a list of directories separated by ':' (on Linux or Mac) or ';' (on Windows).
11. Load the file specified on the command line using the option `--hpx:app-config`. Note that this file will be merged as the content for a top level section `[application]`.

Note: Any changes made to the configuration database caused by one of the steps will influence the loading process for all subsequent steps. For instance, if one of the ini files loaded changes the property `hpx.ini_path`, this will influence the directories searched in step 9 as described above.

Important: The *HPX* core library will verify that all configuration settings specified on the command line (using the `--hpx:ini` option) will be checked for validity. That means that the library will accept only *known* configuration settings. This is to protect the user from unintentional typos while specifying those settings. This behavior can be overwritten by appending a '!' to the configuration key, thus forcing the setting to be entered into the configuration database. For instance: `--hpx:ini=hpx.foo! = 1`

If any of the environment variables or files listed above are not found, the corresponding loading step will be silently skipped.

Loading components

HPX relies on loading application specific components during the runtime of an application. Moreover, *HPX* comes with a set of preinstalled components supporting basic functionalities useful for almost every application. Any component in *HPX* is loaded from a shared library, where any of the shared libraries can contain more than one component type. During startup, *HPX* tries to locate all available components (e.g., their corresponding shared libraries) and creates an internal component registry for later use. This section describes the algorithm used by *HPX* to locate all relevant shared libraries on a system. As described, this algorithm is customizable by the configuration properties loaded from the ini files (see section *Loading INI files*).

Loading components is a two-stage process. First *HPX* tries to locate all component shared libraries, loads those, and generates a default configuration section in the internal configuration database for each component found. For each found component the following information is generated:

```
[hpx.components.<component_instance_name>]
name = <name_of_shared_library>
path = ${component_path}
enabled = ${hpx.components.load_external}
default = 1
```

The values in this section correspond to the expected configuration information for a component as described in the section *Built-in default configuration settings*.

In order to locate component shared libraries, *HPX* will try loading all shared libraries (files with the platform specific extension of a shared library, Linux: *.so, Windows: *.dll, MacOS: *.dylib found in the directory referenced by the ini property `hpx.component_path`).

This first step corresponds to step 1) during the process of filling the internal configuration database with default information as described in section *Loading INI files*.

After all of the configuration information has been loaded, *HPX* performs the second step in terms of loading components. During this step, *HPX* scans all existing configuration sections `[hpx.component.<some_component_instance_name>]` and instantiates a special factory object for each of the successfully located and loaded components. During the application's life time, these factory objects are responsible for creating new and discarding old instances of the component they are associated with. This step is performed after step 1) of the process of filling the internal configuration database with default information as described in section *Loading INI files*.

Application specific component example

This section assumes there is a simple application component that exposes one member function as a component action. The header file `app_server.hpp` declares the C++ type to be exposed as a component. This type has a member function `print_greeting()`, which is exposed as an action `print_greeting_action`. We assume the source files for this example are located in a directory referenced by `$APP_ROOT`:

```
// file: $APP_ROOT/app_server.hpp
#include <hpx/hpx.hpp>
#include <hpx/include/iostreams.hpp>

namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
    public:
        void print_greeting ()
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }

        // Component actions need to be declared, this also defines the
        // type 'print_greeting_action' representing the action.
        HPX_DEFINE_COMPONENT_ACTION(server, print_greeting, print_greeting_action);
    };
}

// Declare boilerplate code required for each of the component actions.
HPX_REGISTER_ACTION_DECLARATION(app::server::print_greeting_action);
```

The corresponding source file contains mainly macro invocations that define the boilerplate code needed for *HPX* to function properly:

```
// file: $APP_ROOT/app_server.cpp
#include "app_server.hpp"

// Define boilerplate required once per component module.
HPX_REGISTER_COMPONENT_MODULE();

// Define factory object associated with our component of type 'app::server'.
HPX_REGISTER_COMPONENT(app::server, app_server);

// Define boilerplate code required for each of the component actions. Use the
// same argument as used for HPX_REGISTER_ACTION_DECLARATION above.
HPX_REGISTER_ACTION(app::server::print_greeting_action);
```

The following gives an example of how the component can be used. Here, one instance of the `app::server` component is created on the current *locality* and the exposed action `print_greeting_action` is invoked using the global id of the newly created instance. Note that no special code is required to delete the component instance after it is not needed anymore. It will be deleted automatically when its last reference goes out of scope (shown in the example below at the closing brace of the block surrounding the code):

```
// file: $APP_ROOT/use_app_server_example.cpp
#include <hpx/hpx_init.hpp>
#include "app_server.hpp"

int hpx_main()
{
    {
        // Create an instance of the app_server component on the current locality.
        hpx::naming::id_type app_server_instance =
            hpx::create_component<app::server>(hpx::find_here());

        // Create an instance of the action 'print_greeting_action'.
        app::server::print_greeting_action print_greeting;

        // Invoke the action 'print_greeting' on the newly created component.
        print_greeting(app_server_instance);
    }
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::init(argc, argv);
}
```

In order to make sure that the application will be able to use the component `app::server`, special configuration information must be passed to *HPX*. The simplest way to allow *HPX* to ‘find’ the component is to provide special ini configuration files that add the necessary information to the internal configuration database. The component should have a special ini file containing the information specific to the component `app_server`.

```
# file: $APP_ROOT/app_server.ini
[hpx.components.app_server]
name = app_server
path = $APP_LOCATION/
```

Here, `$APP_LOCATION` is the directory where the (binary) component shared library is located. *HPX* will attempt to load the shared library from there. The section name `hpx.components.app_server` reflects the instance name of the component (`app_server` is an arbitrary, but unique name). The property value for `hpx.components.app_server.name` should be the same as used for the second argument to the macro `HPX_REGISTER_COMPONENT` above.

Additionally, a file `.hpx.ini`, which could be located in the current working directory (see step 3 as described in the section *Loading INI files*), can be used to add to the ini search path for components:

```
# file: $PWD/.hpx.ini
[hpx]
ini_path = ${hpx.ini_path}:$APP_ROOT/
```

This assumes that the above ini file specific to the component is located in the directory `$APP_ROOT`.

Note: It is possible to reference the defined property from inside its value. *HPX* will gracefully use the previous value of `hpx.ini_path` for the reference on the right hand side and assign the overall (now expanded) value to the property.

Logging

HPX uses a sophisticated logging framework, allowing users to follow in detail what operations have been performed inside the *HPX* library in what sequence. This information proves to be very useful for diagnosing problems or just for improving the understanding of what is happening in *HPX* as a consequence of invoking *HPX* API functionality.

Default logging

Enabling default logging is a simple process. The detailed description in the remainder of this section explains different ways to customize the defaults. Default logging can be enabled by using one of the following:

- A command line switch `--hpx:debug-hpx-log`, which will enable logging to the console terminal.
- The command line switch `--hpx:debug-hpx-log=<filename>`, which enables logging to a given file `<filename>`.
- Setting an environment variable `HPX_LOGLEVEL=<loglevel>` while running the *HPX* application. In this case `<loglevel>` should be a number between (or equal to) 1 and 5 where 1 means minimal logging and 5 causes all available messages to be logged. When setting the environment variable, the logs will be written to a file named `hpx.<PID>.lo` in the current working directory, where `<PID>` is the process id of the console instance of the application.

Customizing logging

Generally, logging can be customized either using environment variable settings or using by an ini configuration file. Logging is generated in several categories, each of which can be customized independently. All customizable configuration parameters have reasonable defaults, allowing for the use of logging without any additional configuration effort. The following table lists the available categories.

Table 2.5: Logging categories

Category	Category shortcut	Information to be generated	Environment variable
General	None	Logging information generated by different subsystems of <i>HPX</i> , such as thread-manager, parcel layer, LCOs, etc.	<code>HPX_LOGLEVEL</code>
<i>AGAS</i>	<code>AGAS</code>	Logging output generated by the <i>AGAS</i> subsystem	<code>HPX_AGAS_LOGLEVEL</code>
Application	<code>APP</code>	Logging generated by applications.	<code>HPX_APP_LOGLEVEL</code>

By default, all logging output is redirected to the console instance of an application, where it is collected and written to a file, one file for each logging category.

Each logging category can be customized at two levels. The parameters for each are stored in the ini configuration sections `hpx.logging.CATEGORY` and `hpx.logging.console.CATEGORY` (where `CATEGORY` is the category shortcut as listed in the table above). The former influences logging at the source *locality* and the latter modifies the logging behaviour for each of the categories at the console instance of an application.

Levels

All *HPX* logging output has seven different logging levels. These levels can be set explicitly or through environment variables in the main *HPX* ini file as shown below. The logging levels and their associated integral values are shown in the table below, ordered from most verbose to least verbose. By default, all *HPX* logs are set to 0, e.g., all logging output is disabled by default.

Table 2.6: Logging levels

Logging level	Integral value
<debug>	5
<info>	4
<warning>	3
<error>	2
<fatal>	1
No logging	0

Tip: The easiest way to enable logging output is to set the environment variable corresponding to the logging category to an integral value as described in the table above. For instance, setting `HPX_LOGLEVEL=5` will enable full logging output for the general category. Please note that the syntax and means of setting environment variables varies between operating systems.

Configuration

Logs will be saved to destinations as configured by the user. By default, logging output is saved on the console instance of an application to `hpx.<CATEGORY>.<PID>.lo` (where `CATEGORY` and `PID` are placeholders for the category shortcut and the OS process id). The output for the general logging category is saved to `hpx.<PID>.log`. The default settings for the general logging category are shown here (the syntax is described in the section *The HPX ini file format*):

```
[hpx.logging]
level = ${HPX_LOGLEVEL:0}
destination = ${HPX_LOGDESTINATION:console}
format = ${HPX_LOGFORMAT:(T%locality%/%hpxthread%.%hpxphase%/%hpxcomponent%) P%parentloc
↪ %/%hpxparent%.%hpxparentphase% %time%($hh:$mm.$ss.$mili) [%idx%]|\\n}
```

The logging level is taken from the environment variable `HPX_LOGLEVEL` and defaults to zero, e.g., no logging. The default logging destination is read from the environment variable `HPX_LOGDESTINATION`. On any of the localities it defaults to `console`, which redirects all generated logging output to the console instance of an application. The following table lists the possible destinations for any logging output. It is possible to specify more than one destination separated by whitespace.

Table 2.7: Logging destinations

Logging destination	Description
<code>file(<filename>)</code>	Directs all output to a file with the given <code><filename></code> .
<code>cout</code>	Directs all output to the local standard output of the application instance on this <i>locality</i> .
<code>cerr</code>	Directs all output to the local standard error output of the application instance on this <i>locality</i> .
<code>console</code>	Directs all output to the console instance of the application. The console instance has its logging destinations configured separately.
<code>android_log</code>	Directs all output to the (Android) system log (available on Android systems only).

The logging format is read from the environment variable `HPX_LOGFORMAT`, and it defaults to a complex format description. This format consists of several placeholder fields (for instance `%locality%`), which will be replaced by concrete values when the logging output is generated. All other information is transferred verbatim to the output. The table below describes the available field placeholders. The separator character `|` separates the logging message prefix formatted as shown and the actual log message which will replace the separator.

Table 2.8: Available field placeholders

Name	Description
<i>locality</i>	The id of the <i>locality</i> on which the logging message was generated.
<i>hpxthread</i>	The id of the <i>HPX</i> thread generating this logging output.
<i>hpxphase</i>	The phase ⁷⁴ of the <i>HPX</i> thread generating this logging output.
<i>hpxcomponent</i>	The local virtual address of the component which the current <i>HPX</i> thread is accessing.
<i>parentloc</i>	The id of the <i>locality</i> where the <i>HPX</i> thread was running that initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>hpxparent</i>	The id of the <i>HPX</i> thread that initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>hpxparentphase</i>	The phase of the <i>HPX</i> thread when it initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>time</i>	The time stamp for this logging outputline as generated by the source <i>locality</i> .
<i>idx</i>	The sequence number of the logging output line as generated on the source <i>locality</i> .
<i>osthread</i>	The sequence number of the OS thread that executes the current <i>HPX</i> thread.

Note: Not all of the field placeholder may be expanded for all generated logging output. If no value is available for a particular field, it is replaced with a sequence of '-' characters.

Here is an example line from a logging output generated by one of the *HPX* examples (please note that this is generated on a single line, without a line break):

```
(T000000000/0000000002d46f90.01/00000000009ebc10) P-----/0000000002d46f80.02 17:49.37.
↪320 [0000000000000004d]
    <info> [RT] successfully created component {0000000100ff0001, 0000000000030002} of
↪type: component_barrier[7(3)]
```

The default settings for the general logging category on the console is shown here:

```
[hpx.logging.console]
level = ${HPX_LOGLEVEL:[hpx.logging.level]}
destination = ${HPX_CONSOLE_LOGDESTINATION:file(hpx.${system.pid}.log)}
format = ${HPX_CONSOLE_LOGFORMAT:|}
```

These settings define how the logging is customized once the logging output is received by the console instance of an application. The logging level is read from the environment variable `HPX_LOGLEVEL` (as set for the console instance of the application). The level defaults to the same values as the corresponding settings in the general logging configuration shown before. The destination on the console instance is set to be a file that's name is generated based on its OS process id. Setting the environment variable `HPX_CONSOLE_LOGDESTINATION` allows customization of the naming scheme for the output file. The logging format is set to leave the original logging output unchanged, as received from one of the localities the application runs on.

⁷⁴ The phase of a *HPX*-thread counts how often this thread has been activated.

HPX Command Line Options

The predefined command line options for any application using `hpx::init` are described in the following subsections.

HPX options (allowed on command line only)

--hpx:help

Print out program usage (default: this message). Possible values: `full` (additionally prints options from components).

--hpx:version

Print out *HPX* version and copyright information.

--hpx:info

Print out *HPX* configuration information.

--hpx:options-file arg

Specify a file containing command line options (alternatively: `@filepath`).

HPX options (additionally allowed in an options file)

--hpx:worker

Run this instance in worker mode.

--hpx:console

Run this instance in console mode.

--hpx:connect

Run this instance in worker mode, but connecting late.

--hpx:run-agas-server

Run *AGAS* server as part of this runtime instance.

--hpx:run-hpx-main

Run the `hpx_main` function, regardless of *locality* mode.

--hpx:hpx arg

The IP address the *HPX* parcellport is listening on, expected format: `address:port` (default: `127.0.0.1:7910`).

--hpx:agas arg

The IP address the *AGAS* root server is running on, expected format: `address:port` (default: `127.0.0.1:7910`).

--hpx:run-agas-server-only

Run only the *AGAS* server.

--hpx:nodefile arg

The file name of a node file to use (list of nodes, one node name per line and core).

--hpx:nodes arg

The (space separated) list of the nodes to use (usually this is extracted from a node file).

--hpx:endnodes

This can be used to end the list of nodes specified using the option `--hpx:nodes`.

--hpx:ifsuffix arg

Suffix to append to host names in order to resolve them to the proper network interconnect.

--hpx:ifprefix arg

Prefix to prepend to host names in order to resolve them to the proper network interconnect.

--hpx:iftransform arg

Sed-style search and replace (s/search/replace/) used to transform host names to the proper network interconnect.

--hpx:force_ipv4

Network hostnames will be resolved to ipv4 addresses instead of using the first resolved endpoint. This is especially useful on Windows where the local hostname will resolve to an ipv6 address while remote network hostnames are commonly resolved to ipv4 addresses.

--hpx:localities arg

The number of localities to wait for at application startup (default: 1).

--hpx:node arg

Number of the node this *locality* is run on (must be unique).

--hpx:ignore-batch-env

Ignore batch environment variables.

--hpx:expect-connecting-localities

This *locality* expects other localities to dynamically connect (this is implied if the number of initial localities is larger than 1).

--hpx:pu-offset

The first processing unit this instance of *HPX* should be run on (default: 0).

--hpx:pu-step

The step between used processing unit numbers for this instance of *HPX* (default: 1).

--hpx:threads arg

The number of operating system threads to spawn for this *HPX locality*. Possible values are: numeric values 1, 2, 3 and so on, *all* (which spawns one thread per processing unit, includes hyperthreads), or *cores* (which spawns one thread per core) (default: *cores*).

--hpx:cores arg

The number of cores to utilize for this *HPX locality* (default: *all*, i.e., the number of cores is based on the number of threads *--hpx:threads* assuming *--hpx:bind=compact*).

--hpx:affinity arg

The affinity domain the OS threads will be confined to, possible values: *pu*, *core*, *numa*, *machine* (default: *pu*).

--hpx:bind arg

he detailed affinity description for the OS threads, see *More details about HPX command line options* for a detailed description of possible values. Do not use with *--hpx:pu-step*, *--hpx:pu-offset* or *--hpx:affinity* options. Implies *--hpx:numa-sensitive* (*--hpx:bind=none*) disables defining thread affinities).

--hpx:use-process-mask

Use the process mask to restrict available hardware resources (implies *--hpx:ignore-batch-env*).

--hpx:print-bind

Print to the console the bit masks calculated from the arguments specified to all *--hpx:bind* options.

--hpx:queuing arg

The queue scheduling policy to use. Options are local, local-priority-fifo, local-priority-lifo, static, static-priority, abp-priority-fifo, local-workrequesting-fifo, local-workrequesting-lifo, local-workrequesting-mc, and abp-priority-lifo (default: local-priority-fifo).

--hpx:high-priority-threads arg

The number of operating system threads maintaining a high priority queue (default: number of OS threads), valid for `--hpx:queuing=abp-priority`, `--hpx:queuingstatic-priority` and `--hpx:queuinglocal-priority` only.

--hpx:numa-sensitive

Makes the scheduler NUMA sensitive.

HPX configuration options

--hpx:app-config arg

Load the specified application configuration (ini) file.

--hpx:config arg

Load the specified *HPX* configuration (ini) file.

--hpx:ini arg

Add a configuration definition to the default runtime configuration.

--hpx:exit

Exit after configuring the runtime.

HPX debugging options

--hpx:list-symbolic-names

List all registered symbolic names after startup.

--hpx:list-component-types

List all dynamic component types after startup.

--hpx:dump-config-initial

Print the initial runtime configuration.

--hpx:dump-config

Print the final runtime configuration.

--hpx:debug-hpx-log [arg]

Enable all messages on the *HPX* log channel and send all *HPX* logs to the target destination (default: cout).

--hpx:debug-agas-log [arg]

Enable all messages on the *AGAS* log channel and send all *AGAS* logs to the target destination (default: cout).

--hpx:debug-parcel-log [arg]

Enable all messages on the parcel transport log channel and send all parcel transport logs to the target destination (default: cout).

--hpx:debug-timing-log [arg]

Enable all messages on the timing log channel and send all timing logs to the target destination (default: cout).

--hpx:debug-app-log [arg]

Enable all messages on the application log channel and send all application logs to the target destination (default: cout).

--hpx:debug-clp

Debug command line processing.

--hpx:attach-debugger arg

Wait for a debugger to be attached, possible arg values: `startup` or `exception` (default: `startup`)

HPX options related to performance counters**--hpx:print-counter**

Print the specified performance counter either repeatedly and/or at the times specified by `--hpx:print-counter-at` (see also option `--hpx:print-counter-interval`).

--hpx:print-counter-reset

Print the specified performance counter either repeatedly and/or at the times specified by `--hpx:print-counter-at`. Reset the counter after the value is queried (see also option `--hpx:print-counter-interval`).

--hpx:print-counter-interval

Print the performance counter(s) specified with `--hpx:print-counter` repeatedly after the time interval (specified in milliseconds), (default: 0, which means print once at shutdown).

--hpx:print-counter-destination

Print the performance counter(s) specified with `--hpx:print-counter` to the given file (default: console).

--hpx:list-counters

List the names of all registered performance counters, possible values: `minimal` (prints counter name skeletons), `full` (prints all available counter names).

--hpx:list-counter-infos

List the description of all registered performance counters, possible values: `minimal` (prints info for counter name skeletons), `full` (prints all available counter infos).

--hpx:print-counter-format

Print the performance counter(s) specified with `--hpx:print-counter`. Possible formats in CSV include a format with a header or without any header (see option `--hpx:no-csv-header`). Possible values: `csv` (prints counter values in CSV format with full names as header), `csv-short` (prints counter values in CSV format with short names provided with `--hpx:print-counter` as `--hpx:print-counter shortname`, `full-countername`

--hpx:no-csv-header

Print the performance counter(s) specified with `--hpx:print-counter` and `csv` or `csv-short` format specified with `--hpx:print-counter-format` without header.

--hpx:print-counter-at arg

Print the performance counter(s) specified with `--hpx:print-counter` (or `--hpx:print-counter-reset`) at the given point in time, possible argument values: `startup`, `shutdown` (default), `noshutdown`.

--hpx:reset-counters

Reset all performance counter(s) specified with `--hpx:print-counter` after they have been evaluated.

--hpx:print-counters-locally

Each *locality* prints only its own local counters. If this is used with `--hpx:print-counter-destination=<file>`, the code will append a `".<locality_id>"` to the file name in order to avoid clashes between localities.

Command line argument shortcuts

Additionally, the following shortcuts are available from every *HPX* application.

Table 2.9: Predefined command line option shortcuts

Shortcut option	Equivalent long option
-a	--hpx:agas
-c	--hpx:console
-h	--hpx:help
-I	--hpx:ini
-l	--hpx:localities
-p	--hpx:app-config
-q	--hpx:queuing
-r	--hpx:run-agas-server
-t	--hpx:threads
-v	--hpx:version
-w	--hpx:worker
-x	--hpx:hpx
-0	--hpx:node=0
-1	--hpx:node=1
-2	--hpx:node=2
-3	--hpx:node=3
-4	--hpx:node=4
-5	--hpx:node=5
-6	--hpx:node=6
-7	--hpx:node=7
-8	--hpx:node=8
-9	--hpx:node=9

Note: The short options listed above are disabled by default if the application is built using `#include <hpx/hpx_main.hpp>`. See *Re-use the main() function as the main HPX entry point* for more information. The rationale behind this is that in this case the user's application may handle its own command line options, since *HPX* passes all unknown options to `main()`. Short options like `-t` are prone to create ambiguities regarding what the application will support. Hence, the user should instead rely on the corresponding long options like `--hpx:threads` in such a case.

It is possible to define your own shortcut options. In fact, all of the shortcuts listed above are pre-defined using the technique described here. Also, it is possible to redefine any of the pre-defined shortcuts to expand differently as well.

Shortcut options are obtained from the internal configuration database. They are stored as key-value properties in a special properties section named `hpx.commandline`. You can define your own shortcuts by adding the corresponding definitions to one of the ini configuration files as described in the section *Configuring HPX applications*. For instance, in order to define a command line shortcut `--p`, which should expand to `-hpx:print-counter`, the following configuration information needs to be added to one of the ini configuration files:

```
[hpx.commandline.aliases]
--pc = --hpx:print-counter
```

Note: Any arguments for shortcut options passed on the command line are retained and passed as arguments to the corresponding expanded option. For instance, given the definition above, the command line option:

```
--pc=/threads{locality#0/total}/count/cumulative
```

would be expanded to:

```
--hpx:print-counter=/threads{locality#0/total}/count/cumulative
```

Important: Any shortcut option should either start with a single '-' or with two '--' characters. Shortcuts starting with a single '-' are interpreted as short options (i.e., everything after the first character following the '-' is treated as the argument). Shortcuts starting with '--' are interpreted as long options. No other shortcut formats are supported.

Specifying options for single localities only

For runs involving more than one *locality*, it is sometimes desirable to supply specific command line options to single localities only. When the *HPX* application is launched using a scheduler (like PBS; for more details see section *How to use HPX applications with PBS*), specifying dedicated command line options for single localities may be desirable. For this reason all of the command line options that have the general format `--hpx:<some_key>` can be used in a more general form: `--hpx:<N>:<some_key>`, where `<N>` is the number of the *locality* this command line option will be applied to; all other localities will simply ignore the option. For instance, the following PBS script passes the option `--hpx:pu-offset=4` to the *locality* '1' only.

```
#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/.packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:1:pu-offset=4 --hpx:nodes=`cat $PBS_NODEFILE`
```

Caution: If the first application specific argument (inside `$APP_OPTIONS`) is a non-option (i.e., does not start with a - or a --), then it must be placed before the option `--hpx:nodes`, which, in this case, should be the last option on the command line.

Alternatively, use the option `--hpx:endnodes` to explicitly mark the end of the list of node names:

```
$ pbsdsh -u $APP_PATH --hpx:1:pu-offset=4 --hpx:nodes=`cat $PBS_NODEFILE` --
↪hpx:endnodes $APP_OPTIONS
```

More details about *HPX* command line options

This section documents the following list of the command line options in more detail:

- The command line option `--hpx:bind`

The command line option `--hpx:bind`

This command line option allows one to specify the required affinity of the *HPX* worker threads to the underlying processing units. As a result the worker threads will run only on the processing units identified by the corresponding bind specification. The affinity settings are to be specified using `--hpx:bind=<BINDINGS>`, where `<BINDINGS>` have to be formatted as described below.

In addition to the syntax described below, one can use `--hpx:bind=none` to disable all binding of any threads to a particular core. This is mostly supported for debugging purposes.

The specified affinities refer to specific regions within a machine hardware topology. In order to understand the hardware topology of a particular machine, it may be useful to run the `lstopo` tool, which is part of Portable Hardware Locality (HWLOC), to see the reported topology tree. Seeing and understanding a topology tree will definitely help in understanding the concepts that are discussed below.

Affinities can be specified using hwloc tuples. Tuples of hwloc *objects* and associated *indexes* can be specified in the form `object:index`, `object:index-index` or `object:index,...,index`. Hwloc objects represent types of mapped items in a topology tree. Possible values for objects are `socket`, `numanode`, `core` and `pu` (processing unit). Indexes are non-negative integers that specify a unique physical object in a topology tree using its logical sequence number.

Chaining multiple tuples together in the more general form `object1:index1[.object2:index2[...]]` is permissible. While the first tuple's object may appear anywhere in the topology, the *N*th tuple's object must have a shallower topology depth than the (*N*+1)th tuple's object. Put simply: as you move right in a tuple chain, objects must go deeper in the topology tree. Indexes specified in chained tuples are relative to the scope of the parent object. For example, `socket:0.core:1` refers to the second core in the first socket (all indices are zero based).

Multiple affinities can be specified using several `--hpx:bind` command line options or by appending several affinities separated by a `' ; '`. By default, if multiple affinities are specified, they are added.

"all" is a special affinity consisting in the entire current topology.

Note: All "names" in an affinity specification, such as `thread`, `socket`, `numanode`, `pu` or `all`, can be abbreviated. Thus, the affinity specification `threads:0-3=socket:0.core:1.pu:1` is fully equivalent to its shortened form `t:0-3=s:0.c:1.p:1`.

Here is a full grammar describing the possible format of mappings:

```
mappings      ::= distribution | mapping (";" mapping)*
distribution  ::= "compact" | "scatter" | "balanced" | "numa-balanced"
mapping       ::= thread_spec "=" pu_specs
thread_spec   ::= "thread:" range_specs
pu_specs      ::= pu_spec ( "." pu_spec ) *
pu_spec       ::= type ":" range_specs | "~" pu_spec
range_specs   ::= range_spec ( "," range_spec ) *
range_spec    ::= int | int "-" int | "all"
type          ::= "socket" | "numanode" | "core" | "pu"
```


The following example assumes a system with at least 4 cores, where each core has more than 1 processing unit (hardware threads). Running `hello_world_distributed` with 4 OS threads (on 4 processing units), where each of those threads is bound to the first processing unit of each of the cores, can be achieved by invoking:

```
$ hello_world_distributed -t4 --hpx:bind=thread:0-3=core:0-3.pu:0
```

Here, `thread:0-3` specifies the OS threads used to define affinity bindings, and `core:0-3.pu:0` defines that for each of the cores (`core:0-3`) only their first processing unit `pu:0` should be used.

Note: The command line option `--hpx:print-bind` can be used to print the bitmasks generated from the affinity mappings as specified with `--hpx:bind`. For instance, on a system with hyperthreading enabled (i.e. 2 processing units per core), the command line:

```
$ hello_world_distributed -t4 --hpx:bind=thread:0-3=core:0-3.pu:0 --hpx:print-bind
```

will cause this output to be printed:

```
0: PU L#0(P#0), Core L#0, Socket L#0, Node L#0(P#0)
1: PU L#2(P#2), Core L#1, Socket L#0, Node L#0(P#0)
2: PU L#4(P#4), Core L#2, Socket L#0, Node L#0(P#0)
3: PU L#6(P#6), Core L#3, Socket L#0, Node L#0(P#0)
```

where each bit in the bitmasks corresponds to a processing unit the listed worker thread will be bound to run on.

The difference between the four possible predefined distribution schemes (`compact`, `scatter`, `balanced` and `numa-balanced`) is best explained with an example. Imagine that we have a system with 4 cores and 4 hardware threads per core on 2 sockets. If we place 8 threads the assignments produced by the `compact`, `scatter`, `balanced` and `numa-balanced` types are shown in the figure below. Notice that `compact` does not fully utilize all the cores in the system. For this reason it is recommended that applications are run using the `scatter` or `balanced/numa-balanced` options in most cases.

In addition to the predefined distributions it is possible to restrict the resources used by *HPX* to the process CPU mask. The CPU mask is typically set by e.g. `MPI`⁷³ and batch environments. Using the command line option `--hpx:use-process-mask` makes *HPX* act as if only the processing units in the CPU mask are available for use by *HPX*. The number of threads is automatically determined from the CPU mask. The number of threads can still be changed manually using this option, but only to a number less than or equal to the number of processing units in the CPU mask. The option `--hpx:print-bind` is useful in conjunction with `--hpx:use-process-mask` to make sure threads are placed as expected.

2.4.11 Writing single-node applications

Being a C++ Standard Library for Concurrency and Parallelism, *HPX* implements all of the corresponding facilities as defined by the C++ Standard but also those which are proposed as part of the ongoing C++ standardization process. This section focuses on the features available in *HPX* for parallel and concurrent computation on a single node, although many of the features presented here are also implemented to work in the distributed case.

⁷³ https://en.wikipedia.org/wiki/Message_Passing_Interface




Fig. 2.7: Schematic of thread affinity type distributions.

Synchronization objects

The following objects are providing synchronization for *HPX* applications:

1. *Barrier*
2. *Condition variable*
3. *Latch*
4. *Mutex*
5. *Shared mutex*
6. *Semaphore*
7. *Composable guards*

Barrier

Barriers are used for synchronizing multiple threads. They provide a synchronization point, where all threads must wait until they have all reached the barrier, before they can continue execution. This allows multiple threads to work together to solve a common task, and ensures that no thread starts working on the next task until all threads have completed the current task. This ensures that all threads are in the same state before performing any further operations, leading to a more consistent and accurate computation.

Unlike latches, barriers are reusable: once the participating threads are released from a barrier's synchronization point, they can re-use the same barrier. It is thus useful for managing repeated tasks, or phases of a larger task, that are handled by multiple threads. The code below shows how barriers can be used to synchronize two threads:

```
#include <hpx/barrier.hpp>
#include <hpx/future.hpp>
#include <hpx/init.hpp>

#include <iostream>

int hpx_main()
{
    hpx::barrier b(2);

    hpx::future<void> f1 = hpx::async([&b]() {
        std::cout << "Thread 1 started." << std::endl;
        // Do some computation
        b.arrive_and_wait();
        // Continue with next task
        std::cout << "Thread 1 finished." << std::endl;
    });

    hpx::future<void> f2 = hpx::async([&b]() {
        std::cout << "Thread 2 started." << std::endl;
        // Do some computation
        b.arrive_and_wait();
        // Continue with next task
        std::cout << "Thread 2 finished." << std::endl;
    });
}
```

(continues on next page)

(continued from previous page)

```

    f1.get();
    f2.get();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

In this example, two `hpx::future` objects are created, each representing a separate thread of execution. The `wait` function of the `hpx::barrier` object is called by each thread. The threads will wait at the barrier until both have reached it. Once both threads have reached the barrier, they can continue with their next task.

Condition variable

A *condition variable* is a synchronization primitive in *HPX* that allows a thread to wait for a specific condition to be satisfied before continuing execution. It is typically used in conjunction with a mutex or a lock to protect shared data that is being modified by multiple threads. Hence, it blocks one or more threads until another thread both modifies a shared variable (the condition) and notifies the `condition_variable`. The code below shows how two threads modifying the shared variable data can be synchronized using the `condition_variable`:

```

#include <hpx/condition_variable.hpp>
#include <hpx/init.hpp>
#include <hpx/mutex.hpp>
#include <hpx/thread.hpp>

#include <iostream>
#include <string>

hpx::condition_variable cv;
hpx::mutex m;
std::string data;
bool ready = false;
bool processed = false;

void worker_thread()
{
    // Wait until the main thread signals that data is ready
    std::unique_lock<hpx::mutex> lk(m);
    cv.wait(lk, [] { return ready; });

    // Access the shared resource
    std::cout << "Worker thread: Processing data...\n";
    data = "Test data after";

    // Send data back to the main thread
    processed = true;
    std::cout << "Worker thread: data processing is complete\n";
}

```

(continues on next page)

(continued from previous page)

```

    // Manual unlocking is done before notifying, to avoid waking up
    // the waiting thread only to block again
    lk.unlock();
    cv.notify_one();
}

int hpx_main()
{
    hpx::thread worker(worker_thread);

    // Do some work
    std::cout << "Main thread: Preparing data...\n";
    data = "Test data before";
    hpx::this_thread::sleep_for(std::chrono::seconds(1));
    std::cout << "Main thread: Data before processing = " << data << '\n';

    // Signal that data is ready and send data to worker thread
    {
        std::lock_guard<hpx::mutex> lk(m);
        ready = true;
        std::cout << "Main thread: Data is ready...\n";
    }
    cv.notify_one();

    // Wait for the worker thread to finish
    {
        std::unique_lock<hpx::mutex> lk(m);
        cv.wait(lk, [] { return processed; });
    }
    std::cout << "Main thread: Data after processing = " << data << '\n';
    worker.join();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

The main thread of the code above starts by creating a worker thread and preparing the shared variable data. Once the data is ready, the main thread acquires a lock on the mutex `m` using `std::lock_guard<hpx::mutex> lk(m)` and sets the ready flag to true, then signals the worker thread to start processing by calling `cv.notify_one()`. The `cv.wait()` call in the main thread then blocks until the worker thread signals that processing is complete by setting the processed flag.

The worker thread starts by acquiring a lock on the mutex `m` to ensure exclusive access to the shared data. The `cv.wait()` call blocks the thread until the ready flag is set by the main thread. Once this is true, the worker thread accesses the shared data resource, processes it, and sets the processed flag to indicate completion. The mutex is then unlocked using `lk.unlock()` and the `cv.notify_one()` call signals the main thread to resume execution. Finally, the new data is printed by the main thread to the console.

Latch

A *latch* is a downward counter which can be used to synchronize threads. The value of the counter is initialized on creation. Threads may block on the latch until the counter is decremented to zero. There is no possibility to increase or reset the counter, which makes the latch a single-use barrier.

In *HPX*, a latch is implemented as a counting semaphore, which can be initialized with a specific count value and decremented each time a thread reaches the latch. When the count value reaches zero, all waiting threads are unblocked and allowed to continue execution. The code below shows how latch can be used to synchronize 16 threads:

```
std::ptrdiff_t num_threads = 16;

/////////////////////////////////////////////////////////////////
void wait_for_latch(hpx::latch& l)
{
    l.arrive_and_wait();
}

/////////////////////////////////////////////////////////////////
int hpx_main(hpx::program_options::variables_map& vm)
{
    num_threads = vm["num-threads"].as<std::ptrdiff_t>();

    hpx::latch l(num_threads + 1);

    std::vector<hpx::future<void>> results;
    for (std::ptrdiff_t i = 0; i != num_threads; ++i)
        results.push_back(hpx::async(&wait_for_latch, std::ref(l)));

    // Wait for all threads to reach this point.
    l.arrive_and_wait();

    hpx::wait_all(results);

    return hpx::local::finalize();
}
```

In the above code, the `hpx_main` function creates a latch object `l` with a count of `num_threads + 1` and `num_threads` number of threads using `hpx::async`. These threads call the `wait_for_latch` function and pass the reference to the latch object. In the `wait_for_latch` function, the thread calls the `arrive_and_wait` method on the latch, which decrements the count of the latch and causes the thread to wait until the count reaches zero. Finally, the main thread waits for all the threads to arrive at the latch by calling the `arrive_and_wait` method and then waits for all the threads to finish by calling the `hpx::wait_all` method.

Mutex

A *mutex* (short for “mutual exclusion”) is a synchronization primitive in *HPX* used to control access to a shared resource, ensuring that only one thread can access it at a time. A mutex is used to protect data structures from race conditions and other synchronization-related issues. When a thread acquires a mutex, other threads that try to access the same resource will be blocked until the mutex is released. The code below shows the basic use of mutexes:

```
#include <hpx/future.hpp>
#include <hpx/init.hpp>
#include <hpx/mutex.hpp>

#include <iostream>

int hpx_main()
{
    hpx::mutex m;

    hpx::future<void> f1 = hpx::async([&m]() {
        std::scoped_lock sl(m);
        std::cout << "Thread 1 acquired the mutex" << std::endl;
    });

    hpx::future<void> f2 = hpx::async([&m]() {
        std::scoped_lock sl(m);
        std::cout << "Thread 2 acquired the mutex" << std::endl;
    });

    hpx::wait_all(f1, f2);

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

In this example, two *HPX* threads created using `hpx::async` are acquiring a `hpx::mutex m`. `std::scoped_lock sl(m)` is used to take ownership of the given mutex `m`. When control leaves the scope in which the `scoped_lock` object was created, the `scoped_lock` is destructed and the mutex is released.

Attention: A common way to acquire and release mutexes is by using the function `m.lock()` before accessing the shared resource, and `m.unlock()` called after the access is complete. However, these functions may lead to deadlocks in case of exception(s). That is, if an exception happens when the mutex is locked then the code that unlocks the mutex will never be executed, the lock will remain held by the thread that acquired it, and other threads will be unable to access the shared resource. This can cause a deadlock if the other threads are also waiting to acquire the same lock. For this reason, we suggest you use `std::scoped_lock`, which prevents this issue by releasing the lock when control leaves the scope in which the `scoped_lock` object was created.

Shared mutex

A *shared mutex* is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In contrast to other mutex types which facilitate exclusive access, a `shared_mutex` has two levels of access:

- *Exclusive access* prevents any other thread from acquiring the mutex, just as with the normal mutex. It does not matter if the other thread tries to acquire shared or exclusive access.
- *Shared access* allows multiple threads to acquire the mutex, but all of them only in shared mode. Exclusive access is not granted until all of the previous shared holders have returned the mutex (typically, as long as an exclusive request is waiting, new shared ones are queued to be granted after the exclusive access).

Shared mutexes are especially useful when shared data can be safely read by any number of threads simultaneously, but a thread may only write the same data when no other thread is reading or writing at the same time. A typical scenario is a database: The data can be read simultaneously by different threads with no problem. However, modification of the database is critical: if some threads read data while another one is writing, the threads reading may receive inconsistent data. Hence, while a thread is writing, reading should not be allowed. After writing is complete, reads can occur simultaneously again. The code below shows how `shared_mutex` can be used to synchronize reads and writes:

```
int const writers = 3;
int const readers = 3;
int const cycles = 10;

using std::chrono::milliseconds;

int hpx_main()
{
    std::vector<hpx::thread> threads;
    std::atomic<bool> ready(false);
    hpx::shared_mutex stm;

    for (int i = 0; i < writers; ++i)
    {
        threads.emplace_back([&ready, &stm, i] {
            std::mt19937 urng(static_cast<std::uint32_t>(std::time(nullptr)));
            std::uniform_int_distribution<int> dist(1, 1000);

            while (!ready)
            { /** wait... **/
            }

            for (int j = 0; j < cycles; ++j)
            {
                // scope of unique_lock
                {
                    std::unique_lock<hpx::shared_mutex> ul(stm);

                    std::cout << "^^^ Writer " << i << " starting..."
                                << std::endl;
                    hpx::this_thread::sleep_for(milliseconds(dist(urng)));
                    std::cout << "vvv Writer " << i << " finished."
                                << std::endl;
                }
            }
        });
    }
}
```

(continues on next page)

(continued from previous page)

```

        hpx::this_thread::sleep_for(milliseconds(dist(urng)));
    }
    });
}

for (int i = 0; i < readers; ++i)
{
    int k = writers + i;
    threads.emplace_back([&ready, &stm, k, i] {
        HPX_UNUSED(k);
        std::mt19937 urng(static_cast<std::uint32_t>(std::time(nullptr)));
        std::uniform_int_distribution<int> dist(1, 1000);

        while (!ready)
        { /** wait... */
        }

        for (int j = 0; j < cycles; ++j)
        {
            // scope of shared_lock
            {
                std::shared_lock<hpx::shared_mutex> sl(stm);

                std::cout << "Reader " << i << " starting..." << std::endl;
                hpx::this_thread::sleep_for(milliseconds(dist(urng)));
                std::cout << "Reader " << i << " finished." << std::endl;
            }
            hpx::this_thread::sleep_for(milliseconds(dist(urng)));
        }
    });
}

ready = true;
for (auto& t : threads)
    t.join();

return hpx::local::finalize();
}

```

The above code creates writers and readers threads, each of which will perform cycles of operations. Both the writer and reader threads use the `hpx::shared_mutex` object `stm` to synchronize access to a shared resource.

- For the writer threads, a `unique_lock` on the shared mutex is acquired before each write operation and is released after control leaves the scope in which the `unique_lock` object was created.
- For the reader threads, a `shared_lock` on the shared mutex is acquired before each read operation and is released after control leaves the scope in which the `shared_lock` object was created.

Before each operation, both the reader and writer threads sleep for a random time period, which is generated using a random number generator. The random time period simulates the processing time of the operation.

Semaphore

Semaphores are a synchronization mechanism used to control concurrent access to a shared resource. The two types of semaphores are:

- counting semaphore: it has a counter that is bigger than zero. The counter is initialized in the constructor. Acquiring the semaphore decreases the counter and releasing the semaphore increases the counter. If a thread tries to acquire the semaphore when the counter is zero, the thread will block until another thread increments the counter by releasing the semaphore. Unlike `hpx::mutex`, an `hpx::counting_semaphore` is not bound to a thread, which means that the acquire and release call of a semaphore can happen on different threads.
- binary semaphore: it is an alias for a `hpx::counting_semaphore<1>`. In this case, the least maximal value is 1. `hpx::binary_semaphore` can be used to implement locks.

```
#include <hpx/init.hpp>
#include <hpx/semaphore.hpp>
#include <hpx/thread.hpp>

#include <iostream>

// initialize the semaphore with a count of 3
hpx::counting_semaphore<> semaphore(3);

void worker()
{
    semaphore.acquire();    // decrement the semaphore's count
    std::cout << "Entering critical section" << std::endl;
    hpx::this_thread::sleep_for(std::chrono::seconds(1));
    semaphore.release();    // increment the semaphore's count
    std::cout << "Exiting critical section" << std::endl;
}

int hpx_main()
{
    hpx::thread t1(worker);
    hpx::thread t2(worker);
    hpx::thread t3(worker);
    hpx::thread t4(worker);
    hpx::thread t5(worker);

    t1.join();
    t2.join();
    t3.join();
    t4.join();
    t5.join();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

In this example, the counting semaphore is initialized to the value of 3. This means that up to 3 threads can access the

critical section (the section of code inside the `worker()` function) at the same time. When a thread enters the critical section, it acquires the semaphore, which decrements the count, while when it exits the critical section, it releases the semaphore, incrementing thus the count. The `worker()` function simulates a critical section by acquiring the semaphore, sleeping for 1 second and then releasing the semaphore.

In the main function, 5 worker threads are created and started, each trying to enter the critical section. If the count of the semaphore is already 0, a worker will wait until another worker releases the semaphore (increasing its value).

Composable guards

Composable guards operate in a manner similar to locks, but are applied only to asynchronous functions. The guard (or guards) is automatically locked at the beginning of a specified task and automatically unlocked at the end. Because guards are never added to an existing task's execution context, the calling of guards is freely composable and can never deadlock.

To call an application with a single guard, simply declare the guard and call `run_guarded()` with a function (`task`):

```
hpx::lcos::local::guard gu;
run_guarded(gu, task);
```

If a single method needs to run with multiple guards, use a guard set:

```
std::shared_ptr<hpx::lcos::local::guard> gu1(new hpx::lcos::local::guard());
std::shared_ptr<hpx::lcos::local::guard> gu2(new hpx::lcos::local::guard());
gs.add(*gu1);
gs.add(*gu2);
run_guarded(gs, task);
```

Guards use two atomic operations (which are not called repeatedly) to manage what they do, so overhead should be extremely low.

Execution control

The following objects are providing control of the execution in *HPX* applications:

1. *Futures*
2. *Channels*
3. *Task blocks*
4. *Task groups*
5. *Threads*

Futures

Futures are a mechanism to represent the result of a potentially asynchronous operation. A future is a type that represents a value that will become available at some point in the future, and it can be used to write asynchronous and parallel code. Futures can be returned from functions that perform time-consuming operations, allowing the calling code to continue executing while the function performs its work. The value of the future is set when the operation completes and can be accessed later. Futures are used in *HPX* to write asynchronous and parallel code. Below is an example demonstrating different features of futures:

```

#include <hpx/assert.hpp>
#include <hpx/future.hpp>
#include <hpx/hpx_main.hpp>
#include <hpx/tuple.hpp>

#include <iostream>
#include <utility>

int main()
{
    // Asynchronous execution with futures
    hpx::future<void> f1 = hpx::async(hpx::launch::async, []() {});
    hpx::shared_future<int> f2 =
        hpx::async(hpx::launch::async, []() { return 42; });
    hpx::future<int> f3 =
        f2.then([](hpx::shared_future<int>&& f) { return f.get() * 3; });

    hpx::promise<double> p;
    auto f4 = p.get_future();
    HPX_ASSERT(!f4.is_ready());
    p.set_value(123.45);
    HPX_ASSERT(f4.is_ready());

    hpx::packaged_task<int()> t([]() { return 43; });
    hpx::future<int> f5 = t.get_future();
    HPX_ASSERT(!f5.is_ready());
    t();
    HPX_ASSERT(f5.is_ready());

    // Fire-and-forget
    hpx::post([]() {
        std::cout << "This will be printed later\n" << std::flush;
    });

    // Synchronous execution
    hpx::sync([]() {
        std::cout << "This will be printed immediately\n" << std::flush;
    });

    // Combinators
    hpx::future<double> f6 = hpx::async([]() { return 3.14; });
    hpx::future<double> f7 = hpx::async([]() { return 42.0; });
    std::cout
        << hpx::when_all(f6, f7)
            .then([](hpx::future<
                hpx::tuple<hpx::future<double>, hpx::future<double>>>
                f) {
                hpx::tuple<hpx::future<double>, hpx::future<double>> t =
                    f.get();
                double pi = hpx::get<0>(t).get();
                double r = hpx::get<1>(t).get();
                return pi * r * r;
            })

```

(continues on next page)

(continued from previous page)

```

        .get()
    << std::endl;

    // Easier continuations with dataflow; it waits for all future or
    // shared_future arguments before executing the continuation, and also
    // accepts non-future arguments
    hpx::future<double> f8 = hpx::async([]() { return 3.14; });
    hpx::future<double> f9 = hpx::make_ready_future(42.0);
    hpx::shared_future<double> f10 = hpx::async([]() { return 123.45; });
    hpx::future<hpx::tuple<double, double>> f11 = hpx::dataflow(
        [](hpx::future<double> a, hpx::future<double> b,
            hpx::shared_future<double> c, double d) {
            return hpx::make_tuple<>(a.get() + b.get(), c.get() / d);
        },
        f8, f9, f10, -3.9);

    // split_future gives a tuple of futures from a future of tuple
    hpx::tuple<hpx::future<double>, hpx::future<double>> f12 =
        hpx::split_future(std::move(f11));
    std::cout << hpx::get<1>(f12).get() << std::endl;

    return 0;
}

```

The first section of the main function demonstrates how to use futures for asynchronous execution. The first two lines create two futures, one for void and another for an integer, using the `hpx::async()` function. These futures are executed *asynchronously* in separate threads using the `hpx::launch::async` launch policy. The third future is created by *chaining* the second future using the `then()` member function. This future multiplies the result of the second future by 3.

The next part of the code demonstrates how to use *promises* and *packaged tasks*, which are constructs used for communicating data between threads. The `promise` class is used to store a value that can be retrieved *later* using a future. The `packaged_task` class represents a task that can be executed *asynchronously*, and its result can be obtained using a future. The last three lines create a packaged task that returns an integer, obtain its future, execute the task, and check whether the future is ready or not.

The code then demonstrates how to use the `hpx::post()` and `hpx::sync()` functions for *fire-and-forget* and *synchronous* execution, respectively. The `hpx::post()` function executes a given function *asynchronously* and *returns immediately* without waiting for the result. The `hpx::sync()` function executes a given function *synchronously* and *waits* for the result before returning.

Next the code demonstrates the use of *combinators*, which are higher-order functions that combine two or more futures into a single future. The `hpx::when_all()` function is used to combine two futures, which return double values, into a tuple of futures. The `then()` member function is then used to compute the area of a circle using the values of the two futures. The `get()` member function is used to retrieve the result of the computation.

The last section demonstrates the use of `hpx::dataflow()`, which is a higher-order function that waits for all the future or `shared_future` arguments to be ready before executing the continuation. The `hpx::make_ready_future()` function is used to create a future with a given value. The `hpx::split_future()` function is used to split a future of a tuple into a tuple of futures. The last line retrieves the value of the second future in the tuple using `hpx::get()` and prints it to the console.

Extended facilities for futures

Concurrency is about both decomposing and composing the program from the parts that work well individually and together. It is in the composition of connected and multicore components where today's C++ libraries are still lacking.

The functionality of `std::future`⁷⁵ offers a partial solution. It allows for the separation of the initiation of an operation and the act of waiting for its result; however, the act of waiting is synchronous. In communication-intensive code this act of waiting can be unpredictable, inefficient and simply frustrating. The example below illustrates a possible synchronous wait using futures:

```
#include <future>
using namespace std;
int main()
{
    future<int> f = async([]() { return 123; });
    int result = f.get(); // might block
}
```

For this reason, *HPX* implements a set of extensions to `std::future`⁷⁶ (as proposed by N4313⁷⁷). This proposal introduces the following key asynchronous operations to `hpx::future`, `hpx::shared_future` and `hpx::async`, which enhance and enrich these facilities.

Table 2.11: Facilities extending `std::future`

Facility	Description
<code>hpx::future::then</code>	In asynchronous programming, it is very common for one asynchronous operation, on completion, to invoke a second operation and pass data to it. The current C++ standard does not allow one to register a continuation to a future. With <code>then</code> , instead of waiting for the result, a continuation is “attached” to the asynchronous operation, which is invoked when the result is ready. Continuations registered using <code>then</code> function will help to avoid blocking waits or wasting threads on polling, greatly improving the responsiveness and scalability of an application.
unwrapping constructor for <code>hpx::future</code>	In some scenarios, you might want to create a future that returns another future, resulting in nested futures. Although it is possible to write code to unwrap the outer future and retrieve the nested future and its result, such code is not easy to write because users must handle exceptions and it may cause a blocking call. Unwrapping can allow users to mitigate this problem by doing an asynchronous call to unwrap the outermost future.
<code>hpx::future::is_ready</code>	There are often situations where a <code>get()</code> call on a future may not be a blocking call, or is only a blocking call under certain circumstances. This function gives the ability to test for early completion and allows us to avoid associating a continuation, which needs to be scheduled with some non-trivial overhead and near-certain loss of cache efficiency.
<code>hpx::make_ready_future</code>	Some functions may know the value at the point of construction. In these cases the value is immediately available, but needs to be returned as a future. By using <code>hpx::make_ready_future</code> a future can be created that holds a pre-computed result in its shared state. In the current standard it is non-trivial to create a future directly from a value. First a promise must be created, then the promise is set, and lastly the future is retrieved from the promise. This can now be done with one operation.

The standard also omits the ability to compose multiple futures. This is a common pattern that is ubiquitous in other asynchronous frameworks and is absolutely necessary in order to make C++ a powerful asynchronous programming language. Not including these functions is synonymous to Boolean algebra without AND/OR.

⁷⁵ <http://en.cppreference.com/w/cpp/thread/future>

⁷⁶ <http://en.cppreference.com/w/cpp/thread/future>

⁷⁷ <http://wg21.link/n4313>

In addition to the extensions proposed by N4313⁷⁸, HPX adds functions allowing users to compose several futures in a more flexible way.

Table 2.12: Facilities for composing `hpx::futures`

Facility	Description
<code>hpx::when_any</code> , <code>hpx::when_any_n</code>	Asynchronously wait for at least one of multiple future or shared_future objects to finish.
<code>hpx::wait_any</code> , <code>hpx::wait_any_n</code>	Synchronously wait for at least one of multiple future or shared_future objects to finish.
<code>hpx::when_all</code> , <code>hpx::when_all_n</code>	Asynchronously wait for all future and shared_future objects to finish.
<code>hpx::wait_all</code> , <code>hpx::wait_all_n</code>	Synchronously wait for all future and shared_future objects to finish.
<code>hpx::when_some</code> , <code>hpx::when_some_n</code>	Asynchronously wait for multiple future and shared_future objects to finish.
<code>hpx::wait_some</code> , <code>hpx::wait_some_n</code>	Synchronously wait for multiple future and shared_future objects to finish.
<code>hpx::when_each</code>	Asynchronously wait for multiple future and shared_future objects to finish and call a function for each of the future objects as soon as it becomes ready.
<code>hpx::wait_each</code> , <code>hpx::wait_each_n</code>	Synchronously wait for multiple future and shared_future objects to finish and call a function for each of the future objects as soon as it becomes ready.

Channels

Channels combine communication (the exchange of a value) with synchronization (guaranteeing that two calculations (tasks) are in a known state). A channel can transport any number of values of a given type from a sender to a receiver:

```
hpx::lcos::local::channel<int> c;
hpx::future<int> f = c.get();
HPX_ASSERT(!f.is_ready());
c.set(42);
HPX_ASSERT(f.is_ready());
std::cout << f.get() << std::endl;
```

Channels can be handed to another thread (or in case of channel components, to other localities), thus establishing a communication channel between two independent places in the program:

```
void do_something(hpx::lcos::local::receive_channel<int> c,
                 hpx::lcos::local::send_channel<> done)
{
    // prints 43
    std::cout << c.get(hpx::launch::sync) << std::endl;
    // signal back
    done.set();
}

void send_receive_channel()
{
    hpx::lcos::local::channel<int> c;
    hpx::lcos::local::channel<> done;
```

(continues on next page)

⁷⁸ <http://wg21.link/n4313>

(continued from previous page)

```
hpx::post(&do_something, c, done);

// send some value
c.set(43);
// wait for thread to be done
done.get().wait();
}
```

Note how `hpx::lcos::local::channel::get` without any arguments returns a future which is ready when a value has been set on the channel. The launch policy `hpx::launch::sync` can be used to make `hpx::lcos::local::channel::get` block until a value is set and return the value directly.

A channel component is created on one *locality* and can be sent to another *locality* using an action. This example also demonstrates how a channel can be used as a range of values:

```
// channel components need to be registered for each used type (not needed
// for hpx::lcos::local::channel)
HPX_REGISTER_CHANNEL(double)

void channel_sender(hpx::lcos::channel<double> c)
{
    for (double d : c)
        hpx::cout << d << std::endl;
}
HPX_PLAIN_ACTION(channel_sender)

void channel()
{
    // create the channel on this locality
    hpx::lcos::channel<double> c(hpx::find_here());

    // pass the channel to a (possibly remote invoked) action
    hpx::post(channel_sender_action(), hpx::find_here(), c);

    // send some values to the receiver
    std::vector<double> v = {1.2, 3.4, 5.0};
    for (double d : v)
        c.set(d);

    // explicitly close the communication channel (implicit at destruction)
    c.close();
}
```


Task blocks

Task blocks in *HPX* provide a way to structure and organize the execution of tasks in a parallel program, making it easier to manage dependencies between tasks. A task block actually is a group of tasks that can be executed in parallel. Tasks in a task block can depend on other tasks in the same task block. The task block allows the runtime to optimize the execution of tasks, by scheduling them in an optimal order based on the dependencies between them.

The `define_task_block`, `run` and the `wait` functions implemented based on N4755⁷⁹ are based on the `task_block` concept that is a part of the common subset of the [Microsoft Parallel Patterns Library \(PPL\)](https://msdn.microsoft.com/en-us/library/dd492418.aspx)⁸⁰ and the [Intel Threading Building Blocks \(TBB\)](https://www.threadingbuildingblocks.org/)⁸¹ libraries.

These implementations adopt a simpler syntax than exposed by those libraries— one that is influenced by language-based concepts, such as `spawn` and `sync` from [Cilk++](https://ericniebler.com/2014/05/19/cilk-plus/)⁸² and `async` and `finish` from [X10](https://ericniebler.com/2014/05/19/cilk-plus/)⁸³. They improve on existing practice in the following ways:

- The exception handling model is simplified and more consistent with normal C++ exceptions.
- Most violations of strict fork-join parallelism can be enforced at compile time (with compiler assistance, in some cases).
- The syntax allows scheduling approaches other than child stealing.

Consider an example of a parallel traversal of a tree, where a user-provided function `compute` is applied to each node of the tree, returning the sum of the results:

```
template <typename Func>
int traverse(node& n, Func && compute)
{
    int left = 0, right = 0;
    define_task_block(
        [&](task_block<>& tr) {
            if (n.left)
                tr.run([&] { left = traverse(*n.left, compute); });
            if (n.right)
                tr.run([&] { right = traverse(*n.right, compute); });
        });

    return compute(n) + left + right;
}
```

The example above demonstrates the use of two of the functions, `hpx::experimental::define_task_block` and the `hpx::experimental::task_block::run` member function of a `hpx::experimental::task_block`.

The `task_block` function delineates a region in a program code potentially containing invocations of threads spawned by the `run` member function of the `task_block` class. The `run` function spawns an *HPX* thread, a unit of work that is allowed to execute in parallel with respect to the caller. Any parallel tasks spawned by `run` within the task block are joined back to a single thread of execution at the end of the `define_task_block`. `run` takes a user-provided function object `f` and starts it asynchronously—i.e., it may return before the execution of `f` completes. The *HPX* scheduler may choose to run `f` immediately or delay running `f` until compute resources become available.

A `task_block` can be constructed only by `define_task_block` because it has no public constructors. Thus, `run` can be invoked directly or indirectly only from a user-provided function passed to `define_task_block`:

⁷⁹ <http://wg21.link/n4755>

⁸⁰ <https://msdn.microsoft.com/en-us/library/dd492418.aspx>

⁸¹ <https://www.threadingbuildingblocks.org/>

⁸² <https://software.intel.com/en-us/articles/intel-cilk-plus/>

⁸³ <https://x10-lang.org/>

```
void g();

void f(task_block<>& tr)
{
    tr.run(g);          // OK, invoked from within task_block in h
}

void h()
{
    define_task_block(f);
}

int main()
{
    task_block<> tr;      // Error: no public constructor
    tr.run(g);           // No way to call run outside of a define_task_block
    return 0;
}
```

Extensions for task blocks

Using execution policies with task blocks

HPX implements some extensions for `task_block` beyond the actual standards proposal [N4755](http://wg21.link/n4755)⁸⁴. The main addition is that a `task_block` can be invoked with an execution policy as its first argument, very similar to the parallel algorithms.

An execution policy is an object that expresses the requirements on the ordering of functions invoked as a consequence of the invocation of a task block. Enabling passing an execution policy to `define_task_block` gives the user control over the amount of parallelism employed by the created `task_block`. In the following example the use of an explicit `par` execution policy makes the user's intent explicit:

```
template <typename Func>
int traverse(node *n, Func&& compute)
{
    int left = 0, right = 0;

    define_task_block(
        execution::par,          // execution::parallel_policy
        [&](task_block<>& tb) {
            if (n->left)
                tb.run([&] { left = traverse(n->left, compute); });
            if (n->right)
                tb.run([&] { right = traverse(n->right, compute); });
        });

    return compute(n) + left + right;
}
```

This also causes the `hpx::experimental::task_block` object to be a template in our implementation. The template argument is the type of the execution policy used to create the task block. The template argument defaults to `hpx::execution::parallel_policy`.

⁸⁴ <http://wg21.link/n4755>

HPX still supports calling `hpx::experimental::define_task_block` without an explicit execution policy. In this case the task block will run using the `hpx::execution::parallel_policy`.

HPX also adds the ability to access the execution policy that was used to create a given `task_block`.

Using executors to run tasks

Often, users want to be able to not only define an execution policy to use by default for all spawned tasks inside the task block, but also to customize the execution context for one of the tasks executed by `task_block::run`. Adding an optionally passed executor instance to that function enables this use case:

```
template <typename Func>
int traverse(node *n, Func&& compute)
{
    int left = 0, right = 0;

    define_task_block(
        execution::par,                // execution::parallel_policy
        [&](auto& tb) {
            if (n->left)
            {
                // use explicitly specified executor to run this task
                tb.run(my_executor(), [&] { left = traverse(n->left, compute); });
            }
            if (n->right)
            {
                // use the executor associated with the par execution policy
                tb.run([&] { right = traverse(n->right, compute); });
            }
        });

    return compute(n) + left + right;
}
```

HPX still supports calling `hpx::experimental::task_block::run` without an explicit executor object. In this case the task will be run using the executor associated with the execution policy that was used to call `hpx::experimental::define_task_block`.

Task groups

A *task group* in HPX is a synchronization primitive that allows you to execute a group of tasks concurrently and wait for their completion before continuing. The tasks in an `hpx::experimental::task_group` can be added dynamically. This is the HPX implementation of `tbb::task_group` of the Intel Threading Building Blocks (TBB)⁸⁵ library.

The example below shows that to use a task group, you simply create an `hpx::task_group` object and add tasks to it using the `run()` method. Once all the tasks have been added, you can call the `wait()` method to synchronize the tasks and wait for them to complete.

```
#include <hpx/experimental/task_group.hpp>
#include <hpx/init.hpp>
```

(continues on next page)

⁸⁵ <https://www.threadingbuildingblocks.org/>

(continued from previous page)

```
#include <iostream>

void task1()
{
    std::cout << "Task 1 executed." << std::endl;
}

void task2()
{
    std::cout << "Task 2 executed." << std::endl;
}

int hpx_main()
{
    hpx::experimental::task_group tg;

    tg.run(task1);
    tg.run(task2);

    tg.wait();

    std::cout << "All tasks finished!" << std::endl;

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

Note: *task groups* and *task blocks* are both ways to group and synchronize parallel tasks, but *task groups* are used to group multiple tasks together as a single unit, while *task blocks* are used to execute a loop in parallel, with each iteration of the loop executing in a separate task. If the difference is not clear yet, continue reading.

A *task group* is a construct that allows multiple parallel tasks to be grouped together as a single unit. The task group provides a way to synchronize all the tasks in the group before continuing with the rest of the program.

A *task block*, on the other hand, is a parallel loop construct that allows you to execute a loop in parallel, with each iteration of the loop executing in a separate task. The loop iterations are executed in a block, meaning that the loop body is executed as a single task.

Threads

A thread in *HPX* refers to a sequence of instructions that can be executed concurrently with other such sequences in multithreading environments, while sharing a same address space. These threads can communicate with each other through various means, such as futures or shared data structures.

The example below demonstrates how to launch multiple threads and synchronize them using a `hpx::latch` object. It also shows how to query the state of threads and wait for futures to complete.

```
#include <hpx/future.hpp>
#include <hpx/init.hpp>
#include <hpx/thread.hpp>

#include <functional>
#include <iostream>
#include <vector>

int const num_threads = 10;

/////////////////////////////////////////////////////////////////
void wait_for_latch(hpx::latch& l)
{
    l.arrive_and_wait();
}

int hpx_main()
{
    // Spawn a couple of threads
    hpx::latch l(num_threads + 1);

    std::vector<hpx::future<void>> results;
    results.reserve(num_threads);

    for (int i = 0; i != num_threads; ++i)
        results.push_back(hpx::async(&wait_for_latch, std::ref(l)));

    // Allow spawned threads to reach latch
    hpx::this_thread::yield();

    // Enumerate all suspended threads
    hpx::threads::enumerate_threads(
        [](hpx::threads::thread_id_type id) -> bool {
            std::cout << "thread " << hpx::thread::id(id) << " is "
                << hpx::threads::get_thread_state_name(
                    hpx::threads::get_thread_state(id))
                << std::endl;
            return true; // always continue enumeration
        },
        hpx::threads::thread_schedule_state::suspended);

    // Wait for all threads to reach this point.
    l.arrive_and_wait();
}
```

(continues on next page)

(continued from previous page)

```
    hpx::wait_all(results);

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

In more detail, the `wait_for_latch()` function is a simple helper function that waits for a `hpx::latch` object to be released. At this point we remind that `hpx::latch` is a synchronization primitive that allows multiple threads to wait for a common event to occur.

In the `hpx_main()` function, an `hpx::latch` object is created with a count of `num_threads + 1`, indicating that `num_threads` threads need to arrive at the latch before the latch is released. The loop that follows launches `num_threads` asynchronous operations, each of which calls the `wait_for_latch` function. The resulting futures are added to the vector.

After the threads have been launched, `hpx::this_thread::yield()` is called to give them a chance to reach the latch before the program proceeds. Then, the `hpx::threads::enumerate_threads` function prints the state of each suspended thread, while the next call of `l.arrive_and_wait()` waits for all the threads to reach the latch. Finally, `hpx::wait_all` is called to wait for all the futures to complete.

Hint: An advantage of using `hpx::thread` over other threading libraries is that it is optimized for high-performance parallelism, with support for lightweight threads and task scheduling to minimize thread overhead and maximize parallelism. Additionally, `hpx::thread` integrates seamlessly with other features of *HPX* such as futures, promises, and task groups, making it a powerful tool for parallel programming.

Checkout the examples of *Shared mutex*, *Condition variable*, *Semaphore* to see how *HPX* threads are used in combination with other features.

High level parallel facilities

In preparation for the upcoming C++ Standards, there are currently several proposals targeting different facilities supporting parallel programming. *HPX* implements (and extends) some of those proposals. This is well aligned with our strategy to align the APIs exposed from *HPX* with current and future C++ Standards.

At this point, *HPX* implements several of the C++ Standardization working papers, most notably [N4409](http://wg21.link/n4409)⁸⁶ (Working Draft, Technical Specification for C++ Extensions for Parallelism), [N4755](http://wg21.link/n4755)⁸⁷ (Task Blocks), and [N4406](http://wg21.link/n4406)⁸⁸ (Parallel Algorithms Need Executors).

⁸⁶ <http://wg21.link/n4409>

⁸⁷ <http://wg21.link/n4755>

⁸⁸ <http://wg21.link/n4406>

Using parallel algorithms

A parallel algorithm is a function template declared in the namespace `hpx::parallel`.

All parallel algorithms are very similar in semantics to their sequential counterparts (as defined in the namespace `std`) with an additional formal template parameter named `ExecutionPolicy`. The execution policy is generally passed as the first argument to any of the parallel algorithms and describes the manner in which the execution of these algorithms may be parallelized and the manner in which they apply user-provided function objects.

The applications of function objects in parallel algorithms invoked with an execution policy object of type `hpx::execution::sequenced_policy` or `hpx::execution::sequenced_task_policy` execute in sequential order. For `hpx::execution::sequenced_policy` the execution happens in the calling thread.

The applications of function objects in parallel algorithms invoked with an execution policy object of type `hpx::execution::parallel_policy` or `hpx::execution::parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and are indeterminately sequenced within each thread.

Important: It is the caller's responsibility to ensure correctness, such as making sure that the invocation does not introduce data races or deadlocks.

The example below demonstrates how to perform a sequential and parallel `hpx::for_each` loop on a vector of integers.

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>
#include <hpx/init.hpp>

#include <iostream>
#include <vector>

int hpx_main()
{
    std::vector<int> v{1, 2, 3, 4, 5};

    auto print = [](int const& n) { std::cout << n << ' '; };

    std::cout << "Print sequential: ";
    hpx::for_each(v.begin(), v.end(), print);
    std::cout << '\n';

    std::cout << "Print parallel: ";
    hpx::for_each(hpx::execution::par, v.begin(), v.end(), print);
    std::cout << '\n';

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

The above code uses `hpx::for_each` to print the elements of the vector `v{1, 2, 3, 4, 5}`. At first, `hpx::for_each()` is called without an execution policy, which means that it applies the lambda function `print` to each element in the vector sequentially. Hence, the elements are printed in order.

Next, `hpx::for_each()` is called with the `hpx::execution::par` execution policy, which applies the lambda function `print` to each element in the vector in parallel. Therefore, the output order of the elements in the vector is not deterministic and may vary from run to run.

Parallel exceptions

During the execution of a standard parallel algorithm, if temporary memory resources are required by any of the algorithms and no memory is available, the algorithm throws a `std::bad_alloc` exception.

During the execution of any of the parallel algorithms, if the application of a function object terminates with an uncaught exception, the behavior of the program is determined by the type of execution policy used to invoke the algorithm:

- If the execution policy object is of type `hpx::execution::parallel_unsequenced_policy`, `hpx::terminate` shall be called.
- If the execution policy object is of type `hpx::execution::sequenced_policy`, `hpx::execution::sequenced_task_policy`, `hpx::execution::parallel_policy`, or `hpx::execution::parallel_task_policy`, the execution of the algorithm terminates with an `hpx::exception_list` exception. All uncaught exceptions thrown during the application of user-provided function objects shall be contained in the `hpx::exception_list`.

For example, the number of invocations of the user-provided function object in `for_each` is unspecified. When `hpx::for_each` is executed sequentially, only one exception will be contained in the `hpx::exception_list` object.

These guarantees imply that, unless the algorithm has failed to allocate memory and terminated with `std::bad_alloc`, all exceptions thrown during the execution of the algorithm are communicated to the caller. It is unspecified whether an algorithm implementation will “forge ahead” after encountering and capturing a user exception.

The algorithm may terminate with the `std::bad_alloc` exception even if one or more user-provided function objects have terminated with an exception. For example, this can happen when an algorithm fails to allocate memory while creating or adding elements to the `hpx::exception_list` object.

Parallel algorithms

HPX provides implementations of the following parallel algorithms:

Table 2.13: Non-modifying parallel algorithms of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::adjacent_find</code>	Computes the differences between adjacent elements in a range.	<code>adjacent_find</code> ⁸⁹
<code>hpx::all_of</code>	Checks if a predicate is <code>true</code> for all of the elements in a range.	<code>all_any_none_of</code> ⁹⁰
<code>hpx::any_of</code>	Checks if a predicate is <code>true</code> for any of the elements in a range.	<code>all_any_none_of</code> ⁹¹
<code>hpx::count</code>	Returns the number of elements equal to a given value.	<code>count</code> ⁹²
<code>hpx::count_if</code>	Returns the number of elements satisfying a specific criteria.	<code>count_if</code> ⁹³
<code>hpx::equal</code>	Determines if two sets of elements are the same.	<code>equal</code> ⁹⁴
<code>hpx::find</code>	Finds the first element equal to a given value.	<code>find</code> ⁹⁵
<code>hpx::find_end</code>	Finds the last sequence of elements in a certain range.	<code>find_end</code> ⁹⁶
<code>hpx::find_first_of</code>	Searches for any one of a set of elements.	<code>find_first_of</code> ⁹⁷
<code>hpx::find_if</code>	Finds the first element satisfying a specific criteria.	<code>find_if</code> ⁹⁸
<code>hpx::find_if_not</code>	Finds the first element not satisfying a specific criteria.	<code>find_if_not</code> ⁹⁹
<code>hpx::for_each</code>	Applies a function to a range of elements.	<code>for_each</code> ¹⁰⁰
<code>hpx::for_each_n</code>	Applies a function to a number of elements.	<code>for_each_n</code> ¹⁰¹
<code>hpx::lexicographical_compare</code>	Checks if a range of values is lexicographically less than another range of values.	<code>lexicographical_compare</code> ¹⁰²
<code>hpx::mismatch</code>	Finds the first position where two ranges differ.	<code>mismatch</code> ¹⁰³
<code>hpx::none_of</code>	Checks if a predicate is <code>true</code> for none of the elements in a range.	<code>all_any_none_of</code> ¹⁰⁴
<code>hpx::search</code>	Searches for a range of elements.	<code>search</code> ¹⁰⁵
<code>hpx::search_n</code>	Searches for a number consecutive copies of an element in a range.	<code>search_n</code> ¹⁰⁶

⁸⁹ http://en.cppreference.com/w/cpp/algorithm/adjacent_find⁹⁰ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of⁹¹ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of⁹² <http://en.cppreference.com/w/cpp/algorithm/count>⁹³ http://en.cppreference.com/w/cpp/algorithm/count_if⁹⁴ <http://en.cppreference.com/w/cpp/algorithm/equal>⁹⁵ <http://en.cppreference.com/w/cpp/algorithm/find>⁹⁶ http://en.cppreference.com/w/cpp/algorithm/find_end⁹⁷ http://en.cppreference.com/w/cpp/algorithm/find_first_of⁹⁸ http://en.cppreference.com/w/cpp/algorithm/find_if⁹⁹ http://en.cppreference.com/w/cpp/algorithm/find_if_not¹⁰⁰ http://en.cppreference.com/w/cpp/algorithm/for_each¹⁰¹ http://en.cppreference.com/w/cpp/algorithm/for_each_n¹⁰² http://en.cppreference.com/w/cpp/algorithm/lexicographical_compare¹⁰³ <http://en.cppreference.com/w/cpp/algorithm/mismatch>¹⁰⁴ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of¹⁰⁵ <http://en.cppreference.com/w/cpp/algorithm/search>¹⁰⁶ http://en.cppreference.com/w/cpp/algorithm/search_n

Table 2.14: Modifying parallel algorithms of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::copy</code>	Copies a range of elements to a new location.	<code>exclusive_scan</code> ¹⁰⁷
<code>hpx::copy_n</code>	Copies a number of elements to a new location.	<code>copy_n</code> ¹⁰⁸
<code>hpx::copy_if</code>	Copies the elements from a range to a new location for which the given predicate is <code>true</code>	<code>copy</code> ¹⁰⁹
<code>hpx::move</code>	Moves a range of elements to a new location.	<code>move</code> ¹¹⁰
<code>hpx::fill</code>	Assigns a range of elements a certain value.	<code>fill</code> ¹¹¹
<code>hpx::fill_n</code>	Assigns a value to a number of elements.	<code>fill_n</code> ¹¹²
<code>hpx::generate</code>	Saves the result of a function in a range.	<code>generate</code> ¹¹³
<code>hpx::generate_n</code>	Saves the result of N applications of a function.	<code>generate_n</code> ¹¹⁴
<code>hpx::experimental::reduce_by_key</code>	Performs an inclusive scan on consecutive elements with matching keys, with a reduction to output only the final sum for each key. The key sequence <code>{1, 1, 1, 2, 3, 3, 3, 3, 1}</code> and value sequence <code>{2, 3, 4, 5, 6, 7, 8, 9, 10}</code> would be reduced to <code>keys={1, 2, 3, 1}</code> , <code>values={9, 5, 30, 10}</code> .	
<code>hpx::remove</code>	Removes the elements from a range that are equal to the given value.	<code>remove</code> ¹¹⁵
<code>hpx::remove_if</code>	Removes the elements from a range that are equal to the given predicate is <code>false</code>	<code>remove</code> ¹¹⁶
<code>hpx::remove_copy</code>	Copies the elements from a range to a new location that are not equal to the given value.	<code>remove_copy</code> ¹¹⁷
<code>hpx::remove_copy_if</code>	Copies the elements from a range to a new location for which the given predicate is <code>false</code>	<code>remove_copy</code> ¹¹⁸
<code>hpx::replace</code>	Replaces all values satisfying specific criteria with another value.	<code>replace</code> ¹¹⁹
<code>hpx::replace_if</code>	Replaces all values satisfying specific criteria with another value.	<code>replace</code> ¹²⁰
<code>hpx::replace_copy</code>	Copies a range, replacing elements satisfying specific criteria with another value.	<code>replace_copy</code> ¹²¹
<code>hpx::replace_copy_if</code>	Copies a range, replacing elements satisfying specific criteria with another value.	<code>replace_copy</code> ¹²²
<code>hpx::reverse</code>	Reverses the order elements in a range.	<code>reverse</code> ¹²³
<code>hpx::reverse_copy</code>	Creates a copy of a range that is reversed.	<code>reverse_copy</code> ¹²⁴
<code>hpx::rotate</code>	Rotates the order of elements in a range.	<code>rotate</code> ¹²⁵
<code>hpx::rotate_copy</code>	Copies and rotates a range of elements.	<code>rotate_copy</code> ¹²⁶
<code>hpx::shift_left</code>	Shifts the elements in the range left by n positions.	<code>shift_left</code> ¹²⁷
<code>hpx::shift_right</code>	Shifts the elements in the range right by n positions.	<code>shift_right</code> ¹²⁸
<code>hpx::swap_ranges</code>	Swaps two ranges of elements.	<code>swap_ranges</code> ¹²⁹
<code>hpx::transform</code>	Applies a function to a range of elements.	<code>transform</code> ¹³⁰
<code>hpx::unique</code>	Eliminates all but the first element from every consecutive group of equivalent elements from a range.	<code>unique</code> ¹³¹
<code>hpx::unique_copy</code>	Copies the elements from one range to another in such a way that there are no consecutive equal elements.	<code>unique_copy</code> ¹³²

Table 2.15: Set operations on sorted sequences of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::merge</code>	Merges two sorted ranges.	<code>merge</code> ¹³³
<code>hpx::inplace_merge</code>	Merges two ordered ranges in-place.	<code>inplace_merge</code> ¹³⁴
<code>hpx::includes</code>	Returns true if one set is a subset of another.	<code>includes</code> ¹³⁵
<code>hpx::set_difference</code>	Computes the difference between two sets.	<code>set_difference</code> ¹³⁶
<code>hpx::set_intersection</code>	Computes the intersection of two sets.	<code>set_intersection</code> ¹³⁷
<code>hpx::set_symmetric_difference</code>	Computes the symmetric difference between two sets.	<code>set_symmetric_difference</code> ¹³⁸
<code>hpx::set_union</code>	Computes the union of two sets.	<code>set_union</code> ¹³⁹

Table 2.16: Heap operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::is_heap</code>	Returns true if the range is max heap.	<code>is_heap</code> ¹⁴⁰
<code>hpx::is_heap_until</code>	Returns the first element that breaks a max heap.	<code>is_heap_until</code> ¹⁴¹
<code>hpx::make_heap</code>	Constructs a max heap in the range [first, last).	<code>make_heap</code> ¹⁴²

¹⁰⁷ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan¹⁰⁸ http://en.cppreference.com/w/cpp/algorithm/copy_n¹⁰⁹ <http://en.cppreference.com/w/cpp/algorithm/copy>¹¹⁰ <http://en.cppreference.com/w/cpp/algorithm/move>¹¹¹ <http://en.cppreference.com/w/cpp/algorithm/fill>¹¹² http://en.cppreference.com/w/cpp/algorithm/fill_n¹¹³ <http://en.cppreference.com/w/cpp/algorithm/generate>¹¹⁴ http://en.cppreference.com/w/cpp/algorithm/generate_n¹¹⁵ <http://en.cppreference.com/w/cpp/algorithm/remove>¹¹⁶ <http://en.cppreference.com/w/cpp/algorithm/remove>¹¹⁷ http://en.cppreference.com/w/cpp/algorithm/remove_copy¹¹⁸ http://en.cppreference.com/w/cpp/algorithm/remove_copy¹¹⁹ <http://en.cppreference.com/w/cpp/algorithm/replace>¹²⁰ <http://en.cppreference.com/w/cpp/algorithm/replace>¹²¹ http://en.cppreference.com/w/cpp/algorithm/replace_copy¹²² http://en.cppreference.com/w/cpp/algorithm/replace_copy¹²³ <http://en.cppreference.com/w/cpp/algorithm/reverse>¹²⁴ http://en.cppreference.com/w/cpp/algorithm/reverse_copy¹²⁵ <http://en.cppreference.com/w/cpp/algorithm/rotate>¹²⁶ http://en.cppreference.com/w/cpp/algorithm/rotate_copy¹²⁷ http://en.cppreference.com/w/cpp/algorithm/shift_left¹²⁸ http://en.cppreference.com/w/cpp/algorithm/shift_right¹²⁹ http://en.cppreference.com/w/cpp/algorithm/swap_ranges¹³⁰ <http://en.cppreference.com/w/cpp/algorithm/transform>¹³¹ <http://en.cppreference.com/w/cpp/algorithm/unique>¹³² http://en.cppreference.com/w/cpp/algorithm/unique_copy¹³³ <http://en.cppreference.com/w/cpp/algorithm/merge>¹³⁴ http://en.cppreference.com/w/cpp/algorithm/inplace_merge¹³⁵ <http://en.cppreference.com/w/cpp/algorithm/includes>¹³⁶ http://en.cppreference.com/w/cpp/algorithm/set_difference¹³⁷ http://en.cppreference.com/w/cpp/algorithm/set_intersection¹³⁸ http://en.cppreference.com/w/cpp/algorithm/set_symmetric_difference¹³⁹ http://en.cppreference.com/w/cpp/algorithm/set_union

Table 2.17: Minimum/maximum operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::max_element</code>	Returns the largest element in a range.	<code>max_element</code> ¹⁴³
<code>hpx::min_element</code>	Returns the smallest element in a range.	<code>min_element</code> ¹⁴⁴
<code>hpx::minmax_element</code>	Returns the smallest and the largest element in a range.	<code>minmax_element</code> ¹⁴⁵

Table 2.18: Partitioning Operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::nth_element</code>	Partially sorts the given range making sure that it is partitioned by the given element	<code>nth_element</code> ¹⁴⁶
<code>hpx::is_partitioned</code>	Returns <code>true</code> if each true element for a predicate precedes the false elements in a range.	<code>is_partitioned</code> ¹⁴⁷
<code>hpx::partition</code>	Divides elements into two groups without preserving their relative order.	<code>partition</code> ¹⁴⁸
<code>hpx::partition_copy</code>	Copies a range dividing the elements into two groups.	<code>partition_copy</code> ¹⁴⁹
<code>hpx::stable_partition</code>	Divides elements into two groups while preserving their relative order.	<code>stable_partition</code> ¹⁵⁰

Table 2.19: Sorting Operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::is_sorted</code>	Returns <code>true</code> if each element in a range is sorted.	<code>is_sorted</code> ¹⁵¹
<code>hpx::is_sorted_until</code>	Returns the first unsorted element.	<code>is_sorted_until</code> ¹⁵²
<code>hpx::sort</code>	Sorts the elements in a range.	<code>sort</code> ¹⁵³
<code>hpx::stable_sort</code>	Sorts the elements in a range, maintain sequence of equal elements.	<code>stable_sort</code> ¹⁵⁴
<code>hpx::partial_sort</code>	Sorts the first elements in a range.	<code>partial_sort</code> ¹⁵⁵
<code>hpx::partial_sort_copy</code>	Sorts the first elements in a range, storing the result in another range.	<code>partial_sort_copy</code> ¹⁵⁶
<code>hpx::experimental::sort_by_key</code>	Sorts a range of data using keys supplied in another range.	

¹⁴⁰ http://en.cppreference.com/w/cpp/algorithm/is_heap¹⁴¹ http://en.cppreference.com/w/cpp/algorithm/is_heap_until¹⁴² http://en.cppreference.com/w/cpp/algorithm/make_heap¹⁴³ http://en.cppreference.com/w/cpp/algorithm/max_element¹⁴⁴ http://en.cppreference.com/w/cpp/algorithm/min_element¹⁴⁵ http://en.cppreference.com/w/cpp/algorithm/minmax_element¹⁴⁶ http://en.cppreference.com/w/cpp/algorithm/nth_element¹⁴⁷ http://en.cppreference.com/w/cpp/algorithm/is_partitioned¹⁴⁸ <http://en.cppreference.com/w/cpp/algorithm/partition>¹⁴⁹ http://en.cppreference.com/w/cpp/algorithm/partition_copy¹⁵⁰ http://en.cppreference.com/w/cpp/algorithm/stable_partition

Table 2.20: Numeric Parallel Algorithms of header `hpx/numeric.hpp`

Name	Description	C++ standard
<code>hpx::adjacent_difference</code>	Calculates the difference between each element in an input range and the preceding element.	<code>adjacent_difference</code> ¹⁵⁷
<code>hpx::exclusive_scan</code>	Does an exclusive parallel scan over a range of elements.	<code>exclusive_scan</code> ¹⁵⁸
<code>hpx::inclusive_scan</code>	Does an inclusive parallel scan over a range of elements.	<code>inclusive_scan</code> ¹⁵⁹
<code>hpx::reduce</code>	Sums up a range of elements.	<code>reduce</code> ¹⁶⁰
<code>hpx::transform_exclusive_scan</code>	Does an exclusive parallel scan over a range of elements after applying a function.	<code>transform_exclusive_scan</code> ¹⁶¹
<code>hpx::transform_inclusive_scan</code>	Does an inclusive parallel scan over a range of elements after applying a function.	<code>transform_inclusive_scan</code> ¹⁶²
<code>hpx::transform_reduce</code>	Sums up a range of elements after applying a function. Also, accumulates the inner products of two input ranges.	<code>transform_reduce</code> ¹⁶³

¹⁵¹ http://en.cppreference.com/w/cpp/algorithm/is_sorted¹⁵² http://en.cppreference.com/w/cpp/algorithm/is_sorted_until¹⁵³ <http://en.cppreference.com/w/cpp/algorithm/sort>¹⁵⁴ http://en.cppreference.com/w/cpp/algorithm/stable_sort¹⁵⁵ http://en.cppreference.com/w/cpp/algorithm/partial_sort¹⁵⁶ http://en.cppreference.com/w/cpp/algorithm/partial_sort_copy¹⁵⁷ http://en.cppreference.com/w/cpp/algorithm/adjacent_difference¹⁵⁸ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan¹⁵⁹ http://en.cppreference.com/w/cpp/algorithm/inclusive_scan¹⁶⁰ <http://en.cppreference.com/w/cpp/algorithm/reduce>¹⁶¹ http://en.cppreference.com/w/cpp/algorithm/transform_exclusive_scan¹⁶² http://en.cppreference.com/w/cpp/algorithm/transform_inclusive_scan¹⁶³ http://en.cppreference.com/w/cpp/algorithm/transform_reduce

Table 2.21: Dynamic Memory Management of header `hpx/memory.hpp`

Name	Description	C++ standard
<code>hpx::destroy</code>	Destroys a range of objects.	<code>destroy</code> ¹⁶⁴
<code>hpx::destroy_n</code>	Destroys a range of objects.	<code>destroy_n</code> ¹⁶⁵
<code>hpx::uninitialized_copy</code>	Copies a range of objects to an uninitialized area of memory.	<code>uninitialized_copy</code> ¹⁶⁶
<code>hpx::uninitialized_copy_n</code>	Copies a number of objects to an uninitialized area of memory.	<code>uninitialized_copy_n</code> ¹⁶⁷
<code>hpx::uninitialized_default_construct</code>	Constructs a range of objects to an uninitialized area of memory.	<code>uninitialized_default_construct</code> ¹⁶⁸
<code>hpx::uninitialized_default_construct_n</code>	Constructs a number of objects to an uninitialized area of memory.	<code>uninitialized_default_construct_n</code> ¹⁶⁹
<code>hpx::uninitialized_fill</code>	Copies an object to an uninitialized area of memory.	<code>uninitialized_fill</code> ¹⁷⁰
<code>hpx::uninitialized_fill_n</code>	Copies an object to an uninitialized area of memory.	<code>uninitialized_fill_n</code> ¹⁷¹
<code>hpx::uninitialized_move</code>	Moves a range of objects to an uninitialized area of memory.	<code>uninitialized_move</code> ¹⁷²
<code>hpx::uninitialized_move_n</code>	Moves a number of objects to an uninitialized area of memory.	<code>uninitialized_move_n</code> ¹⁷³
<code>hpx::uninitialized_value_construct</code>	Constructs objects in an uninitialized area of memory.	<code>uninitialized_value_construct</code> ¹⁷⁴
<code>hpx::uninitialized_value_construct_n</code>	Constructs objects in an uninitialized area of memory.	<code>uninitialized_value_construct_n</code> ¹⁷⁵

Table 2.22: Index-based for-loops of header `hpx/algorithm.hpp`

Name	Description
<code>hpx::experimental::for_loop</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_strided</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_n</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_n_strided</code>	Implements loop functionality over a range specified by integral or iterator bounds.

¹⁶⁴ <http://en.cppreference.com/w/cpp/memory/destroy>¹⁶⁵ http://en.cppreference.com/w/cpp/memory/destroy_n¹⁶⁶ http://en.cppreference.com/w/cpp/memory/uninitialized_copy¹⁶⁷ http://en.cppreference.com/w/cpp/memory/uninitialized_copy_n¹⁶⁸ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct¹⁶⁹ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct_n¹⁷⁰ http://en.cppreference.com/w/cpp/memory/uninitialized_fill¹⁷¹ http://en.cppreference.com/w/cpp/memory/uninitialized_fill_n¹⁷² http://en.cppreference.com/w/cpp/memory/uninitialized_move¹⁷³ http://en.cppreference.com/w/cpp/memory/uninitialized_move_n¹⁷⁴ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct¹⁷⁵ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct_n

Executor parameters and executor parameter traits

HPX introduces the notion of execution parameters and execution parameter traits. At this point, the only parameter that can be customized is the size of the chunks of work executed on a single *HPX* thread (such as the number of loop iterations combined to run as a single task).

An executor parameter object is responsible for exposing the calculation of the size of the chunks scheduled. It abstracts the (potentially platform-specific) algorithms of determining those chunk sizes.

The way executor parameters are implemented is aligned with the way executors are implemented. All functionalities of concrete executor parameter types are exposed and accessible through a corresponding customization point, e.g. `get_chunk_size()`.

With `executor_parameter_traits`, clients access all types of executor parameters uniformly, e.g.:

```
std::size_t chunk_size =
    hpx::execution::experimental::get_chunk_size(my_parameter, my_executor,
        num_cores, num_tasks);
```

This call synchronously retrieves the size of a single chunk of loop iterations (or similar) to combine for execution on a single *HPX* thread if the overall number of cores `num_cores` and tasks to schedule is given by `num_tasks`. The lambda function exposes a means of test-probing the execution of a single iteration for performance measurement purposes. The execution parameter type might dynamically determine the execution time of one or more tasks in order to calculate the chunk size; see `hpx::execution::experimental::auto_chunk_size` for an example of this executor parameter type.

Other functions in the interface exist to discover whether an executor parameter type should be invoked once (i.e., it returns a static chunk size; see `hpx::execution::experimental::static_chunk_size`) or whether it should be invoked for each scheduled chunk of work (i.e., it returns a variable chunk size; for an example, see `hpx::execution::experimental::guided_chunk_size`).

Although this interface appears to require executor parameter type authors to implement all different basic operations, none are required. In practice, all operations have sensible defaults. However, some executor parameter types will naturally specialize all operations for maximum efficiency.

HPX implements the following executor parameter types:

- `hpx::execution::experimental::auto_chunk_size`: Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameter type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.
- `hpx::execution::experimental::static_chunk_size`: Loop iterations are divided into pieces of a given size and then assigned to threads. If the size is not specified, the iterations are, if possible, evenly divided contiguously among the threads. This executor parameters type is equivalent to OpenMP's STATIC scheduling directive.
- `hpx::execution::experimental::dynamic_chunk_size`: Loop iterations are divided into pieces of a given size and then dynamically scheduled among the cores; when a core finishes one chunk, it is dynamically assigned another. If the size is not specified, the default chunk size is 1. This executor parameter type is equivalent to OpenMP's DYNAMIC scheduling directive.
- `hpx::execution::experimental::guided_chunk_size`: Iterations are dynamically assigned to cores in blocks as cores request them until no blocks remain to be assigned. This is similar to `dynamic_chunk_size` except that the block size decreases each time a number of loop iterations is given to a thread. The size of the initial block is proportional to `number_of_iterations / number_of_cores`. Subsequent blocks are proportional to `number_of_iterations_remaining / number_of_cores`. The optional chunk size parameter defines the minimum block size. The default minimal chunk size is 1. This executor parameter type is equivalent to OpenMP's GUIDED scheduling directive.

2.4.12 Writing distributed applications

This section focuses on the features of *HPX* needed to write distributed applications, namely the *Active Global Address Space* (AGAS), remotely executable functions (i.e., *actions*), and distributed objects (i.e., *components*).

Global names

HPX implements an *Active Global Address Space* (AGAS) which exposes a single uniform address space spanning all localities an application runs on. AGAS is a fundamental component of the ParalleX execution model. Conceptually, there is no rigid demarcation of local or global memory in AGAS; all available memory is a part of the same address space. AGAS enables named objects to be moved (migrated) across localities without having to change the object's name; i.e., no references to migrated objects have to be ever updated. This feature has significance for dynamic load balancing and in applications where the workflow is highly dynamic, allowing work to be migrated from heavily loaded nodes to less loaded nodes. In addition, immutability of names ensures that AGAS does not have to keep extra indirections ("bread crumbs") when objects move, hence, minimizing complexity of code management for system developers as well as minimizing overheads in maintaining and managing aliases.

The AGAS implementation in *HPX* does not automatically expose every local address to the global address space. It is the responsibility of the programmer to explicitly define which of the objects have to be globally visible and which of the objects are purely local.

In *HPX* global addresses (global names) are represented using the `hpx::id_type` data type. This data type is conceptually very similar to `void*` pointers as it does not expose any type information of the object it is referring to.

The only predefined global addresses are assigned to all localities. The following *HPX* API functions allow one to retrieve the global addresses of localities:

- `hpx::find_here`: retrieves the global address of the *locality* this function is called on.
- `hpx::find_all_localities`: retrieves the global addresses of all localities available to this application (including the *locality* the function is being called on).
- `hpx::find_remote_localities`: retrieves the global addresses of all remote localities available to this application (not including the *locality* the function is being called on).
- `hpx::get_num_localities`: retrieves the number of localities available to this application.
- `hpx::find_locality`: retrieves the global address of any *locality* supporting the given component type.
- `hpx::get_colocation_id`: retrieves the global address of the *locality* currently hosting the object with the given global address.

Additionally, the global addresses of localities can be used to create new instances of components using the following *HPX* API function:

- `hpx::components::new_`: Creates a new instance of the given *Component* type on the specified *locality*.

Note: *HPX* does not expose any functionality to delete component instances. All global addresses (as represented using `hpx::id_type`) are automatically garbage collected. When the last (global) reference to a particular component instance goes out of scope, the corresponding component instance is automatically deleted.

Posting actions

Action type definition

Actions are special types used to describe possibly remote operations. For every global function and every member function which has to be invoked distantly, a special type must be defined. For any global function the special macro `HPX_PLAIN_ACTION` can be used to define the action type. Here is an example demonstrating this:

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which represents
// the function 'app::some_global_function'.
HPX_PLAIN_ACTION(app::some_global_function, some_global_action);
```

Important: The macro `HPX_PLAIN_ACTION` has to be placed in global namespace, even if the wrapped function is located in some other namespace. The newly defined action type is placed in the global namespace as well.

If the action type should be defined somewhere not in global namespace, the action type definition has to be split into two macro invocations (`HPX_DEFINE_PLAIN_ACTION` and `HPX_REGISTER_ACTION`) as shown in the next example:

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }

    // On conforming compilers the following macro expands to:
    //
    //     typedef hpx::actions::make_action<
    //         decltype(&some_global_function), &some_global_function
    //     >::type some_global_action;
    //
    // This will define the action type 'some_global_action' which represents
    // the function 'some_global_function'.
    HPX_DEFINE_PLAIN_ACTION(some_global_function, some_global_action);
}

// The following macro expands to a series of definitions of global objects
// which are needed for proper serialization and initialization support
// enabling the remote invocation of the function`some_global_function`
HPX_REGISTER_ACTION(app::some_global_action, app_some_global_action);
```

The shown code defines an action type `some_global_action` inside the namespace `app`.

Important: If the action type definition is split between two macros as shown above, the name of the action type to

create has to be the same for both macro invocations (here `some_global_action`).

Important: The second argument passed to `HPX_REGISTER_ACTION` (`app_some_global_action`) has to comprise a globally unique C++ identifier representing the action. This is used for serialization purposes.

For member functions of objects which have been registered with AGAS (e.g., ‘components’), a different registration macro `HPX_DEFINE_COMPONENT_ACTION` has to be utilized. Any component needs to be declared in a header file and have some special support macros defined in a source file. Here is an example demonstrating this. The first snippet has to go into the header file:

```
namespace app
{
    struct some_component
    : hpx::components::component_base<some_component>
    {
        int some_member_function(std::string s)
        {
            return std::stoi(s);
        }

        // This will define the action type 'some_member_action' which
        // represents the member function 'some_member_function' of the
        // object type 'some_component'.
        HPX_DEFINE_COMPONENT_ACTION(some_component, some_member_function,
            some_member_action);
    };
}

// Note: The second argument to the macro below has to be systemwide-unique
// C++ identifiers
HPX_REGISTER_ACTION_DECLARATION(app::some_component::some_member_action, some_component_
↪some_action);
```

The next snippet belongs in a source file (e.g., the main application source file) in the simplest case:

```
typedef hpx::components::component<app::some_component> component_type;
typedef app::some_component some_component;

HPX_REGISTER_COMPONENT(component_type, some_component);

// The parameters for this macro have to be the same as used in the corresponding
// HPX_REGISTER_ACTION_DECLARATION() macro invocation above
typedef some_component::some_member_action some_component_some_action;
HPX_REGISTER_ACTION(some_component_some_action);
```

While these macro invocations are a bit more complex than those for simple global functions, they should still be manageable.

The most important macro invocation is the `HPX_DEFINE_COMPONENT_ACTION` in the header file as this defines the action type we need to invoke the member function. For a complete example of a simple component action see `component_in_executable.cpp`.

Reflection-based component actions (experimental)

Note: This feature requires a compiler with C++26 reflection support (HPX_HAVE_CXX26_REFLECTION) and is currently experimental.

When reflection support is available, component actions can be defined with a single macro instead of the three-step process described above:

```
namespace app
{
    struct some_component
    : hpx::components::component_base<some_component>
    {
        int some_member_function(std::string s)
        {
            return std::stoi(s);
        }
        // This single line replaces HPX_DEFINE_COMPONENT_ACTION,
        // HPX_REGISTER_ACTION_DECLARATION, and HPX_REGISTER_ACTION.
        HPX_COMPONENT_ACTION(some_component, some_member_function,
            some_member_action);
    };
}
```

The resulting `some_member_action` type can be used exactly like an action type created with `HPX_DEFINE_COMPONENT_ACTION`, with `hpx::post`, `hpx::async`, and `hpx::sync`, or by invoking it directly. No separate registration step is required in the source file.

Action invocation

The process of invoking a global function (or a member function of an object) with the help of the associated action is called ‘posting the action’. Actions can have arguments, which will be supplied while the action is applied. At the minimum, one parameter is required to post any action - the id of the *locality* the associated function should be invoked on (for global functions), or the id of the component instance (for member functions). Generally, *HPX* provides several ways to post an action, all of which are described in the following sections.

Generally, *HPX* actions are very similar to ‘normal’ C++ functions except that actions can be invoked remotely. Fig. ?? below shows an overview of the main API exposed by *HPX*. This shows the function invocation syntax as defined by the C++ language (dark gray), the additional invocation syntax as provided through C++ Standard Library features (medium gray), and the extensions added by *HPX* (light gray) where:

- `f` function to invoke,
- `p...`: (optional) arguments,
- `R`: return type of `f`,
- `action`: action type defined by, `HPX_DEFINE_PLAIN_ACTION` or `HPX_DEFINE_COMPONENT_ACTION` encapsulating `f`,
- `a`: an instance of the type `action`,
- `id`: the global address the action is applied to.

$R \ f(p \dots)$	Synchronous (return R)	Asynchronous (return $\text{future}<R>$)	Fire & Forget (return void)
Functions (direct)	$f(p \dots)$ C++	$\text{async}(f, p \dots)$	$\text{post}(f, p \dots)$
Functions (lazy)	$\text{bind}(f, p \dots)(\dots)$	$\text{async}(\text{bind}(f, p \dots), \dots)$ C++ Library	$\text{post}(\text{bind}(f, p \dots), \dots)$
Actions (direct)	$\text{HPX_ACTION}(f, a)$ $a(\text{id}, p \dots)$	$\text{HPX_ACTION}(f, a)$ $\text{async}(a, \text{id}, p \dots)$	$\text{HPX_ACTION}(f, a)$ $\text{post}(a, \text{id}, p \dots)$
Actions (lazy)	$\text{HPX_ACTION}(f, a)$ $\text{bind}(a, \text{id}, p \dots)(\dots)$	$\text{HPX_ACTION}(f, a)$ $\text{async}(\text{bind}(a, \text{id}, p \dots), \dots)$	$\text{HPX_ACTION}(f, a)$ $\text{post}(\text{bind}(a, \text{id}, p \dots), \dots)$ HPX

Fig. 2.8: Overview of the main API exposed by *HPX*.

This figure shows that *HPX* allows the user to **post** actions with a syntax similar to the C++ standard. In fact, all action types have an overloaded function operator allowing to synchronously **post** the action. Further, *HPX* implements `hpx::async` which semantically works similar to the way `std::async` works for plain C++ function.

Note: The similarity of posting an action to conventional function invocations extends even further. *HPX* implements `hpx::bind` and `hpx::function` two facilities which are semantically equivalent to the `std::bind` and `std::function` types as defined by the C++11 Standard. While `hpx::async` extends beyond the conventional semantics by supporting actions and conventional C++ functions, the *HPX* facilities `hpx::bind` and `hpx::function` extend beyond the conventional standard facilities too. The *HPX* facilities not only support conventional functions, but can be used for actions as well.

Additionally, *HPX* exposes `hpx::post` and `hpx::async_continue` both of which refine and extend the standard C++ facilities.

The different ways to invoke a function in *HPX* will be explained in more detail in the following sections.

Posting an action asynchronously without any synchronization

This method ('fire and forget') will make sure the function associated with the action is scheduled to run on the target *locality*. Posting the action does not wait for the function to start running, instead it is a fully asynchronous operation. The following example shows how to **post** the action as defined in the previous section on the local *locality* (the *locality* this code runs on):

```
some_global_action act;    // define an instance of some_global_action
hpx::post(act, hpx::find_here(), 2.0);
```

(the function `hpx::find_here()` returns the id of the local *locality*, i.e. the *locality* this code executes on).

Any component member function can be invoked using the same syntactic construct. Given that `id` is the global address for a component instance created earlier, this invocation looks like:

```
some_component_action act;    // define an instance of some_component_action
hpx::post(act, id, "42");
```

In this case any value returned from this action (e.g. in this case the integer 42 is ignored. Please look at *Action type definition* for the code defining the component action `some_component_action` used.

Posting an action asynchronously with synchronization

This method will make sure the action is scheduled to run on the target *locality*. Posting the action itself does not wait for the function to start running or to complete, instead this is a fully asynchronous operation similar to using `hpx::post` as described above. The difference is that this method will return an instance of a `hpx::future<>` encapsulating the result of the (possibly remote) execution. The future can be used to synchronize with the asynchronous operation. The following example shows how to post the action from above on the local *locality*:

```
some_global_action act;    // define an instance of some_global_action
hpx::future<void> f = hpx::async(act, hpx::find_here(), 2.0);
//
// ... other code can be executed here
//
f.get();    // this will possibly wait for the asynchronous operation to 'return'
```

(as before, the function `hpx::find_here()` returns the id of the local *locality* (the *locality* this code is executed on).

Note: The use of a `hpx::future<void>` allows the current thread to synchronize with any remote operation not returning any value.

Note: Any `std::future<>` returned from `std::async()` is required to block in its destructor if the value has not been set for this future yet. This is not true for `hpx::future<>` which will never block in its destructor, even if the value has not been returned to the future yet. We believe that consistency in the behavior of futures is more important than standards conformance in this case.

Any component member function can be invoked using the same syntactic construct. Given that `id` is the global address for a component instance created earlier, this invocation looks like:

```
some_component_action act;    // define an instance of some_component_action
hpx::future<int> f = hpx::async(act, id, "42");
//
// ... other code can be executed here
//
cout << f.get();    // this will possibly wait for the asynchronous operation to 'return'
↪ 42
```

Note: The invocation of `f.get()` will return the result immediately (without suspending the calling thread) if the result from the asynchronous operation has already been returned. Otherwise, the invocation of `f.get()` will suspend the execution of the calling thread until the asynchronous operation returns its result.

Posting an action synchronously

This method will schedule the function wrapped in the specified action on the target *locality*. While the invocation appears to be synchronous (as we will see), the calling thread will be suspended while waiting for the function to return. Invoking a plain action (e.g. a global function) synchronously is straightforward:

```
some_global_action act;    // define an instance of some_global_action
act(hpx::find_here(), 2.0);
```

While this call looks just like a normal synchronous function invocation, the function wrapped by the action will be scheduled to run on a new thread and the calling thread will be suspended. After the new thread has executed the wrapped global function, the waiting thread will resume and return from the synchronous call.

Equivalently, any action wrapping a component member function can be invoked synchronously as follows:

```
some_component_action act;    // define an instance of some_component_action
int result = act(id, "42");
```

The action invocation will either schedule a new thread locally to execute the wrapped member function (as before, *id* is the global address of the component instance the member function should be invoked on), or it will send a parcel to the remote *locality* of the component causing a new thread to be scheduled there. The calling thread will be suspended until the function returns its result. This result will be returned from the synchronous action invocation.

It is very important to understand that this ‘synchronous’ invocation syntax in fact conceals an asynchronous function call. This is beneficial as the calling thread is suspended while waiting for the outcome of a potentially remote operation. The *HPX* thread scheduler will schedule other work in the meantime, allowing the application to make further progress while the remote result is computed. This helps overlapping computation with communication and hiding communication latencies.

Note: The syntax of posting an action is always the same, regardless whether the target *locality* is remote to the invocation *locality* or not. This is a very important feature of *HPX* as it frees the user from the task of keeping track what actions have to be applied locally and which actions are remote. If the target for posting an action is local, a new thread is automatically created and scheduled. Once this thread is scheduled and run, it will execute the function encapsulated by that action. If the target is remote, *HPX* will send a parcel to the remote *locality* which encapsulates the action and its parameters. Once the parcel is received on the remote *locality* *HPX* will create and schedule a new thread there. Once this thread runs on the remote *locality*, it will execute the function encapsulated by the action.

Posting an action with a continuation but without any synchronization

This method is very similar to the method described in section *Posting an action asynchronously without any synchronization*. The difference is that it allows the user to chain a sequence of asynchronous operations, while handing the (intermediate) results from one step to the next step in the chain. Where `hpx::post` invokes a single function using ‘fire and forget’ semantics, `hpx::post_continue` asynchronously triggers a chain of functions without the need for the execution flow ‘to come back’ to the invocation site. Each of the asynchronous functions can be executed on a different *locality*.

Posting an action with a continuation and with synchronization

This method is very similar to the method described in section *Posting an action asynchronously with synchronization*. In addition to what `hpx::async` can do, the functions `hpx::async_continue` takes an additional function argument. This function will be called as the continuation of the executed action. It is expected to perform additional operations and to make sure that a result is returned to the original invocation site. This method chains operations asynchronously by providing a continuation operation which is automatically executed once the first action has finished executing.

As an example we chain two actions, where the result of the first action is forwarded to the second action and the result of the second action is sent back to the original invocation site:

```
// first action
std::int32_t action1(std::int32_t i)
{
    return i+1;
}
HPX_PLAIN_ACTION(action1);    // defines action1_type

// second action
std::int32_t action2(std::int32_t i)
{
    return i*2;
}
HPX_PLAIN_ACTION(action2);    // defines action2_type

// this code invokes 'action1' above and passes along a continuation
// function which will forward the result returned from 'action1' to
// 'action2'.
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1, hpx::make_continuation(act2),
        hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 86 ((42 + 1) * 2)
```

By default, the continuation is executed on the same *locality* as `hpx::async_continue` is invoked from. If you want to specify the *locality* where the continuation should be executed, the code above has to be written as:

```
// this code invokes 'action1' above and passes along a continuation
// function which will forward the result returned from 'action1' to
// 'action2'.
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1, hpx::make_continuation(act2, hpx::find_here()),
        hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 86 ((42 + 1) * 2)
```

Similarly, it is possible to chain more than 2 operations:

```
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1,
```

(continues on next page)

(continued from previous page)

```
    hpx::make_continuation(act2, hpx::make_continuation(act1)),
    hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 87 ((42 + 1) * 2 + 1)
```

The function `hpx::make_continuation` creates a special function object which exposes the following prototype:

```
struct continuation
{
    template <typename Result>
    void operator()(hpx::id_type id, Result&& result) const
    {
        ...
    }
};
```

where the parameters passed to the overloaded function operator `operator()()` are:

- the `id` is the global id where the final result of the asynchronous chain of operations should be sent to (in most cases this is the id of the `hpx::future` returned from the initial call to `hpx::async_continue`. Any custom continuation function should make sure this `id` is forwarded to the last operation in the chain.
- the `result` is the result value of the current operation in the asynchronous execution chain. This value needs to be forwarded to the next operation.

Note: All of those operations are implemented by the predefined continuation function object which is returned from `hpx::make_continuation`. Any (custom) function object used as a continuation should conform to the same interface.

Action error handling

Like in any other asynchronous invocation scheme it is important to be able to handle error conditions occurring while the asynchronous (and possibly remote) operation is executed. In *HPX* all error handling is based on standard C++ exception handling. Any exception thrown during the execution of an asynchronous operation will be transferred back to the original invocation *locality*, where it is rethrown during synchronization with the calling thread.

Important: Exceptions thrown during asynchronous execution can be transferred back to the invoking thread only for the synchronous and the asynchronous case with synchronization. Like with any other unhandled exception, any exception thrown during the execution of an asynchronous action *without* synchronization will result in calling `hpx::terminate` causing the running application to exit immediately.

Note: Even if error handling internally relies on exceptions, most of the API functions exposed by *HPX* can be used without throwing an exception. Please see *Working with exceptions* for more information.

As an example, we will assume that the following remote function will be executed:

```
namespace app
{
    void some_function_with_error(int arg)
```

(continues on next page)

(continued from previous page)

```

{
    if (arg < 0) {
        HPX_THROW_EXCEPTION(hpx::error::bad_parameter,
            "some_function_with_error",
            "some really bad error happened");
    }
    // do something else...
}
}

// This will define the action type 'some_error_action' which represents
// the function 'app::some_function_with_error'.
HPX_PLAIN_ACTION(app::some_function_with_error, some_error_action);

```

The use of `HPX_THROW_EXCEPTION` to report the error encapsulates the creation of a `hpx::exception` which is initialized with the error code `hpx::error::bad_parameter`. Additionally it carries the passed strings, the information about the file name, line number, and call stack of the point the exception was thrown from.

We invoke this action using the synchronous syntax as described before:

```

// note: wrapped function will throw hpx::exception
some_error_action act;           // define an instance of some_error_action
try {
    act(hpx::find_here(), -3);    // exception will be rethrown from here
}
catch (hpx::exception const& e) {
    // prints: 'some really bad error happened: HPX(bad parameter)'
    cout << e.what();
}

```

If this action is invoked asynchronously with synchronization, the exception is propagated to the waiting thread as well and is re-thrown from the future's function `get()`:

```

// note: wrapped function will throw hpx::exception
some_error_action act;           // define an instance of some_error_action
hpx::future<void> f = hpx::async(act, hpx::find_here(), -3);
try {
    f.get();                     // exception will be rethrown from here
}
catch (hpx::exception const& e) {
    // prints: 'some really bad error happened: HPX(bad parameter)'
    cout << e.what();
}

```

For more information about error handling please refer to the section *Working with exceptions*. There we also explain how to handle error conditions without having to rely on exception.

Writing components

A component in *HPX* is a C++ class which can be created remotely and for which its member functions can be invoked remotely as well. The following sections highlight how components can be defined, created, and used.

Defining components

In order for a C++ class type to be managed remotely in *HPX*, the type must be derived from the `hpx::components::component_base` template type. We call such C++ class types ‘components’.

Note that the component type itself is passed as a template argument to the base class:

```
// header file some_component.hpp

#include <hpx/include/components.hpp>

namespace app
{
    // Define a new component type 'some_component'
    struct some_component
        : hpx::components::component_base<some_component>
    {
        // This member function is has to be invoked remotely
        int some_member_function(std::string const& s)
        {
            return std::stoi(s);
        }

        // This will define the action type 'some_member_action' which
        // represents the member function 'some_member_function' of the
        // object type 'some_component'.
        HPX_DEFINE_COMPONENT_ACTION(some_component, some_member_function, some_member_
↪action);
    };
}

// This will generate the necessary boiler-plate code for the action allowing
// it to be invoked remotely. This declaration macro has to be placed in the
// header file defining the component itself.
//
// Note: The second argument to the macro below has to be systemwide-unique
//       C++ identifiers
//
HPX_REGISTER_ACTION_DECLARATION(app::some_component::some_member_action, some_component_
↪some_action);
```

There is more boiler plate code which has to be placed into a source file in order for the component to be usable. Every component type is required to have macros placed into its source file, one for each component type and one macro for each of the actions defined by the component type.

For instance:

```
// source file some_component.cpp
```

(continues on next page)

(continued from previous page)

```

#include "some_component.hpp"

// The following code generates all necessary boiler plate to enable the
// remote creation of 'app::some_component' instances with 'hpx::new_<>()'
//
using some_component = app::some_component;
using some_component_type = hpx::components::component<some_component>;

// Please note that the second argument to this macro must be a
// (system-wide) unique C++-style identifier (without any namespaces)
//
HPX_REGISTER_COMPONENT(some_component_type, some_component);

// The parameters for this macro have to be the same as used in the corresponding
// HPX_REGISTER_ACTION_DECLARATION() macro invocation in the corresponding
// header file.
//
// Please note that the second argument to this macro must be a
// (system-wide) unique C++-style identifier (without any namespaces)
//
HPX_REGISTER_ACTION(app::some_component::some_member_action, some_component_some_action);

```

Defining client side representation classes

Often it is very convenient to define a separate type for a component which can be used on the client side (from where the component is instantiated and used). This step might seem as unnecessary duplicating code, however it significantly increases the type safety of the code.

A possible implementation of such a client side representation for the component described in the previous section could look like:

```

#include <hpx/include/components.hpp>

namespace app
{
    // Define a client side representation type for the component type
    // 'some_component' defined in the previous section.
    //
    struct some_component_client
    : hpx::components::client_base<some_component_client, some_component>
    {
        using base_type = hpx::components::client_base<
            some_component_client, some_component>;

        some_component_client(hpx::future<hpx::id_type> && id)
            : base_type(std::move(id))
        {}

        hpx::future<int> some_member_function(std::string const& s)
        {
            some_component::some_member_action act;

```

(continues on next page)

(continued from previous page)

```

        return hpx::async(act, get_id(), s);
    }
};
}

```

A client side object stores the global id of the component instance it represents. This global id is accessible by calling the function `client_base<>::get_id()`. The special constructor which is provided in the example allows to create this client side object directly using the API function `hpx::new_`.

Creating component instances

Instances of defined component types can be created in two different ways. If the component to create has a defined client side representation type, then this can be used, otherwise use the server type.

The following examples assume that `some_component_type` is the type of the server side implementation of the component to create. All additional arguments (see , ... notation below) are passed through to the corresponding constructor calls of those objects:

```

// create one instance on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f =
    hpx::new_<some_component_type>(here, ...);

// create one instance using the given distribution
// policy (here: hpx::colocating_distribution_policy)
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f =
    hpx::new_<some_component_type>(hpx::colocated(here), ...);

// create multiple instances on the given locality
hpx::id_type here = find_here();
hpx::future<std::vector<hpx::id_type>> f =
    hpx::new_<some_component_type[]>(here, num, ...);

// create multiple instances using the given distribution
// policy (here: hpx::binpacking_distribution_policy)
hpx::future<std::vector<hpx::id_type>> f = hpx::new_<some_component_type[]>(
    hpx::binpacking(hpx::find_all_localities()), num, ...);

```

The examples below demonstrate the use of the same API functions for creating client side representation objects (instead of just plain ids). These examples assume that `client_type` is the type of the client side representation of the component type to create. As above, all additional arguments (see , ... notation below) are passed through to the corresponding constructor calls of the server side implementation objects corresponding to the `client_type`:

```

// create one instance on the given locality
hpx::id_type here = hpx::find_here();
client_type c = hpx::new_<client_type>(here, ...);

// create one instance using the given distribution
// policy (here: hpx::colocating_distribution_policy)
hpx::id_type here = hpx::find_here();
client_type c = hpx::new_<client_type>(hpx::colocated(here), ...);

```

(continues on next page)

(continued from previous page)

```

// create multiple instances on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<std::vector<client_type>>> f =
    hpx::new_<client_type[]>(here, num, ...);

// create multiple instances using the given distribution
// policy (here: hpx::binpacking_distribution_policy)
hpx::future<std::vector<client_type>>> f = hpx::new_<client_type[]>(
    hpx::binpacking(hpx::find_all_localities()), num, ...);

```

Using component instances

After having created the component instances as described above, we can simply use them as indicated below:

```

#include <hpx/include/components.hpp>
#include <iostream>
#include <vector>

// Define a simple component
struct some_component : hpx::components::component_base<some_component>
{
    void print() const
    {
        std::cout << "Hello from component instance!" << std::endl;
    }
    HPX_DEFINE_COMPONENT_ACTION(some_component, print, print_action);
};

typedef some_component::print_action print_action;

// Create one instance on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f1 =
    hpx::new_<some_component>(here);

// Get the future value
hpx::id_type instance_id = f1.get();

// Invoke action on the instance
hpx::async<print_action>(instance_id).get();

// Create multiple instances on the given locality
int num = 3;
hpx::future<std::vector<hpx::id_type>>> f2 =
    hpx::new_<some_component[]>(here, num);

// Get the future value
std::vector<hpx::id_type> instance_ids = f2.get();

// Invoke action on each instance

```

(continues on next page)

(continued from previous page)

```
for (const auto& id : instance_ids)
{
    hpx::async<print_action>(id).get();
}
```

We can use the component instances with distribution policies the same way.

Segmented containers

In parallel programming, there is now a plethora of solutions aimed at implementing “partially contiguous” or segmented data structures, whether on shared memory systems or distributed memory systems. *HPX* implements such structures by drawing inspiration from Standard C++ containers.

Using segmented containers

A segmented container is a template class that is described in the namespace `hpx`. All segmented containers are very similar semantically to their sequential counterpart (defined in namespace `std` but with an additional template parameter named `DistPolicy`). The distribution policy is an optional parameter that is passed last to the segmented container constructor (after the container size when no default value is given, after the default value if not). The distribution policy describes the manner in which a container is segmented and the placement of each segment among the available runtime localities.

However, only a part of the `std` container member functions were reimplemented:

- (constructor), (destructor), operator=
- operator[]
- begin, cbegin, end, cend
- size

An example of how to use the `partitioned_vector` container would be:

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

// By default, the number of segments is equal to the current number of
// localities
//
hpx::partitioned_vector<double> va(50);
hpx::partitioned_vector<double> vb(50, 0.0);
```

An example of how to use the `partitioned_vector` container with distribution policies would be:

```
#include <hpx/include/partitioned_vector.hpp>
#include <hpx/modules/runtime_distributed.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
```

(continues on next page)

(continued from previous page)

```
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

std::size_t num_segments = 10;
std::vector<hpx::id_type> locs = hpx::find_all_localities();

auto layout =
    hpx::container_layout( num_segments, locs );

// The number of segments is 10 and those segments are spread across the
// localities collected in the variable locs in a Round-Robin manner
//
hpx::partitioned_vector<double> va(50, layout);
hpx::partitioned_vector<double> vb(50, 0.0, layout);
```

By definition, a segmented container must be accessible from any thread although its construction is synchronous only for the thread who has called its constructor. To overcome this problem, it is possible to assign a symbolic name to the segmented container:

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

hpx::future<void> fserver = hpx::async(
    []() {
        hpx::partitioned_vector<double> v(50);

        // Register the 'partitioned_vector' with the name "some_name"
        //
        v.register_as("some_name");

        /* Do some code */
    });

hpx::future<void> fclient =
    hpx::async(
        []() {
            // Naked 'partitioned_vector'
            //
            hpx::partitioned_vector<double> v;

            // Now the variable v points to the same 'partitioned_vector' that has
            // been registered with the name "some_name"
            //
            v.connect_to("some_name");

            /* Do some code */
        });
```

Segmented containers

HPX provides the following segmented containers:

Table 2.23: Sequence containers

Name	Description	In header	C++ standard
<code>hpx::partitioned_vector</code>	Dynamic segmented contiguous array.	<code><hpx/include/partitioned_vector.hpp></code>	<code>vector</code> ¹⁷⁶

Table 2.24: Unordered associative containers

Name	Description	In header	C++ standard
<code>hpx::unordered_map</code>	Segmented collection of key-value pairs, hashed by keys, keys are unique.	<code><hpx/include/unordered_map.hpp></code>	<code>unordered_map</code> ¹⁷⁷

Segmented iterators and segmented iterator traits

The basic iterator used in the STL library is only suitable for one-dimensional structures. The iterators we use in HPX must adapt to the segmented format of our containers. Our iterators are then able to know when incrementing themselves if the next element of type T is in the same data segment or in another segment. In this second case, the iterator will automatically point to the beginning of the next segment.

Note: Note that the dereference operation `operator *` does not directly return a reference of type T& but an intermediate object wrapping this reference. When this object is used as an l-value, a remote write operation is performed; When this object is used as an r-value, implicit conversion to T type will take care of performing remote read operation.

It is sometimes useful not only to iterate element by element, but also segment by segment, or simply get a local iterator in order to avoid additional construction costs at each dereferencing operations. To mitigate this need, the `hpx::traits::segmented_iterator_traits` are used.

With `segmented_iterator_traits` users can uniformly get the iterators which specifically iterates over segments (by providing a segmented iterator as a parameter), or get the local begin/end iterators of the nearest local segment (by providing a per-segment iterator as a parameter):

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using iterator = hpx::partitioned_vector<T>::iterator;
using traits    = hpx::traits::segmented_iterator_traits<iterator>;

hpx::partitioned_vector<T> v;
std::size_t count = 0;
```

(continues on next page)

¹⁷⁶ <http://en.cppreference.com/w/cpp/container/vector>

¹⁷⁷ http://en.cppreference.com/w/cpp/container/unordered_map

(continued from previous page)

```

auto seg_begin = traits::segment(v.begin());
auto seg_end   = traits::segment(v.end());

// Iterate over segments
for (auto seg_it = seg_begin; seg_it != seg_end; ++seg_it)
{
    auto loc_begin = traits::begin(seg_it);
    auto loc_end   = traits::end(seg_it);

    // Iterate over elements inside segments
    for (auto lit = loc_begin; lit != loc_end; ++lit, ++count)
    {
        *lit = count;
    }
}

```

Which is equivalent to:

```

hpx::partitioned_vector<T> v;
std::size_t count = 0;

auto begin = v.begin();
auto end   = v.end();

for (auto it = begin; it != end; ++it, ++count)
{
    *it = count;
}

```

Using views

The use of multidimensional arrays is quite common in the numerical field whether to perform dense matrix operations or to process images. It exist many libraries which implement such object classes overloading their basic operators (e.g. +, -, *, (), etc.). However, such operation becomes more delicate when the underlying data layout is segmented or when it is mandatory to use optimized linear algebra subroutines (i.e. BLAS subroutines).

Our solution is thus to relax the level of abstraction by allowing the user to work not directly on n-dimensionnal data, but on “n-dimensionnal collections of 1-D arrays”. The use of well-accepted techniques on contiguous data is thus preserved at the segment level, and the composability of the segments is made possible thanks to multidimensional array-inspired access mode.

Preface: Why SPMD?

Although *HPX* refutes by design this programming model, the *locality* plays a dominant role when it comes to implement vectorized code. To maximize local computations and avoid unneeded data transfers, a parallel section (or Single Programming Multiple Data section) is required. Because the use of global variables is prohibited, this parallel section is created via the RAII idiom.

To define a parallel section, simply write an action taking a `spmd_block` variable as a first parameter:

```
#include <hpx/modules/collectives.hpp>

void bulk_function(hpx::lcos::spmd_block block /* , arg0, arg1, ... */)
{
    // Parallel section

    /* Do some code */
}
HPX_PLAIN_ACTION(bulk_function, bulk_action);
```

Note: In the following paragraphs, we will use the term “image” several times. An image is defined as a lightweight process whose entry point is a function provided by the user. It’s an “image of the function”.

The `spmd_block` class contains the following methods:

- Team information: `get_num_images`, `this_image`, `images_per_locality`
- Control statements: `sync_all`, `sync_images`

Here is a sample code summarizing the features offered by the `spmd_block` class:

```
#include <hpx/modules/collectives.hpp>

void bulk_function(hpx::lcos::spmd_block block /* , arg0, arg1, ... */)
{
    std::size_t num_images = block.get_num_images();
    std::size_t this_image = block.this_image();
    std::size_t images_per_locality = block.images_per_locality();

    /* Do some code */

    // Synchronize all images in the team
    block.sync_all();

    /* Do some code */

    // Synchronize image 0 and image 1
    block.sync_images(0,1);

    /* Do some code */

    std::vector<std::size_t> vec_images = {2,3,4};

    // Synchronize images 2, 3 and 4
    block.sync_images(vec_images);
}
```

(continues on next page)

(continued from previous page)

```

// Alternative call to synchronize images 2, 3 and 4
block.sync_images(vec_images.begin(), vec_images.end());

/* Do some code */

// Non-blocking version of sync_all()
hpx::future<void> event =
    block.sync_all(hpx::launch::async);

// Callback waiting for 'event' to be ready before being scheduled
hpx::future<void> cb =
    event.then(
        [] (hpx::future<void>)
        {

            /* Do some code */

        });

// Finally wait for the execution tree to be finished
cb.get();
}
HPX_PLAIN_ACTION(bulk_test_function, bulk_test_action);

```

Then, in order to invoke the parallel section, call the function `define_spmd_block` specifying an arbitrary symbolic name and indicating the number of images per *locality* to create:

```

void bulk_function(hpx::lcos::spmd_block block, /* , arg0, arg1, ... */)
{
}
HPX_PLAIN_ACTION(bulk_test_function, bulk_test_action);

int main()
{
    /* std::size_t arg0, arg1, ...; */

    bulk_action act;
    std::size_t images_per_locality = 4;

    // Instantiate the parallel section
    hpx::lcos::define_spmd_block(
        "some_name", images_per_locality, std::move(act) /*, arg0, arg1, ... */);

    return 0;
}

```

Note: In principle, the user should never call the `spmd_block` constructor. The `define_spmd_block` function is responsible of instantiating `spmd_block` objects and broadcasting them to each created image.

SPMD multidimensional views

Some classes are defined as “container views” when the purpose is to observe and/or modify the values of a container using another perspective than the one that characterizes the container. For example, the values of an `std::vector` object can be accessed via the expression `[i]`. Container views can be used, for example, when it is desired for those values to be “viewed” as a 2D matrix that would have been flattened in a `std::vector`. The values would be possibly accessible via the expression `vv(i, j)` which would call internally the expression `v[k]`.

By default, the `partitioned_vector` class integrates 1-D views of its segments:

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using iterator = hpx::partitioned_vector<double>::iterator;
using traits    = hpx::traits::segmented_iterator_traits<iterator>;

hpx::partitioned_vector<double> v;

// Create a 1-D view of the vector of segments
auto vv = traits::segment(v.begin());

// Access segment i
std::vector<double> v = vv[i];
```

Our views are called “multidimensional” in the sense that they generalize to N dimensions the purpose of `segmented_iterator_traits::segment()` in the 1-D case. Note that in a parallel section, the 2-D expression `a(i, j) = b(i, j)` is quite confusing because without convention, each of the images invoked will race to execute the statement. For this reason, our views are not only multidimensional but also “spmd-aware”.

Note: SPMD-awareness: The convention is simple. If an assignment statement contains a view subscript as an l-value, it is only and only the image holding the r-value who is evaluating the statement. (In MPI sense, it is called a Put operation).

Subscript-based operations

Here are some examples of using subscripts in the 2-D view case:

```
#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using Vec = hpx::partitioned_vector<double>;
using View_2D = hpx::partitioned_vector_view<double, 2>;
```

(continues on next page)

(continued from previous page)

```

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t height, width;

    // Instantiate the view
    View_2D vv(block, v.begin(), v.end(), {height,width});

    // The l-value is a view subscript, the image that owns vv(1,0)
    // evaluates the assignment.
    vv(0,1) = vv(1,0);

    // The l-value is a view subscript, the image that owns the r-value
    // (result of expression 'std::vector<double>(4,1.0)') evaluates the
    // assignment : oops! race between all participating images.
    vv(2,3) = std::vector<double>(4,1.0);
}

```

Iterator-based operations

Here are some examples of using iterators in the 3-D view case:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(int);

using Vec = hpx::partitioned_vector<int>;
using View_3D = hpx::partitioned_vector_view<int,3>;

/* Do some code */

Vec v1, v2;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t size_x, size_y, size_z;

    // Instantiate the views
    View_3D vv1(block, v1.begin(), v1.end(), {size_x,size_y,size_z});
    View_3D vv2(block, v2.begin(), v2.end(), {size_x,size_y,size_z});

    // Save previous segments covered by vv1 into segments covered by vv2
    auto vv2_it = vv2.begin();

```

(continues on next page)

(continued from previous page)

```

auto vv1_it = vv1.cbegin();

for(; vv2_it != vv2.end(); vv2_it++, vv1_it++)
{
    // It's a Put operation
    *vv2_it = *vv1_it;
}

// Ensure that all images have performed their Put operations
block.sync_all();

// Ensure that only one image is putting updated data into the different
// segments covered by vv1
if(block.this_image() == 0)
{
    int idx = 0;

    // Update all the segments covered by vv1
    for(auto i = vv1.begin(); i != vv1.end(); i++)
    {
        // It's a Put operation
        *i = std::vector<float>(elt_size,idx++);
    }
}
}

```

Here is an example that shows how to iterate only over segments owned by the current image:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/components/containers/partitioned_vector/partitioned_vector_local_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(float);

using Vec = hpx::partitioned_vector<float>;
using View_1D = hpx::partitioned_vector_view<float,1>;

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t num_segments;

    // Instantiate the view
    View_1D vv(block, v.begin(), v.end(), {num_segments});

    // Instantiate the local view from the view

```

(continues on next page)

(continued from previous page)

```

auto local_vv = hpx::local_view(vv);

for ( auto i = local_vv.begin(); i != local_vv.end(); i++ )
{
    std::vector<float> & segment = *i;

    /* Do some code */
}
}

```

Instantiating sub-views

It is possible to construct views from other views: we call it sub-views. The constraint nevertheless for the subviews is to retain the dimension and the value type of the input view. Here is an example showing how to create a sub-view:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(float);

using Vec = hpx::partitioned_vector<float>;
using View_2D = hpx::partitioned_vector_view<float,2>;

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t N = 20;
    std::size_t tilesz = 5;

    // Instantiate the view
    View_2D vv(block, v.begin(), v.end(), {N,N});

    // Instantiate the subview
    View_2D svv(
        block,&vv(tilesz,0),&vv(2*tilesz-1,tilesz-1),{tilesz,tilesz},{N,N});

    if(block.this_image() == 0)
    {
        // Equivalent to 'vv(tilesz,0) = 2.0f'
        svv(0,0) = 2.0f;

        // Equivalent to 'vv(2*tilesz-1,tilesz-1) = 3.0f'
        svv(tilesz-1,tilesz-1) = 3.0f;
    }
}

```

(continues on next page)

(continued from previous page)

}

Note: The last parameter of the subview constructor is the size of the original view. If one would like to create a subview of the subview and so on, this parameter should stay unchanged. {N,N} for the above example).

C++ co-arrays

Fortran has extended its scalar element indexing approach to reference each segment of a distributed array. In this extension, a segment is attributed a ?co-index? and lives in a specific *locality*. A co-index provides the application with enough information to retrieve the corresponding data reference. In C++, containers present themselves as a ?smarter? alternative of Fortran arrays but there are still no corresponding standardized features similar to the Fortran co-indexing approach. We present here an implementation of such features in *HPX*.

Preface: co-array, a segmented container tied to a SPMD multidimensional views

As mentioned before, a co-array is a distributed array whose segments are accessible through an array-inspired access mode. We have previously seen that it is possible to reproduce such access mode using the concept of views. Nevertheless, the user must pre-create a segmented container to instantiate this view. We illustrate below how a single constructor call can perform those two operations:

```
#include <hpx/components/containers/coarray/coarray.hpp>
#include <hpx/modules/collectives.hpp>

// The following code generates all necessary boiler plate to enable the
// co-creation of 'coarray'
//
HPX_REGISTER_COARRAY(double);

// Parallel section (suppose 'block' an spmd_block instance)
{
    using hpx::container::placeholders::_;

    std::size_t height=32, width=4, segment_size=10;

    hpx::coarray<double,3> a(block, "a", {height,width,_}, segment_size);

    /* Do some code */
}
```

Unlike segmented containers, a co-array object can only be instantiated within a parallel section. Here is the description of the parameters to provide to the coarray constructor:

Table 2.25: Parameters of coarray constructor

Parameter	Description
<code>block</code>	Reference to a <code>spmd_block</code> object
<code>"a"</code>	Symbolic name of type <code>std::string</code>
<code>{height,width, _}</code>	Dimensions of the coarray object
<code>segment_size</code>	Size of a co-indexed element (i.e. size of the object referenced by the expression <code>a(i,j,k)</code>)

Note that the “last dimension size” cannot be set by the user. It only accepts the constexpr variable `hpx::container::placeholders::_`. This size, which is considered private, is equal to the number of current images (value returned by `block.get_num_images()`).

Note: An important constraint to remember about coarray objects is that all segments sharing the same “last dimension index” are located in the same image.

Using co-arrays

The member functions owned by the coarray objects are exactly the same as those of `spmd` multidimensional views. These are:

- * Subscript-based operations
- * Iterator-based operations

However, one additional functionality is provided. Knowing that the element `a(i,j,k)` is in the memory of the `k`th image, the use of local subscripts is possible.

Note: For `spmd` multidimensional views, subscripts are only global as it still involves potential remote data transfers.

Here is an example of using local subscripts:

```
#include <hpx/components/containers/coarray/coarray.hpp>
#include <hpx/modules/collectives.hpp>

// The following code generates all necessary boiler plate to enable the
// co-creation of 'coarray'
//
HPX_REGISTER_COARRAY(double);

// Parallel section (suppose 'block' an spmd_block instance)
{
    using hpx::container::placeholders::_;

    std::size_t height=32, width=4, segment_size=10;

    hpx::coarray<double,3> a(block, "a", {height,width,_}, segment_size);

    double idx = block.this_image()*height*width;

    for (std::size_t j = 0; j<width; j++)
```

(continues on next page)

(continued from previous page)

```

    for (std::size_t i = 0; i < height; i++)
    {
        // Local write operation performed via the use of local subscript
        a(i,j,_) = std::vector<double>(elt_size,idx);
        idx++;
    }

    block.sync_all();
}

```

Note: When the “last dimension index” of a subscript is equal to `hpx::container::placeholders::_`, local subscript (and not global subscript) is used. It is equivalent to a global subscript used with a “last dimension index” equal to the value returned by `block.this_image()`.

2.4.13 Running on batch systems

This section walks you through launching *HPX* applications on various batch systems.

How to use *HPX* applications with PBS

Most *HPX* applications are executed on parallel computers. These platforms typically provide integrated job management services that facilitate the allocation of computing resources for each parallel program. *HPX* includes support for one of the most common job management systems, the Portable Batch System (PBS).

All PBS jobs require a script to specify the resource requirements and other parameters associated with a parallel job. The PBS script is basically a shell script with PBS directives placed within commented sections at the beginning of the file. The remaining (not commented-out) portions of the file executes just like any other regular shell script. While the description of all available PBS options is outside the scope of this tutorial (the interested reader may refer to in-depth [documentation](#)¹⁷⁸ for more information), below is a minimal example to illustrate the approach. The following test application will use the multithreaded `hello_world_distributed` program, explained in the section *Remote execution with actions*.

```

#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/.packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`

```

Caution: If the first application specific argument (inside `$APP_OPTIONS`) is a non-option (i.e., does not start with a `-` or a `--`), then the argument has to be placed before the option `--hpx:nodes`, which, in this case, should be the last option on the command line.

Alternatively, use the option `--hpx:endnodes` to explicitly mark the end of the list of node names:

```
$ pbsdsh -u $APP_PATH --hpx:nodes`cat $PBS_NODEFILE` --hpx:endnodes $APP_OPTIONS
```

¹⁷⁸ <http://www.clusterresources.com/torquedocs21/>

The `#PBS -l nodes=2:ppn=4` directive will cause two compute nodes to be allocated for the application, as specified in the option `nodes`. Each of the nodes will dedicate four cores to the program, as per the option `ppn`, short for “processors per node” (PBS does not distinguish between processors and cores). Note that requesting more cores per node than physically available is pointless and may prevent PBS from accepting the script.

On newer PBS versions the PBS command syntax might be different. For instance, the PBS script above would look like:

```
#!/bin/bash
#
#PBS -l select=2:ncpus=4

APP_PATH=~/packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`
```

`APP_PATH` and `APP_OPTIONS` are shell variables that respectively specify the correct path to the executable (`hello_world_distributed` in this case) and the command line options. Since the `hello_world_distributed` application doesn’t need any command line options, `APP_OPTIONS` has been left empty. Unlike in other execution environments, there is no need to use the `--hpx:threads` option to indicate the required number of OS threads per node; the *HPX* library will derive this parameter automatically from PBS.

Finally, `pbsdsh` is a PBS command that starts tasks to the resources allocated to the current job. It is recommended to leave this line as shown and modify only the PBS options and shell variables as needed for a specific application.

Important: A script invoked by `pbsdsh` starts in a very basic environment: the user’s `$HOME` directory is defined and is the current directory, the `LANG` variable is set to `C` and the `PATH` is set to the basic `/usr/local/bin:/usr/bin:/bin` as defined in a system-wide file `pbs_environment`. Nothing that would normally be set up by a system shell profile or user shell profile is defined, unlike the environment for the main job script.

Another choice is for the `pbsdsh` command in your main job script to invoke your program via a shell, like `sh` or `bash`, so that it gives an initialized environment for each instance. Users can create a small script `runme.sh`, which is used to invoke the program:

```
#!/bin/bash
# Small script which invokes the program based on what was passed on its
# command line.
#
# This script is executed by the bash shell which will initialize all
# environment variables as usual.
$@
```

Now, the script is invoked using the `pbsdsh` tool:

```
#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/packages/hpx/bin/hello_world_distributed
APP_OPTIONS=
```

(continues on next page)

(continued from previous page)

```
pbsdsh -u runme.sh $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`
```

All that remains now is submitting the job to the queuing system. Assuming that the contents of the PBS script were saved in the file `pbs_hello_world.sh` in the current directory, this is accomplished by typing:

```
$ qsub ./pbs_hello_world_pbs.sh
```

If the job is accepted, `qsub` will print out the assigned job ID, which may look like:

```
$ 42.supercomputer.some.university.edu
```

To check the status of your job, issue the following command:

```
$ qstat 42.supercomputer.some.university.edu
```

and look for a single-letter job status symbol. The common cases include:

- *Q* - signifies that the job is queued and awaiting its turn to be executed.
- *R* - indicates that the job is currently running.
- *C* - means that the job has completed.

The example `qstat` output below shows a job waiting for execution resources to become available:

Job id	Name	User	Time Use	S	Queue
-----	-----	-----	-----	-----	-----
42.supercomputer	...ello_world.sh	joe_user		0 Q	batch

After the job completes, PBS will place two files, `pbs_hello_world.sh.o42` and `pbs_hello_world.sh.e42`, in the directory where the job was submitted. The first contains the standard output and the second contains the standard error from all the nodes on which the application executed. In our example, the error output file should be empty and the standard output file should contain something similar to:

```
hello world from OS-thread 3 on locality 0
hello world from OS-thread 2 on locality 0
hello world from OS-thread 1 on locality 1
hello world from OS-thread 0 on locality 0
hello world from OS-thread 3 on locality 1
hello world from OS-thread 2 on locality 1
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 1
```

Congratulations! You have just run your first distributed *HPX* application!

How to use HPX applications with SLURM

Just like PBS (described in section *How to use HPX applications with PBS*), SLURM is a job management system which is widely used on large supercomputing systems. Any HPX application can easily be run using SLURM. This section describes how this can be done.

The easiest way to run an HPX application using SLURM is to utilize the command line tool `srun`, which interacts with the SLURM batch scheduling system:

```
$ srun -p <partition> -N <number-of-nodes> hpx-application <application-arguments>
```

Here, `<partition>` is one of the node partitions existing on the target machine (consult the machine's documentation to get a list of existing partitions) and `<number-of-nodes>` is the number of compute nodes that should be used. By default, the HPX application is started with one *locality* per node and uses all available cores on a node. You can change the number of localities started per node (for example, to account for NUMA effects) by specifying the `-n` option of `srun`. The number of cores per *locality* can be set by `-c`. The `<application-arguments>` are any application specific arguments that need to be passed on to the application.

Note: There is no need to use any of the HPX command line options related to the number of localities, number of threads, or related to networking ports. All of this information is automatically extracted from the SLURM environment by the HPX startup code.

Important: The `srun` documentation explicitly states: “If `-c` is specified without `-n`, as many tasks will be allocated per node as possible while satisfying the `-c` restriction. For instance on a cluster with 8 CPUs per node, a job request for 4 nodes and 3 CPUs per task may be allocated 3 or 6 CPUs per node (1 or 2 tasks per node) depending upon resource consumption by other jobs.” For this reason, it's recommended to always specify `-n <number-of-instances>`, even if `<number-of-instances>` is equal to one (1).

Interactive shells

To get an interactive development shell on one of the nodes, users can issue the following command:

```
$ srun -p <node-type> -N <number-of-nodes> --pty /bin/bash -l
```

After the shell has been opened, users can run their HPX application. By default, it uses all available cores. Note that if you requested one node, you don't need to do `srun` again. However, if you requested more than one node, and want to run your distributed application, you can use `srun` again to start up the distributed HPX application. It will use the resources that have been requested for the interactive shell.

Scheduling batch jobs

The above mentioned method of running HPX applications is fine for development purposes. The disadvantage that comes with `srun` is that it only returns once the application is finished. This might not be appropriate for longer-running applications (for example, benchmarks or larger scale simulations). In order to cope with that limitation, users can use the `sbatch` command.

The `sbatch` command expects a script that it can run once the requested resources are available. In order to request resources, users need to add `#SBATCH` comments in their script or provide the necessary parameters to `sbatch` directly. The parameters are the same as with `run`. The commands you need to execute are the same you would need to start your application as if you were in an interactive shell.

2.4.14 Debugging HPX applications

Using a debugger with HPX applications

Using a debugger such as `gdb` with *HPX* applications is no problem. However, there are some things to keep in mind to make the experience somewhat more productive.

Call stacks in *HPX* can often be quite unwieldy as the library is heavily templated and the call stacks can be very deep. For this reason it is sometimes a good idea compile *HPX* in `RelWithDebInfo` mode, which applies some optimizations but keeps debugging symbols. This can often compress call stacks significantly. On the other hand, stepping through the code can also be more difficult because of statements being reordered and variables being optimized away. Also, note that because *HPX* implements user-space threads and context switching, call stacks may not always be complete in a debugger.

HPX launches not only worker threads but also a few helper threads. The first thread is the main thread, which typically does no work in an *HPX* application, except at startup and shutdown. If using the default settings, *HPX* will spawn six additional threads (used for service thread pools). The first worker thread is usually the eighth thread, and most user codes will be run on these worker threads. The last thread is a helper thread used for *HPX* shutdown.

Finally, since *HPX* is a multi-threaded runtime, the following `gdb` options can be helpful:

```
set pagination off
set non-stop on
```

Non-stop mode allows users to have a single thread stop on a breakpoint without stopping all other threads as well.

Using sanitizers with HPX applications

Warning: Not all parts of *HPX* are sanitizer clean. This means that users may end up with false positives from *HPX* itself when using sanitizers for their applications.

To use sanitizers with *HPX*, turn on `HPX_WITH_SANITIZERS` and turn off `HPX_WITH_STACKOVERFLOW_DETECTION` during `CMake`¹⁷⁹ configuration. It's recommended to also build Boost with the same sanitizers that will be used for *HPX*. The appropriate sanitizers can then be enabled using `CMake` by appending `-fsanitize=address` `-fno-omit-frame-pointer` to `CMAKE_CXX_FLAGS` and `-fsanitize=address` to `CMAKE_EXE_LINKER_FLAGS`. Replace `address` with the sanitizer that you want to use.

Debugging applications using core files

For *HPX* to generate useful core files, *HPX* has to be compiled without signal and exception handlers `HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL`. If this option is not specified, the signal handlers change the application state. For example, after a segmentation fault the stack trace will show the signal handler. Similarly, unhandled exceptions are also caught by these handlers and the stack trace will not point to the location where the unhandled exception was thrown.

In general, core files are a helpful tool to inspect the state of the application at the moment of the crash (post-mortem debugging), without the need of attaching a debugger beforehand. This approach to debugging is especially useful if the error cannot be reliably reproduced, as only a single crashed application run is required to gain potentially helpful information like a stacktrace.

To debug with core files, the operating system first has to be told to actually write them. On most Unix systems this can be done by calling:

¹⁷⁹ <https://www.cmake.org>

```
$ ulimit -c unlimited
```

in the shell. Now the debugger can be started up with:

```
$ gdb <application> <core file name>
```

The debugger should now display the last state of the application. The default file name for core files is `core`.

2.4.15 Optimizing HPX applications

Performance counters

Performance counters in *HPX* are used to provide information as to how well the runtime system or an application is performing. The counter data can help determine system bottlenecks, and fine-tune system and application performance. The *HPX* runtime system, its networking, and other layers provide counter data that an application can consume to provide users with information about how well the application is performing.

Applications can also use counter data to determine how much system resources to consume. For example, an application that transfers data over the network could consume counter data from a network switch to determine how much data to transfer without competing for network bandwidth with other network traffic. The application could use the counter data to adjust its transfer rate as the bandwidth usage from other network traffic increases or decreases.

Performance counters are *HPX* parallel processes that expose a predefined interface. *HPX* exposes special API functions that allow one to create, manage, and read the counter data, and release instances of performance counters. Performance Counter instances are accessed by name, and these names have a predefined structure which is described in the section *Performance counter names*. The advantage of this is that any Performance Counter can be accessed remotely (from a different *locality*) or locally (from the same *locality*). Moreover, since all counters expose their data using the same API, any code consuming counter data can be utilized to access arbitrary system information with minimal effort.

Counter data may be accessed in real time. More information about how to consume counter data can be found in the section *Consuming performance counter data*.

All *HPX* applications provide command line options related to performance counters, such as the ability to list available counter types, or periodically query specific counters to be printed to the screen or save them in a file. For more information, please refer to the section *HPX Command Line Options*.

Performance counter names

All Performance Counter instances have a name uniquely identifying each instance. This name can be used to access the counter, retrieve all related meta data, and to query the counter data (as described in the section *Consuming performance counter data*). Counter names are strings with a predefined structure. The general form of a countername is:

```
/objectname{full_instancename}/countername@parameters
```

where `full_instancename` could be either another (full) counter name or a string formatted as:

```
parentinstancename#parentindex/instancename#instanceindex
```

Each separate part of a countername (e.g., `objectname`, `countername`, `parentinstancename`, `instancename`, and `parameters`) should start with a letter ('a'... 'z', 'A'... 'Z') or an underscore character ('_'), optionally followed by letters, digits ('0'... '9'), hyphen ('-'), or underscore characters. Whitespace is not allowed inside a counter name. The characters '/', '{', '}', '#', and '@' have a special meaning and are used to delimit the different parts of the counter name.

The parts `parentinstanceindex` and `instanceindex` are integers. If an index is not specified, *HPX* will assume a default of `-1`.

Two counter name examples

This section gives examples of both simple counter names and aggregate counter names. For more information on simple and aggregate counter names, please see *Performance counter instances*.

An example of a well-formed (and meaningful) simple counter name would be:

```
/threads{locality#0/total}/count/cumulative
```

This counter returns the current cumulative number of executed (retired) *HPX* threads for the *locality* `0`. The counter type of this counter is `/threads/count/cumulative` and the full instance name is `locality#0/total`. This counter type does not require an `instanceindex` or `parameters` to be specified.

In this case, the `parentindex` (the `'0'`) designates the *locality* for which the counter instance is created. The counter will return the number of *HPX* threads retired on that particular *locality*.

Another example for a well formed (aggregate) counter name is:

```
/statistics{/threads{locality#0/total}/count/cumulative}/average@500
```

This counter takes the simple counter from the first example, samples its values every `500` milliseconds, and returns the average of the value samples whenever it is queried. The counter type of this counter is `/statistics/average` and the instance name is the full name of the counter for which the values have to be averaged. In this case, the `parameters` (the `'500'`) specify the sampling interval for the averaging to take place (in milliseconds).

Performance counter types

Every performance counter belongs to a specific performance counter type which classifies the counters into groups of common semantics. The type of a counter is identified by the `objectname` and the `countername` parts of the name.

```
/objectname/countername
```

When an application starts *HPX* will register all available counter types on each of the localities. These counter types are held in a special performance counter registration database, which can be used to retrieve the meta data related to a counter type and to create counter instances based on a given counter instance name.

Performance counter instances

The `full_instancename` distinguishes different counter instances of the same counter type. The formatting of the `full_instancename` depends on the counter type. There are two types of counters: simple counters, which usually generate the counter values based on direct measurements, and aggregate counters, which take another counter and transform its values before generating their own counter values. An example for a simple counter is given *above*: counting retired *HPX* threads. An aggregate counter is shown as an example *above* as well: calculating the average of the underlying counter values sampled at constant time intervals.

While simple counters use instance names formatted as `parentinstancename#parentindex/instancename#instanceindex`, most aggregate counters have the full counter name of the embedded counter as their instance name.

Not all simple counter types require specifying all four elements of a full counter instance name; some of the parts (`parentinstancename`, `parentindex`, `instancename`, and `instanceindex`) are optional for specific counters.

Please refer to the documentation of a particular counter for more information about the formatting requirements for the name of this counter (see *Existing HPX performance counters*).

The `parameters` are used to pass additional information to a counter at creation time. They are optional, and they fully depend on the concrete counter. Even if a specific counter type allows additional parameters to be given, those usually are not required as sensible defaults will be chosen. Please refer to the documentation of a particular counter for more information about what parameters are supported, how to specify them, and what default values are assumed (see also *Existing HPX performance counters*).

Every *locality* of an application exposes its own set of performance counter types and performance counter instances. The set of exposed counters is determined dynamically at application start based on the execution environment of the application. For instance, this set is influenced by the current hardware environment for the *locality* (such as whether the *locality* has access to accelerators), and the software environment of the application (such as the number of OS threads used to execute *HPX* threads).

Using wildcards in performance counter names

It is possible to use wildcard characters when specifying performance counter names. Performance counter names can contain two types of wildcard characters:

- Wildcard characters in the performance counter type
- Wildcard characters in the performance counter instance name

A wildcard character has a meaning which is very close to usual file name wildcard matching rules implemented by common shells (like `bash`).

Table 2.26: Wildcard characters in the performance counter type

Wild-card	Description
<code>*</code>	This wildcard character matches any number (zero or more) of arbitrary characters.
<code>?</code>	This wildcard character matches any single arbitrary character.
<code>[...]</code>	This wildcard character matches any single character from the list of specified within the square brackets.

Table 2.27: Wildcard characters in the performance counter instance name

Wild-card	Description
<code>*</code>	This wildcard character matches any <i>locality</i> or any thread, depending on whether it is used for <code>locality#*</code> or <code>worker-thread#*</code> . No other wildcards are allowed in counter instance names.

Consuming performance counter data

You can consume performance data using either the command line interface, the *HPX* application or the *HPX* API. The command line interface is easier to use, but it is less flexible and does not allow one to adjust the behaviour of your application at runtime. The command line interface provides a convenience abstraction but simplified abstraction for querying and logging performance counter data for a set of performance counters.

Consuming performance counter data from the command line

HPX provides a set of predefined command line options for every application that uses `hpx::init` for its initialization. While there are many more command line options available (see *HPX Command Line Options*), the set of options related to performance counters allows one to list existing counters, and query existing counters once at application termination or repeatedly after a constant time interval.

The following table summarizes the available command line options:

Table 2.28: *HPX* Command Line Options Related to Performance Counters

Command line option	Description
<code>--hpx:print-counter</code>	Prints the specified performance counter either repeatedly and/or at the times specified by <code>--hpx:print-counter-at</code> (see also option <code>--hpx:print-counter-interval</code>).
<code>--hpx:print-counter-reset</code>	Prints the specified performance counter either repeatedly and/or at the times specified by <code>--hpx:print-counter-at</code> . Reset the counter after the value is queried (see also option <code>--hpx:print-counter-interval</code>).
<code>--hpx:print-counter-interval</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> repeatedly after the time interval (specified in milliseconds) (default:0 which means print once at shutdown).
<code>--hpx:print-counter-destination</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> to the given file (default: console).
<code>--hpx:list-counters</code>	List names of all registered performance counters.
<code>--hpx:list-counter-infos</code>	List detailed description of all registered performance counters.
<code>--hpx:print-counter-format</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> . Possible formats in CVS format with header or without any header (see option <code>--hpx:no-csv-header</code>), possible values: <code>csv</code> (prints counter values in CSV format with full names as header) <code>csv-short</code> (prints counter values in CSV format with shortnames provided with <code>--hpx:print-counter</code> as <code>--hpx:print-counter-shortname,full-countername</code>).
<code>--hpx:no-csv-header</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> and <code>csv</code> or <code>csv-short</code> format specified with <code>--hpx:print-counter-format</code> without header.
<code>--hpx:print-counter-at arg</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> (or <code>--hpx:print-counter-reset</code>) at the given point in time. Possible argument values: <code>startup</code> , <code>shutdown</code> (default), <code>noshutdown</code> .
<code>--hpx:reset-counters</code>	Reset the performance counter(s) specified with <code>--hpx:print-counter</code> after they have been evaluated.
<code>--hpx:print-counter-types</code>	Append counter types description to generated output.
<code>--hpx:print-local-only</code>	Prints only its own local counters.

While the options `--hpx:list-counters` and `--hpx:list-counter-infos` give a short list of all available counters, the full documentation for those can be found in the section *Existing HPX performance counters*.

HPX-Top

HPX-Top is a real-time, terminal-based dashboard designed for monitoring the health and performance of distributed *HPX* applications. Inspired by tools like *htop* and *bt*, it provides a high-level overview of system utilization, network flow, and internal runtime metrics.



Fig. 2.9: HPX-Top Real-time Performance Dashboard

Features

- **Locality-Aware Monitoring:** Automatically detects and displays metrics for all localities in a running distributed application.
- **Thread Pool Utilization:** Visualizes real-time usage of worker threads with instantaneous counts and historical sparkline graphs.
- **Parcel Throughput:** Tracks incoming and outgoing parcels, helping to identify network-bound bottlenecks or communication hotspots.
- **AGAS Health Monitor:** Displays cache hit and miss rates for the Application Global Address Space (AGAS), crucial for diagnosing naming service bottlenecks.

Usage

HPX-Top is implemented as a Python script that acts as a wrapper around your *HPX* application. It automatically configures the necessary performance counters and output formats.

The tool requires the rich Python library for rendering the terminal UI:

```
$ pip install rich
```

To monitor an *HPX* application, launch it through `hpx-top.py`:

```
$ python3 tools/hpx-top.py ./your_application --hpx:threads=4 [other HPX flags]
```

You can also run HPX-Top in mock mode to explore the interface without a running *HPX* application:

```
$ python3 tools/hpx-top.py --mock
```

Technical Details

The tool leverages *HPX*'s built-in performance counter framework. It launches the target application with specific flags (`--hpx:print-counter-interval` and `--hpx:print-counter-format=csv-short`) and parses the standard output in a non-blocking background thread to update the TUI.

HPX Smart Telemetry (`hpx_stat_viewer`)

HPX Smart Telemetry (`hpx_stat_viewer.py`) is an intelligent, lightweight performance dashboard designed to identify performance anomalies in real-time. While `hpx-top` provides a broad system overview, `hpx_stat_viewer` focuses on deep-dive analysis of specific metrics with built-in heuristic alerting.



Fig. 2.10: HPX Smart Telemetry Dashboard with Anomaly Detection

Features

- **Heuristic Anomaly Detection:** Uses an Exponential Moving Average (EMA) to monitor counter trends. It automatically flags sudden spikes (+150%) or drops (-60%) with prominent visual alerts like [SPIKE] and [DROP].
- **Live History Sparklines:** Displays 10-tick historical trend graphs next to every metric, helping developers distinguish between momentary noise and persistent bottlenecks.
- **Smart Filtering and Grouping:** Supports regex-based counter filtering and automatically groups metrics by locality for large-scale distributed runs.
- **Zero-Dependency Core:** Requires no external TUI libraries, making it highly portable for various terminal environments.

Usage

`hpx_stat_viewer.py` reads HPX counter data from standard input in `csv-short` transient format. This allows it to be used for both live monitoring and post-mortem analysis of log files.

To monitor a live application with smart filtering:

```
$ ./your_hpx_app --hpx:print-counter-interval=500 --hpx:print-counter-format=csv-short ..
↩ | \
python3 tools/hpx_stat_viewer.py --filter "threads|utilization"
```

To replay an offline performance log for analysis:

```
$ python3 tools/hpx_stat_viewer.py --replay your_hpx_counters.csv --speed 0.5
```

Technical Details

The dashboard implements a thread-safe parser that handles HPX's CSV-short format. The anomaly detection engine uses a smoothing factor of 0.4 for its EMA calculations, balancing responsiveness with stability. It is officially integrated into the HPX installation rules under the `tools` component.

A simple example

All of the commandline options mentioned above can be tested using the `hello_world_distributed` example.

Listing all available counters `hello_world_distributed --hpx:list-counters` yields:

```
List of available counter instances (replace * below with the appropriate
sequence number)
```

```
-----
/agas/count/allocate /agas/count/bind /agas/count/bind_gid
/agas/count/bind_name ... /threads{locality#*/allocator#*/count/objects
/threads{locality#*/total}/count/stack-recycles
/threads{locality#*/total}/idle-rate
/threads{locality#*/worker-thread#*/idle-rate
```

Providing more information about all available counters, `hello_world_distributed --hpx:list-counter-infos` yields:

```
Information about available counter instances (replace * below with the
appropriate sequence number)
```

```
-----
fullname: /agas/count/allocate helptext: returns the number of invocations of
the AGAS service 'allocate' type: counter_type::raw version: 1.0.0
-----
```

```
-----
fullname: /agas/count/bind helptext: returns the number of invocations of the
AGAS service 'bind' type: counter_type::raw version: 1.0.0
-----
```

```
-----
fullname: /agas/count/bind_gid helptext: returns the number of invocations of
the AGAS service 'bind_gid' type: counter_type::raw version: 1.0.0
-----
```

```
...
```

This command will not only list the counter names but also a short description of the data exposed by this counter.

Note: The list of available counters may differ depending on the concrete execution environment (hardware or software) of your application.

Requesting the counter data for one or more performance counters can be achieved by invoking `hello_world_distributed` with a list of counter names:

```
$ hello_world_distributed \
  --hpx:print-counter=/threads{locality#0/total}/count/cumulative \
  --hpx:print-counter=/agas{locality#0/total}/count/bind
```

which yields for instance:

```
hello world from OS-thread 0 on locality 0
/threads{locality#0/total}/count/cumulative,1,0.212527,[s],33
/agas{locality#0/total}/count/bind,1,0.212790,[s],11
```

The first line is the normal output generated by `hello_world_distributed` and has no relation to the counter data listed. The last two lines contain the counter data as gathered at application shutdown. These lines have six fields, the counter name, the sequence number of the counter invocation, the time stamp at which this information has been sampled, the unit of measure for the time stamp, the actual counter value and an optional unit of measure for the counter value.

Note: The command line option `--hpx:print-counter-types` will append a seventh field to the generated output. This field will hold an abbreviated counter type.

The actual counter value can be represented by a single number (for counters returning singular values) or a list of numbers separated by ':' (for counters returning an array of values, like for instance a histogram).

Note: The name of the performance counter will be enclosed in double quotes ''' if it contains one or more commas ',', '.'.

Requesting to query the counter data once after a constant time interval with this command line:

```
$ hello_world_distributed \
  --hpx:print-counter=/threads{locality#0/total}/count/cumulative \
  --hpx:print-counter=/agas{locality#0/total}/count/bind \
  --hpx:print-counter-interval=20
```

yields for instance (leaving off the actual console output of the `hello_world_distributed` example for brevity):

```
threads{locality#0/total}/count/cumulative,1,0.002409,[s],22
agas{locality#0/total}/count/bind,1,0.002542,[s],9
threads{locality#0/total}/count/cumulative,2,0.023002,[s],41
agas{locality#0/total}/count/bind,2,0.023557,[s],10
threads{locality#0/total}/count/cumulative,3,0.037514,[s],46
agas{locality#0/total}/count/bind,3,0.038679,[s],10
```

The command `--hpx:print-counter-destination=<file>` will redirect all counter data gathered to the specified file name, which avoids cluttering the console output of your application.

The command line option `--hpx:print-counter` supports using a limited set of wildcards for a (very limited) set of use cases. In particular, all occurrences of `#*` as in `locality#*` and in `worker-thread#*` will be automatically expanded to the proper set of performance counter names representing the actual environment for the executed program. For instance, if your program is utilizing four worker threads for the execution of *HPX* threads (see command line option `--hpx:threads`) the following command line

```
$ hello_world_distributed \
  --hpx:threads=4 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative
```

will print the value of the performance counters monitoring each of the worker threads:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
hello world from OS-thread 3 on locality 0
hello world from OS-thread 2 on locality 0
/threads{locality#0/worker-thread#0}/count/cumulative,1,0.0025214,[s],27
/threads{locality#0/worker-thread#1}/count/cumulative,1,0.0025453,[s],33
/threads{locality#0/worker-thread#2}/count/cumulative,1,0.0025683,[s],29
/threads{locality#0/worker-thread#3}/count/cumulative,1,0.0025904,[s],33
```

The command `--hpx:print-counter-format` takes values `csv` and `csv-short` to generate CSV formatted counter values with a header.

With format as `csv`:

```
$ hello_world_distributed \
  --hpx:threads=2 \
  --hpx:print-counter-format csv \
  --hpx:print-counter /threads{locality#*/total}/count/cumulative \
  --hpx:print-counter /threads{locality#*/total}/count/cumulative-phases
```

will print the values of performance counters in CSV format with the full countername as a header:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
/threads{locality#*/total}/count/cumulative,/threads{locality#*/total}/count/cumulative-
↪phases
39,93
```

With format `csv-short`:

```
$ hello_world_distributed \
  --hpx:threads 2 \
  --hpx:print-counter-format csv-short \
  --hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \
  --hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases
```

will print the values of performance counters in CSV format with the short countername as a header:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
cumulative,phases
39,93
```

With format `csv` and `csv-short` when used with `--hpx:print-counter-interval`:

```
$ hello_world_distributed \
  --hpx:threads 2 \
  --hpx:print-counter-format csv-short \
```

(continues on next page)

(continued from previous page)

```
--hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \
--hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases \
--hpx:print-counter-interval 5
```

will print the header only once repeating the performance counter value(s) repeatedly:

```
cum,phases
25,42
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
44,95
```

The command `--hpx:no-csv-header` can be used with `--hpx:print-counter-format` to print performance counter values in CSV format without any header:

```
$ hello_world_distributed \
--hpx:threads 2 \
--hpx:print-counter-format csv-short \
--hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \
--hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases \
--hpx:no-csv-header
```

will print:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
37,91
```

Consuming performance counter data using the HPX API

HPX provides an API that allows users to discover performance counters and to retrieve the current value of any existing performance counter from any application.

Discover existing performance counters

Retrieve the current value of any performance counter

Performance counters are specialized *HPX* components. In order to retrieve a counter value, the performance counter needs to be instantiated. *HPX* exposes a client component object for this purpose:

```
hpx::performance_counters::performance_counter counter(std::string const& name);
```

Instantiating an instance of this type will create the performance counter identified by the given name. Only the first invocation for any given counter name will create a new instance of that counter. All following invocations for a given counter name will reference the initially created instance. This ensures that at any point in time there is never more than one active instance of any of the existing performance counters.

In order to access the counter value (or to invoke any of the other functionality related to a performance counter, like `start`, `stop` or `reset`) member functions of the created client component instance should be called:

```
// print the current number of threads created on locality 0
hpx::performance_counters::performance_counter count(
    "/threads{locality#0/total}/count/cumulative");
hpx::cout << count.get_value<int>().get() << std::endl;
```

For more information about the client component type, see `hpx::performance_counters::performance_counter`

Note: In the above example `count.get_value()` returns a future. In order to print the result we must append `.get()` to retrieve the value. You could write the above example like this for more clarity:

```
// print the current number of threads created on locality 0
hpx::performance_counters::performance_counter count(
    "/threads{locality#0/total}/count/cumulative");
hpx::future<int> result = count.get_value<int>();
hpx::cout << result.get() << std::endl;
```

Providing performance counter data

HPX offers several ways by which you may provide your own data as a performance counter. This has the benefit of exposing additional, possibly application-specific information using the existing Performance Counter framework, unifying the process of gathering data about your application.

An application that wants to provide counter data can implement a performance counter to provide the data. When a consumer queries performance data, the HPX runtime system calls the provider to collect the data. The runtime system uses an internal registry to determine which provider to call.

Generally, there are two ways of exposing your own performance counter data: a simple, function-based way and a more complex, but more powerful way of implementing a full performance counter. Both alternatives are described in the following sections.

Exposing performance counter data using a simple function

The simplest way to expose arbitrary numeric data is to write a function which will then be called whenever a consumer queries this counter. Currently, this type of performance counter can only be used to expose integer values. The expected signature of this function is:

```
std::int64_t some_performance_data(bool reset);
```

The argument `bool reset` (which is supplied by the runtime system when the function is invoked) specifies whether the counter value should be reset after evaluating the current value (if applicable).

For instance, here is such a function returning how often it was invoked:

```
// The atomic variable 'counter' ensures the thread safety of the counter.
boost::atomic<std::int64_t> counter(0);

std::int64_t some_performance_data(bool reset)
{
    std::int64_t result = ++counter;
    if (reset)
        counter = 0;
}
```

(continues on next page)

(continued from previous page)

```

    return result;
}

```

This example function exposes a linearly-increasing value as our performance data. The value is incremented on each invocation, i.e., each time a consumer requests the counter data of this performance counter.

The next step in exposing this counter to the runtime system is to register the function as a new raw counter type using the HPX API function `hpx::performance_counters::install_counter_type`. A counter type represents certain common characteristics of counters, like their counter type name and any associated description information. The following snippet shows an example of how to register the function `some_performance_data`, which is shown above, for a counter type named `"/test/data"`. This registration has to be executed before any consumer instantiates, and queries an instance of this counter type:

```

#include <hpx/include/performance_counters.hpp>

void register_counter_type()
{
    // Call the HPX API function to register the counter type.
    hpx::performance_counters::install_counter_type(
        "/test/data",                // counter type name
        &some_performance_data,      // function providing counter_
↪data
        "returns a linearly increasing counter value" // description text (optional)
        ""                          // unit of measure (optional)
    );
}

```

Now it is possible to instantiate a new counter instance based on the naming scheme `"/test{locality#*/total}/data"` where `*` is a zero-based integer index identifying the *locality* for which the counter instance should be accessed. The function `hpx::performance_counters::install_counter_type` enables users to instantiate exactly one counter instance for each *locality*. Repeated requests to instantiate such a counter will return the same instance, i.e., the instance created for the first request.

If this counter needs to be accessed using the standard HPX command line options, the registration has to be performed during application startup, before `hpx_main` is executed. The best way to achieve this is to register an HPX startup function using the API function `hpx::register_startup_function` before calling `hpx::init` to initialize the runtime system:

```

int main(int argc, char* argv[])
{
    // By registering the counter type we make it available to any consumer
    // who creates and queries an instance of the type "/test/data".
    //
    // This registration should be performed during startup. The
    // function 'register_counter_type' should be executed as an HPX thread right
    // before hpx_main is executed.
    hpx::register_startup_function(&register_counter_type);

    // Initialize and run HPX.
    return hpx::init(argc, argv);
}

```

Please see the code in `simplest_performance_counter.cpp` for a full example demonstrating this functionality.

Implementing a full performance counter

Sometimes, the simple way of exposing a single value as a performance counter is not sufficient. For that reason, *HPX* provides a means of implementing full performance counters which support:

- Retrieving the descriptive information about the performance counter
- Retrieving the current counter value
- Resetting the performance counter (value)
- Starting the performance counter
- Stopping the performance counter
- Setting the (initial) value of the performance counter

Every full performance counter will implement a predefined interface:

```
// Copyright (c) 2007-2026 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#include <hpx/modules/async_base.hpp>
#include <hpx/modules/components.hpp>
#include <hpx/modules/execution.hpp>
#include <hpx/modules/functional.hpp>
#include <hpx/modules/futures.hpp>

#include <hpx/performance_counters/counters_fwd.hpp>
#include <hpx/performance_counters/server/base_performance_counter.hpp>

#include <string>
#include <utility>
#include <vector>

#include <hpx/config/warnings_prefix.hpp>

////////////////////////////////////
namespace hpx::performance_counters {
    //////////////////////////////////////
    HPX_CXX_EXPORT struct HPX_EXPORT performance_counter
        : components::client_base<performance_counter,
            server::base_performance_counter>
    {
        using base_type = components::client_base<performance_counter,
            server::base_performance_counter>;

        performance_counter() = default;
    };
}
```

(continues on next page)

(continued from previous page)

```

explicit performance_counter(std::string const& name);

performance_counter(
    std::string const& name, hpx::id_type const& locality);

performance_counter(id_type const& id)
    : base_type(id)
{
}

performance_counter(future<id_type>&& id)
    : base_type(HPX_MOVE(id))
{
}

performance_counter(hpx::future<performance_counter>&& c)
    : base_type(HPX_MOVE(c))
{
}

////////////////////////////////////
future<counter_info> get_info() const;
counter_info get_info(
    launch::sync_policy, error_code& ec = throws) const;

future<counter_value> get_counter_value(bool reset) const;
counter_value get_counter_value(
    launch::sync_policy, bool reset, error_code& ec = throws) const;

future<counter_value> get_counter_value() const;
counter_value get_counter_value(
    launch::sync_policy, error_code& ec = throws) const;

future<counter_values_array> get_counter_values_array(bool reset) const;
counter_values_array get_counter_values_array(
    launch::sync_policy, bool reset, error_code& ec = throws) const;

future<counter_values_array> get_counter_values_array() const;
counter_values_array get_counter_values_array(
    launch::sync_policy, error_code& ec = throws) const;

////////////////////////////////////
future<bool> start() const;
bool start(launch::sync_policy, error_code& ec = throws) const;

future<bool> stop() const;
bool stop(launch::sync_policy, error_code& ec = throws) const;

future<void> reset() const;
void reset(launch::sync_policy, error_code& ec = throws) const;

future<void> reinit(bool reset = true) const;

```

(continues on next page)

(continued from previous page)

```

void reinit(launch::sync_policy, bool reset = true,
            error_code& ec = throws) const;

////////////////////////////////////
future<std::string> get_name() const;
std::string get_name(
    launch::sync_policy, error_code& ec = throws) const;

private:
    template <typename T>
    static T extract_value(future<counter_value>&& value)
    {
        return value.get().get_value<T>();
    }

public:
    template <typename T>
    future<T> get_value(bool reset = false)
    {
        return get_counter_value(reset).then(hpx::launch::sync,
            hpx::bind_front(&performance_counter::extract_value<T>));
    }
    template <typename T>
    T get_value(
        launch::sync_policy, bool reset = false, error_code& ec = throws)
    {
        return get_counter_value(launch::sync, reset).get_value<T>(ec);
    }

    template <typename T>
    future<T> get_value() const
    {
        return get_counter_value(false).then(hpx::launch::sync,
            hpx::bind_front(&performance_counter::extract_value<T>));
    }
    template <typename T>
    T get_value(launch::sync_policy, error_code& ec = throws) const
    {
        return get_counter_value(launch::sync, false).get_value<T>(ec);
    }
};

// Return all counters matching the given name (with optional wild cards).
HPX_CXX_EXPORT HPX_EXPORT std::vector<performance_counter>
discover_counters(std::string const& name, error_code& ec = throws);
} // namespace hpx::performance_counters

#include <hpx/config/warnings_suffix.hpp>

```

In order to implement a full performance counter, you have to create an *HPX* component exposing this interface. To simplify this task, *HPX* provides a ready-made base class which handles all the boiler plate of creating a component for you. The remainder of this section will explain the process of creating a full performance counter based on the Sine example, which you can find in the directory `examples/performance_counters/sine/`.

The base class is defined in the header file `base_performance_counter.cpp` as:

```
// Copyright (c) 2007-2026 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#include <hpx/modules/actions_base.hpp>
#include <hpx/modules/components_base.hpp>
#include <hpx/modules/runtime_local.hpp>

#include <hpx/performance_counters/counters.hpp>
#include <hpx/performance_counters/server/base_performance_counter.hpp>

#ifdef DOXYGEN
//[performance_counter_base_class
namespace hpx::performance_counters {

    template <typename Derived>
    class base_performance_counter;
} // namespace hpx::performance_counters
//]
#endif

//[performance_counter_base_class
namespace hpx::performance_counters {

    HPX_CXX_EXPORT template <typename Derived>
    class base_performance_counter
    : public hpx::performance_counters::server::base_performance_counter
    , public hpx::components::component_base<Derived>
    {
    private:
        using base_type = hpx::components::component_base<Derived>;

    public:
        using type_holder = Derived;
        using base_type_holder =
            hpx::performance_counters::server::base_performance_counter;

        // NOLINTBEGIN(bugprone-crt-p-constructor-accessibility)
        base_performance_counter() = default;

        explicit base_performance_counter(
            hpx::performance_counters::counter_info const& info)
            : base_type_holder(info)
        {
        }
    }
}
//]

```

(continues on next page)

(continued from previous page)

```

// NOLINTEND(bugprone-crtpp-constructor-accessibility)

// Disambiguate finalize() which is implemented in both base classes
void finalize()
{
    base_type_holder::finalize();
    base_type::finalize();
}

hpx::naming::address get_current_address() const
{
    return hpx::naming::address(
        hpx::naming::get_gid_from_locality_id(hpx::get_locality_id()),
        hpx::components::get_component_type<Derived>(),
        const_cast<Derived*>(static_cast<Derived const*>(this)));
}
};
} // namespace hpx::performance_counters

```

The single template parameter is expected to receive the type of the derived class implementing the performance counter. In the Sine example this looks like:

```

// Copyright (c) 2007-2012 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/lcos_local.hpp>
#include <hpx/include/performance_counters.hpp>
#include <hpx/include/util.hpp>

#include <cstdint>

namespace performance_counters { namespace sine { namespace server {
    //////////////////////////////////////
    //[sine_counter_definition
    class sine_counter
    : public hpx::performance_counters::base_performance_counter<sine_counter>
    {
    public:
        sine_counter()
            : current_value_(0)
            , evaluated_at_(0)
        {
        }
    }
}
}
}

```

(continues on next page)

(continued from previous page)

```

explicit sine_counter(
    hpx::performance_counters::counter_info const& info);

    /// This function will be called in order to query the current value of
    /// this performance counter
    hpx::performance_counters::counter_value get_counter_value(bool reset);

    /// The functions below will be called to start and stop collecting
    /// counter values from this counter.
    bool start();
    bool stop();

    /// finalize() will be called just before the instance gets destructed
    void finalize();

protected:
    bool evaluate();

private:
    typedef hpx::spinlock mutex_type;

    mutable mutex_type mtx_;
    double current_value_;
    std::uint64_t evaluated_at_;

    hpx::util::interval_timer timer_;
};
}}} /// namespace performance_counters::sine::server
#endif

```

i.e., the type `sine_counter` is derived from the base class passing the type as a template argument (please see `simplest_performance_counter.cpp` for the full source code of the counter definition). For more information about this technique (called Curiously Recurring Template Pattern - CRTP), please see for instance the corresponding [Wikipedia article](http://en.wikipedia.org/wiki/Curiously_recurring_template_pattern)¹⁸⁰. This base class itself is derived from the `performance_counter` interface described above.

Additionally, a full performance counter implementation not only exposes the actual value but also provides information about:

- The point in time a particular value was retrieved.
- A (sequential) invocation count.
- The actual counter value.
- An optional scaling coefficient.
- Information about the counter status.

¹⁸⁰ http://en.wikipedia.org/wiki/Curiously_recurring_template_pattern

Existing HPX performance counters

The HPX runtime system exposes a wide variety of predefined performance counters. These counters expose critical information about different modules of the runtime system. They can help determine system bottlenecks and fine-tune system and application performance.

Table 2.29: AGAS performance counter /agas/count/<agas_service>

Counter type	/agas/count/<agas_service> where <agas_service> is one of the following: <i>primary namespace services:</i> route, bind_gid, resolve_gid, unbind_gid, increment_credit, decrement_credit, allocate, begin_migration, end_migration <i>component namespace services:</i> bind_prefix, bind_name, resolve_id, unbind_name, iterate_types, get_component_type_name, num_localities_type <i>locality namespace services:</i> free, localities, num_localities, num_threads, resolve_locality, resolved_localities <i>symbol namespace services:</i> bind, resolve, unbind, iterate_names, on_symbol_namespace_event
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be locality#0 where 0 is the root <i>locality</i> (the id of the locality hosting the AGAS service). The value for * can be any <i>locality</i> id for the following <agas_service>: route, bind_gid, resolve_gid, unbind_gid, increment_credit, decrement_credit, bin, resolve, unbind, and iterate_names (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on locality#0 only).
Description	Returns the total number of invocations of the specified AGAS service since its creation.

Table 2.30: AGAS performance counter /agas/<agas_service_category>/count

Counter type	/agas/<agas_service_category>/count where <agas_service_category> is one of the following: primary, locality, component or symbol
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be locality#0 where 0 is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category>, primary or symbol for which the value for * can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on locality#0 only).
Description	Returns the overall total number of invocations of all AGAS services provided by the given AGAS service category since its creation.

Table 2.31: AGAS performance counter /agas/<agas_service_category>/count

Counter type	/agas/<agas_service_category>/count where <agas_service_category> is one of the following: <code>primary</code> , <code>locality</code> , <code>component</code> or <code>symbol</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category>, <code>primary</code> or <code>symbol</code> for which the value for <code>*</code> can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall total number of invocations of all AGAS services provided by the given AGAS service category since its creation.

Table 2.32: AGAS performance counter agas/time/<agas_service>

Counter type	agas/time/<agas_service> where <agas_service> is one of the following: <i>primary namespace services:</i> <code>route</code> , <code>bind_gid</code> , <code>resolve_gid</code> , <code>unbind_gid</code> , <code>increment_credit</code> , <code>decrement_credit</code> , <code>allocate</code> , <code>begin_migration</code> , <code>end_migration</code> <i>component namespace services:</i> <code>bind_prefix</code> , <code>bind_name</code> , <code>resolve_id</code> , <code>unbind_name</code> , <code>iterate_types</code> , <code>get_component_typename</code> , <code>num_localities_type</code> <i>locality namespace services:</i> <code>free</code> , <code>localities</code> , <code>num_localities</code> , <code>num_threads</code> , <code>resolve_locality</code> , <code>resolved_localities</code> <i>symbol namespace services:</i> <code>bind</code> , <code>resolve</code> , <code>unbind</code> , <code>iterate_names</code> , <code>on_symbol_namespace_event</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). The value for <code>*</code> can be any <i>locality</i> id for the following <agas_service>: <code>route</code> , <code>bind_gid</code> , <code>resolve_gid</code> , <code>unbind_gid</code> , <code>increment_credit</code> , <code>decrement_credit</code> , <code>bin</code> , <code>resolve</code> , <code>unbind</code> , and <code>iterate_names</code> (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall execution time of the specified AGAS service since its creation (in nanoseconds).

Table 2.33: AGAS performance counter /agas/<agas_service_category>/time`

Counter type	/agas/<agas_service_category>/time where <agas_service_category> is one of the following: <code>primary</code> , <code>locality</code> , <code>component</code> or <code>symbol</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category> <code>primary</code> or <code>symbol</code> for which the value for <code>*</code> can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall execution time of all AGAS services provided by the given AGAS service category since its creation (in nanoseconds).

Table 2.34: AGAS performance counter /agas/count/entries

Counter type	/agas/count/entries
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of cache entries resident in the AGAS cache of the specified <i>locality</i> (see <cache_statistics>).

Table 2.35: AGAS performance counter /agas/count/<cache_statistics>

Counter type	/agas/count/<cache_statistics> where <cache_statistics> is one of the following: cache/evictions, cache/hits, cache/insertions, cache/misses
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i>
Description	Returns the number of cache events (evictions, hits, inserts, and misses) in the AGAS cache of the specified <i>locality</i> (see <cache_statistics>).

Table 2.36: AGAS performance counter /agas/count/<full_cache_statistics>

Counter type	/agas/count/<full_cache_statistics> where <full_cache_statistics> is one of the following: cache/get_entry, cache/insert_entry, cache/update_entry, cache/erase_entry
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of invocations of the specified cache API function of the AGAS cache.

Table 2.37: AGAS performance counter /agas/time/<full_cache_statistics>

Counter type	/agas/time/<full_cache_statistics> where <full_cache_statistics> is one of the following: cache/get_entry, cache/insert_entry, cache/update_entry, cache/erase_entry
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time spent executing of the specified API function of the AGAS cache.

Table 2.38: Parcel layer performance counter `/data/count/<connection_type>/<operation>`

Counter type	<code>/data/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of raw (uncompressed) bytes sent or received (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) for the specified <code><connection_type></code> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.39: Parcel layer performance counter `/data/time/<connection_type>/<operation>`

Counter type	<code>/data/time/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the total transmission time should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total time (in nanoseconds) between the start of each asynchronous transmission operation and the end of the corresponding operation for the specified <code><connection_type></code> the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.40: Parcel layer performance counter `/serialize/count/<connection_type>/<operation>`

Counter type	<code>/serialize/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of bytes transferred (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code> possibly compressed) for the specified <code><connection_type></code> by the given <i>locality</i> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.
Description	If the configure-time option <code>-DHPX_WITH_PARCELPORNT_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the number of bytes transmitted for the given action only.

Table 2.41: Parcel layer performance counter `/serialize/time/<connection_type>/<operation>`

Counter type	<code>/serialize/time/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the serialization time should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time spent performing outgoing data serialization for the specified <code><connection_type></code> on the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.
Parameters	If the configure-time option <code>-DHPX_WITH_PARCELPORNT_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the serialization time for the given action only.

Table 2.42: Parcel layer performance counter `/parcels/count/routed`

Counter type	<code>/parcels/count/routed</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of routed parcels should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of routed (outbound) parcels transferred by the given <i>locality</i> . Routed parcels are those which cannot directly be delivered to its destination as the local AGAS is not able to resolve the destination address. In this case a parcel is sent to the AGAS service component which is responsible for creating the destination GID (and is responsible for resolving the destination address). This AGAS service component will deliver the parcel to its final target.
Parameters	If the configure-time option <code>-DHPX_WITH_PARCELPOR_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the number of parcels for the given action only.

Table 2.43: Parcel layer performance counter `/parcels/count/<connection_type>/<operation>`

Counter type	<code>/parcels/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of parcels should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of parcels transferred using the specified <code><connection_type></code> by the given <i>locality</i> (see <code>operation</code> , e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.44: Parcel layer performance counter `/messages/count/<connection_type>/<operation>`

Counter type	<code>/messages/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of messages should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of messages ¹⁸¹ transferred using the specified <code><connection_type></code> by the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.45: Parcel layer performance counter `/parcelport/count/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/count/<connection_type>/zero_copy_chunks/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of zero-copy chunks sent or received (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) for the specified <code><connection_type></code> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

¹⁸¹ A message can potentially consist of more than one *parcel*.

Table 2.46: Parcel layer performance counter `/parcelport/count-max/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/count-max/<connection_type>/zero_copy_chunks/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the maximum number of zero-copy chunks sent or received per message (see <operation>, e.g. <code>sent</code> or <code>received</code>) for the specified <connection_type>. The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.47: Parcel layer performance counter `/parcelport/size/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/size/<connection_type>/zero_copy_chunks/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall size of zero-copy chunks sent or received (see <operation>, e.g. <code>sent</code> or <code>received</code>) for the specified <connection_type>. The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.48: Parcel layer performance counter `/parcelport/size-max/`
`<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/size-max/<connection_type>/zero_copy_chunks/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the maximum size of zero-copy chunks sent or received (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) for the specified <code><connection_type></code> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.49: Parcel layer performance counter `/parcelport/count/`
`<connection_type>/<cache_statistics>`

Counter type	<code>/parcelport/count/<connection_type>/<cache_statistics></code> where: <code><cache_statistics></code> is one of the following: <code>cache/insertions</code> , <code>cache/evictions</code> , <code>cache/hits</code> , <code>cache/misses</code> , <code>cache/reclaims</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of messages should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number cache events (evictions, hits, inserts, misses, and reclaims) for the connection cache of the given connection type on the given <i>locality</i> (see <code><cache_statistics></code> , e.g. <code>ache/insertions</code> , <code>cache/evictions</code> , <code>cache/hits</code> , <code>cache/misses</code> or <code>cache/reclaims</code>). The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.50: Parcel layer performance counter `/parcelport/count/<connection_type>/cache-reservation-failures`

Counter type	<code>/parcelport/count/<connection_type>/cache-reservation-failures</code> where <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the counter should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the cumulative number of times <code>get_or_reserve()</code> returned <code>false</code> because every connection slot in the connection cache was already checked out (pool saturation). This is distinct from ordinary cache misses, which occur whenever a new connection to a <i>locality</i> is first created and do not cause parcel deferral. A non-zero and growing value of this counter means that outgoing parcels are being silently queued until a connection is reclaimed; raising <code>hpx.max_connections</code> or <code>hpx.max_connections_per_locality</code> in the ini configuration will relieve the saturation. When pool exhaustion is detected, <i>HPX</i> also emits a warning-level log message (throttled to at most once every five seconds) of the form: <code>parcelport connection cache exhausted: N/M connections in use, K deferred reservation(s) since last reset</code>. The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code>. Please see <i>CMake options</i> for more details.

Table 2.51: Parcel layer performance counters `/parcelport/count/<connection_type>/cache-connections` and `/parcelport/count/<connection_type>/cache-max-connections`

Counter type	<code>/parcelport/count/<connection_type>/cache-connections</code> <code>/parcelport/count/<connection_type>/cache-max-connections</code> where <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the counter should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	<code>cache-connections</code> returns the current number of connections tracked by the connection cache for the given connection type on the given <i>locality</i>. This includes both connections that are currently checked out and connections that are idle and available for reuse. <code>cache-max-connections</code> returns the configured upper limit on the total number of connections the cache is allowed to hold. This value is fixed at startup and corresponds to the <code>hpx.max_connections</code> ini key. Together these two counters give the pool utilisation ratio. If <code>cache-connections</code> is consistently equal to <code>cache-max-connections</code> and <code>cache-reservation-failures</code> is increasing, the connection pool is saturated and the limit should be raised. The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code>. Please see <i>CMake options</i> for more details.

Table 2.52: Parcel layer performance counter `/parcelqueue/length/<operation>`

Counter type	<code>/parcelqueue/length/<operation></code> where <code><operation></code> is one of the following: <code>sent</code> , <code>receive</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the <i>parcel</i> queue should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the current number of parcels stored in the <i>parcel</i> queue (see <code><operation></code> for which queue to query, e.g. <code>sent</code> or <code>received</code>).

Table 2.53: Thread manager performance counter `/threads/count/cumulative`

Counter type	<code>/threads/count/cumulative</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall number of retired <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall number of retired <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall number of executed (retired) <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the accumulated number of retired <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall number of retired <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> is set to <code>ON</code> (default: <code>ON</code>).

Table 2.54: Thread manager performance counter `/threads/time/average`

Counter type	<code>/threads/time/average</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time spent executing one <i>HPX</i> -thread should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average time spent executing one <i>HPX</i> -thread should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average time spent executing one <i>HPX</i> -thread on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent executing one <i>HPX</i> -thread for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent executing one <i>HPX</i> -thread for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.55: Thread manager performance counter `/threads/time/average-overhead`

Counter type	<code>/threads/time/average-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average overhead spent executing one <i>HPX</i> -thread should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average overhead spent executing one <i>HPX</i> -thread should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average time spent on overhead while executing one <i>HPX</i> -thread on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent on overhead while executing one <i>HPX</i> -thread for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent on overhead executing one <i>HPX</i> -thread for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.56: Thread manager performance counter `/threads/count/cumulative-phases`

Counter type	<code>/threads/count/cumulative-phases</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall number of executed <i>HPX</i> -thread phases (invocations) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall number of executed <i>HPX</i> -thread phases (invocations) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the overall number of executed <i>HPX</i> -thread phases (invocations) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the accumulated number of executed <i>HPX</i> -thread phases (invocations) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall number of executed <i>HPX</i> -thread phases for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> is set to ON (default: ON). The unit of measure for this counter is nanosecond [ns].

Table 2.57: Thread manager performance counter `/threads/time/average-phase`

Counter type	<code>/threads/time/average-phase</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time spent executing one <i>HPX</i> -thread phase (invocation) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average time executing one <i>HPX</i> -thread phase (invocation) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the average time spent executing one <i>HPX</i> -thread phase (invocation) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent executing one <i>HPX</i> -thread phase (invocation) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent executing one <i>HPX</i> -thread phase for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.58: Thread manager performance counter `/threads/time/average-phase-overhead`

Counter type	<code>/threads/time/average-phase-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time overhead executing one <i>HPX</i> -thread phase (invocation) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average overhead executing one <i>HPX</i> -thread phase (invocation) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the average time spent on overhead executing one <i>HPX</i> -thread phase (invocation) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent on overhead while executing one <i>HPX</i> -thread phase (invocation) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent on overhead executing one <i>HPX</i> -thread phase for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.59: Thread manager performance counter `/threads/time/overall`

Counter type	<code>/threads/time/overall</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall time spent running the scheduler should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent running the scheduler should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the overall time spent running the scheduler on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall time spent running the scheduler for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent running the scheduler for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_IDLE_RATES</code> is set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.60: Thread manager performance counter `/threads/time/cumulative`

Counter type	<code>/threads/time/cumulative</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall time spent executing all <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent executing all <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall time spent executing all <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall time spent executing all <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent executing all <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_THREAD_MAINTAIN_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_THREAD_MAINTAIN_IDLE_RATES</code> are set to ON (default: OFF).

Table 2.61: Thread manager performance counter `/threads/time/cumulative-overheads`

Counter type	<code>/threads/time/cumulative-overheads</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall overhead time incurred by executing all <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the the overall overhead time incurred by executing all <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall overhead time incurred executing all <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall overhead time incurred executing all <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall overhead time incurred executing all <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_THREAD_MAINTAIN_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_THREAD_MAINTAIN_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.62: Thread manager performance counter `threads/count/instantaneous/<thread-state>`

Counter type	<code>threads/count/instantaneous/<thread-state></code> where: <code><thread-state></code> is one of the following: <code>all</code> , <code>active</code> , <code>pending</code> , <code>suspended</code> , <code>terminated</code> , <code>staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current number of threads with the given state should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current number of threads with the given state should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool. The <code>staged</code> thread state refers to registered tasks before they are converted to thread objects.
Description	Returns the current number of <i>HPX</i> -threads having the given thread state on the given <i>locality</i> . If the instance name is <code>total</code> the counter returns the current number of <i>HPX</i> -threads of the given state for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the current number of <i>HPX</i> -threads in the given state for all worker threads separately.

Table 2.63: Thread manager performance counter `threads/wait-time/<thread-state>`

Counter type	<code>threads/wait-time/<thread-state></code> where: <code><thread-state></code> is one of the following: <code>pending staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average wait time of <i>HPX</i> -threads (<code>pending</code>) or thread descriptions (<code>staged</code>) with the given state should be queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average wait time for the given state should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool. The <code>staged</code> thread state refers to the wait time of registered tasks before they are converted into thread objects, while the <code>pending</code> thread state refers to the wait time of threads in any of the scheduling queues.
Description	Returns the average wait time of <i>HPX</i> -threads (if the thread state is <code>pending</code> or of task descriptions (if the thread state is <code>staged</code> on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the wait time of <i>HPX</i> -threads of the given state for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the wait time of <i>HPX</i> -threads in the given state for all worker threads separately. These counters are available only if the compile time constant <code>HPX_WITH_THREAD_QUEUE_WAITTIME</code> was defined while compiling the <i>HPX</i> core library (default: <code>OFF</code>). The unit of measure for this counter is nanosecond [ns].

Table 2.64: Thread manager performance counter `/threads/idle-rate`

Counter type	<code>/threads/idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> . The idle rate is defined as the ratio of the time spent on scheduling and management tasks and the overall time spent executing work since the application started. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_IDLE_RATES</code> is set to ON (default: OFF).

Table 2.65: Thread manager performance counter `/threads/creation-idle-rate`

Counter type	<code>/threads/creation-idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average creation idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> which is caused by creating new threads. The creation idle rate is defined as the ratio of the time spent on creating new threads and the overall time spent executing work since the application started. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_IDLE_RATES</code> (default: OFF) and <code>HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES</code> are set to ON.

Table 2.66: Thread manager performance counter `/threads/cleanup-idle-rate`

Counter type	<code>/threads/cleanup-idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average cleanup idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged cleanup idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> which is caused by cleaning up terminated threads. The cleanup idle rate is defined as the ratio of the time spent on cleaning up terminated thread objects and the overall time spent executing work since the application started. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_IDLE_RATES</code> (default: OFF) and <code>HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES</code> are set to ON.

Table 2.67: Thread manager performance counter `/threadqueue/length`

Counter type	<code>/threadqueue/length</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current length of all thread queues in the scheduler for all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current length of all thread queues in the scheduler should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the overall length of all queues for the given worker thread(s) on the given <i>locality</i> .

Table 2.68: Thread manager performance counter `/threads/count/stack-unbinds`

Counter type	<code>/threads/count/stack-unbinds</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the unbind (madvise) operations should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -thread unbind (madvise) operations performed for the referenced <i>locality</i> . Note that this counter is not available on Windows based platforms.

Table 2.69: Thread manager performance counter `/threads/count/stack-recycles`

Counter type	<code>/threads/count/stack-recycles</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the recycling operations should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -thread recycling operations performed.

Table 2.70: Thread manager performance counter `/threads/count/stolen-from-pending`

Counter type	<code>/threads/count/stolen-from-pending</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of ‘stole’ threads should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ from the pending thread queue by a neighboring thread worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to <code>ON</code> (default: <code>ON</code>).

Table 2.71: Thread manager performance counter `/threads/count/pending-misses`

Counter type	<code>/threads/count/pending-misses</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of pending queue misses of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of pending queue misses should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of times that the referenced worker-thread on the referenced <i>locality</i> failed to find pending <i>HPX</i> -threads in its associated queue. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.72: Thread manager performance counter `/threads/count/pending-accesses`

Counter type	<code>/threads/count/pending-accesses</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of pending queue accesses of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of pending queue accesses should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of times that the referenced worker-thread on the referenced <i>locality</i> looked for pending <i>HPX</i> -threads in its associated queue. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.73: Thread manager performance counter `/threads/count/stolen-from-staged`

Counter type	<code>/threads/count/stolen-from-staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen from the staged queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen from the staged queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ from the staged thread queue by a neighboring worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.74: Thread manager performance counter `/threads/count/stolen-to-pending`

Counter type	<code>/threads/count/stolen-to-pending</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen to the pending queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen to the pending queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ to the pending thread queue of the worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.75: Thread manager performance counter `/threads/count/stolen-to-staged`

Counter type	<code>/threads/count/stolen-to-staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen to the staged queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen to the staged queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ to the staged thread queue of a neighboring worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.76: Thread manager performance counter `/threads/count/objects`

Counter type	<code>/threads/count/objects</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/allocator#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current (cumulative) number of all created <i>HPX</i> -thread objects should be queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>allocator#*</code> is defining the number of the allocator instance using which the threads have been created. <i>HPX</i> uses a varying number of allocators to create (and recycle) <i>HPX</i> -thread objects, most likely these counters are of use for debugging purposes only. The allocator id (given by <code>*</code>) is a (zero based) number identifying the allocator to query.
Description	Returns the total number of <i>HPX</i> -thread objects created. Note that thread objects are reused to improve system performance, thus this number does not reflect the number of actually executed (retired) <i>HPX</i> -threads.

Table 2.77: Thread manager performance counter `/scheduler/`
`utilization/instantaneous`

Counter type	<code>/scheduler/utilization/instantaneous</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current (instantaneous) scheduler utilization queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total (instantaneous) scheduler utilization. This is the current percentage of scheduler threads executing <i>HPX</i> threads.
Parameters	Percent

Table 2.78: Thread manager performance counter `/threads/`
`idle-loop-count/instantaneous`

Counter type	<code>/threads/idle-loop-count/instantaneous</code>
Counter instance formatting	<code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all idle-loop counters of all worker threads should be queried. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current value of the idle-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the current (instantaneous) idle-loop count for the given <i>HPX</i> - worker thread or the accumulated value for all worker threads.

Table 2.79: Thread manager performance counter `/threads/busy-loop-count/instantaneous`

Counter type	<code>/threads/busy-loop-count/instantaneous</code>
Counter instance formatting	<code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all busy-loop counters of all worker threads should be queried. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current value of the busy-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the current (instantaneous) busy-loop count for the given <i>HPX</i> - worker thread or the accumulated value for all worker threads.

Table 2.80: Thread manager performance counter `/threads/time/background-work-duration`

Counter type	<code>/threads/time/background-work-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.81: Thread manager performance counter `/threads/background-overhead`

Counter type	<code>/threads/background-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure displayed for this counter is 0.1%.

Table 2.82: Thread manager performance counter `/threads/time/background-send-duration`

Counter type	<code>/threads/time/background-send-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work related to sending parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work related to sending parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work related to sending parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns]. This counter will currently return meaningful values for the MPI parcellport only.

Table 2.83: Thread manager performance counter `/threads/background-send-overhead`

Counter type	<code>/threads/background-send-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead related to sending parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead related to sending parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead related to sending parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure displayed for this counter is 0.1%. This counter will currently return meaningful values for the MPI parcelport only.

Table 2.84: Thread manager performance counter `/threads/time/background-receive-duration`

Counter type	<code>/threads/time/background-receive-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work related to receiving parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work related to receiving parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work related to receiving parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns]. This counter will currently return meaningful values for the MPI parcelport only.

Table 2.85: Thread manager performance counter `/threads/background-receive-overhead`

Counter type	<code>/threads/background-receive-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead related to receiving should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead related to receiving parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead related to receiving parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: <code>OFF</code>) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to <code>ON</code> (default: <code>OFF</code>). The unit of measure displayed for this counter is 0.1%. This counter will currently return meaningful values for the MPI parcelport only.

Table 2.86: General performance counter `/runtime/count/component`

Counter type	<code>/runtime/count/component</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of components should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of currently active components of the specified type on the given <i>locality</i> .
Parameters	The type of the component. This is the string which has been used while registering the component with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <code>HPX_REGISTER_COMPONENT</code> .

Table 2.87: General performance counter `/runtime/count/action-invocation`

Counter type	<code>/runtime/count/action-invocation</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of action invocations should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall (local) invocation count of the specified action type on the given <i>locality</i> .
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <code>HPX_REGISTER_ACTION</code> or <code>HPX_REGISTER_ACTION_ID</code> .

Table 2.88: General performance counter `/runtime/count/remote-action-invocation`

Counter type	<code>/runtime/count/remote-action-invocation</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of action invocations should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall (remote) invocation count of the specified action type on the given <i>locality</i> .
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.89: General performance counter `/runtime/uptime`

Counter type	<code>/runtime/uptime</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the system uptime should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time since application start on the given <i>locality</i> in nanoseconds.

Table 2.90: General performance counter `/runtime/memory/virtual`

Counter type	<code>/runtime/memory/virtual</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the allocated virtual memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the amount of virtual memory currently allocated by the referenced <i>locality</i> (in bytes).

Table 2.91: General performance counter `/runtime/memory/resident`

Counter type	<code>/runtime/memory/resident</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the allocated resident memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the amount of resident memory currently allocated by the referenced <i>locality</i> (in bytes).

Table 2.92: General performance counter `/runtime/memory/total`

Counter type	<code>/runtime/memory/total</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the total available memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> . Note: only supported in Linux.
Description	Returns the total available memory for use by the referenced <i>locality</i> (in bytes). This counter is available on Linux and Windows systems only.

Table 2.93: General performance counter `/runtime/io/read_bytes_issued`

Counter type	<code>/runtime/io/read_bytes_issued</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes read should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes read by the process (aggregate of count arguments passed to <code>read()</code> call or its analogues). This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.94: General performance counter `/runtime/io/write_bytes_issued`

Counter type	<code>/runtime/io/write_bytes_issued</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes written should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes written by the process (aggregate of count arguments passed to <code>write()</code> call or its analogues). This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.95: General performance counter `/runtime/io/read_syscalls`

Counter type	<code>/runtime/io/read_syscalls</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of system calls should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of system calls that perform I/O reads. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.96: General performance counter `/runtime/io/write_syscalls`

Counter type	<code>/runtime/io/write_syscalls</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of system calls should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of system calls that perform I/O writes. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.97: General performance counter `/runtime/io/read_bytes_transferred`

Counter type	<code>/runtime/io/read_bytes_transferred</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes retrieved from storage by I/O operations. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.98: General performance counter `/runtime/io/write_bytes_transferred`

Counter type	<code>/runtime/io/write_bytes_transferred</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes retrieved from storage by I/O operations. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.99: General performance counter `/runtime/io/write_bytes_cancelled`

Counter type	<code>/runtime/io/write_bytes_cancelled</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes not being transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes accounted by <code>write_bytes_transferred</code> that has not been ultimately stored due to truncation or deletion. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.100: Performance counter `/papi/<papi_event>`

Counter type	<code>/papi/<papi_event></code> where: <papi_event> is the name of the PAPI event to expose as a performance counter (such as <code>PAPI_SR_INS</code>). Note that the list of available PAPI events changes depending on the used architecture. For a full list of available PAPI events and their (short) description use the <code>--hpx:list-counters</code> and <code>--hpx:papi-event-info=all</code> command line options.
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all busy-loop counters of all worker threads should be queried. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i>. <code>worker-thread#*</code> is defining the worker thread for which the current value of the busy-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code>.
Description	Returns the current count of occurrences of the specified PAPI event. This counter is available only if the configuration time constant <code>HPX_WITH_PAPI</code> is set to <code>ON</code> (default: <code>OFF</code>).

Table 2.101: Performance counter `/statistics/average`

Counter type	<code>/statistics/average</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current average (mean) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.102: Performance counter `/statistics/rolling_average`

Counter type	<code>/statistics/rolling_average</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling average (mean) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is <code>10</code> . The third value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.103: Performance counter `/statistics/stddev`

Counter type	<code>/statistics/stddev</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current standard deviation (stddev) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.104: Performance counter `/statistics/rolling_stddev`

Counter type	<code>/statistics/rolling_stddev</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling variance (stddev) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is 10. The third value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.105: Performance counter `/statistics/median`

Counter type	<code>/statistics/median</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current (statistically estimated) median value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.106: Performance counter `/statistics/max`

Counter type	<code>/statistics/max</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current maximum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.107: Performance counter `/statistics/rolling_max`

Counter type	<code>/statistics/rolling_max</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling maximum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is 10. The third value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.108: Performance counter `/statistics/min`

Counter type	<code>/statistics/min</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current minimum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.109: Performance counter `/statistics/rolling_min`

Counter type	<code>/statistics/rolling_min</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling minimum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is 10. The third value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.110: Performance counter `/arithmetics/add`

Counter type	<code>/arithmetics/add</code>
Description	Returns the sum calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.111: Performance counter `/arithmetics/subtract`

Counter type	<code>/arithmetics/subtract</code>
Description	Returns the difference calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.112: Performance counter `/arithmetics/multiply`

Counter type	<code>/arithmetics/multiply</code>
Description	Returns the product calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.113: Performance counter `/arithmetics/divide`

Counter type	<code>/arithmetics/divide</code>
Description	Returns the result of division of the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.114: Performance counter `/arithmetics/mean`

Counter type	<code>/arithmetics/mean</code>
Description	Returns the average value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.115: Performance counter `/arithmetics/variance`

Counter type	<code>/arithmetics/variance</code>
Description	Returns the standard deviation of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.116: Performance counter `/arithmetics/median`

Counter type	<code>/arithmetics/median</code>
Description	Returns the median value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.117: Performance counter `/arithmetics/min`

Counter type	<code>/arithmetics/min</code>
Description	Returns the minimum value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.118: Performance counter `/arithmetics/max`

Counter type	<code>/arithmetics/max</code>
Description	Returns the maximum value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.119: Performance counter `/arithmetics/count`

Counter type	<code>/arithmetics/count</code>
Description	Returns the count value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Note: The `/arithmetics` counters can consume an arbitrary number of other counters. For this reason those have to be specified as parameters (a comma separated list of counters appended after a '@'). For instance:

```
$ ./bin/hello_world_distributed -t2 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative \
  --hpx:print-counter=/arithmetics/add@/threads{locality#0/worker-thread#*}/count/
↪cumulative
hello world from OS-thread 0 on locality 0
hello world from OS-thread 1 on locality 0
/threads{locality#0/worker-thread#0}/count/cumulative,1,0.515640,[s],25
/threads{locality#0/worker-thread#1}/count/cumulative,1,0.515520,[s],36
/arithmetics/add@/threads{locality#0/worker-thread#*}/count/cumulative,1,0.516445,[s],64
```

Since all wildcards in the parameters are expanded, this example is fully equivalent to specifying both counters separately to `/arithmetics/add`:

```
$ ./bin/hello_world_distributed -t2 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative \
  --hpx:print-counter=/arithmetics/add@
  /threads{locality#0/worker-thread#0}/count/cumulative,\
  /threads{locality#0/worker-thread#1}/count/cumulative
```

Table 2.120: Performance counter /coalescing/count/parcels

Counter type	/coalescing/count/parcels
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of parcels handled by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.121: Performance counter /coalescing/count/messages

Counter type	/coalescing/count/messages
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of messages for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of messages generated by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.122: Performance counter /coalescing/count/average-parcels-per-message

Counter type	/coalescing/count/average-parcels-per-message
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of messages for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the average number of parcels sent in a message generated by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.123: Performance counter /coalescing/time/average-parcel-arrival

Counter type	/coalescing/time/average-parcel-arrival
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the average time between parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the average time between arriving parcels for the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.124: Performance counter /coalescing/time/parcel-arrival-histogram

Counter type	/coalescing/time/parcel-arrival-histogram
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the average time between parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns a histogram representing the times between arriving parcels for the action which is given by the counter parameter. This counter returns an array of values, where the first three values represent the three parameters used for the histogram followed by one value for each of the histogram buckets. The first unit of measure displayed for this counter [ns] refers to the lower and upper boundary values in the returned histogram data only. The second unit of measure displayed [0.1%] refers to the actual histogram data. For each bucket the counter shows a value between 0 and 1000 which corresponds to a percentage value between 0% and 100%.
Parameters	The action type and optional histogram parameters. The action type is the string which has been used while registering the action with HPX, e.g. which has been passed as the second parameter to the macro <code>HPX_REGISTER_ACTION</code> or <code>HPX_REGISTER_ACTION_ID</code> . The action type may be followed by a comma separated list of up-to three numbers: the lower and upper boundaries for the collected histogram, and the number of buckets for the histogram to generate. By default these three numbers will be assumed to be 0 ([ns], lower bound), 1000000 ([ns], upper bound), and 20 (number of buckets to generate).

Note: The performance counters related to *parcel* coalescing are available only if the configuration time constant `HPX_WITH_PARCEL_COALESCING` is set to ON (default: ON). However, even in this case it will be available only for actions that are enabled for parcel coalescing (see the macros `HPX_ACTION_USES_MESSAGE_COALESCING` and `HPX_ACTION_USES_MESSAGE_COALESCING_NOTHROW`).

APEX integration

HPX provides integration with APEX¹⁸², which is a framework for application profiling using task timers and various performance counters Huck *et al.*¹⁹⁰. It can be added as a git submodule by turning on the option `HPX_WITH_APEX:BOOL` during CMake¹⁸³ configuration. TAU¹⁸⁴ is an optional dependency when using APEX.

To build HPX with APEX¹⁸⁵, add `HPX_WITH_APEX=ON`, and, optionally, `Tau_ROOT=$PATH_TO_TAU` to your CMake¹⁸⁶ configuration. In addition, you can override the tag used for APEX¹⁸⁷ with the `HPX_WITH_APEX_TAG` option. Please see the APEX HPX documentation¹⁸⁸ for detailed instructions on using APEX¹⁸⁹ with HPX.

¹⁸² <http://uo-oaciss.github.io/apex>

¹⁹⁰ K. A. Huck, A. Porterfield, N Chaimov, H. Kaiser, A. D. Malony, T. Sterling, and R. Fowler. *An autonomic performance environment for exascale*. Supercomputing Frontiers and Innovations, 2015.

¹⁸³ <https://www.cmake.org>

¹⁸⁴ <https://www.cs.uoregon.edu/research/tau/home.php>

¹⁸⁵ <http://uo-oaciss.github.io/apex>

¹⁸⁶ <https://www.cmake.org>

¹⁸⁷ <http://uo-oaciss.github.io/apex>

¹⁸⁸ <https://uo-oaciss.github.io/apex/usage/#hpx-louisiana-state-university>

¹⁸⁹ <http://uo-oaciss.github.io/apex>

References

2.4.16 Using the LCI parcelport

Basic information

The [Lightweight Communication Interface](#)¹⁹¹ (LCI) is an ongoing research project aiming to provide efficient support for applications with irregular and asynchronous communication patterns such as graph analysis, sparse linear algebra, and task-based runtime on modern parallel architectures. Its features include (a) support for more communication primitives such as two-sided send/recv and one-sided (dynamic or direct) remote put/get (b) better multi-threaded performance (c) explicit user control of communication resource (d) flexible signaling mechanisms such as synchronizer, completion queue, and active message handler. It is designed to be a low-level communication library used by high-level libraries and frameworks.

The LCI parcelport is an experimental parcelport. It aims to provide the best possible communication performance on high-performance computation platforms. Compared to the MPI parcelport, it uses much fewer messages and memory copies to transfer an *HPX* parcel over the network. Its message transmission path involves minimum synchronization points and is almost lock-free. It is expected to be much faster than the MPI parcelport.

Build *HPX* with the LCI parcelport

While building *HPX*, you can specify a set of [CMake](#)¹⁹² variables to enable and configure the LCI parcelport. Below, there is a set of the most important and frequently used CMake variables.

HPX_WITH_PARCELPORT_LCI

Enable the LCI parcelport. This enables the use of LCI for networking operations in the *HPX* runtime. The default value is OFF because it's not available on all systems and/or requires another dependency. However, this experimental parcelport may provide better performance than the MPI parcelport. You must set this variable to ON in order to use the LCI parcelport. All the following variables only make sense when this variable is set to ON.

HPX_WITH_FETCH_LCI

Use FetchContent to fetch LCI. The default value is OFF. If this option is set to OFF. You need to install your own LCI library and *HPX* will try to find it using [CMake](#)¹⁹³ `find_package`. You can specify the location of the LCI installation by the environmental variable `LCI_ROOT`. Refer to the [LCI README](#)¹⁹⁴ for how to install LCI. If this option is set to ON, *HPX* will fetch and build LCI for you. You can use the following [CMake](#)¹⁹⁵ variables to configure this behavior for your platform.

HPX_WITH_LCI_TAG

This variable only takes effect when `HPX_WITH_FETCH_LCI` is set to ON and `FETCHCONTENT_SOURCE_DIR_LCI` is not set. *HPX* will fetch LCI from its github repository. This variable controls the branch/tag LCI will be fetched.

FETCHCONTENT_SOURCE_DIR_LCI

This variable only takes effect when `HPX_WITH_FETCH_LCI` is set to ON. When it is defined, `HPX_WITH_LCI_TAG` will be ignored. It accepts a path to a local version of LCI source code and *HPX* will fetch and build LCI from there. The default value is set conservatively for the stability of *HPX*, but users are welcome to set this variable to `master` for potentially better performance.

¹⁹¹ <https://github.com/uiuc-hpc/lci>

¹⁹² <https://www.cmake.org>

¹⁹³ <https://www.cmake.org>

¹⁹⁴ <https://github.com/uiuc-hpc/lci#readme>

¹⁹⁵ <https://www.cmake.org>

Run HPX with the LCI parcelport

We use the same mechanisms as MPI to launch LCI, so you can use the same way you run MPI parcelport to run LCI parcelport. Typically, it would be `hpxrun.py`, `mpirun`, or `srun`.

`hpxrun.py` serves as a wrapper for `mpirun` and `srun`. If you are using `hpxrun.py`, pass `-p lci` to the scripts. You also need to pass either `-r mpi` or `-r srun` to select the correct run wrapper according to the platform.

If you are using `mpirun` or `srun`, you can just pass `--hpx:ini=hpx.parcels.lci.priority=1000`, `--hpx:ini=hpx.parcels.lci.enable=1`, and `--hpx:ini=hpx.parcels.bootstrap=lci` to the HPX applications.

The `hpxrun.py` argument `-r none` (the default option for the run wrapper) and its corresponding HPX arguments `--hpx:hpx` and `--hpx:agas` do not work for the MPI or the LCI parcelport.

Performance tuning of the LCI parcelport

We encourage users to set the following environmental variables when using the LCI parcelport to get better performance.

```
$ export LCI_SERVER_MAX_SENDS=1024
$ export LCI_SERVER_MAX_RECVS=4096
$ export LCI_SERVER_NUM_PKTS=65536
$ export LCI_SERVER_MAX_CQES=65536
$ export LCI_PACKET_SIZE=12288
```

This setting needs roughly 800MB memory per process. The memory consumption mainly comes from the packets, which can be calculated using $LCI_SERVER_NUM_PKTS \times LCI_PACKET_SIZE$.

In addition, users can tune the following command-line options when using the LCI parcelport to get better performance.

--hpx:ini=hpx.parcels.lci.ndevices=<int>

The number of LCI devices to use. The default value is 2. An LCI device represents a collection of network resources. More devices lead to lower thread contention, but too many devices may lead to load imbalance or hardware overhead.

--hpx:ini=hpx.parcels.lci.progress_type=<worker|rp>

The way to progress the LCI device. The default value is `worker`. The `worker` option uses all worker threads to progress the LCI devices. The `rp` option uses dedicated pinned threads to progress the LCI devices. Normally, the `worker` option gives better performance, but the `rp` option has been observed with better performance on some clusters with prior generation of InfiniBand hardware.

Reference

Yan, Jiakun, Hartmut Kaiser, and Marc Snir. *Understanding the Communication Needs of Asynchronous Many-Task Systems—A Case Study of HPX+ LCI*. arXiv preprint, 2025.

Yan, Jiakun, and Marc Snir. *LCI: a Lightweight Communication Interface for Efficient Asynchronous Multithreaded Communication*. The International Conference for High Performance Computing, Networking, Storage, and Analysis (SC), 2025.

2.4.17 Using the LCW parcelport

Basic information

The LCW parcelport is an advanced MPI parcelport that can utilize the MPICH VCI and Continuation extensions. The exact MPI implementation is wrapped in a thin wrapper layer (the Lightweight Communication Wrapper, or LCW). This wrapper provides an active message, send/recv, completion queue, and device abstraction on top of MPI (with/without extensions), GASNet-EX, and LCI. The GASNet-EX backend of LCW cannot be used in *HPX* for now, as it lacks send/recv support.

Build *HPX* with the LCW parcelport

While building *HPX*, you can specify a set of [CMake](https://www.cmake.org)¹⁹⁶ variables to enable and configure the LCW parcelport. Below, there is a set of the most important and frequently used CMake variables.

HPX_WITH_PARCELPORT_LCW

Enable the LCW parcelport. This enables the use of LCW for networking operations in the *HPX* runtime. The default value is OFF because it's not available on all systems and/or requires another dependency. You must set this variable to ON in order to use the LCW parcelport. All the following variables only make sense when this variable is set to ON.

HPX_WITH_FETCH_LCW

Use FetchContent to fetch LCW. The default value is OFF. If this option is set to OFF. You need to install your own LCW library and *HPX* will try to find it using [CMake](https://www.cmake.org)¹⁹⁷ `find_package`. You can specify the location of the LCW installation by the environmental variable `LCW_ROOT`. Refer to the [LCW README](https://github.com/JiakunYan/lcw#readme)¹⁹⁸ for how to install LCW. If this option is set to ON. *HPX* will fetch and build LCW for you. You can use the following [CMake](https://www.cmake.org)¹⁹⁹ variables to configure this behavior for your platform.

HPX_WITH_LCW_TAG

This variable only takes effect when `HPX_WITH_FETCH_LCW` is set to ON and `FETCHCONTENT_SOURCE_DIR_LCW` is not set. *HPX* will fetch LCW from its github repository. This variable controls the branch/tag LCW will be fetched.

FETCHCONTENT_SOURCE_DIR_LCW

This variable only takes effect when `HPX_WITH_FETCH_LCW` is set to ON. When it is defined, `HPX_WITH_LCW_TAG` will be ignored. It accepts a path to a local version of LCW source code and *HPX* will fetch and build LCW from there.

Run *HPX* with the LCW parcelport

You can configure runtime behavior with the following options.

--hpx:ini=hpx.parcel.lcw.ndevices=<n>

The number of LCW devices to use (default: 2). Each LCW device maps to an MPI communicator or an LCI device. When the MPICH VCI extension is enabled, each MPI communicator will be mapped to a dedicated collection of network resources. More devices lead to lower thread contention, but too many devices may lead to load imbalance or hardware overhead.

¹⁹⁶ <https://www.cmake.org>

¹⁹⁷ <https://www.cmake.org>

¹⁹⁸ <https://github.com/JiakunYan/lcw#readme>

¹⁹⁹ <https://www.cmake.org>

Reference

Yan, Jiakun, Marc Snir, and Yanfei Guo. *Examining MPI and its Extensions for Asynchronous Multithreaded Communication*. In *European MPI Users' Group Meeting*, pp. 122-142. Cham: Springer Nature Switzerland, 2025.

2.4.18 HPX runtime and resources

HPX thread scheduling policies

The HPX runtime has six thread scheduling policies: local-priority, static-priority, local, static, local-workrequesting-fifo, and abp-priority. These policies can be specified from the command line using the command line option `--hpx:queuing`. In order to use a particular scheduling policy, the runtime system must be built with the appropriate scheduler flag turned on (e.g. `cmake -DHPX_THREAD_SCHEDULERS=local`, see *CMake options* for more information).

Priority local scheduling policy (default policy)

The priority local scheduling policy maintains one queue per operating system (OS) thread. The OS thread pulls its work from this queue. By default the number of high priority queues is equal to the number of OS threads; the number of high priority queues can be specified on the command line using `--hpx:high-priority-threads`. High priority threads are executed by any of the OS threads before any other work is executed. When a queue is empty, work will be taken from high priority queues first. There is one low priority queue from which threads will be scheduled only when there is no other work.

For this scheduling policy there is an option to turn on NUMA sensitivity using the command line option `--hpx:numa-sensitive`. When NUMA sensitivity is turned on, work stealing is done from queues associated with the same NUMA domain first, only after that work is stolen from other NUMA domains.

This scheduler is enabled at build time by default using the FIFO (first-in-first-out) queueing policy. This policy can be invoked using `--hpx:queuinglocal-priority-fifo`. The scheduler can also be enabled using the LIFO (last-in-first-out) policy. This is not the default policy and must be invoked using the command line option `--hpx:queuinglocal-priority-lifo`.

Static priority scheduling policy

- invoke using: `--hpx:queuingstatic-priority` (or `-qs`)

The static scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads). Threads are distributed in a round robin fashion. There is no thread stealing in this policy.

Local scheduling policy

- invoke using: `--hpx:queuinglocal` (or `-ql`)
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=local`

The local scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads).

Static scheduling policy

- invoke using: `--hpx:queuingstatic`
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=static`

The static scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads). Threads are distributed in a round robin fashion. There is no thread stealing in this policy.

Priority ABP scheduling policy

- invoke using: `--hpx:queuingabp-priority-fifo`
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=abp-priority`

Priority ABP policy maintains a double ended lock free queue for each OS thread. By default the number of high priority queues is equal to the number of OS threads; the number of high priority queues can be specified on the command line using `--hpx:high-priority-threads`. High priority threads are executed by the first OS threads before any other work is executed. When a queue is empty work will be taken from high priority queues first. There is one low priority queue from which threads will be scheduled only when there is no other work. For this scheduling policy there is an option to turn on NUMA sensitivity using the command line option `--hpx:numa-sensitive`. When NUMA sensitivity is turned on work stealing is done from queues associated with the same NUMA domain first, only after that work is stolen from other NUMA domains.

This scheduler can be used with two underlying queuing policies (FIFO: first-in-first-out, and LIFO: last-in-first-out). In order to use the LIFO policy use the command line option `--hpx:queuingabp-priority-lifo`.

Work requesting scheduling policies

- invoke using: `--hpx:queuinglocal-workrequesting-fifo`, using `--hpx:queuinglocal-workrequesting-lifo`, or using `--hpx:queuinglocal-workrequesting-mc`

The work-requesting policies rely on a different mechanism of balancing work between cores (compared to the other policies listed above). Instead of actively trying to steal work from other cores, requesting work relies on a less disruptive mechanism. If a core runs out of work, instead of actively looking at the queues of neighboring cores, in this case a request is posted to another core. This core now (whenever it is not busy with other work) either responds to the original core by sending back work or passes the request on to the next possible core in the system. In general, this scheme avoids contention on the work queues as those are always accessed by their own cores only.

The HPX resource partitioner

The *HPX* resource partitioner lets you take the execution resources available on a system—processing units, cores, and numa domains—and assign them to thread pools. By default *HPX* creates a single thread pool name `default`. While this is good for most use cases, the resource partitioner lets you create multiple thread pools with custom resources and options.

Creating custom thread pools is useful for cases where you have tasks which absolutely need to run without interference from other tasks. An example of this is when using `MPI`²⁰⁰ for distribution instead of the built-in mechanisms in *HPX* (useful in legacy applications). In this case one can create a thread pool containing a single thread for MPI communication. MPI tasks will then always run on the same thread, instead of potentially being stuck in a queue behind other threads.

²⁰⁰ https://en.wikipedia.org/wiki/Message_Passing_Interface

Note that *HPX* thread pools are completely independent from each other in the sense that task stealing will never happen between different thread pools. However, tasks running on a particular thread pool can schedule tasks on another thread pool.

Note: It is simpler in some situations to schedule important tasks with high priority instead of using a separate thread pool.

Using the resource partitioner

The `hpx::resource::partitioner` is now created during *HPX* runtime initialization without explicit action needed from the user. To specify some of the initialization parameters you can use the `hpx::init_params`.

The resource partitioner callback is the interface to add thread pools to the *HPX* runtime and to assign resources to the thread pools. In order to create custom thread pools you can specify the resource partitioner callback `hpx::init_params::rp_callback` which will be called once the resource partitioner will be created, see the example below. You can also specify other parameters, see `hpx::init_params`.

To add a thread pool use the `hpx::resource::partitioner::create_thread_pool` method. If you simply want to use the default scheduler and scheduler options, it is enough to call `rp.create_thread_pool("my-thread-pool")`.

Then, to add resources to the thread pool you can use the `hpx::resource::partitioner::add_resource` method. The resource partitioner exposes the hardware topology retrieved using [Portable Hardware Locality \(HWLOC\)](#)²⁰¹ and lets you iterate through the topology to add the wanted processing units to the thread pool. Below is an example of adding all processing units from the first NUMA domain to a custom thread pool, unless there is only one NUMA domain in which case we leave the first processing unit for the default thread pool:

Note: Whatever processing units are not assigned to a thread pool by the time `hpx::init` is called will be added to the default thread pool. It is also possible to explicitly add processing units to the default thread pool, and to create the default thread pool manually (in order to e.g. set the scheduler type).

Tip: The command line option `--hpx:print-bind` is useful for checking that the thread pools have been set up the way you expect.

Difference between the old and new version

In the old version, you had to create an instance of the `resource_partitioner` with `argc` and `argv`.

```
int main(int argc, char** argv)
{
    hpx::resource::partitioner rp(argc, argv);
    hpx::init();
}
```

From *HPX* 1.5.0 onwards, you just pass `argc` and `argv` to `hpx::init()` or `hpx::start()` for the binding options to be parsed by the resource partitioner.

²⁰¹ <https://www.open-mpi.org/projects/hwloc/>

```
int main(int argc, char** argv)
{
    hpx::init_params init_args;
    hpx::init(argc, argv, init_args);
}
```

In the old version, when creating a custom thread pool, you just called the utilities on the resource partitioner instantiated previously.

```
int main(int argc, char** argv)
{
    hpx::resource::partitioner rp(argc, argv);

    rp.create_thread_pool("my-thread-pool");

    bool one_numa_domain = rp.numa_domains().size() == 1;
    bool skipped_first_pu = false;

    hpx::resource::numa_domain const& d = rp.numa_domains()[0];

    for (const hpx::resource::core& c : d.cores())
    {
        for (const hpx::resource::pu& p : c.pus())
        {
            if (one_numa_domain && !skipped_first_pu)
            {
                skipped_first_pu = true;
                continue;
            }

            rp.add_resource(p, "my-thread-pool");
        }
    }

    hpx::init();
}
```

You now specify the resource partitioner callback which will tie the resources to the resource partitioner created during runtime initialization.

```
void init_resource_partitioner_handler(hpx::resource::partitioner& rp)
{
    rp.create_thread_pool("my-thread-pool");

    bool one_numa_domain = rp.numa_domains().size() == 1;
    bool skipped_first_pu = false;

    hpx::resource::numa_domain const& d = rp.numa_domains()[0];

    for (const hpx::resource::core& c : d.cores())
    {
        for (const hpx::resource::pu& p : c.pus())
        {
```

(continues on next page)

(continued from previous page)

```

        if (one_numa_domain && !skipped_first_pu)
        {
            skipped_first_pu = true;
            continue;
        }

        rp.add_resource(p, "my-thread-pool");
    }
}

int main(int argc, char* argv[])
{
    hpx::init_params init_args;
    init_args.rp_callback = &init_resource_partitioner_handler;

    hpx::init(argc, argv, init_args);
}

```

Advanced usage

It is possible to customize the built in schedulers by passing scheduler options to `hpx::resource::partitioner::create_thread_pool`. It is also possible to create and use custom schedulers.

Note: It is not recommended to create your own scheduler. The *HPX* developers use this to experiment with new scheduler designs before making them available to users via the standard mechanisms of choosing a scheduler (command line options). If you would like to experiment with a custom scheduler the resource partitioner example `shared_priority_queue_scheduler.cpp` contains a fully implemented scheduler with logging, etc. to make exploration easier.

To choose a scheduler and custom mode for a thread pool, pass additional options when creating the thread pool like this:

```

rp.create_thread_pool("my-thread-pool",
    hpx::resource::policies::local_priority_lifo,
    hpx::policies::scheduler_mode(
        hpx::policies::scheduler_mode::default |
        hpx::policies::scheduler_mode::enable_elasticity));

```

The available schedulers are documented here: `hpx::resource::scheduling_policy`, and the available scheduler modes here: `hpx::threads::policies::scheduler_mode`. Also see the examples folder for examples of advanced resource partitioner usage: `simple_resource_partitioner.cpp` and `oversubscribing_resource_partitioner.cpp`.

2.4.19 Executors

Executors in *HPX* provide a flexible way to control **how, when, and where** tasks are executed. Instead of manually creating threads or managing thread pools, you can hand your tasks to an executor, and it takes care of the details of running them.

This page introduces the concept of executors, the main types available in *HPX*, and how to create custom executors.

What is an executor?

An **executor** is an abstraction that separates the *what* from the *how* of task execution:

- **What:** the work to be performed (e.g. a function or task).
- **How:** whether the task runs synchronously, asynchronously, or in parallel across multiple cores.

By using executors, you can switch between execution strategies without rewriting your algorithms. *HPX* provides a rich set of executors with a unified API.

Main Executors in *HPX*

HPX provides multiple executors. Below are three of the most commonly used:

Parallel Executor

- Default in *HPX*.
- Creates a new HPX thread for every scheduled task.
- Works well for large tasks, but frequent small tasks incur overhead due to thread creation/destruction.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::for_each(
    hpx::execution::par,
    data.begin(), data.end(),
    [](int &x) {
        x += 1;
    }
);
```


Fork-Join Executor

- Spawns one thread per CPU core when created.
- Threads are reused across tasks, avoiding repeated creation costs.
- Efficient for workloads with many sequential parallel regions.
- May waste resources if parallel work is limited.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::execution::experimental::fork_join_executor exec;

hpx::for_each(
    hpx::execution::par.on(exec),
    data.begin(), data.end(),
    [](int &x) {
        x += 1;
    }
);
```

Sequential Executor

- Executes all tasks synchronously on the calling thread.
- Useful for debugging (deterministic execution) or when parallelism brings no benefit.
- Maintains the same executor-based API while running tasks sequentially.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::execution::sequenced_executor seq_exec;

hpx::for_each(
    hpx::execution::seq.on(seq_exec),
    data.begin(), data.end(),
    [](int &x) { x += 1; }
);
```

Executors in real-world applications

A practical example is the **LULESH** mini-application (a hydrodynamics benchmark).




Fig. 2.11: Parallel executor: creates and destroys threads for each loop.

- With the **parallel executor**, each parallel loop creates and destroys new threads, introducing overhead.
- With the **fork-join executor**, threads are created once and reused across loops, reducing overhead and improving performance.

In studies, the fork-join executor achieved significant speedups, in some cases more than twice as fast as traditional OpenMP implementations.




Fig. 2.13: Performance comparison between executors in the LULESH benchmark.

Custom executors

While *HPX* provides a variety of built-in executors, you may sometimes need to adapt task execution to your own requirements. This is where **custom executors** come in. By writing a small wrapper around an existing executor, you can extend its behavior—for example, to add logging, profiling information, or special scheduling rules—while still taking advantage of the *HPX* executor API.

Custom annotating executor

The following example shows how to implement a simple executor that annotates tasks with a string label for easier debugging and profiling.

Note: Annotations do not affect how tasks run or what results they produce. Their main purpose is to give human-readable names to tasks so that they can be identified in profilers, and debuggers.

Full example code

```
#include <hpx/hpx_main.hpp>
#include <hpx/include/parallel_executors.hpp>
#include <hpx/include/async.hpp>
#include <hpx/execution.hpp>
#include <hpx/modules/async_base.hpp>
#include <hpx/modules/threading_base.hpp>

#include <iostream>
#include <string>
#include <utility>

template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}

    // Non-blocking one-way executor
    template <typename F, typename... Ts>
    friend void tag_invoke(hpx::parallel::execution::post_t,
                          simple_annotating_executor const& exec,
                          F&& f, Ts&&... ts)
    {
        hpx::post(
```

(continues on next page)

(continued from previous page)

```

        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
    }

    // Synchronous execution
    template <typename F, typename... Ts>
    friend auto tag_invoke(hpx::parallel::execution::sync_execute_t,
        simple_annotating_executor const& exec,
        F&& f, Ts&&... ts)
    {
        return hpx::parallel::execution::sync_execute(
            exec.base_,
            hpx::annotated_function(std::forward<F>(f), exec.annotation_),
            std::forward<Ts>(ts)...);
    }
};

// Example functions
int compute_square(int x)
{
    std::cout << "[sync_execute] Running task with annotation\n";
    return x * x;
}

void say_hello()
{
    std::cout << "[post] Running task with annotation\n";
}

int main()
{
    simple_annotating_executor exec(hpx::execution::parallel_executor{}, "my_custom_task
↪");

    // Synchronous execution
    int result = hpx::parallel::execution::sync_execute(exec, &compute_square, 7);
    std::cout << "Result from sync_execute: " << result << "\n";

    // Post a task
    hpx::parallel::execution::post(exec, &say_hello);

    return 0;
}

```

Explanation

The first lines pull in the necessary HPX headers for executors, asynchronous execution, and annotated functions. The key one here is `hpx/threading_base/annotated_function.hpp`, which provides the facility to tag tasks with a string label. We then define a `simple_annotating_executor` that wraps another executor and associates an annotation string with every task:

```
template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}
};
```

The `post` customization schedules a task to run asynchronously. We wrap the task in `hpx::annotated_function` so that it carries the annotation. Executors in HPX customize these operations through `tag_invoke` overloads, which are selected by special tag objects like `post_t` and `sync_execute_t`. This is why the executor interface may look different from a normal member function API.

```
template <typename F, typename... Ts>
friend void tag_invoke(hpx::parallel::execution::post_t,
                      simple_annotating_executor const& exec,
                      F&& f, Ts&&... ts)
{
    hpx::post(
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
}
```

The `sync_execute` customization runs a task immediately and returns the result. Again, we wrap the function with an annotation before executing. The key difference is that `post` schedules a task in a fire-and-forget style (no result is returned), while `sync_execute` blocks until the task finishes and gives you the result back.

```
template <typename F, typename... Ts>
friend auto tag_invoke(hpx::parallel::execution::sync_execute_t,
                      simple_annotating_executor const& exec,
                      F&& f, Ts&&... ts)
{
    return hpx::parallel::execution::sync_execute(
        exec.base_,
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
}
```

Note how we delegate the actual execution to `exec.base_`, the underlying executor. This makes the custom executor lightweight: it only adds annotations, while leaving the scheduling strategy to the base executor (here, a `parallel_executor`).

We define two simple functions to demonstrate both synchronous and asynchronous execution: These functions also print to `std::cout`, but this output is not the actual annotation. Annotations are stored internally by HPX and become visible when you use debugging or profiling tools.

```

int compute_square(int x)
{
    std::cout << "[sync_execute] Running task with annotation\n";
    return x * x;
}

void say_hello()
{
    std::cout << "[post] Running task with annotation\n";
}

```

Finally, in main we create the executor with a base executor and annotation string. We then run one task with `sync_execute` (blocking, returns result) and one with `post` (asynchronous, fire-and-forget). You can also create multiple annotating executors with different strings, so each task gets its own label. This is especially useful in larger applications with many different kinds of tasks, where annotations make it much easier to trace what is happening.

```

int main()
{
    simple_annotating_executor exec(hpx::execution::parallel_executor{}, "my_custom_task
↪");

    // Synchronous execution
    int result = hpx::parallel::execution::sync_execute(exec, &compute_square, 7);
    std::cout << "Result from sync_execute: " << result << "\n";

    // Post a task
    hpx::parallel::execution::post(exec, &say_hello);

    return 0;
}

```

Custom annotating executor with parallel algorithms

The following example demonstrates how to use a custom annotating executor with *HPX* parallel algorithms, such as `for_each`. This allows you to attach annotations to tasks while executing them in parallel.

Full example code

```

#include <hpx/execution.hpp>
#include <hpx/hpx_main.hpp>
#include <hpx/include/parallel_algorithm.hpp>
#include <hpx/include/parallel_executors.hpp>
#include <hpx/modules/threading_base.hpp>

#include <iostream>
#include <utility>
#include <vector>

template <typename BaseExecutor>
struct simple_annotating_executor

```

(continues on next page)

(continued from previous page)

```

{
    BaseExecutor base_;
    char const* annotation_;

    using execution_category =
        hpx::traits::executor_execution_category_t<BaseExecutor>;

    simple_annotating_executor(BaseExecutor exec, char const* ann)
    : base_(std::move(exec))
    , annotation_(ann)
    {
    }

    // Bulk async_execute (used by parallel algorithms)
    template <typename F, typename Shape, typename... Ts>
    friend auto tag_invoke(hpx::parallel::execution::bulk_async_execute_t,
        simple_annotating_executor const& exec, F&& f, Shape const& shape,
        Ts&&... ts)
    {
        return hpx::parallel::execution::bulk_async_execute(
            exec.base_,
            hpx::annotated_function(std::forward<F>(f), exec.annotation_),
            shape, std::forward<Ts>(ts)...);
    }
};

namespace hpx::execution::experimental {

    // The annotating executor exposes the same executor categories as its
    // underlying (wrapped) executor.

    template <typename BaseExecutor>
    struct is_two_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_two_way_executor<BaseExecutor>
    {
    };
} // namespace hpx::execution::experimental

int main()
{
    using base_executor = hpx::execution::parallel_executor;
    simple_annotating_executor exec(base_executor{}, "for_each_task");

    std::vector<int> data = {1, 2, 3, 4, 5};

    // Use the custom executor with a parallel algorithm
    hpx::for_each(hpx::execution::par.on(exec), // attach executor
        data.begin(), data.end(), [](int& x) {
            std::cout << "Processing " << x << " on thread "
                << hpx::get_worker_thread_num() << "\n";
            x *= x;
        });
}

```

(continues on next page)

(continued from previous page)

```

std::cout << "Squared values: ";
for (int v : data)
    std::cout << v << " ";
std::cout << "\n";

return 0;
}

```

Explanation

Similar as before, the first lines pull in the necessary HPX headers for executors, asynchronous execution, and annotated functions. The key one here is *hpx/threading_base/annotated_function.hpp*, which provides the facility to tag tasks with a string label. We then define a *simple_annotating_executor* that wraps another executor and associates an annotation string with every task:

```

template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    using execution_category =
        hpx::traits::executor_execution_category_t<BaseExecutor>;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}
};

```

Note that we expose the execution category of the custom executor with *using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>*. We inherit the execution category from the underlying executor (*BaseExecutor*), which ensures that our *simple_annotating_executor* behaves like the base executor in terms of parallelism and task execution capabilities.

The *bulk_async_execute* customization schedules a set of tasks to run asynchronously. We wrap each task in *hpx::annotated_function* so that it carries the annotation. Executors in *HPX* customize these operations through *tag_invoke* overloads, which are selected by special tag objects like *bulk_async_execute_t*. This is why the executor interface may look different from a normal member function API - it uses tag dispatch to integrate seamlessly with the *HPX* parallel algorithms infrastructure.

```

template <typename F, typename Shape, typename... Ts>
friend auto tag_invoke(hpx::parallel::execution::bulk_async_execute_t,
    simple_annotating_executor const& exec, F&& f, Shape const& shape,
    Ts&&... ts)
{
    return hpx::parallel::execution::bulk_async_execute(
        exec.base_,
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        shape, std::forward<Ts>(ts)...);
}

```


Note how we delegate the actual execution to `exec.base_`, the underlying executor. This makes the custom executor lightweight: it only adds annotations, while leaving the scheduling strategy to the base executor (here, a `parallel_executor`).

The `hpx::execution::experimental` namespace contains traits that describe executor capabilities, such as whether an executor can run tasks one-way, two-way, or never-blocking. These traits are used internally by *HPX* to verify that an executor is compatible with a given parallel algorithm or execution policy.

```
namespace hpx::execution::experimental {

    // The annotating executor exposes the same executor categories as its
    // underlying (wrapped) executor.

    template <typename BaseExecutor>
    struct is_never_blocking_one_way_executor<
        simple_annotating_executor<BaseExecutor>>
    : is_never_blocking_one_way_executor<BaseExecutor>
    {
    };

    template <typename BaseExecutor>
    struct is_one_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_one_way_executor<BaseExecutor>
    {
    };

    template <typename BaseExecutor>
    struct is_two_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_two_way_executor<BaseExecutor>
    {
    };

}
```

- `is_never_blocking_one_way_executor` indicates whether the executor can schedule tasks in a fire-and-forget style without blocking.
- `is_one_way_executor` indicates support for one-way execution (tasks can be scheduled but no result is returned).
- `is_two_way_executor` indicates support for two-way execution (tasks return a result or a future).

In all cases, the custom executor inherits the capabilities of the base executor, so it integrates seamlessly with *HPX* algorithms.

This design ensures that `simple_annotating_executor` can be used anywhere its underlying executor could be used, while still adding the annotation functionality. It keeps the custom executor lightweight and fully compatible with the parallel algorithms infrastructure.

In main, we create the executor with a base executor and an annotation string, and then use it with a parallel algorithm:

```
int main()
{
    using base_executor = hpx::execution::parallel_executor;
    simple_annotating_executor exec(base_executor{}, "for_each_task");

    std::vector<int> data = {1, 2, 3, 4, 5};

    // Use the custom executor with a parallel algorithm
```

(continues on next page)

(continued from previous page)

```

hpx::for_each(hpx::execution::par.on(exec),    // attach executor
    data.begin(), data.end(), [](int& x) {
        std::cout << "Processing " << x << " on thread "
            << hpx::get_worker_thread_num() << "\n";
        x *= x;
    });

std::cout << "Squared values: ";
for (int v : data)
    std::cout << v << " ";
std::cout << "\n";

return 0;
}

```

First, we create a base executor (*parallel_executor*) and wrap it in our *simple_annotating_executor*, providing an annotation string “for_each_task”. This custom executor will attach the annotation to every task it schedules, while delegating actual execution to the base executor.

We then use `hpx::for_each` with a parallel execution policy and attach our custom executor using `par.on(exec)`: `hpx::execution::par.on(exec)` attaches our custom executor to the algorithm. `for_each` internally partitions the work across threads and schedules each task using *bulk_async_execute*. Each task is annotated with “for_each_task”, visible in debuggers and profilers. The results of the parallel computation are stored in the data vector, demonstrating that the algorithm

executed successfully in parallel.

This pattern is especially useful in larger applications with many tasks, as annotations make it much easier to trace and debug the execution of parallel algorithms.

2.4.20 Error handling

Like in any other asynchronous invocation scheme, it is important to be able to handle error conditions occurring while the asynchronous (and possibly remote) operation is executed. In *HPX* all error handling is based on standard C++ exception handling. Any exception thrown during the execution of an asynchronous operation will be transferred back to the original invocation *locality*, where it will be rethrown during synchronization with the calling thread.

The source code for this example can be found here: `error_handling.cpp`.

Working with exceptions

For the following description assume that the function `raise_exception()` is executed by invoking the plain action `raise_exception_type`.

```

void raise_exception()
{
    HPX_THROW_EXCEPTION(
        hpx::error::no_success, "raise_exception", "simulated error");
}
HPX_PLAIN_ACTION(raise_exception, raise_exception_action)

```

The exception is thrown using the macro `HPX_THROW_EXCEPTION`. The type of the thrown exception is `hpx::exception`. This associates additional diagnostic information with the exception, such as file name and line

number, *locality* id and thread id, and stack backtrace from the point where the exception was thrown.

Any exception thrown during the execution of an action is transferred back to the (asynchronous) invocation site. It will be rethrown in this context when the calling thread tries to wait for the result of the action by invoking either `future<>::get()` or the synchronous action invocation wrapper as shown here:

Note: The exception is transferred back to the invocation site even if it is executed on a different *locality*.

Additionally, this example demonstrates how an exception thrown by an (possibly remote) action can be handled. It shows the use of `hpx::diagnostic_information`, which retrieves all available diagnostic information from the exception as a formatted string. This includes, for instance, the name of the source file and line number, the sequence number of the OS thread and the HPX thread id, the *locality* id and the stack backtrace of the point where the original exception was thrown.

Under certain circumstances it is desirable to output only some of the diagnostics, or to output those using different formatting. For this case, HPX exposes a set of lower-level functions as demonstrated in the following code snippet:

Working with error codes

Most of the API functions exposed by HPX can be invoked in two different modes. By default those will throw an exception on error as described above. However, sometimes it is desirable not to throw an exception in case of an error condition. In this case an object instance of the `hpx::error_code` type can be passed as the last argument to the API function. In case of an error, the error condition will be returned in that `hpx::error_code` instance. The following example demonstrates extracting the full diagnostic information without exception handling:

```
hpx::cout << "Error reporting using error code\n";

// Create a new error_code instance.
hpx::error_code ec;

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print just the essential error information.
    hpx::cout << "returned error: " << ec.get_message() << "\n";

    // Print all of the available diagnostic information as stored with
    // the exception.
    hpx::cout << "diagnostic information:"
               << hpx::diagnostic_information(ec) << "\n";
}

hpx::cout << std::flush;
```

Note: The error information is transferred back to the invocation site even if it is executed on a different *locality*.

This example shows how an error can be handled without having to resolve to exceptions and that the returned `hpx::error_code` instance can be used in a very similar way as the `hpx::exception` type above. Simply pass it to the `hpx::diagnostic_information`, which retrieves all available diagnostic information from the error code instance as a formatted string.

As for handling exceptions, when working with error codes, under certain circumstances it is desirable to output only some of the diagnostics, or to output those using different formatting. For this case, *HPX* exposes a set of lower-level functions usable with error codes as demonstrated in the following code snippet:

```
hpx::cout << "Detailed error reporting using error code\n";

// Create a new error_code instance.
hpx::error_code ec;

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print the elements of the diagnostic information separately.
    hpx::cout << "{what}: " << hpx::get_error_what(ec) << "\n";
    hpx::cout << "{locality-id}: " << hpx::get_error_locality_id(ec)
        << "\n";
    hpx::cout << "{hostname}: " << hpx::get_error_host_name(ec)
        << "\n";
    hpx::cout << "{pid}: " << hpx::get_error_process_id(ec) << "\n";
    hpx::cout << "{function}: " << hpx::get_error_function_name(ec)
        << "\n";
    hpx::cout << "{file}: " << hpx::get_error_file_name(ec) << "\n";
    hpx::cout << "{line}: " << hpx::get_error_line_number(ec)
        << "\n";
    hpx::cout << "{os-thread}: " << hpx::get_error_os_thread(ec)
        << "\n";
    hpx::cout << "{thread-id}: " << std::hex
        << hpx::get_error_thread_id(ec) << "\n";
    hpx::cout << "{thread-description}: "
        << hpx::get_error_thread_description(ec) << "\n\n";
    hpx::cout << "{state}: " << std::hex << hpx::get_error_state(ec)
        << "\n";
    hpx::cout << "{stack-trace}: " << hpx::get_error_backtrace(ec)
        << "\n";
    hpx::cout << "{env}: " << hpx::get_error_env(ec) << "\n";
}

hpx::cout << std::flush;
```

For more information please refer to the documentation of `hpx::get_error_what`, `hpx::get_error_locality_id`, `hpx::get_error_host_name`, `hpx::get_error_process_id`, `hpx::get_error_function_name`, `hpx::get_error_file_name`, `hpx::get_error_line_number`, `hpx::get_error_os_thread`, `hpx::get_error_thread_id`, `hpx::get_error_thread_description`, `hpx::get_error_backtrace`, `hpx::get_error_env`, and `hpx::get_error_state`.

Lightweight error codes

Sometimes it is not desirable to collect all the ambient information about the error at the point where it happened as this might impose too much overhead for simple scenarios. In this case, *HPX* provides a lightweight error code facility that will hold the error code only. The following snippet demonstrates its use:

```
hpx::cout << "Error reporting using an lightweight error code\n";

// Create a new error_code instance.
hpx::error_code ec(hpx::throwmode::lightweight);

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print just the essential error information.
    hpx::cout << "returned error: " << ec.get_message() << "\n";

    // Print all of the available diagnostic information as stored with
    // the exception.
    hpx::cout << "error code:" << ec.value() << "\n";
}

hpx::cout << std::flush;
```

All functions that retrieve other diagnostic elements from the `hpx::error_code` will fail if called with a lightweight `error_code` instance.

2.4.21 The *HPX* I/O-streams component

The *HPX* I/O-streams subsystem extends the standard C++ output streams `std::cout` and `std::cerr` to work in the distributed setting of an *HPX* application. All of the output streamed to `hpx::cout` will be dispatched to `std::cout` on the console *locality*. Likewise, all output generated from `hpx::cerr` will be dispatched to `std::cerr` on the console *locality*.

Note: All existing standard manipulators can be used in conjunction with `hpx::cout` and `hpx::cerr`.

In order to use either `hpx::cout` or `hpx::cerr`, application codes need to `#include <hpx/include/iostreams.hpp>`. For an example, please see the following ‘Hello world’ program:

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
```

(continues on next page)

(continued from previous page)

```
hpx::cout << "Hello World!\n" << std::flush;
return 0;
}
```

Additionally, those applications need to link with the `iostreams` component. When using CMake this can be achieved by using the `COMPONENT_DEPENDENCIES` parameter; for instance:

```
include(HPX_AddExecutable)

add_hpx_executable(
    hello_world
    SOURCES hello_world.cpp
    COMPONENT_DEPENDENCIES iostreams
)
```

Note: The `hpx::cout` and `hpx::cerr` streams buffer all output locally until a `std::endl` or `std::flush` is encountered. That means that no output will appear on the console as long as either of these is explicitly used.

2.4.22 Troubleshooting

Common issues

This section contains commonly encountered problems when compiling or using HPX.

See also the closed issues on [GitHub](https://github.com/TheHPXProject/hpx/issues?q=is%3Aissue+is%3Aclosed)²⁰² to find out how other people resolved a similar problem. If nothing of that works, you can also open a new issue on [GitHub](https://github.com/TheHPXProject/hpx/issues)²⁰³ or contact us using one the options found in [Support for deploying and using HPX](#)²⁰⁴.

`hpx::iostreams_component` target not found

You may see a [CMake](https://www.cmake.org)²⁰⁵ error message that looks a bit like this:

```
error: `hpx::iostreams_component` target not found
```

Simply ensure that *HPX* is installed with `HPX_WITH_DISTRIBUTED_RUNTIME=ON` to prevent encountering such error(s). This is required if you want to use `hpx::cout`.

²⁰² <https://github.com/TheHPXProject/hpx/issues?q=is%3Aissue+is%3Aclosed>

²⁰³ <https://github.com/TheHPXProject/hpx/issues>

²⁰⁴ <https://github.com/TheHPXProject/hpx/blob/master/.github/SUPPORT.md>

²⁰⁵ <https://www.cmake.org>

Undefined reference to `hpx::cout`

You may see a linker error message that looks a bit like this:

```
hello_world.cpp:(.text+0x5aa): undefined reference to `hpx::cout'
```

This usually happens if you are trying to use *HPX* iostreams functionality such as `hpx::cout` but are not linking against it. The iostreams functionality is not part of the core *HPX* library, and must be linked to explicitly. Typically this can be solved by adding `COMPONENT_DEPENDENCIES iostreams` to a call to `add_hpx_library/add_hpx_executable/hpx_setup_target` if using *CMake*²⁰⁶. See *Creating HPX projects* for more details.

Build fails with ASIO error

You may see an error message that looks a bit like this:

```
Cannot open include file asio/io_context.hpp
```

This can be resolved by using `-DHPX_WITH_FETCH_ASIO=ON` to the `cmake` command line.

See also the corresponding closed [Issue #5404](#)²⁰⁷ for more information.

Build fails with TCMalloc error

You may see an error message that looks a bit like this:

```
Could NOT find TCMalloc (missing: Tcmalloc_LIBRARY Tcmalloc_INCLUDE_DIR)
ERROR: HPX_WITH_MALLOC was set to tcmalloc, but tcmalloc could not be
found. Valid options for HPX_WITH_MALLOC are: system, tcmalloc, jemalloc,
mimalloc, tbbmalloc, and custom
```

This can be resolved either by defining `HPX_WITH_MALLOC=system` or by installing TCMalloc. This error occurs when users don't specify an option for `HPX_WITH_MALLOC`; in that case, *HPX* will be looking `tcmalloc`, which is the default value.

Useful suggestions

Reducing compilation time

If you want to significantly reduce compilation time, you can just use the local part of *HPX* for parallelism by disabling the distributed functionality. Moreover, you can avoid compiling examples. These can be done with the following flags:

```
-DHPX_WITH_NETWORKING=OFF
-DHPX_WITH_DISTRIBUTED_RUNTIME=OFF
-DHPX_WITH_EXAMPLES=OFF
-DHPX_WITH_TESTS=OFF
```

²⁰⁶ <https://www.cmake.org>

²⁰⁷ <https://github.com/TheHPXProject/hpx/issues/5404>

Linking *HPX* to your application

If you want to avoid installing and linking *HPX*, you can just build *HPX* and then use the following flag on your *HPX* application CMake configuration:

```
-DHPX_DIR=<build_dir>/lib/cmake/HPX
```

Note: For this to work you need not to specify `-DCMAKE_INSTALL_PREFIX` when building *HPX*.

HPX-application build type conformance

Your application's build type should align with the *HPX* build type. For example, if you specified `-DCMAKE_BUILD_TYPE=Debug` during the *HPX* compilation, then your application needs to be compiled with the same flag. We recommend keeping a separate build folder for different build types and just point accordingly to the type you want by using `-DHPX_DIR=<build_dir>/lib/cmake/HPX`.

2.5 Terminology

This section gives definitions for some of the terms used throughout the *HPX* documentation and source code.

Locality

A locality in *HPX* describes a synchronous domain of execution, or the domain of bounded upper response time. This normally is just a single node in a cluster or a NUMA domain in a SMP machine.

Active Global Address Space

AGAS

HPX incorporates a global address space. Any executing thread can access any object within the domain of the parallel application with the caveat that it must have appropriate access privileges. The model does not assume that global addresses are cache coherent; all loads and stores will deal directly with the site of the target object. All global addresses within a Synchronous Domain are assumed to be cache coherent for those processor cores that incorporate transparent caches. The Active Global Address Space used by *HPX* differs from research PGAS²⁰⁸ models. Partitioned Global Address Space is passive in their means of address translation. Copy semantics, distributed compound operations, and affinity relationships are some of the global functionality supported by AGAS.

Process

The concept of the “process” in *HPX* is extended beyond that of either sequential execution or communicating sequential processes. While the notion of process suggests action (as do “function” or “subroutine”) it has a further responsibility of context, that is, the logical container of program state. It is this aspect of operation that process is employed in *HPX*. Furthermore, referring to “parallel processes” in *HPX* designates the presence of parallelism within the context of a given process, as well as the coarse grained parallelism achieved through concurrency of multiple processes of an executing user job. *HPX* processes provide a hierarchical name space within the framework of the active global address space and support multiple means of internal state access from external sources.

Parcel

The Parcel is a component in *HPX* that communicates data, invokes an action at a distance, and distributes flow-control through the migration of continuations. Parcels bridge the gap of asynchrony between synchronous domains while maintaining symmetry of semantics between local and global execution. Parcels enable message-driven computation and may be seen as a form of “active messages”. Other important forms of message-driven

²⁰⁸ <https://www.pgas.org/>

computation predating active messages include *dataflow tokens*²⁰⁹, the *J-machine*'s²¹⁰ support for remote method instantiation, and at the coarse grained variations of Unix remote procedure calls, among others. This enables work to be moved to the data as well as performing the more common action of bringing data to the work. A parcel can cause actions to occur remotely and asynchronously, among which are the creation of threads at different system nodes or synchronous domains.

Local Control Object

Lightweight Control Object

LCO

A local control object (sometimes called a lightweight control object) is a general term for the synchronization mechanisms used in *HPX*. Any object implementing a certain concept can be seen as an LCO. This concept encapsulates the ability to be triggered by one or more events which when taking the object into a predefined state will cause a thread to be executed. This could either create a new thread or resume an existing thread.

The LCO is a family of synchronization functions potentially representing many classes of synchronization constructs, each with many possible variations and multiple instances. The LCO is sufficiently general that it can subsume the functionality of conventional synchronization primitives such as spinlocks, mutexes, semaphores, and global barriers. However due to the rich concept an LCO can represent powerful synchronization and control functionality not widely employed, such as dataflow and futures (among others), which open up enormous opportunities for rich diversity of distributed control and operation.

See *lcoss* for more details on how to use LCOs in *HPX*.

Action

An action is a function that can be invoked remotely. In *HPX* a plain function can be made into an action using a macro. See *applying_actions* for details on how to use actions in *HPX*.

Component

A component is a C++ object which can be accessed remotely. A component can also contain member functions which can be invoked remotely. These are referred to as component actions. See *Writing components* for details on how to use components in *HPX*.

2.6 Why *HPX*?

Current advances in high performance computing (HPC) continue to suffer from the issues plaguing parallel computation. These issues include, but are not limited to, ease of programming, inability to handle dynamically changing workloads, scalability, and efficient utilization of system resources. Emerging technological trends such as multi-core processors further highlight limitations of existing parallel computation models. To mitigate the aforementioned problems, it is necessary to rethink the approach to parallelization models. ParalleX contains mechanisms such as multi-threading, *parcels*, *global name space* support, percolation and *local control objects (LCO)*. By design, ParalleX overcomes limitations of current models of parallelism by alleviating contention, latency, overhead and starvation. With ParalleX, it is further possible to increase performance by at least an order of magnitude on challenging parallel algorithms, e.g., dynamic directed graph algorithms and adaptive mesh refinement methods for astrophysics. An additional benefit of ParalleX is fine-grained control of power usage, enabling reductions in power consumption.

²⁰⁹ http://en.wikipedia.org/wiki/Dataflow_architecture

²¹⁰ <http://en.wikipedia.org/wiki/J%E2%80%93Machine>

2.6.1 ParalleX—a new execution model for future architectures

ParalleX is a new parallel execution model that offers an alternative to the conventional computation models, such as message passing. ParalleX distinguishes itself by:

- Split-phase transaction model
- Message-driven
- Distributed shared memory (not cache coherent)
- Multi-threaded
- Futures synchronization
- *Local Control Objects (LCOs)*
- Synchronization for anonymous producer-consumer scenarios
- Percolation (pre-staging of task data)

The ParalleX model is intrinsically latency hiding, delivering an abundance of variable-grained parallelism within a hierarchical namespace environment. The goal of this innovative strategy is to enable future systems delivering very high efficiency, increased scalability and ease of programming. ParalleX can contribute to significant improvements in the design of all levels of computing systems and their usage from application algorithms and their programming languages to system architecture and hardware design together with their supporting compilers and operating system software.

2.6.2 What is HPX?

High Performance ParalleX (*HPX*) is the first runtime system implementation of the ParalleX execution model. The *HPX* runtime software package is a modular, feature-complete, and performance-oriented representation of the ParalleX execution model targeted at conventional parallel computing architectures, such as SMP nodes and commodity clusters. It is academically developed and freely available under an open source license. We provide *HPX* to the community for experimentation and application to achieve high efficiency and scalability for dynamic adaptive and irregular computational problems. *HPX* is a C++ library that supports a set of critical mechanisms for dynamic adaptive resource management and lightweight task scheduling within the context of a global address space. It is solidly based on many years of experience in writing highly parallel applications for HPC systems.

The two-decade success of the communicating sequential processes (CSP) execution model and its message passing interface (MPI) programming model have been seriously eroded by challenges of power, processor core complexity, multi-core sockets, and heterogeneous structures of GPUs. Both efficiency and scalability for some current (strong scaled) applications and future Exascale applications demand new techniques to expose new sources of algorithm parallelism and exploit unused resources through adaptive use of runtime information.

The ParalleX execution model replaces CSP to provide a new computing paradigm embodying the governing principles for organizing and conducting highly efficient scalable computations greatly exceeding the capabilities of today's problems. *HPX* is the first practical, reliable, and performance-oriented runtime system incorporating the principal concepts of the ParalleX model publicly provided in open source release form.

HPX is designed by the STE||AR²¹¹ Group (Systems Technology, Emergent Parallelism, and Algorithm Research) at Louisiana State University (LSU)²¹²'s Center for Computation and Technology (CCT)²¹³ to enable developers to exploit the full processing power of many-core systems with an unprecedented degree of parallelism. STE||AR²¹⁴ is a research group focusing on system software solutions and scientific application development for hybrid and many-core hardware architectures.

²¹¹ <https://stellar-group.org>

²¹² <https://www.lsu.edu>

²¹³ <https://www.cct.lsu.edu>

²¹⁴ <https://stellar-group.org>

For more information about the STE||AR²¹⁵ Group, see *People*.

2.6.3 What makes our systems slow?

Estimates say that we currently run our computers at well below 100% efficiency. The theoretical peak performance (usually measured in **FLOPS**²¹⁶—floating point operations per second) is much higher than any practical peak performance reached by any application. This is particularly true for highly parallel hardware. The more hardware parallelism we provide to an application, the better the application must scale in order to efficiently use all the resources of the machine. Roughly speaking, we distinguish two forms of scalability: strong scaling (see *Amdahl's Law*²¹⁷) and weak scaling (see *Gustafson's Law*²¹⁸). Strong scaling is defined as how the solution time varies with the number of processors for a fixed **total** problem size. It gives an estimate of how much faster we can solve a particular problem by throwing more resources at it. Weak scaling is defined as how the solution time varies with the number of processors for a fixed problem size **per processor**. In other words, it defines how much more data can we process by using more hardware resources.

In order to utilize as much hardware parallelism as possible an application must exhibit excellent strong and weak scaling characteristics, which requires a high percentage of work executed in parallel, i.e., using multiple threads of execution. Optimally, if you execute an application on a hardware resource with N processors it either runs N times faster or it can handle N times more data. Both cases imply 100% of the work is executed on all available processors in parallel. However, this is just a theoretical limit. Unfortunately, there are more things that limit scalability, mostly inherent to the hardware architectures and the programming models we use. We break these limitations into four fundamental factors that make our systems *SLOW*:

- **Starvation** occurs when there is insufficient concurrent work available to maintain high utilization of all resources.
- **Latencies** are imposed by the time-distance delay intrinsic to accessing remote resources and services.
- **Overhead** is work required for the management of parallel actions and resources on the critical execution path, which is not necessary in a sequential variant.
- **Waiting** for contention resolution is the delay due to the lack of availability of oversubscribed shared resources.

Each of those four factors manifests itself in multiple and different ways; each of the hardware architectures and programming models expose specific forms. However, the interesting part is that all of them are limiting the scalability of applications no matter what part of the hardware jungle we look at. Hand-helds, PCs, supercomputers, or the cloud, all suffer from the reign of the 4 horsemen: **Starvation**, **Latency**, **Overhead**, and **Contention**. This realization is very important as it allows us to derive the criteria for solutions to the scalability problem from first principles, and it allows us to focus our analysis on very concrete patterns and measurable metrics. Moreover, any derived results will be applicable to a wide variety of targets.

2.6.4 Technology demands new response

Today's computer systems are designed based on the initial ideas of *John von Neumann*²¹⁹, as published back in 1945, and later extended by the *Harvard architecture*²²⁰. These ideas form the foundation, the execution model, of computer systems we use currently. However, a new response is required in the light of the demands created by today's technology.

So, what are the overarching objectives for designing systems allowing for applications to scale as they should? In our opinion, the main objectives are:

- **Performance**: as previously mentioned, scalability and efficiency are the main criteria people are interested in.

²¹⁵ <https://stellar-group.org>

²¹⁶ <http://en.wikipedia.org/wiki/FLOPS>

²¹⁷ http://en.wikipedia.org/wiki/Amdahl%27s_law

²¹⁸ http://en.wikipedia.org/wiki/Gustafson%27s_law

²¹⁹ <http://qss.stanford.edu/~godfrey/vonNeumann/vnedvac.pdf>

²²⁰ http://en.wikipedia.org/wiki/Harvard_architecture

- Fault tolerance: the low expected mean time between failures ([MTBF²²¹](http://en.wikipedia.org/wiki/Mean_time_between_failures)) of future systems requires embracing faults, not trying to avoid them.
- Power: minimizing energy consumption is a must as it is one of the major cost factors today, and will continue to rise in the future.
- Generality: any system should be usable for a broad set of use cases.
- Programmability: for programmer this is a very important objective, ensuring long term platform stability and portability.

What needs to be done to meet those objectives, to make applications scale better on tomorrow's architectures? Well, the answer is almost obvious: we need to devise a new execution model—a set of governing principles for the holistic design of future systems—targeted at minimizing the effect of the outlined **SLOW** factors. Everything we create for future systems, every design decision we make, every criteria we apply, have to be validated against this single, uniform metric. This includes changes in the hardware architecture we prevalently use today, and it certainly involves new ways of writing software, starting from the operating system, runtime system, compilers, and at the application level. However, the key point is that all those layers have to be co-designed; they are interdependent and cannot be seen as separate facets. The systems we have today have been evolving for over 50 years now. All layers function in a certain way, relying on the other layers to do so. But we do not have the time to wait another 50 years for a new coherent system to evolve. The new paradigms are needed now—therefore, co-design is the key.

2.6.5 Governing principles applied while developing *HPX*

As it turns out, we do not have to start from scratch. Not everything has to be invented and designed anew. Many of the ideas needed to combat the 4 horsemen already exist, many for more than 30 years. All it takes is to gather them into a coherent approach. We'll highlight some of the derived principles we think to be crucial for defeating **SLOW**. Some of those are focused on high-performance computing, others are more general.

Focus on latency hiding instead of latency avoidance

It is impossible to design a system exposing zero latencies. In an effort to come as close as possible to this goal many optimizations are mainly targeted towards minimizing latencies. Examples for this can be seen everywhere, such as low latency network technologies like [InfiniBand²²²](http://en.wikipedia.org/wiki/InfiniBand), caching memory hierarchies in all modern processors, the constant optimization of existing [MPI²²³](https://en.wikipedia.org/wiki/Message_Passing_Interface) implementations to reduce related latencies, or the data transfer latencies intrinsic to the way we use [GPGPU²²⁴](http://en.wikipedia.org/wiki/GPGPU) today. It is important to note that existing latencies are often tightly related to some resource having to wait for the operation to be completed. At the same time it would be perfectly fine to do some other, unrelated work in the meantime, allowing the system to hide the latencies by filling the idle-time with useful work. Modern systems already employ similar techniques (pipelined instruction execution in the processor cores, asynchronous input/output operations, and many more). What we propose is to go beyond anything we know today and to make latency hiding an intrinsic concept of the operation of the whole system stack.

²²¹ http://en.wikipedia.org/wiki/Mean_time_between_failures

²²² <http://en.wikipedia.org/wiki/InfiniBand>

²²³ https://en.wikipedia.org/wiki/Message_Passing_Interface

²²⁴ <http://en.wikipedia.org/wiki/GPGPU>

Embrace fine-grained parallelism instead of heavyweight threads

If we plan to hide latencies even for very short operations, such as fetching the contents of a memory cell from main memory (if it is not already cached), we need to have very lightweight threads with extremely short context switching times, optimally executable within one cycle. Granted, for mainstream architectures, this is not possible today (even if we already have special machines supporting this mode of operation, such as the [Cray XMT](#)²²⁵). For conventional systems, however, the smaller the overhead of a context switch and the finer the granularity of the threading system, the better will be the overall system utilization and its efficiency. For today's architectures we already see a flurry of libraries providing exactly this type of functionality: non-pre-emptive, task-queue based parallelization solutions, such as [Intel Threading Building Blocks \(TBB\)](#)²²⁶, [Microsoft Parallel Patterns Library \(PPL\)](#)²²⁷, [Cilk++](#)²²⁸, and many others. The possibility to suspend a current task if some preconditions for its execution are not met (such as waiting for I/O or the result of a different task), seamlessly switching to any other task which can continue, and to reschedule the initial task after the required result has been calculated, which makes the implementation of latency hiding almost trivial.

Rediscover constraint-based synchronization to replace global barriers

The code we write today is riddled with implicit (and explicit) global barriers. By “global barriers,” we mean the synchronization of the control flow between several (very often all) threads (when using [OpenMP](#)²²⁹) or processes ([MPI](#)²³⁰). For instance, an implicit global barrier is inserted after each loop parallelized using [OpenMP](#)²³¹ as the system synchronizes the threads used to execute the different iterations in parallel. In [MPI](#)²³² each of the communication steps imposes an explicit barrier onto the execution flow as (often all) nodes have to be synchronized. Each of those barriers is like the eye of a needle the overall execution is forced to be squeezed through. Even minimal fluctuations in the execution times of the parallel threads (jobs) causes them to wait. Additionally, it is often only one of the executing threads that performs the actual reduce operation, which further impedes parallelism. A closer analysis of a couple of key algorithms used in science applications reveals that these global barriers are not always necessary. In many cases it is sufficient to synchronize a small subset of the threads. Any operation should proceed whenever the preconditions for its execution are met, and only those. Usually there is no need to wait for iterations of a loop to finish before you can continue calculating other things; all you need is to complete the iterations that produce the required results for the next operation. Good bye global barriers, hello constraint based synchronization! People have been trying to build this type of computing (and even computers) since the 1970s. The theory behind what they did is based on ideas around static and dynamic dataflow. There are certain attempts today to get back to those ideas and to incorporate them with modern architectures. For instance, a lot of work is being done in the area of constructing dataflow-oriented execution trees. Our results show that employing dataflow techniques in combination with the other ideas, as outlined herein, considerably improves scalability for many problems.

²²⁵ http://en.wikipedia.org/wiki/Cray_XMT

²²⁶ <https://www.threadingbuildingblocks.org/>

²²⁷ <https://msdn.microsoft.com/en-us/library/dd492418.aspx>

²²⁸ <https://software.intel.com/en-us/articles/intel-cilk-plus/>

²²⁹ <https://openmp.org/wp/>

²³⁰ https://en.wikipedia.org/wiki/Message_Passing_Interface

²³¹ <https://openmp.org/wp/>

²³² https://en.wikipedia.org/wiki/Message_Passing_Interface

Adaptive locality control instead of static data distribution

While this principle seems to be a given for single desktop or laptop computers (the operating system is your friend), it is everything but ubiquitous on modern supercomputers, which are usually built from a large number of separate nodes (i.e., Beowulf clusters), tightly interconnected by a high-bandwidth, low-latency network. Today's prevalent programming model for those is MPI, which does not directly help with proper data distribution, leaving it to the programmer to decompose the data to all of the nodes the application is running on. There are a couple of specialized languages and programming environments based on PGAS²³³ (Partitioned Global Address Space) designed to overcome this limitation, such as Chapel²³⁴, X10²³⁵, UPC²³⁶, or Fortress²³⁷. However, all systems based on PGAS rely on static data distribution. This works fine as long as this static data distribution does not result in heterogeneous workload distributions or other resource utilization imbalances. In a distributed system these imbalances can be mitigated by migrating part of the application data to different localities (nodes). The only framework supporting (limited) migration today is Charm++²³⁸. The first attempts towards solving related problem go back decades as well, a good example is the Linda coordination language²³⁹. Nevertheless, none of the other mentioned systems support data migration today, which forces the users to either rely on static data distribution and live with the related performance hits or to implement everything themselves, which is very tedious and difficult. We believe that the only viable way to flexibly support dynamic and adaptive *locality* control is to provide a global, uniform address space to the applications, even on distributed systems.

Prefer moving work to the data over moving data to the work

For the best performance it seems obvious to minimize the amount of bytes transferred from one part of the system to another. This is true on all levels. At the lowest level we try to take advantage of processor memory caches, thus, minimizing memory latencies. Similarly, we try to amortize the data transfer time to and from GPGPUs²⁴⁰ as much as possible. At high levels we try to minimize data transfer between different nodes of a cluster or between different virtual machines on the cloud. Our experience (well, it's almost common wisdom) shows that the amount of bytes necessary to encode a certain operation is very often much smaller than the amount of bytes encoding the data the operation is performed upon. Nevertheless, we still often transfer the data to a particular place where we execute the operation just to bring the data back to where it came from afterwards. As an example let's look at the way we usually write our applications for clusters using MPI. This programming model is all about data transfer between nodes. MPI is the prevalent programming model for clusters, and it is fairly straightforward to understand and to use. Therefore, we often write applications in a way that accommodates this model, centered around data transfer. These applications usually work well for smaller problem sizes and for regular data structures. The larger the amount of data we have to churn and the more irregular the problem domain becomes, the worse the overall machine utilization and the (strong) scaling characteristics become. While it is not impossible to implement more dynamic, data driven, and asynchronous applications using MPI, it is somewhat difficult to do so. At the same time, if we look at applications that prefer to execute the code close to the *locality* where the data was placed, i.e., utilizing active messages (for instance based on Charm++²⁴¹), we see better asynchrony, simpler application codes, and improved scaling.

²³³ <https://www.pgas.org/>

²³⁴ <https://chapel.cray.com/>

²³⁵ <https://x10-lang.org/>

²³⁶ <https://upc.lbl.gov/>

²³⁷ <https://labs.oracle.com/projects/plrg/Publications/index.html>

²³⁸ <https://charm.cs.uiuc.edu/>

²³⁹ [http://en.wikipedia.org/wiki/Linda_\(coordination_language\)](http://en.wikipedia.org/wiki/Linda_(coordination_language))

²⁴⁰ <http://en.wikipedia.org/wiki/GPGPU>

²⁴¹ <https://charm.cs.uiuc.edu/>

Favor message driven computation over message passing

Today's prevalently used programming model on parallel (multi-node) systems is MPI. It is based on message passing, as the name implies, which means that the receiver has to be aware of a message about to come in. Both codes, the sender and the receiver, have to synchronize in order to perform the communication step. Even the newer, asynchronous interfaces require explicitly coding the algorithms around the required communication scheme. As a result, everything but the most trivial MPI applications spends a considerable amount of time waiting for incoming messages, thus, causing starvation and latencies to impede full resource utilization. The more complex and more dynamic the data structures and algorithms become, the larger the adverse effects. The community discovered message-driven and data-driven methods of implementing algorithms a long time ago, and systems such as Charm++²⁴² have already integrated active messages demonstrating the validity of the concept. Message-driven computation allows for sending messages without requiring the receiver to actively wait for them. Any incoming message is handled asynchronously and triggers the encoded action by passing along arguments and—possibly—continuations. HPX combines this scheme with work-queue based scheduling as described above, which allows the system to almost completely overlap any communication with useful work, thereby minimizing latencies.

2.7 Additional material

- 2-day workshop held at CSCS in 2016
 - Recorded lectures²⁴³
 - Slides²⁴⁴
- Tutorials repository²⁴⁵
- C++ Lectures <https://www.youtube.com/playlist?list=PL7vEgTL3FalY2eBxudIwsfz8OKvE9sd_z>
- Parallel C++ for Scientific Applications Lectures <<https://www.youtube.com/watch?v=RdmXiilArM&list=PL7vEgTL3Falab59uJ>>
- STE||AR Group blog posts²⁴⁶
- Basic HPX recipes
 - Exporting a free function from a shared library which lives in a namespace, to use as Action²⁴⁷
 - Turning a struct or class into a component and use it's methods²⁴⁸
 - Creating and referencing components in hpx²⁴⁹

²⁴² <https://charm.cs.uiuc.edu/>

²⁴³ <https://www.youtube.com/playlist?list=PL1tk5lGm7zvSXfS-sqOOmIJ0lFNjKze18>

²⁴⁴ <https://github.com/STELLAR-GROUP/tutorials/tree/master/cscs2016>

²⁴⁵ <https://github.com/STELLAR-GROUP/tutorials>

²⁴⁶ <http://stellar-group.org/blog/>

²⁴⁷ <https://gitlab.com/-/snippets/1821389>

²⁴⁸ <https://gitlab.com/-/snippets/1822983>

²⁴⁹ <https://gitlab.com/-/snippets/1828131>

2.8 Overview

HPX is organized into different sub-libraries and those in turn into modules. The libraries and modules are independent, with clear dependencies and no cycles. As an end-user, the use of these libraries is completely transparent. If you use e.g. `add_hpx_executable` to create a target in your project you will automatically get all modules as dependencies. See below for a list of the available libraries and modules. Currently these are nothing more than an internal grouping and do not affect usage. They cannot be consumed individually at the moment.

Note: There is a dependency report that displays useful information about the structure of the code. It is available for each commit at [HPX Dependency report](#).

2.8.1 Core modules

affinity

The affinity module contains helper functionality for mapping worker threads to hardware resources.

See the API reference of the module for more details.

algorithms

The algorithms module exposes the full set of algorithms defined by the C++ standard. There is also partial support for C++ ranges.

See the *API reference* of the module for more details.

allocator_support

This module provides utilities for allocators. It contains `hpx::util::internal_allocator` which directly forwards allocation calls to `jemalloc`. This utility is mainly useful on Windows.

See the API reference of the module for more details.

asio

The asio module is a thin wrapper around the [Boost.Asio](#)²⁵⁰ library, providing a few additional helper functions.

See the *API reference* of the module for more details.

²⁵⁰ https://www.boost.org/doc/libs/release/doc/html/boost_asio.html

assertion

The assertion library implements the macros `HPX_ASSERT` and `HPX_ASSERT_MSG`. Those two macros can be used to implement assertions which are turned off during a release build.

By default, the location and function where the assert has been called from are displayed when the assertion fires. This behavior can be modified by using `hpx::assertion::set_assertion_handler`. When HPX initializes, it uses this function to specify a more elaborate assertion handler. If your application needs to customize this, it needs to do so before calling `hpx::init`, `hpx_main` or using the C-main wrappers.

See the *API reference* of the module for more details.

async_base

The `async_base` module defines the basic functionality for spawning tasks on thread pools. This module does not implement any functionality on its own, but is extended by `async_local` and `async_distributed` with implementations for the local and distributed cases.

See the *API reference* of this module for more details.

async_combinators

This module contains combinators for futures. The `when_*` functions allow you to turn multiple futures into a single future which is ready when all, any, some, or each of the given futures are ready. The `wait_*` combinators are equivalent to the `when_*` functions except that they do not return a future. Those wait for all futures to become ready before returning to the user. Note that the `wait_*` functions will rethrow one of the exceptions from exceptional futures. The `wait_*_nothrow` combinators are equivalent to the `wait_*` functions except that they do not throw if one of the futures has become exceptional.

The `split_future` combinator takes a single future of a container (e.g. `tuple`) and turns it into a container of futures.

See `lcos_local`, `synchronization`, and `async_distributed` for other synchronization facilities.

See the *API reference* of this module for more details.

async_cuda

This library adds a simple API that enables the user to retrieve a future from a [CUDA](https://www.nvidia.com/object/cuda_home_new.html)²⁵¹ stream. Typically, a user may launch one or more kernels and then get a future from the stream that will become ready when those kernels have completed. It is important to note that multiple kernels may be launched without fetching a future, and multiple futures may be obtained from the helper. Please refer to the unit tests and examples for further examples.

See the *API reference* of this module for more details.

²⁵¹ https://www.nvidia.com/object/cuda_home_new.html

async_local

This module extends *async_base* to provide local implementations of *hpx::async*, *hpx::post*, *hpx::sync*, and *hpx::dataflow*. The *async_distributed* module extends the functionality in this module to work with *actions*.

See the API reference of this module for more details.

async_mpi

The MPI library is intended to simplify the process of integrating [MPI²⁵²](#) based codes with the *HPX* runtime. Any MPI function that is asynchronous and uses an *MPI_Request* may be converted into an *hpx::future*. The syntax is designed to allow a simple replacement of the MPI call with a futurized async version that accepts an executor instead of a communicator, and returns a future instead of assigning a request. Typically, an MPI call of the form

```
int MPI_Isend(buf, count, datatype, rank, tag, comm, request);
```

becomes

```
hpx::future<int> f = hpx::async(executor, MPI_Isend, buf, count, datatype, rank, tag);
```

When the MPI operation is complete, the future will become ready. This allows communication to be integrated cleanly with the rest of *HPX*, in particular the continuation style of programming may be used to build up more complex code. Consider the following example, that chains user processing, sends and receives using continuations...

```
// create an executor for MPI dispatch
hpx::mpi::experimental::executor exec(MPI_COMM_WORLD);

// post an asynchronous receive using MPI_Irecv
hpx::future<int> f_recv = hpx::async(
    exec, MPI_Irecv, &data, rank, MPI_INT, rank_from, i);

// attach a continuation to run when the recv completes,
f_recv.then([=, &tokens, &counter](auto&&)
{
    // call an application specific function
    msg_recv(rank, size, rank_to, rank_from, tokens[i], i);

    // send a new message
    hpx::future<int> f_send = hpx::async(
        exec, MPI_Isend, &tokens[i], 1, MPI_INT, rank_to, i);

    // when that send completes
    f_send.then([=, &tokens, &counter](auto&&)
    {
        // call an application specific function
        msg_send(rank, size, rank_to, rank_from, tokens[i], i);
    });
});
```

The example above makes use of *MPI_Isend* and *MPI_Irecv*, but *any* MPI function that uses requests may be futurized in this manner. The following is a (non exhaustive) list of MPI functions that *should* be supported, though not all have been tested at the time of writing (please report any problems to the issue tracker).

²⁵² https://en.wikipedia.org/wiki/Message_Passing_Interface

```

int MPI_Isend(...);
int MPI_Ibsend(...);
int MPI_Issend(...);
int MPI_Irsend(...);
int MPI_Irecv(...);
int MPI_Imrecv(...);
int MPI_Ibarrier(...);
int MPI_Ibcast(...);
int MPI_Igather(...);
int MPI_Igatherv(...);
int MPI_Iscatter(...);
int MPI_Iscatterv(...);
int MPI_Iallgather(...);
int MPI_Iallgatherv(...);
int MPI_Ialltoall(...);
int MPI_Ialltoallv(...);
int MPI_Ialltoallw(...);
int MPI_Ireduce(...);
int MPI_Iallreduce(...);
int MPI_Ireduce_scatter(...);
int MPI_Ireduce_scatter_block(...);
int MPI_Iscan(...);
int MPI_Iexscan(...);
int MPI_Ineighbor_allgather(...);
int MPI_Ineighbor_allgatherv(...);
int MPI_Ineighbor_alltoall(...);
int MPI_Ineighbor_alltoallv(...);
int MPI_Ineighbor_alltoallw(...);

```

Note that the *HPX* mpi futurization wrapper should work with *any* asynchronous MPI call, as long as the function signature has the last two arguments `MPI_xxx(..., MPI_Comm comm, MPI_Request *request)` - internally these two parameters will be substituted by the executor and future data parameters that are supplied by template instantiations inside the `hpx::mpi` code.

See the API reference of this module for more details.

async_sycl

This module allows creating HPX futures using SYCL²⁵³ events, effectively integrating asynchronous SYCL kernels and memory transfers with HPX. Building on this integration, this module also contains a SYCL executor. This executor encapsulates a SYCL queue. When SYCL queue member functions are launched with this executor, the user can automatically obtain the HPX futures associated with them.

The creation of the HPX futures using SYCL events is based on the same event polling mechanism that the CUDA HPX integration uses. Each registered event gets an associated callback and gets inserted into a callback vector to be polled by the scheduler in between tasks. Once the polling reveals the event is complete, the callback will be called, which in turn sets the future to ready (see `sycl_event_callback.cpp`). There are multiple adaptations for HipSYCL for this: To keep the runtime alive (avoiding the repeated on-the-fly creation of the runtime during the polling), we keep a default queue. Furthermore, we flush the internal SYCL DAG to ensure that the launched SYCL function is actually being executed.

The SYCL executor offers the usual `post` and `async_execute` functions. Additionally, it contains two `get_future` functions. One expects a pre-existing SYCL event to return a future, the other one does not but will launch an empty SYCL kernel instead, to obtain an event (causing higher overhead for the sake of being more convenient). The `post` and

²⁵³ <https://en.wikipedia.org/wiki/SYCL>

async_execute implementations here are actually different for HipSYCL and OneAPI, since the sycl::queue in OneAPI uses a different interface (using a code_location parameter) which requires some adaptations here.

To make this module compile, we use the -fno-sycl and -fsycl compiler parameters for the OneAPI use-case (requiring HPX to be compiled with dpcpp). For HipSYCL we use its cmake integration instead (requiring HPX to be compiled with clang++ and including HipSYCL as a library).

To build with OneAPI, use the CMake Variable HPX_WITH_SYCL=ON. To build with HipSYCL, use HPX_WITH_SYCL=ON and HPX_WITH_HIPSYCL=ON (and make sure find_package will find HipSYCL).

Lastly, the module contains three tests/examples. All three implement a simple vector add example. The first one obtains a future using the free method get_future, the second one uses a single SYCL executor and the last one is using multiple executors called from multiple host threads.

To build the tests, use "make tests.unit.modules.async_sycl" To run the tests, use "ctest -R sycl".

NOTE: Theoretically, this module could work with other SYCL implementations, but was only tested using OneAPI and HipSYCL so far.

See the *API reference* of this module for more details.

batch_environments

This module allows for the detection of execution as batch jobs, a series of programs executed without user intervention. All data is preselected and will be executed according to preset parameters, such as date or completion of another task. Batch environments are especially useful for executing repetitive tasks.

HPX supports the creation of batch jobs through the Portable Batch System (PBS) and SLURM.

For more information on batch environments, see *Running on batch systems* and the API reference for the module.

cache

This module provides two cache data structures:

- `hpx::util::cache::local_cache`
- `hpx::util::cache::lru_cache`

See the *API reference* of the module for more details.

checkpoint_base

The checkpoint_base module contains lower level facilities that wrap simple check-pointing capabilities. This module does not implement special handling for futures or components, but simply serializes all arguments to or from a given container.

This module exposes the `hpx::util::save_checkpoint_data`, `hpx::util::restore_checkpoint_data`, and `hpx::util::prepare_checkpoint_data` APIs. These functions encapsulate the basic serialization functionalities necessary to save/restore a variadic list of arguments to/from a given data container.

See the *API reference* of this module for more details.

command_line_handling_local

TODO: High-level description of the module.

See the API reference of this module for more details.

compute_local

TODO: High-level description of the module.

See the *API reference* of this module for more details.

concepts

This module provides helpers for emulating concepts. It provides the following macros:

- `HPX_CONCEPT_REQUIRES`
- `HPX_HAS_MEMBER_XXX_TRAIT_DEF`
- `HPX_HAS_XXX_TRAIT_DEF`

See the API reference of the module for more details.

concurrency

This module provides concurrency primitives useful for multi-threaded programming such as:

- `hpx::barrier`
- `hpx::util::cache_line_data` and `hpx::util::cache_aligned_data`: wrappers for aligning and padding data to cache lines.
- various lockfree queue data structures

See the API reference of the module for more details.

config

The config module contains various configuration options, typically hidden behind macros that choose the correct implementation based on the compiler and other available options. It also contains platform independent macros to control inlining, export sets and more.

See the *API reference* of the module for more details.

config_registry

The config_registry module is a low level module providing helper functionality for registering configuration entries to a global registry from other modules. The `hpx::config_registry::add_module_config` function is used to add configuration options, and `hpx::config_registry::get_module_configs` can be used to retrieve configuration entries registered so far. `add_module_config_helper` can be used to register configuration entries through static global options.

See the API reference of this module for more details.

contracts

The contracts module provides C++ contracts support for HPX with intelligent fallback to assertions when native contracts are not available. This module implements a forward-compatible API that works across different C++ standards and compiler capabilities.

The module provides three primary macros: *HPX_PRE*, *HPX_POST*, and *HPX_CONTRACT_ASSERT*. These macros automatically adapt their behavior based on compiler capabilities:

- When C++26 native contracts are available (`__cpp_contracts` defined), they map to standard contract syntax
- When `HPX_WITH_CXX26_CONTRACTS=OFF`, preconditions and postconditions become no-ops while contract assertions remain available as enhanced assertions

Configuration

Enable contracts in CMake:

```
cmake -DHPX_WITH_CXX26_CONTRACTS=ON -DCMAKE_CXX_STANDARD=26
```

Enable contract-enhanced assertions (optional):

```
cmake -DHPX_WITH_CXX26_CONTRACTS=ON -DHPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON
```

Contract assertions work even when contracts are disabled:

```
cmake -DHPX_WITH_CXX26_CONTRACTS=OFF # HPX_CONTRACT_ASSERT still maps to HPX_ASSERT
```

Advanced Features

Contract-Enhanced Assertions

When `HPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON` is enabled, regular *HPX_ASSERT* calls are automatically upgraded to use contract assertions in C++26 mode:

```
void example_function(int value)
{
    HPX_ASSERT(value > 0); // Becomes contract_assert(value > 0) in C++26 mode
    // ... rest of function
}
```

Warning: Enhanced assertions only provide benefits when native C++26 contracts are supported by the compiler. Without native contract support, `HPX_ASSERT` -> `HPX_CONTRACT_ASSERT` -> `HPX_ASSERT` (no enhancement). CMake will issue a warning if you enable this option without native contract support.

This provides enhanced contract semantics throughout your existing codebase without requiring changes to assertion code. The transformation occurs in the contracts module (`contracts.hpp`) where the `HPX_ASSERT` macro is overridden to use `HPX_CONTRACT_ASSERT` when `HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON`:

- `HPX_WITH_CXX26_CONTRACTS=ON` - Contracts module is enabled
- `HPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON` - Assertion enhancement is enabled

The implementation works by redefining `HPX_ASSERT` in `contracts.hpp` to use `HPX_CONTRACT_ASSERT`, which automatically adapts to the current contract mode (native C++26 contracts or assertion fallback). This ensures all existing `HPX_ASSERT` calls throughout the HPX codebase automatically gain contract semantics when available.

Usage Examples

Preconditions and postconditions using declaration syntax (C++26):

```
int divide(int a, int b) HPX_PRE(b != 0)
{
    return a / b;
}

int factorial(int n) HPX_PRE(n >= 0) HPX_POST(r; r > 0)
{
    return n <= 1 ? 1 : n * factorial(n - 1);
}
```

Contract assertions (available in all modes):

```
void process_array(std::vector<int>& arr, size_t index)
{
    HPX_CONTRACT_ASSERT(index < arr.size());
    arr[index] *= 2;
}
```

Design Philosophy

HPX_CONTRACT_ASSERT: Enhanced assertion mechanism

Available even when `HPX_WITH_CONTRACTS=OFF` because it provides value as an enhanced assertion. Maps to `HPX_ASSERT` in all configurations.

HPX_PRE/HPX_POST: True contract syntax

Represent language-level contract semantics. When contracts are enabled but native C++26 contracts are not available, these become no-ops to maintain forward compatibility. When `HPX_WITH_CONTRACTS=OFF`, they are also no-ops. This prepares for C++26 migration where they will be attached to function declarations rather than used in function bodies.

Migration Strategy

The module is designed for smooth migration to C++26 native contracts:

Current (transition mode):

```
int func(int x)
{
    HPX_PRE(x > 0);    // No-op in fallback mode, active in native mode
    return x;
}
```

Target (C++26 native):

```
int func(int x) HPX_PRE(x > 0)
{
    return x;
}
```

Note: In fallback mode, HPX_PRE and HPX_POST become no-ops to maintain forward compatibility and avoid performance overhead. Use HPX_CONTRACT_ASSERT when you need runtime validation in all modes.

Testing

The module includes comprehensive testing with automatic compiler capability detection. Tests are organized into three categories:

- **Declaration tests:** Test C++26 native contract syntax when `__cpp_contracts` is available
- **Fallback tests:** Test assertion fallback behavior when contracts are not natively supported
- **Disabled tests:** Test no-op behavior when contracts are disabled

The test suite automatically detects compiler capabilities at configure time and builds only the appropriate tests for the current configuration.

See the *API reference* of the module for more details.

coroutines

The coroutines module provides coroutine (user-space thread) implementations for different platforms.

See the *API reference* of the module for more details.

datastructures

The datastructures module provides basic data structures (typically provided for compatibility with older C++ standards):

- `hpx::detail::small_vector`
- `hpx::util::basic_any`
- `hpx::util::member_pack`
- `hpx::optional`
- `hpx::tuple`
- `hpx::variant`

See the *API reference* of the module for more details.

debugging

This module provides helpers for demangling symbol names.

See the *API reference* of the module for more details.

errors

This module provides support for exceptions and error codes:

- `hpx::exception`
- `hpx::error_code`
- `hpx::error`

See the *API reference* of the module for more details.

execution

This library implements executors and execution policies for use with parallel algorithms and other facilities related to managing the execution of tasks.

See the *API reference* of the module for more details.

execution_base

The basic execution module is the main entry point to implement parallel and concurrent operations. It is modeled after P0443²⁵⁴ with some additions and implementations for the described concepts. Most notably, it provides an abstraction for execution resources, execution contexts and execution agents in such a way, that it provides customization points that those aforementioned concepts can be replaced and combined with ease.

For that purpose, three virtual base classes are provided to be able to provide implementations with different properties:

- **resource_base:** This is the abstraction for execution resources, that is for example CPU cores or an accelerator.
- **context_base:** An execution context uses execution resources and is able to spawn new execution agents, as new threads of executions on the available resources.
- **agent_base:** The execution agent represents the thread of execution, and can be used to yield, suspend, resume or abort a thread of execution.

executors

The executors module exposes executors and execution policies. Most importantly, it exposes the following classes and constants:

- `hpx::execution::sequenced_executor`
- `hpx::execution::parallel_executor`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`

²⁵⁴ <http://wg21.link/p0443>

- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`
- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`

See the *API reference* of this module for more details.

filesystem

This module provides a compatibility layer for the C++17 filesystem library. If the filesystem library is available this module will simply forward its contents into the `hpx::filesystem` namespace. If the library is not available it will fall back to `Boost.Filesystem` instead.

See the *API reference* of the module for more details.

format

The format module exposes the `format` and `format_to` functions for formatting strings.

See the *API reference* of the module for more details.

functional

This module provides function wrappers and helpers for managing functions and their arguments.

- `hpx::function`
- `hpx::function_ref`
- `hpx::move_only_function`
- `hpx::bind`
- `hpx::bind_back`
- `hpx::bind_front`
- `hpx::util::deferred_call`
- `hpx::invoke`
- `hpx::invoke_r`
- `hpx::invoke_fused`
- `hpx::invoke_fused_r`
- `hpx::mem_fn`
- `hpx::util::one_shot`
- `hpx::util::protect`
- `hpx::util::result_of`
- `hpx::placeholders::_1`

- `hpx::placeholders::_2`
- ...
- `hpx::placeholders::_9`

See the *API reference* of the module for more details.

futures

This module defines the `hpx::future` and `hpx::shared_future` classes corresponding to the C++ standard library classes `std::future`²⁵⁵ and `std::shared_future`²⁵⁶. Note that the specializations of `hpx::future::then` for executors and execution policies are defined in the *execution* module.

See the *API reference* of this module for more details.

hardware

The hardware module abstracts away hardware specific details of timestamps and CPU features.

See the *API reference* of the module for more details.

hashing

The hashing module provides two hashing implementations:

- `hpx::util::fibhash`
- `hpx::util::jenkins_hash`

See the *API reference* of the module for more details.

include_local

This module provides no functionality in itself. Instead it provides headers that group together other headers that often appear together. This module provides local-only headers.

See the *API reference* of this module for more details.

ini

TODO: High-level description of the module.

See the *API reference* of this module for more details.

²⁵⁵ <http://en.cppreference.com/w/cpp/thread/future>

²⁵⁶ http://en.cppreference.com/w/cpp/thread/shared_future

init_runtime_local

TODO: High-level description of the module.

See the API reference of this module for more details.

io_service

This module provides an abstraction over Boost.ASIO, combining multiple `asio::io_contexts` into a single pool. `hpx::util::io_service_pool` provides a simple pool of `asio::io_contexts` with an API similar to `asio::io_context`. `hpx::threads::detail::io_service_thread_pool` wraps `hpx::util::io_service_pool` into an interface derived from `hpx::threads::detail::thread_pool_base`.

See the *API reference* of this module for more details.

iterator_support

This module provides helpers for iterators. It provides `hpx::util::iterator_facade` and `hpx::util::iterator_adaptor` for creating new iterators, and the trait `hpx::util::is_iterator` along with more specific iterator traits.

See the API reference of the module for more details.

itt_notify

This module provides support for profiling with Intel VTune²⁵⁷.

See the API reference of this module for more details.

lci_base

This module provides helper functionality for detecting LCI environments.

See the API reference of this module for more details.

lcos_local

This module provides the following local *LCOs*:

- `hpx::lcos::local::and_gate`
- `hpx::lcos::local::channel`
- `hpx::lcos::local::one_element_channel`
- `hpx::lcos::local::receive_channel`
- `hpx::lcos::local::send_channel`
- `hpx::lcos::local::guard`
- `hpx::lcos::local::guard_set`
- `hpx::lcos::local::run_guarded`
- `hpx::lcos::local::conditional_trigger`

²⁵⁷ <https://software.intel.com/content/www/us/en/develop/tools/vtune-profiler.html>

- `hpx::packaged_task`
- `hpx::promise`
- `hpx::lcos::local::receive_buffer`
- `hpx::lcos::local::trigger`

See *lcos_distributed* for distributed LCOs. Basic synchronization primitives for use in *HPX* threads can be found in *synchronization*. *async_combinators* contains useful utility functions for combining futures.

See the *API reference* of this module for more details.

likwid

TODO: High-level description of the module.

See the *API reference* of this module for more details.

lock_registration

This module contains functionality for registering locks to detect when they are locked and unlocked on different threads.

See the *API reference* of this module for more details.

logging

This module provides useful macros for logging information.

See the *API reference* of the module for more details.

memory

Part of this module is a forked version of `boost::intrusive_ptr` from `Boost.SmartPtr`²⁵⁸.

See the *API reference* of the module for more details.

mpi_base

This module provides helper functionality for detecting `MPI`²⁵⁹ environments.

See the *API reference* of this module for more details.

²⁵⁸ https://www.boost.org/doc/libs/release/libs/smart_ptr/doc/html/smart_ptr.html

²⁵⁹ https://en.wikipedia.org/wiki/Message_Passing_Interface

pack_traversal

This module exposes the basic functionality for traversing various packs, both synchronously and asynchronously: `hpx::util::traverse_pack` and `hpx::util::traverse_pack_async`. It also exposes the higher level functionality of unwrapping nested futures: `hpx::util::unwrap` and its function object form `hpx::util::functional::unwrap`.

See the *API reference* of this module for more details.

plugin

This module provides base utilities for creating plugins.

See the *API reference* of the module for more details.

prefix

This module provides utilities for handling the prefix of an *HPX* application, i.e. the paths used for searching components and plugins.

See the *API reference* of this module for more details.

preprocessor

This library contains useful preprocessor macros:

- `HPX_PP_CAT`: Concatenate two tokens
- `HPX_PP_EXPAND`: Expands a preprocessor token
- `HPX_PP_NARGS`: Determines the number of arguments passed to a variadic macro
- `HPX_PP_STRINGIZE`: Turns a token into a string
- `HPX_PP_STRIP_PARENS`: Strips parenthesis from a token

See the *API reference* of the module for more details.

program_options

The module `program_options` is a direct fork of the `Boost.Program_options`²⁶⁰ library (Boost V1.70.0²⁶¹). In order to be included as an *HPX* module, the `Boost.Program_options` library has been moved to the namespace `hpx::program_options`. We have also replaced all Boost facilities the library depends on with either the equivalent facilities from the standard library or from *HPX*. As a result, the *HPX* `program_options` module is fully interface compatible with `Boost.Program_options` (sans the `hpx` namespace and the `#include <hpx/modules/program_options.hpp>` changes that need to be applied to all code relying on this library).

All credit goes to Vladimir Prus, the author of the excellent `Boost.Program_options` library. All bugs have been introduced by us.

See the *API reference* of the module for more details.

²⁶⁰ https://www.boost.org/doc/html/program_options.html

²⁶¹ https://www.boost.org/doc/libs/1_70_0/doc/html/program_options.html

properties

This module implements the `prefer` customization point for properties in terms of [P2220](https://wg21.link/p2220)²⁶². This differs from [P1393](http://wg21.link/p1393)²⁶³ in that it relies fully on `tag_invoke` overloads and fewer base customization points. Actual properties are defined in modules. All functionality is experimental and can be accessed through the `hpx::experimental` namespace.

See the API reference of this module for more details.

resiliency

In *HPX*, a program failure is a manifestation of a failing task. This module exposes several APIs that allow users to manage failing tasks in a convenient way by either replaying a failed task or by replicating a specific task.

Task replay is analogous to the Checkpoint/Restart mechanism found in conventional execution models. The key difference being localized fault detection. When the runtime detects an error, it replays the failing task as opposed to completely rolling back the entire program to the previous checkpoint.

Task replication is designed to provide reliability enhancements by replicating a set of tasks and evaluating their results to determine a consensus among them. This technique is most effective in situations where there are few tasks in the critical path of the DAG which leaves the system underutilized or where hardware or software failures may result in an incorrect result instead of an error. However, the drawback of this method is the additional computational cost incurred by repeating a task multiple times.

The following API functions are exposed:

- `hpx::resiliency::experimental::async_replay`: This version of task replay will catch user-defined exceptions and automatically reschedule the task *N* times before throwing an `hpx::resiliency::experimental::abort_replay_exception` if no task is able to complete execution without an exception.
- `hpx::resiliency::experimental::async_replay_validate`: This version of replay adds an argument to `async_replay` which receives a user-provided validation function to test the result of the task against. If the task's output is validated, the result is returned. If the output fails the check or an exception is thrown, the task is replayed until no errors are encountered or the number of specified retries has been exceeded.
- `hpx::resiliency::experimental::async_replicate`: This is the most basic implementation of the task replication. The API returns the first result that runs without detecting any errors.
- `hpx::resiliency::experimental::async_replicate_validate`: This API additionally takes a validation function which evaluates the return values produced by the threads. The first task to compute a valid result is returned.
- `hpx::resiliency::experimental::async_replicate_vote`: This API adds a vote function to the basic replicate function. Many hardware or software failures are silent errors which do not interrupt program flow. In order to detect errors of this kind, it is necessary to run the task several times and compare the values returned by every version of the task. In order to determine which return value is “correct”, the API allows the user to provide a custom consensus function to properly form a consensus. This voting function then returns the “correct” answer.
- `hpx::resiliency::experimental::async_replicate_vote_validate`: This combines the features of the previously discussed replicate set. Replicate vote validate allows a user to provide a validation function to filter results. Additionally, as described in replicate vote, the user can provide a “voting function” which returns the consensus formed by the voting logic.

²⁶² <https://wg21.link/p2220>

²⁶³ <http://wg21.link/p1393>

- `hpx::resiliency::experimental::dataflow_replay`: This version of dataflow replay will catch user-defined exceptions and automatically reschedules the task N times before throwing an `hpx::resiliency::experimental::abort_replay_exception` if no task is able to complete execution without an exception. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replay_validate`: This version of replay adds an argument to dataflow replay which receives a user-provided validation function to test the result of the task against. If the task's output is validated, the result is returned. If the output fails the check or an exception is thrown, the task is replayed until no errors are encountered or the number of specified retries have been exceeded. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate`: This is the most basic implementation of the task replication. The API returns the first result that runs without detecting any errors. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_validate`: This API additionally takes a validation function which evaluates the return values produced by the threads. The first task to compute a valid result is returned. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_vote`: This API adds a vote function to the basic replicate function. Many hardware or software failures are silent errors which do not interrupt program flow. In order to detect errors of this kind, it is necessary to run the task several times and compare the values returned by every version of the task. In order to determine which return value is "correct", the API allows the user to provide a custom consensus function to properly form a consensus. This voting function then returns the "correct" answer. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_vote_validate`: This combines the features of the previously discussed replicate set. Replicate vote validate allows a user to provide a validation function to filter results. Additionally, as described in replicate vote, the user can provide a "voting function" which returns the consensus formed by the voting logic. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.

See the *API reference* of the module for more details.

resource_partitioner

The `resource_partitioner` module defines `hpx::resource::partitioner`, the class used by the runtime and users to partition available hardware resources into thread pools. See *Using the resource partitioner* for more details on using the resource partitioner in applications.

See the API reference of this module for more details.

runtime_configuration

This module handles the configuration options required by the runtime.

See the *API reference* of this module for more details.

runtime_local

TODO: High-level description of the library.

See the *API reference* of this module for more details.

schedulers

This module provides schedulers used by thread pools in the *thread_pools* module. There are currently three main schedulers:

- `hpx::threads::policies::local_priority_queue_scheduler`
- `hpx::threads::policies::static_priority_queue_scheduler`
- `hpx::threads::policies::shared_priority_queue_scheduler`

Other schedulers are specializations or variations of the above schedulers. See the examples of the *resource_partitioner* module for examples of specifying a custom scheduler for a thread pool.

See the *API reference* of this module for more details.

serialization

This module provides serialization primitives and support for all built-in types as well as all C++ Standard Library collection and utility types. This list is extended by *HPX* vocabulary types with proper support for global reference counting. *HPX*'s mode of serialization is derived from [Boost's serialization model](https://www.boost.org/doc/libs/1_72_0/libs/serialization/doc/index.html)²⁶⁴ and, as such, is mostly interface compatible with its Boost counterpart.

The purest form of serializing data is to copy the content of the payload bit by bit; however, this method is impractical for generic C++ types, which might be composed of more than just regular built-in types. Instead, *HPX*'s approach to serialization is derived from the Boost Serialization library, and is geared towards allowing the programmer of a given class explicit control and syntax of what to serialize. It is based on operator overloading of two special archive types that hold a buffer or stream to store the serialized data and is responsible for dispatching the serialization mechanism to the intrusive or non-intrusive version. The serialization process is recursive. Each member that needs to be serialized must be specified explicitly. The advantage of this approach is that the serialization code is written in C++ and leverages all necessary programming techniques. The generic, user-facing interface allows for effective application of the serialization process without obstructing the algorithms that need special code for packing and unpacking. It also allows for optimizations in the implementation of the archives.

See the *API reference* of the module for more details.

²⁶⁴ https://www.boost.org/doc/libs/1_72_0/libs/serialization/doc/index.html

static_reinit

This module provides a simple wrapper around static variables that can be reinitialized.

See the *API reference* of this module for more details.

string_util

This module contains string utilities inspired by the Boost String Algorithms Library.

See the *API reference* of this module for more details.

synchronization

This module provides synchronization primitives that should be used rather than the C++ standard ones in *HPX* threads:

- `hpx::barrier`
- `hpx::binary_semaphore`
- `hpx::call_once`
- `hpx::condition_variable`
- `hpx::condition_variable_any`
- `hpx::counting_semaphore`
- `hpx::lcos::local::event`
- `hpx::latch`
- `hpx::mutex`
- `hpx::no_mutex`
- `hpx::once_flag`
- `hpx::recursive_mutex`
- `hpx::shared_mutex`
- `hpx::sliding_semaphore`
- `hpx::spinlock` (*std::mutex* compatible spinlock)
- `hpx::spinlock_no_backoff` (*boost::mutex* compatible spinlock)
- `hpx::spinlock_pool`
- `hpx::stop_callback`
- `hpx::stop_source`
- `hpx::stop_token`
- `hpx::in_place_stop_token`
- `hpx::timed_mutex`
- `hpx::upgrade_to_unique_lock`
- `hpx::upgrade_lock`

See *lcos_local*, *async_combinators*, and *async_distributed* for higher level synchronization facilities.

See the *API reference* of this module for more details.

tag_invoke

TODO: High-level description of the module.

See the *API reference* of this module for more details.

testing

The testing module contains useful macros for testing. The results of tests can be printed with `hpx::util::report_errors`. The following macros are provided:

- `HPX_TEST`
- `HPX_TEST_MSG`
- `HPX_TEST_EQ`
- `HPX_TEST_NEQ`
- `HPX_TEST_LT`
- `HPX_TEST_LTE`
- `HPX_TEST_RANGE`
- `HPX_TEST_EQ_MSG`
- `HPX_TEST_NEQ_MSG`
- `HPX_SANITY`
- `HPX_SANITY_MSG`
- `HPX_SANITY_EQ`
- `HPX_SANITY_NEQ`
- `HPX_SANITY_LT`
- `HPX_SANITY_LTE`
- `HPX_SANITY_RANGE`
- `HPX_SANITY_EQ_MSG`

See the API reference of the module for more details.

thread_pool_util

This module contains helper functions for asynchronously suspending and resuming thread pools and their worker threads.

See the *API reference* of this module for more details.

thread_pools

This module defines the thread pools and utilities used by the *HPX* runtime. The only thread pool implementation provided by this module is `hpx::threads::detail::scheduled_thread_pool`, which is derived from `hpx::threads::detail::thread_pool_base` defined in the *threading_base* module.

See the API reference of this module for more details.

thread_support

This module provides miscellaneous utilities for threading and concurrency.

See the *API reference* of the module for more details.

threading

This module provides the equivalents of `std::thread` and `std::jthread` for lightweight *HPX* threads:

- `hpx::thread`
- `hpx::jthread`

See the *API reference* of this module for more details.

threading_base

This module contains the base class definition required for threads. The base class `hpx::threads::thread_data` is inherited by two specializations for stackful and stackless threads: `hpx::threads::thread_data_stackful` and `hpx::threads::thread_data_stackless`. In addition, the module defines the base classes for schedulers and thread pools: `hpx::threads::policies::scheduler_base` and `hpx::threads::thread_pool_base`.

See the API reference of this module for more details.

thread_manager

This module defines the `hpx::threads::threadmanager` class. This is used by the runtime to manage the creation and destruction of thread pools. The *resource_partitioner* module handles the partitioning of resources into thread pools, but not the creation of thread pools.

See the API reference of this module for more details.

thrust

The thrust module integrates *HPX* parallel algorithms with NVIDIA Thrust, enabling GPU acceleration using familiar *HPX* algorithm syntax.

Execution Policies

- hpx::thrust::thrust_host_policy**
CPU execution using optimized parallel implementations
- hpx::thrust::thrust_device_policy**
Synchronous GPU execution
- hpx::thrust::thrust_task_policy**
Asynchronous GPU execution returning *HPX* futures

Policy Mappings

The *HPX* thrust policies map directly to Thrust execution policies:

```
// Policy mappings
hpx::thrust::thrust_host_policy    -> thrust::host
hpx::thrust::thrust_device_policy  -> thrust::device
hpx::thrust::thrust_task_policy    -> thrust::par_nosync
```

Usage

Synchronous Device Execution

```
#include <hpx/modules/thrust.hpp>
#include <thrust/device_vector.h>

hpx::thrust::thrust_device_policy device{};
thrust::device_vector<int> d_vec(1000, 0);

hpx::fill(device, d_vec.begin(), d_vec.end(), 42);
int sum = hpx::reduce(device, d_vec.begin(), d_vec.end(), 0);
```

Asynchronous Execution with Futures

```
#include <hpx/modules/async_cuda.hpp>
#include <hpx/modules/thrust.hpp>

int hpx_main() {
    // Required for async operations
    hpx::cuda::experimental::enable_user_polling polling_guard("default");

    hpx::thrust::thrust_task_policy task{};
    thrust::device_vector<int> d_vec(1000, 1);

    auto fill_future = hpx::fill(task, d_vec.begin(), d_vec.end(), 42);
    fill_future.get(); // Standard HPX future operations
}
```

Build Requirements

- CUDA Toolkit 12.4.0+
- *HPX* with `HPX_WITH_CUDA=ON`
- Enable with: `cmake -DHPX_WITH_CUDA=ON ...`

See Also

- *async_cuda* - CUDA integration
- *execution* - *HPX* execution policies

timed_execution

This module provides extensions to the executor interfaces defined in the *execution* module that allow timed submission of tasks on thread pools (at or after a specified time).

See the *API reference* of this module for more details.

timing

This module provides the timing utilities (clocks and timers).

See the *API reference* of the module for more details.

topology

This module provides the class `hpx::threads::topology` which represents the hardware resources available on a node. The class is a light wrapper around the [Portable Hardware Locality \(HWLOC\)](https://www.open-mpi.org/projects/hwloc/)²⁶⁵ library. The `hpx::threads::cpu_mask` is a small companion class that represents a set of resources on a node.

See the *API reference* of the module for more details.

tracy

This modules enables the integration of *HPX* applications with the [|tracy|](https://github.com/jacobpriebe/tracy) profiler.

type_support

This module provides helper facilities related to types.

See the *API reference* of the module for more details.

²⁶⁵ <https://www.open-mpi.org/projects/hwloc/>

util

The util module provides miscellaneous standalone utilities.

See the *API reference* of the module for more details.

version

This module macros and functions for accessing version information about *HPX* and its dependencies.

See the *API reference* of this module for more details.

2.8.2 Main HPX modules

actions

TODO: High-level description of the library.

See the *API reference* of this module for more details.

actions_base

TODO: High-level description of the library.

See the *API reference* of this module for more details.

agas

TODO: High-level description of the module.

See the *API reference* of this module for more details.

agas_base

This module holds the implementation of the four AGAS services: primary namespace, locality namespace, component namespace, and symbol namespace.

See the *API reference* of this module for more details.

async_colocated

TODO: High-level description of the module.

See the *API reference* of this module for more details.

async_distributed

This module contains functionality for asynchronously launching work on remote localities: `hpx::async`, `hpx::post`. This module extends the local-only functions in `libs_async_local`.

See the API reference of this module for more details.

checkpoint

A common need of users is to periodically backup an application. This practice provides resiliency and potential restart points in code. *HPX* utilizes the concept of a **checkpoint** to support this use case.

Found in `hpx/util/checkpoint.hpp`, checkpoints are defined as objects that hold a serialized version of an object or set of objects at a particular moment in time. This representation can be stored in memory for later use or it can be written to disk for storage and/or recovery at a later point. In order to create and fill this object with data, users must use a function called `save_checkpoint`. In code the function looks like this:

```
hpx::future<hpx::util::checkpoint> hpx::util::save_checkpoint(a, b, c, ...);
```

`save_checkpoint` takes arbitrary data containers, such as `int`, `double`, `float`, `vector`, and `future`, and serializes them into a newly created checkpoint object. This function returns a `future` to a `checkpoint` containing the data. Here's an example of a simple use case:

```
using hpx::util::checkpoint;
using hpx::util::save_checkpoint;

std::vector<int> vec{1,2,3,4,5};
hpx::future<checkpoint> save_checkpoint(vec);
```

Once the future is ready, the checkpoint object will contain the `vector` `vec` and its five elements.

`prepare_checkpoint` takes arbitrary data containers (same as for `save_checkpoint`), , such as `int`, `double`, `float`, `vector`, and `future`, and calculates the necessary buffer space for the checkpoint that would be created if `save_checkpoint` was called with the same arguments. This function returns a `future` to a `checkpoint` that is appropriately initialized. Here's an example of a simple use case:

```
using hpx::util::checkpoint;
using hpx::util::prepare_checkpoint;

std::vector<int> vec{1,2,3,4,5};
hpx::future<checkpoint> prepare_checkpoint(vec);
```

Once the future is ready, the checkpoint object will be initialized with an appropriately sized internal buffer.

It is also possible to modify the launch policy used by `save_checkpoint`. This is accomplished by passing a launch policy as the first argument. It is important to note that passing `hpx::launch::sync` will cause `save_checkpoint` to return a `checkpoint` instead of a `future` to a `checkpoint`. All other policies passed to `save_checkpoint` will return a `future` to a `checkpoint`.

Sometimes `checkpoint` s must be declared before they are used. `save_checkpoint` allows users to move pre-created `checkpoint` s into the function as long as they are the first container passing into the function (In the case where a launch policy is used, the `checkpoint` will immediately follow the launch policy). An example of these features can be found below:


```

char character = 'd';
int integer = 10;
float flt = 10.01f;
bool boolean = true;
std::string str = "I am a string of characters";
std::vector<char> vec(str.begin(), str.end());
checkpoint archive;

// Test 1
// test basic functionality
hpx::shared_future<checkpoint> f_archive = save_checkpoint(
    std::move(archive), character, integer, flt, boolean, str, vec);

```

Once users can create checkpoints they must now be able to restore the objects they contain into memory. This is accomplished by the function `restore_checkpoint`. This function takes a `checkpoint` and fills its data into the containers it is provided. It is important to remember that the containers must be ordered in the same way they were placed into the checkpoint. For clarity see the example below:

```

char character2;
int integer2;
float flt2;
bool boolean2;
std::string str2;
std::vector<char> vec2;

restore_checkpoint(data, character2, integer2, flt2, boolean2, str2, vec2);

```

The core utility of `checkpoint` is in its ability to make certain data persistent. Often, this means that the data needs to be stored in an object, such as a file, for later use. *HPX* has two solutions for these issues: stream operator overloads and access iterators.

HPX contains two stream overloads, `operator<<` and `operator>>`, to stream data out of and into `checkpoint`. Here is an example of the overloads in use below:

```

double a9 = 1.0, b9 = 1.1, c9 = 1.2;
std::ofstream test_file_9("test_file_9.txt");
hpx::future<checkpoint> f_9 = save_checkpoint(a9, b9, c9);
test_file_9 << f_9.get();
test_file_9.close();

double a9_1, b9_1, c9_1;
std::ifstream test_file_9_1("test_file_9.txt");
checkpoint archive9;
test_file_9_1 >> archive9;
restore_checkpoint(archive9, a9_1, b9_1, c9_1);

```

This is the primary way to move data into and out of a `checkpoint`. It is important to note, however, that users should be cautious when using a stream operator to load data and another function to remove it (or vice versa). Both `operator<<` and `operator>>` rely on a `.write()` and a `.read()` function respectively. In order to know how much data to read from the `std::istream`, the `operator<<` will write the size of the checkpoint before writing the checkpoint data. Correspondingly, the `operator>>` will read the size of the stored data before reading the data into a new instance of `checkpoint`. As long as the user employs the `operator<<` and `operator>>` to stream the data, this detail can be ignored.

Important: Be careful when mixing `operator<<` and `operator>>` with other facilities to read and write to a checkpoint. `operator<<` writes an extra variable, and `operator>>` reads this variable back separately. Used together the user will not encounter any issues and can safely ignore this detail.

Users may also move the data into and out of a checkpoint using the exposed `.begin()` and `.end()` iterators. An example of this use case is illustrated below.

```
std::ofstream test_file_7("checkpoint_test_file.txt");
std::vector<float> vec7{1.02f, 1.03f, 1.04f, 1.05f};
hpx::future<checkpoint> fut_7 = save_checkpoint(vec7);
checkpoint archive7 = fut_7.get();
std::copy(archive7.begin(),      // Write data to ofstream
          archive7.end(),        // ie. the file
          std::ostream_iterator<char>(test_file_7));
test_file_7.close();

std::vector<float> vec7_1;
std::vector<char> char_vec;
std::ifstream test_file_7_1("checkpoint_test_file.txt");
if (test_file_7_1)
{
    test_file_7_1.seekg(0, test_file_7_1.end);
    auto length = test_file_7_1.tellg();
    test_file_7_1.seekg(0, test_file_7_1.beg);
    char_vec.resize(length);
    test_file_7_1.read(char_vec.data(), length);
}
checkpoint archive7_1(std::move(char_vec));    // Write data to checkpoint
restore_checkpoint(archive7_1, vec7_1);
```

Checkpointing components

`save_checkpoint` and `restore_checkpoint` are also able to store components inside checkpoints. This can be done in one of two ways. First a client of the component can be passed to `save_checkpoint`. When the user wishes to resurrect the component she can pass a client instance to `restore_checkpoint`.

This technique is demonstrated below:

```
// Try to checkpoint and restore a component with a client
std::vector<int> vec3{10, 10, 10, 10, 10};

// Create a component instance through client constructor
data_client D(hpx::find_here(), std::move(vec3));
hpx::future<checkpoint> f3 = save_checkpoint(D);

// Create a new client
data_client E;

// Restore server inside client instance
restore_checkpoint(f3.get(), E);
```

The second way a user can save a component is by passing a `shared_ptr` to the component to `save_checkpoint`.

This component can be resurrected by creating a new instance of the component type and passing a `shared_ptr` to the new instance to `restore_checkpoint`.

This technique is demonstrated below:

```
// test checkpoint a component using a shared_ptr
std::vector<int> vec{1, 2, 3, 4, 5};
data_client A(hpx::find_here(), std::move(vec));

// Checkpoint Server
hpx::id_type old_id = A.get_id();

hpx::future<std::shared_ptr<data_server>> f_a_ptr =
    hpx::get_ptr<data_server>(A.get_id());
std::shared_ptr<data_server> a_ptr = f_a_ptr.get();
hpx::future<checkpoint> f = save_checkpoint(a_ptr);
auto&& data = f.get();

// test prepare_checkpoint API
checkpoint c = prepare_checkpoint(hpx::launch::sync, a_ptr);
HPX_TEST(c.size() == data.size());

// Restore Server
// Create a new server instance
std::shared_ptr<data_server> b_server;
restore_checkpoint(data, b_server);
```

collectives

The `collectives` module exposes a set of distributed collective operations. Those can be used to exchange data between participating sites in a coordinated way. At this point the module exposes the following collective primitives:

- `hpx::collectives::all_gather`: receives a set of values from all participating sites.
- `hpx::collectives::all_reduce`: performs a reduction on data from each participating site to each participating site.
- `hpx::collectives::all_to_all`: each participating site provides its element of the data to collect while all participating sites receive the data from every other site.
- `hpx::collectives::broadcast_to` and `hpx::collectives::broadcast_from`: performs a broadcast operation from a root site to all participating sites.
- **cpp:func:hpx::collectives::exclusive_scan**
performs an exclusive scan operation
on a set of values received from all call sites operating on the given base name.
- `hpx::collectives::gather_here` and `hpx::collectives::gather_there`: gathers values from all participating sites.
- **cpp:func:hpx::collectives::inclusive_scan**
performs an inclusive scan operation
on a set of values received from all call sites operating on the given base name.
- `hpx::collectives::reduce_here` and `hpx::collectives::reduce_there`: performs a reduction on data from each participating site to a root site.

- `hpx::collectives::scatter_to` and `hpx::collectives::scatter_from`: receives an element of a set of values operating on the given base name.
- `hpx::lcos::broadcast`: performs a given action on all given global identifiers.
- `hpx::distributed::barrier`: distributed barrier.
- `hpx::lcos::fold`: performs a fold with a given action on all given global identifiers.
- `hpx::distributed::latch`: distributed latch.
- `hpx::lcos::reduce`: performs a reduction on data from each given global identifiers.
- `hpx::lcos::spmd_block`: performs the same operation on a local image while providing handles to the other images.

See the *API reference* of the module for more details.

command_line_handling

The `command_line_handling` module defines and handles the command-line options required by the *HPX* runtime, combining them with configuration options defined by the *runtime_configuration* module. The actual parsing of command line options is handled by the *program_options* module.

See the *API reference* of the module for more details.

components

TODO: High-level description of the module.

See the *API reference* of this module for more details.

components_base

TODO: High-level description of the library.

See the *API reference* of this module for more details.

compute

The `compute` module provides utilities for handling task and memory affinity on host systems.

See the *API reference* of the module for more details.

distribution_policies

TODO: High-level description of the module.

See the *API reference* of this module for more details.

executors_distributed

This module provides the executor `hpx::parallel::execution::distribution_policy_executor`. It allows one to create work that is implicitly distributed over multiple localities.

See the *API reference* of this module for more details.

include

This module provides no functionality in itself. Instead it provides headers that group together other headers that often appear together.

See the *API reference* of this module for more details.

init_runtime

TODO: High-level description of the library.

See the *API reference* of this module for more details.

lcos_distributed

This module contains distributed *LCOs*. Currently the only LCO provided is `cpp:class::hpx::lcos::channel`, a construct for sending values from one *locality* to another. See `libs_lcos_local` for local LCOs.

See the *API reference* of this module for more details.

naming

TODO: High-level description of the module.

See the *API reference* of this module for more details.

naming_base

This module provides a forward declaration of *address_type*, *component_type* and *invalid_locality_id*.

See the *API reference* of this module for more details.

parcelport_lci

TODO: High-level description of the module.

See the *API reference* of this module for more details.

parcelport_mpi

TODO: High-level description of the module.

See the API reference of this module for more details.

parcelport_tcp

TODO: High-level description of the module.

See the API reference of this module for more details.

parcelset

TODO: High-level description of the module.

See the *API reference* of this module for more details.

parcelset_base

TODO: High-level description of the module.

See the *API reference* of this module for more details.

performance_counters

This module provides the basic functionality required for defining performance counters. See *Performance counters* for more information about performance counters.

See the *API reference* of this module for more details.

plugin_factories

TODO: High-level description of the module.

See the *API reference* of this module for more details.

resiliency_distributed

Software resiliency features of *HPX* were introduced in the *resiliency module*. This module extends the APIs to run on distributed-memory systems allowing the user to invoke the failing task on other localities at runtime. This is useful in cases where a node is identified to fail more often (e.g., for certain ALU computes) as the task can now be replayed or replicated among different localities. The API exposed allows for an easy integration with the local only resiliency APIs as well.

Distributed software resilience APIs have a similar function signature and lives under the same namespace of *hpx::resiliency::experimental*. The difference arises in the formal parameters where distributed APIs takes the localities as the first argument, and an action as opposed to a function or a function object. The localities signify the order in which the API will either schedule (in case of Task Replay) tasks in a round robin fashion or replicate the tasks onto the list of localities.

The list of APIs exposed by distributed resiliency modules is the same as those defined in *local resiliency module*.

See the API reference of this module for more details.

runtime_components

TODO: High-level description of the module.

See the *API reference* of this module for more details.

runtime_distributed

TODO: High-level description of the module.

See the *API reference* of this module for more details.

segmented_algorithms

Segmented algorithms extend the usual parallel *algorithms* by providing overloads that work with distributed containers, such as partitioned vectors.

See the *API reference* of the module for more details.

statistics

This module provide some statistics utilities like rolling min/max and histogram.

See the *API reference* of the module for more details.

2.9 API reference

HPX follows a versioning scheme with three numbers: `major.minor.patch`. We guarantee no breaking changes in the API for patch releases. Minor releases may remove or break existing APIs, but only after a deprecation period of at least two minor releases. In rare cases do we outright remove old and unused functionality without a deprecation period.

We do not provide any ABI compatibility guarantees between any versions, debug and release builds, and builds with different C++ standards.

The public API of *HPX* is presented below. Clicking on a name brings you to the full documentation for the class or function. Including the header specified in a heading brings in the features listed under that heading.

Note: Names listed here are guaranteed stable with respect to semantic versioning. However, at the moment the list is incomplete and certain unlisted features are intended to be in the public API. While we work on completing the list, if you're unsure about whether a particular unlisted name is part of the public API you can get into contact with us or open an issue and we'll clarify the situation.

2.9.1 Public API

Our API is semantically conforming; hence, the reader is highly encouraged to refer to the corresponding facility in the C++ Standard²⁶⁶ if needed. All names below are also available in the top-level `hpx` namespace unless otherwise noted. The names in `hpx` should be preferred. The names in sub-namespaces will eventually be removed.

`hpx/algorithm.hpp`

The header `hpx/algorithm.hpp`²⁶⁷ corresponds to the C++ standard library header `algorithm`²⁶⁸. See *Using parallel algorithms* for more information about the parallel algorithms.

Classes

Table 2.125: Classes of header `hpx/algorithm.hpp`

Class	C++ standard
<code>hpx::experimental::reduction</code>	N4808 ²⁶⁹
<code>hpx::experimental::induction</code>	N4808 ²⁷⁰

Functions

Table 2.126: *hpx* functions of header `hpx/algorithm.hpp`

<i>hpx</i> function	C++ standard
<code>hpx::adjacent_find</code>	<code>std::adjacent_find</code> ²⁷¹
<code>hpx::all_of</code>	<code>std::all_of</code> ²⁷²
<code>hpx::any_of</code>	<code>std::any_of</code> ²⁷³
<code>hpx::copy</code>	<code>std::copy</code> ²⁷⁴
<code>hpx::copy_if</code>	<code>std::copy_if</code> ²⁷⁵
<code>hpx::copy_n</code>	<code>std::copy_n</code> ²⁷⁶
<code>hpx::count</code>	<code>std::count</code> ²⁷⁷
<code>hpx::count_if</code>	<code>std::count_if</code> ²⁷⁸
<code>hpx::ends_with</code>	<code>std::ends_with</code> ²⁷⁹
<code>hpx::equal</code>	<code>std::equal</code> ²⁸⁰
<code>hpx::fill</code>	<code>std::fill</code> ²⁸¹
<code>hpx::fill_n</code>	<code>std::fill_n</code> ²⁸²
<code>hpx::find</code>	<code>std::find</code> ²⁸³
<code>hpx::find_end</code>	<code>std::find_end</code> ²⁸⁴
<code>hpx::find_first_of</code>	<code>std::find_first_of</code> ²⁸⁵
<code>hpx::find_if</code>	<code>std::find_if</code> ²⁸⁶
<code>hpx::find_if_not</code>	<code>std::find_if_not</code> ²⁸⁷
<code>hpx::for_each</code>	<code>std::for_each</code> ²⁸⁸
<code>hpx::for_each_n</code>	<code>std::for_each_n</code> ²⁸⁹
<code>hpx::generate</code>	<code>std::generate</code> ²⁹⁰

continues on next page

²⁶⁶ <https://en.cppreference.com/w/cpp/header>

²⁶⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

²⁶⁸ <http://en.cppreference.com/w/cpp/header/algorithm>

²⁶⁹ <http://wg21.link/n4808>

²⁷⁰ <http://wg21.link/n4808>

Table 2.126 – continued from previous page

<i>hpx</i> function	C++ standard
<i>hpx::generate_n</i>	std::generate_n ²⁹¹
<i>hpx::includes</i>	std::includes ²⁹²
<i>hpx::inplace_merge</i>	std::inplace_merge ²⁹³
<i>hpx::is_heap</i>	std::is_heap ²⁹⁴
<i>hpx::is_heap_until</i>	std::is_heap_until ²⁹⁵
<i>hpx::is_partitioned</i>	std::is_partitioned ²⁹⁶
<i>hpx::is_sorted</i>	std::is_sorted ²⁹⁷
<i>hpx::is_sorted_until</i>	std::is_sorted_until ²⁹⁸
<i>hpx::lexicographical_compare</i>	std::lexicographical_compare ²⁹⁹
<i>hpx::make_heap</i>	std::make_heap ³⁰⁰
<i>hpx::max_element</i>	std::max_element ³⁰¹
<i>hpx::merge</i>	std::merge ³⁰²
<i>hpx::min_element</i>	std::min_element ³⁰³
<i>hpx::minmax_element</i>	std::minmax_element ³⁰⁴
<i>hpx::mismatch</i>	std::mismatch ³⁰⁵
<i>hpx::move</i>	std::move ³⁰⁶
<i>hpx::none_of</i>	std::none_of ³⁰⁷
<i>hpx::nth_element</i>	std::nth_element ³⁰⁸
<i>hpx::partial_sort</i>	std::partial_sort ³⁰⁹
<i>hpx::partial_sort_copy</i>	std::partial_sort_copy ³¹⁰
<i>hpx::partition</i>	std::partition ³¹¹
<i>hpx::partition_copy</i>	std::partition_copy ³¹²
<i>hpx::experimental::reduce_by_key</i>	reduce_by_key ³¹³
<i>hpx::remove</i>	std::remove ³¹⁴
<i>hpx::remove_copy</i>	std::remove_copy ³¹⁵
<i>hpx::remove_copy_if</i>	std::remove_copy_if ³¹⁶
<i>hpx::remove_if</i>	std::remove_if ³¹⁷
<i>hpx::replace</i>	std::replace ³¹⁸
<i>hpx::replace_copy</i>	std::replace_copy ³¹⁹
<i>hpx::replace_copy_if</i>	std::replace_copy_if ³²⁰
<i>hpx::replace_if</i>	std::replace_if ³²¹
<i>hpx::reverse</i>	std::reverse ³²²
<i>hpx::reverse_copy</i>	std::reverse_copy ³²³
<i>hpx::rotate</i>	std::rotate ³²⁴
<i>hpx::rotate_copy</i>	std::rotate_copy ³²⁵
<i>hpx::search</i>	std::search ³²⁶
<i>hpx::search_n</i>	std::search_n ³²⁷
<i>hpx::set_difference</i>	std::set_difference ³²⁸
<i>hpx::set_intersection</i>	std::set_intersection ³²⁹
<i>hpx::set_symmetric_difference</i>	std::set_symmetric_difference ³³⁰
<i>hpx::set_union</i>	std::set_union ³³¹
<i>hpx::shift_left</i>	std::shift_left ³³²
<i>hpx::shift_right</i>	std::shift_right ³³³
<i>hpx::sort</i>	std::sort ³³⁴
<i>hpx::experimental::sort_by_key</i>	sort_by_key ³³⁵
<i>hpx::stable_partition</i>	std::stable_partition ³³⁶
<i>hpx::stable_sort</i>	std::stable_sort ³³⁷
<i>hpx::starts_with</i>	std::starts_with ³³⁸
<i>hpx::swap_ranges</i>	std::swap_ranges ³³⁹

continues on next page

Table 2.126 – continued from previous page

<i>hpx</i> function	C++ standard
<i>hpx::transform</i>	std::transform ³⁴⁰
<i>hpx::unique</i>	std::unique ³⁴¹
<i>hpx::unique_copy</i>	std::unique_copy ³⁴²
<i>hpx::experimental::for_loop</i>	N4808 ³⁴³
<i>hpx::experimental::for_loop_strided</i>	N4808 ³⁴⁴
<i>hpx::experimental::for_loop_n</i>	N4808 ³⁴⁵
<i>hpx::experimental::for_loop_n_strided</i>	N4808 ³⁴⁶

271 http://en.cppreference.com/w/cpp/algorithm/adjacent_find
 272 http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
 273 http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
 274 <http://en.cppreference.com/w/cpp/algorithm/copy>
 275 <http://en.cppreference.com/w/cpp/algorithm/copy>
 276 http://en.cppreference.com/w/cpp/algorithm/copy_n
 277 <http://en.cppreference.com/w/cpp/algorithm/count>
 278 <http://en.cppreference.com/w/cpp/algorithm/count>
 279 http://en.cppreference.com/w/cpp/algorithm/ranges/ends_with
 280 <http://en.cppreference.com/w/cpp/algorithm/equal>
 281 <http://en.cppreference.com/w/cpp/algorithm/fill>
 282 http://en.cppreference.com/w/cpp/algorithm/fill_n
 283 <http://en.cppreference.com/w/cpp/algorithm/find>
 284 http://en.cppreference.com/w/cpp/algorithm/find_end
 285 http://en.cppreference.com/w/cpp/algorithm/find_first_of
 286 <http://en.cppreference.com/w/cpp/algorithm/find>
 287 <http://en.cppreference.com/w/cpp/algorithm/find>
 288 http://en.cppreference.com/w/cpp/algorithm/for_each
 289 http://en.cppreference.com/w/cpp/algorithm/for_each_n
 290 <http://en.cppreference.com/w/cpp/algorithm/generate>
 291 http://en.cppreference.com/w/cpp/algorithm/generate_n
 292 <http://en.cppreference.com/w/cpp/algorithm/includes>
 293 http://en.cppreference.com/w/cpp/algorithm/inplace_merge
 294 http://en.cppreference.com/w/cpp/algorithm/is_heap
 295 http://en.cppreference.com/w/cpp/algorithm/is_heap_until
 296 http://en.cppreference.com/w/cpp/algorithm/is_partitioned
 297 http://en.cppreference.com/w/cpp/algorithm/is_sorted
 298 http://en.cppreference.com/w/cpp/algorithm/is_sorted_until
 299 http://en.cppreference.com/w/cpp/algorithm/lexicographical_compare
 300 http://en.cppreference.com/w/cpp/algorithm/make_heap
 301 http://en.cppreference.com/w/cpp/algorithm/max_element
 302 <http://en.cppreference.com/w/cpp/algorithm/merge>
 303 http://en.cppreference.com/w/cpp/algorithm/min_element
 304 http://en.cppreference.com/w/cpp/algorithm/minmax_element
 305 <http://en.cppreference.com/w/cpp/algorithm/mismatch>
 306 <http://en.cppreference.com/w/cpp/algorithm/move>
 307 http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
 308 http://en.cppreference.com/w/cpp/algorithm/nth_element
 309 http://en.cppreference.com/w/cpp/algorithm/partial_sort
 310 http://en.cppreference.com/w/cpp/algorithm/partial_sort_copy
 311 <http://en.cppreference.com/w/cpp/algorithm/partition>
 312 http://en.cppreference.com/w/cpp/algorithm/partition_copy
 313 https://thrust.github.io/doc/group__reductions_gad5623f203f9b3fdcab72481c3913f0e0.html
 314 <http://en.cppreference.com/w/cpp/algorithm/remove>
 315 http://en.cppreference.com/w/cpp/algorithm/remove_copy
 316 http://en.cppreference.com/w/cpp/algorithm/remove_copy
 317 <http://en.cppreference.com/w/cpp/algorithm/remove>
 318 <http://en.cppreference.com/w/cpp/algorithm/replace>
 319 http://en.cppreference.com/w/cpp/algorithm/replace_copy
 320 http://en.cppreference.com/w/cpp/algorithm/replace_copy
 321 <http://en.cppreference.com/w/cpp/algorithm/replace>
 322 <http://en.cppreference.com/w/cpp/algorithm/reverse>
 323 http://en.cppreference.com/w/cpp/algorithm/reverse_copy
 324 <http://en.cppreference.com/w/cpp/algorithm/rotate>
 325 http://en.cppreference.com/w/cpp/algorithm/rotate_copy
 326 <http://en.cppreference.com/w/cpp/algorithm/search>
 327 http://en.cppreference.com/w/cpp/algorithm/search_n
 328 http://en.cppreference.com/w/cpp/algorithm/set_difference
 329 http://en.cppreference.com/w/cpp/algorithm/set_intersection
 330 http://en.cppreference.com/w/cpp/algorithm/set_symmetric_difference
 331 http://en.cppreference.com/w/cpp/algorithm/set_union
 332 <http://en.cppreference.com/w/cpp/algorithm/shift>
 333 <http://en.cppreference.com/w/cpp/algorithm/shift>
 334 <http://en.cppreference.com/w/cpp/algorithm/sort>
 335 https://thrust.github.io/doc/group__sorting_gabe038d6107f7c824cf74120500ef45ea.html
 336 http://en.cppreference.com/w/cpp/algorithm/stable_partition
 337 http://en.cppreference.com/w/cpp/algorithm/stable_sort
 338 http://en.cppreference.com/w/cpp/algorithm/ranges/starts_with
 339 http://en.cppreference.com/w/cpp/algorithm/swap_ranges
 340 <http://en.cppreference.com/w/cpp/algorithm/transform>
 341 <http://en.cppreference.com/w/cpp/algorithm/unique>
 342 http://en.cppreference.com/w/cpp/algorithm/unique_copy
 343 <http://wg21.link/n4808>
 344 <http://wg21.link/n4808>

Table 2.127: *hpx::ranges* functions of header *hpx/algorithm.hpp*

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::adjacent_find</i>	<code>std::adjacent_find</code> ³⁴⁷
<i>hpx::ranges::all_of</i>	<code>std::all_of</code> ³⁴⁸
<i>hpx::ranges::any_of</i>	<code>std::any_of</code> ³⁴⁹
<i>hpx::ranges::copy</i>	<code>std::copy</code> ³⁵⁰
<i>hpx::ranges::copy_if</i>	<code>std::copy_if</code> ³⁵¹
<i>hpx::ranges::copy_n</i>	<code>std::copy_n</code> ³⁵²
<i>hpx::ranges::count</i>	<code>std::count</code> ³⁵³
<i>hpx::ranges::count_if</i>	<code>std::count_if</code> ³⁵⁴
<i>hpx::ranges::ends_with</i>	<code>std::ends_with</code> ³⁵⁵
<i>hpx::ranges::equal</i>	<code>std::equal</code> ³⁵⁶
<i>hpx::ranges::fill</i>	<code>std::fill</code> ³⁵⁷
<i>hpx::ranges::fill_n</i>	<code>std::fill_n</code> ³⁵⁸
<i>hpx::ranges::find</i>	<code>std::find</code> ³⁵⁹
<i>hpx::ranges::find_end</i>	<code>std::find_end</code> ³⁶⁰
<i>hpx::ranges::find_first_of</i>	<code>std::find_first_of</code> ³⁶¹
<i>hpx::ranges::find_if</i>	<code>std::find_if</code> ³⁶²
<i>hpx::ranges::find_if_not</i>	<code>std::find_if_not</code> ³⁶³
<i>hpx::ranges::for_each</i>	<code>std::for_each</code> ³⁶⁴
<i>hpx::ranges::for_each_n</i>	<code>std::for_each_n</code> ³⁶⁵
<i>hpx::ranges::generate</i>	<code>std::generate</code> ³⁶⁶
<i>hpx::ranges::generate_n</i>	<code>std::generate_n</code> ³⁶⁷
<i>hpx::ranges::includes</i>	<code>std::includes</code> ³⁶⁸
<i>hpx::ranges::inplace_merge</i>	<code>std::inplace_merge</code> ³⁶⁹
<i>hpx::ranges::is_heap</i>	<code>std::is_heap</code> ³⁷⁰
<i>hpx::ranges::is_heap_until</i>	<code>std::is_heap_until</code> ³⁷¹
<i>hpx::ranges::is_partitioned</i>	<code>std::is_partitioned</code> ³⁷²
<i>hpx::ranges::is_sorted</i>	<code>std::is_sorted</code> ³⁷³
<i>hpx::ranges::is_sorted_until</i>	<code>std::is_sorted_until</code> ³⁷⁴
<i>hpx::ranges::make_heap</i>	<code>std::make_heap</code> ³⁷⁵
<i>hpx::ranges::max_element</i>	<code>std::max_element</code> ³⁷⁶
<i>hpx::ranges::merge</i>	<code>std::merge</code> ³⁷⁷
<i>hpx::ranges::min_element</i>	<code>std::min_element</code> ³⁷⁸
<i>hpx::ranges::minmax_element</i>	<code>std::minmax_element</code> ³⁷⁹
<i>hpx::ranges::mismatch</i>	<code>std::mismatch</code> ³⁸⁰
<i>hpx::ranges::move</i>	<code>std::move</code> ³⁸¹
<i>hpx::ranges::none_of</i>	<code>std::none_of</code> ³⁸²
<i>hpx::ranges::nth_element</i>	<code>std::nth_element</code> ³⁸³
<i>hpx::ranges::partial_sort</i>	<code>std::partial_sort</code> ³⁸⁴
<i>hpx::ranges::partial_sort_copy</i>	<code>std::partial_sort_copy</code> ³⁸⁵
<i>hpx::ranges::partition</i>	<code>std::partition</code> ³⁸⁶
<i>hpx::ranges::partition_copy</i>	<code>std::partition_copy</code> ³⁸⁷
<i>hpx::ranges::set_difference</i>	<code>std::set_difference</code> ³⁸⁸
<i>hpx::ranges::set_intersection</i>	<code>std::set_intersection</code> ³⁸⁹
<i>hpx::ranges::set_symmetric_difference</i>	<code>std::set_symmetric_difference</code> ³⁹⁰
<i>hpx::ranges::set_union</i>	<code>std::set_union</code> ³⁹¹
<i>hpx::ranges::shift_left</i>	P2440 ³⁹²
<i>hpx::ranges::shift_right</i>	P2440 ³⁹³
<i>hpx::ranges::sort</i>	<code>std::sort</code> ³⁹⁴

continues on next page

Table 2.127 – continued from previous page

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::stable_partition</i>	<code>std::stable_partition</code> ³⁹⁵
<i>hpx::ranges::stable_sort</i>	<code>std::stable_sort</code> ³⁹⁶
<i>hpx::ranges::starts_with</i>	<code>std::starts_with</code> ³⁹⁷
<i>hpx::ranges::swap_ranges</i>	<code>std::swap_ranges</code> ³⁹⁸
<i>hpx::ranges::transform</i>	<code>std::transform</code> ³⁹⁹
<i>hpx::ranges::unique</i>	<code>std::unique</code> ⁴⁰⁰
<i>hpx::ranges::unique_copy</i>	<code>std::unique_copy</code> ⁴⁰¹
<i>hpx::ranges::experimental::for_loop</i>	N4808 ⁴⁰²
<i>hpx::ranges::experimental::for_loop_strided</i>	N4808 ⁴⁰³

hpx/any.hpp

The header `hpx/any.hpp`⁴⁰⁴ corresponds to the C++ standard library header `any`⁴⁰⁵.

`hpx::any` is compatible with `std::any`.

```
347 http://en.cppreference.com/w/cpp/algorithm/ranges/adjacent\_find
348 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
349 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
350 http://en.cppreference.com/w/cpp/algorithm/ranges/copy
351 http://en.cppreference.com/w/cpp/algorithm/ranges/copy
352 http://en.cppreference.com/w/cpp/algorithm/ranges/copy\_n
353 http://en.cppreference.com/w/cpp/algorithm/ranges/count
354 http://en.cppreference.com/w/cpp/algorithm/ranges/count
355 http://en.cppreference.com/w/cpp/algorithm/ranges/ends\_with
356 http://en.cppreference.com/w/cpp/algorithm/ranges/equal
357 http://en.cppreference.com/w/cpp/algorithm/ranges/fill
358 http://en.cppreference.com/w/cpp/algorithm/ranges/fill\_n
359 http://en.cppreference.com/w/cpp/algorithm/ranges/find
360 http://en.cppreference.com/w/cpp/algorithm/ranges/find\_end
361 http://en.cppreference.com/w/cpp/algorithm/ranges/find\_first\_of
362 http://en.cppreference.com/w/cpp/algorithm/ranges/find
363 http://en.cppreference.com/w/cpp/algorithm/ranges/find
364 http://en.cppreference.com/w/cpp/algorithm/ranges/for\_each
365 http://en.cppreference.com/w/cpp/algorithm/ranges/for\_each\_n
366 http://en.cppreference.com/w/cpp/algorithm/ranges/generate
367 http://en.cppreference.com/w/cpp/algorithm/ranges/generate\_n
368 http://en.cppreference.com/w/cpp/algorithm/ranges/includes
369 http://en.cppreference.com/w/cpp/algorithm/ranges/inplace\_merge
370 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_heap
371 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_heap\_until
372 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_partitioned
373 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_sorted
374 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_sorted\_until
375 http://en.cppreference.com/w/cpp/algorithm/ranges/make\_heap
376 http://en.cppreference.com/w/cpp/algorithm/ranges/max\_element
377 http://en.cppreference.com/w/cpp/algorithm/ranges/merge
378 http://en.cppreference.com/w/cpp/algorithm/ranges/min\_element
379 http://en.cppreference.com/w/cpp/algorithm/ranges/minmax\_element
380 http://en.cppreference.com/w/cpp/algorithm/ranges/mismatch
381 http://en.cppreference.com/w/cpp/algorithm/ranges/move
382 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
383 http://en.cppreference.com/w/cpp/algorithm/ranges/nth\_element
384 http://en.cppreference.com/w/cpp/algorithm/ranges/partial\_sort
385 http://en.cppreference.com/w/cpp/algorithm/ranges/partial\_sort\_copy
386 http://en.cppreference.com/w/cpp/algorithm/ranges/partition
387 http://en.cppreference.com/w/cpp/algorithm/ranges/partition\_copy
388 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_difference
389 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_intersection
390 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_symmetric\_difference
391 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_union
392 https://wg21.link/p2440
393 https://wg21.link/p2440
394 http://en.cppreference.com/w/cpp/algorithm/ranges/sort
395 http://en.cppreference.com/w/cpp/algorithm/ranges/stable\_partition
396 http://en.cppreference.com/w/cpp/algorithm/ranges/stable\_sort
397 http://en.cppreference.com/w/cpp/algorithm/ranges/starts\_with
398 http://en.cppreference.com/w/cpp/algorithm/ranges/swap\_ranges
399 http://en.cppreference.com/w/cpp/algorithm/ranges/transform
400 http://en.cppreference.com/w/cpp/algorithm/ranges/unique
401 http://en.cppreference.com/w/cpp/algorithm/ranges/unique\_copy
402 http://wg21.link/n4808
403 http://wg21.link/n4808
404 http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include\_local/include/hpx/any.hpp
405 http://en.cppreference.com/w/cpp/header/any
```

Classes

Table 2.128: Classes of header `hpx/any.hpp`

Class	C++ standard
<code>hpx::any</code>	<code>std::any</code> ⁴⁰⁶
<code>hpx::any_noner</code>	
<code>hpx::bad_any_cast</code>	<code>std::bad_any_cast</code> ⁴⁰⁷
<code>hpx::unique_any_noner</code>	

Functions

Table 2.129: Functions of header `hpx/any.hpp`

Function	C++ standard
<code>hpx::any_cast</code>	<code>std::any_cast</code> ⁴⁰⁸
<code>hpx::make_any</code>	<code>std::make_any</code> ⁴⁰⁹
<code>hpx::make_any_noner</code>	
<code>hpx::make_unique_any_noner</code>	

`hpx/assert.hpp`

The header `hpx/assert.hpp`⁴¹⁰ corresponds to the C++ standard library header `cassert`⁴¹¹.

`HPX_ASSERT` is the *HPX* equivalent to `assert` in `cassert`. `HPX_ASSERT` can also be used in CUDA device code.

Macros

Table 2.130: Macros of header `hpx/assert.hpp`

Macro
<code>HPX_ASSERT</code>
<code>HPX_ASSERT_MSG</code>

⁴⁰⁶ <http://en.cppreference.com/w/cpp/utility/any>

⁴⁰⁷ http://en.cppreference.com/w/cpp/utility/any/bad_any_cast

⁴⁰⁸ http://en.cppreference.com/w/cpp/utility/any/any_cast

⁴⁰⁹ http://en.cppreference.com/w/cpp/utility/any/make_any

⁴¹⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/assertion/include/hpx/assert.hpp>

⁴¹¹ <http://en.cppreference.com/w/cpp/header/cassert>

`hpx/barrier.hpp`

The header `hpx/barrier.hpp`⁴¹² corresponds to the C++ standard library header `barrier`⁴¹³ and contains a distributed barrier implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.131: Classes of header `hpx/barrier.hpp`

Class	C++ standard
<code>hpx::barrier</code>	<code>std::barrier</code> ⁴¹⁴

Table 2.132: Distributed implementation of classes of header `hpx/barrier.hpp`

Class
<code>hpx::distributed::barrier</code>

`hpx/channel.hpp`

The header `hpx/channel.hpp`⁴¹⁵ contains a local and a distributed channel implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.133: Classes of header `hpx/channel.hpp`

Class
<code>hpx::channel</code>

Table 2.134: Distributed implementation of classes of header `hpx/channel.hpp`

Class
<code>hpx::distributed::channel</code>

⁴¹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/barrier.hpp>

⁴¹³ <http://en.cppreference.com/w/cpp/header/barrier>

⁴¹⁴ <http://en.cppreference.com/w/cpp/thread/barrier>

⁴¹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/channel.hpp>

hpx/chrono.hpp

The header `hpx/chrono.hpp`⁴¹⁶ corresponds to the C++ standard library header `chrono`⁴¹⁷. The following replacements and extensions are provided compared to `chrono`⁴¹⁸.

Classes

Table 2.135: Classes of header `hpx/chrono.hpp`

Class	C++ standard
<code>hpx::chrono::high_resolution_clock</code>	<code>std::high_resolution_clock</code> ⁴¹⁹
<code>hpx::chrono::high_resolution_timer</code>	
<code>hpx::chrono::steady_time_point</code>	<code>std::time_point</code> ⁴²⁰

hpx/condition_variable.hpp

The header `hpx/condition_variable.hpp`⁴²¹ corresponds to the C++ standard library header `condition_variable`⁴²².

Classes

Table 2.136: Classes of header `hpx/condition_variable.hpp`

Class	C++ standard
<code>hpx::condition_variable</code>	<code>std::condition_variable</code> ⁴²³
<code>hpx::condition_variable_any</code>	<code>std::condition_variable_any</code> ⁴²⁴
<code>hpx::cv_status</code>	<code>std::cv_status</code> ⁴²⁵

hpx/exception.hpp

The header `hpx/exception.hpp`⁴²⁶ corresponds to the C++ standard library header `exception`⁴²⁷. `hpx::exception` extends `std::exception` and is the base class for all exceptions thrown in *HPX*. `HPX_THROW_EXCEPTION` can be used to throw *HPX* exceptions with file and line information attached to the exception.

⁴¹⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/chrono.hpp

⁴¹⁷ <http://en.cppreference.com/w/cpp/header/chrono>

⁴¹⁸ <http://en.cppreference.com/w/cpp/header/chrono>

⁴¹⁹ http://en.cppreference.com/w/cpp/chrono/high_resolution_clock

⁴²⁰ http://en.cppreference.com/w/cpp/chrono/time_point

⁴²¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/condition_variable.hpp

⁴²² http://en.cppreference.com/w/cpp/header/condition_variable

⁴²³ http://en.cppreference.com/w/cpp/thread/condition_variable

⁴²⁴ http://en.cppreference.com/w/cpp/thread/condition_variable_any

⁴²⁵ http://en.cppreference.com/w/cpp/thread/cv_status

⁴²⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/exception.hpp

⁴²⁷ <http://en.cppreference.com/w/cpp/header/exception>

Macros

- `HPX_THROW_EXCEPTION`

Classes

Table 2.137: Classes of header `hpx/exception.hpp`

Class	C++ standard
<code>hpx::exception</code>	<code>std::exception</code> ⁴²⁸

`hpx/execution.hpp`

The header `hpx/execution.hpp`⁴²⁹ corresponds to the C++ standard library header `execution`⁴³⁰. See *High level parallel facilities*, *Using parallel algorithms* and *Executor parameters and executor parameter traits* for more information about execution policies and executor parameters.

Note: These names are only available in the `hpx::execution` namespace, not in the top-level `hpx` namespace.

Constants

Table 2.138: Constants of header `hpx/execution.hpp`

Constant	C++ standard
<code>hpx::execution::seq</code>	<code>std::execution_policy_tag</code> ⁴³¹
<code>hpx::execution::par</code>	<code>std::execution_policy_tag</code> ⁴³²
<code>hpx::execution::par_unseq</code>	<code>std::execution_policy_tag</code> ⁴³³
<code>hpx::execution::task</code>	

⁴²⁸ <http://en.cppreference.com/w/cpp/error/exception>

⁴²⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

⁴³⁰ <http://en.cppreference.com/w/cpp/header/execution>

⁴³¹ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

⁴³² http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

⁴³³ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

Classes

Table 2.139: Classes of header `hpx/execution.hpp`

Class	C++ standard
<code>hpx::execution::sequenced_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁴
<code>hpx::execution::parallel_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁵
<code>hpx::execution::parallel_unsequenced_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁶
<code>hpx::execution::sequenced_task_policy</code>	
<code>hpx::execution::parallel_task_policy</code>	
<code>hpx::execution::experimental::auto_chunk_size</code>	
<code>hpx::execution::experimental::dynamic_chunk_size</code>	
<code>hpx::execution::experimental::guided_chunk_size</code>	
<code>hpx::execution::experimental::persistent_auto_chunk_size</code>	
<code>hpx::execution::experimental::static_chunk_size</code>	
<code>hpx::execution::experimental::num_cores</code>	

`hpx/functional.hpp`

The header `hpx/functional.hpp`⁴³⁷ corresponds to the C++ standard library header `functional`⁴³⁸. `hpx::function` is a more efficient and serializable replacement for `std::function`.

Constants

The following constants correspond to the C++ standard `std::placeholders`⁴³⁹

Table 2.140: Constants of header `hpx/functional.hpp`

Constant
<code>hpx::placeholders::_1</code>
<code>hpx::placeholders::_2</code>
...
<code>hpx::placeholders::_9</code>

Classes

Table 2.141: Classes of header `hpx/functional.hpp`

Class	C++ standard
<code>hpx::function</code>	<code>std::function</code> ⁴⁴⁰
<code>hpx::function_ref</code>	<code>P0792</code> ⁴⁴¹
<code>hpx::move_only_function</code>	<code>std::move_only_function</code> ⁴⁴²
<code>hpx::is_bind_expression</code>	<code>std::is_bind_expression</code> ⁴⁴³
<code>hpx::is_placeholder</code>	<code>std::is_placeholder</code> ⁴⁴⁴
<code>hpx::scoped_annotation</code>	

⁴³⁴ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁵ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁶ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

⁴³⁸ <http://en.cppreference.com/w/cpp/header/functional>

⁴³⁹ <http://en.cppreference.com/w/cpp/utility/functional/placeholders>

Functions

Table 2.142: Functions of header `hpx/functional.hpp`

Function	C++ standard
<code>hpx::annotated_function</code>	
<code>hpx::bind</code>	<code>std::bind</code> ⁴⁴⁵
<code>hpx::bind_back</code>	<code>std::bind_front</code> ⁴⁴⁶
<code>hpx::bind_front</code>	<code>std::bind_front</code> ⁴⁴⁷
<code>hpx::invoke</code>	<code>std::invoke</code> ⁴⁴⁸
<code>hpx::invoke_fused</code>	<code>std::apply</code> ⁴⁴⁹
<code>hpx::invoke_fused_r</code>	
<code>hpx::mem_fn</code>	<code>std::mem_fn</code> ⁴⁵⁰

`hpx/future.hpp`

The header `hpx/future.hpp`⁴⁵¹ corresponds to the C++ standard library header `future`⁴⁵². See *Extended facilities for futures* for more information about extensions to futures compared to the C++ standard library.

This header file also contains overloads of `hpx::async`, `hpx::post`, `hpx::sync`, and `hpx::dataflow` that can be used with actions. See *Action invocation* for more information about invoking actions.

Classes

Table 2.143: Classes of header `hpx/future.hpp`

Class	C++ standard
<code>hpx::future</code>	<code>std::future</code> ⁴⁵³
<code>hpx::shared_future</code>	<code>std::shared_future</code> ⁴⁵⁴
<code>hpx::promise</code>	<code>std::promise</code> ⁴⁵⁵
<code>hpx::launch</code>	<code>std::launch</code> ⁴⁵⁶
<code>hpx::packaged_task</code>	<code>std::packaged_task</code> ⁴⁵⁷

Note: All names except `hpx::promise` are also available in the top-level `hpx` namespace. `hpx::promise` refers to `hpx::distributed::promise`, a distributed variant of `hpx::promise`, but will eventually refer to `hpx::promise`

⁴⁴⁰ <http://en.cppreference.com/w/cpp/utility/functional/function>

⁴⁴¹ <http://wg21.link/p0792>

⁴⁴² http://en.cppreference.com/w/cpp/utility/functional/move_only_function

⁴⁴³ http://en.cppreference.com/w/cpp/utility/functional/is_bind_expression

⁴⁴⁴ http://en.cppreference.com/w/cpp/utility/functional/is_placeholder

⁴⁴⁵ <http://en.cppreference.com/w/cpp/utility/functional/bind>

⁴⁴⁶ http://en.cppreference.com/w/cpp/utility/functional/bind_front

⁴⁴⁷ http://en.cppreference.com/w/cpp/utility/functional/bind_front

⁴⁴⁸ <http://en.cppreference.com/w/cpp/utility/functional/invoke>

⁴⁴⁹ <http://en.cppreference.com/w/cpp/utility/apply>

⁴⁵⁰ http://en.cppreference.com/w/cpp/utility/functional/mem_fn

⁴⁵¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

⁴⁵² <http://en.cppreference.com/w/cpp/header/future>

⁴⁵³ <http://en.cppreference.com/w/cpp/thread/future>

⁴⁵⁴ http://en.cppreference.com/w/cpp/thread/shared_future

⁴⁵⁵ <http://en.cppreference.com/w/cpp/thread/promise>

⁴⁵⁶ <http://en.cppreference.com/w/cpp/thread/launch>

⁴⁵⁷ http://en.cppreference.com/w/cpp/thread/packaged_task

after a deprecation period.

Table 2.144: Distributed implementation of classes of header `hpx/future.hpp`

Class
<code>hpx::distributed::promise</code>

Functions

Table 2.145: Functions of header `hpx/future.hpp`

Function	C++ standard
<code>hpx::async</code>	<code>std::async</code> ⁴⁵⁸
<code>hpx::post</code>	
<code>hpx::sync</code>	
<code>hpx::dataflow</code>	
<code>hpx::make_future</code>	
<code>hpx::make_shared_future</code>	
<code>hpx::make_ready_future</code>	P0159 ⁴⁵⁹
<code>hpx::make_ready_future_alloc</code>	
<code>hpx::make_ready_future_at</code>	
<code>hpx::make_ready_future_after</code>	
<code>hpx::make_exceptional_future</code>	P0159 ⁴⁶⁰
<code>hpx::when_all</code>	P0159 ⁴⁶¹
<code>hpx::when_any</code>	P0159 ⁴⁶²
<code>hpx::when_some</code>	
<code>hpx::when_each</code>	
<code>hpx::wait_all</code>	
<code>hpx::wait_any</code>	
<code>hpx::wait_some</code>	
<code>hpx::wait_each</code>	

`hpx/init.hpp`

The header `hpx/init.hpp`⁴⁶³ contains functionality for starting, stopping, suspending, and resuming the *HPX* runtime. This is the main way to explicitly start the *HPX* runtime. See *Starting the HPX runtime* for more details on starting the *HPX* runtime.

⁴⁵⁸ <http://en.cppreference.com/w/cpp/thread/async>

⁴⁵⁹ <http://wg21.link/p0159>

⁴⁶⁰ <http://wg21.link/p0159>

⁴⁶¹ <http://wg21.link/p0159>

⁴⁶² <http://wg21.link/p0159>

⁴⁶³ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Classes

Table 2.146: Classes of header `hpx/init.hpp`

Class
<code>hpx::init_params</code>
<code>hpx::runtime_mode</code>

Functions

Table 2.147: Functions of header `hpx/init.hpp`

Function
<code>hpx::init</code>
<code>hpx::start</code>
<code>hpx::finalize</code>
<code>hpx::disconnect</code>
<code>hpx::suspend</code>
<code>hpx::resume</code>

`hpx/latch.hpp`

The header `hpx/latch.hpp`⁴⁶⁴ corresponds to the C++ standard library header `latch`⁴⁶⁵. It contains a local and a distributed latch implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.148: Classes of header `hpx/latch.hpp`

Class	C++ standard
<code>hpx::latch</code>	<code>std::latch</code> ⁴⁶⁶

Table 2.149: Distributed implementation of classes of header `hpx/latch.hpp`

Class
<code>hpx::distributed::latch</code>

⁴⁶⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/latch.hpp>

⁴⁶⁵ <http://en.cppreference.com/w/cpp/header/latch>

⁴⁶⁶ <http://en.cppreference.com/w/cpp/thread/latch>

hpx/mutex.hpp

The header `hpx/mutex.hpp`⁴⁶⁷ corresponds to the C++ standard library header `mutex`⁴⁶⁸.

Classes

Table 2.150: Classes of header `hpx/mutex.hpp`

Class	C++ standard
<code>hpx::mutex</code>	<code>std::mutex</code> ⁴⁶⁹
<code>hpx::no_mutex</code>	
<code>hpx::once_flag</code>	<code>std::once_flag</code> ⁴⁷⁰
<code>hpx::recursive_mutex</code>	<code>std::recursive_mutex</code> ⁴⁷¹
<code>hpx::spinlock</code>	
<code>hpx::timed_mutex</code>	<code>std::timed_mutex</code> ⁴⁷²
<code>hpx::unlock_guard</code>	

Functions

Table 2.151: Functions of header `hpx/mutex.hpp`

Class	C++ standard
<code>hpx::call_once</code>	<code>std::call_once</code> ⁴⁷³

hpx/memory.hpp

The header `hpx/memory.hpp`⁴⁷⁴ corresponds to the C++ standard library header `memory`⁴⁷⁵. It contains parallel versions of the copy, fill, move, and construct helper functions in `memory`⁴⁷⁶. See *Using parallel algorithms* for more information about the parallel algorithms.

⁴⁶⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

⁴⁶⁸ <http://en.cppreference.com/w/cpp/header/mutex>

⁴⁶⁹ <http://en.cppreference.com/w/cpp/thread/mutex>

⁴⁷⁰ http://en.cppreference.com/w/cpp/thread/once_flag

⁴⁷¹ http://en.cppreference.com/w/cpp/thread/recursive_mutex

⁴⁷² http://en.cppreference.com/w/cpp/thread/timed_mutex

⁴⁷³ http://en.cppreference.com/w/cpp/thread/call_once

⁴⁷⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/memory.hpp

⁴⁷⁵ <http://en.cppreference.com/w/cpp/header/memory>

⁴⁷⁶ <http://en.cppreference.com/w/cpp/header/memory>

Functions

Table 2.152: *hpx* functions of header *hpx/memory.hpp*

<i>hpx</i> function	C++ standard
<i>hpx::uninitialized_copy</i>	<code>std::uninitialized_copy</code> ⁴⁷⁷
<i>hpx::uninitialized_copy_n</i>	<code>std::uninitialized_copy_n</code> ⁴⁷⁸
<i>hpx::uninitialized_default_construct</i>	<code>std::uninitialized_default_construct</code> ⁴⁷⁹
<i>hpx::uninitialized_default_construct_n</i>	<code>std::uninitialized_default_construct_n</code> ⁴⁸⁰
<i>hpx::uninitialized_fill</i>	<code>std::uninitialized_fill</code> ⁴⁸¹
<i>hpx::uninitialized_fill_n</i>	<code>std::uninitialized_fill_n</code> ⁴⁸²
<i>hpx::uninitialized_move</i>	<code>std::uninitialized_move</code> ⁴⁸³
<i>hpx::uninitialized_move_n</i>	<code>std::uninitialized_move_n</code> ⁴⁸⁴
<i>hpx::uninitialized_value_construct</i>	<code>std::uninitialized_value_construct</code> ⁴⁸⁵
<i>hpx::uninitialized_value_construct_n</i>	<code>std::uninitialized_value_construct_n</code> ⁴⁸⁶

Table 2.153: *hpx::ranges* functions of header *hpx/memory.hpp*

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::uninitialized_copy</i>	<code>std::uninitialized_copy</code> ⁴⁸⁷
<i>hpx::ranges::uninitialized_copy_n</i>	<code>std::uninitialized_copy_n</code> ⁴⁸⁸
<i>hpx::ranges::uninitialized_default_construct</i>	<code>std::uninitialized_default_construct</code> ⁴⁸⁹
<i>hpx::ranges::uninitialized_default_construct_n</i>	<code>std::uninitialized_default_construct_n</code> ⁴⁹⁰
<i>hpx::ranges::uninitialized_fill</i>	<code>std::uninitialized_fill</code> ⁴⁹¹
<i>hpx::ranges::uninitialized_fill_n</i>	<code>std::uninitialized_fill_n</code> ⁴⁹²
<i>hpx::ranges::uninitialized_move</i>	<code>std::uninitialized_move</code> ⁴⁹³
<i>hpx::ranges::uninitialized_move_n</i>	<code>std::uninitialized_move_n</code> ⁴⁹⁴
<i>hpx::ranges::uninitialized_value_construct</i>	<code>std::uninitialized_value_construct</code> ⁴⁹⁵
<i>hpx::ranges::uninitialized_value_construct_n</i>	<code>std::uninitialized_value_construct_n</code> ⁴⁹⁶

⁴⁷⁷ http://en.cppreference.com/w/cpp/memory/uninitialized_copy⁴⁷⁸ http://en.cppreference.com/w/cpp/memory/uninitialized_copy_n⁴⁷⁹ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct⁴⁸⁰ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct_n⁴⁸¹ http://en.cppreference.com/w/cpp/memory/uninitialized_fill⁴⁸² http://en.cppreference.com/w/cpp/memory/uninitialized_fill_n⁴⁸³ http://en.cppreference.com/w/cpp/memory/uninitialized_move⁴⁸⁴ http://en.cppreference.com/w/cpp/memory/uninitialized_move_n⁴⁸⁵ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct⁴⁸⁶ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct_n⁴⁸⁷ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_copy⁴⁸⁸ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_copy_n⁴⁸⁹ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_default_construct⁴⁹⁰ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_default_construct_n⁴⁹¹ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_fill⁴⁹² http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_fill_n⁴⁹³ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_move⁴⁹⁴ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_move_n⁴⁹⁵ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_value_construct⁴⁹⁶ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_value_construct_n

hpx/numeric.hpp

The header `hpx/numeric.hpp`⁴⁹⁷ corresponds to the C++ standard library header `numeric`⁴⁹⁸. See *Using parallel algorithms* for more information about the parallel algorithms.

Functions

Table 2.154: *hpx* functions of header `hpx/numeric.hpp`

<i>hpx</i> function	C++ standard
<code>hpx::adjacent_difference</code>	<code>std::adjacent_difference</code> ⁴⁹⁹
<code>hpx::exclusive_scan</code>	<code>std::exclusive_scan</code> ⁵⁰⁰
<code>hpx::inclusive_scan</code>	<code>std::inclusive_scan</code> ⁵⁰¹
<code>hpx::reduce</code>	<code>std::reduce</code> ⁵⁰²
<code>hpx::transform_exclusive_scan</code>	<code>std::transform_exclusive_scan</code> ⁵⁰³
<code>hpx::transform_inclusive_scan</code>	<code>std::transform_inclusive_scan</code> ⁵⁰⁴
<code>hpx::transform_reduce</code>	<code>std::transform_reduce</code> ⁵⁰⁵

Table 2.155: *hpx::ranges* functions of header `hpx/numeric.hpp`

<i>hpx::ranges</i> function
<code>hpx::ranges::adjacent_difference</code>
<code>hpx::ranges::exclusive_scan</code>
<code>hpx::ranges::inclusive_scan</code>
<code>hpx::ranges::reduce</code>
<code>hpx::ranges::transform_exclusive_scan</code>
<code>hpx::ranges::transform_inclusive_scan</code>
<code>hpx::ranges::transform_reduce</code>

hpx/optional.hpp

The header `hpx/optional.hpp`⁵⁰⁶ corresponds to the C++ standard library header `optional`⁵⁰⁷. `hpx::optional` is compatible with `std::optional`.

⁴⁹⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/numeric.hpp

⁴⁹⁸ <http://en.cppreference.com/w/cpp/header/numeric>

⁴⁹⁹ http://en.cppreference.com/w/cpp/algorithm/adjacent_difference

⁵⁰⁰ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan

⁵⁰¹ http://en.cppreference.com/w/cpp/algorithm/inclusive_scan

⁵⁰² <http://en.cppreference.com/w/cpp/algorithm/reduce>

⁵⁰³ http://en.cppreference.com/w/cpp/algorithm/transform_exclusive_scan

⁵⁰⁴ http://en.cppreference.com/w/cpp/algorithm/transform_inclusive_scan

⁵⁰⁵ http://en.cppreference.com/w/cpp/algorithm/transform_reduce

⁵⁰⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/optional.hpp

⁵⁰⁷ <http://en.cppreference.com/w/cpp/header/optional>

Constants

- `hpx::nullopt`

Classes

Table 2.156: Classes of header `hpx/optional.hpp`

Class	C++ standard
<code>hpx::optional</code>	<code>std::optional</code> ⁵⁰⁸
<code>hpx::nullopt_t</code>	<code>std::nullopt_t</code> ⁵⁰⁹
<code>hpx::bad_optional_access</code>	<code>std::bad_optional_access</code> ⁵¹⁰

`hpx/runtime.hpp`

The header `hpx/runtime.hpp`⁵¹¹ contains functions for accessing local and distributed runtime information.

Typedefs

Table 2.157: Typedefs of header `hpx/runtime.hpp`

Typedef
<code>hpx::startup_function_type</code>
<code>hpx::shutdown_function_type</code>

⁵⁰⁸ <http://en.cppreference.com/w/cpp/utility/optional>

⁵⁰⁹ http://en.cppreference.com/w/cpp/utility/nullopt_t

⁵¹⁰ http://en.cppreference.com/w/cpp/utility/optional/bad_optional_access

⁵¹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Functions

Table 2.158: Functions of header `hpx/runtime.hpp`

Function
<code>hpx::find_root_locality</code>
<code>hpx::find_all_localities</code>
<code>hpx::find_remote_localities</code>
<code>hpx::find_locality</code>
<code>hpx::get_colocation_id</code>
<code>hpx::get_locality_id</code>
<code>hpx::get_num_worker_threads</code>
<code>hpx::get_worker_thread_num</code>
<code>hpx::get_thread_name</code>
<code>hpx::register_pre_startup_function</code>
<code>hpx::register_startup_function</code>
<code>hpx::register_pre_shutdown_function</code>
<code>hpx::register_shutdown_function</code>
<code>hpx::get_num_localities</code>
<code>hpx::get_locality_name</code>
<code>hpx::local::termination_detection</code>

`hpx/experimental/scope.hpp`

The header `hpx/experimental/scope.hpp`⁵¹² corresponds to the C++ standard library header `experimental/scope`⁵¹³.

Classes

Table 2.159: Classes of header `hpx/scope.hpp`

Class	C++ standard
<code>hpx::experimental::scope_exit</code>	<code>std::scope_exit</code> ⁵¹⁴
<code>hpx::experimental::scope_fail</code>	<code>std::scope_fail</code> ⁵¹⁵
<code>hpx::experimental::scope_success</code>	<code>std::scope_success</code> ⁵¹⁶

`hpx/semaphore.hpp`

The header `hpx/semaphore.hpp`⁵¹⁷ corresponds to the C++ standard library header `semaphore`⁵¹⁸.

⁵¹² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/experimental/scope.hpp

⁵¹³ <http://en.cppreference.com/w/cpp/header/experimental/scope>

⁵¹⁴ http://en.cppreference.com/w/cpp/header/experimental/scope_exit

⁵¹⁵ http://en.cppreference.com/w/cpp/header/experimental/scope_fail

⁵¹⁶ http://en.cppreference.com/w/cpp/header/experimental/scope_success

⁵¹⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/semaphore.hpp

⁵¹⁸ <http://en.cppreference.com/w/cpp/header/semaphore>

Classes

Table 2.160: Classes of header `hpx/semaphore.hpp`

Class	C++ standard
<code>hpx::binary_semaphore</code>	<code>std::counting_semaphore</code> ⁵¹⁹
<code>hpx::counting_semaphore</code>	<code>std::counting_semaphore</code> ⁵²⁰

`hpx/shared_mutex.hpp`

The header `hpx/shared_mutex.hpp`⁵²¹ corresponds to the C++ standard library header `shared_mutex`⁵²².

Classes

Table 2.161: Classes of header `hpx/shared_mutex.hpp`

Class	C++ standard
<code>hpx::shared_mutex</code>	<code>std::shared_mutex</code> ⁵²³

`hpx/source_location.hpp`

The header `hpx/source_location.hpp`⁵²⁴ corresponds to the C++ standard library header `source_location`⁵²⁵.

Classes

Table 2.162: Classes of header `hpx/system_error.hpp`

Class	C++ standard
<code>hpx::source_location</code>	<code>std::source_location</code> ⁵²⁶

`hpx/stop_token.hpp`

The header `hpx/stop_token.hpp`⁵²⁷ corresponds to the C++ standard library header `stop_token`⁵²⁸.

⁵¹⁹ http://en.cppreference.com/w/cpp/thread/counting_semaphore

⁵²⁰ http://en.cppreference.com/w/cpp/thread/counting_semaphore

⁵²¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/shared_mutex.hpp

⁵²² http://en.cppreference.com/w/cpp/header/shared_mutex

⁵²³ http://en.cppreference.com/w/cpp/thread/shared_mutex

⁵²⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/source_location.hpp

⁵²⁵ http://en.cppreference.com/w/cpp/header/source_location

⁵²⁶ http://en.cppreference.com/w/cpp/utility/source_location

⁵²⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/stop_token.hpp

⁵²⁸ http://en.cppreference.com/w/cpp/header/stop_token

Constants

Table 2.163: Constants of header `hpx/stop_token.hpp`

Constant	C++ standard
<code>hpx::nostopstate</code>	<code>std::nostopstate</code> ⁵²⁹

Classes

Table 2.164: Classes of header `hpx/stop_token.hpp`

Class	C++ standard
<code>hpx::stop_callback</code>	<code>std::stop_callback</code> ⁵³⁰
<code>hpx::stop_source</code>	<code>std::stop_source</code> ⁵³¹
<code>hpx::stop_token</code>	<code>std::stop_token</code> ⁵³²
<code>hpx::nostopstate_t</code>	<code>std::nostopstate_t</code> ⁵³³

`hpx/system_error.hpp`

The header `hpx/system_error.hpp`⁵³⁴ corresponds to the C++ standard library header `system_error`⁵³⁵.

Classes

Table 2.165: Classes of header `hpx/system_error.hpp`

Class	C++ standard
<code>hpx::error_code</code>	<code>std::error_code</code> ⁵³⁶

`hpx/task_block.hpp`

The header `hpx/task_block.hpp`⁵³⁷ corresponds to the `task_block` feature in N4755⁵³⁸. See `using_task_block` for more details on using task blocks.

⁵²⁹ http://en.cppreference.com/w/cpp/thread/stop_source/nostopstate

⁵³⁰ http://en.cppreference.com/w/cpp/thread/stop_callback

⁵³¹ http://en.cppreference.com/w/cpp/thread/stop_source

⁵³² http://en.cppreference.com/w/cpp/thread/stop_token

⁵³³ http://en.cppreference.com/w/cpp/thread/stop_source/nostopstate_t

⁵³⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/system_error.hpp

⁵³⁵ http://en.cppreference.com/w/cpp/header/system_error

⁵³⁶ http://en.cppreference.com/w/cpp/error/error_code

⁵³⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/task_block.hpp

⁵³⁸ <http://wg21.link/n4755>

Classes

Table 2.166: Classes of header `hpx/task_block.hpp`

Class
<code>hpx::experimental::task_canceled_exception</code>
<code>hpx::experimental::task_block</code>

Functions

Table 2.167: Functions of header `hpx/task_block.hpp`

Function
<code>hpx::experimental::define_task_block</code>
<code>hpx::experimental::define_task_block_restore_thread</code>

`hpx/experimental/task_group.hpp`

The header `hpx/experimental/task_group.hpp`⁵³⁹ corresponds to the `task_group` feature in oneAPI Threading Building Blocks (oneTBB)⁵⁴⁰.

Classes

Table 2.168: Classes of header `hpx/experimental/task_group.hpp`

Class
<code>hpx::experimental::task_group</code>

`hpx/thread.hpp`

The header `hpx/thread.hpp`⁵⁴¹ corresponds to the C++ standard library header `thread`⁵⁴². The functionality in this header is equivalent to the standard library thread functionality, with the exception that the *HPX* equivalents are implemented on top of lightweight threads and the *HPX* runtime.

Classes

Table 2.169: Classes of header `hpx/thread.hpp`

Class	C++ standard
<code>hpx::thread</code>	<code>std::thread</code> ⁵⁴³
<code>hpx::jthread</code>	<code>std::jthread</code> ⁵⁴⁴

⁵³⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/experimental/task_group.hpp

⁵⁴⁰ https://spec.oneapi.io/versions/1.0-rev-3/elements/oneTBB/source/task_scheduler/task_group/task_group_cls.html

⁵⁴¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/thread.hpp

⁵⁴² <http://en.cppreference.com/w/cpp/header/thread>

⁵⁴³ <http://en.cppreference.com/w/cpp/thread/thread>

⁵⁴⁴ <http://en.cppreference.com/w/cpp/thread/jthread>

Functions

Table 2.170: Functions of header `hpx/thread.hpp`

Function	C++ standard
<code>hpx::this_thread::yield</code>	<code>std::yield</code> ⁵⁴⁵
<code>hpx::this_thread::get_id</code>	<code>std::get_id</code> ⁵⁴⁶
<code>hpx::this_thread::sleep_for</code>	<code>std::sleep_for</code> ⁵⁴⁷
<code>hpx::this_thread::sleep_until</code>	<code>std::sleep_until</code> ⁵⁴⁸

`hpx/tuple.hpp`

The header `hpx/tuple.hpp`⁵⁴⁹ corresponds to the C++ standard library header `tuple`⁵⁵⁰. `hpx::tuple` can be used in CUDA device code, unlike `std::tuple`.

Constants

Table 2.171: Constants of header `hpx/tuple.hpp`

Constant	C++ standard
<code>hpx::ignore</code>	<code>std::ignore</code> ⁵⁵¹

Classes

Table 2.172: Classes of header `hpx/tuple.hpp`

Class	C++ standard
<code>hpx::tuple</code>	<code>std::tuple</code> ⁵⁵²
<code>hpx::tuple_size</code>	<code>std::tuple_size</code> ⁵⁵³
<code>hpx::tuple_element</code>	<code>std::tuple_element</code> ⁵⁵⁴

⁵⁴⁵ <http://en.cppreference.com/w/cpp/thread/yield>

⁵⁴⁶ http://en.cppreference.com/w/cpp/thread/get_id

⁵⁴⁷ http://en.cppreference.com/w/cpp/thread/sleep_for

⁵⁴⁸ http://en.cppreference.com/w/cpp/thread/sleep_until

⁵⁴⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/tuple.hpp

⁵⁵⁰ <http://en.cppreference.com/w/cpp/header/tuple>

⁵⁵¹ <http://en.cppreference.com/w/cpp/utility/tuple/ignore>

⁵⁵² <http://en.cppreference.com/w/cpp/utility/tuple>

⁵⁵³ http://en.cppreference.com/w/cpp/utility/tuple_size

⁵⁵⁴ http://en.cppreference.com/w/cpp/utility/tuple_element

Functions

Table 2.173: Functions of header `hpx/tuple.hpp`

Function	C++ standard
<code>hpx::make_tuple</code>	std::tuple_element ⁵⁵⁵
<code>hpx::tie</code>	std::tie ⁵⁵⁶
<code>hpx::forward_as_tuple</code>	std::forward_as_tuple ⁵⁵⁷
<code>hpx::tuple_cat</code>	std::tuple_cat ⁵⁵⁸
<code>hpx::get</code>	std::get ⁵⁵⁹

`hpx/type_traits.hpp`

The header `hpx/type_traits.hpp`⁵⁶⁰ corresponds to the C++ standard library header `type_traits`⁵⁶¹.

Classes

Table 2.174: Classes of header `hpx/type_traits.hpp`

Class	C++ standard
<code>hpx::is_invocable</code>	std::is_invocable ⁵⁶²
<code>hpx::is_invocable_r</code>	std::is_invocable ⁵⁶³

`hpx/unwrap.hpp`

The header `hpx/unwrap.hpp`⁵⁶⁴ contains utilities for unwrapping futures.

Classes

Table 2.175: Classes of header `hpx/unwrap.hpp`

Class
<code>hpx::functional::unwrap</code>
<code>hpx::functional::unwrap_n</code>
<code>hpx::functional::unwrap_all</code>

⁵⁵⁵ http://en.cppreference.com/w/cpp/utility/tuple/tuple_element

⁵⁵⁶ <http://en.cppreference.com/w/cpp/utility/tuple/tie>

⁵⁵⁷ http://en.cppreference.com/w/cpp/utility/tuple/forward_as_tuple

⁵⁵⁸ http://en.cppreference.com/w/cpp/utility/tuple/tuple_cat

⁵⁵⁹ <http://en.cppreference.com/w/cpp/utility/tuple/get>

⁵⁶⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/type_traits.hpp

⁵⁶¹ http://en.cppreference.com/w/cpp/header/type_traits

⁵⁶² http://en.cppreference.com/w/cpp/types/is_invocable

⁵⁶³ http://en.cppreference.com/w/cpp/types/is_invocable

⁵⁶⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/unwrap.hpp

Functions

Table 2.176: Functions of header `hpx/unwrap.hpp`

Function
<code>hpx::unwrap</code>
<code>hpx::unwrap_n</code>
<code>hpx::unwrap_all</code>
<code>hpx::unwrapping</code>
<code>hpx::unwrapping_n</code>
<code>hpx::unwrapping_all</code>

`hpx/version.hpp`

The header `hpx/version.hpp`⁵⁶⁵ provides version information about *HPX*.

Macros

Table 2.177: Macros of header `hpx/version.hpp`

Macro
<code>HPX_VERSION_MAJOR</code>
<code>HPX_VERSION_MINOR</code>
<code>HPX_VERSION_SUBMINOR</code>
<code>HPX_VERSION_FULL</code>
<code>HPX_VERSION_DATE</code>
<code>HPX_VERSION_TAG</code>
<code>HPX_AGAS_VERSION</code>

Functions

Table 2.178: Functions of header `hpx/version.hpp`

Function
<code>hpx::major_version</code>
<code>hpx::minor_version</code>
<code>hpx::subminor_version</code>
<code>hpx::full_version</code>
<code>hpx::full_version_as_string</code>
<code>hpx::tag</code>
<code>hpx::agas_version</code>
<code>hpx::build_type</code>
<code>hpx::build_date_time</code>

⁵⁶⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/version/include/hpx/version.hpp>

`hpx/wrap_main.hpp`

The header `hpx/wrap_main.hpp`⁵⁶⁶ does not provide any direct functionality but is used for implicitly using `main` as the runtime entry point. See *Re-use the `main()` function as the main HPX entry point* for more details on implicitly starting the HPX runtime.

2.9.2 Public distributed API

Our Public Distributed API offers a rich set of tools and functions that enable developers to harness the full potential of distributed computing. Here, you'll find a comprehensive list of header files, classes and functions for various distributed computing features provided by HPX.

`hpx/barrier.hpp`

The header `hpx/barrier.hpp`⁵⁶⁷ includes a distributed barrier implementation. For information regarding the C++ standard library header `barrier`⁵⁶⁸, see *Public API*.

Classes

Table 2.179: Distributed implementation of classes of header `hpx/barrier.hpp`

Class
<code>hpx::distributed::barrier</code>

Functions

Table 2.180: *hpx* functions of header `hpx/barrier.hpp`

Function
<code>hpx::distributed::wait</code>
<code>hpx::distributed::synchronize</code>

`hpx/collectives.hpp`

The header `hpx/collectives.hpp`⁵⁶⁹ contains definitions and implementations related to the collectives operations.

⁵⁶⁶ http://github.com/TheHPXProject/hpx/blob/unknown/wrap/include/hpx/wrap_main.hpp

⁵⁶⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/barrier.hpp>

⁵⁶⁸ <http://en.cppreference.com/w/cpp/header/barrier>

⁵⁶⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/collectives.hpp>

Classes

Table 2.181: *hpx* classes of header `hpx/collectives.hpp`

Class
<code>hpx::collectives::num_sites_arg</code>
<code>hpx::collectives::this_site_arg</code>
<code>hpx::collectives::that_site_arg</code>
<code>hpx::collectives::generation_arg</code>
<code>hpx::collectives::root_site_arg</code>
<code>hpx::collectives::tag_arg</code>
<code>hpx::collectives::arity_arg</code>
<code>hpx::collectives::communicator</code>
<code>hpx::collectives::channel_communicator</code>

Functions

Table 2.182: *hpx* functions of header `hpx/collectives.hpp`

Function
<code>hpx::collectives::all_gather</code>
<code>hpx::collectives::all_reduce</code>
<code>hpx::collectives::all_to_all</code>
<code>hpx::collectives::broadcast_to</code>
<code>hpx::collectives::broadcast_from</code>
<code>hpx::collectives::create_channel_communicator</code>
<code>hpx::collectives::set</code>
<code>hpx::collectives::get</code>
<code>hpx::collectives::create_communicator</code>
<code>hpx::collectives::create_hierarchical_communicator</code>
<code>hpx::collectives::create_local_communicator</code>
<code>hpx::collectives::communicator::set_info</code>
<code>hpx::collectives::communicator::get_info</code>
<code>hpx::collectives::communicator::is_root</code>
<code>hpx::collectives::exclusive_scan</code>
<code>hpx::collectives::gather_here</code>
<code>hpx::collectives::gather_there</code>
<code>hpx::collectives::inclusive_scan</code>
<code>hpx::collectives::reduce_here</code>
<code>hpx::collectives::reduce_there</code>
<code>hpx::collectives::scatter_from</code>
<code>hpx::collectives::scatter_to</code>

hpx/latch.hpp

The header `hpx/latch.hpp`⁵⁷⁰ includes a distributed latch implementation. For information regarding the C++ standard library header `latch`⁵⁷¹, see *Public API*.

Classes

Table 2.183: Distributed implementation of classes of header `hpx/latch.hpp`

Class
<code>hpx::distributed::latch</code>

Member functions

Table 2.184: *hpx* functions of class `hpx::distributed::latch` from header `hpx/latch.hpp`

Function
<code>hpx::distributed::latch::count_down_and_wait</code>
<code>hpx::distributed::latch::arrive_and_wait</code>
<code>hpx::distributed::latch::count_down</code>
<code>hpx::distributed::latch::is_ready</code>
<code>hpx::distributed::latch::try_wait</code>
<code>hpx::distributed::latch::wait</code>

hpx/async.hpp

The header `hpx/async.hpp`⁵⁷² includes distributed implementations of `hpx::async`, `hpx::post`, `hpx::sync`, and `hpx::dataflow`. For information regarding the C++ standard library header, see *Public API*.

Functions

Table 2.185: Distributed implementation of functions of header `hpx/async.hpp`

Functions
<code>hpx::async (distributed)</code>
<code>hpx::sync (distributed)</code>
<code>hpx::post (distributed)</code>
<code>hpx::dataflow (distributed)</code>

⁵⁷⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/latch.hpp>

⁵⁷¹ <http://en.cppreference.com/w/cpp/header/latch>

⁵⁷² http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/async_distributed/include/hpx/async.hpp

hpx/components.hpp

The header `hpx/include/components.hpp`⁵⁷³ includes the components implementation. A component in *hpx* is a C++ class which can be created remotely and for which its member functions can be invoked remotely as well. More information about how components can be defined, created, and used can be found in *Writing components*. *Components and actions* includes examples on the accumulator, template accumulator and template function accumulator.

Macros

Table 2.186: *hpx* macros of header `hpx/components.hpp`

Macro
<code>HPX_DEFINE_COMPONENT_ACTION</code>
<code>HPX_REGISTER_ACTION_DECLARATION</code>
<code>HPX_REGISTER_ACTION</code>
<code>HPX_REGISTER_COMMANDLINE_MODULE</code>
<code>HPX_REGISTER_COMPONENT</code>
<code>HPX_REGISTER_COMPONENT_MODULE</code>
<code>HPX_REGISTER_STARTUP_MODULE</code>

Classes

Table 2.187: *hpx* classes of header `hpx/components.hpp`

Class
<code>hpx::components::client</code>
<code>hpx::components::client_base</code>
<code>hpx::components::component</code>
<code>hpx::components::component_base</code>
<code>hpx::components::component_commandline_base</code>

Functions

Table 2.188: *hpx* functions of header `hpx/components.hpp`

Function
<code>hpx::new_</code>

2.9.3 Full API

The full API of *HPX* is presented below. The listings for the public API above refer to the full documentation below.

Note: Most names listed in the full API reference are implementation details or considered unstable. They are listed mostly for completeness. If there is a particular feature you think deserves being in the public API we may consider promoting it. In general we prioritize making sure features corresponding to C++ standard library features are stable and complete.

⁵⁷³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/include/components.hpp>

algorithms

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::experimental::task_canceled_exception, **hpx::experimental::task_block,**
hpx::experimental::define_task_block, **hpx::experimental::define_task_block_restore_thread**

Defined in header `hpx/task_block.hpp`⁵⁷⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename ExPolicy, typename F>  
decltype(auto) define_task_block(ExPolicy &&policy, F &&f)
```

Constructs a `task_block`, *tr*, using the given execution policy *policy*, and invokes the expression *f(tr)* on the user-provided object, *f*.

Postcondition: All tasks spawned from *f* have finished execution. A call to `define_task_block` may return on a different thread than that on which it was called.

Note: It is expected (but not mandated) that *f* will (directly or indirectly) call *tr.run(callable_object)*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the task block may be parallelized.
- **F** – The type of the user defined function to invoke inside the `define_task_block` (deduced). *F* shall be `MoveConstructible`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **f** – The user defined function to invoke inside the task block. Given an lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

```
template<typename F>  
void define_task_block(F &&f)
```

Constructs a `task_block`, *tr*, and invokes the expression *f(tr)* on the user-provided object, *f*. This version uses *parallel_policy* for task scheduling.

Postcondition: All tasks spawned from *f* have finished execution. A call to `define_task_block` may return on a different thread than that on which it was called.

⁵⁷⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/task_block.hpp

Note: It is expected (but not mandated) that *f* will (directly or indirectly) call *tr.run(callable_object)*.

Template Parameters

F – The type of the user defined function to invoke inside the `define_task_block` (deduced).
F shall be `MoveConstructible`.

Parameters

f – The user defined function to invoke inside the task block. Given a lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

```
template<typename ExPolicy, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> define_task_block_restore_thread(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               F
                                                                                               &&f)
```

Constructs a `task_block`, *tr*, and invokes the expression *f(tr)* on the user-provided object, *f*.

Postcondition: All tasks spawned from *f* have finished execution. A call to *define_task_block_restore_thread* always returns on the same thread as that on which it was called.

Note: It is expected (but not mandated) that *f* will (directly or indirectly) call *tr.run(callable_object)*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the task block may be parallelized.
- **F** – The type of the user defined function to invoke inside the `define_task_block` (deduced). *F* shall be `MoveConstructible`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **f** – The user defined function to invoke inside the `define_task_block`. Given an lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

```
template<typename F>
void define_task_block_restore_thread(F &&f)
```

Constructs a `task_block`, *tr*, and invokes the expression *f(tr)* on the user-provided object, *f*. This version uses *parallel_policy* for task scheduling.

Postcondition: All tasks spawned from *f* have finished execution. A call to *define_task_block_restore_thread* always returns on the same thread as that on which it was called.

Note: It is expected (but not mandated) that *f* will (directly or indirectly) call *tr.run(callable_object)*.

Template Parameters

F – The type of the user defined function to invoke inside the `define_task_block` (deduced).
F shall be `MoveConstructible`.

Parameters

f – The user defined function to invoke inside the `define_task_block`. Given an lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

```
template<typename ExPolicy = hpx::execution::parallel_policy>
```

```
class task_block
```

#include <task_block.hpp> The class *task_block* defines an interface for forking and joining parallel tasks. The *define_task_block* and *define_task_block_restore_thread* function templates create an object of type *task_block* and pass a reference to that object to a user-provided callable object.

An object of class *task_block* cannot be constructed, destroyed, copied, or moved except by the implementation of the task region library. Taking the address of a *task_block* object via `operator&` or `addressof` is ill formed. The result of obtaining its address by any other means is unspecified.

A *task_block* is active if it was created by the nearest enclosing task block, where “task block” refers to an invocation of *define_task_block* or *define_task_block_restore_thread* and “nearest

enclosing” means the most recent invocation that has not yet completed. Code designated for execution in another thread by means other than the facilities in this section (e.g., using `thread` or `async`) are not enclosed in the task region and a *task_block* passed to (or captured by) such code is not active within that code. Performing any operation on a *task_block* that is not active results in undefined behavior.

The *task_block* that is active before a specific call to the `run` member function is not active within the asynchronous function that invoked `run`. (The invoked function should not, therefore, capture the *task_block* from the surrounding block.)

Example:

```
define_task_block([&](auto& tr) {
    tr.run([&] {
        tr.run([] { f(); });           // Error: tr is not active
        define_task_block([&](auto& tr) { // Nested task block
            tr.run(f);                 // OK: inner tr is active
            /// ...
        });
    }); /// ...
});
```

Template Parameters

ExPolicy – The execution policy an instance of a *task_block* was created with. This defaults to *parallel_policy*.

Public Types

using **execution_policy** = *ExPolicy*

Refers to the type of the execution policy used to create the *task_block*.

Public Functions

```
inline constexpr execution_policy const &get_execution_policy() const noexcept
```

Return the execution policy instance used to create this *task_block*

```
template<typename F, typename ...Ts>
```

```
inline void run(F &&f, Ts&&... ts)
```

Causes the expression *f()* to be invoked asynchronously. The invocation of *f* is permitted to run on an unspecified thread in an unordered fashion relative to the sequence of operations following the call to *run(f)* (the continuation), or indeterminately sequenced within the same thread as the continuation.

The call to *run* synchronizes with the invocation of *f*. The completion of *f()* synchronizes with the next invocation of wait on the same *task_block* or completion of the nearest enclosing task block (i.e., the *define_task_block* or *define_task_block_restore_thread* that created this task block).

Requires: *F* shall be MoveConstructible. The expression, *(void)f()*, shall be well-formed.

Precondition: this shall be the active *task_block*.

Postconditions: A call to *run* may return on a different thread than that on which it was called.

Note: The call to *run* is sequenced before the continuation as if *run* returns on the same thread. The invocation of the user-supplied callable object *f* may be immediate or may be delayed until compute resources are available. *run* might or might not return before invocation of *f* completes.

Throws

task_canceled_exception – described in Exception Handling.

```
template<typename Executor, typename F, typename ...Ts>
```

```
inline void run(Executor &&exec, F &&f, Ts&&... ts)
```

Causes the expression *f()* to be invoked asynchronously using the given executor. The invocation of *f* is permitted to run on an unspecified thread associated with the given executor and in an unordered fashion relative to the sequence of operations following the call to *run(exec, f)* (the continuation), or indeterminately sequenced within the same thread as the continuation.

The call to *run* synchronizes with the invocation of *f*. The completion of *f()* synchronizes with the next invocation of wait on the same *task_block* or completion of the nearest enclosing task block (i.e., the *define_task_block* or *define_task_block_restore_thread* that created this task block).

Requires: *Executor* shall be a type modeling the *Executor* concept. *F* shall be MoveConstructible. The expression, *(void)f()*, shall be well-formed.

Precondition: this shall be the active *task_block*.

Postconditions: A call to *run* may return on a different thread than that on which it was called.

Note: The call to *run* is sequenced before the continuation as if *run* returns on the same thread. The invocation of the user-supplied callable object *f* may be immediate or may be delayed until compute resources are available. *run* might or might not return before invocation of *f* completes.

Throws

task_canceled_exception – described in Exception Handling. The function will also throw an *exception_list* holding all exceptions that were caught while executing the tasks.

inline void **wait**()

Blocks until the tasks spawned using this *task_block* have finished.

Precondition: this shall be the active *task_block*.

Postcondition: All tasks spawned by the nearest enclosing task region have finished. A call to wait may return on a different thread than that on which it was called.

Example:

```
define_task_block([&](auto& tr) {  
    tr.run([&]{ process(a, w, x); }); // Process a[w] through a[x]  
    if (y < x) tr.wait(); // Wait if overlap between [w, x) and [y,   
↪z)  
    process(a, y, z); // Process a[y] through a[z]  
});
```

Note: The call to *wait* is sequenced before the continuation as if *wait* returns on the same thread.

Throws

This – function may throw *task_canceled_exception*, as described in Exception Handling. The function will also throw a *exception_list* holding all exceptions that were caught while executing the tasks.

inline *ExPolicy* &**policy**() noexcept

Returns a reference to the execution policy used to construct this object.

Precondition: this shall be the active *task_block*.

inline constexpr *ExPolicy* const &**policy**() const noexcept

Returns a reference to the execution policy used to construct this object.

Precondition: this shall be the active *task_block*.

Private Members

hpx::experimental::task_group **tasks_**

threads::thread_id_type **id_**

ExPolicy **policy_**

class **task_canceled_exception** : public *exception*

#include <task_block.hpp> The class *task_canceled_exception* defines the type of objects thrown by *task_block::run* or *task_block::wait* if they detect that an exception is pending within the current parallel region.

Public Functions

```
inline task_canceled_exception() noexcept
```

```
namespace parallel
```

Typedefs

```
typedef hpx::experimental::task_canceled_exception instead
```

Functions

```
template<typename ExPolicy, typename F> HPX_DEPRECATED_V (1, 9,
"hpx::parallel:v2::define_task_block is deprecated,
use " "hpx::experimental::define_task_block instead") hpx
```

```
template<typename ExPolicy, typename F> HPX_DEPRECATED_V (1, 9,
"hpx::parallel:v2::define_task_block is deprecated,
use " "hpx::experimental::define_task_block instead") void define_task_block(ExPolicy &&policy
```

```
template<typename F> HPX_DEPRECATED_V (1, 9,
"hpx::parallel:v2::define_task_block is deprecated,
use " "hpx::experimental::define_task_block instead") void define_task_block(F &&f)
```

Variables

```
F && f {return hpx::experimental::define_task_block(policy, f)
```

hpx::experimental::run_on_all

Defined in header [hpx/task_block.hpp](http://github.com/HPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/task_block.hpp)⁵⁷⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace experimental
```

Top-level namespace.

⁵⁷⁵ http://github.com/HPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/task_block.hpp

Functions

```
template<typename ExPolicy, typename T, typename ...Ts>  
decltype(auto) run_on_all(ExPolicy &&policy, T &&t, Ts&&... ts)
```

Run a function on all available worker threads with reduction support using the given execution policy

Template Parameters

- **ExPolicy** – The execution policy type
- **T** – The first type in a list of reduction types and the function type to invoke (last argument)
- **Ts** – The list of reduction types and the function type to invoke (last argument)

Parameters

- **policy** – The execution policy to use
- **t** – The first in a list of reductions and the function to invoke (last argument)
- **ts** – The list of reductions and the function to invoke (last argument)

```
template<typename T, typename ...Ts>  
decltype(auto) run_on_all(T &&t, Ts&&... ts)
```

Run a function on all available worker threads with reduction support using the *hpx::execution::par* execution policy

Template Parameters

- **T** – The first type in a list of reduction types and the function type to invoke (last argument)
- **Ts** – The list of reduction types and the function type to invoke (last argument)

Parameters

- **t** – The first in a list of reductions and the function to invoke (last argument)
- **ts** – The list of reductions and the function to invoke (last argument)

hpx::experimental::task_group

Defined in header [hpx/experimental/task_group.hpp](#)⁵⁷⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Typedefs

```
    using instead = hpx::experimental::task_group
```

```
namespace experimental
```

Top-level namespace.

```
class task_group
```

#include <task_group.hpp> A *task_group* represents concurrent execution of a group of tasks. Tasks can be dynamically added to the group while it is executing.

⁵⁷⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/experimental/task_group.hpp

Public Functions

task_group()

~task_group()

task_group(*task_group* const&) = delete

task_group(*task_group*&&) = delete

task_group &**operator**=(*task_group* const&) = delete

task_group &**operator**=(*task_group*&&) = delete

template<typename **Executor**, typename **F**, typename ...**Ts**>

inline void **run**(*Executor* &&exec, *F* &&f, *Ts*&&... ts)

Adds a task to compute *f*() and returns immediately.

Template Parameters

- **Executor** – The type of the executor to associate with this execution policy.
- **F** – The type of the user defined function to invoke.
- **Ts** – The type of additional arguments used to invoke *f*() .

Parameters

- **exec** – The executor to use for the execution of the parallel algorithm the returned execution policy is used with.
- **f** – The user defined function to invoke inside the task group.
- **ts** – Additional arguments to use to invoke *f*() .

template<typename **F**, typename ...**Ts**>

inline void **run**(*F* &&f, *Ts*&&... ts)

Adds a task to compute *f*() and returns immediately.

Template Parameters

- **F** – The type of the user defined function to invoke.
- **Ts** – The type of additional arguments used to invoke *f*() .

Parameters

- **f** – The user defined function to invoke inside the task group.
- **ts** – Additional arguments to use to invoke *f*() .

void **wait**()

Waits for all tasks in the group to complete or be cancelled.

void **add_exception**(*std::exception_ptr* p)

Adds an exception to this *task_group*.

Private Types

using **shared_state_type** = *lcos::detail::future_data*<void>

Private Functions

void **serialize**(*serialization::output_archive&*, unsigned const)

Private Members

hpx::lcos::local::latch **latch_**

hpx::intrusive_ptr<shared_state_type> **state_**

hpx::exception_list **errors_**

std::atomic<bool> **has_arrived_**

Private Static Functions

static inline constexpr void **serialize**(*serialization::input_archive&*, unsigned const) noexcept

Friends

friend class *serialization::access*

hpx::ranges::nth_element

Defined in header [hpx/algorithm.hpp](#)⁵⁷⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

Functions

template<typename **RandomIt**, typename **Sent**, typename **Pred** = *hpx::parallel::detail::less*, typename **Proj** = *hpx::identity*>

RandomIt **nth_element**(*RandomIt* first, *RandomIt* nth, *Sent* last, *Pred* &&pred = *Pred*(), *Proj* &&proj = *Proj*())

nth_element is a partial sorting algorithm that rearranges elements in [first, last) such that the element pointed at by *nth* is changed to whatever element would occur in that position if [first, last) were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

⁵⁷⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *nth_element* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **RandomIt** – The type of the source begin, nth, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The *nth_element* algorithm returns *RandomIt*. The *nth_element* algorithm returns an iterator equal to last.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Pred =
hpx::parallel::detail::less, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, RandomIt> nth_element(ExPolicy &&policy,
RandomIt first, RandomIt
nth, Sent last, Pred
&&pred = Pred(), Proj
&&proj = Proj())
```

nth_element is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by *nth* is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *nth_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified

threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source begin, *nth*, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *RandomIt*.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to *Type*. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The *partition* algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type *parallel_task_policy* and returns *RandomIt* otherwise. The *nth_element* algorithm returns an iterator equal to *last*.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> nth_element(Rng &&rng, std::ranges::iterator_t<Rng> nth, Pred &&pred
                                         = Pred(), Proj &&proj = Proj())
```

nth_element is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by *nth* is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate,

and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type `randomIt` can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The `nth_element` algorithm returns `std::ranges::iterator_t<Rng>`. The `nth_element` algorithm returns an iterator equal to `last`.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> nth_element(ExPolicy
&&pol-
icy, Rng
&&rng,
std::ranges::iterator_t<Rng>
nth,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

`nth_element` is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by `nth` is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new `nth` element are less than or equal to the elements after the new `nth` element.

The comparison operations in the parallel `nth_element` invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The assignments in the parallel `nth_element` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified

threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type `randomIt` can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The *partition* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type `parallel_task_policy` and returns `std::ranges::iterator_t<Rng>` otherwise. The *nth_element* algorithm returns an iterator equal to last.

`hpx::ranges::experimental::for_loop`, `hpx::ranges::experimental::for_loop_strided`,
`hpx::ranges::experimental::for_loop_n`, `hpx::ranges::experimental::for_loop_n_strided`

Defined in header `hpx/algorithm.hpp`⁵⁷⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

namespace **experimental**

⁵⁷⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename Iter, typename Sent, typename ...Args>
hpx::parallel::util::detail::algorithm_result<ExPolicy>::type for_loop(ExPolicy &&policy, Iter
                                                                    first, Sent last, Args&&...
                                                                    args)
```

The `for_loop` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Iter* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the iteration variable (forward iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *Iter*.
- **Args** – A parameter pack, its last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Iter, typename Sent, typename ...Args>  
void for_loop(Iter first, Sent last, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *Iter* shall meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of MoveConstructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is last - first.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **Iter** – The type of the iteration variable (input iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for Iter.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename R, typename ...Args>
hpx::parallel::util::detail::algorithm_result<ExPolicy>::type for_loop(ExPolicy &&policy, R
&&rng, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Rng::iterator* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of MoveConstructible.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding f , an additional argument is passed to each application of f as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of f in the input sequence.

Complexity: Applies f exactly once for each element of the input sequence.

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **R** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Rng, typename ...Args>  
void for_loop(Rng &&rng, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: `Rng::iterator` shall meet the requirements of an input iterator type. The `args` parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of `MoveConstructible`.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the `args` parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **rng** – Refers to theof the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename Iter, typename Sent, typename S, typename ...Args>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> for_loop_strided(ExPolicy &&policy,
                                                                    Iter first, Sent last, S
                                                                    stride, Args&&...
                                                                    args)
```

The `for_loop_strided` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Iter* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or

induction function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of MoveConstructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is last - first.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the iteration variable (forward iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for Iter.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if Iter meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```


The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop_strided` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Iter, typename Sent, typename S, typename ...Args>
void for_loop_strided(Iter first, Sent last, S stride, Args&&... args)
```

The `for_loop_strided` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop_strided` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *Iter* shall meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Iter** – The type of the iteration variable (input iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *Iter*.
- **S** – The type of the stride variable. This should be an integral type.

- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *Iter* meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by *[first, last)* should expose a signature equivalent to:

`<ignored> pred(Iter const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename Rng, typename S, typename ...Args>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> for_loop_strided(ExPolicy &&policy,
                                                                           Rng &&rng, S stride,
                                                                           Args&&... args)
```

The `for_loop_strided` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Rng::iterator* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed

using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if `Rng::iterator` meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)` should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop_strided` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Rng, typename S, typename ...Args>
void for_loop_strided(Rng &&rng, S stride, Args&&... args)
```

The `for_loop_strided` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop_strided` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: `Rng::iterator` shall meet the requirements of an input iterator type. The `args` parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of `MoveConstructible`.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the `args` parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **rng** – Refers to theof the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if `Rng::iterator` meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)` should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

hpx::ranges::move

Defined in header `hpx/algorithm.hpp`⁵⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
namespace ranges
```

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2>
hpx::parallel::util::detail::algorithm_result<ExPolicy, move_result<Iter1, Iter2>>::type move(ExPolicy
                                                    &&policy,
                                                    Iter1 first,
                                                    Sent1 last,
                                                    Iter2 dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `hpx::future<ranges::move_result<iterator_t<Rng>,`

⁵⁷⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

FwdIter2>> if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::move_result<iterator_t<Rng>, FwdIter2>* otherwise. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename Rng, typename Iter2>
hpx::parallel::util::detail::algorithm_result<ExPolicy, move_result<std::ranges::iterator_t<Rng>, Iter2>>>::type move(ExPol
&&pc
icy,
Rng
&&rn
Iter2
dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a *hpx::future<ranges::move_result<iterator_t<Rng>, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::move_result<iterator_t<Rng>, FwdIter2>* otherwise. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Iter1, typename Sent1, typename Iter2>
move_result<Iter1, Iter2> move(Iter1 first, Sent1 last, Iter2 dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns `ranges::move_result<iterator_t<Rng>, FwdIter2>`. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Rng, typename Iter2>
move_result<std::ranges::iterator_t<Rng>, Iter2> move(Rng &&rng, Iter2 dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `ranges::move_result<iterator_t<Rng>, FwdIter2>`. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

hpx::ranges::starts_with

Defined in header `hpx/algorithm.hpp`⁵⁸⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

⁵⁸⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =  
ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
bool starts_with(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&pred = Pred(), Proj1  
                &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2)

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Iter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename  
Sent2, typename Pred = ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 =  
hpx::identity>
```



```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> starts_with(ExPolicy &&policy,
                                                                    FwdIter1 first1, Sent1
                                                                    last1, FwdIter2 first2,
                                                                    Sent2 last2, Pred &&pred
                                                                    = Pred(), Proj1 &&proj1 =
                                                                    Proj1(), Proj2 &&proj2 =
                                                                    Proj2())

```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2)

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
bool starts_with(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1 &&proj1 = Proj1(),
                Proj2 &&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the prefix of the first range *rng1*.

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = ranges::equal_to,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type starts_with(ExPolicy &&policy,
Rng1 &&rng1, Rng2
&&rng2, Pred
&&pred = Pred(),
Proj1 &&proj1 =
Proj1(), Proj2
&&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the prefix of the first range *rng1*.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

hpx::ranges::remove_copy, hpx::ranges::remove_copy_if

Defined in header `hpx/algorithm.hpp`⁵⁸¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁵⁸¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

namespace **ranges**

hpx/parallel/container_algorithms/iota.hpp

Defined in header `hpx/parallel/container_algorithms/iota.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename T>  
iota_result<FwdIter, T> iota(FwdIter first, Sent last, T value)
```

Fills the range [first, last) with sequentially increasing values, starting with *value* and repetitively evaluating ++*value*.

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input or output iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for **FwdIter**.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::ranges::iota_result* containing the final iterator and the final value.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, iota_result<FwdIter, T>> iota(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter first,  
                                                                                      Sent last, T  
                                                                                      value)
```

Fills the range [first, last) with sequentially increasing values, starting with *value* and repetitively evaluating ++*value*.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::future<iota_result>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *iota_result* otherwise.

```
template<typename Range, typename T>
iota_result<typename hpx::traits::range_traits<Range>::iterator_type, T> iota(Range &&r, T value)
    Fills the range r with sequentially increasing values, starting with value and repetitively evaluating ++value.
```

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly *std::ranges::distance(r)* assignments and increments.

Template Parameters

- **Range** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input or output iterator
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **r** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::ranges::iota_result* containing the final iterator and the final value.

```
template<typename ExPolicy, typename Range, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, iota_result<typename hpx::traits::range_traits<Range>::iterator_type
```

Fills the range *r* with sequentially increasing values, starting with *value* and repetitively evaluating `++value`.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly `std::ranges::distance(r)` assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Range** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **r** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a `hpx::future<iota_result>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *iota_result* otherwise.

hpx::ranges::shift_right

Defined in header `hpx/algorithm.hpp`⁵⁸².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

⁵⁸² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

template<typename **FwdIter**, typename **Sent**, typename **Size**>
FwdIter **shift_right**(*FwdIter* first, *Sent* last, *Size* n)

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns *FwdIter*. The *shift_right* algorithm returns an iterator to the end of the resulting range.

template<typename **ExPolicy**, typename **FwdIter**, typename **Sent**, typename **Size**>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> **shift_right**(*ExPolicy* &&policy,
FwdIter first, *Sent* last,
Size n)

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_right* algorithm returns an iterator to the end of the resulting range.

```
template<typename Rng, typename Size>  
std::ranges::iterator_t<Rng> shift_right(Rng &&rng, Size n)
```

Shifts the elements in the range $[first, last)$ by n positions towards the end of the range. For every integer i in $[0, last - first - n)$, moves the element originally at position $first + i$ to position $first$

- $n + i$.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most $(last - first) - n$ assignments.

Note: The type of dereferenced *std::ranges::iterator_t<Rng>* must meet the requirements of *MoveAssignable*.

Template Parameters

- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns *std::ranges::iterator_t<Rng>*. The *shift_right* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename Rng, typename Size>
```

```
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>>> shift_right (ExPolicy
                                                    &&pol-
                                                    icy, Rng
                                                    &&rng,
                                                    Size n)
```

Shifts the elements in the range `[first, last)` by `n` positions towards the end of the range. For every integer `i` in `[0, last - first - n)`, moves the element originally at position `first + i` to position `first`

- `n + i`.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) - n$ assignments.

Note: The type of dereferenced *std::ranges::iterator_t<Rng>* must meet the requirements of *Move-Assignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a *hpx::future<std::ranges::iterator_t<Rng>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *std::ranges::iterator_t<Rng>* otherwise. The *shift_right* algorithm returns an iterator to the end of the resulting range.

hpx::ranges::is_partitioned

Defined in header `hpx/algorithm.hpp`⁵⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

⁵⁸³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename Sent, typename Pred, typename Proj = hpx::identity>
bool is_partitioned(FwdIter first, Sent last, Pred &&pred, Proj &&proj = Proj())
```

Determines if the range [first, last) is partitioned.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range [first, last) contains less than two elements, the function is always true.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_partitioned(ExPolicy &&policy,
                                                                    FwdIter first, Sent last,
                                                                    Pred &&pred, Proj
                                                                    &&proj = Proj())
```

Determines if the range [first, last) is partitioned.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *Copy-Constructible* when using a parallel policy.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range $[\text{first}, \text{last})$ contains less than two elements, the function is always true.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
bool is_partitioned(Rng &&rng, Pred &&pred, Proj &&proj = Proj())
```

Determines if the range *rng* is partitioned.

Note: Complexity: at most (N) predicate evaluations where $N = \text{std::size}(\text{rng})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *rng* contains less than two elements, the function is always true.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_partitioned(ExPolicy &&policy,
                                                                              Rng &&rng, Pred
                                                                              &&pred, Proj &&proj
                                                                              = Proj())
```

Determines if the range [first, last) is partitioned.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (*N*) predicate evaluations where *N* = `std::size(rng)`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *Copy-Constructible* when using a parallel policy.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *rng* contains less than two elements, the function is always true.

hpx::ranges::unique, hpx::ranges::unique_copy

Defined in header [hpx/algorithm.hpp](#)⁵⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename Pred = ranges::equal_to, typename Proj =
hpx::identity>
subrange_t<FwdIter, Sent> unique(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj =
Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

⁵⁸⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t<FwdIter, Sent>*. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred = ranges::equal_to,
typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type unique(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter
                                                                                               first, Sent
                                                                                               last, Pred
                                                                                               &&pred =
                                                                                               Pred(),
                                                                                               Proj
                                                                                               &&proj =
                                                                                               Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t<FwdIter, Sent>*. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename Rng, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>> unique(Rng &&rng, Pred
&&pred = Pred(), Proj
&&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range *rng* and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than N assignments, exactly N - 1 applications of the predicate *pred* and no more than twice as many applications of the projection *proj*, where N = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>*. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename ExPolicy, typename Rng, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>> u
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range *rng* and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *N* assignments, exactly *N* - 1 applications of the predicate *pred* and no more than twice as many applications of the projection *proj*, where *N* = *std::distance(begin(rng), end(rng))*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to *std::equal_to<>*
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns a *hpx::future* <subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>> if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>* otherwise. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename InIter, typename Sent, typename O, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
unique_copy_result<InIter, O> unique_copy(InIter first, Sent last, O dest, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Copies the elements from the range [first, last), to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **O** – The type of the iterator representing the destination range (deduced).
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to std::equal_to<>
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent

to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns a `unique_copy_result<InIter, O>`. The *unique_copy* algorithm returns an `in_out_result` with the source iterator to one past the last element and out containing the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename O, typename Pred =
    ranges::equal_to, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, unique_copy_result<FwdIter, O>>::type unique_copy(ExPolicy
    &&pol-
    icy,
    FwdIter
    first,
    Sent
    last,
    O
    dest,
    Pred
    &&pred
    =
    Pred(),
    Proj
    &&proj
    =
    Proj())
```

Copies the elements from the range `[first, last)`, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter1`.
- **O** – The type of the iterator representing the destination range (deduced).
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns a `hpx::future< unique_copy_result<FwdIter, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *unique_copy_result<FwdIter, O>* otherwise. The *unique_copy* algorithm returns an *in_out_result* with the source iterator to one past the last element and out containing the destination iterator to the end of the *dest* range.

```
template<typename Rng, typename O, typename Pred = ranges::equal_to, typename Proj =
hpx::identity>
unique_copy_result<std::ranges::iterator_t<Rng>, O> unique_copy(Rng &&rng, O dest, Pred &&pred
= Pred(), Proj &&proj = Proj())
```

Copies the elements from the range *rng*, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *N* assignments, exactly *N* - 1 applications of the predicate *pred*, where *N* = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential

form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns *unique_copy_result*< `std::ranges::iterator_t<Rng>`, `O`>. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename Rng, typename O, typename Pred = ranges::equal_to,  
typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, unique_copy_result<std::ranges::iterator_t<Rng>, O>> unique_copy (Ex
```

Copies the elements from the range *rng*, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *N* assignments, exactly *N* - 1 applications of the predicate *pred*, where *N* = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns a `hpx::future<unique_copy_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *unique_copy_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

hpx::ranges::adjacent_find

Defined in header `hpx/algorithm.hpp`⁵⁸⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

⁵⁸⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename Sent, typename Proj = hpx::identity, typename Pred =
detail::equal_to>
```

```
FwdIter adjacent_find(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Proj = hpx::identity,
typename Pred = detail::equal_to>
```

```
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type adjacent_find(ExPolicy &&policy,
                                                                    FwdIter first, Sent
                                                                    last, Pred &&pred =
                                                                    Pred(), Proj &&proj
                                                                    = Proj())
```

Searches the range [first, last) for two consecutive identical elements. This version uses the given binary predicate *pred*

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *adjacent_find* is available if the user decides to provide their algorithm their own binary predicate *pred*.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::equal_to<>*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns a *hpx::future<InIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *InIter* otherwise. The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename Proj = hpx::identity, typename Pred = detail::equal_to>
hpx::traits::range_traits<Rng>::iterator_type adjacent_find(Rng &&rng, Pred &&pred = Pred(), Proj
&&proj = Proj())
```

Searches the range *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - std::begin(rng)) + 1 and (std::begin(rng) - std::end(rng)) - 1 applications of the predicate where *result* is the value returned

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`
- **Pred** – The type of an optional function/function object to use.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – The binary predicate which returns `true` if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types `Type1` must be such that objects of type `FwdIter` can be dereferenced and then implicitly converted to `Type1`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `adjacent_find` algorithm returns an iterator to the first of the identical elements. If no such elements are found, `last` is returned.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename Pred =  
detail::equal_to>
```

```
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type adjacent_
```

Searches the range `rng` for two consecutive identical elements.

The comparison operations in the parallel `adjacent_find` invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The comparison operations in the parallel `adjacent_find` invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of `adjacent_find` is available if the user decides to provide their algorithm their own binary predicate `pred`.

Note: Complexity: Exactly the smaller of $(\text{result} - \text{std::begin}(\text{rng})) + 1$ and $(\text{std::begin}(\text{rng}) - \text{std::end}(\text{rng})) - 1$ applications of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `adjacent_find` requires `Pred` to meet the requirements of `CopyConstructible`. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – The binary predicate which returns `true` if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types `Type1` must be such that objects of type `FwdIter` can be dereferenced and then implicitly converted to `Type1`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `adjacent_find` algorithm returns a `hpx::future<InIter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `InIter` otherwise. The `adjacent_find` algorithm returns an iterator to the first of the identical elements. If no such elements are found, `last` is returned.

hpx::ranges::remove, hpx::ranges::remove_if

Defined in header `hpx/algorithm.hpp`⁵⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename Iter, typename Sent, typename Pred, typename Proj = hpx::identity>
subrange_t<Iter, Sent> remove_if(Iter first, Sent sent, Pred &&pred, Proj &&proj = Proj())
```

Removes all elements for which predicate `pred` returns true from the range `[first, last)` and returns a subrange `[ret, last)`, where `ret` is a past-the-end iterator for the new end of the range.

The assignments in the parallel `remove_if` algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than `last - first` assignments, exactly `last - first` applications of the predicate `pred` and the projection `proj`.

Template Parameters

⁵⁸⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Iter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `remove_if` requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `remove_if` algorithm returns a `subrange_t<FwdIter, Sent>`. The `remove_if` algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> remove_if(Rng &&rng, Pred &&pred, Proj &&proj =
                                                    Proj())
```

Removes all elements that are equal to *value* from the range *rng* and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel `remove_if` algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than `util::end(rng)`

- `util::begin(rng)` assignments, exactly `util::end(rng) - util::begin(rng)` applications of the operator `==()` and the projection *proj*.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `remove_if` requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a *subrange_t<std::ranges::iterator_t<Rng>>*. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =
hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type remove_if(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
sent,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Removes all elements for which predicate *pred* returns true from the range [first, last) and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred* and the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a *hpx::future<subrange_t<FwdIter, Sent>>*. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> remove_if(ExPolicy
&&pol-
icy,
Rng
&&rng,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Removes all elements that are equal to *value* from the range *rng* and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator==() and the projection *proj*.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a *hpx::future<subrange_t<std::ranges::iterator_t<Rng>>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<Iter, Proj>::value_type>
```

```
subrange_t<Iter, Sent> remove(Iter first, Sent last, T const &value, Proj &&proj = Proj())
```

Removes all elements that are equal to *value* from the range [first, last) and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the operator *==()* and the projection *proj*.

Template Parameters

- **Iter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *subrange_t<FwdIter, Sent>*. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
subrange_t<std::ranges::iterator_t<Rng>> remove(Rng &&rng, T const &value, Proj &&proj = Proj())
```

Removes all elements that are equal to *value* from the range *rng* and and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator==() and the projection *proj*.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *subrange_t<std::ranges::iterator_t<**Rng**>>*. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Proj = hpx::identity,
typename T = typename hpx::parallel::traits::projected<FwdIter, Proj>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type remove(ExPolicy
&&policy,
FwdIter
first, Sent
last, T
const
&value,
Proj
&&proj =
Proj())
```

Removes all elements that are equal to *value* from the range [first, last) and and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified

threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the operator `==()` and the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for **FwdIter**.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *hpx::future<subrange_t<FwdIter, Sent>>*. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> remove(ExPolicy
&&pol-
icy,
Rng
&&rng,
T
const
&value,
Proj
&&proj
=
Proj())
```

Removes all elements that are equal to *value* from the range *rng* and and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator *==()* and the projection *proj*.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *hpx::future< subrange_t<std::ranges::iterator_t<Rng>>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove* algorithm returns the iterator to the new end of the range.

hpx::ranges::make_heap

Defined in header [hpx/algorithm.hpp](#)⁵⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> make_heap(ExPolicy &&policy, Iter first,  
Sent last, Comp &&comp,  
Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

⁵⁸⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Comp, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>>> make_heap(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               Rng
                                                                                               &&rng,
                                                                                               Comp
                                                                                               &&comp,
                                                                                               Proj
                                                                                               &&proj
                                                                                               =
                                                                                               Proj{ })
```

Constructs a *max heap* in the range `[first, last)`.

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy

object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> make_heap(ExPolicy &&policy, Iter first,
                                                                    Sent last, Proj &&proj =
                                                                    Proj{})
```

Constructs a *max heap* in the range `[first, last)`.

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for `Iter1`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `make_heap` algorithm returns a `hpx::future<Iter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `Iter` otherwise. It returns `last`.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> make_heap(ExPolicy
                                                    &&pol-
                                                    icy,
                                                    Rng
                                                    &&rng,
                                                    Proj
                                                    &&proj
                                                    =
                                                    Proj{ })
```

Constructs a *max heap* in the range `[first, last)`.

The predicate operations in the parallel `make_heap` algorithm invoked with an execution policy object of type `sequential_execution_policy` executes in sequential order in the calling thread.

The comparison operations in the parallel `make_heap` algorithm invoked with an execution policy object of type `parallel_execution_policy` or `parallel_task_execution_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `make_heap` algorithm returns a `hpx::future<Iter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `Iter` otherwise. It returns `last`.

```
template<typename Iter, typename Sent, typename Comp, typename Proj = hpx::identity>
```

Iter **make_heap**(*Iter* first, *Sent* last, *Comp* &&comp, *Proj* &&proj = *Proj*{ })

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Comp, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> make_heap(Rng &&rng, Comp &&comp, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Iter, typename Sent, typename Proj = hpx::identity>
Iter make_heap(Iter first, Sent last, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter*1.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> make_heap(Rng &&rng, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

hpx::ranges::for_each, hpx::ranges::for_each_n

Defined in header [hpx/algorithm.hpp](#)⁵⁸⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace ranges
```

⁵⁸⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename InIter, typename Sent, typename F, typename Proj = hpx::identity>  
for_each_result<InIter, F> for_each(InIter first, Sent last, F &&f, Proj &&proj = Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, last).

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

{last, HPX_MOVE(f)} where last is the iterator corresponding to the input sentinel last.

```
template<typename Rng, typename F, typename Proj = hpx::identity>  
for_each_result<std::ranges::iterator_t<Rng>, F> for_each(Rng &&rng, F &&f, Proj &&proj =  
Proj())
```

Applies *f* to the result of dereferencing every iterator in the given range *rng*.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *size(rng)* times.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

```
{std::end(rng), HPX_MOVE(f)}
```

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> for_each(ExPolicy &&policy,  
FwdIter first, Sent last, F  
&&f, Proj &&proj =  
Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, last).

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.

- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `for_each` requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `for_each` algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns *FwdIter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>>> for_each(ExPolicy
                                                                                               &&pol-
                                                                                               icy, Rng
                                                                                               &&rng,
                                                                                               F &&f,
                                                                                               Proj
                                                                                               &&proj
                                                                                               =
                                                                                               Proj())
```

Applies *f* to the result of dereferencing every iterator in the given range *rng*.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of `for_each` does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies f exactly $size(rng)$ times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires F to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *for_each* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename InIter, typename Size, typename F, typename Proj = hpx::identity>
for_each_n_result<InIter, F> for_each_n(InIter first, Size count, F &&f, Proj &&proj = Proj())
```

Applies f to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

If f returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, f may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

Note: Complexity: Applies f exactly $count$ times.

Template Parameters

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply f to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires F to meet the requirements of *Copy-Constructible*.

- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

`<ignored> pred(const Type &a);`

The signature does not need to have `const&`. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

It returns *last*.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type for_each_n(ExPolicy &&policy,  
FwdIter first, Size  
count, F &&f, Proj  
&&proj = Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *count* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *for_each* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

hpx::ranges::transform

Defined in header `hpx/algorithm.hpp`⁵⁸⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename
F, typename Proj = hpx::identity>
```

⁵⁸⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

parallel::util::detail::algorithm_result<ExPolicy, ranges::unary_transform_result<FwdIter1, FwdIter2>>::type transform

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\text{size}(\text{rng})$ applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *FwdIter1*.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [*first*, *last*). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns a `hpx::future<ranges::unary_transform_result<FwdIter1, FwdIter2>>` if the execution policy is of type *parallel_task_policy* and returns `ranges::unary_transform_result<FwdIter1, FwdIter2>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename F, typename Proj =
hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, ranges::unary_transform_result<std::ranges::iterator_t<Rng>, FwdIter>> >
```

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly `size(rng)` applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

`Ret fun(const Type &a);`

The signature does not need to have `const&`. The type *Type* must be such that an object of type *range_iterator<Rng>::type* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *OutIter* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns a *hpx::future<ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>>* if the execution policy is of type *parallel_task_policy* and returns *ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>* otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename  
Sent2, typename FwdIter3, typename F, typename Proj1 = hpx::identity, typename Proj2 =  
hpx::identity>  
parallel::util::detail::algorithm_result<ExPolicy, ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>>::type t
```

Applies the given function f to pairs of elements from two ranges: one defined by rng and the other beginning at $first2$, and stores the result in another range, beginning at $dest$.

The invocations of f in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of f in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\text{size}(rng)$ applications of f

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of f .
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter2.
- **FwdIter3** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires F to meet the requirements of *Copy-Constructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types FwdIter1 and FwdIter2 can be dereferenced and then implicitly

converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns `A hpx::future<ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>>` if the execution policy is of type *parallel_task_policy* and returns `ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename FwdIter, typename F,
        typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter, F, Proj1, Proj2>>
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\min(\text{last2}-\text{first2}, \text{last1}-\text{first1})$ applications of *f*

Note: The algorithm will invoke the binary predicate until it reaches the end of the shorter of the two

given input sequences

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types `range_iterator<Rng1>::type` and `range_iterator<Rng2>::type` can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns a `hpx::future<ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter> >` if the execution policy is of type *parallel_task_policy* and returns `ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter2, typename F, typename Proj =
hpx::identity>
ranges::unary_transform_result<FwdIter1, FwdIter2> transform(FwdIter1 first, Sent1 last, FwdIter2
dest, F &&f, Proj &&proj = Proj())
```

Applies the given function f to the given range rng and stores the result in another range, beginning at $dest$.

Note: Complexity: Exactly $\text{size}(rng)$ applications of f

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires F to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate f is invoked.

Returns

The *transform* algorithm returns `ranges::unary_transform_result<FwdIter1, FwdIter2>`. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter, typename F, typename Proj = hpx::identity>
ranges::unary_transform_result<std::ranges::iterator_t<Rng>, FwdIter> transform(Rng &&rng,
                                                                              FwdIter dest, F
                                                                              &&f, Proj &&proj
                                                                              = Proj())
```

Applies the given function f to the given range rng and stores the result in another range, beginning at $dest$.

Note: Complexity: Exactly $\text{size}(rng)$ applications of f

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *range_iterator<Rng>::type* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *OutIter* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns *ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2, typename
FwdIter3, typename F, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3> transform(FwdIter1 first1, Sent1
last1, FwdIter2 first2, Sent2 last2, FwdIter3 dest,
F &&f, Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 =
Proj2())
```

Applies the given function *f* to pairs of elements from two ranges: one defined by *rng* and the other beginning at *first2*, and stores the result in another range, beginning at *dest*.

Note: Complexity: Exactly `size(rng)` applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *FwdIter1*.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *FwdIter2*.
- **FwdIter3** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns *ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename FwdIter, typename F, typename Proj1 =  
hpx::identity, typename Proj2 = hpx::identity>
```

```

ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter> transform(Rng1
&&r
Rng2
&&r
FwdI
dest,
F
&&f,
Proj1
&&p
=
Proj1
Proj2
&&p
=
Proj2

```

Applies the given function f to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest.

Note: Complexity: Exactly $\min(\text{last2}-\text{first2}, \text{last1}-\text{first1})$ applications of f

Note: The algorithm will invoke the binary predicate until it reaches the end of the shorter of the two given input sequences

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires F to meet the requirements of *Copy-Constructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types `range_iterator<Rng1>::type` and `range_iterator<Rng2>::type` can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret*

must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns *ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter>*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

hpx::ranges::uninitialized_move, hpx::ranges::uninitialized_move_n

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent1, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> uninitialized_move(InIter first1, Sent1 last1,
                                                                    FwdIter first2, Sent2 last2)
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

⁵⁹⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move* algorithm returns an *in_out_result*<*InIter*, *FwdIter*>. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>
```

```
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type uninitialized
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *in_out_result<InIter, FwdIter>* otherwise. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Rng1, typename Rng2>
hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **rng1** – Refers to the range from which the elements will be moved from
- **rng2** – Refers to the range to which the elements will be moved to

Returns

The *uninitialized_move* algorithm returns an *in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>*. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename Rng1, typename Rng2>
parallel::util::detail::algorithm_result<ExPolicy, hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>>
```


Moves the elements in the range, defined by `[first, last)`, to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in `[first, last)` are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the range from which the elements will be moved from
- **rng2** – Refers to the range to which the elements will be moved to

Returns

The *uninitialized_move* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result< typename hpx::traits::range_traits<Rng1>::iterator_type , typename hpx::traits::range_traits<Rng2>::iterator_type>` otherwise. The *uninitialized_move* algorithm returns the input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename InIter, typename Size, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> uninitialized_move_n(InIter first1, Size count,
                                                                    FwdIter first2, Sent2 last2)
```

Moves the elements in the range `[first, first + count)`, starting from *first* and proceeding to *first + count - 1*, to another range beginning at *dest*. If an exception is thrown during the initialization, some objects in `[first, first + count)` are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* movements, if *count* > 0, no move operations otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move_n* algorithm returns `in_out_result<InIter, FwdIter>`. The *uninitialized_move_n* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2, typename Sent2>
```

```
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>>::type uninitialized
```

Moves the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`, to another range beginning at `dest`. If an exception is thrown during the initialization, some objects in `[first, first + count)` are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* movements, if *count* > 0, no move operations otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move_n* algorithm returns a `hpx::future<in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_move_n* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

hpx::ranges::partial_sort

Defined in header `hpx/algorithm.hpp`⁵⁹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename RandomIt, typename Sent, typename Comp = ranges::less, typename Proj =
hpx::identity>
RandomIt partial_sort(RandomIt first, RandomIt middle, Sent last, Comp &&comp = Comp(), Proj
&&proj = Proj())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

The assignments in the parallel *partial_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

⁵⁹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator. Comp defaults to detail::less.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate comp is invoked.

Returns

The *partial_sort* algorithm returns *RandomIt*. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less,
        typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type partial_sort(ExPolicy &&policy,
                                                                    RandomIt first,
                                                                    RandomIt middle,
                                                                    Sent last, Comp
                                                                    &&comp = Comp(),
                                                                    Proj &&proj =
                                                                    Proj())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to detail::less.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. `Comp` defaults to `detail::less`.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `partial_sort` algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `RandomIt` otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> partial_sort(Rng &&rng, std::ranges::iterator_t<Rng> middle, Comp
&&comp = Comp(), Proj &&proj = Proj())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to `comp` into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

The assignments in the parallel `partial_sort` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Approximately $(last - first) * \log(middle - first)$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. `Comp` defaults to `detail::less`.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `partial_sort` algorithm returns `std::ranges::iterator_t<Rng>`. It returns `last`.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj =
hpx::identity>
```

```
parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> partial_sort(ExPolicy  
                                                    &&pol-  
                                                    icy,  
                                                    Rng  
                                                    &&rng,  
                                                    std::ranges::iterator_t<Rn  
                                                    mid-  
                                                    dle,  
                                                    Comp  
                                                    &&comp  
                                                    =  
                                                    Comp(),  
                                                    Proj  
                                                    &&proj  
                                                    =  
                                                    Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced). *Comp* defaults to `detail::less`;
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the `INVOKE` operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that

comp will not apply any non-constant function through the dereferenced iterator. Comp defaults to `detail::less`.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *partial_sort* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. It returns *last*.

**hpx::ranges::fold_left, hpx::ranges::fold_left_first, hpx::ranges::fold_right,
hpx::ranges::fold_right_last, hpx::ranges::fold_left_with_iter, hpx::ranges::fold_left_first_with_iter**

Defined in header `hpx/algorithm.hpp`⁵⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent, typename T, typename F>
auto fold_left(InIter first, Sent last, T init, F f)
```

Left-folds a range of elements using a binary operator.

Note: Complexity: Exactly N applications of the binary operator, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced). This iterator must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of left-folding the range.

```
template<typename Rng, typename T, typename F>
auto fold_left(Rng &&rng, T init, F f)
```

Left-folds a range of elements using a binary operator.

⁵⁹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Exactly N applications of the binary operator, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of left-folding the range.

```
template<typename InIter, typename Sent, typename F>  
auto fold_left_first(InIter first, Sent last, F f)
```

Left-folds a range using the first element as the initial value.

Note: Complexity: Exactly N-1 applications of the binary operator, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

```
template<typename Rng, typename F>  
auto fold_left_first(Rng &&rng, F f)
```

Left-folds a range using the first element as the initial value.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

```
template<typename BidIter, typename Sent, typename T, typename F>  
auto fold_right(BidIter first, Sent last, T init, F f)
```

Right-folds a range of elements using a binary operator.

Note: Complexity: Exactly N applications of the binary operator.

Template Parameters

- **BidIter** – The type of the source begin iterator (deduced). This iterator must meet the requirements of a bidirectional iterator.
- **Sent** – The type of the source sentinel (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of right-folding the range.

```
template<typename Rng, typename T, typename F>
auto fold_right(Rng &&rng, T init, F f)
```

Right-folds a range of elements using a binary operator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of right-folding the range.

```
template<typename BidIter, typename Sent, typename F>
auto fold_right_last(BidIter first, Sent last, F f)
```

Right-folds a range using the last element as the initial value.

Template Parameters

- **BidIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

```
template<typename Rng, typename F>
auto fold_right_last(Rng &&rng, F f)
```

Right-folds a range using the last element as the initial value.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

```
template<typename InIter, typename Sent, typename T, typename F>
```

```
auto fold_left_with_iter(InIter first, Sent last, T init, F f) -> fold_left_with_iter_result<InIter,  
    std::decay_t<hpx::util::invoke_result_t<F&, T,  
    hpx::traits::iter_reference_t<InIter>>>>>
```

Left-folds a range and returns both the result and the end iterator.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_with_iter_result` containing the end iterator and the fold result.

```
template<typename Rng, typename T, typename F>  
auto fold_left_with_iter(Rng &&rng, T init, F f) ->  
    fold_left_with_iter_result<std::ranges::iterator_t<Rng>,  
    std::decay_t<hpx::util::invoke_result_t<F&, T,  
    hpx::traits::range_reference_t<Rng>>>>>
```

Left-folds a range and returns both the result and the end iterator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_with_iter_result` containing the end iterator and the fold result.

```
template<typename InIter, typename Sent, typename F>  
auto fold_left_first_with_iter(InIter first, Sent last, F f) ->  
    fold_left_first_with_iter_result<InIter,  
    hpx::optional<std::decay_t<hpx::util::invoke_result_t<F&,  
    hpx::traits::iter_reference_t<InIter>,  
    hpx::traits::iter_reference_t<InIter>>>>>
```

Left-folds a range using the first element and returns both an optional result and the end iterator.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_first_with_iter_result` containing the end iterator and an optional with the fold result.

```
template<typename Rng, typename F>
```

```
auto fold_left_first_with_iter(Rng &&rng, F f) ->
    fold_left_first_with_iter_result<std::ranges::iterator_t<Rng>,
    hpx::optional<std::decay_t<hpx::util::invoke_result_t<F&,
    hpx::traits::range_reference_t<Rng>,
    hpx::traits::range_reference_t<Rng>>>>>
```

Left-folds a range using the first element and returns both an optional result and the end iterator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_first_with_iter_result` containing the end iterator and an optional with the fold result.

hpx::ranges::search, hpx::ranges::search_n

Defined in header `hpx/algorithm.hpp`⁵⁹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
namespace ranges
```

Functions

```
template<typename FwdIter, typename Sent, typename FwdIter2, typename Sent2, typename Pred =
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
FwdIter search(FwdIter first, Sent last, FwdIter2 s_first, Sent2 s_last, Pred &&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most ($S \cdot N$) comparisons where S = distance(s_first, s_last) and N = distance(first, last).

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used for the first range (deduced). This iterator type must meet the requirements of an sentinel.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

⁵⁹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence `[s_first, s_last)` in range `[first, last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename FwdIter2, typename
Sent2, typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type search(ExPolicy &&policy, FwdIter
first, Sent last, FwdIter2 s_first,
Sent2 s_last, Pred &&op =
Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 =
Proj2())
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used for the first range (deduced). This iterator type must meet the requirements of an sentinel.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [*s_first*, *s_last*) in range [*first*, *last*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *last*), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
std::ranges::iterator_t<Rng1> search(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range [*first*, *last*) for any elements in the range [*s_first*, *s_last*). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most (*S***N*) comparisons where *S* = distance(*s_first*, *s_last*) and *N* = distance(*first*, *last*).

Template Parameters

- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::equal_to<>*
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng2*.

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an

iterator to the beginning of the first subsequence [s_first, s_last) in range [first, last). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, last), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred =
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng1>>> search(ExPolicy
&&policy,
Rng1
&&rng1,
Rng2
&&rng2,
Pred
&&op =
Pred(),
Proj1
&&proj1
= Proj1(),
Proj2
&&proj2
= Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where S = distance(s_first, s_last) and N = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements the algorithm will be examining.

- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [*s_first*, *s_last*) in range [*first*, *last*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *last*), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename FwdIter, typename FwdIter2, typename Sent2, typename Pred =
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
FwdIter search_n(FwdIter first, std::size_t count, FwdIter2 s_first, Sent s_last, Pred &&op = Pred(),
Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range [*first*, *last*) for any elements in the range [*s_first*, *s_last*). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search_n* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most (*S***N*) comparisons where *S* = distance(*s_first*, *s_last*) and *N* = count.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate is invoked.

Returns

The *search_n* algorithm returns *FwdIter*. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [*s_first*, *s_last*) in range [*first*, *first*+*count*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *first*+*count*), *first* is returned. Additionally, if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Sent2, typename
Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type search_n(ExPolicy &&policy,
FwdIter first,
std::size_t count,
FwdIter2 s_first, Sent2
s_last, Pred &&op =
Pred(), Proj1 &&proj1
= Proj1(), Proj2
&&proj2 = Proj2())
```

Searches the range [*first*, *last*) for any elements in the range [*s_first*, *s_last*). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (*S***N*) comparisons where *S* = distance(*s_first*, *s_last*) and *N* = count.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it

executes the assignments.

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search_n* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [*s_first*, *s_last*) in range [*first*, *first*+*count*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *first*+*count*), *first* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
std::ranges::iterator_t<Rng1> search_n(Rng1 &&rng1, std::size_t count, Rng2 &&rng2, Pred &&op =
Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range [*first*, *last*) for any elements in the range [*s_first*, *s_last*). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng2*.

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **count** – The number of elements to apply the algorithm on.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence $[s_first, s_last)$ in range $[first, last)$. If the length of the subsequence $[s_first, s_last)$ is greater than the length of the range $[first, last)$, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred =
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng1>>> search_n(ExPolicy
                                                    &&pol-
                                                    icy,
                                                    Rng1
                                                    &&rng1,
                                                    std::size_t
                                                    count,
                                                    Rng2
                                                    &&rng2,
                                                    Pred
                                                    &&op
                                                    =
                                                    Pred(),
                                                    Proj1
                                                    &&proj1
                                                    =
                                                    Proj1(),
                                                    Proj2
                                                    &&proj2
                                                    =
                                                    Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where S = distance(s_first, s_last) and N = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements the algorithm will be examining.

- **count** – The number of elements to apply the algorithm on.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [*s_first*, *s_last*) in range [*first*, *last*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *last*), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

hpx::ranges::set_difference

Defined in header `hpx/algorithm.hpp`⁵⁹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

⁵⁹⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,
typename Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename
Proj2 = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_difference_result<Iter1, Iter3>>::type set_difference(ExPolicy
&&pol-
icy,
Iter1
first1,
Sent1
last1,
Iter2
first2,
Sent2
last2,
Iter3
dest,
Pred
&&op
=
Pred(),
Proj1
&&proj
=
Proj1(),
Proj2
&&proj
=
Proj2()
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range $[first1, last1)$ and not present in the range $[first2, last2)$. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in $[first1, last1)$ and *n* times in $[first2, last2)$, it will be copied to *dest* exactly $\text{std::max}(m-n, 0)$ times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns a `hpx::future<ranges::set_difference_result<Iter1, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_difference_result<Iter1, Iter3>` otherwise. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

hpx::parallel::util::detail::algorithm_result<ExPolicy, set_difference_result<std::ranges::iterator_t<Rng1>, Iter3>> set_di.

Constructs a sorted range beginning at *dest* consisting of all elements present in the range [*first1*, *last1*) and not present in the range [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), it will be copied to *dest* exactly $\text{std::max}(m-n, 0)$ times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter1* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns a `hpx::future<ranges::set_difference_result<Iter1, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_difference_result<Iter1, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
set_difference_result<Iter1, Iter3> set_difference(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2,
Iter3 dest, Pred &&op = Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 = Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range `[first1, last1)` and not present in the range `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in `[first1, last1)` and *n* times in `[first2, last2)`, it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns `ranges::set_difference_result<Iter1, Iter3>`. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_difference_result<std::ranges::iterator_t<Rng1>, Iter3> set_difference(Rng1 &&rng1, Rng2
&&rng2, Iter3 dest, Pred
&&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range $[first1, last1)$ and not present in the range $[first2, last2)$. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in $[first1, last1)$ and *n* times in $[first2, last2)$, it will be copied to *dest* exactly $\text{std::max}(m-n, 0)$ times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns `ranges::set_difference_result<Iter1, Iter3>`. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::transform_exclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp,  
typename T = typename std::iterator_traits<InIter>::value_type>  
transform_exclusive_scan_result<InIter, OutIter> transform_exclusive_scan(InIter first, Sent last,  
OutIter dest, T init,  
BinOp &&binary_op,  
UnOp &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of transform_exclusive_scan may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN) where $1 < K+1 = M \leq N$).
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

⁵⁹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns *transform_exclusive_scan_result<InIter, OutIter>*. The *transform_exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename
BinOp, typename UnOp, typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, transform_exclusive_result<FwdIter1, FwdIter2>>::type transform_exc
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aK*), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *aM*, ..., *aN*)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns a *hpx::future<transform_exclusive_result<FwdIter1, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_exclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O> transform_exclusive_scan(Rng
&&rng,
O
dest,
T
init,
BinOp
&&binary_op,
UnOp
&&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1)))`.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns a *transform_exclusive_scan_result*< `std::ranges::iterator_t<Rng>`, *O*>. The *transform_exclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp, typename
T = typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aK*), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *aM*, ..., *aN*)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of

this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns a *hpx::future<transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_exclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::uninitialized_default_construct, hpx::ranges::uninitialized_default_construct_n

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

template<typename **FwdIter**, typename **Sent**>

FwdIter **uninitialized_default_construct**(*FwdIter* first, *Sent* last)

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_default_construct* algorithm returns a *returns FwdIter*. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

template<typename **ExPolicy**, typename **FwdIter**, typename **Sent**>

⁵⁹⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> **uninitialized_default_construct**(*ExPolicy* &&pol-
icy,
FwdIter
first,
Sent
last)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_default_construct* algorithm returns the iterator to the element in the source range, one past the last element constructed.

template<typename **Rng**>
hpx::traits::range_traits<Rng>::iterator_type **uninitialized_default_construct**(*Rng* &&rng)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the range to which will be default constructed.

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::traits::range_traits<Rng>::iterator_type*. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename Rng>
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type uninitial
```

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be default constructed

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename FwdIter, typename Size>
FwdIter uninitialized_default_construct_n(FwdIter first, Size count)
```

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range [first, first + count) by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a returns *FwdIter*. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type uninitialized_default_construct_n(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter
                                                                                                     first,
                                                                                                     Size
                                                                                                     count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::min_element, hpx::ranges::max_element, hpx::ranges::minmax_element

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter min_element(FwdIter first, Sent last, F &&f = F(), Proj &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

⁵⁹⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns *FwdIter*. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> min_element(Rng &&rng, F &&f = F(), Proj &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns a *hpx::traits::range_iterator<Rng>::type* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F =
hpx::parallel::detail::less, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> min_element(ExPolicy &&policy,
                                                                              FwdIter first, Sent last,
                                                                              F &&f = F(), Proj
                                                                              &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *min_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> min_element(ExPolicy
&&pol-
icy,
Rng
&&rng,
F
&&f
=
F(),
Proj
&&proj
=
Proj())

```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *min_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns a *hpx::future<hpx::traits::range_iterator<Rng>::type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest

element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter max_element(FwdIter first, Sent last, F &&f = F(), Proj &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *FwdIter*. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>  
std::ranges::iterator_t<Rng> max_element(Rng &&rng, F &&f = F(), Proj &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a `hpx::traits::range_iterator<Rng>::type` otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F =
hpx::parallel::detail::less, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> max_element(ExPolicy &&policy,
                                                                              FwdIter first, Sent last,
                                                                              F &&f = F(), Proj
                                                                              &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> max_element(ExPolicy
&&pol-
icy,
Rng
&&rng,
F
&&f
=
F(),
Proj
&&proj
=
Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *hpx::future<hpx::traits::range_iterator<Rng>::type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj =
hpx::identity>
minmax_element_result<FwdIter> minmax_element(FwdIter first, Sent last, F &&f = F(), Proj
&&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The assignments in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to *std::less*. The signature of the predi-

cate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*, *FwdIter*>. The *minmax_element* algorithm returns a *min_max_result* consisting of an iterator to the smallest element as the min element and an iterator to the greatest element as the max element. Returns *minmax_element_result*{first, first} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
minmax_element_result<std::ranges::iterator_t<Rng>> minmax_element(Rng &&rng, F &&f = F(),
                                                                    Proj &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The assignments in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*hpx::traits::range_iterator*<*Rng*>::type, *hpx::traits::range_iterator*<*Rng*>::type>. The *minmax_element* algorithm returns a *min_max_result* consisting of an range iterator to the smallest element as the min element and an range iterator to the greatest element as the max element. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If

several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F =
    hpx::parallel::detail::less, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<FwdIter>> minmax_element(ExPolicy
    &&pol-
    icy,
    FwdIter
    first,
    Sent
    last,
    F
    &&f
    =
    F(),
    Proj
    &&proj
    =
    Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to *std::less*. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*, *FwdIter*>. The *minmax_element* algorithm returns a *min_max_result* consisting of an iterator to the smallest element as the min element and an iterator to the greatest element as the max element. Returns *minmax_element_result*{first, first} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<std::ranges::iterator_t<Rng>>> minmax_e
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *Copy-Constructible*.

- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*hpx::traits::range_iterator*<*Rng*>::*type*, *hpx::traits::range_iterator*<*Rng*>::*type*>. The *minmax_element* algorithm returns a *min_max_result* consisting of an range iterator to the smallest element as the min element and an range iterator to the greatest element as the max element. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

hpx::ranges::copy, hpx::ranges::copy_n, hpx::ranges::copy_if

Defined in header `hpx/algorithm.hpp`⁵⁹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter>
parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_result<FwdIter1, FwdIter>>::type copy(ExPolicy
&&pol-
icy,
FwdIter1
iter,
Sent1
sent,
FwdIter
dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

⁵⁹⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a *hpx::future<ranges::copy_result<FwdIter1, FwdIter> >* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::copy_result<FwdIter1, FwdIter>* otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter>
parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_result<typename hpx::traits::range_traits<Rng>::iterator_type
```

Copies the elements in the range *rng* to another range beginning at *dest*.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a *hpx::future<ranges::copy_result<iterator_t<Rng>, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::copy_result<iterator_t<Rng>, FwdIter2>* otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter>
ranges::copy_result<FwdIter1, FwdIter> copy(FwdIter1 iter, Sent1 sent, FwdIter dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter>
ranges::copy_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter> copy(Rng
                                                                                               &&rng,
                                                                                               FwdIter
                                                                                               dest)
```

Copies the elements in the range *rng* to another range beginning at *dest*.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_n_result<FwdIter1, FwdIter2>>::type copy_n(ExPolic
&&pol-
icy,
FwdIter
first,
Size
count,
FwdIter
dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a *hpx::future<ranges::copy_n_result<FwdIter1, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::copy_n_result<FwdIter1, FwdIter2>* otherwise. The *copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last

element copied.

```
template<typename FwdIter1, typename Size, typename FwdIter2>
```

```
ranges::copy_n_result<FwdIter1, FwdIter2> copy_n(FwdIter1 first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter, typename Pred, typename Proj = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_if_result<FwdIter1, FwdIter>>::type copy_if(ExPolicy &&policy, FwdIter1 first, Sent1 sent, FwdIter first_iter, Pred pred, Proj proj, Proj proj_end) = Proj()
```

Copies the elements in the range, defined by [first, last) to another range beginning at *dest*. The order of the elements that are not removed is preserved.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for FwdIter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns `true` if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types `Type1` must be such that objects of type `FwdIter` can be dereferenced and then implicitly converted to `Type1`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `copy_if` algorithm returns a `hpx::future<ranges::copy_if_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `ranges::copy_if_result<iterator_t<Rng>, FwdIter2>` otherwise. The `copy_if` algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Pred, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_if_result<typename hpx::traits::range_traits<Rng>::iter
```

Copies the elements in the range, defined by *rng* to another range beginning at *dest*. The order of the elements that are not removed is preserved.

The assignments in the parallel `copy_if` algorithm invoked with an execution policy object of type

sequenced_policy execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const* &, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns a *hpx::future<ranges::copy_if_result<iterator_t<Rng>, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::copy_if_result<iterator_t<Rng>, FwdIter2>* otherwise. The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter, typename Pred, typename Proj = hpx::identity>
```

```
ranges::copy_if_result<FwdIter1, FwdIter> copy_if(FwdIter1 iter, Sent1 sent, FwdIter dest, Pred
&&pred, Proj &&proj = Proj())
```

Copies the elements in the range, defined by [first, last) to another range beginning at *dest*. The order of the elements that are not removed is preserved.

Template Parameters

- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *FwdIter1*.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter, typename Pred, typename Proj = hpx::identity>
ranges::copy_if_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter> copy_if(Rng
                                                                                               &&rng,
                                                                                               FwdIter
                                                                                               dest,
                                                                                               Pred
                                                                                               &&pred,
                                                                                               Proj
                                                                                               &&proj
                                                                                               =
                                                                                               Proj())
```

Copies the elements in the range, defined by *rng* to another range beginning at *dest*. The order of the elements that are not removed is preserved.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::swap_ranges

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter1, typename Sent1, typename InIter2, typename Sent2>
swap_ranges_result<InIter1, InIter2> swap_ranges(InIter1 first1, Sent1 last1, InIter2 first2, Sent2 last2)
```

Exchanges elements between range [first1, last1) and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **InIter1** – The type of the first range of iterators to swap (deduced).
- **Sent1** – The type of the first sentinel (deduced). This sentinel type must be a sentinel for *InIter1*.
- **InIter2** – The type of the second range of iterators to swap (deduced).
- **Sent2** – The type of the second sentinel (deduced). This sentinel type must be a sentinel for *InIter2*.

Parameters

- **first1** – Refers to the beginning of the sequence of elements for the first range.
- **last1** – Refers to sentinel value denoting the end of the sequence of elements for the first range.
- **first2** – Refers to the beginning of the sequence of elements for the second range.
- **last2** – Refers to sentinel value denoting the end of the sequence of elements for the second range.

Returns

The *swap_ranges* algorithm returns *swap_ranges_result*<*InIter1*, *InIter2*>. The *swap_ranges* algorithm returns *in_in_result* with the first element as the iterator to the element past the last element exchanged in range beginning with *first1* and the second element as the iterator to the element past the last element exchanged in the range beginning with *first2*.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>
```

⁵⁹⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

```

parallel::util::detail::algorithm_result<ExPolicy, swap_ranges_result<FwdIter1, FwdIter2>>>::type swap_ranges(ExPolicy
&&pol-
icy,
FwdIter1
first1,
Sent1
last1,
FwdIter2
first2,
Sent2
last2)

```

Exchanges elements between range [first1, last1) and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first range of iterators to swap (deduced).
- **Sent1** – The type of the first sentinel (deduced). This sentinel type must be a sentinel for FwdIter1.
- **FwdIter2** – The type of the second range of iterators to swap (deduced).
- **Sent2** – The type of the second sentinel (deduced). This sentinel type must be a sentinel for FwdIter2.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements for the first range.
- **last1** – Refers to sentinel value denoting the end of the sequence of elements for the first range.
- **first2** – Refers to the beginning of the sequence of elements for the second range.
- **last2** – Refers to sentinel value denoting the end of the sequence of elements for the second range.

Returns

The *swap_ranges* algorithm returns a *hpx::future<swap_ranges_result<FwdIter1, FwdIter2>>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter2* otherwise. The *swap_ranges* algorithm returns in *in_result* with the first element as the iterator to the element past the last element exchanged in range beginning with *first1* and the second element as the iterator to the element past the last element exchanged in the range beginning with *first2*.

```

template<typename Rng1, typename Rng2>
swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>> swap_ranges(Rng1
&&rng1,
Rng2
&&rng2)

```

Exchanges elements between range [first1, last1) and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **rng1** – Refers to the sequence of elements of the first range.
- **rng2** – Refers to the sequence of elements of the second range.

Returns

The *swap_ranges* algorithm returns *swap_ranges_result*< std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>. The *swap_ranges* algorithm returns in *_in_result* with the first element as the iterator to the element past the last element exchanged in range beginning with *first1* and the second element as the iterator to the element past the last element exchanged in the range beginning with *first2*.

```
template<typename ExPolicy, typename Rng1, typename Rng2>
parallel::util::detail::algorithm_result<ExPolicy, swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<
```

Exchanges elements between range [first1, last1) and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements of the first range.
- **rng2** – Refers to the sequence of elements of the second range.

Returns

The `swap_ranges` algorithm returns a `hpx::future<swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>>` if the execution policy is of type `parallel_task_policy` and returns `swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>`. otherwise. The `swap_ranges` algorithm returns `in_in_result` with the first element as the iterator to the element past the last element exchanged in range beginning with `first1` and the second element as the iterator to the element past the last element exchanged in the range beginning with `first2`.

hpx::ranges::mismatch

Defined in header `hpx/algorithm.hpp`⁶⁰⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,
typename Pred = equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, mismatch_result<Iter1, Iter2>>::type mismatch(ExPolicy
&&pol-
icy,
Iter1
first1,
Sent1
last1,
Iter2
first2,
Sent2
last2,
Pred
&&op
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Returns true if the range [first1, last1) is mismatch to the range [first2, last2), and false otherwise.

⁶⁰⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate f . If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate f are made.

Note: The two ranges are considered mismatch if, for every iterator i in the range $[\text{first1}, \text{last1})$, $*i$ mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *mismatch* algorithm returns true if the elements in the two ranges are mismatch, otherwise it returns false. If the length of the range [first1, last1) does not mismatch the length of the range [first2, last2), it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = equal_to, typename  
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, mismatch_result<typename hpx::traits::range_traits<Rng1>::iterator_
```

Returns `std::pair` with iterators to the first two non-equivalent elements.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1, FwdIter2> >` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1, FwdIter2>` otherwise. The *mismatch* algorithm returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2, last2)`.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =
equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
mismatch_result<Iter1, Iter2> mismatch(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&op =
Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if the range `[first1, last1)` is mismatch to the range `[first2, last2)`, and false otherwise.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *f*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *f* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1, last1)`, $*i$ mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses operator`==` to determine if two elements are mismatch.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns *bool*. The *mismatch* algorithm returns true if the elements in the two ranges are mismatch, otherwise it returns false. If the length of the range [first1, last1) does not mismatch the length of the range [first2, last2), it returns false.

```
template<typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
```

```
mismatch_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterat
```


Returns `std::pair` with iterators to the first two non-equivalent elements.

Note: Complexity: At most *last1* - *first1* applications of the predicate *f*.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns `std::pair<FwdIter1, FwdIter2>`. The *mismatch* algorithm returns the first mismatching pair of elements from two ranges: one defined by [*first1*, *last1*) and another defined by [*first2*, *last2*).

`hpx::ranges::find`, `hpx::ranges::find_if`, `hpx::ranges::find_if_not`, `hpx::ranges::find_end`,
`hpx::ranges::find_first_of`, `hpx::ranges::find_last`, `hpx::ranges::find_last_if`,
`hpx::ranges::find_last_if_not`

Defined in header `hpx/algorithm.hpp`⁶⁰¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

⁶⁰¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::rotate, hpx::ranges::rotate_copy

Defined in header `hpx/algorithm.hpp`⁶⁰².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent>  
subrange_t<FwdIter, Sent> rotate(FwdIter first, FwdIter middle, Sent last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element middle becomes the first element of the new range and middle - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *subrange_t*<*FwdIter*, *Sent*>. The *rotate* algorithm returns the iterator equal to pair(first + (last - middle), last).

```
template<typename ExPolicy, typename FwdIter, typename Sent>  
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type rotate(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter  
                                                                                      first,  
                                                                                      FwdIter  
                                                                                      middle,  
                                                                                      Sent last)
```

⁶⁰² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element middle becomes the first element of the new range and middle - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *hpx::future<subrange_t<FwdIter, Sent>>* if the execution policy is of type *parallel_task_policy* and returns a *subrange_t<FwdIter, Sent>* otherwise. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

```
template<typename Rng>
subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>> rotate(Rng &&rng,
                                                                              std::ranges::iterator_t<Rng>
                                                                              middle)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element middle becomes the first element of the new range and middle - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

Returns

The *rotate* algorithm returns a *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>*. The *rotate* algorithm returns the iterator equal to *pair(first + (last - middle), last)*.

```
template<typename ExPolicy, typename Rng>  
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>> r
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range *[first, last)* in such a way that the element *middle* becomes the first element of the new range and *middle - 1* becomes the last element.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

Returns

The *rotate* algorithm returns a *hpx::future* `<subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>*. otherwise. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

```
template<typename FwdIter, typename Sent, typename OutIter>
rotate_copy_result<FwdIter, OutIter> rotate_copy(FwdIter first, FwdIter middle, Sent last, OutIter
                                                    dest_first)
```

Copies the elements from the range `[first, last)`, to another range beginning at *dest_first* in such a way, that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range `[first,last)`.

Returns

The *rotate_copy* algorithm returns a *rotate_copy_result*`<FwdIter, OutIter>`. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2>
parallel::util::detail::algorithm_result<ExPolicy, rotate_copy_result<FwdIter1, FwdIter2>>::type rotate_copy(ExPolicy
&&policy,
FwdIter1
first,
FwdIter1
mid-
dle,
Sent
last,
FwdIter2
dest_first)
```

Copies the elements from the range `[first, last)`, to another range beginning at *dest_first* in such a way, that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last

element.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range [first,last).

Returns

The *rotate_copy* algorithm returns `hpx::future< rotate_copy_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *rotate_copy_result<FwdIter1, FwdIter2>* otherwise. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename Rng, typename OutIter>
rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter> rotate_copy(Rng &&rng,
                                                                    std::ranges::iterator_t<Rng>
                                                                    middle, OutIter dest_first)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *middle* becomes the first element of the new range and *middle - 1* becomes the last element.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.

- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range [first,last).

Returns

The *rotate* algorithm returns a *rotate_copy_result*<std::ranges::iterator_t<Rng>, OutIter>. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename Rng, typename OutIter>
parallel::util::detail::algorithm_result<ExPolicy, rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>> rotate_copy
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the

range [first,last).

Returns

The `rotate_copy` algorithm returns a `hpx::future<rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>>` if the execution policy is of type `parallel_task_policy` and returns `rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>` otherwise. The `rotate_copy` algorithm returns the output iterator to the element past the last element copied.

hpx::ranges::includes

Defined in header `hpx/algorithm.hpp`⁶⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,
typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> includes(ExPolicy &&policy, Iter1
first1, Sent1 last1, Iter2 first2,
Sent2 last2, Pred &&op =
Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 =
Proj2())
```

Returns true if every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

⁶⁰³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *includes* algorithm returns true every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
bool includes(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&op = Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2*(N1+N2-1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns true every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> includes(ExPolicy &&policy, Rng1
&&rng1, Rng2 &&rng2, Pred
&&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Returns true if every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *includes* algorithm returns true every element from the sorted range [first2, last2) is found within the

sorted range [first1, last1). Also returns true if [first2, last2) is empty.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::parallel::detail::less, typename Proj1
= hpx::identity, typename Proj2 = hpx::identity>
bool includes(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Returns true if every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns true every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty.

hpx::ranges::adjacent_difference

Defined in header `hpx/algorithm.hpp`⁶⁰⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter1, typename FwdIter2, typename Sent>
FwdIter2 adjacent_difference(FwdIter1 first, Sent last, FwdIter2 dest)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename FwdIter2>
FwdIter2 adjacent_difference(Rng &&rng, FwdIter2 dest)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

⁶⁰⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy
                                                                                      &&policy,
                                                                                      FwdIter1
                                                                                      first, Sent
                                                                                      last,
                                                                                      FwdIter2
                                                                                      dest)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename Rng, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy
                                                                                      &&policy,
                                                                                      Rng
                                                                                      &&rng,
                                                                                      FwdIter2
                                                                                      dest)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename FwdIter1, typename Sent, typename FwdIter2, typename Op>
FwdIter2 adjacent_difference(FwdIter1 first, Sent last, FwdIter2 dest, Op &&op)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename FwdIter2, typename Op>
FwdIter2 adjacent_difference(Rng &&rng, FwdIter2 dest, Op &&op)
```

Searches the *rng* for two consecutive identical elements.

Template Parameters

- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*?

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename  
Op>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter1  
                                                                                      first, Sent  
                                                                                      last,  
                                                                                      FwdIter2  
                                                                                      dest, Op  
                                                                                      &&op)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm

will be applied to.

- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type `iterator_traits<InputIt>::value_type` can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*?

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename Rng, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy
                                                                                       &&policy,
                                                                                       Rng
                                                                                       &&rng,
                                                                                       FwdIter2
                                                                                       dest, Op
                                                                                       &&op)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of $(result - first) + 1$ and $(last - first) - 1$ application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type `iterator_traits<InputIt>::value_type` can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

hpx::ranges::stable_sort

Defined in header `hpx/algorithm.hpp`⁶⁰⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename RandomIt, typename Sent, typename Comp = ranges::less, typename Proj =
hpx::identity>
```

```
RandomIt stable_sort(RandomIt first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *stable_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: O(N log(N)), where N = std::distance(first, last) comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first

⁶⁰⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

argument of the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns `RandomIt`. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less,
        typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type stable_sort(ExPolicy &&policy,
                                                                              RandomIt first, Sent
                                                                              last, Comp &&comp =
                                                                              Comp(), Proj &&proj
                                                                              = Proj())
```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `RandomIt`.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields true if the first

argument of the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `RandomIt` otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> stable_sort(Rng &&rng, Comp &&comp = Comp(), Proj &&proj =
    Proj())
```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The assignments in the parallel `stable_sort` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns `std::ranges::iterator_t<Rng>`. It returns `last`.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj =
    hpx::identity>
```

```

parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> stable_sort(ExPolicy
                                                    &&pol-
                                                    icy, Rng
                                                    &&rng,
                                                    Comp
                                                    &&comp
                                                    = Comp(),
                                                    Proj
                                                    &&proj =
                                                    Proj())

```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `std::ranges::iterator_t<Rng>` otherwise. It returns `last`.

hpx::ranges::partial_sort_copy

Defined in header `hpx/algorithm.hpp`⁶⁰⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent1, typename RandIter, typename Sent2, typename Comp =  
ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
partial_sort_copy_result<InIter, RandIter> partial_sort_copy(InIter first, Sent1 last, RandIter  
r_first, Sent2 r_last, Comp &&comp =  
Comp(), Proj1 &&proj1 = Proj1(),  
Proj2 &&proj2 = Proj2())
```

Sorts some of the elements in the range [first, last) in ascending order, storing the result in the range [r_first, r_last). At most r_last - r_first of the elements are placed sorted to the range [r_first, r_first + n) where n is the number of elements to sort (n = min(last - first, r_last - r_first)).

The assignments in the parallel *partial_sort_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **RandIter** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent2** – The type of the destination sentinel (deduced). This sentinel type must be a sentinel for RandIter.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function for the output range. This defaults to `hpx::identity`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the sentinel value denoting the end of the sequence of elements the algorithm will be applied to.

⁶⁰⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **r_first** – Refers to the beginning of the destination range.
- **r_last** – Refers to the sentinel denoting the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate `comp` is invoked.

Returns

The `partial_sort_copy` algorithm returns a `partial_sort_copy_result<InIter, RandIter>`. The algorithm returns `{last, result_first + N}`.

```
template<typename ExPolicy, typename FwdIter, typename Sent1, typename RandIter, typename
Sent2, typename Comp = ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, partial_sort_copy_result<FwdIter, RandIter>> partial_sort_copy(E
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[r_first, r_last)`. At most `r_last - r_first` of the elements are placed sorted to the range `[r_first, r_first + n)` where `n` is the number of elements to sort (`n = min(last - first, r_last - r_first)`).

The application of function objects in parallel algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D =$

`std::distance(r_first, r_last)` comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **RandIter** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent2** – The type of the destination sentinel (deduced). This sentinel type must be a sentinel for `RandIter`.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function for the output range. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the sentinel value denoting the end of the sequence of elements the algorithm will be applied to.
- **r_first** – Refers to the beginning of the destination range.
- **r_last** – Refers to the sentinel denoting the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate `comp` is invoked.

Returns

The `partial_sort_copy` algorithm returns a `hpx::future<partial_sort_copy_result<FwdIter, RandIter>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `partial_sort_copy_result<FwdIter, RandIter>` otherwise. The algorithm returns `{last, result_first + N}`.

```
template<typename Rng1, typename Rng2, typename Comp = ranges::less, typename Proj1 =  
hpx::identity, typename Proj2 = hpx::identity>
```



```

partial_sort_copy_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>> partial_sort_copy(Rng1
&&rng1,
Rng2
&&rng2,
Comp
&&comp
=
Comp(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())

```

Sorts some of the elements in the range [first, last) in ascending order, storing the result in the range [r_first, r_last). At most r_last - r_first of the elements are placed sorted to the range [r_first, r_first + n) where n is the number of elements to sort (n = min(last - first, r_last - r_first)).

The assignments in the parallel *partial_sort_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function for the output range. This defaults to `hpx::identity`.

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate *comp* is invoked.

Returns

The *partial_sort_copy* algorithm returns *partial_sort_copy_result*<range_iterator_t<Rng1>, range_iterator_t<Rng2>>. The algorithm returns {last, result_first + N}.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Comp = ranges::less,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, partial_sort_copy_result<std::ranges::iterator_t<Rng1>, std::ranges::iter
```

Sorts some of the elements in the range [first, last) in ascending order, storing the result in the range [r_first, r_last). At most r_last - r_first of the elements are placed sorted to the range [r_first, r_first + n) where n is the number of elements to sort (n = min(last - first, r_last - r_first)).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to *detail::less*.
- **Proj1** – The type of an optional projection function for the input range. This defaults to *hpx::identity*.
- **Proj2** – The type of an optional projection function for the output range. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.

- **rng2** – Refers to the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate `comp` is invoked.

Returns

The `partial_sort_copy` algorithm returns a `hpx::future<partial_sort_copy_result<range_iterator_t<Rng1>, range_iterator_t<Rng2>>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `partial_sort_copy_result<range_iterator_t<Rng1>, range_iterator_t<Rng2>>` otherwise. The algorithm returns `{last, result_first + N}`.

hpx::ranges::uninitialized_copy, hpx::ranges::uninitialized_copy_n

Defined in header `hpx/algorithm.hpp`⁶⁰⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent1, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> uninitialized_copy(InIter first1, Sent1 last1,
                                                                    FwdIter first2, Sent2 last2)
```

Copies the elements in the range, defined by `[first, last)`, to an uninitialized memory area beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel `uninitialized_copy` algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

⁶⁰⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy* algorithm returns an *in_out_result*<*InIter*, *FwdIter*>. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>
```

```
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type uninitialized
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *in_out_result<InIter, FwdIter>* otherwise. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2>
hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **rng1** – Refers to the range from which the elements will be copied from
- **rng2** – Refers to the range to which the elements will be copied to

Returns

The *uninitialized_copy* algorithm returns an *in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>*. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2>
parallel::util::detail::algorithm_result<ExPolicy, hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type>>
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the range from which the elements will be copied from
- **rng2** – Refers to the range to which the elements will be copied to

Returns

The *uninitialized_copy* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result< typename hpx::traits::range_traits<Rng1>::iterator_type , typename hpx::traits::range_traits<Rng2>::iterator_type>` otherwise. The *uninitialized_copy* algorithm returns the input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename Size, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> uninitialized_copy_n(InIter first1, Size count,
                                                                    FwdIter first2, Sent2 last2)
```

Copies the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`, to another range beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy_n* algorithm returns *in_out_result<InIter, FwdIter>*. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2, typename Sent2>
```

```
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type uninitialized
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy_n* algorithm returns a *hpx::future<in_out_result<FwdIter1, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::ends_with

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =  
ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
bool ends_with(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&pred = Pred(), Proj1 &&proj1  
               = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2)

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Iter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

⁶⁰⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *ends_with* algorithm returns *bool*. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename
Sent2, typename Pred = ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, bool>::type ends_with(ExPolicy &&policy, FwdIter1
first1, Sent1 last1, FwdIter2
first2, Sent2 last2, Pred
&&pred = Pred(), Proj1
&&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2)

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used(deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter2** – The type of the begin destination iterators used deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.

- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate is invoked.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename Proj1 =  
hpx::identity, typename Proj2 = hpx::identity>  
bool ends_with(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1 &&proj1 = Proj1(),  
               Proj2 &&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the suffix of the first range *rng1*.

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns *bool*. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = ranges::equal_to,
        typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type ends_with(ExPolicy &&policy, Rng1
                                                                    &&rng1, Rng2 &&rng2,
                                                                    Pred &&pred = Pred(),
                                                                    Proj1 &&proj1 = Proj1(),
                                                                    Proj2 &&proj2 =
                                                                    Proj2())
```

Checks whether the second range *rng2* matches the suffix of the first range *rng1*.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.

- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

hpx::ranges::fill, hpx::ranges::fill_n

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng, typename T = typename  
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type fill C
```

Assigns the given value to the elements in the range [first, last).

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

⁶⁰⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename ExPolicy, typename Iter, typename Sent, typename T = typename
std::iterator_traits<Iter>::value_type>
hpx::parallel::util::detail::algorithm_result<ExPolicy, Iter>::type fill(ExPolicy &&policy, Iter first,
Sent last, T const &value)
```

Assigns the given value to the elements in the range [first, last).

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *Iter*.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
std::ranges::iterator_t<Rng> fill(Rng &&rng, T const &value)
```

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns *void*.

```
template<typename Iter, typename Sent, typename T = typename  
std::iterator_traits<Iter>::value_type>
```

```
Iter fill(Iter first, Sent last, T const &value)
```

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns *void*.

```
template<typename ExPolicy, typename Rng, typename T = typename  
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> fill_n(ExPolicy  
                                                    &&pol-  
                                                    icy, Rng  
                                                    &&rng, T  
                                                    const  
                                                    &value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type fill_n(ExPolicy &&policy,
FwdIter first, Size count,
T const &value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, for count > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::traits::range_traits<Rng>::iterator_type fill_n(Rng &&rng, T const &value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0.

Does nothing otherwise.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns an output iterator that compares equal to last.

```
template<typename FwdIter, typename Size, typename T = typename
```

```
std::iterator_traits<FwdIter>::value_type>
```

```
FwdIter fill_n(Iterator first, Size count, T const &value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0.
Does nothing otherwise.

Note: Complexity: Performs exactly *count* assignments, for count > 0.

Template Parameters

- **Iterator** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns an output iterator that compares equal to last.

hpx::ranges::uninitialized_fill, hpx::ranges::uninitialized_fill_n

Defined in header [hpx/algorithm.hpp](#)⁶¹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

⁶¹⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename Sent, typename T>
FwdIter uninitialized_fill(FwdIter first, Sent last, T const &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the ranges *uninitialized_fill* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a *FwdIter*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_fill(ExPolicy
                                                                                      &&policy,
                                                                                      FwdIter first,
                                                                                      Sent last, T
                                                                                      const
                                                                                      &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it

executes the assignments.

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a returns *FwdIter*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename Rng, typename T>
```

```
hpx::traits::range_traits<Rng>::iterator_type uninitialized_fill(Rng &&rng, T const &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the range to which the value will be filled
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a returns *hpx::traits::range_traits<Rng>::iterator_type*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename T>
```

```
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type uninitia
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be filled
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a *hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_fill* algorithm returns the iterator to one past the last element filled in the range.

```
template<typename FwdIter, typename Size, typename T>
FwdIter uninitialized_fill_n(FwdIter first, Size count, T const &value)
```

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at *first*. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *FwdIter*. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_fill_n(ExPolicy
                                                                                          &&policy,
                                                                                          FwdIter
                                                                                          first, Size
                                                                                          count, T
                                                                                          const
                                                                                          &value)
```

Copies the given *value* value to the first *count* elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *hpx::future<FwdIter>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

hpx::ranges::set_union

Defined in header [hpx/algorithm.hpp](#)⁶¹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶¹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,
typename Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename
Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_union_result<Iter1, Iter2, Iter3>>::type set_union(ExPolicy
&&pol-
icy,
Iter1
first1,
Sent1
last1,
Iter2
first2,
Sent2
last2,
Iter3
dest,
Pred
&&op
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, then all *m* elements will be copied from *[first1, last1)* to *dest*, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from *[first2, last2)* to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns a `hpx::future<ranges::set_union_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_union_result<Iter1, Iter2, Iter3>` otherwise. The *set_union* algo-

rithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
    hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_union_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, std::ranges::iterator_t<Iter3>, Proj1, Proj2, Pred>>
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, then all *m* elements will be copied from *[first1, last1)* to *dest*, preserving order, and then exactly $\text{std::max}(n-m, 0)$ elements will be copied from *[first2, last2)* to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns a `hpx::future<ranges::set_union_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_union_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
set_union_result<Iter1, Iter2, Iter3> tag_fallback_invoke(set_union_t, Iter1 first1, Sent1 last1, Iter2
first2, Sent2 last2, Iter3 dest, Pred &&op
= Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, then all *m* elements will be copied from *[first1, last1)* to *dest*, preserving order, and then exactly `std::max(n-m, 0)` elements will

be copied from [first2, last2) to dest, also preserving order.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns `ranges::set_union_result<Iter1, Iter2, Iter3>`. The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_union_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> set_union(Rng1
&&rng1,
Rng2
&&rng2,
Iter3
dest,
Pred
&&op
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, then all *m* elements will be copied from *[first1, last1)* to *dest*, preserving order, and then exactly *std::max(n-m, 0)* elements will be copied from *[first2, last2)* to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::less<>*
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal.

The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns *ranges::set_union_result<Iter1, Iter2, Iter3>*. where *Iter1* is *range_iterator_t<Rng1>* and *Iter2* is *range_iterator_t<Rng2>* The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::lexicographical_compare

Defined in header `hpx/algorithm.hpp`⁶¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter1, typename Sent1, typename InIter2, typename Sent2, typename Proj1
= hpx::identity, typename Proj2 = hpx::identity, typename Pred = hpx::parallel::detail::less>
bool lexicographical_compare(InIter1 first1, Sent1 last1, InIter2 first2, Sent2 last2, Pred &&pred =
    Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element

⁶¹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **InIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter1.
- **InIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for FwdIter1. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for FwdIter2. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns *bool*. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2,  
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity, typename Pred =  
hpx::parallel::detail::less>
```

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> lexicographical_compare(ExPolicy
                                                                 &&policy,
                                                                 FwdIter1
                                                                 first1,
                                                                 Sent1 last1,
                                                                 FwdIter2
                                                                 first2,
                                                                 Sent2 last2,
                                                                 Pred
                                                                 &&pred =
                                                                 Pred(),
                                                                 Proj1
                                                                 &&proj1 =
                                                                 Proj1(),
                                                                 Proj2
                                                                 &&proj2 =
                                                                 Proj2())

```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter2`.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `lexicographical_compare` requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for `FwdIter1`. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for `FwdIter2`. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The `lexicographically_compare` algorithm returns a `hpx::future<bool>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `bool` otherwise. The `lexicographically_compare` algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename Rng1, typename Rng2, typename Proj1 = hpx::identity, typename Proj2 =  
hpx::identity, typename Pred = hpx::parallel::detail::less>  
bool lexicographical_compare(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1  
    &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks if the first range `rng1` is lexicographically less than the second range `rng2`. uses a provided predicate to compare elements.

The comparison operations in the parallel `lexicographical_compare` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{std::begin}(\text{rng1}), \text{std::end}(\text{rng1}))$ and $N2 = \text{std::distance}(\text{std::begin}(\text{rng2}), \text{std::end}(\text{rng2}))$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
- The first mismatching element defines which range is lexicographically *less* or *greater* than the other
- If one range is a prefix of another, the shorter range is lexicographically *less* than the other

- If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
- An empty range is lexicographically *less* than any non-empty range
- Two empty ranges are lexicographically *equal*

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for elements of the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate is invoked.

Returns

The *lexicographically_compare* algorithm returns *bool*. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Proj1 = hpx::identity,
        typename Proj2 = hpx::identity, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> lexicographical_compare(ExPolicy
                                                                                          &&policy,
                                                                                          Rng1
                                                                                          &&rng1,
                                                                                          Rng2
                                                                                          &&rng2,
                                                                                          Pred
                                                                                          &&pred =
                                                                                          Pred(),
                                                                                          Proj1
                                                                                          &&proj1 =
                                                                                          Proj1(),
                                                                                          Proj2
                                                                                          &&proj2 =
                                                                                          Proj2())
```

Checks if the first range `rng1` is lexicographically less than the second range `rng2`. uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execu-

tion policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{std::begin}(\text{rng1}), \text{std::end}(\text{rng1}))$ and $N2 = \text{std::distance}(\text{std::begin}(\text{rng2}), \text{std::end}(\text{rng2}))$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for elements of the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

hpx::ranges::sort

Defined in header `hpx/algorithm.hpp`⁶¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename RandomIt, typename Sent, typename Comp = ranges::less, typename Proj =
hpx::identity>
```

```
RandomIt sort(RandomIt first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: O(N log(N)), where N = detail::distance(first, last) comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

⁶¹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *sort* algorithm returns *RandomIt*. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less,
        typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type sort(ExPolicy &&policy, RandomIt
                                                                    first, Sent last, Comp &&comp
                                                                    = Comp(), Proj &&proj =
                                                                    Proj())
```

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{detail::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns a *hpx::future<RandomIt>* if the execution policy is of type *se-*

quenced_task_policy or *parallel_task_policy* and returns *RandomIt* otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp, typename Proj>
std::ranges::iterator_t<Rng> sort(Rng &&rng, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range *rng* in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the `INVOKE` operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns `std::ranges::iterator_t<Rng>`. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj =
hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> sort(ExPolicy
&&policy, Rng
&&rng, Comp
&&comp =
Comp(), Proj
&&proj = Proj())
```

Sorts the elements in the range *rng* in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing

to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the `INVOKE` operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns a *hpx::future<std::ranges::iterator_t<Rng>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *std::ranges::iterator_t<Rng>* otherwise. It returns *last*.

hpx::ranges::merge, hpx::ranges::inplace_merge

Defined in header [hpx/algorithm.hpp](#)⁶¹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

⁶¹⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Comp =
hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, hpx::ranges::merge_result<std::ranges::iterator_t<Rng1>, std::ranges::
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *Copy-*

Constructible. This defaults to `std::less<>`

- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first range of elements the algorithm will be applied to.
- **rng2** – Refers to the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – `comp` is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison `comp` is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison `comp` is invoked.

Returns

The *merge* algorithm returns a `hpx::future<merge_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `merge_result<Iter1, Iter2, Iter3>` otherwise. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,  
typename Iter3, typename Comp = hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2  
= hpx::identity>
```

```

hpx::parallel::util::detail::algorithm_result<ExPolicy, hpx::ranges::merge_result<Iter1, Iter2, Iter3>>::type merge(ExPolicy,
&&pol-
icy,
Iter1
first1,
Sent1
last1,
Iter2
first2,
Sent2
last2,
Iter3
dest,
Comp
&&com
=
Comp(),
Proj1
&&proj
=
Proj1(),
Proj2
&&proj
=
Proj2())

```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at `dest`. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.

- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns a `hpx::future<merge_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `merge_result<Iter1, Iter2, Iter3>` otherwise. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Comp = hpx::ranges::less,
        typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

hpx::ranges::merge_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> merge(Rng1
&&rng1,
Rng2
&&rng2,
Iter3
dest,
Comp
&&comp
=
Comp(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())

```

Merges two sorted ranges [first1, last1) and [first2, last2) into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first range of elements the algorithm will be applied to.
- **rng2** – Refers to the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the

elements of the first range as a projection operation before the actual comparison *comp* is invoked.

- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns *merge_result*<*Iter1*, *Iter2*, *Iter3*>. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Comp = hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::ranges::merge_result<Iter1, Iter2, Iter3> merge(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2,
                                                    Iter3 dest, Comp &&comp = Comp(), Proj1
                                                    &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Merges two sorted ranges [*first1*, *last1*) and [*first2*, *last2*) into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for *Iter2*.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns *merge_result*<*Iter1*, *Iter2*, *Iter3*>. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename Rng, typename Iter, typename Comp = hpx::ranges::less,
typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> inplace_merge(ExPolicy &&policy, Rng
&&rng, Iter middle,
Comp &&comp =
Comp(), Proj &&proj =
Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the range of elements the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns a `hpx::future<Iter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp = hpx::ranges::less,
        typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> inplace_merge(ExPolicy &&policy, Iter
                                                                    first, Iter middle, Sent
                                                                    last, Comp &&comp =
                                                                    Comp(), Proj &&proj =
                                                                    Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename Rng, typename Iter, typename Comp = hpx::ranges::less, typename Proj = hpx::identity>
```

```
Iter inplace_merge(Rng &&rng, Iter middle, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the range of elements the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns *Iter*. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename Iter, typename Sent, typename Comp = hpx::ranges::less, typename Proj = hpx::identity>
```

```
Iter inplace_merge(Iter first, Iter middle, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs O(std::distance(first, last)) applications of the comparison *comp* and the each projection.

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm *Iter*. The *inplace_merge* algorithm returns the source iterator *last*

hpx::ranges::generate, hpx::ranges::generate_n

Defined in header `hpx/algorithm.hpp`⁶¹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng, typename F>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> generate(ExPolicy
                                                    &&pol-
                                                    icy, Rng
                                                    &&rng,
                                                    F &&f)
```

Assign each element in range [first, last) a value generated by the given function object *f*

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

```
Ret fun();
```

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type

⁶¹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

sequenced_task_policy or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> generate(ExPolicy &&policy, Iter first,  
                                                                    Sent last, F &&f)
```

Assign each element in range [first, last) a value generated by the given function object *f*

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source end iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

```
Ret fun();
```

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename Rng, typename F>  
std::ranges::iterator_t<Rng> generate(Rng &&rng, F &&f)
```

Assign each element in range [first, last) a value generated by the given function object *f*

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

```
Ret fun();
```

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

```
template<typename Iter, typename Sent, typename F>
Iter generate(Iter first, Sent last, F &&f)
```

Assign each element in range [first, last) a value generated by the given function object *f*

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **Iter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source end iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

```
Ret fun();
```

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> generate_n(ExPolicy &&policy,
                                                                              FwdIter first, Size count,
                                                                              F &&f)
```

Assigns each element in range [first, first+count) a value generated by the given function object *g*.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type

parallel_policy or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for *count* > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

Ret fun();

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename FwdIter, typename Size, typename F>
FwdIter generate_n(FwdIter first, Size count, F &&f)
```

Assigns each element in range *[first, first+count)* a value generated by the given function object *g*.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for *count* > 0.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

```
Ret fun();
```

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

hpx::ranges::uninitialized_value_construct, hpx::ranges::uninitialized_value_construct_n

Defined in header [hpx/algorithm.hpp](#)⁶¹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent>
FwdIter uninitialized_value_construct(FwdIter first, Sent last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_value_construct* algorithm returns a returns *FwdIter*. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Sent>
```

⁶¹⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> **uninitialized_value_construct**(*ExPolicy* &&pol-
icy,
FwdIter first,
Sent last)

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_value_construct* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct* algorithm returns the iterator to the element in the source range, one past the last element constructed.

template<typename **Rng**>
hpx::traits::range_traits<Rng>::iterator_type **uninitialized_value_construct**(*Rng* &&rng)

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the range to which will be value constructed.

Returns

The *uninitialized_value_construct* algorithm returns a *returns* *hpx::traits::range_traits<Rng>::iterator_type*. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename Rng>
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type uninitial
```

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be value constructed

Returns

The *uninitialized_value_construct* algorithm returns a *hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename FwdIter, typename Size>
FwdIter uninitialized_value_construct_n(FwdIter first, Size count)
```

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range [first, first + count) by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a returns *FwdIter*. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_value_construct_n(ExPolicy
&&pol-
icy,
FwdIter
first,
Size
count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::is_heap, hpx::ranges::is_heap_until

Defined in header [hpx/algorithm.hpp](#)⁶¹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng, typename Comp = hpx::parallel::detail::less, typename
Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_heap(ExPolicy &&policy, Rng
&&rng, Comp &&comp =
Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

⁶¹⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp =  
hpx::parallel::detail::less, typename Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_heap(ExPolicy &&policy, Iter first,  
Sent last, Comp &&comp =  
Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
bool is_heap(Rng &&rng, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap* algorithm returns *bool*. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
bool is_heap(Iter first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap* algorithm returns *bool*. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename ExPolicy, typename Rng, typename Comp = hpx::parallel::detail::less, typename  
Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> is_heap_until(ExPolicy  
                                                    &&pol-  
                                                    icy,  
                                                    Rng  
                                                    &&rng,  
                                                    Comp  
                                                    &&comp  
                                                    =  
                                                    Comp(),  
                                                    Proj  
                                                    &&proj  
                                                    =  
                                                    Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most $2 * N$ applications of the projection *proj*, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [*first*, *it*) is a max heap.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp =
    hpx::parallel::detail::less, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> is_heap_until(ExPolicy &&policy, Iter
    first, Sent last, Comp
    &&comp = Comp(), Proj
    &&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [*first*, *it*) is a max heap. The function uses the given comparison function object *comp* (defaults to using *operator<()*).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```
template<typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> is_heap_until(Rng &&rng, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using *operator<()*).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns *RandIter*. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```
template<typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
Iter is_heap_until(Iter first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using *operator<()*).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `is_heap_until` algorithm returns `RandIter`. The `is_heap_until` algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

hpx::ranges::destroy, hpx::ranges::destroy_n

Defined in header `hpx/algorithm.hpp`⁶¹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> destroy(ExPolicy
                                                    &&policy,
                                                    Rng
                                                    &&rng)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range [first, last).

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

⁶¹⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename ExPolicy, typename Iter, typename Sent>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> destroy(ExPolicy &&policy, Iter first,
                                                                    Sent last)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, last).

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename Rng>
hpx::traits::range_iterator<Rng>::type destroy(Rng &&rng)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, last).

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns *void*.

```
template<typename Iter, typename Sent>
```

```
Iter destroy(Iter first, Sent last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, last)`.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns *void*.

```
template<typename ExPolicy, typename FwdIter, typename Size>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type destroy_n(ExPolicy &&policy,  
                                                                                   FwdIter first, Size  
                                                                                   count)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, first + count)`.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename FwdIter, typename Size>
FwdIter destroy_n(FwdIter first, Size count)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range *[first, first + count)*.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::count, hpx::ranges::count_if

Defined in header [hpx/algorithm.hpp](#)⁶¹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
```

⁶¹⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng>

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*. The *count* algorithm returns the number of elements satisfying the given criteria.

template<typename **ExPolicy**, typename **Iter**, typename **Sent**, typename **Proj** = *hpx::identity*,
typename **T** = typename *hpx::parallel::traits::projected<Iter, Proj>::value_type*>

hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<Iter>::difference_type>::type **count** (Ex

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*. The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
```

```

std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::difference_type count(Rng
                                                    &&rng,
                                                    T
                                                    const
                                                    &value,
                                                    Proj
                                                    &&proj
                                                    =
                                                    Proj())

```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

```

template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<Iter, Proj>::value_type>
std::iterator_traits<Iter>::difference_type count(Iter first, Sent last, T const &value, Proj &&proj =
Proj())

```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng>
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count_if* algorithm returns *hpx::future<difference_type>* if the execution policy is of

type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by `std::iterator_traits<FwdIter>::difference_type`. The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj =
    hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<Iter>::difference_type>::type count_if
```

Returns the number of elements in the range `[first, last)` satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count_if* algorithm returns `hpx::future<difference_type>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by `std::iterator_traits<FwdIter>::difference_type`). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::difference_type count_if(Rng
                                                                                                     &&rng,
                                                                                                     F
                                                                                                     &&f,
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
std::iterator_traits<Iter>::difference_type count_if(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version

counts elements for which predicate f returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `count_if` requires F to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `count` algorithm returns the number of elements satisfying the given criteria.

`hpx::ranges::partition`, `hpx::ranges::stable_partition`, `hpx::ranges::partition_copy`

Defined in header `hpx/algorithm.hpp`⁶²⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **ranges**

⁶²⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> partition(Rng &&rng, Pred &&pred, Proj &&proj =
    Proj())
```

Reorders the elements in the range *rng* in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs at most $2 * N$ swaps, exactly N applications of the predicate and projection, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *subrange_t<std::ranges::iterator_t<Rng>>* The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> partition(ExPolicy
    &&pol-
    icy,
    Rng
    &&rng,
    Pred
    &&pred,
    Proj
    &&proj
    =
    Proj())
```


Reorders the elements in the range *rng* in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most $2 * N$ swaps, exactly N applications of the predicate and projection, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is a unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate is invoked.

Returns

The *partition* algorithm returns a `hpx::future<subrange_t<std::ranges::iterator_t<Rng>>>` if the execution policy is of type *parallel_task_policy* and returns `subrange_t<std::ranges::iterator_t<Rng>>` The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename FwdIter, typename Sent, typename Pred, typename Proj = hpx::identity>
subrange_t<FwdIter> partition(FwdIter first, Sent last, Pred &&pred, Proj &&proj = Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *subrange_t<FwdIter>*. The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =
hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter>>::type partition(ExPolicy
&&policy,
FwdIter first,
Sent last,
Pred
&&pred,
Proj &&proj
= Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate is invoked.

Returns

The *partition* algorithm returns a *hpx::future<subrange_t<FwdIter>>* if the execution policy is of type *parallel_task_policy* and returns *subrange_t<FwdIter>* otherwise. The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> stable_partition(Rng &&rng, Pred &&pred, Proj
&&proj = Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) INVOKE(*f*, INVOKE(*proj*, **j*)) != false, and for every iterator *k* in the range [*i*, last), INVOKE(*f*, INVOKE(*proj*, **k*)) == false

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an bidirectional iterator
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), $f(*j) \neq \text{false}$ INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), $f(*k) == \text{false}$ INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> stable_partition(ExPolicy
&&pol-
icy,
Rng
&&rng,
Pred
&&pred
Proj
&&proj
=
Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an bidirectional iterator
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), $f(*j) \neq \text{false}$ INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), $f(*k) == \text{false}$ INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a `future<>` referring to this iterator.

```
template<typename BidirIter, typename Sent, typename Pred, typename Proj = hpx::identity>
subrange_t<BidirIter> stable_partition(BidirIter first, Sent last, Pred &&pred, Proj &&proj =
    Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `BidirIter`.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), `f(*j) != false INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator *k* in the range [*i*, last), `f(*k) == false INVOKE(f, INVOKE(proj, *k)) == false`. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename BidirIter, typename Sent, typename Pred, typename Proj
= hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<BidirIter>>::type stable_partition(ExPolicy
&&pol-
icy,
BidirIter
first,
Sent
last,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) `INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator *k* in the range [*i*, last), `INVOKE(f, INVOKE(proj, *k)) == false`

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly *last* - *first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *BidirIter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [*first*, *last*). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [*first*, *i*), $f(*j) \neq \text{false}$ INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, *last*), $f(*k) == \text{false}$ INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a `future<>` referring to this iterator.

```
template<typename Rng, typename OutIter2, typename OutIter3, typename Pred, typename Proj =
hpx::identity>
partition_copy_result<std::ranges::iterator_t<Rng>, OutIter2, OutIter3> partition_copy(Rng &&rng,
                                                                                      OutIter2
                                                                                      dest_true,
                                                                                      OutIter3
                                                                                      dest_false,
                                                                                      Pred
                                                                                      &&pred,
                                                                                      Proj &&proj
                                                                                      = Proj())
```

Copies the elements in the range *rng*, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the

elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than N assignments, exactly N applications of the predicate *pred*, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a `partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>`. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename Rng, typename FwdIter2, typename FwdIter3, typename Pred, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>
```

Copies the elements in the range *rng*, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than N assignments, exactly N applications of the predicate *pred*, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't

satisfy the predicate *pred*.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a *hpx::future<partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>* if the execution policy is of type *parallel_task_policy* and returns *partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>* otherwise. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename InIter, typename Sent, typename OutIter2, typename OutIter3, typename
Pred, typename Proj = hpx::identity>
partition_copy_result<InIter, OutIter2, OutIter3> partition_copy(InIter first, Sent last, OutIter2
                                                                dest_true, OutIter3 dest_false, Pred
                                                                &&pred, Proj &&proj = Proj())
```

Copies the elements in the range, defined by [first, last), to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a *partition_copy_result*<*FwdIter*, *OutIter2*, *OutIter3*>. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename OutIter2, typename OutIter3, typename Pred, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, partition_copy_result<FwdIter, OutIter2, OutIter3>>::type partition_c
```

Copies the elements in the range, defined by [first, last), to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a *hpx::future<partition_copy_result<FwdIter, OutIter2, OutIter3>>* if the execution policy is of type *parallel_task_policy* and returns *partition_copy_result<FwdIter, OutIter2, OutIter3>* otherwise. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

hpx::ranges::shift_left

Defined in header `hpx/algorithm.hpp`⁶²¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename Size>
FwdIter shift_left(FwdIter first, Sent last, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the beginning of the range. For every integer i in [0, last - first

- n), moves the element originally at position first + n + i to position first + i.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns *FwdIter*. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> shift_left(ExPolicy &&policy,
                                                                              FwdIter first, Sent last,
                                                                              Size n)
```

Shifts the elements in the range [first, last) by n positions towards the beginning of the range. For every integer i in [0, last - first

- n), moves the element originally at position first + n + i to position first + i.

⁶²¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename Rng, typename Size>  
std::ranges::iterator_t<Rng> shift_left(Rng &&rng, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the beginning of the range. For every integer i in [0, last - first

- n), moves the element originally at position first + n + i to position first + i.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *std::ranges::iterator_t<Rng>* must meet the requirements of *MoveAssignable*.

Template Parameters

- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns *std::ranges::iterator_t<Rng>*. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename Rng, typename Size>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> shift_left(ExPolicy
                                                    &&policy,
                                                    Rng
                                                    &&rng,
                                                    Size n)
```

Shifts the elements in the range [first, last) by n positions towards the beginning of the range. For every integer i in [0, last - first

- n), moves the element originally at position first + n + i to position first + i.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *std::ranges::iterator_t<Rng>* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a *hpx::future<std::ranges::iterator_t<Rng>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *std::ranges::iterator_t<Rng>* otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range.

hpx::ranges::set_intersection

Defined in header [hpx/algorithm.hpp](http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp)⁶²².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace ranges
```

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,  
        typename Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename  
        Proj2 = hpx::identity>  
    hpx::parallel::util::detail::algorithm_result<ExPolicy, set_intersection_result<Iter1, Iter2, Iter3>>::type set_intersection
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, the first *std::min(m, n)* elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

⁶²² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.

- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns a *hpx::future<ranges::set_intersection_result<Iter1, Iter2, Iter3>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::set_intersection_result<Iter1, Iter2, Iter3>* otherwise. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =  
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_intersection_result<std::ranges::iterator_t<Rng1>, std::ranges::ite
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first *std::min(m, n)* elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence

and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns a `hpx::future<ranges::set_intersection_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_intersection_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
set_intersection_result<Iter1, Iter2, Iter3> set_intersection(Iter1 first1, Sent1 last1, Iter2 first2,
Sent2 last2, Iter3 dest, Pred &&op =
Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges

[first1, last1) and [first2, last2). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in [first1, last1) and *n* times in [first2, last2), the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op*

is invoked.

Returns

The *set_intersection* algorithm returns *ranges::set_intersection_result<Iter1, Iter2, Iter3>*.

The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less,
        typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```
set_intersection_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> set_intersection(Rng1
&&rng1,
Rng2
&&rng2,
Iter3
dest,
Pred
&&op
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first *std::min(m, n)* elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::less<>*
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns *ranges::set_intersection_result<Iter1, Iter2, Iter3>*. where *Iter1* is *range_iterator_t<Rng1>* and *Iter2* is *range_iterator_t<Rng2>*. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::inclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁶²³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent, typename OutIter, typename Op = std::plus<typename  
std::iterator_traits<InIter>::value_type>>
```

```
inclusive_scan_result<InIter, OutIter> inclusive_scan(InIter first, Sent last, OutIter dest, Op &&op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

⁶²³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

Ret fun(const Type1 &a, const Type1 &b);

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns *util::in_out_result<InIter, OutIter>*. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename
Op = std::plus<typename std::iterator_traits<FwdIter1>::value_type>>
```

```
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<FwdIter1, FwdIter2>>::type inclusive_scan(ExPolicy, FwdIter1, Sent, FwdIter2, Op, ...)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<FwdIter1, FwdIter2>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.


```
template<typename Rng, typename O, typename Op = std::plus<typename
hpx::traits::range_traits<Rng>::value_type>>
inclusive_scan_result<std::ranges::iterator_t<Rng>, O> inclusive_scan(Rng &&rng, O dest, Op
&&op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns *util::in_out_result<std::ranges::iterator_t<*Rng*>, *O*>*. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename Op = std::plus<typename
hpx::traits::range_traits<Rng>::value_type>>
```

`parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<std::ranges::iterator_t<Rng>, O>> inclusive_sca`

Assigns through each iterator i in $[\text{result}, \text{result} + (\text{last} - \text{first}))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM`(`op`, `*first`, ..., `*(first + (i - result))`).

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the i th input element in the i th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when N is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM`(`op`, `a1`, ..., `aK`)
 - `GENERALIZED_NONCOMMUTATIVE_SUM`(`+`, `aM`, ..., `aN`) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by

the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied

```
template<typename InIter, typename Sent, typename OutIter, typename Op, typename T = typename
std::iterator_traits<InIter>::value_type>
```

```
inclusive_scan_result<InIter, OutIter> inclusive_scan(InIter first, Sent last, OutIter dest, Op &&op,
T init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- *a1* when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns `util::in_out_result<InIter, OutIter>`. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename
Op, typename T = typename std::iterator_traits<FwdIter1>::value_type>
```

```
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<FwdIter1, FwdIter2>>::type inclusive_scan(Ex
```

```
&&
icy;
InI
firs
Sen
last
Ou
Iter
des
Op
&&
T
init
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a *hpx::future<util::in_out_result<InIter, OutIter>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *util::in_out_result<InIter, OutIter>* otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename Op, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
inclusive_scan_result<std::ranges::iterator_t<Rng>, O> inclusive_scan(Rng &&rng, O dest, Op
&&op, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns *util::in_out_result<std::ranges::iterator_t<Rng>, O>*. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename Op, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<std::ranges::iterator_t<Rng>, O>> inclusive_sca
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in

unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*1, ..., *a*N) is defined as:

- *a*1 when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*1, ..., *a*K), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*M, ..., *a*N)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied

hpx::ranges::is_sorted, hpx::ranges::is_sorted_until

Defined in header `hpx/algorithm.hpp`⁶²⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename Pred = hpx::parallel::detail::less, typename  
Proj = hpx::identity>
```

```
bool is_sorted(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most (N+S-1) comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element

⁶²⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred =
    hpx::parallel::detail::less, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_sorted(ExPolicy &&policy, FwdIter
    first, Sent last, Pred &&pred
    = Pred(), Proj &&proj =
    Proj())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a `hpx::future<bool>` if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_sorted* algorithm returns a *bool*

if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
bool is_sorted(Rng &&rng, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Determines if the range rng is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most (N+S-1) comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element in the rng satisfies the predicate passed. If the range rng contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename
Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_sorted(ExPolicy &&policy, Rng
&&rng, Pred &&pred =
Pred(), Proj &&proj =
Proj())
```

Determines if the range rng is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N+S-1) comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a `hpx::future<bool>` if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_sorted* algorithm returns a *bool* if each element in the range *rng* satisfies the predicate passed. If the range *rng* contains less than two elements, the function always returns true.

```
template<typename FwdIter, typename Sent, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter is_sorted_until(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred =  
hpx::parallel::detail::less, typename Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type is_sorted_until(ExPolicy  
                                            &&policy,  
                                            FwdIter first,  
                                            Sent last, Pred  
                                            &&pred =  
                                            Pred(), Proj  
                                            &&proj =  
                                            Proj())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> is_sorted_until(Rng &&rng, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Returns the first element in the range *rng* that is not sorted. Uses a predicate to compare elements or the less than operator.

Note: Complexity: at most $(N+S-1)$ comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* returns *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is

returned.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename
Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> is_sorted_until(ExPolicy
&&pol-
icy,
Rng
&&rng,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

Returns the first element in the range *rng* that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = size(*rng*). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::less<>*
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have *const* &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

hpx::ranges::reduce

Defined in header [hpx/algorithm.hpp](#)⁶²⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F, typename T =
typename std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, FwdIter first,
                                                                    Sent last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

⁶²⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename F, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, Rng &&rng, T
init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
- op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and

– $1 < K+1 = M \leq N$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, FwdIter first,
                                                                    Sent last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns T otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator $+$ ()) over the elements given by the input range $[\text{first}, \text{last})$.

```
template<typename ExPolicy, typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, Rng &&rng, T
init)
```

Returns $\text{GENERALIZED_SUM}(+, \text{init}, *first, \dots, *(first + (\text{last} - first) - 1))$.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator $+$).

Note: $\text{GENERALIZED_SUM}(+, a_1, \dots, a_N)$ is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename Sent>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type reduce(B
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the *value_type* of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `T` otherwise (where `T` is the `value_type` of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying `operator+()`) over the elements given by the input range `[first, last)`.

```
template<typename ExPolicy, typename Rng>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng
```

Returns `GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1))`.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the `operator+()`.

Note: The type of the initial value (and the result type) *T* is determined from the `value_type` of the used *FwdIterB*.

Note: `GENERALIZED_SUM(+, a1, ..., aN)` is defined as follows:

- `a1` when `N` is 1
 - `op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN))`, where:
 - `b1, ..., bN` may be any permutation of `a1, ..., aN` and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `T` otherwise (where `T` is the `value_type` of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying `operator+()`) over the elements given by the input range `[first, last)`.

```
template<typename FwdIter, typename Sent, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
T reduce(FwdIter first, Sent last, T init, F &&f)
```

Returns `GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1))`.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- `a1` when `N` is 1
 - `op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN))`, where:
 - `b1, ..., bN` may be any permutation of `a1, ..., aN` and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those

- types.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename Rng, typename F, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
T reduce(Rng &&rng, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename FwdIter, typename Sent, typename T = typename
std::iterator_traits<FwdIter>::value_type>
T reduce(FwdIter first, Sent last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
T reduce(Rng &&rng, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter, typename Sent>
std::iterator_traits<FwdIter>::value_type reduce(FwdIter first, Sent last)
    Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).
```

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the value_type of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns *T* (where T is the value_type of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename Rng>
std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::value_type reduce(Rng
                                                                                               &&rng)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) T is determined from the `value_type` of the used `FwdIterB`.

Note: `GENERALIZED_SUM(+, a1, ..., aN)` is defined as follows:

- a_1 when N is 1
 - `op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN))`, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns T (where T is the `value_type` of `FwdIterB`). The *reduce* algorithm returns the result of the generalized sum (applying `operator+()`) over the elements given by the input range `[first, last)`.

hpx::ranges::transform_reduce

Defined in header `hpx/algorithm.hpp`⁶²⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename Iter, typename Sent, typename T, typename Reduce, typename Convert>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Iter
                                                                    first, Sent last, T init, Reduce
                                                                    &&red_op, Convert
                                                                    &&conv_op)
```

Returns `GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))`.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

⁶²⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced

and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [*first*, *last*).

```
template<typename Iter, typename Sent, typename T, typename Reduce, typename Convert>
T transform_reduce(Iter first, Sent last, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range `[first, last)`.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Iter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Iter
                                                                    first, Sent last, Iter2 first2, T
                                                                    init)
```

Returns GENERALIZED_SUM(*red_op*, *init*, *conv_op*(**first*), ..., *conv_op**(*first* + (*last* - *first*) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(*op*, *a1*, ..., *aN*) is defined as follows:

- *a1* when *N* is 1
 - *op*(GENERALIZED_SUM(*op*, *b1*, ..., *bK*), GENERALIZED_SUM(*op*, *bM*, ..., *bN*)), where:
 - *b1*, ..., *bN* may be any permutation of *a1*, ..., *aN* and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename Iter, typename Sent, typename Iter2, typename T>
```

```
T transform_reduce(Iter first, Sent last, Iter2 first2, T init)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter.

- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Iter, typename Sent, typename Iter2, typename T, typename  
Reduce, typename Convert>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Iter  
first, Sent last, Iter2 first2, T  
init, Reduce &&red_op,  
Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for **Iter**.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename Iter, typename Sent, typename Iter2, typename T, typename Reduce, typename Convert>
```

T **transform_reduce**(*Iter* first, *Sent* last, *Iter2* first2, *T* init, *Reduce* &&red_op, *Convert* &&conv_op)

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename T, typename Reduce, typename Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Rng
&&rng, T init, Reduce
&&red_op, Convert
&&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename Rng, typename T, typename Reduce, typename Convert>  
T transform_reduce(Rng &&rng, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
- op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:

- $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
- $1 < K+1 = M \leq N$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename Iter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Rng
&&rng, Iter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename Rng, typename Iter2, typename T>  
T transform_reduce(Rng &&rng, Iter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.

- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns *T*.

```
template<typename ExPolicy, typename Rng, typename Iter2, typename T, typename Reduce, typename
Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, Rng
&&rng, Iter2 first2, T init,
Reduce &&red_op, Convert
&&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.
- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *op2*. This is a binary predicate. The signature of this predicate should be equivalent to should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *op1*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename Rng, typename Iter2, typename T, typename Reduce, typename Convert>  
T transform_reduce(Rng &&rng, Iter2 first2, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.
- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *op2*. This is a binary predicate. The signature of this predicate should be equivalent to should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *op1*.

Returns

The *transform_reduce* algorithm returns *T*.

hpx::ranges::reverse, hpx::ranges::reverse_copy

Defined in header `hpx/algorithm.hpp`⁶²⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename Iter, typename Sent>
Iter reverse(Iter first, Sent sent)
```

Reverses the order of the elements in the range `[first, last)`. Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a *Iter*. It returns *last*.

```
template<typename Rng>
```

⁶²⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

`std::ranges::iterator_t<Rng> reverse(Rng &&rng)`

Uses *rng* as the source range, as if using `util::begin(rng)` as *first* and `ranges::end(rng)` as *last*. Reverses the order of the elements in the range $[first, last)$. Behaves as if applying `std::iter_swap` to every pair of iterators $first+i, (last-i) - 1$ for each non-negative $i < (last-first)/2$.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::traits::range_iterator<Rng>::type`. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> reverse(ExPolicy &&policy, Iter first,
                                                                    Sent sent)
```

Reverses the order of the elements in the range $[first, last)$. Behaves as if applying `std::iter_swap` to every pair of iterators $first+i, (last-i) - 1$ for each non-negative $i < (last-first)/2$.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::future<Iter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng>
```

```
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> reverse(ExPolicy
&&policy, Rng
&&rng)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Reverses the order of the elements in the range $[first, last)$. Behaves as if applying `std::iter_swap` to every pair of iterators $first+i$, $(last-i) - 1$ for each non-negative $i < (last-first)/2$.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `hpx::future< std::ranges::iterator_t<Rng>>` otherwise. It returns *last*.

```
template<typename Iter, typename Sent, typename OutIter>
reverse_copy_result<Iter, OutIter> reverse_copy(Iter first, Sent last, OutIter result)
```

Copies the elements from the range $[first, last)$ to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, $[first, last)$ and $[result, result+(last-first))$ respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *reverse_copy_result<Iter, OutIter>*. The *reverse_copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename OutIter>
reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter> reverse_copy(Rng &&rng, OutIter result)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range [first, last) to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [result, result+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>*. The *reverse_copy* algorithm returns an object equal to {last, result + N} where $N = last - first$

```
template<typename ExPolicy, typename Iter, typename Sent, typename FwdIter>
parallel::util::detail::algorithm_result<ExPolicy, reverse_copy_result<Iter, FwdIter>>::type reverse_copy(ExPolicy
&&pol-
icy,
Iter
first,
Sent
last,
FwdIter
re-
sult)
```

Copies the elements from the range [first, last) to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [result, result+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a `hpx::future<reverse_copy_result<Iter, FwdIter> >` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *reverse_copy_result<Iter, FwdIter>* otherwise. The *reverse_copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename OutIter>
parallel::util::detail::algorithm_result<ExPolicy, reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>>>:type revers
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range [first, last) to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [result, result+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type

parallel_policy or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *hpx::future<ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>* otherwise. The *reverse_copy* algorithm returns an object equal to {last, result + N} where N = last - first

hpx::ranges::set_symmetric_difference

Defined in header [hpx/algorithm.hpp](#)⁶²⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,  
typename Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename  
Proj2 = hpx::identity>
```

⁶²⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result<ExPolicy, set_symmetric_difference_result<Iter1, Iter2, Iter3>>::type **set_sym**

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns a `hpx::future<ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>` otherwise. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

hpx::parallel::util::detail::algorithm_result<ExPolicy, set_symmetric_difference_result<std::ranges::iterator_t<Rng1>, std::

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns a `hpx::future<ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>`. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
set_symmetric_difference_result<Iter1, Iter2, Iter3> set_symmetric_difference(Iter1 first1, Sent1
                                                                    last1, Iter2 first2,
                                                                    Sent2 last2, Iter3
                                                                    dest, Pred &&op =
                                                                    Pred(), Proj1
                                                                    &&proj1 = Proj1(),
                                                                    Proj2 &&proj2 =
                                                                    Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest*

exactly `std::abs(m-n)` times. If $m > n$, then the last $m-n$ of those elements are copied from `[first1,last1)`, otherwise the last $n-m$ elements are copied from `[first2,last2)`. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns *ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>*. The *set_symmetric_difference* algorithm returns the output iterator to the

element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less,  
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
set_symmetric_difference_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> set_symmetric_di.
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.

- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns *ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>*. where *Iter1* is *range_iterator_t<Rng1>* and *Iter2* is *range_iterator_t<Rng2>*
The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::replace,
hpx::ranges::replace_copy_if

hpx::ranges::replace_if,

hpx::ranges::replace_copy,

Defined in header [hpx/algorithm.hpp](#)⁶²⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

template<typename **Iter**, typename **Sent**, typename **Pred**, typename **Proj** = *hpx::identity*, typename **T** = typename *hpx::parallel::traits::projected<Iter, Proj>::value_type*>

Iter **replace_if**(*Iter* first, *Sent* sent, *Pred* &&pred, *T* const &new_value, *Proj* &&proj = *Proj*())

Replaces all elements satisfying specific criteria (for which predicate *f* returns true) with *new_value* in the range [first, sent).

Effects: Substitutes elements referred by the iterator *it* in the range [first, sent) with *new_value*, when the following corresponding conditions hold: *INVOKE*(*f*, *INVOKE*(*proj*, **it*)) != false

The assignments in the parallel *replace_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent* - *first* applications of the predicate.

⁶²⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for **Iter**.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
std::ranges::iterator_t<Rng> replace_if(Rng &&rng, Pred &&pred, T const &new_value, Proj
&&proj = Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `rng`. This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns an `hpx::traits::range_iterator<Rng>::type`. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Pred, typename Proj =
hpx::identity, typename T = typename hpx::parallel::traits::projected<Iter, Proj>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> replace_if(ExPolicy &&policy, Iter
first, Sent sent, Pred
&&pred, T const
&new_value, Proj &&proj =
Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy*. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity,  
        typename T = typename hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>  
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> replace_if(ExPolicy  
                                                &&policy,  
                                                Rng  
                                                &&rng,  
                                                Pred  
                                                &&pred, T  
                                                const  
                                                &new_value,  
                                                Proj  
                                                &&proj =  
                                                Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by *rng*. This is a unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns a *hpx::future<std::ranges::iterator_t<Rng>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy*. It returns *last*.

```
template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<Iter, Proj>::value_type, typename T2 = T1>
```

```
Iter replace(Iter first, Sent sent, T1 const &old_value, T2 const &new_value, Proj &&proj = Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator *it* in the range [first,last) with *new_value*, when the following corresponding conditions hold: *INVOKE(proj, *i) == old_value*

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns an *Iter*.

```
template<typename Rng, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
std::ranges::iterator_t<Rng> replace(Rng &&rng, T1 const &old_value, T2 const &new_value, Proj
&&proj = Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns an `hpx::traits::range_iterator<Rng>::type`.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Proj = hpx::identity,
typename T1 = typename hpx::parallel::traits::projected<Iter, Proj>::value_type, typename T2 = T1>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> replace(ExPolicy &&policy, Iter first,
Sent sent, T1 const &old_value,
T2 const &new_value, Proj
&&proj = Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range `[first, last)`.

Effects: Substitutes elements referred by the iterator *it* in the range `[first,last)` with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> replace(ExPolicy
&&policy, Rng
&&rng, T1
const
&old_value, T2
const
&new_value,
Proj &&proj =
Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Returns

The *replace* algorithm returns an *hpx::future<hpx::traits::range_iterator<Rng>::type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *hpx::traits::range_iterator<Rng>::type* otherwise.

```
template<typename InIter, typename Sent, typename OutIter, typename Pred, typename T =
typename std::iterator_traits<OutIter>::value_type, typename Proj = hpx::identity>
replace_copy_if_result<InIter, OutIter> replace_copy_if(InIter first, Sent sent, OutIter dest, Pred
&&pred, T const &new_value, Proj
&&proj = Proj())
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE(f, INVOKE(proj, *(first + (i - result)))) != false*

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *InIter*.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyCon-*

structible. (deduced).

- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns a *in_out_result<InIter, OutIter>*. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename OutIter, typename Pred, typename T = typename
std::iterator_traits<OutIter>::value_type, typename Proj = hpx::identity>
replace_copy_if_result<std::ranges::iterator_t<Rng>, OutIter> replace_copy_if(Rng &&rng, OutIter
dest, Pred &&pred,
T const &new_value,
Proj &&proj =
Proj())
```

Copies the all elements from the range *rng* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range [*result*, *result* + (*util::end*(*rng*) - *util::begin*(*rng*))) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE*(*f*, *INVOKE*(*proj*, **(first + (i - result))*)) != *false*

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *util::end*(*rng*) - *util::begin*(*rng*) applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).

- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an *in_out_result*<*std::ranges::iterator_t*<*Rng*>, *OutIter*>. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Pred,  
typename T = typename std::iterator_traits<FwdIter2>::value_type, typename Proj =  
hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, replace_copy_if_result<FwdIter1, FwdIter2>>::type replace_copy_if(
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(f, INVOKE(proj, *(first + (i - result)))) != false`

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *InIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an *hpx::future<FwdIter1, FwdIter2>*. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Pred, typename T =
typename std::iterator_traits<FwdIter>::value_type, typename Proj = hpx::identity>
```

parallel::util::detail::algorithm_result<ExPolicy, replace_copy_if_result<std::ranges::iterator_t<Rng>, FwdIter>>::type **rep**

Copies the all elements from the range *rng* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range $[\text{result}, \text{result} + (\text{util::end}(\text{rng}) - \text{util::begin}(\text{rng}))]$ either *new_value* or $*(\text{first} + (\text{it} - \text{result}))$ depending on whether the following corresponding condition holds: $\text{INVOKE}(\text{f}, \text{INVOKE}(\text{proj}, *(\text{first} + (\text{i} - \text{result})))) \neq \text{false}$

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly $\text{util::end}(\text{rng}) - \text{util::begin}(\text{rng})$ applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[\text{first}, \text{last})$. This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an `hpx::future<in_out_result<std::ranges::iterator_t<Rng>, OutIter>>`. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename Sent, typename OutIter, typename Proj = hpx::identity,
typename T1 = typename hpx::parallel::traits::projected<InIter, Proj>::value_type, typename T2 = T1>
replace_copy_result<InIter, OutIter> replace_copy(InIter first, Sent sent, OutIter dest, T1 const
&old_value, T2 const &new_value, Proj &&proj
= Proj())
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns an `in_out_result<InIter, OutIter>`. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the

destination range, one past the last element copied.

```
template<typename Rng, typename OutIter, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
replace_copy_result<std::ranges::iterator_t<Rng>, OutIter> replace_copy(Rng &&rng, OutIter dest,
                                                                    T1 const &old_value, T2
                                                                    const &new_value, Proj
                                                                    &&proj = Proj())
```

Copies the all elements from the range *rbg* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [*result*, *result* + (*util::end*(*rng*) - *util::begin*(*rng*))) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE*(*proj*, **(first + (i - result))*) == *old_value*

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *util::end*(*rng*) - *util::begin*(*rng*) applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns an *in_out_result*<*std::ranges::iterator_t*<*Rng*>, *OutIter*>. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename
Proj = hpx::identity, typename T1 = typename hpx::parallel::traits::projected<FwdIter1,
Proj>::value_type, typename T2 = T1>
```

```

parallel::util::detail::algorithm_result<ExPolicy, replace_copy_result<FwdIter1, FwdIter2>>::type replace_copy(ExPolicy
&&pol
icy,
FwdIter
first,
Sent
sent,
FwdIter
dest,
T1
const
&old_v
T2
const
&new_v
Proj
&&pro
=
Proj())

```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for Iter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns a `hpx::future<in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result<FwdIter1, FwdIter2>` otherwise. The *copy* algorithm returns the pair of the forward iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Proj = hpx::identity,
        typename T1 = typename hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>,
        Proj>::value_type, typename T2 = T1>
parallel::util::detail::algorithm_result<ExPolicy, replace_copy_result<std::ranges::iterator_t<Rng>, FwdIter>>>::type repla
```

Copies the all elements from the range *rbg* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range `[result, result + (util::end(rng) - util::begin(rng))]` either *new_value* or `*(first + (it - result))` depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `replace_copy` algorithm returns a `hpx::future<in_out_result<std::ranges::iterator_t<Rng>, FwdIter>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `in_out_result<std::ranges::iterator_t<Rng>, FwdIter>>` The `copy` algorithm returns the pair of the input iterator *last* and the forward iterator to the element in the destination range, one past the last element copied.

hpx::ranges::equal

Defined in header `hpx/algorithm.hpp`⁶³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2,
typename Pred = equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, Iter1 first1,
                                                                    Sent1 last1, Iter2 first2, Sent2
                                                                    last2, Pred &&op = Pred(), Proj1
                                                                    &&proj1 = Proj1(), Proj2
                                                                    &&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶³⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate f .

Note: The two ranges are considered equal if, for every iterator i in the range $[\text{first1}, \text{last1})$, $*i$ equals $*(\text{first2} + (i - \text{first1}))$. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `equal` requires `Pred` to meet the requirements of `CopyConstructible`. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types `Type1` and `Type2` must be such that objects of types `FwdIter1` and `FwdIter2` can be dereferenced and then implicitly converted to `Type1` and `Type2` respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The `equal` algorithm returns a `hpx::future<bool>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `bool` otherwise. The `equal` algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range $[\text{first1}, \text{last1})$ does not equal the length of the range $[\text{first2}, \text{last2})$,

it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = equal_to, typename
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, Rng1
&&rng1, Rng2 &&rng2, Pred
&&op = Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range starting at first2, and false otherwise.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =
equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
bool equal(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&op = Pred(), Proj1 &&proj1 =
Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

Note: Complexity: At most min(last1 - first1, last2 - first2) applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1*

and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
bool equal(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range starting at first2, and false otherwise.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

hpx::ranges::all_of, hpx::ranges::any_of, hpx::ranges::none_of

Defined in header `hpx/algorithm.hpp`⁶³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> none_of(ExPolicy &&policy, Rng
                                                                    &&rng, F &&f, Proj &&proj =
                                                                    Proj())
```

Checks if unary predicate *f* returns true for no elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

⁶³¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>


```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> none_of(ExPolicy &&policy, Iter first,
                                                                    Sent last, F &&f, Proj &&proj
                                                                    = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
bool none_of(Rng &&rng, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool none_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential

form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> any_of(ExPolicy &&policy, Rng &&rng,
                                                                    F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> any_of(ExPolicy &&policy, Iter first,
                                                                    Sent last, F &&f, Proj &&proj =
                                                                    Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
bool any_of(Rng &&rng, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool any_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential

form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> all_of(ExPolicy &&policy, Rng &&rng,
                                                                    F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> all_of(ExPolicy &&policy, Iter first,
                                                                    Sent last, F &&f, Proj &&proj =
                                                                    Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```


The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
bool all_of(Rng &&rng, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool all_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential

form, the parallel overload of *none_of* requires *F* to meet the requirements of *Copy-Constructible*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

hpx::ranges::exclusive_scan

Defined in header `hpx/algorithm.hpp`⁶³².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent, typename OutIter, typename T = typename
std::iterator_traits<InIter>::value_type, typename Op = std::plus<T>>
exclusive_scan_result<InIter, OutIter> exclusive_scan(InIter first, Sent last, OutIter dest, T init, Op
&&op = Op())
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1)).

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *ith* input element in the *ith* sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

⁶³² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter1.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename T
= typename std::iterator_traits<FwdIter1>::value_type, typename Op = std::plus<T>>
parallel::util::detail::algorithm_result<ExPolicy, exclusive_scan_result<FwdIter1, FwdIter2>>::type exclusive_scan(Ex
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERAL-

IZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1)).

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aK*), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *aM*, ..., *aN*)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter1*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<util::in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<FwdIter1, FwdIter2>` otherwise. The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type, typename Op = std::plus<T>>
exclusive_scan_result<std::ranges::iterator_t<Rng>, O> exclusive_scan(Rng &&rng, O dest, T init,
                                                                    Op &&op = Op())
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))`

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate `std::plus<T>`.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type, typename Op = std::plus<T>>
```

parallel::util::detail::algorithm_result<ExPolicy, exclusive_scan_result<std::ranges::iterator_t<Rng>, O>> exclusive_sca

Assigns through each iterator i in $[\text{result}, \text{result} + (\text{last} - \text{first}))$ the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the i th input element in the i th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *std::plus<T>*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate

should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>` otherwise. The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::transform_inclusive_scan

Defined in header `hpx/algorithm.hpp`⁶³³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp>
transform_inclusive_scan_result<InIter, OutIter> transform_inclusive_scan(InIter first, Sent last,
                                                                           OutIter dest, BinOp
                                                                           &&binary_op, UnOp
                                                                           &&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1

⁶³³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN) where  $1 < K+1 = M \leq N$ .`

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns *transform_inclusive_scan_result<InIter, OutIter>*. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename BinOp, typename UnOp>
```

parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_result<FwdIter1, FwdIter2>>::type **transform_inc**

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp>
transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O> transform_inclusive_scan(Rng
                                                                                               &&rng,
                                                                                               O
                                                                                               dest,
                                                                                               BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The `transform_inclusive_scan` algorithm returns a `transform_inclusive_scan_result< std::ranges::iterator_t<Rng>, O>`. The `transform_inclusive_scan` algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp>
```

```
parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel `transform_inclusive_scan` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The reduce operations in the parallel `transform_inclusive_scan` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither `conv` nor `op` shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of `transform_inclusive_scan` may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates `op` and `conv`.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp,
typename T = typename std::iterator_traits<InIter>::value_type>
transform_inclusive_scan_result<InIter, OutIter> transform_inclusive_scan(InIter first, Sent last,
                                                                    OutIter dest, BinOp
                                                                    &&binary_op, UnOp
                                                                    &&unary_op, T init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns *transform_inclusive_scan_result<InIter, OutIter>*. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename BinOp, typename UnOp, typename T = typename std::iterator_traits<FwdIter1>::value_type>
```

parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_result<FwdIter1, FwdIter2>>::type **transform_inc**

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a *hpx::future<transform_inclusive_result<FwdIter1, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O> transform_inclusive_scan(Rng
&&rng,
O
dest,
BinOp
&&binary_op,
UnOp
&&unary_op,
T
init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result)))).

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of `transform_inclusive_scan` may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The `transform_inclusive_scan` algorithm returns a `transform_inclusive_scan_result< std::ranges::iterator_t<Rng>, O>`. The `transform_inclusive_scan` algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp, typename T = typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
```

parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a *hpx::future<transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

hpx/parallel/util/range.hpp

Defined in header `hpx/parallel/util/range.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **util**

Typedefs

```
template<typename Iterator, typename Sentinel = Iterator>
using range = hpx::util::iterator_range<Iterator, Sentinel>
```

Functions

```
template<typename Iter, typename Sent>
range<Iter, Sent> concat(range<Iter, Sent> const &it1, range<Iter, Sent> const &it2)

template<typename Iter1, typename Sent1, typename Iter2, typename Sent2>
range<Iter2, Iter2> init_move(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const &src)
```

Move objects from the range src to dest.

Parameters

- **dest** – [in] : range where move the objects
- **src** – [in] : range from where move the objects

Returns

range with the objects moved and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2>
range<Iter2, Sent2> uninit_move(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const
&src)
```

Move objects from the range src creating them in dest.

Parameters

- **dest** – [in] : range where move and create the objects
- **src** – [in] : range from where move the objects

Returns

range with the objects moved and the size adjusted

```
template<typename Iter, typename Sent>
void destroy_range(range<Iter, Sent> r)
```

destroy a range of objects

Parameters

r – [in] : range to destroy

```
template<typename Iter, typename Sent>
range<Iter, Sent> init(range<Iter, Sent> const &r, typename std::iterator_traits<Iter>::value_type
&val)
```

initialize a range of objects with the object val moving across them

Parameters

- **r** – [in] : range of elements not initialized
- **val** – [in] : object used for the initialization

Returns

range initialized

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
bool is_mergeable(range<Iter1, Sent1> const &src1, range<Iter2, Sent2> const &src2, Compare
comp)
```

: indicate if two ranges have a possible merge

Remark

Parameters

- **src1** – [in] : first range
- **src2** – [in] : second range
- **comp** – [in] : object for to compare elements

Returns

true : they can be merged false : they can't be merged

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Sent3, typename Compare>
```

```
range<Iter3, Sent3> full_merge(range<Iter3, Sent3> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

Merge two contiguous ranges src1 and src2 , and put the result in the range dest, returning the range merged.

Parameters

- **dest** – [in] : range where locate the elements merged. the size of dest must be greater or equal than the sum of the sizes of src1 and src2
- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **comp** – [in] : comparison object

Returns

range with the elements merged and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Value,
typename Compare>
```

```
range<Value*> uninit_full_merge(range<Value*> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

Merge two contiguous ranges src1 and src2 , and create and move the result in the uninitialized range dest, returning the range merged.

Parameters

- **dest** – [in] : range where locate the elements merged. the size of dest must be greater or equal than the sum of the sizes of src1 and src2. Initially is un-initialize memory
- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **comp** – [in] : comparison object

Returns

range with the elements merged and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
```

```
range<Iter2, Sent2> half_merge(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

: Merge two buffers. The first buffer is in a separate memory

Parameters

- **dest** – [in] : range where finish the two buffers merged
- **src1** – [in] : first range to merge in a separate memory
- **src2** – [in] : second range to merge, in the final part of the range where deposit the final results
- **comp** – [in] : object for compare two elements of the type pointed by the Iter1 and Iter2

Returns

: range with the two buffers merged

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Sent3, typename Compare>
```

```
bool in_place_merge_uncontiguous(range<Iter1, Sent1> const &src1, range<Iter2, Sent2>
                                const &src2, range<Iter3, Sent3> &aux, Compare comp)
```

: merge two non contiguous buffers src1 , src2, using the range aux as auxiliary memory

Remark

Parameters

- **src1** – [**in**] : first range to merge
- **src2** – [**in**] : second range to merge
- **aux** – [**in**] : auxiliary range used in the merge
- **comp** – [**in**] : object for to compare elements

Returns

true : not changes done false : changes in the buffers

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
```

```
range<Iter1, Sent1> in_place_merge(range<Iter1, Sent1> const &src1, range<Iter1, Sent1> const
                                &src2, range<Iter2, Sent2> &buf, Compare comp)
```

: merge two contiguous buffers (src1, src2) using buf as auxiliary memory

Remark

Parameters

- **src1** – [**in**] : first range to merge
- **src2** – [**in**] : second range to merge
- **buf** – [**in**] : auxiliary memory used in the merge
- **comp** – [**in**] : object for to compare elements

Returns

true : not changes done false : changes in the buffers

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
```

```
void merge_flow(range<Iter1, Sent1> rng1, range<Iter2, Sent2> rbuf, range<Iter1, Sent1> rng2,
                Compare cmp)
```

hpx::reduce_by_key

Defined in header `hpx/algorithm.hpp`⁶³⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename ExPolicy, typename RanIter, typename RanIter2, typename FwdIter1,
typename FwdIter2, typename Compare = std::equal_to<typename
std::iterator_traits<RanIter>::value_type>, typename Func = std::plus<typename
std::iterator_traits<RanIter2>::value_type>>
util::detail::algorithm_result<ExPolicy, util::in_out_result<FwdIter1, FwdIter2>>::type reduce_by_key(ExPolicy
&&pol-
icy,
Ran-
Iter
key_first,
Ran-
Iter
key_last,
Ran-
Iter2
val-
ues_first,
FwdIter1
keys_output,
FwdIter2
val-
ues_output,
Com-
pare
&&comp
=
Com-
pare(),
Func
&&func
=
Func())
```

Reduce by Key performs an inclusive scan reduction operation on elements supplied in key/value pairs. The algorithm produces a single output value for each set of equal consecutive keys in [key_first, key_last). the value being the GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result))). for the run of consecutive matching keys. The number of keys supplied must match the number of values.

⁶³⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RanIter** – The type of the key iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **RanIter2** – The type of the value iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **FwdIter1** – The type of the iterator representing the destination key range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination value range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Compare** – The type of the optional function/function object to use to compare keys (deduced). Assumed to be `std::equal_to` otherwise.
- **Func** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce_by_key* requires *Func* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **key_first** – Refers to the beginning of the sequence of key elements the algorithm will be applied to.
- **key_last** – Refers to the end of the sequence of key elements the algorithm will be applied to.
- **values_first** – Refers to the beginning of the sequence of value elements the algorithm will be applied to.
- **keys_output** – Refers to the start output location for the keys produced by the algorithm.
- **values_output** – Refers to the start output location for the values produced by the algorithm.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **func** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1 Ret* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce_by_key* algorithm returns a `hpx::future<pair<Iter1,Iter2>>` if the exe-

cution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *pair<Iter1,Iter2>* otherwise.

hpx::nth_element

Defined in header [hpx/algorithm.hpp](#)⁶³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename RandomIt, typename Pred = hpx::parallel::detail::less>  
void nth_element(RandomIt first, RandomIt nth, RandomIt last, Pred &&pred = Pred())
```

nth_element is a partial sorting algorithm that rearranges elements in [first, last) such that the element pointed at by *nth* is changed to whatever element would occur in that position if [first, last) were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element. Executed according to the policy.

The comparison operations in the parallel *nth_element* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **RandomIt** – The type of the source begin, *nth*, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second. This defaults to `std::less<>`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to *Type*. This defaults to `std::less<>`.

⁶³⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *nth_element* algorithms returns nothing.

```
template<typename ExPolicy, typename RandomIt, typename Pred = hpx::parallel::detail::less>
void nth_element(ExPolicy &&policy, RandomIt first, RandomIt nth, RandomIt last, Pred &&pred =
    Pred())
```

nth_element is a partial sorting algorithm that rearranges elements in $[first, last)$ such that the element pointed at by *nth* is changed to whatever element would occur in that position if $[first, last)$ were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *nth_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in $\text{std::distance}(first, last)$ on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = last - first$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source begin, *nth*, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second. This defaults to `std::less<>`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to *Type*. This defaults to `std::less<>`.

Returns

The *nth_element* algorithms returns nothing.

hpx::experimental::for_loop, hpx::experimental::for_loop_strided, hpx::experimental::for_loop_n, hpx::experimental::for_loop_n_strided

Defined in header [hpx/algorithm.hpp](#)⁶³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename I, typename ...Args>
void for_loop(std::decay_t<I> first, I last, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last* - *first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

⁶³⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename ...Args>
auto for_loop(ExPolicy &&policy, std::decay_t<I> first, I last, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: I shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of *MoveConstructible*.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last* - *first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding f , an additional argument is passed to each application of f as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of f in the input sequence.

Complexity: Applies f exactly once for each element of the input sequence.

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop* algorithm returns a *hpx::future<void>* if the execution policy is of type *hpx::execution::sequenced_task_policy* or *hpx::execution::parallel_task_policy* and returns *void* otherwise.

```
template<typename I, typename S, typename ...Args>
void for_loop_strided(std::decay_t<I> first, I last, S stride, Args&&... args)
```

The *for_loop_strided* implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble *for_each* from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of *for_loop* without specifying an execution policy is equivalent to specifying *hpx::execution::seq* as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *I* has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename S, typename ...Args>
auto for_loop_strided(ExPolicy &&policy, std::decay_t<I> first, I last, S stride, Args&&... args)
```

The `for_loop_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using *advance* and *distance*.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *I* has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [*first*, *last*) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename I, typename Size, typename ...Args>
void for_loop_n(I first, Size size, Args&&... args)
```

The *for_loop_n* implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble *for_each* from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of *for_loop_n* without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.

- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **Args** – A parameter pack, its last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename Size, typename ...Args>  
auto for_loop_n(ExPolicy &&policy, I first, Size size, Args&&... args)
```

The `for_loop_n` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last* - *first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop_n` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename I, typename Size, typename S, typename ...Args>
void for_loop_n_strided(I first, Size size, S stride, Args&&... args)
```

The `for_loop_n_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: I shall be an integral type or meet the requirements of an input iterator type. The $args$ parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of *MoveConstructible*.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the $args$ parameter pack. The length of the input sequence is $last - first$.

The first element in the input sequence is specified by $first$. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *I* has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename Size, typename S, typename ...Args>  
auto for_loop_n_strided(ExPolicy &&policy, I first, Size size, S stride, Args&&... args)
```

The `for_loop_n_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using *advance* and *distance*.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *I* has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [*first*, *last*) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_n_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

hpx::move

Defined in header `hpx/algorithm.hpp`⁶³⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> move(ExPolicy &&policy, FwdIter1 first,  
                                                                           FwdIter1 last, FwdIter2 dest)
```

Moves the elements in the range `[first, last)`, to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move. Executed according to the policy.

The move assignments in the parallel *move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The move assignments in the parallel *move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* move assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the move assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

⁶³⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename FwdIter1, typename FwdIter2>
FwdIter2 move(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Moves the elements in the range [first, last), to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly *last - first* move assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a *FwdIter2*. The *move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

hpx::starts_with

Defined in header [hpx/algorithm.hpp](#)⁶³⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶³⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::equal_to>  
bool starts_with(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred = Pred())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2)

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **InIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to *hpx::parallel::detail::equal_to*.

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename Pred = ranges::equal_to>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> starts_with(ExPolicy &&policy, InIter1  
first1, InIter1 last1, InIter2  
first2, InIter2 last2, Pred  
&&pred = Pred())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2). Executed according to the policy.

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to *ranges::equal_to*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

hpx::remove_copy, hpx::remove_copy_if

Defined in header [hpx/algorithm.hpp](#)⁶³⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename OutIter, typename T = typename
std::iterator_traits<InIter>::value_type>
OutIter remove_copy(InIter first, InIter last, OutIter dest, T const &value)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the comparison operator returns false when compare to value. The order of the elements that are not removed is preserved.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: **it == value*

The assignments in the parallel *remove_copy* algorithm execute in sequential order in the calling thread.

⁶³⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*, here comparison operator.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type that the result of dereferencing *FwdIter1* is compared to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **value** – Value to be removed.

Returns

The *remove_copy* algorithm returns an *OutIter*. The *remove_copy* algorithm returns the iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T = typename
std::iterator_traits<InIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> remove_copy(ExPolicy &&policy,
                                                                    FwdIter1 first, FwdIter1
                                                                    last, FwdIter2 dest, T const
                                                                    &value)
```

Copies the elements in the range, defined by *[first, last)*, to another range beginning at *dest*. Copies only the elements for which the comparison operator returns false when compare to value. The order of the elements that are not removed is preserved. Executed according to the policy.

Effects: Copies all the elements referred to by the iterator it in the range *[first,last)* for which the following corresponding conditions do not hold: **it == value*

The assignments in the parallel *remove_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*, here comparison operator.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type that the result of dereferencing FwdIter1 is compared to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **value** – Value to be removed.

Returns

The *remove_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *remove_copy* algorithm returns the iterator to the element past the last element copied.

```
template<typename InIter, typename OutIter, typename Pred>
OutIter remove_copy_if(InIter first, InIter last, OutIter dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *pred* returns false. The order of the elements that are not removed is preserved.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: `INVOKE(pred, *it) != false`.

The assignments in the parallel *remove_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements to be removed. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_copy_if* algorithm returns an *OutIter*. The *remove_copy_if* algorithm returns the iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> remove_copy_if(ExPolicy &&policy,
                                                                                   FwdIter1 first,
                                                                                   FwdIter1 last, FwdIter2
                                                                                   dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *pred* returns false. The order of the elements that are not removed is preserved. Executed according to the policy.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: `INVOKE(pred, *it) != false`.

The assignments in the parallel *remove_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_copy_if* requires *Pred* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements to be removed. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_copy_if* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *remove_copy_if* algorithm returns the iterator to the element past the last element copied.

hpx/parallel/algorithms/iota.hpp

Defined in header `hpx/parallel/algorithms/iota.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Sent, typename T>
void iota(FwdIter first, Sent last, T value)
```

Fills the range [first, last) with sequentially increasing values, starting with *value* and repetitively evaluating `++value`.

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly `std::distance(first, last)` assignments and increments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input or output iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

- **T** – The type of the value to be assigned (deduced). This type must be weakly incrementable.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns *void*.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> iota(ExPolicy &&policy, FwdIter first, Sent last, T
                                                                value)
```

Fills the range [first, last) with sequentially increasing values, starting with *value* and repetitively evaluating ++*value*.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **T** – The type of the value to be assigned (deduced). This type must be weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::shift_right

Defined in header `hpx/algorithm.hpp`⁶⁴⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Size>
FwdIter shift_right(FwdIter first, FwdIter last, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns *FwdIter*. The *shift_right* algorithm returns an iterator to the beginning of the resulting range. Specifically: If *n* is 0 or *n* >= (last - first), does nothing and returns *first* and *last* respectively. Otherwise returns *first* + n.

```
template<typename ExPolicy, typename FwdIter, typename Size>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter> shift_right(ExPolicy &&policy, FwdIter
first, FwdIter last, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

⁶⁴⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- $n + i$. Executed according to the policy.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(\text{last} - \text{first}) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_right* algorithm returns an iterator to the beginning of the resulting range. Specifically: If n is 0, does nothing and returns *first*. If $n \geq (\text{last} - \text{first})$, does nothing and returns *last*. Otherwise returns *first* + n .

hpx::is_partitioned

Defined in header [hpx/algorithm.hpp](#)⁶⁴¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁴¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename Pred>
bool is_partitioned(FwdIter first, FwdIter last, Pred &&pred)
```

Determines if the range [first, last) is partitioned.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which pred returns true precedes those for which pred returns false. Otherwise *is_partitioned* returns false. If the range [first, last) contains less than two elements, the function is always true.

```
template<typename ExPolicy, typename FwdIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_partitioned(ExPolicy &&policy, FwdIter
first, FwdIter last, Pred
&&pred)
```

Determines if the range [first, last) is partitioned. Executed according to the policy.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *CopyConstructible* when using a parallel policy.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *[first, last)* contains less than two elements, the function is always true.

hpx::unique, hpx::unique_copy

Defined in header `hpx/algorithm.hpp`⁶⁴².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Pred = hpx::parallel::detail::equal_to, typename Proj =  
hpx::identity>  
FwdIter unique(FwdIter first, FwdIter last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range *[first, last)* and returns a past-the-end iterator for the new logical end of the range.

⁶⁴² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* - 1 applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique* algorithm returns *FwdIter*. The *unique* algorithm returns the iterator to the new end of the range.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::equal_to,
typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type unique(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred =
                                                                    Pred(), Proj &&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range. Executed according to the policy.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *unique* algorithm returns the iterator to the new end of the range.

```
template<typename InIter, typename OutIter, typename Pred = hpx::parallel::detail::equal_to, typename Proj = hpx::identity>
```

```
OutIter unique_copy(InIter first, InIter last, OutIter dest, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Copies the elements from the range [first, last), to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique_copy* algorithm returns a returns *OutIter*. The *unique_copy* algorithm returns the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =
hpx::parallel::detail::equal_to, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type unique_copy(ExPolicy &&policy,
FwdIter1 first, FwdIter1 last,
FwdIter2 dest, Pred &&pred
= Pred(), Proj &&proj =
Proj())
```

Copies the elements from the range [first, last), to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied. Executed according to the policy.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique_copy* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

hpx::adjacent_find

Defined in header `hpx/algorithm.hpp`⁶⁴³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename Pred = hpx::parallel::detail::equal_to>
InIter adjacent_find(InIter first, InIter last, Pred &&pred = Pred())
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of $(result - first) + 1$ and $(last - first) - 1$ application of the predicate where *result* is the value returned

Template Parameters

- **InIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> adjacent_find(ExPolicy &&policy,
                                                                              FwdIter first, FwdIter
                                                                              last, Pred &&pred =
                                                                              Pred())
```

Searches the range [first, last) for two consecutive identical elements. This version uses the given binary predicate *pred*

⁶⁴³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *adjacent_find* is available if the user decides to provide their algorithm their own binary predicate *pred*.

Note: Complexity: Exactly the smaller of $(result - first) + 1$ and $(last - first) - 1$ application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *adjacent_find* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

hpx::remove, hpx::remove_if

Defined in header `hpx/algorithm.hpp`⁶⁴⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

template<typename **FwdIter**, typename **T** = typename `std::iterator_traits<FwdIter>::value_type`>
FwdIter **remove**(*FwdIter* first, *FwdIter* last, *T* const &value)

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements that are equal to *value*.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the `operator==()`.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.

Returns

The *remove* algorithm returns a *FwdIter*. The *remove* algorithm returns the iterator to the new end of the range.

template<typename **ExPolicy**, typename **FwdIter**, typename **T** = typename
`std::iterator_traits<FwdIter>::value_type`>
hpx::parallel::util::detail::algorithm_result_t<*ExPolicy*, *FwdIter*> **remove**(*ExPolicy* &&policy, *FwdIter* first,
FwdIter last, *T* const &value)

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements that are equal to *value*. Executed according to the policy.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁴⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the `operator==()`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.

Returns

The *remove* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove* algorithm returns the iterator to the new end of the range.

```
template<typename FwdIter, typename Pred>  
FwdIter remove_if(FwdIter first, FwdIter last, Pred &&pred)
```

Removes all elements satisfying specific criteria from the range `[first, last)` and returns a past-the-end iterator for the new end of the range. This version removes all elements for which predicate *pred* returns true.

The assignments in the parallel *remove_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_if* algorithm returns a *FwdIter*. The *remove_if* algorithm returns the iterator to the new end of the range.

```
template<typename ExPolicy, typename FwdIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> remove_if(ExPolicy &&policy, FwdIter
first, FwdIter last, Pred
&&pred)
```

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements for which predicate *pred* returns true. Executed according to the policy.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove_if* algorithm returns the iterator to the new end of the range.

hpx::make_heap

Defined in header `hpx/algorithm.hpp`⁶⁴⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename RndIter, typename Comp>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> make_heap(ExPolicy &&policy, RndIter first,  
                                                                    RndIter last, Comp &&comp)
```

Constructs a *max heap* in the range [first, last). Executed according to the policy.

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.

⁶⁴⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Comp** – Comparison function object (i.e. an object that satisfies the requirements of Compare) which returns true if the first argument is less than the second. The signature of the comparison function should be equivalent to the following:

```
bool cmp(const Type1 &a, const Type2 &b);
```

While the signature does not need to have const &, the function must not modify the objects passed to it and must be able to accept all values of type (possibly *const*) *Type1* and *Type2* regardless of value category (thus, *Type1* & is not allowed, nor is *Type1* unless for *Type1* a move is equivalent to a copy. The types *Type1* and *Type2* must be such that an object of type *RandomIt* can be dereferenced and then implicitly converted to both of them.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *make_heap* algorithm returns a *hpx::future<void>* if the execution policy is of type *task_execution_policy* and returns *void* otherwise.

```
template<typename ExPolicy, typename RndIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> make_heap(ExPolicy &&policy, RndIter first,
                                                                    RndIter last)
```

Constructs a *max heap* in the range [first, last). Uses the operator < for comparisons. Executed according to the policy.

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.

Returns

The *make_heap* algorithm returns a *hpx::future<void>* if the execution policy is of type *task_execution_policy* and returns *void* otherwise.

```
template<typename RndIter, typename Comp>  
void make_heap(RndIter first, RndIter last, Comp &&comp)
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.
- **Comp** – Comparison function object (i.e. an object that satisfies the requirements of Compare) which returns true if the first argument is less than the second. The signature of the comparison function should be equivalent to the following:

```
bool cmp(const Type1 &a, const Type2 &b);
```

While the signature does not need to have `const &`, the function must not modify the objects passed to it and must be able to accept all values of type (possibly *const*) *Type1* and *Type2* regardless of value category (thus, *Type1* & is not allowed, nor is *Type1* unless for *Type1* a move is equivalent to a copy. The types *Type1* and *Type2* must be such that an object of type *RandomIt* can be dereferenced and then implicitly converted to both of them.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *make_heap* algorithm returns a *void*.

```
template<typename RndIter>
void make_heap(RndIter first, RndIter last)
    Constructs a max heap in the range [first, last).
```

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

RndIter – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.

Returns

The *make_heap* algorithm returns a *void*.

hpx::experimental::reduction_max

Defined in header [hpx/algorithm.hpp](#)⁶⁴⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::max_of<T>> reduction_max(T
                                                                                                     &var)
```

The function template *reduction_max* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::max_of{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_max* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::max_of{ }` operation until a single value remains, which is then assigned back to the live-out object.

⁶⁴⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The live-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of T . When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of *identity*, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::max_of<T>> reduction_max(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::for_each, hpx::for_each_n

Defined in header `hpx/algorithm.hpp`⁶⁴⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename F>
F for_each(InIter first, InIter last, F &&f)
```

Applies f to the result of dereferencing every iterator in the range $[first, last)$.

If f returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, f may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies f exactly $last - first$ times.

⁶⁴⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **InIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). **F** must meet requirements of *MoveConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

f.

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, void> for_each(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Applies *f* to the result of dereferencing every iterator in the range [first, last). Executed according to the policy.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **FwdIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

`<ignored> pred(const Type &a);`

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *for_each* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `void` otherwise.

```
template<typename InIter, typename Size, typename F>  
InIter for_each_n(InIter first, Size count, F &&f)
```

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *count* times.

Template Parameters

- **InIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). *F* must meet requirements of *MoveConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

Returns

first + count for non-negative values of *count* and *first* for negative values.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
util::detail::algorithm_result_t<ExPolicy, FwdIter> for_each_n(ExPolicy &&policy, FwdIter first, Size
count, F &&f)
```

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1. Executed according to the policy.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each_n* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *count* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each_n* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *for_each_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *first* + *count* for non-negative values of *count* and *first* for negative values.

hpx::transform

Defined in header `hpx/algorithm.hpp`⁶⁴⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter1, typename FwdIter2, typename F>  
FwdIter2 transform(FwdIter1 first, FwdIter1 last, FwdIter2 dest, F &&f)
```

Applies the given function *f* to the range [first, last) and stores the result in another range, beginning at dest.

Note: Complexity: Exactly *last* - *first* applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁶⁴⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *FwdIter2*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> transform(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 dest, F
                                                                    &&f)
```

Applies the given function *f* to the range [first, last) and stores the result in another range, beginning at dest. Executed according to the policy.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename F>  
FwdIter3 transform(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter3 dest, F &&f)
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators for the second range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *FwdIter3*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> transform(ExPolicy &&policy, FwdIter1
                                                                    first1, FwdIter1 last1, FwdIter2
                                                                    first2, FwdIter3 dest, F &&f)
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest. Executed according to the policy.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators for the second range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.

- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *hpx::future<FwdIter3>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter3* otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

hpx::uninitialized_move, hpx::uninitialized_move_n

Defined in header `hpx/algorithm.hpp`⁶⁴⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename FwdIter>  
FwdIter uninitialized_move(InIter first, InIter last, FwdIter dest)
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

⁶⁴⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move* algorithm returns *FwdIter*. The *uninitialized_move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> uninitialized_move(ExPolicy
                                                                    &&policy,
                                                                    FwdIter1 first,
                                                                    FwdIter1 last,
                                                                    FwdIter2 dest)
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state. Executed according to the policy.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move* algorithm returns a *hpx::future<FwdIter2>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename InIter, typename Size, typename FwdIter>
```

std::pair<InIter, FwdIter> uninitialized_move_n(InIter first, Size count, FwdIter dest)

Moves the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the initialization, some objects in [first, first + count) are left in a valid but unspecified state.

Note: Complexity: Performs exactly *count* movements, if count > 0, no move operations otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move_n* algorithm returns a returns *std::pair<InIter, FwdIter>*. The *uninitialized_move_n* algorithm returns A pair whose first element is an iterator to the element past the last element moved in the source range, and whose second element is an iterator to the element past the last element moved in the destination range.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
parallel::util::detail::algorithm_result<ExPolicy, std::pair<FwdIter1, FwdIter2>>>::type uninitialized_move_n(ExPolicy
&&pol-
icy,
FwdIter1
first,
Size
count,
FwdIter2
dest)
```

Moves the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the initialization, some objects in [first, first + count) are left in a valid but unspecified state. Executed according to the policy.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* movements, if count > 0, no move operations otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move_n* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. The *uninitialized_move_n* algorithm returns A pair whose first element is an iterator to the element past the last element moved in the source range, and whose second element is an iterator to the element past the last element moved in the destination range.

hpx::partial_sort

Defined in header `hpx/algorithm.hpp`⁶⁵⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
RandIter partial_sort(RandIter first, RandIter middle, RandIter last, Comp &&comp = Comp())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **RandIter** – The type of the source begin, middle, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.

⁶⁵⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. It defaults to `detail::less`.

Returns

The *partial_sort* algorithm returns a *RandIter* that refers to *last*.

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> partial_sort(ExPolicy &&policy, RandIter
                                                                    first, RandIter middle, RandIter
                                                                    last, Comp &&comp =
                                                                    Comp())
```

Places the first middle - first elements from the range `[first, last)` as sorted with respect to `comp` into the range `[first, middle)`. The rest of the elements in the range `[middle, last)` are placed in an unspecified order.

Note: Complexity: Approximately $(last - first) * \log(middle - first)$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RandIter** – The type of the source begin, middle, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. It defaults to `detail::less`.

Returns

The *partial_sort* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The iterator returned refers to *last*.

hpx::search, hpx::search_n

Defined in header [hpx/algorithm.hpp](#)⁶⁵¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename FwdIter2, typename Pred = parallel::detail::equal_to>
FwdIter search(FwdIter first, FwdIter last, FwdIter2 s_first, FwdIter2 s_last, Pred &&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::equal_to<>*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

⁶⁵¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence `[s_first, s_last)` in range `[first, last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Pred =  
parallel::detail::equal_to>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> search(ExPolicy &&policy, FwdIter first,  
                                                                           FwdIter last, FwdIter2 s_first,  
                                                                           FwdIter2 s_last, Pred &&op =  
                                                                           Pred())
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Uses a provided predicate to compare elements. Executed according to the policy.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S \cdot N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [*s_first*, *s_last*) in range [*first*, *last*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *last*), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename FwdIter, typename Searcher>
FwdIter search(FwdIter first, FwdIter last, Searcher &&searcher)
```

Searches the range [*first*, *last*) using a searcher object.

Template Parameters

- **FwdIter** – The type of the source iterators (deduced). This iterator type must meet the requirements of a forward iterator.
- **Searcher** – A callable searcher object meeting the C++ Searcher requirements (e.g. `std::boyer_moore_searcher`).

Parameters

- **first** – Refers to the beginning of the sequence to search.
- **last** – Refers to the end of the sequence to search.
- **searcher** – A callable object performing the search.

Returns

An iterator to the beginning of the found subsequence, or *last* if no subsequence is found.

```
template<typename ExPolicy, typename FwdIter, typename Searcher>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> search(ExPolicy &&policy, FwdIter first,
                                                                 FwdIter last, Searcher
                                                                 &&searcher)
```

Searches the range [*first*, *last*) using a searcher object. Executed according to the policy.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced).

- **FwdIter** – The type of the source iterators (deduced).
- **Searcher** – A callable searcher object meeting the C++ Searcher requirements.

Parameters

- **policy** – The execution policy to use.
- **first** – Refers to the beginning of the sequence to search.
- **last** – Refers to the end of the sequence to search.
- **searcher** – A callable object performing the search.

Returns

The algorithm returns a `hpx::future<FwdIter>` if the execution policy is a task policy, or `FwdIter` otherwise.

```
template<typename FwdIter, typename FwdIter2, typename Pred = parallel::detail::equal_to>  
FwdIter search_n(FwdIter first, std::size_t count, FwdIter2 s_first, FwdIter2 s_last, Pred &&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel `search_n` algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{count}$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `search_n` requires `Pred` to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *search_n* algorithm returns *FwdIter*. The *search_n* algorithm returns an iterator to the beginning of the last subsequence `[s_first, s_last)` in range `[first, first+count)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, first+count)`, *first* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Pred =
parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> search_n(ExPolicy &&policy, FwdIter
first, std::size_t count, FwdIter2
s_first, FwdIter2 s_last, Pred
&&op = Pred())
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Uses a provided predicate to compare elements. Executed according to the policy.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S \cdot N)$ comparisons where S = distance(`s_first`, `s_last`) and N = count.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search_n* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.

- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [s_first, s_last) in range [first, first+count). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, first+count), *first* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

hpx::set_difference

Defined in header `hpx/algorithm.hpp`⁶⁵².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename
Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> set_difference(ExPolicy &&policy,
                                          FwdIter1 first1,
                                          FwdIter1 last1,
                                          FwdIter2 first2,
                                          FwdIter2 last2,
                                          FwdIter3 dest, Pred
                                          &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range [first1, last1) and not present in the range [first2, last2). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

Equivalent elements are treated individually, that is, if some element is found *m* times in [first1, last1) and *n* times in [first2, last2), it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

⁶⁵² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_difference* algorithm returns a `hpx::future<FwdIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The

set_difference algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
FwdIter3 set_difference(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest,  
                        Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range [*first1*, *last1*) and not present in the range [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

Equivalent elements are treated individually, that is, if some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), it will be copied to *dest* exactly $\text{std::max}(m-n, 0)$ times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_difference* algorithm returns a *FwdIter3*. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::transform_exclusive_scan

Defined in header `hpx/algorithm.hpp`⁶⁵³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<InIter>::value_type>
OutIter transform_exclusive_scan(InIter first, InIter last, OutIter dest, T init, BinOp &&binary_op,
                                UnOp &&unary_op)
```

Transforms each element in the range `[first, last)` with *unary_op*, then computes an exclusive prefix sum operation using *binary_op* over the resulting range, with *init* as the initial value, and writes the results to the range beginning at *dest*. “exclusive” means that the *i*-th input element is not included in the *i*-th sum. Formally, assigns through each iterator *i* in `[dest, d_first + (last - first))` the value of the generalized noncommutative sum of *init*, *unary_op*(**j*)... for every *j* in `[first, first + (i - d_first))` over *binary_op*, where generalized noncommutative sum *GNSUM*(*op*, *a1*, ..., *aN*) is defined as follows:

- if *N*=1, *a1*
- if *N* > 1, *op*(*GNSUM*(*op*, *a1*, ..., *aK*), *GNSUM*(*op*, *aM*, ..., *aN*)) for any *K* where $1 < K+1 = M \leq N$ In other words, the summation operations may be performed in arbitrary order, and the behavior is nondeterministic if *binary_op* is not associative.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *unary_op* nor *binary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1

⁶⁵³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN) where  $1 < K+1 = M \leq N$ .`

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Binary *FunctionObject* that will be applied to the result of *unary_op*, the results of other *binary_op*, and *init*.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_exclusive_scan* algorithm returns a returns *OutIter*. The *transform_exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp,
        typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type transform_exclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, T init,
                                                                                               BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))`. Executed according to the policy.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *unary_op* nor *binary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of each of *binary_op* and *unary_op*.

Note: *GENERALIZED_NONCOMMUTATIVE_SUM*(*op*, *a*₁, ..., *a*_N) is defined as:

- *a*₁ when *N* is 1
 - *op*(*GENERALIZED_NONCOMMUTATIVE_SUM*(*op*, *a*₁, ..., *a*_K), *GENERALIZED_NONCOMMUTATIVE_SUM*(*op*, *a*_M, ..., *a*_N) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init*.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_exclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform_exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::experimental::induction

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

template<typename **T**>

constexpr *hpx::parallel::detail::induction_stride_helper<T>* **induction**(*T* &&value, *std::size_t* stride)

The function template returns an induction object of unspecified type having a value type and encapsulating an initial *value* of that type and, optionally, a stride.

For each element in the input range, a looping algorithm over input sequence *S* computes an induction value from an induction variable and ordinal position *p* within *S* by the formula $i + p * \text{stride}$ if a stride was specified or $i + p$ otherwise. This induction value is passed to the element access function.

If the *value* argument to *induction* is a non-const lvalue, then that lvalue becomes the live-out object for the returned induction object. For each induction object that has a live-out object, the looping algorithm assigns the value of $i + n * \text{stride}$ to the live-out object upon return, where *n* is the number of elements in the input range.

Template Parameters

T – The value type to be used by the induction object.

Parameters

- **value** – [in] The initial value to use for the induction object
- **stride** – [in] The (optional) stride to use for the induction object (default: 1)

Returns

This returns an induction object with value type *T*, initial *value*, and (if specified) *stride*. If *T* is a lvalue of non-const type, *value* is used as the live-out object for the induction object; otherwise there is no live-out object.

template<typename **T**>

constexpr *hpx::parallel::detail::induction_helper<T>* **induction**(*T* &&value)

⁶⁵⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

hpx::uninitialized_default_construct, hpx::uninitialized_default_construct_n

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter>
void uninitialized_default_construct(FwdIter first, FwdIter last)
```

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_default_construct* algorithm returns nothing

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> uninitialized_default_construct(ExPolicy
                                                                                          &&policy,
                                                                                          FwdIter
                                                                                          first,
                                                                                          FwdIter
                                                                                          last)
```

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁵⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

```
template<typename FwdIter, typename Size>  
FwdIter uninitialized_default_construct_n(FwdIter first, Size count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by default-initialization. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a *FwdIter*. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
```

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_default_construct_n(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter
                                                                                                     first,
                                                                                                     Size
                                                                                                     count)

```

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range `[first, first + count)` by default-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel `uninitialized_default_construct_n` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The assignments in the parallel `uninitialized_default_construct_n` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The `uninitialized_default_construct_n` algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `FwdIter` otherwise. The `uninitialized_default_construct_n` algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::min_element, hpx::max_element, hpx::minmax_element

Defined in header `hpx/algorithm.hpp`⁶⁵⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>
FwdIter min_element(FwdIter first, FwdIter last, F &&f)
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *min_element* algorithm returns *FwdIter*. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> min_element(ExPolicy &&policy, FwdIter
first, FwdIter last, F &&f)
```

⁶⁵⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Finds the smallest element in the range `[first, last)` using the given comparison function `f`. Executed according to the policy.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *min_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *min_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>
FwdIter max_element(FwdIter first, FwdIter last, F &&f)
```

Finds the largest element in the range `[first, last)` using the given comparison function `f`.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if left argument is less than the right element. This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *max_element* algorithm returns *FwdIter*. The *max_element* algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns `last` if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type max_element(ExPolicy &&policy,
                                                                                   FwdIter first, FwdIter
                                                                                   last, F &&f)
```

Removes all elements satisfying specific criteria from the range Finds the largest element in the range `[first, last)` using the given comparison function *f*. Executed according to the policy.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if left argument is less than the right element. This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *max_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>
minmax_element_result<FwdIter> minmax_element(FwdIter first, FwdIter last, F &&f)
```

Finds the largest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*>. The *minmax_element* algorithm returns a pair consisting of an iterator to the smallest element as the min element and an iterator to the largest element as the max element. Returns *minmax_element_result*<*FwdIter*>{*first*,*first*} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<FwdIter>> minmax_element(ExPolicy
&&pol-
icy,
FwdIter
first,
FwdIter
last,
F
&&f)
```

Finds the largest element in the range [*first*, *last*) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *minmax_element* algorithm returns a `hpx::future<minmax_element_result<FwdIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *minmax_element_result<FwdIter>* otherwise. The *minmax_element* algorithm returns a pair consisting of an iterator to the smallest element as the min element and an iterator to the largest element as the max element. Returns *std::make_pair(first,first)* if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

hpx::copy, hpx::copy_n, hpx::copy_if

Defined in header `hpx/algorithm.hpp`⁶⁵⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> copy(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Executed according to the policy.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶⁵⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2>  
FwdIter2 copy(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a *FwdIter2*. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.


```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> copy_n(ExPolicy &&policy, FwdIter1
                                                                    first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. Executed according to the policy.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy_n* algorithm returns Iterator in the destination range, pointing past the last element copied if count>0 or result otherwise.

```
template<typename FwdIter1, typename Size, typename FwdIter2>
FwdIter2 copy_n(FwdIter1 first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a *FwdIter2* . The *copy_n* algorithm returns Iterator in the destination range, pointing past the last element copied if count>0 or result otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> copy_if(ExPolicy &&policy, FwdIter1  
first, FwdIter1 last, FwdIter2  
dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *f* returns true. The order of the elements that are not removed is preserved. Executed according to the policy.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *copy_if* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy_if* algorithm returns output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
FwdIter2 copy_if(FwdIter1 first, FwdIter1 last, FwdIter2 dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *f* returns true. The order of the elements that are not removed is preserved.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *copy_if* algorithm returns a *FwdIter2*. The *copy_if* algorithm returns output iterator to the element in the destination range, one past the last element copied.

hpx::swap_ranges

Defined in header `hpx/algorithm.hpp`⁶⁵⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter1, typename FwdIter2>
FwdIter2 swap_ranges(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2)
```

Exchanges elements between range `[first1, last1)` and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first1* and *last1*.

Template Parameters

- **FwdIter1** – The type of the first range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.

Returns

The *swap_ranges* algorithm returns *FwdIter2*. The *swap_ranges* algorithm returns iterator to the element past the last element exchanged in the range beginning with *first2*.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
```

⁶⁵⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> swap_ranges(ExPolicy &&policy,
                                                                              FwdIter1 first1, FwdIter1
                                                                              last1, FwdIter2 first2)
```

Exchanges elements between range [first1, last1) and another range starting at *first2*. Executed according to the policy.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first1* and *last1*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the swap operations.
- **FwdIter1** – The type of the first range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.

Returns

The *swap_ranges* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter2* otherwise. The *swap_ranges* algorithm returns iterator to the element past the last element exchanged in the range beginning with *first2*.

hpx::mismatch

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁵⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> mismatch(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter1
                                                                                               first1,
                                                                                               FwdIter1
                                                                                               last1,
                                                                                               FwdIter2
                                                                                               first2,
                                                                                               FwdIter2
                                                                                               last2,
                                                                                               Pred
                                                                                               &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2,last2). If last2 is not provided, it denotes first2 + (last1 - first1). Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range [first1,last1), **i* mismatches *(first2 + (i - first1)). This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> mismatch(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter1
                                                                                                     first1,
                                                                                                     FwdIter1
                                                                                                     last1,
                                                                                                     FwdIter2
                                                                                                     first2,
                                                                                                     FwdIter2
                                                                                                     last2)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`. Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of `operator==`. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no

applications of *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[first1, last1)$, **i* mismatches $*(first2 + (i - first1))$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a *hpx::future<std::pair<FwdIter1, FwdIter2>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *std::pair<FwdIter1, FwdIter2>* otherwise. If no mismatches are found when the comparison reaches *last1* or *last2*, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> mismatch(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter1
                                                                                               first1,
                                                                                               FwdIter1
                                                                                               last1,
                                                                                               FwdIter2
                                                                                               first2,
                                                                                               Pred
                                                                                               &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by $[first1, last1)$ and another defined by $[first2, last2)$. If *last2* is not provided, it denotes $first2 + (last1 - first1)$. Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\text{last1} - \text{first1}$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1, FwdIter2>>` if the

execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *std::pair<FwdIter1,FwdIter2>* otherwise. If no mismatches are found when the comparison reaches last1 or last2, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> mismatch(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter1
                                                                                               first1,
                                                                                               FwdIter1
                                                                                               last1,
                                                                                               FwdIter2
                                                                                               first2)
```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2,last2). If last2 is not provided, it denotes first2 + (last1 - first1). Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last1 - first1 applications of *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and (last1 - first1) != (last2 - first2) then no applications of *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range [first1,last1), **i* mismatches *(first2 + (i - first1)). This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::equal_to<>*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. If no mismatches are found when the comparison reaches last1 or last2, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
std::pair<FwdIter1, FwdIter2> mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2,
                                     Pred &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2,last2). If last2 is not provided, it denotes first2 + (last1 - first1).

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range [first1,last1), **i* mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1,FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2>
std::pair<FwdIter1, FwdIter2> mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of `operator==`. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of `operator==` are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1,last1)`, `*i` mismatches `*(first2 + (i - first1))`. This overload of *mismatch* uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1,FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
std::pair<FwdIter1, FwdIter2> mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, Pred &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2, last2). If last2 is not provided, it denotes first2 + (last1 - first1).

Note: Complexity: At most last1 - first1 applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and (last1 - first1) != (last2 - first2) then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range [first1, last1), **i* mismatches *(first2 + (i - first1)). This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1, FwdIter2>`. If no mismatches are found when the comparison reaches last1 or last2, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2>
std::pair<FwdIter1, FwdIter2> mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2)
```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2, last2). If last2 is not provided, it denotes first2 + (last1 - first1).

Note: Complexity: At most $\text{last1} - \text{first1}$ applications of `operator==`. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of `operator==` are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of `mismatch` uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `mismatch` requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The `mismatch` algorithm returns a `std::pair<FwdIter1, FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

`hpx::find`, `hpx::find_if`, `hpx::find_if_not`, `hpx::find_end`, `hpx::find_first_of`

Defined in header `hpx/algorithm.hpp`⁶⁶⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁶⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter, typename T>
util::detail::algorithm_result_t<ExPolicy, FwdIter> find(ExPolicy &&policy, FwdIter first, FwdIter last, T
                                                         const &val)
```

Returns the first element in the range [first, last) that is equal to value. Executed according to the policy.

The comparison operations in the parallel *find* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the operator==().

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to find (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **val** – the value to compare the elements to

Returns

The *find* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find* algorithm returns the first element in the range [first,last) that is equal to *val*. If no such element in the range of [first,last) is equal to *val*, then the algorithm returns *last*.

```
template<typename InIter, typename T>
InIter find(InIter first, InIter last, T const &val)
```

Returns the first element in the range [first, last) that is equal to value. Executed according to the policy.

Note: Complexity: At most last - first applications of the operator==().

Template Parameters

- **InIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.

- **T** – The type of the value to find (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **val** – the value to compare the elements to

Returns

The *find* algorithm returns a *InIter*. The *find* algorithm returns the first element in the range [first,last) that is equal to *val*. If no such element in the range of [first,last) is equal to *val*, then the algorithm returns *last*.

```
template<typename ExPolicy, typename FwdIter, typename F>  
util::detail::algorithm_result_t<ExPolicy, FwdIter> find_if(ExPolicy &&policy, FwdIter first, FwdIter last,  
                                                             F &&f)
```

Returns the first element in the range [first, last) for which predicate *f* returns true. Executed according to the policy.

The comparison operations in the parallel *find_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns true for the required element. The signature of the predicate should be equivalent to:


```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_if* algorithm returns the first element in the range `[first,last)` that satisfies the predicate *f*. If no such element exists that satisfies the predicate *f*, the algorithm returns *last*.

```
template<typename InIter, typename F>
InIter find_if(InIter first, InIter last, F &&f)
```

Returns the first element in the range `[first, last)` for which predicate *f* returns true.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns true for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if* algorithm returns a *InIter*. The *find_if* algorithm returns the first element in the range `[first,last)` that satisfies the predicate *f*. If no such element exists that satisfies the predicate *f*, the algorithm returns *last*.

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, FwdIter> find_if_not(ExPolicy &&policy, FwdIter first, FwdIter
                                                                last, F &&f)
```

Returns the first element in the range `[first, last)` for which predicate *f* returns false. Executed according to the policy.

The comparison operations in the parallel *find_if_not* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_if_not* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns false for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if_not* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_if_not* algorithm returns the first element in the range `[first, last)` that does **not** satisfy the predicate *f*. If no such element exists that does not satisfy the predicate *f*, the algorithm returns *last*.

```
template<typename FwdIter, typename F>  
FwdIter find_if_not(FwdIter first, FwdIter last, F &&f)
```

Returns the first element in the range `[first, last)` for which predicate *f* returns false.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns false for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if_not* algorithm returns a *FwdIter*. The *find_if_not* algorithm returns the first element in the range [first, last) that does **not** satisfy the predicate *f*. If no such element exists that does not satisfy the predicate *f*, the algorithm returns *last*.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> find_end(ExPolicy &&policy, FwdIter1 first1, FwdIter1
                                                             last1, FwdIter2 first2, FwdIter2 last2, Pred
                                                             &&op = Pred())
```

Returns the last subsequence of elements [first2, last2) found in the range [first, last) using the given predicate *op* to compare elements. Executed according to the policy.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *find_end* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *replace* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_end* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_end* algorithm returns an iterator to the beginning of the last subsequence `[first2, last2)` in range `[first, last)`. If the length of the subsequence `[first2, last2)` is greater than the length of the range `[first1, last1)`, *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> find_end(ExPolicy &&policy, FwdIter1 first1, FwdIter1
                                                             last1, FwdIter2 first2, FwdIter2 last2)
```

Returns the last subsequence of elements `[first2, last2)` found in the range `[first, last)`. Elements are compared using *operator==*. Executed according to the policy.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_end* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_end* algorithm returns an iterator to the beginning of the last subsequence [first2, last2) in range [first, last). If the length of the subsequence [first2, last2) is greater than the length of the range [first1, last1), *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
FwdIter1 find_end(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns the last subsequence of elements [first2, last2) found in the range [first, last) using the given predicate *op* to compare elements.

This overload of *find_end* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *replace* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_end* algorithm returns a *FwdIter1*. The *find_end* algorithm returns an iterator to the beginning of the last subsequence `[first2, last2)` in range `[first, last)`. If the length of the subsequence `[first2, last2)` is greater than the length of the range `[first1, last1)`, *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename FwdIter1, typename FwdIter2>
FwdIter1 find_end(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns the last subsequence of elements `[first2, last2)` found in the range `[first, last)`. Elements are compared using *operator==*.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_end* algorithm returns a *FwdIter1*. The *find_end* algorithm returns an iterator to the beginning of the last subsequence [first2, last2) in range [first, last). If the length of the subsequence [first2, last2) is greater than the length of the range [first1, last1), *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> find_first_of(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 s_first,
                                                                    FwdIter2 s_last, Pred &&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses binary predicate *op* to compare elements. Executed according to the policy.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *find_first_of* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.

- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_first_of* algorithm returns a *hpx::future<FwdIter1>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter1* otherwise. The *find_first_of* algorithm returns an iterator to the first element in the range `[first, last)` that is equal to an element from the range `[s_first, s_last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> find_first_of(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 s_first,
                                                                    FwdIter2 s_last)
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Elements are compared using *operator==*. Executed according to the policy.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S \cdot N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_first_of* algorithm returns a *hpx::future<FwdIter1>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter1* otherwise. The *find_first_of* algorithm returns an iterator to the first element in the range [first, last) that is equal to an element from the range [s_first, s_last). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, last), *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
FwdIter1 find_first_of(FwdIter1 first, FwdIter1 last, FwdIter2 s_first, FwdIter2 s_last, Pred &&op =
    Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses binary predicate *op* to compare elements.

This overload of *find_first_of* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_first_of* algorithm returns a *FwdIter1*. The *find_first_of* algorithm returns an iterator to the first element in the range `[first, last)` that is equal to an element from the range `[s_first, s_last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename FwdIter1, typename FwdIter2>
```

```
FwdIter1 find_first_of(FwdIter1 first, FwdIter1 last, FwdIter2 s_first, FwdIter2 s_last)
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Elements are compared using *operator==*.

Note: Complexity: at most $(S \cdot N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_first_of* algorithm returns a *FwdIter1*. The *find_first_of* algorithm returns an iterator to the first element in the range `[first, last)` that is equal to an element from the range `[s_first, s_last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename ExPolicy, typename BidIter, typename T>
```

```
util::detail::algorithm_result_t<ExPolicy, BidIter> find_last(ExPolicy &&policy, BidIter first, BidIter last, T const &val)
```

Returns the last element in the range `[first, last)` that is equal to *val*. Executed according to the policy.

The comparison operations in the parallel *find_last* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_last* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the operator `==`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **T** – The type of the value to find (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **val** – The value to find.

Returns

The *find_last* algorithm returns a `hpx::future<BidIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *BidIter* otherwise. The *find_last* algorithm returns an iterator to the last element in the range `[first, last)` that is equal to *val*. If no such element is found, the function returns *last*.

```
template<typename InIter, typename T>
InIter find_last(InIter first, InIter last, T const &val)
```

Returns the last element in the range `[first, last)` that is equal to *val*.

Note: Complexity: At most *last - first* applications of the operator `==`.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to find (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **val** – The value to find.

Returns

The *find_last* algorithm returns a *InIter*. The *find_last* algorithm returns an iterator to the last element in the range [first, last) that is equal to *val*. If no such element is found, the function returns *last*.

```
template<typename ExPolicy, typename BidIter, typename F>  
util::detail::algorithm_result_t<ExPolicy, BidIter> find_last_if(ExPolicy &&policy, BidIter first, BidIter  
last, F &&f)
```

Returns the last element in the range [first, last) for which predicate *f* returns true. Executed according to the policy.

The comparison operations in the parallel *find_last_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_last_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/predicate to use (deduced). Must be callable with the type of the elements in the range.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The predicate to check.

Returns

The *find_last_if* algorithm returns a *hpx::future<BidIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *BidIter* otherwise. The *find_last_if* algorithm returns an iterator to the last element in the range [first, last) for which predicate *f* returns true. If no such element is found, the function returns *last*.

```
template<typename InIter, typename F>  
InIter find_last_if(InIter first, InIter last, F &&f)
```

Returns the last element in the range [first, last) for which predicate *f* returns true.

Note: Complexity: At most *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/predicate to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The predicate to check.

Returns

The *find_last_if* algorithm returns a *InIter*. The *find_last_if* algorithm returns an iterator to the last element in the range [first, last) for which predicate *f* returns true. If no such element is found, the function returns *last*.

```
template<typename ExPolicy, typename BidiIter, typename F>
util::detail::algorithm_result_t<ExPolicy, BidiIter> find_last_if_not(ExPolicy &&policy, BidiIter first,
                                                                    BidiIter last, F &&f)
```

Returns the last element in the range [first, last) for which predicate *f* returns false. Executed according to the policy.

The comparison operations in the parallel *find_last_if_not* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_last_if_not* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidiIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/predicate to use (deduced). Must be callable with the type of the elements in the range.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The predicate to check.

Returns

The *find_last_if_not* algorithm returns a *hpx::future<BidIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *BidIter* otherwise. The *find_last_if_not* algorithm returns an iterator to the last element in the range [first, last) for which predicate *f* returns false. If no such element is found, the function returns *last*.

```
template<typename InIter, typename F>  
InIter find_last_if_not(InIter first, InIter last, F &&f)
```

Returns the last element in the range [first, last) for which predicate *f* returns false.

Note: Complexity: At most *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/predicate to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The predicate to check.

Returns

The *find_last_if_not* algorithm returns a *InIter*. The *find_last_if_not* algorithm returns an iterator to the last element in the range [first, last) for which predicate *f* returns false. If no such element is found, the function returns *last*.

hpx::experimental::reduction_plus

Defined in header [hpx/algorithm.hpp](#)⁶⁶¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

⁶⁶¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::plus<T>>> reduction_plus(T &var)
```

The function template *reduction_plus* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::plus{}` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_plus* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::plus{}` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::plus<T>>> reduction_plus(T &var, T const
                                                                    &identity)
```

hpx::experimental::reduction_min

Defined in header `hpx/algorithm.hpp`⁶⁶².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁶² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

namespace **experimental**

Top-level namespace.

Functions

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::min_of<T>> reduction_min(T
                                                                                                     &var)
```

The function template *reduction_min* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::min_of{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_min* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::min_of{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::min_of<T>> reduction_min(T
                                                                                                     &var,
                                                                                                     T
                                                                                                     const
                                                                                                     &iden-
                                                                                                     tity)
```


hpx::rotate, hpx::rotate_copy

Defined in header [hpx/algorithm.hpp](#)⁶⁶³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter>
FwdIter rotate(FwdIter first, FwdIter new_first, FwdIter last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element new_first becomes the first element of the new range and new_first - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *FwdIter*. The *rotate* algorithm returns the iterator to the new location of the element pointed by first, equal to first + (last - new_first).

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> rotate(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter new_first, FwdIter last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element new_first becomes the first element of the new range and new_first - 1 becomes the last element. Executed according to the policy.

⁶⁶³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *rotate* algorithm returns the iterator equal to *first* + (*last* - *new_first*).

```
template<typename FwdIter, typename OutIter>  
OutIter rotate_copy(FwdIter first, FwdIter new_first, FwdIter last, OutIter dest_first)
```

Copies the elements from the range [*first*, *last*), to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **OutIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Refers to the begin of the destination range.

Returns

The *rotate_copy* algorithm returns a output iterator, The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> rotate_copy(ExPolicy &&policy,
                                          FwdIter1 first, FwdIter1
                                          new_first, FwdIter1 last,
                                          FwdIter2 dest_first)
```

Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element. Executed according to the policy.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Refers to the begin of the destination range.

Returns

The *rotate_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type

parallel_task_policy and returns `FwdIter2` otherwise. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

hpx::includes

Defined in header `hpx/algorithm.hpp`⁶⁶⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =  
hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool>::type includes(ExPolicy &&policy, FwdIter1  
first1, FwdIter1 last1,  
FwdIter2 first2, FwdIter2  
last2, Pred &&op = Pred())
```

Returns true if every element from the sorted range $[first2, last2)$ is found within the sorted range $[first1, last1)$. Also returns true if $[first2, last2)$ is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*. Executed according to the policy.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(first1, last1)$ and $N2 = \text{std::distance}(first2, last2)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`

Parameters

⁶⁶⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *includes* algorithm returns true every element from the sorted range $[first2, last2)$ is found within the sorted range $[first1, last1)$. Also returns true if $[first2, last2)$ is empty.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = hpx::parallel::detail::less>
bool includes(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if every element from the sorted range $[first2, last2)$ is found within the sorted range $[first1, last1)$. Also returns true if $[first2, last2)$ is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(first1, last1)$ and $N2 = \text{std::distance}(first2, last2)$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.

- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *includes* algorithm returns a *bool*. The *includes* algorithm returns true every element from the sorted range [*first2*, *last2*) is found within the sorted range [*first1*, *last1*). Also returns true if [*first2*, *last2*) is empty.

hpx::experimental::sort_by_key

Defined in header `hpx/algorithm.hpp`⁶⁶⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename ExPolicy, typename KeyIter, typename ValueIter, typename Compare =  
detail::less>  
util::detail::algorithm_result_t<ExPolicy, sort_by_key_result<KeyIter, ValueIter>> sort_by_key(ExPolicy  
                                                    &&pol-  
                                                    icy,  
                                                    KeyIter  
                                                    key_first,  
                                                    KeyIter  
                                                    key_last,  
                                                    Val-  
                                                    ueIter  
                                                    value_first,  
                                                    Com-  
                                                    pare  
                                                    &&comp  
                                                    =  
                                                    Com-  
                                                    pare())
```

⁶⁶⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Sorts one range of data using keys supplied in another range. The key elements in the range [key_first, key_last) are sorted in ascending order with the corresponding elements in the value range moved to follow the sorted order. The algorithm is not stable, the order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()). Executed according to the policy.

A sequence is sorted with respect to a comparator *comp* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, *(i + n), *i) == false.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **KeyIter** – The type of the key iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **ValueIter** – The type of the value iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Compare** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **key_first** – Refers to the beginning of the sequence of key elements the algorithm will be applied to.
- **key_last** – Refers to the end of the sequence of key elements the algorithm will be applied to.
- **value_first** – Refers to the beginning of the sequence of value elements the algorithm will be applied to, the range of elements must match [key_first, key_last)
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.

Returns

The *sort_by_key* algorithm returns a `hpx::future<sort_by_key_result<KeyIter, ValueIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *otherwise*. The algorithm returns a pair holding an iterator pointing to the first element after the last element in the input key sequence and an iterator pointing to the first element after the last element in the input value sequence.

hpx::adjacent_difference

Defined in header [hpx/algorithm.hpp](#)⁶⁶⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename FwdIter1, typename FwdIter2>  
FwdIter2 adjacent_difference(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first.

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.

Returns

The *adjacent_difference* algorithm returns a *FwdIter2*. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter1 first,  
                                                                                      FwdIter1 last,  
                                                                                      FwdIter2 dest)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first. Executed according to the policy.

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁶⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.

Returns

The *adjacent_difference* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename FwdIter1, typename FwdIter2, typename Op>
FwdIter2 adjacent_difference(FwdIter1 first, FwdIter1 last, FwdIter2 dest, Op &&op)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *Copy-Constructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.
- **op** – The binary operator which returns the difference of elements. The signature should be equivalent to the following:

```
bool op(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter1* can be dereferenced and then implicitly converted to the dereferenced type of *dest*.

Returns

The *adjacent_difference* algorithm returns *FwdIter2*. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> adjacent_difference(ExPolicy
                                                                                      &&policy,
                                                                                      FwdIter1 first,
                                                                                      FwdIter1 last,
                                                                                      FwdIter2 dest,
                                                                                      Op &&op)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.
- **op** – The binary operator which returns the difference of elements. The signature should be equivalent to the following:

```
bool op(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter1* can be dereferenced and then implicitly converted to the dereferenced type of *dest*.

Returns

The *adjacent_difference* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

hpx::stable_sort

Defined in header `hpx/algorithm.hpp`⁶⁶⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
void stable_sort(RandomIt first, RandomIt last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i + n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *stable_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.

⁶⁶⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to *bool*, yields *true* if the first argument of the call is less than the second, and *false* otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *stable_sort* algorithm returns *void*.

```
template<typename ExPolicy, typename RandomIt, typename Comp = hpx::parallel::detail::less, typename  
Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> stable_sort(ExPolicy &&policy, RandomIt first,  
                                                                    RandomIt last, Comp &&comp =  
                                                                    Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range *[first, last)* in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object *comp* (defaults to using operator<()). Executed according to the policy.

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i + n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns a `hpx::future<void>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `void` otherwise.

hpx::partial_sort_copy

Defined in header [hpx/algorithm.hpp](#)⁶⁶⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename RandIter, typename Comp = hpx::parallel::detail::less>
RandIter partial_sort_copy(InIter first, InIter last, RandIter d_first, RandIter d_last, Comp &&comp =
    Comp())
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[d_first, d_last)`. At most `d_last - d_first` of the elements are placed sorted to the range `[d_first, d_first + n)` where `n` is the number of elements to sort (`n = min(last - first, d_last - d_first)`).

The application of function objects in parallel algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{d_first}, \text{d_last})$ comparisons.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁶⁶⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **RandIter** – The type of the destination iterators used(deduced) This iterator type must meet the requirements of an random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **d_first** – Refers to the beginning of the destination range.
- **d_last** – Refers to the end of the destination range.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.

Returns

The *partial_sort_copy* algorithm returns a *RandomIt*. The algorithm returns an iterator to the element defining the upper boundary of the sorted range i.e. `d_first + min(last - first, d_last - d_first)`

```
template<typename ExPolicy, typename FwdIter, typename RandIter, typename Comp =  
hpx::parallel::detail::less>  
parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> partial_sort_copy(ExPolicy &&policy,  
FwdIter first, FwdIter  
last, RandIter d_first,  
RandIter d_last, Comp  
&&comp = Comp())
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[d_first, d_last)`. At most `d_last - d_first` of the elements are placed sorted to the range `[d_first, d_first + n)` where `n` is the number of elements to sort (`n = min(last - first, d_last - d_first)`). Executed according to the policy.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{d_first}, \text{d_last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

- **RandIter** – The type of the destination iterators used(deduced) This iterator type must meet the requirements of an random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **d_first** – Refers to the beginning of the destination range.
- **d_last** – Refers to the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.

Returns

The *partial_sort_copy* algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandomIt* otherwise. The algorithm returns an iterator to the element defining the upper boundary of the sorted range i.e. `d_first + min(last - first, d_last - d_first)`

hpx::uninitialized_copy, hpx::uninitialized_copy_n

Defined in header `hpx/algorithm.hpp`⁶⁶⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename FwdIter>
FwdIter uninitialized_copy(InIter first, InIter last, FwdIter dest)
```

Copies the elements in the range, defined by `[first, last)`, to an uninitialized memory area beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

⁶⁶⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy* algorithm returns *FwdIter*. The *uninitialized_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> uninitialized_copy(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter1 first,  
                                                                                      FwdIter1 last,  
                                                                                      FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy* algorithm returns a `hpx::future<FwdIter2>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename Size, typename FwdIter>
FwdIter uninitialized_copy_n(InIter first, Size count, FwdIter dest)
```

Copies the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`., to another range beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy_n* algorithm returns a returns *FwdIter*. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> uninitialized_copy_n(ExPolicy
                                                                                          &&policy,
                                                                                          FwdIter1 first,
                                                                                          Size count,
                                                                                          FwdIter2 dest)
```

Copies the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`., to another range beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy_n* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::reduce_deterministic

Defined in header [hpx/algorithm.hpp](#)⁶⁷⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁷⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce_deterministic(ExPolicy &&policy,
                                          FwdIter first, FwdIter
                                          last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
util::detail::algorithm_result_t<ExPolicy, T> reduce_deterministic(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type reduce_deter
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the *value_type* of the used *FwdIter*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
- op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:

- $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `T` otherwise (where `T` is the *value_type* of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying `operator+()`) over the elements given by the input range `[first, last)`.

```
template<typename FwdIter, typename F, typename T = typename std::iterator_traits<FwdIter>::value_type>  
T reduce_deterministic(FwdIter first, FwdIter last, T init, F &&f)
```

Returns `GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1))`. Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- a_1 when N is 1
 - `op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN))`, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1* *Ret* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename FwdIter, typename T = typename std::iterator_traits<FwdIter>::value_type>
T reduce_deterministic(FwdIter first, FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter>
```

```
std::iterator_traits<FwdIter>::value_type reduce_deterministic(FwdIter first, FwdIter last)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the value_type of the used *FwdIter*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

FwdIter – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns *T* (where T is the value_type of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

hpx::ends_with

Defined in header `hpx/algorithm.hpp`⁶⁷¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::equal_to>
bool ends_with(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred = Pred())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2)

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **InIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of a input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to *hpx::parallel::detail::equal_to*.

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Refers to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *ends_with* algorithm returns *bool*. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =
ranges::equal_to>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type ends_with(ExPolicy &&policy, FwdIter1
first1, FwdIter1 last1, FwdIter2
first2, FwdIter2 last2, Pred
&&pred = Pred())
```

⁶⁷¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2). Executed according to the policy.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to *ranges::equal_to*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Refers to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

hpx::fill, hpx::fill_n

Defined in header `hpx/algorithm.hpp`⁶⁷².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter, typename T>
util::detail::algorithm_result_t<ExPolicy> fill(ExPolicy &&policy, FwdIter first, FwdIter last, T value)
```

Assigns the given value to the elements in the range [first, last). Executed according to the policy.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename FwdIter, typename T>
```

⁶⁷² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

void **fill**(*FwdIter* first, *FwdIter* last, *T* value)

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *void*.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>
util::detail::algorithm_result_t<ExPolicy, FwdIter> fill_n(ExPolicy &&policy, FwdIter first, Size count, T
                                                         value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise. Executed according to the policy.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, for count > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename FwdIter, typename Size, typename T>
FwdIter fill_n(FwdIter first, Size count, T value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise.

Note: Complexity: Performs exactly *count* assignments, for count > 0.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *FwdIter*.

hpx::uninitialized_fill, hpx::uninitialized_fill_n

Defined in header [hpx/algorithm.hpp](#)⁶⁷³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁷³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename T>
void uninitialized_fill(FwdIter first, FwdIter last, T const &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns nothing

```
template<typename ExPolicy, typename FwdIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> uninitialized_fill(ExPolicy &&policy, FwdIter
                                                                 first, FwdIter last, T const
                                                                 &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The initializations in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The initializations in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

```
template<typename FwdIter, typename Size, typename T>
FwdIter uninitialized_fill_n(FwdIter first, Size count, T const &value)
```

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *hpx::future<FwdIter>*. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>
FwdIter uninitialized_fill_n(ExPolicy policy, FwdIter first,
                             Size count, T const &value)
```

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The initializations in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The initializations in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *hpx::future<FwdIter>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

hpx::set_union

Defined in header [hpx/algorithm.hpp](#)⁶⁷⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename  
Pred = hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> set_union(ExPolicy &&policy, FwdIter1  
first1, FwdIter1 last1,  
FwdIter2 first2, FwdIter2  
last2, FwdIter3 dest, Pred  
&&op = Pred())
```

⁶⁷⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, then all *m* elements will be copied from *[first1, last1)* to *dest*, preserving order, and then exactly $\text{std::max}(n-m, 0)$ elements will be copied from *[first2, last2)* to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Op** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The `set_union` algorithm returns a `hpx::future<FwdIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The `set_union` algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
FwdIter3 set_union(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest, Pred  
                  &&op = Pred())
```

Constructs a sorted range beginning at `dest` consisting of all elements present in one or both sorted ranges `[first1, last1)` and `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found *m* times in `[first1, last1)` and *n* times in `[first2, last2)`, then all *m* elements will be copied from `[first1, last1)` to `dest`, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from `[first2, last2)` to `dest`, also preserving order.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Op** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `set_union` requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_union* algorithm returns a *FwdIter3*. The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::lexicographical_compare

Defined in header `hpx/algorithm.hpp`⁶⁷⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::less>
bool lexicographical_compare(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred)
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
- The first mismatching element defines which range is lexicographically *less* or *greater* than the other
- If one range is a prefix of another, the shorter range is lexicographically *less* than the other

⁶⁷⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **InIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to

Returns

The *lexicographically_compare* algorithm returns a *bool* if the execution policy object is not passed in. The *lexicographical_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =  
hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> lexicographical_compare(ExPolicy  
                                                    &&policy,  
                                                    FwdIter1 first1,  
                                                    FwdIter1 last1,  
                                                    FwdIter2 first2,  
                                                    FwdIter2 last2,  
                                                    Pred &&pred)
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to

Returns

The *lexicographically_compare* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The

lexicographically_compare algorithm returns true if the first range is lexicographically less, otherwise it returns false. *range* [first2, last2), it returns false.

hpx::experimental::reduction_multiplies

Defined in header `hpx/algorithm.hpp`⁶⁷⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::multiplies<T>> reduction_multiplies(T
                                                                                               &var)
```

The function template *reduction_multiplies* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::multiplies{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_multiplies* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::multiplies{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.

⁶⁷⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::multiplies<T>> reduction_multiplies(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::sort

Defined in header `hpx/algorithm.hpp`⁶⁷⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
void sort(RandomIt first, RandomIt last, Comp &&comp, Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

⁶⁷⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns *void*.

```
template<typename ExPolicy, typename RandomIt, typename Comp = hpx::parallel::detail::less, typename  
Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> sort(ExPolicy &&policy, RandomIt first, RandomIt  
last, Comp &&comp, Proj &&proj)
```

Sorts the elements in the range `[first, last)` in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`). Executed according to the policy.

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::merge, hpx::inplace_merge

Defined in header [hpx/algorithm.hpp](#)⁶⁷⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename RandIter1, typename RandIter2, typename RandIter3,
        typename Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, RandIter3> merge(ExPolicy &&policy, RandIter1
                                                                    first1, RandIter1 last1, RandIter2
                                                                    first2, RandIter2 last2, RandIter3
                                                                    dest, Comp &&comp = Comp())
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges. Executed according to the policy.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and each projection.

Template Parameters

⁶⁷⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter1** – The type of the source iterators used (deduced) representing the first sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter2** – The type of the source iterators used (deduced) representing the second sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first range of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first range of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second range of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter1* and *RandIter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *merge* algorithm returns a `hpx::future<RandIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter3* otherwise. The *merge* algorithm returns the destination iterator to the end of the *dest* range.

```
template<typename RandIter1, typename RandIter2, typename RandIter3, typename Comp =  
hpx::parallel::detail::less>  
RandIter3 merge(RandIter1 first1, RandIter1 last1, RandIter2 first2, RandIter2 last2, RandIter3 dest, Comp  
                &&comp = Comp())
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **RandIter1** – The type of the source iterators used (deduced) representing the first sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter2** – The type of the source iterators used (deduced) representing the second sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the first range of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first range of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second range of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter1* and *RandIter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *merge* algorithm returns a *RandIter3*. The *merge* algorithm returns the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> inplace_merge(ExPolicy &&policy, RandIter first,
                                                                    RandIter middle, RandIter last,
                                                                    Comp &&comp = Comp())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. Executed according to the policy.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *inplace_merge* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns void otherwise. The *inplace_merge* algorithm returns the source iterator *last*.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
void inplace_merge(RandIter first, RandIter middle, RandIter last, Comp &&comp = Comp())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.

- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *inplace_merge* algorithm returns a *void*. The *inplace_merge* algorithm returns the source iterator *last*.

hpx::generate, hpx::generate_n

Defined in header `hpx/algorithm.hpp`⁶⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> generate(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, F &&f)
```

Assign each element in range $[first, last)$ a value generated by the given function object *f*. Executed according to the policy.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

⁶⁷⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise.

```
template<typename FwdIter, typename F>  
void generate(FwdIter first, FwdIter last, F &&f)
```

Assign each element in range [*first*, *last*) a value generated by the given function object *f*.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate* algorithm returns void.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> generate_n(ExPolicy &&policy, FwdIter
first, Size count, F &&f)
```

Assigns each element in range $[first, first+)$ a value generated by the given function object *f*. Executed according to the policy.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for count > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

Ret fun();

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. *generate_n* algorithm returns iterator one past the last element assigned if count>0, first otherwise.

```
template<typename FwdIter, typename Size, typename F>
```

FwdIter **generate_n**(*FwdIter* first, *Size* count, *F* &&*f*)

Assigns each element in range [*first*, *first*+) a value generated by the given function object *f*.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for *count* > 0.

Template Parameters

- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

`Ret fun();`

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate_n* algorithm returns a *FwdIter*. *generate_n* algorithm returns iterator one past the last element assigned if *count*>0, first otherwise.

hpx::uninitialized_value_construct, hpx::uninitialized_value_construct_n

Defined in header [hpx/algorithm.hpp](#)⁶⁸⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter>
void uninitialized_value_construct(FwdIter first, FwdIter last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *last* - *first* assignments.

⁶⁸⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_value_construct* algorithm returns nothing

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> uninitialized_value_construct(ExPolicy
                                                                                          &&policy,
                                                                                          FwdIter first,
                                                                                          FwdIter last)
```

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_value_construct* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

```
template<typename FwdIter, typename Size>
```

FwdIter **uninitialized_value_construct_n**(*FwdIter* first, *Size* count)

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *FwdIter*. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_value_construct_n(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter
                                                                                                     first,
                                                                                                     Size
                                                                                                     count)
```

Constructs objects of type `typename iterator_traits<ForwardIt> ::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::is_heap, hpx::is_heap_until

Defined in header [hpx/algorithm.hpp](#)⁶⁸¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_heap(ExPolicy &&policy, RandIter first,
                                                                    RandIter last, Comp &&comp =
                                                                    Comp())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()). Executed according to the policy.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

⁶⁸¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>  
bool is_heap(RandIter first, RandIter last, Comp &&comp = Comp())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap* a *bool*. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
```

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> is_heap_until(ExPolicy &&policy,
                                           RandIter first, RandIter
                                           last, Comp &&comp =
                                           Comp())

```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using `operator<()`). Executed according to the policy.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```

template<typename RandIter, typename Comp = hpx::parallel::detail::less>
RandIter is_heap_until(RandIter first, RandIter last, Comp &&comp = Comp())

```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap_until* algorithm returns a *RandIter*. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

hpx::destroy, hpx::destroy_n

Defined in header [hpx/algorithm.hpp](#)⁶⁸².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter>
util::detail::algorithm_result_t<ExPolicy> destroy(ExPolicy &&policy, FwdIter first, FwdIter last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range [first, last). Executed according to the policy.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

⁶⁸² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename FwdIter>
void destroy(FwdIter first, FwdIter last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, last)`.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *void*

```
template<typename ExPolicy, typename FwdIter, typename Size>
util::detail::algorithm_result_t<ExPolicy, FwdIter> destroy_n(ExPolicy &&policy, FwdIter first, Size count)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, first + count)`. Executed according to the policy.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename FwdIter, typename Size>  
FwdIter destroy_n(FwdIter first, Size count)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, first + count).

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *FwdIter* . The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::count, hpx::count_if

Defined in header `hpx/algorithm.hpp`⁶⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter, typename T>
util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::difference_type>::type count(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter
                                                                                                     first,
                                                                                                     FwdIter
                                                                                                     last,
                                                                                                     T
                                                                                                     const
                                                                                                     &value)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*. Executed according to the policy.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **FwdIter** – The type of the source iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to search for (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

⁶⁸³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIterB>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename InIter, typename T>  
std::iterator_traits<InIter>::difference_type count(InIter first, InIter last, T const &value)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.

Returns

The *count* algorithm returns a *difference_type* (where *difference_type* is defined by *std::iterator_traits<InIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename ExPolicy, typename FwdIter, typename F>  
util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::difference_type>::type count_if(ExPolicy  
    &&pol-  
    icy,  
    FwdIter  
    first,  
    FwdIter  
    last,  
    F  
    &&f)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true. Executed according to the policy.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *count_if* algorithm returns *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename InIter, typename F>
std::iterator_traits<InIter>::difference_type count_if(InIter first, InIter last, F &&f)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *count_if* algorithm returns *difference_type* (where a *difference_type* is defined by *std::iterator_traits<InIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

hpx::partition, hpx::stable_partition, hpx::partition_copy

Defined in header `hpx/algorithm.hpp`⁶⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Pred, typename Proj = hpx::identity>  
FwdIter partition(FwdIter first, FwdIter last, Pred &&pred, Proj &&proj = Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

⁶⁸⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *FwdIter*. The *partition* algorithm returns the iterator to the first element of the second group.

```
template<typename ExPolicy, typename FwdIter, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> partition(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred, Proj
                                                                    &&proj = Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter* otherwise. The *partition* algorithm returns the iterator to the first element of the second group.

```
template<typename BidirIter, typename F, typename Proj = hpx::identity>  
BidirIter stable_partition(BidirIter first, BidirIter last, F &&f, Proj &&proj = Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) `INVOKE(f, INVOKE (proj, *j)) != false`, and for every iterator *k* in the range [*i*, last), `INVOKE(f, INVOKE (proj, *k)) == false`

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), $f(*j) \neq \text{false}$ INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), $f(*k) == \text{false}$ INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename BidirIter, typename F, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, BidirIter> stable_partition(ExPolicy &&policy,
                                          BidirIter first, BidirIter
                                          last, F &&f, Proj &&proj
                                          = Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [*i*, last), INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(\text{last} - \text{first}) * \log(\text{last} - \text{first})$ swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), `f(*j) != false INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator *k* in the range [*i*, last), `f(*k) == false INVOKE(f, INVOKE(proj, *k)) == false`. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a *future*<> referring to this iterator.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred, typename Proj =
hpx::identity>
std::pair<FwdIter2, FwdIter3> partition_copy(FwdIter1 first, FwdIter1 last, FwdIter2 dest_true, FwdIter3
dest_false, Pred &&pred, Proj &&proj = Proj())
```

Copies the elements in the range, defined by [first, last), to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.

- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns *std::pair<OutIter1, OutIter2>*. The *partition_copy* algorithm returns the pair of the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename
Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter2, FwdIter3>> partition_copy(ExPolicy
&&policy,
FwdIter1
first,
FwdIter1
last,
FwdIter2
dest_true,
FwdIter3
dest_false,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Copies the elements in the range, defined by `[first, last)`, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred*, are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a `hpx::future<std::pair<OutIter1, OutIter2>>` if the execution policy is of type *parallel_task_policy* and returns `std::pair<OutIter1, OutIter2>` otherwise. The *partition_copy* algorithm returns the pair of the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

hpx/parallel/algorithms/transform_reduce_binary.hpp

Defined in header `hpx/parallel/algorithms/transform_reduce_binary.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::shift_left

Defined in header `hpx/algorithm.hpp`⁶⁸⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Size>
FwdIter shift_left(FwdIter first, FwdIter last, Size n)
```

Shifts the elements in the range `[first, last)` by `n` positions towards the beginning of the range. For every integer `i` in `[0, last - first)`

- `n`), moves the element originally at position `first + n + i` to position `first + i`.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most $(last - first) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

⁶⁸⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns *FwdIter*. The *shift_left* algorithm returns an iterator to the end of the resulting range. Specifically: If *n* is 0 or $n \geq (\text{last} - \text{first})$, does nothing and returns *last* and *first* respectively. Otherwise returns $\text{first} + ((\text{last} - \text{first}) - n)$.

```
template<typename ExPolicy, typename FwdIter, typename Size>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter> shift_left(ExPolicy &&policy, FwdIter  
first, FwdIter last, Size n)
```

Shifts the elements in the range $[\text{first}, \text{last})$ by *n* positions towards the beginning of the range. For every integer *i* in $[0, \text{last} - \text{first})$

- *n*), moves the element originally at position $\text{first} + n + i$ to position $\text{first} + i$. Executed according to the policy.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(\text{last} - \text{first}) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range. Specifically: If *n* is 0, does nothing and returns *last*. If *n* >= (last - first), does nothing and returns *first*. Otherwise returns *first* + ((last - first) - n).

hpx::set_intersection

Defined in header `hpx/algorithm.hpp`⁶⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename
Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> set_intersection(ExPolicy &&policy,
                                                                                      FwdIter1 first1,
                                                                                      FwdIter1 last1,
                                                                                      FwdIter2 first2,
                                                                                      FwdIter2 last2,
                                                                                      FwdIter3 dest, Pred
                                                                                      &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶⁸⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator with sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_intersection* algorithm returns a `hpx::future<FwdIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>
```

```
FwdIter3 set_intersection(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest,
                          Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator with sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_intersection* algorithm returns a *FwdIter3*. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::inclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁶⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

template<typename **InIter**, typename **OutIter**>

OutIter **inclusive_scan**(*InIter* first, *InIter* last, *OutIter* dest)

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*, here `std::plus<>()`.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*₁, ..., *a*_{*N*}) is defined as:

- *a*₁ when *N* is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*₁, ..., *a*_{*K*})
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*_{*M*}, ..., *a*_{*N*}) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

⁶⁸⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **dest** – Refers to the beginning of the destination range.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> inclusive_scan(ExPolicy &&policy,
                                                                                      FwdIter1 first,
                                                                                      FwdIter1 last, FwdIter2
                                                                                      dest)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, *first, ..., *(first + (i - result))). Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*, here `std::plus<>()`.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a*N) is defined as:

- *a*1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a*K)
– GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*M, ..., *a*N) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename Op>  
OutIter inclusive_scan(InIter first, InIter last, OutIter dest, Op &&op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> inclusive_scan(ExPolicy &&policy,
                                           FwdIter1 first,
                                           FwdIter1 last, FwdIter2
                                           dest, Op &&op)
```

Assigns through each iterator *i* in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`. Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(last - first)$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK)`
 – `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename Op, typename T>
```

```
OutIter inclusive_scan(InIter first, InIter last, OutIter dest, Op &&op, T init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> inclusive_scan(ExPolicy &&policy,
                                          FwdIter1 first,
                                          FwdIter1 last, FwdIter2
                                          dest, Op &&op, T init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`. Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
- `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

`hpx::is_sorted`, `hpx::is_sorted_until`

Defined in header `hpx/algorithm.hpp`⁶⁸⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁶⁸⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename FwdIter, typename Pred = hpx::parallel::detail::less>
bool is_sorted(FwdIter first, FwdIter last, Pred &&pred = Pred())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> is_sorted(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred =
                                                                    Pred())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements. Executed according to the policy.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_sorted* algorithm returns a *bool* if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename FwdIter, typename Pred = hpx::parallel::detail::less>  
FwdIter is_sorted_until(FwdIter first, FwdIter last, Pred &&pred = Pred())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted_until* algorithm returns a *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type is_sorted_until(ExPolicy &&policy,
                                                                                      FwdIter first,
                                                                                      FwdIter last, Pred
                                                                                      &&pred = Pred())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator. Executed according to the policy.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N+S-1) comparisons where *N* = distance(first, last). *S* = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *Copy-Constructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted_until* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

hpx::experimental::reduction_bit_xor

Defined in header `hpx/algorithm.hpp`⁶⁸⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

template<typename **T**>

constexpr *hpx::parallel::detail::reduction_helper<T, std::bit_xor<T>>* **reduction_bit_xor**(*T* &var)

The function template *reduction_bit_xor* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::bit_xor{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_xor* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function,

⁶⁸⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::bit_xor{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The live-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_xor<T>> reduction_bit_xor(T &var, T
                                                                    const
                                                                    &identity)
```

hpx::reduce

Defined in header `hpx/algorithm.hpp`⁶⁹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁶⁹⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1 Ret* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
util::detail::algorithm_result_t<ExPolicy, T> reduce(ExPolicy &&policy, FwdIter first, FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type reduce(ExPolicy&&policy,
FwdIter first,
FwdIter last)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the *value_type* of the used *FwdIter*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise (where *T* is the value_type of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter, typename F, typename T = typename std::iterator_traits<FwdIter>::value_type>
T reduce(FwdIter first, FwdIter last, T init, F &&f)
```

Returns GENERALIZED_SUM(*f*, *init*, **first*, ..., *(*first* + (*last* - *first*) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(*op*, *a1*, ..., *aN*) is defined as follows:

- *a1* when *N* is 1
 - *op*(GENERALIZED_SUM(*op*, *b1*, ..., *bK*), GENERALIZED_SUM(*op*, *bM*, ..., *bN*)), where:
 - *b1*, ..., *bN* may be any permutation of *a1*, ..., *aN* and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&. The types *Type1 Ret* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename FwdIter, typename T = typename std::iterator_traits<FwdIter>::value_type>
T reduce(FwdIter first, FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).


```
template<typename FwdIter>
std::iterator_traits<FwdIter>::value_type reduce(FwdIter first, FwdIter last)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) T is determined from the value_type of the used *FwdIter*.

Note: GENERALIZED_SUM(+, $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

FwdIter – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns T (where T is the value_type of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

hpx::transform_reduce

Defined in header `hpx/algorithm.hpp`⁶⁹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁶⁹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter, typename T, typename Reduce, typename Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, T init,
                                                                    Reduce &&red_op, Convert
                                                                    &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))). Executed according to the policy.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename InIter, typename T, typename Reduce, typename Convert>
T transform_reduce(InIter first, InIter last, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy,
                                                                              FwdIter1 first1, FwdIter1
                                                                              last1, FwdIter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*. Executed according to the policy.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as return values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename InIter1, typename InIter2, typename T>
T transform_reduce(InIter1 first1, InIter1 last1, InIter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **InIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as return values (deduced).

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *T*.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Reduce,  
typename Convert>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> transform_reduce(ExPolicy &&policy,  
FwdIter1 first1, FwdIter1  
last1, FwdIter2 first2, T init,  
Reduce &&red_op, Convert  
&&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*. Executed according to the policy.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *red_op*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename InIter1, typename InIter2, typename T, typename Reduce, typename Convert>
T transform_reduce(ExPolicy &&policy, InIter1 first1, InIter1 last1, InIter2 first2, T init, Reduce
&&red_op, Convert &&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **InIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *red_op*.

Returns

The *transform_reduce* algorithm returns a *T*.

hpx::reverse, hpx::reverse_copy

Defined in header `hpx/algorithm.hpp`⁶⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename BidirIter>
void reverse(BidirIter first, BidirIter last)
```

Reverses the order of the elements in the range `[first, last)`. Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

BidirIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

⁶⁹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *reverse* algorithm returns *void*.

```
template<typename ExPolicy, typename BidirIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, void> reverse(ExPolicy &&policy, BidirIter first,
                                                                    BidirIter last)
```

Reverses the order of the elements in the range `[first, last)`. Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`. Executed according to the policy.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename BidirIter, typename OutIter>
OutIter reverse_copy(BidirIter first, BidirIter last, OutIter dest)
```

Copies the elements from the range `[first, last)` to another range beginning at `dest` in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment `*(dest + (last - first) - 1 - i) = *(first + i)` once for each non-negative `i < (last - first)`. If the source and destination ranges (that is, `[first, last)` and `[dest, dest+(last-first))` respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns an *OutIter*. The *reverse_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename BidirIter, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> reverse_copy(ExPolicy &&policy,
                                          BidirIter first, BidirIter
                                          last, FwdIter dest)
```

Copies the elements from the range [first, last) to another range beginning at dest in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(dest + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [dest, dest+(last-first)) respectively) overlap, the behavior is undefined. Executed according to the policy.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *reverse_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::experimental::for_each_index

Defined in header [hpx/algorithm.hpp](#)⁶⁹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename Mapping, typename Fun>
constexpr void for_each_index(Mapping const &mapping, Fun fun)
```

Calls *fun* with every multidimensional index in the domain of *mapping* (i.e., its extents), in sequential order.

If *fun* returns a result, the result is ignored.

The layout mapping is a hint; implementations are encouraged to choose an iteration order that performs well for the given mapping.

Note: Complexity: Applies *fun* exactly the product of all extents of *mapping* times.

Template Parameters

- **Mapping** – A type meeting the layout mapping requirements. Must expose *index_type*, *extents_type*, *static rank()*, and *extents()*.
- **Fun** – The type of the function/function object to use (deduced). *Fun* must meet *Copy-Constructible* and be invocable with exactly *Mapping::rank()* arguments of type *Mapping::index_type*.

Parameters

- **mapping** – The layout mapping whose extents define the iteration domain.
- **fun** – Callable invoked as *fun*(*i0*, *i1*, ...) for every multidimensional index in the domain.

```
template<typename ExPolicy, typename Mapping, typename Fun>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> for_each_index(ExPolicy &&policy,
                                                                    Mapping const &mapping,
                                                                    Fun fun)
```

⁶⁹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Calls *fun* with every multidimensional index in the domain of *mapping* (i.e., its extents), executed according to *policy*.

If *fun* returns a result, the result is ignored.

Note: Complexity: Applies *fun* exactly the product of all extents of *mapping* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced).
- **Mapping** – A type meeting the layout mapping requirements. Must meet *CopyConstructible*.
- **Fun** – The type of the function/function object to use (deduced). Must meet *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for scheduling.
- **mapping** – The layout mapping whose extents define the iteration domain.
- **fun** – Callable invoked as `fun(i0, i1, ...)` for every multidimensional index in the domain.

Returns

hpx::future<void> if the execution policy is *sequenced_task_policy* or *parallel_task_policy*, *void* otherwise.

hpx::experimental::reduction_bit_or

Defined in header `hpx/algorithm.hpp`⁶⁹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_or<T>> reduction_bit_or(T &var)
```

The function template *reduction_bit_or* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::bit_or{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_or* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

⁶⁹⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::bit_or{}` operation until a single value remains, which is then assigned back to the live-out object.

`T` shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_or<T>> reduction_bit_or(T &var, T
                                                                    const
                                                                    &identity)
```

hpx::experimental::reduction

Defined in header `hpx/algorithm.hpp`⁶⁹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

⁶⁹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename T, typename Op>
constexpr hpx::parallel::detail::reduction_helper<T, std::decay_t<Op>> reduction(T &var, T const
                                                                    &identity, Op
                                                                    &&combiner)
```

The function template returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, a combiner function object, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses reduction objects by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the reduction object's combiner operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*. The expression

```
var = combiner(var, var)
```

shall be well-formed.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation. For example if the combiner is `plus<T>`, incrementing the view would be consistent with the combiner but doubling it or assigning to it would not.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.
- **combiner** – [in] The binary function (object) used to perform a pairwise reduction on the elements.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of *identity*, and views are combined by invoking the copy of *combiner*, passing it the two views to be combined.

```
template<typename T, typename Op>
constexpr hpx::parallel::detail::reduction_helper<T, std::decay_t<Op>> reduction(T &var, Op
                                                                    &&combiner)
```

hpx::uninitialized_relocate, hpx::uninitialized_relocate_n

Defined in header `hpx/algorithm.hpp`⁶⁹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

template<typename **InIter1**, typename **InIter2**, typename **FwdIter**>
FwdIter **uninitialized_relocate**(*InIter1* first, *InIter2* last, *FwdIter* dest)

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: time: O(n), space: O(1) 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): std::distance(first, last)*sizeof(T) bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): std::distance(first, last) memory copies of sizeof(T) bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): std::distance(first, last) move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the HPX_DECLARE_TRIVIALY_RELOCATABLE macros found in <hpx/type_support/is_trivially_relocatable.hpp>.

Template Parameters

- **InIter1** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterator last (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁶⁹⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *uninitialized_relocate* algorithm returns *FwdIter*. The *uninitialized_relocate* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_relocate(ExPolicy
                                                                                      &&policy,
                                                                                      InIter1 first,
                                                                                      InIter2 last,
                                                                                      FwdIter dest)
```

Relocates the elements in the range defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last}) * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last})$ memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): $\text{std::distance}(\text{first}, \text{last})$ move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Note: Parallel execution requires both *first* and *dest* to be contiguous iterators. If either iterator is non-contiguous, the algorithm cannot determine whether the source and destination ranges overlap, and will silently fall back to sequential execution regardless of the execution policy provided.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter1** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterator last (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range. The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Returns

The *uninitialized_relocate* algorithm returns a *hpx::future<FwdIter>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_relocate* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

```
template<typename BiIter1, typename BiIter2>
BiIter2 uninitialized_relocate_backward(BiIter1 first, BiIter1 last, BiIter2 dest_last)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area ending at *dest_last*. The objects are processed in reverse order. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last}) * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last})$ memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): $\text{std::distance}(\text{first}, \text{last})$ move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Template Parameters

- **BiIter1** – The type of the source range (deduced). This iterator type must meet the requirements of a Bidirectional iterator.
- **BiIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a Bidirectional iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_last** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate_backward* algorithm returns *BiIter2*. The *uninitial-*

ized_relocate_backward algorithm returns the bidirectional iterator to the first element in the destination range.

```
template<typename ExPolicy, typename BiIter1, typename BiIter2>
hpx::parallel::util::detail::algorithm_result<ExPolicy, BiIter2> uninitialized_relocate_backward(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               Bi-
                                                                                               Iter1
                                                                                               first,
                                                                                               Bi-
                                                                                               Iter1
                                                                                               last,
                                                                                               Bi-
                                                                                               Iter2
                                                                                               dest_last)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area ending at *dest_last*. The order of the relocation of the objects depends on the execution policy. If an exception is thrown during the the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate_backward* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Using the *uninitialized_relocate_backward* algorithm with the with a non-sequenced execution policy, will not guarantee the order of the relocation of the objects.

Note: Complexity: time: O(n), space: O(1) 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): std::distance(first, last)*sizeof(T) bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): std::distance(first, last) memory copies of sizeof(T) bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): std::distance(first, last) move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the HPX_DECLARE_TRIVIALY_RELOCATABLE macros found in <hpx/type_support/is_trivially_relocatable.hpp>.

Note: Parallel execution requires both *first* and *dest_last* to be contiguous iterators. If either iterator is non-contiguous, the algorithm cannot determine whether the source and destination ranges overlap, and will silently fall back to sequential execution regardless of the execution policy provided.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **BiIter1** – The type of the source range (deduced). This iterator type must meet the requirements of a Bidirectional iterator.
- **BiIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a Bidirectional iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_last** – Refers to the end of the destination range.

Returns

The *uninitialized_relocate_backward* algorithm returns a *hpx::future<FwdIter>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *BiIter2* otherwise. The *uninitialized_relocate_backward* algorithm returns the bidirectional iterator to the first element in the destination range.

```
template<typename InIter, typename Size, typename FwdIter>
FwdIter uninitialized_relocate_n(InIter first, Size count, FwdIter dest)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, first+count): $\text{count} * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, first+count): count memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): count move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Template Parameters

- **InIter** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to relocate.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate_n* algorithm returns *FwdIter*. The *uninitialized_relocate_n* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

```
template<typename ExPolicy, typename InIter, typename Size, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> uninitialized_relocate_n(ExPolicy
                                                                                               &&policy,
                                                                                               InIter first,
                                                                                               Size count,
                                                                                               FwdIter
                                                                                               dest)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, first+count): $\text{count} * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, first+count): count memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): count move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALLY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Note: Parallel execution requires both *first* and *dest* to be contiguous iterators. If either iterator is non-contiguous, the algorithm cannot determine whether the source and destination ranges overlap, and will silently fall back to sequential execution regardless of the execution policy provided.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to relocate.

- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_relocate_n* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

hpx::experimental::reduction_bit_and

Defined in header [hpx/algorithm.hpp](#)⁶⁹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **experimental**

Top-level namespace.

Functions

template<typename T>

constexpr *hpx::parallel::detail::reduction_helper<T, std::bit_and<T>>* **reduction_bit_and**(T &var)

The function template *reduction_bit_and* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses *std::bit_and{ }* as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_and* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the *std::bit_and{ }* operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

⁶⁹⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The live-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_and<T>> reduction_bit_and(T &var, T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::set_symmetric_difference

Defined in header `hpx/algorithm.hpp`⁶⁹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁶⁹⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename
Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter3>::type set_symmetric_difference(ExPolicy
&&pol-
icy,
FwdIter1
first1,
FwdIter1
last1,
FwdIter2
first2,
FwdIter2
last2,
FwdIter3
dest,
Pred
&&op
=
Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.

- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_symmetric_difference* algorithm returns a `hpx::future<FwdIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =
hpx::parallel::detail::less>
FwdIter3 set_symmetric_difference(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2,
FwdIter3 dest, Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly `std::abs(m-n)` times. If *m>n*, then the last *m-n* of those elements are copied from *[first1,last1)*, otherwise the last *n-m* elements are copied from *[first2,last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_symmetric_difference* algorithm returns a *FwdIter3*. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::replace, hpx::replace_if, hpx::replace_copy, hpx::replace_copy_if

Defined in header [hpx/algorithm.hpp](#)⁶⁹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename T = typename std::iterator_traits<InIter>::value_type>
void replace(InIter first, InIter last, T const &old_value, T const &new_value)
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator it in the range [first, last) with new_value, when the following corresponding conditions hold: *it == old_value

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the old and new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace* algorithm returns a *void*.

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, void> replace(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T const &old_value, T
                                                                    const &new_value)
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last). Executed according to the policy.

Effects: Substitutes elements referred by the iterator it in the range [first, last) with new_value, when the following corresponding conditions hold: *it == old_value

⁶⁹⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the old and new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename Iter, typename Pred, typename T = typename std::iterator_traits<Iter>::value_type>
void replace_if(Iter first, Iter last, Pred &&pred, T const &new_value)
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator it in the range [first, last) with *new_value*, when the following corresponding conditions hold: INVOKE(f, *it) != false

The assignments in the parallel *replace_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).

- **T** – The type of the new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_if* algorithm returns *void*.

```
template<typename ExPolicy, typename FwdIter, typename Pred, typename T = typename  
std::iterator_traits<FwdIter>::value_type>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, void> replace_if(ExPolicy &&policy, FwdIter first,  
                                     FwdIter last, Pred &&pred, T  
                                     const &new_value)
```

Replaces all elements satisfying specific criteria (for which predicate *f* returns true) with *new_value* in the range [first, last). Executed according to the policy.

Effects: Substitutes elements referred by the iterator *it* in the range [first, last) with *new_value*, when the following corresponding conditions hold: `INVOKE(f, *it) != false`

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).

- **T** – The type of the new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_if* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename InIter, typename OutIter, typename T = typename
std::iterator_traits<OutIter>::value_type>
```

```
OutIter replace_copy(InIter first, InIter last, OutIter dest, T const &old_value, T const &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: **(first + (i - result)) == old_value*

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the old and new values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy* algorithm returns an *OutIter*. The *replace_copy* algorithm returns the Iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T = typename
std::iterator_traits<FwdIter2>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> replace_copy(ExPolicy &&policy,
                                          FwdIter1 first, FwdIter1
                                          last, FwdIter2 dest, T
                                          const &old_value, T const
                                          &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*. Executed according to the policy.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: $*(first + (i - result)) == old_value$

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the old and new values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *replace_copy* algorithm returns the Iterator to the element past the last element copied.

```
template<typename InIter, typename OutIter, typename Pred, typename T = typename
std::iterator_traits<OutIter>::value_type>
```

```
OutIter replace_copy_if(InIter first, InIter last, OutIter dest, Pred &&pred, T const &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE(f, *(first + (i - result))) != false*

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy_if* algorithm returns an *OutIter*. The *replace_copy_if* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred, typename T =  
typename std::iterator_traits<FwdIter2>::value_type>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> replace_copy_if(ExPolicy &&policy,  
FwdIter1 first,  
FwdIter1 last,  
FwdIter2 dest, Pred  
&&pred, T const  
&new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(f, *(first + (i - result))) != false`

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *replace_copy_if* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy_if* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *replace_copy_if* algorithm returns the iterator to the element in the destination range, one past the last element copied.

hpx::equal

Defined in header `hpx/algorithm.hpp`⁷⁰⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                       FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise. Executed according to the policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$ applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1, last1), **i* equals **(first2 + (i - first1))*. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

⁷⁰⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range `[first1, last1)` does not equal the length of the range `[first2, last2)`, it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                       FwdIter2 first2, FwdIter2 last2)
```

Returns true if the range `[first1, last1)` is equal to the range `[first2, last2)`, and false otherwise. Executed according to policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$ applications of the predicate `std::equal_to`.

Note: The two ranges are considered equal if, for every iterator i in the range $[\text{first1}, \text{last1})$, $*i$ equals $*(\text{first2} + (i - \text{first1}))$. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The `equal` algorithm returns a `hpx::future<bool>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `bool` otherwise. The `equal` algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range $[\text{first1}, \text{last1})$ does not equal the length of the range $[\text{first2}, \text{last2})$, it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                    FwdIter2 first2, Pred &&op = Pred())
```

Returns true if the range $[\text{first1}, \text{last1})$ is equal to the range starting at `first2`, and false otherwise. Executed according to policy.

The comparison operations in the parallel `equal` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The comparison operations in the parallel `equal` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$ applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* equals $*(\text{first2} + (i - \text{first1}))$. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, bool> equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                       FwdIter2 first2)
```

Returns true if the range $[\text{first1}, \text{last1})$ is equal to the range $[\text{first2}, \text{last2})$, and false otherwise. Executed according to policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[first1, last1)$, $*i$ equals $*(first2 + (i - first1))$. This overload of *equal* uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *equal* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range $[first1, last1)$ does not equal the length of the range $[first2, last2)$, it returns false.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
bool equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if the range $[first1, last1)$ is equal to the range $[first2, last2)$, and false otherwise.

Note: Complexity: At most $\min(last1 - first1, last2 - first2)$ applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[first1, last1)$, $*i$ equals $*(first2 + (i - first1))$. This overload of *equal* uses `operator==` to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a *bool* . The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename FwdIter1, typename FwdIter2>
```

```
bool equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *std::equal_to*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1, last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses *operator==* to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *equal* algorithm returns a *bool*. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
bool equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, Pred &&op = Pred())
```

Returns true if the range [first1, last1) is equal to the range [first2, first2 + (last1 - first1)), and false otherwise.

Note: Complexity: At most *last1 - first1* applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1, last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a *bool*. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range `[first1, last1)` does not equal the length of the range `[first2, last2)`, it returns false.

hpx::all_of, hpx::any_of, hpx::none_of

Defined in header `hpx/algorithm.hpp`⁷⁰¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, bool> none_of(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Checks if unary predicate *f* returns true for no elements in the range `[first, last)`.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

⁷⁰¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *none_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename InIter, typename F>
bool none_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *none_of* algorithm returns a *bool*. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename F>
```

```
util::detail::algorithm_result_t<ExPolicy, bool> any_of(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Checks if unary predicate *f* returns true for at least one element in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *any_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename InIter, typename F>
bool any_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for at least one element in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *any_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *any_of* algorithm returns a *bool*. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, bool> all_of(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Checks if unary predicate *f* returns true for all elements in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *all_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *all_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename InIter, typename F>  
bool all_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for all elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *all_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *all_of* algorithm returns a *bool*. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

hpx::exclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁷⁰².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename OutIter, typename T>
OutIter exclusive_scan(InIter first, InIter last, OutIter dest, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))

The reduce operations in the parallel *exclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *std::plus*<*T*>.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a**N*) is defined as:

- *a*1 when *N* is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a**K*)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a**M*, ..., *a**N*) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.

⁷⁰² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *exclusive_scan* algorithm returns *OutIter*. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T>
util::detail::algorithm_result_t<ExPolicy, FwdIter2> exclusive_scan(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 dest, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *std::plus<T>*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.

Returns

The *exclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename T, typename Op>
OutIter exclusive_scan(InIter first, InIter last, OutIter dest, T init, Op &&op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1)).

The reduce operations in the parallel *exclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*₁, ..., *a*_N) is defined as:

- *a*₁ when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*₁, ..., *a*_K), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*_M, ..., *a*_N)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns *OutIter*. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
util::detail::algorithm_result_t<ExPolicy, FwdIter2> exclusive_scan(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 dest, T init,
                                                                    Op &&op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1))`.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- *a1* when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<OutIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *OutIter* otherwise. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::transform_inclusive_scan

Defined in header `hpx/algorithm.hpp`⁷⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp>
OutIter transform_inclusive_scan(InIter first, InIter last, OutIter dest, BinOp &&binary_op, UnOp
&&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum.

⁷⁰³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(\text{last} - \text{first})$ applications of each of *binary_op* and *unary_op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_inclusive_scan* algorithm returns a *returns OutIter*. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type transform_inclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`. Executed according to the policy.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(last - first)$ applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*₁, ..., *a*_N) is defined as:

- *a*₁ when N is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*₁, ..., *a*_K), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a*_M, ..., *a*_N)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_inclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<InIter>::value_type>
```

```
OutIter transform_inclusive_scan(InIter first, InIter last, OutIter dest, BinOp &&binary_op, UnOp
&&unary_op, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, conv(*first), ..., conv(*(first + (i - result)))).

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum. If *binary_op* is not mathematically associative, the behavior of *transform_inclusive_scan* may be non-deterministic.

Note: Complexity: O(last - first) applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where 1 < K+1 = M <= N.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.
- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a returns *OutIter*. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp,
        typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type transform_inclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op,
                                                                                               T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, conv(*first), ..., conv(*(first + (i - result)))). Executed according to the policy.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum. If *binary_op* is not mathematically associative, the behavior of *transform_inclusive_scan* may be non-deterministic.

Note: Complexity: O(last - first) applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1

- `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.
- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

asio

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/asio/asio_util.hpp

Defined in header `hpx/asio/asio_util.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

bool **get_endpoint**(*std::string* const &addr, *std::uint16_t* port, *asio::ip::tcp::endpoint* &ep, bool force_ipv4 = false)

std::string **get_endpoint_name**(*asio::ip::tcp::endpoint* const &ep)

asio::ip::tcp::endpoint **resolve_hostname**(*std::string* const &hostname, *std::uint16_t* port, *asio::io_context* &io_service, bool force_ipv4 = false)

detail::endpoint_iterator_type **connect_begin**(*std::string* const &address, *std::uint16_t* port, *asio::io_context* &io_service)

template<typename **Locality**>

detail::endpoint_iterator_type **connect_begin**(*Locality* const &loc, *asio::io_context* &io_service)

Returns an iterator which when dereferenced will give an endpoint suitable for a call to `connect()` related to this locality.

inline *detail::endpoint_iterator_type* **connect_end**()

detail::endpoint_iterator_type **accept_begin**(*std::string* const &address, *std::uint16_t* port, *asio::io_context* &io_service)

template<typename **Locality**>

detail::endpoint_iterator_type **accept_begin**(*Locality* const &loc, *asio::io_context* &io_service)

Returns an iterator which when dereferenced will give an endpoint suitable for a call to `accept()` related to this locality.

inline *detail::endpoint_iterator_type* **accept_end**()

assertion

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/assertion/api.hpp

Defined in header `hpx/assertion/api.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **assertion**

Typedefs

using **assertion_handler** = void (*)(hpx::source_location const &loc, char const *expr, std::string const &msg)

The signature for an assertion handler.

Functions

assertion_handler **set_assertion_handler**(*assertion_handler* handler)

Set the assertion handler to be used within a program. If the handler has been set already once, the call to this function will be ignored.

Note: This function is not thread safe

HPX_ASSERT, HPX_ASSERT_MSG

Defined in header `hpx/assert.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_ASSERT(*expr*)

This macro asserts that *expr* evaluates to true.

If *expr* evaluates to false, The source location and *msg* is being printed along with the expression and additional. Afterward, the program is being aborted. The assertion handler can be customized by calling `hpx::assertion::set_assertion_handler()`.

Asserts are enabled if *HPX_DEBUG* is set. This is the default for *CMAKE_BUILD_TYPE=Debug*

Parameters

- **expr** – The expression to assert on. This can either be an expression that's convertible to bool or a callable which returns bool
- **msg** – The optional message that is used to give further information if the assert fails. This should be convertible to a `std::string`

HPX_ASSERT_MSG(expr, msg)

See also:

HPX_ASSERT

HPX_CURRENT_SOURCE_LOCATION, hpx::source_location

Defined in header [hpx/source_location.hpp](http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/source_location.hpp)⁷⁰⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`std::ostream &operator<<(std::ostream &os, source_location const &loc)`

hpx/assertion/evaluate_assert.hpp

Defined in header `hpx/assertion/evaluate_assert.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **assertion**

async_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::launch

Defined in header [hpx/future.hpp](http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/future.hpp)⁷⁰⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁷⁰⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/source_location.hpp

⁷⁰⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Enums

enum class **launch_policy** : *std::int8_t*

Values:

enumerator **async**

enumerator **deferred**

enumerator **task**

enumerator **sync**

enumerator **fork**

enumerator **apply**

enumerator **sync_policies**

enumerator **async_policies**

enumerator **all**

struct **launch** : public detail::policy_holder<>

#include <launch_policy.hpp> Launch policies for *hpx::async* etc.

Public Functions

inline constexpr **launch**() noexcept

Default constructor. This creates a launch policy representing all possible launch modes

inline constexpr **launch**(detail::async_policy const p) noexcept

Create a launch policy representing asynchronous execution.

inline constexpr **launch**(detail::fork_policy const p) noexcept

Create a launch policy representing asynchronous execution. The new thread is executed in a preferred way

inline constexpr **launch**(detail::sync_policy const p) noexcept

Create a launch policy representing synchronous execution.

inline constexpr **launch**(detail::deferred_policy const p) noexcept

Create a launch policy representing deferred execution.

inline constexpr **launch**(detail::apply_policy const p) noexcept

Create a launch policy representing fire and forget execution.

template<typename **F**>

```
inline constexpr launch(detail::select_policy<F> const &p) noexcept
```

Create a launch policy representing fire and forget execution.

```
template<typename Launch, typename Enable =
```

```
std::enable_if_t<hpx::traits::is_launch_policy_v<Launch>>>
```

```
inline constexpr launch(Launch l, threads::thread_priority const priority, threads::thread_stacksize  
const stacksize, threads::thread_schedule_hint const hint) noexcept
```

Public Static Attributes

```
static const detail::async_policy async
```

Predefined launch policy representing asynchronous execution.

```
static const detail::fork_policy fork
```

Predefined launch policy representing asynchronous execution. The new thread is executed in a preferred way

```
static const detail::sync_policy sync
```

Predefined launch policy representing synchronous execution.

```
static const detail::deferred_policy deferred
```

Predefined launch policy representing deferred execution.

```
static const detail::apply_policy apply
```

Predefined launch policy representing fire and forget execution.

```
static const detail::select_policy_generator select
```

Predefined launch policy representing delayed policy selection.

hpx::sync

Defined in header [hpx/future.hpp](#)⁷⁰⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename F, typename ...Ts>
```

```
decltype(auto) sync(F &&f, Ts&&... ts)
```

The function template *sync* runs the function *f* synchronously and returns a *hpx::future* that will eventually hold the result of that function call.

⁷⁰⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

hpx::async

Defined in header `hpx/future.hpp`⁷⁰⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename F, typename ...Ts>  
decltype(auto) async(F &&f, Ts&&... ts)
```

The function template *async* runs the function *f* asynchronously (potentially in a separate thread which might be a part of a thread pool) and returns a *hpx::future* that will eventually hold the result of that function call. If no policy is defined, *async* behaves as if it is called with policy being *hpx::launch::async* | *hpx::launch::deferred*. Otherwise, it calls a function *f* with arguments *ts* according to a specific launch policy.

- If the *async* flag is set (i.e. `(policy & hpx::launch::async) != 0`), then *async* executes the callable object *f* on a new thread of execution (with all thread-locals initialized) as if spawned by `hpx::thread(std::forward<F>(f), std::forward<Ts>(ts)...) ,` except that if the function *f* returns a value or throws an exception, it is stored in the shared state accessible through the *hpx::future* that *async* returns to the caller.
- If the *deferred* flag is set (i.e. `(policy & hpx::launch::deferred) != 0`), then *async* converts *f* and *ts...* the same way as by *hpx::thread* constructor, but does not spawn a new thread of execution. Instead, lazy evaluation is performed: the first call to a non-timed wait function on the *hpx::future* that *async* returned to the caller will cause the copy of *f* to be invoked (as a rvalue) with the copies of *ts...* (also passed as rvalues) in the current thread (which does not have to be the thread that originally called *hpx::async*). The result or exception is placed in the shared state associated with the future and only then it is made ready. All further accesses to the same *hpx::future* will return the result immediately.
- If neither *hpx::launch::async* nor *hpx::launch::deferred*, nor any implementation-defined policy flag is set in policy, the behavior is undefined.

If more than one flag is set, it is implementation-defined which policy is selected. For the default (both the *hpx::launch::async* and *hpx::launch::deferred* flags are set in policy), standard recommends (but doesn't require) utilizing available concurrency, and deferring any additional tasks.

In any case, the call to *hpx::async* synchronizes-with (as defined in `std::memory_order`) the call to *f*, and the completion of *f* is sequenced-before making the shared state ready. If the *async* policy is chosen, the associated thread completion synchronizes-with the successful return from the first function that is waiting on the shared state, or with the return of the last function that releases the shared state, whichever comes first. If `std::decay<Function>::type` or each type in `std::decay<Ts>::type` is not constructible from its corresponding argument, the program is ill-formed.

Parameters

- **f** – Callable object to call
- **ts** – parameters to pass to *f*

Returns

hpx::future referring to the shared state created by this call to *hpx::async*.

⁷⁰⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

hpx::dataflow

Defined in header `hpx/future.hpp`⁷⁰⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename F, typename ...Ts>
decltype(auto) dataflow(F &&f, Ts&&... ts)
```

The function template *dataflow* runs the function *f* asynchronously (potentially in a separate thread which might be a part of a thread pool) and returns a `hpx::future` that will eventually hold the result of that function call. Its behavior is similar to `hpx::async` with the exception that if one of the arguments is a *future*, then `hpx::dataflow` will wait for the *future* to be ready to launch the thread. Hence, the operation is delayed until all the arguments are ready.

hpx::post

Defined in header `hpx/future.hpp`⁷⁰⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename F, typename ...Ts>
bool post(F &&f, Ts&&... ts)
```

Runs the function *f* asynchronously (potentially in a separate thread which might be a part of a thread pool). This is done in a fire-and-forget manner, meaning there is no return value or way to synchronize with the function execution (it does not return an `hpx::future` that would hold the result of that function call).

`hpx::post` is particularly useful when synchronization mechanisms as heavyweight as futures are not desired, and instead, more lightweight mechanisms like latches or atomic variables are preferred. Essentially, the `post` function enables the launch of a new thread without the overhead of creating a future.

Note: `hpx::post` is similar to `hpx::async` but does not return a future. This is why there is no way of finding out the result/failure of the execution of this function.

⁷⁰⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

⁷⁰⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

async_combinators

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::wait_any

Defined in header `hpx/future.hpp`⁷¹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename InputIter>
void wait_any(InputIter first, InputIter last)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_any* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_any* should wait.

```
template<typename R>
void wait_any(std::vector<future<R>> &futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

⁷¹⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Parameters

futures – [in] A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_any* should wait.

```
template<typename R, std::size_t N>
void wait_any(std::array<future<R>, N> &futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

futures – [in] An array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_any* should wait.

```
template<typename ...T>
void wait_any(T&&... futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_any* should wait.

```
template<typename InputIter>
void wait_any_n(InputIter first, std::size_t count)
```

The function *wait_any_n* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any_n* returns after at least one future has become ready. All input futures are still valid after *wait_any_n* returns.

Note: The function *wait_any_n* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_n_nothrow* instead.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_any_n* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

hpx::when_some

Defined in header [hpx/future.hpp](#)⁷¹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename InputIter, typename Container = vector<future<typename  
std::iterator_traits<InputIter>::value_type>>>  
future<when_some_result<Container>> when_some(std::size_t n, Iterator first, Iterator last)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

Note: Calling this version of *when_some* where *first* == *last*, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and indices pointing to ready futures.

- `future<when_some_result<Container<future<R>>>>>`: If the input cardinality is unknown at compile time and the futures are all of the same type. The order of the futures in the output container will be the same as given by the input iterator.

⁷¹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>


```
template<typename Range>
future<when_some_result<Range>> when_some(std::size_t n, Range &&futures)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] A container holding an arbitrary amount of *future* or *shared_future* objects for which *when_some* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and indices pointing to ready futures.

- *future<when_some_result<Container<future<R>>>>*: If the input cardinality is unknown at compile time and the futures are all of the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename ...Ts>
future<when_some_result<tuple<future<T>...>>> when_some(std::size_t n, Ts&&... futures)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_some* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and an index pointing to a ready future..

- `future<when_some_result<tuple<future<T0>, future<T1>...>>>`: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.
- `future<when_some_result<tuple<>>>` if *when_some* is called with zero arguments. The returned future will be initially ready.

```
template<typename InputIter, typename Container = vector<future<typename  
std::iterator_traits<InputIter>::value_type>>>  
future<when_some_result<Container>> when_some_n(std::size_t n, Iterator first, std::size_t count)
```

The function *when_some_n* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some_n* becomes ready when at least *n* argument futures have become ready.

Note: Calling this version of *when_some_n* where *count* == 0, returns a future with the same elements as the arguments that is immediately ready. Possibly none of the futures in that container are ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some_n* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and indices pointing to ready futures.

- `future<when_some_result<Container<future<R>>>>`: If the input cardinality is unknown at compile time and the futures are all of the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename Sequence>
```

```
struct when_some_result
```

```
#include <when_some.hpp> Result type for when_some, contains a sequence of futures and indices point-  
ing to ready futures.
```

Public Members

`std::vector<std::size_t> indices`

List of indices of futures that have become ready.

Sequence **futures**

The sequence of futures as passed to `hpx::when_some`.

`hpx::when_all`

Defined in header `hpx/future.hpp`⁷¹².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

template<typename **InputIter**, typename **Container** = vector<future<typename
std::iterator_traits<InputIter>::value_type>>>

`hpx::future<Container> when_all(InputIter first, InputIter last)`

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Calling this version of *when_all* where `first == last`, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- `future<Container<future<R>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

template<typename **Range**>

⁷¹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

hpx::future<Range> **when_all**(*Range* &&values)

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Calling this version of *when_all* where the input container is empty, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

Parameters

values – [in] A range holding an arbitrary amount of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- *future<Container<future<R>>>*: If the input cardinality is unknown at compile time and the futures are all have the same type.

template<typename ...**T**>

hpx::future<hpx::tuple<hpx::future<T>...>> **when_all**(*T*&&... futures)

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- *future<tuple<future<T0>, future<T1>, future<T2>...>>*: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.
- *future<tuple<>>* if *when_all* is called with zero arguments. The returned future will be initially ready.

template<typename **InputIter**, typename **Container** = vector<*future*<typename *std::iterator_traits<InputIter>::value_type>>>*

hpx::future<Container> **when_all_n**(*InputIter* begin, *std::size_t* count)

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Note: None of the futures in the input sequence are invalidated.

Parameters

- **begin** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all_n* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

Throws

This – function will throw errors which are encountered while setting up the requested operation only. Errors encountered while executing the operations delivering the results to be stored in the futures are reported through the futures themselves.

Returns

Returns a future holding the same list of futures as has been passed to *when_all_n*.

- `future<Container<future<R>>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output vector will be the same as given by the input iterator.

hpx::when_any

Defined in header `hpx/future.hpp`⁷¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename InputIter, typename Container = vector<future<typename
std::iterator_traits<InputIter>::value_type>>>
```

```
future<when_any_result<Container>> when_any(InputIter first, InputIter last)
```

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_any* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_any* should wait.

⁷¹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- `future<when_any_result<Container<future<R>>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename Range>
```

```
future<when_any_result<Range>> when_any(Range &values)
```

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

values – [in] A range holding an arbitrary amount of *futures* or *shared_future* objects for which *when_any* should wait.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- `future<when_any_result<Container<future<R>>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename ...T>
```

```
future<when_any_result<tuple<future<T>...>>> when_any(T&&... futures)
```

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_any* should wait.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- `future<when_any_result<tuple<future<T0>, future<T1>...>>>`: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.
- `future<when_any_result<tuple<>>>` if *when_any* is called with zero arguments. The returned future will be initially ready.

```
template<typename InputIter, typename Container = vector<future<typename  
std::iterator_traits<InputIter>::value_type>>>
```

```
future<when_any_result<Container>> when_any_n(InputIter first, std::size_t count)
```

function *when_any_n* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Note: None of the futures in the input sequence are invalidated.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_any_n* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- `future<when_any_result<Container<future<R>>>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename Sequence>
```

```
struct when_any_result
```

#include <*when_any.hpp*> Result type for *when_any*, contains a sequence of futures and an index pointing to a ready future.

Public Members

`std::size_t` **index**

The index of a future which has become ready.

Sequence **futures**

The sequence of futures as passed to `hpx::when_any`

hpx::wait_some

Defined in header `hpx/future.hpp`⁷¹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

⁷¹⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Functions

```
template<typename InputIter>
void wait_some(std::size_t n, InputIter first, InputIter last)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the function to return.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

```
template<typename R>
void wait_some(std::size_t n, std::vector<future<R>> &&futures)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_some* should wait.

```
template<typename R, std::size_t N>
void wait_some(std::size_t n, std::array<future<R>, N> &&futures)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_some* should wait.

```
template<typename ...T>
void wait_some(std::size_t n, T&&... futures)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_all* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_some* should wait.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
template<typename InputIter>
void wait_some_n(std::size_t n, InputIter first, std::size_t count)
```

The function *wait_some_n* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some_n* returns after *n* futures have become ready. All input futures are still valid after *wait_some_n* returns.

Note: The function `wait_some_n` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_some_n_nothrow` instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

hpx::wait_each

Defined in header `hpx/future.hpp`⁷¹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename F, typename Future>
void wait_each(F &&f, std::vector<Future> &&futures)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that `std::size_t` is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_each* should wait.

```
template<typename F, typename Iterator>
void wait_each(F &&f, Iterator begin, Iterator end)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called

⁷¹⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.
- **end** – The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.

```
template<typename F, typename ...T>
void wait_each(F &&f, T&&... futures)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_each* should wait.

```
template<typename F, typename Iterator>
void wait_each_n(F &&f, Iterator begin, std::size_t count)
```

The function *wait_each* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each_n* should wait.
- **count** – The number of elements in the sequence starting at *first*.

hpx::wait_all

Defined in header [hpx/future.hpp](#)⁷¹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename InputIter>  
void wait_all(InputIter first, InputIter last)
```

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after all futures have become ready. All input futures are still valid after *wait_all* returns.

Note: The function *wait_all* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_all_nothrow* instead.

Parameters

- **first** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all* should wait.
- **last** – The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_all* should wait.

```
template<typename R>  
void wait_all(std::vector<future<R>> &&futures)
```

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after all futures have become ready. All input futures are still valid after *wait_all* returns.

⁷¹⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Note: The function `wait_all` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which `wait_all` should wait.

```
template<typename R, std::size_t N>
void wait_all(std::array<future<R>, N> &&futures)
```

The function `wait_all` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function `wait_all` returns after all futures have become ready. All input futures are still valid after `wait_all` returns.

Note: The function `wait_all` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which `wait_all` should wait.

```
template<typename T>
void wait_all(hpx::future<T> const &f)
```

The function `wait_all` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function `wait_all` returns after the future has become ready. The input future is still valid after `wait_all` returns.

Note: The function `wait_all` will rethrow any exceptions captured by the future while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

f – A *future* or *shared_future* for which `wait_all` should wait.

```
template<typename ...T>
void wait_all(T&&... futures)
```

The function `wait_all` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function `wait_all` returns after all futures have become ready. All input futures are still valid after `wait_all` returns.

Note: The function `wait_all` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

futures – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which `wait_all` should wait.

```
template<typename InputIter>
void wait_all_n(InputIter begin, std::size_t count)
```

The function `wait_all_n` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function `wait_all_n` returns after all futures have become ready. All input futures are still valid after `wait_all_n` returns.

Note: The function `wait_all_n` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_all_n_nothrow` instead.

Parameters

- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which `wait_all_n` should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

The function `wait_all_n` will return an iterator referring to the first element in the input sequence after the last processed element.

hpx/async_combinators/split_future.hpp

Defined in header `hpx/async_combinators/split_future.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename ...Ts>
inline tuple<future<Ts>...> split_future(future<tuple<Ts...>> &&f)
```

The function `split_future` is an operator allowing to split a given future of a sequence of values (any tuple, `std::pair`, or `std::array`) into an equivalent container of futures where each future represents one of the values from the original future. In some sense this function provides the inverse operation of `when_all`.

Note: The following cases are special:

```
tuple<future<void> > split_future(future<tuple<> > && f);
array<future<void>, 1> split_future(future<array<T, 0> > && f);
```

here the returned futures are directly representing the futures which were passed to the function.

Parameters

f – [in] A future holding an arbitrary sequence of values stored in a tuple-like container. This facility supports *hpx::tuple<>*, *std::pair<T1, T2>*, and *std::array<T, N>*

Returns

Returns an equivalent container (same container type as passed as the argument) of futures, where each future refers to the corresponding value in the input parameter. All the returned futures become ready once the input future has become ready. If the input future is exceptional, all output futures will be exceptional as well.

```
template<typename T>
inline std::vector<future<T>> split_future(future<std::vector<T>> &&f, std::size_t size)
```

The function *split_future* is an operator allowing to split a given future of a sequence of values (any *std::vector*) into a *std::vector* of futures where each future represents one of the values from the original *std::vector*. In some sense this function provides the inverse operation of *when_all*.

Parameters

- **f** – [in] A future holding an arbitrary sequence of values stored in a *std::vector*.
- **size** – [in] The number of elements the vector will hold once the input future has become ready

Returns

Returns a *std::vector* of futures, where each future refers to the corresponding value in the input parameter. All the returned futures become ready once the input future has become ready. If the input future is exceptional, all output futures will be exceptional as well.

hpx::when_each

Defined in header [hpx/future.hpp](#)⁷¹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

⁷¹⁷ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Functions

```
template<typename F, typename Future>  
future<void> when_each(F &&f, std::vector<Future> &&futures)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

```
template<typename F, typename Iterator>  
future<Iterator> when_each(F &&f, Iterator begin, Iterator end)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.
- **end** – The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

```
template<typename F, typename ...Ts>  
future<void> when_each(F &&f, Ts&&... futures)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

```
template<typename F, typename Iterator>
future<Iterator> when_each_n(F &&f, Iterator begin, std::size_t count)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each_n* should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

Returns a future holding the iterator pointing to the first element after the last one.

async_cuda

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_cuda/cublas_executor.hpp

Defined in header `hpx/async_cuda/cublas_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_cuda/cuda_executor.hpp

Defined in header `hpx/async_cuda/cuda_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **cuda**

namespace **experimental**

struct **cuda_executor** : public *hpx::cuda::experimental::cuda_executor_base*

Public Functions

inline explicit **cuda_executor**(*std::size_t* const device, bool const event_mode = true)

inline ~**cuda_executor**()

template<typename **R**, typename ...**Params**, typename ...**Args**>

inline void **post**(*R* (*cuda_function)(*Params*...), *Args*&&... args) const

template<typename **F**, typename ...**Ts**>

inline decltype(auto) **async_execute**(*F* &&f, *Ts*&&... ts) const

template<typename **R**, typename ...**Params**, typename ...**Args**>

inline *hpx::future*<void> **async**(*R* (*cuda_kernel)(*Params*...), *Args*&&... args) const

struct **cuda_executor_base**

Subclassed by *hpx::cuda::experimental::cuda_executor*

Public Types

using **future_type** = *hpx::future*<void>

Public Functions

inline **cuda_executor_base**(*std::size_t* device, bool const event_mode)

inline *future_type* **get_future**() const

Protected Attributes

int **device_**

bool **event_mode_**

cudaStream_t **stream_**

std::shared_ptr<hpx::cuda::experimental::target> **target_**

namespace **execution**

namespace **experimental**

async_mpi

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_mpi/mpi_executor.hpp

Defined in header `hpx/async_mpi/mpi_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **mpi**

namespace **experimental**

struct **executor**

Public Types

```
using execution_category = hpx::execution::parallel_execution_tag
```

```
using executor_parameters_type = hpx::execution::experimental::default_parameters
```

Public Functions

```
inline explicit constexpr executor(MPI_Comm communicator = MPI_COMM_WORLD)
```

```
template<typename F, typename ...Ts>
```

```
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const
```

```
inline std::size_t in_flight_estimate() const
```

Private Members

```
MPI_Comm communicator_
```

hpx/async_mpi/transform_mpi.hpp

Defined in header `hpx/async_mpi/transform_mpi.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace mpi
```

```
namespace experimental
```

Variables

```
hpx::mpi::experimental::transform_mpi_t transform_mpi
```

```
struct transform_mpi_t : public hpx::functional::detail::tag_fallback<transform_mpi_t>
```

Friends

```
template<typename Sender,
typename F> inline friend constexpr friend auto tag_fallback_invoke (transform_mpi_t,
Sender &&s, F &&f)

template<typename F> inline friend constexpr friend auto tag_fallback_invoke (transform
F &&f)
```

async_sycl

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_sycl/sycl_executor.hpp

Defined in header `hpx/async_sycl/sycl_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Executor, typename ...Ts>
decltype(auto) async(Executor &&exec, hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<Ts...>
&&f, Ts&&... ts)
```

`hpx::async` overload for launching `sycl` queue member functions with an `sycl` executor

```
template<typename Executor, typename ...Ts>
bool apply(Executor &&exec, hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<Ts...> &&f,
Ts&&... ts)
```

`hpx::apply` overload for launching `sycl` queue member functions with an `sycl` executor

namespace **execution**

namespace **experimental**

namespace **sycl**

namespace **experimental**

struct **sycl_executor**

Public Types

```
using future_type = hpx::future<void>
```

```
template<typename ...Params>
```

```
using queue_function_ptr_t = ::sycl::event  
(::sycl::queue::*)(std::conditional_t<std::is_trivial_v<std::remove_reference_t<Params>>,  
std::decay_t<Params>, Params>...)
```

Default Implementation without the extra intel code_location parameter. Removes the reference for trivial types to make the function matching easier (see `sycl_stream.cpp` test)

Public Functions

```
template<typename sycl_device_selector>  
inline explicit sycl_executor(sycl_device_selector const &selector)
```

Create a SYCL executor (based on a sycl queue)

```
~sycl_executor() = default
```

```
inline future_type get_future()
```

Get future for this command_queue (NOTE will be more efficient if an event is provided — otherwise a dummy kernel must be submitted to get an event)

```
inline future_type get_future(::sycl::event event)
```

Get future for that becomes ready when the given event completes.

```
template<typename ...Params>  
inline void post(queue_function_ptr_t<Params...> &&queue_member_function, Params&&...  
args)
```

Invoke queue member function given queue and parameters — do not use event to return a `hpx::future` (One way)

```
template<typename ...Params>  
inline hpx::future<void> async_execute(queue_function_ptr_t<Params...>  
&&queue_member_function, Params&&... args)
```

Invoke queue member function given queue and parameters — `hpx::future` tied to the sycl event / (two way)

```
inline ::sycl::device get_device() const
```

Return the device used by the underlying SYCL queue.

```
inline ::sycl::context get_context() const
```

Return the context used by the underlying SYCL queue.

```
inline ::sycl::queue &get_queue()
```

Return the underlying queue for direct access.

Protected Attributes

`::sycl::queue` **command_queue**

cache

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/cache/local_cache.hpp

Defined in header `hpx/cache/local_cache.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

namespace **cache**

```
template<typename Key, typename Entry, typename UpdatePolicy = std::less<Entry>, typename
InsertPolicy = policies::always<Entry>, typename CacheStorage = std::map<Key, Entry>,
typename Statistics = statistics::no_statistics>
class local_cache
```

#include <hpx/cache/local_cache.hpp> The `local_cache` implements the basic functionality needed for a local (non-distributed) cache.

Template Parameters

- **Key** – The type of the keys to use to identify the entries stored in the cache
- **Entry** – The type of the items to be held in the cache, must model the `CacheEntry` concept
- **UpdatePolicy** – A (optional) type specifying a (binary) function object used to sort the cache entries based on their ‘age’. The ‘oldest’ entries (according to this sorting criteria) will be discarded first if the maximum capacity of the cache is reached. The default is `std::less<Entry>`. The function object will be invoked using 2 entry instances of the type `Entry`. This type must model the `UpdatePolicy` model.
- **InsertPolicy** – A (optional) type specifying a (unary) function object used to allow global decisions whether a particular entry should be added to the cache or not. The default is `policies::always`, imposing no global insert related criteria on the cache. The function object will be invoked using the entry instance to be inserted into the cache. This type must model the `InsertPolicy` model.
- **CacheStorage** – A (optional) container type used to store the cache items. The container must be an associative and STL compatible container. The default is a `std::map<Key, Entry>`.
- **Statistics** – A (optional) type allowing to collect some basic statistics about the operation of the cache instance. The type must conform to the `CacheStatistics` concept. The default value is the type `statistics::no_statistics` which does not collect any numbers, but provides empty stubs allowing the code to compile.

Public Types

```
using key_type = Key

using entry_type = Entry

using update_policy_type = UpdatePolicy

using insert_policy_type = InsertPolicy

using storage_type = CacheStorage

using statistics_type = Statistics

using value_type = typename entry_type::value_type

using size_type = typename storage_type::size_type

using storage_value_type = typename storage_type::value_type
```

Public Functions

```
inline explicit local_cache(size_type max_size = 0, update_policy_type const &up =  
    update_policy_type(), insert_policy_type const &ip =  
    insert_policy_type())
```

Construct an instance of a *local_cache*.

Parameters

- **max_size** – [in] The maximal size this cache is allowed to reach any time. The default is zero (no size limitation). The unit of this value is usually determined by the unit of the values returned by the entry's *get_size* function.
- **up** – [in] An instance of the *UpdatePolicy* to use for this cache. The default is to use a default constructed instance of the type as defined by the *UpdatePolicy* template parameter.
- **ip** – [in] An instance of the *InsertPolicy* to use for this cache. The default is to use a default constructed instance of the type as defined by the *InsertPolicy* template parameter.

```
local_cache(local_cache const &other) = default
```

```
local_cache(local_cache &&other) = default
```

```
local_cache &operator=(local_cache const &other) = default
```

```
local_cache &operator=(local_cache &&other) = default
```

```
~local_cache() = default
```


inline constexpr *size_type* **size**() const noexcept

Return current size of the cache.

Returns

The current size of this cache instance.

inline constexpr *size_type* **capacity**() const noexcept

Access the maximum size the cache is allowed to grow to.

Note: The unit of this value is usually determined by the unit of the return values of the entry's function *entry::get_size*.

Returns

The maximum size this cache instance is currently allowed to reach. If this number is zero the cache has no limitation with regard to a maximum size.

inline bool **reserve**(*size_type* max_size)

Change the maximum size this cache can grow to.

Parameters

max_size – [in] The new maximum size this cache will be allowed to grow to.

Returns

This function returns *true* if successful. It returns *false* if the new *max_size* is smaller than the current limit and the cache could not be shrunk to the new maximum size.

inline bool **holds_key**(*key_type* const &k) const

Check whether the cache currently holds an entry identified by the given key.

Note: This function does not call the entry's function *entry::touch*. It just checks if the cache contains an entry corresponding to the given key.

Parameters

k – [in] The key for the entry which should be looked up in the cache.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

inline bool **get_entry**(*key_type* const &k, *key_type* &realkey, *entry_type* &val)

Get a specific entry identified by the given key.

Note: The function will call the entry's *entry::touch* function if the value corresponding to the provided key is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache.
- **realkey[out]** – Return the full real key found in the cache
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

inline bool **get_entry**(*key_type* const &k, *entry_type* &val)

Get a specific entry identified by the given key.

Note: The function will call the entry's `entry::touch` function if the value corresponding to the provided key is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache.
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &k, value_type &val)
```

Get a specific entry identified by the given key.

Note: The function will call the entry's `entry::touch` function if the value corresponding to the provided is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding value.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool insert(key_type const &k, value_type const &val)
```

Insert a new element into this cache.

Note: This function invokes both, the insert policy as provided to the constructor and the function `entry::insert` of the newly constructed entry instance. If either of these functions returns false the key/value pair doesn't get inserted into the cache and the `insert` function will return *false*. Other reasons for this function to fail (return *false*) are a) the key/value pair is already held in the cache or b) inserting the new value into the cache maxed out its capacity and it was not possible to free any of the existing entries.

Parameters

- **k** – [in] The key for the entry which should be added to the cache.
- **val** – [in] The value which should be added to the cache.

Returns

This function returns *true* if the entry has been successfully added to the cache, otherwise it returns *false*.

```
inline bool insert(key_type const &k, value_type &&val)
```

```
template<typename Entry_, std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>,  
entry_type>, int> = 0>
```

```
inline bool insert(key_type const &k, Entry_ &&e)
```

Insert a new entry into this cache.

Note: This function invokes both, the insert policy as provided to the constructor and the function `entry::insert` of the provided entry instance. If either of these functions returns false

the key/value pair doesn't get inserted into the cache and the *insert* function will return *false*. Other reasons for this function to fail (return *false*) are a) the key/value pair is already held in the cache or b) inserting the new value into the cache maxed out its capacity and it was not possible to free any of the existing entries.

Parameters

- **k** – [in] The key for the entry which should be added to the cache.
- **e** – [in] The entry which should be added to the cache.

Returns

This function returns *true* if the entry has been successfully added to the cache, otherwise it returns *false*.

```
template<typename Value, std::enable_if_t<std::is_convertible_v<std::decay_t<Value>, value_type>, int> = 0>
```

```
inline bool update(key_type const &k, Value &&val)
```

Update an existing element in this cache.

Note: The function will call the entry's *entry::touch* function if the indexed value is found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **k** – [in] The key for the value which should be updated in the cache.
- **val** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename F, typename Value, typename = std::enable_if_t<std::is_convertible_v<std::decay_t<Value>, value_type>>>
```

```
inline bool update_if(key_type const &k, Value &&val, F &&f)
```

Update an existing element in this cache.

Note: The function will call the entry's *entry::touch* function if the indexed value is found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **k** – [in] The key for the value which should be updated in the cache.
- **val** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.

- **f** – [in] A callable taking two arguments, *k* and the key found in the cache (in that order). If *f* returns true, then the update will continue. If *f* returns false, then the update will not succeed.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Entry_, std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>,
entry_type>, int> = 0>
```

```
inline bool update(key_type const &k, Entry_ &&e)
```

Update an existing entry in this cache.

Note: The function will call the entry's *entry::touch* function if the indexed value is found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the whole cache entry, while the other overload replaces the cached value only, leaving the cache entry properties untouched.

Parameters

- **k** – [in] The key for the entry which should be updated in the cache.
- **e** – [in] The entry which should be used as a replacement for the existing entry in the cache. Any existing entry is first removed and then this entry is added.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Func = policies::always<storage_value_type>>
```

```
inline size_type erase(Func &&ep = Func())
```

Remove stored entries from the cache for which the supplied function object returns true.

Parameters

ep – [in] This parameter has to be a (unary) function object. It is invoked for each of the entries currently held in the cache. An entry is considered for removal from the cache whenever the value returned from this invocation is *true*. Even then the entry might not be removed from the cache as its *entry::remove* function might return false.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type erase()
```

Remove all stored entries from the cache.

Note: All entries are considered for removal, but in the end an entry might not be removed from the cache as its *entry::remove* function might return false. This function is very useful for instance in conjunction with an entry's *entry::remove* function enforcing additional criteria like entry expiration, etc.

Returns

This function returns the overall size of the removed entries (which is the sum of the

values returned by the *entry::get_size* functions of the removed entries).

inline void **clear**()

Clear the cache.

Unconditionally removes all stored entries from the cache.

inline constexpr *statistics_type* const &**get_statistics**() const noexcept

Allow to access the embedded statistics instance.

Returns

This function returns a reference to the statistics instance embedded inside this cache

inline *statistics_type* &**get_statistics**() noexcept

Protected Functions

inline bool **free_space**(long num_free)

Private Types

using **iterator** = typename *storage_type*::iterator

using **const_iterator** = typename *storage_type*::const_iterator

using **heap_type** = std::deque<iterator>

using **heap_iterator** = typename *heap_type*::iterator

using **adapted_update_policy_type** = adapt<UpdatePolicy, iterator>

using **update_on_exit** = typename *statistics_type*::update_on_exit

Private Members

size_type **max_size_**

size_type **current_size_**

storage_type **store_**

heap_type **entry_heap_**

adapted_update_policy_type **update_policy_**

insert_policy_type **insert_policy_**

```
statistics_type statistics_  
template<typename Func, typename Iterator>  
struct adapt
```

Public Functions

```
inline explicit adapt(Func const &f)  
inline explicit adapt(Func &&f) noexcept  
inline bool operator() (Iterator const &lhs, Iterator const &rhs) const
```

Public Members

```
Func f_
```

hpx/cache/lru_cache.hpp

Defined in header `hpx/cache/lru_cache.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace util
```

```
namespace cache
```

```
template<typename Key, typename Entry, typename Statistics = statistics::no_statistics>
```

```
class lru_cache
```

#include <hpx/cache/lru_cache.hpp> The `lru_cache` implements the basic functionality needed for a local (non-distributed) LRU cache.

Template Parameters

- **Key** – The type of the keys to use to identify the entries stored in the cache
- **Entry** – The type of the items to be held in the cache.
- **Statistics** – A (optional) type allowing to collect some basic statistics about the operation of the cache instance. The type must conform to the `CacheStatistics` concept. The default value is the type `statistics::no_statistics` which does not collect any numbers, but provides empty stubs allowing the code to compile.

Public Types

```
using key_type = Key

using entry_type = Entry

using statistics_type = Statistics

using entry_pair = std::pair<key_type, entry_type>

using storage_type = std::list<entry_pair>

using map_type = std::map<Key, typename storage_type::iterator>

using size_type = std::size_t
```

Public Functions

```
inline explicit lru_cache(size_type max_size = 0)
```

Construct an instance of a *lru_cache*.

Parameters

max_size – [in] The maximal size this cache is allowed to reach any time. The default is zero (no size limitation). The unit of this value is usually determined by the unit of the values returned by the entry's *get_size* function.

```
lru_cache(lru_cache const &other) = default
```

```
lru_cache(lru_cache &&other) = default
```

```
lru_cache &operator=(lru_cache const &other) = default
```

```
lru_cache &operator=(lru_cache &&other) = default
```

```
~lru_cache() = default
```

```
inline constexpr size_type size() const noexcept
```

Return current size of the cache.

Returns

The current size of this cache instance.

```
inline constexpr size_type capacity() const noexcept
```

Access the maximum size the cache is allowed to grow to.

Note: The unit of this value is usually determined by the unit of the return values of the entry's function *entry::get_size*.

Returns

The maximum size this cache instance is currently allowed to reach. If this number is zero the cache has no limitation with regard to a maximum size.

```
inline void reserve(size_type max_size)
```

Change the maximum size this cache can grow to.

Parameters

max_size – [in] The new maximum size this cache will be allowed to grow to.

```
inline bool holds_key(key_type const &key) const
```

Check whether the cache currently holds an entry identified by the given key.

Note: This function does not call the entry’s function *entry::touch*. It just checks if the cache contains an entry corresponding to the given key.

Parameters

key – [in] The key for the entry which should be looked up in the cache.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &key, key_type &realkey, entry_type &entry)
```

Get a specific entry identified by the given key.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Parameters

- **key** – [in] The key for the entry which should be retrieved from the cache.
- **realkey[out]** – Return the full real key found in the cache
- **entry** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &key, entry_type const &entry)
```

Get a specific entry identified by the given key.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Parameters

- **key** – [in] The key for the entry which should be retrieved from the cache.
- **entry** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
template<typename Entry_, typename =  
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>  
inline bool insert(key_type const &key, Entry_ &&entry)
```

Insert a new entry into this cache.

Note: This function assumes that the entry is not in the cache already. Inserting an already existing entry is considered undefined behavior

Parameters

- **key** – [in] The key for the entry which should be added to the cache.
- **entry** – [in] The entry which should be added to the cache.

```
template<typename Entry_, typename =
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>
inline void update(key_type const &key, Entry_ &&entry)
```

Update an existing element in this cache.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **key** – [in] The key for the value which should be updated in the cache.
- **entry** – [in] The entry which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.

```
template<typename F, typename Entry_,
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>, int> = 0>
inline bool update_if(key_type const &key, Entry_ &&entry, F &&f)
```

Update an existing element in this cache.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **key** – [in] The key for the value which should be updated in the cache.
- **entry** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.
- **f** – [in] A callable taking two arguments, *k* and the key found in the cache (in that order). If *f* returns true, then the update will continue. If *f* returns false, then the update will not succeed.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Func>
inline size_type erase(Func const &ep)
```

Remove stored entries from the cache for which the supplied function object returns true.

Parameters

ep – [in] This parameter has to be a (unary) function object. It is invoked for each of the entries currently held in the cache. An entry is considered for removal from the cache whenever the value returned from this invocation is *true*.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type erase()
```

Remove all stored entries from the cache.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type clear()
```

Clear the cache.

Unconditionally removes all stored entries from the cache.

```
inline constexpr statistics_type const &get_statistics() const noexcept
```

Allow to access the embedded statistics instance.

Returns

This function returns a reference to the statistics instance embedded inside this cache

```
inline statistics_type &get_statistics() noexcept
```

Private Types

```
using update_on_exit = typename statistics_type::update_on_exit
```

Private Functions

```
template<typename Entry_, typename =
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>
inline void insert_nonexist(key_type const &key, Entry_ &&entry)
```

```
inline void touch(typename storage_type::iterator it)
```

```
inline void evict()
```

Private Members

```
size_type max_size_
```

```
size_type current_size_ = 0
```

```
storage_type storage_
```

map_type **map_**

statistics_type **statistics_**

hpx/cache/statistics/no_statistics.hpp

Defined in header `hpx/cache/statistics/no_statistics.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **statistics**

Enums

enum class **method**

Values:

enumerator **get_entry**

enumerator **insert_entry**

enumerator **update_entry**

enumerator **erase_entry**

class **no_statistics**

Subclassed by `hpx::util::cache::statistics::local_statistics`

Public Static Functions

static inline constexpr void **got_hit**() noexcept

The function `got_hit` will be called by a cache instance whenever an entry got touched.

static inline constexpr void **got_miss**() noexcept

The function `got_miss` will be called by a cache instance whenever a requested entry has not been found in the cache.

static inline constexpr void **got_insertion**() noexcept

The function *got_insertion* will be called by a cache instance whenever a new entry has been inserted.

static inline constexpr void **got_eviction**() noexcept

The function *got_eviction* will be called by a cache instance whenever an entry has been removed from the cache because a new inserted entry let the cache grow beyond its capacity.

static inline constexpr void **clear**() noexcept

Reset all statistics.

static inline constexpr std::int64_t **get_get_entry_count**(bool) noexcept

The function *get_get_entry_count* returns the number of invocations of the *get_entry*() API function of the cache.

static inline constexpr std::int64_t **get_insert_entry_count**(bool) noexcept

The function *get_insert_entry_count* returns the number of invocations of the *insert_entry*() API function of the cache.

static inline constexpr std::int64_t **get_update_entry_count**(bool) noexcept

The function *get_update_entry_count* returns the number of invocations of the *update_entry*() API function of the cache.

static inline constexpr std::int64_t **get_erase_entry_count**(bool) noexcept

The function *get_erase_entry_count* returns the number of invocations of the *erase*() API function of the cache.

static inline constexpr std::int64_t **get_get_entry_time**(bool) noexcept

The function *get_get_entry_time* returns the overall time spent executing of the *get_entry*() API function of the cache.

static inline constexpr std::int64_t **get_insert_entry_time**(bool) noexcept

The function *get_insert_entry_time* returns the overall time spent executing of the *insert_entry*() API function of the cache.

static inline constexpr std::int64_t **get_update_entry_time**(bool) noexcept

The function *get_update_entry_time* returns the overall time spent executing of the *update_entry*() API function of the cache.

static inline constexpr std::int64_t **get_erase_entry_time**(bool) noexcept

The function *get_erase_entry_time* returns the overall time spent executing of the *erase*() API function of the cache.

struct **update_on_exit**

#include <no_statistics.hpp> Helper class to update timings and counts on function exit.

Public Functions

```

inline constexpr update_on_exit(no_statistics const&, method) noexcept
~update_on_exit() = default
update_on_exit(update_on_exit const&) = delete
update_on_exit(update_on_exit&&) = delete
update_on_exit &operator=(update_on_exit const&) = delete
update_on_exit &operator=(update_on_exit&&) = delete

```

hpx/cache/statistics/local_statistics.hpp

Defined in header `hpx/cache/statistics/local_statistics.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **statistics**

```
class local_statistics : public hpx::util::cache::statistics::no_statistics
```

Public Functions

```

local_statistics() = default
inline constexpr std::size_t hits() const noexcept
inline constexpr std::size_t misses() const noexcept
inline constexpr std::size_t insertions() const noexcept
inline constexpr std::size_t evictions() const noexcept
inline std::size_t hits(bool const reset) noexcept
inline std::size_t misses(bool const reset) noexcept
inline std::size_t insertions(bool const reset) noexcept
inline std::size_t evictions(bool const reset) noexcept
inline void got_hit() noexcept

```

The function `got_hit` will be called by a cache instance whenever an entry got touched.

inline void **got_miss**() noexcept

The function *got_miss* will be called by a cache instance whenever a requested entry has not been found in the cache.

inline void **got_insertion**() noexcept

The function *got_insertion* will be called by a cache instance whenever a new entry has been inserted.

inline void **got_eviction**() noexcept

The function *got_eviction* will be called by a cache instance whenever an entry has been removed from the cache because a new inserted entry let the cache grow beyond its capacity.

inline void **clear**() noexcept

Reset all statistics.

Private Members

std::size_t **hits_** = 0

std::size_t **misses_** = 0

std::size_t **insertions_** = 0

std::size_t **evictions_** = 0

Private Static Functions

static inline *std::size_t* **get_and_reset**(*std::size_t* &value, bool const reset) noexcept

hpx/cache/entries/size_entry.hpp

Defined in header `hpx/cache/entries/size_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

```
class size_entry : public hpx::util::cache::entries::entry<Value>
```

#include <hpx/cache/entries/size_entry.hpp> The `size_entry` type can be used to store values in a cache which have a size associated (such as files, etc.). Using this type as the cache's entry type makes sure that the entries with the biggest size are discarded from the cache first.

Note: The `size_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'discard smallest first' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

size_entry() = default

Any cache entry has to be default constructible.

```
inline explicit size_entry(Value const &val, std::size_t size = 0)
    noexcept(std::is_nothrow_constructible_v<base_type, Value
             const&>)
```

Construct a new instance of a cache entry holding the given value.

```
inline explicit size_entry(Value &&val, std::size_t size = 0) noexcept
```

Construct a new instance of a cache entry holding the given value.

```
inline constexpr std::size_t get_size() const noexcept
```

Return the 'size' of this entry.

Private Types

```
using base_type = entry<Value>
```

Private Members

```
std::size_t size_ = 0
```

Friends

```
inline friend auto operator<(size_entry const &lhs, size_entry const &rhs) noexcept
    Compare the ‘age’ of two entries. An entry is ‘older’ than another entry if it has a bigger size.
inline friend auto operator>(size_entry const &lhs, size_entry const &rhs) noexcept
inline friend auto operator<= (size_entry const &lhs, size_entry const &rhs) noexcept
inline friend auto operator>= (size_entry const &lhs, size_entry const &rhs) noexcept
inline friend auto operator== (size_entry const &lhs, size_entry const &rhs) noexcept
inline friend auto operator!= (size_entry const &lhs, size_entry const &rhs) noexcept
```

hpx/cache/entries/lfu_entry.hpp

Defined in header `hpx/cache/entries/lfu_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **lfu_entry** : public *hpx::util::cache::entries::entry<Value>*

#include <hpx/cache/entries/lfu_entry.hpp> The `lfu_entry` type can be used to store arbitrary values in a cache. Using this type as the cache’s entry type makes sure that the least frequently used entries are discarded from the cache first.

Note: The `lfu_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a ‘most frequently used’ cache policy if it is used with a `std::greater` as the caches’ `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

lfu_entry() = default

Any cache entry has to be default constructible.

```
inline explicit lfu_entry(Value const &val)
    noexcept(std::is_nothrow_constructible_v<base_type, Value
    const&>)
```

Construct a new instance of a cache entry holding the given value.

```
inline explicit lfu_entry(Value &&val) noexcept
```

Construct a new instance of a cache entry holding the given value.

```
inline bool touch() noexcept
```

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

In the case of the LFU entry we store the reference count tracking the number of times this entry has been requested. This which will be used to compare the age of an entry during the invocation of the *operator<()*.

Returns

This function should return true if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

```
inline constexpr unsigned long const &get_access_count() const noexcept
```

Private Types

```
using base_type = entry<Value>
```

Private Members

```
unsigned long ref_count_ = 0
```

Friends

```
inline friend auto operator<(lfu_entry const &lhs, lfu_entry const &rhs)
```

Compare the 'age' of two entries. An entry is 'older' than another entry if it has been accessed less frequently (LFU).

```
inline friend auto operator>(lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator<= (lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator>= (lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator== (lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator!= (lfu_entry const &lhs, lfu_entry const &rhs)
```

hpx/cache/entries/entry.hpp

Defined in header `hpx/cache/entries/entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **entry**

#include <hpx/cache/entries/entry.hpp>

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and less_than_comparable.

Subclassed by `hpx::util::cache::entries::fifo_entry< Value >`,
`hpx::util::cache::entries::lru_entry< Value >`,
`hpx::util::cache::entries::size_entry< Value >`

Public Types

using **value_type** = *Value*

Public Functions

entry() = default

Any cache entry has to be default constructible.

inline explicit **entry**(*value_type* const &val)
noexcept(*std::is_nothrow_copy_constructible_v<value_type>*)

Construct a new instance of a cache entry holding the given value.

inline explicit **entry**(*value_type* &&val) noexcept

Construct a new instance of a cache entry holding the given value.

inline *value_type* &**get**() noexcept

Get a reference to the stored data value.

Note: This function is part of the CacheEntry concept

inline constexpr *value_type* const &**get**() const noexcept

Public Static Functions

static inline constexpr bool **touch**() noexcept

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

Note: It is possible to change the entry in a way influencing the sort criteria mandated by the UpdatePolicy. In this case the function should return *true* to indicate this to the cache, forcing to reorder the cache entries.

Note: This function is part of the CacheEntry concept

Returns

This function should return *true* if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

static inline constexpr bool **insert**() noexcept

The function *insert* is called by a cache whenever it is about to be inserted into the cache.

Note: This function is part of the CacheEntry concept

Returns

This function should return *true* if the entry should be added to the cache, otherwise it should return *false*.

static inline constexpr bool **remove**() noexcept

The function *remove* is called by a cache holding this instance whenever it is about to be removed from the cache.

Note: This function is part of the CacheEntry concept

Returns

The return value can be used to avoid removing this instance from the cache. If the value is *true* it is ok to remove the entry, otherwise it will stay in the cache.

static inline constexpr std::size_t **get_size**() noexcept

Return the 'size' of this entry. By default, the size of each entry is just one (1), which is sensible if the cache has a limit (capacity) measured in number of entries.

Private Members

value_type **value_**

Friends

friend auto operator (entry const &, entry const &)=default

Forwarding operator<=> allowing to compare entries instead of the values.

hpx/cache/entries/fifo_entry.hpp

Defined in header `hpx/cache/entries/fifo_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **fifo_entry** : public `hpx::util::cache::entries::entry<Value>`

#include <hpx/cache/entries/fifo_entry.hpp> The `fifo_entry` type can be used to store arbitrary values in a cache. Using this type as the cache's entry type makes sure that the least recently inserted entries are discarded from the cache first.

Note: The `fifo_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'last in first out' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

fifo_entry() = default

Any cache entry has to be default constructible.

```
inline explicit fifo_entry(Value const &val)
    noexcept(std::is_nothrow_constructible_v<base_type, Value
    const&>)
```

Construct a new instance of a cache entry holding the given value.

```
inline explicit fifo_entry(Value &&val) noexcept
```

Construct a new instance of a cache entry holding the given value.

```
inline constexpr bool insert()
```

The function *insert* is called by a cache whenever it is about to be inserted into the cache.

Note: This function is part of the CacheEntry concept

Returns

This function should return *true* if the entry should be added to the cache, otherwise it should return *false*.

```
inline constexpr time_point const &get_creation_time() const noexcept
```

Private Types

```
using base_type = entry<Value>
```

```
using time_point = std::chrono::steady_clock::time_point
```

Private Members

```
time_point insertion_time_
```

Friends

```
inline friend auto operator<(fifo_entry const &lhs, fifo_entry const &rhs)
```

Compare the ‘age’ of two entries. An entry is ‘older’ than another entry if it has been created earlier (FIFO).

```
inline friend auto operator>(fifo_entry const &lhs, fifo_entry const &rhs)
```

```
inline friend auto operator<=(fifo_entry const &lhs, fifo_entry const &rhs)
```

```
inline friend auto operator>=(fifo_entry const &lhs, fifo_entry const &rhs)
```

```
inline friend auto operator==(fifo_entry const &lhs, fifo_entry const &rhs)
```

```
inline friend auto operator!=(fifo_entry const &lhs, fifo_entry const &rhs)
```

hpx/cache/entries/lru_entry.hpp

Defined in header `hpx/cache/entries/lru_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **lru_entry** : public *hpx::util::cache::entries::entry<Value>*

#include <hpx/cache/entries/lru_entry.hpp> The `lru_entry` type can be used to store arbitrary values in a cache. Using this type as the cache's entry type makes sure that the least recently used entries are discarded from the cache first.

Note: The `lru_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'most recently used' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

inline **lru_entry**()

Any cache entry has to be default constructible.

inline explicit **lru_entry**(*Value* const &val)
noexcept(*std::is_nothrow_constructible_v<base_type, Value*
const&>)

Construct a new instance of a cache entry holding the given value.

inline explicit **lru_entry**(*Value* &&val) noexcept

Construct a new instance of a cache entry holding the given value.

inline bool **touch**()

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

In the case of the LRU entry we store the time of the last access which will be used to compare the age of an entry during the invocation of the *operator<()*.

Returns

This function should return true if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

```
inline constexpr time_point const &get_access_time() const noexcept
```

Returns the last access time of the entry.

Private Types

```
using base_type = entry<Value>
```

```
using time_point = std::chrono::steady_clock::time_point
```

Private Members

```
time_point access_time_
```

Friends

```
inline friend auto operator<(lru_entry const &lhs, lru_entry const &rhs)
```

Compare the ‘age’ of two entries. An entry is ‘older’ than another entry if it has been accessed less recently (LRU).

```
inline friend auto operator>(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator<=(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator>=(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator==(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator!=(lru_entry const &lhs, lru_entry const &rhs)
```

checkpoint_base

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/checkpoint_base/checkpoint_data.hpp

Defined in header `hpx/checkpoint_base/checkpoint_data.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
    namespace util
```

Functions

```
template<typename Container, typename ...Ts>
void save_checkpoint_data(Container &data, Ts&&... ts)
    save_checkpoint_data
```

`Save_checkpoint_data` takes any number of objects which a user may wish to store in the given container.

Template Parameters

- **Container** – Container used to store the check-pointed data.
- **Ts** – Types of variables to checkpoint

Parameters

- **data** – Container instance used to store the checkpoint data
- **ts** – Variable instances to be inserted into the checkpoint.

```
template<typename ...Ts>
std::size_t prepare_checkpoint_data(Ts const&... ts)
    prepare_checkpoint_data
```

`prepare_checkpoint_data` takes any number of objects which a user may wish to store in a subsequent `save_checkpoint_data` operation. The function will return the number of bytes necessary to store the data that will be produced.

Template Parameters

Ts – Types of variables to checkpoint

Parameters

ts – Variable instances to be inserted into the checkpoint.

```
template<typename Container, typename ...Ts>
void restore_checkpoint_data(Container const &cont, Ts&... ts)
    restore_checkpoint_data
```

`restore_checkpoint_data` takes any number of objects which a user may wish to restore from the given container. The sequence of objects has to correspond to the sequence of objects for the corresponding call to `save_checkpoint_data` that had used the given container instance.

Template Parameters

- **Container** – Container used to restore the check-pointed data.
- **Ts** – Types of variables to restore

Parameters

- **cont** – Container instance used to restore the checkpoint data
- **ts** – Variable instances to be restored from the container

```
struct checkpointing_tag

template<>

struct extra_data_helper<checkpointing_tag>
```


Public Static Functions

static extra_data_id_type **id**() noexcept

static inline constexpr void **reset**(*checkpointing_tag**) noexcept

compute_local

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/compute_local/vector.hpp

Defined in header `hpx/compute_local/vector.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **compute**

Functions

```
template<typename T, typename Allocator>
void swap(vector<T, Allocator> &x, vector<T, Allocator> &y) noexcept
    Effects: x.swap(y);
template<typename T, typename Allocator = std::allocator<T>>
class vector
```

Public Types

```
using value_type = T
    Member types (FIXME: add reference to std.

using allocator_type = Allocator

using access_target = typename alloc_traits::access_target

using size_type = std::size_t

using difference_type = std::ptrdiff_t

using reference = typename alloc_traits::reference

using const_reference = typename alloc_traits::const_reference
```

```
using pointer = typename alloc_traits::pointer

using const_pointer = typename alloc_traits::const_pointer

using iterator = detail::iterator<T, Allocator>

using const_iterator = detail::iterator<T const, Allocator>

using reverse_iterator = std::reverse_iterator<iterator>

using const_reverse_iterator = std::reverse_iterator<const_iterator>
```

Public Functions

```
inline explicit vector(Allocator const &alloc = Allocator())

inline vector(size_type count, T const &value, Allocator const &alloc = Allocator())

inline explicit vector(size_type count, Allocator const &alloc = Allocator())

template<typename InIter>
inline vector(InIter first, InIter last, Allocator const &alloc = Allocator())

inline vector(vector const &other)

inline vector(vector const &other, Allocator const &alloc)

inline vector(vector &&other) noexcept

inline vector(vector &&other, Allocator const &alloc)

inline vector(std::initializer_list<T> init, Allocator const &alloc)

inline ~vector()

inline vector &operator=(vector const &other)

inline vector &operator=(vector &&other) noexcept

inline void assign(size_type count, T const &value)

template<typename InIter>
inline void assign(InIter first, InIter last)

inline void assign(std::initializer_list<T> ilist)

inline allocator_type get_allocator() const noexcept
    Returns the allocator associated with the container.

inline reference at(size_type pos)

inline const_reference at(size_type pos) const
```

inline *reference* **operator[]**(*size_type* pos)

inline *const_reference* **operator[]**(*size_type* pos) const

inline *reference* **front**()

Returns a reference to the first element in the container. Calling front on an empty container is undefined.

inline *const_reference* **front**() const

Returns a reference to the first element in the container. Calling front on an empty container is undefined.

inline *reference* **back**()

Returns a reference to the last element in the container. Calling back on an empty container is undefined.

inline *const_reference* **back**() const

Returns a reference to the last element in the container. Calling back on an empty container is undefined.

inline *pointer* **data**() noexcept

Returns pointer to the underlying array serving as element storage. The pointer is such that range [*data()*; *data()* + *size()*) is always a valid range, even if the container is empty (*data()* is not dereference-able in that case).

inline *const_pointer* **data**() const noexcept

Returns pointer to the underlying array serving as element storage. The pointer is such that range [*data()*; *data()* + *size()*) is always a valid range, even if the container is empty (*data()* is not dereference-able in that case).

inline *T* ***device_data**() const noexcept

Returns a raw pointer corresponding to the address of the data allocated on the device.

inline *std::size_t* **size**() const noexcept

inline *std::size_t* **capacity**() const noexcept

inline bool **empty**() const noexcept

Returns: *size()* == 0.

inline void **resize**(*size_type*)

Effects: If *size* <= *size()*, equivalent to calling *pop_back()* *size()*

- *size* times. If *size()* < *size*, appends *size* - *size()* default-inserted elements to the sequence.

Requires: *T* shall be MoveInsertable and DefaultInsertable into *this.

Remarks: If an exception is thrown other than by the move constructor of a non-CopyInsertable *T* there are no effects.

inline void **resize**(*size_type*, *T* const&)

Effects: If *size* <= *size()*, equivalent to calling *pop_back()* *size()* - *size* times. If *size()* < *size*, appends *size* - *size()* copies of *val* to the sequence.

Requires: *T* shall be CopyInsertable into *this.

Remarks: If an exception is thrown there are no effects.

inline *iterator* **begin**() noexcept

inline *iterator* **end**() noexcept

inline *const_iterator* **cbegin**() const noexcept

inline *const_iterator* **cend**() const noexcept

inline *const_iterator* **begin**() const noexcept

inline *const_iterator* **end**() const noexcept

inline *reverse_iterator* **rbegin**() noexcept

inline *reverse_iterator* **rend**() noexcept

inline *const_reverse_iterator* **crbegin**() const noexcept

inline *const_reverse_iterator* **crend**() const noexcept

inline *const_reverse_iterator* **rbegin**() const noexcept

inline *const_reverse_iterator* **rend**() const noexcept

inline void **swap**(*vector* &other) noexcept

Effects: Exchanges the contents and capacity() of *this with that of x.

Complexity: Constant time.

inline void **clear**() noexcept

Effects: Erases all elements in the range [begin(),end()). Destroys all elements in 'a'. Invalidates all references, pointers, and iterators referring to the elements of a and may invalidate the past-the-end iterator.

Post: a.empty() returns true.

Complexity: Linear.

Private Types

using **alloc_traits** = *traits::allocator_traits*<*Allocator*>

Private Members

size_type **size_**

size_type **capacity_**

allocator_type **alloc_**

pointer **data_**

namespace **traits**

hpx/compute_local/host/block_fork_join_executor.hpp

Defined in header `hpx/compute_local/host/block_fork_join_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

class **block_fork_join_executor**

#include <block_fork_join_executor.hpp> An executor with fork-join (blocking) semantics.

The *block_fork_join_executor* creates on construction a set of worker threads that are kept alive for the duration of the executor. Copying the executor has reference semantics, i.e. copies of a *fork_join_executor* hold a reference to the worker threads of the original instance. Scheduling work through the executor concurrently from different threads is undefined behaviour.

The executor keeps a set of worker threads alive for the lifetime of the executor, meaning other work will not be executed while the executor is busy or waiting for work. The executor has a customizable delay after which it will yield to other work. Since starting and resuming the worker threads is a slow operation the executor should be reused whenever possible for multiple adjacent parallel algorithms or invocations of `bulk_(a)sync_execute`.

This behaviour is similar to the plain *fork_join_executor* except that the *block_fork_join_executor* creates a hierarchy of *fork_join_executors*, one for each target used to initialize it.

Public Functions

```
inline explicit block_fork_join_executor(threads::thread_priority const priority =
                                         threads::thread_priority::bound,
                                         threads::thread_stacksize const stacksize =
                                         threads::thread_stacksize::small_,
                                         fork_join_executor::loop_schedule const
                                         schedule =
                                         fork_join_executor::loop_schedule::static_,
                                         std::chrono::nanoseconds const yield_delay =
                                         std::chrono::milliseconds(1))
```

Construct a *block_fork_join_executor*.

Note: This constructor will create one *fork_join_executor* for each numa domain

Parameters

- **priority** – The priority of the worker threads.
- **stacksize** – The stacksize of the worker threads. Must not be `nostack`.
- **schedule** – The loop schedule of the parallel regions.
- **yield_delay** – The time after which the executor yields to other work if it has not received any new work for execution.

```
inline explicit block_fork_join_executor(std::vector<compute::host::target> const
                                         &targets, threads::thread_priority const priority
                                         = threads::thread_priority::bound,
                                         threads::thread_stacksize const stacksize =
                                         threads::thread_stacksize::small_,
                                         fork_join_executor::loop_schedule const
                                         schedule =
                                         fork_join_executor::loop_schedule::static_,
                                         std::chrono::nanoseconds const yield_delay =
                                         std::chrono::milliseconds(1))
```

Construct a *block_fork_join_executor*.

Note: This constructor will create one *fork_join_executor* for each given target

Parameters

- **targets** – The list of targets to use for thread placement
- **priority** – The priority of the worker threads.
- **stacksize** – The stacksize of the worker threads. Must not be nostack.
- **schedule** – The loop schedule of the parallel regions.
- **yield_delay** – The time after which the executor yields to other work if it has not received any new work for execution.

Private Members

fork_join_executor **exec_**

std::vector<*fork_join_executor*> **block_execs_**

Private Static Functions

```
static inline hpx::threads::mask_type cores_for_targets(std::vector<compute::host::target>
                                                         const &targets)
```

hpx/compute_local/host/block_executor.hpp

Defined in header *hpx/compute_local/host/block_executor.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Executor>
```

```
struct executor_execution_category<compute::host::block_executor<Executor>>
```

Public Types

```

using type = hpx::execution::parallel_execution_tag

template<typename Executor>

struct is_never_blocking_one_way_executor<compute::host::block_executor<Executor>>> : public
is_never_blocking_one_way_executor<Executor>

template<typename Executor>

struct is_one_way_executor<compute::host::block_executor<Executor>>> : public
is_one_way_executor<Executor>

template<typename Executor>

struct is_two_way_executor<compute::host::block_executor<Executor>>> : public
is_two_way_executor<Executor>

template<typename Executor>

struct is_bulk_one_way_executor<compute::host::block_executor<Executor>>> : public
is_bulk_one_way_executor<Executor>

template<typename Executor>

struct is_bulk_two_way_executor<compute::host::block_executor<Executor>>> : public
is_bulk_two_way_executor<Executor>

namespace hpx

    namespace compute

        namespace host

            template<typename Executor = hpx::execution::experimental::restricted_thread_pool_executor>

            struct block_executor

                #include <block_executor.hpp> The block executor can be used to build NUMA aware programs.
                It will distribute work evenly across the passed targets

                Template Parameters

                Executor – The underlying executor to use

```

Public Types

```

using executor_parameters_type = hpx::execution::experimental::default_parameters

```

Public Functions

```
inline explicit block_executor(std::vector<host::target> const &targets,  
                               threads::thread_priority priority =  
                               threads::thread_priority::high, threads::thread_stacksize  
                               stacksize = threads::thread_stacksize::default_,  
                               threads::thread_schedule_hint schedulehint = { })  
  
inline explicit block_executor(std::vector<host::target> &&targets)  
  
inline block_executor(block_executor const &other)  
  
inline block_executor(block_executor &&other) noexcept  
  
inline block_executor &operator=(block_executor const &other)  
  
inline block_executor &operator=(block_executor &&other) noexcept  
  
template<typename F, typename ...Ts>  
inline decltype(auto) post(F &&f, Ts&&... ts) const  
  
template<typename F, typename ...Ts>  
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const  
  
template<typename F, typename ...Ts>  
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const  
  
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_async_execute_impl(F &&f, Shape const &shape, Ts&&... ts)  
                                             const  
  
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_async_execute(F &&f, Shape const &shape, Ts&&... ts) const  
  
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_sync_execute_impl(F &&f, Shape const &shape, Ts&&... ts)  
                                             const  
  
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_sync_execute(F &&f, Shape const &shape, Ts&&... ts) const  
  
inline std::vector<host::target> const &targets() const noexcept
```

Private Functions

```
inline auto get_next_executor() const  
  
inline void init_executors()
```


Private Members

std::vector<host::target> **targets_**

mutable *std::atomic<std::size_t>* **current_**

std::vector<Executor> **executors_**

threads::thread_priority **priority_** = *threads::thread_priority::high*

threads::thread_stacksize **stacksize_** = *threads::thread_stacksize::default_*

threads::thread_schedule_hint **schedulehint_** = { }

namespace **execution**

namespace **experimental**

template<typename Executor> block_executor< Executor > >

Public Types

using **type** = *hpx::execution::parallel_execution_tag*

template<typename Executor> block_executor< Executor > > : public is_bulk_one_way_executor<

template<typename Executor> block_executor< Executor > > : public is_bulk_two_way_executor<

template<typename Executor> block_executor< Executor > > : public is_never_blocking_one_way

template<typename Executor> block_executor< Executor > > : public is_one_way_executor< Exec

template<typename Executor> block_executor< Executor > > : public is_two_way_executor< Exec

config

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/config/endian.hpp

Defined in header hpx/config/endian.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

contracts

See *Public API* for a list of names and headers that are part of the public *HPX* API.

HPX_PRE, HPX_POST, HPX_CONTRACT_ASSERT

Defined in header hpx/contracts.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PRE(x)

HPX_POST(x)

HPX_CONTRACT_ASSERT(expr)

coroutines

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/coroutines/thread_id_type.hpp

Defined in header hpx/coroutines/thread_id_type.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

struct **hash**<::hpx::threads::thread_id>

Public Functions

inline *std::size_t* **operator()**(::hpx::threads::thread_id const &v) const noexcept

template<>

struct **hash**<::hpx::threads::thread_id_ref>

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id_ref const &v) const noexcept
```

namespace **hpx**

namespace **threads**

Enums

```
enum class thread_id_addrf : std::uint8_t
```

Values:

enumerator **yes**

enumerator **no**

Variables

```
constexpr const thread_id invalid_thread_id
```

```
struct thread_id
```

Public Functions

```
constexpr thread_id() noexcept = default
```

```
thread_id(thread_id const&) noexcept = default
```

```
thread_id &operator=(thread_id const&) noexcept = default
```

```
~thread_id() = default
```

```
inline constexpr thread_id(thread_id &&rhs) noexcept
```

```
inline constexpr thread_id &operator=(thread_id &&rhs) noexcept
```

```
inline explicit constexpr thread_id(thread_id_repr const thrd) noexcept
```

```
inline constexpr thread_id &operator=(thread_id_repr const rhs) noexcept
```

```
inline explicit constexpr operator bool() const noexcept
```

```
inline constexpr thread_id_repr get() const noexcept
```

```
inline constexpr void reset() noexcept
```

Private Types

```
using thread_id_repr = void*
```

Private Members

```
thread_id_repr thrd_ = nullptr
```

Friends

```
inline friend constexpr friend bool operator== (std::nullptr_t,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (std::nullptr_t,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator< (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator> (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator<= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator>= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
friend std::ostream &operator<<(std::ostream &os, thread_id const &id)
```

```
friend void format_value(std::ostream &os, std::string_view spec, thread_id const &id)
```

```
struct thread_id_ref
```

Public Types

using **thread_repr** = detail::thread_data_reference_counting

Public Functions

thread_id_ref() noexcept = default

thread_id_ref(*thread_id_ref* const&) = default

thread_id_ref &**operator**=(*thread_id_ref* const&) = default

thread_id_ref(*thread_id_ref* &&rhs) noexcept = default

thread_id_ref &**operator**=(*thread_id_ref* &&rhs) noexcept = default

~thread_id_ref() = default

inline explicit **thread_id_ref**(*thread_id_repr* const &thrd) noexcept

inline explicit **thread_id_ref**(*thread_id_repr* &&thrd) noexcept

inline *thread_id_ref* &**operator**=(*thread_id_repr* const &rhs) noexcept

inline *thread_id_ref* &**operator**=(*thread_id_repr* &&rhs) noexcept

inline explicit **thread_id_ref**(*thread_repr* *thrd, *thread_id_addrf* const addrf =
thread_id_addrf::yes) noexcept

inline *thread_id_ref* &**operator**=(*thread_repr* *rhs) noexcept

inline **thread_id_ref**(*thread_id* const &noref)

inline **thread_id_ref**(*thread_id* &&noref) noexcept

inline *thread_id_ref* &**operator**=(*thread_id* const &noref)

inline *thread_id_ref* &**operator**=(*thread_id* &&noref) noexcept

inline explicit constexpr **operator bool**() const noexcept

inline constexpr *thread_id* **noref**() const noexcept

inline constexpr *thread_id_repr* &**get**() & noexcept

inline *thread_id_repr* &&**get**() && noexcept

inline constexpr *thread_id_repr* const &**get**() const & noexcept

inline void **reset**() noexcept

inline void **reset**(*thread_repr* *thrd, bool const add_ref = true) noexcept

inline constexpr *thread_repr* ***detach**() noexcept

Private Types

```
using thread_id_repr = hpx::intrusive_ptr<detail::thread_data_reference_counting>
```

Private Members

```
thread_id_repr thrd_
```

Friends

```
inline friend constexpr friend bool operator== (std::nullptr_t,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (std::nullptr_t,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id_ref const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id_ref const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator< (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator> (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator<= (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator>= (thread_id_ref const &lhs,  
thread_id_ref const &rhs) noexcept
```

```
friend std::ostream &operator<<(std::ostream &os, thread_id_ref const &id)
```

```
friend void format_value(std::ostream &os, std::string_view spec, thread_id_ref const &id)
```

```
namespace std
```

```
template<> thread_id >
```

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id const &v) const noexcept
```

```
template<> thread_id_ref >
```

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id_ref const &v) const noexcept
```

hpx/coroutines/thread_enums.hpp

Defined in header `hpx/coroutines/thread_enums.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace threads
```

Enums

```
enum class thread_schedule_state : std::int8_t
```

The *thread_schedule_state* enumerator encodes the current state of a *thread* instance

Values:

```
enumerator unknown
```

```
enumerator active
```

thread is currently active (running, has resources)

```
enumerator pending
```

thread is pending (ready to run, but no hardware resource available)

```
enumerator suspended
```

thread has been suspended (waiting for synchronization event, but still known and under control of the thread-manager)

```
enumerator depleted
```

thread has been depleted (deeply suspended, it is not known to the thread-manager)

```
enumerator terminated
```

thread has been stopped and may be garbage collected

enumerator **staged**

this is not a real thread state, but allows to reference staged task descriptions, which eventually will be converted into thread objects

enumerator **pending_do_not_schedule**

this is not a real thread state, but allows to create a thread in pending state without scheduling it (internal, do not use)

enumerator **pending_boost**

this is not a real thread state, but allows to suspend a thread in pending state without high priority rescheduling

enumerator **deleted**

thread has been stopped and was deleted

enum class **thread_priority** : *std::int8_t*

This enumeration lists all possible thread-priorities for HPX threads.

Values:

enumerator **unknown**

enumerator **default_**

Will assign the priority of the task to the default (normal) priority.

enumerator **low**

Task goes onto a special low priority queue and will not be executed until all high/normal priority tasks are done, even if they are added after the low priority task.

enumerator **normal**

Task will be executed when it is taken from the normal priority queue, this is usually a first in-first-out ordering of tasks (depending on scheduler choice). This is the default priority.

enumerator **high_recursive**

The task is a high priority task and any child tasks spawned by this task will be made high priority as well - unless they are specifically flagged as non default priority.

enumerator **boost**

Same as *thread_priority_high* except that the thread will fall back to *thread_priority_normal* if resumed after being suspended.

enumerator **high**

Task goes onto a special high priority queue and will be executed before normal/low priority tasks are taken (some schedulers modify the behavior slightly and the documentation for those should be consulted).

enumerator **bound**

Task goes onto a special high priority queue and will never be stolen by another thread after initial assignment. This should be used for thread placement tasks such as OpenMP type for loops.

enumerator **initially_bound**

Task initially goes onto a special high priority queue and will never be stolen by another thread after initial assignment. If the thread is rescheduled later, it will use normal priority.

enum class **thread_restart_state** : *std::int8_t*

The *thread_restart_state* enumerator encodes the reason why a thread is being restarted

Values:

enumerator **unknown**

enumerator **signaled**

The thread has been signaled.

enumerator **timeout**

The thread has been reactivated after a timeout.

enumerator **terminate**

The thread needs to be terminated.

enumerator **abort**

The thread needs to be aborted.

enum class **thread_stacksize** : *std::int8_t*

A *thread_stacksize* references any of the possible stack-sizes for HPX threads.

Values:

enumerator **unknown**

enumerator **small_**

use small stack size (the underscore is to work around 'small' being defined to char on Windows)

enumerator **medium**

use medium sized stack size

enumerator **large**

use large stack size

enumerator **huge**

use very large stack size

enumerator **nostack**

this thread does not suspend (does not need a stack)

enumerator **current**

use size of current thread's stack

enumerator **default_**

use default stack size

enumerator **minimal**

use minimally stack size

enumerator **maximal**

use maximally stack size

enum class **thread_schedule_hint_mode** : *std::int8_t*

The type of hint given when creating new tasks.

Values:

enumerator **none**

A hint that leaves the choice of scheduling entirely up to the scheduler.

enumerator **thread**

A hint that tells the scheduler to prefer scheduling a task on the local thread number associated with this hint. Local thread numbers are indexed from zero. It is up to the scheduler to decide how to interpret thread numbers that are larger than the number of threads available to the scheduler. Typically, thread numbers will wrap around when too large.

enumerator **numa**

A hint that tells the scheduler to prefer scheduling a task on the NUMA domain associated with this hint. NUMA domains are indexed from zero. It is up to the scheduler to decide how to interpret NUMA domain indices that are larger than the number of available NUMA domains to the scheduler. Typically, indices will wrap around when too large.

enum class **thread_placement_hint** : *std::int8_t*

The type of hint given to the scheduler related to thread placement

The type of hint given to the scheduler related running a thread as a child directly in the context of the parent thread

Values:

enumerator **none**

No hint is specified. The implementation is free to chose what placement methods to use.

enumerator **depth_first**

A hint that tells the scheduler to prefer spreading thread placement on a depth-first basis (i.e. consecutively scheduled threads are placed on the same core).

enumerator **breadth_first**

A hint that tells the scheduler to prefer spreading thread placement on a breadth-first basis (i.e. consecutively scheduled threads are placed on the neighboring cores).

enumerator **depth_first_reverse**

A hint that tells the scheduler to prefer spreading thread placement on a depth-first basis (i.e. consecutively scheduled threads are placed on the same core). Threads are being scheduled in reverse order.

enumerator **breadth_first_reverse**

A hint that tells the scheduler to prefer spreading thread placement on a breadth-first basis (i.e. consecutively scheduled threads are placed on the neighboring cores). Threads are being scheduled in reverse order.

enum class **thread_sharing_hint** : *std::int8_t*

The type of hint given to the scheduler related to whether it is ok to share the invoked function object between threads

Values:

enumerator **none**

No hint is specified. The implementation is free to chose what sharing methods to use.

enumerator **do_not_share_function**

A hint that tells the scheduler to avoid sharing the given function (object) between threads.

enumerator **do_not_combine_tasks**

A hint that tells the scheduler to avoid combining tasks on the same thread. This is important for tasks that may synchronize between each other, which could lead to deadlocks if those tasks are combined running by the same thread.

enum class **thread_execution_hint** : *std::int8_t*

Values:

enumerator **none**

No hint is specified. Always run the thread in its own execution environment.

enumerator **run_as_child**

Attempt to run the thread in the execution context of the parent thread.

Functions

`std::ostream &operator<<(std::ostream &os, thread_schedule_state t)`

`char const *get_thread_state_name(thread_schedule_state state) noexcept`

Returns the name of the given state.

Get the readable string representing the name of the given thread_state constant.

Parameters

state – this represents the thread state.

`std::ostream &operator<<(std::ostream &os, thread_priority t)`

`char const *get_thread_priority_name(thread_priority priority) noexcept`

Return the thread priority name.

Get the readable string representing the name of the given thread_priority constant.

Parameters

priority – this represents the thread priority.

`std::ostream &operator<<(std::ostream &os, thread_restart_state t)`

`char const *get_thread_state_ex_name(thread_restart_state state) noexcept`

Get the readable string representing the name of the given thread_restart_state constant.

`char const *get_thread_state_name(thread_state state) noexcept`

Get the readable string representing the name of the given thread_state constant.

`std::ostream &operator<<(std::ostream &os, thread_stacksize t)`

`char const *get_stack_size_enum_name(thread_stacksize size) noexcept`

Returns the stack size name.

Get the readable string representing the given stack size constant.

Parameters

size – this represents the stack size

`constexpr bool do_not_share_function(thread_sharing_hint hint) noexcept`

`constexpr bool do_not_combine_tasks(thread_sharing_hint hint) noexcept`

`constexpr thread_sharing_hint operator|(thread_sharing_hint lhs, thread_sharing_hint rhs) noexcept`

`constexpr bool run_as_child(thread_execution_hint hint) noexcept`

Variables

`constexpr thread_execution_hint default_runs_as_child_hint = thread_execution_hint::none`

Default value to use for runs-as-child mode (if *true*, then futures will attempt to execute associated threads directly if they have not started running).

struct **thread_schedule_hint**

#include <thread_enums.hpp> A hint given to a scheduler to guide where a task should be scheduled.

A scheduler is free to ignore the hint, or modify the hint to suit the resources available to the scheduler.

Public Functions

inline constexpr **thread_schedule_hint**() noexcept

Construct a default hint with mode `thread_schedule_hint_mode::none`.

inline explicit constexpr **thread_schedule_hint**(*std::int16_t* const thread_hint,
 thread_placement_hint placement =
 thread_placement_hint::none,
 thread_execution_hint runs_as_child =
 default_runs_as_child_hint,
 thread_sharing_hint sharing =
 thread_sharing_hint::none) noexcept

Construct a hint with mode `thread_schedule_hint_mode::thread` and the given hint as the local thread number.

inline constexpr **thread_schedule_hint**(*thread_schedule_hint_mode* const mode, *std::int16_t*
 const hint, *thread_placement_hint* placement =
 thread_placement_hint::none, *thread_execution_hint*
 runs_as_child = *default_runs_as_child_hint*,
 thread_sharing_hint sharing =
 thread_sharing_hint::none) noexcept

Construct a hint with the given mode and hint. The numerical hint is unused when the mode is `thread_schedule_hint_mode::none`.

inline explicit constexpr **thread_schedule_hint**(*thread_placement_hint* placement) noexcept

Construct a hint with the given placement hint.

inline explicit constexpr **thread_schedule_hint**(*thread_execution_hint* runs_as_child) noexcept

Construct a hint with the given execution hint.

inline explicit constexpr **thread_schedule_hint**(*thread_sharing_hint* sharing) noexcept

Construct a hint with the given sharing hint.

inline constexpr *thread_placement_hint* **placement_mode**() const noexcept

inline void **placement_mode**(*thread_placement_hint* bits) noexcept

inline constexpr *thread_sharing_hint* **sharing_mode**() const noexcept

inline void **sharing_mode**(*thread_sharing_hint* bits) noexcept

inline constexpr *thread_execution_hint* **runs_as_child_mode**() const noexcept

inline void **runs_as_child_mode**(*thread_execution_hint* bits) noexcept

inline void **schedule_hint**(*std::int16_t* core) noexcept

Public Members

`std::int16_t hint = -1`

The hint associated with the mode. The interpretation of this hint depends on the given mode.

`thread_schedule_hint_mode mode = thread_schedule_hint_mode::none`

The mode of the scheduling hint.

`std::uint8_t placement_mode_bits`

The mode of the desired thread placement.

`std::uint8_t sharing_mode_bits`

The mode of the desired sharing hint.

`std::uint8_t runs_as_child_mode_bits`

The thread will run as a child directly in the context of the current thread

datastructures

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::any_nonser, hpx::bad_any_cast, hpx::unique_any_nonser, hpx::any_cast,
hpx::make_any_nonser, hpx::make_unique_any_nonser

Defined in header `hpx/any.hpp`⁷¹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

class **basic_any**<void, void, void, std::true_type>

Public Functions

inline constexpr **basic_any**() noexcept

inline **basic_any**(*basic_any* const &x)

inline **basic_any**(*basic_any* &&x) noexcept

template<typename T>

inline explicit **basic_any**(T &&x, std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* =
nullptr)

template<typename T, typename ...Ts>

inline explicit **basic_any**(std::in_place_type_t<T>, Ts&&... ts)

template<typename T, typename U, typename ...Ts>

⁷¹⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/any.hpp

```

inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)

inline ~basic_any()

inline basic_any &operator=(basic_any const &x)

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs)

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()

```

Private Functions

```

inline basic_any &assign(basic_any const &x)

```

Private Members

```

detail::any::fxn_ptr_table<void, void, void, std::true_type> *table

```

```

void *object

```

Private Static Functions

```

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)

template<typename Char>
class basic_any<void, void, Char, std::true_type>

```

Public Functions

```
inline constexpr basic_any() noexcept

inline basic_any(basic_any const &x)

inline basic_any(basic_any &&x) noexcept

template<typename T>
inline explicit basic_any(T &&x, std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* =
    nullptr)

template<typename T, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)

template<typename T, typename U, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)

inline ~basic_any()

inline basic_any &operator=(basic_any const &x)

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs) noexcept

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()
```

Private Functions

```
inline basic_any &assign(basic_any const &x)
```

Private Members

```
detail::any::fxn_ptr_table<void, void, Char, std::true_type> *table
```

```
void *object
```


Private Static Functions

```
template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)

template<>
class basic_any<void, void, void, std::false_type>
```

Public Functions

```
inline constexpr basic_any() noexcept

inline basic_any(basic_any &&x) noexcept

template<typename T>
inline explicit basic_any(T &&x, std::enable_if_t<std::is_move_constructible_v<std::decay_t<T>>>* =
    nullptr)

template<typename T, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)

template<typename T, typename U, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)

basic_any(basic_any const &x) = delete

basic_any &operator=(basic_any const &x) = delete

inline ~basic_any()

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs)

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()
```

Private Members

detail::any::fxn_ptr_table<void, void, void, std::false_type> ***table**

void ***object**

Private Static Functions

template<typename **T**, typename ...**Ts**>
static inline void **new_object**(void *&object, std::true_type, Ts&&... ts)

template<typename **T**, typename ...**Ts**>
static inline void **new_object**(void *&object, std::false_type, Ts&&... ts)

template<typename **Char**>

class **basic_any**<void, void, *Char*, std::false_type>

Public Functions

inline constexpr **basic_any**() noexcept

inline **basic_any**(*basic_any* &&x) noexcept

template<typename **T**>
inline explicit **basic_any**(*T* &&x, std::enable_if_t<std::is_move_constructible_v<std::decay_t<*T*>>>* =
nullptr)

template<typename **T**, typename ...**Ts**>
inline explicit **basic_any**(std::in_place_type_t<*T*>, Ts&&... ts)

template<typename **T**, typename **U**, typename ...**Ts**>
inline explicit **basic_any**(std::in_place_type_t<*T*>, std::initializer_list<*U*> il, Ts&&... ts)

basic_any(*basic_any* const &x) = delete

basic_any &**operator**=(*basic_any* const &x) = delete

inline ~**basic_any**()

inline *basic_any* &**operator**=(*basic_any* &&rhs) noexcept

template<typename **T**>
inline *basic_any* &**operator**=(*T* &&rhs) noexcept

inline *basic_any* &**swap**(*basic_any* &x) noexcept

inline std::type_info const &**type**() const

template<typename **T**>
inline *T* const &**cast**() const

inline bool **has_value**() const noexcept

inline void **reset**()

Private Members

detail::any::fxn_ptr_table<void, void, *Char*, *std::false_type*> ***table**

void ***object**

Private Static Functions

template<typename **T**, typename ...**Ts**>
static inline void **new_object**(void *&object, *std::true_type*, *Ts*&&... ts)

template<typename **T**, typename ...**Ts**>
static inline void **new_object**(void *&object, *std::false_type*, *Ts*&&... ts)

namespace **hpx**

Top level HPX namespace.

Typedefs

using **any_nonser** = *util::basic_any*<void, void, void, *std::true_type*>

using **unique_any_nonser** = *util::basic_any*<void, void, void, *std::false_type*>

Functions

template<typename **T**, typename ...**Ts**>
util::basic_any<void, void, void, *std::true_type*> **make_any_nonser**(*Ts*&&... ts)

template<typename **T**, typename **U**, typename ...**Ts**>
util::basic_any<void, void, void, *std::true_type*> **make_any_nonser**(*std::initializer_list*<**U**> il, *Ts*&&... ts)

template<typename **T**, typename ...**Ts**>
util::basic_any<void, void, void, *std::false_type*> **make_unique_any_nonser**(*Ts*&&... ts)

template<typename **T**, typename **U**, typename ...**Ts**>
util::basic_any<void, void, void, *std::false_type*> **make_unique_any_nonser**(*std::initializer_list*<**U**> il,
Ts&&... ts)

template<typename **T**>
util::basic_any<void, void, void, *std::true_type*> **make_any_nonser**(**T** &&t)

template<typename **T**>
util::basic_any<void, void, void, *std::false_type*> **make_unique_any_nonser**(**T** &&t)

template<typename **T**, typename **IArch**, typename **OArch**, typename **Char**, typename **Copyable**>
T ***any_cast**(*util::basic_any*<**IArch**, **OArch**, **Char**, **Copyable**> *operand) noexcept

Performs type-safe access to the contained object.

Parameters

operand – target any object

Returns

If operand is not a null pointer, and the *typeid* of the requested *T* matches that of the contents of *operand*, a pointer to the value contained by *operand*, otherwise a null pointer.

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T const *any_cast(util::basic_any<IArch, OArch, Char, Copyable> const *operand) noexcept
```

Performs type-safe access to the contained object.

Parameters

operand – target any object

Returns

If operand is not a null pointer, and the *typeid* of the requested *T* matches that of the contents of *operand*, a pointer to the value contained by *operand*, otherwise a null pointer.

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T any_cast(util::basic_any<IArch, OArch, Char, Copyable> &operand)
```

Performs type-safe access to the contained object. Let *U* be `std::remove_cv_t<std::remove_reference_t<T>>`. The program is ill-formed if `std::is_constructible_v<T, U&>` is false.

Parameters

operand – target any object

Returns

`static_cast<T>(*std::any_cast<U>(&operand))`

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T const &any_cast(util::basic_any<IArch, OArch, Char, Copyable> const &operand)
```

Performs type-safe access to the contained object. Let *U* be `std::remove_cv_t<std::remove_reference_t<T>>`. The program is ill-formed if `std::is_constructible_v<T, const U&>` is false.

Parameters

operand – target any object

Returns

`static_cast<T>(*std::any_cast<U>(&operand))`

```
struct bad_any_cast : public bad_cast
```

`#include <any.hpp>` Defines a type of object to be thrown by the value-returning forms of `hpx::any_cast` on failure.

Public Functions

```
inline bad_any_cast(std::type_info const &src, std::type_info const &dest)
```

Constructs a new *bad_any_cast* object with an implementation-defined null-terminated byte string which is accessible through *what()*.

```
inline char const *what() const noexcept override
```

Returns the explanatory string.

Note: Implementations are allowed but not required to override *what()*.

Returns

Pointer to a null-terminated string with explanatory information. The string is suitable for conversion and display as a `std::wstring`. The pointer is guaranteed to be valid at least until the exception object from which it is obtained is destroyed, or until a non-const member function (e.g. copy assignment operator) on the exception object is called.

Public Members

char const ***from**

char const ***to**

namespace **util**

Typedefs

using **streamable_any_nonser** = *basic_any*<void, void, char, *std::true_type*>

using **streamable_wany_nonser** = *basic_any*<void, void, wchar_t, *std::true_type*>

using **streamable_unique_any_nonser** = *basic_any*<void, void, char, *std::false_type*>

using **streamable_unique_wany_nonser** = *basic_any*<void, void, wchar_t, *std::false_type*>

Functions

```
template<typename IArch, typename OArch, typename Char, typename Copyable, typename Enable =
std::enable_if_t<!std::is_void_v<Char>>>
std::basic_istream<Char> &operator>>(std::basic_istream<Char> &i, basic_any<IArch, OArch,
Char, Copyable> &obj)
```

```
template<typename IArch, typename OArch, typename Char, typename Copyable, typename Enable =
std::enable_if_t<!std::is_void_v<Char>>>
std::basic_ostream<Char> &operator<<(std::basic_ostream<Char> &o, basic_any<IArch, OArch,
Char, Copyable> const &obj)
```

```
template<typename IArch, typename OArch, typename Char, typename Copyable>
void swap(basic_any<IArch, OArch, Char, Copyable> &lhs, basic_any<IArch, OArch, Char, Copyable>
&rhs) noexcept
```

```
template<typename T, typename Char, typename ...Ts>
basic_any<void, void, Char, std::true_type> make_streamable_any_nonser(Ts&&... ts)
```

```
template<typename T, typename Char, typename U, typename ...Ts>
basic_any<void, void, Char, std::true_type> make_streamable_any_nonser(std::initializer_list<U>
il, Ts&&... ts)
```

```
template<typename T, typename Char, typename ...Ts>
```

```
basic_any<void, void, Char, std::false_type> make_streamable_unique_any_nonser(Ts&&... ts)

template<typename T, typename Char, typename U, typename ...Ts>
basic_any<void, void, Char, std::false_type> make_streamable_unique_any_nonser(std::initializer_list<U>
                                                                              il, Ts&&... ts)

template<typename T, typename Char>
basic_any<void, void, Char, std::true_type> make_streamable_any_nonser(T &&t)

template<typename T, typename Char>
basic_any<void, void, Char, std::false_type> make_streamable_unique_any_nonser(T &&t)

template<typename IArch, typename OArch, typename Char = char, typename Copyable =
std::true_type>
class basic_any

template<typename Char> false_type >
```

Public Functions

```
inline constexpr basic_any() noexcept

inline basic_any(basic_any &&x) noexcept

template<typename T>
inline explicit basic_any(T &&x,
                        std::enable_if_t<std::is_move_constructible_v<std::decay_t<T>>>* =
                        nullptr)

template<typename T, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)

template<typename T, typename U, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)

basic_any(basic_any const &x) = delete

basic_any &operator=(basic_any const &x) = delete

inline ~basic_any()

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs) noexcept

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()
```

Private Members

```
detail::any::fxn_ptr_table<void, void, Char, std::false_type> *table
```

```
void *object
```

Private Static Functions

```
template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)
```

```
template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)
```

```
template<typename Char> true_type >
```

Public Functions

```
inline constexpr basic_any() noexcept
```

```
inline basic_any(basic_any const &x)
```

```
inline basic_any(basic_any &&x) noexcept
```

```
template<typename T>
inline explicit basic_any(T &&x,
    std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* =
    nullptr)
```

```
template<typename T, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)
```

```
inline ~basic_any()
```

```
inline basic_any &operator=(basic_any const &x)
```

```
inline basic_any &operator=(basic_any &&rhs) noexcept
```

```
template<typename T>
inline basic_any &operator=(T &&rhs) noexcept
```

```
inline basic_any &swap(basic_any &x) noexcept
```

```
inline std::type_info const &type() const
```

```
template<typename T>
inline T const &cast() const
```

```
inline bool has_value() const noexcept
```

```
inline void reset()
```

Private Functions

```
inline basic_any &assign(basic_any const &x)
```

Private Members

```
detail::any::fxn_ptr_table<void, void, Char, std::true_type> *table
```

```
void *object
```

Private Static Functions

```
template<typename T, typename ...Ts>  
static inline void new_object(void *&object, std::true_type, Ts&&... ts)
```

```
template<typename T, typename ...Ts>  
static inline void new_object(void *&object, std::false_type, Ts&&... ts)
```

```
template<> false_type >
```

Public Functions

```
inline constexpr basic_any() noexcept
```

```
inline basic_any(basic_any &&x) noexcept
```

```
template<typename T>  
inline explicit basic_any(T &&x,  
                           std::enable_if_t<std::is_move_constructible_v<std::decay_t<T>>>* =  
                           nullptr)
```

```
template<typename T, typename ...Ts>  
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>  
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)
```

```
basic_any(basic_any const &x) = delete
```

```
basic_any &operator=(basic_any const &x) = delete
```

```
inline ~basic_any()
```

```
inline basic_any &operator=(basic_any &&rhs) noexcept
```

```
template<typename T>  
inline basic_any &operator=(T &&rhs)
```

```
inline basic_any &swap(basic_any &x) noexcept
```

```
inline std::type_info const &type() const
```

```
template<typename T>
```



```

inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()

```

Private Members

```

detail::any::fxn_ptr_table<void, void, void, std::false_type> *table

void *object

```

Private Static Functions

```

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)

```

```

template<> true_type >

```

Public Functions

```

inline constexpr basic_any() noexcept

inline basic_any(basic_any const &x)

inline basic_any(basic_any &&x) noexcept

template<typename T>
inline explicit basic_any(T &&x,
                        std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* =
                        nullptr)

template<typename T, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)

template<typename T, typename U, typename ...Ts>
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)

inline ~basic_any()

inline basic_any &operator=(basic_any const &x)

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs)

inline basic_any &swap(basic_any &x) noexcept

```

```
inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()
```

Private Functions

```
inline basic_any &assign(basic_any const &x)
```

Private Members

```
detail::any::fxn_ptr_table<void, void, void, std::true_type> table
```

```
void object
```

Private Static Functions

```
template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)
```

hpx::ignore, **hpx::tuple**, **hpx::tuple_size**, **hpx::tuple_element**, **hpx::make_tuple**, **hpx::tie**,
hpx::forward_as_tuple, **hpx::tuple_cat**, **hpx::get**

Defined in header [hpx/tuple.hpp](http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/tuple.hpp)⁷¹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

```
template<typename ...Ts>
constexpr tuple<util::decay_unwrap_t<Ts>...> make_tuple(Ts&&... ts)
```

Provides compile-time indexed access to the types of the elements of the tuple.

```
template<typename ...Ts>
```

⁷¹⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/tuple.hpp

```
constexpr tuple<Ts&&...> forward_as_tuple(Ts&&... ts)
```

Constructs a tuple of references to the arguments in args suitable for forwarding as an argument to a function. The tuple has rvalue reference data members when rvalues are used as arguments, and otherwise has lvalue reference data members.

Parameters

ts – zero or more arguments to construct the tuple from

Returns

hpx::tuple object created as if by

```
hpx::tuple<Ts&&...>(HPX_FORWARD(Ts, ts) ...)
```

```
template<typename ...Ts>
```

```
constexpr tuple<Ts&...> tie(Ts&... ts)
```

Creates a tuple of lvalue references to its arguments or instances of *hpx::ignore*.

Parameters

ts – zero or more lvalue arguments to construct the tuple from.

Returns

hpx::tuple object containing lvalue references.

```
template<typename ...Tuples>
```

```
constexpr auto tuple_cat(Tuples&&... tuples)
```

Constructs a tuple that is a concatenation of all tuples in **tuples**. The behavior is undefined if any type in `std::decay_t<Tuples>...` is not a specialization of *hpx::tuple*. However, an implementation may choose to support types (such as `std::array` and `std::pair`) that follow the tuple-like protocol.

Parameters

tuples – - zero or more tuples to concatenate

Returns

hpx::tuple object composed of all elements of all argument tuples constructed from *hpx::get<Is>(HPX_FORWARD(UTuple,t))* for each individual element.

```
template<std::size_t I>
```

```
util::at_index<I, Ts...>::type &get() noexcept
```

Extracts the *I*th element from the tuple. *I* must be an integer value in `[0, sizeof...(Ts))`.

```
template<std::size_t I>
```

```
util::at_index<I, Ts...>::type const &get() const noexcept
```

Extracts the *I*th element from the tuple. *I* must be an integer value in `[0, sizeof...(Ts))`.

Variables

```
constexpr hpx::detail::ignore_type ignore = {}
```

An object of unspecified type such that any value can be assigned to it with no effect. Intended for use with *hpx::tie* when unpacking a *hpx::tuple*, as a placeholder for the arguments that are not used. While the behavior of *hpx::ignore* outside of *hpx::tie* is not formally specified, some code guides recommend using *hpx::ignore* to avoid warnings from unused return values of `[[nodiscard]]` functions.

```
template<typename ...Ts>
```

```
class tuple
```

#include <tuple.hpp> Class template *hpx::tuple* is a fixed-size collection of heterogeneous values. It is

a generalization of `hpx::pair`. If `std::is_trivially_destructible<Ti>::value` is true for every `Ti` in `Ts`, the destructor of tuple is trivial.

Param Ts...

the types of the elements that the tuple stores.

```
template<std::size_t I, typename T, typename Enable = void>
```

```
struct tuple_element
```

#include <tuple.hpp> Provides compile-time indexed access to the types of the elements of a tuple-like type.

The primary template is not defined. An explicit (full) or partial specialization is required to make a type tuple-like.

```
template<typename T>
```

```
struct tuple_size
```

#include <tuple.hpp> Provides access to the number of elements in a tuple-like type as a compile-time constant expression.

The primary template is not defined. An explicit (full) or partial specialization is required to make a type tuple-like.

hpx::any, hpx::make_any

Defined in header `hpx/any.hpp`⁷²⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename IArch, typename OArch, typename Char>
```

```
class basic_any<IArch, OArch, Char, std::true_type>
```

Public Functions

```
inline constexpr basic_any() noexcept
```

```
inline basic_any(basic_any const &x)
```

```
inline basic_any(basic_any &&x) noexcept
```

```
template<typename T>
```

```
inline basic_any(T &&x, std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* = nullptr)
```

```
template<typename T, typename ...Ts>
```

```
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>
```

```
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)
```

```
inline ~basic_any()
```

```
inline basic_any &operator=(basic_any const &x)
```

⁷²⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/any.hpp

```

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs)

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()

inline bool equal_to(basic_any const &rhs) const noexcept

```

Private Functions

```

inline basic_any &assign(basic_any const &x)

inline void load(IArch &ar, unsigned const version)

inline void save(OArch &ar, unsigned const version) const

```

Private Members

```

detail::any::fxn_ptr_table<IArch, OArch, Char, std::true_type> *table

void *object

```

Private Static Functions

```

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)

```

Friends

```
friend class hpx::serialization::access
```

namespace **hpx**

Top level HPX namespace.

Typedefs

```
using any = util::basic_any<serialization::input_archive, serialization::output_archive, char, std::true_type>
```

Functions

```
template<typename T, typename Char>
```

```
util::basic_any<serialization::input_archive, serialization::output_archive, Char> make_any(T && t)
```

Constructs an any object containing an object of type *T*, passing the provided arguments to *T*'s constructor.
Equivalent to:

```
return std::any(std::in_place_type<T>, std::forward<Args>(args)...);
```

namespace **util**

Typedefs

```
using wany = basic_any<serialization::input_archive, serialization::output_archive, wchar_t,  
std::true_type>
```

Functions

```
template<typename T, typename Char, typename ...Ts>
```

```
basic_any<serialization::input_archive, serialization::output_archive, Char> make_any(Ts&&... ts)
```

```
template<typename T, typename Char, typename U, typename ...Ts>
```

```
basic_any<serialization::input_archive, serialization::output_archive, Char> make_any(std::initializer_list<U>  
il, Ts&&... ts)
```

```
template<typename IArch, typename OArch, typename Char> true_type >
```

Public Functions

```
inline constexpr basic_any() noexcept
```

```
inline basic_any(basic_any const &x)
```

```
inline basic_any(basic_any &&x) noexcept
```

```
template<typename T>
```

```
inline basic_any(T &&x, std::enable_if_t<std::is_copy_constructible_v<std::decay_t<T>>>* =  
nullptr)
```

```
template<typename T, typename ...Ts>
```

```
inline explicit basic_any(std::in_place_type_t<T>, Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>
```

```
inline explicit basic_any(std::in_place_type_t<T>, std::initializer_list<U> il, Ts&&... ts)
```

```

inline ~basic_any()

inline basic_any &operator=(basic_any const &x)

inline basic_any &operator=(basic_any &&rhs) noexcept

template<typename T>
inline basic_any &operator=(T &&rhs)

inline basic_any &swap(basic_any &x) noexcept

inline std::type_info const &type() const

template<typename T>
inline T const &cast() const

inline bool has_value() const noexcept

inline void reset()

inline bool equal_to(basic_any const &rhs) const noexcept

```

Private Functions

```

inline basic_any &assign(basic_any const &x)

inline void load(IArch &ar, unsigned const version)

inline void save(OArch &ar, unsigned const version) const

```

Private Members

```

detail::any::fxn_ptr_table<IArch, OArch, Char, std::true_type> *table

void *object

```

Private Static Functions

```

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::true_type, Ts&&... ts)

template<typename T, typename ...Ts>
static inline void new_object(void *&object, std::false_type, Ts&&... ts)

```

Friends

friend class hpx::serialization::access

struct **hash_any**

Public Functions

```
template<typename Char>
std::size_t operator()(basic_any<serialization::input_archive, serialization::output_archive,
                        Char, std::true_type> const &elem) const
```

debugging

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/debugging/print.hpp

Defined in header hpx/debugging/print.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

errors

See *Public API* for a list of names and headers that are part of the public *HPX* API.

HPX_THROW_EXCEPTION, HPX_THROW_BAD_ALLOC, HPX_THROWS_IF

Defined in header [hpx/exception.hpp](#)⁷²¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

hpx/errors/macros.hpp

Defined in header hpx/errors/macros.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

⁷²¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/exception.hpp

Defines

HPX_THROW_EXCEPTION(errcode, f, ...)

Throw a *hpx::exception* initialized from the given parameters.

The macro *HPX_THROW_EXCEPTION* can be used to throw a *hpx::exception*. The purpose of this macro is to prepend the source file name and line number of the position where the exception is thrown to the error message. Moreover, this associates additional diagnostic information with the exception, such as file name and line number, locality id and thread id, and stack backtrace from the point where the exception was thrown.

The parameter *errcode* holds the *hpx::error* code the new exception should encapsulate. The parameter *f* is expected to hold the name of the function exception is thrown from and the parameter *msg* holds the error message the new exception should encapsulate.

```
void raise_exception()
{
    // Throw a hpx::exception initialized from the given parameters.
    // Additionally associate with this exception some detailed
    // diagnostic information about the throw-site.
    HPX_THROW_EXCEPTION(hpx::error::no_success, "raise_exception",
        "simulated error");
}
```

Example:

HPX_THROW_BAD_ALLOC(f)

Throw a *hpx::bad_alloc_exception* initialized from the given parameters.

The macro *HPX_THROW_BAD_ALLOC* can be used to throw a *hpx::exception*. The purpose of this macro is to prepend the source file name and line number of the position where the exception is thrown to the error message. Moreover, this associates additional diagnostic information with the exception, such as file name and line number, locality id and thread id, and stack backtrace from the point where the exception was thrown.

The parameter *errcode* holds the *hpx::error* code the new exception should encapsulate. The parameter *f* is expected to hold the name of the function exception is thrown from and the parameter *msg* holds the error message the new exception should encapsulate.

```
void raise_exception()
{
    // Throw a hpx::exception initialized from the given parameters.
    // Additionally associate with this exception some detailed
    // diagnostic information about the throw-site.
    HPX_THROW_BAD_ALLOC("raise_exception", "simulated error");
}
```

Example:

HPX_THROWS_IF(ec, errcode, f, ...)

Either throw a *hpx::exception* or initialize *hpx::error_code* from the given parameters.

The macro *HPX_THROWS_IF* can be used to either throw a `hpx::exception` or to initialize a `hpx::error_code` from the given parameters. If `&ec == &hpx::throws`, the semantics of this macro are equivalent to *HPX_THROW_EXCEPTION*. If `&ec != &hpx::throws`, the `hpx::error_code` instance `ec` is initialized instead.

The parameter `errcode` holds the `hpx::error_code` from which the new exception should be initialized. The parameter `f` is expected to hold the name of the function exception is thrown from and the parameter `msg` holds the error message the new exception should encapsulate.

HPX_THROWS_BAD_ALLOC_IF(`ec, f`)

Either throw a *hpx::bad_alloc_exception* or `hpx::error_code` to *out_of_memory*.

The macro *HPX_THROWS_BAD_ALLOC_IF* can be used to either throw a `hpx::bad_alloc_exception` or to initialize a `hpx::error_code` to *hpx::error::out_of_memory*. If `&ec == &hpx::throws`, the semantics of this macro are equivalent to *HPX_THROW_BAD_ALLOC*. If `&ec != &hpx::throws`, the `hpx::error_code` instance `ec` is initialized instead.

HPX_DEFINE_ERROR_INFO(`NAME, TYPE`)

hpx/errors/error.hpp

Defined in header `hpx/errors/error.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_ERROR_UNSCOPED_ENUM_DEPRECATION_MSG

namespace **hpx**

Enums

enum class **error** : *std::int16_t*

Possible error conditions.

This enumeration lists all possible error conditions which can be reported from any of the API functions.

Values:

enumerator **success**

The operation was successful.

enumerator **no_success**

The operation did failed, but not in an unexpected manner.

enumerator **not_implemented**

The operation is not implemented.

enumerator **out_of_memory**

The operation caused an out of memory condition.

enumerator **bad_action_code**

enumerator **bad_component_type**

The specified component type is not known or otherwise invalid.

enumerator **network_error**

A generic network error occurred.

enumerator **version_too_new**

The version of the network representation for this object is too new.

enumerator **version_too_old**

The version of the network representation for this object is too old.

enumerator **version_unknown**

The version of the network representation for this object is unknown.

enumerator **unknown_component_address**

enumerator **duplicate_component_address**

The given global id has already been registered.

enumerator **invalid_status**

The operation was executed in an invalid status.

enumerator **bad_parameter**

One of the supplied parameters is invalid.

enumerator **internal_server_error**

enumerator **service_unavailable**

enumerator **bad_request**

enumerator **repeated_request**

enumerator **lock_error**

enumerator **duplicate_console**

There is more than one console locality.

enumerator **no_registered_console**

There is no registered console locality available.

enumerator **startup_timed_out**

enumerator **uninitialized_value**

enumerator **bad_response_type**

enumerator **deadlock**

enumerator **assertion_failure**

enumerator **null_thread_id**

Attempt to invoke an API function from a non-HPX thread.

enumerator **invalid_data**

enumerator **yield_aborted**

The yield operation was aborted.

enumerator **dynamic_link_failure**

enumerator **commandline_option_error**

One of the options given on the command line is erroneous.

enumerator **serialization_error**

There was an error during serialization of this object.

enumerator **unhandled_exception**

An unhandled exception has been caught.

enumerator **kernel_error**

The OS kernel reported an error.

enumerator **broken_task**

The task associated with this future object is not available anymore.

enumerator **task_moved**

The task associated with this future object has been moved.

enumerator **task_already_started**

The task associated with this future object has already been started.

enumerator **future_already_retrieved**

The future object has already been retrieved.

enumerator **promise_already_satisfied**

The value for this future object has already been set.

enumerator **future_does_not_support_cancellation**

The future object does not support cancellation.

enumerator **future_can_not_be_cancelled**

The future can't be canceled at this time.

enumerator **no_state**

The future object has no valid shared state.

enumerator **broken_promise**

The promise has been deleted.

enumerator **thread_resource_error**

enumerator **future_cancelled**

enumerator **thread_cancelled**

enumerator **thread_not_interruptable**

enumerator **duplicate_component_id**

The component type has already been registered.

enumerator **unknown_error**

An unknown error occurred.

enumerator **bad_plugin_type**

The specified plugin type is not known or otherwise invalid.

enumerator **filesystem_error**

The specified file does not exist or other filesystem related error.

enumerator **bad_function_call**

equivalent of `std::bad_function_call`

enumerator **task_canceled_exception**

`parallel::task_canceled_exception`

enumerator **task_block_not_active**

`task_region` is not active

enumerator **out_of_range**

Equivalent to `std::out_of_range`.

enumerator **length_error**

Equivalent to `std::length_error`.

enumerator **migration_needs_retry**

migration failed because of global race, retry

Functions

constexpr bool **operator==**(int lhs, *error* rhs) noexcept

constexpr bool **operator==**(*error* lhs, int rhs) noexcept

constexpr bool **operator!=**(int lhs, *error* rhs) noexcept

constexpr bool **operator!=**(*error* lhs, int rhs) noexcept

constexpr bool **operator<**(int lhs, *error* rhs) noexcept

constexpr bool **operator>=**(int lhs, *error* rhs) noexcept

constexpr int **operator&**(*error* lhs, *error* rhs) noexcept

constexpr int **operator&**(int lhs, *error* rhs) noexcept

constexpr int **operator|**=(int &lhs, *error* rhs) noexcept

char const ***get_error_name**(*error* e) noexcept

Variables

constexpr *error* **success** = *error::success*

constexpr *error* **no_success** = *error::no_success*

constexpr *error* **not_implemented** = *error::not_implemented*

constexpr *error* **out_of_memory** = *error::out_of_memory*

constexpr *error* **bad_action_code** = *error::bad_action_code*

constexpr *error* **bad_component_type** = *error::bad_component_type*

constexpr *error* **network_error** = *error::network_error*

```
constexpr error version_too_new = error::version_too_new

constexpr error version_too_old = error::version_too_old

constexpr error version_unknown = error::version_unknown

constexpr error unknown_component_address = error::unknown_component_address

constexpr error duplicate_component_address = error::duplicate_component_address

constexpr error invalid_status = error::invalid_status

constexpr error bad_parameter = error::bad_parameter

constexpr error internal_server_error = error::internal_server_error

constexpr error service_unavailable = error::service_unavailable

constexpr error bad_request = error::bad_request

constexpr error repeated_request = error::repeated_request

constexpr error lock_error = error::lock_error

constexpr error duplicate_console = error::duplicate_console

constexpr error no_registered_console = error::no_registered_console

constexpr error startup_timed_out = error::startup_timed_out

constexpr error uninitialized_value = error::uninitialized_value

constexpr error bad_response_type = error::bad_response_type

constexpr error deadlock = error::deadlock

constexpr error assertion_failure = error::assertion_failure

constexpr error null_thread_id = error::null_thread_id

constexpr error invalid_data = error::invalid_data
```

```
constexpr error yield_aborted = error::yield_aborted

constexpr error dynamic_link_failure = error::dynamic_link_failure

constexpr error commandline_option_error = error::commandline_option_error

constexpr error serialization_error = error::serialization_error

constexpr error unhandled_exception = error::unhandled_exception

constexpr error kernel_error = error::kernel_error

constexpr error broken_task = error::broken_task

constexpr error task_moved = error::task_moved

constexpr error task_already_started = error::task_already_started

constexpr error future_already_retrieved = error::future_already_retrieved

constexpr error promise_already_satisfied = error::promise_already_satisfied

constexpr error future_does_not_support_cancellation =
error::future_does_not_support_cancellation

constexpr error future_can_not_be_cancelled = error::future_can_not_be_cancelled

constexpr error no_state = error::no_state

constexpr error broken_promise = error::broken_promise

constexpr error thread_resource_error = error::thread_resource_error

constexpr error future_cancelled = error::future_cancelled

constexpr error thread_cancelled = error::thread_cancelled

constexpr error thread_not_interruptable = error::thread_not_interruptable

constexpr error duplicate_component_id = error::duplicate_component_id

constexpr error unknown_error = error::unknown_error
```



```
constexpr error bad_plugin_type = error::bad_plugin_type

constexpr error filesystem_error = error::filesystem_error

constexpr error bad_function_call = error::bad_function_call

constexpr error task_canceled_exception = error::task_canceled_exception

constexpr error task_block_not_active = error::task_block_not_active

constexpr error out_of_range = error::out_of_range

constexpr error length_error = error::length_error

constexpr error migration_needs_retry = error::migration_needs_retry
```

hpx/errors/exception_fwd.hpp

Defined in header `hpx/errors/exception_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Enums

```
enum class throwmode : std::uint8_t
    Encode error category for new error_code.
    Values:

    enumerator plain

    enumerator rethrow

    enumerator lightweight
```

Functions

constexpr bool **operator&**(*throwmode* lhs, *throwmode* rhs) noexcept

Variables

error_code **throws**

Predefined *error_code* object used as “throw on error” tag.

The predefined *hpx::error_code* object *hpx::throws* is supplied for use as a “throw on error” tag.

Functions that specify an argument in the form ‘*error_code*& ec=throws’ (with appropriate namespace qualifiers), have the following error handling semantics:

If &ec != &throws and an error occurred: ec.value() returns the implementation specific error number for the particular error that occurred and ec.category() returns the error_category for ec.value().

If &ec != &throws and an error did not occur, ec.clear().

If an error occurs and &ec == &throws, the function throws an exception of type *hpx::exception* or of a type derived from it. The exception’s *get_errorcode()* member function returns a reference to a *hpx::error_code* object with the behavior as specified above.

hpx/errors/exception_list.hpp

Defined in header *hpx/errors/exception_list.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

class **exception_list** : public *hpx::exception*

#include <exception_list.hpp> The class *exception_list* is a container of *exception_ptr* objects parallel algorithms may use to communicate uncaught exceptions encountered during parallel execution to the caller of the algorithm

The type *exception_list::const_iterator* fulfills the requirements of a forward iterator.

Public Types

using **iterator** = *exception_list_type::const_iterator*
bidirectional iterator

Public Functions

inline `std::size_t size()` const noexcept

The number of `exception_ptr` objects contained within the *exception_list*.

Note: Complexity: Constant time.

inline `exception_list_type::const_iterator begin()` const noexcept

An iterator referring to the first `exception_ptr` object contained within the *exception_list*.

inline `exception_list_type::const_iterator end()` const noexcept

An iterator which is the past-the-end value for the *exception_list*.

hpx::exception

Defined in header `hpx/exception.hpp`⁷²².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Typedefs

using **custom_exception_info_handler_type** = `std::function<hpx::exception_info(std::string const&, std::string const&, long, std::string const&)>`

using **pre_exception_handler_type** = `std::function<void()>`

Functions

void **set_custom_exception_info_handler**(*custom_exception_info_handler_type* f)

void **set_pre_exception_handler**(*pre_exception_handler_type* f)

`std::string` **get_error_what**(*exception_info* const &xi)

Return the error message of the thrown exception.

The function `hpx::get_error_what` can be used to extract the diagnostic information element representing the error message as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`,
`hpx::get_error()`, `hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

⁷²² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/exception.hpp

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The error message stored in the exception. If the exception instance does not hold this information, the function will return an empty string.

error **get_error**(*hpx::exception* const &*e*)

Return the error code value of the exception thrown.

The function *hpx::get_error* can be used to extract the diagnostic information element representing the error value code as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

e – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception*, *hpx::error_code*, or *std::exception_ptr*.

Throws

nothing –

Returns

The error value code of the locality where the exception was thrown. If the exception instance does not hold this information, the function will return *hpx::naming::invalid_locality_id*.

error **get_error**(*hpx::error_code* const &*e*)

std::string **get_error_function_name**(*hpx::exception_info* const &*xi*)

Return the function name from which the exception was thrown.

The function *hpx::get_error_function_name* can be used to extract the diagnostic information element representing the name of the function as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_file_name(), *hpx::get_error_line_number()*, *hpx::get_error_os_thread()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The name of the function from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::string **get_error_file_name**(*hpx::exception_info* const &xi)

Return the (source code) file name of the function from which the exception was thrown.

The function *hpx::get_error_file_name* can be used to extract the diagnostic information element representing the name of the source file as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_line_number()*, *hpx::get_error_os_thread()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The name of the source file of the function from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

long **get_error_line_number**(*hpx::exception_info* const &xi)

Return the line number in the (source code) file of the function from which the exception was thrown.

The function *hpx::get_error_line_number* can be used to extract the diagnostic information element representing the line number as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_os_thread()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

nothing –

Returns

The line number of the place where the exception was thrown. If the exception instance does not hold this information, the function will return -1.

```
class bad_alloc_exception : public hpx::exception, public bad_alloc
```

Public Functions**bad_alloc_exception()**

Construct a *hpx::bad_alloc_exception*.

error_code **get_error_code**(*throwmode mode = throwmode::plain*) const noexcept

The function *get_error_code()* returns a *hpx::error_code* which represents the same error condition as this *hpx::exception* instance.

Parameters

mode – The parameter *mode* specifies whether the returned *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *throwmode::plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

Public Static Functions

```
static inline constexpr error get_error() noexcept
```

The function *get_error()* returns *hpx::error::out_of_memory*

Throws

nothing –

```
class exception : public system_error
```

#include <exception.hpp> A *hpx::exception* is the main exception type used by HPX to report errors.

The *hpx::exception* type is the main exception type used by HPX to report errors. Any exceptions thrown by functions in the HPX library are either of this type or of a type derived from it. This implies that it is always safe to use this type only in catch statements guarding HPX library calls.

Subclassed by *hpx::bad_alloc_exception*, *hpx::exception_list*

Public Functions

explicit **exception**(*error e = hpx::error::success*)

Construct a *hpx::exception* from a *hpx::error*.

Parameters

e – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.

explicit **exception**(*std::system_error const &e*)

Construct a *hpx::exception* from a *boost::system_error*.

explicit **exception**(*std::error_code const &e*)

Construct a *hpx::exception* from a *boost::system::error_code* (this is new for Boost V1.69). This constructor is required to compensate for the changes introduced as a resolution to LWG3162 (<https://cplusplus.github.io/LWG/issue3162>).

exception(*error e, char const *msg, throwmode mode = throwmode::plain*)

Construct a *hpx::exception* from a *hpx::error* and an error message.

Parameters

- e** – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.
- msg** – The parameter *msg* holds the error message the new exception should encapsulate.
- mode** – The parameter *mode* specifies whether the returned *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

exception(*error e, std::string const &msg, throwmode mode = throwmode::plain*)

Construct a *hpx::exception* from a *hpx::error* and an error message.

Parameters

- e** – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.
- msg** – The parameter *msg* holds the error message the new exception should encapsulate.
- mode** – The parameter *mode* specifies whether the returned *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

~exception() override

Destruct a *hpx::exception*

Throws

nothing –

error **get_error**() const noexcept

The function *get_error()* returns the *hpx::error* code stored in the referenced instance of a *hpx::exception*. It returns the *hpx::error* code this exception instance was constructed from.

Throws

nothing –

error_code **get_error_code**(*throwmode mode = throwmode::plain*) const noexcept

The function *get_error_code()* returns a *hpx::error_code* which represents the same error condition as this *hpx::exception* instance.

Parameters

- mode** – The parameter *mode* specifies whether the returned *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *throwmode::plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

struct **thread_interrupted** : public *exception*

#include <exception.hpp> A *hpx::thread_interrupted* is the exception type used by HPX to interrupt a running HPX thread.

The `hpx::thread_interrupted` type is the exception type used by HPX to interrupt a running thread.

A running thread can be interrupted by invoking the `interrupt()` member function of the corresponding `hpx::thread` object. When the interrupted thread next executes one of the specified interruption points (or if it is currently blocked whilst executing one) with interruption enabled, then a *`hpx::thread_interrupted`* exception will be thrown in the interrupted thread. If not caught, this will cause the execution of the interrupted thread to terminate. As with any other exception, the stack will be unwound, and destructors for objects of automatic storage duration will be executed.

If a thread wishes to avoid being interrupted, it can create an instance of *`hpx::this_thread::disable_interruption`*. Objects of this class disable interruption for the thread that created them on construction, and restore the interruption state to whatever it was before on destruction.

```
void f()
{
    // interruption enabled here
    {
        hpx::this_thread::disable_interruption di;
        // interruption disabled
        {
            hpx::this_thread::disable_interruption di2;
            // interruption still disabled
        } // di2 destroyed, interruption state restored
        // interruption still disabled
    } // di destroyed, interruption state restored
    // interruption now enabled
}
```

The effects of an instance of *`hpx::this_thread::disable_interruption`* can be temporarily reversed by constructing an instance of *`hpx::this_thread::restore_interruption`*, passing in the *`hpx::this_thread::disable_interruption`* object in question. This will restore the interruption state to what it was when the *`hpx::this_thread::disable_interruption`* object was constructed, and then disable interruption again when the *`hpx::this_thread::restore_interruption`* object is destroyed.

```
void g()
{
    // interruption enabled here
    {
        hpx::this_thread::disable_interruption di;
        // interruption disabled
        {
            hpx::this_thread::restore_interruption ri(di);
            // interruption now enabled
        } // ri destroyed, interruption disable again
    } // di destroyed, interruption state restored
    // interruption now enabled
}
```

At any point, the interruption state for the current thread can be queried by calling *`hpx::this_thread::interruption_enabled()`*.

hpx/errors/define_error_info.hpp

Defined in header `hpx/errors/define_error_info.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::error_code

Defined in header `hpx/system_error.hpp`⁷²³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Unnamed Group

```
inline error_code make_error_code(std::exception_ptr const &e)
```

```
inline error_code make_error_code(error e, throwmode mode = throwmode::plain)
```

Returns a new *error_code* constructed from the given parameters.

```
inline error_code make_error_code(error e, char const *func, char const *file, long line, throwmode mode = throwmode::plain)
```

```
inline error_code make_error_code(error e, char const *msg, throwmode mode = throwmode::plain)
```

Returns *error_code*(e, msg, mode).

```
inline error_code make_error_code(error e, char const *msg, char const *func, char const *file, long line, throwmode mode = throwmode::plain)
```

```
inline error_code make_error_code(error e, std::string const &msg, throwmode mode = throwmode::plain)
```

Returns *error_code*(e, msg, mode).

```
inline error_code make_error_code(error e, std::string const &msg, char const *func, char const *file, long line, throwmode mode = throwmode::plain)
```

Functions

```
std::error_category const &get_hpx_category() noexcept
```

Returns generic HPX error category used for new errors.

```
std::error_category const &get_hpx_rethrow_category() noexcept
```

Returns generic HPX error category used for errors re-thrown after the exception has been de-serialized.

```
inline error_code make_success_code(throwmode mode = throwmode::plain)
```

Returns *error_code*(hpx::error::success, “success”, mode).

⁷²³ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/system_error.hpp

class **error_code** : public *error_code*

#include <error_code.hpp> A *hpx::error_code* represents an arbitrary error condition.

The class *hpx::error_code* describes an object used to hold error code values, such as those originating from the operating system or other low-level application program interfaces.

Note: Class *hpx::error_code* is an adjunct to error reporting by exception

Public Functions

inline explicit **error_code**(*throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

mode – The parameter *mode* specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

Throws

nothing –

explicit **error_code**(*error* e, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.
- **mode** – The parameter *mode* specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

Throws

nothing –

error_code(*error* e, char const **func*, char const **file*, long *line*, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.
- **func** – The name of the function where the error was raised.
- **file** – The file name of the code where the error was raised.
- **line** – The line number of the code line where the error was raised.
- **mode** – The parameter *mode* specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

Throws

nothing –

error_code(*error* e, char const **msg*, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter *e* holds the *hpx::error* code the new exception should encapsulate.
- **msg** – The parameter *msg* holds the error message the new exception should encapsulate.
- **mode** – The parameter *mode* specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if *mode* is *plain*, this is the default) or to the category *hpx_category_rethrow* (if *mode* is *rethrow*).

Throws

std::bad_alloc – (if allocation of a copy of the passed string fails).

error_code(*error* e, char const *msg, char const *func, char const *file, long line, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter **e** holds the *hpx::error* code the new exception should encapsulate.
- **msg** – The parameter **msg** holds the error message the new exception should encapsulate.
- **func** – The name of the function where the error was raised.
- **file** – The file name of the code where the error was raised.
- **line** – The line number of the code line where the error was raised.
- **mode** – The parameter **mode** specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if mode is *plain*, this is the default) or to the category *hpx_category_rethrow* (if mode is *rethrow*).

Throws

std::bad_alloc – (if allocation of a copy of the passed string fails).

error_code(*error* e, *std::string* const &msg, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter **e** holds the *hpx::error* code the new exception should encapsulate.
- **msg** – The parameter **msg** holds the error message the new exception should encapsulate.
- **mode** – The parameter **mode** specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if mode is *plain*, this is the default) or to the category *hpx_category_rethrow* (if mode is *rethrow*).

Throws

std::bad_alloc – (if allocation of a copy of the passed string fails).

error_code(*error* e, *std::string* const &msg, char const *func, char const *file, long line, *throwmode* mode = *throwmode::plain*)

Construct an object of type *error_code*.

Parameters

- **e** – The parameter **e** holds the *hpx::error* code the new exception should encapsulate.
- **msg** – The parameter **msg** holds the error message the new exception should encapsulate.
- **func** – The name of the function where the error was raised.
- **file** – The file name of the code where the error was raised.
- **line** – The line number of the code line where the error was raised.
- **mode** – The parameter **mode** specifies whether the constructed *hpx::error_code* belongs to the error category *hpx_category* (if mode is *plain*, this is the default) or to the category *hpx_category_rethrow* (if mode is *rethrow*).

Throws

std::bad_alloc – (if allocation of a copy of the passed string fails).

error_code(*error_code*&&) = default

error_code &**operator**=(*error_code*&&) = default

~error_code() = default

std::string **get_message**() const

Return a reference to the error message stored in the *hpx::error_code*.

Throws

nothing –

inline void **clear**()

Clear this *error_code* object. The postconditions of invoking this method are.

- `value() == hpx::error::success` and `category() == hpx::get_hpx_category()`

error_code(*error_code* const &rhs)

Copy constructor for *error_code*

Note: This function maintains the error category of the left hand side if the right hand side is a success code.

error_code &**operator=**(*error_code* const &rhs)

Assignment operator for *error_code*

Note: This function maintains the error category of the left hand side if the right hand side is a success code.

Private Functions

error_code(int err, *hpx::exception* const &e)

explicit **error_code**(*std::exception_ptr* const &e)

Private Members

std::exception_ptr **exception_**

Friends

friend class *exception*

friend *error_code* **make_error_code**(*std::exception_ptr* const&)

execution

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/execution/traits/is_execution_policy.hpp

Defined in header `hpx/execution/traits/is_execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Variables

```
template<typename T>
```

```
constexpr bool is_execution_policy_v = is_execution_policy<T>::value
```

```
template<typename T> concept execution_policy    = is_execution_policy<T>::value
```

```
template<typename T>
```

```
constexpr bool is_parallel_execution_policy_v = is_parallel_execution_policy<T>::value
```

```
template<typename T>
```

```
constexpr bool is_sequenced_execution_policy_v = is_sequenced_execution_policy<T>::value
```

```
template<typename T>
```

```
constexpr bool is_async_execution_policy_v = is_async_execution_policy<T>::value
```

```
template<typename T>
```

```
struct is_async_execution_policy : public hpx::detail::is_async_execution_policy<std::decay_t<T>>
```

```
    #include <is_execution_policy.hpp> Extension: Detect whether given execution policy makes algorithms asynchronous
```

- i. The type *is_async_execution_policy* can be used to detect asynchronous execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If T is the type of the standard or implementation-defined execution policy, *is_async_execution_policy*<T> shall be publicly derived from *integral_constant*<bool, true>, otherwise from *integral_constant*<bool, false>.
- iii. The behavior of a program that adds specializations for *is_async_execution_policy* is undefined.

```
template<typename T>
```

```
struct is_execution_policy : public hpx::detail::is_execution_policy<std::decay_t<T>>
```

```
    #include <is_execution_policy.hpp>
```

- i. The type *is_execution_policy* can be used to detect execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If T is the type of the standard or implementation-defined execution policy, *is_execution_policy*<T> shall be publicly derived from *integral_constant*<bool, true>, otherwise from *integral_constant*<bool, false>.
- iii. The behavior of a program that adds specializations for *is_execution_policy* is undefined.

```
template<typename T>
```

```
struct is_parallel_execution_policy : public
```

```
hpx::detail::is_parallel_execution_policy<std::decay_t<T>>
```

```
    #include <is_execution_policy.hpp> Extension: Detect whether given execution policy enables parallelization
```

- i. The type `is_parallel_execution_policy` can be used to detect parallel execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_parallel_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.
- iii. The behavior of a program that adds specializations for `is_parallel_execution_policy` is undefined.

```
template<typename T>
```

```
struct is_sequenced_execution_policy: public
```

```
hpx::detail::is_sequenced_execution_policy<std::decay_t<T>>
```

```
    #include <is_execution_policy.hpp> Extension: Detect whether given execution policy does not enable parallelization
```

- i. The type `is_sequenced_execution_policy` can be used to detect non-parallel execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_sequenced_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.
- iii. The behavior of a program that adds specializations for `is_sequenced_execution_policy` is undefined.

hpx::execution::experimental::persistent_auto_chunk_size

Defined in header `hpx/execution.hpp`⁷²⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

Typedefs

```
    typedef hpx::execution::experimental::persistent_auto_chunk_size instead
```

```
    namespace experimental
```

```
        struct persistent_auto_chunk_size
```

```
            #include <persistent_auto_chunk_size.hpp> Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameters type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.
```

⁷²⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

Public Functions

inline explicit constexpr **persistent_auto_chunk_size**(*std::uint64_t* const
num_iters_for_timing = 0) noexcept

Construct an `persistent_auto_chunk_size` executor parameters object

Note: Default constructed `persistent_auto_chunk_size` executor parameter types will use 0 microseconds as the execution time for each chunk and 80 microseconds as the minimal time for which any of the scheduled chunks should run.

inline explicit **persistent_auto_chunk_size**(*hpx::chrono::steady_duration* const &time_cs,
std::uint64_t const num_iters_for_timing = 0)
noexcept

Construct an `persistent_auto_chunk_size` executor parameters object

Parameters

- **time_cs** – The execution time for each chunk.
- **num_iters_for_timing** – [in] The number of iterations to use for measuring the execution time of one iteration

inline **persistent_auto_chunk_size**(*hpx::chrono::steady_duration* const &time_cs,
hpx::chrono::steady_duration const &rel_time,
std::uint64_t const num_iters_for_timing = 0)
noexcept

Construct an `persistent_auto_chunk_size` executor parameters object

Parameters

- **rel_time** – [in] The time duration to use as the minimum to decide how many loop iterations should be combined.
- **time_cs** – The execution time for each chunk.
- **num_iters_for_timing** – [in] The number of iterations to use for measuring the execution time of one iteration

`hpx::execution::experimental::collect_chunking_parameters`

Defined in header `hpx/execution.hpp`⁷²⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **execution**

namespace **experimental**

struct **chunking_parameters**

#include <collect_chunking_parameters.hpp> Collected execution parameters.

⁷²⁵ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

Public Functions

```
template<typename Archive>
inline void serialize(Archive &ar, unsigned int const)
```

Public Members

```
std::size_t num_elements
```

```
std::size_t num_cores
```

```
std::size_t num_chunks
```

```
std::size_t chunk_size
```

```
struct collect_chunking_parameters
```

#include <collect_chunking_parameters.hpp> Collect various parameters used for running a parallel algorithm.

Public Functions

```
inline explicit constexpr collect_chunking_parameters(chunking_parameters
                                                         &exec_params) noexcept
```

hpx/execution/executors/default_parameters.hpp

Defined in header `hpx/execution/executors/default_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            struct default_parameters
```

#include <default_parameters.hpp> Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's `STATIC` scheduling directive.

Public Functions

default_parameters() = default

Construct a default_parameters executor parameters object

Note: By default, the number of loop iterations is determined from the number of available cores and the overall number of loop iterations to schedule.

hpx/execution/executors/adaptive_static_chunk_size.hpp

Defined in header hpx/execution/executors/adaptive_static_chunk_size.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **execution**

namespace **experimental**

struct **adaptive_static_chunk_size**

#include <adaptive_static_chunk_size.hpp> Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's STATIC scheduling directive.

Public Functions

adaptive_static_chunk_size() = default

Construct a adaptive_static_chunk_size executor parameters object

Note: By default the number of loop iterations is determined from the number of available cores and the overall number of loop iterations to schedule.

inline explicit constexpr **adaptive_static_chunk_size**(std::size_t const chunk_size)
noexcept

Construct a adaptive_static_chunk_size executor parameters object

Parameters

chunk_size – [in] The optional chunk size to use as the number of loop iterations to run on a single thread.

hpx::execution::experimental::dynamic_chunk_size

Defined in header [hpx/execution.hpp](#)⁷²⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            struct dynamic_chunk_size
```

```
                #include <dynamic_chunk_size.hpp> Loop iterations are divided into pieces of size chunk_size and then dynamically scheduled among the threads; when a thread finishes one chunk, it is dynamically assigned another. If chunk_size is not specified, the default chunk size is 1.
```

Note: This executor parameters type is equivalent to OpenMP's DYNAMIC scheduling directive.

Public Functions

```
dynamic_chunk_size() = default
```

Construct an `dynamic_chunk_size` executor parameters object

Note: Default constructed `dynamic_chunk_size` executor parameter types will use a chunk size of '1'.

```
inline explicit constexpr dynamic_chunk_size(std::size_t chunk_size) noexcept
```

Construct a `dynamic_chunk_size` executor parameters object

Parameters

chunk_size – [in] The optional chunk size to use as the number of loop iterations to schedule together. The default chunk size is 1.

hpx/execution/executors/execution.hpp

Defined in header `hpx/execution/executors/execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
        namespace execution
```

⁷²⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

hpx/execution/executors/execution_parameters_fwd.hpp

Defined in header `hpx/execution/executors/execution_parameters_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Variables

```
constexpr struct hpx::execution::experimental::null_parameters_t null_parameters
```

```
constexpr struct hpx::execution::experimental::get_chunk_size_t get_chunk_size
```

```
constexpr struct hpx::execution::experimental::measure_iteration_t measure_iteration
```

```
constexpr struct hpx::execution::experimental::maximal_number_of_chunks_t  
maximal_number_of_chunks
```

```
constexpr struct hpx::execution::experimental::reset_thread_distribution_t  
reset_thread_distribution
```

```
constexpr struct hpx::execution::experimental::processing_units_count_t  
processing_units_count
```

```
constexpr struct hpx::execution::experimental::with_processing_units_count_t  
with_processing_units_count
```

```
constexpr struct hpx::execution::experimental::mark_begin_execution_t mark_begin_execution
```

```
constexpr struct hpx::execution::experimental::mark_end_of_scheduling_t  
mark_end_of_scheduling
```

```
constexpr struct hpx::execution::experimental::mark_end_execution_t mark_end_execution
```

```
constexpr struct hpx::execution::experimental::mark_partition_t mark_partition
```

```
constexpr struct hpx::execution::experimental::collect_execution_parameters_t  
collect_execution_parameters
```

struct **collect_execution_parameters_t**

#include <execution_parameters_fwd.hpp> Collect various parameters of the chunking for this parallel algorithm execution

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param num_elements

[in] The overall number of elements for the algorithm.

Param num_cores

[in] The overall number of cores to utilize for the algorithm.

Param num_chunks

[in] The overall number of chunks for the algorithm.

Param chunk_size

[in] The size of the chunks created for the algorithm.

Public Functions

template<typename **Parameters**, typename **Executor**>

inline decltype(auto) **operator()**(*Parameters* &¶ms, *Executor* &&exec, *std::size_t* num_elements, *std::size_t* num_cores, *std::size_t* num_chunks, *std::size_t* chunk_size) const

struct **get_chunk_size_t**

#include <execution_parameters_fwd.hpp> Return the number of invocations of the given function *f* which should be combined into a single task

Param params

[in] The executor parameters object to use for determining the chunk size for the given number of tasks *num_tasks*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param iteration_duration

[in] The time one of the tasks require to be executed.

Param cores

[in] The number of cores the number of chunks should be determined for.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Return

The size of the chunks (number of iterations per chunk) that should be used for parallel execution.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec,
                                   hpx::chrono::steady_duration const &iteration_duration,
                                   std::size_t cores, std::size_t num_tasks) const

template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t cores,
                                   std::size_t num_tasks) const
```

```
template<>
```

```
struct is_scheduling_property<with_processing_units_count_t> : public true_type
```

```
struct mark_begin_execution_t
```

```
#include <execution_parameters_fwd.hpp> Mark the begin of a parallel algorithm execution
```

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

```
struct mark_end_execution_t
```

```
#include <execution_parameters_fwd.hpp> Mark the end of a parallel algorithm execution
```

Note: This calls `params.mark_end_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

```
struct mark_end_of_scheduling_t
```

```
#include <execution_parameters_fwd.hpp> Mark the end of scheduling tasks during parallel algorithm execution
```

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

struct **mark_partition_t**

#include <execution_parameters_fwd.hpp> Mark custom point in parallel algorithm execution

Note: This calls `params.mark_partition(exec, partition, args...)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor, typename ...Args>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t
                                   partition, Args&&... args) const
```

struct **maximal_number_of_chunks_t**

#include <execution_parameters_fwd.hpp> Return the largest reasonable number of chunks to create for a single algorithm invocation.

Param params

[in] The executor parameters object to use for determining the number of chunks for the given number of *cores*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param cores

[in] The number of cores the number of chunks should be determined for.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec, std::size_t cores,
                                   std::size_t num_tasks) const
```

```
struct measure_iteration_t
```

#include <execution_parameters_fwd.hpp> Return the measured execution time for one iteration based on running the given function.

Note: The parameter *f* is expected to be a nullary function returning a `std::size_t` representing the number of iteration the function has already executed (i.e. which don't have to be scheduled anymore).

Param params

[in] The executor parameters object to use for determining the chunk size for the given number of tasks *num_tasks*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param f

[in] The function which will be optionally scheduled using the given executor.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Return

The execution time for one of the tasks.

Public Functions

```
template<typename Parameters, typename Executor, typename F>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec, F &&f,
                                   std::size_t num_tasks) const
```

```
struct null_parameters_t
```

```
struct processing_units_count_t
```

#include <execution_parameters_fwd.hpp> Retrieve the number of (kernel-)threads used by the associated executor.

Note: This calls `params.processing_units_count(Executor&&)` if it exists; otherwise it forwards the request to the executor parameters object.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param iteration_duration

[in] The time one of the tasks require to be executed.

Param num_tasks

[in] The number of tasks the number of cores should be determined for

Return

The number of cores to use

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec,
                                   hpx::chrono::steady_duration const &iteration_duration,
                                   std::size_t num_tasks) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t
                                   num_tasks) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &iteration_duration, std::size_t num_tasks) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_tasks) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec,
                                   hpx::chrono::steady_duration const &iteration_duration,
                                   std::size_t num_tasks) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t
                                   num_tasks = 0) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &iteration_duration, std::size_t num_tasks) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_tasks = 0) const
```

```
template<typename ExPolicy>
inline decltype(auto) operator() (ExPolicy &&policy) const
```

struct **reset_thread_distribution_t**

#include <execution_parameters_fwd.hpp> Reset the internal round robin thread distribution scheme for the given executor.

Note: This calls `params.reset_thread_distribution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use for resetting the thread distribution scheme.

Param exec

[in] The executor object to use.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

```
struct with_processing_units_count_t
```

#include <execution_parameters_fwd.hpp> Generate a policy that supports setting the number of cores for execution.

Public Functions

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_cores) const

template<typename Policy, typename Property>
inline decltype(auto) operator() (Policy &&policy, Property &&property) const
```

hpx/execution/executors/execution_parameters.hpp

Defined in header `hpx/execution/executors/execution_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

Functions

```
template<typename ...Params>
constexpr executor_parameters_join<Params...>::type join_executor_parameters (Params&&...
                                                                    params)

template<typename Param>
constexpr Param &&join_executor_parameters (Param &&param) noexcept

template<typename ...Params>

struct executor_parameters_join
```

Public Types

```
using type = detail::executor_parameters<std::decay_t<Params>...>

template<typename Param>

struct executor_parameters_join<Param>
```

Public Types

```
using type = Param
```

hpx/execution/executors/polymorphic_executor.hpp

Defined in header `hpx/execution/executors/polymorphic_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx

{
    namespace execution

    {
        namespace experimental

        {
            namespace parallel

            {
                namespace execution

                {
                    template<typename Sig>

                    class polymorphic_executor

                    {
                    public:
                        template<typename R, typename ...Ts>

                        class polymorphic_executor<R(Ts...)> : private
                            hpx::parallel::execution::detail::polymorphic_executor_base
                    };
                };
            };
        };
    };
}
```

Public Types

```
template<typename>

using future_type = hpx::future<R>
```

Public Functions

```

inline constexpr polymorphic_executor() noexcept

inline polymorphic_executor(polymorphic_executor const &other)

inline polymorphic_executor(polymorphic_executor &&other) noexcept

inline polymorphic_executor &operator=(polymorphic_executor const &other)

inline polymorphic_executor &operator=(polymorphic_executor &&other) noexcept

template<typename Exec, typename PE = std::decay_t<Exec>, typename Enable =
std::enable_if_t<!std::is_same_v<PE, polymorphic_executor>>>
inline polymorphic_executor(Exec &&exec)

template<typename Exec, typename PE = std::decay_t<Exec>, typename Enable =
std::enable_if_t<!std::is_same_v<PE, polymorphic_executor>>>
inline polymorphic_executor &operator=(Exec &&exec)

inline void reset() noexcept

template<typename F>
inline void post(F &&f, Ts... ts) const

template<typename F>
inline R sync_execute(F &&f, Ts... ts) const

template<typename F>
inline hpx::future<R> async_execute(F &&f, Ts... ts) const

template<typename F, typename Future>
inline hpx::future<R> then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename Shape>
inline std::vector<R> bulk_sync_execute(F &&f, Shape const &s, Ts&&... ts) const

template<typename F, typename Shape>
inline hpx::future<std::vector<R>> bulk_async_execute(F &&f, Shape const &s, Ts&&...
                                                    ts) const

template<typename F, typename Shape>
inline hpx::future<std::vector<R>> bulk_then_execute(F &&f, Shape const &s,
                                                    hpx::shared_future<void> const
                                                    &predecessor, Ts&&... ts) const

```

Private Types

```

using base_type = detail::polymorphic_executor_base

using vtable = detail::polymorphic_executor_vtable<R(Ts...)>

```

Private Functions

```
inline void assign(std::nullptr_t) noexcept

template<typename Exec>
inline void assign(Exec &&exec)
```

Private Static Functions

```
static inline constexpr vtable const *get_empty_vtable() noexcept

template<typename T>
static inline constexpr vtable const *get_vtable() noexcept
```

hpx/execution/executors/rebind_executor.hpp

Defined in header `hpx/execution/executors/rebind_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Typedefs

```
template<typename ExPolicy, typename Executor, typename Parameters>
using rebind_executor_t = typename rebind_executor<ExPolicy, Executor, Parameters>::type
```

Variables

```
constexpr struct hpx::execution::experimental::create_rebound_policy_t create_rebound_policy
```

```
struct create_rebound_policy_t
```

Public Functions

```
template<typename ExPolicy, typename Executor, typename Parameters>
inline constexpr decltype(auto) operator() (ExPolicy&&, Executor &&exec, Parameters
&&parameters) const

template<typename ExPolicy, typename Executor>
inline constexpr decltype(auto) operator() (ExPolicy &&policy, Executor &&exec) const

template<typename ExPolicy, typename Parameters>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy, Parameters &&parameters)
    const
```

```
template<typename ExPolicy, typename Executor, typename Parameters>
```

```
struct rebind_executor
```

#include <rebind_executor.hpp> Rebind the type of executor used by an execution policy. The execution category of `Executor` shall not be weaker than that of `ExecutionPolicy`.

Public Types

```
using type = typename policy_type::template rebind<executor_type, parameters_type>::type
```

The type of the rebound execution policy.

hpx::execution::experimental::static_chunk_size

Defined in header `hpx/execution.hpp`⁷²⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
struct static_chunk_size
```

#include <static_chunk_size.hpp> Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's `STATIC` scheduling directive.

Public Functions

```
static_chunk_size() = default
```

Construct a `static_chunk_size` executor parameters object

Note: By default, the number of loop iterations is determined from the number of available cores and the overall number of loop iterations to schedule.

```
inline explicit constexpr static_chunk_size(std::size_t const chunk_size) noexcept
```

Construct a `static_chunk_size` executor parameters object

⁷²⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

Parameters

chunk_size – [in] The optional chunk size to use as the number of loop iterations to run on a single thread.

hpx::execution::experimental::guided_chunk_size

Defined in header [hpx/execution.hpp](#)⁷²⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **execution**

namespace **experimental**

struct **guided_chunk_size**

#include <guided_chunk_size.hpp> Iterations are dynamically assigned to threads in blocks as threads request those until no blocks remain to be assigned. Similar to `dynamic_chunk_size` except that the block size decreases each time a number of loop iterations is given to a thread. The size of the initial block is proportional to *number_of_iterations / number_of_cores*. Subsequent blocks are proportional to *number_of_iterations_remaining / number_of_cores*. The optional chunk size parameter defines the minimum block size. The default chunk size is 1.

Note: This executor parameters type is equivalent to OpenMP's GUIDED scheduling directive.

Public Functions

guided_chunk_size() = default

Construct an `dynamic_chunk_size` executor parameters object

Note: Default constructed `dynamic_chunk_size` executor parameter types will use a chunk size of '1'.

inline explicit constexpr **guided_chunk_size**(std::size_t const min_chunk_size) noexcept

Construct a `guided_chunk_size` executor parameters object

Parameters

min_chunk_size – [in] The optional minimal chunk size to use as the minimal number of loop iterations to schedule together. The default minimal chunk size is 1.

⁷²⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

hpx/execution/executors/execution_information.hpp

Defined in header `hpx/execution/executors/execution_information.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Variables

constexpr struct `hpx::execution::experimental::has_pending_closures_t` **has_pending_closures**

constexpr struct `hpx::execution::experimental::get_pu_mask_t` **get_pu_mask**

constexpr struct `hpx::execution::experimental::set_scheduler_mode_t` **set_scheduler_mode**

struct **get_pu_mask_t**

#include <execution_information.hpp> Retrieve the bitmask describing the processing units the given thread is allowed to run on

All `threads::executors` invoke `sched.get_pu_mask()`.

Note: If the executor does not support this operation, this call will always invoke `hpx::threads::get_pu_mask()`

Param exec

[in] The executor object to use for querying the number of pending tasks.

Param topo

[in] The topology object to use to extract the requested information.

Param thream_num

[in] The sequence number of the thread to retrieve information for.

Public Functions

template<typename **Executor**>

inline decltype(auto) **operator()** (*Executor* &&exec, *threads::topology* &topo, *std::size_t* thread_num) const

template<typename **Executor**>

inline decltype(auto) **operator()** (*Executor*&&, *threads::topology* &topo, *std::size_t* thread_num) const

struct **has_pending_closures_t**

#include <execution_information.hpp> Retrieve whether this executor has operations pending or not.

Note: If the executor does not expose this information, this call will always return *false*

Param exec

[in] The executor object to use to extract the requested information for.

Public Functions

template<typename **Executor**>
inline decltype(auto) **operator()** (*Executor* &&exec) const

template<typename **Executor**>
inline decltype(auto) **operator()** (*Executor*&&) const

struct **set_scheduler_mode_t**

#include <execution_information.hpp> Set various modes of operation on the scheduler underneath the given executor.

Note: This calls `exec.set_scheduler_mode(mode)` if it exists; otherwise it does nothing.

Param exec

[in] The executor object to use.

Param mode

[in] The new mode for the scheduler to pick up

Public Functions

template<typename **Executor**, typename **Mode**>
inline void **operator()** (*Executor* &&exec, *Mode* const &mode) const

template<typename **Executor**, typename **Mode**>
inline void **operator()** (*Executor*&&, *Mode* const&) const

hpx::execution::experimental::max_num_chunks

Defined in header `hpx/execution.hpp`⁷²⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

⁷²⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

namespace **experimental**

struct **max_num_chunks**

#include <max_num_chunks.hpp> Loop iterations are divided into not more than *num_chunks* partitions that are assigned to threads. If *num_chunks* is not specified, the number of chunks is determined based on the number of available cores.

Public Functions

max_num_chunks() = default

Construct a max_num_chunks executor parameters object

Note: By default, the number of chunks is determined from the number of available cores.

inline explicit constexpr **max_num_chunks**(std::size_t const num_chunks) noexcept

Construct a max_num_chunks executor parameters object

Parameters

num_chunks – [in] The optional number of chunks to use to run on a single thread.

hpx::execution::experimental::num_cores

Defined in header [hpx/execution.hpp](#)⁷³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **execution**

namespace **experimental**

struct **num_cores**

#include <num_cores.hpp> Control number of cores in executors which need a functionality for setting the number of cores to be used by an algorithm directly

Public Functions

inline explicit constexpr **num_cores**(std::size_t const cores = 1) noexcept

Construct a num_cores executor parameters object

Note: make sure the minimal number of cores is and the maximum number of cores is what's available to HPX

⁷³⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

hpx::execution::experimental::auto_chunk_size

Defined in header [hpx/execution.hpp](#)⁷³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            struct auto_chunk_size
```

```
                #include <auto_chunk_size.hpp> Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameters type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.
```

Public Functions

```
inline explicit constexpr auto_chunk_size(std::uint64_t const num_iters_for_timing = 0)
                                         noexcept
```

Construct an auto_chunk_size executor parameters object

Note: Default constructed auto_chunk_size executor parameter types will use 80 microseconds as the minimal time for which any of the scheduled chunks should run.

```
inline explicit auto_chunk_size(hpx::chrono::steady_duration const &rel_time, std::uint64_t
                                const num_iters_for_timing = 0) noexcept
```

Construct an auto_chunk_size executor parameters object

Parameters

- **rel_time** – [in] The time duration to use as the minimum to decide how many loop iterations should be combined.
- **num_iters_for_timing** – [in] The number of iterations to use for the timing operation

execution_base

See *Public API* for a list of names and headers that are part of the public HPX API.

⁷³¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

hpx/execution_base/execution.hpp

Defined in header `hpx/execution_base/execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

struct **parallel_execution_tag**

#include <execution.hpp> Function invocations executed by a group of parallel execution agents execute in unordered fashion. Any such invocations executing in the same thread are indeterminately sequenced with respect to each other.

Note: `parallel_execution_tag` is weaker than `sequenced_execution_tag`.

struct **sequenced_execution_tag**

#include <execution.hpp> Function invocations executed by a group of sequential execution agents execute in sequential order.

struct **unsequenced_execution_tag**

#include <execution.hpp> Function invocations executed by a group of vector execution agents are permitted to execute in unordered fashion when executed in different threads, and un-sequenced with respect to one another when executed in the same thread.

Note: `unsequenced_execution_tag` is weaker than `parallel_execution_tag`.

namespace **parallel**

namespace **execution**

Variables

constexpr struct `hpx::parallel::execution::sync_execute_t` **sync_execute**

constexpr struct `hpx::parallel::execution::async_execute_t` **async_execute**

constexpr struct `hpx::parallel::execution::then_execute_t` **then_execute**

constexpr struct `hpx::parallel::execution::post_t` **post**

constexpr struct `hpx::parallel::execution::bulk_sync_execute_t` **bulk_sync_execute**

```
constexpr struct hpx::parallel::execution::bulk_async_execute_t bulk_async_execute
```

```
constexpr struct hpx::parallel::execution::bulk_then_execute_t bulk_then_execute
```

```
constexpr struct hpx::parallel::execution::async_invoke_t async_invoke
```

```
constexpr struct hpx::parallel::execution::sync_invoke_t sync_invoke
```

```
struct async_execute_t
```

#include <execution.hpp> Customization point for asynchronous execution agent creation.

This asynchronously creates a single function invocation *f*() using the associated executor.

Note: Executors have to implement only `async_execute()`. All other functions will be emulated by this or other customization points in terms of this single basic primitive. However, some executors will naturally specialize all operations for maximum efficiency.

Note: This is valid for one way executors (calls `make_ready_future(exec.sync_execute(f, ts...))` if it exists) and for two-way executors (calls `exec.async_execute(f, ts...)` if it exists).

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts*

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result through a future

Public Functions

```
template<typename Executor, typename F, typename ...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
struct async_invoke_t
```

#include <execution.hpp> Asynchronously invoke the given set of nullary functions, each on its own execution agent

This creates a group of function invocations whose ordering is given by the `execution_category` associated with the executor.

All exceptions thrown by invocations of the functions are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This calls `exec.async_invoke(fs...)` if it exists; otherwise it executes `async_execute(fs)` for each `fs`.

Param exec

[in] The executor object to use for scheduling of the functions `fs`.

Param fs

[in] The functions which will be scheduled using the given executor.

Return

The return type of `executor_type::async_invoke` if defined by `executor_type`. Otherwise, a `future<void>` representing finishing the execution of all functions `fs`.

Public Functions

```
template<typename Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

```
template<executor_any Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

```
struct bulk_async_execute_t
```

```
#include <execution.hpp> Bulk form of asynchronous execution agent creation.
```

This asynchronously creates a group of function invocations `f(i)` whose ordering is given by the `execution_category` associated with the executor.

Here *i* takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of `f(i)` are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `bulk_async_execute` customization points specified in P0443. The `bulk_async_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_async_execute(f, shape, ts...)` if it exists; otherwise it executes `async_execute(f, shape, ts...)` as often as needed.

Param exec

[in] The executor object to use for scheduling of the function `f`.

Param f

[in] The function which will be scheduled using the given executor.

Param shape

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to `f`.

Param ts

[in] Additional arguments to use to invoke `f`.

Return

The return type of `executor_type::bulk_async_execute` if defined by `executor_type`. Otherwise, a vector of futures holding the returned values of each invocation of `f`.

Public Functions

```
template<typename Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<typename Executor, typename F, typename Shape, typename ...Ts>
inline auto operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts) const ->
    decltype(HPX_FORWARD(Executor,
        exec).bulk_async_execute(HPX_FORWARD(F, f), shape,
        HPX_FORWARD(Ts, ts)...))
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

struct **bulk_sync_execute_t**

#include <execution.hpp> Bulk form of synchronous execution agent creation.

This synchronously creates a group of function invocations $f(i)$ whose ordering is given by the `execution_category` associated with the executor. The function synchronizes the execution of all scheduled functions with the caller.

Here i takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of $f(i)$ are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `bulk_sync_execute` customization points specified in P0443. The `bulk_sync_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_sync_execute(f, shape, ts...)` if it exists; otherwise it executes `sync_execute(f, shape, ts...)` as often as needed.

Param `exec`

[in] The executor object to use for scheduling of the function f .

Param `f`

[in] The function which will be scheduled using the given executor.

Param `shape`

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to f .

Param `ts`

[in] Additional arguments to use to invoke f .

Return

The return type of `executor_type::bulk_sync_execute` if defined by `executor_type`. Otherwise, a vector holding the returned values of each invocation of f except when f returns void, which case void is returned.

Public Functions

```
template<typename Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
struct bulk_then_execute_t
```

#include <execution.hpp> Bulk form of execution agent creation depending on a given future.

This creates a group of function invocations $f(i)$ whose ordering is given by the `execution_category` associated with the executor.

Here i takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of $f(i)$ are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `then_sync_execute` customization points specified in P0443. The `bulk_then_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_then_execute(f, shape, pred, ts...)` if it exists; otherwise it executes `sync_execute(f, shape, pred.share(), ts...)` (if this executor is also an `OneWayExecutor`), or `async_execute(f, shape, pred.share(), ts...)` (if this executor is also a `TwoWayExecutor`) - as often as needed.

Param `exec`

[in] The executor object to use for scheduling of the function f .

Param `f`

[in] The function which will be scheduled using the given executor.

Param `shape`

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to f .

Param `predecessor`

[in] The future object the execution of the given function depends on.

Param `ts`

[in] Additional arguments to use to invoke f .

Return

The return type of `executor_type::bulk_then_execute` if defined by `executor_type`. Otherwise, a vector holding the returned values of each invocation of f .

Public Functions

```
template<typename Executor, typename F, typename Shape, typename Future, typename  
...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future  
    &&predecessor, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename Shape, typename Future, typename  
...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future  
    &&predecessor, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename Shape, typename Future, typename  
...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future  
    &&predecessor, Ts&&... ts) const
```

struct **post_t**

#include <execution.hpp> Customization point for asynchronous fire & forget execution agent creation.

This asynchronously (fire & forget) creates a single function invocation *f*() using the associated executor.

Note: This is valid for two-way executors (calls *exec.post(f, ts...)*, if available, otherwise it calls *exec.async_execute(f, ts...)* while discarding the returned future), and for non-blocking two-way executors (calls *exec.post(f, ts...)* if it exists).

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts*

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<typename Executor, typename F, typename ...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>  
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

struct **sync_execute_t**

#include <execution.hpp> Customization point for synchronous execution agent creation.

This synchronously creates a single function invocation *f*() using the associated executor. The execution of the supplied function synchronizes with the caller

Note: It will call *exec.sync_execute(f, ts...)* if the executor exposes a corresponding member function. For two-way executors it will invoke *async_execute* and wait for the task's completion

before returning.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param f

[in] The function which will be scheduled using the given executor.

Param ts

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<typename Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

struct **sync_invoke_t**

#include <execution.hpp> Synchronously invoke the given set of nullary functions, each on its own execution agent

This creates a group of function invocations whose ordering is given by the *execution_category* associated with the executor.

All exceptions thrown by invocations of the functions are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This calls *exec.sync_invoke(fs...)* if it exists; otherwise it executes *sync_execute(fs)* for each *fs*.

Param exec

[in] The executor object to use for scheduling of the functions *fs*.

Param fs

[in] The functions which will be scheduled using the given executor.

Return

The return type of *executor_type::async_invoke* if defined by *executor_type*.

Public Functions

```
template<typename Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

```
template<executor_any Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

struct **then_execute_t**

#include <execution.hpp> Customization point for execution agent creation depending on a given future.

This creates a single function invocation `f()` using the associated executor after the given future object has become ready.

Note: This is valid for two-way executors (calls `exec.then_execute(f, predecessor, ts...)` if it exists) and for one way executors (calls `predecessor.then(bind(f, ts...))`).

Param `exec`

[in] The executor object to use for scheduling of the function `f`.

Param `f`

[in] The function which will be scheduled using the given executor.

Param `predecessor`

[in] The future object the execution of the given function depends on.

Param `ts`

[in] Additional arguments to use to invoke `f`.

Return

`f(ts...)`'s result through a future

Public Functions

```
template<typename Executor, typename F, typename Future, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Future &&predecessor, Ts&&...
                                   ts) const
```

```
template<executor_any Executor, typename F, typename Future, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Future &&predecessor, Ts&&...
                                   ts) const
```

hpx/execution_base/traits/is_executor_parameters.hpp

Defined in header `hpx/execution_base/traits/is_executor_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Executor>
```

```
struct extract_executor_parameters<Executor, std::void_t<typename Executor::executor_parameters_type>>
```

Public Types

```
using type = typename Executor::executor_parameters_type
```

```
template<typename Parameters>
```

```
struct extract_has_variable_chunk_size<Parameters, std::void_t<typename
Parameters::has_variable_chunk_size>> : public true_type
```

```
template<typename Parameters>
```

```
struct extract_has_variable_chunk_size<::std::reference_wrapper<Parameters>> : public
hpx::execution::experimental::extract_has_variable_chunk_size<Parameters>
```

```
template<typename Parameters>
```

```
struct extract_invokes_testing_function<::std::reference_wrapper<Parameters>> : public
    hpx::execution::experimental::extract_invokes_testing_function<Parameters>
```

```
namespace hpx
```

Variables

```
template<typename Parameters> concept executor_parameters =hpx::traits::is_executor_parameters_v<Parameters>
```

```
namespace execution
```

```
    namespace experimental
```

Typedefs

```
template<typename Executor>
using extract_executor_parameters_t = typename
    extract_executor_parameters<Executor>::type
```

Variables

```
template<typename Parameters>
constexpr bool extract_has_variable_chunk_size_v =
    extract_has_variable_chunk_size<Parameters>::value

template<typename Parameters>
constexpr bool extract_invokes_testing_function_v =
    extract_invokes_testing_function<Parameters>::value

template<typename T>
constexpr bool is_executor_parameters_v = is_executor_parameters<T>::value

template<typename Executor, typename Enable = void>
struct extract_executor_parameters
```

Public Types

```
using type = sequential_executor_parameters

template<typename Executor> executor_parameters_type > >
```

Public Types

```
using type = typename Executor::executor_parameters_type

template<typename Parameters, typename Enable = void>
struct extract_has_variable_chunk_size : public false_type

template<typename Parameters> has_variable_chunk_size > > : public true_type

template<typename Parameters> reference_wrapper< Parameters > > : public hpx::execution::ex

template<typename Parameters, typename Enable = void>
struct extract_invokes_testing_function : public false_type

template<typename Parameters> reference_wrapper< Parameters > > : public hpx::execution::ex

template<typename T>
struct is_executor_parameters : public detail::is_executor_parameters<std::decay_t<T>>

struct sequential_executor_parameters
```

namespace **traits**

Variables

```
template<typename T>
constexpr bool is_executor_parameters_v = is_executor_parameters<T>::value

template<typename Parameters, typename Enable>
struct is_executor_parameters
```

executors

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
hpx::execution::seq,           hpx::execution::par,           hpx::execution::par_unseq,
hpx::execution::task,         hpx::execution::sequenced_policy, hpx::execution::parallel_policy,
hpx::execution::parallel_unsequenced_policy, hpx::execution::sequenced_task_policy,
hpx::execution::parallel_task_policy
```

Defined in header [hpx/execution.hpp](#)⁷³².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

⁷³² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/execution.hpp

namespace **hpx**

namespace **execution**

Typedefs

```
using sequenced_task_policy = detail::sequenced_task_policy_shim<sequenced_executor,  
hpx::traits::executor_parameters_type_t<sequenced_executor>>
```

Extension: The class `sequenced_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may not be parallelized (has to run sequentially).

The algorithm returns a future representing the result of the corresponding algorithm when invoked with the `sequenced_policy`.

```
using sequenced_policy = detail::sequenced_policy_shim<sequenced_executor,  
hpx::traits::executor_parameters_type_t<sequenced_executor>>
```

The class `sequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and require that a parallel algorithm's execution may not be parallelized.

```
using parallel_task_policy = detail::parallel_task_policy_shim<parallel_executor,  
hpx::traits::executor_parameters_type_t<parallel_executor>>
```

Extension: The class `parallel_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized.

The algorithm returns a future representing the result of the corresponding algorithm when invoked with the `parallel_policy`.

```
using parallel_policy = detail::parallel_policy_shim<parallel_executor,  
hpx::traits::executor_parameters_type_t<parallel_executor>>
```

The class `parallel_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized.

```
using parallel_unsequenced_task_policy =  
detail::parallel_unsequenced_task_policy_shim<parallel_executor,  
hpx::traits::executor_parameters_type_t<parallel_executor>>
```

The class `parallel_unsequenced_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized and vectorized.

```
using parallel_unsequenced_policy =  
detail::parallel_unsequenced_policy_shim<parallel_executor,  
hpx::traits::executor_parameters_type_t<parallel_executor>>
```

The class `parallel_unsequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized and vectorized.

```
using unsequenced_task_policy = detail::unsequenced_task_policy_shim<sequenced_executor,  
hpx::traits::executor_parameters_type_t<sequenced_executor>>
```

The class `unsequenced_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be vectorized.

```
using unsequenced_policy = detail::unsequenced_policy_shim<sequenced_executor,  
hpx::traits::executor_parameters_type_t<sequenced_executor>>
```

The class `unsequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be vectorized.

Variables

```
constexpr task_policy_tag task = { }
```

```
constexpr non_task_policy_tag non_task = { }
```

```
constexpr sequenced_policy seq = { }
```

Default sequential execution policy object.

```
constexpr parallel_policy par = { }
```

Default parallel execution policy object.

```
constexpr parallel_unsequenced_policy par_unseq = { }
```

Default vector execution policy object.

```
constexpr unsequenced_policy unseq = { }
```

Default vector execution policy object.

```
struct non_task_policy_tag : public hpx::execution::experimental::to_non_task_t
```

```
struct task_policy_tag : public hpx::execution::experimental::to_task_t
```

```
namespace experimental
```

```
    template<>
```

```
    struct is_execution_policy_mapping<non_task_policy_tag> : public true_type
```

```
    template<>
```

```
    struct is_execution_policy_mapping<task_policy_tag> : public true_type
```

hpx/executors/execution_policy_annotation.hpp

Defined in header `hpx/executors/execution_policy_annotation.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```

namespace hpx

    namespace execution

        namespace experimental

```

hpx/executors/thread_pool_scheduler.hpp

Defined in header `hpx/executors/thread_pool_scheduler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```

namespace hpx

    namespace execution

        namespace experimental

```

Typedefs

```

using thread_pool_scheduler = thread_pool_policy_scheduler<hpx::launch>

```

Variables

```

template<typename Sender> concept bulk_chunked_or_unchunked_sender =sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_t> ||sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_chunked_t> ||sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_unchunked_t>

```

```

template<typename Policy>

constexpr bool is_sequenced_policy_v = false

template<>

constexpr bool is_sequenced_policy_v<sequenced_policy> = true

template<>

constexpr bool is_sequenced_policy_v<unsequenced_policy> = true

template<typename Policy>

```

```
constexpr bool is_unsequenced_bulk_policy_v = false

template<>

constexpr bool is_unsequenced_bulk_policy_v<unsequenced_policy> = true

template<>

constexpr bool is_unsequenced_bulk_policy_v<parallel_unsequenced_policy> = true

template<typename Policy>

struct thread_pool_domain : public sync_wait_domain
```

Public Functions

```
template<bulk_chunked_or_unchunked_sender Sender, typename Env>
inline constexpr thread_pool_policy_scheduler<Policy> auto transform_sender(hpx::execution::experimental::ex
                                                                    Sender
                                                                    &&sndr,
                                                                    Env const
                                                                    &env) const
                                                                    noexcept

template<typename Sender,
typename Env> inline requires constexpr sender_invokes_algorithm_v< Sender,
hpx::execution::experimental::continues_on_t > auto transform_sender (hpx::execution::ex
Sender &&sndr, Env const &) const noexcept

template<typename Policy>

struct thread_pool_policy_scheduler
```

Public Types

```
using policy_type = Policy

using execution_category = std::conditional_t<std::is_same_v<Policy,
launch::sync_policy>, sequenced_execution_tag, parallel_execution_tag>
```

Public Functions

```
inline explicit constexpr thread_pool_policy_scheduler(Policy l = experimen-
                                                                    tal::detail::get_default_scheduler_policy<Policy>::c

inline explicit thread_pool_policy_scheduler(hpx::threads::thread_pool_base *pool,
                                                                    Policy l = experimen-
                                                                    tal::detail::get_default_scheduler_policy<Policy>::call())
                                                                    noexcept
```


hpx/executors/restricted_thread_pool_executor.hpp

Defined in header `hpx/executors/restricted_thread_pool_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Typedefs

using **restricted_thread_pool_executor** = *restricted_policy_executor*<*hpx::launch*>

template<typename **Policy**>

class **restricted_policy_executor**

Public Types

using **execution_category** = typename *embedded_executor*::*execution_category*

Associate the *parallel_execution_tag* executor tag type as a default with this executor.

using **executor_parameters_type** = typename
embedded_executor::*executor_parameters_type*

Public Functions

```
inline explicit restricted_policy_executor(std::size_t first_thread = 0, std::size_t
    num_threads = 1, threads::thread_priority
    priority = threads::thread_priority::default_,
    threads::thread_stacksize stacksize =
    threads::thread_stacksize::default_,
    threads::thread_schedule_hint schedulehint =
    { }, [[maybe_unused]] std::size_t
    hierarchical_threshold =
    hierarchical_threshold_default_)
```

Create a new parallel executor.

```
inline restricted_policy_executor(restricted_policy_executor const &other) noexcept
    cept(std::is_nothrow_copy_constructible_v<embedded_executor>)
```

```
inline restricted_policy_executor(restricted_policy_executor &&other) noexcept
```

```
inline restricted_policy_executor &operator=(restricted_policy_executor const &rhs) noexcept
    cept(std::is_nothrow_copy_assignable_v<embedded_executor>)
```

```
inline restricted_policy_executor &operator=(restricted_policy_executor &&rhs) noexcept  
inline constexpr hpx::execution::experimental::executor_scheduler<restricted_policy_executor> query(hpx::execution::experimental::executor_scheduler<restricted_policy_executor>&&rhs) const  
noexcept  
except(std::exception)
```

Private Types

```
using embedded_executor = hpx::execution::parallel_policy_executor<Policy>
```

Private Members

```
std::uint16_t first_thread_  
  
mutable std::atomic<std::size_t> os_thread_  
  
embedded_executor exec_
```

Private Static Attributes

```
static constexpr std::size_t hierarchical_threshold_default_ = 6
```

hpx/executors/current_executor.hpp

Defined in header `hpx/executors/current_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx  
  
    namespace parallel  
  
        namespace execution
```

Typedefs

```
typedef hpx::execution::parallel_executor instead  
  
namespace this_thread
```

Functions

hpx::execution::parallel_executor **get_executor**(*error_code* &ec = *throws*)

Returns a reference to the executor that was used to create the current thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw a *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

namespace **threads**

Functions

hpx::execution::parallel_executor **get_executor**(*thread_id_type* const &id, *error_code* &ec = *throws*)

Returns a reference to the executor that was used to create the given thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw a *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

hpx/executors/parallel_executor_aggregated.hpp

Defined in header *hpx/executors/parallel_executor_aggregated.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **execution**

hpx/executors/sequenced_executor.hpp

Defined in header *hpx/executors/sequenced_executor.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

struct **sequenced_executor**

#include <sequenced_executor.hpp> A *sequential_executor* creates groups of sequential execution agents which execute in the calling thread. The sequential order is given by the lexicographical order of indices in the index space.

Private Static Functions

```
template<typename F, typename ...Ts>
static inline decltype(auto) sync_execute_impl(F &&f, Ts&&... ts)
```

```
template<typename F, typename ...Ts>
static inline decltype(auto) async_execute_impl(hpx::threads::thread_description const &desc, F
&&f, Ts&&... ts)
```

```
template<typename Archive>
static inline constexpr void serialize(Archive&, unsigned int const) noexcept
```

Friends

```
friend class hpx::serialization::access
```

```
namespace experimental
```

hpx/executors/parallel_executor.hpp

Defined in header `hpx/executors/parallel_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

Typedefs

```
using parallel_executor = parallel_policy_executor<hpx::launch>
```

```
using parallel_executor_spawn_hierarchically = parallel_policy_executor<hpx::launch, true>
```

Functions

```

template<typename Policy>
constexpr parallel_policy_executor<Policy, true> to_hierarchical_spawning(parallel_policy_executor<Policy>
                                                                    &exec) noexcept

template<typename Policy>
constexpr parallel_policy_executor<Policy, true> to_hierarchical_spawning(parallel_policy_executor<Policy>
                                                                    &&exec) noexcept

template<typename Policy>
constexpr parallel_policy_executor<Policy, true> to_hierarchical_spawning(parallel_policy_executor<Policy>
                                                                    const &exec)
                                                                    noexcept

template<typename Executor>
constexpr Executor to_hierarchical_spawning(Executor &&exec) noexcept

template<typename Policy>
constexpr parallel_policy_executor<Policy> to_non_hierarchical_spawning(parallel_policy_executor<Policy,
                                                                    true> &exec)
                                                                    noexcept

template<typename Policy>
constexpr parallel_policy_executor<Policy> to_non_hierarchical_spawning(parallel_policy_executor<Policy,
                                                                    true> &&exec)
                                                                    noexcept

template<typename Policy>
constexpr parallel_policy_executor<Policy> to_non_hierarchical_spawning(parallel_policy_executor<Policy,
                                                                    true> const &exec)
                                                                    noexcept

template<typename Executor>
constexpr Executor to_non_hierarchical_spawning(Executor &&exec) noexcept

template<typename Policy, bool HierarchicalSpawning = false>
struct parallel_policy_executor : public hpx::execution::parallel_policy_executor_base<Policy>

```

Public Types

```

using base_type = parallel_policy_executor_base<Policy>

```

Public Functions

```
inline explicit constexpr parallel_policy_executor(threads::thread_priority priority,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_stacksize stacksize,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_schedule_hint
                                                    schedulehint, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(Policy l) noexcept

constexpr parallel_policy_executor() noexcept = default

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool, Policy l)
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool,
                                                    threads::thread_priority priority =
                                                    threads::thread_priority::default_,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

parallel_policy_executor(parallel_policy_executor const&) = default

parallel_policy_executor(parallel_policy_executor&&) = default

parallel_policy_executor &operator=(parallel_policy_executor const&) = default

parallel_policy_executor &operator=(parallel_policy_executor&&) = default

inline auto query(experimental::with_processing_units_count_t, std::size_t num_cores) const

template<typename Parameters>
inline std::size_t query(experimental::processing_units_count_t, Parameters &&params,
                        hpx::chrono::steady_duration const &iter_dur = hpx::chrono::null_duration,
                        std::size_t num_tasks = 0) const

inline auto query(experimental::with_first_core_t, std::size_t first_core) const noexcept

inline constexpr std::size_t query(experimental::get_first_core_t) const noexcept
```

```

inline auto query(experimental::get_processing_units_mask_t) const

inline auto query(experimental::get_cores_mask_t) const

template<typename Tag, typename Property>
inline auto query(Tag tag, Property &&prop) const

template<typename Tag>
inline auto query(Tag tag) const

template<typename F, typename ...Ts>
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename Future, typename ...Ts>
inline decltype(auto) then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename ...Ts>
inline void post(F &&f, Ts&&... ts) const

template<typename F, typename S, typename Future, typename ...Ts>
inline decltype(auto) bulk_then_execute(F &&f, S const &shape, Future &&predecessor,
                                         Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_sync_execute(F &&f, S const &shape, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline decltype(auto) to_non_par() const

template<typename Policy, bool HierarchicalSpawning>
constexpr hpx::execution::experimental::executor_scheduler<parallel_policy_executor<Policy, HierarchicalSpawning>

template<typename Policy>

struct parallel_policy_executor<Policy, true> : public
hpx::execution::parallel_policy_executor_base<Policy>

```

Public Types

```
using base_type = parallel_policy_executor_base<Policy>
```

Public Functions

```
inline explicit constexpr parallel_policy_executor(threads::thread_priority priority,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call(),
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_stacksize stacksize,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_schedule_hint
                                                    schedulehint, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(Policy l) noexcept

constexpr parallel_policy_executor() noexcept = default

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool, Policy l,
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool,
                                                    threads::thread_priority priority =
                                                    threads::thread_priority::default_,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call(),
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline constexpr void set_hierarchical_threshold(std::size_t const threshold) noexcept

parallel_policy_executor(parallel_policy_executor const&) = default

parallel_policy_executor(parallel_policy_executor&&) = default

parallel_policy_executor &operator=(parallel_policy_executor const&) = default

parallel_policy_executor &operator=(parallel_policy_executor&&) = default

~parallel_policy_executor() = default

inline auto query(experimental::with_processing_units_count_t, std::size_t num_cores) const

template<typename Parameters>
```



```

inline std::size_t query(experimental::processing_units_count_t, Parameters &&params,
                          hpx::chrono::steady_duration const &iter_dur = hpx::chrono::null_duration,
                          std::size_t num_tasks = 0) const

inline auto query(experimental::with_first_core_t, std::size_t first_core) const noexcept

inline constexpr std::size_t query(experimental::get_first_core_t) const noexcept

inline auto query(experimental::get_processing_units_mask_t) const

inline auto query(experimental::get_cores_mask_t) const

template<typename Tag, typename Property>
inline auto query(Tag tag, Property &&prop) const

template<typename Tag>
inline auto query(Tag tag) const

template<typename F, typename ...Ts>
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename Future, typename ...Ts>
inline decltype(auto) then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename ...Ts>
inline void post(F &&f, Ts&&... ts) const

template<typename F, typename S, typename Future, typename ...Ts>
inline decltype(auto) bulk_then_execute(F &&f, S const &shape, Future &&predecessor,
                                         Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_sync_execute(F &&f, S const &shape, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline decltype(auto) to_non_par() const

template<typename Policy>
struct parallel_policy_executor_base
    #include <parallel_executor.hpp> A parallel_executor creates groups of parallel execution agents
    which execute in threads implicitly created by the executor. This executor prefers continuing with the
    creating thread first before executing newly created threads.

    This executor conforms to the concepts of a TwoWayExecutor, and a BulkTwoWayExecutor

    Subclassed      by      hpx::execution::parallel_policy_executor<      Policy,      Hierarchi-
    calSpawning      >,      hpx::execution::parallel_policy_executor<      Policy,      true      >,
    hpx::execution::parallel_policy_executor< Policy >

```

Public Types

using **execution_category** = *std::conditional_t<std::is_same_v<Policy, launch::sync_policy>, sequenced_execution_tag, parallel_execution_tag>*

Associate the parallel_execution_tag executor tag type as a default with this executor, except if the given launch policy is sync.

using **executor_parameters_type** = *experimental::default_parameters*

Associate the default_parameters executor parameters type as a default with this executor.

Public Functions

inline **parallel_policy_executor_base**(*parallel_policy_executor_base* const &rhs) noexcept

inline *parallel_policy_executor_base* &**operator=**(*parallel_policy_executor_base* const &rhs)
noexcept

constexpr ~**parallel_policy_executor_base**() = default

template<typename **Parameters**>

inline *std::size_t* **processing_units_count**(*Parameters&&*, *hpx::chrono::steady_duration* const&
= *hpx::chrono::null_duration*, *std::size_t* = 0) const

Public Static Functions

template<typename **Self**>

static inline *Self* **with_num_cores**(*Self* self, *std::size_t* num_cores)

template<typename **Self**>

static inline *Self* **with_first_core**(*Self* self, *std::size_t* first_core) noexcept

Protected Functions

inline explicit constexpr **parallel_policy_executor_base**(*threads::thread_priority* priority,
threads::thread_stacksize stacksize =
threads::thread_stacksize::default_,
threads::thread_schedule_hint
schedulehint = {}, *Policy* l = *parallel::execution::detail::get_default_policy<Policy>::call*)
noexcept

Create a new parallel executor.

inline explicit constexpr **parallel_policy_executor_base**(*threads::thread_stacksize* stacksize,
threads::thread_schedule_hint
schedulehint = {}, *Policy* l = *parallel::execution::detail::get_default_policy<Policy>::call*)
noexcept

```

inline explicit constexpr parallel_policy_executor_base(threads::thread_schedule_hint
                                                         schedulehint, Policy l = paral-
                                                         lel::execution::detail::get_default_policy<Policy>::call
                                                         noexcept

inline explicit constexpr parallel_policy_executor_base(Policy l) noexcept

inline constexpr parallel_policy_executor_base() noexcept

inline explicit constexpr parallel_policy_executor_base(threads::thread_pool_base *pool,
                                                         Policy l) noexcept

inline explicit constexpr parallel_policy_executor_base(threads::thread_pool_base *pool,
                                                         threads::thread_priority priority =
                                                         threads::thread_priority::default_,
                                                         threads::thread_stacksize stacksize =
                                                         threads::thread_stacksize::default_,
                                                         threads::thread_schedule_hint
                                                         schedulehint = {}, Policy l = paral-
                                                         lel::execution::detail::get_default_policy<Policy>::call

namespace experimental

    template<typename Executor>

    struct executor_scheduler

namespace parallel

    namespace execution

```

hpx/executors/explicit_scheduler_executor.hpp

Defined in header `hpx/executors/explicit_scheduler_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```

namespace hpx

    namespace execution

        namespace experimental

```

Functions

```
template<typename BaseScheduler>
explicit explicit_scheduler_executor(BaseScheduler &&sched) -> explicit_scheduler_executor<std::decay_t<BaseScheduler>>

template<typename BaseScheduler>
struct explicit_scheduler_executor
```

hpx/executors/service_executors.hpp

Defined in header `hpx/executors/service_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
        namespace execution
```

hpx/executors/execution_policy_scheduling_property.hpp

Defined in header `hpx/executors/execution_policy_scheduling_property.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

hpx/executors/fork_join_executor.hpp

Defined in header `hpx/executors/fork_join_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/exception_list.hpp

Defined in header `hpx/executors/exception_list.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

hpx/executors/execution_policy_mappings.hpp

Defined in header `hpx/executors/execution_policy_mappings.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Variables

```
template<typename Tag>
```

```
constexpr bool is_execution_policy_mapping_v = is_execution_policy_mapping<Tag>::value
```

```
constexpr struct hpx::execution::experimental::to_non_par_t to_non_par
```

```
constexpr struct hpx::execution::experimental::to_par_t to_par
```

```
constexpr struct hpx::execution::experimental::to_non_task_t to_non_task
```

```
constexpr struct hpx::execution::experimental::to_task_t to_task
```

```
constexpr struct hpx::execution::experimental::to_non_unseq_t to_non_unseq
```

```
constexpr struct hpx::execution::experimental::to_unseq_t to_unseq
```

```
template<typename Tag>
```

```
struct is_execution_policy_mapping : public false_type
```

```
template<>
```

```
struct is_execution_policy_mapping<to_non_par_t> : public true_type
```

```
template<>
```

```
struct is_execution_policy_mapping<to_non_task_t> : public true_type
template<>
struct is_execution_policy_mapping<to_non_unseq_t> : public true_type
template<>
struct is_execution_policy_mapping<to_par_t> : public true_type
template<>
struct is_execution_policy_mapping<to_task_t> : public true_type
template<>
struct is_execution_policy_mapping<to_unseq_t> : public true_type

struct to_non_par_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
template<execution_policy ExPolicy>
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires    = { t.to_non_par()
```

```
struct to_non_task_t
```

Subclassed by *hpx::execution::non_task_policy_tag*

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
template<execution_policy ExPolicy>
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_non_task()
```

```
struct to_non_unseq_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_non_unseq()
```

```
struct to_par_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_par()
```

```
struct to_task_t
```

Subclassed by *hpx::execution::task_policy_tag*

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_task()
```

```
struct to_unseq_t
```

Public Functions

```
inline constexpr decltype(auto) operator()(Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator()(ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_unseq()
```

hpx/executors/annotating_executor.hpp

Defined in header `hpx/executors/annotating_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
template<executor_any BaseExecutor>
```

```
struct annotating_executor
```

```
#include <annotating_executor.hpp> An annotating_executor wraps any other executor and adds the capability to add annotations to the launched threads.
```

Public Functions

```
template<executor_any Executor>
```

```
inline explicit constexpr annotating_executor(Executor &&exec, char const *annotation = nullptr)
```

```
template<executor_any Executor>
```

```
inline explicit annotating_executor(Executor &&exec, std::string annotation)
```


hpx/executors/scheduler_executor.hpp

Defined in header `hpx/executors/scheduler_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Functions

```

template<typename BaseScheduler>
explicit scheduler_executor(BaseScheduler &&sched) ->
    scheduler_executor<std::decay_t<BaseScheduler>>

template<typename BaseScheduler>
struct scheduler_executor

```

hpx/executors/std_execution_policy.hpp

Defined in header `hpx/executors/std_execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/execution_policy_parameters.hpp

Defined in header `hpx/executors/execution_policy_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/thread_pool_continues_on_sender.hpp

Defined in header `hpx/executors/thread_pool_continues_on_sender.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Domain-optimized `continues_on` sender for HPX thread pool schedulers.

When `stdexec::continues_on` is applied with an HPX `thread_pool_scheduler`, the generic `stdexec` implementation creates two operation states: one for the source sender and one for the scheduler hop (`schedule_from`). This double-state overhead adds ~1 us per task in microbenchmarks.

This header provides a custom sender that replaces the generic path by:

1. Connecting the source sender to a lightweight receiver that captures the downstream receiver and the scheduler.
2. On `set_value`: if we are already on the same HPX thread pool, forwarding inline; otherwise, posting a single HPX task to forward the values.

This eliminates the intermediate `__storage_for_t`, the second operation state, and the `run_loop` overhead.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

hpx/executors/executor_scheduler.hpp

Defined in header `hpx/executors/executor_scheduler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            template<typename Executor>
```

```
            struct executor_scheduler
```

hpx/executors/datapar/execution_policy.hpp

Defined in header `hpx/executors/datapar/execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/datapar/execution_policy_mappings.hpp

Defined in header `hpx/executors/datapar/execution_policy_mappings.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

filesystem

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/filesystem/api.hpp

Defined in header `hpx/filesystem/api.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

This file provides a compatibility layer using Boost.Filesystem for the C++17 filesystem library. It is *not* intended to be a complete compatibility layer. It only contains functions required by the HPX codebase. It also provides some functions only available in Boost.Filesystem when using C++17 filesystem.

namespace **hpx**

namespace **filesystem**

Functions

inline path **initial_path**()

inline *std::string* **to_string**(path const &p)

inline *std::string* **basename**(path const &p)

inline path **canonical**(path const &p, path const &base)

inline path **canonical**(path const &p, path const &base, *std::error_code* &ec)

namespace **filesystem**

functional

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::invoke_fused, **hpx::invoke_fused_r**

Defined in header [hpx/functional.hpp](#)⁷³³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

Functions

template<typename **F**, typename **Tuple**>

constexpr detail::invoke_fused_result_t<*F*, *Tuple*> **invoke_fused**(*F* &&*f*, *Tuple* &&*t*) noexcept(
 cept(noexcept(detail::invoke_fused_impl(detail::fused_index,
 HPX_FORWARD(*F*, *f*),
 HPX_FORWARD(*Tuple*, *t*))))

Invokes the given callable object *f* with the content of the sequenced type *t* (tuples, pairs).

Note: This function is similar to `std::apply` (C++17). The difference between `hpx::invoke` and `hpx::invoke_fused` is that the later unpacks the tuples while the former cannot. Turning a tuple into a parameter pack is not a trivial operation which makes `hpx::invoke_fused` rather useful.

Parameters

⁷³³ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

- **f** – Must be a callable object. If **f** is a member function pointer, the first argument in the sequenced type will be treated as the callee (this object).
- **t** – A type whose contents are accessible through a call to `hpx::get`.

Throws

`std::exception` – like objects thrown by call to object **f** with the arguments contained in the sequenceable type **t**.

Returns

The result of the callable object when it's called with the content of the given sequenced type.

```
template<typename R, typename F, typename Tuple>
constexpr R invoke_fused_r(F &&f, Tuple &&t) noexcept
    {
        cept(noexcept(detail::invoke_fused_impl(detail::fused_index_pack_t<Tuple>{}),
        HPX_FORWARD(F, f), HPX_FORWARD(Tuple, t))))
    }
```

Invokes the given callable object **f** with the content of the sequenced type **t** (tuples, pairs).

Note: This function is similar to `std::apply` (C++17). The difference between `hpx::invoke` and `hpx::invoke_fused` is that the later unpacks the tuples while the former cannot. Turning a tuple into a parameter pack is not a trivial operation which makes `hpx::invoke_fused` rather useful.

Note: The difference between `hpx::invoke_fused` and `hpx::invoke_fused_r` is that the later allows to specify the return type as well.

Parameters

- **f** – Must be a callable object. If **f** is a member function pointer, the first argument in the sequenced type will be treated as the callee (this object).
- **t** – A type whose contents are accessible through a call to `hpx::get`.

Throws

`std::exception` – like objects thrown by call to object **f** with the arguments contained in the sequenceable type **t**.

Template Parameters

R – The result type of the function when it's called with the content of the given sequenced type.

Returns

The result of the callable object when it's called with the content of the given sequenced type.

hpx::reference_wrapper, hpx::ref, hpx::cref

Defined in header `hpx/functionality.hpp`⁷³⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename T>
```

```
struct reference_wrapper<T, std::enable_if_t<traits::needs_reference_semantics_v<T>>>
```

⁷³⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functionality.hpp

Public Types

```
using type = T
```

Public Functions

```
reference_wrapper() = default
```

```
template<typename U, typename Enable = std::enable_if_t<!std::is_same_v<std::decay_t<U>,  
reference_wrapper>>>
```

```
inline reference_wrapper(U &&val)
```

```
inline reference_wrapper(reference_wrapper const &rhs)
```

```
reference_wrapper(reference_wrapper &&rhs) = default
```

```
inline reference_wrapper &operator=(reference_wrapper const &rhs)
```

```
reference_wrapper &operator=(reference_wrapper &&rhs) = default
```

```
inline operator type() const
```

```
inline type get() const
```

Private Members

```
T ptr = {}
```

```
template<typename T>
```

```
struct unwrap_reference<::hpx::reference_wrapper<T>>
```

Public Types

```
using type = T
```

```
template<typename T>
```

```
struct unwrap_reference<::hpx::reference_wrapper<T>> const>
```

Public Types

```
using type = T
```

```
namespace hpx
```

```
    Top level namespace.
```

Functions

```
template<typename T>
reference_wrapper(T&) -> reference_wrapper<T>

template<typename T>
constexpr reference_wrapper<T> ref(T &val) noexcept

template<typename T>
void ref(T const&&) = delete

template<typename T>
constexpr reference_wrapper<T> ref(reference_wrapper<T> val) noexcept

template<typename T>
constexpr reference_wrapper<T const> cref(T const &val) noexcept

template<typename T>
void cref(T const&&) = delete

template<typename T>
constexpr reference_wrapper<T const> cref(reference_wrapper<T> val) noexcept

template<typename T>
reference_wrapper<T> ref(T &&val) noexcept

template<typename T, typename Enable = void>

struct reference_wrapper : public std::reference_wrapper<T>
```

Public Functions

```
reference_wrapper() = delete

template<typename T> needs_reference_semantics_v< T > > >
```

Public Types

```
using type = T
```

Public Functions

```
reference_wrapper() = default

template<typename U, typename Enable = std::enable_if_t!std::is_same_v<std::decay_t<U>,
reference_wrapper>>>
inline reference_wrapper(U &&val)

inline reference_wrapper(reference_wrapper const &rhs)

reference_wrapper(reference_wrapper &&rhs) = default
```

```

inline reference_wrapper &operator=(reference_wrapper const &rhs)
reference_wrapper &operator=(reference_wrapper &&rhs) = default
inline operator  type() const
inline type get() const

```

Private Members

```
T ptr = {}
```

```
namespace traits
```

Variables

```

template<typename T>
constexpr bool needs_reference_semantics_v = needs_reference_semantics<T>::value
template<typename T>
struct needs_reference_semantics : public false_type
    Subclassed by hpx::traits::needs_reference_semantics< T const >
template<typename T>
struct needs_reference_semantics<T const> : public hpx::traits::needs_reference_semantics<T>

```

```
namespace util
```

```
template<typename T> reference_wrapper< T > >
```

Public Types

```
using type = T
```

```
template<typename T> reference_wrapper< T > const >
```

Public Types

```
using type = T
```

hpx::bind_back

Defined in header [hpx/functional.hpp](#)⁷³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

Functions

```
template<typename F, typename ...Ts>
constexpr hpx::detail::bound_back<std::decay_t<F>, util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind
```

Function templates `bind_back` generate a forwarding call wrapper for `f`. Calling this wrapper is equivalent to invoking `f` with its last `sizeof...(Ts)` parameters bound to `vs`.

Parameters

- **f** – Callable object (function object, pointer to function, reference to function, pointer to member function, or pointer to data member) that will be bound to some arguments
- **vs** – list of the arguments to bind to the last `sizeof...(Ts)` parameters of `f`

Returns

A function object of type `T` that is unspecified, except that the types of objects returned by two calls to `hpx::bind_back` with the same arguments are the same.

```
template<typename F>
constexpr std::decay_t<F> bind_back(F &&f)
```

namespace **serialization**

Functions

```
template<typename Archive, typename F, typename ...Ts>
void serialize(Archive &ar, ::hpx::detail::bound_back<F, Ts...> &bound, unsigned int const version =
    0)
```

hpx::mem_fn

Defined in header [hpx/functional.hpp](#)⁷³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

⁷³⁵ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

⁷³⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

Functions

```
template<typename M, typename C>
constexpr detail::mem_fn<M C::*> mem_fn(M C::* pm) noexcept
```

Function template `hpx::mem_fn` generates wrapper objects for pointers to members, which can store, copy, and invoke a pointer to member. Both references and pointers (including smart pointers) to an object can be used when invoking a `hpx::mem_fn`.

Parameters

pm – pointer to member that will be wrapped

Returns

a call wrapper of unspecified type with the following member:

```
template <typename... Ts>
constexpr typename util::invoke_result_t<MemberPointer, Ts...>::type
operator()(Ts&&... vs) noexcept;
```

Let `fn` be the call wrapper returned by a call to `hpx::mem_fn` with a pointer to member `pm`. Then the expression `fn(t,a2,...,aN)` is equivalent to `HPX_INVOKE(pm,t,a2,...,aN)`. Thus, the return type of `operator()` is `std::result_of<decltype(pm)(Ts&&...)>::type` or equivalently `std::invoke_result_t<decltype(pm),Ts&&...>`, and the value in `noexcept` specifier is equal to `std::is_nothrow_invocable_v<decltype(pm),Ts&&...>`. Each argument in `vs` is perfectly forwarded, as if by `std::forward<Ts>(vs)...`.

```
template<typename R, typename C, typename ...Ps>
constexpr detail::mem_fn<R (C::*)(Ps...)> mem_fn(R (C::* pm)(Ps...)) noexcept
```

Function template `hpx::mem_fn` generates wrapper objects for pointers to members, which can store, copy, and invoke a pointer to member. Both references and pointers (including smart pointers) to an object can be used when invoking a `hpx::mem_fn`.

Parameters

pm – pointer to member that will be wrapped

Returns

a call wrapper of unspecified type with the following member:

```
template <typename... Ts>
constexpr typename util::invoke_result_t<MemberPointer, Ts...>::type
operator()(Ts&&... vs) noexcept;
```

Let `fn` be the call wrapper returned by a call to `hpx::mem_fn` with a pointer to member `pm`. Then the expression `fn(t,a2,...,aN)` is equivalent to `HPX_INVOKE(pm,t,a2,...,aN)`. Thus, the return type of `operator()` is `std::result_of<decltype(pm)(Ts&&...)>::type` or equivalently `std::invoke_result_t<decltype(pm),Ts&&...>`, and the value in `noexcept` specifier is equal to `std::is_nothrow_invocable_v<decltype(pm),Ts&&...>`. Each argument in `vs` is perfectly forwarded, as if by `std::forward<Ts>(vs)...`.

```
template<typename R, typename C, typename ...Ps>
constexpr detail::mem_fn<R (C::*)(Ps...) const> mem_fn(R (C::* pm)(Ps...) const) noexcept
```

Function template `hpx::mem_fn` generates wrapper objects for pointers to members, which can store, copy, and invoke a pointer to member. Both references and pointers (including smart pointers) to an object can be used when invoking a `hpx::mem_fn`.

Parameters

pm – pointer to member that will be wrapped

Returns

a call wrapper of unspecified type with the following member:

```
template <typename... Ts>
constexpr typename util::invoke_result<MemberPointer, Ts...>::type
operator()(Ts&&... vs) noexcept;
```

Let `fn` be the call wrapper returned by a call to `hpx::mem_fn` with a pointer to member `pm`. Then the expression `fn(t,a2,...,aN)` is equivalent to `HPX_INVOKE(pm,t,a2,...,aN)`. Thus, the return type of `operator()` is `std::result_of<decltype(pm)(Ts&&...)>::type` or equivalently `std::invoke_result_t<decltype(pm),Ts&&...>`, and the value in `noexcept` specifier is equal to `std::is_nothrow_invocable_v<decltype(pm),Ts&&...>`. Each argument in `vs` is perfectly forwarded, as if by `std::forward<Ts>(vs)...`.

hpx::function_ref

Defined in header `hpx/functionality.hpp`⁷³⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

template<typename **Sig**>

class **function_ref**

#include <function_ref.hpp> **function_ref** class is a vocabulary type with reference semantics for passing entities to call.

An example use case that benefits from higher-order functions is `retry(n, f)` which attempts to call `f` up to `n` times synchronously until success. This example might model the real-world scenario of repeatedly querying a flaky web service.

```
using payload = std::optional< /* ... */ >;
// Repeatedly invokes `action` up to `times` repetitions.
// Immediately returns if `action` returns a valid `payload`.
// Returns `std::nullopt` otherwise.
payload retry(size_t times, /* ????? */ action);
```

The passed-in action should be a callable entity that takes no arguments and returns a payload. This can be done with function pointers, `hpx::function` or a template but it is much simpler with `function_ref` as seen below:

```
payload retry(size_t times, function_ref<payload()> action);
```

template<typename **R**, typename ...**Ts**>

class **function_ref**<*R*(*Ts*...)>

⁷³⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functionality.hpp

Public Functions

```

template<typename F, typename FD = std::decay_t<F>, typename Enable =
std::enable_if_t<!std::is_same_v<FD, function_ref> && is_invocable_r_v<R, F&, Ts...>>>
inline function_ref(F &&f)

inline function_ref(function_ref const &other) noexcept

template<typename F, typename FD = std::decay_t<F>, typename Enable =
std::enable_if_t<!std::is_same_v<FD, function_ref> && is_invocable_r_v<R, F&, Ts...>>>
inline function_ref &operator=(F &&f)

inline function_ref &operator=(function_ref const &other) noexcept

template<typename F, typename T = std::remove_reference_t<F>, typename Enable =
std::enable_if_t<!std::is_pointer_v<T>>>
inline void assign(F &&f)

template<typename T>
inline void assign(std::reference_wrapper<T> f_ref) noexcept

template<typename T>
inline void assign(T *f_ptr) noexcept

inline void swap(function_ref &f) noexcept

inline R operator()(Ts... vs) const

inline std::size_t get_function_address() const

inline char const *get_function_annotation() const

inline hpx::tracing::annotation_handle get_function_annotation_tracing() const

```

Protected Attributes

```
R (*vp_ptr)(void*, Ts&&...)
```

```
void *object
```

Private Types

```
using VTable = util::detail::function_ref_vtable<R(Ts...)>
```

Private Static Functions

```
template<typename T>
static inline constexpr VTable const *get_vtable() noexcept
```

```
namespace util
```

hpx::bind_front

Defined in header `hpx/functional.hpp`⁷³⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Top level namespace.

Functions

```
template<typename F, typename ...Ts>
constexpr detail::bound_front<std::decay_t<F>, util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind_front(F &&f, Ts...)
```

Function template `bind_front` generates a forwarding call wrapper for `f`. Calling this wrapper is equivalent to invoking `f` with its first `sizeof...(Ts)` parameters bound to `vs`.

Parameters

- **f** – Callable object (function object, pointer to function, reference to function, pointer to member function, or pointer to data member) that will be bound to some arguments
- **vs** – list of the arguments to bind to the first or `sizeof...(Ts)` parameters of `f`

Returns

A function object of type `T` that is unspecified, except that the types of objects returned by two calls to `hpx::bind_front` with the same arguments are the same.

```
template<typename F>
constexpr std::decay_t<F> bind_front(F &&f)
```

```
namespace serialization
```

⁷³⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

Functions

```
template<typename Archive, typename F, typename ...Ts>
void serialize(Archive &ar, ::hpx::detail::bound_front<F, Ts...> &bound, unsigned int const version =
    0)
```

hpx::move_only_function

Defined in header [hpx/functional.hpp](#)⁷³⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level namespace.

```
template<typename Sig, bool Serializable = false>
```

```
class move_only_function
```

#include <move_only_function.hpp> Class template *hpx::move_only_function* is a general-purpose polymorphic function wrapper. *hpx::move_only_function* objects can store and invoke any constructible (not required to be move constructible) Callable target [§21.2](#); functions, lambda expressions, bind expressions, or other function objects, as well as pointers to member functions and pointers to member objects.

The stored callable object is called the target of *hpx::move_only_function*. If an *hpx::move_only_function* contains no target, it is called empty. Unlike *hpx::function*, invoking an empty *hpx::move_only_function* results in undefined behavior.

*hpx::move_only_function*s supports every possible combination of cv-qualifiers, ref-qualifiers, and noexcept-specifiers not including volatile provided in its template parameter. These qualifiers and specifier (if any) are added to its operator(). *hpx::move_only_function* satisfies the requirements of MoveConstructible and MoveAssignable, but does not satisfy CopyConstructible or CopyAssignable.

```
template<typename R, typename ...Ts, bool Serializable>
```

```
class move_only_function<R(Ts...), Serializable> : public util::detail::basic_function<R(Ts...), false,
    Serializable>
```

Public Types

```
using result_type = R
```

Public Functions

```
inline constexpr move_only_function(std::nullptr_t = nullptr) noexcept
```

```
move_only_function(move_only_function const&) = delete
```

```
move_only_function(move_only_function&&) noexcept = default
```

```
move_only_function &operator=(move_only_function const&) = delete
```

⁷³⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

```
move_only_function &operator=(move_only_function&&) noexcept = default

~move_only_function() = default

template<typename F, typename FD = std::decay_t<F>, typename Enable1 =
std::enable_if_t<!std::is_same_v<FD, move_only_function>>, typename Enable2 =
std::enable_if_t<is_invocable_r_v<R, FD&, Ts...>>>
inline move_only_function(F &&f)

template<typename F, typename FD = std::decay_t<F>, typename Enable1 =
std::enable_if_t<!std::is_same_v<FD, move_only_function>>, typename Enable2 =
std::enable_if_t<is_invocable_r_v<R, FD&, Ts...>>>
inline move_only_function &operator=(F &&f)
```

Private Types

```
using base_type = util::detail::basic_function<R(Ts...), false, Serializable>
```

```
namespace distributed
```

Typedefs

```
template<typename Sig>

using move_only_function = hpx::move_only_function<Sig, true>
```

hpx::function

Defined in header [hpx/functional.hpp](#)⁷⁴⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
    Top level namespace.
```

```
    template<typename Sig, bool Serializable = false>
```

```
    class function
```

```
        #include <function.hpp> Class template hpx::function is a general-purpose polymorphic function wrapper.
        Instances of hpx::function can store, copy, and invoke any CopyConstructible Callable target §8212;
        functions, lambda expressions, bind expressions, or other function objects, as well as pointers to member
        functions and pointers to data members. The stored callable object is called the target of hpx::function.
        If an hpx::function contains no target, it is called empty. Invoking the target of an empty hpx::function
        results in hpx::error::bad_function_call exception being thrown. hpx::function satisfies the requirements
        of CopyConstructible and CopyAssignable.
```

```
    template<typename R, typename ...Ts, bool Serializable>
```

```
    class function<R(Ts...), Serializable> : public util::detail::basic_function<R(Ts...), true, Serializable>
```

⁷⁴⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

Public Types

```
using result_type = R
```

Public Functions

```
inline constexpr function(std::nullptr_t = nullptr) noexcept
function(function const&) = default
function(function&&) noexcept = default
function &operator=(function const&) = default
function &operator=(function&&) noexcept = default
~function() = default

template<typename F, typename FD = std::decay_t<F>, typename Enable1 =
std::enable_if_t<!std::is_same_v<FD, function>>, typename Enable2 =
std::enable_if_t<is_invocable_r_v<R, FD&, Ts...>>>
inline function(F &&f)

template<typename F, typename FD = std::decay_t<F>, typename Enable1 =
std::enable_if_t<!std::is_same_v<FD, function>>, typename Enable2 =
std::enable_if_t<is_invocable_r_v<R, FD&, Ts...>>>
inline function &operator=(F &&f)
```

Private Types

```
using base_type = util::detail::basic_function<R(Ts...), true, Serializable>
```

```
namespace distributed
```

Typedefs

```
template<typename Sig>
using function = hpx::function<Sig, true>
```

hpx::bind, **hpx::placeholders::_1**, **hpx::placeholders::_2**, ..., **hpx::placeholders::_9**

Defined in header `hpx/functionality.hpp`⁷⁴¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

Top level namespace.

⁷⁴¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functionality.hpp

Functions

```
template<typename F, typename ...Ts>
constexpr detail::bound<std::decay_t<F>, util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind(F
&&f,
Ts&&...
vs)
```

The function template *bind* generates a forwarding call wrapper for *f*. Calling this wrapper is equivalent to invoking *f* with some of its arguments bound to *vs*.

Parameters

- **f** – Callable object (function object, pointer to function, reference to function, pointer to member function, or pointer to data member) that will be bound to some arguments
- **vs** – list of arguments to bind, with the unbound arguments replaced by the placeholders `_1, _2, _3...` of namespace `hpx::placeholders`

Returns

A function object of unspecified type *T*, for which

```
hpx::is_bind_expression<T>::value == true.
```

namespace placeholders

The `hpx::placeholders` namespace contains the placeholder objects `[_1, ..., _N]` where *N* is an implementation defined maximum number.

When used as an argument in a `hpx::bind` expression, the placeholder objects are stored in the generated function object, and when that function object is invoked with unbound arguments, each placeholder `_N` is replaced by the corresponding *N*th unbound argument.

The types of the placeholder objects are `DefaultConstructible` and `CopyConstructible`, their default copy/move constructors do not throw exceptions, and for any placeholder `_N`, the type `hpx::is_placeholder<decltype(_N)>` is defined, where `hpx::is_placeholder<decltype(_N)>` is derived from `std::integral_constant<int, N>`.

Variables

```
constexpr detail::placeholder<1> _1 = { }
```

```
constexpr detail::placeholder<2> _2 = { }
```

```
constexpr detail::placeholder<3> _3 = { }
```

```
constexpr detail::placeholder<4> _4 = { }
```

```
constexpr detail::placeholder<5> _5 = { }
```

```
constexpr detail::placeholder<6> _6 = { }
```



```
constexpr detail::placeholder<7> _7 = { }
```

```
constexpr detail::placeholder<8> _8 = { }
```

```
constexpr detail::placeholder<9> _9 = { }
```

namespace **serialization**

Functions

```
template<typename Archive, typename F, typename ...Ts>
void serialize(Archive &ar, ::hpx::detail::bound<F, Ts...> &bound, unsigned int const version = 0)
```

```
template<typename Archive, std::size_t I>
constexpr void serialize(Archive&, ::hpx::detail::placeholder<I>&, unsigned int const = 0) noexcept
```

hpx::is_placeholder

Defined in header [hpx/functional.hpp](#)⁷⁴².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

```
template<typename T>
```

```
struct is_placeholder
```

#include <is_placeholder.hpp> If T is a standard, Boost, or HPX placeholder (`_1`, `_2`, `_3`, ...) then this template is derived from `std::integral_constant<int,1>`, `std::integral_constant<int,2>`, `std::integral_constant<int,3>`, respectively. Otherwise, it is derived from `std::integral_constant<int,0>`.

The template may be specialized for any user-defined T type: the specialization must satisfy *UnaryTypeTrait* with base characteristic of `std::integral_constant<int,N>` with N>0 to indicate that T should be treated as N'th placeholder type. `hpx::bind` uses `hpx::is_placeholder` to detect placeholders for unbound arguments.

hpx::is_bind_expression

Defined in header [hpx/functional.hpp](#)⁷⁴³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level namespace.

⁷⁴² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

⁷⁴³ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

Variables

```
template<typename T>
```

```
constexpr bool is_bind_expression_v = is_bind_expression<T>::value
```

```
template<typename T>
```

```
struct is_bind_expression : public std::is_bind_expression<T>
```

#include <is_bind_expression.hpp> If T is the type produced by a call to *hpx::bind*, this template is derived from *std::true_type*. For any other type, this template is derived from *std::false_type*.

This template may be specialized for a user-defined type T to implement *UnaryTypeTrait* with base characteristic of *std::true_type* to indicate that T should be treated by *hpx::bind* as if it were the type of a bind subexpression: when a bind-generated function object is invoked, a bound argument of this type will be invoked as a function object and will be given all the unbound arguments passed to the bind-generated object.

Subclassed by *hpx::is_bind_expression< T const >*

```
template<typename T>
```

```
struct is_bind_expression<T const> : public hpx::is_bind_expression<T>
```

hpx::experimental::scope_exit

Defined in header *hpx/experimental/scope.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level namespace.

namespace **experimental**

Functions

```
template<typename F>
```

```
auto scope_exit(F &&f)
```

The class template *scope_exit* is a general-purpose scope guard intended to call its exit function when a scope is exited.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

hpx::experimental::scope_fail

Defined in header `hpx/experimental/scope.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level namespace.

namespace **experimental**

Functions

```
template<typename F>
auto scope_fail(F &&f)
```

The class template `scope_fail` is a general-purpose scope guard intended to call its exit function when a scope is exited via an exception.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

hpx::experimental::scope_success

Defined in header `hpx/experimental/scope.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level namespace.

namespace **experimental**

Functions

```
template<typename F>
auto scope_success(F &&f)
```

The class template `scope_success` is a general-purpose scope guard intended to call its exit function when a scope is normally exited.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

futures

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::future, **hpx::shared_future,** **hpx::make_future,** **hpx::make_shared_future,**
hpx::make_ready_future, **hpx::make_ready_future_alloc,** **hpx::make_ready_future_at,**
hpx::make_ready_future_after, **hpx::make_exceptional_future**

Defined in header [hpx/future.hpp](#)⁷⁴⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

template<typename **R**, typename **U**>
hpx::future<R> make_future(hpx::future<U> &&f)
Converts any future of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

template<typename **R**, typename **U**, typename **Conv**>
hpx::future<R> make_future(hpx::future<U> &&f, Conv &&conv)
Converts any future of type **U** to any other future of type **R** based on a given conversion function: **R conv(U)**.

template<typename **R**, typename **U**>
hpx::future<R> make_future(hpx::shared_future<U> f)
Converts any *shared_future* of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

template<typename **R**, typename **U**, typename **Conv**>
hpx::future<R> make_future(hpx::shared_future<U> f, Conv &&conv)
Converts any future of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

template<typename **R**>
hpx::shared_future<R> make_shared_future(hpx::future<R> &&f) noexcept
Converts any future or *shared_future* of type **T** to a corresponding *shared_future* of type **T**.

template<typename **R**>
hpx::shared_future<R> &make_shared_future(hpx::shared_future<R> &f) noexcept
Converts any future or *shared_future* of type **T** to a corresponding *shared_future* of type **T**.

template<typename **R**>
hpx::shared_future<R> &&make_shared_future(hpx::shared_future<R> &&f) noexcept
Converts any future or *shared_future* of type **T** to a corresponding *shared_future* of type **T**.

template<typename **R**>
hpx::shared_future<R> const &make_shared_future(hpx::shared_future<R> const &f) noexcept
Converts any future or *shared_future* of type **T** to a corresponding *shared_future* of type **T**.

template<typename **T**, typename **Allocator**, typename ...**Ts**>

⁷⁴⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

```
std::enable_if_t<std::is_constructible_v<T, Ts&&...> || std::is_void_v<T>, future<T>> make_ready_future_alloc(Allocator const
&a,
Ts&&...
ts)
```

Creates a pre-initialized future object with allocator (extension)

```
template<typename T, typename ...Ts>
std::enable_if_t<std::is_constructible_v<T, Ts&&...> || std::is_void_v<T>, future<T>> make_ready_future(Ts&&...
ts)
```

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

```
template<int DeductionGuard = 0, typename Allocator, typename T>
future<hpx::util::decay_unwrap_t<T>> make_ready_future_alloc(Allocator const &a, T &&init)
```

```
template<int DeductionGuard = 0, typename T>
future<hpx::util::decay_unwrap_t<T>> make_ready_future(T &&init)
```

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

```
template<typename T>
future<T> make_exceptional_future(std::exception_ptr const &e)
```

Creates a pre-initialized future object which holds the given error (extension)

```
template<typename T, typename E>
future<T> make_exceptional_future(E e)
```

Creates a pre-initialized future object which holds the given error (extension)

```
template<int DeductionGuard = 0, typename T>
future<hpx::util::decay_unwrap_t<T>> make_ready_future_at(hpx::chrono::steady_time_point const
&abs_time, T &&init)
```

Creates a pre-initialized future object which gets ready at a given point in time (extension)

```
template<int DeductionGuard = 0, typename T>
future<hpx::util::decay_unwrap_t<T>> make_ready_future_after(hpx::chrono::steady_duration const
&rel_time, T &&init)
```

Creates a pre-initialized future object which gets ready after a given point in time (extension)

```
template<typename Allocator>
inline future<void> make_ready_future_alloc(Allocator const &a)
```

```
future<void> make_ready_future()
```

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

```
inline future<void> make_ready_future_at(hpx::chrono::steady_time_point const &abs_time)
```

Creates a pre-initialized future object which gets ready at a given point in time (extension)

```
inline future<void> make_ready_future_after(hpx::chrono::steady_duration const &rel_time)
```

Creates a pre-initialized future object which gets ready after a given point in time (extension)

```
template<typename R>
```

```
class future : public hpx::lcos::detail::future_base<future<R>, R>
```

`#include <future_fwd.hpp>` The class template `hpx::future` provides a mechanism to access the result of asynchronous operations:

- An asynchronous operation (created via `hpx::async`, `hpx::packaged_task`, or `hpx::promise`) can provide a `hpx::future` object to the creator of that asynchronous operation.
- The creator of the asynchronous operation can then use a variety of methods to query, wait for, or extract a value from the `hpx::future`. These methods may block if the asynchronous operation has not yet provided a value.
- When the asynchronous operation is ready to send a result to the creator, it can do so by modifying shared state (e.g. `hpx::promise::set_value`) that is linked to the creator's `hpx::future`. Note that `hpx::future` references shared state that is not shared with any other asynchronous return objects (as opposed to `hpx::shared_future`).

Public Types

using **result_t_type** = *R*

using **shared_state_type** = *base_type::shared_state_type*

Public Functions

constexpr **future**() noexcept = default

future(*future* &&other) noexcept = default

future(*future* const &other) noexcept = delete

inline **future**(*future*<*future*> &&other) noexcept

inline **future**(*future*<*shared_future*<*R*>> &&other) noexcept

template<typename **T**>

inline **future**(*future*<*T*> &&other, *std::enable_if_t<std::is_void_v<R> && !traits::is_future_v<T>, T>** = nullptr) noexcept

~future() = default

future &**operator**=(*future* &&other) noexcept = default

future &**operator**=(*future* const &other) noexcept = delete

inline *shared_future*<*R*> **share**() noexcept

inline *hpx::traits::future_traits*<*future*>::result_type **get**()

inline *hpx::traits::future_traits*<*future*>::result_type **get**(*error_code* &ec)

template<typename **F**>

inline decltype(auto) **then**(*F* &&*f*, *error_code* &ec = *throws*)

Attaches a continuation to **this*. The behavior is undefined if **this* has no associated shared state (i.e., *valid()==false*).

In cases where *decltype(func(*this))* is *future*<*R*>, the resulting type is *future*<*R*> instead of *future*<*future*<*R*>>. Effects:

- The continuation is called when the object's shared state is ready (has a value or exception stored).
- The continuation launches according to the specified launch policy or executor.

- When the executor or launch policy is not provided the continuation inherits the parent's launch policy or executor.
- If the parent was created with `std::promise` or with a `packaged_task` (has no associated launch policy), the continuation behaves the same as the third overload with a policy argument of `launch::async` | `launch::deferred` and the same argument for `func`.
- If the parent has a policy of `launch::deferred` and the continuation does not have a specified launch policy or scheduler, then the parent is filled by immediately calling `.wait()`, and the policy of the antecedent is `launch::deferred`

Note: Postcondition:

- The future object is moved to the parameter of the continuation function.
 - `valid() == false` on original future object immediately after it returns.
-

Template Parameters

F – The type of the function/function object to use (deduced). **F** must meet requirements of *MoveConstructible*.

Parameters

- **f** – A continuation to be attached.
- **ec** – Used to hold error code value originated during the operation. Defaults to `throws` — A special 'throw on error' `error_code`.

Returns

An object of type `future<decltype(func(*this))>` that refers to the shared state created by the continuation.

```
template<typename T0, typename F>
```

```
inline decltype(auto) then(T0 &&t0, F &&f, error_code &ec = throws)
```

Attaches a continuation to `*this`. The behavior is undefined if `*this` has no associated shared state (i.e., `valid() == false`). \copydetail `hpx::future::then(F&& f, error_code& ec = throws)`

Note: Postcondition:

- The future object is moved to the parameter of the continuation function.
 - `valid() == false` on original future object immediately after it returns.
-

Template Parameters

- **T0** – The type of executor or launch policy.
- **F** – The type of the function/function object to use (deduced). **F** must meet requirements of *MoveConstructible*.

Parameters

- **t0** – The executor or launch policy to be used.
- **f** – A continuation to be attached.
- **ec** – Used to hold error code value originated during the operation. Defaults to `throws` — A special 'throw on error' `error_code`.

Returns

An object of type `future<decltype(func(*this))>` that refers to the shared state created by the continuation.

```
template<typename Allocator, typename F>
```

```
inline auto then_alloc(Allocator const &alloc, F &&f, error_code &ec = throws) ->
```

```
    decltype(base_type::then_alloc(alloc, std::move(*this), std::forward<F>(f),  
    ec))
```

Private Types

```
using base_type = lcos::detail::future_base<future<R>, R>
```

Private Functions

```
inline explicit future(hpx::intrusive_ptr<shared_state_type> const &state)
```

```
inline explicit future(hpx::intrusive_ptr<shared_state_type> &&state)
```

```
template<typename SharedState>
```

```
inline explicit future(hpx::intrusive_ptr<SharedState> const &state)
```

Friends

```
friend struct hpx::traits::future_access
```

```
template<typename R>
```

```
class shared_future : public hpx::lcos::detail::future_base<shared_future<R>, R>
```

#include <future_fwd.hpp> The class template *hpx::shared_future* provides a mechanism to access the result of asynchronous operations, similar to *hpx::future*, except that multiple threads are allowed to wait for the same shared state. Unlike *hpx::future*, which is only moveable (so only one instance can refer to any particular asynchronous result), *hpx::shared_future* is copyable and multiple shared future objects may refer to the same shared state. Access to the same shared state from multiple threads is safe if each thread does it through its own copy of a *shared_future* object.

Public Types

```
using result_type = R
```

```
using shared_state_type = base_type::shared_state_type
```

Public Functions

```
constexpr shared_future() noexcept = default
```

```
shared_future(shared_future const &other) = default
```

```
shared_future(shared_future &&other) noexcept = default
```

```
inline shared_future(future<R> &&other) noexcept
```

```
inline shared_future(future<shared_future> &&other) noexcept
```

```
template<typename T>
```

```
inline shared_future(shared_future<T> const &other, std::enable_if_t<std::is_void_v<R> &&  
!traits::is_future_v<T>, T>* = nullptr)
```

```
~shared_future() = default
```


shared_future &**operator**=(*shared_future* const &other) = default

shared_future &**operator**=(*shared_future* &&other) noexcept = default

inline *hpx::traits::future_traits*<*shared_future*>::result_type **get**() const

inline *hpx::traits::future_traits*<*shared_future*>::result_type **get**(*error_code* &ec) const

template<typename **F**>

inline decltype(auto) **then**(*F* &&*f*, *error_code* &ec = *throws*) const

Attaches a continuation to **this*. The behavior is undefined if **this* has no associated shared state (i.e., *valid()==false*).

In cases where *decltype(func(*this))* is *future<R>*, the resulting type is *future<R>* instead of *future<future<R>>*. Effects:

- The continuation is called when the object's shared state is ready (has a value or exception stored).
- The continuation launches according to the specified launch policy or executor.
- When the executor or launch policy is not provided the continuation inherits the parent's launch policy or executor.
- If the parent was created with *std::promise* or with a *packaged_task* (has no associated launch policy), the continuation behaves the same as the third overload with a policy argument of *launch::async* | *launch::deferred* and the same argument for *func*.
- If the parent has a policy of *launch::deferred* and the continuation does not have a specified launch policy or scheduler, then the parent is filled by immediately calling *.wait()*, and the policy of the antecedent is *launch::deferred*

Note: Postcondition:

- The future object is moved to the parameter of the continuation function.
 - *valid() == false* on original future object immediately after it returns.
-

Template Parameters

F – The type of the function/function object to use (deduced). *F* must meet requirements of *MoveConstructible*.

Parameters

- **f** – A continuation to be attached.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special 'throw on error' *error_code*.

Returns

An object of type *future<decltype(func(*this))>* that refers to the shared state created by the continuation.

template<typename **T0**, typename **F**>

inline decltype(auto) **then**(*T0* &&*t0*, *F* &&*f*, *error_code* &ec = *throws*) const

Attaches a continuation to **this*. The behavior is undefined if **this* has no associated shared state (i.e., *valid()==false*). \copydetail *hpx::future::then*(*F*&& *f*, *error_code*& *ec* = *throws*)

Note: Postcondition:

- The future object is moved to the parameter of the continuation function.
 - *valid() == false* on original future object immediately after it returns.
-

Template Parameters

- **T0** – The type of executor or launch policy.
- **F** – The type of the function/function object to use (deduced). *F* must meet requirements of *MoveConstructible*.

Parameters

- **t0** – The executor or launch policy to be used.
- **f** – A continuation to be attached.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

An object of type *future<decltype(func(*this))>* that refers to the shared state created by the continuation.

```
template<typename Allocator, typename F>
inline auto then_alloc(Allocator const &alloc, F &&f, error_code &ec = throws) ->
    decltype(base_type::then_alloc(alloc, std::move(*this), std::forward<F>(f),
    ec))
```

Private Types

```
using base_type = lcos::detail::future_base<shared_future<R>, R>
```

Private Functions

```
inline explicit shared_future(hpx::intrusive_ptr<shared_state_type> const &state)
```

```
inline explicit shared_future(hpx::intrusive_ptr<shared_state_type> &&state)
```

```
template<typename SharedState>
```

```
inline explicit shared_future(hpx::intrusive_ptr<SharedState> const &state)
```

Friends

```
friend struct hpx::traits::future_access
```

```
namespace lcos
```

```
namespace serialization
```

Functions

```
template<typename Archive, typename T>
```

```
void serialize(Archive &ar, ::hpx::future<T> &f, unsigned version)
```

```
template<typename Archive, typename T>
```

```
void serialize(Archive &ar, ::hpx::shared_future<T> &f, unsigned version)
```

hpx::packaged_task

Defined in header `hpx/future.hpp`⁷⁴⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Sig, typename Allocator>
```

```
struct uses_allocator<hpx::packaged_task<Sig>, Allocator> : public true_type
```

```
namespace hpx
```

```
    Top level HPX namespace.
```

```
    template<typename Sig>
```

```
        class packaged_task
```

```
            #include <packaged_task.hpp> The class template hpx::packaged_task wraps any Callable` target (function, lambda expression, bind expression, or another function object) so that it can be invoked asynchronously. Its return value or exception thrown is stored in a shared state which can be accessed through hpx::future objects. Just like hpx::function, hpx::packaged_task is a polymorphic, allocator-aware container: the stored callable target may be allocated on heap or with a provided allocator.
```

```
        template<typename R, typename ...Ts>
```

```
            class packaged_task<R(Ts...)>
```

Public Functions

```
packaged_task() = default
```

```
template<typename F, typename FD = std::decay_t<F>, typename Enable =  
std::enable_if_t<!std::is_same_v<FD, packaged_task> && is_invocable_r_v<R, FD&, Ts...>>>  
inline explicit packaged_task(F &&f)
```

```
template<typename Allocator, typename F, typename FD = std::decay_t<F>, typename Enable =  
std::enable_if_t<!std::is_same_v<FD, packaged_task> && is_invocable_r_v<R, FD&, Ts...>>>  
inline explicit packaged_task(std::allocator_arg_t, Allocator const &a, F &&f)
```

```
packaged_task(packaged_task const &rhs) noexcept = delete
```

```
packaged_task(packaged_task &&rhs) noexcept = default
```

```
packaged_task &operator=(packaged_task const &rhs) noexcept = delete
```

```
packaged_task &operator=(packaged_task &&rhs) noexcept = default
```

```
inline void swap(packaged_task &rhs) noexcept
```

```
inline void operator()(Ts... ts)
```

```
inline hpx::future<R> get_future(error_code &ec = throws)
```

```
inline bool valid() const noexcept
```

```
inline void reset(error_code &ec = throws)
```

```
inline void set_exception(std::exception_ptr const &e)
```

⁷⁴⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Private Types

```
using function_type = hpx::move_only_function<R(Ts...)>
```

Private Members

```
function_type function_
```

```
hpx::promise<R> promise_
```

```
namespace std
```

Functions

```
template<typename Sig>  
void swap(hpx::packaged_task<Sig> &lhs, hpx::packaged_task<Sig> &rhs) noexcept
```

```
template<typename Sig, typename Allocator> packaged_task< Sig >,  
Allocator > : public true_type
```

`hpx/futures/future_fwd.hpp`

Defined in header `hpx/futures/future_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Top level HPX namespace.

```
template<typename R>
```

```
class future : public hpx::lcos::detail::future_base<future<R>, R>
```

```
    #include <future_fwd.hpp>
```

```
template<typename R>
```

```
class promise
```

#include <*promise.hpp*> The class template *hpx::promise* provides a facility to store a value or an exception that is later acquired asynchronously via a *hpx::future* object created by the *hpx::promise* object. Note that the *hpx::promise* object is meant to be used only once. Each promise is associated with a shared state, which contains some state information and a result which may be not yet evaluated, evaluated to a value (possibly void) or evaluated to an exception. A promise may do three things with the shared state:

- make ready: the promise stores the result or the exception in the shared state. Marks the state ready and unblocks any thread waiting on a future associated with the shared state.
- release: the promise gives up its reference to the shared state. If this was the last such reference, the shared state is destroyed. Unless this was a shared state created by *hpx::async* which is not yet ready, this operation does not block.

- **abandon**: the promise stores the exception of type `hpx::future_error` with error code `hpx::error::broken_promise`, makes the shared state ready, and then releases it. The promise is the “push” end of the promise-future communication channel: the operation that stores a value in the shared state synchronizes-with (as defined in `hpx::memory_order`) the successful return from any function that is waiting on the shared state (such as `hpx::future::get`). Concurrent access to the same shared state may conflict otherwise: for example multiple callers of `hpx::shared_future::get` must either all be read-only or provide external synchronization.

```
template<typename R>
```

```
class shared_future : public hpx::lcos::detail::future_base<shared_future<R>, R>  
    #include <future_fwd.hpp>
```

```
namespace lcos
```

```
namespace lcos
```

hpx::promise

Defined in header [hpx/future.hpp](#)⁷⁴⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename R, typename Allocator>
```

```
struct uses_allocator<hpx::promise<R>, Allocator> : public true_type
```

```
namespace hpx
```

Top level HPX namespace.

```
template<typename R>
```

```
class promise
```

```
    #include <promise.hpp>
```

```
template<typename R>
```

```
class promise<R&> : public hpx::detail::promise_base<R&>
```

Public Functions

```
promise() = default
```

```
template<typename Allocator>  
inline promise(std::allocator_arg_t, Allocator const &a)
```

```
promise(promise &&other) noexcept = default
```

```
promise(promise const &other) = delete
```

```
~promise() = default
```

⁷⁴⁶ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

```
promise &operator=(promise &&other) noexcept = default
promise &operator=(promise const &other) = delete
inline void swap(promise &other) noexcept
inline void set_value(R &r)
```

Private Types

```
using base_type = detail::promise_base<R&>
template<>
class promise<void> : public hpx::detail::promise_base<void>
```

Public Functions

```
promise() = default
template<typename Allocator>
inline promise(std::allocator_arg_t, Allocator const &a)
promise(promise &&other) noexcept = default
promise(promise const &other) noexcept = delete
~promise() = default
promise &operator=(promise &&other) noexcept = default
promise &operator=(promise const &other) noexcept = delete
inline void swap(promise &other) noexcept
inline void set_value()
```

Private Types

```
using base_type = detail::promise_base<void>
```

```
namespace std
```

Functions

```
template<typename R>
void swap(hpx::promise<R> &x, hpx::promise<R> &y) noexcept
```

```
template<typename R, typename Allocator> promise< R >,
Allocator > : public true_type
```

io_service

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/io_service/io_service_pool.hpp

Defined in header `hpx/io_service/io_service_pool.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace util
```

```
class io_service_pool
```

```
#include <io_service_pool.hpp> A pool of io_service objects.
```

Public Functions

```
explicit io_service_pool(std::size_t pool_size = 2, threads::policies::callback_notifier const
                        &notifier = threads::policies::callback_notifier(), char const
                        *pool_name = "", char const *name_postfix = "")
```

Construct the `io_service` pool.

Parameters

- **pool_size** – [in] The number of threads to run to serve incoming requests
- **notifier** – [in]
- **pool_name** – [in]
- **name_postfix** – [in]

```
explicit io_service_pool(threads::policies::callback_notifier const &notifier, char const
                        *pool_name = "", char const *name_postfix = "")
```

Construct the `io_service` pool.

Parameters

- **notifier** – [in]
- **pool_name** – [in]
- **name_postfix** – [in]

```
io_service_pool(io_service_pool const&) = delete
```

```
io_service_pool(io_service_pool&&) = delete
```

```
io_service_pool &operator=(io_service_pool const&) = delete
```

io_service_pool &**operator**=(*io_service_pool*&&) = delete

~io_service_pool()

bool **run**(bool join_threads = true, *barrier* *startup = nullptr) const

Run all *io_service* objects in the pool. If *join_threads* is true this will also wait for all threads to complete

bool **run**(*std::size_t* num_threads, bool join_threads = true, *barrier* *startup = nullptr) const

Run all *io_service* objects in the pool. If *join_threads* is true this will also wait for all threads to complete

void **stop**() const

Stop all *io_service* objects in the pool.

void **join**() const

Join all *io_service* threads in the pool.

void **clear**() const

Clear all internal data structures.

void **wait**() const

Wait for all work to be done.

bool **stopped**() const

::asio::io_context &**get_io_service**(int index = -1) const

Get an *io_service* to use.

std::thread &**get_os_thread_handle**(*std::size_t* thread_num) const

access underlying thread handle

std::size_t **size**() const noexcept

Get number of threads associated with this I/O service.

void **thread_run**(*std::size_t* index, *barrier* *startup = nullptr) const

Activate the thread *index* for this thread pool.

char const ***get_name**() const noexcept

Return name of this pool.

void **init**(*std::size_t* pool_size) const

Private Members

detail::io_service_pool_base ***pool_**

lcos_local

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/lcos_local/trigger.hpp

Defined in header `hpx/lcos_local/trigger.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **lcos**

namespace **local**

template<typename **Mutex** = *hpx::spinlock*>

struct **base_trigger**

Public Functions

inline **base_trigger**() noexcept

inline **base_trigger**(*base_trigger* &&rhs) noexcept

inline *base_trigger* &**operator**=(*base_trigger* &&rhs) noexcept

inline *hpx::future*<void> **get_future**(*std::size_t* *generation_value = nullptr, *error_code* &ec = *hpx::throws*)

get a future allowing to wait for the trigger to fire

inline bool **set**(*error_code* &ec = *throws*)

Trigger this object.

inline void **synchronize**(*std::size_t* generation_value, char const *function_name = "trigger::synchronize", *error_code* &ec = *throws*)

Wait for the generational counter to reach the requested stage.

inline *std::size_t* **next_generation**()

inline *std::size_t* **generation**() const

Protected Types

using **mutex_type** = *Mutex*

Protected Functions

```
inline bool trigger_conditions(error_code &ec = throws)
```

```
template<typename Lock>
```

```
inline void synchronize(std::size_t generation_value, Lock &l, char const *function_name =  
    "trigger::synchronize", error_code &ec = throws)
```

Private Types

```
using condition_list_type = hpx::detail::intrusive_list<condition_list_entry>
```

Private Functions

```
inline bool test_condition(std::size_t const generation_value) const noexcept
```

Private Members

```
mutable mutex_type mtx_
```

```
hpx::promise<void> promise_
```

```
std::size_t generation_
```

```
condition_list_type conditions_
```

```
struct condition_list_entry : public conditional_trigger
```

Public Functions

```
condition_list_entry() = default
```

Public Members

```
condition_list_entry *prev = nullptr
```

```
condition_list_entry *next = nullptr
```

```
struct manage_condition
```

Public Functions

```

inline manage_condition(base_trigger &gate, condition_list_entry &cond) noexcept

inline ~manage_condition()

template<typename Condition>
inline hpx::future<void> get_future(Condition &&func, error_code &ec = hpx::throws)

```

Public Members

```
base_trigger &this_
```

```
condition_list_entry &e_
```

```
struct trigger : public hpx::lcos::local::base_trigger<hpx::no_mutex>
```

Public Functions

```

trigger() = default

inline trigger(trigger &&rhs) noexcept

inline trigger &operator=(trigger &&rhs) noexcept

template<typename Lock>
inline void synchronize(std::size_t generation_value, Lock &l, char const *function_name =
    "trigger::synchronize", error_code &ec = throws)

```

Private Types

```
using base_type = base_trigger<hpx::no_mutex>
```

pack_traversal

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::functional::unwrap, **hpx::functional::unwrap_n**, **hpx::functional::unwrap_all**, **hpx::unwrap**, **hpx::unwrap_n**, **hpx::unwrap_all**, **hpx::unwrapping**, **hpx::unwrapping_n**, **hpx::unwrapping_all**

Defined in header `hpx/unwrap.hpp`⁷⁴⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁷⁴⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/unwrap.hpp

Functions

```
template<typename ...Args>
auto unwrap(Args&&... args) -> decltype(util::detail::unwrap_depth_impl<1U>(HPX_FORWARD(Args,
    args)...))
```

A helper function for retrieving the actual result of any `hpx::future` like type which is wrapped in an arbitrary way.

Unwraps the given pack of arguments, so that any `hpx::future` object is replaced by its future result type in the argument pack:

- `hpx::future<int> -> int`
- `hpx::future<std::vector<float>> -> std::vector<float>`
- `std::vector<future<float>> -> std::vector<float>`

The function is capable of unwrapping `hpx::future` like objects that are wrapped inside any container or tuple like type, see `hpx::util::map_pack()` for a detailed description about which surrounding types are supported. Non `hpx::future` like types are permitted as arguments and passed through.

```
hpx::unwrap(hpx::make_ready_future(0));

// Multiple arguments hpx::tuple<int, int> i2 =
    hpx::unwrap(hpx::make_ready_future(1),
        hpx::make_ready_future(2));
```

Note: This function unwraps the given arguments until the first traversed nested `hpx::future` which corresponds to an unwrapping depth of one. See `hpx::unwrap_n()` for a function which unwraps the given arguments to a particular depth or `hpx::unwrap_all()` that unwraps all future like objects recursively which are contained in the arguments.

Parameters

args – the arguments that are unwrapped which may contain any arbitrary future or non-future type.

Throws

`std::exception` – like objects in case any of the given wrapped `hpx::future` objects were resolved through an exception. See `hpx::future::get()` for details.

Returns

Depending on the count of arguments this function returns a `hpx::tuple` containing the unwrapped arguments if multiple arguments are given. In case the function is called with a single argument, the argument is unwrapped and returned.

```
template<std::size_t Depth, typename ...Args>
auto unwrap_n(Args&&... args) ->
    decltype(util::detail::unwrap_depth_impl<Depth>(HPX_FORWARD(Args, args)...))
```

An alternative version of `hpx::unwrap()`, which unwraps the given arguments to a certain depth of `hpx::future` like objects.

See `unwrap` for a detailed description.

Template Parameters

Depth – The count of `hpx::future` like objects which are unwrapped maximally.

```
template<typename ...Args>
auto unwrap_all(Args&&... args) ->
    decltype(util::detail::unwrap_depth_impl<0U>(HPX_FORWARD(Args, args)...))
```

An alternative version of `hpx::unwrap()`, which unwraps the given arguments recursively so that all contained `hpx::future` like objects are replaced by their actual value.

See `hpx::unwrap()` for a detailed description.

```
template<typename T>
auto unwrapping(T &&callable) ->
    decltype(util::detail::functional_unwrap_depth_impl<1U>(HPX_FORWARD(T, callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the `hpx::unwrap()` function and then passes the result to the given callable object.

```
    return left + right;
});

int i1 = callable(hpx::make_ready_future(1),
                  hpx::make_ready_future(2));
```

See `hpx::unwrap()` for a detailed description.

Parameters

callable – the callable object which is called with the result of the corresponding `unwrap` function.

```
template<std::size_t Depth, typename T>
auto unwrapping_n(T &&callable) ->
    decltype(util::detail::functional_unwrap_depth_impl<Depth>(HPX_FORWARD(T,
    callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the `hpx::unwrap_n()` function and then passes the result to the given callable object.

See `hpx::unwrapping()` for a detailed description.

```
template<typename T>
auto unwrapping_all(T &&callable) ->
    decltype(util::detail::functional_unwrap_depth_impl<0U>(HPX_FORWARD(T,
    callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the `hpx::unwrap_all()` function and then passes the result to the given callable object.

See `hpx::unwrapping()` for a detailed description.

namespace **functional**

struct **unwrap**

#include <unwrap.hpp> A helper function object for functionally invoking `hpx::unwrap`. For more information please refer to its documentation.

struct **unwrap_all**

#include <unwrap.hpp> A helper function object for functionally invoking `hpx::unwrap_all`. For more information please refer to its documentation.

```
template<std::size_t Depth>
```

struct **unwrap_n**

#include <unwrap.hpp> A helper function object for functionally invoking `hpx::unwrap_n`. For more information please refer to its documentation.

hpx/pack_traversal/pack_traversal_async.hpp

Defined in header `hpx/pack_traversal/pack_traversal_async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

```
template<typename Visitor, typename ...T>
auto traverse_pack_async(Visitor &&visitor, T&&... pack) ->
    decltype(detail::apply_pack_transform_async(HPX_FORWARD(Visitor,
        visitor), HPX_FORWARD(T, pack)...))
```

Traverses the pack with the given visitor in an asynchronous way.

This function works in the same way as `traverse_pack`, however, we are able to suspend and continue the traversal at later time. Thus, we require a visitor callable object which provides three `operator()` overloads as depicted by the code sample below:

```
// The synchronous overload is called for each object, // it may
return false to suspend the current control. // In that case the
overload below is called. template <typename T> bool
operator()(async_traverse_visit_tag, T&& element) {
    return true;
}

// The asynchronous overload this is called when the //
synchronous overload returned false. // In addition to the
current visited element the overload is // called with a
continuation callable object which resumes the // traversal when
it's called later. // The continuation next may be stored and
called later or // dropped completely to abort the traversal
early. template <typename T, typename N> void
operator()(async_traverse_detach_tag, T&& element, N&& next) { }

// The overload is called when the traversal was finished. // As
argument the whole pack is passed over which we // traversed
asynchronously. template <typename T> void
operator()(async_traverse_complete_tag, T&& pack) { }
};
```

See `traverse_pack` for a detailed description about the traversal behavior and capabilities.

Parameters

- **visitor** – A visitor object which provides the three `operator()` overloads that were described above. Additionally, the visitor must be compatible for referencing it from a `hpx::intrusive_ptr`. The visitor should have a virtual destructor!
- **pack** – The arbitrary parameter pack which is traversed asynchronously. Nested objects inside containers and tuple like types are traversed recursively.

Returns

A `hpx::intrusive_ptr` that references an instance of the given visitor object.

hpx/pack_traversal/pack_traversal.hpp

Defined in header `hpx/pack_traversal/pack_traversal.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

Functions

```
template<typename Mapper, typename...  
T> < unspecified > map_pack (Mapper &&mapper, T &&... pack)
```

Maps the pack with the given mapper.

This function tries to visit all plain elements which may be wrapped in:

- homogeneous containers (`std::vector`, `std::list`)
- heterogeneous containers (`hpx::tuple`, `std::pair`, `std::array`) and re-assembles the pack with the result of the mapper. Mapping from one type to a different one is supported.

Elements that aren't accepted by the mapper are routed through and preserved through the hierarchy.

```
// Maps all integers to floats  
map_pack([](int value) {  
    return float(value);  
},  
1, hpx::make_tuple(2, std::vector<int>{3, 4}), 5);
```

Throws

`std::exception` – like objects which are thrown by an invocation to the mapper.

Parameters

- **mapper** – A callable object, which accept an arbitrary type and maps it to another type or the same one.
- **pack** – An arbitrary variadic pack which may contain any type.

Returns

The mapped element or in case the pack contains multiple elements, the pack is wrapped into a `hpx::tuple`.

preprocessor

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/preprocessor/strip_parens.hpp

Defined in header `hpx/preprocessor/strip_parens.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_STRIP_PARENS(X)

For any symbol *X*, this macro returns the same symbol from which potential outer parens have been removed. If no outer parens are found, this macros evaluates to *X* itself without error.

The original implementation of this macro is from Steven Watanbe as shown in <http://boost.2283326.n4.nabble.com/preprocessor-removing-parentheses-td2591973.html#a2591976>

```
HPX_PP_STRIP_PARENS(no_parens)
HPX_PP_STRIP_PARENS((with_parens))
```

Example Usage:

This produces the following output

```
no_parens
with_parens
```

Parameters

- **X** – Symbol to strip parens from

hpx/preprocessor/nargs.hpp

Defined in header `hpx/preprocessor/nargs.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_NARGS(...)

Expands to the number of arguments passed in

Example Usage:

```
HPX_PP_NARGS(hpx, pp, nargs)
HPX_PP_NARGS(hpx, pp)
HPX_PP_NARGS(hpx)
```


Expands to:

```
3
2
1
```

Parameters

- ... – The variadic number of arguments

hpx/preprocessor/stringize.hpp

Defined in header `hpx/preprocessor/stringize.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_STRINGIZE(X)

The `HPX_PP_STRINGIZE` macro stringizes its argument after it has been expanded.

The passed argument `X` will expand to "`X`". Note that the stringizing operator (`#`) prevents arguments from expanding. This macro circumvents this shortcoming.

Parameters

- **X** – The text to be converted to a string literal

hpx/preprocessor/cat.hpp

Defined in header `hpx/preprocessor/cat.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_CAT(A, B)

Concatenates the tokens `A` and `B` into a single token. Evaluates to `AB`

Parameters

- **A** – First token
- **B** – Second token

hpx/preprocessor/expand.hpp

Defined in header `hpx/preprocessor/expand.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_EXPAND(X)

The `HPX_PP_EXPAND` macro performs a double macro-expansion on its argument.

This macro can be used to produce a delayed preprocessor expansion.

Example:

```
#define MACRO(a, b, c) (a)(b)(c)
#define ARGS() (1, 2, 3)

HPX_PP_EXPAND(MACRO ARGS()) // expands to (1)(2)(3)
```

Parameters

- **X** – Token to be expanded twice

resiliency

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/resiliency/replicate_executor.hpp

Defined in header `hpx/resiliency/replicate_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename BaseExecutor, typename Voter, typename Validator>
```

```
struct is_two_way_executor<hpx::resiliency::experimental::replicate_executor<BaseExecutor, Voter,  
Validator>> : public true_type
```

```
template<typename BaseExecutor, typename Voter, typename Validator>
```

```
struct is_bulk_two_way_executor<hpx::resiliency::experimental::replicate_executor<BaseExecutor, Voter,  
Validator>> : public true_type
```

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
template<typename BaseExecutor, typename Voter,
typename Validator> replicate_executor< BaseExecutor, Voter,
Validator > > : public true_type
```

```
template<typename BaseExecutor, typename Voter,
typename Validator> replicate_executor< BaseExecutor, Voter,
Validator > > : public true_type
```

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Tag, typename BaseExecutor, typename Vote, typename Validate,
typename Property>
auto tag_invoke(Tag tag, replicate_executor<BaseExecutor, Vote, Validate> const &exec,
Property &&prop) -> decltype(replicate_executor<BaseExecutor, Vote,
Validate>(std::declval<Tag>())(std::declval<BaseExecutor>(),
std::declval<Property>()), std::declval<std::size_t>(), std::declval<Vote>(),
std::declval<Validate>()))
```

```
template<typename Tag, typename BaseExecutor, typename Vote, typename Validate>
auto tag_invoke(Tag tag, replicate_executor<BaseExecutor, Vote, Validate> const &exec) ->
decltype(std::declval<Tag>())(std::declval<BaseExecutor>())
```

```
template<executor_any BaseExecutor, typename Voter, typename Validate>
replicate_executor<BaseExecutor, std::decay_t<Voter>, std::decay_t<Validate>> make_replicate_executor(BaseExecutor &exec,
std::size_t n,
Voter &&voter,
Validate &&validator,
i-date &&vote_date,
i-date &&validate_date)
```

```
template<executor_any BaseExecutor, typename Validate>
replicate_executor<BaseExecutor, detail::replicate_voter, std::decay_t<Validate>> make_replicate_executor(BaseExecutor &exec,
std::size_t n,
Validate &&validator,
i-date &&vote_date,
i-date &&validate_date)
```

```
template<executor_any BaseExecutor>
replicate_executor<BaseExecutor, detail::replicate_voter, detail::replicate_validator> make_replicate_executor(B
```

```
template<typename BaseExecutor, typename Vote, typename Validate>
class replicate_executor
```

Public Types

```
using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>

using executor_parameters_type = hpx::traits::executor_parameters_type_t<BaseExecutor>

template<typename Result>

using future_type = hpx::traits::executor_future_t<BaseExecutor, Result>
```

Public Functions

```
template<typename BaseExecutor_, typename V, typename F>
inline explicit replicate_executor(BaseExecutor_ &&exec, std::size_t n, V &&v, F &&f)

inline bool operator==(replicate_executor const &rhs) const noexcept

inline bool operator!=(replicate_executor const &rhs) const noexcept

inline constexpr replicate_executor const &context() const noexcept

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline BaseExecutor const &get_executor() const

inline std::size_t get_replicate_count() const

inline Vote const &get_voter() const

inline Validate const &get_validator() const

template<typename Tag, typename ...Args>
inline auto query(Tag tag, Args&&... args) const ->
    decltype(replicate_executor<BaseExecutor, Vote,
        Validate>(std::declval<Tag>()(std::declval<BaseExecutor>()),
        HPX_FORWARD(Args, args)...), std::declval<std::size_t>(),
        std::declval<Vote>(), std::declval<Validate>()))
```

Public Static Attributes

static constexpr int **num_spread** = 4

static constexpr int **num_tasks** = 128

Private Members

BaseExecutor **exec_**

std::size_t **replicate_count_**

Vote **voter_**

Validate **validator_**

hpx/resiliency/replay_executor.hpp

Defined in header `hpx/resiliency/replay_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename BaseExecutor, typename Validator>
```

```
struct is_two_way_executor<hpx::resiliency::experimental::replay_executor<BaseExecutor, Validator>> : public  
true_type
```

```
template<typename BaseExecutor, typename Validator>
```

```
struct is_bulk_two_way_executor<hpx::resiliency::experimental::replay_executor<BaseExecutor, Validator>> :  
public true_type
```

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            template<typename BaseExecutor,  
                    typename Validator> replay_executor< BaseExecutor,  
                    Validator > > : public true_type
```

```
            template<typename BaseExecutor,  
                    typename Validator> replay_executor< BaseExecutor,  
                    Validator > > : public true_type
```

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Tag, typename BaseExecutor, typename Validate, typename Property>  
auto tag_invoke(Tag tag, replay_executor<BaseExecutor, Validate> const &exec, Property  
                &&prop) -> decltype(replay_executor<BaseExecutor,  
                Validate>(std::declval<Tag>()(std::declval<BaseExecutor>(),  
                std::declval<Property>()), std::declval<std::size_t>(), std::declval<Validate>()))
```

```
template<typename Tag, typename BaseExecutor, typename Validate>  
auto tag_invoke(Tag tag, replay_executor<BaseExecutor, Validate> const &exec) ->  
    decltype(std::declval<Tag>()(std::declval<BaseExecutor>()))
```

```
template<executor_any BaseExecutor, typename Validate>  
replay_executor<BaseExecutor, std::decay_t<Validate>> make_replay_executor(BaseExecutor  
                                                                           &exec,  
                                                                           std::size_t n,  
                                                                           Validate  
                                                                           &&validate)
```

```
template<executor_any BaseExecutor>  
replay_executor<BaseExecutor, detail::replay_validator> make_replay_executor(BaseExecutor  
                                                                           &exec,  
                                                                           std::size_t n)
```

```
template<typename BaseExecutor, typename Validate>
```

```
class replay_executor
```

Public Types

```
using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>
```

```
using executor_parameters_type = hpx::traits::executor_parameters_type_t<BaseExecutor>
```

```
template<typename Result>
```

```
using future_type = hpx::traits::executor_future_t<BaseExecutor, Result>
```

Public Functions

```

template<typename BaseExecutor_, typename F>
inline explicit replay_executor(BaseExecutor_ &&exec, std::size_t n, F &&f)

inline bool operator==(replay_executor const &rhs) const noexcept

inline bool operator!=(replay_executor const &rhs) const noexcept

inline constexpr replay_executor const &context() const noexcept

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline BaseExecutor const &get_executor() const

inline std::size_t get_replay_count() const

inline Validate const &get_validator() const

template<typename Tag, typename ...Args>
inline auto query(Tag tag, Args&&... args) const -> decltype(replay_executor<BaseExecutor,
    Validate>(std::declval<Tag>()(std::declval<BaseExecutor>()),
    HPX_FORWARD(Args, args)...), std::declval<std::size_t>(),
    std::declval<Validate>()))

```

Public Static Attributes

```
static constexpr int num_spread = 4
```

```
static constexpr int num_tasks = 128
```

Private Members

```
BaseExecutor exec_
```

```
std::size_t replay_count_
```

```
Validate validator_
```

runtime_configuration

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_configuration/component_registry_base.hpp

Defined in header `hpx/runtime_configuration/component_registry_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

struct **component_registry_base**

#include <component_registry_base.hpp> The `component_registry_base` has to be used as a base class for all component registries.

Public Functions

virtual **~component_registry_base**() = default

virtual bool **get_component_info**(*std::vector<std::string> &fillini*, *std::string const &filepath*,
bool *is_static* = false) = 0

Return the ini-information for all contained components.

Parameters

- **fillini** – [in, out] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.
- **filepath** – [in]
- **is_static** – [in]

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

virtual void **register_component_type**() = 0

Register the component type represented by this component.

hpx/runtime_configuration/plugin_registry_base.hpp

Defined in header `hpx/runtime_configuration/plugin_registry_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **plugins**

struct **plugin_registry_base**

#include <plugin_registry_base.hpp> The `plugin_registry_base` has to be used as a base class for all plugin registries.

Public Functions

virtual `~plugin_registry_base()` = default

virtual bool `get_plugin_info(std::vector<std::string> &fillini) = 0`

Return the configuration information for any plugin implemented by this module

Parameters

fillini – [in, out] The module is expected to fill this vector with the ini-information (one line per vector element) for all plugins implemented in this module.

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

inline virtual void `init(int*, char***, util::runtime_configuration&)`

HPX_REGISTER_COMPONENT_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_REGISTER_COMMANDLINE_REGISTRY(RegistryType, componentname)

The macro *HPX_REGISTER_COMMANDLINE_REGISTRY* is used to register the given component factory with `Hpx.Plugin`. This macro has to be used for each of the components.

HPX_REGISTER_COMMANDLINE_REGISTRY_DYNAMIC(RegistryType, componentname)

HPX_REGISTER_COMMANDLINE_OPTIONS()

The macro *HPX_REGISTER_COMMANDLINE_OPTIONS* is used to define the required `Hpx.Plugin` entry point for the command line option registry. This macro has to be used in not more than one compilation unit of a component module.

HPX_REGISTER_COMMANDLINE_OPTIONS_DYNAMIC()

HPX_REGISTER_COMPONENT_FACTORY(componentname)

This macro is used to register the given component factory with `Hpx.Plugin`. This macro has to be used for each of the component factories.

HPX_REGISTER_COMPONENT_MODULE()

This macro is used to define the required `Hpx.Plugin` entry points. This macro has to be used in exactly one compilation unit of a component module. Ungated: a component may live in a shared library, in a statically linked build, or directly in the application executable.

HPX_REGISTER_COMPONENT_MODULE_DYNAMIC()

HPX_REGISTER_COMPONENT_REGISTRY(RegistryType, componentname)

This macro is used to register the given component factory with `Hpx.Plugin`. This macro has to be used for each of the components.

HPX_REGISTER_COMPONENT_REGISTRY_DYNAMIC(RegistryType, componentname)

HPX_REGISTER_REGISTRY_MODULE()

This macro is used to define the required Hpx.Plugin entry points. This macro has to be used in exactly one compilation unit of a component module. Ungated: see HPX_REGISTER_COMPONENT_MODULE.

HPX_REGISTER_REGISTRY_MODULE_DYNAMIC()**HPX_REGISTER_PLUGIN_BASE_REGISTRY(PluginType, name)**

This macro is used to register the given plugin factory with Hpx.Plugin. This macro has to be used for each of the plugins. Ungated, matching the component analog (HPX_REGISTER_COMPONENT_REGISTRY).

HPX_REGISTER_PLUGIN_REGISTRY_MODULE()

This macro is used to define the required Hpx.Plugin entry points. This macro has to be used in exactly one compilation unit of a plugin module. Ungated: a plugin may live in a shared library, in a statically linked build, or directly in the application executable.

HPX_REGISTER_PLUGIN_REGISTRY_MODULE_DYNAMIC()**HPX_DECLARE_FACTORY_STATIC(name, base)****HPX_DEFINE_FACTORY_STATIC(module, name, base)****HPX_INIT_REGISTRY_MODULE_STATIC(name, base)****HPX_INIT_REGISTRY_FACTORY_STATIC(name, componentname, base)****HPX_INIT_REGISTRY_COMMANDLINE_STATIC(name, base)****HPX_INIT_REGISTRY_STARTUP_SHUTDOWN_STATIC(name, base)****HPX_INIT_REGISTRY_PLUGIN_MODULE_STATIC(name, base)****HPX_INIT_REGISTRY_PLUGIN_FACTORY_STATIC(name, pluginname, base)****hpx::components::component_commandline_base**

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

struct **component_commandline_base**

#include <component_commandline_base.hpp> The `component_commandline_base` has to be used as a base class for all component command-line line handling registries.

Public Functions

virtual `~component_commandline_base()` = default

virtual `hpx::program_options::options_description add_commandline_options()` = 0

Return any additional command line options valid for this component.

Note: This function will be executed by the runtime system during system startup.

Returns

The module is expected to fill a `options_description` object with any additional command line options this component will handle.

`hpx::runtime_mode`

Defined in header `hpx/init.hpp`⁷⁴⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Enums

enum class **runtime_mode** : `std::int8_t`

A HPX runtime can be executed in two different modes: console mode and worker mode.

Values:

enumerator **invalid**

enumerator **console**

The runtime is the console locality.

enumerator **worker**

The runtime is a worker locality.

enumerator **connect**

The runtime is a worker locality connecting late

enumerator **local**

The runtime is fully local.

enumerator **default_**

The runtime mode will be determined based on the command line arguments

enumerator **last**

⁷⁴⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Functions

char const ***get_runtime_mode_name**(runtime_mode state) noexcept

Get the readable string representing the name of the given runtime_mode constant.

runtime_mode **get_runtime_mode_from_name**(std::string const &mode)

Returns the internal representation (runtime_mode constant) from the readable string representing the name.

This represents the internal representation from the readable string representing the name.

Parameters

mode – this represents the runtime mode

runtime_local

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_local/custom_exception_info.hpp

Defined in header hpx/runtime_local/custom_exception_info.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

std::string **diagnostic_information**(exception_info const &xi)

Extract the diagnostic information embedded in the given exception and return a string holding a formatted message.

The function *hpx::diagnostic_information* can be used to extract all diagnostic information stored in the given exception instance as a formatted string. This simplifies debug output as it composes the diagnostics into one, easy to use function call. This includes the name of the source file and line number, the sequence number of the OS-thread and the HPX-thread id, the locality id and the stack backtrace of the point where the original exception was thrown.

See also:

hpx::get_error_locality_id(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error(), *hpx::get_error_backtrace()*, *hpx::get_error_env()*, *hpx::get_error_what()*,
hpx::get_error_config(), *hpx::get_error_state()*

Parameters

xi – The parameter *e* will be inspected for all diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if any of the required allocation operations fail)

Returns

The formatted string holding all the available diagnostic information stored in the given exception instance.

`std::string default_diagnostic_information(std::exception_ptr const &e)`

`std::uint32_t get_error_locality_id(hpx::exception_info const &xi) noexcept`

Return the locality id where the exception was thrown.

The function `hpx::get_error_locality_id` can be used to extract the diagnostic information element representing the locality id as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`,
`hpx::get_error()`, `hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_what()`,
`hpx::get_error_config()`, `hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

nothing –

Returns

The locality id of the locality where the exception was thrown. If the exception instance does not hold this information, the function will return `hpx::naming::invalid_locality_id`.

`std::string get_error_host_name(hpx::exception_info const &xi)`

Return the hostname of the locality where the exception was thrown.

The function `hpx::get_error_host_name` can be used to extract the diagnostic information element representing the host name as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_process_id()`, `hpx::get_error_function_name()`,
`hpx::get_error_file_name()`, `hpx::get_error_line_number()`, `hpx::get_error_os_thread()`,
`hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`, `hpx::get_error()`,
`hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

The hostname of the locality where the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

`std::int64_t get_error_process_id(hpx::exception_info const &xi) noexcept`

Return the (operating system) process id of the locality where the exception was thrown.

The function `hpx::get_error_process_id` can be used to extract the diagnostic information element representing the process id as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_function_name()`,
`hpx::get_error_file_name()`, `hpx::get_error_line_number()`, `hpx::get_error_os_thread()`,
`hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`, `hpx::get_error()`,
`hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

nothing –

Returns

The process id of the OS-process which threw the exception. If the exception instance does not hold this information, the function will return 0.

`std::string get_error_env(hpx::exception_info const &xi)`

Return the environment of the OS-process at the point the exception was thrown.

The function `hpx::get_error_env` can be used to extract the diagnostic information element representing the environment of the OS-process collected at the point the exception was thrown.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`,
`hpx::get_error()`, `hpx::get_error_backtrace()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

The environment from the point the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

`std::string get_error_backtrace(hpx::exception_info const &xi)`

Return the stack backtrace from the point the exception was thrown.

The function `hpx::get_error_backtrace` can be used to extract the diagnostic information element representing the stack backtrace collected at the point the exception was thrown.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`,
`hpx::get_error()`, `hpx::get_error_env()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

The stack back trace from the point the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

`std::size_t get_error_os_thread(hpx::exception_info const &xi) noexcept`

Return the sequence number of the OS-thread used to execute HPX-threads from which the exception was thrown.

The function `hpx::get_error_os_thread` can be used to extract the diagnostic information element representing the sequence number of the OS-thread as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_thread_id()`, `hpx::get_error_thread_description()`, `hpx::get_error()`,
`hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

nothing –

Returns

The sequence number of the OS-thread used to execute the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return `std::size(-1)`.

`std::size_t` **get_error_thread_id**(*hpx::exception_info* const &xi) noexcept

Return the unique thread id of the HPX-thread from which the exception was thrown.

The function `hpx::get_error_thread_id` can be used to extract the diagnostic information element representing the HPX-thread id as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_description()`, `hpx::get_error()`,
`hpx::get_error_backtrace()`, `hpx::get_error_env()`, `hpx::get_error_what()`, `hpx::get_error_config()`,
`hpx::get_error_state()`

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

nothing –

Returns

The unique thread id of the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return `std::size_t(0)`.

`std::string` **get_error_thread_description**(*hpx::exception_info* const &xi)

Return any additionally available thread description of the HPX-thread from which the exception was thrown.

The function `hpx::get_error_thread_description` can be used to extract the diagnostic information element representing the additional thread description as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_backtrace()`,
`hpx::get_error_env()`, `hpx::get_error()`, `hpx::get_error_state()`, `hpx::get_error_what()`,
`hpx::get_error_config()`

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

Any additionally available thread description of the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

`std::string get_error_config(hpx::exception_info const &xi)`

Return the HPX configuration information point from which the exception was thrown.

The function `hpx::get_error_config` can be used to extract the HPX configuration information element representing the full HPX configuration information as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_backtrace()`,
`hpx::get_error_env()`, `hpx::get_error()`, `hpx::get_error_state()` `hpx::get_error_what()`,
`hpx::get_error_thread_description()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

Any additionally available HPX configuration information the point from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

`std::string get_error_state(hpx::exception_info const &xi)`

Return the HPX runtime state information at which the exception was thrown.

The function `hpx::get_error_state` can be used to extract the HPX runtime state information element representing the state the runtime system is currently in as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_backtrace()`,
`hpx::get_error_env()`, `hpx::get_error()`, `hpx::get_error_what()`, `hpx::get_error_thread_description()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

The point runtime state at the point at which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

hpx::get_initial_num_localities, hpx::get_num_localities

Defined in header [hpx/runtime.hpp](#)⁷⁴⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

`std::uint32_t get_initial_num_localities()`

Return the number of localities which were registered at startup for the running application.

The function `get_initial_num_localities` returns the number of localities which were connected to the console at application startup.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

`hpx::future<std::uint32_t> get_num_localities()`

Asynchronously return the number of localities which are currently registered for the running application.

The function `get_num_localities` asynchronously returns the number of localities currently connected to the console. The returned future represents the actual result.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

`std::uint32_t get_num_localities(launch::sync_policy, error_code &ec = throws)`

Return the number of localities which are currently registered for the running application.

The function `get_num_localities` returns the number of localities currently connected to the console.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

⁷⁴⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::startup_function_type, hpx::register_pre_startup_function, hpx::register_startup_function

Defined in header [hpx/runtime.hpp](#)⁷⁵⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Typedefs

using **startup_function_type** = *hpx::move_only_function*<void()>

The type of the function which is registered to be executed as a startup or pre-startup function.

Functions

void **register_pre_startup_function**(*startup_function_type* f)

Add a function to be executed by a HPX thread before *hpx_main* but guaranteed before any startup function is executed (system-wide).

Any of the functions registered with *register_pre_startup_function* are guaranteed to be executed by an HPX thread before any of the registered startup functions are executed (see *hpx::register_startup_function()*).

This function is one of the few API functions which can be called before the runtime system has been fully initialized. It will automatically stage the provided startup function to the runtime system during its initialization (if necessary).

See also:

hpx::register_startup_function()

Note: If this function is called while the pre-startup functions are being executed or after that point, it will raise *aninvalid_status* exception.

⁷⁵⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Parameters

f – [in] The function to be registered to run by an HPX thread as a pre-startup function.

void **register_startup_function**(*startup_function_type* f)

Add a function to be executed by a HPX thread before `hpx_main` but guaranteed after any pre-startup function is executed (system-wide).

Any of the functions registered with `register_startup_function` are guaranteed to be executed by an HPX thread after any of the registered pre-startup functions are executed (see: `hpx::register_pre_startup_function()`), but before `hpx_main` is being called.

This function is one of the few API functions which can be called before the runtime system has been fully initialized. It will automatically stage the provided startup function to the runtime system during its initialization (if necessary).

See also:

`hpx::register_pre_startup_function()`

Note: If this function is called while the startup functions are being executed or after that point, it will raise an `invalid_status` exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a startup function.

hpx::get_locality_name

Defined in header `hpx/runtime.hpp`⁷⁵¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

std::string **get_locality_name**()

Return the name of the locality this function is called on.

This function returns the name for the locality on which this function is called.

See also:

future<std::string> `get_locality_name(hpx::id_type const& id)`

Returns

This function returns the name for the locality on which the function is called. The name is retrieved from the underlying networking layer and may be different for different parcelports.

⁷⁵¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

hpx/runtime_local/get_worker_thread_num.hpp

Defined in header `hpx/runtime_local/get_worker_thread_num.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_local/get_os_thread_count.hpp

Defined in header `hpx/runtime_local/get_os_thread_count.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`std::size_t get_os_thread_count()`

Return the number of OS-threads running in the runtime instance the current HPX-thread is associated with.

`std::size_t get_os_thread_count(threads::executor const &exec)`

Return the number of worker OS- threads used by the given executor to execute HPX threads.

This function returns the number of cores used to execute HPX threads for the given executor. If the function is called while no HPX runtime system is active, it will return zero. If the executor is not valid, this function will fall back to retrieving the number of OS threads used by HPX.

Parameters

exec – [in] The executor to be used.

namespace **threads**

hpx/runtime_local/thread_pool_helpers.hpp

Defined in header `hpx/runtime_local/thread_pool_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resource**

Functions

`std::size_t get_num_thread_pools()`

Return the number of thread pools currently managed by the *resource_partitioner*

`std::size_t get_num_threads()`

Return the number of threads in all thread pools currently managed by the *resource_partitioner*

`std::size_t get_num_threads(std::string const &pool_name)`

Return the number of threads in the given thread pool currently managed by the *resource_partitioner*

`std::size_t get_num_threads(std::size_t pool_index)`

Return the number of threads in the given thread pool currently managed by the *resource_partitioner*

`std::size_t get_pool_index(std::string const &pool_name)`

Return the internal index of the pool given its name.

`std::string const &get_pool_name(std::size_t pool_index)`

Return the name of the pool given its internal index.

`threads::thread_pool_base &get_thread_pool(std::string const &pool_name)`

Return the name of the pool given its name.

`threads::thread_pool_base &get_thread_pool(std::size_t pool_index)`

Return the thread pool given its internal index.

`bool pool_exists(std::string const &pool_name)`

Return true if the pool with the given name exists.

`bool pool_exists(std::size_t pool_index)`

Return true if the pool with the given index exists.

namespace **threads**

Functions

`std::int64_t get_thread_count(thread_schedule_state state = thread_schedule_state::unknown)`

The function *get_thread_count* returns the number of currently known threads.

Note: If `state == unknown` this function will not only return the number of currently existing threads, but will add the number of registered task descriptions (which have not been converted into threads yet).

Parameters

state – [in] This specifies the thread-state for which the number of threads should be retrieved.

`std::int64_t get_thread_count(thread_priority priority, thread_schedule_state state = thread_schedule_state::unknown)`

The function *get_thread_count* returns the number of currently known threads.

Note: If `state == unknown` this function will not only return the number of currently existing threads, but will add the number of registered task descriptions (which have not been converted into threads yet).

Parameters

- **priority** – [in] This specifies the thread-priority for which the number of threads should be retrieved.
- **state** – [in] This specifies the thread-state for which the number of threads should be retrieved.

`std::int64_t` **get_idle_core_count()**

The function `get_idle_core_count` returns the number of currently idling threads (cores).

`mask_type` **get_idle_core_mask()**

The function `get_idle_core_mask` returns a bit-mask representing the currently idling threads (cores).

`bool` **enumerate_threads**(*hpx::function<bool(thread_id_type)> const &f, thread_schedule_state state = thread_schedule_state::unknown*)

The function `enumerate_threads` will invoke the given function *f* for each thread with a matching thread state.

Parameters

- **f** – [in] The function which should be called for each matching thread. Returning ‘false’ from this function will stop the enumeration process.
- **state** – [in] This specifies the thread-state for which the threads should be enumerated.

hpx/runtime_local/service_executors.hpp

Defined in header `hpx/runtime_local/service_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Enums

enum class **service_executor_type** : `std::uint8_t`

Values:

enumerator **io_thread_pool**

Selects creating a service executor using the I/O pool of threads

enumerator **parcel_thread_pool**

Selects creating a service executor using the parcel pool of threads

enumerator **timer_thread_pool**

Selects creating a service executor using the timer pool of threads

enumerator **main_thread**

Selects creating a service executor using the main thread

struct **io_pool_executor** : public *hpx::execution::experimental::service_executor*

Public Functions

io_pool_executor()

struct **main_pool_executor** : public *hpx::execution::experimental::service_executor*

Public Functions

main_pool_executor()

struct **parcel_pool_executor** : public *hpx::execution::experimental::service_executor*

Public Functions

explicit **parcel_pool_executor**(char const *name_suffix = "-tcp")

struct **service_executor** : public *service_executor*

Subclassed by *hpx::execution::experimental::io_pool_executor*,
hpx::execution::experimental::main_pool_executor, *hpx::execution::experimental::parcel_pool_executor*,
hpx::execution::experimental::timer_pool_executor

Public Functions

explicit **service_executor**(*service_executor_type* t, char const *name_suffix = "")

struct **timer_pool_executor** : public *hpx::execution::experimental::service_executor*

Public Functions

timer_pool_executor()

hpx::shutdown_function_type, hpx::register_pre_shutdown_function, hpx::register_shutdown_function

Defined in header [hpx/runtime.hpp](#)⁷⁵².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Typedefs

using **shutdown_function_type** = *hpx::move_only_function*<void()>

The type of the function which is registered to be executed as a shutdown or pre-shutdown function.

Functions

void **register_pre_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed by a HPX thread during *hpx::finalize()* but guaranteed before any shutdown function is executed (system-wide)

Any of the functions registered with *register_pre_shutdown_function* are guaranteed to be executed by an HPX thread during the execution of *hpx::finalize()* before any of the registered shutdown functions are executed (see: *hpx::register_shutdown_function()*).

See also:

hpx::register_shutdown_function()

Note: If this function is called while the pre-shutdown functions are being executed, or after that point, it will raise an *invalid_status* exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a pre-shutdown function.

void **register_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed by a HPX thread during *hpx::finalize()* but guaranteed after any pre-shutdown function is executed (system-wide)

Any of the functions registered with *register_shutdown_function* are guaranteed to be executed by an HPX thread during the execution of *hpx::finalize()* after any of the registered pre-shutdown functions are executed (see: *hpx::register_pre_shutdown_function()*).

See also:

hpx::register_pre_shutdown_function()

Note: If this function is called while the shutdown functions are being executed, or after that point, it will raise an *invalid_status* exception.

⁷⁵² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Parameters

f – [in] The function to be registered to run by an HPX thread as a shutdown function.

hpx/runtime_local/runtime_local.hpp

Defined in header `hpx/runtime_local/runtime_local.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

void **set_error_handlers**(*hpx::util::runtime_configuration* const &cfg)

class **runtime**

Public Types

using **notification_policy_type** = *threads::policies::callback_notifier*

Generate a new notification policy instance for the given thread name prefix

using **hpx_main_function_type** = int()

The *hpx_main_function_type* is the default function type usable as the main HPX thread function.

using **hpx_errorsink_function_type** = void(*std::uint32_t*, *std::string* const&)

Public Functions

virtual *notification_policy_type* **get_notification_policy**(char const *prefix,
runtime_local::os_thread_type type)

state **get_state**() const

void **set_state**(state s)

explicit **runtime**(*hpx::util::runtime_configuration* rtcfg, bool initialize)

Construct a new HPX runtime instance.

virtual **~runtime**()

The destructor makes sure all HPX runtime services are properly shut down before exiting.

void **on_exit**(*hpx::function*<void()> const &f)

Manage list of functions to call on exit.

void **starting**()

Manage runtime ‘stopped’ state.

void **stopping**()

Call all registered `on_exit` functions.

bool **stopped**() const

This accessor returns whether the runtime instance has been stopped.

hpx::util::runtime_configuration &**get_config**()

access configuration information

hpx::util::runtime_configuration const &**get_config**() const

std::size_t **get_instance_number**() const

util::thread_mapper &**get_thread_mapper**() const

Return a reference to the internal PAPI thread manager.

threads::topology const &**get_topology**() const

virtual int **run**(*hpx::function<hpx_main_function_type>* const &func)

Run the HPX runtime system, use the given function for the main *thread* and block waiting for all threads to finish.

Note: The parameter *func* is optional. If no function is supplied, the runtime system will simply wait for the shutdown action without explicitly executing any main thread.

Parameters

func – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*. This parameter is optional and defaults to none main thread function, in which case all threads have to be scheduled explicitly.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter **func**.

virtual int **run**()

Run the HPX runtime system, initially use the given number of (OS) threads in the thread-manager and block waiting for all threads to finish.

Returns

This function will always return 0 (zero).

virtual void **rethrow_exception**()

Rethrow any stored exception (to be called after *stop()*)

virtual int **start**(*hpx::function<hpx_main_function_type>* const &func, bool blocking = false)

Start the runtime system.

Parameters

- **func** – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*.
- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function `runtime::start` will call `runtime::wait` internally.

Returns

If a blocking is a true, this function will return the value as returned as the result of the

invocation of the function object given by the parameter `func`. Otherwise, it will return zero.

virtual int **start**(bool blocking = false)

Start the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function `runtime::start` will call `runtime::wait` internally .

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter `func`. Otherwise, it will return zero.

virtual int **wait**()

Wait for the shutdown action to be executed.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter `func`.

virtual void **stop**(bool blocking = true)

Initiate termination of the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.

virtual int **suspend**()

Suspend the runtime system.

virtual int **resume**()

Resume the runtime system.

virtual int **finalize**(double)

virtual bool **is_networking_enabled**()

Return true if networking is enabled.

virtual *hpx::threads::threadmanager* &**get_thread_manager**()

Allow access to the thread manager instance used by the HPX runtime.

virtual *std::string* **here**() const

Returns a string of the locality endpoints (usable in debug output)

virtual bool **report_error**(*std::size_t* num_thread, *std::exception_ptr* const &*e*, bool terminate_all = true)

Report a non-recoverable error to the runtime system.

Parameters

- **num_thread** – [in] The number of the operating system thread the error has been detected in.
- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] signal whether all localities should be terminated

virtual bool **report_error**(*std::exception_ptr* const &*e*, bool terminate_all = true)

Report a non-recoverable error to the runtime system.

Note: This function will retrieve the number of the current shepherd thread and forward to the `report_error` function above.

Parameters

- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] signal whether all localities should be terminated

virtual void **add_pre_startup_function**(*startup_function_type* f)

Add a function to be executed inside a HPX thread before `hpx_main` but guaranteed to be executed before any startup function registered with `add_startup_function`.

Note: The difference to a startup function is that all pre-startup functions will be (system-wide) executed before any startup function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to set up the runtime environment of the application (install performance counters, etc.)

virtual void **add_startup_function**(*startup_function_type* f)

Add a function to be executed inside a HPX thread before `hpx_main`

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to set up the runtime environment of the application (install performance counters, etc.)

virtual void **add_pre_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed inside a HPX thread during `hpx::finalize`, but guaranteed before any of the shutdown functions is executed.

Note: The difference to a shutdown function is that all pre-shutdown functions will be (system-wide) executed before any shutdown function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

virtual void **add_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed inside a HPX thread during `hpx::finalize`

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

virtual `hpx::util::io_service_pool` ***get_thread_pool**(char const *name)

Access one of the internal thread pools (`io_service` instances) HPX is using to perform specific tasks. The three possible values for the argument `name` are “main_pool”, “io_pool”, “parcel_pool”, and “timer_pool”. For any other argument value the function will return zero.

virtual bool **register_thread**(char const *name, `std::size_t` num = 0, bool service_thread = true, `error_code` &ec = throws)

Register an external OS-thread with HPX.

This function should be called from any OS-thread which is external to HPX (not created by HPX), but which needs to access HPX functionality, such as setting a value on a promise or similar.

‘main’, ‘io’, ‘timer’, ‘parcel’, ‘worker’

Note: The function will compose a thread name of the form ‘<name>-thread#<num>’ which is used to register the thread. It is the user’s responsibility to ensure that each (composed) thread name is unique. HPX internally uses the following names for the threads it creates, do not reuse those:

Note: This function should be called for each thread exactly once. It will fail if it is called more than once.

Parameters

- **name** – [in] The name to use for thread registration.
- **num** – [in] The sequence number to use for thread registration. The default for this parameter is zero.
- **service_thread** – [in] The thread should be registered as a service thread. The default for this parameter is ‘true’. Any service threads will be pinned to cores not currently used by any of the HPX worker threads.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will return whether the requested operation succeeded or not.

virtual bool **unregister_thread()**

Unregister an external OS-thread with HPX.

This function will unregister any external OS-thread from HPX.

Note: This function should be called for each thread exactly once. It will fail if it is called more than once. It will fail as well if the thread has not been registered before (see *register_thread*).

Returns

This function will return whether the requested operation succeeded or not.

virtual runtime_local::os_thread_data **get_os_thread_data**(std::string const &label) const

Access data for a given OS thread that was previously registered by *register_thread*.

virtual bool **enumerate_os_threads**(hpx::function<bool(runtime_local::os_thread_data const&)>
const &f) const

Enumerate all OS threads that have registered with the runtime.

notification_policy_type::on_startstop_type **on_start_func**() const

notification_policy_type::on_startstop_type **on_stop_func**() const

notification_policy_type::on_error_type **on_error_func**() const

notification_policy_type::on_startstop_type **on_start_func**(notification_policy_type::on_startstop_type&&)

```

notification_policy_type::on_startstop_type on_stop_func(notification_policy_type::on_startstop_type&&)
notification_policy_type::on_error_type on_error_func(notification_policy_type::on_error_type&&)
virtual std::uint32_t get_locality_id(error_code &ec) const
virtual std::size_t get_num_worker_threads() const
virtual std::uint32_t get_num_localities(hpx::launch::sync_policy, error_code &ec) const
virtual std::uint32_t get_initial_num_localities() const
virtual hpx::future<std::uint32_t> get_num_localities() const
virtual std::string get_locality_name() const
virtual std::uint32_t assign_cores(std::string const&, std::uint32_t)
virtual std::uint32_t assign_cores()
inline hpx::program_options::options_description const &get_app_options() const
inline void set_app_options(hpx::program_options::options_description const &app_options)

```

Public Static Functions

```

static std::uint64_t get_system_uptime()
    Return the system uptime measure on the thread executing this call.

```

Protected Types

```

using on_exit_type = std::vector<hpx::function<void()>>

```

Protected Functions

```

explicit runtime(hpx::util::runtime_configuration rtcfg)
void set_notification_policies(notification_policy_type &&notifier,
                               threads::detail::network_background_callback_type const
                               &network_background_callback)
void init()
    Common initialization for different constructors.
void init_global_data()
threads::thread_result_type run_helper(hpx::function<runtime::hpx_main_function_type> const
                                         &func, int &result, bool call_startup_functions, void
                                         (*handle_print_bind)(std::size_t) = nullptr)
void wait_helper(std::mutex &mtx, std::condition_variable &cond, bool &running)

```

Protected Attributes

on_exit_type **on_exit_functions_**

mutable *std::mutex* **mtx_**

hpx::util::runtime_configuration **rtcfg_**

long **instance_number_**

std::unique_ptr<util::thread_mapper> **thread_support_**

threads::topology &**topology_**

std::atomic<state> **state_**

notification_policy_type::on_startstop_type **on_start_func_**

notification_policy_type::on_startstop_type **on_stop_func_**

notification_policy_type::on_error_type **on_error_func_**

int **result_**

std::exception_ptr **exception_**

notification_policy_type **main_pool_notifier_**

std::unique_ptr<util::io_service_pool> **main_pool_**

notification_policy_type **notifier_**

std::unique_ptr<hpx::threads::threadmanager> **thread_manager_**

Protected Static Functions

static void **deinit_global_data()**

Protected Static Attributes

`static std::atomic<int> instance_number_counter_`

Private Functions

void **stop_helper**(bool blocking, *std::condition_variable* &cond, *std::mutex* &mtx) const

Helper function to stop the runtime.

Parameters

- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.
- **cond** –
- **mtx** –

void **deinit_tss_helper**(char const *context, *std::size_t* num) const

void **init_tss_ex**(char const *context, *runtime_local::os_thread_type* type, *std::size_t* local_thread_num, *std::size_t* global_thread_num, char const *pool_name, char const *postfix, bool service_thread, *error_code* &ec) const

void **init_tss_helper**(char const *context, *runtime_local::os_thread_type* type, *std::size_t* local_thread_num, *std::size_t* global_thread_num, char const *pool_name, char const *postfix, bool service_thread) const

void **notify_finalize**()

void **wait_finalize**()

void **call_startup_functions**(bool pre_startup)

Private Members

std::list<startup_function_type> **pre_startup_functions_**

std::list<startup_function_type> **startup_functions_**

std::list<shutdown_function_type> **pre_shutdown_functions_**

std::list<shutdown_function_type> **shutdown_functions_**

bool **stop_called_**

bool **stop_done_**

std::condition_variable **wait_condition_**

hpx::program_options::options_description **app_options_**

namespace **threads**

Functions

char const ***get_stack_size_name**(*std::ptrdiff_t* size)

Returns the stack size name.

Get the readable string representing the given stack size constant.

Parameters

size – this represents the stack size

std::ptrdiff_t **get_default_stack_size**()

Returns the default stack size.

Get the default stack size in bytes.

std::ptrdiff_t **get_stack_size**(*thread_stacksize* size)

Returns the stack size corresponding to the given stack size enumeration.

Get the stack size corresponding to the given stack size enumeration.

Parameters

size – this represents the stack size

namespace **util**

Functions

bool **retrieve_commandline_arguments**(*hpx::program_options::options_description* const
&app_options, *hpx::program_options::variables_map*
&vm)

bool **retrieve_commandline_arguments**(*std::string* const &app_name,
hpx::program_options::variables_map &vm)

hpx/runtime_local/thread_hooks.hpp

Defined in header *hpx/runtime_local/thread_hooks.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

threads::policies::callback_notifier::on_startstop_type **get_thread_on_start_func()**

Retrieve the currently installed start handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered start function chains into the previous one (see *register_thread_on_start_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_startstop_type **get_thread_on_stop_func()**

Retrieve the currently installed stop handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered stop function chains into the previous one (see *register_thread_on_stop_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_error_type **get_thread_on_error_func()**

Retrieve the currently installed error handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered error function chains into the previous one (see *register_thread_on_error_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_startstop_type **register_thread_on_start_func**(*threads::policies::callback_notifier::*
&&f)

Set the currently installed start handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered start function chains into the previous one (see *get_thread_on_start_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new start handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

threads::policies::callback_notifier::on_startstop_type **register_thread_on_stop_func**(*threads::policies::callback_notifier::on_startstop_type* &&f)

Set the currently installed stop handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered stop function chains into the previous one (see *get_thread_on_stop_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new stop handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

threads::policies::callback_notifier::on_error_type **register_thread_on_error_func**(*threads::policies::callback_notifier::on_error_type* &&f)

Set the currently installed error handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered error function chains into the previous one (see *get_thread_on_error_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new error handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

hpx/runtime_local/report_error.hpp

Defined in header `hpx/runtime_local/report_error.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

void **report_error**(std::size_t num_thread, std::exception_ptr const &e)

The function report_error reports the given exception to the console.

void **report_error**(std::exception_ptr const &e)

The function report_error reports the given exception to the console.

hpx::get_locality_id

Defined in header [hpx/runtime.hpp](#)⁷⁵³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

std::uint32_t **get_locality_id**(error_code &ec = throws)

Return the number of the locality this function is being called from.

This function returns the id of the current locality.

Note: The returned value is zero based and its maximum value is smaller than the overall number of localities the current application is running on (as returned by get_num_localities()).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx/runtime_local/termination_detection.hpp

Defined in header `hpx/runtime_local/termination_detection.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **local**

⁷⁵³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Functions

void **termination_detection**()

Wait for all local HPX threads to complete execution.

This function blocks the calling thread until all HPX worker threads on the current locality have completed their work and become idle. It performs local termination detection by waiting for the thread manager to drain all pending tasks.

Example:

```
#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>

int hpx_main()
{
    // Launch some asynchronous work
    for (int i = 0; i < 100; ++i)
    {
        hpx::post([]{ /* do work */ });
    }

    // Wait for all local threads to complete
    hpx::local::termination_detection();

    return hpx::finalize();
}
```

Note: This function should be called from an HPX thread or after the HPX runtime has been initialized.

Throws

hpx::exception – if called when the runtime is not in a valid state (e.g., before initialization or after shutdown).

bool **termination_detection**(*hpx::chrono::steady_duration* const &timeout)

Wait for all local HPX threads to complete with a timeout.

This function blocks the calling thread until either all HPX worker threads have completed their work, or the specified timeout duration has elapsed.

See also:

`termination_detection()`

Example:

```
#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <chrono>

int hpx_main()
{
```

(continues on next page)

(continued from previous page)

```

// Launch some work
hpx::post([]{ /* long running task */ });

// Wait up to 5 seconds
if (!hpx::local::termination_detection(std::chrono::seconds(5)))
{
    std::cerr << "Warning: Work did not complete within timeout\n";
    // Implement fallback strategy
}

return hpx::finalize();
}

```

Parameters

timeout – Maximum duration to wait for termination. The function will return false if this duration elapses before all threads complete.

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed before the timeout, false if the timeout elapsed.

bool **termination_detection**(*hpx::chrono::steady_time_point* const &deadline)

Wait for all local HPX threads to complete until a deadline.

This function blocks the calling thread until either all HPX worker threads have completed their work, or the specified deadline time point is reached.

See also:

termination_detection(std::chrono::duration<double>)

Example:

```

#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <chrono>

int hpx_main()
{
    auto deadline = std::chrono::steady_clock::now() +
        std::chrono::seconds(10);

    hpx::post([]{ /* work */ });

    if (!hpx::local::termination_detection(deadline))
    {
        std::cerr << "Deadline reached\n";
    }

    return hpx::finalize();
}

```

Parameters

deadline – Absolute time point when waiting should stop. The function will return false

if this time is reached before all threads complete.

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed before the deadline, false if the deadline was reached.

```
bool termination_detection(hpx::stop_token stop_token, hpx::chrono::steady_duration const
                           &timeout =
                           hpx::chrono::steady_duration((hpx::chrono::steady_clock::duration::max)()))
```

Wait for all local HPX threads with cancellation support.

This function blocks the calling thread until all HPX worker threads have completed, the timeout elapses, or a stop is requested via the stop_token. This enables cooperative cancellation of the wait operation.

See also:

`termination_detection(std::chrono::duration<double>)`

Example:

```
#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <hpx/stop_token.hpp>
#include <chrono>

int hpx_main()
{
    hpx::stop_source stop_src;

    // In shutdown handler
    hpx::thread shutdown_thread([&stop_src]() {
        hpx::this_thread::sleep_for(std::chrono::seconds(30));
        stop_src.request_stop();
    });

    hpx::post([]{ /* work */ });

    // Wait with cancellation support
    bool completed = hpx::local::termination_detection(
        stop_src.get_token(),
        std::chrono::minutes(1)
    );

    if (!completed)
    {
        std::cerr << "Cancelled or timed out\n";
    }

    shutdown_thread.join();
    return hpx::finalize();
}
```

Parameters

- **stop_token** – Token that can be used to request cancellation of the wait operation.

- **timeout** – Maximum duration to wait. Defaults to maximum duration (effectively infinite).

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed, false if timeout elapsed or stop was requested.

hpx::get_thread_name

Defined in header [hpx/runtime.hpp](#)⁷⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

std::string **get_thread_name**()

Return the name of the calling thread.

This function returns the name of the calling thread. This name uniquely identifies the thread in the context of HPX. If the function is called while no HPX runtime system is active, the result will be “<unknown>”.

hpx::register_thread, **hpx::unregister_thread**, **hpx::get_os_thread_data**,
hpx::enumerate_os_threads, **hpx::get_runtime_instance_number**, **hpx::register_on_exit**,
hpx::is_starting, **hpx::tolerate_node_faults**, **hpx::is_running**, **hpx::is_stopped**,
hpx::is_stopped_or_shutting_down, **hpx::get_num_worker_threads**, **hpx::get_system_uptime**

Defined in header [hpx/runtime.hpp](#)⁷⁵⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

bool **register_thread**(*runtime *rt*, char const *name, *error_code &ec* = *throws*)

Register the current kernel thread with HPX, this should be done once for each external OS-thread intended to invoke HPX functionality. Calling this function more than once will return false.

void **unregister_thread**(*runtime *rt*)

Unregister the thread from HPX, this should be done once in the end before the external thread exists.

runtime_local::os_thread_data **get_os_thread_data**(*std::string const &label*)

Access data for a given OS thread that was previously registered by *register_thread*. This function must be called from a thread that was previously registered with the runtime.

bool **enumerate_os_threads**(*hpx::function<bool(os_thread_data const&)> const &f*)

Enumerate all OS threads that have registered with the runtime.

⁷⁵⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

⁷⁵⁵ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

`std::size_t get_runtime_instance_number()`

Return the runtime instance number associated with the runtime instance the current thread is running in.

bool **register_on_exit**(*hpx::function<void()> const&*)

Register a function to be called during system shutdown.

bool **is_starting**()

Test whether the runtime system is currently being started.

This function returns whether the runtime system is currently being started or not, e.g. whether the current state of the runtime system is *hpx::state::startup*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

bool **tolerate_node_faults**()

Test if HPX runs in fault-tolerant mode.

This function returns whether the runtime system is running in fault-tolerant mode

bool **is_running**()

Test whether the runtime system is currently running.

This function returns whether the runtime system is currently running or not, e.g. whether the current state of the runtime system is *hpx::state::running*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

bool **is_stopped**()

Test whether the runtime system is currently stopped.

This function returns whether the runtime system is currently stopped or not, e.g. whether the current state of the runtime system is *hpx::state::stopped*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

bool **is_stopped_or_shutting_down**()

Test whether the runtime system is currently being shut down.

This function returns whether the runtime system is currently being shut down or not, e.g. whether the current state of the runtime system is *hpx::state::stopped* or *hpx::state::shutdown*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

`std::size_t get_num_worker_threads()`

Return the number of worker OS- threads used to execute HPX threads.

This function returns the number of OS-threads used to execute HPX threads. If the function is called while no HPX runtime system is active, it will return zero.

`std::uint64_t get_system_uptime()`

Return the system uptime measure on the thread executing this call.

This function returns the system uptime measured in nanoseconds for the thread executing this call. If the function is called while no HPX runtime system is active, it will return zero.

namespace **threads**

hpx/runtime_local/component_startup_shutdown_base.hpp

Defined in header `hpx/runtime_local/component_startup_shutdown_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

struct **component_startup_shutdown_base**

#include <component_startup_shutdown_base.hpp> The `component_startup_shutdown_base` has to be used as a base class for all component startup/shutdown registries.

Public Functions

virtual `~component_startup_shutdown_base()` = default

virtual bool **get_startup_function**(*startup_function_type* &startup, bool &pre_startup) = 0

Return any startup function for this component.

Parameters

- **startup** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_startup** – [in, out] Will be set to true if the returned startup function is executed during the first round of calls.

Returns

Returns *true* if the parameter *startup* has been successfully initialized with the startup function.

virtual bool **get_shutdown_function**(*shutdown_function_type* &shutdown, bool &pre_shutdown) = 0

Return any startup function for this component.

Parameters

- **shutdown** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_shutdown** – [in, out] Will be set to true if the returned shutdown function is executed during the first round of calls.

Returns

Returns *true* if the parameter *shutdown* has been successfully initialized with the shutdown function.

serialization

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/serialization/base_object.hpp

Defined in header `hpx/serialization/base_object.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Derived, typename Base>
```

```
struct base_object_type<Derived, Base, std::enable_if_t<hpx::traits::is_intrusive_polymorphic_v<Derived>>>
```

Public Functions

```
inline explicit constexpr base_object_type(Derived &d) noexcept
```

```
template<typename Archive>  
inline void save(Archive &ar, unsigned) const
```

```
template<typename Archive>  
inline void load(Archive &ar, unsigned)
```

```
HPX_SERIALIZATION_SPLIT_MEMBER()
```

Public Members

Derived &**d_**

```
namespace hpx
```

```
namespace serialization
```

Functions

```
template<typename Base, typename Derived>  
constexpr base_object_type<Derived, Base> base_object(Derived &d) noexcept
```

```
template<typename D, typename B>  
output_archive &operator<<(output_archive &ar, base_object_type<D, B> t)
```

```
template<typename D, typename B>  
input_archive &operator>>(input_archive &ar, base_object_type<D, B> t)
```

```
template<typename D, typename B>  
output_archive &operator&(output_archive &ar, base_object_type<D, B> t)
```

```
template<typename D, typename B>  
input_archive &operator&(input_archive &ar, base_object_type<D, B> t)
```

```
template<typename Derived, typename Base, typename Enable = void>
```

```
struct base_object_type
```

Public Functions

```
inline explicit constexpr base_object_type(Derived &d) noexcept
```

```
template<typename Archive>
inline void serialize(Archive &ar, unsigned)
```

Public Members

Derived &d_

```
template<typename Derived,
typename Base> is_intrusive_polymorphic_v< Derived > > >
```

Public Functions

```
inline explicit constexpr base_object_type(Derived &d) noexcept
```

```
template<typename Archive>
inline void save(Archive &ar, unsigned) const
```

```
template<typename Archive>
inline void load(Archive &ar, unsigned)
```

```
HPX_SERIALIZATION_SPLIT_MEMBER()
```

Public Members

Derived &d_

synchronization

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/synchronization/event.hpp

Defined in header `hpx/synchronization/event.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace lcos
```

namespace **local**

class **event**

#include <event.hpp> Event semaphores can be used for synchronizing multiple threads that need to wait for an event to occur. When the event occurs, all threads waiting for the event are woken up.

Public Functions

inline **event**() noexcept

Construct a new event semaphore.

inline bool **occurred**() const noexcept

Check if the event has occurred.

inline void **wait**()

Wait for the event to occur.

inline void **set**()

Release all threads waiting on this semaphore.

inline void **reset**() noexcept

Reset the event.

Private Types

using **mutex_type** = *hpx::spinlock*

Private Functions

inline void **wait_locked**(*std::unique_lock<mutex_type>* &l)

inline void **set_locked**(*std::unique_lock<mutex_type>* l)

Private Members

mutex_type **mtx_**

This mutex protects the queue.

local::detail::condition_variable **cond_**

std::atomic<bool> **event_**

hpx::no_mutex

Defined in header [hpx/mutex.hpp](#)⁷⁵⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

struct **no_mutex**

#include <no_mutex.hpp> **no_mutex** class can be used in cases where the shared data between multiple threads can be accessed simultaneously without causing inconsistencies.

Public Static Functions

static inline constexpr void **lock**() noexcept

static inline constexpr bool **try_lock**() noexcept

static inline constexpr void **unlock**() noexcept

hpx::binary_semaphore

Defined in header [hpx/semaphore.hpp](#)⁷⁵⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

class **binary_semaphore**

#include <binary_semaphore.hpp> A binary semaphore is a semaphore object that has only two states. **binary_semaphore** is an alias for specialization of **hpx::counting_semaphore** with *LeastMaxValue* being 1. HPX's implementation of **binary_semaphore** is more efficient than the default implementation of a counting semaphore with a unit resource count (**hpx::counting_semaphore**).

Public Functions

binary_semaphore(*binary_semaphore* const&) = delete

binary_semaphore &**operator**=(*binary_semaphore* const&) = delete

binary_semaphore(*binary_semaphore*&&) = delete

binary_semaphore &**operator**=(*binary_semaphore*&&) = delete

explicit **binary_semaphore**(*std::ptrdiff_t* value = 1)

Constructs an object of type **hpx::binary_semaphore** with the internal counter initialized to *value*.

⁷⁵⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

⁷⁵⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/semaphore.hpp

Parameters

value – The initial value of the internal semaphore lock count. Normally this value should be zero (which is the default), values greater than zero are equivalent to the same number of signals pre-set, and negative values are equivalent to the same number of waits pre-set.

~binary_semaphore() = default

void **release**(std::ptrdiff_t update = 1)

Atomically increments the internal counter by the value of update. Any thread(s) waiting for the counter to be greater than 0, such as due to being blocked in acquire, will subsequently be unblocked.

Note: Synchronization: Strongly happens before invocations of *try_acquire* that observe the result of the effects.

Throws

std::system_error –

Parameters

update – the amount to increment the internal counter by

Pre

Both `update >= 0` and `update <= max() - counter` are *true*, where *counter* is the value of the internal counter.

bool **try_acquire**() noexcept

Tries to atomically decrement the internal counter by 1 if it is greater than 0; no blocking occurs regardless.

Returns

true if it decremented the internal counter, otherwise *false*

void **acquire**()

Repeatedly performs the following steps, in order:

- Evaluates `try_acquire`. If the result is true, returns.
- Blocks on `*this` until counter is greater than zero.

Throws

std::system_error –

Returns

void.

bool **try_acquire_until**(hpx::chrono::steady_time_point const &abs_time)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the *abs_time* time point has been passed.

Parameters

abs_time – the earliest time the function must wait until in order to fail

Throws

std::system_error –

Returns

true if it decremented the internal counter, otherwise *false*.

bool **try_acquire_for**(hpx::chrono::steady_duration const &rel_time)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the *rel_time* duration has been exceeded.

Throws`std::system_error` –**Parameters****rel_time** – the minimum duration the function must wait for to fail**Returns**`true` if it decremented the internal counter, otherwise `false`**Public Static Functions**static constexpr `std::ptrdiff_t` **max()** noexceptReturns The maximum value of counter. This value is greater than or equal to *LeastMaxValue*.**Returns**The internal counter's maximum possible value, as a `std::ptrdiff_t`.**hpx::condition_variable, hpx::condition_variable_any, hpx::cv_status**Defined in header `hpx/condition_variable.hpp`⁷⁵⁸.See *Public API* for a list of names and headers that are part of the public HPX API.namespace **hpx****Enums**enum class **cv_status**

The scoped enumeration `hpx::cv_status` describes whether a timed wait returned because of timeout or not. `hpx::cv_status` is used by the `wait_for` and `wait_until` member functions of `hpx::condition_variable` and `hpx::condition_variable_any`.

*Values:*enumerator **no_timeout**The condition variable was awakened with `notify_all`, `notify_one`, or spuriouslyenumerator **timeout**

the condition variable was awakened by timeout expiration

enumerator **error**

there was an error

class **condition_variable**

`#include <condition_variable.hpp>` The `condition_variable` class is a synchronization primitive that can be used to block a thread, or multiple threads at the same time, until another thread both modifies a shared variable (the condition), and notifies the `condition_variable`.

The thread that intends to modify the shared variable has to

- i. acquire a `hpx::mutex` (typically via `std::lock_guard`)

⁷⁵⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/condition_variable.hpp

- ii. perform the modification while the lock is held
- iii. execute *notify_one* or *notify_all* on the *condition_variable* (the lock does not need to be held for notification)

Even if the shared variable is atomic, it must be modified under the mutex in order to correctly publish the modification to the waiting thread. Any thread that intends to wait on *condition_variable* has to

- i. acquire a *std::unique_lock<hpx::mutex>*, on the same mutex as used to protect the shared variable
- ii. either
 - A. check the condition, in case it was already updated and notified
 - B. execute *wait*, *wait_for*, or *wait_until*. The wait operations atomically release the mutex and suspend the execution of the thread.
 - C. When the condition variable is notified, a timeout expires, or a spurious wakeup occurs, the thread is awakened, and the mutex is atomically reacquired. The thread should then check the condition and resume waiting if the wake up was spurious. or
- A. use the predicated overload of *wait*, *wait_for*, and *wait_until*, which takes care of the three steps above.

hpx::condition_variable works only with *std::unique_lock<hpx::mutex>*. This restriction allows for maximal efficiency on some platforms. *hpx::condition_variable_any* provides a condition variable that works with any [BasicLockable](#)⁷⁵⁹ object, such as *std::shared_lock*.

Condition variables permit concurrent invocation of the *wait*, *wait_for*, *wait_until*, *notify_one* and *notify_all* member functions.

The class *hpx::condition_variable* is a [StandardLayoutType](#)⁷⁶⁰. It is not [CopyConstructible](#)⁷⁶¹, [MoveConstructible](#)⁷⁶², [CopyAssignable](#)⁷⁶³, or [MoveAssignable](#)⁷⁶⁴.

Public Functions

inline condition_variable()

Construct an object of type *hpx::condition_variable*.

~condition_variable() = default

Destroys the object of type *hpx::condition_variable*.

IOW, *~condition_variable()* can execute before a signaled thread returns from a wait. If this happens with *condition_variable*, that waiting thread will attempt to lock the destructed mutex. To fix this, there must be shared ownership of the data members between the *condition_variable* object and the member functions *wait* (*wait_for*, etc.).

Note: Preconditions: There is no thread blocked on **this*. [Note: That is, all threads have been notified; they could subsequently block on the lock specified in the wait. This relaxes the usual rules, which would have required all wait calls to happen before destruction. Only the notification to unblock the wait needs to happen before destruction. The user should take care to ensure that no threads wait on **this* once the destructor has been started, especially when the waiting threads are calling the *wait* functions in a loop or using the overloads of *wait*, *wait_for*, or *wait_until* that take a predicate. end note]

condition_variable(*condition_variable* const&) = delete

condition_variable(*condition_variable*&&) = delete

condition_variable &**operator**=(*condition_variable* const&) = delete

condition_variable &**operator**=(*condition_variable*&&) = delete

inline void **notify_one**(*error_code* &ec = *throws*) const

If any threads are waiting on **this*, calling *notify_one* unblocks one of the waiting threads.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

notify_one returns *void*.

inline void **notify_all**(*error_code* &ec = *throws*) const

Unblocks all threads currently waiting for **this*.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

notify_all returns *void*.

template<typename **Mutex**>

inline void **wait**(*std::unique_lock*<*Mutex*> &lock, *error_code* &ec = *throws*)

wait causes the current thread to block until the condition variable is notified or a spurious wakeup occurs, optionally looping until some predicate is satisfied (*bool*(*pred*())==*true*).

Atomically unlocks lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when *notify_all*() or *notify_one*() is executed. It may also be unblocked spuriously. When unblocked, regardless of the reason, lock is reacquired and *wait* exits.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.

A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.

Template Parameters

Mutex – Type of mutex to wait on.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

wait returns *void*.

template<typename **Mutex**, typename **Predicate**>

inline void **wait**(*std::unique_lock*<*Mutex*> &lock, *Predicate* pred, *error_code*& = *throws*)

wait causes the current thread to block until the condition variable is notified or a spurious wakeup occurs, optionally looping until some predicate is satisfied (*bool*(*pred*())==*true*).

Equivalent to

```
while (!pred()) {
    wait(lock);
}
```

This overload may be used to ignore spurious awakenings while waiting for a specific condition to become true. Note that lock must be acquired before entering this method, and it is reacquired after *wait(lock)* exits, which means that lock can be used to guard access to *pred()*.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.
A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.

Template Parameters

- **Mutex** – Type of mutex to wait on.
- **Predicate** – Type of predicate *pred* function.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread
- **pred** – Predicate which returns *false* if the waiting should be continued (`bool(pred())==false`). The signature of the predicate function should be equivalent to the following: `bool pred();`

Returns

wait returns *void*.

```
template<typename Mutex>
inline cv_status wait_until(std::unique_lock<Mutex> &lock, hpx::chrono::steady_time_point const
                             &abs_time, error_code &ec = throws)
```

wait_until causes the current thread to block until the condition variable is notified, a specific time is reached, or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred())==true`).

Atomically releases lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when `notify_all()` or `notify_one()` is executed, or when the absolute time point *abs_time* is reached. It may also be unblocked spuriously. When unblocked, regardless of the reason, lock is reacquired and *wait_until* exits.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.
A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.

Template Parameters

Mutex – Type of mutex to wait on.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread
- **abs_time** – Represents the time when waiting should be stopped
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`cv_status wait_until` returns `hpx::cv_status::timeout` if the absolute timeout specified by *abs_time* was reached and `hpx::cv_status::no_timeout` otherwise.

```
template<typename Mutex, typename Predicate>
inline bool wait_until(std::unique_lock<Mutex> &lock, hpx::chrono::steady_time_point const
                       &abs_time, Predicate pred, error_code &ec = throws)
```

wait_until causes the current thread to block until the condition variable is notified, a specific time is reached, or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred())==true`).

Equivalent to

```
while (!pred()) {
    if (wait_until(lock, abs_time) == hpx::cv_status::timeout) {
        return pred();
    }
}
return true;
```

This overload may be used to ignore spurious wakeups.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.
 A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.

Template Parameters

- **Mutex** – Type of mutex to wait on.
- **Predicate** – Type of predicate *pred* function.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread
- **abs_time** – Represents the time when waiting should be stopped
- **pred** – Predicate which returns *false* if the waiting should be continued (`bool(pred())==false`). The signature of the predicate function should be equivalent to the following: `bool pred()`;
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`bool wait_until` returns *false* if the predicate *pred* still evaluates to false after the *abs_time* timeout has expired, otherwise *true*. If the timeout had already expired, evaluates and returns the result of *pred*.

```
template<typename Mutex>
inline cv_status wait_for(std::unique_lock<Mutex> &lock, hpx::chrono::steady_duration const
    &rel_time, error_code &ec = throws)
```

Atomically releases lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when `notify_all()` or `notify_one()` is executed, or when the relative timeout *rel_time* expires. It may also be unblocked spuriously. When unblocked, regardless of the reason, lock is reacquired and `wait_for()` exits.

The standard recommends that a steady clock be used to measure the duration. This function may block for longer than *rel_time* due to scheduling or resource contention delays.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.
 A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.
 B. Even if notified under lock, this overload makes no guarantees about the state of the associated predicate when returning due to timeout.

Template Parameters

Mutex – Type of mutex to wait on.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread

- **rel_time** – represents the maximum time to spend waiting. Note that *rel_time* must be small enough not to overflow when added to *hpx::chrono::steady_clock::now()*.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

cv_status *hpx::cv_status::timeout* if the relative timeout specified by *rel_time* expired, *hpx::cv_status::no_timeout* otherwise.

```
template<typename Mutex, typename Predicate>  
inline bool wait_for(std::unique_lock<Mutex> &lock, hpx::chrono::steady_duration const &rel_time,  
                    Predicate pred, error_code &ec = throws)
```

Equivalent to.

```
return wait_until(lock,  
                 hpx::chrono::steady_clock::now() + rel_time,  
                 hpx::move(pred));
```

This overload may be used to ignore spurious awakenings by looping until some predicate is satisfied (*bool*(pred())==*true*).

The standard recommends that a steady clock be used to measure the duration. This function may block for longer than *rel_time* due to scheduling or resource contention delays.

Note: 1. Calling this function if *lock.mutex()* is not locked by the current thread is undefined behavior.
A. Calling this function if *lock.mutex()* is not the same mutex as the one used by all other threads that are currently waiting on the same condition variable is undefined behavior.

Template Parameters

- **Mutex** – Type of mutex to wait on.
- **Predicate** – Type of predicate *pred* function.

Parameters

- **lock** – *unique_lock* that must be locked by the current thread
- **rel_time** – represents the maximum time to spend waiting. Note that *rel_time* must be small enough not to overflow when added to *hpx::chrono::steady_clock::now()*.
- **pred** – Predicate which returns *false* if the waiting should be continued (*bool*(pred())==*false*). The signature of the predicate function should be equivalent to the following: *bool pred()* ;
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool wait_for returns *false* if the predicate *pred* still evaluates to *false* after the *rel_time* timeout expired, otherwise *true*.

Private Types

```
using mutex_type = lcos::local::detail::condition_variable_data::mutex_type
```

```
using data_type = hpx::intrusive_ptr<lcos::local::detail::condition_variable_data>
```

Private Members

```
hpx::util::cache_aligned_data_derived<data_type> data_
```

```
class condition_variable_any
```

#include <condition_variable.hpp> The `condition_variable_any` class is a generalization of `hpx::condition_variable`. Whereas `hpx::condition_variable` works only on `std::unique_lock<std::mutex>`, a `condition_variable_any` can operate on any lock that meets the [BasicLockable⁷⁶⁵](#) requirements.

See `hpx::condition_variable` for the description of the semantics of condition variables. It is not [CopyConstructible⁷⁶⁶](#), [MoveConstructible⁷⁶⁷](#), [CopyAssignable⁷⁶⁸](#), or [MoveAssignable⁷⁶⁹](#).

Public Functions

```
inline condition_variable_any()
```

Constructs an object of type `hpx::condition_variable_any`.

```
~condition_variable_any() = default
```

Destroys the object of type `hpx::condition_variable_any`.

It is only safe to invoke the destructor if all threads have been notified. It is not required that they have exited their respective wait functions: some threads may still be waiting to reacquire the associated lock, or may be waiting to be scheduled to run after reacquiring it.

The programmer must ensure that no threads attempt to wait on **this* once the destructor has been started, especially when the waiting threads are calling the wait functions in a loop or are using the overloads of the wait functions that take a predicate.

Preconditions: There is no thread blocked on **this*. [Note: That is, all threads have been notified; they could subsequently block on the lock specified in the wait. This relaxes the usual rules, which would have required all wait calls to happen before destruction. Only the notification to unblock the wait needs to happen before destruction. The user should take care to ensure that no threads wait on **this* once the destructor has been started, especially when the waiting threads are calling the *wait* functions in a loop or using the overloads of *wait*, *wait_for*, or *wait_until* that take a predicate. end note]

IOW, `~condition_variable_any()` can execute before a signaled thread returns from a wait. If this happens with `condition_variable_any`, that waiting thread will attempt to lock the destructed mutex. To fix this, there must be shared ownership of the data members between the `condition_variable_any` object and the member functions *wait* (*wait_for*, etc.).

```
condition_variable_any(condition_variable_any const&) = delete
```

```
condition_variable_any(condition_variable_any&&) = delete
```

```
condition_variable_any &operator=(condition_variable_any const&) = delete
```

condition_variable_any &operator=(*condition_variable_any*&&) = delete

inline void **notify_one**(*error_code* &ec = *throws*) const

If any threads are waiting on **this*, calling *notify_one* unblocks one of the waiting threads.

The notifying thread does not need to hold the lock on the same mutex as the one held by the waiting thread(s); in fact doing so is a pessimization, since the notified thread would immediately block again, waiting for the notifying thread to release the lock. However, some implementations (in particular many implementations of pthreads) recognize this situation and avoid this “hurry up and wait” scenario by transferring the waiting thread from the condition variable’s queue directly to the queue of the mutex within the notify call, without waking it up.

Notifying while under the lock may nevertheless be necessary when precise scheduling of events is required, e.g. if the waiting thread would exit the program if the condition is satisfied, causing destruction of the notifying thread’s condition variable. A spurious wakeup after mutex unlock but before notify would result in notify called on a destroyed object.

Note: The effects of *notify_one()/notify_all()* and each of the three atomic parts of *wait()/wait_for()/wait_until()* (unlock+wait wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for *notify_one()* to, for example, be delayed and unblock a thread that started waiting just after the call to *notify_one()* was made.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

notify_one returns *void*.

inline void **notify_all**(*error_code* &ec = *throws*) const

Unblocks all threads currently waiting for **this*.

The notifying thread does not need to hold the lock on the same mutex as the one held by the waiting thread(s); in fact doing so is a pessimization, since the notified thread would immediately block again, waiting for the notifying thread to release the lock.

Note: The effects of *notify_one()/notify_all()* and each of the three atomic parts of *wait()/wait_for()/wait_until()* (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for *notify_one()* to, for example, be delayed and unblock a thread that started waiting just after the call to *notify_one()* was made.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

notify_all returns *void*.

template<typename **Lock**>

inline void **wait**(Lock &lock, error_code &ec = throws)

wait causes the current thread to block until the condition variable is notified or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred())==true`).

Atomically unlocks lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when `notify_all()` or `notify_one()` is executed. It may also be unblocked spuriously. When unblocked, regardless of the reason, lock is reacquired and wait exits.

The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Note: If these functions fail to meet the postconditions (lock is locked by the calling thread), `std::terminate` is called. For example, this could happen if re-locking the mutex throws an exception.

Template Parameters

Lock – Type of *lock*.

Parameters

- **lock** – An object of type *Lock* that meets the [BasicLockable](#)⁷⁷⁰ requirements, which must be locked by the current thread
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special 'throw on error' *error_code*.

Returns

wait returns *void*.

template<typename **Lock**, typename **Predicate**>

inline void **wait**(Lock &lock, Predicate pred, error_code& = throws)

wait causes the current thread to block until the condition variable is notified or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred())==true`).

Equivalent to

```
while (!pred()) {
    wait(lock);
}
```

This overload may be used to ignore spurious awakenings while waiting for a specific condition to become true. Note that lock must be acquired before entering this method, and it is reacquired after `wait(lock)` exits, which means that lock can be used to guard access to `pred()`.

The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Note: If these functions fail to meet the postconditions (lock is locked by the calling thread), `std::terminate` is called. For example, this could happen if re-locking the mutex throws an exception.

Template Parameters

- **Lock** – Type of *lock*.
- **Predicate** – Type of *pred*.

Parameters

- **lock** – an object of type *Lock* that meets the [BasicLockable](#)⁷⁷¹ requirements, which must be locked by the current thread
- **pred** – predicate which returns `false` if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred()`.

Returns

wait returns *void*.

```
template<typename Lock>
inline cv_status wait_until(Lock &lock, hpx::chrono::steady_time_point const &abs_time, error_code
                             &ec = throws)
```

wait_until causes the current thread to block until the condition variable is notified, a specific time is reached, or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred()) == true`).

Atomically releases lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when `notify_all()` or `notify_one()` is executed, or when the absolute time point *abs_time* is reached. It may also be unblocked spuriously. When unblocked, regardless of the reason, lock is reacquired and *wait_until* exits.

Note: The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (`unlock+wait`, `wakeup`, and `lock`) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Template Parameters

Lock – Type of *lock*.

Parameters

- **lock** – an object of type *Lock* that meets the requirements of [BasicLockable](#)⁷⁷², which must be locked by the current thread
- **abs_time** – represents the time when waiting should be stopped.
- **ec** – used to hold error code value originated during the operation. Defaults to *throws* `—`; A special ‘throw on error’ *error_code*.

Returns

`cv_status hpx::cv_status::timeout` if the absolute timeout specified by *abs_time* was reached, `hpx::cv_status::no_timeout` otherwise.

```
template<typename Lock, typename Predicate>
inline bool wait_until(Lock &lock, hpx::chrono::steady_time_point const &abs_time, Predicate pred,
                       error_code &ec = throws)
```

wait_until causes the current thread to block until the condition variable is notified, a specific time is reached, or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred()) == true`).

Equivalent to

```
while (!pred()) {
    if (wait_until(lock, timeout_time) == hpx::cv_status::timeout) {
        return pred();
    }
}
```

(continues on next page)

(continued from previous page)

```

    }
}
return true;

```

This overload may be used to ignore spurious wakeups.

Note: The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Template Parameters

- **Lock** – Type of *lock*.
- **Predicate** – Type of *pred*.

Parameters

- **lock** – an object of type *Lock* that meets the requirements of [BasicLockable⁷⁷³](#), which must be locked by the current thread
- **abs_time** – represents the time when waiting should be stopped.
- **pred** – predicate which returns *false* if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred();`
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool false if the predicate *pred* still evaluates to *false* after the *abs_time* timeout expired, otherwise true. If the timeout had already expired, evaluates and returns the result of *pred*.

```

template<typename Lock>
inline cv_status wait_for(Lock &lock, hpx::chrono::steady_duration const &rel_time, error_code &ec
                        = throws)

```

Atomically releases lock, blocks the current executing thread, and adds it to the list of threads waiting on **this*. The thread will be unblocked when `notify_all()` or `notify_one()` is executed, or when the relative timeout *rel_time* expires. It may also be unblocked spuriously. When unblocked, regardless of the reason, *lock* is reacquired and `wait_for()` exits.

The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Note: Even if notified under lock, this overload makes no guarantees about the state of the associated predicate when returning due to timeout.

Template Parameters

Lock – Type of *lock*.

Parameters

- **lock** – an object of type *Lock* that meets the [BasicLockable⁷⁷⁴](#) requirements, which must be locked by the current thread.

- **rel_time** – an object of type `hpx::chrono::duration` representing the maximum time to spend waiting. Note that `rel_time` must be small enough not to overflow when added to `hpx::chrono::steady_clock::now()`.
- **ec** – Used to hold error code value originated during the operation. Defaults to `throws` — A special ‘throw on error’ `error_code`.

Returns

`cv_status hpx::cv_status::timeout` if the relative timeout specified by `rel_time` expired, `hpx::cv_status::no_timeout` otherwise.

```
template<typename Lock, typename Predicate>
inline bool wait_for(Lock &lock, hpx::chrono::steady_duration const &rel_time, Predicate pred,
                    error_code &ec = throws)
```

Equivalent to.

```
return wait_until(lock,
                  hpx::chrono::steady_clock::now() + rel_time,
                  std::move(pred));
```

This overload may be used to ignore spurious awakenings by looping until some predicate is satisfied (`bool(pred()) == true`).

Note: The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Template Parameters

- **Lock** – Type of `lock`.
- **Predicate** – Type of `pred`.

Parameters

- **lock** – an object of type `Lock` that meets the [BasicLockable](#)⁷⁷⁵ requirements, which must be locked by the current thread.
- **rel_time** – an object of type `hpx::chrono::duration` representing the maximum time to spend waiting. Note that `rel_time` must be small enough not to overflow when added to `hpx::chrono::steady_clock::now()`.
- **pred** – predicate which returns `false` if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred();`.
- **ec** – Used to hold error code value originated during the operation. Defaults to `throws` — A special ‘throw on error’ `error_code`.

Returns

`bool false` if the predicate `pred` still evaluates to `false` after the `rel_time` timeout expired, otherwise `true`.

```
template<typename Lock, typename Predicate>
inline bool wait(Lock &lock, stop_token token, Predicate pred, error_code &ec = throws)
```

`wait` causes the current thread to block until the condition variable is notified or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred())==true`).

An interruptible wait: registers the `condition_variable_any` for the duration of `wait()`, to be notified if a stop request is made on the given token’s associated stop-state; it is then equivalent to

```

while (!stoken.stop_requested()) {
    if (pred()) return true;
    wait(lock);
}
return pred();

```

Note that the returned value indicates whether *pred* evaluated to *true*, regardless of whether there was a stop requested or not.

Note: The effects of *notify_one()*/*notify_all()* and each of the three atomic parts of *wait()*/*wait_for()*/*wait_until()* (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for *notify_one()* to, for example, be delayed and unblock a thread that started waiting just after the call to *notify_one()* was made.

Template Parameters

- **Lock** – Type of *lock*.
- **Predicate** – Type of *pred*.

Parameters

- **lock** – an object of type *Lock* that meets the [BasicLockable](#)⁷⁷⁶ requirements, which must be locked by the current thread
- **stoken** – a *hpx::stop_token* to register interruption for
- **pred** – predicate which returns *false* if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred()`.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool result of *pred()*.

```

template<typename Lock, typename Predicate>
inline bool wait_until(Lock &lock, stop_token stoken, hpx::chrono::steady_time_point const
    &abs_time, Predicate pred, error_code &ec = throws)

```

wait_until causes the current thread to block until the condition variable is notified, a specific time is reached, or a spurious wakeup occurs, optionally looping until some predicate is satisfied (`bool(pred()) == true`).

An interruptible wait: registers the *condition_variable_any* for the duration of *wait_until()*, to be notified if a stop request is made on the given *stoken*’s associated stop-state; it is then equivalent to

```

while (!stoken.stop_requested()) {
    if (pred())
        return true;
    if (wait_until(lock, timeout_time) == hpx::cv_status::timeout)
        return pred();
}
return pred();

```

Note: The effects of *notify_one()*/*notify_all()* and each of the three atomic parts of *wait()*/*wait_for()*/*wait_until()* (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for *notify_one()* to, for example, be delayed and unblock a

thread that started waiting just after the call to `notify_one()` was made.

Template Parameters

- **Lock** – Type of *lock*.
- **Predicate** – Type of *pred*.

Parameters

- **lock** – an object of type *Lock* that meets the requirements of [BasicLockable⁷⁷⁷](#), which must be locked by the current thread.
- **stoken** – a `hpx::stop_token` to register interruption for.
- **abs_time** – represents the time when waiting should be stopped.
- **pred** – predicate which returns *false* if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred();`.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* `—` A special ‘throw on error’ *error_code*.

Returns

`bool pred()`, regardless of whether the timeout was met or stop was requested.

template<typename **Lock**, typename **Predicate**>

inline bool **wait_for**(*Lock* &lock, *stop_token* stoken, *hpx::chrono::steady_duration* const &rel_time, *Predicate* pred, *error_code* &ec = *throws*)

Equivalent to.

```
return wait_until(lock, std::move(stoken),
    hpx::chrono::steady_clock::now() + rel_time,
    std::move(pred));
```

Note: The effects of `notify_one()/notify_all()` and each of the three atomic parts of `wait()/wait_for()/wait_until()` (unlock+wait, wakeup, and lock) take place in a single total order that can be viewed as modification order of an atomic variable: the order is specific to this individual condition variable. This makes it impossible for `notify_one()` to, for example, be delayed and unblock a thread that started waiting just after the call to `notify_one()` was made.

Template Parameters

- **Lock** – Type of *lock*.
- **Predicate** – Type of *pred*.

Parameters

- **lock** – an object of type *Lock* that meets the [BasicLockable⁷⁷⁸](#) requirements, which must be locked by the current thread.
- **stoken** – a `hpx::stop_token` to register interruption for.
- **rel_time** – an object of type *hpx::chrono::duration* representing the maximum time to spend waiting. Note that *rel_time* must be small enough not to overflow when added to *hpx::chrono::steady_clock::now()*.
- **pred** – predicate which returns *false* if the waiting should be continued (`bool(pred()) == false`). The signature of the predicate function should be equivalent to the following: `bool pred();`.
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* `—` A special ‘throw on error’ *error_code*.

Returns

`bool pred()`, regardless of whether the timeout was met or stop was requested.

Private Types

```
using mutex_type = lcos::local::detail::condition_variable_data::mutex_type
```

```
using data_type = hpx::intrusive_ptr<lcos::local::detail::condition_variable_data>
```

Private Members

```
hpx::util::cache_aligned_data_derived<data_type> data_
```

hpx::barrier

Defined in header [hpx/barrier.hpp](#)⁷⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

```
template<typename OnCompletion = detail::empty_oncompletion>
```

```
class barrier
```

#include <barrier.hpp> A barrier is a thread coordination mechanism whose lifetime consists of a sequence of barrier phases, where each phase allows at most an expected number of threads to block until the expected number of threads arrive at the barrier. [Note: A barrier is useful for managing repeated tasks that are handled by multiple threads. - end note] Each barrier phase consists of the following steps:

- The expected count is decremented by each call to `arrive` or `arrive_and_drop`.
- When the expected count reaches zero, the phase completion step is run. For the specialization with the default value of the `CompletionFunction` template parameter, the completion step is run as part of the call to `arrive` or `arrive_and_drop` that caused the expected count to reach zero. For other specializations, the completion step is run on one of the threads that arrived at the barrier during the phase.

⁷⁵⁹ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁶⁰ https://en.cppreference.com/w/cpp/named_req/StandardLayoutType
⁷⁶¹ https://en.cppreference.com/w/cpp/named_req/CopyConstructible
⁷⁶² https://en.cppreference.com/w/cpp/named_req/MoveConstructible
⁷⁶³ https://en.cppreference.com/w/cpp/named_req/CopyAssignable
⁷⁶⁴ https://en.cppreference.com/w/cpp/named_req/MoveAssignable
⁷⁶⁵ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁶⁶ https://en.cppreference.com/w/cpp/named_req/CopyConstructible
⁷⁶⁷ https://en.cppreference.com/w/cpp/named_req/MoveConstructible
⁷⁶⁸ https://en.cppreference.com/w/cpp/named_req/CopyAssignable
⁷⁶⁹ https://en.cppreference.com/w/cpp/named_req/MoveAssignable
⁷⁷⁰ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷¹ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷² https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷³ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁴ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁵ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁶ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁷ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁸ https://en.cppreference.com/w/cpp/named_req/BasicLockable
⁷⁷⁹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/barrier.hpp>

- When the completion step finishes, the expected count is reset to what was specified by the expected argument to the constructor, possibly adjusted by calls to `arrive_and_drop`, and the next phase starts.

Each phase defines a phase synchronization point. Threads that arrive at the barrier during the phase can block on the phase synchronization point by calling `wait`, and will remain blocked until the phase completion step is run. The phase completion step that is executed at the end of each phase has the following effects:

- Invokes the completion function, equivalent to `completion()`.
- Unblocks all threads that are blocked on the phase synchronization point.

The end of the completion step strongly happens before the returns from all calls that were unblocked by the completion step. For specializations that do not have the default value of the `CompletionFunction` template parameter, the behavior is undefined if any of the barrier object's member functions other than `wait` are called while the completion step is in progress.

Concurrent invocations of the member functions of `barrier`, other than its destructor, do not introduce data races. The member functions `arrive` and `arrive_and_drop` execute atomically.

`CompletionFunction` shall meet the `Cpp17MoveConstructible` (Table 28) and `Cpp17Destructible` (Table 32) requirements. `std::is_nothrow_invocable_v<CompletionFunction&>` shall be true.

The default value of the `CompletionFunction` template parameter is an unspecified type, such that, in addition to satisfying the requirements of `CompletionFunction`, it meets the `Cpp17DefaultConstructible` requirements (Table 27) and `completion()` has no effects.

`barrier::arrival_token` is an unspecified type, such that it meets the `Cpp17MoveConstructible` (Table 28), `Cpp17MoveAssignable` (Table 30), and `Cpp17Destructible` (Table 32) requirements.

Public Types

using **arrival_token** = bool

Public Functions

inline explicit constexpr **barrier**(*std::ptrdiff_t* expected, *OnCompletion* completion = *OnCompletion*())

Preconditions: `expected >= 0` is true and `expected <= max()` is true.

Effects: Sets both the initial expected count for each barrier phase and the current expected count for the first phase to `expected`. Initializes completion with `std::move(f)`. Starts the first phase. [Note: If `expected` is 0 this object can only be destroyed.- end note]

Throws: Any exception thrown by `CompletionFunction`'s move constructor.

~barrier() = default

inline *arrival_token* **arrive**(*std::ptrdiff_t* update = 1)

Preconditions: `update > 0` is true, and `update` is less than or equal to the expected count for the current barrier phase.

Effects: Constructs an object of type `arrival_token` that is associated with the phase synchronization point for the current phase. Then, decrements the expected count by `update`.

Synchronization: The call to `arrive` strongly happens before the start of the phase completion step for the current phase.

Error conditions: Any of the error conditions allowed for mutex types ([thread.mutex.requirements.mutex]). [Note: This call can cause the completion step for the current phase to start.- end note]

Throws

`system_error` – when an exception is required ([thread.req.exception]).

Returns

: The constructed `arrival_token` object.

inline void **wait**(*arrival_token* &&old_phase) const

Preconditions: arrival is associated with the phase synchronization point for the current phase or the immediately preceding phase of the same barrier object.

Effects: Blocks at the synchronization point associated with `HPX_MOVE(arrival)` until the phase completion step of the synchronization point's phase is run. [Note: If arrival is associated with the synchronization point for a previous phase, the call returns immediately. - end note]

Throws

`system_error` – when an exception is required ([thread.req.exception]). Error conditions: Any of the error conditions allowed for mutex types ([thread.mutex.requirements.mutex]).

inline void **arrive_and_wait**()

Effects: Equivalent to: `wait(arrive())`.

inline void **arrive_and_drop**()

Preconditions: The expected count for the current barrier phase is greater than zero.

Effects: Decrements the initial expected count for all subsequent phases by one. Then decrements the expected count for the current phase by one.

Synchronization: The call to `arrive_and_drop` strongly happens before the start of the phase completion step for the current phase.

Throws

`system_error` – when an exception is required ([thread.req.exception]). Error conditions: Any of the error conditions allowed for mutex types ([thread.mutex.requirements.mutex]). [Note: This call can cause the completion step for the current phase to start.- end note]

Public Static Functions

static inline constexpr std::ptrdiff_t() max () noexcept

Private Types

using **mutex_type** = *hpx::spinlock*

Private Members

`hpx::intrusive_ptr<detail::barrier_data> mtx_`

`mutable hpx::local::detail::condition_variable cond_`

`std::ptrdiff_t expected_`

`std::ptrdiff_t arrived_`

`OnCompletion completion_`

`bool phase_`

`hpx::counting_semaphore`

Defined in header `hpx/semaphore.hpp`⁷⁸⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

template<*std::ptrdiff_t* **LeastMaxValue** = PTRDIFF_MAX>

class **counting_semaphore**

#include <counting_semaphore.hpp> A semaphore is a protected variable (an entity storing a value) or abstract data type (an entity grouping several variables that may or may not be numerical) which constitutes the classic method for restricting access to shared resources, such as shared memory, in a multiprogramming environment. Semaphores exist in many variants, though usually the term refers to a counting semaphore, since a binary semaphore is better known as a mutex. A counting semaphore is a counter for a set of available resources, rather than a locked/unlocked flag of a single resource. It was invented by Edsger Dijkstra. Semaphores are the classic solution to preventing race conditions in the dining philosophers problem, although they do not prevent resource deadlocks.

Counting semaphores can be used for synchronizing multiple threads as well: one thread waiting for several other threads to touch (signal) the semaphore, or several threads waiting for one other thread to touch this semaphore. Unlike `hpx::mutex` a `counting_semaphore` is not tied to threads of execution — acquiring a semaphore can occur on a different thread than releasing the semaphore, for example. All operations on `counting_semaphore` can be performed concurrently and without any relation to specific threads of execution, with the exception of the destructor which cannot be performed concurrently but can be performed on a different thread.

Semaphores are lightweight synchronization primitives used to constrain concurrent access to a shared resource. They are widely used to implement other synchronization primitives and, whenever both are applicable, can be more efficient than condition variables.

A counting semaphore is a semaphore object that models a non-negative resource count.

Class template `counting_semaphore` maintains an internal counter that is initialized when the semaphore is created. The counter is decremented when a thread acquires the semaphore, and is incremented when

⁷⁸⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/semaphore.hpp

a thread releases the semaphore. If a thread tries to acquire the semaphore when the counter is zero, the thread will block until another thread increments the counter by releasing the semaphore.

Specializations of `hpx::counting_semaphore` are not [DefaultConstructible](#)⁷⁸¹, [CopyConstructible](#)⁷⁸², [MoveConstructible](#)⁷⁸³, [CopyAssignable](#)⁷⁸⁴, or [MoveAssignable](#)⁷⁸⁵.

Note: `counting_semaphore`'s `try_acquire()` can spuriously fail.

Template Parameters

LeastMaxValue – `counting_semaphore` allows more than one concurrent access to the same resource, for at least *LeastMaxValue* concurrent accessors. As its name indicates, the *LeastMaxValue* is the minimum max value, not the actual max value. Thus `max()` can yield a number larger than *LeastMaxValue*.

Public Functions

`counting_semaphore(counting_semaphore const&) = delete`

`counting_semaphore &operator=(counting_semaphore const&) = delete`

`counting_semaphore(counting_semaphore&&) = delete`

`counting_semaphore &operator=(counting_semaphore&&) = delete`

explicit `counting_semaphore(std::ptrdiff_t value)`

Constructs an object of type `hpx::counting_semaphore` with the internal counter initialized to *value*.

Parameters

value – The initial value of the internal semaphore lock count. Normally this value should be zero (which is the default), values greater than zero are equivalent to the same number of signals pre-set, and negative values are equivalent to the same number of waits pre-set.

`~counting_semaphore()` = default

void `release(std::ptrdiff_t update = 1)`

Atomically increments the internal counter by the value of *update*. Any thread(s) waiting for the counter to be greater than 0, such as due to being blocked in `acquire`, will subsequently be unblocked.

Note: Synchronization: Strongly happens before invocations of `try_acquire` that observe the result of the effects.

Throws

`std::system_error` –

Parameters

update – the amount to increment the internal counter by

Pre

Both `update >= 0` and `update <= max() - counter` are *true*, where *counter* is the value of the internal counter.

bool `try_acquire()` noexcept

Tries to atomically decrement the internal counter by 1 if it is greater than 0; no blocking occurs regardless.

Returns

true if it decremented the internal counter, otherwise *false*

void **acquire**()

Repeatedly performs the following steps, in order:

- Evaluates `try_acquire`. If the result is true, returns.
- Blocks on `*this` until counter is greater than zero.

Throws

`std::system_error` –

Returns

`void`.

bool **try_acquire_until**(`hpx::chrono::steady_time_point` const &`abs_time`)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the `abs_time` time point has been passed.

Parameters

`abs_time` – the earliest time the function must wait until in order to fail

Throws

`std::system_error` –

Returns

`true` if it decremented the internal counter, otherwise `false`.

bool **try_acquire_for**(`hpx::chrono::steady_duration` const &`rel_time`)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the `rel_time` duration has been exceeded.

Throws

`std::system_error` –

Parameters

`rel_time` – the minimum duration the function must wait for to fail

Returns

`true` if it decremented the internal counter, otherwise `false`

Public Static Functions

static constexpr `std::ptrdiff_t` **max**() noexcept

Returns The maximum value of counter. This value is greater than or equal to *LeastMaxValue*.

Returns

The internal counter's maximum possible value, as a `std::ptrdiff_t`.

template<typename **Mutex** = `hpx::spinlock`, int **N** = 0>

class **counting_semaphore_var**

`#include <counting_semaphore.hpp>` A semaphore is a protected variable (an entity storing a value) or abstract data type (an entity grouping several variables that may or may not be numerical) which constitutes the classic method for restricting access to shared resources, such as shared memory, in a multiprogramming environment. Semaphores exist in many variants, though usually the term refers to a counting semaphore, since a binary semaphore is better known as a mutex. A counting semaphore is a counter for a set of available resources, rather than a locked/unlocked flag of a single resource. It was invented by Edsger Dijkstra. Semaphores are the classic solution to preventing race conditions in the dining philosophers problem, although they do not prevent resource deadlocks.

Counting semaphores can be used for synchronizing multiple threads as well: one thread waiting for several other threads to touch (signal) the semaphore, or several threads waiting for one other thread to touch this

semaphore. Unlike `hpx::mutex` a `counting_semaphore_var` is not tied to threads of execution — acquiring a semaphore can occur on a different thread than releasing the semaphore, for example. All operations on `counting_semaphore_var` can be performed concurrently and without any relation to specific threads of execution, with the exception of the destructor which cannot be performed concurrently but can be performed on a different thread.

Semaphores are lightweight synchronization primitives used to constrain concurrent access to a shared resource. They are widely used to implement other synchronization primitives and, whenever both are applicable, can be more efficient than condition variables.

A counting semaphore is a semaphore object that models a non-negative resource count.

Class template `counting_semaphore_var` maintains an internal counter that is initialized when the semaphore is created. The counter is decremented when a thread acquires the semaphore, and is incremented when a thread releases the semaphore. If a thread tries to acquire the semaphore when the counter is zero, the thread will block until another thread increments the counter by releasing the semaphore.

Specializations of `hpx::counting_semaphore_var` are not [DefaultConstructible](#)⁷⁸⁶, [CopyConstructible](#)⁷⁸⁷, [MoveConstructible](#)⁷⁸⁸, [CopyAssignable](#)⁷⁸⁹, or [MoveAssignable](#)⁷⁹⁰.

Note: `counting_semaphore_var`'s `try_acquire()` can spuriously fail.

Template Parameters

- **Mutex** – Type of mutex
- **N** – The initial value of the internal semaphore lock count.

Public Functions

explicit **counting_semaphore_var**(*std::ptrdiff_t* value = *N*)

Constructs an object of type `hpx::counting_semaphore_value` with the internal counter initialized to *N*.

Parameters

value – The initial value of the internal semaphore lock count. Normally this value should be zero, values greater than zero are equivalent to the same number of signals pre-set, and negative values are equivalent to the same number of waits pre-set. Defaults to *N* (which in turn defaults to zero).

counting_semaphore_var(*counting_semaphore_var* const&) = delete

counting_semaphore_var &**operator**=(*counting_semaphore_var* const&) = delete

void **wait**(*std::ptrdiff_t* count = 1)

Wait for the semaphore to be signaled.

Parameters

count – The value by which the internal lock count will be decremented. At the same time this is the minimum value of the lock count at which the thread is not yielded.

bool **try_wait**(*std::ptrdiff_t* count = 1)

Try to wait for the semaphore to be signaled.

Parameters

count – The value by which the internal lock count will be decremented. At the same time this is the minimum value of the lock count at which the thread is not yielded.

Returns

try_wait returns true if the calling thread was able to acquire the requested amount of credits.
try_wait returns false if not sufficient credits are available at this point in time.

void **signal**(*std::ptrdiff_t* count = 1)

Signal the semaphore.

Parameters

count – The value by which the internal lock count will be incremented.

std::ptrdiff_t **signal_all**()

Unblock all acquirers.

Returns

std::ptrdiff_t internal lock count after the operation.

void **release**(*std::ptrdiff_t* update = 1)

Atomically increments the internal counter by the value of *update*. Any thread(s) waiting for the counter to be greater than 0, such as due to being blocked in acquire, will subsequently be unblocked.

Note: Synchronization: Strongly happens before invocations of *try_acquire* that observe the result of the effects.

Throws

std::system_error –

Parameters

update – the amount to increment the internal counter by

Pre

Both *update* ≥ 0 and *update* $\leq \text{max}() - \text{counter}$ are *true*, where *counter* is the value of the internal counter.

bool **try_acquire**() noexcept

Tries to atomically decrement the internal counter by 1 if it is greater than 0; no blocking occurs regardless.

Returns

true if it decremented the internal counter, otherwise *false*

void **acquire**()

Repeatedly performs the following steps, in order:

- Evaluates *try_acquire*. If the result is true, returns.

Blocks on **this* until counter is greater than zero.

Throws

std::system_error –

Returns

void.

bool **try_acquire_until**(*hpx::chrono::steady_time_point* const &*abs_time*)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the *abs_time* time point has been passed.

Parameters

abs_time – the earliest time the function must wait until in order to fail

Throws

std::system_error –

Returns

true if it decremented the internal counter, otherwise *false*.

bool **try_acquire_for**(*hpx::chrono::steady_duration* const &rel_time)

Tries to atomically decrement the internal counter by 1 if it is greater than 0; otherwise blocks until it is greater than 0 and can successfully decrement the internal counter, or the *rel_time* duration has been exceeded.

Throws

std::system_error –

Parameters

rel_time – the minimum duration the function must wait for to fail

Returns

true if it decremented the internal counter, otherwise *false*

Public Static Functions

static constexpr *std::ptrdiff_t* **max**() noexcept

Returns The maximum value of counter. This value is greater than or equal to *LeastMaxValue*.

Returns

The internal counter's maximum possible value, as a *std::ptrdiff_t*.

Private Types

using **mutex_type** = *Mutex*

hpx::spinlock

Defined in header [hpx/mutex.hpp](#)⁷⁹¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁷⁸¹ https://en.cppreference.com/w/cpp/named_req/DefaultConstructible

⁷⁸² https://en.cppreference.com/w/cpp/named_req/CopyConstructible

⁷⁸³ https://en.cppreference.com/w/cpp/named_req/MoveConstructible

⁷⁸⁴ https://en.cppreference.com/w/cpp/named_req/CopyAssignable

⁷⁸⁵ https://en.cppreference.com/w/cpp/named_req/MoveAssignable

⁷⁸⁶ https://en.cppreference.com/w/cpp/named_req/DefaultConstructible

⁷⁸⁷ https://en.cppreference.com/w/cpp/named_req/CopyConstructible

⁷⁸⁸ https://en.cppreference.com/w/cpp/named_req/MoveConstructible

⁷⁸⁹ https://en.cppreference.com/w/cpp/named_req/CopyAssignable

⁷⁹⁰ https://en.cppreference.com/w/cpp/named_req/MoveAssignable

⁷⁹¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

Typedefs

using **spinlock** = detail::spinlock<true>

spinlock is a type of lock that causes a thread attempting to obtain it to check for its availability while waiting in a loop continuously.

using **spinlock_no_backoff** = detail::spinlock<false>

hpx::nostopstate, **hpx::stop_callback**, **hpx::stop_source**, **hpx::stop_token**, **hpx::nostopstate_t**

Defined in header [hpx/stop_token.hpp](#)⁷⁹².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

template<typename **Callback**>

stop_callback(*stop_token*, *Callback*) -> *stop_callback*<*Callback*>

The **stop_callback** class template provides an RAII object type that registers a callback function for an associated **hpx::stop_token** object, such that the callback function will be invoked when the **hpx::stop_token**'s associated **hpx::stop_source** is requested to stop. Callback functions registered via **stop_callback**'s constructor are invoked either in the same thread that successfully invokes *request_stop()* for a **hpx::stop_source** of the **stop_callback**'s associated **hpx::stop_token**; or if stop has already been requested prior to the constructor's registration, then the callback is invoked in the thread constructing the **stop_callback**. More than one **stop_callback** can be created for the same **hpx::stop_token**, from the same or different threads concurrently. No guarantee is provided for the order in which they will be executed, but they will be invoked synchronously; except for *stop_callback(s)* constructed after stop has already been requested for the **hpx::stop_token**, as described previously. If an invocation of a callback exits via an exception then **hpx::terminate** is called. **hpx::stop_callback** is not *CopyConstructible*, *CopyAssignable*, *MoveConstructible*, nor *MoveAssignable*. The template param **Callback** type must be both *invocable* and *destructible*. Any return value is ignored.

inline void **swap**(*stop_token* &lhs, *stop_token* &rhs) noexcept

inline void **swap**(*stop_source* &lhs, *stop_source* &rhs) noexcept

Variables

constexpr *nostopstate_t* **nostopstate** = { }

This is a constant object instance of *hpx::nostopstate_t* for use in constructing an empty *hpx::stop_source*, as a placeholder value in the non-default constructor.

struct **nostopstate_t**

#include <*stop_token.hpp*> Unit type intended for use as a placeholder in *hpx::stop_source* non-default constructor, that makes the constructed *hpx::stop_source* empty with no associated stop-state.

⁷⁹² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/stop_token.hpp

Public Functions

explicit **nostopstate_t**() = default

template<typename **Callback**>

class **stop_callback**

class **stop_source**

#include <stop_token.hpp> The `stop_source` class provides the means to issue a stop request, such as for `hpx::jthread` cancellation. A stop request made for one `stop_source` object is visible to all `stop_sources` and `hpx::stop_tokens` of the same associated stop-state; any `hpx::stop_callback(s)` registered for associated `hpx::stop_token(s)` will be invoked, and any `hpx::condition_variable_any` objects waiting on associated `hpx::stop_token(s)` will be awoken. Once a stop is requested, it cannot be withdrawn. Additional stop requests have no effect.

Note: For the purposes of `hpx::jthread` cancellation the `stop_source` object should be retrieved from the `hpx::jthread` object using `get_stop_source()`; or stop should be requested directly from the `hpx::jthread` object using `request_stop()`. This will then use the same associated stop-state as that passed into the `hpx::jthread`'s invoked function argument (i.e., the function being executed on its thread). For other uses, however, a `stop_source` can be constructed separately using the default constructor, which creates new stop-state.

Public Functions

inline **stop_source**()

inline explicit **stop_source**(*nostopstate_t*) noexcept

inline **stop_source**(*stop_source* const &rhs) noexcept

stop_source(*stop_source*&&) noexcept = default

inline *stop_source* &**operator**=(*stop_source* const &rhs) noexcept

stop_source &**operator**=(*stop_source*&&) noexcept = default

inline ~**stop_source**()

inline void **swap**(*stop_source* &s) noexcept

swaps two *stop_source* objects

inline *stop_token* **get_token**() const noexcept

returns a *stop_token* for the associated stop-state

inline bool **stop_possible**() const noexcept

checks whether associated stop-state can be requested to stop

inline bool **stop_requested**() const noexcept

checks whether the associated stop-state has been requested to stop

inline bool **request_stop**() const noexcept

makes a stop request for the associated stop-state, if any

Private Members

hpx::intrusive_ptr<detail::stop_state> **state_**

Friends

inline friend bool **operator==(***stop_source* const &lhs, *stop_source* const &rhs) noexcept

inline friend bool **operator!=(***stop_source* const &lhs, *stop_source* const &rhs) noexcept

class **stop_token**

#include <stop_token.hpp> The *stop_token* class provides the means to check if a stop request has been made or can be made, for its associated *hpx::stop_source* object. It is essentially a thread-safe “view” of the associated stop-state. The *stop_token* can also be passed to the constructor of *hpx::stop_callback*, such that the callback will be invoked if the *stop_token*’s associated *hpx::stop_source* is requested to stop. And *stop_token* can be passed to the interruptible waiting functions of *hpx::condition_variable_any*, to interrupt the condition variable’s wait if stop is requested.

Note: A *stop_token* object is not generally constructed independently, but rather retrieved from a *hpx::jthread* or *hpx::stop_source*. This makes it share the same associated stop-state as the *hpx::jthread* or *hpx::stop_source*.

Public Types

template<typename **Callback**>

using **callback_type** = *stop_callback<Callback>*

Public Functions

constexpr **stop_token**() noexcept = default

stop_token(*stop_token* const &rhs) = default

stop_token(*stop_token*&&) noexcept = default

stop_token &**operator=(***stop_token* const &rhs) = default

stop_token &**operator=(***stop_token*&&) noexcept = default

~stop_token() = default

inline void **swap**(*stop_token* &s) noexcept

swaps two *stop_token* objects

inline bool **stop_requested**() const noexcept

checks whether the associated stop-state has been requested to stop

inline bool **stop_possible**() const noexcept

checks whether associated stop-state can be requested to stop

Private Functions

```
inline explicit stop_token(hpx::intrusive_ptr<detail::stop_state> state) noexcept
```

Private Members

```
hpx::intrusive_ptr<detail::stop_state> state_
```

Friends

```
friend class stop_callback
```

```
friend class stop_source
```

```
inline friend constexpr friend bool operator== (stop_token const &lhs,  
stop_token const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (stop_token const &lhs,  
stop_token const &rhs) noexcept
```

```
namespace experimental
```

```
namespace p2300_stop_token
```

Functions

```
template<typename Callback>  
in_place_stop_callback(in_place_stop_token, Callback) -> in_place_stop_callback<Callback>
```

```
template<typename Callback>
```

```
class in_place_stop_callback
```

```
class in_place_stop_source
```

Public Functions

```
inline in_place_stop_source() noexcept
```

```
inline ~in_place_stop_source()
```

```
in_place_stop_source(in_place_stop_source const&) = delete
```

```
in_place_stop_source(in_place_stop_source&&) noexcept = delete
```

```
in_place_stop_source &operator=(in_place_stop_source const&) = delete
```

```
in_place_stop_source &operator=(in_place_stop_source&&) noexcept = delete
```

```
inline in_place_stop_token get_token() const noexcept
```

```
inline bool request_stop() noexcept
```

```
inline bool stop_requested() const noexcept
```

```
inline bool stop_possible() const noexcept
```

Private Functions

```
inline bool register_callback(hpx::detail::stop_callback_base *cb) noexcept
```

```
inline void remove_callback(hpx::detail::stop_callback_base *cb) noexcept
```

Private Members

```
hpx::detail::stop_state state_
```

Friends

```
friend class in_place_stop_token
```

```
friend class in_place_stop_callback
```

```
class in_place_stop_token
```

Public Types

```
template<typename Callback>
```

```
using callback_type = in_place_stop_callback<Callback>
```

Public Functions

```
inline constexpr in_place_stop_token() noexcept
```

```
~in_place_stop_token() = default
```

```
in_place_stop_token(in_place_stop_token const &rhs) noexcept = default
```

```
inline in_place_stop_token(in_place_stop_token &&rhs) noexcept
```

```
in_place_stop_token &operator=(in_place_stop_token const &rhs) noexcept = default
```

```
inline in_place_stop_token &operator=(in_place_stop_token &&rhs) noexcept
```

```
inline bool stop_requested() const noexcept
```

```
inline bool stop_possible() const noexcept
```

```
inline void swap(in_place_stop_token &rhs) noexcept
```

Private Functions

```
inline explicit in_place_stop_token(in_place_stop_source const *source) noexcept
```

Private Members

```
in_place_stop_source const *source_
```

Friends

```
friend class in_place_stop_source
```

```
friend class in_place_stop_callback
```

```
inline friend constexpr friend bool operator== (in_place_stop_token const &lhs,  
in_place_stop_token const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!  
= (in_place_stop_token const &lhs, in_place_stop_token const &rhs) noexcept
```

```
inline friend void swap(in_place_stop_token &x, in_place_stop_token &y) noexcept
```

```
struct never_stop_token
```

Public Types

```
template<typename>
```

```
using callback_type = callback_impl
```

Public Static Functions

```
static inline constexpr bool stop_requested() noexcept
```

```
static inline constexpr bool stop_possible() noexcept
```

Friends

```
inline friend constexpr friend bool operator== (never_stop_token,  
never_stop_token) noexcept
```

```
inline friend constexpr friend bool operator!= (never_stop_token,  
never_stop_token) noexcept
```

```
struct callback_impl
```

Public Functions

```
template<typename Callback>
inline explicit constexpr callback_impl(never_stop_token, Callback&&) noexcept
```

hpx::latch

Defined in header [hpx/latch.hpp](#)⁷⁹³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

class **latch**

#include <latch.hpp> Latches are a thread coordination mechanism that allow one or more threads to block until an operation is completed. An individual latch is a single-use object; once the operation has been completed, the latch cannot be reused.

Subclassed by *hpx::lcos::local::latch*

Public Functions

latch(*latch* const&) = delete

latch(*latch*&&) = delete

latch &**operator**=(*latch* const&) = delete

latch &**operator**=(*latch*&&) = delete

inline explicit **latch**(*std::ptrdiff_t* count)

Initialize the latch

Requires: count >= 0. Synchronization: None Postconditions: counter_ == count.

~latch() = default

Requires: No threads are blocked at the synchronization point.

Note: May be called even if some threads have not yet returned from *wait()* or *count_down_and_wait()*, provided that counter_ is 0.

Note: The destructor might not return until all threads have exited *wait()* or *count_down_and_wait()*.

Note: It is the caller's responsibility to ensure that no other thread enters *wait()* after one thread has called the destructor. This may require additional coordination.

⁷⁹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/latch.hpp>

```
inline void count_down(std::ptrdiff_t update)
```

Decrements counter_ by n. Does not block.

Requires: counter_ >= n and n >= 0.

Synchronization: Synchronizes with all calls that block on this latch and with all try_wait calls on this latch that return true .

Throws

Nothing. –

```
inline bool try_wait() const noexcept
```

Returns: With very low probability false. Otherwise, counter == 0.

```
inline void wait() const
```

If counter_ is 0, returns immediately. Otherwise, blocks the calling thread at the synchronization point until counter_ reaches 0.

Throws

Nothing. –

```
inline void arrive_and_wait(std::ptrdiff_t update = 1)
```

Effects: Equivalent to: count_down(update); wait();

Public Static Functions

```
static inline constexpr std::ptrdiff_t() max() noexcept
```

Returns: The maximum value of counter that the implementation supports.

Protected Types

```
using mutex_type = hpx::spinlock
```

Protected Attributes

```
mutable util::cache_line_data<mutex_type> mtx_
```

```
mutable util::cache_line_data<hpx::lcos::local::detail::condition_variable> cond_
```

```
std::atomic<std::ptrdiff_t> counter_
```

```
bool notified_
```

```
namespace lcos
```

```
namespace local
```

class **latch** : public *hpx::latch*

#include <latch.hpp> A latch maintains an internal counter_ that is initialized when the latch is created. Threads may block at a synchronization point waiting for counter_ to be decremented to 0. When counter_ reaches 0, all such blocked threads are released.

Calls to *countdown_and_wait()*, *count_down()*, *wait()*, *is_ready()*, *count_up()*, and *reset()* behave as atomic operations.

Note: A *hpx::latch* is not an LCO in the sense that it has no global id, and it can't be triggered using the action (parcel) mechanism. Use *hpx::distributed::latch* instead if this is required. It is just a low level synchronization primitive allowing to synchronize a given number of *threads*.

Public Functions

latch(*latch* const&) = delete

latch(*latch*&&) = delete

latch &**operator**=(*latch* const&) = delete

latch &**operator**=(*latch*&&) = delete

inline explicit **latch**(*std::ptrdiff_t* count)

Initialize the latch

Requires: count >= 0. Synchronization: None Postconditions: counter_ == count.

~latch() = default

Requires: No threads are blocked at the synchronization point.

Note: May be called even if some threads have not yet returned from *wait()* or *count_down_and_wait()*, provided that counter_ is 0.

Note: The destructor might not return until all threads have exited *wait()* or *count_down_and_wait()*.

Note: It is the caller's responsibility to ensure that no other thread enters *wait()* after one thread has called the destructor. This may require additional coordination.

inline void **count_down_and_wait**()

Decrements counter_ by 1 . Blocks at the synchronization point until counter_ reaches 0.

Requires: counter_ > 0.

Synchronization: Synchronizes with all calls that block on this latch and with all *is_ready* calls on this latch that return true.

Throws

Nothing. –


```

inline bool is_ready() const noexcept
    Returns: counter_ == 0. Does not block.
Throws
    Nothing. –

inline void abort_all() const

inline void count_up(std::ptrdiff_t n)
    Increments counter_ by n. Does not block.
    Requires: n >= 0.
Throws
    Nothing. –

inline void reset(std::ptrdiff_t n)
    Reset counter_ to n. Does not block.
    Requires: n >= 0.
Throws
    Nothing. –

inline bool reset_if_needed_and_count_up(std::ptrdiff_t n, std::ptrdiff_t count)
    Effects: Equivalent to: if (is_ready()) reset(count); count_up(n); Returns: true if the latch was reset

```

hpx::once_flag, hpx::call_once

Defined in header [hpx/mutex.hpp](#)⁷⁹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```

template<typename F, typename ...Args>
void call_once(once_flag &flag, F &&f, Args&&... args)

```

Executes the Callable object *f* exactly once, even if called concurrently, from several threads.

In detail:

- If, by the time *call_once* is called, flag indicates that *f* was already called, *call_once* returns right away (such a call to *call_once* is known as passive).
- Otherwise, *call_once* invokes `std::forward<Callable>(f)` with the arguments `std::forward<Args>(args)...` (as if by `hpx::invoke`). Unlike the `hpx::thread` constructor or `hpx::async`, the arguments are not moved or copied because they don't need to be transferred to another thread of execution. (such a call to *call_once* is known as active).
 - If that invocation throws an exception, it is propagated to the caller of *call_once*, and the flag is not flipped so that another call will be attempted (such a call to *call_once* is known as exceptional).
 - If that invocation returns normally (such a call to *call_once* is known as returning), the flag is flipped, and all other calls to *call_once* with the same flag are guaranteed to be passive. All active calls on the same flag form a single total order consisting of zero or more exceptional calls,

⁷⁹⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

followed by one returning call. The end of each active call synchronizes-with the next active call in that order. The return from the returning call synchronizes-with the returns from all passive calls on the same flag: this means that all concurrent calls to *call_once* are guaranteed to observe any side-effects made by the active call, with no additional synchronization.

Note: If concurrent calls to *call_once* pass different functions *f*, it is unspecified which *f* will be called. The selected function runs in the same thread as the *call_once* invocation it was passed to. Initialization of function-local statics is guaranteed to occur only once even when called from multiple threads, and may be more efficient than the equivalent code using `hpx::call_once`. The POSIX equivalent of this function is *pthread_once*.

Parameters

- **flag** – an object, for which exactly one function gets executed
- **f** – Callable object to invoke
- **args** – arguments to pass to the function

Throws

`std::system_error` – if any condition prevents calls to *call_once* from executing as specified or any exception thrown by *f*

struct **once_flag**

#include <once.hpp> The class `hpx::once_flag` is a helper structure for `hpx::call_once`. An object of type `hpx::once_flag` that is passed to multiple calls to `hpx::call_once` allows those calls to coordinate with each other such that only one of the calls will actually run to completion. `hpx::once_flag` is neither copyable nor movable.

Public Functions

`once_flag(once_flag const&) = delete`

`once_flag(once_flag&&) = delete`

`once_flag &operator=(once_flag const&) = delete`

`once_flag &operator=(once_flag&&) = delete`

inline `once_flag()` noexcept

Constructs an `once_flag` object. The internal state is set to indicate that no function has been called yet.

Private Members

`std::atomic<long> status_`

`lcos::local::event event_`

Friends

```
template<typename F, typename ...Args>
friend void call_once(once_flag &flag, F &&f, Args&&... args)
```

Executes the Callable object *f* exactly once, even if called concurrently, from several threads.

In detail:

- If, by the time *call_once* is called, *flag* indicates that *f* was already called, *call_once* returns right away (such a call to *call_once* is known as passive).
- Otherwise, *call_once* invokes `std::forward<Callable>(f)` with the arguments `std::forward<Args>(args)...` (as if by `hpx::invoke`). Unlike the `hpx::thread` constructor or `hpx::async`, the arguments are not moved or copied because they don't need to be transferred to another thread of execution. (such a call to *call_once* is known as active).
 - If that invocation throws an exception, it is propagated to the caller of *call_once*, and the flag is not flipped so that another call will be attempted (such a call to *call_once* is known as exceptional).
 - If that invocation returns normally (such a call to *call_once* is known as returning), the flag is flipped, and all other calls to *call_once* with the same flag are guaranteed to be passive. All active calls on the same flag form a single total order consisting of zero or more exceptional calls, followed by one returning call. The end of each active call synchronizes-with the next active call in that order. The return from the returning call synchronizes-with the returns from all passive calls on the same flag: this means that all concurrent calls to *call_once* are guaranteed to observe any side-effects made by the active call, with no additional synchronization.

Note: If concurrent calls to *call_once* pass different functions *f*, it is unspecified which *f* will be called. The selected function runs in the same thread as the *call_once* invocation it was passed to. Initialization of function-local statics is guaranteed to occur only once even when called from multiple threads, and may be more efficient than the equivalent code using `hpx::call_once`. The POSIX equivalent of this function is *pthread_once*.

Parameters

- **flag** – an object, for which exactly one function gets executed
- **f** – Callable object to invoke
- **args** – arguments to pass to the function

Throws

`std::system_error` – if any condition prevents calls to *call_once* from executing as specified or any exception thrown by *f*

hpx::shared_mutex

Defined in header `hpx/shared_mutex.hpp`⁷⁹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

⁷⁹⁵ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/shared_mutex.hpp

Typedefs

using **shared_mutex** = detail::shared_mutex<>

The *shared_mutex* class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In contrast to other mutex types which facilitate exclusive access, a *shared_mutex* has two levels of access:

- *shared* - several threads can share ownership of the same mutex.
- *exclusive* - only one thread can own the mutex.

If one thread has acquired the exclusive lock (through *lock*, *try_lock*), no other threads can acquire the lock (including the shared). If one thread has acquired the shared lock (through *lock_shared*, *try_lock_shared*), no other thread can acquire the exclusive lock, but can acquire the shared lock. Only when the exclusive lock has not been acquired by any thread, the shared lock can be acquired by multiple threads. Within one thread, only one lock (shared or exclusive) can be acquired at the same time. Shared mutexes are especially useful when shared data can be safely read by any number of threads simultaneously, but a thread may only write the same data when no other thread is reading or writing at the same time. The *shared_mutex* class satisfies all requirements of *SharedMutex* and *StandardLayoutType*.

hpx::mutex, hpx::timed_mutex

Defined in header [hpx/mutex.hpp](#)⁷⁹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

class **mutex**

#include <mutex.hpp> *mutex* class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. *mutex* offers exclusive, non-recursive ownership semantics:

- A calling thread owns a mutex from the time that it successfully calls either *lock* or *try_lock* until it calls *unlock*.
- When a thread owns a *mutex*, all other threads will block (for calls to *lock*) or receive a *false* return value (for *try_lock*) if they attempt to claim ownership of the *mutex*.
- A calling thread must not own the *mutex* prior to calling *lock* or *try_lock*.

The behavior of a program is undefined if a *mutex* is destroyed while still owned by any threads, or a thread terminates while owning a *mutex*. The mutex class satisfies all requirements of *Mutex*⁷⁹⁷ and *StandardLayoutType*⁷⁹⁸.

hpx::mutex is neither copyable nor movable.

Subclassed by *hpx::timed_mutex*

⁷⁹⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

Public Functions

mutex(*mutex* const&) = delete

hpx::mutex is neither copyable nor movable

mutex(*mutex*&&) = delete

mutex &**operator**=(*mutex* const&) = delete

mutex &**operator**=(*mutex*&&) = delete

inline HPX_HOST_DEVICE_CONSTEXPR **mutex**(char const*const = "") noexcept

Constructs the *mutex*. The *mutex* is in unlocked state after the constructor completes.

Note: Because the default constructor is *constexpr*, static mutexes are initialized as part of static non-local initialization, before any dynamic non-local initialization begins. This makes it safe to lock a *mutex* in a constructor of any static object.

Parameters

description – description of the *mutex*.

~mutex()

Destroys the *mutex*. The behavior is undefined if the *mutex* is owned by any thread or if any thread terminates while holding any ownership of the *mutex*.

void **lock**(char const *description, *error_code* &ec = *throws*)

Locks the mutex. If another thread has already locked the mutex, a call to lock will block execution until the lock is acquired. If lock is called by a thread that already owns the mutex, the behavior is undefined: for example, the program may deadlock. hpx::mutex can detect the invalid usage and throws a *std::system_error* with error condition *resource_deadlock_would_occur* instead of deadlocking. Prior unlock() operations on the same mutex synchronize- with (as defined in *std::memory_order*) this operation.

Note: lock() is usually not called directly: *std::unique_lock*, *std::scoped_lock*, and *std::lock_guard* are used to manage exclusive locking.

Parameters

- **description** – Description of the *mutex*
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

void *lock* returns *void*.

inline void **lock**(*error_code* &ec = *throws*)

Locks the mutex. If another thread has already locked the mutex, a call to lock will block execution until the lock is acquired. If lock is called by a thread that already owns the mutex, the behavior is undefined: for example, the program may deadlock. hpx::mutex can detect the invalid usage and throws a *std::system_error* with error condition *resource_deadlock_would_occur* instead of deadlocking. Prior unlock() operations on the same mutex synchronize - with(as defined in *std::memory_order*) this operation.

Note: lock() is usually not called directly: *std::unique_lock*, *std::scoped_lock*, and *std::lock_guard* are used to manage exclusive locking. This overload essentially calls void lock(char const*

`description, error_code& ec =throws);` with *description* as `mutex::lock`.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`void lock` returns *void*.

`bool try_lock(char const *description, error_code &ec = throws)`

Tries to lock the *mutex*. Returns immediately. On successful lock acquisition returns *true*, otherwise returns *false*. This function is allowed to fail spuriously and return *false* even if the *mutex* is not currently locked by any other thread. If *try_lock* is called by a thread that already owns the *mutex*, the behavior is undefined. Prior `unlock()` operation on the same mutex synchronizes-with (as defined in *std::memory_order*) this operation if it returns *true*. Note that prior `lock()` does not synchronize with this operation if it returns *false*.

Parameters

- **description** – Description of the *mutex*
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`bool try_lock` returns *true* on successful lock acquisition, otherwise returns *false*.

`inline bool try_lock(error_code &ec = throws)`

Tries to lock the *mutex*. Returns immediately. On successful lock acquisition returns *true*, otherwise returns *false*. This function is allowed to fail spuriously and return *false* even if the *mutex* is not currently locked by any other thread. If *try_lock* is called by a thread that already owns the *mutex*, the behavior is undefined. Prior `unlock()` operation on the same mutex synchronizes-with (as defined in *std::memory_order*) this operation if it returns *true*. Note that prior `lock()` does not synchronize with this operation if it returns *false*.

Note: This overload essentially calls

```
void try_lock(char const* description,
              error_code& ec = throws);
```

with *description* as `mutex::try_lock`.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`bool try_lock` returns *true* on successful lock acquisition, otherwise returns *false*.

`void unlock(error_code &ec = throws)`

Unlocks the *mutex*. The *mutex* must be locked by the current thread of execution, otherwise, the behavior is undefined. This operation *synchronizes-with* (as defined in *std::memory_order*) any subsequent *lock* operation that obtains ownership of the same *mutex*.

Parameters

ec – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`unlock` returns *void*.

class **timed_mutex** : private *hpx::mutex*

#include <mutex.hpp> The `timed_mutex` class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In a manner similar to *mutex*, `timed_mutex` offers exclusive, non-recursive ownership semantics. In addition, `timed_mutex` provides the ability to attempt to claim ownership of a `timed_mutex` with a timeout via the member functions `try_lock_for()` and `try_lock_until()`. The `timed_mutex` class satisfies all requirements of [TimedMutex](#)⁷⁹⁹ and [StandardLayoutType](#)⁸⁰⁰.

`hpx::timed_mutex` is neither copyable nor movable.

Public Functions

timed_mutex(*timed_mutex* const&) = delete

`hpx::timed_mutex` is neither copyable nor movable

timed_mutex(*timed_mutex*&&) = delete

timed_mutex &**operator**=(*timed_mutex* const&) = delete

timed_mutex &**operator**=(*timed_mutex*&&) = delete

timed_mutex(char const *const description = "")

Constructs a `timed_mutex`. The mutex is in unlocked state after the call.

Parameters

description – Description of the `timed_mutex`.

~timed_mutex()

Destroys the `timed_mutex`. The behavior is undefined if the mutex is owned by any thread or if any thread terminates while holding any ownership of the mutex.

bool **try_lock_until**(*hpx::chrono::steady_time_point* const &*abs_time*, char const **description*, *error_code* &*ec* = *throws*)

Tries to lock the mutex. Blocks until specified *abs_time* has been reached or the lock is acquired, whichever comes first. On successful lock acquisition returns *true*, otherwise returns *false*. If *abs_time* has already passed, this function behaves like `try_lock()`. As with `try_lock()`, this function is allowed to fail spuriously and return *false* even if the mutex was not locked by any other thread at some point before *abs_time*. Prior `unlock()` operation on the same mutex *synchronizes-with* (as defined in *std::memory_order*) this operation if it returns *true*. If `try_lock_until` is called by a thread that already owns the mutex, the behavior is undefined.

Parameters

- **abs_time** – time point to block until
- **description** – Description of the `timed_mutex`
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool `try_lock_until` returns *true* if the lock was acquired successfully, otherwise *false*.

inline bool **try_lock_until**(*hpx::chrono::steady_time_point* const &*abs_time*, *error_code* &*ec* = *throws*)

Tries to lock the mutex. Blocks until specified *abs_time* has been reached or the lock is acquired, whichever comes first. On successful lock acquisition returns *true*, otherwise returns *false*. If *abs_time* has already passed, this function behaves like `try_lock()`. As with `try_lock()`, this function is allowed to fail spuriously and return *false* even if the mutex was not locked by any other thread at some point before *abs_time*. Prior `unlock()` operation on the same mutex *synchronizes-with* (as defined in

std::memory_order) this operation if it returns *true*. If *try_lock_until* is called by a thread that already owns the mutex, the behavior is undefined.

Note: This overload essentially calls

```
bool try_lock_until(  
    hpx::chrono::steady_time_point const& abs_time,  
    char const* description, error_code& ec = throws);
```

with *description* as `mutex::try_lock_until`.

Parameters

- **abs_time** – time point to block until
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`bool try_lock_until` returns *true* if the lock was acquired successfully, otherwise *false*.

```
inline bool try_lock_for(hpx::chrono::steady_duration const &rel_time, char const *description,  
    error_code &ec = throws)
```

Tries to lock the mutex. Blocks until specified *rel_time* has elapsed or the lock is acquired, whichever comes first. On successful lock acquisition returns *true*, otherwise returns *false*. If *rel_time* is less or equal *rel_time.zero()*, the function behaves like `try_lock()`. This function may block for longer than *rel_time* due to scheduling or resource contention delays. As with `try_lock()`, this function is allowed to fail spuriously and return *false* even if the mutex was not locked by any other thread at some point during *rel_time*. Prior `unlock()` operation on the same mutex *synchronizes-with* (as defined in *std::memory_order*) this operation if it returns *true*. If *try_lock_for* is called by a thread that already owns the mutex, the behavior is undefined.

Parameters

- **rel_time** – minimum duration to block for
- **description** – Description of the timed_mutex
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

`bool try_lock_for` returns *true* if the lock was acquired successfully, otherwise *false*.

```
inline bool try_lock_for(hpx::chrono::steady_duration const &rel_time, error_code &ec = throws)
```

Tries to lock the mutex. Blocks until specified *rel_time* has elapsed or the lock is acquired, whichever comes first. On successful lock acquisition returns *true*, otherwise returns *false*. If *rel_time* is less or equal *rel_time.zero()*, the function behaves like `try_lock()`. This function may block for longer than *rel_time* due to scheduling or resource contention delays. As with `try_lock()`, this function is allowed to fail spuriously and return *false* even if the mutex was not locked by any other thread at some point during *rel_time*. Prior `unlock()` operation on the same mutex *synchronizes-with* (as defined in *std::memory_order*) this operation if it returns *true*. If *try_lock_for* is called by a thread that already owns the mutex, the behavior is undefined.

Note: This overload essentially calls

```
bool try_lock_for(  
    hpx::chrono::steady_duration const& rel_time,  
    char const* description, error_code& ec = throws)
```


with *description* as `mutex::try_lock_for`.

Parameters

- **rel_time** – minimum duration to block for
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* `—` A special ‘throw on error’ *error_code*.

Returns

`bool try_lock_for` returns *true* if the lock was acquired successfully, otherwise *false*.

`void lock(char const *description, error_code &ec = throws)`

Locks the mutex. If another thread has already locked the mutex, a call to lock will block execution until the lock is acquired. If lock is called by a thread that already owns the mutex, the behavior is undefined: for example, the program may deadlock. `hpx::mutex` can detect the invalid usage and throws a `std::system_error` with error condition *resource_deadlock_would_occur* instead of deadlocking. Prior `unlock()` operations on the same mutex synchronize- with (as defined in *std::memory_order*) this operation.

Note: `lock()` is usually not called directly: *std::unique_lock*, *std::scoped_lock*, and *std::lock_guard* are used to manage exclusive locking.

Parameters

- **description** – Description of the *mutex*
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* `—` A special ‘throw on error’ *error_code*.

Returns

`void lock` returns *void*.

`inline void lock(error_code &ec = throws)`

Locks the mutex. If another thread has already locked the mutex, a call to lock will block execution until the lock is acquired. If lock is called by a thread that already owns the mutex, the behavior is undefined: for example, the program may deadlock. `hpx::mutex` can detect the invalid usage and throws a `std::system_error` with error condition *resource_deadlock_would_occur* instead of deadlocking. Prior `unlock()` operations on the same mutex synchronize - with(as defined in *std::memory_order*) this operation.

Note: `lock()` is usually not called directly: *std::unique_lock*, *std::scoped_lock*, and *std::lock_guard* are used to manage exclusive locking. This overload essentially calls `void lock(char const* description, error_code& ec =throws);` with *description* as *mutex::lock*.

Parameters

- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* `—` A special ‘throw on error’ *error_code*.

Returns

`void lock` returns *void*.

`bool try_lock(char const *description, error_code &ec = throws)`

Tries to lock the *mutex*. Returns immediately. On successful lock acquisition returns *true*, otherwise returns *false*. This function is allowed to fail spuriously and return *false* even if the *mutex* is not currently locked by any other thread. If *try_lock* is called by a thread that already owns the *mutex*, the behavior is undefined. Prior `unlock()` operation on the same mutex synchronizes-with (as defined in *std::memory_order*) this operation if it returns *true*. Note that prior `lock()` does not synchronize with this operation if it returns *false*.

Parameters

- **description** – Description of the *mutex*
- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool try_lock returns *true* on successful lock acquisition, otherwise returns *false*.

inline **bool try_lock**(*error_code* &ec = *throws*)

Tries to lock the *mutex*. Returns immediately. On successful lock acquisition returns *true*, otherwise returns *false*. This function is allowed to fail spuriously and return *false* even if the *mutex* is not currently locked by any other thread. If *try_lock* is called by a thread that already owns the *mutex*, the behavior is undefined. Prior *unlock()* operation on the same *mutex* synchronizes-with (as defined in *std::memory_order*) this operation if it returns *true*. Note that prior *lock()* does not synchronize with this operation if it returns *false*.

Note: This overload essentially calls

```
void try_lock(char const* description,
              error_code& ec = throws);
```

with *description* as *mutex::try_lock*.

Parameters

- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

bool try_lock returns *true* on successful lock acquisition, otherwise returns *false*.

void **unlock**(*error_code* &ec = *throws*)

Unlocks the *mutex*. The *mutex* must be locked by the current thread of execution, otherwise, the behavior is undefined. This operation *synchronizes-with* (as defined in *std::memory_order*) any subsequent *lock* operation that obtains ownership of the same *mutex*.

Parameters

- **ec** – Used to hold error code value originated during the operation. Defaults to *throws* — A special ‘throw on error’ *error_code*.

Returns

unlock returns *void*.

namespace **threads**

Typedefs

using **thread_id_ref_type** = *thread_id_ref*

using **thread_self** = *coroutines::detail::coroutine_self*

Functions

thread_id **get_self_id**() noexcept

The function *get_self_id* returns the HPX thread id of the current thread (or zero if the current thread is not a HPX thread).

thread_self ***get_self_ptr**() noexcept

The function *get_self_ptr* returns a pointer to the (OS thread specific) self reference to the current HPX thread.

hpx/synchronization/sliding_semaphore.hpp

Defined in header `hpx/synchronization/sliding_semaphore.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Typedefs

using **sliding_semaphore** = *sliding_semaphore_var*<>

template<typename **Mutex** = *hpx::spinlock*>

class **sliding_semaphore_var**

#include <sliding_semaphore.hpp> A semaphore is a protected variable (an entity storing a value) or abstract data type (an entity grouping several variables that may or may not be numerical) which constitutes the classic method for restricting access to shared resources, such as shared memory, in a multiprogramming environment. Semaphores exist in many variants, though usually the term refers to a counting semaphore, since a binary semaphore is better known as a mutex. A counting semaphore is a counter for a set of available resources, rather than a locked/unlocked flag of a single resource. It was invented by Edsger Dijkstra. Semaphores are the classic solution to preventing race conditions in the dining philosophers problem, although they do not prevent resource deadlocks.

Sliding semaphores can be used for synchronizing multiple threads as well: one thread waiting for several other threads to touch (signal) the semaphore, or several threads waiting for one other thread to touch this semaphore. The difference to a counting semaphore is that a sliding semaphore will not limit the number of threads which are allowed to proceed, but will make sure that the difference between the (arbitrary) number passed to set and wait does not exceed a given threshold.

⁷⁹⁷ https://en.cppreference.com/w/cpp/named_req/Mutex

⁷⁹⁸ https://en.cppreference.com/w/cpp/named_req/StandardLayoutType

⁷⁹⁹ https://en.cppreference.com/w/cpp/named_req/TimedMutex

⁸⁰⁰ https://en.cppreference.com/w/cpp/named_req/StandardLayoutType

Public Functions

sliding_semaphore_var(*sliding_semaphore_var* const&) = delete

sliding_semaphore_var &**operator**=(*sliding_semaphore_var* const&) = delete

sliding_semaphore_var(*sliding_semaphore_var*&&) = delete

sliding_semaphore_var &**operator**=(*sliding_semaphore_var*&&) = delete

inline explicit **sliding_semaphore_var**(*std::int64_t* max_difference, *std::int64_t* lower_limit = 0)
noexcept

Construct a new sliding semaphore.

Parameters

- **max_difference** – [in] The max difference between the upper limit (as set by *wait()*) and the lower limit (as set by *signal()*) which is allowed without suspending any thread calling *wait()*.
- **lower_limit** – [in] The initial lower limit.

inline void **set_max_difference**(*std::int64_t* max_difference, *std::int64_t* lower_limit = 0) noexcept

Set/Change the difference that will cause the semaphore to trigger

Parameters

- **max_difference** – [in] The max difference between the upper limit (as set by *wait()*) and the lower limit (as set by *signal()*) which is allowed without suspending any thread calling *wait()*.
- **lower_limit** – [in] The initial lower limit.

inline void **wait**(*std::int64_t* upper_limit)

Wait for the semaphore to be signaled.

Parameters

upper_limit – [in] The new upper limit. The calling thread will be suspended if the difference between this value and the largest *lower_limit* which was set by *signal()* is larger than the *max_difference*.

inline bool **try_wait**(*std::int64_t* upper_limit = 1)

Try to wait for the semaphore to be signaled.

Parameters

upper_limit – [in] The new upper limit. The calling thread will be suspended if the difference between this value and the largest *lower_limit* which was set by *signal()* is larger than the *max_difference*.

Returns

The function returns true if the calling thread would not block if it was calling *wait()*.

inline void **signal**(*std::int64_t* lower_limit)

Signal the semaphore.

Parameters

lower_limit – [in] The new lower limit. This will update the current lower limit of this semaphore. It will also re-schedule all suspended threads for which their associated upper limit is not larger than the lower limit plus the *max_difference*.

inline *std::int64_t* **signal_all**()

Private Types

```
using mutex_type = Mutex
```

```
using data_type = lcos::local::detail::sliding_semaphore_data<mutex_type>
```

Private Members

```
hpx::intrusive_ptr<data_type> data_
```

hpx::recursive_mutex

Defined in header [hpx/mutex.hpp](#)⁸⁰¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Typedefs

```
using recursive_mutex = detail::recursive_mutex_impl<>
```

tag_invoke

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::invoke

Defined in header [hpx/functional.hpp](#)⁸⁰².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

⁸⁰¹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

⁸⁰² http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

Functions

```
template<typename F, typename ...Ts>
constexpr util::invoke_result_t<F, Ts&&...> invoke(F &&f, Ts&&... vs)
    noexcept(noexcept(HPX_INVOKE(HPX_FORWARD(F,
    f), HPX_FORWARD(Ts, vs)...)))
```

Invokes the given callable object `f` with the content of the argument pack `vs`

Note: This function is similar to `std::invoke` (C++17)

Parameters

- **f** – Requires to be a callable object. If `f` is a member function pointer, the first argument in the pack will be treated as the callee (this object).
- **vs** – An arbitrary pack of arguments

Throws

`std::exception` – like objects thrown by call to object `f` with the argument types `vs`.

Returns

The result of the callable object when it's called with the given argument types.

```
template<typename R, typename F, typename ...Ts>
constexpr R invoke_r(F &&f, Ts&&... vs) noexcept(noexcept(HPX_INVOKE(HPX_FORWARD(F, f),
    HPX_FORWARD(Ts, vs)...)))
```

Template Parameters

R – The result type of the function when it's called with the content of the given argument types `vs`.

namespace **functional**

struct **invoke**

Public Functions

```
template<typename F, typename ...Ts>
inline constexpr util::invoke_result_t<F, Ts&&...> operator()(F &&f, Ts&&... vs) const noexcept(
    noexcept(HPX_INVOKE(HPX_FORWARD(F, f), HPX_FORWARD(Ts, vs)...)))
```

```
template<typename R>
```

```
struct invoke_r
```

Public Functions

```
template<typename F, typename ...Ts>
inline constexpr R operator() (F &&f, Ts&&... vs) const
    noexcept(noexcept(HPX_INVOKE(HPX_FORWARD(F, f),
    HPX_FORWARD(Ts, vs)...)))
```

hpx::is_invocable, hpx::is_invocable_r

Defined in header `hpx/type_traits.hpp`⁸⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Variables

```
template<typename F, typename ...Ts>
constexpr bool is_invocable_v = is_invocable<F, Ts...>::value

template<typename R, typename F, typename ...Ts>
constexpr bool is_invocable_r_v = is_invocable_r<R, F, Ts...>::value

template<typename F, typename ...Ts>
constexpr bool is_nothrow_invocable_v = is_nothrow_invocable<F, Ts...>::value

template<typename F, typename ...Ts>
```

```
struct is_invocable : public hpx::detail::is_invocable_impl<F&&(Ts&&...)>
```

#include <is_invocable.hpp> Determines whether *F* can be invoked with the arguments *Ts...*. Formally, determines whether

```
INVOKE(std::declval<F>(), std::declval<Ts>()...)
```

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*.

F, *R* and all types in the parameter pack *Ts* shall each be a complete type, (possibly cv-qualified) void, or an array of unknown bound. Otherwise, the behavior is undefined. If an instantiation of a template above depends, directly or indirectly, on an incomplete type, and that instantiation could yield a different result if that type were hypothetically completed, the behavior is undefined.

```
template<typename R, typename F, typename ...Ts>
```

```
struct is_invocable_r : public hpx::detail::is_invocable_r_impl<F&&(Ts&&...), R>
```

#include <is_invocable.hpp> Determines whether *F* can be invoked with the arguments *Ts...* to yield a result that is convertible to *R* and the implicit conversion does not bind a reference to a temporary object (since C++23). If *R* is cv void, the result can be any type. Formally, determines whether

```
INVOKE<R>(std::declval<F>(), std::declval<Ts>()...)
```

⁸⁰³ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/type_traits.hpp

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*. Determines whether *F* can be invoked with the arguments *Ts...*. Formally, determines whether

`INVOKE(std::declval<F>(), std::declval<Ts>()...)`

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*.

F, *R* and all types in the parameter pack *Ts* shall each be a complete type, (possibly cv-qualified) void, or an array of unknown bound. Otherwise, the behavior is undefined. If an instantiation of a template above depends, directly or indirectly, on an incomplete type, and that instantiation could yield a different result if that type were hypothetically completed, the behavior is undefined.

```
template<typename F, typename ...Ts>
```

```
struct is_nothrow_invocable : public hpx::detail::is_nothrow_invocable_impl<F(Ts...), is_invocable_v<F,  
Ts...>>
```

thread_pool_util

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/thread_pool_util/thread_pool_suspension_helpers.hpp

Defined in header `hpx/thread_pool_util/thread_pool_suspension_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
namespace threads
```

Functions

```
hpx::future<void> resume_processing_unit(thread_pool_base &pool, std::size_t virt_core)
```

Resumes the given processing unit. When the processing unit has been resumed the returned future will be ready.

Note: Can only be called from an HPX thread. Use `resume_processing_unit_cb` or to resume the processing unit from outside HPX. Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to resume a processing unit on.
- **virt_core** – [in] The processing unit on the pool to be resumed. The processing units are indexed starting from 0.

Returns

A `future<void>` which is ready when the given processing unit has been resumed.

```
void resume_processing_unit_cb(thread_pool_base &pool, hpx::function<void()> callback,  
std::size_t virt_core, error_code &ec = throws)
```

Resumes the given processing unit. Takes a callback as a parameter which will be called when the processing unit has been resumed.

Note: Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to resume a processing unit on.
- **callback** – [in] Callback which is called when the processing unit has been suspended.
- **virt_core** – [in] The processing unit to resume.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

`hpx::future<void> suspend_processing_unit(thread_pool_base &pool, std::size_t virt_core)`

Suspends the given processing unit. When the processing unit has been suspended the returned future will be ready.

Note: Can only be called from an HPX thread. Use `suspend_processing_unit_cb` or to suspend the processing unit from outside HPX. Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to suspend a processing unit from.
- **virt_core** – [in] The processing unit on the pool to be suspended. The processing units are indexed starting from 0.

Throws

`hpx::exception` – if called from outside the HPX runtime.

Returns

A `future<void>` which is ready when the given processing unit has been suspended.

`void suspend_processing_unit_cb(hpx::function<void()> callback, thread_pool_base &pool, std::size_t virt_core, error_code &ec = throws)`

Suspends the given processing unit. Takes a callback as a parameter which will be called when the processing unit has been suspended.

Note: Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to suspend a processing unit from.
- **callback** – [in] Callback which is called when the processing unit has been suspended.
- **virt_core** – [in] The processing unit to suspend.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

`hpx::future<void> resume_pool(thread_pool_base &pool)`

Resumes the thread pool. When the all OS threads on the thread pool have been resumed the returned future will be ready.

Note: Can only be called from an HPX thread. Use `resume_cb` or `resume_direct` to suspend the pool from outside HPX.

Parameters

pool – [in] The thread pool to resume.

Throws

`hpx::exception` – if called from outside the HPX runtime.

Returns

A `future<void>` which is ready when the thread pool has been resumed.

void **resume_pool_cb**(*thread_pool_base* &pool, *hpx::function<void()>* callback, *error_code* &ec = *throws*)

Resumes the thread pool. Takes a callback as a parameter which will be called when all OS threads on the thread pool have been resumed.

Parameters

- **pool** – [in] The thread pool to resume.
- **callback** – [in] called when the thread pool has been resumed.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::future<void> **suspend_pool**(*thread_pool_base* &pool)

Suspends the thread pool. When the all OS threads on the thread pool have been suspended the returned future will be ready.

Note: Can only be called from an HPX thread. Use `suspend_cb` or `suspend_direct` to suspend the pool from outside HPX. A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

pool – [in] The thread pool to suspend.

Throws

hpx::exception – if called from outside the HPX runtime.

Returns

A `future<void>` which is ready when the thread pool has been suspended.

void **suspend_pool_cb**(*thread_pool_base* &pool, *hpx::function<void()>* callback, *error_code* &ec = *throws*)

Suspends the thread pool. Takes a callback as a parameter which will be called when all OS threads on the thread pool have been suspended.

Note: A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

- **pool** – [in] The thread pool to suspend.
- **callback** – [in] called when the thread pool has been suspended.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if called from an HPX thread which is running on the pool itself.

thread_support

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::unlock_guard

Defined in header `hpx/mutex.hpp`⁸⁰⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

```
template<typename Mutex>
```

```
class unlock_guard
```

#include <unlock_guard.hpp> The class *unlock_guard* is a mutex wrapper that provides a convenient mechanism for releasing a mutex for the duration of a scoped block.

unlock_guard performs the opposite functionality of *lock_guard*. When a *lock_guard* object is created, it attempts to take ownership of the mutex it is given. When control leaves the scope in which the *lock_guard* object was created, the *lock_guard* is destructed and the mutex is released. Accordingly, when an *unlock_guard* object is created, it attempts to release the ownership of the mutex it is given. So, when control leaves the scope in which the *unlock_guard* object was created, the *unlock_guard* is destructed and the mutex is owned again. In this way, the mutex is unlocked in the constructor and locked in the destructor, so that one can have an unlocked section within a locked one.

Public Types

```
using mutex_type = Mutex
```

Public Functions

```
inline explicit constexpr unlock_guard(Mutex &m) noexcept
```

```
HPX_NON_COPYABLE(unlock_guard)
```

```
inline ~unlock_guard()
```

Private Members

```
Mutex &m_
```

```
namespace util
```

⁸⁰⁴ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/mutex.hpp

Typedefs

```
using instead = hpx::unlock_guard<Mutex>
```

threading

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::jthread

Defined in header *hpx/jthread.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
inline void swap(jthread &lhs, jthread &rhs) noexcept
```

```
class jthread
```

#include <jthread.hpp> The class *jthread* represents a single thread of execution. It has the same general behavior as *hpx::thread*, except that *jthread* automatically rejoins on destruction, and can be cancelled/stopped in certain situations. Threads begin execution immediately upon construction of the associated thread object (pending any OS scheduling delays), starting at the top-level function provided as a constructor argument. The return value of the top-level function is ignored and if it terminates by throwing an exception, *hpx::terminate* is called. The top-level function may communicate its return value or an exception to the caller via *hpx::promise* or by modifying shared variables (which may require synchronization, see *hpx::mutex* and *hpx::atomic*) Unlike *hpx::thread*, the *jthread* logically holds an internal private member of type *hpx::stop_source*, which maintains a shared stop-state. The *jthread* constructor accepts a function that takes a *hpx::stop_token* as its first argument, which will be passed in by the *jthread* from its internal *stop_source*. This allows the function to check if stop has been requested during its execution, and return if it has. *hpx::jthread* objects may also be in the state that does not represent any thread (after default construction, move from, detach, or join), and a thread of execution may be not associated with any *jthread* objects (after detach). No two *hpx::jthread* objects may represent the same thread of execution; *hpx::jthread* is not *CopyConstructible* or *CopyAssignable*, although it is *MoveConstructible* and *MoveAssignable*.

Public Types

```
using id = thread::id
```

```
using native_handle_type = thread::native_handle_type
```

Public Functions

inline **jthread**() noexcept

template<typename **F**, typename ...**Ts**>
inline explicit **jthread**(*F* &&*f*, *Ts*&&... *ts*)

inline ~**jthread**()

jthread(*jthread* const&) = delete

jthread(*jthread* &&*x*) noexcept = default

jthread &**operator**=(*jthread* const&) = delete

jthread &**operator**=(*jthread*&&) noexcept = default
moves the *jthread* object

inline void **swap**(*jthread* &*t*) noexcept
swaps two *jthread* objects

inline bool **joinable**() const noexcept
checks whether the thread is joinable, i.e. potentially running in parallel context

inline void **join**()
waits for the thread to finish its execution

inline void **detach**()
permits the thread to execute independently of the thread handle

inline *id* **get_id**() const noexcept
returns the id of the thread

inline *native_handle_type* **native_handle**() const
returns the underlying implementation-defined thread handle

inline *stop_source* **get_stop_source**() noexcept
returns a *stop_source* object associated with the shared stop state of the thread

inline *stop_token* **get_stop_token**() const noexcept
returns a *stop_token* associated with the shared stop state of the thread

inline bool **request_stop**() const noexcept
requests execution stop via the shared stop state of the thread

Public Static Functions

static inline unsigned int **hardware_concurrency**() noexcept
returns the number of concurrent threads supported by the implementation

Private Members

stop_source **ssource_**

hpx::thread **thread_** = { }

Private Static Functions

```
template<typename F, typename ...Ts>
static inline void invoke(std::false_type, F &&f, stop_token&&, Ts&&... ts)
```

```
template<typename F, typename ...Ts>
static inline void invoke(std::true_type, F &&f, stop_token &&st, Ts&&... ts)
```

hpx::thread, **hpx::this_thread::yield**, **hpx::this_thread::get_id**, **hpx::this_thread::sleep_for**,
hpx::this_thread::sleep_until

Defined in header [hpx/thread.hpp](#)⁸⁰⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

struct **hash**<::hpx::thread::id>

Public Functions

```
inline std::size_t operator() (::hpx::thread::id const &id) const noexcept
```

namespace **hpx**

Typedefs

```
using thread_termination_handler_type = hpx::function<void(std::exception_ptr const &e)>
```

Functions

```
void set_thread_termination_handler(thread_termination_handler_type f)
```

```
inline void swap(thread &x, thread &y) noexcept
```

```
inline bool operator==(thread::id const &x, thread::id const &y) noexcept
```

```
inline bool operator!=(thread::id const &x, thread::id const &y) noexcept
```

```
inline bool operator<(thread::id const &x, thread::id const &y) noexcept
```

⁸⁰⁵ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/thread.hpp

```

inline bool operator>(thread::id const &x, thread::id const &y) noexcept

inline bool operator<=(thread::id const &x, thread::id const &y) noexcept

inline bool operator>=(thread::id const &x, thread::id const &y) noexcept

template<typename Char, typename Traits>
std::basic_ostream<Char, Traits> &operator<<(std::basic_ostream<Char, Traits> &out, thread::id const
&id)

```

class **thread**

#include <thread.hpp> The class `thread` represents a single thread of execution. Threads allow multiple functions to execute concurrently. Threads begin execution immediately upon construction of the associated thread object (pending any OS scheduling delays), starting at the top-level function provided as a constructor argument. The return value of the top-level function is ignored and if it terminates by throwing an exception, *hpx::terminate* is called. The top-level function may communicate its return value or an exception to the caller via *hpx::promise* or by modifying shared variables (which may require synchronization, see *hpx::mutex* and *hpx::atomic*) *hpx::thread* objects may also be in the state that does not represent any thread (after default construction, move from, detach, or join), and a thread of execution may not be associated with any thread objects (after detach). No two *hpx::thread* objects may represent the same thread of execution; *hpx::thread* is not *CopyConstructible* or *CopyAssignable*, although it is *MoveConstructible* and *MoveAssignable*.

Public Types

```
using native_handle_type = threads::thread_id_type
```

Public Functions

```
thread() noexcept
```

```
template<typename F>
inline explicit thread(F &&f)
```

```
template<typename F, typename ...Ts>
inline explicit thread(F &&f, Ts&&... vs)
```

```
template<typename F>
inline thread(threads::thread_pool_base *pool, F &&f)
```

```
template<typename F, typename ...Ts>
inline thread(threads::thread_pool_base *pool, F &&f, Ts&&... vs)
```

```
~thread()
```

```
thread(thread&&) noexcept
```

```
thread &operator=(thread&&) noexcept
```

```
void swap(thread&) noexcept
    swaps two thread objects
```

inline bool **joinable**() const noexcept

Checks whether the thread is joinable, i.e. potentially running in parallel context

void **join**()

waits for the thread to finish its execution

inline void **detach**()

permits the thread to execute independently of the thread handle

id **get_id**() const noexcept

returns the id of the thread

inline *native_handle_type* **native_handle**() const

returns the underlying implementation-defined thread handle

void **interrupt**(bool flag = true) const

bool **interruption_requested**() const

hpx::future<void> **get_future**(*error_code* &ec = *throws*) const

std::size_t **get_thread_data**() const

std::size_t **set_thread_data**(*std::size_t*) const

Public Static Functions

static unsigned int **hardware_concurrency**() noexcept

returns the number of concurrent threads supported by the implementation

static void **interrupt**(*id* const&, bool flag = true)

Private Types

using **mutex_type** = *hpx::spinlock*

Private Functions

inline bool **joinable_locked**() const noexcept

inline void **detach_locked**()

void **start_thread**(*threads::thread_pool_base* *pool, *hpx::move_only_function<void()>* &&func)

Private Members

mutable *mutex_type* **mtx_**

threads::thread_id_ref_type **id_**

Private Static Functions

static *threads::thread_result_type* **thread_function_nullary**(*hpx::move_only_function*<void()> const &func)

class **id**

Public Functions

id() noexcept = default

inline explicit **id**(*threads::thread_id_type* const &i) noexcept

inline explicit **id**(*threads::thread_id_type* &&i) noexcept

inline explicit **id**(*threads::thread_id_ref_type* const &i) noexcept

inline explicit **id**(*threads::thread_id_ref_type* &&i) noexcept

inline *threads::thread_id_type* const &**native_handle**() const noexcept

Private Members

threads::thread_id_type **id_**

Friends

friend class thread

friend bool operator==(*thread::id* const &x, *thread::id* const &y) noexcept

friend bool operator!=(*thread::id* const &x, *thread::id* const &y) noexcept

friend bool operator<(*thread::id* const &x, *thread::id* const &y) noexcept

friend bool operator>(*thread::id* const &x, *thread::id* const &y) noexcept

friend bool operator<=(*thread::id* const &x, *thread::id* const &y) noexcept

friend bool operator>=(*thread::id* const &x, *thread::id* const &y) noexcept

template<typename **Char**, typename **Traits**>

friend std::basic_ostream<*Char*, *Traits*> &**operator<<**(*std::basic_ostream*<*Char*, *Traits*>&, *thread::id* const&)

namespace **this_thread**

Functions

thread::id **get_id**() noexcept

Returns the id of the current thread.

void **yield**() noexcept

Provides a hint to the implementation to reschedule the execution of threads, allowing other threads to run.

Note: The exact behavior of this function depends on the implementation, in particular on the mechanics of the OS scheduler in use and the state of the system. For example, a first-in-first-out realtime scheduler (SCHED_FIFO in Linux) would suspend the current thread and put it on the back of the queue of the same-priority threads that are ready to run (and if there are no other threads at the same priority, yield has no effect).

void **yield_to**(*thread::id* const&) noexcept

threads::thread_priority **get_priority**() noexcept

std::ptrdiff_t **get_stack_size**() noexcept

void **interruption_point**()

bool **interruption_enabled**()

bool **interruption_requested**()

void **interrupt**()

void **sleep_until**(*hpx::chrono::steady_time_point* const &*abs_time*)

Blocks the execution of the current thread until specified *abs_time* has been reached.

It is recommended to use the clock tied to *abs_time*, in which case adjustments of the clock may be taken into account. Thus, the duration of the block might be more or less than *abs_time* - *Clock::now*() at the time of the call, depending on the direction of the adjustment and whether it is honored by the implementation. The function also may block until after *abs_time* has been reached due to process scheduling or resource contention delays.

Parameters

abs_time – absolute time to block until

inline void **sleep_for**(*hpx::chrono::steady_duration* const &*rel_time*)

Blocks the execution of the current thread for at least the specified *rel_time*. This function may block for longer than *rel_time* due to scheduling or resource contention delays.

It is recommended to use a steady clock to measure the duration. If an implementation uses a system clock instead, the wait time may also be sensitive to clock adjustments.

Parameters

rel_time – time duration to sleep

std::size_t **get_thread_data**()

std::size_t **set_thread_data**(*std::size_t*)

class **disable_interruption**

Public Functions

disable_interruption(*disable_interruption*&&) = delete

disable_interruption &**operator**=(*disable_interruption*&&) = delete

disable_interruption(*disable_interruption* const&) = delete

disable_interruption &**operator**=(*disable_interruption* const&) = delete

disable_interruption()

~disable_interruption()

Public Members

bool **interruption_was_enabled_**

Friends

friend class **restore_interruption**

class **restore_interruption**

Public Functions

restore_interruption(*restore_interruption*&&) = delete

restore_interruption &**operator**=(*restore_interruption*&&) = delete

restore_interruption(*restore_interruption* const&) = delete

restore_interruption &**operator**=(*restore_interruption* const&) = delete

explicit **restore_interruption**(*disable_interruption* const &d)

~restore_interruption()

Public Members

bool **interruption_was_enabled_**

threading_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/threading_base/print.hpp

Defined in header `hpx/threading_base/print.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/threading_base/thread_helpers.hpp

Defined in header `hpx/threading_base/thread_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **this_thread**

Functions

```
threads::thread_restart_state suspend(threads::thread_schedule_state state, threads::thread_id_type
                                     nextid, threads::thread_description const &description =
                                     threads::thread_description("this_thread::suspend"),
                                     hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to the thread state passed as the parameter.

Note: Must be called from within a HPX-thread.

Throws

If `!&ec` != `&throws`, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(threads::thread_schedule_state state =
                                             threads::thread_schedule_state::pending,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to the thread state passed as the parameter.

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
threads::thread_restart_state suspend(hpx::chrono::steady_time_point const &abs_time,
                                       threads::thread_id_type id, threads::thread_description const
                                       &description =
                                       threads::thread_description("this_thread::suspend"),
                                       hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads at the given time.

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_time_point const &abs_time,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads at the given time.

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_duration const &rel_time,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads after the given duration.

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_duration const &rel_time,  
                                             threads::thread_id_type const &id,  
                                             threads::thread_description const &description =  
                                             threads::thread_description("this_thread::suspend"),  
                                             hpx::error_code &ec = hpx::throws)
```

The function `suspend` will return control to the thread manager (suspends the current thread). It sets the new state of this thread to `suspended` and schedules a wakeup for this threads after the given duration.

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
inline threads::thread_restart_state suspend(std::uint64_t ms, threads::thread_description const  
                                             &description =  
                                             threads::thread_description("this_thread::suspend"),  
                                             hpx::error_code &ec = hpx::throws)
```

The function `suspend` will return control to the thread manager (suspends the current thread). It sets the new state of this thread to `suspended` and schedules a wakeup for this threads after the given time (specified in milliseconds).

Note: Must be called from within a HPX-thread.

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

```
threads::thread_pool_base *get_pool(hpx::error_code &ec = hpx::throws)
```

Returns a pointer to the pool that was used to run the current thread

Throws

If `- &ec != &throws`, never throws, but will set `ec` to an appropriate value when an error occurs. Otherwise, this function will throw an `hpx::exception` with an error code of `hpx::error::yield_aborted` if it is signaled with `wait_aborted`. If called outside a HPX-thread, this function will throw an `hpx::exception` with an error code of `hpx::error::null_thread_id`. If this function is called while the thread-manager is not running, it will throw an `hpx::exception` with an error code of `hpx::error::invalid_status`.

namespace **threads**

Functions

```
thread_state set_thread_state(thread_id_type const &id, thread_schedule_state state =
    thread_schedule_state::pending, thread_restart_state stateex =
    thread_restart_state::signaled, thread_priority priority =
    thread_priority::normal, bool retry_on_active = true, hpx::error_code
    &ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Note: If the thread referenced by the parameter *id* is in *thread_state::active* state this function schedules a new thread which will set the state of the thread as soon as it is not active anymore. The function returns *thread_state::active* in this case.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the previous state of the thread referenced by the *id* parameter. It will return one of the values as defined by the *thread_state* enumeration. If the thread is not known to the thread-manager the return value will be *thread_state::unknown*.

```
thread_id_ref_type set_thread_state(thread_id_type const &id, hpx::chrono::steady_time_point
    const &abs_time, std::atomic<bool> *started,
    thread_schedule_state state = thread_schedule_state::pending,
    thread_restart_state stateex = thread_restart_state::timeout,
    thread_priority priority = thread_priority::normal, bool
    retry_on_active = true, hpx::error_code &ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Set a timer to set the state of the given *thread* to the given new value after it expired (at the given time)

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **abs_time** – [in] Absolute point in time for the new thread to be run
- **started** – [in,out] A helper variable allowing to track the state of the timer helper thread

- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

```
inline thread_id_ref_type set_thread_state(thread_id_type const &id,
                                           hpx::chrono::steady_time_point const &abs_time,
                                           thread_schedule_state state =
                                           thread_schedule_state::pending, thread_restart_state
                                           stateex = thread_restart_state::timeout, thread_priority
                                           priority = thread_priority::normal, bool retry_on_active
                                           = true, hpx::error_code& = throws)

inline thread_id_ref_type set_thread_state(thread_id_type const &id, hpx::chrono::steady_duration
                                           const &rel_time, thread_schedule_state state =
                                           thread_schedule_state::pending, thread_restart_state
                                           stateex = thread_restart_state::timeout, thread_priority
                                           priority = thread_priority::normal, bool retry_on_active
                                           = true, hpx::error_code &ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Set a timer to set the state of the given *thread* to the given new value after it expired (after the given duration)

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **rel_time** – [in] Time duration after which the new thread should be run
- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

```
thread_state get_thread_state(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
                                noexcept
```

The function `get_thread_backtrace` is part of the thread related API allows to query the currently stored thread back trace (which is captured during thread suspension).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*. The function `get_thread_state` is part of the thread related API. It queries the state of one of the threads known to the thread-manager.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread being queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.
- **id** – [in] The thread id of the thread the state should be modified for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the currently captured stack back trace of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be the zero.

Returns

This function returns the thread state of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be *terminated*.

std::size_t **get_thread_phase**(thread_id_type const &id, *hpx::error_code* &ec = *hpx::throws*) noexcept

The function *get_thread_phase* is part of the thread related API. It queries the phase of one of the threads known to the thread-manager.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the phase should be modified for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the thread phase of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be ~0.

bool **get_thread_interruption_enabled**(thread_id_type const &id, *hpx::error_code* &ec = *hpx::throws*)

Returns whether the given thread can be interrupted at this point.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the given thread can be interrupted at this point in time. It will return *false* otherwise.

bool **set_thread_interruption_enabled**(thread_id_type const &id, bool enable, *hpx::error_code* &ec = *hpx::throws*)

Set whether the given thread can be interrupted at this point.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should receive the new value.
- **enable** – [in] This value will determine the new interruption enabled status for the given thread.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the previous value of whether the given thread could have been interrupted.

```
bool get_thread_interruption_requested(thread_id_type const &id, hpx::error_code &ec =  
                                         hpx::throws)
```

Returns whether the given thread has been flagged for interruption.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the given thread was flagged for interruption. It will return *false* otherwise.

```
void interrupt_thread(thread_id_type const &id, bool flag, hpx::error_code &ec = hpx::throws)
```

Flag the given thread for interruption.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be interrupted.
- **flag** – [in] The flag encodes whether the thread should be interrupted (if it is *true*), or 'uninterrupted' (if it is *false*).
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
inline void interrupt_thread(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
```

```
void interruption_point(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
```

Interrupt the current thread at this point if it was canceled. This will throw a *thread_interrupted* exception, which will cancel the thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be interrupted.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

threads::thread_priority **get_thread_priority**(thread_id_type const &id, hpx::error_code &ec = *hpx::throws*) noexcept

Return priority of the given thread

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread whose priority is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

std::ptrdiff_t **get_stack_size**(thread_id_type const &id, hpx::error_code &ec = *hpx::throws*) noexcept

Return stack size of the given thread

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread whose priority is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

*threads::thread_pool_base ****get_pool**(thread_id_type const &id, hpx::error_code &ec = *hpx::throws*)

Returns a pointer to the pool that was used to run the current thread

Throws

If *ec* != *&throws*, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

hpx/threading_base/thread_data.hpp

Defined in header *hpx/threading_base/thread_data.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

```
constexpr thread_data *get_thread_id_data(thread_id_ref_type const &tid) noexcept  
constexpr thread_data *get_thread_id_data(thread_id_type const &tid) noexcept  
constexpr tracing::region_init_data get_region_init_data(thread_data const*) noexcept  
constexpr tracing::fiber_region_init_data get_fiber_region_init_data(thread_data const*)  
                                                                    noexcept
```

class **thread_data** : public *thread_data_reference_counting*

#include <thread_data.hpp> A *thread* is the representation of a HPX thread. It's a first class object in HPX. In our implementation this is a user level thread running on top of one of the OS threads spawned by the *thread-manager*.

A *thread* encapsulates:

- A thread status word (see the functions *thread::get_state* and *thread::set_state*)
- A function to execute (the thread function)
- A frame (in this implementation this is a block of memory used as the threads stack)
- A block of registers (not implemented yet)

Generally, *threads* are not created or executed directly. All functionality related to the management of *threads* is implemented by the *thread-manager*.

Public Types

```
using spinlock_pool = util::spinlock_pool<thread_data>
```

Public Functions

```
thread_data(thread_data const&) = delete
```

```
thread_data(thread_data&&) = delete
```

```
thread_data &operator=(thread_data const&) = delete
```

```
thread_data &operator=(thread_data&&) = delete
```

```
inline thread_state get_state(std::memory_order const order = std::memory_order_acquire) const  
                                                                    noexcept
```

The *get_state* function queries the state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will be retrieved by using the function *threadmanager::get_state*.

Returns

This function returns the current state of this thread. It will return one of the values as defined by the *thread_state* enumeration.

```
inline thread_state set_state(thread_schedule_state const state, thread_restart_state state_ex =
    thread_restart_state::unknown, std::memory_order const load_order
    = std::memory_order_acquire, std::memory_order const
    exchange_order = std::memory_order_acq_rel) const noexcept
```

The `set_state` function changes the state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the thread-manager. Moreover, changing the thread state using this function does not change its scheduling status. It only sets the thread's status word. To change the thread's scheduling status `threadmanager::set_state` should be used.

Parameters

- **state** – [in] The new state to be set for the thread.
- **state_ex** – [in]
- **load_order** – [in]
- **exchange_order** – [in]

```
inline bool set_state_tagged(thread_schedule_state const newstate, thread_state const
    &prev_state, thread_state &new_tagged_state, std::memory_order
    exchange_order = std::memory_order_acq_rel) const noexcept
```

```
inline bool restore_state(thread_state const new_state, thread_state const old_state,
    std::memory_order const load_order = std::memory_order_relaxed,
    std::memory_order const load_exchange =
    std::memory_order_acq_rel) const noexcept
```

The `restore_state` function changes the state of this thread instance depending on its current state. It will change the state atomically only if the current state is still the same as passed as the second parameter. Otherwise, it won't touch the thread state of this instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the threadmanager. Moreover, changing the thread state using this function does not change its scheduling status. It only sets the thread's status word. To change the thread's scheduling status `threadmanager::set_state` should be used.

Parameters

- **new_state** – [in] The new state to be set for the thread.
- **old_state** – [in] The old state of the thread which still has to be the current state.
- **load_order** – [in]
- **load_exchange** – [in]

Returns

This function returns `true` if the state has been changed successfully

```
inline bool restore_state(thread_schedule_state new_state, thread_restart_state const state_ex,
    thread_state old_state, std::memory_order const load_exchange =
    std::memory_order_acq_rel) const noexcept
```

```
inline constexpr thread_priority get_priority() const noexcept
```

```
inline void set_priority(thread_priority priority) noexcept
```

```
inline constexpr bool interruption_requested() const noexcept
```

```
inline constexpr bool interruption_enabled() const noexcept
```

```
inline bool set_interruption_enabled(bool enable) noexcept

inline void interrupt(bool const flag = true)

bool interruption_point(bool throw_on_interrupt = true)

bool add_thread_exit_callback(function<void()> const &f)

void run_thread_exit_callbacks()

void free_thread_exit_callbacks()

inline bool runs_as_child(std::memory_order mo = std::memory_order_acquire) const noexcept

inline constexpr bool is_stackless() const noexcept

void destroy_thread() override

inline constexpr policies::scheduler_base *get_scheduler_base() const noexcept

inline constexpr std::uint16_t get_last_worker_thread_num() const noexcept

inline void set_last_worker_thread_num(std::uint16_t last_worker_thread_num) noexcept

inline constexpr std::ptrdiff_t get_stack_size() const noexcept

inline thread_stacksize get_stack_size_enum() const noexcept

template<typename ThreadQueue>
inline constexpr ThreadQueue &get_queue() noexcept

inline coroutine_type::result_type operator() (hpx::execution_base::this_thread::detail::agent_storage
                                             *agent_storage)
```

Execute the thread function.

Returns

This function returns the thread state the thread should be scheduled from this point on.
The thread manager will use the returned value to set the thread's scheduling status.

```
inline coroutine_type::result_type invoke_directly()
```

Directly execute the thread function (inline)

Returns

This function returns the thread state the thread should be scheduled from this point on.
The thread manager will use the returned value to set the thread's scheduling status.

```
inline virtual thread_id_type get_thread_id() const
```

```
inline virtual std::size_t get_thread_phase() const noexcept
```

```
virtual std::size_t get_thread_data() const = 0
```

```
virtual std::size_t set_thread_data(std::size_t data) = 0
```

```
virtual void init() = 0
```

```
virtual void rebind(thread_init_data &init_data) = 0
```

```
inline hpx::tracing::task_timer_data get_timer_data() const noexcept
```

```
inline void set_timer_data(hpx::tracing::task_timer_data data) noexcept
```

thread_data(thread_init_data &init_data, void *queue, *std::ptrdiff_t* stacksize, bool is_stackless = false, *thread_id_addrf* addrf = *thread_id_addrf::yes*)

~thread_data() override

virtual void **destroy**() noexcept = 0

Public Static Functions

static inline constexpr *std::uint64_t* **get_component_id**() noexcept

Return the id of the component this thread is running in.

static inline constexpr *threads::thread_description* **get_description**() noexcept

static inline constexpr *threads::thread_description* **set_description**(*threads::thread_description*) noexcept

static inline constexpr *threads::thread_description* **get_lco_description**() noexcept

static inline constexpr *threads::thread_description* **set_lco_description**(*threads::thread_description*) noexcept

static inline constexpr *std::uint32_t* **get_parent_locality_id**() noexcept

Return the locality of the parent thread.

static inline constexpr *thread_id_type* **get_parent_thread_id**() noexcept

Return the thread id of the parent thread.

static inline constexpr *std::size_t* **get_parent_thread_phase**() noexcept

Return the phase of the parent thread.

static inline constexpr *util::backtrace* const ***get_backtrace**() noexcept

static inline constexpr *util::backtrace* const ***set_backtrace**(*util::backtrace* const*) noexcept

Protected Functions

inline *thread_restart_state* **set_state_ex**(*thread_restart_state* const new_state, *std::memory_order* const load_order = *std::memory_order_acquire*, *std::memory_order* const load_exchange = *std::memory_order_acq_rel*) const noexcept

The set_state function changes the extended state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the threadmanager.

Parameters

- **new_state** – [in] The new extended state to be set for the thread.
- **load_order** – [in]
- **load_exchange** – [in]

void **rebind_base**(thread_init_data &init_data)

Private Members

thread_priority **priority_**

bool **requested_interrupt_**

bool **enabled_interrupt_**

bool **ran_exit_funcs_**

const bool **is_stackless_**

std::atomic<bool> **runs_as_child_**

std::uint16_t **last_worker_thread_num_**

thread_stacksize **stacksize_enum_**

HPX_NO_UNIQUE_ADDRESS *hpx::tracing::task_timer_data* **timer_data_**

std::int32_t **stacksize_**

mutable *std::atomic<thread_state>* **current_state_**

std::forward_list<hpx::function<void()>> **exit_funcs_**

policies::scheduler_base ***scheduler_base_**

void ***queue_**

hpx/threading_base/thread_pool_base.hpp

Defined in header `hpx/threading_base/thread_pool_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

`std::ostream &operator<<(std::ostream &os, thread_pool_base const &thread_pool)`

class **thread_pool_base**

#include <thread_pool_base.hpp> The base class used to manage a pool of OS threads.

Public Functions

virtual void **suspend_processing_unit_direct**(*std::size_t virt_core, error_code &ec = throws*)
= 0

Suspends the given processing unit. Blocks until the processing unit has been suspended.

Parameters

- **virt_core** – [in] The processing unit on the pool to be suspended. The processing units are indexed starting from 0.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

virtual void **resume_processing_unit_direct**(*std::size_t virt_core, error_code &ec = throws*)
= 0

Resumes the given processing unit. Blocks until the processing unit has been resumed.

Parameters

- **virt_core** – [in] The processing unit on the pool to be resumed. The processing units are indexed starting from 0.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

virtual void **resume_direct**(*error_code &ec = throws*) = 0

Resumes the thread pool. Blocks until all OS threads on the thread pool have been resumed.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

virtual void **suspend_direct**(*error_code &ec = throws*) = 0

Suspends the thread pool. Blocks until all OS threads on the thread pool have been suspended.

Note: A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if called from an HPX thread which is running on the pool itself.

struct **thread_pool_init_parameters**

Public Functions

```
inline thread_pool_init_parameters(std::string const &name, std::size_t index,  
                                   policies::scheduler_mode mode, std::size_t num_threads,  
                                   std::size_t thread_offset,  
                                   hpx::threads::policies::callback_notifier &notifier,  
                                   hpx::threads::policies::detail::affinity_data const  
                                   &affinity_data,  
                                   hpx::threads::detail::network_background_callback_type  
                                   const &network_background_callback =  
                                   hpx::threads::detail::network_background_callback_type(),  
                                   std::size_t max_background_threads =  
                                   static_cast<std::size_t>(-1), std::size_t  
                                   max_idle_loop_count =  
                                   HPX_IDLE_LOOP_COUNT_MAX, std::size_t  
                                   max_busy_loop_count =  
                                   HPX_BUSY_LOOP_COUNT_MAX, std::size_t  
                                   shutdown_check_count = 10)
```

Public Members

std::string const &**name_**

std::size_t **index_**

policies::scheduler_mode **mode_**

std::size_t **num_threads_**

std::size_t **thread_offset_**

hpx::threads::policies::callback_notifier &**notifier_**

hpx::threads::policies::detail::affinity_data const &**affinity_data_**

hpx::threads::detail::network_background_callback_type const
&**network_background_callback_**

std::size_t **max_background_threads_**

std::size_t **max_idle_loop_count_**

std::size_t **max_busy_loop_count_**

std::size_t **shutdown_check_count_**

hpx::scoped_annotation

Defined in header [hpx/functional.hpp](#)⁸⁰⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

struct **scoped_annotation**

#include <scoped_annotation.hpp> *scoped_annotation* associates a **name** with a section of code (scope). It can be used to visualize code execution in profiling tools like *Intel VTune*, *Apex Profiler*, etc. That allows analyzing performance to figure out which part(s) of code is (are) responsible for performance degradation, etc.

Public Functions

scoped_annotation(*scoped_annotation* const&) = delete

scoped_annotation(*scoped_annotation*&&) = delete

scoped_annotation &**operator**=(*scoped_annotation* const&) = delete

scoped_annotation &**operator**=(*scoped_annotation*&&) = delete

inline explicit constexpr **scoped_annotation**(char const*) noexcept

template<typename **F**>

inline explicit constexpr **scoped_annotation**(*F*&&) noexcept

inline ~**scoped_annotation**()

hpx::annotated_function

Defined in header [hpx/functional.hpp](#)⁸⁰⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

template<typename **F**>

constexpr *F* &&**annotated_function**(*F* &&*f*, char const* = nullptr) noexcept

Returns a function annotated with the given annotation.

Annotating includes setting the thread description per thread id.

Parameters

f – Function to annotate

template<typename **F**>

⁸⁰⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

⁸⁰⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/functional.hpp

```
constexpr F &&annotated_function(F &&f, std::string const&) noexcept
```

hpx/threading_base/register_thread.hpp

Defined in header `hpx/threading_base/register_thread.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **threads**

Functions

```
template<typename F>  
thread_function_type make_thread_function(F &&f)
```

```
template<typename F, typename ...Ts>  
thread_function_type make_thread_function_nullary(F &&f, Ts&&... ts)
```

```
void register_thread(threads::thread_init_data &data, threads::thread_pool_base *pool,  
                    threads::thread_id_ref_type &id, error_code &ec = hpx::throws)
```

Create a new *thread* using the given data.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **pool** – [in] The thread pool to use for launching the work.
- **id** – [out] The id of the newly created thread (if applicable)
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

Returns

This function will return the internal id of the newly created HPX-thread.

```
threads::thread_id_ref_type register_thread(threads::thread_init_data &data,  
                                             threads::thread_pool_base *pool, error_code &ec =  
                                             hpx::throws)
```

```
void register_thread(threads::thread_init_data &data, threads::thread_id_ref_type &id, error_code  
                    &ec = throws)
```

Create a new *thread* using the given data on the same thread pool as the calling thread, or on the default thread pool if not on an HPX thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **id** – [out] The id of the newly created thread (if applicable)
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

Returns

This function will return the internal id of the newly created HPX-thread.

threads::thread_id_ref_type **register_thread**(*threads::thread_init_data* &data, *error_code* &ec = *throws*)

thread_id_ref_type **register_work**(*threads::thread_init_data* &data, *threads::thread_pool_base* *pool, *error_code* &ec = *hpx::throws*)

Create a new work item using the given data.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **pool** – [in] The thread pool to use for launching the work.
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

thread_id_ref_type **register_work**(*threads::thread_init_data* &data, *error_code* &ec = *throws*)

Create a new work item using the given data on the same thread pool as the calling thread, or on the default thread pool if not on an HPX thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

hpx::get_worker_thread_num, hpx::get_local_worker_thread_num, hpx::get_local_worker_thread_num, hpx::get_thread_pool_num, hpx::get_thread_pool_num

Defined in header [hpx/runtime.hpp](#)⁸⁰⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

⁸⁰⁸ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Functions

`std::size_t get_worker_thread_num()` noexcept

Return the number of the current OS-thread running in the runtime instance the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the overall number of OS-threads executed (as returned by `get_os_thread_count()`).

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t get_worker_thread_num(error_code &ec)` noexcept

Return the number of the current OS-thread running in the runtime instance the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the overall number of OS-threads executed (as returned by `get_os_thread_count()`). It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

`std::size_t get_local_worker_thread_num()` noexcept

Return the number of the current OS-thread running in the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread on the current thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of OS-threads executed on the current thread pool. It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t get_local_worker_thread_num(error_code &ec)` noexcept

Return the number of the current OS-thread running in the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread on the current thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of OS-threads executed on the current thread pool. It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

`std::size_t` **get_thread_pool_num()** noexcept

Return the number of the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of thread pools started by the runtime. It will return -1 if the current thread pool is not a known thread pool or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t` **get_thread_pool_num**(*error_code* &ec) noexcept

Return the number of the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of thread pools started by the runtime. It will return -1 if the current thread pool is not a known thread pool or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

namespace **threads**

hpx/threading_base/thread_description.hpp

Defined in header `hpx/threading_base/thread_description.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

```
std::ostream &operator<<(std::ostream&, thread_description const&)
```

```
std::string as_string(thread_description const &desc)
```

```
threads::thread_description get_thread_description(thread_id_type const &id, error_code &ec =  
                                                    throws)
```

The function `get_thread_description` is part of the thread related API allows to query the description of one of the threads known to the thread-manager.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread being queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the description of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be the string “<unknown>”.

```
threads::thread_description set_thread_description(thread_id_type const &id,  
                                                    threads::thread_description const &desc =  
                                                    threads::thread_description(), error_code &ec  
                                                    = throws)
```

```
threads::thread_description get_thread_lco_description(thread_id_type const &id, error_code  
                                                        &ec = throws)
```

```
threads::thread_description set_thread_lco_description(thread_id_type const &id,  
                                                        threads::thread_description const &desc  
                                                        = threads::thread_description(),  
                                                        error_code &ec = throws)
```

```
struct thread_description
```


Public Types

enum class **data_type** : *std::uint8_t*

Values:

enumerator **description**

enumerator **address**

Public Functions

thread_description() noexcept = default

inline constexpr **thread_description**(char const*) noexcept

inline explicit constexpr **thread_description**(*std::string* const&) noexcept

template<typename **F**, typename = *std::enable_if_t<!std::is_same_v<F, thread_description> && !traits::is_action_v<F>>>*

inline explicit constexpr **thread_description**(*F* const&, char const* = nullptr) noexcept

template<typename **Action**, typename = *std::enable_if_t<traits::is_action_v<Action>>>*

inline explicit constexpr **thread_description**(*Action*, char const* = nullptr) noexcept

inline explicit constexpr **operator bool**() const noexcept

Public Static Functions

static inline constexpr *data_type* **kind**() noexcept

static inline constexpr char const* **get_description**() noexcept

static inline constexpr *std::size_t* **get_address**() noexcept

static inline constexpr bool **valid**() noexcept

Private Functions

void **init_from_alternative_name**(char const* altname)

namespace **util**

Typedefs

using **instead** = *hpx::threads::thread_description*

hpx/threading_base/threading_base_fwd.hpp

Defined in header `hpx/threading_base/threading_base_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

thread_data ***get_self_id_data**() noexcept

The function *get_self_id_data* returns the data of the HPX thread id associated with the current thread (or nullptr if the current thread is not a HPX thread).

thread_self &**get_self**()

The function *get_self* returns a reference to the (OS thread specific) self reference to the current HPX thread.

thread_self ***get_self_ptr**() noexcept

The function *get_self_ptr* returns a pointer to the (OS thread specific) self reference to the current HPX thread.

thread_self_impl_type ***get_ctx_ptr**()

The function *get_ctx_ptr* returns a pointer to the internal data associated with each coroutine.

thread_self ***get_self_ptr_checked**(error_code &ec = throws)

The function *get_self_ptr_checked* returns a pointer to the (OS thread specific) self reference to the current HPX thread.

thread_id_type **get_self_id**() noexcept

The function *get_self_id* returns the HPX thread id of the current thread (or zero if the current thread is not a HPX thread).

HPX_DEPRECATED_V (2, 0, "hpx::threads::get_outer_self_id is deprecated, use " "hpx::threads::get_self_id instead") inline thread_id_type get_outer_self_id() noexcept

The function *get_outer_self_id* returns the HPX thread id of the current outer thread (or zero if the current thread is not a HPX thread). This now always returns the same as *get_self_id*, even for directly executed threads.

thread_id_type **get_parent_id**() noexcept

The function *get_parent_id* returns the HPX thread id of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

`std::size_t get_parent_phase()` noexcept

The function `get_parent_phase` returns the HPX phase of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

`std::ptrdiff_t get_self_stacksize()` noexcept

The function `get_self_stacksize` returns the stack size of the current thread (or zero if the current thread is not a HPX thread).

`thread_stacksize get_self_stacksize_enum()` noexcept

The function `get_self_stacksize_enum` returns the stack size of the `/`.

`std::uint32_t get_parent_locality_id()` noexcept

The function `get_parent_locality_id` returns the id of the locality of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

`std::uint64_t get_self_component_id()` noexcept

The function `get_self_component_id` returns the lva of the component the current thread is acting on

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_TARGET_ADDRESS` being defined.

namespace **policies**

namespace **tracing**

threadmanager

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/threadmanager/threadmanager.hpp

Defined in header `hpx/threadmanager/threadmanager.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

class **threadmanager**

#include <threadmanager.hpp> The *thread-manager* class is the central instance of management for all (non-depleted) threads

Public Types

using **notification_policy_type** = *threads::policies::callback_notifier*

using **pool_type** = *std::unique_ptr<thread_pool_base>*

using **pool_vector** = *std::vector<pool_type>*

Public Functions

threadmanager(*hpx::util::runtime_configuration &rtcfg*, *notification_policy_type ¬ifier*,
 detail::network_background_callback_type network_background_callback =
 detail::network_background_callback_type())

threadmanager(*threadmanager const&*) = delete

threadmanager(*threadmanager&&*) = delete

threadmanager &operator=(*threadmanager const&*) = delete

threadmanager &operator=(*threadmanager&&*) = delete

~threadmanager()

void **init**() const

void **create_pools**()

void **print_pools**(*std::ostream&*) const

FIXME move to private and add `—hpx:printpools` cmd line option.

thread_pool_base &default_pool() const

thread_pool_base &get_pool(*std::string const &pool_name*) const

thread_pool_base &get_pool(*pool_id_type const &pool_id*) const

thread_pool_base &get_pool(*std::size_t thread_index*) const

bool **pool_exists**(*std::string const &pool_name*) const

bool **pool_exists**(*std::size_t pool_index*) const

thread_id_ref_type register_work(*thread_init_data &data*, *error_code &ec* = *throws*) const

The function *register_work* adds a new work item to the thread manager. It doesn't immediately create a new *thread*, it just adds the task parameters (function, initial state and description) to the internal management data structures. The thread itself will be created when the number of existing threads drops below the number of threads specified by the constructors *max_count* parameter.

Parameters

- **data** – [in] The value of this parameter allows to specify a description of the thread to create. This information is used for logging purposes mainly, but might be useful for debugging as well. This parameter is optional and defaults to an empty string.
- **ec** –

void **register_thread**(thread_init_data &data, thread_id_ref_type &id, error_code &ec = throws) const

The function *register_thread* adds a new work item to the thread manager. It creates a new *thread*, adds it to the internal management data structures, and schedules the new thread, if appropriate.

Parameters

- **data** – [in] The value of this parameter allows to specify a description of the thread to create. This information is used for logging purposes mainly, but might be useful for debugging as well. This parameter is optional and defaults to an empty string.
- **id** – [out] This parameter will hold the id of the created thread. This id is guaranteed to be validly initialized before the thread function is executed.
- **ec** –

bool **run**() const

Run the thread manager's work queue. This function instantiates the specified number of OS threads in each pool. All OS threads are started to execute the function *tfunc*.

Returns

The function returns *true* if the thread manager has been started successfully, otherwise it returns *false*.

void **stop**(bool blocking = true) const

Forcefully stop the thread-manager.

Parameters

blocking –

bool **is_busy**() const

bool **is_idle**() const

void **wait**() const

bool **wait_for**(hpx::chrono::steady_duration const &rel_time) const

template<typename **StopToken**>

inline bool **wait_for**(StopToken &&stop_token, hpx::chrono::steady_duration const &rel_time) const

void **suspend**() const

void **resume**() const

hpx::state **status**() const

Return whether the thread manager is still running This returns the “minimal state”, i.e. the state of the least advanced thread pool

std::int64_t **get_thread_count**(thread_schedule_state state = thread_schedule_state::unknown, thread_priority priority = thread_priority::default_, std::size_t num_thread = static_cast<std::size_t>(-1), bool reset = false) const

return the number of HPX-threads with the given state

Note: This function locks the internal OS lock in the thread manager

```
std::int64_t get_idle_core_count() const

mask_type get_idle_core_mask() const

std::int64_t get_background_thread_count() const

bool enumerate_threads(hpx::function<bool(thread_id_type)> const &f, thread_schedule_state
                        state = thread_schedule_state::unknown) const

void abort_all_suspended_threads() const

bool cleanup_terminated(bool delete_all) const

std::size_t get_os_thread_count() const
    Return the number of OS threads running in this thread-manager.
    This function will return correct results only if the thread-manager is running.

std::thread &get_os_thread_handle(std::size_t num_thread) const

void report_error(std::size_t num_thread, std::exception_ptr const &e) const
    API functions forwarding to notification policy.
    This notifies the thread manager that the passed exception has been raised. The exception will be
    routed through the notifier and the scheduler (which will result in it being passed to the runtime
    object, which in turn will report it to the console, etc.).

mask_type get_used_processing_units() const
    Returns the mask identifying all processing units used by this thread manager.

hwloc_bitmap_ptr get_pool_numa_bitmap(std::string const &pool_name) const

void set_scheduler_mode(threads::policies::scheduler_mode mode,
                        hpx::threads::mask_cref_type pu_mask) const noexcept

void add_scheduler_mode(threads::policies::scheduler_mode mode,
                        hpx::threads::mask_cref_type pu_mask) const noexcept

void add_remove_scheduler_mode(threads::policies::scheduler_mode to_add_mode,
                                threads::policies::scheduler_mode to_remove_mode,
                                hpx::threads::mask_cref_type pu_mask) const noexcept

void remove_scheduler_mode(threads::policies::scheduler_mode mode,
                            hpx::threads::mask_cref_type pu_mask) const noexcept

void reset_thread_distribution() const noexcept

std::int64_t get_queue_length(bool reset) const

std::int64_t get_cumulative_duration(bool reset) const

std::int64_t get_thread_count_unknown(bool reset) const

std::int64_t get_thread_count_active(bool reset) const

std::int64_t get_thread_count_pending(bool reset) const

std::int64_t get_thread_count_suspended(bool reset) const

std::int64_t get_thread_count_terminated(bool reset) const

std::int64_t get_thread_count_staged(bool reset) const
```

Public Static Functions

static void **init_tss**(*std::size_t* global_thread_num)

static void **deinit_tss**()

Private Types

using **mutex_type** = *std::mutex*

Private Functions

policies::thread_queue_init_parameters **get_init_parameters**() const

void **create_scheduler_user_defined**(*hpx::resource::scheduler_function* const&, *thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&)

void **create_scheduler_local**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_local_priority_fifo**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_local_priority_lifo**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_static**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_static_priority**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_abp_priority_fifo**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_abp_priority_lifo**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_shared_priority**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

void **create_scheduler_local_workrequesting_fifo**(*thread_pool_init_parameters* const&, *policies::thread_queue_init_parameters* const&, *std::size_t*)

```
void create_scheduler_local_workrequesting_lifo(thread_pool_init_parameters const&,
                                              policies::thread_queue_init_parameters
                                              const&, std::size_t)

void create_scheduler_local_workrequesting_mc(thread_pool_init_parameters const&,
                                              policies::thread_queue_init_parameters
                                              const&, std::size_t)
```

Private Members

```
mutable mutex_type mtx_

hpx::util::runtime_configuration &rtcfg_

std::vector<pool_id_type> threads_lookup_

pool_vector pools_

notification_policy_type &notifier_

detail::network_background_callback_type network_background_callback_
```

timed_execution

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/timed_execution/timed_execution_fwd.hpp

Defined in header `hpx/timed_execution/timed_execution_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
        namespace execution
```


Variables

constexpr struct *hpx::parallel::execution::post_at_t* **post_at**

constexpr struct *hpx::parallel::execution::post_after_t* **post_after**

constexpr struct *hpx::parallel::execution::async_execute_at_t* **async_execute_at**

constexpr struct *hpx::parallel::execution::async_execute_after_t* **async_execute_after**

constexpr struct *hpx::parallel::execution::sync_execute_at_t* **sync_execute_at**

constexpr struct *hpx::parallel::execution::sync_execute_after_t* **sync_execute_after**

struct **async_execute_after_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous execution agent creation supporting timed execution.

This asynchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.async_execute_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::async_execute()` on the underlying non-time-scheduled execution agent.

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *rel_time*

[in] The duration of time after which the given function should be scheduled to run.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts...*

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result through a future

Public Functions

template<executor_any **Executor**, typename **F**, typename ...**Ts**>

inline decltype(auto) **operator()** (*Executor* &&*exec*, *hpx::chrono::steady_duration* const &*rel_time*, *F* &&*f*, *Ts*&&... *ts*) const

template<executor_any **Executor**, typename **F**, typename ...**Ts**>

inline decltype(auto) **operator()** (*Executor* &&*exec*, *hpx::chrono::steady_duration* const &*rel_time*, *F* &&*f*, *Ts*&&... *ts*) const

struct **async_execute_at_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous execution agent creation supporting timed execution.

This asynchronously creates a single function invocation *f()* using the associated executor at the given point in time.

Note: This calls `exec.async_execute_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::async_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param abs_time

[in] The point in time the given function should be scheduled at to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(ts...)'s result through a future

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                   &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                   &abs_time, F &&f, Ts&&... ts) const
```

struct **post_after_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous fire & forget execution agent creation supporting timed execution.

This asynchronously (fire & forget) creates a single function invocation *f()* using the associated executor at the given point in time.

Note: This calls `exec.post_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::post()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param rel_time

[in] The duration of time after which the given function should be scheduled to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```

struct **post_at_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous fire & forget execution agent creation supporting timed execution.

This asynchronously (fire & forget) creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.post_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::post()` on the underlying non-time-scheduled execution agent.

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *abs_time*

[in] The point in time the given function should be scheduled at to run.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts...*

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

struct **sync_execute_after_t**

#include <timed_execution_fwd.hpp> Customization point of synchronous execution agent creation supporting timed execution.

This synchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.sync_execute_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::sync_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param rel_time

[in] The duration of time after which the given function should be scheduled to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &rel_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &rel_time, F &&f, Ts&&... ts) const
```

struct **sync_execute_at_t**

#include <timed_execution_fwd.hpp> Customization point of synchronous execution agent creation supporting timed execution.

This synchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.sync_execute_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::sync_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param abs_time

[in] The point in time the given function should be scheduled at to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any BaseExecutor>
```

```
struct timed_executor
```

hpx/timed_execution/timed_execution.hpp

Defined in header `hpx/timed_execution/timed_execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
        namespace execution
```

hpx/timed_execution/timed_executors.hpp

Defined in header `hpx/timed_execution/timed_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            namespace parallel
```

```
                namespace execution
```

Typedefs

```
using sequenced_timed_executor = timed_executor<hpx::execution::sequenced_executor>

using parallel_timed_executor = timed_executor<hpx::execution::parallel_executor>

template<executor_any BaseExecutor>

struct timed_executor
```

`hpx/timed_execution/traits/is_timed_executor.hpp`

Defined in header `hpx/timed_execution/traits/is_timed_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Variables

```
template<typename Executor> concept timed_executor    = hpx::traits::is_timed_executor_v<Executor>
```

```
namespace parallel
```

```
    namespace execution
```

Typedefs

```
template<typename T>

using is_timed_executor_t = typename is_timed_executor<T>::type
```

Variables

```
template<typename T>

constexpr bool is_timed_executor_v = is_timed_executor<T>::value

template<typename T>

struct is_timed_executor : public detail::is_timed_executor<std::decay_t<T>>
```

```
namespace traits
```

Variables

```
template<typename T>
constexpr bool is_timed_executor_v = is_timed_executor<T>::value

template<typename Executor, typename Enable = void>

struct is_timed_executor : public hpx::parallel::execution::is_timed_executor<Executor>
```

timing

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::chrono::high_resolution_clock

Defined in header `hpx/chrono.hpp`⁸⁰⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **chrono**

struct **high_resolution_clock**

#include <high_resolution_clock.hpp> Class `hpx::chrono::high_resolution_clock` represents the clock with the smallest tick period provided by the implementation. It may be an alias of `std::chrono::system_clock` or `std::chrono::steady_clock`, or a third, independent clock. `hpx::chrono::high_resolution_clock` meets the requirements of *TrivialClock*.

Public Static Functions

static inline `std::uint64_t` **now**() noexcept
returns a `std::chrono::time_point` representing the current value of the clock

static inline constexpr `std::uint64_t`() **min** () noexcept

static inline constexpr `std::uint64_t`() **max** () noexcept

⁸⁰⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/chrono.hpp

hpx::chrono::high_resolution_timer

Defined in header [hpx/chrono.hpp](#)⁸¹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **chrono**

class **high_resolution_timer**

#include <high_resolution_timer.hpp> *high_resolution_timer* is a timer object which measures the elapsed time

Public Types

enum class **init**

Values:

enumerator **no_init**

Public Functions

inline **high_resolution_timer**() noexcept

inline explicit constexpr **high_resolution_timer**(*init*) noexcept

inline explicit constexpr **high_resolution_timer**(double t) noexcept

inline void **restart**() noexcept

restarts the timer

inline double **elapsed**() const noexcept

returns the elapsed time in seconds

inline *std::int64_t* **elapsed_microseconds**() const noexcept

returns the elapsed time in microseconds

inline *std::int64_t* **elapsed_nanoseconds**() const noexcept

returns the elapsed time in nanoseconds

⁸¹⁰ http://github.com/TheHPXProject/hpx/blob/unknown/libs/core/include_local/include/hpx/chrono.hpp

Public Static Functions

static inline double **now**() noexcept

returns the current time

static inline constexpr double **elapsed_max**() noexcept

returns the estimated maximum value for *elapsed*()

static inline constexpr double **elapsed_min**() noexcept

returns the estimated minimum value for *elapsed*()

Protected Static Functions

static inline *std::uint64_t* **take_time_stamp**() noexcept

Private Members

std::uint64_t **start_time_**

topology

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/topology/cpu_mask.hpp

Defined in header `hpx/topology/cpu_mask.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

hpx/topology/topology.hpp

Defined in header `hpx/topology/topology.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Typedefs

```
using hwloc_bitmap_ptr = std::shared_ptr<hpx_hwloc_bitmap_wrapper>
```

Enums

```
enum hpx_hwloc_membind_policy
```

Please see hwloc documentation for the corresponding enums HWLOC_MEMBIND_XXX.

Values:

enumerator **membind_default**

enumerator **membind_firsttouch**

enumerator **membind_bind**

enumerator **membind_interleave**

enumerator **membind_replicate**

enumerator **membind_nexttouch**

enumerator **membind_mixed**

enumerator **membind_user**

Functions

```
topology &create_topology()
```

```
inline topology const &get_topology()
```

Get the global topology instance.

```
inline std::size_t get_memory_page_size()
```

```
struct hpx_hwloc_bitmap_wrapper
```

Public Functions

HPX_NON_COPYABLE(*hpx_hwloc_bitmap_wrapper*)

inline **hpx_hwloc_bitmap_wrapper**() noexcept

inline explicit **hpx_hwloc_bitmap_wrapper**(void *bmp) noexcept

inline **~hpx_hwloc_bitmap_wrapper**()

inline void **reset**(hwloc_bitmap_t bmp) noexcept

inline explicit constexpr **operator bool**() const noexcept

inline hwloc_bitmap_t **get_bmp**() const noexcept

Private Members

hwloc_bitmap_t **bmp_**

Friends

friend *std::ostream* &**operator**<<(*std::ostream* &os, *hpx_hwloc_bitmap_wrapper* const *bmp)

struct **topology**

Public Functions

topology()

topology(*topology* const&) = delete

topology(*topology*&&) = delete

topology &**operator**=(*topology* const&) = delete

topology &**operator**=(*topology*&&) = delete

~topology()

inline *std::size_t* **get_socket_number**(*std::size_t* num_thread, [[maybe_unused]] *error_code* &ec = *throws*) const noexcept

Return the Socket number of the processing unit the given thread is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

inline *std::size_t* **get_numa_node_number**(*std::size_t* num_thread, [[maybe_unused]] *error_code* &ec = *throws*) const noexcept

Return the NUMA node number of the processing unit the given thread is running on.

Parameters

- **num_thread** – [in]

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

inline *std::size_t* **get_numa_distance**(*std::size_t* node_a, *std::size_t* node_b) const noexcept

Return the hardware latency distance between two NUMA nodes. Values are sourced from hwloc's distance matrix when available; otherwise a standard default (10 = local, 20 = remote) is returned.

Parameters

- **node_a** – [in] logical index of the first NUMA node
- **node_b** – [in] logical index of the second NUMA node

mask_cref_type **get_machine_affinity_mask**(*error_code* &ec = *throws*) const noexcept

Return a bit mask where each set bit corresponds to a processing unit available to the application.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_type **get_service_affinity_mask**(mask_cref_type used_processing_units, *error_code* &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit available to the service threads in the application.

Parameters

- **used_processing_units** – [in] This is the mask of processing units which are not available for service threads.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_socket_affinity_mask**(*std::size_t* num_thread, *error_code* &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the socket it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_numa_node_affinity_mask**(*std::size_t* num_thread, *error_code* &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the NUMA domain it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_core_affinity_mask**(*std::size_t* num_thread, *error_code* &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the core it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_thread_affinity_mask**(*std::size_t* num_thread, *error_code* &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

void **set_thread_affinity_mask**(mask_cref_type mask, error_code &ec = *throws*) const

Use the given bit mask to set the affinity of the given thread. Each set bit corresponds to a processing unit the thread will be allowed to run on.

Note: Use this function on systems where the affinity must be set from inside the thread itself.

Parameters

- **mask** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_type **get_thread_affinity_mask_from_lva**(void const *lva, error_code &ec = *throws*) const

Return a bit mask where each set bit corresponds to a processing unit co-located with the memory the given address is currently allocated on.

Parameters

- **lva** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

void **print_affinity_mask**(std::ostream &os, std::size_t num_thread, mask_cref_type m, std::string const &pool_name) const

Prints the given mask *m* to os in a human-readable form.

bool **reduce_thread_priority**(error_code &ec = *throws*) const

Reduce thread priority of the current thread.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

std::size_t **get_number_of_sockets**() const

Return the number of available NUMA domains.

std::size_t **get_number_of_numa_nodes**() const

Return the number of available NUMA domains.

std::size_t **get_number_of_cores**() const

Return the number of available cores.

std::size_t **get_number_of_pus**() const noexcept

Return the number of available hardware processing units.

std::size_t **get_number_of_numa_node_cores**(std::size_t numa) const

Return number of cores in given numa domain.

std::size_t **get_number_of_numa_node_pus**(std::size_t numa) const

Return number of processing units in a given numa domain.

std::size_t **get_number_of_socket_pus**(std::size_t socket) const

Return number of processing units in a given socket.

`std::size_t` **get_number_of_core_pus**(`std::size_t` core) const
Return number of processing units in given core.

`std::size_t` **get_number_of_socket_cores**(`std::size_t` socket) const
Return number of cores units in given socket.

inline `std::size_t` **get_core_number**(`std::size_t` num_thread, *error_code* &= *throws*) const

`std::size_t` **get_pu_number**(`std::size_t` num_core, `std::size_t` num_pu, *error_code* &ec = *throws*) const

`std::size_t` **get_cache_size**(*mask_cref_type* mask, int level) const
Return the size of the cache associated with the given mask.

mask_type **get_cpubind_mask**(*error_code* &ec = *throws*) const

mask_type **get_cpubind_mask**(`std::thread` &handle, *error_code* &ec = *throws*) const

hwloc_bitmap_ptr **cpuset_to_nodese**(*mask_cref_type* mask) const
convert a cpu mask into a numa node mask in hwloc bitmap form

void **write_to_log**() const

void ***allocate**(`std::size_t` len) const
This is equivalent to malloc(), except that it tries to allocate page-aligned memory from the OS.

void ***allocate_membind**(`std::size_t` len, *hwloc_bitmap_ptr* const &bitmap, *hpx_hwloc_membind_policy* policy, int flags) const
allocate memory with binding to a numa node set as specified by the policy and flags (see hwloc docs)

threads::mask_type **get_area_membind_nodese**(void const *addr, `std::size_t` len) const

bool **set_area_membind_nodese**(void const *addr, `std::size_t` len, void *nodese) const

int **get_numa_domain**(void const *addr) const

void **deallocate**(void *addr, `std::size_t` len) const noexcept
Free memory that was previously allocated by allocate.

void **print_hwloc**(`std::ostream` &) const

mask_type **init_socket_affinity_mask_from_socket**(`std::size_t` num_socket) const

mask_type **init_numa_node_affinity_mask_from_numa_node**(`std::size_t` num_numa_node) const

mask_type **init_core_affinity_mask_from_core**(`std::size_t` num_core, *mask_cref_type* default_mask = *empty_mask*) const

mask_type **init_thread_affinity_mask**(`std::size_t` num_thread) const

mask_type **init_thread_affinity_mask**(`std::size_t` num_core, `std::size_t` num_pu) const

hwloc_bitmap_t **mask_to_bitmap**(*mask_cref_type* mask, *hwloc_obj_type_t* htype, unsigned *count = nullptr) const

mask_type **bitmap_to_mask**(*hwloc_bitmap_t* bitmap, *hwloc_obj_type_t* htype) const

Public Static Functions

static void **print_vector**(*std::ostream* &os, *std::vector*<*std::size_t*> const &v)

static void **print_mask_vector**(*std::ostream* &os, *std::vector*<mask_type> const &v)

Private Types

using **mutex_type** = *hpx::util::spinlock*

Private Functions

std::size_t **init_node_number**(*std::size_t* num_thread, hwloc_obj_type_t type) const

inline *std::size_t* **init_socket_number**(*std::size_t* num_thread) const

std::size_t **init_numa_node_number**(*std::size_t* num_thread) const

inline *std::size_t* **init_core_number**(*std::size_t* num_thread) const

void **extract_node_mask**(hwloc_obj_t parent, mask_type &mask) const

std::size_t **get_number_of_core_pus_locked**(*std::size_t* core) const

std::size_t **extract_node_count**(hwloc_obj_t parent, hwloc_obj_type_t type, *std::size_t* count)
const

std::size_t **extract_node_count_locked**(hwloc_obj_t parent, hwloc_obj_type_t type, *std::size_t*
count) const

mask_type **init_machine_affinity_mask**() const

inline mask_type **init_socket_affinity_mask**(*std::size_t* num_thread) const

inline mask_type **init_numa_node_affinity_mask**(*std::size_t* num_thread) const

inline mask_type **init_core_affinity_mask**(*std::size_t* num_thread) const

void **init_num_of_pus**()

hwloc_obj_t **get_pu_obj**(*std::size_t* num_pu) const

void **init_numa_node_distances**()

Private Members

hwloc_topology_t **topo** = nullptr

std::size_t **num_of_pus** = 0

bool **use_pus_as_cores** = false

```
mutable mutex_type topo_mtx

std::vector<std::size_t> socket_numbers_

std::vector<std::size_t> numa_node_numbers_

std::vector<std::size_t> core_numbers_

mask_type machine_affinity_mask_ = mask_type()

std::vector<mask_type> socket_affinity_masks_

std::vector<mask_type> numa_node_affinity_masks_

std::vector<mask_type> core_affinity_masks_

std::vector<mask_type> thread_affinity_masks_

std::vector<std::vector<std::size_t>> numa_node_distances_
```

Private Static Attributes

```
static mask_type empty_mask

static std::size_t memory_page_size_

static constexpr std::size_t pu_offset = 0

static constexpr std::size_t core_offset = 0
```

Friends

```
friend std::size_t get_memory_page_size()
```

tracing

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/tracing/tracing.hpp

Defined in header `hpx/tracing/tracing.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

namespace **tracing**

struct **lock_context**

#include <tracing.hpp> Context for annotating lock acquisitions and releases.

This struct is used to provide tracing annotations for synchronization primitives such as spinlocks and mutexes. It registers the creation, acquisition, and release of locks to the active tracing backend.

Public Functions

explicit **lock_context**(char const *name = nullptr, void const *addr = nullptr) noexcept

Constructs a lock context.

Parameters

- **name** – The name or description of the lock.
- **addr** – The memory address of the lock, used to track it uniquely.

explicit **lock_context**(char const *prefix, char const *suffix, void const *addr = nullptr) noexcept

Constructs a lock context with a dynamic name.

Parameters

- **prefix** – The prefix for the lock name.
- **suffix** – The suffix for the lock name.
- **addr** – The memory address of the lock, used to track it uniquely.

bool **before_lock**() const noexcept

Called immediately before attempting to acquire the lock.

Returns

true if the prepare event was recorded and `after_lock` should be called.

void **after_lock**() const noexcept

Called immediately after the lock is successfully acquired.

void **after_try_lock**(bool success) const noexcept

Called after a try-lock operation completes.

Parameters

success – true if the lock was acquired, false if it failed.

void **before_unlock**() const noexcept

Called immediately before releasing the lock.

void **after_unlock**() const noexcept

Called immediately after releasing the lock.

namespace **util**

namespace **external_timer**

util

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/util/sed_transform.hpp

Defined in header `hpx/util/sed_transform.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

bool **parse_sed_expression**(*std::string* const &input, *std::string* &search, *std::string* &replace)

Parse a sed command.

Note: Currently, only supports search and replace syntax (s/search/replace/)

Parameters

- **input** – [in] The content to parse.
- **search** – [out] If the parsing is successful, this string is set to the search expression.
- **replace** – [out] If the parsing is successful, this string is set to the replace expression.

Returns

true if the parsing was successful, *false* otherwise.

struct **sed_transform**

#include <sed_transform.hpp> An unary function object which applies a sed command to its subject and returns the resulting string.

Note: Currently, only supports search and replace syntax (s/search/replace/)

Public Functions

sed_transform(*std::string* const &search, *std::string* replace)

explicit **sed_transform**(*std::string* const &expression)

std::string **operator**()(*std::string* const &input) const

inline explicit **operator** **bool**() const noexcept

inline **bool** **operator!**() const noexcept

Private Members

std::shared_ptr<command> **command_**

hpx/util/insert_checked.hpp

Defined in header `hpx/util/insert_checked.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

Functions

template<typename **Iterator**>

constexpr **bool** **insert_checked**(*std::pair*<*Iterator*, **bool**> const &r) noexcept

Helper function for writing predicates that test whether an `std::map` insertion succeeded. This inline template function negates the need to explicitly write the sometimes lengthy `std::pair<Iterator, bool>` type.

Parameters

r – [in] The return value of a `std::map` insert operation.

Returns

This function returns **r.second**.

template<typename **Iterator**>

bool **insert_checked**(*std::pair*<*Iterator*, **bool**> const &r, *Iterator* &it)

Helper function for writing predicates that test whether an `std::map` insertion succeeded. This inline template function negates the need to explicitly write the sometimes lengthy `std::pair<Iterator, bool>` type.

Parameters

- r** – [in] The return value of a `std::map` insert operation.
- r** – [out] A reference to an `Iterator`, which is set to **r.first**.
- it** – [out] on exit, will hold the iterator referring to the inserted element

Returns

This function returns **r.second**.

actions

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/transfer_action.hpp

Defined in header `hpx/actions/transfer_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/action_support.hpp

Defined in header `hpx/actions/action_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/actions_fwd.hpp

Defined in header `hpx/actions/actions_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/base_action.hpp

Defined in header `hpx/actions/base_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/transfer_base_action.hpp

Defined in header `hpx/actions/transfer_base_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

actions_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions_base/actions_base_support.hpp

Defined in header `hpx/actions_base/actions_base_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **actions**

hpx/actions_base/preassigned_action_id.hpp

Defined in header `hpx/actions_base/preassigned_action_id.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

hpx/actions_base/macros.hpp

Defined in header `hpx/actions_base/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_REGISTER_ACTION_INVOCATION_COUNT(Action)

HPX_REGISTER_PER_ACTION_DATA_COUNTER_TYPES(Action)

HPX_MAKE_ACTION(func)

HPX_MAKE_DIRECT_ACTION(func)

HPX_DECLARE_ACTION(...)

Declares an action type.

HPX_REGISTER_ACTION_DECLARATION(...)

Declare the necessary component action boilerplate code.

The macro *HPX_REGISTER_ACTION_DECLARATION* can be used to declare all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to declare the boilerplate for.

This macro can be invoked with an optional second parameter. This parameter specifies a unique name of the action to be used for serialization purposes. The second parameter has to be specified if the first parameter is not usable as a plain (nonqualified) C++ identifier, i.e. the first parameter contains special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

```

namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
        void print_greeting ()
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }
    }
}

```

(continues on next page)

(continued from previous page)

```
// Component actions need to be declared, this also defines the
// type 'print_greeting_action' representing the action.
HPX_DEFINE_COMPONENT_ACTION(server,
    print_greeting, print_greeting_action);
};
}

// Declare boilerplate code required for each of the component actions.
HPX_REGISTER_ACTION_DECLARATION(app::server::print_greeting_action)
```

Example:

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* macros. It has to be visible in all translation units using the action, thus it is recommended to place it into the header file defining the component.

HPX_REGISTER_ACTION_DECLARATION(...)**HPX_REGISTER_ACTION_DECLARATION_1(action)****HPX_REGISTER_ACTION(...)**

Define the necessary component action boilerplate code.

The macro *HPX_REGISTER_ACTION* can be used to define all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to define the boilerplate for.

This macro can be invoked with an optional second parameter. This parameter specifies a unique name of the action to be used for serialization purposes. The second parameter has to be specified if the first parameter is not usable as a plain (nonqualified) C++ identifier, i.e. the first parameter contains special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* or *HPX_DEFINE_PLAIN_ACTION* macros. It has to occur exactly once for each of the actions, thus it is recommended to place it into the source file defining the component.

Note: Only one of the forms of this macro *HPX_REGISTER_ACTION* or *HPX_REGISTER_ACTION_ID* should be used for a particular action, never both.

HPX_REGISTER_ACTION_ID(action, actionname, actionid)

Define the necessary component action boilerplate code and assign a predefined unique id to the action.

The macro *HPX_REGISTER_ACTION* can be used to define all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to define the boilerplate for.

The parameter *actionname* specifies a unique name of the action to be used for serialization purposes. The second parameter has to be usable as a plain (nonqualified) C++ identifier, it should not contain special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

The parameter *actionid* specifies a unique integer value which will be used to represent the action during serialization.

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* or global actions *HPX_DEFINE_PLAIN_ACTION* macros. It has to occur exactly once for each of the actions, thus it is recommended to place it into the source file defining the component.

Note: Only one of the forms of this macro *HPX_REGISTER_ACTION* or *HPX_REGISTER_ACTION_ID* should be used for a particular action, never both.

HPX_DEFINE_COMPONENT_ACTION(...)

Registers a member function of a component as an action type with HPX.

The macro *HPX_DEFINE_COMPONENT_ACTION* can be used to register a member function of a component as an action type named *action_type*.

The parameter *component* is the type of the component exposing the member function *func* which should be associated with the newly defined action type. The parameter *action_type* is the name of the action type to register with HPX.

```
namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
    public:
        void print_greeting() const
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }

        // Component actions need to be declared, this also defines the
        // type 'print_greeting_action' representing the action.
        HPX_DEFINE_COMPONENT_ACTION(server, print_greeting,
            print_greeting_action);
    };
}
```

Example:

The first argument must provide the type name of the component the action is defined for.

The second argument must provide the member function name the action should wrap.

The default value for the third argument (the typename of the defined action) is derived from the name of the function (as passed as the second argument) by appending ‘_action’. The third argument can be omitted only if the second argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name.

Note: The macro *HPX_DEFINE_COMPONENT_ACTION* can be used with 2 or 3 arguments. The third argument is optional.

HPX_DEFINE_PLAIN_ACTION(...)

Defines a plain action type.

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }

    // This will define the action type 'app::some_global_action' which
    // represents the function 'app::some_global_function'.
    HPX_DEFINE_PLAIN_ACTION(some_global_function, some_global_action);
}
```

Example:

Note: Usually this macro will not be used in user code unless the intent is to avoid defining the action_type in global namespace. Normally, the use of the macro *HPX_PLAIN_ACTION* is recommended.

Note: The macro *HPX_DEFINE_PLAIN_ACTION* can be used with 1 or 2 arguments. The second argument is optional. The default value for the second argument (the typename of the defined action) is derived from the name of the function (as passed as the first argument) by appending ‘_action’. The second argument can be omitted only if the first argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name.

HPX_DECLARE_PLAIN_ACTION(...)

Declares a plain action type.

HPX_PLAIN_ACTION(...)

Defines a plain action type based on the given function *func* and registers it with HPX.

The macro *HPX_PLAIN_ACTION* can be used to define a plain action (e.g. an action encapsulating a global or free function) based on the given function *func*. It defines the action type *name* representing the given function. This macro additionally registers the newly define action type with HPX.

The parameter *func* is a global or free (non-member) function which should be encapsulated into a plain action. The parameter *name* is the name of the action type defined by this macro.


```

namespace app {
    void some_global_function(double d) {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which
// represents the function 'app::some_global_function'.
HPX_PLAIN_ACTION(app::some_global_function, some_global_action)

```

Example:

Note: The macro *HPX_PLAIN_ACTION* has to be used at global namespace even if the wrapped function is located in some other namespace. The newly defined action type is placed into the global namespace as well.

Note: The macro *HPX_PLAIN_ACTION_ID* can be used with 1, 2, or 3 arguments. The second and third arguments are optional. The default value for the second argument (the typename of the defined action) is derived from the name of the function (as passed as the first argument) by appending ‘_action’. The second argument can be omitted only if the first argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name. The default value for the third argument is *hpx::components::factory_state::check*.

Note: Only one of the forms of this macro *HPX_PLAIN_ACTION* or *HPX_PLAIN_ACTION_ID* should be used for a particular action, never both.

HPX_PLAIN_ACTION_ID(func, name, id)

Defines a plain action type based on the given function *func* and registers it with HPX.

The macro *HPX_PLAIN_ACTION_ID* can be used to define a plain action (e.g. an action encapsulating a global or free function) based on the given function *func*. It defines the action type *actionname* representing the given function.

The parameter *actionid* specifies a unique integer value which will be used to represent the action during serialization.

The parameter *func* is a global or free (non-member) function which should be encapsulated into a plain action. The parameter *name* is the name of the action type defined by this macro.

The second parameter has to be usable as a plain (nonqualified) C++ identifier, it should not contain special characters which cannot be part of a C++ identifier, such as ‘<’, ‘>’, or ‘.’.

```

namespace app {
    void some_global_function(double d) {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which
// represents the function 'app::some_global_function'.

```

(continues on next page)

(continued from previous page)

```
HPX_PLAIN_ACTION_ID(app::some_global_function, some_global_action,  
    some_unique_id);
```

Example:

Note: The macro *HPX_PLAIN_ACTION_ID* has to be used at global namespace even if the wrapped function is located in some other namespace. The newly defined action type is placed into the global namespace as well.

Note: Only one of the forms of this macro *HPX_PLAIN_ACTION* or *HPX_PLAIN_ACTION_ID* should be used for a particular action, never both.

HPX_REGISTER_ACTION_FACTORY_ID(Name, Id)

HPX_REGISTER_ACTION_DECLARATION, HPX_REGISTER_ACTION

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

HPX_DEFINE_COMPONENT_ACTION

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

hpx/actions_base/basic_action_fwd.hpp

Defined in header `hpx/actions_base/basic_action_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

```
        template<typename Component, typename Signature, typename Derived>
```

```
struct basic_action
    #include <basic_action_fwd.hpp>
    Template Parameters
    • Component – component type
    • Signature – return type and arguments
    • Derived – derived action class
```

hpx/actions_base/lambda_to_action.hpp

Defined in header `hpx/actions_base/lambda_to_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions_base/plain_action.hpp

Defined in header `hpx/actions_base/plain_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **actions**

namespace **traits**

hpx/actions_base/actions_base_fwd.hpp

Defined in header `hpx/actions_base/actions_base_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **actions**

hpx/actions_base/reflect_action.hpp

Defined in header `hpx/actions_base/reflect_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Reflection-based action definition for HPX remote operations.

hpx/actions_base/traits/action_remote_result.hpp

Defined in header `hpx/actions_base/traits/action_remote_result.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace traits
```

Typedefs

```
    template<typename Result>
```

```
        using action_remote_result_t = typename action_remote_result<Result>::type
```

```
    template<typename Result>
```

```
        struct action_remote_result : public detail::action_remote_result_customization_point<Result>
```

agas

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/agas/addressing_service.hpp

Defined in header `hpx/agas/addressing_service.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace agas
```

```
        struct addressing_service
```

Public Types

```
        using component_id_type = components::component_type
```

```
        using iterate_names_return_type = std::map<std::string, hpx::id_type>
```

```
        using iterate_types_function_type = hpx::function<void(std::string const&, components::component_type), true>
```

```
        using mutex_type = hpx::spinlock
```

```

using gva_cache_type = hpx::util::cache::lru_cache<gva_cache_key, gva,
hpx::util::cache::statistics::local_full_statistics>

using migrated_objects_table_type = std::set<naming::gid_type>

using refcnt_requests_type = std::map<naming::gid_type, std::int64_t>

using resolved_localities_type = std::map<naming::gid_type, parcelset::endpoints_type>

```

Public Functions

```

HPX_NON_COPYABLE(addressing_service)

explicit addressing_service(util::runtime_configuration const &ini_)

~addressing_service() = default

void bootstrap(parcelset::endpoints_type const &endpoints, util::runtime_configuration &rtcfg)

void initialize(std::uint64_t rts_lva)

void adjust_local_cache_size(std::size_t) const
    Adjust the size of the local AGAS Address resolution cache.

inline state get_status() const

inline void set_status(state new_state)

inline naming::gid_type const &get_local_locality(error_code& = throws) const

void set_local_locality(naming::gid_type const &g)

void register_console(parcelset::endpoints_type const &eps)

inline bool is_bootstrap() const

inline bool is_console() const
    Returns whether this addressing_service represents the console locality.

inline bool is_connecting() const
    Returns whether this addressing_service is connecting to a running application.

bool resolve_locally_known_addresses(naming::gid_type const &id, naming::address &addr)
    const

void register_server_instances()

void garbage_collect_non_blocking(error_code &ec = throws)

void garbage_collect(error_code &ec = throws)

inline server::primary_namespace &get_local_primary_namespace_service()

inline naming::address::address_type get_primary_ns_lva() const

```

```
inline naming::address::address_type get_symbol_ns_lva() const
inline server::component_namespace *get_local_component_namespace_service() const
inline server::locality_namespace *get_local_locality_namespace_service() const
inline server::symbol_namespace &get_local_symbol_namespace_service() const
inline naming::address::address_type get_runtime_support_lva() const

std::uint64_t get_cache_entries(bool) const
std::uint64_t get_cache_hits(bool) const
std::uint64_t get_cache_misses(bool) const
std::uint64_t get_cache_evictions(bool) const
std::uint64_t get_cache_insertions(bool) const
std::uint64_t get_cache_get_entry_count(bool reset) const
std::uint64_t get_cache_insertion_entry_count(bool reset) const
std::uint64_t get_cache_update_entry_count(bool reset) const
std::uint64_t get_cache_erase_entry_count(bool reset) const
std::uint64_t get_cache_get_entry_time(bool reset) const
std::uint64_t get_cache_insertion_entry_time(bool reset) const
std::uint64_t get_cache_update_entry_time(bool reset) const
std::uint64_t get_cache_erase_entry_time(bool reset) const

bool register_locality(parcelset::endpoints_type const &endpoints, naming::gid_type &prefix,
                      std::uint32_t num_threads, error_code &ec = throws)
    Add a locality to the runtime.

parcelset::endpoints_type const &resolve_locality(naming::gid_type const &gid, error_code
                                                &ec = throws)
    Resolve a locality to its prefix.

Returns
    Returns an empty vector if the locality is not registered.

bool has_resolved_locality(naming::gid_type const &gid)

bool unregister_locality(naming::gid_type const &gid, error_code &ec = throws)
    Remove a locality from the runtime.

void remove_resolved_locality(naming::gid_type const &gid)
    remove given locality from locality cache

bool get_console_locality(naming::gid_type &locality, error_code &ec = throws)
    Get locality locality_id of the console locality.
```

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **locality** – [out] The locality_id value uniquely identifying the console locality. This is valid only, if the return value of this function is true.
- **try_cache** – [in] If this is set to true the console is first tried to be found in the local cache. Otherwise this function will always query AGAS, even if the console locality_id is already known locally.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a console locality_id exists and returns *false* otherwise.

```
bool get_localities(std::vector<naming::gid_type> &locality_ids,
                    components::component_type type, error_code &ec = throws) const
```

Query for the locality_ids of all known localities.

This function returns the locality_ids of all localities known to the AGAS server or all localities having a registered factory for a given component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **locality_ids** – [out] The vector will contain the prefixes of all localities registered with the AGAS server. The returned vector holds the prefixes representing the runtime_support components of these localities.
- **type** – [in] The component type will be used to determine the set of prefixes having a registered factory for this component. The default value for this parameter is *components::component_enum_type::invalid*, which will return prefixes of all localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
inline bool get_localities(std::vector<naming::gid_type> &locality_ids, error_code &ec =
                           throws) const
```

```
hpx::future<std::uint32_t> get_num_localities_async(components::component_type type =
                                                    to_int(hpx::components::component_enum_type::invalid))
                                                    const
```

Query for the number of all known localities.

This function returns the number of localities known to the AGAS server or the number of localities having a registered factory for a given component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **type** – [in] The component type will be used to determine the set of prefixes having a registered factory for this component. The default value for this parameter is *components::component_type::invalid*, which will return prefixes of all localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
std::uint32_t get_num_localities(components::component_type type, error_code &ec = throws)
                                const
```

```
inline std::uint32_t get_num_localities(error_code &ec = throws) const  
  
hpx::future<std::uint32_t> get_num_overall_threads_async() const  
  
std::uint32_t get_num_overall_threads(error_code &ec = throws) const  
  
hpx::future<std::vector<std::uint32_t>> get_num_threads_async() const  
  
std::vector<std::uint32_t> get_num_threads(error_code &ec = throws) const  
  
components::component_type get_component_id(std::string const &name, error_code &ec =  
                                              throws) const
```

Return a unique id usable as a component type.

This function returns the component type id associated with the given component name. If this is the first request for this component name a new unique id will be created.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The component name (string) to get the component type for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns the currently associated component type. Any error results in an exception thrown from this function.

```
void iterate_types(iterate_types_function_type const &f, error_code &ec = throws) const  
  
std::string get_component_type_name(components::component_type id, error_code &ec =  
                                     throws) const  
  
inline components::component_type register_factory(naming::gid_type const &locality_id,  
                                                    std::string const &name, error_code &ec  
                                                    = throws) const
```

Register a factory for a specific component type.

This function allows to register a component factory for a given locality and component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **locality_id** – [in] The locality value uniquely identifying the given locality the factory needs to be registered for.
- **name** – [in] The component name (string) to register a factory for the given component type for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns the currently associated component type. Any error results in an exception thrown from this function. The returned component type is the same as if the function *get_component_id* was called using the same component name.

```
components::component_type register_factory(std::uint32_t locality_id, std::string const
&name, error_code &ec = throws) const
```

```
bool get_id_range(std::uint64_t count, naming::gid_type &lower_bound, naming::gid_type
&upper_bound, error_code &ec = throws)
```

Get unique range of freely assignable global ids.

Every locality needs to be able to assign global ids to different components without having to consult the AGAS server for every id to generate. This function can be called to preallocate a range of ids usable for this purpose.

Note: This function assigns a range of global ids usable by the given locality for newly created components. Any of the returned global ids still has to be bound to a local address, either by calling *bind* or *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **l** – [in] The locality the locality id needs to be generated for. Repeating calls using the same locality results in identical *locality_id* values.
- **count** – [in] The number of global ids to be generated.
- **lower_bound** – [out] The lower bound of the assigned id range. The returned value can be used as the first id to assign. This is valid only, if the return value of this function is true.
- **upper_bound** – [out] The upper bound of the assigned id range. The returned value can be used as the last id to assign. This is valid only, if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call. Any error results in an exception thrown from this function.

```
inline bool bind_local(naming::gid_type const &id, naming::address const &addr, error_code
&ec = throws)
```

Bind a global address to a local address.

Every element in the HPX namespace has a unique global address (global id). This global address has to be associated with a concrete local address to be able to address an instance of a component using its global address.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: Binding a gid to a local address sets its global reference count to one.

Parameters

- **id** – [in] The global address which has to be bound to the local address.

- **addr** – [in] The local address to be bound to the global address.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true*, if this global id got associated with an local address. It returns *false* otherwise.

```
inline hpx::future<bool> bind_async(naming::gid_type const &id, naming::address const &addr,  
                                   std::uint32_t locality_id)
```

```
inline hpx::future<bool> bind_async(naming::gid_type const &id, naming::address const &addr,  
                                   naming::gid_type const &locality)
```

```
bool bind_range_local(naming::gid_type const &lower_id, std::uint64_t count, naming::address  
                     const &baseaddr, std::uint64_t offset, error_code &ec = throws)
```

Bind unique range of global ids to given base address.

Every locality needs to be able to bind global ids to different components without having to consult the AGAS server for every id to bind. This function can be called to bind a range of consecutive global ids to a range of consecutive local addresses (separated by a given *offset*).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: Binding a gid to a local address sets its global reference count to one.

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value can be used as the first id to assign.
- **count** – [in] The number of consecutive global ids to bind starting at *lower_id*.
- **baseaddr** – [in] The local address to bind to the global id given by *lower_id*. This is the base address for all additional local addresses to bind to the remaining global ids.
- **offset** – [in] The offset to use to calculate the local addresses to be bound to the range of global ids.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true*, if the given range was successfully bound. It returns *false* otherwise.

```
hpx::future<bool> bind_range_async(naming::gid_type const &lower_id, std::uint64_t count,  
                                   naming::address const &baseaddr, std::uint64_t offset,  
                                   naming::gid_type const &locality)
```

```
inline hpx::future<bool> bind_range_async(naming::gid_type const &lower_id, std::uint64_t  
                                         count, naming::address const &baseaddr,  
                                         std::uint64_t offset, std::uint32_t locality_id)
```

```
inline bool unbind_local(naming::gid_type const &id, error_code &ec = throws)
```

Unbind a global address.

Remove the association of the given global address with any local address, which was bound to this global address. Additionally it returns the local address which was bound at the time of this call.

Note: You can unbind only global ids bound using the function *bind*. Do not use this function to unbind any of the global ids bound using *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **id** – [in] The global address (id) for which the association has to be removed.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the association has been removed, and it returns *false* if no association existed. Any error results in an exception thrown from this function.

```
inline bool unbind_local(naming::gid_type const &id, naming::address &addr, error_code &ec =
                        throws)
```

Unbind a global address.

Remove the association of the given global address with any local address, which was bound to this global address. Additionally it returns the local address which was bound at the time of this call.

Note: You can unbind only global ids bound using the function *bind*. Do not use this function to unbind any of the global ids bound using *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **id** – [in] The global address (id) for which the association has to be removed.
- **addr** – [out] The local address which was associated with the given global address (id). This is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the association has been removed, and it returns *false* if no association existed. Any error results in an exception thrown from this function.

```
inline bool unbind_range_local(naming::gid_type const &lower_id, std::uint64_t count,
                                error_code &ec = throws)
```

Unbind the given range of global ids.

Note: You can unbind only global ids bound using the function *bind_range*. Do not use this function to unbind any of the global ids bound using *bind*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value must be the first id of the range as specified to the corresponding call to *bind_range*.
- **count** – [in] The number of consecutive global ids to unbind starting at *lower_id*. This number must be identical to the number of global ids bound by the corresponding call to *bind_range*.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call. Any error results in an exception thrown from this function.

```
bool unbind_range_local(naming::gid_type const &lower_id, std::uint64_t count,  
                        naming::address &addr, error_code &ec = throws)
```

Unbind the given range of global ids.

Note: You can unbind only global ids bound using the function *bind_range*. Do not use this function to unbind any of the global ids bound using *bind*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value must be the first id of the range as specified to the corresponding call to *bind_range*.
- **count** – [in] The number of consecutive global ids to unbind starting at *lower_id*. This number must be identical to the number of global ids bound by the corresponding call to *bind_range*.
- **addr** – [out] The local address which was associated with the given global address (id). This is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first

time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call.

```
hpx::future<naming::address> unbind_range_async(naming::gid_type const &lower_id,
                                                std::uint64_t count = 1)
```

```
inline bool is_local_address_cached(naming::gid_type const &id, error_code &ec = throws)
```

Test whether the given address refers to a local object.

This function will test whether the given address refers to an object living on the locality of the caller.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The address to test.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the passed address refers to an object which lives on the locality of the caller.

```
bool is_local_address_cached(naming::gid_type const &id, naming::address &addr,
                             error_code &ec = throws)
```

```
bool is_local_address_cached(naming::gid_type const &id, naming::address &addr,
                             std::pair<bool, components::pinned_ptr> &r,
                             hpx::move_only_function<std::pair<bool,
                             components::pinned_ptr>(naming::address const&)> &&f,
                             error_code &ec = throws)
```

```
bool is_local_lva_encoded_address(std::uint64_t msb) const
```

```
inline bool resolve_local(naming::gid_type const &id, naming::address &addr, error_code &ec
                           = throws)
```

Resolve a given global address (*id*) to its associated local address.

This function returns the local address which is currently associated with the given global address (*id*).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The global address (*id*) for which the associated local address should be returned.
- **addr** – [out] The local address which currently is associated with the given global address (*id*), this is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the global address has been resolved successfully (there exists an association to a local address) and the associated local address has been returned. The

function returns *false* if no association exists for the given global address. Any error results in an exception thrown from this function.

```
inline bool resolve_local(hpx::id_type const &id, naming::address &addr, error_code &ec =
    throws)

inline naming::address resolve_local(naming::gid_type const &id, error_code &ec = throws)

inline naming::address resolve_local(hpx::id_type const &id, error_code &ec = throws)

hpx::future_or_value<naming::address> resolve_async(naming::gid_type const &id)

inline hpx::future_or_value<naming::address> resolve_async(hpx::id_type const &id)

hpx::future_or_value<id_type> get_colocation_id_async(hpx::id_type const &id)

bool resolve_full_local(naming::gid_type const &id, naming::address &addr, error_code &ec
    = throws)

inline bool resolve_full_local(hpx::id_type const &id, naming::address &addr, error_code &ec
    = throws)

inline naming::address resolve_full_local(naming::gid_type const &id, error_code &ec =
    throws)

inline naming::address resolve_full_local(hpx::id_type const &id, error_code &ec = throws)

hpx::future_or_value<naming::address> resolve_full_async(naming::gid_type const &id)

inline hpx::future_or_value<naming::address> resolve_full_async(hpx::id_type const &id)

bool resolve_cached(naming::gid_type const &id, naming::address &addr, error_code &ec =
    throws)

inline bool resolve_cached(hpx::id_type const &id, naming::address &addr, error_code &ec =
    throws)

inline bool resolve_local(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
    hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

bool resolve_full_local(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
    hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

bool resolve_cached(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
    hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

hpx::future_or_value<std::int64_t> incref_async(naming::gid_type const &gid, std::int64_t
    credits = 1, hpx::id_type const &keep_alive =
    hpx::invalid_id)
```

Increment the global reference count for the given id.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **gid** – [in] The global address (id) for which the global reference count has to be incremented.

- **credits** – [in] The number of reference counts to add for the given id.
- **keep_alive** – [in] Id to keep alive (if valid)
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

Whether the operation was successful.

```
inline std::int64_t incref(naming::gid_type const &gid, std::int64_t credits = 1, error_code &ec =
    throws)
```

```
void decref(naming::gid_type const &id, std::int64_t credits = 1, error_code &ec = throws)
```

Decrement the global reference count for the given id.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The global address (id) for which the global reference count has to be decremented.
- **t** – [out] If this was the last outstanding global reference for the given gid (the return value of this function is zero), *t* will be set to the component type of the corresponding element. Otherwise *t* will not be modified.
- **credits** – [in] The number of reference counts to add for the given id.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global reference count after the decrement.

```
hpx::future<iterate_names_return_type> iterate_ids(std::string const &pattern) const
```

Invoke the supplied *hpx::function* for every registered global name.

This function iterates over all registered global ids and returns every found entry matching the given name pattern. Any error results in an exception thrown (or reported) from this function.

Parameters

pattern – [in] pattern (possibly using wildcards) to match all existing entries against

```
bool register_name(std::string const &name, naming::gid_type const &id, error_code &ec =
    throws) const
```

Register a global name with a global address (id)

This function registers an association between a global name (string) and a global address (id) usable with one of the functions above (bind, unbind, and resolve).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) to be associated with the global address.
- **id** – [in] The global address (id) to be associated with the global address.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the global name was registered. It returns false if the global name is not registered.

hpx::future<bool> **register_name_async**(*std::string* const &name, *hpx::id_type* const &id) const
bool **register_name**(*std::string* const &name, *hpx::id_type* const &id, *error_code* &ec = *throws*) const

hpx::future<hpx::id_type> **unregister_name_async**(*std::string* const &name) const

Unregister a global name (release any existing association)

This function releases any existing association of the given global name with a global address (id).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) for which any association with a global address (id) has to be released.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if an association of this global name has been released, and it returns *false*, if no association existed. Any error results in an exception thrown from this function.

hpx::id_type **unregister_name**(*std::string* const &name, *error_code* &ec = *throws*) const

hpx::future<hpx::id_type> **resolve_name_async**(*std::string* const &name) const

Query for the global address associated with a given global name.

This function returns the global address associated with the given global name.

This function returns true if it returned global address (id), which is currently associated with the given global name, and it returns false, if currently there is no association for this global name. Any error results in an exception thrown from this function.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) for which the currently associated global address has to be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

[out] The id currently associated with the given global name (valid only if the return value is true).

hpx::id_type **resolve_name**(*std::string* const &name, *error_code* &ec = *throws*) const

future<hpx::id_type> **on_symbol_namespace_event**(*std::string* const &name, bool
call_for_past_events = false) const

Install a listener for a given symbol namespace event.

This function installs a listener for a given symbol namespace event. It returns a future which becomes ready as a result of the listener being triggered.

Note: The only event type which is currently supported is *symbol_ns_bind*, i.e. the listener is triggered whenever a global id is registered with the given name.

Parameters

- **name** – [in] The global name (string) for which the given event should be triggered.
- **evt** – [in] The event for which a listener should be installed.
- **call_for_past_events** – [in, optional] Trigger the listener even if the given event has already happened in the past. The default for this parameter is *false*.

Returns

A future instance encapsulating the global id which is causing the registered listener to be triggered.

```
void update_cache_entry(naming::gid_type const &gid, gva const &gva, error_code &ec =
                        throws)
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
inline void update_cache_entry(naming::gid_type const &gid, naming::address const &addr,
                                std::uint64_t count = 0, std::uint64_t offset = 0, error_code &ec
                                = throws)
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
bool get_cache_entry(naming::gid_type const &gid, gva &gva, naming::gid_type &idbase,
                     error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void remove_cache_entry(naming::gid_type const &id, error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void clear_cache(error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void start_shutdown(error_code &ec = throws)
```

hpx::future<std::pair<hpx::id_type, naming::address>> **begin_migration**(*hpx::id_type* const &id)

start/stop migration of an object

Returns

Current locality and address of the object to migrate

bool **end_migration**(*hpx::id_type* const &id)

std::pair<bool, components::pinned_ptr> **was_object_migrated**(*naming::gid_type* const &gid,
hpx::move_only_function<components::pinned_ptr>
&&f)

Maintain list of migrated objects.

hpx::future<void> **mark_as_migrated**(*naming::gid_type* const &gid,
hpx::move_only_function<std::pair<bool,
hpx::future<void>>()> &&f, bool
expect_to_be_marked_as_migrating)

Mark the given object as being migrated (if the object is unpinned). Delay migration until the object is unpinned otherwise.

void **unmark_as_migrated**(*naming::gid_type* const &gid, *hpx::move_only_function<void()>*
&&f)

Remove the given object from the table of migrated objects.

void **pre_cache_endpoints**(*std::vector<parcelset::endpoints_type>* const&)

Public Members

mutable *hpx::shared_mutex* **gva_cache_mtx_**

std::shared_ptr<gva_cache_type> **gva_cache_**

mutable *mutex_type* **migrated_objects_mtx_** =
mutex_type("addressing_service::migrated_objects_mtx")

migrated_objects_table_type **migrated_objects_table_**

mutable *mutex_type* **console_cache_mtx_** =
mutex_type("addressing_service::console_cache_mtx")

std::uint32_t **console_cache_**

const *std::size_t* **max_refcnt_requests_**

mutex_type **refcnt_requests_mtx_** = *mutex_type*("addressing_service::refcnt_requests_mtx")

std::size_t **refcnt_requests_count_**

bool **enable_refcnt_caching_**

```
std::shared_ptr<refcnt_requests_type> refcnt_requests_
```

```
const service_mode service_type
```

```
const runtime_mode runtime_type
```

```
const bool caching_
```

```
const bool range_caching_
```

```
const threads::thread_priority action_priority_
```

```
std::uint64_t rts_lva_
```

```
std::unique_ptr<component_namespace> component_ns_
```

```
std::unique_ptr<locality_namespace> locality_ns_
```

```
symbol_namespace symbol_ns_
```

```
primary_namespace primary_ns_
```

```
std::atomic<hpx::state> state_
```

```
naming::gid_type locality_
```

```
mutable hpx::shared_mutex resolved_localities_mtx_
```

```
resolved_localities_type resolved_localities_
```

Public Static Functions

```
static std::int64_t synchronize_with_async_incref(std::int64_t old_credit, hpx::id_type const  
                                                &id, std::int64_t compensated_credit)
```

Protected Functions

```
void launch_bootstrap(parcelset::endpoints_type const &endpoints, util::runtime_configuration  
                      &rtcfg)
```

```
naming::address resolve_full_postproc(naming::gid_type const &id,  
                                         primary_namespace::resolved_type const&)
```

```
bool bind_postproc(naming::gid_type const &id, gva const &g, future<bool> f)
```

```
bool was_object_migrated_locked(naming::gid_type const &id)
```

Maintain list of migrated objects.

Private Functions

```
void send_refcnt_requests(std::unique_lock<mutex_type> &l, error_code &ec = throws)
```

Assumes that *refcnt_requests_mtx_* is locked.

```
void send_refcnt_requests_non_blocking(std::unique_lock<mutex_type> &l, error_code  
                                     &ec)
```

Assumes that *refcnt_requests_mtx_* is locked.

```
std::vector<hpx::future<std::vector<std::int64_t>>> send_refcnt_requests_async(std::unique_lock<mutex_type>  
                                                                              &l)
```

Assumes that *refcnt_requests_mtx_* is locked.

```
void send_refcnt_requests_sync(std::unique_lock<mutex_type> &l, error_code &ec)
```

Assumes that *refcnt_requests_mtx_* is locked.

agas_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/agas_base/server/primary_namespace.hpp

Defined in header `hpx/agas_base/server/primary_namespace.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Variables

```
HPX_ACTION_USES_MEDIUM_STACK(hpx::agas::server::primary_namespace::allocate_action) HPX_REGISTER_ACTION  
hpx::naming::address > std_pair_address_id_type
```

namespace **hpx**

namespace **agas**

Functions

naming::gid_type **bootstrap_primary_namespace_gid()**

hpx::id_type **bootstrap_primary_namespace_id()**

namespace **server**

AGAS's primary namespace maps 128-bit global identifiers (GIDs) to resolved addresses.

The following is the canonical description of the partitioning of AGAS's primary namespace.

-----MSB----- -----LSB----- BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB prefix RC ----identifier----	
MSB	- Most significant bits (bit 64 to bit 127)
LSB	- Least significant bits (bit 0 to bit 63)
prefix	- Highest 32 bits (bit 96 to bit 127) of the MSB. Each locality is assigned a prefix. This creates a 96-bit address space for each locality.
RC	- Bit 88 to bit 92 of the MSB. This is the log2 of the number of reference counting credits on the GID. Bit 93 is used by the locking scheme for <i>gid_types</i> . Bit 94 is a flag which is set if the credit value is valid. Bit 95 is a flag that is set if a GID's credit count is ever split (e.g. if the GID is ever passed to another locality).
identifier	- Bit 87 marks the gid such that it will not be stored in any of the AGAS caches. This is used mainly for ids which represent 'one-shot' objects (like promises). - Bit 64 to bit 86 of the MSB, and the entire LSB. The content of these bits depends on the component type of the underlying object. For all user-defined components, these bits contain a unique 88-bit number which is assigned sequentially for each locality. For <code>\a hpx#components#component_enum_type#runtime_support</code> the high 24 bits are zeroed and the low 64 bits hold the LVA of the component.

The following address ranges are reserved. Some are either explicitly or implicitly protected by AGAS. The letter x represents a single-byte wild card.

```

00000000xxxxxxxxxxxxxxxxxxxxxxxx
    Historically unused address space reserved for future use.
xxxxxxxxxxx0000xxxxxxxxxxxxxxxx
    Address space for LVA-encoded GIDs.
00000001xxxxxxxxxxxxxxxxxxxxxxxx
    Prefix of the bootstrap AGAS locality.
00000001000000010000000000000001
    Address of the primary_namespace component on the bootstrap AGAS
    locality.
00000001000000010000000000000002

```

(continues on next page)

(continued from previous page)

```
Address of the component_namespace component on the bootstrap AGAS
locality.
0000000010000000010000000000000003
Address of the symbol_namespace component on the bootstrap AGAS
locality.
0000000010000000010000000000000004
Address of the locality_namespace component on the bootstrap AGAS
locality.
```

Note: The layout of the address space is implementation defined, and subject to change. Never write application code that relies on the internal layout of GIDs. AGAS only guarantees that all assigned GIDs will be unique.

Variables

```
constexpr char const *const primary_namespace_service_name = "primary/"
```

```
struct primary_namespace : public components::fixed_component_base<primary_namespace>
```

Public Types

```
using mutex_type = hpx::spinlock
```

```
using base_type = components::fixed_component_base<primary_namespace>
```

```
using component_type = std::int32_t
```

```
using gva_table_data_type = std::pair<gva, naming::gid_type>
```

```
using gva_table_type = std::map<naming::gid_type, gva_table_data_type>
```

```
using refcnt_table_type = std::map<naming::gid_type, std::int64_t>
```

```
using resolved_type = hpx::tuple<naming::gid_type, gva, naming::gid_type>
```

Public Functions

```

inline mutex_type &mutex()

void wait_for_migration_locked(std::unique_lock<mutex_type> &l, naming::gid_type
                               const &id, error_code &ec)

inline primary_namespace()

void finalize() const

inline void set_local_locality(naming::gid_type const &g)

void register_server_instance(char const *servicename, std::uint32_t locality_id =
                               naming::invalid_locality_id, error_code &ec = throws)

void unregister_server_instance(error_code &ec = throws) const

bool bind_gid(gva const &g, naming::gid_type id, naming::gid_type const &locality)

std::pair<hpx::id_type, naming::address> begin_migration(naming::gid_type id)

bool end_migration(naming::gid_type const &id)

resolved_type resolve_gid(naming::gid_type const &id)

hpx::id_type colocate(naming::gid_type const &id)

naming::address unbind_gid(std::uint64_t count, naming::gid_type id)

std::int64_t increment_credit(std::int64_t credits, naming::gid_type lower,
                               naming::gid_type upper)

std::vector<std::int64_t> decrement_credit(std::vector<hpx::tuple<std::int64_t,
                                           naming::gid_type, naming::gid_type>> const
                                           &requests)

std::pair<naming::gid_type, naming::gid_type> allocate(std::uint64_t count)

resolved_type resolve_gid_locked(std::unique_lock<mutex_type> &l, naming::gid_type
                                   const &gid, error_code &ec)

```

Public Members

```

counter_data counter_data_

```

Private Types

```

using migration_table_type = std::map<naming::gid_type, hpx::tuple<bool, std::size_t,
                               lcos::local::detail::condition_variable>>

using free_entry_allocator_type = util::internal_allocator<free_entry>

using free_entry_list_type = std::list<free_entry, free_entry_allocator_type>

```

Private Functions

```
resolved_type resolve_gid_locked_non_local(std::unique_lock<mutex_type> &l,  
                                             naming::gid_type const &gid, error_code  
                                             &ec)  
  
void increment(naming::gid_type const &lower, naming::gid_type const &upper, std::int64_t  
               const &credits, error_code &ec)  
  
void resolve_free_list(std::unique_lock<mutex_type> &l,  
                       std::list<refcnt_table_type::iterator> const &free_list,  
                       free_entry_list_type &free_entry_list, naming::gid_type const  
                       &lower, naming::gid_type const &upper, error_code &ec)  
  
void decrement_sweep(free_entry_list_type &free_list, naming::gid_type const &lower,  
                     naming::gid_type const &upper, std::int64_t credits, error_code &ec)  
  
void free_components_sync(free_entry_list_type const &free_list, naming::gid_type const  
                           &lower, naming::gid_type const &upper, error_code &ec)  
                           const
```

Private Members

```
mutex_type mutex_ = mutex_type("primary_namespace")  
  
gva_table_type gvas_  
  
refcnt_table_type refcnts_  
  
std::string instance_name_  
  
naming::gid_type next_id_  
  
naming::gid_type locality_  
  
migration_table_type migrating_objects_  
  
struct counter_data
```

Public Functions

```
counter_data(counter_data const&) = delete  
  
counter_data(counter_data&&) = delete  
  
counter_data &operator=(counter_data const&) = delete  
  
counter_data &operator=(counter_data&&) = delete
```



```

counter_data() = default

std::int64_t get_bind_gid_count(bool)

std::int64_t get_resolve_gid_count(bool)

std::int64_t get_unbind_gid_count(bool)

std::int64_t get_increment_credit_count(bool)

std::int64_t get_decrement_credit_count(bool)

std::int64_t get_allocate_count(bool)

std::int64_t get_begin_migration_count(bool)

std::int64_t get_end_migration_count(bool)

std::int64_t get_overall_count(bool)

std::int64_t get_bind_gid_time(bool)

std::int64_t get_resolve_gid_time(bool)

std::int64_t get_unbind_gid_time(bool)

std::int64_t get_increment_credit_time(bool)

std::int64_t get_decrement_credit_time(bool)

std::int64_t get_allocate_time(bool)

std::int64_t get_begin_migration_time(bool)

std::int64_t get_end_migration_time(bool)

std::int64_t get_overall_time(bool)

void increment_bind_gid_count()

void increment_resolve_gid_count()

void increment_unbind_gid_count()

void increment_increment_credit_count()

void increment_decrement_credit_count()

void increment_allocate_count()

void increment_begin_migration_count()

void increment_end_migration_count()

void enable_all()

```

Public Members

api_counter_data **bind_gid_**

api_counter_data **resolve_gid_**

api_counter_data **unbind_gid_**

api_counter_data **increment_credit_**

api_counter_data **decrement_credit_**

api_counter_data **allocate_**

api_counter_data **begin_migration_**

api_counter_data **end_migration_**

struct **api_counter_data**

Public Members

std::atomic<std::int64_t> **count_** = 0

std::atomic<std::int64_t> **time_** = 0

bool **enabled_** = false

struct **free_entry**

Public Functions

inline **free_entry**(*agas::gva* const &gva, *naming::gid_type* const &gid, *naming::gid_type* const &loc)

Public Members

agas::gva **gva_**

naming::gid_type **gid_**

naming::gid_type **locality_**

async_colocated

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::get_colocation_id

Defined in header `hpx/runtime.hpp`⁸¹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

hpx::id_type **get_colocation_id**(*launch::sync_policy*, *hpx::id_type* const &id, *error_code* &ec = *throws*)

Return the id of the locality where the object referenced by the given id is currently located on.

The function *hpx::get_colocation_id()* returns the id of the locality where the given object is currently located.

See also:

hpx::get_colocation_id()

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The id of the object to locate.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

⁸¹¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

```
hpx::future<hpx::id_type> get_colocation_id(hpx::id_type const &id)
```

Asynchronously return the id of the locality where the object referenced by the given id is currently located on.

See also:

```
hpx::get_colocation_id(launch::sync_policy)
```

Parameters

id – [in] The id of the object to locate.

async_distributed

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/async_distributed/packaged_action.hpp

Defined in header `hpx/async_distributed/packaged_action.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **lcos**

```
template<typename Action, typename Result, bool DirectExecute>
```

```
class packaged_action
```

#include <packaged_action.hpp> A *packaged_action* can be used by a single *thread* to invoke a (remote) action and wait for the result. The result is expected to be sent back to the *packaged_action* using the LCO's *set_event* action

A *packaged_action* is one of the simplest synchronization primitives provided by HPX. It allows to synchronize on an eager evaluated remote operation returning a result of the type *Result*.

Note: The action executed using the *packaged_action* as a continuation must return a value of a type convertible to the type as specified by the template parameter *Result*.

Template Parameters

- **Action** – The template parameter *Action* defines the action to be executed by this *packaged_action* instance. The arguments *arg0*,... *argN* are used as parameters for this action.
- **Result** – The template parameter *Result* defines the type this *packaged_action* is expected to return from its associated future *packaged_action::get_future*.
- **DirectExecute** – The template parameter *DirectExecute* is an optimization aid allowing to execute the action directly if the target is local (without spawning a new thread for this). This template does not have to be supplied explicitly as it is derived from the template parameter *Action*.

```
template<typename Action, typename Result>
```

```
class packaged_action<Action, Result, false> : public hpx::distributed::promise<Result,
hpx::traits::extract_action<Action>::remote_result_type>
```

Subclassed by *hpx::lcos::packaged_action*< Action, Result, true >

Public Functions

```
inline packaged_action()
```

```
template<typename Allocator>
```

```
inline packaged_action(std::allocator_arg_t, Allocator const &alloc)
```

```
template<typename ...Ts>
```

```
inline void post(hpx::id_type const &id, Ts&&... vs)
```

```
template<typename ...Ts>
```

```
inline void post(naming::address &&addr, hpx::id_type const &id, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_cb(hpx::id_type const &id, Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_cb(naming::address &&addr, hpx::id_type const &id, Callback &&cb, Ts&&...
vs)
```

```
template<typename ...Ts>
```

```
inline void post_p(hpx::id_type const &id, hpx::launch policy, Ts&&... vs)
```

```
template<typename ...Ts>
```

```
inline void post_p(naming::address &&addr, hpx::id_type const &id, hpx::launch policy, Ts&&...
vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_p_cb(hpx::id_type const &id, hpx::launch policy, Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_p_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,
Callback &&cb, Ts&&... vs)
```

```
template<typename ...Ts>
```

```
inline void post_deferred(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,
Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_deferred_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch
policy, Callback &&cb, Ts&&... vs)
```

Protected Types

```
using action_type = hpx::traits::extract_action<Action>::type
```

```
using remote_result_type = action_type::remote_result_type
```

```
using base_type = hpx::distributed::promise<Result, remote_result_type>
```

Protected Functions

```
template<typename ...Ts>  
inline void do_post(naming::address &&addr, hpx::id_type const &id, hpx::launch policy, Ts&&...  
                   vs)
```

```
template<typename ...Ts>  
inline void do_post(hpx::id_type const &id, hpx::launch policy, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>  
inline void do_post_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,  
                      Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>  
inline void do_post_cb(hpx::id_type const &id, hpx::launch policy, Callback &&cb, Ts&&... vs)
```

```
template<typename Action, typename Result>
```

```
class packaged_action<Action, Result, true> : public hpx::lcos::packaged_action<Action, Result,  
false>
```

Public Functions

```
inline packaged_action()
```

Construct a (non-functional) instance of a `packaged_action`. To use this instance its member function `post` needs to be directly called.

```
template<typename Allocator>  
inline packaged_action(std::allocator_arg_t, Allocator const &alloc)
```

```
template<typename ...Ts>  
inline void post(hpx::id_type const &id, Ts&&... vs)
```

```
template<typename ...Ts>  
inline void post(naming::address &&addr, hpx::id_type const &id, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>  
inline void post_cb(hpx::id_type const &id, Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>  
inline void post_cb(naming::address &&addr, hpx::id_type const &id, Callback &&cb, Ts&&...  
                   vs)
```

Private Types

using **action_type** = *packaged_action*<*Action*, *Result*, false>::action_type

hpx/async_distributed/trigger_lco.hpp

Defined in header `hpx/async_distributed/trigger_lco.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

hpx/async_distributed/base_lco_with_value.hpp

Defined in header `hpx/async_distributed/base_lco_with_value.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

namespace **lcos**

template<typename **Result**, typename **RemoteResult**, typename **ComponentTag**>

class **base_lco_with_value** : public *hpx::lcos::base_lco*, public *ComponentTag*

#include <*base_lco_with_value.hpp*> The *base_lco_with_value* class is the common base class for all LCO's synchronizing on a value. The *RemoteResult* template argument should be set to the type of the argument expected for the *set_value* action.

Template Parameters

- **RemoteResult** – The type of the result value to be carried back to the LCO instance.
- **ComponentTag** – The tag type representing the type of the component (either *component_tag* or *managed_component_tag*).

Public Types

using **wrapping_type** = detail::base_lco_wrapping_type<*ComponentTag*, *base_lco_with_value*>::type

using **base_type_holder** = *base_lco_with_value*

Public Functions

inline void **set_value_nonvirt**(*RemoteResult* &&result)

The *function* `set_value_nonvirt` is called whenever a *set_value_action* is applied on this LCO instance. This function just forwards to the virtual function *set_value*, which is overloaded by the derived concrete LCO.

Parameters

result – [in] The result value to be transferred from the remote operation back to this LCO instance.

inline *Result* **get_value_nonvirt**()

The *function* `get_result_nonvirt` is called whenever a *get_result_action* is applied on this LCO instance. This function just forwards to the virtual function *get_result*, which is overloaded by the derived concrete LCO.

HPX_DEFINE_COMPONENT_DIRECT_ACTION (*base_lco_with_value*, *set_value_nonvirt*, *set_value_action*) **HPX_DEFINE_COMPONENT_DIRECT_ACTION**(*base_lco_with_value*

The *set_value_action* may be used to trigger any LCO instances while carrying an additional parameter of any type.

RemoteResult is taken by rvalue ref. This allows for perfect forwarding. When the action thread function is created, the values are moved into the called function. If we took it by const lvalue reference, we would disable the possibility to further move the result to the designated destination.

Parameters

RemoteResult – [in] The type of the result to be transferred back to this LCO instance.

The *get_value_action* may be used to query the value this LCO instance exposes as its ‘result’ value.

Public Members

get_value_nonvirt

Public Static Functions

static inline *components::component_type* **get_component_type**() noexcept

static inline void **set_component_type**(*components::component_type* type)

Protected Types

using **result_type** = *std::conditional_t*<*std::is_void_v*<*Result*>, *util::unused_type*, *Result*>

Protected Functions

~base_lco_with_value() override = default

Destructor, needs to be virtual to allow for clean destruction of derived objects

inline virtual void **set_event()** override

virtual void **set_value**(*RemoteResult* &&result) = 0

virtual *result_type* **get_value()** = 0

inline virtual *result_type* **get_value**(*error_code*&)

template<typename **ComponentTag**>

class **base_lco_with_value**<void, void, *ComponentTag*> : public *hpx::lcos::base_lco*, public *ComponentTag*

#include <base_lco_with_value.hpp> The *base_lco*<void> specialization is used whenever the *set_event* action for a particular LCO doesn't carry any argument.

Template Parameters

void – This specialization expects no result value and is almost completely equivalent to the plain *base_lco*.

Public Types

using **wrapping_type** = detail::base_lco_wrapping_type<*ComponentTag*, *base_lco_with_value*>::type

using **base_type_holder** = *base_lco_with_value*

using **set_value_action** = *base_lco*::set_event_action

Public Functions

inline void **get_value()**

Protected Functions

~base_lco_with_value() override = default

Destructor, needs to be virtual to allow for clean destruction of derived objects

namespace **traits**

hpx/async_distributed/trigger_lco_fwd.hpp

Defined in header `hpx/async_distributed/trigger_lco_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

void **trigger_lco_event**(*hpx::id_type* id, *naming::address* &&addr, bool move_credits = true)

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

inline void **trigger_lco_event**(*hpx::id_type* const &id, bool move_credits = true)

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

void **trigger_lco_event**(*hpx::id_type* id, *naming::address* &&addr, *hpx::id_type* const &cont, bool move_credits = true)

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

inline void **trigger_lco_event**(*hpx::id_type* const &id, *hpx::id_type* const &cont, bool move_credits = true)

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(hpx::id_type id, naming::address &&addr, Result &&t, bool move_credits = true)

Set the result value for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **t** – [in] This is the value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(hpx::id_type const &id, Result &&t, bool move_credits = true)

Set the result value for the (managed) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value_unmanaged**(hpx::id_type const &id, Result &&t, bool move_credits = true)

Set the result value for the (unmanaged) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(hpx::id_type id, naming::address &&addr, Result &&t, hpx::id_type const &cont, bool move_credits = true)

Set the result value for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(hpx::id_type const &id, Result &&t, hpx::id_type const &cont, bool move_credits = true)

Set the result value for the (managed) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
template<typename Result>  
void set_lco_value_unmanaged(hpx::id_type const &id, Result &&t, hpx::id_type const &cont, bool  
    move_credits = true)
```

Set the result value for the (unmanaged) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
void set_lco_error(hpx::id_type id, naming::address &&addr, std::exception_ptr const &e, bool  
    move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
void set_lco_error(hpx::id_type id, naming::address &&addr, std::exception_ptr &&e, bool move_credits  
    = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr const &e, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr &&e, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
void set_lco_error(hpx::id_type id, naming::address &&addr, std::exception_ptr const &e, hpx::id_type const &cont, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
void set_lco_error(hpx::id_type id, naming::address &&addr, std::exception_ptr &&e, hpx::id_type const &cont, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr const &e, hpx::id_type const &cont, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr &&e, hpx::id_type const &cont, bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

hpx::sync (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Action, typename Target, typename ...Ts>  
decltype(auto) sync(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::sync` can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID. The action executes synchronously.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

`hpx::future` referring to the shared state created by this call to `hpx::sync`

hpx/async_distributed/base_lco.hpp

Defined in header `hpx/async_distributed/base_lco.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<>
```

```
struct get_lva<hpx::lcos::base_lco>
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco *call(hpx::naming::address_type lva) noexcept
template<>
struct get_lva<hpx::lcos::base_lco const>
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco const *call(hpx::naming::address_type lva) noexcept

namespace hpx
```

```
template<> base_lco >
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco *call(hpx::naming::address_type lva) noexcept

template<> base_lco const >
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco const *call(hpx::naming::address_type lva) noexcept

namespace lcos
```

```
class base_lco
```

#include <base_lco.hpp> The `base_lco` class is the common base class for all LCO's implementing a simple `set_event` action

Subclassed by `hpx::lcos::base_lco_with_value< Result, RemoteResult, ComponentTag >`, `hpx::lcos::base_lco_with_value< void, void, ComponentTag >`

Public Types

```
typedef components::managed_component<base_lco> wrapping_type
```

```
typedef base_lco base_type_holder
```

Public Functions

virtual void **set_event**() = 0

virtual void **set_exception**(std::exception_ptr const &e)

virtual void **connect**(hpx::id_type const&)

virtual void **disconnect**(hpx::id_type const&)

virtual **~base_lco**()

Destructor, needs to be virtual to allow for clean destruction of derived objects

void **set_event_nonvirt**()

The *function* `set_event_nonvirt` is called whenever a *set_event_action* is applied on a instance of a LCO. This function just forwards to the virtual function *set_event*, which is overloaded by the derived concrete LCO.

void **set_exception_nonvirt**(std::exception_ptr const &e)

The *function* `set_exception` is called whenever a *set_exception_action* is applied on a instance of a LCO. This function just forwards to the virtual function *set_exception*, which is overloaded by the derived concrete LCO.

Parameters

e – [in] The exception encapsulating the error to report to this LCO instance.

void **connect_nonvirt**(hpx::id_type const &id)

The *function* `connect_nonvirt` is called whenever a *connect_action* is applied on a instance of a LCO. This function just forwards to the virtual function *connect*, which is overloaded by the derived concrete LCO.

Parameters

id – [in] target id

void **disconnect_nonvirt**(hpx::id_type const &id)

The *function* `disconnect_nonvirt` is called whenever a *disconnect_action* is applied on a instance of a LCO. This function just forwards to the virtual function *disconnect*, which is overloaded by the derived concrete LCO.

Parameters

id – [in] target id

**HPX_DEFINE_COMPONENT_DIRECT_ACTION (base_lco, set_event_nonvirt,
set_event_action) HPX_DEFINE_COMPONENT_DIRECT_ACTION(base_lco**

Each of the exposed functions needs to be encapsulated into an action type, allowing to generate all required boilerplate code for threads, serialization, etc.

The *set_event_action* may be used to unconditionally trigger any LCO instances, it carries no additional parameters. The *set_exception_action* may be used to transfer arbitrary error information from the remote site to the LCO instance specified as a continuation. This action carries 2 parameters:

Parameters

std::exception_ptr – [in] The exception encapsulating the error to report to this LCO instance.

**set_exception_action HPX_DEFINE_COMPONENT_DIRECT_ACTION (base_lco,
connect_nonvirt, connect_action) HPX_DEFINE_COMPONENT_DIRECT_ACTION(base_lco**

The *connect_action* may be used to.

The `set_exception_action` may be used to

Public Members

`set_exception_nonvirt`

`set_exception_action` `disconnect_nonvirt`

Public Static Functions

static `components::component_type` `get_component_type()` noexcept

static void `set_component_type(components::component_type type)`

`hpx::distributed::promise`

Defined in header `hpx/future.hpp`⁸¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace `hpx`

namespace `distributed`

template<typename `Result`, typename `RemoteResult`>

class `promise`

#include <promise.hpp> A promise can be used by a single *thread* to invoke a (remote) action and wait for the result. The result is expected to be sent back to the promise using the LCO's `set_event` action

A promise is one of the simplest synchronization primitives provided by HPX. It allows to synchronize on a eager evaluated remote operation returning a result of the type *Result*. The *promise* allows to synchronize exactly one *thread* (the one passed during construction time).

```
// Create the promise (the expected result is a id_type)
hpx::distributed::promise<hpx::id_type> p;

// Get the associated future
future<hpx::id_type> f = p.get_future();

// initiate the action supplying the promise as a
// continuation
apply<some_action>(new continuation(p.get_id()), ...);

// Wait for the result to be returned, yielding control
// in the meantime.
hpx::id_type result = f.get();
// ...
```

⁸¹² <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/future.hpp>

Note: The action executed by the promise must return a value of a type convertible to the type as specified by the template parameter *RemoteResult*

Template Parameters

- **Result** – The template parameter *Result* defines the type this promise is expected to return from *promise::get*.
- **RemoteResult** – The template parameter *RemoteResult* defines the type this promise is expected to receive from the remote action.

namespace **lcos**

```
template<typename Result, typename RemoteResult, typename ComponentTag>
class base_lco_with_value : public hpx::lcos::base_lco, public ComponentTag
    #include <base_lco_with_value.hpp>
template<typename Action, typename Result, bool DirectExecute>
class packaged_action
    #include <packaged_action.hpp>
```

namespace **lcos**

hpx/async_distributed/transfer_continuation_action.hpp

Defined in header *hpx/async_distributed/transfer_continuation_action.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::async (distributed)

Defined in header *hpx/async.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Action, typename Target, typename ...Ts>
auto async(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of **hpx::async** can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID. The action executes asynchronously.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

`hpx::future` referring to the shared state created by this call to `hpx::async`

hpx::dataflow (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Action, typename Target, typename ...Ts>
decltype(auto) dataflow(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::dataflow` can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID. The action executes asynchronously.

Note: Its behavior is similar to `hpx::async` with the exception that if one of the arguments is a future, then `hpx::dataflow` will wait for the future to be ready to launch the thread.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

`hpx::future` referring to the shared state created by this call to `hpx::dataflow`

hpx::post (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Action, typename Target, typename ...Ts>  
bool post(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::post` can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

`true` if the action was successfully posted, `false` otherwise.

hpx/async_distributed/promise.hpp

Defined in header `hpx/async_distributed/promise.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<>
```

```
class promise<void, hpx::util::unused_type> : public lcos::detail::promise_base<void, hpx::util::unused_type,  
lcos::detail::promise_data<void>>
```

Public Functions

promise() = default

constructs a promise object and a shared state.

```
template<typename Allocator>  
inline promise(std::allocator_arg_t, Allocator const &a)
```

constructs a promise object and a shared state. The constructor uses the allocator *to* allocate the memory for the shared state.

promise(*promise* &&*other*) noexcept = default

constructs a new promise object and transfers ownership of the shared state of *other* (if any) to the newly-constructed object.

Post

other has no shared state.

~promise() = default

Abandons any shared state.

promise &**operator**=(*promise* &&*other*) noexcept = default

Abandons any shared state (30.6.4) and then as if `promise(HPX_MOVE(other)).swap(*this)`.

Returns

*this.

inline void **swap**(*promise* &*other*) noexcept

Exchanges the shared state of *this and *other*.

Post

*this has the shared state (if any) that *other* had prior to the call to swap. *other* has the shared state (if any) that *this had prior to the call to swap.

inline void **set_value**()

atomically stores the value *r* in the shared state and makes that state ready (30.6.4).

Throws

future_error – if its shared state already has a stored value. if shared state has no stored value exception is raised. **promise_already_satisfied** if its shared state already has a stored value or exception. **no_state** if *this has no shared state.

Private Types

```
using base_type = lcos::detail::promise_base<void, hpx::util::unused_type,
lcos::detail::promise_data<void>>
```

```
template<typename R, typename Allocator>
```

```
struct uses_allocator<hpx::distributed::promise<R>, Allocator> : public true_type
```

```
#include <promise.hpp> Requires: Allocator shall be an allocator (17.6.3.5)
```

```
namespace hpx
```

```
namespace distributed
```

Functions

```
template<typename Result, typename RemoteResult>
void swap(promise<Result, RemoteResult> &x, promise<Result, RemoteResult> &y) noexcept

template<typename Result, typename RemoteResult>

class promise
    #include <promise.hpp>

template<> unused_type > : public lcos::detail::promise_base< void,
hpx::util::unused_type, lcos::detail::promise_data< void > >
```

Public Functions

promise() = default

constructs a promise object and a shared state.

```
template<typename Allocator>
inline promise(std::allocator_arg_t, Allocator const &a)
```

constructs a promise object and a shared state. The constructor uses the allocator *to* allocate the memory for the shared state.

promise(*promise &&other*) noexcept = default

constructs a new promise object and transfers ownership of the shared state of other (if any) to the newly- constructed object.

Post

other has no shared state.

~promise() = default

Abandons any shared state.

promise &operator=(*promise &&other*) noexcept = default

Abandons any shared state (30.6.4) and then as if `promise(HPX_MOVE(other)).swap(*this)`.

Returns

*this.

inline void **swap**(*promise &other*) noexcept

Exchanges the shared state of *this and other.

Post

*this has the shared state (if any) that other had prior to the call to swap. other has the shared state (if any) that *this had prior to the call to swap.

inline void **set_value**()

atomically stores the value r in the shared state and makes that state ready (30.6.4).

Throws

future_error – if its shared state already has a stored value. if shared state has no stored value exception is raised. **promise_already_satisfied** if its shared state already has a stored value or exception. **no_state** if *this has no shared state.

Private Types

```
using base_type = lcos::detail::promise_base<void, hpx::util::unused_type,  
lcos::detail::promise_data<void>>
```

namespace **std**

```
template<typename R, typename Allocator> promise< R >,  
Allocator > : public true_type  
    #include <promise.hpp> Requires: Allocator shall be an allocator (17.6.3.5)
```

checkpoint

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/checkpoint/checkpoint.hpp

Defined in header `hpx/checkpoint/checkpoint.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

This header defines the `save_checkpoint` and `restore_checkpoint` functions. These functions are designed to help HPX application developer's checkpoint their applications. `Save_checkpoint` serializes one or more objects and saves them as a byte stream. `Restore_checkpoint` converts the byte stream back into instances of the objects.

namespace **hpx**

namespace **util**

Functions

```
std::ostream &operator<<(std::ostream &ost, checkpoint const &ckp)  
    Operator<< Overload
```

This overload is the main way to write data from a checkpoint to an object such as a file. Inside the function, the size of the checkpoint will be written to the stream before the checkpoint's data. The `operator>>` overload uses this to read the correct number of bytes. Be mindful of this additional write and read when you use different facilities to write out or read in data to a checkpoint!

Parameters

- **ost** – Output stream to write to.
- **ckp** – Checkpoint to copy from.

Returns

`Operator<<` returns the ostream object.

```
std::istream &operator>>(std::istream &ist, checkpoint &ckp)  
    Operator>> Overload
```

This overload is the main way to read in data from an object such as a file to a checkpoint. It is important to note that inside the function, the first variable to be read is the size of the checkpoint. This size variable is written to the stream before the checkpoint's data in the operator<< overload. Be mindful of this additional read and write when you use different facilities to read in or write out data from a checkpoint!

Parameters

- **ist** – Input stream to write from.
- **ckp** – Checkpoint to write to.

Returns

Operator>> returns the ostream object.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> save_checkpoint(T &&t, Ts&&... ts)
    Save_checkpoint
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **U** – This parameter is used to make sure that T is not a launch policy or a checkpoint. This forces the compiler to choose the correct overload.

Parameters

- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass hpx::launch::sync as the first argument. In this case save_checkpoint will simply return a checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> save_checkpoint(checkpoint &&c, T &&t, Ts&&... ts)
    Save_checkpoint - Take a pre-initialized checkpoint
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.

Parameters

- **c** – Takes a pre-initialized checkpoint to copy data into.

- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass `hpx::launch::sync` as the first argument. In this case `save_checkpoint` will simply return a checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> save_checkpoint(hpx::launch p, T &&t, Ts&&... ts)
Save_checkpoint - Policy overload
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a `shared_ptr` to the component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. `async`, `sync`, etc.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass `hpx::launch::sync` as the first argument. In this case `save_checkpoint` will simply return a checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> save_checkpoint(hpx::launch p, checkpoint &&c, T &&t, Ts&&... ts)
Save_checkpoint - Policy overload & pre-initialized checkpoint
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a `shared_ptr` to the component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. `async`, `sync`, etc.
- **c** – Takes a pre-initialized checkpoint to copy data into.
- **t** – A container to restore.

- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass `hpx::launch::sync` as the first argument. In this case `save_checkpoint` will simply return a checkpoint.

```
template<typename T, typename ...Ts>
checkpoint save_checkpoint(hpx::launch::sync_policy sync_p, T &&t, Ts&&... ts)
    Save_checkpoint - Sync_policy overload
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a `shared_ptr` to the component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **U** – This parameter is used to make sure that **T** is not a checkpoint. This forces the compiler to choose the correct overload.

Parameters

- **sync_p** – `hpx::launch::sync_policy`
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint which is passed `hpx::launch::sync_policy` will return a checkpoint which contains the serialized values checkpoint.

```
template<typename T, typename ...Ts>
checkpoint save_checkpoint(hpx::launch::sync_policy sync_p, checkpoint &&c, T &&t, Ts&&... ts)
    Save_checkpoint - Sync_policy overload & pre-init. checkpoint
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a `shared_ptr` to the component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.

Parameters

- **sync_p** – `hpx::launch::sync_policy`
- **c** – Takes a pre-initialized checkpoint to copy data into.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint which is passed `hpx::launch::sync_policy` will return a checkpoint which contains the serialized values checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> prepare_checkpoint(T const &t, Ts const&... ts)
prepare_checkpoint
```

`prepare_checkpoint` takes the containers which have to be filled from the byte stream by a subsequent `restore_checkpoint` invocation. `prepare_checkpoint` will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

`prepare_checkpoint` returns a properly resized checkpoint object that can be used for a subsequent `restore_checkpoint` operation.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> prepare_checkpoint(checkpoint &&c, T const &t, Ts const&... ts)
prepare_checkpoint
```

`prepare_checkpoint` takes the containers which have to be filled from the byte stream by a subsequent `restore_checkpoint` invocation. `prepare_checkpoint` will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – Takes a pre-initialized checkpoint to prepare
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

`prepare_checkpoint` returns a properly resized checkpoint object that can be used for a subsequent `restore_checkpoint` operation.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> prepare_checkpoint(hpx::launch p, T const &t, Ts const&... ts)
prepare_checkpoint
```

`prepare_checkpoint` takes the containers which have to be filled from the byte stream by a subsequent `restore_checkpoint` invocation. `prepare_checkpoint` will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> prepare_checkpoint(hpx::launch p, checkpoint &&c, T const &t, Ts
                                         const&... ts)
```

prepare_checkpoint

prepare_checkpoint takes the containers which have to be filled from the byte stream by a subsequent restore_checkpoint invocation. prepare_checkpoint will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **c** – Takes a pre-initialized checkpoint to prepare
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
void restore_checkpoint(checkpoint const &c, T &t, Ts&... ts)
```

Restore_checkpoint

Restore_checkpoint takes a checkpoint object as a first argument and the containers which will be filled from the byte stream (in the same order as they were placed in save_checkpoint). Restore_checkpoint can resurrect a stored component in two ways: by passing in an instance of a component's shared_ptr or by passing in an instance of the component's client.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – The checkpoint to restore.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Restore_checkpoint returns void.

```
class checkpoint
```

```
#include <checkpoint.hpp> Checkpoint Object
```

Checkpoint is the container object which is produced by `save_checkpoint` and is consumed by a `re-store_checkpoint`. A checkpoint may be moved into the `save_checkpoint` object to write the byte stream to the pre-created checkpoint object.

Checkpoints are able to store all containers which are serializable including components.

Public Types

```
using const_iterator = std::vector<char>::const_iterator
```

Public Functions

```
checkpoint() = default
```

```
~checkpoint() = default
```

```
checkpoint(checkpoint const &c) = default
```

```
checkpoint(checkpoint &&c) noexcept = default
```

```
inline explicit checkpoint(std::vector<char> const &vec)
```

```
inline explicit checkpoint(std::vector<char> &&vec) noexcept
```

```
checkpoint &operator=(checkpoint const &c) = default
```

```
checkpoint &operator=(checkpoint &&c) noexcept = default
```

```
inline const_iterator begin() const noexcept
```

```
inline const_iterator end() const noexcept
```

```
inline std::size_t size() const noexcept
```

```
inline char *data() noexcept
```

```
inline char const *data() const noexcept
```

Private Functions

```
template<typename Archive>
```

```
inline void serialize(Archive &arch, unsigned int const)
```

Private Members

```
std::vector<char> data_
```

Friends

friend class hpx::serialization::access

friend *std::ostream* &**operator**<<(*std::ostream* &ost, *checkpoint* const &ckp)

Operator<< Overload

This overload is the main way to write data from a checkpoint to an object such as a file. Inside the function, the size of the checkpoint will be written to the stream before the checkpoint's data. The `operator>>` overload uses this to read the correct number of bytes. Be mindful of this additional write and read when you use different facilities to write out or read in data to a checkpoint!

Parameters

- **ost** – Output stream to write to.
- **ckp** – Checkpoint to copy from.

Returns

Operator<< returns the ostream object.

friend *std::istream* &**operator**>>(*std::istream* &ist, *checkpoint* &ckp)

Operator>> Overload

This overload is the main way to read in data from an object such as a file to a checkpoint. It is important to note that inside the function, the first variable to be read is the size of the checkpoint. This size variable is written to the stream before the checkpoint's data in the `operator<<` overload. Be mindful of this additional read and write when you use different facilities to read in or write out data from a checkpoint!

Parameters

- **ist** – Input stream to write from.
- **ckp** – Checkpoint to write to.

Returns

Operator>> returns the ostream object.

template<typename **T**, typename ...**Ts**>

friend void **restore_checkpoint**(*checkpoint* const &c, *T* &t, *Ts*&... ts)

Restore_checkpoint

Restore_checkpoint takes a checkpoint object as a first argument and the containers which will be filled from the byte stream (in the same order as they were placed in `save_checkpoint`). Restore_checkpoint can resurrect a stored component in two ways: by passing in an instance of a component's `shared_ptr` or by passing in an instance of the component's client.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – The checkpoint to restore.
- **t** – A container to restore.
- **ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Returns

Restore_checkpoint returns void.

inline friend bool **operator**==(*checkpoint* const &lhs, *checkpoint* const &rhs) noexcept

inline friend bool **operator**!=(*checkpoint* const &lhs, *checkpoint* const &rhs) noexcept

collectives

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/collectives/all_reduce.hpp

Defined in header `hpx/collectives/all_reduce.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T, typename F>
hpx::future<std::decay_t<T>>> all_reduce(char const *basename, T &&result, F &&op,
                                     num_sites_arg num_sites = num_sites_arg(), this_site_arg
                                     this_site = this_site_arg(), generation_arg generation =
                                     generation_arg(), root_site_arg root_site = root_site_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_reduce` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **root_site** – The site that is responsible for creating the `all_reduce` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_reduce` operation has been completed.

```
template<typename T, typename F>
hpx::future<std::decay_t<T>>> all_reduce(communicator comm, T &&result, F &&op, this_site_arg
                                     this_site = this_site_arg(), generation_arg generation =
                                     generation_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_reduce` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_reduce` operation has been completed.

```
template<typename T, typename F>
decltype(auto) all_reduce(hpx::launch::sync_policy policy, char const *basename, T &&result, F
                        &&op, num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site
                        = this_site_arg(), generation_arg generation = generation_arg(),
                        root_site_arg root_site = root_site_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the `all_reduce` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_reduce` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.


```
template<typename T, typename F>
decltype(auto) all_reduce(hpx::launch::sync_policy policy, communicator comm, T &&result, F
                        &&op, this_site_arg this_site = this_site_arg(), generation_arg generation
                        = generation_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/reduce_direct.hpp

Defined in header `hpx/collectives/reduce_direct.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **lcos**

Functions

```
template<typename Action, typename ReduceOp, typename ArgN, ...  
> hpx::future< decltype(Action(hpx::id_type, ArgN,...  
)>> reduce (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op,  
ArgN argN,...)
```

Perform a distributed reduction operation.

The function `hpx::lcos::reduce` performs a distributed reduction operation over results returned from action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **reduce_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the reduction operation performed on its arguments.
- **argN** – [in] Any number of arbitrary arguments (passed by by const reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall reduction operation.

```
template<typename Action, typename ReduceOp, typename ArgN, ...  
> hpx::future< decltype(Action(hpx::id_type, ArgN,...,  
std::size_t))> reduce_with_index (std::vector< hpx::id_type > const &ids,  
ReduceOp &&reduce_op, ArgN argN,...)
```

Perform a distributed reduction operation.

The function `hpx::lcos::reduce_with_index` performs a distributed reduction operation over results returned from action invocations on a given set of global identifiers. The action can be either plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The function passes the index of the global identifier in the given list of identifiers as the last argument to the action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **reduce_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the reduction operation performed on its arguments.
- **argN** – [in] Any number of arbitrary arguments (passed by by const reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall reduction operation.

hpx/collectives/channel_communicator.hpp

Defined in header `hpx/collectives/channel_communicator.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
hpx::future<channel_communicator> create_channel_communicator(char const *basename,
                                                                num_sites_arg num_sites =
                                                                num_sites_arg(), this_site_arg
                                                                this_site = this_site_arg())
```

Create a new communicator object usable with peer-to-peer channel-based operations

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of channel-based peer-to-peer operations.

Note: The caller must ensure that the communicator object returned by this function is kept alive (i.e., does not go out of scope) until all participating sites have successfully connected. Destroying the communicator before all sites have reached the creation point may cause the remaining sites to hang indefinitely. Consider using a barrier or similar synchronization mechanism after creating the communicator to ensure all sites are connected before allowing it to be destroyed.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future to a new communicator object usable with the collective operation.

```
channel_communicator create_channel_communicator(hpx::launch::sync_policy, char const
                                                    *basename, num_sites_arg num_sites =
                                                    num_sites_arg(), this_site_arg this_site =
                                                    this_site_arg())
```

Create a new communicator object usable with peer-to-peer channel-based operations

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of channel-based peer-to-peer operations.

Note: The caller must ensure that the communicator object returned by this function is kept alive (i.e., does not go out of scope) until all participating sites have successfully connected. Destroying the communicator before all sites have reached the creation point may cause the remaining sites to hang indefinitely. Consider using a barrier or similar synchronization mechanism after creating the communicator to ensure all sites are connected before allowing it to be destroyed.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a new communicator object usable with the collective operation.

```
template<typename T>
hpx::future<void> set(channel_communicator comm, that_site_arg site, T &&value, tag_arg tag =
    tag_arg())
```

Send a value to the given site

This function sends a value to the given site based on the given communicator.

Parameters

- **comm** – The channel communicator object to use for the data transfer
- **site** – The destination site
- **value** – The value to send
- **tag** – The (optional) tag identifying the concrete operation

Returns

This function returns a `future<void>` that becomes ready once the data transfer operation has finished.

```
template<typename T>
hpx::future<T> get(channel_communicator comm, that_site_arg site, tag_arg tag = tag_arg())
```

Send a value to the given site

This function receives a value from the given site based on the given communicator.

Parameters

- **comm** – The channel communicator object to use for the data transfer
- **site** – The source site

Returns

This function returns a `future<T>` that becomes ready once the data transfer operation has finished. The future will hold the received value.

```
class channel_communicator
```

```
    #include <channel_communicator.hpp> A handle identifying the communication channel to use for
    get/set operations
```

hpx/collectives/gather.hpp

Defined in header `hpx/collectives/gather.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T>
hpx::future<std::vector<decay_t<T>>> gather_here(char const *basename, T &&result,
                                              num_sites_arg num_sites = num_sites_arg(),
                                              this_site_arg this_site = this_site_arg(),
                                              generation_arg generation = generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
hpx::future<std::vector<decay_t<T>>> gather_here(communicator comm, T &&result, this_site_arg
                                              this_site = this_site_arg(), generation_arg
                                              generation = generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.

- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
hpx::future<void> gather_there(char const *basename, T &&result, this_site_arg this_site =
                                this_site_arg(), generation_arg generation = generation_arg(),
                                root_site_arg root_site = root_site_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Parameters

- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central gather point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
hpx::future<void> gather_there(communicator comm, T &&result, this_site_arg this_site =
                                this_site_arg(), generation_arg generation = generation_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
decltype(auto) gather_here(hpx::launch::sync_policy, char const *basename, T &&result,
                           num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site =
                           this_site_arg(), generation_arg generation = generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
decltype(auto) gather_here(hpx::launch::sync_policy, communicator comm, T &&result, this_site_arg
                           this_site = this_site_arg(), generation_arg generation = generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
void gather_there(hpx::launch::sync_policy, char const *basename, T &&result, this_site_arg
                  this_site = this_site_arg(), generation_arg generation = generation_arg(),
                  root_site_arg root_site = root_site_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central gather point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
void gather_there(hpx::launch::sync_policy, communicator comm, T &&result, this_site_arg
                  this_site = this_site_arg(), generation_arg generation = generation_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/macros.hpp

Defined in header `hpx/collectives/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

```
HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION(...)
HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_(...)
HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_1(Action)
HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_2(Action, Name)
HPX_REGISTER_BROADCAST_POST_ACTION(...)
HPX_REGISTER_BROADCAST_POST_ACTION_(...)
HPX_REGISTER_BROADCAST_POST_ACTION_1(Action)
HPX_REGISTER_BROADCAST_POST_ACTION_2(Action, Name)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION(...)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_(...)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_1(Action)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_2(Action, Name)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION(...)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_(...)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_1(Action)
HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_2(Action, Name)
HPX_REGISTER_BROADCAST_ACTION_DECLARATION(...)
HPX_REGISTER_BROADCAST_ACTION_DECLARATION_(...)
HPX_REGISTER_BROADCAST_ACTION_DECLARATION_1(Action)
HPX_REGISTER_BROADCAST_ACTION_DECLARATION_2(Action, Name)
HPX_REGISTER_BROADCAST_ACTION(...)
HPX_REGISTER_BROADCAST_ACTION_(...)
HPX_REGISTER_BROADCAST_ACTION_1(Action)
HPX_REGISTER_BROADCAST_ACTION_2(Action, Name)
HPX_REGISTER_BROADCAST_ACTION_ID(Action, Name, Id)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION(...)
```

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_ (...)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_1 (Action)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_2 (Action, Name)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION (...)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_ (...)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_1 (Action)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_2 (Action, Name)

HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_ID (Action, Name, Id)

HPX_REGISTER_FOLD_ACTION_DECLARATION (...)

HPX_REGISTER_FOLD_ACTION_DECLARATION_ (...)

HPX_REGISTER_FOLD_ACTION_DECLARATION_2 (Action, FoldOp)

HPX_REGISTER_FOLD_ACTION_DECLARATION_3 (Action, FoldOp, Name)

HPX_REGISTER_FOLD_ACTION (...)

HPX_REGISTER_FOLD_ACTION_ (...)

HPX_REGISTER_FOLD_ACTION_2 (Action, FoldOp)

HPX_REGISTER_FOLD_ACTION_3 (Action, FoldOp, Name)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION (...)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_ (...)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_2 (Action, FoldOp)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_3 (Action, FoldOp, Name)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION (...)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_ (...)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_2 (Action, FoldOp)

HPX_REGISTER_FOLD_WITH_INDEX_ACTION_3 (Action, FoldOp, Name)

HPX_REGISTER_REDUCE_ACTION_DECLARATION (...)

HPX_REGISTER_REDUCE_ACTION_DECLARATION_ (...)

HPX_REGISTER_REDUCE_ACTION_DECLARATION_2 (Action, ReduceOp)

HPX_REGISTER_REDUCE_ACTION_DECLARATION_3 (Action, ReduceOp, Name)

HPX_REGISTER_REDUCE_ACTION (...)

HPX_REGISTER_REDUCE_ACTION_ (...)

HPX_REGISTER_REDUCE_ACTION_2 (Action, ReduceOp)

```
HPX_REGISTER_REDUCE_ACTION_3(Action, ReduceOp, Name)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_3(Action, ReduceOp, Name)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_3(Action, ReduceOp, Name)
```

[hpx/collectives/all_to_all.hpp](#)

Defined in header `hpx/collectives/all_to_all.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T>
hpx::future<std::vector<T>> all_to_all(char const *basename, std::vector<T> &&local_result,
                                     num_sites_arg num_sites = num_sites_arg(), this_site_arg
                                     this_site = this_site_arg(), generation_arg generation =
                                     generation_arg(), root_site_arg root_site = root_site_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_to_all` operation
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_to_all` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_to_all` operation has been completed.

```
template<typename T>
hpx::future<std::vector<T>> all_to_all(communicator fid, std::vector<T> &&local_result,
                                     this_site_arg this_site = this_site_arg(), generation_arg
                                     generation = generation_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_to_all` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_to_all` operation has been completed.

```
template<typename T>
std::vector<T> all_to_all(hpx::launch::sync_policy policy, char const *basename, std::vector<T>
                          &&local_result, num_sites_arg num_sites = num_sites_arg(), this_site_arg
                          this_site = this_site_arg(), generation_arg generation = generation_arg(),
                          root_site_arg root_site = root_site_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the `all_to_all` operation

- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_to_all` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
std::vector<T> all_to_all(hpx::launch::sync_policy policy, communicator fid, std::vector<T>
                        &&local_result, this_site_arg this_site = this_site_arg(), generation_arg
                        generation = generation_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **fid** – A communicator object returned from `create_communicator`
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **fid** – A communicator object returned from `create_communicator`
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/broadcast_direct.hpp

Defined in header `hpx/collectives/broadcast_direct.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

namespace **lcos**

Functions

```
template<typename Action, typename ArgN, ...
> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,...
))> > broadcast (std::vector< hpx::id_type > const &ids, ArgN argN,...)
```

Perform a distributed broadcast operation.

The function `hpx::lcos::broadcast` performs a distributed broadcast operation resulting in action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The given action is invoked asynchronously on all given identifiers, and the arguments `ArgN` are passed along to those invocations.

Note: If `decltype(Action(...))` is void, then the result of this function is `future<void>`.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **argN** – [in] Any number of arbitrary arguments (passed by const reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall reduction operation.

```
template<typename Action, typename ArgN, ...
> void broadcast_post (std::vector< hpx::id_type > const &ids, ArgN argN,...)
```

Perform an asynchronous (fire&forget) distributed broadcast operation.

The function `hpx::lcos::broadcast_post` performs an asynchronous (fire&forget) distributed broadcast operation resulting in action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The given action is invoked asynchronously on all given identifiers, and the arguments `ArgN` are passed along to those invocations.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **argN** – [in] Any number of arbitrary arguments (passed by const reference) which will be forwarded to the action invocation.

```
template<typename Action, typename ArgN, ...  
> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,...,  
std::size_t))> > broadcast_with_index (std::vector< hpx::id_type > const &ids,  
ArgN argN,...)
```

Perform a distributed broadcast operation.

The function `hpx::lcos::broadcast_with_index` performs a distributed broadcast operation resulting in action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The given action is invoked asynchronously on all given identifiers, and the arguments `ArgN` are passed along to those invocations.

The function passes the index of the global identifier in the given list of identifiers as the last argument to the action.

Note: If `decltype(Action(...))` is void, then the result of this function is `future<void>`.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **argN** – [in] Any number of arbitrary arguments (passed by const reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall reduction operation.

```
template<typename Action, typename ArgN, ...  
> void broadcast_post_with_index (std::vector< hpx::id_type > const &ids,  
ArgN argN,...)
```

Perform an asynchronous (fire&forget) distributed broadcast operation.

The function `hpx::lcos::broadcast_post_with_index` performs an asynchronous (fire&forget) distributed broadcast operation resulting in action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The given action is invoked asynchronously on all given identifiers, and the arguments `ArgN` are passed along to those invocations.

The function passes the index of the global identifier in the given list of identifiers as the last argument to the action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **argN** – [in] Any number of arbitrary arguments (passed by const reference) which will be forwarded to the action invocation.

hpx/collectives/fold.hpp

Defined in header `hpx/collectives/fold.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **lcos**

Functions

```
template<typename Action, typename FoldOp, typename Init, typename ArgN, ...
> hpx::future< decltype(Action(hpx::id_type, ArgN,...
))> fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init,
ArgN argN,...)
```

Perform a distributed fold operation.

The function `hpx::lcos::fold` performs a distributed folding operation over results returned from action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

Note: The type of the initial value must be convertible to the result type returned from the invoked action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **fold_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the folding operation performed on its arguments.
- **init** – [in] The initial value to be used for the folding operation
- **argN** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall folding operation.

```
template<typename Action, typename FoldOp, typename Init, typename ArgN, ...
> hpx::future< decltype(Action(hpx::id_type, ArgN,...,
std::size_t))> fold_with_index (std::vector< hpx::id_type > const &ids,
FoldOp &&fold_op, Init &&init, ArgN argN,...)
```

Perform a distributed folding operation.

The function `hpx::lcos::fold_with_index` performs a distributed folding operation over results returned from action invocations on a given set of global identifiers. The action can be either plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The function passes the index of the global identifier in the given list of identifiers as the last argument to the action.

Note: The type of the initial value must be convertible to the result type returned from the invoked action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **fold_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the folding operation performed on its arguments.
- **init** – [in] The initial value to be used for the folding operation
- **argN** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall folding operation.

```
template<typename Action, typename FoldOp, typename Init, typename ArgN, ...  
> hpx::future< decltype(Action(hpx::id_type, ArgN,...  
>>> inverse_fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op,  
Init &&init, ArgN argN,...)
```

Perform a distributed inverse folding operation.

The function `hpx::lcos::inverse_fold` performs an inverse distributed folding operation over results returned from action invocations on a given set of global identifiers. The action can be either a plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

Note: The type of the initial value must be convertible to the result type returned from the invoked action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **fold_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the folding operation performed on its arguments.
- **init** – [in] The initial value to be used for the folding operation
- **argN** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall folding operation.

```
template<typename Action, typename FoldOp, typename Init, typename ArgN, ...  
> hpx::future< decltype(Action(hpx::id_type, ArgN,...,  
std::size_t))> inverse_fold_with_index (std::vector< hpx::id_type > const &ids,  
FoldOp &&fold_op, Init &&init, ArgN argN,...)
```

Perform a distributed inverse folding operation.

The function `hpx::lcos::inverse_fold_with_index` performs an inverse distributed folding operation over results returned from action invocations on a given set of global identifiers. The action can be either plain action (in which case the global identifiers have to refer to localities) or a component action (in which case the global identifiers have to refer to instances of a component type which exposes the action).

The function passes the index of the global identifier in the given list of identifiers as the last argument to the action.

Note: The type of the initial value must be convertible to the result type returned from the invoked action.

Parameters

- **ids** – [in] A list of global identifiers identifying the target objects for which the given action will be invoked.
- **fold_op** – [in] A binary function expecting two results as returned from the action invocations. The function (or function object) is expected to return the result of the folding operation performed on its arguments.
- **init** – [in] The initial value to be used for the folding operation
- **argN** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the action invocation.

Returns

This function returns a future representing the result of the overall folding operation.

hpx/collectives/argument_types.hpp

Defined in header `hpx/collectives/argument_types.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Typedefs

using **num_sites_arg** = detail::argument_type<detail::num_sites_tag>

The number of participating sites (default: all localities)

using **this_site_arg** = detail::argument_type<detail::this_site_tag>

The local end of the communication channel.

using **that_site_arg** = detail::argument_type<detail::that_site_tag>

The opposite end of the communication channel.

using **generation_arg** = detail::argument_type<detail::generation_tag>

The generational counter identifying the sequence number of the operation performed on the given base name. It needs to be supplied only if the operation on the given base name has to be performed more than once. It must be a positive number greater than zero.

using **root_site_arg** = detail::argument_type<detail::root_site_tag, 0>

The site that is responsible for creating the support object of the operation. It defaults to '0' (zero).

```
using tag_arg = detail::argument_type<detail::tag_tag, 0>
```

The tag identifying the concrete operation.

```
using arity_arg = detail::argument_type<detail::arity_tag, 2>
```

The number of children each of the communication nodes is connected to (default: 2).

```
using flat_fallback_threshold_arg = detail::argument_type<detail::flat_fallback_threshold_tag,  
16>
```

The site-count threshold below which a hierarchical_communicator collapses to a single flat communicator spanning all sites. At small site counts, flat collectives outperform hierarchical composition because tree-walking overhead exceeds the synchronization-depth benefit. Pass 0 to disable the fallback and always build a tree.

hpx/collectives/all_gather.hpp

Defined in header `hpx/collectives/all_gather.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T>  
hpx::future<std::vector<std::decay_t<T>>>> all_gather(char const *basename, T &&result,  
                                                    num_sites_arg num_sites = num_sites_arg(),  
                                                    this_site_arg this_site = this_site_arg(),  
                                                    generation_arg generation = generation_arg(),  
                                                    root_site_arg root_site = root_site_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_gather` operation
- **result** – The value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_gather` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the all_gather operation has been completed.

```
template<typename T>
hpx::future<std::vector<std::decay_t<T>>> all_gather(communicator comm, T &&result,
                                                    this_site_arg this_site = this_site_arg(),
                                                    generation_arg generation =
                                                    generation_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the all_gather operation performed on the given base name. This is optional and needs to be supplied only if the all_gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the all_gather operation performed on the given base name. This is optional and needs to be supplied only if the all_gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the all_gather operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the all_gather operation has been completed.

```
template<typename T>
std::vector<std::decay_t<T>> all_gather(hpx::launch::sync_policy, char const *basename, T
&&result, num_sites_arg num_sites = num_sites_arg(),
this_site_arg this_site = this_site_arg(), generation_arg
generation = generation_arg(), root_site_arg root_site =
root_site_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **sync_policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the all_gather operation
- **result** – The value to transmit to all participating sites from this call site.

- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_gather` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
std::vector<std::decay_t<T>> all_gather(hpx::launch::sync_policy, communicator comm, T
&&result, this_site_arg this_site = this_site_arg(),
generation_arg generation = generation_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **sync_policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **sync_policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/scatter.hpp

Defined in header `hpx/collectives/scatter.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T>
hpx::future<T> scatter_from(char const *basename, this_site_arg this_site = this_site_arg(),
                             generation_arg generation = generation_arg(), root_site_arg root_site =
                             root_site_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Parameters

- **basename** – The base name identifying the scatter operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central scatter point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
hpx::future<T> scatter_from(communicator comm, this_site_arg this_site = this_site_arg(),
                             generation_arg generation = generation_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
hpx::future<T> scatter_to(char const *basename, std::vector<T> &&result, num_sites_arg num_sites
                        = num_sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg
                        generation = generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Parameters

- **basename** – The base name identifying the scatter operation
- **result** – The value to transmit to the central scatter point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
hpx::future<T> scatter_to(communicator comm, std::vector<T> &&result, this_site_arg this_site =
                        this_site_arg(), generation_arg generation = generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
T scatter_from(hpx::launch::sync_policy, char const *basename, this_site_arg this_site =
    this_site_arg(), generation_arg generation = generation_arg(), root_site_arg root_site
    = root_site_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the scatter operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central scatter point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

```
template<typename T>
T scatter_from(hpx::launch::sync_policy, communicator comm, this_site_arg this_site =
    this_site_arg(), generation_arg generation = generation_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

```
template<typename T>
```

```
T scatter_to(hpx::launch::sync_policy, char const *basename, std::vector<T> &&result,  
            num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site = this_site_arg(),  
            generation_arg generation = generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the scatter operation
- **result** – The value to transmit to the central scatter point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

```
template<typename T>
T scatter_to(hpx::launch::sync_policy, communicator comm, std::vector<T> &&result, this_site_arg
            this_site = this_site_arg(), generation_arg generation = generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

hpx::distributed::barrier

Defined in header [hpx/barrier.hpp](#)⁸¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

namespace **distributed**

Functions

explicit **barrier**(std::string const &base_name)

Creates a barrier, rank is locality id, size is number of localities

A barrier *base_name* is created. It expects that `hpx::get_num_localities()` participate and the local rank is `hpx::get_locality_id()`.

Parameters

base_name – The name of the barrier

barrier(std::string const &base_name, std::size_t num)

Creates a barrier with a given size, rank is locality id

A barrier *base_name* is created. It expects that *num* participate and the local rank is `hpx::get_locality_id()`.

Parameters

- **base_name** – The name of the barrier
- **num** – The number of participating threads

barrier(std::string const &base_name, std::size_t num, std::size_t rank)

Creates a barrier with a given size and rank

A barrier *base_name* is created. It expects that *num* participate and the local rank is *rank*.

Parameters

- **base_name** – The name of the barrier
- **num** – The number of participating threads
- **rank** – The rank of the calling site for this invocation

barrier(std::string const &base_name, std::vector<std::size_t> const &ranks, std::size_t rank)

Creates a barrier with a vector of ranks

A barrier *base_name* is created. It expects that `ranks.size()` and the local rank is *rank* (must be contained in *ranks*).

Parameters

- **base_name** – The name of the barrier
- **ranks** – Gives a list of participating ranks (this could be derived from a list of locality ids)

⁸¹³ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/barrier.hpp>

- **rank** – The rank of the calling site for this invocation

void **wait**() const

Wait until each participant entered the barrier. Must be called by all participants

Returns

This function returns once all participants have entered the barrier (have called *wait*).

hpx::future<void> **wait**(*hpx::launch::async_policy*) const

Wait until each participant entered the barrier. Must be called by all participants

Returns

a future that becomes ready once all participants have entered the barrier (have called *wait*).

static void **synchronize**()

Perform a global synchronization using the default global barrier. The barrier is created once at startup and can be reused throughout the lifetime of an HPX application.

Note: This function currently does not support dynamic connection and disconnection of localities.

hpx/collectives/inclusive_scan.hpp

Defined in header `hpx/collectives/inclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

template<typename **T**, typename **F**>

hpx::future<std::decay_t<T>> **inclusive_scan**(char const *basename, *T* &&result, *F* &&op,
 num_sites_arg num_sites = *num_sites_arg*(),
 this_site_arg this_site = *this_site_arg*(),
 generation_arg generation = *generation_arg*(),
 root_site_arg root_site = *root_site_arg*())

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `inclusive_scan` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `inclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `inclusive_scan` operation on the given base name has to be performed

more than once. The generation number (if given) must be a positive number greater than zero.

- **root_site** – The site that is responsible for creating the `inclusive_scan` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `inclusive_scan` operation has been completed.

```
template<typename T, typename F>
hpx::future<std::decay_t<T>> inclusive_scan(communicator comm, T &&result, F &&op,
                                           this_site_arg this_site = this_site_arg(),
                                           generation_arg generation = generation_arg())
```

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `inclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `inclusive_scan` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the `inclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `inclusive_scan` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `inclusive_scan` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `inclusive_scan` operation has been completed.

```
template<typename T, typename F>
decltype(auto) inclusive_scan(hpx::launch::sync_policy, char const *basename, T &&result, F
                               &&op, num_sites_arg num_sites = num_sites_arg(), this_site_arg
                               this_site = this_site_arg(), generation_arg generation =
                               generation_arg(), root_site_arg root_site = root_site_arg())
```

Inclusive inclusive_scan a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the inclusive_scan operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the inclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the inclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the inclusive_scan support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T, typename F>
decltype(auto) inclusive_scan(hpx::launch::sync_policy, communicator comm, T &&result, F
                               &&op, this_site_arg this_site = this_site_arg(), generation_arg
                               generation = generation_arg())
```

Inclusive inclusive_scan a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Inclusive inclusive_scan a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the inclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the inclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the inclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the inclusive_scan operation on the given base name has to be performed

more than once. The generation number (if given) must be a positive number greater than zero.

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx::distributed::latch

Defined in header `hpx/latch.hpp`⁸¹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Top level HPX namespace.

namespace **distributed**

class **latch** : public *components::client_base*<*latch*, *hpx::lcos::server::latch*>

#include <latch.hpp> Latch is an implementation of a synchronization primitive that allows multiple threads to wait for a shared event to occur before proceeding. This latch can be invoked in a distributed application.

For a local only latch

See also:

`hpx::latch`.

Public Functions

latch() = default

explicit **latch**(*std::ptrdiff_t* count)

Initialize the latch

Requires: count >= 0. Synchronization: None Postconditions: counter_ == count.

inline **latch**(*hpx::id_type* const &id)

Extension: Create a client side representation for the existing *server::latch* instance with the given global id *id*.

inline **latch**(*hpx::future*<*hpx::id_type*> &&f)

Extension: Create a client side representation for the existing *server::latch* instance with the given global id *id*.

⁸¹⁴ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/latch.hpp>

inline **latch**(*hpx::shared_future*<*hpx::id_type*> const &id)

Extension: Create a client side representation for the existing *server::latch* instance with the given global id *id*.

inline **latch**(*hpx::shared_future*<*hpx::id_type*> &&id)

inline void **count_down_and_wait**()

Decrements counter_ by 1 . Blocks at the synchronization point until counter_ reaches 0.

Requires: counter_ > 0.

Synchronization: Synchronizes with all calls that block on this latch and with all is_ready calls on this latch that return true.

Throws

Nothing. –

inline void **arrive_and_wait**()

Decrements counter_ by update . Blocks at the synchronization point until counter_ reaches 0.

Requires: counter_ > 0.

Synchronization: Synchronizes with all calls that block on this latch and with all is_ready calls on this latch that return true.

Throws

Nothing. –

inline void **count_down**(*std::ptrdiff_t* n)

Decrements counter_ by n. Does not block.

Requires: counter_ >= n and n >= 0.

Synchronization: Synchronizes with all calls that block on this latch and with all is_ready calls on this latch that return true .

Throws

Nothing. –

inline bool **is_ready**() const noexcept

Returns: counter_ == 0. Does not block.

Throws

Nothing. –

inline bool **try_wait**() const noexcept

Returns: counter_ == 0. Does not block.

Throws

Nothing. –

inline void **wait**() const

If counter_ is 0, returns immediately. Otherwise, blocks the calling thread at the synchronization point until counter_ reaches 0.

Throws

Nothing. –

Private Types

```
typedef components::client_base<latch, hpx::lcos::server::latch> base_type
```

hpx/collectives/reduce.hpp

Defined in header `hpx/collectives/reduce.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T, typename F>  
hpx::future<std::decay_t<T>> reduce_here(char const *basename, T &&result, F &&op,  
                                         num_sites_arg num_sites = num_sites_arg(), this_site_arg  
                                         this_site = this_site_arg(), generation_arg generation =  
                                         generation_arg())
```

Reduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the reduce operation
- **result** – A value to reduce on the central reduction point from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the reduce operation has been completed.

```
template<typename T, typename F>  
hpx::future<decay_t<T>> reduce_here(communicator comm, T &&result, F &&op, this_site_arg  
                                     this_site = this_site_arg(), generation_arg generation =  
                                     generation_arg())
```

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

```
template<typename T, typename F>
hpx::future<void> reduce_there(char const *basename, T &&result, this_site_arg this_site =
                                this_site_arg(), generation_arg generation = generation_arg(),
                                root_site_arg root_site = root_site_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Parameters

- **basename** – The base name identifying the reduction operation
- **result** – A future referring to the value to transmit to the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central reduction point (usually the locality

id). This value is optional and defaults to 0.

Returns

This function returns a `future<void>`. It will become ready once the reduction operation has been completed.

```
template<typename T>
hpx::future<void> reduce_there(communicator comm, T &&result, this_site_arg this_site =
                                this_site_arg(), generation_arg generation = generation_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

```
template<typename T, typename F>
decltype(auto) reduce_here(hpx::launch::sync_policy, char const *basename, T &&result, F &&op,
                            num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site =
                            this_site_arg(), generation_arg generation = generation_arg())
```

Reduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the reduce operation
- **result** – A value to reduce on the central reduction point from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

The final reduced value after applying `op` to all contributions.

```
template<typename T, typename F>
decltype(auto) reduce_here(hpx::launch::sync_policy, communicator comm, T &&result, F &&op,
                           this_site_arg this_site = this_site_arg(), generation_arg generation =
                           generation_arg())
```

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied

only if the reduce operation on the given base name has to be performed more than once.
The generation number (if given) must be a positive number greater than zero.

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

The final reduced value after applying *op* to all contributions.

Returns

The final reduced value after applying *op* to all contributions.

```
template<typename T>
void reduce_there(hpx::launch::sync_policy, char const *basename, T &&result, this_site_arg
                  this_site = this_site_arg(), generation_arg generation = generation_arg(),
                  root_site_arg root_site = root_site_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the reduction operation
- **result** – A future referring to the value to transmit to the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central reduction point (usually the locality id). This value is optional and defaults to 0.

```
template<typename T>
void reduce_there(hpx::launch::sync_policy, communicator comm, T &&result, this_site_arg
                  this_site = this_site_arg(), generation_arg generation = generation_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – A value to reduce on the central reduction point from this call site.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

hpx/collectives/create_communicator.hpp

Defined in header `hpx/collectives/create_communicator.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
communicator create_communicator(char const *basename, num_sites_arg num_sites =
                                num_sites_arg(), this_site_arg this_site = this_site_arg(),
                                generation_arg generation = generation_arg(), root_site_arg
                                root_site = root_site_arg())
```

Create a new communicator object usable with any collective operation

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of the collective operations (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a new communicator object usable with the collective operation.

```
communicator create_local_communicator(char const *basename, num_sites_arg num_sites,  
                                         this_site_arg this_site, generation_arg generation =  
                                         generation_arg(), root_site_arg root_site =  
                                         root_site_arg())
```

Create a new communicator object usable with any local collective operation

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of the collective operations (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites
- **this_site** – The sequence number of this invocation (usually the sequence number of the object participating in the collective operation). This value must be in the range [0, num_sites).
- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a new communicator object usable for all local collective operations.

```
hierarchical_communicator create_hierarchical_communicator(char const *basename,  
                                                            num_sites_arg num_sites =  
                                                            num_sites_arg(), this_site_arg  
                                                            this_site = this_site_arg(),  
                                                            arity_arg arity = arity_arg(),  
                                                            generation_arg generation =  
                                                            generation_arg(), root_site_arg  
                                                            root_site = root_site_arg(),  
                                                            flat_fallback_threshold_arg  
                                                            threshold =  
                                                            flat_fallback_threshold_arg())
```

Create a new hierarchical communicator object usable with collective operations

This functions creates a new *hierarchical_communicator* object that can be called in order to pre-allocate a communicator object usable with multiple invocations of a collective operation (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Note: The sub-communicators of a *hierarchical_communicator* share one generation sequence per registered name. Every hierarchical collective advances each sub-communicator it touches by exactly two internal generations per call (a single-pass collective such as *broadcast*, *gather*, *scatter* or *reduce*, and the inter-group exchange of *all_to_all*, skip the second generation in one step rather than performing a second round-trip). A single *hierarchical_communicator* instance may therefore be shared freely across collective operations, provided every call uses an explicit, strictly consecutive generation number so the shared sequence stays gap-free. Because the two-phase hierarchical collectives (*all_gather*, *all_reduce*, *all_to_all* and the hierarchical *barrier*) derive their phase generations from that explicit number, they require it and reject an auto (default) generation. The non-hierarchical (flat) collectives keep supporting the default generation, falling back to the internal per-communicator counter maintained in the *and_gate*.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **arity** – The arity of the hierarchical tree of communicators to create for the given endpoint. The default arity is 2.
- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. This value is optional and defaults to '0' (zero).
- **threshold** – The site-count threshold below which the communicator collapses to a single flat communicator spanning all sites (strict comparison: `num_sites < threshold`). The default is 16; pass 0 to disable the fallback and always build a tree.

Returns

This function returns a new communicator object usable with the collective operation.

struct **communicator**

#include <create_communicator.hpp> A communicator instance represents the list of sites that participate in a particular collective operation.

Public Functions

void **set_info**(*num_sites_arg* num_sites, *this_site_arg* this_site) noexcept

Store the number of used sites and the index of the current site for this communicator instance.

Parameters

- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this site (usually the locality id).

std::pair<num_sites_arg, this_site_arg> **get_info**() const noexcept

Retrieve the number of used sites and the index of the current site for this communicator instance.

bool **is_root**() const

Return whether this communicator instance represents the root site of the communication operation.

hpx/collectives/broadcast.hpp

Defined in header `hpx/collectives/broadcast.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T>
hpx::future<T> broadcast_to(char const *basename, T &&local_result, num_sites_arg num_sites =
    num_sites_arg(), this_site_arg this_site = this_site_arg(),
    generation_arg generation = generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the broadcast operation
- **local_result** – A value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> broadcast_to(communicator comm, T &&local_result, this_site_arg this_site =
    this_site_arg(), generation_arg generation = generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> broadcast_to(communicator comm, generation_arg generation, T &&local_result,
    this_site_arg this_site = this_site_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> broadcast_from(char const *basename, this_site_arg this_site = this_site_arg(),
                               generation_arg generation = generation_arg(), root_site_arg
                               root_site = root_site_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the broadcast operation
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **root_site** – The site responsible for broadcasting the value. This is optional and defaults to site 0 (zero).

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> broadcast_from(communicator comm, this_site_arg this_site = this_site_arg(),
                               generation_arg generation = generation_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from `create_communicator`
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
decltype(auto) broadcast_to(hpx::launch::sync_policy policy, char const *basename, T
                           &&local_result, num_sites_arg num_sites = num_sites_arg(),
                           this_site_arg this_site = this_site_arg(), generation_arg generation =
                           generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the broadcast operation
- **local_result** – A value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
decltype(auto) broadcast_to(hpx::launch::sync_policy policy, communicator comm, T
                           &&local_result, this_site_arg this_site = this_site_arg(), generation_arg
                           generation = generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
T broadcast_from(hpx::launch::sync_policy policy, char const *basename, this_site_arg this_site =
    this_site_arg(), generation_arg generation = generation_arg(), root_site_arg
    root_site = root_site_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the broadcast operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site responsible for broadcasting the value. This is optional and defaults to site 0 (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
T broadcast_from(hpx::launch::sync_policy policy, communicator comm, this_site_arg this_site =
               this_site_arg(), generation_arg generation = generation_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/exclusive_scan.hpp

Defined in header `hpx/collectives/exclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

namespace **collectives**

Functions

```
template<typename T, typename F>
hpx::future<std::decay_t<T>> exclusive_scan(char const *basename, T &&result, F &&op,
                                           num_sites_arg num_sites = num_sites_arg(),
                                           this_site_arg this_site = this_site_arg(),
                                           generation_arg generation = generation_arg(),
                                           root_site_arg root_site = root_site_arg())
```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: The result returned on the `root_site` is always the same as the result returned on `thus_site == 1` and is the same as the value provided by the `root_site`.

Parameters

- **basename** – The base name identifying the `exclusive_scan` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `exclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `exclusive_scan` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `exclusive_scan` support object. This value is optional and defaults to '0' (zero).

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function `op`) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the `exclusive_scan` operation has been completed.

```
template<typename T, typename F>
hpx::future<std::decay_t<T>> exclusive_scan(communicator comm, T &&result, F &&op,
                                           this_site_arg this_site = this_site_arg(),
                                           generation_arg generation = generation_arg())
```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: The result returned on the `root_site` is always the same as the result returned on `thus_site == 1`

and is the same as the value provided by the `root_site`.

Note: The result returned on the `root_site` is always the same as the result returned on `thus_site == 1` and is the same as the value provided by the `root_site`.

Parameters

- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function `op`) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the exclusive_scan operation has been completed.

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function `op`) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the exclusive_scan operation has been completed.

```
template<typename T, typename F>
decltype(auto) exclusive_scan(hpx::launch::sync_policy, char const *basename, T &&result, F
                               &&op, num_sites_arg num_sites = num_sites_arg(), this_site_arg
                               this_site = this_site_arg(), generation_arg generation =
                               generation_arg(), root_site_arg root_site = root_site_arg())
```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: The result returned on the `root_site` is always the same as the result returned on `thus_site == 1` and is the same as the value provided by the `root_site`.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the exclusive_scan operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the exclusive_scan support object. This value is optional and defaults to '0' (zero).

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the exclusive_scan operation has been completed.

```
template<typename T, typename F>
decltype(auto) exclusive_scan(hpx::launch::sync_policy, communicator comm, T &&result, F
                               &&op, this_site_arg this_site = this_site_arg(), generation_arg
                               generation = generation_arg())
```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: The result returned on the `root_site` is always the same as the result returned on `this_site == 1` and is the same as the value provided by the `root_site`.

Note: The result returned on the `root_site` is always the same as the result returned on `this_site == 1` and is the same as the value provided by the `root_site`.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed

more than once. The generation number (if given) must be a positive number greater than zero.

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the exclusive_scan operation has been completed.

Returns

For the participating site *i* this function returns the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. The value returned on participating site 0 is undefined. The value returned on participating site on process 1 is always the value passed in by participating site 1. The returned future will become ready once the exclusive_scan operation has been completed.

components

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::components::client

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

template<typename **Component**, typename **Data** = void>

class **client** : public `hpx::components::client_base<client<Component, void>, Component, void>`

#include <client.hpp> The client class is a wrapper that manages a distributed component. It extends *client_base* with specific **Component** and **Data** types.

Template Parameters

- **Component** – The type of the component.
- **Data** – The type of the data associated with the client (default is void).

Public Functions

```

client() = default

inline explicit client(hpx::id_type const &id)

inline explicit client(hpx::id_type &&id)

inline explicit client(future_type const &f) noexcept

inline explicit client(future_type &&f) noexcept

inline client(future<hpx::id_type> &&f) noexcept

inline client(future<client> &&c)

client(client const &rhs) noexcept = default

client(client &&rhs) noexcept = default

~client() = default

inline client &operator=(hpx::id_type const &id)

inline client &operator=(hpx::id_type &&id)

inline client &operator=(future_type const &f) noexcept

inline client &operator=(future_type &&f) noexcept

inline client &operator=(future<hpx::id_type> &&f) noexcept

client &operator=(client const &rhs) noexcept = default

client &operator=(client &&rhs) noexcept = default

```

Private Types

```

using base_type = client_base<client, Component, Data>

using future_type = typename base_type::future_type

```

hpx::components::client_base

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```

template<typename Derived>
struct is_client<Derived, std::void_t<typename Derived::is_client_tag>> : public true_type

namespace hpx

```

```

    namespace components

```

Functions

```
template<typename Derived, typename Stub, typename Data>
bool operator==(client_base<Derived, Stub, Data> const &lhs, client_base<Derived, Stub, Data>
               const &rhs)

template<typename Derived, typename Stub, typename Data>
bool operator<(client_base<Derived, Stub, Data> const &lhs, client_base<Derived, Stub, Data> const
              &rhs)

template<typename Derived, typename Stub, typename Data>
class client_base : public detail::make_stub::type<Stub>
    #include <client_base.hpp> This class template serves as a base class for client components, providing
    common functionality such as managing shared state, ID retrieval, and asynchronous operations.
    Template Parameters
    • Derived – The derived client component type.
    • Stub – The stub type used for communication.
    • Data – The extra data type used for additional information.
```

Public Types

```
using stub_argument_type = Stub

using server_component_type = typename detail::make_stub<Stub>::server_component_type

using is_client_tag = void
```

Public Functions

```
client_base() = default

inline explicit client_base(id_type const &id)

inline explicit client_base(id_type &&id)

inline client_base(id_type const &id, bool make_unmanaged)

inline client_base(id_type &&id, bool make_unmanaged)

inline explicit client_base(hpx::shared_future<hpx::id_type> const &f) noexcept

inline explicit client_base(hpx::shared_future<hpx::id_type> &&f) noexcept

inline explicit client_base(hpx::future<hpx::id_type> &&f) noexcept

client_base(client_base const &rhs) = default

client_base(client_base &&rhs) noexcept = default

inline client_base(hpx::future<Derived> &&d)

~client_base() = default
```

```

inline client_base &operator=(hpx::id_type const &id)

inline client_base &operator=(hpx::id_type &&id)

inline client_base &operator=(hpx::shared_future<hpx::id_type> const &f) noexcept

inline client_base &operator=(hpx::shared_future<hpx::id_type> &&f) noexcept

inline client_base &operator=(hpx::future<hpx::id_type> &&f) noexcept

client_base &operator=(client_base const &rhs) = default

client_base &operator=(client_base &&rhs) noexcept = default

inline bool valid() const noexcept

inline explicit operator bool() const noexcept

inline void free()

inline hpx::id_type const &get_id(error_code &ec = hpx::throws) const

inline naming::gid_type const &get_raw_gid() const

inline hpx::shared_future<hpx::id_type> detach()

inline hpx::shared_future<hpx::id_type> share() const

inline void reset(hpx::id_type const &id)

inline void reset(hpx::id_type &&id)

inline void reset(shared_future<hpx::id_type> &&rhs)

inline id_type const &get(error_code &ec = hpx::throws) const

inline bool is_ready() const noexcept

inline bool has_value() const noexcept

inline bool has_exception() const noexcept

inline void wait() const

inline std::exception_ptr get_exception_ptr() const

template<typename F>
inline hpx::traits::future_then_result_t<Derived, F> then(launch l, F &&f) const

template<typename F>
inline hpx::traits::future_then_result_t<Derived, F> then(launch::sync_policy l, F &&f) const

template<typename F>
inline hpx::traits::future_then_result_t<Derived, F> then(F &&f) const

inline hpx::future<bool> register_as(std::string symbolic_name, bool manage_lifetime = true)

inline bool register_as(launch::sync_policy, std::string symbolic_name, bool manage_lifetime =
                        true)

```

```
inline void connect_to(std::string const &symbolic_name)

inline std::string const &registered_name() const

template<typename T>
inline T &get_extra_data()

template<typename T>
inline T *try_get_extra_data() const noexcept
```

Protected Types

```
using stub_type = typename detail::make_stub<Stub>::type

using base_shared_state_type = lcos::detail::future_data_base<hpx::id_type>

using shared_state_type = lcos::detail::future_data<hpx::id_type>

using future_type = shared_future<hpx::id_type>

using extra_data_type = Data
```

Protected Functions

```
inline client_base(hpx::intrusive_ptr<base_shared_state_type> const &state)

inline client_base(hpx::intrusive_ptr<base_shared_state_type> &&state)
```

Protected Attributes

```
hpx::intrusive_ptr<base_shared_state_type> shared_state_
```

Private Static Functions

```
template<typename F>
static inline hpx::traits::future_then_result<Derived, F>::cont_result on_ready(hpx::shared_future<id_type>
                                                                              &&fut, F f)

static inline bool register_as_helper(client_base const &f, std::string symbolic_name, bool
                                     manage_lifetime)
```

```
namespace lcos
```

```
namespace serialization
```

Functions

```
template<typename Archive, typename Derived, typename Stub, typename Data>
void serialize(Archive &ar, ::hpx::components::client_base<Derived, Stub, Data> &f, unsigned
               version)
```

namespace **traits**

```
template<typename Derived> is_client_tag > > : public true_type
```

namespace **util**

hpx/components/get_ptr.hpp

Defined in header `hpx/components/get_ptr.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename Component>
hpx::future<std::shared_ptr<Component>> get_ptr(hpx::id_type const &id)
```

Returns a future referring to the pointer to the underlying memory of a component.

The function `hpx::get_ptr` can be used to extract a future referring to the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the calling locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Parameters

id – [in] The global id of the component for which the pointer to the underlying memory should be retrieved.

Template Parameters

Component – The type of the server side component.

Returns

This function returns a future representing the pointer to the underlying memory for the component instance with the given *id*.

```
template<typename Derived, typename Stub, typename Data>
```

hpx::future<std::shared_ptr<typename components::client_base<Derived, Stub, Data>::server_component_type>> **get_ptr**(*com*
Stub
Data
com
&c

Returns a future referring to the pointer to the underlying memory of a component.

The function `hpx::get_ptr` can be used to extract a future referring to the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the calling locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Parameters

c – [in] A client side representation of the component for which the pointer to the underlying memory should be retrieved.

Returns

This function returns a future representing the pointer to the underlying memory for the component instance with the given *id*.

```
template<typename Component>  
std::shared_ptr<Component> get_ptr(launch::sync_policy p, hpx::id_type const &id, error_code &ec =  
throws)
```

Returns the pointer to the underlying memory of a component.

The function `hpx::get_ptr_sync` can be used to extract the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the requesting locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

Parameters

- **p** – [in] The parameter *p* represents a placeholder type to turn make the call synchronous.
- **id** – [in] The global id of the component for which the pointer to the underlying memory should be retrieved.

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Template Parameters

Component – The only template parameter has to be the type of the server side component.

Returns

This function returns the pointer to the underlying memory for the component instance with the given *id*.

```
template<typename Derived, typename Stub, typename Data>
std::shared_ptr<typename components::client_base<Derived, Stub, Data>::server_component_type> get_ptr(launch::sync_policy p,
com-
po-
nents::client_base<Derived, Stub, Data> const
&c,
er-
ror_code
&ec
=
throws)
```

Returns the pointer to the underlying memory of a component.

The function `hpx::get_ptr_sync` can be used to extract the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the requesting locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

Parameters

- **p** – [in] The parameter *p* represents a placeholder type to turn make the call synchronous.
- **c** – [in] A client side representation of the component for which the pointer to the underlying memory should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the pointer to the underlying memory for the component instance with the given *id*.

hpx/components/basename_registration.hpp

Defined in header `hpx/components/basename_registration.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename Client>  
std::vector<Client> find_all_from_basename(std::string base_name, std::size_t num_ids)
```

Return all registered clients from all localities from the given base name.

This function locates all ids which were registered with the given base name. It returns a list of futures representing those ids.

Return all registered ids from all localities from the given base name.

This function locates all ids which were registered with the given base name. It returns a list of futures representing those ids.

Note: The futures embedded in the returned client objects will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The futures will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Template Parameters

Client – The client type to return

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **num_ids** – [in] The number of registered ids to expect.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **num_ids** – [in] The number of registered ids to expect.

Returns

A list of futures representing the ids which were registered using the given base name.

Returns

A list of futures representing the ids which were registered using the given base name.

```
template<typename Client>
```

```
std::vector<Client> find_all_from_basename(hpx::launch::sync_policy policy, std::string base_name,
                                          std::size_t num_ids)
```

```
template<typename Client>
```

```
std::vector<Client> find_from_basename(std::string base_name, std::vector<std::size_t> const &ids)
```

Return registered clients from the given base name and sequence numbers.

This function locates the ids which were registered with the given base name and the given sequence numbers. It returns a list of futures representing those ids.

Return registered ids from the given base name and sequence numbers.

This function locates the ids which were registered with the given base name and the given sequence numbers. It returns a list of futures representing those ids.

Note: The futures embedded in the returned client objects will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The futures will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Template Parameters

Client – The client type to return

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **ids** – [in] The sequence numbers of the registered ids.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **ids** – [in] The sequence numbers of the registered ids.

Returns

A list of futures representing the ids which were registered using the given base name and sequence numbers.

Returns

A list of futures representing the ids which were registered using the given base name and sequence numbers.

```
template<typename Client>
```

```
std::vector<Client> find_from_basename(hpx::launch::sync_policy policy, std::string base_name,
                                          std::vector<std::size_t> const &ids)
```

```
template<typename Client>
```

```
Client find_from_basename(std::string base_name, std::size_t sequence_nr)
```

Return registered id from the given base name and sequence number.

This function locates the id which was registered with the given base name and the given sequence number. It returns a future representing those id.

This function locates the id which was registered with the given base name and the given sequence number. It returns a future representing those id.

Note: The future embedded in the returned client object will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The future will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Template Parameters

Client – The client type to return

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in] The sequence number of the registered id.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in] The sequence number of the registered id.

Returns

A representing the id which was registered using the given base name and sequence numbers.

Returns

A representing the id which was registered using the given base name and sequence numbers.

```
template<typename Client>
```

```
Client find_from_basename(hpx::launch::sync_policy policy, std::string base_name, std::size_t  
sequence_nr)
```

```
template<typename Client, typename Stub, typename Data>
```

```
hpx::future<bool> register_with_basename(std::string base_name, components::client_base<Client, Stub,  
Data> &client, std::size_t sequence_nr)
```

Register the id wrapped in the given client using the given base name.

The function registers the object the given client refers to using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Template Parameters

Client – The client type to register

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **client** – [in] The client which should be registered using the given base name.

- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

```
template<typename Client>
```

```
Client unregister_with_basename(std::string base_name, std::size_t sequence_nr =  
~static_cast<std::size_t>(0))
```

Unregister the given id using the given base name.

Unregister the given base name.

The function unregisters the given ids using the provided base name.

The function unregisters the given ids using the provided base name.

Template Parameters

Client – The client type to return

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in, optional] The sequential number to use for the un-registration. This number has to be the same as has been used with *register_with_basename* before.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in, optional] The sequential number to use for the un-registration. This number has to be the same as has been used with *register_with_basename* before.

Returns

A future representing the result of the un-registration operation itself.

Returns

A future representing the result of the un-registration operation itself.

hpx/components/basename_registration_fwd.hpp

Defined in header `hpx/components/basename_registration_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

hpx::future<bool> **register_with_basename**(*std::string* base_name, *hpx::id_type* const &id, *std::size_t* sequence_nr = ~static_cast<*std::size_t*>(0))

Register the given id using the given base name.

The function registers the given ids using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **id** – [in] The id to register using the given base name.
- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

bool **register_with_basename**(*hpx::launch::sync_policy*, *std::string* base_name, *hpx::id_type* const &id, *std::size_t* sequence_nr = ~static_cast<*std::size_t*>(0), *error_code* &ec = *throws*)

hpx::future<bool> **register_with_basename**(*std::string* base_name, *hpx::future<hpx::id_type>* f, *std::size_t* sequence_nr = ~static_cast<*std::size_t*>(0))

Register the id wrapped in the given future using the given base name.

The function registers the object the given future refers to using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **f** – [in] The future which should be registered using the given base name.
- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

components_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/components_base/component_type.hpp

Defined in header `hpx/components_base/component_type.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_COMPONENT_ENUM_TYPE_ENUM_DEPRECATION_MSG

HPX_FACTORY_STATE_ENUM_DEPRECATION_MSG

namespace **hpx**

namespace **components**

Typedefs

using **component_deleter_type** = void (*)(hpx::naming::gid_type const&, hpx::naming::address const&)

Enums

enum class **component_enum_type** : naming::component_type

Values:

enumerator **invalid**

enumerator **runtime_support**

enumerator **plain_function**

enumerator **base_lco**

enumerator **base_lco_with_value_unmanaged**

enumerator **base_lco_with_value**

enumerator **latch**

enumerator **barrier**

enumerator **promise**

enumerator **agas_locality_namespace**

enumerator **agas_primary_namespace**

enumerator **agas_component_namespace**

enumerator **agas_symbol_namespace**

enumerator **last**

enumerator **first_dynamic**

enum class **factory_state** : *std::uint8_t*

Values:

enumerator **enabled**

enumerator **disabled**

enumerator **check**

Functions

constexpr *naming::component_type* **to_int**(*component_enum_type* t) noexcept

constexpr int **to_int**(*factory_state* t) noexcept

bool &**enabled**(*component_type* type)

util::atomic_count &**instance_count**(*component_type* type)

component_deleter_type &**deleter**(*component_type* type)

bool **enumerate_instance_counts**(*hpx::move_only_function*<bool(*component_type*)> const &f)

std::string **get_component_type_name**(*component_type* type)

Return the string representation for a given component type id.

constexpr *component_type* **get_base_type**(*component_type* t) noexcept

The lower short word of the component type is the type of the component exposing the actions.

constexpr *component_type* **get_derived_type**(*component_type* t) noexcept

The upper short word of the component is the actual component type.


```
constexpr component_type derived_component_type(component_type derived, component_type
                                                    base) noexcept
```

A component derived from a base component exposing the actions needs to have a specially formatted component type.

```
constexpr bool types_are_compatible(component_type lhs, component_type rhs) noexcept
```

Verify the two given component types are matching (compatible)

```
template<typename Component, typename Enable = void>
char const *get_component_name() noexcept
```

```
template<typename Component, typename Enable = void>
char const *get_component_base_name() noexcept
```

```
template<typename Component>
component_type get_component_type() noexcept
```

```
template<typename Component>
void set_component_type(component_type type)
```

Variables

```
constexpr component_enum_type component_invalid = component_enum_type::invalid
```

```
constexpr component_enum_type component_runtime_support =
component_enum_type::runtime_support
```

```
constexpr component_enum_type component_plain_function =
component_enum_type::plain_function
```

```
constexpr component_enum_type component_base_lco = component_enum_type::base_lco
```

```
constexpr component_enum_type component_base_lco_with_value_unmanaged =
component_enum_type::base_lco_with_value_unmanaged
```

```
constexpr component_enum_type component_base_lco_with_value =
component_enum_type::base_lco_with_value
```

```
constexpr component_enum_type component_latch = component_enum_type::latch
```

```
constexpr component_enum_type component_barrier = component_enum_type::barrier
```

```
constexpr component_enum_type component_promise = component_enum_type::promise
```

```
constexpr component_enum_type component_agas_locality_namespace =
component_enum_type::agas_locality_namespace
```

```
constexpr component_enum_type component_agas_primary_namespace =
component_enum_type::agas_primary_namespace
```

```
constexpr component_enum_type component_agas_component_namespace =  
    component_enum_type::agas_component_namespace  
  
constexpr component_enum_type component_agas_symbol_namespace =  
    component_enum_type::agas_symbol_namespace  
  
constexpr component_enum_type component_last = component_enum_type::last  
  
constexpr component_enum_type component_first_dynamic = component_enum_type::first_dynamic  
  
constexpr factory_state factory_enabled = factory_state::enabled  
  
constexpr factory_state factory_disabled = factory_state::disabled  
  
constexpr factory_state factory_check = factory_state::check  
  
constexpr int component_type_mask = 0x3FF  
  
constexpr int component_type_shift = 10
```

hpx/components_base/get_lva.hpp

Defined in header `hpx/components_base/get_lva.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

```
template<typename Component, typename Enable = void>
```

```
struct get_lva
```

#include <get_lva.hpp> The `get_lva` template is a helper structure allowing to convert a local virtual address as stored in a local address (returned from the function `agas::addressing_service::resolve`) to the address of the component implementing the action.

The default implementation uses the template argument *Component* to deduce the type wrapping the component implementing the action. This is used to get the needed address.

Template Parameters

Component – This is the type of the component implementing the action to execute.

Public Static Functions

static inline constexpr *Component* ***call**(*naming::address_type* lva) noexcept

HPX_REGISTER_STARTUP_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

```
template<bool (*Startup)(startup_function_type&, bool&), bool
(*Shutdown)(shutdown_function_type&, bool&)>
struct component_startup_shutdown : public component_startup_shutdown_base
    #include <component_startup_shutdown.hpp> The component_startup_shutdown class provides a
    minimal implementation of a component's startup/shutdown function provider.
```

Public Functions

inline bool **get_startup_function**(*startup_function_type* &startup, bool &pre_startup) override

Return any startup function for this component.

Parameters

- **startup** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_startup** –

Returns

Returns *true* if the parameter *startup* has been successfully initialized with the startup function.

inline bool **get_shutdown_function**(*shutdown_function_type* &shutdown, bool &pre_shutdown) override

Return any startup function for this component.

Parameters

- **shutdown** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_shutdown** –

Returns

Returns *true* if the parameter *shutdown* has been successfully initialized with the shutdown function.

hpx::components::component, hpx::components::component_base

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

template<typename **Component** = void>

class **abstract_component_base**

template<typename **Component**, typename **Derived** = void>

class **abstract_managed_component_base**

template<typename **Component**>

class **component**

#include <components_base_fwd.hpp> The *component* class wraps around a given component type, adding additional type aliases and constructors. It inherits from the specified component type.

template<typename **Component** = void>

class **component_base**

#include <components_base_fwd.hpp> *component_base* serves as a base class for components. It provides common functionality needed by components, such as address and ID retrieval. The template parameter *Component* specifies the derived component type.

template<typename **Component**>

class **fixed_component**

template<typename **Component**>

class **fixed_component_base**

template<typename **Component**, typename **Derived**>

class **managed_component**

#include <managed_component_base.hpp> The *managed_component* template is used as an indirection layer for components allowing to gracefully handle the access to non-existing components.

Additionally, it provides memory management capabilities for the wrapping instances, and it integrates the memory management with the AGAS service. Every instance of a *managed_component* gets assigned a global id. The provided memory management allocates the *managed_component* instances from a special heap, ensuring fast allocation and avoids a full network round trip to the AGAS service for each of the allocated instances.

Template Parameters

- **Component** – Component type
- **Derived** – Most derived component type

template<typename **Component**, typename **Wrapper**, typename **CtorPolicy**, typename **DtorPolicy**>

class **managed_component_base**

hpx/components_base/agas_interface.hpp

Defined in header `hpx/components_base/agas_interface.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **agas**

Functions

bool **is_console**()

bool **register_name**(*launch::sync_policy*, *std::string* const &name, *naming::gid_type* const &gid, *error_code* &ec = *throws*)

bool **register_name**(*launch::sync_policy*, *std::string* const &name, *hpx::id_type* const &id, *error_code* &ec = *throws*)

hpx::future<bool> **register_name**(*std::string* const &name, *hpx::id_type* const &id)

hpx::id_type **unregister_name**(*launch::sync_policy*, *std::string* const &name, *error_code* &ec = *throws*)

hpx::future<*hpx::id_type*> **unregister_name**(*std::string* const &name)

hpx::id_type **resolve_name**(*launch::sync_policy*, *std::string* const &name, *error_code* &ec = *throws*)

hpx::future<*hpx::id_type*> **resolve_name**(*std::string* const &name)

hpx::future<*std::uint32_t*> **get_num_localities**(*naming::component_type* type = *naming::component_invalid*)

std::uint32_t **get_num_localities**(*launch::sync_policy*, *naming::component_type* type, *error_code* &ec = *throws*)

inline *std::uint32_t* **get_num_localities**(*launch::sync_policy*, *error_code* &ec = *throws*)

std::string **get_component_type_name**(*naming::component_type* type, *error_code* &ec = *throws*)

hpx::future<*std::vector*<*std::uint32_t*>> **get_num_threads**()

std::vector<*std::uint32_t*> **get_num_threads**(*launch::sync_policy*, *error_code* &ec = *throws*)

hpx::future<*std::uint32_t*> **get_num_overall_threads**()

std::uint32_t **get_num_overall_threads**(*launch::sync_policy*, *error_code* &ec = *throws*)

std::uint32_t **get_locality_id**(*error_code* &ec = *throws*)

inline *hpx::naming::gid_type* **get_locality**()

std::vector<*std::uint32_t*> **get_all_locality_ids**(*naming::component_type* type, *error_code* &ec = *throws*)

```
inline std::vector<std::uint32_t> get_all_locality_ids(error_code &ec = throws)

bool is_local_address_cached(naming::gid_type const &gid, error_code &ec = throws)

bool is_local_address_cached(naming::gid_type const &gid, naming::address &addr, error_code
                             &ec = throws)

bool is_local_address_cached(naming::gid_type const &gid, naming::address &addr,
                             std::pair<bool, components::pinned_ptr> &r,
                             hpx::move_only_function<std::pair<bool,
                             components::pinned_ptr>(naming::address const&)> &&f,
                             error_code &ec = throws)

inline bool is_local_address_cached(hpx::id_type const &id, error_code &ec = throws)

inline bool is_local_address_cached(hpx::id_type const &id, naming::address &addr, error_code
                                     &ec = throws)

inline bool is_local_address_cached(hpx::id_type const &id, naming::address &addr,
                                     std::pair<bool, components::pinned_ptr> &r,
                                     hpx::move_only_function<std::pair<bool,
                                     components::pinned_ptr>(naming::address const&)> &&f,
                                     error_code &ec = throws)

void update_cache_entry(naming::gid_type const &gid, naming::address const &addr, std::uint64_t
                        count = 0, std::uint64_t offset = 0, error_code &ec = throws)

bool is_local_lva_encoded_address(naming::gid_type const &gid)

inline bool is_local_lva_encoded_address(hpx::id_type const &id)

hpx::future_or_value<naming::address> resolve_async(hpx::id_type const &id)

hpx::future<naming::address> resolve(hpx::id_type const &id)

naming::address resolve(launch::sync_policy, hpx::id_type const &id, error_code &ec = throws)

bool resolve_local(naming::gid_type const &gid, naming::address &addr, error_code &ec = throws)

bool resolve_cached(naming::gid_type const &gid, naming::address &addr)

hpx::future<bool> bind(naming::gid_type const &gid, naming::address const &addr, std::uint32_t
                      locality_id)

bool bind(launch::sync_policy, naming::gid_type const &gid, naming::address const &addr,
          std::uint32_t locality_id, error_code &ec = throws)

hpx::future<bool> bind(naming::gid_type const &gid, naming::address const &addr, naming::gid_type
                      const &locality_)

bool bind(launch::sync_policy, naming::gid_type const &gid, naming::address const &addr,
          naming::gid_type const &locality_, error_code &ec = throws)

hpx::future<naming::address> unbind(naming::gid_type const &gid, std::uint64_t count = 1)

naming::address unbind(launch::sync_policy, naming::gid_type const &gid, std::uint64_t count = 1,
                      error_code &ec = throws)
```

```

bool bind_gid_local(naming::gid_type const &gid, naming::address const &addr, error_code &ec =
    throws)

void unbind_gid_local(naming::gid_type const &gid, error_code &ec = throws)

bool bind_range_local(naming::gid_type const &gid, std::size_t count, naming::address const &addr,
    std::size_t offset, error_code &ec = throws)

void unbind_range_local(naming::gid_type const &gid, std::size_t count, error_code &ec = throws)

void garbage_collect_non_blocking(error_code &ec = throws)

void garbage_collect(error_code &ec = throws)

void garbage_collect_non_blocking(hpx::id_type const &id, error_code &ec = throws)
    Invoke an asynchronous garbage collection step on the given target locality.

void garbage_collect(hpx::id_type const &id, error_code &ec = throws)
    Invoke a synchronous garbage collection step on the given target locality.

hpx::id_type get_console_locality(error_code &ec = throws)
    Return an id_type referring to the console locality.

naming::gid_type get_next_id(std::size_t count, error_code &ec = throws)

void decref(naming::gid_type const &id, std::int64_t credits, error_code &ec = throws)

hpx::future_or_value<std::int64_t> incref(naming::gid_type const &gid, std::int64_t credits,
    hpx::id_type const &keep_alive = hpx::invalid_id)

std::int64_t incref(launch::sync_policy, naming::gid_type const &gid, std::int64_t credits = 1,
    hpx::id_type const &keep_alive = hpx::invalid_id, error_code &ec = throws)

std::int64_t replenish_credits(naming::gid_type &gid)

hpx::future_or_value<id_type> get_colocation_id(hpx::id_type const &id)

hpx::id_type get_colocation_id(launch::sync_policy, hpx::id_type const &id, error_code &ec =
    throws)

hpx::future<hpx::id_type> on_symbol_namespace_event(std::string const &name, bool
    call_for_past_events)

hpx::future<std::pair<hpx::id_type, naming::address>> begin_migration(hpx::id_type const &id)

bool end_migration(hpx::id_type const &id)

hpx::future<void> mark_as_migrated(naming::gid_type const &gid,
    hpx::move_only_function<std::pair<bool,
    hpx::future<void>>()> &&f, bool
    expect_to_be_marked_as_migrating)

std::pair<bool, components::pinned_ptr> was_object_migrated(naming::gid_type const &gid,
    hpx::move_only_function<components::pinned_ptr()>
    &&f)

void unmark_as_migrated(naming::gid_type const &gid, hpx::move_only_function<void()> &&f)

```

```
hpx::future<std::map<std::string, hpx::id_type>> find_symbols(std::string const &pattern = "")
std::map<std::string, hpx::id_type> find_symbols(hpx::launch::sync_policy, std::string const &pattern
                                                = "")

naming::component_type register_factory(std::uint32_t prefix, std::string const &name, error_code
                                         &ec = throws)

naming::component_type get_component_id(std::string const &name, error_code &ec = throws)

void destroy_component(naming::gid_type const &gid, naming::address const &addr)

naming::address_type get_primary_ns_lva()

naming::address_type get_symbol_ns_lva()

naming::address_type get_runtime_support_lva()

struct agas_interface_functions &agas_init()
```

HPX_REGISTER_COMMANDLINE_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

```
struct component_commandline : public component_commandline_base
    #include <component_commandline.hpp> The component_startup_shutdown provides a minimal im-
    plementation of a component's startup/shutdown function provider.
```

Public Functions

```
inline hpx::program_options::options_description add_commandline_options() override
    Return any additional command line options valid for this component.
```

Note: This function will be executed by the runtime system during system startup.

Returns

The module is expected to fill a `options_description` object with any additional command line options this component will handle.

namespace **commandline_options_provider**

Functions

`hpx::program_options::options_description add_commandline_options()`

`hpx/components_base/server/managed_component_base.hpp`

Defined in header `hpx/components_base/server/managed_component_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

struct **init**<traits::construct_with_back_ptr>

Public Static Functions

template<typename **Component**, typename **Managed**>
static inline constexpr void **call**(*Component**, *Managed**) noexcept

template<typename **Component**, typename **Managed**, typename ...**Ts**>
static inline void **call_new**(*Component* *&component, *Managed* *this_, *Ts*&&... vs)

template<>

struct **init**<traits::construct_without_back_ptr>

Public Static Functions

template<typename **Component**, typename **Managed**>
static inline void **call**(*Component* *component, *Managed* *this_)

template<typename **Component**, typename **Managed**, typename ...**Ts**>
static inline void **call_new**(*Component* *&component, *Managed* *this_, *Ts*&&... vs)

template<>

struct **destroy_backptr**<traits::managed_object_is_lifetime_controlled>

Public Static Functions

template<typename **BackPtr**>
static inline void **call**(*BackPtr* *back_ptr)

template<>

struct **destroy_backptr**<traits::managed_object_controls_lifetime>

Public Static Functions

```
template<typename BackPtr>
static inline constexpr void call(BackPtr*) noexcept

template<>

struct manage_lifetime<traits::managed_object_is_lifetime_controlled>
```

Public Static Functions

```
template<typename Component>
static inline constexpr void call(Component*) noexcept

template<typename Component>
static inline void addref(Component *component) noexcept

template<typename Component>
static inline void release(Component *component) noexcept

template<>

struct manage_lifetime<traits::managed_object_controls_lifetime>
```

Public Static Functions

```
template<typename Component>
static inline void call(Component *component) noexcept(noexcept(component->finalize()))

template<typename Component>
static inline constexpr void addref(Component*) noexcept

template<typename Component>
static inline constexpr void release(Component*) noexcept

namespace hpx

    namespace components
```

Functions

```
template<typename Component, typename Derived>
void intrusive_ptr_add_ref(managed_component<Component, Derived> *p) noexcept

template<typename Component, typename Derived>
void intrusive_ptr_release(managed_component<Component, Derived> *p) noexcept

template<typename Component, typename Derived>

class managed_component
    #include <managed_component_base.hpp>

template<typename Component, typename Wrapper, typename CtorPolicy, typename DtorPolicy>
```

```
class managed_component_base
```

```
namespace detail_adl_barrier
```

```
    template<typename DtorTag>
```

```
    struct destroy_backptr
```

```
template<> managed_object_controls_lifetime >
```

Public Static Functions

```
    template<typename BackPtr>
```

```
    static inline constexpr void call(BackPtr*) noexcept
```

```
template<> managed_object_is_lifetime_controlled >
```

Public Static Functions

```
    template<typename BackPtr>
```

```
    static inline void call(BackPtr *back_ptr)
```

```
template<typename BackPtrTag>
```

```
struct init
```

```
template<> construct_with_back_ptr >
```

Public Static Functions

```
    template<typename Component, typename Managed>
```

```
    static inline constexpr void call(Component*, Managed*) noexcept
```

```
    template<typename Component, typename Managed, typename ...Ts>
```

```
    static inline void call_new(Component *&component, Managed *this_, Ts&&... vs)
```

```
template<> construct_without_back_ptr >
```

Public Static Functions

```
    template<typename Component, typename Managed>
```

```
    static inline void call(Component *component, Managed *this_)
```

```
    template<typename Component, typename Managed, typename ...Ts>
```

```
    static inline void call_new(Component *&component, Managed *this_, Ts&&... vs)
```

```
template<typename DtorTag>
```

```
struct manage_lifetime
```

```
template<> managed_object_controls_lifetime >
```

Public Static Functions

```
template<typename Component>  
static inline void call(Component *component) noexcept(noexcept(component->finalize()))
```

```
template<typename Component>  
static inline constexpr void addref(Component*) noexcept
```

```
template<typename Component>  
static inline constexpr void release(Component*) noexcept
```

```
template<> managed_object_is_lifetime_controlled >
```

Public Static Functions

```
template<typename Component>  
static inline constexpr void call(Component*) noexcept
```

```
template<typename Component>  
static inline void addref(Component *component) noexcept
```

```
template<typename Component>  
static inline void release(Component *component) noexcept
```

hpx/components_base/server/fixed_component_base.hpp

Defined in header `hpx/components_base/server/fixed_component_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace components
```

```
template<typename Component>
```

```
class fixed_component
```

```
template<typename Component>
```

```
class fixed_component_base
```

hpx/components_base/server/migration_support.hpp

Defined in header `hpx/components_base/server/migration_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

template<typename **BaseComponent**, typename **Mutex** = *hpx::spinlock*>

struct **migration_support** : public *BaseComponent*

#include <migration_support.hpp> This hook has to be inserted into the derivation chain of any component for it to support migration.

Public Types

using **decorates_action** = void

Public Functions

inline **migration_support**()

template<typename **T**, typename ...**Ts**, typename =
std::enable_if_t<!std::is_same_v<std::decay_t<T>, migration_support>>>
inline explicit **migration_support**(*T* &&*t*, *Ts*&&... *ts*)

migration_support(*migration_support* const&) = default

migration_support(*migration_support*&&) = default

migration_support &**operator**=(*migration_support* const&) = default

migration_support &**operator**=(*migration_support*&&) = default

~migration_support() = default

inline *naming::gid_type* **get_base_gid**(*naming::gid_type* const &*assign_gid* =
naming::invalid_gid) const

inline bool **pin**() noexcept

inline bool **unpin**()

inline *std::uint32_t* **pin_count**() const noexcept

inline void **mark_as_migrated**()

inline *hpx::future<void>* **mark_as_migrated**(*hpx::id_type* const &*to_migrate*)

inline void **unmark_as_migrated**(*hpx::id_type* const &*to_migrate*)

Public Static Functions

```
static inline constexpr bool supports_migration() noexcept
```

```
static inline constexpr void on_migrated() noexcept
```

```
template<typename F>
```

```
static inline threads::thread_function_type decorate_action(naming::address_type lva, F &&f)
```

```
static inline std::pair<bool, components::pinned_ptr> was_object_migrated(hpx::naming::gid_type  
                                                                    const &id, nam-  
                                                                    ing::address_type  
                                                                    lva)
```

Protected Functions

```
inline threads::thread_result_type thread_function(threads::thread_function_type &&f,  
                                                    components::pinned_ptr,  
                                                    threads::thread_restart_state state)
```

Private Types

```
using base_type = BaseComponent
```

```
using this_component_type = typename base_type::this_component_type
```

Private Members

```
hpx::intrusive_ptr<detail::migration_support_data<Mutex>> data_
```

```
hpx::promise<void> trigger_migration_
```

```
bool started_migration_ = false
```

```
bool was_marked_for_migration_ = false
```

compute

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/compute/host/target_distribution_policy.hpp

Defined in header hpx/compute/host/target_distribution_policy.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

distribution_policies

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/distribution_policies/target_distribution_policy.hpp

Defined in header hpx/distribution_policies/target_distribution_policy.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **components**

Variables

const *target_distribution_policy* **target**

A predefined instance of the *target_distribution_policy*. It will represent the local locality and will place all items to create here.

struct **target_distribution_policy**

#include <target_distribution_policy.hpp> This class specifies the parameters for a simple distribution policy to use for creating (and evenly distributing) a given number of items on a given set of localities.

Public Functions

target_distribution_policy() = default

Default-construct a new instance of a *target_distribution_policy*. This policy will represent one locality (the local locality).

inline *target_distribution_policy* **operator()** (id_type const &id) const

Create a new *target_distribution_policy* representing the given locality

Parameters

loc – [in] The locality the new instance should represent

template<typename **Component**, typename ...**Ts**>

inline *hpx::future*<*hpx::id_type*> **create** (*Ts*&&... vs) const

Create one object on one of the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

```
template<bool WithCount, typename Component, typename ...Ts>
inline hpx::future<std::vector<bulk_locality_result>> bulk_create(std::size_t count, Ts&&... vs)
                                                    const
```

Create multiple objects on the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

```
template<typename Action, typename ...Ts>
inline async_result<Action>::type async(launch policy, Ts&&... vs) const

template<typename Action, typename Callback, typename ...Ts>
inline async_result<Action>::type async_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Continuation, typename ...Ts>
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
inline bool apply(launch policy, Ts&&... vs) const

template<typename Action, typename Continuation, typename Callback, typename ...Ts>
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

```
inline std::size_t get_num_localities() const
```

Returns the number of associated localities for this distribution policy

Note: This function is part of the creation policy implemented by this class

```
inline hpx::id_type get_next_target() const
```

Returns the locality which is anticipated to be used for the next async operation


```
template<typename Action>
struct async_result
    #include <target_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

hpx/distribution_policies/binpacking_distribution_policy.hpp

Defined in header `hpx/distribution_policies/binpacking_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```

Variables

```
constexpr char const *const default_binpacking_counter_name =
"/runtime{locality/total}/count/component@"
```

```
const binpacking_distribution_policy binpacked
```

A predefined instance of the binpacking *distribution_policy*. It will represent the local locality and will place all items to create here.

```
struct binpacking_distribution_policy
```

#include <binpacking_distribution_policy.hpp> This class specifies the parameters for a binpacking distribution policy to use for creating a given number of items on a given set of localities. The binpacking policy will distribute the new objects in a way such that each of the localities will equalize the number of overall objects of this type based on a given criteria (by default this criteria is the overall number of objects of this type).

Public Functions

inline **binpacking_distribution_policy**()

Default-construct a new instance of a `binpacking_distribution_policy`. This policy will represent one locality (the local locality).

inline *binpacking_distribution_policy* **operator**() (*std::vector<id_type>* const &locs, char const *perf_counter_name = *default_binpacking_counter_name*) const

Create a new *default_distribution* policy representing the given set of localities.

Parameters

- **locs** – [in] The list of localities the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter which should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

inline *binpacking_distribution_policy* **operator**() (*std::vector<id_type>* &&locs, char const *perf_counter_name = *default_binpacking_counter_name*) const

Create a new *default_distribution* policy representing the given set of localities.

Parameters

- **locs** – [in] The list of localities the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter which should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

inline *binpacking_distribution_policy* **operator**() (*id_type* const &loc, char const *perf_counter_name = *default_binpacking_counter_name*) const

Create a new *default_distribution* policy representing the given locality

Parameters

- **loc** – [in] The locality the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter that should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

template<typename **Component**, typename ...**Ts**>
inline *hpx::future<hpx::id_type>* **create**(*Ts*&&... vs) const

Create one object on one of the localities associated by this policy instance

Parameters

- **vs** – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

template<bool **WithCount**, typename **Component**, typename ...**Ts**>
inline *hpx::future<std::vector<bulk_locality_result>>* **bulk_create**(*std::size_t* count, *Ts*&&... vs) const

Create multiple objects on the localities associated by this policy instance

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

```
inline std::string const &get_counter_name() const
```

Returns the name of the performance counter associated with this policy instance.

```
inline std::size_t get_num_localities() const
```

Returns the number of associated localities for this distribution policy

Note: This function is part of the creation policy implemented by this class

hpx/distribution_policies/unwrapping_result_policy.hpp

Defined in header `hpx/distribution_policies/unwrapping_result_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

struct **unwrapping_result_policy**

#include <unwrapping_result_policy.hpp> This class is a distribution policy that can be used with actions that return futures. For those actions it is possible to apply certain optimizations if the action is invoked synchronously.

Public Functions

```
inline explicit unwrapping_result_policy(id_type const &id)
```

```
template<typename Client, typename Stub, typename Data>
```

```
inline explicit unwrapping_result_policy(client_base<Client, Stub, Data> const &client)
```

```
template<typename Action, typename ...Ts>
```

```
inline async_result<Action>::type async(launch policy, Ts&&... vs) const
```

```
template<typename Action, typename ...Ts>
```

```
inline async_result<Action>::type async(launch::sync_policy, Ts&&... vs) const
```

```
template<typename Action, typename Callback, typename ...Ts>
```

```
inline async_result<Action>::type async_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

```
template<typename Action, typename Continuation, typename ...Ts>
```

```
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
```

```
inline bool apply(launch policy, Ts&&... vs) const
```

```
template<typename Action, typename Continuation, typename Callback, typename ...Ts>
```

```
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const

inline hpx::id_type const &get_next_target() const

template<typename Action>

struct async_result
```

Public Types

```
using type = typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type
```

hpx/distribution_policies/colocating_distribution_policy.hpp

Defined in header `hpx/distribution_policies/colocating_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace components
```

Variables

```
const colocating_distribution_policy colocated
```

A predefined instance of the co-locating *distribution_policy*. It will represent the local locality and will place all items to create here.

```
struct colocating_distribution_policy
```

#include <colocating_distribution_policy.hpp> This class specifies the parameters for a distribution policy to use for creating a given number of items on the locality where a given object is currently placed.

Public Functions

constexpr **colocating_distribution_policy**() = default

Default-construct a new instance of a `colocating_distribution_policy`. This policy will represent the local locality.

inline *colocating_distribution_policy* **operator**() (id_type const &id) const

Create a new `colocating_distribution_policy` representing the locality where the given object is current located

Parameters

id – [in] The global address of the object with which the new instances should be colocated on

template<typename **Client**, typename **Stub**, typename **Data**>

inline *colocating_distribution_policy* **operator**() (*client_base*<*Client*, *Stub*, *Data*> const &client) const

Create a new `colocating_distribution_policy` representing the locality where the given object is current located

Parameters

client – [in] The client side representation of the object with which the new instances should be colocated on

template<typename **Component**, typename ...**Ts**>

inline *hpx::future*<*hpx::id_type*> **create**(*Ts*&&... vs) const

Create one object on the locality of the object this distribution policy instance is associated with

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

template<bool **WithCount**, typename **Component**, typename ...**Ts**>

inline *hpx::future*<*std::vector*<*bulk_locality_result*>> **bulk_create**(*std::size_t* count, *Ts*&&... vs) const

Create multiple objects colocated with the object represented by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

template<typename **Action**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async**(*launch* policy, *Ts*&&... vs) const

template<typename **Action**, typename **Callback**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async_cb**(*launch* policy, *Callback* &&cb, *Ts*&&... vs) const

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Continuation, typename ...Ts>
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
inline bool apply(launch policy, Ts&&... vs) const

template<typename Action, typename Continuation, typename Callback, typename ...Ts>
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const

inline hpx::id_type get_next_target() const
    Returns the locality which is anticipated to be used for the next async operation
```

Public Static Functions

```
static inline std::size_t get_num_localities()
    Returns the number of associated localities for this distribution policy
```

Note: This function is part of the creation policy implemented by this class

```
template<typename Action>

struct async_result
    #include <colocating_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

hpx/distribution_policies/default_distribution_policy.hpp

Defined in header `hpx/distribution_policies/default_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```

Variables

```
const default_distribution_policy default_layout
```

A predefined instance of the default *distribution_policy*. It will represent the local locality and will place all items to create here.

```
struct default_distribution_policy
```

#include <default_distribution_policy.hpp> This class specifies the parameters for a simple distribution policy to use for creating (and evenly distributing) a given number of items on a given set of localities.

Public Functions

```
constexpr default_distribution_policy() = default
```

Default-construct a new instance of a *default_distribution_policy*. This policy will represent one locality (the local locality).

```
inline default_distribution_policy operator() (std::vector<id_type> locs) const
```

Create a new *default_distribution* policy representing the given set of localities.

Parameters

locs – [in] The list of localities the new instance should represent

```
inline default_distribution_policy operator() (id_type loc) const
```

Create a new *default_distribution* policy representing the given locality

Parameters

loc – [in] The locality the new instance should represent

```
template<typename Component, typename ...Ts>
```

```
inline hpx::future<hpx::id_type> create(Ts&&... vs) const
```

Create one object on one of the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
inline hpx::future<std::vector<bulk_locality_result>> bulk_create(std::size_t count, Ts&&... vs)
                                                    const
```

Create multiple objects on the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses that represent the newly created objects

```
template<typename Action, typename ...Ts>
inline async_result<Action>::type async(launch policy, Ts&&... vs) const
```

```
template<typename Action, typename Callback, typename ...Ts>
inline async_result<Action>::type async_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Continuation, typename ...Ts>
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
inline bool apply(threads::thread_priority priority, Ts&&... vs) const
```

```
template<typename Action, typename Continuation, typename Callback, typename ...Ts>
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

```
inline std::size_t get_num_localities() const
```

Returns the number of associated localities for this distribution policy

Note: This function is part of the creation policy implemented by this class

```
inline hpx::id_type get_next_target() const
```

Returns the locality which is anticipated to be used for the next async operation

```
template<typename Action>
```

```
struct async_result
```

```
    #include <default_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

executors_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors_distributed/distribution_policy_executor.hpp

Defined in header `hpx/executors_distributed/distribution_policy_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Functions

```
template<typename DistPolicy>
distribution_policy_executor(DistPolicy&&) ->
    distribution_policy_executor<std::decay_t<DistPolicy>>
```

```
template<typename DistPolicy> HPX_DEPRECATED_V(1, 9,
    "hpx::parallel::execution::make_distribution_policy_executor is " "deprecated,
    use " "hpx::parallel::execution::distribution_policy_executor instead") distribution_policy_executor
```

Create a new *distribution_policy_executor* from the given *distribution_policy*.

Parameters

policy – The *distribution_policy* to create an executor from

```
template<typename DistPolicy>
```

```
class distribution_policy_executor
```

#include <*distribution_policy_executor.hpp*> A *distribution_policy_executor* creates groups of parallel execution agents that execute in threads implicitly created by the executor and placed on any of the associated localities.

Template Parameters

DistPolicy – The distribution policy type for which an executor should be created. The expression *hpx::traits::is_distribution_policy_v*<*DistPolicy*> must evaluate to true.

include

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/experimental/sandbox.hpp

Defined in header `hpx/experimental/sandbox.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

namespace **sandbox**

Functions

environment_info **detect_environment**()

Detect and return information about the current environment.

inline void **describe_environment**(*std::ostream* &os)

Print a formatted environment report.

template<typename **F**>

double **measure**(*F* &&fn, *std::size_t* iterations = 5)

Measure the mean execution time of a callable.

template<typename **SeqFn**, typename **ParFn**>

benchmark_report **benchmark**(*std::string* label, *SeqFn* &&seq_fn, *ParFn* &&par_fn, *std::size_t* iterations = 5)

Compare sequential and parallel execution of the same work.

struct **benchmark_report**

#include <sandbox.hpp> Holds the results of a comparative benchmark.

Public Functions

void **print**(*std::ostream* &os) const

Print a formatted benchmark report.

Parameters

os – Output stream.

Public Members

`std::string label`

User-provided description.

`std::size_t iterations = 0`

Measurement iterations.

`double seq_mean_ms = 0.0`

Sequential mean time (ms)

`double par_mean_ms = 0.0`

Parallel mean time (ms)

`double speedup = 0.0`

$\text{seq_time} / \text{par_time}$

`double efficiency_pct = 0.0`

$(\text{speedup} / \text{workers}) * 100$

`std::size_t num_workers = 0`

HPX workers during measurement.

struct **environment_info**

#include <sandbox.hpp> Describes the hardware and runtime environment.

Public Functions

void **print**(`std::ostream &os`) const

Print a formatted environment report.

Parameters

os – Output stream.

Public Members

`std::size_t cores = 0`

Physical CPU cores.

`std::size_t pus = 0`

Processing units (hardware threads)

`std::size_t numa_nodes = 0`

NUMA domains.

```
std::size_t hpx_workers = 0
```

Active HPX worker threads.

```
bool is_sandbox = false
```

Likely constrained environment.

init_runtime

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/hpx_start.hpp

Defined in header `hpx/hpx_start.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

hpx/hpx_init.hpp

Defined in header `hpx/hpx_init.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

hpx::init_params

Defined in header `hpx/init.hpp`⁸¹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    struct init_params
```

```
        #include <hpx_init_params.hpp> Parameters used to initialize the HPX runtime through hpx::init and hpx::start.
```

⁸¹⁵ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Public Functions

inline **init_params()**

Public Members

std::reference_wrapper<hpx::program_options::options_description const> **desc_cmdline** = *hpx::local::detail::default_desc*(HPX_APPLICATION_STRING)

std::vector<std::string> **cfg**

std::function<void()> **startup**

std::function<void()> **shutdown**

hpx::runtime_mode **mode** = *::hpx::runtime_mode::default_*

hpx::resource::partitioner_mode **rp_mode** = *::hpx::resource::partitioner_mode::default_*

hpx::resource::rp_callback_type **rp_callback**

hpx::suspend, hpx::resume

Defined in header [hpx/init.hpp](#)⁸¹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

int **suspend**(*error_code* &ec = *throws*)

Suspend the runtime system.

The function *hpx::suspend* is used to suspend the HPX runtime system. It can only be used when running HPX on a single locality. It will block waiting for all thread pools to be empty. This function only be called when the runtime is running, or already suspended in which case this function will do nothing.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

⁸¹⁶ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Returns

This function will always return zero.

```
int resume(error_code &ec = throws)
```

Resume the HPX runtime system.

The function `hpx::resume` is used to resume the HPX runtime system. It can only be used when running HPX on a single locality. It will block waiting for all thread pools to be resumed. This function only be called when the runtime suspended, or already running in which case this function will do nothing.

Note: As long as `ec` is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter `ec`. Otherwise it throws an instance of `hpx::exception`.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

This function will always return zero.

hpx::init

Defined in header `hpx/init.hpp`⁸¹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx_startup
```

Variables

```
std::function<int(hpx::program_options::variables_map&)> const &get_main_func()
```

```
namespace hpx
```

Functions

```
inline int init(std::function<int(hpx::program_options::variables_map&)> f, int argc, char **argv,  
               init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

⁸¹⁷ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int init(std::function<int(int, char*)> f, int argc, char **argv, init_params const &params =  
    init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int init(int argc, char **argv, init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. This overload expects a user-defined function named `hpx_main` at global scope, which will be used as the entry point for the HPX application.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from `hpx_main` (or 0 when executed in worker mode).

```
inline int init(std::nullptr_t f, int argc, char **argv, init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int init(init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is a simplified main entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings). This overload expects a user-defined function named `hpx_main` at global scope, which will be used as the entry point for the HPX application.

This is a simplified main entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings).

Note: The created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. If not command line arguments are passed, console mode is assumed.

Note: If no command line arguments are passed the HPX runtime system will not support any of the default command line options as described in the section ‘HPX Command Line Options’.

Parameters

params – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from `hpx_main` (or 0 when executed in worker mode).

hpx::finalize, hpx::disconnect

Defined in header `hpx/init.hpp`⁸¹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX API*.

namespace **hpx**

⁸¹⁸ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

Functions

int **finalize**(double shutdown_timeout, double localwait = -1.0, *hpx::error_code* &ec = *throws*)

Main function to gracefully terminate the HPX runtime system.

The function *hpx::finalize* is the main way to (gracefully) exit any HPX application. It must be called at least once, but can be called multiple times as well. However, only the first invocation will have effect. It will notify all connected localities to finish execution. Only after all other localities have exited this function will return, allowing to exit the console locality as well.

During the execution of this function the runtime system will invoke all registered shutdown functions (see *hpx::init*) on all localities.

The default value (-1.0) will try to find a globally set timeout value (can be set as the configuration parameter *hpx.shutdown_timeout*), and if that is not set or -1.0 as well, it will disable any timeout, each connected locality will wait for all existing HPX-threads to terminate.

The default value (-1.0) will try to find a globally set wait time value (can be set as the configuration parameter “*hpx.finalize_wait_time*”), and if this is not set or -1.0 as well, it will disable any addition local wait time before proceeding.

This function will block and wait for all connected localities to exit before returning to the caller. It should be the last HPX-function called by any application.

Using this function is an alternative to *hpx::disconnect*, these functions do not need to be called both.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **shutdown_timeout** – This parameter allows to specify a timeout (in microseconds), specifying how long any of the connected localities should wait for pending tasks to be executed. After this timeout, all suspended HPX-threads will be aborted. Note, that this function will not abort any running HPX-threads. In any case the shutdown will not proceed as long as there is at least one pending/running HPX-thread.
- **localwait** – This parameter allows to specify a local wait time (in microseconds) before the connected localities will be notified and the overall shutdown process starts.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

inline int **finalize**(*hpx::error_code* &ec = *throws*)

Main function to gracefully terminate the HPX runtime system.

The function *hpx::finalize* is the main way to (gracefully) exit any HPX application. It must be called at least once, but can be called multiple times as well. However, only the first invocation will have effect. It will notify all connected localities to finish execution. Only after all other localities have exited this function will return, allowing to exit the console locality as well.

During the execution of this function the runtime system will invoke all registered shutdown functions (see *hpx::init*) on all localities.

This function will block and wait for all connected localities to exit before returning to the caller. It should be the last HPX-function called by any application.

Using this function is an alternative to *hpx::disconnect*, these functions do not need to be called both.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

void **terminate**()

Terminate any application non-gracefully.

The function *hpx::terminate* is the non-graceful way to exit any application immediately. It can be called from any locality and will terminate all localities currently used by the application.

Note: This function will cause HPX to call `std::terminate()` on all localities associated with this application. If the function is called not from an HPX thread it will fail and return an error using the argument *ec*.

int **disconnect**(double shutdown_timeout, double localwait = -1.0, *hpx::error_code* &ec = *throws*)

Disconnect this locality from the application.

The function *hpx::disconnect* can be used to disconnect a locality from a running HPX application.

During the execution of this function the runtime system will invoke all registered shutdown functions (see *hpx::init*) on this locality.

The default value (-1.0) will try to find a globally set timeout value (can be set as the configuration parameter "hpx.shutdown_timeout"), and if that is not set or -1.0 as well, it will disable any timeout, each connected locality will wait for all existing HPX-threads to terminate.

The default value (-1.0) will try to find a globally set wait time value (can be set as the configuration parameter *hpx.finalize_wait_time*), and if this is not set or -1.0 as well, it will disable any addition local wait time before proceeding.

This function will block and wait for this locality to finish executing before returning to the caller. It should be the last HPX-function called by any locality being disconnected.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **shutdown_timeout** – This parameter allows to specify a timeout (in microseconds), specifying how long this locality should wait for pending tasks to be executed. After this timeout, all suspended HPX-threads will be aborted. Note, that this function will not abort any running HPX-threads. In any case the shutdown will not proceed as long as there is at least one pending/running HPX-thread.
- **localwait** – This parameter allows to specify a local wait time (in microseconds) before the connected localities will be notified and the overall shutdown process starts.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

```
inline int disconnect(hpx::error_code &ec = throws)
```

Disconnect this locality from the application.

The function *hpx::disconnect* can be used to disconnect a locality from a running HPX application.

During the execution of this function the runtime system will invoke all registered shutdown functions (see *hpx::init*) on this locality.

This function will block and wait for this locality to finish executing before returning to the caller. It should be the last HPX-function called by any locality being disconnected.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

```
int stop(hpx::error_code &ec = throws)
```

Stop the runtime system.

This function will block and wait for this locality to finish executing before returning to the caller. It should be the last HPX-function called on every locality. This function should be used only if the runtime system was started using *hpx::start*.

Returns

The function returns the value, which has been returned from the user supplied main HPX function (usually *hpx_main*).

hpx::start

Defined in header `hpx/init.hpp`⁸¹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx_startup**

namespace **hpx**

Functions

```
inline bool start(std::function<int(hpx::program_options::variables_map&)> f, int argc, char **argv,
                  init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

⁸¹⁹ http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/init_runtime/include/hpx/init.hpp

```
inline bool start(std::function<int(int, char**)> f, int argc, char **argv, init_params const &params =  
    init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool start(int argc, char **argv, init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise,

it will be executed as specified by the `parametermode`.

Parameters

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool start(std::nullptr_t f, int argc, char **argv, init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter mode is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the `parametermode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool start(init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is a simplified main, non-blocking entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings). It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: The created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. If not command line arguments are passed, console mode is assumed.

Note: If no command line arguments are passed the HPX runtime system will not support any of the default command line options as described in the section 'HPX Command Line Options'.

Parameters

params – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

naming_base

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/naming_base/unmanaged.hpp

Defined in header `hpx/naming_base/unmanaged.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

`hpx::id_type unmanaged(hpx::id_type const &id)`

The helper function `hpx::unmanaged` can be used to generate a global identifier which does not participate in the automatic garbage collection.

Note: This function allows to apply certain optimizations to the process of memory management in HPX. It however requires the user to take full responsibility for keeping the referenced objects alive long enough.

Parameters

id – [in] The id to generated the unmanaged global id from This parameter can be itself a managed or a unmanaged global id.

Returns

This function returns a new global id referencing the same object as the parameter *id*. The only difference is that the returned global identifier does not participate in the automatic garbage collection.

namespace **naming**

parcelset

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/parcelset/message_handler_fwd.hpp

Defined in header `hpx/parcelset/message_handler_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/parcelset/connection_cache.hpp

Defined in header `hpx/parcelset/connection_cache.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/parcelset/parcelset_fwd.hpp

Defined in header `hpx/parcelset/parcelset_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/parcelset/parcelhandler.hpp

Defined in header hpx/parcelset/parcelhandler.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

parcelset_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset_base/parcelset_base_fwd.hpp

Defined in header hpx/parcelset_base/parcelset_base_fwd.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PARCELPORNT_BACKGROUND_MODE_ENUM_DEPRECATION_MSG

namespace **hpx**

namespace **parcelset**

Typedefs

using **parcel_write_handler_type** = *hpx::function*<void(*std::error_code* const&, *parcelset::parcel* const&)>

The type of the function that can be registered as a parcel write handler using the function *hpx::set_parcel_write_handler*.

Note: A parcel write handler is a function which is called by the parcel layer whenever a parcel has been sent by the underlying networking library and if no explicit parcel handler function was specified for the parcel.

Enums

enum class **parcelexport_background_mode** : *std::uint8_t*

Type of background work to perform.

Values:

enumerator **flush_buffers**

perform buffer flush operations

enumerator **send**
 perform send operations (includes buffer flush)

enumerator **receive**
 perform receive operations

enumerator **all**
 perform all operations

Functions

inline bool **operator&**(*parcelport_background_mode* lhs, *parcelport_background_mode* rhs)
 char const ***get_parcelport_background_mode_name**(*parcelport_background_mode* mode)

Variables

parcel **empty_parcel**

constexpr *parcelport_background_mode* **parcelport_background_mode_flush_buffers** =
parcelport_background_mode::flush_buffers

constexpr *parcelport_background_mode* **parcelport_background_mode_send** =
parcelport_background_mode::send

constexpr *parcelport_background_mode* **parcelport_background_mode_receive** =
parcelport_background_mode::receive

constexpr *parcelport_background_mode* **parcelport_background_mode_all** =
parcelport_background_mode::all

hpx/parcelset_base/parcelport.hpp

Defined in header `hpx/parcelset_base/parcelport.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset_base/set_parcel_write_handler.hpp

Defined in header `hpx/parcelset_base/set_parcel_write_handler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

performance_counters

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/performance_counters/registry.hpp

Defined in header `hpx/performance_counters/registry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **performance_counters**

class **registry**

Public Functions

registry() = default

void **clear()**

Reset registry by deleting all stored counter types.

counter_status **add_counter_type**(*counter_info* const &info, *create_counter_func* const
&create_counter, *discover_counters_func* const
&discover_counters, *error_code* &ec = throws)

Add a new performance counter type to the (local) registry.

counter_status **discover_counter_types**(*discover_counter_func* discover_counter,
discover_counters_mode mode, *error_code* &ec =
throws) const

Call the supplied function for all registered counter types.

counter_status **discover_counter_type**(std::string const &fullname, *discover_counter_func*
discover_counter, *discover_counters_mode* mode,
error_code &ec = throws)

Call the supplied function for the given registered counter type.

inline *counter_status* **discover_counter_type**(*counter_info* const &info, *discover_counter_func*
const &f, *discover_counters_mode* mode,
error_code &ec = throws)

counter_status **get_counter_create_function**(*counter_info* const &info, *create_counter_func*
&create_counter, *error_code* &ec = throws)
const

Retrieve the counter creation function which is associated with a given counter type.

counter_status **get_counter_discovery_function**(*counter_info* const &info,
discover_counters_func &func, *error_code*
&ec) const

Retrieve the counter discovery function which is associated with a given counter type.

counter_status **remove_counter_type**(*counter_info* const &info, *error_code* &ec = throws)

Remove an existing counter type from the (local) registry.

Note: This doesn't remove existing counters of this type, it just inhibits defining new counters using this type.

counter_status **create_raw_counter_value**(*counter_info* const &info, *std::int64_t* *countervalue, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance of type *raw_counter* based on given counter value.

counter_status **create_raw_counter**(*counter_info* const &info, *hpx::function<std::int64_t()>* const &f, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance of type *raw_counter* based on given function returning the counter value.

counter_status **create_raw_counter**(*counter_info* const &info, *hpx::function<std::int64_t(bool)>* const &f, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance of type *raw_counter* based on given function returning the counter value.

counter_status **create_raw_counter**(*counter_info* const &info, *hpx::function<std::vector<std::int64_t>()>* const &f, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance of type *raw_counter* based on given function returning the counter value.

counter_status **create_raw_counter**(*counter_info* const &info, *hpx::function<std::vector<std::int64_t>(bool)>* const &f, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance of type *raw_counter* based on given function returning the counter value.

counter_status **create_counter**(*counter_info* const &info, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new performance counter instance based on given counter info.

counter_status **create_statistics_counter**(*counter_info* const &info, *std::string* const &base_counter_name, *std::vector<std::size_t>* const ¶meters, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new statistics performance counter instance based on given base counter name and given base time interval (milliseconds).

counter_status **create_arithmetics_counter**(*counter_info* const &info, *std::vector<std::string>* const &base_counter_names, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new arithmetics performance counter instance based on given base counter names.

counter_status **create_arithmetics_counter_extended**(*counter_info* const &info, *std::vector<std::string>* const &base_counter_names, *naming::gid_type* &id, *error_code* &ec = throws)

Create a new extended arithmetics performance counter instance based on given base counter names.

```
counter_status add_counter(hpx::id_type const &id, counter_info const &info, error_code &ec =  
    throws)
```

Add an existing performance counter instance to the registry.

```
counter_status remove_counter(counter_info const &info, hpx::id_type const &id, error_code  
    &ec = throws)
```

remove the existing performance counter from the registry

```
counter_status get_counter_type(std::string const &name, counter_info &info, error_code &ec  
    = throws)
```

Retrieve counter type information for given counter name.

Public Static Functions

```
static registry &instance()
```

Protected Functions

```
counter_type_map_type::iterator locate_counter_type(std::string const &type_name)
```

```
counter_type_map_type::const_iterator locate_counter_type(std::string const &type_name)  
    const
```

Private Types

```
using counter_type_map_type = std::map<std::string, counter_data>
```

Private Members

```
counter_type_map_type countertypes_
```

```
struct counter_data
```

Public Functions

```
inline counter_data(counter_info const &info, create_counter_func const &create_counter,  
    discover_counters_func const &discover_counters)
```

Public Members

counter_info **info_**

create_counter_func **create_counter_**

discover_counters_func **discover_counters_**

hpx/performance_counters/manage_counter_type.hpp

Defined in header `hpx/performance_counters/manage_counter_type.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **performance_counters**

Functions

counter_status **install_counter_type**(*std::string* const &name, *hpx::function*<*std::int64_t*(bool)>
const &counter_value, *std::string* const &helpertext = "",
std::string const &uom = "", *counter_type* type =
counter_type::raw, *error_code* &ec = *throws*)

Install a new generic performance counter type in a way, which will uninstall it automatically during shutdown.

The function *install_counter_type* will register a new generic counter type based on the provided function. The counter type will be automatically unregistered during system shutdown. Any consumer querying any instance of this counter type will cause the provided function to be called and the returned value to be exposed as the counter value.

The counter type is registered such that there can be one counter instance per locality. The expected naming scheme for the counter instances is: `'/objectname{locality#<*>/total}/countername'` where `'<*>'` is a zero based integer identifying the locality the counter is created on.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: The counter type registry is a locality based service. You will have to register each counter type on every locality where a corresponding performance counter will be created.

Parameters

- **name** – [in] The global virtual name of the counter type. This name is expected to have the format `/objectname/countername`.
- **counter_value** – [in] The function to call whenever the counter value is requested by a consumer.

- **helptext** – [in, optional] A longer descriptive text shown to the user to explain the nature of the counters created from this type.
- **uom** – [in] The unit of measure for the new performance counter type.
- **type** – [in] Type for the new performance counter type.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

If successful, this function returns *valid_data*, otherwise it will either throw an exception or return an *error_code* from the enum *counter_status* (also, see note related to parameter *ec*).

```
counter_status install_counter_type(std::string const &name,  
                                   hpx::function<std::vector<std::int64_t>(bool)> const  
                                   &counter_value, std::string const &helptext = "", std::string  
                                   const &uom = "", error_code &ec = throws)
```

Install a new generic performance counter type returning an array of values in a way, that will uninstall it automatically during shutdown.

The function *install_counter_type* will register a new generic counter type that returns an array of values based on the provided function. The counter type will be automatically unregistered during system shutdown. Any consumer querying any instance of this counter type will cause the provided function to be called and the returned array value to be exposed as the counter value.

The counter type is registered such that there can be one counter instance per locality. The expected naming scheme for the counter instances is: *'/objectname{locality#<*>/total}/countertype'* where *'<*>'* is a zero based integer identifying the locality the counter is created on.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: The counter type registry is a locality based service. You will have to register each counter type on every locality where a corresponding performance counter will be created.

Parameters

- **name** – [in] The global virtual name of the counter type. This name is expected to have the format */objectname/countertype*.
- **counter_value** – [in] The function to call whenever the counter value (array of values) is requested by a consumer.
- **helptext** – [in, optional] A longer descriptive text shown to the user to explain the nature of the counters created from this type.
- **uom** – [in] The unit of measure for the new performance counter type.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

If successful, this function returns *valid_data*, otherwise it will either throw an exception or return an *error_code* from the enum *counter_status* (also, see note related to parameter *ec*).

```
void install_counter_type(std::string const &name, counter_type type, error_code &ec = throws)
```

Install a new performance counter type in a way, which will uninstall it automatically during shutdown.

The function *install_counter_type* will register a new counter type based on the provided

counter_type_info. The counter type will be automatically unregistered during system shutdown.

Note: The counter type registry is a locality based service. You will have to register each counter type on every locality where a corresponding performance counter will be created.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global virtual name of the counter type. This name is expected to have the format /objectname/countertype.
- **type** – [in] The type of the counters of this counter_type.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

If successful, this function returns *valid_data*, otherwise it will either throw an exception or return an error_code from the enum *counter_status* (also, see note related to parameter *ec*).

counter_status **install_counter_type**(*std::string* const &name, *counter_type* type, *std::string* const &helptext, *std::string* const &uom = "", *std::uint32_t* version = *HPX_PERFORMANCE_COUNTER_V1*, *error_code* &ec = *throws*)

Install a new performance counter type in a way, which will uninstall it automatically during shutdown.

The function *install_counter_type* will register a new counter type based on the provided *counter_type_info*. The counter type will be automatically unregistered during system shutdown.

Note: The counter type registry is a locality based service. You will have to register each counter type on every locality where a corresponding performance counter will be created.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global virtual name of the counter type. This name is expected to have the format /objectname/countertype.
- **type** – [in] The type of the counters of this counter_type.
- **helptext** – [in] A longer descriptive text shown to the user to explain the nature of the counters created from this type.
- **uom** – [in] The unit of measure for the new performance counter type.
- **version** – [in] The version of the counter type. This is currently expected to be set to *HPX_PERFORMANCE_COUNTER_V1*.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

If successful, this function returns *valid_data*, otherwise it will either throw an exception or return an error_code from the enum *counter_status* (also, see note related to parameter *ec*).

```
counter_status install_counter_type(std::string const &name, counter_type type, std::string const  
                                     &helptext, create_counter_func const &create_counter,  
                                     discover_counters_func const &discover_counters,  
                                     std::uint32_t version =  
                                     HPX_PERFORMANCE_COUNTER_V1, std::string const  
                                     &uom = "", error_code &ec = throws)
```

Install a new generic performance counter type in a way, which will uninstall it automatically during shutdown.

The function *install_counter_type* will register a new generic counter type based on the provided *counter_type_info*. The counter type will be automatically unregistered during system shutdown.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: The counter type registry is a locality based service. You will have to register each counter type on every locality where a corresponding performance counter will be created.

Parameters

- **name** – [in] The global virtual name of the counter type. This name is expected to have the format /objectname/countertype.
- **type** – [in] The type of the counters of this counter_type.
- **helptext** – [in] A longer descriptive text shown to the user to explain the nature of the counters created from this type.
- **version** – [in] The version of the counter type. This is currently expected to be set to *HPX_PERFORMANCE_COUNTER_V1*.
- **create_counter** – [in] The function which will be called to create a new instance of this counter type.
- **discover_counters** – [in] The function will be called to discover counter instances which can be created.
- **uom** – [in] The unit of measure of the counter type (default: "")
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

If successful, this function returns *valid_data*, otherwise it will either throw an exception or return an *error_code* from the enum *counter_status* (also, see note related to parameter *ec*).

hpx/performance_counters/counters.hpp

Defined in header *hpx/performance_counters/counters.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **performance_counters**

Typedefs

```
typedef hpx::function<naming::gid_type(counter_info const&, error_code&)> create_counter_func
```

This declares the type of a function, which will be called by HPX whenever a new performance counter instance of a particular type needs to be created.

```
typedef hpx::function<bool(counter_info const&, error_code&)> discover_counter_func
```

This declares a type of a function, which will be passed to a *discover_counters_func* in order to be called for each discovered performance counter instance.

```
typedef hpx::function<bool(counter_info const&, discover_counter_func const&,
discover_counters_mode, error_code&)> discover_counters_func
```

This declares the type of a function, which will be called by HPX whenever it needs to discover all performance counter instances of a particular type.

Enums

```
enum class counter_type
```

Values:

```
enumerator text
```

text shows a variable-length text string. It does not deliver calculated values.

Formula: None Average: None Type: Text

```
enumerator raw
```

raw shows the last observed value only. It does not deliver an average.

Formula: None. Shows raw data as collected. Average: None Type: Instantaneous

```
enumerator monotonically_increasing
```

monotonically_increasing shows the cumulatively accumulated observed value. It does not deliver an average.

Formula: None. Shows cumulatively accumulated data as collected. Average: None Type: Instantaneous

```
enumerator average_base
```

average_base is used as the base data (denominator) in the computation of time or count averages for the *counter_type::average_count* and *counter_type::average_timer* counter types. This counter type collects the last observed value only.

Formula: None. This counter uses raw data in fractional calculations without delivering an output. Average: SUM (N) / x Type: Instantaneous

```
enumerator average_count
```

average_count shows how many items are processed, on average, during an operation. Counters of this type display a ratio of the items processed (such as bytes sent) to the number of operations completed. The ratio is calculated by comparing the number of items processed during the last interval to the number of operations completed during the last interval.

Formula: $(N1 - N0) / (D1 - D0)$, where the numerator (N) represents the number of items processed during the last sample interval, and the denominator (D) represents the number of operations completed during the last two sample intervals. Average: $(Nx - N0) / (Dx - D0)$ Type: Average

enumerator **aggregating**

aggregating applies a function to an embedded counter instance. The embedded counter is usually evaluated repeatedly after a fixed (but configurable) time interval.

Formula: $F(Nx)$

enumerator **average_timer**

average_timer measures the average time it takes to complete a process or operation. Counters of this type display a ratio of the total elapsed time of the sample interval to the number of processes or operations completed during that time. This counter type measures time in ticks of the system clock. The variable F represents the number of ticks per second. The value of F is factored into the equation so that the result is displayed in seconds.

Formula: $((N1 - N0) / F) / (D1 - D0)$, where the numerator (N) represents the number of ticks counted during the last sample interval, the variable F represents the frequency of the ticks, and the denominator (D) represents the number of operations completed during the last sample interval. Average: $((Nx - N0) / F) / (Dx - D0)$ Type: Average

enumerator **elapsed_time**

elapsed_time shows the total time between when the component or process started and the time when this value is calculated. The variable F represents the number of time units that elapse in one second. The value of F is factored into the equation so that the result is displayed in seconds.

Formula: $(D0 - N0) / F$, where the nominator (D) represents the current time, the numerator (N) represents the time the object was started, and the variable F represents the number of time units that elapse in one second. Average: $(Dx - N0) / F$ Type: Difference

enumerator **histogram**

histogram exposes a histogram of the measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

The first three values in the returned array represent the lower and upper boundaries, and the size of the histogram buckets. All remaining values in the returned array represent the number of measurements for each of the buckets in the histogram.

enumerator **raw_values**

raw_values exposes an array of measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

enumerator **text**

enumerator **raw**

enumerator **monotonically_increasing**

enumerator **average_base**

enumerator **average_count**

enumerator **aggregating**

enumerator **average_timer**

enumerator **elapsed_time**

enumerator **histogram**

enumerator **raw_values**

raw_values counter exposes an array of measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

enum class **counter_status**

Status and error codes used by the functions related to performance counters.

Values:

enumerator **valid_data**

No error occurred, data is valid.

enumerator **new_data**

Data is valid and different from last call.

enumerator **invalid_data**

Some error occurred, data is not value.

enumerator **already_defined**

The type or instance already has been defined.

enumerator **counter_unknown**

The counter instance is unknown.

enumerator **counter_type_unknown**

The counter type is unknown.

enumerator **generic_error**

A unknown error occurred.

enumerator **valid_data**

enumerator **new_data**

enumerator **invalid_data**

enumerator **already_defined**

enumerator **counter_unknown**

enumerator **counter_type_unknown**

enumerator **generic_error**

Functions

inline bool **status_is_valid**(*counter_status* s)

Variables

constexpr const char **counter_prefix**[] = "/counters"

constexpr *std::size_t* **counter_prefix_len** = *std::size(counter_prefix)* - 1

struct **counter_info**

Public Functions

inline explicit **counter_info**(*counter_type* type = *counter_type::raw*)

inline explicit **counter_info**(*std::string* const &name)

inline **counter_info**(*counter_type* type, *std::string* const &name, *std::string* const &helptext = "",
 std::uint32_t version = *HPX_PERFORMANCE_COUNTER_V1*, *std::string*
 const &uom = "")

Public Members

counter_type **type_**

The type of the described counter.

std::uint32_t **version_**

The version of the described counter using the 0xMMmmSSSS scheme

counter_status **status_**

The status of the counter object.

std::string **fullname_**

The full name of this counter.

std::string **helptext_**

The full descriptive text for this counter.

std::string **unit_of_measure_**

The unit of measure for this counter.

Private Functions

void **serialize**(*serialization::output_archive* &ar, unsigned int) const

void **serialize**(*serialization::input_archive* &ar, unsigned int)

Friends

friend class *hpx::serialization::access*

struct **counter_path_elements** : public *hpx::performance_counters::counter_type_path_elements*

#include <counters.hpp> A *counter_path_elements* holds the elements of a full name for a counter instance. Generally, a full name of a counter instance has the structure:

/objectname{parentinstancename::parentindex/instancename#instanceindex} */counter-name#parameters*

i.e. */queue{localityprefix/thread#2}/length*

Public Types

using **base_type** = *counter_type_path_elements*

Public Functions

inline **counter_path_elements**()

inline **counter_path_elements**(*std::string* const &objectname, *std::string* const &countername, *std::string* const ¶meters, *std::string* const &parentname, *std::string* const &instancename, *std::int64_t* parentindex = -1, *std::int64_t* instanceindex = -1, bool parentinstance_is_basename = false)

inline **counter_path_elements**(*std::string* const &objectname, *std::string* const &countername, *std::string* const ¶meters, *std::string* const &parentname, *std::string* const &instancename, *std::string* const &subinstancename, *std::int64_t* parentindex = -1, *std::int64_t* instanceindex = -1, *std::int64_t* subinstanceindex = -1, bool parentinstance_is_basename = false)

Public Members

std::string **parentinstancename_**
the name of the parent instance

std::string **instancename_**
the name of the object instance

std::string **subinstancename_**
the name of the object sub-instance

std::int64_t **parentinstanceindex_**
the parent instance index

std::int64_t **instanceindex_**
the instance index

std::int64_t **subinstanceindex_**
the sub-instance index

bool **parentinstance_is_basename_**
the parentinstancename_

Private Functions

void **serialize**(*serialization::output_archive* &ar, unsigned int)

void **serialize**(*serialization::input_archive* &ar, unsigned int)

Friends

friend class *hpx::serialization::access*

struct **counter_type_path_elements**

#include <counters.hpp> A *counter_type_path_elements* holds the elements of a full name for a counter type. Generally, a full name of a counter type has the structure:

/objectname/countername

i.e. */queue/length*

Subclassed by *hpx::performance_counters::counter_path_elements*

Public Functions

counter_type_path_elements() = default

inline **counter_type_path_elements**(*std::string* const &objectname, *std::string* const &countername, *std::string* const ¶meters)

Public Members

std::string **objectname_**

the name of the performance object

std::string **countername_**

contains the counter name

std::string **parameters_**

optional parameters for the counter instance

Protected Functions

void **serialize**(*serialization::output_archive* &ar, unsigned int) const

void **serialize**(*serialization::input_archive* &ar, unsigned int)

Friends

friend class `hpx::serialization::access`

struct **counter_value**

Public Functions

inline **counter_value**(*std::int64_t* value = 0, *std::int64_t* scaling = 1, bool scale_inverse = false)

template<typename **T**>

inline **T** **get_value**(*error_code* &ec = *throws*) const

Retrieve the ‘real’ value of the *counter_value*, converted to the requested type *T*.

Public Members

std::uint64_t **time_**

The local time when data was collected.

std::uint64_t **count_**

The invocation counter for the data.

std::int64_t **value_**

The current counter value.

std::int64_t **scaling_**

The scaling of the current counter value.

counter_status **status_**

The status of the counter value.

bool **scale_inverse_**

If true, *value_* needs to be divided by *scaling_*, otherwise it has to be multiplied.

Private Functions

void **serialize**(*serialization::output_archive* &ar, unsigned int const) const

void **serialize**(*serialization::input_archive* &ar, unsigned int const)

Friends

friend class `hpx::serialization::access`

struct **counter_values_array**

Public Functions

inline **counter_values_array**(*std::int64_t* scaling = 1, bool scale_inverse = false)

inline **counter_values_array**(*std::vector<std::int64_t>* &&values, *std::int64_t* scaling = 1, bool scale_inverse = false)

inline **counter_values_array**(*std::vector<std::int64_t>* const &values, *std::int64_t* scaling = 1, bool scale_inverse = false)

template<typename T>

inline T **get_value**(*std::size_t* index, *error_code* &ec = throws) const

Retrieve the ‘real’ value of the *counter_value*, converted to the requested type *T*.

Public Members

std::uint64_t **time_**

The local time when data was collected.

std::uint64_t **count_**

The invocation counter for the data.

std::vector<std::int64_t> **values_**

The current counter values.

std::int64_t **scaling_**

The scaling of the current counter values.

counter_status **status_**

The status of the counter value.

bool **scale_inverse_**

If true, *value_* needs to be divided by *scaling_*, otherwise it has to be multiplied.

Private Functions

void **serialize**(*serialization::output_archive* &ar, unsigned int const) const

void **serialize**(*serialization::input_archive* &ar, unsigned int const)

Friends

friend class *hpx::serialization::access*

hpx/performance_counters/counter_creators.hpp

Defined in header *hpx/performance_counters/counter_creators.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **performance_counters**

Functions

bool **default_counter_discoverer**(*counter_info* const&, *discover_counter_func* const&,
 discover_counters_mode, *error_code*&)

Default discovery function for performance counters; to be registered with the counter types. It will pass the *counter_info* and the *error_code* to the supplied function.

bool **locality_counter_discoverer**(*counter_info* const&, *discover_counter_func* const&,
 discover_counters_mode, *error_code*&)

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

/<objectname>(locality#<locality_id>/total)/<instancename>

bool **locality_pool_counter_discoverer**(*counter_info* const&, *discover_counter_func* const&,
 discover_counters_mode, *error_code*&)

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

/<objectname>(locality#<locality_id>/pool#<pool_name>/total)/<instancename>

bool **locality0_counter_discoverer**(*counter_info* const&, *discover_counter_func* const&,
 discover_counters_mode, *error_code*&)

Default discoverer function for AGAS performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

/<objectname>{locality#0/total}/<instancename>

bool **locality_thread_counter_discoverer**(*counter_info* const&, *discover_counter_func* const&,
 discover_counters_mode, *error_code*&)

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

/<objectname>(locality#<locality_id>/worker-thread#<threadnum>)/<instancename>

```
bool locality_pool_thread_counter_discoverer(counter_info const &info,
                                              discover_counter_func const &f,
                                              discover_counters_mode mode, error_code
                                              &ec)
```

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

```
/<objectname>{locality#<locality_id>/pool#<poolname>/thread#<threadnum>}/<instancename>
```

```
bool locality_pool_thread_no_total_counter_discoverer(counter_info const &info,
                                                       discover_counter_func const &f,
                                                       discover_counters_mode mode,
                                                       error_code &ec)
```

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

```
/<objectname>{locality#<locality_id>/pool#<poolname>/thread#<threadnum>}/<instancename>
```

This is essentially the same as above just that locality#/total is not supported.

```
bool locality_numa_counter_discoverer(counter_info const&, discover_counter_func const&,
                                       discover_counters_mode, error_code&)
```

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

```
/<objectname>(locality#<locality_id>/numa-node#<threadnum>)/<instancename>
```

```
naming::gid_type locality_raw_counter_creator(counter_info const&,
                                                hpx::function<std::int64_t(bool)> const&,
                                                error_code&)
```

Creation function for raw counters. The passed function is encapsulating the actual value to monitor. This function checks the validity of the supplied counter name, it has to follow the scheme:

```
/<objectname>(locality#<locality_id>/total)/<instancename>
```

```
naming::gid_type locality_raw_values_counter_creator(counter_info const&,
                                                        hpx::function<std::vector<std::int64_t>(bool)>
                                                        const&, error_code&)
```

```
naming::gid_type agas_raw_counter_creator(counter_info const&, error_code&, char const*const)
```

Creation function for raw counters. The passed function is encapsulating the actual value to monitor. This function checks the validity of the supplied counter name, it has to follow the scheme:

```
/agas(<objectinstance>/total)/<instancename>
```

```
bool agas_counter_discoverer(counter_info const&, discover_counter_func const&,
                              discover_counters_mode, error_code&)
```

Default discoverer function for performance counters; to be registered with the counter types. It is suitable to be used for all counters following the naming scheme:

```
/agas(<objectinstance>/total)/<instancename>
```

```
naming::gid_type local_action_invocation_counter_creator(counter_info const&,
                                                            error_code&)
```

```
bool local_action_invocation_counter_discoverer(counter_info const&,
                                                discover_counter_func const&,
                                                discover_counters_mode, error_code&)
```

hpx/performance_counters/counters_fwd.hpp

Defined in header `hpx/performance_counters/counters_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

`HPX_COUNTER_TYPE_UNSCOPED_ENUM_DEPRECATION_MSG`

`HPX_COUNTER_STATUS_UNSCOPED_ENUM_DEPRECATION_MSG`

`HPX_DISCOVER_COUNTERS_MODE_UNSCOPED_ENUM_DEPRECATION_MSG`

namespace **hpx**

namespace **performance_counters**

Enums

enum class **counter_type** : *std::uint8_t*

Values:

enumerator **text**

text shows a variable-length text string. It does not deliver calculated values.

Formula: None Average: None Type: Text

enumerator **raw**

raw shows the last observed value only. It does not deliver an average.

Formula: None. Shows raw data as collected. Average: None Type: Instantaneous

enumerator **monotonically_increasing**

monotonically_increasing shows the cumulatively accumulated observed value. It does not deliver an average.

Formula: None. Shows cumulatively accumulated data as collected. Average: None Type: Instantaneous

enumerator **average_base**

average_base is used as the base data (denominator) in the computation of time or count averages for the *counter_type::average_count* and *counter_type::average_timer* counter types. This counter type collects the last observed value only.

Formula: None. This counter uses raw data in fractional calculations without delivering an output. Average: SUM (N) / x Type: Instantaneous

enumerator `average_count`

average_count shows how many items are processed, on average, during an operation. Counters of this type display a ratio of the items processed (such as bytes sent) to the number of operations completed. The ratio is calculated by comparing the number of items processed during the last interval to the number of operations completed during the last interval.

Formula: $(N1 - N0) / (D1 - D0)$, where the numerator (N) represents the number of items processed during the last sample interval, and the denominator (D) represents the number of operations completed during the last two sample intervals. Average: $(Nx - N0) / (Dx - D0)$ Type: Average

enumerator `aggregating`

aggregating applies a function to an embedded counter instance. The embedded counter is usually evaluated repeatedly after a fixed (but configurable) time interval.

Formula: $F(Nx)$

enumerator `average_timer`

average_timer measures the average time it takes to complete a process or operation. Counters of this type display a ratio of the total elapsed time of the sample interval to the number of processes or operations completed during that time. This counter type measures time in ticks of the system clock. The variable F represents the number of ticks per second. The value of F is factored into the equation so that the result is displayed in seconds.

Formula: $((N1 - N0) / F) / (D1 - D0)$, where the numerator (N) represents the number of ticks counted during the last sample interval, the variable F represents the frequency of the ticks, and the denominator (D) represents the number of operations completed during the last sample interval. Average: $((Nx - N0) / F) / (Dx - D0)$ Type: Average

enumerator `elapsed_time`

elapsed_time shows the total time between when the component or process started and the time when this value is calculated. The variable F represents the number of time units that elapse in one second. The value of F is factored into the equation so that the result is displayed in seconds.

Formula: $(D0 - N0) / F$, where the nominator (D) represents the current time, the numerator (N) represents the time the object was started, and the variable F represents the number of time units that elapse in one second. Average: $(Dx - N0) / F$ Type: Difference

enumerator `histogram`

histogram exposes a histogram of the measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

The first three values in the returned array represent the lower and upper boundaries, and the size of the histogram buckets. All remaining values in the returned array represent the number of measurements for each of the buckets in the histogram.

enumerator `raw_values`

raw_values exposes an array of measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

enumerator **text**

enumerator **raw**

enumerator **monotonically_increasing**

enumerator **average_base**

enumerator **average_count**

enumerator **aggregating**

enumerator **average_timer**

enumerator **elapsed_time**

enumerator **histogram**

enumerator **raw_values**

raw_values counter exposes an array of measured values instead of a single value as many of the other counter types. Counters of this type expose a *counter_value_array* instead of a *counter_value*. Those will also not implement the *get_counter_value()* functionality. The results are exposed through a separate *get_counter_values_array()* function.

enum class **counter_status** : *std::uint8_t*

Values:

enumerator **valid_data**

No error occurred, data is valid.

enumerator **new_data**

Data is valid and different from last call.

enumerator **invalid_data**

Some error occurred, data is not value.

enumerator **already_defined**

The type or instance already has been defined.

enumerator **counter_unknown**

The counter instance is unknown.

enumerator **counter_type_unknown**

The counter type is unknown.

enumerator **generic_error**

A unknown error occurred.

enumerator **valid_data**

enumerator **new_data**

enumerator **invalid_data**

enumerator **already_defined**

enumerator **counter_unknown**

enumerator **counter_type_unknown**

enumerator **generic_error**

enum class **discover_counters_mode** : *std::uint8_t*

Values:

enumerator **minimal**

enumerator **full**

Functions

std::string &**ensure_counter_prefix**(*std::string* &name)

std::string **ensure_counter_prefix**(*std::string* const &counter)

std::string &**remove_counter_prefix**(*std::string* &name)

std::string **remove_counter_prefix**(*std::string* const &counter)

inline constexpr bool **operator<**(*counter_type* lhs, *counter_type* rhs) noexcept

inline constexpr bool **operator>**(*counter_type* lhs, *counter_type* rhs) noexcept

char const ***get_counter_type_name**(*counter_type* state)

std::ostream &**operator<<**(*std::ostream* &os, *counter_status* rhs)

counter_status **get_counter_type_name**(*counter_type_path_elements* const &path, *std::string* &result, *error_code* &ec = *throws*)

Create a full name of a counter type from the contents of the given *counter_type_path_elements* instance. The generated counter type name will not contain any parameters.

counter_status **get_full_counter_type_name**(*counter_type_path_elements* const &path, *std::string* &result, *error_code* &ec = *throws*)

Create a full name of a counter type from the contents of the given *counter_type_path_elements* instance. The generated counter type name will contain all parameters.

counter_status **get_counter_name**(*counter_path_elements* const &path, *std::string* &result, *error_code* &ec = *throws*)

Create a full name of a counter from the contents of the given *counter_path_elements* instance.

counter_status **get_counter_instance_name**(*counter_path_elements* const &path, *std::string* &result, *error_code* &ec = *throws*)

Create a name of a counter instance from the contents of the given *counter_path_elements* instance.

counter_status **get_counter_type_path_elements**(*std::string* const &name, *counter_type_path_elements* &path, *error_code* &ec = *throws*)

Fill the given *counter_type_path_elements* instance from the given full name of a counter type.

counter_status **get_counter_path_elements**(*std::string* const &name, *counter_path_elements* &path, *error_code* &ec = *throws*)

Fill the given *counter_path_elements* instance from the given full name of a counter.

counter_status **get_counter_name**(*std::string* const &name, *std::string* &countername, *error_code* &ec = *throws*)

Return the canonical counter instance name from a given full instance name.

counter_status **get_counter_type_name**(*std::string* const &name, *std::string* &type_name, *error_code* &ec = *throws*)

Return the canonical counter type name from a given (full) instance name.

HPX_DEPRECATED_V (1, 9, HPX_DISCOVER_COUNTERS_MODE_UNSCOPED_ENUM_DEPRECATION_MSG) inline const expr discover_counters_

counter_status **complement_counter_info**(*counter_info* &info, *counter_info* const &type_info, *error_code* &ec = *throws*)

Complement the counter info if parent instance name is missing.

counter_status **complement_counter_info**(*counter_info* &info, *error_code* &ec = *throws*)

counter_status **add_counter_type**(*counter_info* const &info, *create_counter_func* const &create_counter, *discover_counters_func* const &discover_counters, *error_code* &ec = *throws*)

counter_status **add_counter_type**(*counter_info* const &info, *error_code* &ec = *throws*)

counter_status **discover_counter_types**(*discover_counter_func* const &discover_counter, *discover_counters_mode* mode = *discover_counters_mode::minimal*, *error_code* &ec = *throws*)

Call the supplied function for each registered counter type.

counter_status **discover_counter_types**(*std::vector<counter_info>* &counters, *discover_counters_mode* mode = *discover_counters_mode::minimal*, *error_code* &ec = *throws*)

Return a list of all available counter descriptions.

```
counter_status discover_counter_type(std::string const &name, discover_counter_func const
&discover_counter, discover_counters_mode mode =
discover_counters_mode::minimal, error_code &ec =
throws)
```

Call the supplied function for the given registered counter type.

```
counter_status discover_counter_type(counter_info const &info, discover_counter_func const
&discover_counter, discover_counters_mode mode =
discover_counters_mode::minimal, error_code &ec =
throws)
```

```
counter_status discover_counter_type(std::string const &name, std::vector<counter_info>
&counters, discover_counters_mode mode =
discover_counters_mode::minimal, error_code &ec =
throws)
```

Return a list of matching counter descriptions for the given registered counter type.

```
counter_status discover_counter_type(counter_info const &info, std::vector<counter_info>
&counters, discover_counters_mode mode =
discover_counters_mode::minimal, error_code &ec =
throws)
```

```
bool expand_counter_info(counter_info const&, discover_counter_func const&, error_code&)
```

call the supplied function will all expanded versions of the supplied counter info.

This function expands all locality#* and worker-thread#* wild cards only.

```
counter_status remove_counter_type(counter_info const &info, error_code &ec = throws)
```

Remove an existing counter type from the (local) registry.

Note: This doesn't remove existing counters of this type, it just inhibits defining new counters using this type.

```
counter_status get_counter_type(std::string const &name, counter_info &info, error_code &ec =
throws)
```

Retrieve the counter type for the given counter name from the (local) registry.

```
hpx::future<hpx::id_type> get_counter_async(std::string name, error_code &ec = throws)
```

Get the global id of an existing performance counter, if the counter does not exist yet, the function attempts to create the counter based on the given counter name.

```
hpx::future<hpx::id_type> get_counter_async(counter_info const &info, error_code &ec = throws)
```

Get the global id of an existing performance counter, if the counter does not exist yet, the function attempts to create the counter based on the given counter info.

```
hpx::id_type get_counter(std::string const &name, error_code &ec)
```

Get the global id of an existing performance counter, if the counter does not exist yet, the function attempts to create the counter based on the given counter name.

```
hpx::id_type get_counter(counter_info const &info, error_code &ec = throws)
```

Get the global id of an existing performance counter, if the counter does not exist yet, the function attempts to create the counter based on the given counter info.

```
void get_counter_infos(counter_info const &info, counter_type &type, std::string &helptext,  
                      std::uint32_t &version, error_code &ec = throws)
```

Retrieve the meta data specific for the given counter instance.

```
void get_counter_infos(std::string name, counter_type &type, std::string &helptext, std::uint32_t  
                      &version, error_code &ec = throws)
```

Retrieve the meta data specific for the given counter instance.

Variables

```
constexpr counter_type counter_text = counter_type::text
```

```
constexpr counter_type counter_raw = counter_type::raw
```

```
constexpr counter_type counter_monotonically_increasing =  
counter_type::monotonically_increasing
```

```
constexpr counter_type counter_average_base = counter_type::average_base
```

```
constexpr counter_type counter_average_count = counter_type::average_count
```

```
constexpr counter_type counter_aggregating = counter_type::aggregating
```

```
constexpr counter_type counter_average_timer = counter_type::average_timer
```

```
constexpr counter_type counter_elapsed_time = counter_type::elapsed_time
```

```
constexpr counter_type counter_raw_values = counter_type::raw_values
```

```
constexpr counter_type counter_histogram = counter_type::histogram
```

```
constexpr counter_status status_valid_data = counter_status::valid_data
```

```
constexpr counter_status status_new_data = counter_status::new_data
```

```
constexpr counter_status status_invalid_data = counter_status::invalid_data
```

```
constexpr counter_status status_already_defined = counter_status::already_defined
```

```
constexpr counter_status status_counter_unknown = counter_status::counter_unknown
```

```
constexpr counter_status status_counter_type_unknown = counter_status::counter_type_unknown
```

```
constexpr counter_status status_generic_error = counter_status::generic_error
```

```
constexpr std::uint32_t HPX_PERFORMANCE_COUNTER_V1 = 0x01000000
```

plugin_factories

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/plugin_factories/plugin_registry.hpp

Defined in header `hpx/plugin_factories/plugin_registry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace plugins
```

```
template<typename Plugin, char const *const Name, char const *const Section, char const *const Suffix>
```

```
struct plugin_registry : public plugin_registry_base
```

#include <plugin_registry.hpp> The `plugin_registry` provides a minimal implementation of a plugin's registry. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a plugin's registry instance.

Template Parameters

Plugin – The plugin type this registry should be responsible for.

Public Functions

```
inline bool get_plugin_info(std::vector<std::string> &fillini) override
```

Return the ini-information for all contained components.

Parameters

fillini – [in] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

hpx/plugin_factories/binary_filter_factory.hpp

Defined in header `hpx/plugin_factories/binary_filter_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

namespace **plugins**

template<typename **BinaryFilter**>

struct **binary_filter_factory** : public binary_filter_factory_base

#include <binary_filter_factory.hpp> The *message_handler_factory* provides a minimal implementation of a message handler's factory. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a message handler's factory instance.

Template Parameters

BinaryFilter – The message handler type this factory should be responsible for.

Public Functions

inline **binary_filter_factory**(*util::section* const *global, *util::section* const *local, bool isenabled)

Construct a new factory instance.

Note: The contents of both sections has to be cloned in order to save the configuration setting for later use.

Parameters

- **global** – [in] The pointer to a *hpx::util::section* instance referencing the settings read from the [settings] section of the global configuration file (hpx.ini) This pointer may be nullptr if no such section has been found.
- **local** – [in] The pointer to a *hpx::util::section* instance referencing the settings read from the section describing this component type: [hpx.components.<name>], where <name> is the instance name of the component as given in the configuration files.
- **isenabled** –

~**binary_filter_factory**() override = default

inline *serialization::binary_filter* ***create**(bool compress, *serialization::binary_filter* *next_filter = nullptr) override

Create a new instance of a message handler

return Returns the newly created instance of the message handler supported by this factory

Protected Attributes

util::section **global_settings_**

util::section **local_settings_**

bool **isenabled_**

hpx/plugin_factories/parcelport_factory.hpp

Defined in header `hpx/plugin_factories/parcelport_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/plugin_factories/message_handler_factory.hpp

Defined in header `hpx/plugin_factories/message_handler_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

runtime_components

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_components/macros.hpp

Defined in header `hpx/runtime_components/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY(...)

HPX_REGISTER_COMPONENT(...)

HPX_REGISTER_ENABLED_COMPONENT_FACTORY(ComponentType, componentname)

HPX_REGISTER_DISABLED_COMPONENT_FACTORY(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_1(...)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_2(ComponentType)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC(...)

HPX_REGISTER_COMPONENT_DYNAMIC(...)

This macro is used create and to register a minimal component factory for a component type which allows it to be remotely created using the `hpx::new_<>` function. This macro can be invoked with one, two or three arguments

HPX_REGISTER_ENABLED_COMPONENT_FACTORY_DYNAMIC(ComponentType, componentname)

HPX_REGISTER_DISABLED_COMPONENT_FACTORY_DYNAMIC(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC(...)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_1(ComponentType)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY(...)

This macro is used create and to register a minimal component registry with Hpx.Plugin.

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC_3(ComponentType, componentname, state)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY(...)

This macro is used create and to register a minimal component factory with Hpx.Plugin. This macro may be used if the registered component factory is the only factory to be exposed from a particular module. If more than one factory needs to be exposed the *HPX_REGISTER_COMPONENT_FACTORY* and *HPX_REGISTER_COMPONENT_MODULE* macros should be used instead.

HPX_REGISTER_DERIVED_COMPONENT_FACTORY(...)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_3(ComponentType, componentname, basecomponentname)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_4(ComponentType, componentname, basecomponentname, state)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC(...)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC(...)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC_3(ComponentType, componentname,
basecomponentname)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC_4(ComponentType, componentname,
basecomponentname, state)

HPX_DISTRIBUTED_METADATA_DECLARATION(...)

HPX_DISTRIBUTED_METADATA_DECLARATION(...)

HPX_DISTRIBUTED_METADATA_DECLARATION_1(config)

HPX_DISTRIBUTED_METADATA_DECLARATION_2(config, name)

HPX_DISTRIBUTED_METADATA(...)

HPX_DISTRIBUTED_METADATA(...)

HPX_DISTRIBUTED_METADATA_1(config)

HPX_DISTRIBUTED_METADATA_2(config, name)

hpx/runtime_components/components_fwd.hpp

Defined in header hpx/runtime_components/components_fwd.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

components::server::runtime_support *get_runtime_support_ptr()

namespace **components**

template<typename **Component**>

struct **component_factory**

namespace **server**

namespace **stubs**

namespace **components**

hpx::new_

Defined in header hpx/components.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

template<typename **Component**, typename ...**Ts**>

auto **new_**(id_type const &locality, *Ts*&&... vs)

Create one or more new instances of the given *Component* type on the specified locality.

This function creates one or more new instances of the given *Component* type on the specified locality and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<hpx::id_type> f =
    hpx::new_<some_component>(hpx::find_here(), ...);
hpx::id_type id = f.get();
```

Parameters

- **locality** – [in] The global address of the locality where the new instance should be created on.
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents a component type (`traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which can be used to retrieve the global address of the newly created component.
- If the explicit template argument *Component* represents a client side object (`traits::is_client<Component>::value` evaluates to true), the function will return a new instance of that type which can be used to refer to the newly created component instance.

```
template<typename Component, typename ...Ts>  
auto local_new(Ts&&... vs)
```

Create one new instance of the given *Component* type on the current locality.

This function creates one new instance of the given *Component* type on the current locality and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<hpx::id_type> f =  
    hpx::local_new<some_component>(...);  
hpx::id_type id = f.get();
```

Note: The difference of this function to `hpx::new_` is that it can be used in cases where the supplied arguments are non-copyable and non-movable. All operations are guaranteed to be local only.

Parameters

- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents a component type (`traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which can be used to retrieve the global address of the newly created component. If the first argument is `hpx::launch::sync` the function will directly return an `hpx::id_type`.
- If the explicit template argument *Component* represents a client side object (`traits::is_client<Component>::value` evaluates to true), the function will

return a new instance of that type which can be used to refer to the newly created component instance.

```
template<typename Component, typename ...Ts>
auto new_(id_type const &locality, std::size_t count, Ts&&... vs)
```

Create multiple new instances of the given **Component** type on the specified locality.

This function creates multiple new instances of the given **Component** type on the specified locality and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<std::vector<hpx::id_type> > f =
    hpx::new_<some_component[]>(hpx::find_here(), 10, ...);
hpx::id_type id = f.get();
```

Parameters

- **locality** – [in] The global address of the locality where the new instance should be created on.
- **count** – [in] The number of component instances to create
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents an array of a component type (i.e. *Component*[], where `traits::is_component<Component>::value` evaluates to true), the function will return an *hpx::future* object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a global address of one of the newly created components.
- If the explicit template argument *Component* represents an array of a client side object type (i.e. *Component*[], where `traits::is_client<Component>::value` evaluates to true), the function will return an *hpx::future* object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a client side instance of the given type, each representing one of the newly created components.

```
template<typename Component, typename DistPolicy, typename ...Ts>
auto new_(DistPolicy const &policy, Ts&&... vs)
```

Create one or more new instances of the given **Component** type based on the given distribution policy.

This function creates one or more new instances of the given **Component** type on the localities defined by the given distribution policy and returns a future object for global address which can be used to reference the new component instance(s).

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<hpx::id_type> f =  
    hpx::new_<some_component>(hpx::default_layout, ...);  
hpx::id_type id = f.get();
```

Parameters

- **policy** – [in] The distribution policy used to decide where to place the newly created.
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents a component type (`traits::is_component<Component>::value` evaluates to true), the function will return an *hpx::future* object instance which can be used to retrieve the global address of the newly created component.
- If the explicit template argument *Component* represents a client side object (`traits::is_client<Component>::value` evaluates to true), the function will return a new instance of that type which can be used to refer to the newly created component instance.

```
template<typename Component, typename DistPolicy, typename ...Ts>  
auto new_(DistPolicy const &policy, std::size_t count, Ts&&... vs)
```

Create multiple new instances of the given *Component* type on the localities as defined by the given distribution policy.

This function creates multiple new instances of the given *Component* type on the localities defined by the given distribution policy and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<std::vector<hpx::id_type> > f =  
    hpx::new_<some_component[]>(hpx::default_layout, 10, ...);  
hpx::id_type id = f.get();
```

Parameters

- **policy** – [in] The distribution policy used to decide where to place the newly created.
- **count** – [in] The number of component instances to create
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents an array of a component type (i.e. *Component*[], where `traits::is_component<Component>::value` evaluates to true), the function will return an *hpx::future* object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a global address of one of the newly created components.
- If the explicit template argument *Component* represents an array of a client side object type (i.e. *Component*[], where `traits::is_client<Component>::value` evaluates to true), the function will return an *hpx::future* object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a client side instance of the given type, each representing one of the newly created components.

HPX_REGISTER_COMPONENT

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

Defines

HPX_REGISTER_COMPONENT(type, name, mode)

Define a component factory for a component type.

This macro is used create and to register a minimal component factory for a component type which allows it to be remotely created using the *hpx::new_<>* function.

This macro can be invoked with one, two or three arguments

Parameters

- **type** – The *type* parameter is a (fully decorated) type of the component type for which a factory should be defined.
- **name** – The *name* parameter specifies the name to use to register the factory. This should uniquely (system-wide) identify the component type. The *name* parameter must conform to the C++ identifier rules (without any namespace). If this parameter is not given, the first parameter is used.
- **mode** – The *mode* parameter has to be one of the defined enumeration values of the enumeration *hpx::components::factory_state*. The default for this parameter is *hpx::components::factory_state::enabled*.

hpx/runtime_components/component_registry.hpp

Defined in header `hpx/runtime_components/component_registry.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **components**

template<typename **Component**, *factory_state* **state**>

```
struct component_registry : public component_registry_base
```

#include <component_registry.hpp> The `component_registry` provides a minimal implementation of a component's registry. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a component's registry instance.

Template Parameters

Component – The component type this registry should be responsible for.

Public Functions

```
inline bool get_component_info(std::vector<std::string> &fillini, std::string const &filepath, bool  
                                is_static = false) override
```

Return the ini-information for all contained components.

Parameters

- **fillini** – [in] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.
- **filepath** –
- **is_static** –

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

```
inline void register_component_type() override
```

Enables this type of registry and sets its destroy mechanism.

runtime_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_distributed.hpp

Defined in header `hpx/runtime_distributed.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

```
class runtime_distributed : public runtime
```

#include <runtime_distributed.hpp> The *runtime* class encapsulates the *HPX* runtime system in a simple to use way. It makes sure all required parts of the *HPX* runtime system are properly initialized.

Public Functions

explicit **runtime_distributed**(util::runtime_configuration &rtcfg, int (*pre_main)(runtime_mode) = nullptr, void (*post_main)() = nullptr)

Construct a new HPX runtime instance

Parameters

- **rtcfg** – Runtime configuration for this instance
- **pre_main** – Function to be called before running the main action of this instance
- **post_main** – Function to be called after running the main action of this instance

~runtime_distributed()

The destructor makes sure all HPX runtime services are properly shut down before exiting.

int **start**(hpx::function<hpx_main_function_type> const &func, bool blocking = false) override

Start the runtime system.

Parameters

- **func** – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*.
- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function *runtime::start* will call *runtime::wait* internally.

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter *func*. Otherwise it will return zero.

int **start**(bool blocking = false) override

Start the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function *runtime::start* will call *runtime::wait* internally .

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter *func*. Otherwise it will return zero.

int **wait**() override

Wait for the shutdown action to be executed.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter *func*.

void **stop**(bool blocking = true) override

Initiate termination of the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.

int **finalize**(double shutdown_timeout) override

void **stop_helper**(bool blocking, std::condition_variable &cond, std::mutex &mtx)

Stop the runtime system, wait for termination.

Parameters

- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.
- **cond** – Condition used to update all thread when done
- **mtx** – Mutex used by this function to sync all threads

int **suspend**() override

Suspend the runtime system.

int **resume**() override

Resume the runtime system.

bool **report_error**(std::size_t num_thread, std::exception_ptr const &e, bool terminate_all = true) override

Report a non-recoverable error to the runtime system.

Parameters

- **num_thread** – [in] The number of the operating system thread the error has been detected in.
- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] Kill all localities attached to the currently running application (default: true)

bool **report_error**(std::exception_ptr const &e, bool terminate_all = true) override

Report a non-recoverable error to the runtime system.

Note: This function will retrieve the number of the current shepherd thread and forward to the `report_error` function above.

Parameters

- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] Kill all localities attached to the currently running application (default: true)

int **run**(hpx::function<hpx_main_function_type> const &func) override

Run the HPX runtime system, use the given function for the main *thread* and block waiting for all threads to finish.

Note: The parameter *func* is optional. If no function is supplied, the runtime system will simply wait for the shutdown action without explicitly executing any main thread.

Parameters

func – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*. This parameter is optional and defaults to none main thread function, in which case all threads have to be scheduled explicitly.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter *func*.

int **run()** override

Run the HPX runtime system, initially use the given number of (OS) threads in the thread-manager and block waiting for all threads to finish.

Returns

This function will always return 0 (zero).

bool **is_networking_enabled()** override

template<typename **F**>

inline *components::server::console_error_dispatcher::sink_type* **set_error_sink**(*F* &&sink)

performance_counters::registry &**get_counter_registry**()

Allow access to the registry counter registry instance used by the HPX runtime.

performance_counters::registry const &**get_counter_registry**() const

Allow access to the registry counter registry instance used by the HPX runtime.

void **register_query_counters**(*std::shared_ptr<util::query_counters>* const &active_counters)

void **start_active_counters**(*error_code* &ec = *throws*) const

void **stop_active_counters**(*error_code* &ec = *throws*) const

void **reset_active_counters**(*error_code* &ec = *throws*) const

void **reinit_active_counters**(bool reset = true, *error_code* &ec = *throws*) const

void **evaluate_active_counters**(bool reset = false, char const *description = nullptr, *error_code* &ec = *throws*) const

void **stop_evaluating_counters**(bool terminate = false) const

agas::addressing_service &**get_agas_client**()

Allow access to the AGAS client instance used by the HPX runtime.

hpx::threads::threadmanager &**get_thread_manager**() override

Allow access to the thread manager instance used by the HPX runtime.

applier::applier &**get_applier**()

Allow access to the applier instance used by the HPX runtime.

std::string **here**() const override

Returns a string of the locality endpoints (usable in debug output)

naming::address_type **get_runtime_support_lva**() const

naming::gid_type **get_next_id**(*std::size_t* count = 1)

void **init_id_pool_range**()

util::unique_id_ranges &**get_id_pool**()

void **initialize_agas**()

Initialize AGAS operation.

void **add_pre_startup_function**(*startup_function_type* f) override

Add a function to be executed inside a HPX thread before `hpx_main` but guaranteed to be executed before any startup function registered with `add_startup_function`.

Note: The difference to a startup function is that all pre-startup functions will be (system-wide) executed before any startup function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to setup the runtime environment of the application (install performance counters, etc.)

void **add_startup_function**(*startup_function_type* f) override

Add a function to be executed inside a HPX thread before `hpx_main`

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to setup the runtime environment of the application (install performance counters, etc.)

void **add_pre_shutdown_function**(*shutdown_function_type* f) override

Add a function to be executed inside a HPX thread during `hpx::finalize`, but guaranteed before any of the shutdown functions is executed.

Note: The difference to a shutdown function is that all pre-shutdown functions will be (system-wide) executed before any shutdown function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

void **add_shutdown_function**(*shutdown_function_type* f) override

Add a function to be executed inside a HPX thread during `hpx::finalize`

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

hpx::util::io_service_pool ***get_thread_pool**(char const *name) override

Access one of the internal thread pools (`io_service` instances) HPX is using to perform specific tasks. The three possible values for the argument `name` are “`main_pool`”, “`io_pool`”, “`parcel_pool`”, and “`timer_pool`”. For any other argument value the function will return zero.

bool **register_thread**(char const *name, *std::size_t* num = 0, bool service_thread = true, *error_code* &ec = *throws*) override

Register an external OS-thread with HPX.

notification_policy_type **get_notification_policy**(char const *prefix, *runtime_local::os_thread_type* type) override

Generate a new notification policy instance for the given thread name `prefix`

std::uint32_t **get_locality_id**(*error_code* &ec) const override

```

std::size_t get_num_worker_threads() const override
std::uint32_t get_num_localities(hpx::launch::sync_policy, error_code &ec) const override
std::uint32_t get_initial_num_localities() const override
hpx::future<std::uint32_t> get_num_localities() const override
std::string get_locality_name() const override
std::uint32_t get_num_localities(hpx::launch::sync_policy, components::component_type type,
                                error_code &ec) const
hpx::future<std::uint32_t> get_num_localities(components::component_type type) const
std::uint32_t assign_cores(std::string const &locality_basename, std::uint32_t num_threads) override
std::uint32_t assign_cores() override

```

Public Static Functions

```

static void register_counter_types()
    Install all performance counters related to this runtime instance.

```

Private Types

```

using used_cores_map_type = std::map<std::string, std::uint32_t>

```

Private Functions

```

threads::thread_result_type run_helper(hpx::function<runtime::hpx_main_function_type> const
                                         &func, int &result)
void init_global_data()
void deinit_global_data()
void wait_helper(std::mutex &mtx, std::condition_variable &cond, bool &running)
void init_tss_helper(char const *context, runtime_local::os_thread_type type, std::size_t
                    local_thread_num, std::size_t global_thread_num, char const *pool_name, char
                    const *postfix, bool service_thread)
void deinit_tss_helper(char const *context, std::size_t num) const
void init_tss_ex(std::string const &locality, char const *context, runtime_local::os_thread_type type,
                 std::size_t local_thread_num, std::size_t global_thread_num, char const
                 *pool_name, char const *postfix, bool service_thread, error_code &ec) const

```

Private Members

runtime_mode **mode_**

util::unique_id_ranges **id_pool_**

agas::addressing_service **agas_client_**

applier::applier **applier_**

used_cores_map_type **used_cores_map_**

std::unique_ptr<components::server::runtime_support> **runtime_support_**

std::shared_ptr<util::query_counters> **active_counters_**

int (***pre_main_**)(*runtime_mode*)

void (***post_main_**)()

Private Static Functions

static void **default_errorsink**(*std::string* const&)

hpx/runtime_distributed/get_locality_name.hpp

Defined in header `hpx/runtime_distributed/get_locality_name.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

future<std::string> **get_locality_name**(*hpx::id_type* const &id)

Return the name of the referenced locality.

This function returns a future referring to the name for the locality of the given id.

See also:

std::string **get_locality_name**()

Parameters

id – [in] The global id of the locality for which the name should be retrieved

Returns

This function returns the name for the locality of the given id. The name is retrieved from the underlying networking layer and may be different for different parcel ports.

hpx/runtime_distributed/applier_fwd.hpp

Defined in header `hpx/runtime_distributed/applier_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **applier**

Functions

applier &**get_applier**()

The function *get_applier* returns a reference to the (thread specific) applier instance.

applier ***get_applier_ptr**()

The function *get_applier* returns a pointer to the (thread specific) applier instance. The returned pointer is NULL if the current thread is not known to HPX or if the runtime system is not active.

namespace **applier**

The namespace *applier* contains all definitions needed for the class `hpx::applier::applier` and its related functionality. This namespace is part of the HPX core module.

hpx::find_root_locality, hpx::find_all_localities, hpx::find_remote_localities

Defined in header `hpx/runtime.hpp`⁸²⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

hpx::id_type **find_root_locality**(*error_code* &*ec* = *throws*)

Return the global id representing the root locality.

The function `find_root_locality()` can be used to retrieve the global id usable to refer to the root locality. The root locality is the locality where the main AGAS service is hosted.

See also:

`hpx::find_all_localities()`, `hpx::find_locality()`

⁸²⁰ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return *hpx::invalid_id* otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id representing the root locality for this application.

`std::vector<hpx::id_type> find_all_localities(error_code &ec = throws)`

Return the list of global ids representing all localities available to this application.

The function `find_all_localities()` can be used to retrieve the global ids of all localities currently available to this application.

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global ids representing the localities currently available to this application.

`std::vector<hpx::id_type> find_remote_localities(error_code &ec = throws)`

Return the list of locality ids of remote localities supporting the given component type. By default this function will return the list of all remote localities (all but the current locality).

The function `find_remote_localities()` can be used to retrieve the global ids of all remote localities currently available to this application (i.e. all localities except the current one).

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

The global ids representing the remote localities currently available to this application.

hpx/runtime_distributed/runtime_fwd.hpp

Defined in header `hpx/runtime_distributed/runtime_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

runtime_distributed &**get_runtime_distributed**()

runtime_distributed *&**get_runtime_distributed_ptr**()

naming::gid_type const &**get_locality**()

The function *get_locality* returns a reference to the locality prefix.

void **start_active_counters**(*error_code* &*ec* = *throws*)

Start all active performance counters, optionally naming the section of code.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **reset_active_counters**(*error_code* &ec = *throws*)

Resets all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **reinit_active_counters**(bool reset = true, *error_code* &ec = *throws*)

Re-initialize all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

- **reset** – [in] Reset the current values before re-initializing counters (default: true)
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **stop_active_counters**(*error_code* &ec = *throws*)

Stop all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **evaluate_active_counters**(bool reset = false, char const *description = nullptr, *error_code* &ec = *throws*)

Evaluate and output all active performance counters, optionally naming the point in code marked by this function.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The output generated by this function is redirected to the destination specified by the corresponding command line options (see `-hpx:print-counter-destination`).

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

- **reset** – [in] this is an optional flag allowing to reset the counter value after it has been evaluated.
- **description** – [in] this is an optional value naming the point in the code marked by the call to this function.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

serialization::binary_filter ***create_binary_filter**(char const *binary_filter_type, bool compress, *serialization::binary_filter* *next_filter = nullptr, *error_code* &ec = *throws*)

Create an instance of a binary filter plugin.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Parameters

- **binary_filter_type** – [in] The type of the binary filter to create
- **compress** – [in] The created filter should support compression
- **next_filter** – [in] Use this as the filter to dispatch the invocation into.

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx/runtime_distributed/applier.hpp

Defined in header `hpx/runtime_distributed/applier.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **applier**

class **applier**

#include <applier.hpp> The *applier* class is used to decide whether a particular action has to be issued on a local or a remote resource. If the target component is local a new *thread* will be created, if the target is remote a parcel will be sent.

Public Functions

applier(*applier* const&) = delete

applier(*applier*&&) = delete

applier &**operator**=(*applier* const&) = delete

applier &**operator**=(*applier*&&) = delete

applier()

void **init**(*threads::threadmanager* &tm)

~applier() = default

void **initialize**(*std::uint64_t* rts)

threads::threadmanager &**get_thread_manager**()

Access the *thread-manager* instance associated with this *applier*.

This function returns a reference to the thread manager this *applier* instance has been created with.

naming::gid_type const &**get_raw_locality**(*error_code* &ec = *throws*) const

Allow access to the locality of the locality this *applier* instance is associated with.

This function returns a reference to the locality this *applier* instance is associated with.

std::uint32_t **get_locality_id**(*error_code* &ec = *throws*) const

Allow access to the id of the locality this *applier* instance is associated with.

This function returns a reference to the id of the locality this *applier* instance is associated with.

bool **get_raw_remote_localities**(*std::vector<naming::gid_type>* &locality_ids,
 components::component_type type =
 to_int(*hpx::components::component_enum_type::invalid*),
 error_code &ec = *throws*) const

Return list of localities of all remote localities registered with the AGAS service for a specific component type.

This function returns a list of all remote localities (all localities known to AGAS except the local one) supporting the given component type.

Parameters

- **locality_ids** – [out] The reference to a vector of `id_type`s filled by the function.
- **type** – [in] The type of the component which needs to exist on the returned localities.

Returns

The function returns *true* if there is at least one remote locality known to the AGAS service (!`prefixes.empty()`).

```
bool get_remote_localities(std::vector<hpx::id_type> &locality_ids,
                          components::component_type type =
                          to_int(hpx::components::component_enum_type::invalid),
                          error_code &ec = throws) const
```

```
bool get_raw_localities(std::vector<naming::gid_type> &locality_ids,
                       components::component_type type =
                       to_int(hpx::components::component_enum_type::invalid)) const
```

Return list of `locality_ids` of all localities registered with the AGAS service for a specific component type.

This function returns a list of all localities (all localities known to AGAS except the local one) supporting the given component type.

Parameters

- **locality_ids** – [out] The reference to a vector of `id_type`s filled by the function.
- **type** – [in] The type of the component which needs to exist on the returned localities.

Returns

The function returns *true* if there is at least one remote locality known to the AGAS service (!`prefixes.empty()`).

```
bool get_localities(std::vector<hpx::id_type> &locality_ids, error_code &ec = throws) const
```

```
bool get_localities(std::vector<hpx::id_type> &locality_ids, components::component_type
                    type, error_code &ec = throws) const
```

```
inline naming::gid_type const &get_runtime_support_raw_gid() const
```

By convention the `runtime_support` has a `gid` identical to the prefix of the locality the `runtime_support` is responsible for

```
inline hpx::id_type const &get_runtime_support_gid() const
```

By convention the `runtime_support` has a `gid` identical to the prefix of the locality the `runtime_support` is responsible for

Private Members

```
threads::threadmanager *thread_manager_
```

```
hpx::id_type runtime_support_id_
```

hpx/runtime_distributed/copy_component.hpp

Defined in header `hpx/runtime_distributed/copy_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

Functions

```
template<typename Component>  
future<hpx::id_type> copy(hpx::id_type const &to_copy)
```

Copy given component to the specified target locality.

The function `copy<Component>` will create a copy of the component referenced by `to_copy` on the locality specified with `target_locality`. It returns a future referring to the newly created component instance.

Note: The new component instance is created on the locality of the component instance which is to be copied.

Parameters

to_copy – [in] The global id of the component to copy

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

```
template<typename Component>  
future<hpx::id_type> copy(hpx::id_type const &to_copy, hpx::id_type const &target_locality)
```

Copy given component to the specified target locality.

The function `copy<Component>` will create a copy of the component referenced by `to_copy` on the locality specified with `target_locality`. It returns a future referring to the newly created component instance.

Parameters

- **to_copy** – [in] The global id of the component to copy
- **target_locality** – [in] The locality where the copy should be created.

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

```
template<typename Derived, typename Stub, typename Data>  
Derived copy(client_base<Derived, Stub, Data> const &to_copy, hpx::id_type const &target_locality =  
hpx::invalid_id)
```

Copy given component to the specified target locality.

The function `copy` will create a copy of the component referenced by the client side object `to_copy` on the locality specified with `target_locality`. It returns a new client side object future referring to the newly created component instance.

Note: If the second argument is omitted (or is `invalid_id`) the new component instance is created on the locality of the component instance which is to be copied.

Parameters

- **to_copy** – [in] The client side object representing the component to copy
- **target_locality** – [in, optional] The locality where the copy should be created (default is same locality as source).

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

hpx/runtime_distributed/find_here.hpp

Defined in header `hpx/runtime_distributed/find_here.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`hpx::id_type find_here(error_code &ec = throws)`

Return the global id representing this locality.

The function `find_here()` can be used to retrieve the global id usable to refer to the current locality.

See also:

`hpx::find_all_localities()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

Note: This function will return meaningful results only if called from an HPX-thread. It will return `hpx::invalid_id` otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

The global id representing the locality this function has been called on.

hpx::find_locality

Defined in header [hpx/runtime.hpp](#)⁸²¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

`std::vector<hpx::id_type> find_all_localities(components::component_type type, error_code &ec = throws)`

Return the list of global ids representing all localities available to this application which support the given component type.

The function `find_all_localities()` can be used to retrieve the global ids of all localities currently available to this application which support the creation of instances of the given component type.

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return the available localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

The global ids representing the localities currently available to this application which support the creation of instances of the given component type. If no localities supporting the given component type are currently available, this function will return an empty vector.

`std::vector<hpx::id_type> find_remote_localities(components::component_type type, error_code &ec = throws)`

⁸²¹ <http://github.com/TheHPXProject/hpx/blob/unknown/libs/full/include/include/hpx/runtime.hpp>

Return the list of locality ids of remote localities supporting the given component type. By default this function will return the list of all remote localities (all but the current locality).

The function `find_remote_localities()` can be used to retrieve the global ids of all remote localities currently available to this application (i.e. all localities except the current one) which support the creation of instances of the given component type.

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return the available remote localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global ids representing the remote localities currently available to this application.

hpx::id_type **find_locality**(*components::component_type* type, *error_code* &ec = *throws*)

Return the global id representing an arbitrary locality which supports the given component type.

The function `find_locality()` can be used to retrieve the global id of an arbitrary locality currently available to this application which supports the creation of instances of the given component type.

See also:

`hpx::find_here()`, `hpx::find_all_localities()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return *hpx::invalid_id* otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return any available locality.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id representing an arbitrary locality currently available to this application which supports the creation of instances of the given component type. If no locality supporting the given component type is currently available, this function will return *hpx::invalid_id*.

hpx/runtime_distributed/get_num_localities.hpp

Defined in header `hpx/runtime_distributed/get_num_localities.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

hpx::future<std::uint32_t> **get_num_localities**(*components::component_type* t)

Asynchronously return the number of localities which are currently registered for the running application.

The function *get_num_localities* asynchronously returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

hpx::find_all_localities, *hpx::get_num_localities*

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

t – The component type for which the number of connected localities should be retrieved.

std::uint32_t **get_num_localities**(*launch::sync_policy*, *components::component_type* t, *error_code* &ec = *throws*)

Synchronously return the number of localities which are currently registered for the running application.

The function *get_num_localities* returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

hpx::find_all_localities, hpx::get_num_localities

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

- **t** – The component type for which the number of connected localities should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx/runtime_distributed/runtime_support.hpp

Defined in header `hpx/runtime_distributed/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **agas**

Functions

```
struct runtime_components_init_interface_functions &runtime_components_init()
```

namespace **components**

Functions

```
struct counter_interface_functions &counter_init()
```

```
class runtime_support : public hpx::components::stubs::runtime_support
```

#include <runtime_support.hpp> The `runtime_support` class is the client side representation of a `server::runtime_support` component

Public Functions

```
inline runtime_support(hpx::id_type const &gid = hpx::invalid_id)
```

Create a client side representation for the existing `server::runtime_support` instance with the given global id *gid*.

```
template<typename Component, typename ...Ts>
```

```
inline hpx::id_type create_component(Ts&&... vs)
```

Create a new component type using the *runtime_support*.

```
template<typename Component, typename ...Ts>
```

```
inline hpx::future<hpx::id_type> create_component_async(Ts&&... vs)
```

Asynchronously create a new component using the *runtime_support*.

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
inline std::vector<hpx::id_type> bulk_create_component(std::size_t count, Ts&&... vs)
```

Asynchronously create N new default constructed components using the *runtime_support*

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
inline hpx::future<std::vector<hpx::id_type>> bulk_create_components_async(std::size_t  
count, Ts&&...  
vs)
```

Asynchronously create a new component using the *runtime_support*.

```
inline hpx::future<int> load_components_async() const
```

```
inline int load_components() const
```

```
inline hpx::future<void> call_startup_functions_async(bool pre_startup) const
```

```
inline void call_startup_functions(bool pre_startup) const
```

```
inline hpx::future<void> shutdown_async(double timeout = -1) const
```

Shutdown the given runtime system.

```
inline void shutdown(double timeout = -1) const
```

```
inline void shutdown_all(double timeout = -1) const
```

Shutdown the runtime systems of all localities.

```
inline hpx::future<void> terminate_async() const
```

Terminate the given runtime system.

```
inline void terminate() const
```

```
inline void terminate_all() const
```

Terminate the runtime systems of all localities.

```
inline void get_config(util::section &ini) const
```

Retrieve configuration information.

```
inline hpx::id_type const &get_id() const
```

```
inline naming::gid_type const &get_raw_gid() const
```

Private Types

```
using base_type = stubs::runtime_support
```

Private Members

`hpx::id_type gid_`

hpx/runtime_distributed/migrate_component.hpp

Defined in header `hpx/runtime_distributed/migrate_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

Functions

```
template<typename Component, typename DistPolicy>
future<hpx::id_type> migrate(hpx::id_type const &to_migrate, [[maybe_unused]] DistPolicy const
                             &policy)
```

Migrate the given component to the specified target locality

The function `migrate<Component>` will migrate the component referenced by `to_migrate` to the locality specified with `target_locality`. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **policy** – [in] A distribution policy which will be used to determine the locality to migrate this object to.

Template Parameters

- **Component** – Specifies the component type of the component to migrate.
- **DistPolicy** – Specifies the distribution policy to use to determine the destination locality.

Returns

A future representing the global id of the migrated component instance. This should be the same as `migrate_to`.

```
template<typename Derived, typename Stub, typename Data, typename DistPolicy>
Derived migrate(client_base<Derived, Stub, Data> const &to_migrate, DistPolicy const &policy)
```

Migrate the given component to the specified target locality

The function `migrate<Component>` will migrate the component referenced by `to_migrate` to the locality specified with `target_locality`. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **policy** – [in] A distribution policy which will be used to determine the locality to migrate this object to.

Template Parameters

- **Derived** – Specifies the component type of the component to migrate.
- **DistPolicy** – Specifies the distribution policy to use to determine the destination locality.

Returns

A future representing the global id of the migrated component instance. This should be the same as `migrate_to`.

```
template<typename Component>
future<hpx::id_type> migrate(hpx::id_type const &to_migrate, hpx::id_type const &target_locality)
```

Migrate the component with the given id to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The global id of the component to migrate.
- **target_locality** – [in] The locality where the component should be migrated to.

Template Parameters

Component – Specifies the component type of the component to migrate.

Returns

A future representing the global id of the migrated component instance. This should be the same as *migrate_to*.

```
template<typename Derived, typename Stub, typename Data>
Derived migrate(client_base<Derived, Stub, Data> const &to_migrate, hpx::id_type const
&target_locality)
```

Migrate the given component to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **target_locality** – [in] The id of the locality to migrate this object to.

Template Parameters

Derived – Specifies the component type of the component to migrate.

Returns

A client side representation of representing of the migrated component instance. This should be the same as *migrate_to*.

hpx/runtime_distributed/server/copy_component.hpp

Defined in header `hpx/runtime_distributed/server/copy_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```

```
        namespace server
```

Functions

```
template<typename Component>
hpx::id_type copy_component_here(hpx::id_type const &to_copy)

template<typename Component>
future<hpx::id_type> copy_component(hpx::id_type const &to_copy, hpx::id_type const
&target_locality)

template<typename Component>

struct copy_component_action : public hpx::actions::action<future<hpx::id_type>
(*)>(hpx::id_type const&, hpx::id_type const&), &copy_component<Component>,
copy_component_action<Component>>

template<typename Component>

struct copy_component_action_here : public hpx::actions::action<hpx::id_type (*)>(hpx::id_type
const&), &copy_component_here<Component>, copy_component_action_here<Component>>
```

hpx/runtime_distributed/server/runtime_support.hpp

Defined in header `hpx/runtime_distributed/server/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **components**

namespace **server**

class **runtime_support**

Public Types

using **type_holder** = *runtime_support*

Public Functions

```
explicit runtime_support(hpx::util::runtime_configuration &cfg)

inline ~runtime_support()

void delete_function_lists()

void tidy()

template<typename Component>
```

naming::gid_type **create_component**()

Actions to create new objects.

template<typename **Component**, typename **T**, typename ...**Ts**>

naming::gid_type **create_component**(*T v, Ts... vs*)

template<typename **Component**, typename ...**Ts**>

std::vector<naming::gid_type> **bulk_create_component**(*std::size_t count, Ts... vs*)

template<typename **Component**, typename ...**Ts**>

std::vector<naming::gid_type> **bulk_create_component_with_count**(*std::size_t count, Ts... vs*)

template<typename **Component**>

naming::gid_type **copy_create_component**(*std::shared_ptr<Component> const &p, bool*)

template<typename **Component**>

naming::gid_type **migrate_component_to_here**(*std::shared_ptr<Component> const &p, hpx::id_type*)

void **shutdown**(double timeout, *hpx::id_type const &respond_to*)

Gracefully shutdown this runtime system instance.

void **shutdown_all**(double timeout)

Gracefully shutdown runtime system instances on all localities.

void **terminate**(*hpx::id_type const &respond_to*)

Shutdown this runtime system instance.

inline void **terminate_act**(*hpx::id_type const &id*)

void **terminate_all**()

Shutdown runtime system instances on all localities.

inline void **terminate_all_act**()

util::section **get_config**()

Retrieve configuration information.

int **load_components**()

Load all components on this locality.

void **call_startup_functions**(bool pre_startup)

void **call_shutdown_functions**(bool pre_shutdown)

void **garbage_collect**()

Force a garbage collection operation in the AGAS layer.

naming::gid_type **create_performance_counter**(*performance_counters::counter_info const &info*)

Create the given performance counter instance.

void **remove_from_connection_cache**(*naming::gid_type const &gid, parcelset::endpoints_type const &eps*)

Remove the given locality from our connection cache.

HPX_DEFINE_COMPONENT_ACTION (*runtime_support*, *terminate_act*,
terminate_action) **HPX_DEFINE_COMPONENT_ACTION**(*runtime_support*
termination detection)

terminate_all_action **HPX_DEFINE_COMPONENT_ACTION** (*runtime_support*,
remove_from_connection_cache) **void run()**

Start the *runtime_support* component.

void wait()

Wait for the *runtime_support* component to notify the calling thread.

This function will be called from the main thread, causing it to block while the HPX functionality is executed. The main thread will block until the *shutdown_action* is executed, which in turn notifies all waiting threads.

void stop(double timeout, *hpx::id_type* const &*respond_to*, bool *remove_from_remote_caches*)

Notify all waiting (blocking) threads allowing the system to be properly stopped.

Note: This function can be called from any thread.

void stopped()

called locally only

void notify_waiting_main()

inline bool **was_stopped()** const

void add_pre_startup_function(*startup_function_type* f)

void add_startup_function(*startup_function_type* f)

void add_pre_shutdown_function(*shutdown_function_type* f)

void add_shutdown_function(*shutdown_function_type* f)

void remove_here_from_connection_cache()

void remove_here_from_console_connection_cache()

Public Members

terminate_all_act

Public Static Functions

static inline *component_type* **get_component_type()**

static inline void **set_component_type**(*component_type* t)

static inline constexpr void **finalize()**

finalize() will be called just before the instance gets destructed

static inline bool **is_target_valid**(*hpx::id_type* const &*id*)

Protected Functions

```
int load_components(util::section &ini, naming::gid_type const &prefix,  
                   agas::addressing_service &agas_client,  
                   hpx::program_options::options_description &options,  
                   std::set<std::string> &startup_handled)  
  
bool load_component(hpx::util::plugin::dll &d, util::section &ini, std::string const &instance,  
                   std::string const &component, filesystem::path const &lib,  
                   naming::gid_type const &prefix, agas::addressing_service  
                   &agas_client, bool isdefault, bool isenabled,  
                   hpx::program_options::options_description &options,  
                   std::set<std::string> &startup_handled)  
  
bool load_component_dynamic(util::section &ini, std::string const &instance, std::string  
                           const &component, filesystem::path lib, naming::gid_type  
                           const &prefix, agas::addressing_service &agas_client, bool  
                           isdefault, bool isenabled,  
                           hpx::program_options::options_description &options,  
                           std::set<std::string> &startup_handled)  
  
bool load_startup_shutdown_functions(hpx::util::plugin::dll &d, error_code &ec)  
  
bool load_commandline_options(hpx::util::plugin::dll &d,  
                              hpx::program_options::options_description &options,  
                              error_code &ec)  
  
bool load_component_static(util::section &ini, std::string const &instance, std::string const  
                           &component, filesystem::path const &lib, naming::gid_type  
                           const &prefix, agas::addressing_service &agas_client, bool  
                           isdefault, bool isenabled,  
                           hpx::program_options::options_description &options,  
                           std::set<std::string> &startup_handled)  
  
bool load_startup_shutdown_functions_static(std::string const &mod, error_code  
                                           &ec)  
  
bool load_commandline_options_static(std::string const &mod,  
                                     hpx::program_options::options_description  
                                     &options, error_code &ec)  
  
bool load_plugins(util::section &ini, hpx::program_options::options_description &options,  
                  std::set<std::string> &startup_handled)  
  
bool load_plugin(hpx::util::plugin::dll &d, util::section &ini, std::string const &instance,  
                 std::string const &component, filesystem::path const &lib, bool isenabled,  
                 hpx::program_options::options_description &options, std::set<std::string>  
                 &startup_handled)  
  
bool load_plugin_dynamic(util::section &ini, std::string const &instance, std::string const  
                        &component, filesystem::path lib, bool isenabled,  
                        hpx::program_options::options_description &options,  
                        std::set<std::string> &startup_handled)
```



```

bool load_plugin_static(util::section &ini, std::string const &instance, std::string const
                        &plugin, bool isenabled,
                        hpx::program_options::options_description &options,
                        std::set<std::string> &startup_handled)

std::size_t dijkstra_termination_detection(std::vector<hpx::id_type> const
                                           &locality_ids)

```

Private Types

```

using plugin_map_mutex_type = hpx::spinlock

using plugin_factory_type = plugin_factory

using plugin_map_type = std::map<std::string, plugin_factory_type>

using modules_map_type = std::map<std::string, hpx::util::plugin::dll>

using static_modules_type = std::vector<static_factory_load_data_type>

```

Private Members

```

std::mutex mtx_

std::condition_variable wait_condition_

std::condition_variable stop_condition_

bool stop_called_

bool stop_done_

bool terminated_

std::thread::id main_thread_id_

std::atomic<bool> shutdown_all_invoked_

plugin_map_mutex_type p_mtx_

plugin_map_type plugins_

modules_map_type &modules_

```

```
static_modules_type static_modules_  
  
hpx::spinlock globals_mtx_  
  
std::list<startup_function_type> pre_startup_functions_  
  
std::list<startup_function_type> startup_functions_  
  
std::list<shutdown_function_type> pre_shutdown_functions_  
  
std::list<shutdown_function_type> shutdown_functions_  
  
struct plugin_factory
```

Public Functions

```
inline plugin_factory(std::shared_ptr<plugins::plugin_factory_base> const &f, bool  
                    enabled)
```

Public Members

```
std::shared_ptr<plugins::plugin_factory_base> first  
  
bool isenabled
```

hpx/runtime_distributed/stubs/runtime_support.hpp

Defined in header `hpx/runtime_distributed/stubs/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx  
  
    namespace components  
  
        namespace stubs  
  
            struct runtime_support  
                Subclassed by hpx::components::runtime_support
```

Public Static Functions

```
template<typename Component, typename ...Ts>
static inline hpx::future<hpx::id_type> create_component_async(hpx::id_type const &gid,
                                                             Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. This is a non-blocking call. The caller needs to call *future::get* on the result of this function to obtain the global id of the newly created object.

```
template<typename Component, typename ...Ts>
static inline hpx::id_type create_component(hpx::id_type const &gid, Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. Block for the creation to finish.

```
template<bool WithCount, typename Component, typename ...Ts>
static inline hpx::future<std::vector<hpx::id_type>> bulk_create_component_colocated_async(hpx::id_type
                                                                                          const
                                                                                          &gid,
                                                                                          std::size_t
                                                                                          count,
                                                                                          Ts&&...
                                                                                          vs)
```

Create multiple new components *type* using the *runtime_support* colocated with the given *targetgid*. This is a non-blocking call.

```
template<bool WithCount, typename Component, typename ...Ts>
static inline std::vector<hpx::id_type> bulk_create_component_colocated(hpx::id_type
                                                                                          const &gid,
                                                                                          std::size_t
                                                                                          count, Ts&&...
                                                                                          vs)
```

Create multiple new components *type* using the *runtime_support* colocated with the given *targetgid*. Block for the creation to finish.

```
template<bool WithCount, typename Component, typename ...Ts>
static inline hpx::future<std::vector<hpx::id_type>> bulk_create_component_async(hpx::id_type
                                                                                          const
                                                                                          &gid,
                                                                                          std::size_t
                                                                                          count,
                                                                                          Ts&&...
                                                                                          vs)
```

Create multiple new components *type* using the *runtime_support* on the given locality. This is a non-blocking call.

```
template<bool WithCount, typename Component, typename ...Ts>
static inline std::vector<hpx::id_type> bulk_create_component(hpx::id_type const &gid,
                                                             std::size_t count, Ts&&...
                                                             vs)
```

Create multiple new components *type* using the *runtime_support* on the given locality. Block for the creation to finish.

```
template<typename Component, typename ...Ts>
static inline hpx::future<hpx::id_type> create_component_colocated_async(hpx::id_type
                                                                                          const &gid,
                                                                                          Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. This is a non-blocking call. The caller needs to call *future::get* on the result of this function to obtain the global id of the newly created object.

```
template<typename Component, typename ...Ts>
static inline hpx::id_type create_component_colocated(hpx::id_type const &gid, Ts&&...
                                                    vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. Block for the creation to finish.

```
template<typename Component>
static inline hpx::future<hpx::id_type> copy_create_component_async(hpx::id_type const
                                                                    &gid,
                                                                    std::shared_ptr<Component>
                                                                    const &p, bool
                                                                    local_op)
```

```
template<typename Component>
static inline hpx::id_type copy_create_component(hpx::id_type const &gid,
                                                    std::shared_ptr<Component> const &p,
                                                    bool local_op)
```

```
template<typename Component>
static inline hpx::future<hpx::id_type> migrate_component_async(hpx::id_type const
                                                                &target_locality,
                                                                std::shared_ptr<Component>
                                                                const &p, hpx::id_type
                                                                const &to_migrate)
```

```
template<typename Component, typename DistPolicy>
static inline hpx::future<hpx::id_type> migrate_component_async(DistPolicy const &policy,
                                                                std::shared_ptr<Component>
                                                                const &p, hpx::id_type
                                                                const &to_migrate)
```

```
template<typename Component, typename Target>
static inline hpx::id_type migrate_component(Target const &target, hpx::id_type const
                                                                &to_migrate, std::shared_ptr<Component>
                                                                const &p)
```

```
static hpx::future<int> load_components_async(hpx::id_type const &gid)
```

```
static int load_components(hpx::id_type const &gid)
```

```
static hpx::future<void> call_startup_functions_async(hpx::id_type const &gid, bool
                                                    pre_startup)
```

```
static void call_startup_functions(hpx::id_type const &gid, bool pre_startup)
```

```
static hpx::future<void> shutdown_async(hpx::id_type const &targetgid, double timeout = -1)
    Shutdown the given runtime system.
```

```
static void shutdown(hpx::id_type const &targetgid, double timeout = -1)
```

```
static void shutdown_all(hpx::id_type const &targetgid, double timeout = -1)
    Shutdown the runtime systems of all localities.
```

```

static void shutdown_all(double timeout = -1)

static hpx::future<void> terminate_async(hpx::id_type const &targetgid)
    Retrieve configuration information.
    Terminate the given runtime system
static void terminate(hpx::id_type const &targetgid)

static void terminate_all(hpx::id_type const &targetgid)
    Terminate the runtime systems of all localities.
static void terminate_all()

static void garbage_collect_non_blocking(hpx::id_type const &targetgid)

static hpx::future<void> garbage_collect_async(hpx::id_type const &targetgid)

static void garbage_collect(hpx::id_type const &targetgid)

static hpx::future<hpx::id_type> create_performance_counter_async(hpx::id_type const
                                                                &targetgid, performance_counters::counter_info
                                                                const &info)

static hpx::id_type create_performance_counter(hpx::id_type const &targetgid,
                                                performance_counters::counter_info
                                                const &info, error_code &ec = throws)

static hpx::future<util::section> get_config_async(hpx::id_type const &targetgid)
    Retrieve configuration information.
static void get_config(hpx::id_type const &targetgid, util::section &ini)

static void remove_from_connection_cache_async(hpx::id_type const &target,
                                                naming::gid_type const &gid,
                                                parcelset::endpoints_type const
                                                &endpoints)

```

segmented_algorithms

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/parallel/segmented_algorithms/is_partitioned.hpp

Defined in header `hpx/parallel/segmented_algorithms/is_partitioned.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred>
bool tag_invoke(hpx::is_partitioned_t, InIter first, InIter last, Pred &&pred)

template<typename ExPolicy, typename SegIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::is_partitioned_t,
                                                                    ExPolicy &&policy, SegIter
                                                                    first, SegIter last, Pred
                                                                    &&pred)
```

hpx/parallel/segmented_algorithms/adjacent_find.hpp

Defined in header `hpx/parallel/segmented_algorithms/adjacent_find.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred>
InIter tag_invoke(hpx::adjacent_find_t, InIter first, InIter last, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::adjacent_find_t,
                                                                    ExPolicy &&policy,
                                                                    SegIter first, SegIter last,
                                                                    Pred &&pred)
```

hpx/parallel/segmented_algorithms/for_each.hpp

Defined in header `hpx/parallel/segmented_algorithms/for_each.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename F>
InIter tag_invoke(hpx::for_each_t, InIter first, InIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::for_each_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)

template<typename InIter, typename Size, typename F>
InIter tag_invoke(hpx::for_each_n_t, InIter first, Size count, F &&f)

template<typename ExPolicy, typename SegIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::for_each_n_t,
ExPolicy &&policy,
SegIter first, Size count,
F &&f)
```

hpx/parallel/segmented_algorithms/replace_copy.hpp

Defined in header `hpx/parallel/segmented_algorithms/replace_copy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter, typename T>
OutIter tag_invoke(hpx::replace_copy_t, SegIter first, SegIter last, OutIter dest, T const &old_value, T
const &new_value)

template<typename ExPolicy, typename SegIter, typename OutIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> tag_invoke(hpx::replace_copy_t,
ExPolicy &&policy,
SegIter first, SegIter last,
OutIter dest, T const
&old_value, T const
&new_value)

template<typename SegIter, typename OutIter, typename Pred, typename T>
OutIter tag_invoke(hpx::replace_copy_if_t, SegIter first, SegIter last, OutIter dest, Pred &&pred, T
const &new_value)

template<typename ExPolicy, typename SegIter, typename OutIter, typename Pred, typename T>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> tag_invoke(hpx::replace_copy_if_t,
                                                                              ExPolicy &&policy,
                                                                              SegIter first, SegIter last,
                                                                              OutIter dest, Pred
                                                                              &&pred, T const
                                                                              &new_value)
```

hpx/parallel/segmented_algorithms/transform.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter, typename F>
hpx::parallel::util::in_out_result<SegIter, OutIter> tag_invoke(hpx::transform_t, SegIter first, SegIter
                                                                last, OutIter dest, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename OutIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_out_result<SegIter, OutIter>> tag_invoke(
```

```
template<typename InIter1, typename InIter2, typename OutIter, typename F>
hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter> tag_invoke(hpx::transform_t, InIter1
                                                                first1, InIter1 last1, InIter2
                                                                first2, OutIter dest, F &&f)
```

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename OutIter, typename
F>
```


hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter>> tag

```
template<typename InIter1, typename InIter2, typename OutIter, typename F>
hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter> tag_invoke(hpx::transform_t, InIter1
                                                                    first1, InIter1 last1, InIter2
                                                                    first2, InIter2 last2, OutIter
                                                                    dest, F &&f)
```

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename OutIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter>> tag
```

hpx/parallel/segmented_algorithms/transform_exclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform_exclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename T, typename Op, typename Conv>  
OutIter tag_invoke(hpx::transform_exclusive_scan_t, InIter first, InIter last, OutIter dest, T init, Op  
                    &&op, Conv &&conv)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op,  
typename Conv>  
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::transform_exclusive_scan_t,  
                                ExPolicy &&policy,  
                                FwdIter1 first, FwdIter1  
                                last, FwdIter2 dest, T init,  
                                Op &&op, Conv &&conv)
```

hpx/parallel/segmented_algorithms/minmax.hpp

Defined in header `hpx/parallel/segmented_algorithms/minmax.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

Typedefs

```
template<typename T>  
using minmax_element_result = hpx::parallel::util::min_max_result<T>
```

namespace **segmented**

Typedefs

```
template<typename T>
```

```
using minmax_element_result = hpx::parallel::util::min_max_result<T>
```

Functions

```
template<typename SegIter, typename F>
```

```
SegIter tag_invoke(hpx::min_element_t, SegIter first, SegIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::min_element_t,  
ExPolicy &&policy,  
SegIter first, SegIter last,  
F &&f)
```

```
template<typename SegIter, typename F>
```

```
SegIter tag_invoke(hpx::max_element_t, SegIter first, SegIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::max_element_t,  
ExPolicy &&policy,  
SegIter first, SegIter last,  
F &&f)
```

```
template<typename SegIter, typename F>
```

```
minmax_element_result<SegIter> tag_invoke(hpx::minmax_element_t, SegIter first, SegIter last, F  
&&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<SegIter>> tag_invoke(hpx::minmax_ele  
Ex-  
Pol-  
icy  
&&pol-  
icy,  
Se-  
gIter  
first,  
Se-  
gIter  
last,  
F  
&&f)
```

hpx/parallel/segmented_algorithms/copy.hpp

Defined in header `hpx/parallel/segmented_algorithms/copy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter>
OutIter tag_invoke(hpx::copy_t, SegIter first, SegIter last, OutIter dest)

template<typename ExPolicy, typename SegIter, typename OutIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> tag_invoke(hpx::copy_t, ExPolicy
&&policy, SegIter first,
SegIter last, OutIter
dest)
```

hpx/parallel/segmented_algorithms/mismatch.hpp

Defined in header `hpx/parallel/segmented_algorithms/mismatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>
std::pair<SegIter1, SegIter2> tag_invoke(hpx::mismatch_t, SegIter1 first1, SegIter1 last1, SegIter2
first2, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
hpx::parallel::detail::equal_to>
```

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<SegIter1, SegIter2>> tag_invoke(hpx::mismatch_t,
                                                    Ex-
                                                    Pol-
                                                    icy
                                                    &&pol-
                                                    icy,
                                                    Se-
                                                    gIter1
                                                    first1,
                                                    Se-
                                                    gIter1
                                                    last1,
                                                    Se-
                                                    gIter2
                                                    first2,
                                                    Pred
                                                    &&pred
                                                    =
                                                    Pred())

```

```

template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>
std::pair<SegIter1, SegIter2> tag_invoke(hpx::mismatch_t, SegIter1 first1, SegIter1 last1, SegIter2
                                         first2, SegIter2 last2, Pred &&pred = Pred())

```

```

template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<SegIter1, SegIter2>> tag_invoke(hpx::mismatch_t,
                                                    Ex-
                                                    Pol-
                                                    icy
                                                    &&pol-
                                                    icy,
                                                    Se-
                                                    gIter1
                                                    first1,
                                                    Se-
                                                    gIter1
                                                    last1,
                                                    Se-
                                                    gIter2
                                                    first2,
                                                    Se-
                                                    gIter2
                                                    last2,
                                                    Pred
                                                    &&pred
                                                    =
                                                    Pred())

```

hpx/parallel/segmented_algorithms/adjacent_difference.hpp

Defined in header `hpx/parallel/segmented_algorithms/adjacent_difference.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::adjacent_difference_t,
                                                                              ExPolicy &&policy,
                                                                              FwdIter1 first,
                                                                              FwdIter1 last, FwdIter2
                                                                              dest, Op &&op)
```

```
template<typename InIter1, typename InIter2, typename Op>
InIter2 tag_invoke(hpx::adjacent_difference_t, InIter1 first, InIter1 last, InIter2 dest, Op &&op)
```

hpx/parallel/segmented_algorithms/fill.hpp

Defined in header `hpx/parallel/segmented_algorithms/fill.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename T>
SegIter tag_invoke(hpx::fill_t, SegIter first, SegIter last, T const &value)
```

```
template<typename SegIter, typename Size, typename T>
SegIter tag_invoke(hpx::fill_n_t, SegIter first, Size count, T const &value)
```

```
template<typename ExPolicy, typename SegIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::fill_t, ExPolicy
                                                                              &&policy, SegIter first,
                                                                              SegIter last, T const
                                                                              &value)
```

```
template<typename ExPolicy, typename SegIter, typename Size, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::fill_n_t, ExPolicy
&&policy, SegIter first,
Size count, T const
&value)
```

hpx/parallel/segmented_algorithms/generate.hpp

Defined in header `hpx/parallel/segmented_algorithms/generate.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename F>
SegIter tag_invoke(hpx::generate_t, SegIter first, SegIter last, F &&f)
```

```
template<typename SegIter, typename Size, typename F>
SegIter tag_invoke(hpx::generate_n_t, SegIter first, Size count, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::generate_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename Size, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::generate_n_t, ExPolicy
&&policy, SegIter first, Size
count, F &&f)
```

hpx/parallel/segmented_algorithms/count.hpp

Defined in header `hpx/parallel/segmented_algorithms/count.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename T>
std::iterator_traits<InIter>::difference_type tag_invoke(hpx::count_t, InIter first, InIter last, T const
&value)
```

```
template<typename ExPolicy, typename SegIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, typename std::iterator_traits<SegIter>::difference_type> tag_invo
```

```
template<typename InIter, typename F>
std::iterator_traits<InIter>::difference_type tag_invoke(hpx::count_if_t, InIter first, InIter last, F
&&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, typename std::iterator_traits<SegIter>::difference_type> tag_invo
```

hpx/parallel/segmented_algorithms/inclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/inclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```


namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename Op = std::plus<>>
OutIter tag_invoke(hpx::inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op = Op())

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op = std::plus<>>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::inclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1
    last, FwdIter2 dest, Op
    &&op = Op())

template<typename InIter, typename OutIter, typename Op, typename T>
OutIter tag_invoke(hpx::inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op, T &&init)

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::inclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1
    last, FwdIter2 dest, Op
    &&op, T &&init)
```

hpx/parallel/segmented_algorithms/is_sorted.hpp

Defined in header `hpx/parallel/segmented_algorithms/is_sorted.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred = hpx::parallel::detail::less>
InIter tag_invoke(hpx::is_sorted_until_t, InIter first, InIter last, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::is_sorted_until_t,
    ExPolicy &&policy,
    SegIter first, SegIter last,
    Pred &&pred = Pred())

template<typename InIter, typename Pred = hpx::parallel::detail::less>
bool tag_invoke(hpx::is_sorted_t, InIter first, InIter last, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter, typename Pred = hpx::parallel::detail::less>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::is_sorted_t, ExPolicy
&&policy, SegIter first,
SegIter last, Pred &&pred =
Pred())
```

hpx/parallel/segmented_algorithms/reduce.hpp

Defined in header `hpx/parallel/segmented_algorithms/reduce.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
namespace hpx
```

```
    namespace segmented
```

Functions

```
template<typename InIterB, typename InIterE, typename T, typename F>
T tag_invoke(hpx::reduce_t, InIterB first, InIterE last, T init, F &&f)
```

```
template<typename ExPolicy, typename InIterB, typename InIterE, typename T, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, T> tag_invoke(hpx::reduce_t, ExPolicy &&policy,
InIterB first, InIterE last, T init, F
&&f)
```

hpx/parallel/segmented_algorithms/transform_reduce.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform_reduce.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
    namespace segmented
```

Functions

```
template<typename SegIter, typename T, typename Reduce, typename Convert>
std::decay_t<T> tag_invoke(hpx::transform_reduce_t, SegIter first, SegIter last, T &&init, Reduce
&&red_op, Convert &&conv_op)

template<typename ExPolicy, typename SegIter, typename T, typename Reduce, typename
Convert>
parallel::util::detail::algorithm_result_t<ExPolicy, std::decay_t<T>> tag_invoke(hpx::transform_reduce_t,
ExPolicy &&policy,
SegIter first, SegIter
last, T &&init,
Reduce &&red_op,
Convert
&&conv_op)

template<typename FwdIter1, typename FwdIter2, typename T, typename Reduce, typename
Convert>
T tag_invoke(hpx::transform_reduce_t, FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, T init, Reduce
&&red_op, Convert &&conv_op)

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename
Reduce, typename Convert>
parallel::util::detail::algorithm_result_t<ExPolicy, T> tag_invoke(hpx::transform_reduce_t, ExPolicy
&&policy, FwdIter1 first1,
FwdIter1 last1, FwdIter2 first2, T
init, Reduce &&red_op, Convert
&&conv_op)
```

hpx/parallel/segmented_algorithms/replace.hpp

Defined in header `hpx/parallel/segmented_algorithms/replace.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename T>
SegIter tag_invoke(hpx::replace_t, SegIter first, SegIter last, T const &old_value, T const
&new_value)

template<typename ExPolicy, typename SegIter, typename T>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::replace_t, ExPolicy
&&policy, SegIter first,
SegIter last, T const
&old_value, T const
&new_value)

template<typename SegIter, typename Pred, typename T>
SegIter tag_invoke(hpx::replace_if_t, SegIter first, SegIter last, Pred &&pred, T const &new_value)

template<typename ExPolicy, typename SegIter, typename Pred, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> tag_invoke(hpx::replace_if_t,
ExPolicy &&policy,
SegIter first, SegIter last,
Pred &&pred, T const
&new_value)
```

hpx/parallel/segmented_algorithms/equal.hpp

Defined in header `hpx/parallel/segmented_algorithms/equal.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>
bool tag_invoke(hpx::equal_t, SegIter1 first1, SegIter1 last1, SegIter2 first2, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::equal_t, ExPolicy
&&policy, SegIter1 first1,
SegIter1 last1, SegIter2
first2, Pred &&pred =
Pred())
```

hpx/parallel/segmented_algorithms/all_any_none.hpp

Defined in header `hpx/parallel/segmented_algorithms/all_any_none.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename F>
bool tag_invoke(hpx::none_of_t, InIter first, InIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::none_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)
```

```
template<typename InIter, typename F>
bool tag_invoke(hpx::any_of_t, InIter first, InIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::any_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)
```

```
template<typename InIter, typename F>
bool tag_invoke(hpx::all_of_t, InIter first, InIter last, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> tag_invoke(hpx::all_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)
```

hpx/parallel/segmented_algorithms/exclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/exclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename T, typename Op = std::plus<T>>
OutIter tag_invoke(hpx::exclusive_scan_t, InIter first, InIter last, OutIter dest, T init, Op &&op =
    Op())
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op =
    std::plus<T>>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::exclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1
    last, FwdIter2 dest, T init,
    Op &&op = Op())
```

hpx/parallel/segmented_algorithms/transform_inclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform_inclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename Op, typename Conv>
OutIter tag_invoke(hpx::transform_inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op,
    Conv &&conv)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename
    Conv>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::transform_inclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1
    last, FwdIter2 dest, Op
    &&op, Conv &&conv)
```

```
template<typename InIter, typename OutIter, typename T, typename Op, typename Conv>
OutIter tag_invoke(hpx::transform_inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op,
    Conv &&conv, T init)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op,
    typename Conv>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> tag_invoke(hpx::transform_inclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1 last,
    FwdIter2 dest, Op &&op,
    Conv &&conv, T init)
```

2.10 Contributing to HPX

HPX development happens on Github. The following sections are a collection of useful information related to HPX development.

2.10.1 Contributing to HPX

The main source of information to understand the process of how to contribute to HPX can be found in [this document](#)⁸²². This is a living document that is constantly updated with relevant information.

2.10.2 HPX governance model

The HPX project is a meritocratic, consensus-based community project. Anyone with an interest in the project can join the community, contribute to the project design and participate in the decision making process. [This document](#)⁸²³ describes how that participation takes place and how to set about earning merit within the project community.

2.10.3 Release procedure for HPX

Below is a step by step procedure for making an HPX release. We aim to produce two releases per year: one in March-April, and one in September-October.

This is a living document and may not be totally current or accurate. It is an attempt to capture current practices in making an HPX release. Please update it as appropriate.

One way to use this procedure is to print a copy and check off the lines as they are completed to avoid confusion.

1. Notify developers that a release is imminent.
2. For minor and major releases: create and check out a new branch at an appropriate point on `master` with the name `release-major.minor.X`. `major` and `minor` should be the major and minor versions of the release. For patch releases: check out the corresponding `release-major.minor.X` branch.
3. Write release notes in `docs/sphinx/releases/whats_new_${VERSION}.rst`. Keep adding merged PRs and closed issues to this until just before the release is made. Use `tools/generate_pr_issue_list.sh` to generate the lists. Add the new release notes to the table of contents in `docs/sphinx/releases.rst`.
4. Build the docs, and proof-read them. Update any documentation that may have changed, and correct any typos. Pay special attention to:
 - `$HPX_SOURCE/README.rst`
 - Update grant information
 - `docs/sphinx/releases/whats_new_${VERSION}.rst`
 - `docs/sphinx/about_hpx/people.rst`
 - Update collaborators
 - Update grant information
5. This step does not apply to patch releases. For APEX:

⁸²² <https://github.com/TheHPXProject/hpx/blob/master/.github/CONTRIBUTING.md>

⁸²³ <http://hpx.stellar-group.org/documents/governance/>

- Change the release branch to be the most current release tag available in the APEX `git_external` section in the main `CMakeLists.txt`. Please contact the maintainers of the respective packages to generate a new release to synchronize with the *HPX* release ([APEX⁸²⁴](#)).

6. Make sure `HPX_VERSION_MAJOR/MINOR/SUBMINOR` in `CMakeLists.txt` contain the correct values. Change them if needed.
7. Change version references in `CITATION.cff`. There are two occurrences. Change year in the copyright file under `/libs/core/version/src/version.cpp`.
8. This step does not apply to patch releases. Remove features which have been deprecated for at least 2 releases. This involves removing build options which enable those features from the main `CMakeLists.txt` and also deleting all related code and tests from the main source tree.

The general deprecation policy involves a three-step process we have to go through in order to introduce a breaking change:

- a. First release cycle: add a build option that allows for explicitly disabling any old (now deprecated) code.
- b. Second release cycle: turn this build option OFF by default.
- c. Third release cycle: completely remove the old code.

The main `CMakeLists.txt` contains a comment indicating for which version the breaking change was introduced first. In the case of deprecated features which don't have a replacement yet, we keep them around in case (like `Vc` for example).

9. Update the minimum required versions if necessary (compilers, dependencies, etc.) in `prerequisites.rst`. Update latest tested versions.
10. Verify that the Jenkins setups for the release branch on Rostam are running and do not display any errors.
11. Repeat the following steps until satisfied with the release.
 1. Change `HPX_VERSION_TAG` in `CMakeLists.txt` to `-rcN`, where `N` is the current iteration of this step. Start with `-rc1`.
 2. Create a pre-release on GitHub using the script `tools/roll_release.sh`. This script automatically tag with the corresponding release number. The script requires that you have the STE||AR Group signing key.
 3. This step is not necessary for patch releases. Notify hpx-users@stellar-group.org of the availability of the release candidate. Ask users to test the candidate by checking out the release candidate tag.
 4. Allow at least a week for testing of the release candidate.
 - Use `git merge` when possible, and fall back to `git cherry-pick` when needed. For patch releases `git cherry-pick` is most likely your only choice if there have been significant unrelated changes on master since the previous release.
 - Go back to the first step when enough patches have been added.
 - If there are no more patches, continue to make the final release.
12. Update any occurrences of the latest stable release to refer to the version about to be released. For example, `quickstart.rst` contains instructions to check out the latest stable tag. Make sure that refers to the new version.
13. Add a new entry to the RPM changelog (`cmake/packaging/rpm/Changelog.txt`) with the new version number and a link to the corresponding changelog.
14. Change `HPX_VERSION_TAG` in `CMakeLists.txt` to an empty string.
15. Add the release date to the caption of the current “What’s New” section in the docs, and change the value of `HPX_VERSION_DATE` in `CMakeLists.txt`.

⁸²⁴ <http://github.com/UO-OACISS/xpress-apex>

16. Create a release on GitHub using the script `tools/roll_release.sh`. This script automatically tag the with the corresponding release number. The script requires that you have the STE||AR Group signing key.
17. Update the websites (hpx.stellar-group.org⁸²⁵ and stellar-group.org <<https://stellar-group.org>>). You can login on wordpress through *this page* <<https://hpx.stellar-group.org/wp-login.php>>. You can update the pages with the following:
 - Update links on the downloads page. Link to the release on GitHub.
 - Documentation links on the docs page (link to generated documentation on GitHub Pages). Follow the style of previous releases.
 - A new blog post announcing the release, which links to downloads and the “What’s New” section in the documentation (see previous releases for examples).
18. Merge release branch into master.
19. Post-release cleanup. Create a new pull request against master with the following changes:
 1. Modify the release procedure if necessary.
 2. Change `HPX_VERSION_TAG` in `CMakeLists.txt` back to `-trunk`.
 3. Increment `HPX_VERSION_MINOR` in `CMakeLists.txt`.
20. Update Vcpkg (<https://github.com/Microsoft/vcpkg>) to pull from latest release.
 - Update version number in `CONTROL`
 - Update tag and SHA512 to that of the new release
21. Update spack (<https://github.com/spack/spack>) with the latest HPX package.
 - Update version number in `hpx/package.py` and SHA256 to that of the new release
22. Announce the release on hpx-users@stellar-group.org, stellar@cct.lsu.edu, allcct@cct.lsu.edu, faculty@csc.lsu.edu, faculty@ece.lsu.edu, the *HPX* Slack channel, the STE||AR-GROUP Discord channel, our list of external collaborators, isocpp.org, reddit.com, [HPC Wire](https://hpcwire.com), [Inside HPC](https://insidehpc.com), [Heise Online](https://heiseonline.com), and a CCT press release.
23. Beer and pizza.

2.10.4 Testing *HPX*

To ensure correctness of *HPX*, we ship a large variety of unit and regression tests. The tests are driven by the `CTest`⁸²⁶ tool and are executed automatically on each commit to the *HPX* [Github](https://github.com)⁸²⁷ repository. In addition, it is encouraged to run the test suite manually to ensure proper operation on your target system. If a test fails for your platform, we highly recommend submitting an issue on our [HPX Issues](https://github.com/HPXProject/hpx/issues)⁸²⁸ tracker with detailed information about the target system.

⁸²⁵ <https://hpx.stellar-group.org>

⁸²⁶ <https://gitlab.kitware.com/cmake/community/wikis/doc/ctest/Testing-With-CTest>

⁸²⁷ <https://github.com/TheHPXProject/hpx/>

⁸²⁸ <https://github.com/TheHPXProject/hpx/issues>

Running tests manually

Running the tests manually is as easy as typing `make tests` && `make test`. This will build all tests and run them once the tests are built successfully. After the tests have been built, you can invoke separate tests with the help of the `ctest` command. You can list all available test targets using `make help | grep tests`. Please see the [CTest Documentation](#)⁸²⁹ for further details.

Running performance tests

We run performance tests on Piz Daint for each pull request using Jenkins. To run those performance tests locally or on Piz Daint, a script is provided under `tools/perftests_ci/local_run.sh` (to be run in the build directory specifying the *HPX* source directory as the argument to the script, default is `$HOME/projects/hpx_perftests_ci`).

Adding new performance tests

To add a new performance test, you need to wrap the portion of code to benchmark with `hpx::util::perftests_report`, passing the test name, the executor name and the function to time (can be a lambda). This facility is used to output the time results in a json format (format needed to compare the results and plot them). To effectively print them at the end of your test, call `hpx::util::perftests_print_times`. To see an example of use, see `future_overhead_report.cpp`. Finally, you can add the test to the CI report editing the `hpx_targets` variable for the executable name and the `hpx_test_options` variable for the corresponding options to use for the run in the performance test script `.jenkins/cscs-perftests/launch_perftests.sh`. And then run the `tools/perftests_ci/local_run.sh` script to get a reference json run (use the name of the test) to be added in the `tools/perftests_ci/perftest/references/daint_default` directory.

Issue tracker

If you stumble over a bug or missing feature in *HPX*, please submit an issue to our [HPX Issues](#)⁸³⁰ page. For more information on how to submit support requests or other means of getting in contact with the developers, please see the [Support Website](#)⁸³¹ page.

Continuous testing

In addition to manual testing, we run automated tests on various platforms. We also run tests on all pull requests using both [\[github\]](#). You can see the dashboards [CDash HPX dashboard](#)⁸³².

2.10.5 Using docker for development

Although it can often be useful to set up a local development environment with system-provided or self-built dependencies, [Docker](#)⁸³³ provides a convenient alternative to quickly get all the dependencies needed to start development of *HPX*. Our testing setup on [\[github\]](#) uses a docker image to run all tests.

⁸²⁹ <https://www.cmake.org/cmake/help/latest/manual/ctest.1.html>

⁸³⁰ <https://github.com/TheHPXProject/hpx/issues>

⁸³¹ <https://stellar.cct.lsu.edu/support/>

⁸³² <https://cdash.rostam.cct.lsu.edu/index.php?project=HPX>

⁸³³ <https://www.docker.com>

To get started you need to install [Docker](#)⁸³⁴ using whatever means is most convenient on your system. Once you have [Docker](#)⁸³⁵ installed, you can pull or directly run the docker image. The image is based on Debian and Clang, and can be found on [Docker Hub](#)⁸³⁶. To start a container using the *HPX* build environment, run:

```
$ docker run --interactive --tty stellargroup/build_env:latest bash
```

You are now in an environment where all the *HPX* build and runtime dependencies are present. You can install additional packages according to your own needs. Please see the [Docker Documentation](#)⁸³⁷ for more information on using [Docker](#)⁸³⁸.

Warning: All changes made within the container are lost when the container is closed. If you want files to persist (e.g., the *HPX* source tree) after closing the container, you can bind directories from the host system into the container (see [Docker Documentation \(Bind mounts\)](#)⁸³⁹).

2.10.6 Documentation

This documentation is built using [Sphinx](#)⁸⁴⁰, and an automatically generated API reference using [Doxygen](#)⁸⁴¹ and [Breathe](#)⁸⁴².

We always welcome suggestions on how to improve our documentation, as well as pull requests with corrections and additions.

Prerequisites

To build the *HPX* documentation, you need recent versions of the following packages:

- python3
- sphinx 4.5.0 (Python package)
- sphinx-book-theme (Python package)
- breathe 4.33.1 (Python package)
- doxygen
- sphinxcontrib-bibtex
- sphinx-copybutton

If the [Python](#)⁸⁴³ dependencies are not available through your system package manager, you can install them using the Python package manager `pip`:

```
pip install --user "sphinx<5" sphinx-book-theme breathe sphinxcontrib-bibtex sphinx-
↪ copybutton
```

You may need to set the following CMake variables to make sure CMake can find the required dependencies.

⁸³⁴ <https://www.docker.com>

⁸³⁵ <https://www.docker.com>

⁸³⁶ https://hub.docker.com/r/stellargroup/build_env/

⁸³⁷ <https://docs.docker.com/>

⁸³⁸ <https://www.docker.com>

⁸³⁹ <https://docs.docker.com/storage/bind-mounts/>

⁸⁴⁰ <http://www.sphinx-doc.org>

⁸⁴¹ <https://www.doxygen.org>

⁸⁴² <https://breathe.readthedocs.io/en/latest>

⁸⁴³ <https://www.python.org>

Doxygen_ROOT:PATH

Specifies where to look for the installation of the [Doxygen](https://www.doxygen.org)⁸⁴⁴ tool.

Sphinx_ROOT:PATH

Specifies where to look for the installation of the [Sphinx](http://www.sphinx-doc.org)⁸⁴⁵ tool.

Breathe_APIDOC_ROOT:PATH

Specifies where to look for the installation of the [Breathe](https://breathe.readthedocs.io/en/latest)⁸⁴⁶ tool.

Building documentation

Enable building of the documentation by setting `HPX_WITH_DOCUMENTATION=ON` during [CMake](https://www.cmake.org)⁸⁴⁷ configuration. To build the documentation, build the `docs` target using your build tool. The default output format is HTML documentation. You can choose alternative output formats (single-page HTML, PDF, and man) with the `HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS` CMake option.

Note: If you add new source files to the Sphinx documentation, you have to run CMake again to have the files included in the build.

Style guide

The documentation is written using reStructuredText. These are the conventions used for formatting the documentation:

- Use, at most, 80 characters per line.
- Top-level headings use over- and underlines with `=`.
- Sub-headings use only underlines with characters in decreasing level of importance: `=`, `-` and `..`
- Use sentence case in headings.
- Refer to common terminology using `:term:`Component``.
- Indent content of directives (`.. directive::`) by three spaces.
- For C++ code samples at the end of paragraphs, use `::` and indent the code sample by 4 spaces.
 - For other languages (or if you don't want a colon at the end of the paragraph), use `.. code-block:: language` and indent by three spaces as with other directives.
- Use `.. list-table::` to wrap tables with a lot of text in cells.

⁸⁴⁴ <https://www.doxygen.org>

⁸⁴⁵ <http://www.sphinx-doc.org>

⁸⁴⁶ <https://breathe.readthedocs.io/en/latest>

⁸⁴⁷ <https://www.cmake.org>

API documentation

The source code is documented using Doxygen. If you add new API documentation either to existing or new source files, make sure that you add the documented source files to the `doxygen_dependencies` variable in `docs/CMakeLists.txt`.

Adding new API documentation

When you add new public APIs to *HPX*, follow these guidelines to ensure the documentation is correctly generated and easy to use.

Documenting headers

At the top of a new header file, include the standard Doxygen documentation block. For example, if the new feature is called *my_new_feature*, you should:

- List the name of the new file under `\file`.
- Specify the page name with `\page` (e.g., `hpx:my_new_feature`).
- Reference the existing header that will include your new file under `\headerfile`.

```
/// \file my_new_feature.hpp
/// \page hpx:my_new_feature
/// \headerfile hpx/existing_header_of_new_feature.hpp
```

Adding to the public API reference

For the documentation to appear in the generated API reference, add your new API to `docs/sphinx/api/public_api.rst` under the appropriate table (usually “Functions”) for the relevant header (for example, `hpx/existing_header_of_new_feature.hpp`).

Including examples

Do **not** inline examples in the API reference. If you want to provide an example of how to use the new API, there are two recommended options:

1. **Documentation page option** Edit an existing relevant manual page to explain the new functionality and include a code example. Use this option if you want to provide additional context about how the API works.
2. **Standalone examples option** Create a separate example under `docs/sphinx/examples/`. Examples in this directory are typically more comprehensive and executable, making them suitable for richer or more complex scenarios.

2.10.7 Module structure

This section explains the structure of an *HPX* module.

The tool `create_library_skeleton.py`⁸⁴⁸ can be used to generate a basic skeleton. To create a library skeleton, run the tool in the `libs` subdirectory with the module name as an argument:

```
$ ./create_library_skeleton <lib_name>
```

This creates a skeleton with the necessary files for an *HPX* module. It will not create any actual source files. The structure of this skeleton is as follows:

- `<lib_name>/`
 - `README.rst`
 - `CMakeLists.txt`
 - `cmake`
 - `docs/`
 - * `index.rst`
 - `examples/`
 - * `CMakeLists.txt`
 - `include/`
 - * `hpx/`
 - `<lib_name>`
 - `src/`
 - * `CMakeLists.txt`
 - `tests/`
 - * `CMakeLists.txt`
 - * `unit/`
 - `CMakeLists.txt`
 - * `regressions/`
 - `CMakeLists.txt`
 - * `performance/`
 - `CMakeLists.txt`

A `README.rst` should be always included which explains the basic purpose of the library and a link to the generated documentation.

A main `CMakeLists.txt` is created in the root directory of the module. By default it contains a call to `add_hpx_module` which takes care of most of the boilerplate required for a module. You only need to fill in the source and header files in most cases.

`add_hpx_module` requires a module name. Optional flags are:

Optional single-value arguments are:

- `INSTALL_BINARIES`: Install the resulting library.

⁸⁴⁸ https://github.com/TheHPXProject/hpx/blob/master/libs/create_module_skeleton.py

Optional multi-value arguments-are:

- **SOURCES**: List of source files.
- **HEADERS**: List of header files.
- **COMPAT_HEADERS**: List of compatibility header files.
- **DEPENDENCIES**: Libraries that this module depends on, such as other modules.
- **CMAKE_SUBDIRS**: List of subdirectories to add to the module.

The `include` directory should contain only headers that other libraries need. For each of those headers, an automatic header test to check for self containment will be generated. Private headers should be placed under the `src` directory. This allows for clear separation. The `cmake` subdirectory may include additional [CMake](https://www.cmake.org)⁸⁴⁹ scripts needed to generate the respective build configurations.

Compatibility headers (forwarding headers for headers whose location is changed when creating a module, if moving them from the main library) should be placed in an `include_compatibility` directory. This directory is not created by default.

Documentation is placed in the `docs` folder. A empty skeleton for the index is created, which is picked up by the main build system and will be part of the generated documentation. Each header inside the `include` directory will automatically be processed by Doxygen and included into the documentation.

Tests are placed in suitable subdirectories of `tests`.

When in doubt, consult existing modules for examples on how to structure the module.

Finding circular dependencies

Our CI will perform a check to see if there are circular dependencies between modules. In cases where it's not clear what is causing the circular dependency, running the `cpp-dependencies`⁸⁵⁰ tool manually can be helpful. It can give you detailed information on exactly which files are causing the circular dependency. If you do not have the `cpp-dependencies` tool already installed, one way of obtaining it is by using our docker image. This way you will have exactly the same environment as on the CI. See *Using docker for development* for details on how to use the docker image.

To produce the graph produced by CI run the following command (`HPX_SOURCE` is assumed to hold the path to the *HPX* source directory):

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --graph-cycles circular_dependencies.dot
```

This will produce a `dot` file in the current directory. You can inspect this manually with a text editor. You can also convert this to an image if you have `graphviz` installed:

```
$ dot circular_dependencies.dot -Tsvg -o circular_dependencies.svg
```

This produces an `svg` file in the current directory which shows the circular dependencies. Note that if there are no cycles the image will be empty.

You can use `cpp-dependencies` to print the include paths between two modules.

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest <from> <to>
```

prints all possible paths from the module `<from>` to the module `<to>`. For example, as most modules depend on `config`, the following should give you a long list of paths from `algorithms` to `config`:

⁸⁴⁹ <https://www.cmake.org>

⁸⁵⁰ <https://github.com/tomtom-international/cpp-dependencies>

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest algorithms config
```

The following should report that it can't find a path between the two modules:

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest config algorithms
```

2.11 Releases

2.11.1 List of supported releases

HPX V2.0.0 (TBD)

General changes

Breaking changes

Closed issues

Closed pull requests

HPX V1.11.0 (Jun 30, 2025)

This release is the last version of HPX that supports C++17. Future versions of HPX will require compilation using C++20 or above.

General changes

- Added synchronous versions of all collective operations. Added global predefined communicator objects that are accessible through new APIs: `hpx::collectives::get_world_communicator()` refers to all localities and `hpx::collectives::get_local_communicator()` refers to all threads on the calling locality. We unified the interfaces of the different communicator objects.
- Added `hpx::experimental::run_on_all` allowing to run a given function (possibly concurrently) using a given execution policy.
- Added a helper object `hpx::runtime_manager` that simplifies the initialization of HPX without needing to modify the main function of the application.
- We improved the compatibility with various accelerator frameworks (SYCL, OneAPI).
- Applied build system changes that allow building HPX without any prerequisites. This requires to pass `-DHPX_WITH_FETCH_HWLOC=On` and `-DHPX_WITH_FETCH_BOOST=On` to the [CMake](https://www.cmake.org)⁸⁵¹ configuration.
- We have performed a lot of code cleanup and refactoring to improve the overall code quality and decrease compile times.
- Added the `hpx::contains` and `hpx::contains_subrange` parallel algorithms.
- Adapted many of HPX' parallel algorithms to be usable with senders/receivers.

⁸⁵¹ <https://www.cmake.org>

Breaking changes

- We have moved most of the APIs that were defined in the namespace `hpx::parallel::execution` to the namespace `hpx::execution::experimental`. It was not possible to add compatibility facilities that will allow to continue using the old APIs, applications will have to be changed in order to continue functioning correctly.
- The CMake configuration parameter `HPX_WITH_RUN_MAIN_EVERYWHERE` is now deprecated and will be removed in the future. Use the preprocessor macro `HPX_HAVE_RUN_MAIN_EVERYWHERE` on a target-by-target case instead.
- Removed the dysfunctional libfabric parcelport.
- Removed features that were long deprecated (starting V1.8): - `hpx::flush`, `hpx::endl`, `hpx::async_flush`, `hpx::async_endl` - Various enumerator types are now only available as `class enum` requiring explicit scoped use of the enumerator values - Various non-conforming overloads of parallel algorithms - `hpx::for_loop` and friends (now only available as

`hpx::experimental::for_loop`)

- `hpx::parallel::induction` is now only available as `hpx::experimental::induction`
- `hpx::parallel::reduction` and friends are now only available as `hpx::experimental::reduction`
- `hpx::assertion::source_location` is now only available as `hpx::source_location`
- `hpx::lcos::split_future` is now only available as `hpx::split_future`
- `hpx::lcos::wait` and friends have been removed altogether
- `hpx::lcos::wait_any` and friends are now only available as `hpx::wait_any`
- `hpx::lcos::wait_some` and friends are now only available as `hpx::wait_some`
- `hpx::lcos::wait_each` and friends are now only available as `hpx::wait_each`
- `hpx::lcos::wait_all` and friends are now only available as `hpx::wait_all`
- `hpx::lcos::when_all` and friends are now only available as `hpx::when_all`
- `hpx::lcos::when_any` and friends are now only available as `hpx::when_any`
- `hpx::lcos::when_each` and friends are now only available as `hpx::when_each`
- `hpx::lcos::when_some` and friends are now only available as `hpx::when_some`
- `hpx::util::optional` and related facilities are now only available as `hpx::optional`
- `hpx::util::bind` and related facilities are now only available as `hpx::bind`
- `hpx::util::function` and friends are now only available as `hpx::function`
- `hpx::traits::is_bound_action` and related facilities are now only available as `hpx::is_bound_action`
- `hpx::traits::is_bind_expression` and related facilities are now only available as `hpx::is_bind_expression`
- `hpx::traits::is_placeholder` and related facilities are now only available as `hpx::is_placeholder`
- `hpx::lcos::future` and related facilities are now only available as `hpx::future`
- `hpx::memory::intrusive_ptr` is now only available as `hpx::intrusive_ptr`
- `hpx::lcos::local::barrier` is now only available as `hpx::barrier`
- `hpx::lcos::barrier` is now only available as `hpx::distributed::barrier`

- `hpx::lcos::local::cpp20_binary_semaphore` is now only available as `hpx::detail::binary_semaphore`
- `hpx::lcos::local::condition_variable` and friends are now only available as `hpx::condition_variable`
- `hpx::lcos::local::counting_semaphore` and friends are now only available as `hpx::counting_semaphore`
- `hpx::lcos::local::cpp20_latch` and is now only available as `hpx::latch`
- `hpx::lcos::latch` and is now only available as `hpx::distributed::latch`
- `hpx::lcos::local::upgrade_lock` and friends are now only available as `hpx::upgrade_lock`
- `hpx::lcos::local::mutex` and friends are now only available as `hpx::mutex`
- `hpx::lcos::local::spinlock` and friends are now only available as `hpx::spinlock`
- `hpx::lcos::local::call_once` and friends are now only available as `hpx::call_once`
- `hpx::util::annotated_function` and is now only available as `hpx::annotated_function`
- `hpx::components::abstract_simple_component_base` and is now only available as `hpx::components::abstract_component_base`
- `hpx::naming::id_type` and is now only available as `hpx::id_type`

Closed issues

- [Issue #6699](#)⁸⁵² - Catch lower-level runtime error
- [Issue #6696](#)⁸⁵³ - HPX master breaks with Kokkos
- [Issue #6691](#)⁸⁵⁴ - `minimum_category` doesn't work with custom iterator categories
- [Issue #6681](#)⁸⁵⁵ - build break - missing `';`
- [Issue #6658](#)⁸⁵⁶ - CMake error upon building HPX manually
- [Issue #6648](#)⁸⁵⁷ - Asio V1.34 deprecates `io_context::work`
- [Issue #6640](#)⁸⁵⁸ - `iterator_facade` doesn't work with custom iterator categories
- [Issue #6636](#)⁸⁵⁹ - problem with `hpx::collectives::exclusive_scan`
- [Issue #6623](#)⁸⁶⁰ - HPX serialization error with `std::vector<std::vector<std::vector<float>>>`
- [Issue #6616](#)⁸⁶¹ - Add flux support to HPX to run on El Cap
- [Issue #6615](#)⁸⁶² - Too many fails test after installed hpx
- [Issue #6605](#)⁸⁶³ - Partitionend vector copy constructor is broken

⁸⁵² <https://github.com/TheHPXProject/hpx/issues/6699>

⁸⁵³ <https://github.com/TheHPXProject/hpx/issues/6696>

⁸⁵⁴ <https://github.com/TheHPXProject/hpx/issues/6691>

⁸⁵⁵ <https://github.com/TheHPXProject/hpx/issues/6681>

⁸⁵⁶ <https://github.com/TheHPXProject/hpx/issues/6658>

⁸⁵⁷ <https://github.com/TheHPXProject/hpx/issues/6648>

⁸⁵⁸ <https://github.com/TheHPXProject/hpx/issues/6640>

⁸⁵⁹ <https://github.com/TheHPXProject/hpx/issues/6636>

⁸⁶⁰ <https://github.com/TheHPXProject/hpx/issues/6623>

⁸⁶¹ <https://github.com/TheHPXProject/hpx/issues/6616>

⁸⁶² <https://github.com/TheHPXProject/hpx/issues/6615>

⁸⁶³ <https://github.com/TheHPXProject/hpx/issues/6605>

- [Issue #6586⁸⁶⁴](#) - Bullet points in quick start/installing HPX section in documentation incorrectly rendered
- [Issue #6563⁸⁶⁵](#) - Compilation issues on Grace Hopper
- [Issue #6544⁸⁶⁶](#) - Errors in Public Distributed Api for all_to_all and gather_there
- [Issue #6519⁸⁶⁷](#) - Option `-hpx:queuing=local-priority-lifo` is not configured
- [Issue #6501⁸⁶⁸](#) - HPX 1.10 Failed Linking CXX executable for arm64-osx
- [Issue #5728⁸⁶⁹](#) - Add optional `fetch_content` support for needed Boost libraries

Closed pull requests

- [PR #6716⁸⁷⁰](#) - Fixing some of the reported linker warnings
- [PR #6705⁸⁷¹](#) - Adding gcc/15 to jenkins
- [PR #6701⁸⁷²](#) - Attempting to fix shutdown hang on `exception_info`
- [PR #6698⁸⁷³](#) - Making sure `.hpp.in` files are not being installed
- [PR #6697⁸⁷⁴](#) - Minor docs fix
- [PR #6695⁸⁷⁵](#) - Adding missing `‘;’`
- [PR #6693⁸⁷⁶](#) - Adding llvm/19 and 20 and cmake/4 Jenkins
- [PR #6692⁸⁷⁷](#) - Better implementation of `minimal_category`
- [PR #6690⁸⁷⁸](#) - Fixing bad `#include` in example
- [PR #6689⁸⁷⁹](#) - Fix unreachable code warning in `wait_all`
- [PR #6687⁸⁸⁰](#) - lci pp: change default `ndevices=2` and `progress_type=worker`; improve document
- [PR #6686⁸⁸¹](#) - lci pp: upgrade LCI autofetch target to 1.7.9
- [PR #6685⁸⁸²](#) - Improve `run_on_all` implementation and tests
- [PR #6683⁸⁸³](#) - Fix bad element comparison for `reduce_by_key`
- [PR #6682⁸⁸⁴](#) - Add C++23 `std::generator` equivalence test and fix missing semicolon
- [PR #6680⁸⁸⁵](#) - Add `oneapi` device init workaround

⁸⁶⁴ <https://github.com/TheHPXProject/hpx/issues/6586>

⁸⁶⁵ <https://github.com/TheHPXProject/hpx/issues/6563>

⁸⁶⁶ <https://github.com/TheHPXProject/hpx/issues/6544>

⁸⁶⁷ <https://github.com/TheHPXProject/hpx/issues/6519>

⁸⁶⁸ <https://github.com/TheHPXProject/hpx/issues/6501>

⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/5728>

⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6716>

⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/6705>

⁸⁷² <https://github.com/TheHPXProject/hpx/pull/6701>

⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/6698>

⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6697>

⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6695>

⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6693>

⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6692>

⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6690>

⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6689>

⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6687>

⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/6686>

⁸⁸² <https://github.com/TheHPXProject/hpx/pull/6685>

⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/6683>

⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6682>

⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6680>

- PR #6679⁸⁸⁶ - Fix sycl deprecations
- PR #6678⁸⁸⁷ - Fix oneapi overloads
- PR #6677⁸⁸⁸ - Offer a runtime manager object
- PR #6676⁸⁸⁹ - Mention the HPX book
- PR #6675⁸⁹⁰ - Bump required version of JSON library
- PR #6674⁸⁹¹ - Issue 6631
- PR #6673⁸⁹² - Fix: FindTBB.cmake cannot find correct TBB library. #6504
- PR #6672⁸⁹³ - Update modules.rst
- PR #6670⁸⁹⁴ - Add base template template param to execution_policy
- PR #6669⁸⁹⁵ - Add execution policy support to run_on_all
- PR #6667⁸⁹⁶ - Making sure bound threads are rescheduled on their original core
- PR #6666⁸⁹⁷ - Improve documentation for reduction operations
- PR #6664⁸⁹⁸ - Fix CMake template when fetching Boost
- PR #6663⁸⁹⁹ - More run_on_all overloads
- PR #6662⁹⁰⁰ - Fix “unary minus operator applied to unsigned type” warning
- PR #6661⁹⁰¹ - Adding simple experimental::run_on_all
- PR #6659⁹⁰² - fix(reduce): Initialize accumulator with init instead of first element
- PR #6656⁹⁰³ - Add missing channel_communicator::get_info
- PR #6652⁹⁰⁴ - Adding channel-based ping-pong example
- PR #6650⁹⁰⁵ - Adding constructor overloads to partitioned_vector
- PR #6649⁹⁰⁶ - Remove the use of deprecated asio::io_context::work
- PR #6645⁹⁰⁷ - Fixing collectives::exclusive_scan
- PR #6644⁹⁰⁸ - Update result_type in set_union.hpp

⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6679>

⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6678>

⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6677>

⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6676>

⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6675>

⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/6674>

⁸⁹² <https://github.com/TheHPXProject/hpx/pull/6673>

⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/6672>

⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6670>

⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6669>

⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6667>

⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6666>

⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6664>

⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6663>

⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6662>

⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/6661>

⁹⁰² <https://github.com/TheHPXProject/hpx/pull/6659>

⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/6656>

⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6652>

⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6650>

⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6649>

⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6645>

⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6644>

- PR #6643⁹⁰⁹ - Update result_type in set_union.hpp
- PR #6642⁹¹⁰ - Allowing to use custom iterator tags with iterator_facade
- PR #6641⁹¹¹ - Allowing for zip-iterator to refer to sequences of different length
- PR #6639⁹¹² - docs: Fix spelling in example dictionary
- PR #6638⁹¹³ - Update set_union.hpp
- PR #6637⁹¹⁴ - lci/mpi pp: fix the case when non-zero-copy data is larger than INT_MAX
- PR #6635⁹¹⁵ - Adding simplified reduction overload
- PR #6634⁹¹⁶ - Fixed issue 6634: Unqualified calls to insertion_sort
- PR #6633⁹¹⁷ - Increase timeouts for CircleCI tests
- PR #6630⁹¹⁸ - Fix CPUId test
- PR #6628⁹¹⁹ - Link acllocal with acllocal-1.16 as hwloc asks for it
- PR #6626⁹²⁰ - Fixing MPI parcel port issue exposed by #6623
- PR #6622⁹²¹ - Newbranch:HPX-Based Task Scheduler with CUDA-Quantum Integration & Benchmarking
- PR #6621⁹²² - HPX-Based Task Scheduler with CUDA-Quantum Integration & Benchmarking
- PR #6620⁹²³ - new test: very big tchunk
- PR #6619⁹²⁴ - mpi pp: fix transmission chunk send
- PR #6617⁹²⁵ - Adding support for the Flux job scheduling environment
- PR #6614⁹²⁶ - Fix fallback to module mode for CMake finding Boost
- PR #6613⁹²⁷ - Fix partitioned_vector_handle_values test
- PR #6612⁹²⁸ - Fixing naming convention for pp constant
- PR #6611⁹²⁹ - Fix Hwloc fetch content
- PR #6610⁹³⁰ - Add docs for synchronous collective operations
- PR #6609⁹³¹ - Update perfest CI reference measurements

⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6643>

⁹¹⁰ <https://github.com/TheHPXProject/hpx/pull/6642>

⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/6641>

⁹¹² <https://github.com/TheHPXProject/hpx/pull/6639>

⁹¹³ <https://github.com/TheHPXProject/hpx/pull/6638>

⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/6637>

⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/6635>

⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/6634>

⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/6633>

⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/6630>

⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/6628>

⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/6626>

⁹²¹ <https://github.com/TheHPXProject/hpx/pull/6622>

⁹²² <https://github.com/TheHPXProject/hpx/pull/6621>

⁹²³ <https://github.com/TheHPXProject/hpx/pull/6620>

⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/6619>

⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/6617>

⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/6614>

⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/6613>

⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/6612>

⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/6611>

⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/6610>

⁹³¹ <https://github.com/TheHPXProject/hpx/pull/6609>

- PR #6608⁹³² - Partially support data parallel for_loop
- PR #6607⁹³³ - Cleaning up copy_component facility
- PR #6606⁹³⁴ - Making sure copy_component creates a new gid
- PR #6600⁹³⁵ - Fixing sync collectives
- PR #6599⁹³⁶ - Make HPX_HAVE_RUN_MAIN_EVERYWHERE application specific
- PR #6598⁹³⁷ - Adding synchronous collective operations
- PR #6596⁹³⁸ - Minor fixes and optimizations
- PR #6595⁹³⁹ - Rfa parallel
- PR #6594⁹⁴⁰ - Move get_stack_ptr to source
- PR #6593⁹⁴¹ - Fix outdated documentation and missing flags
- PR #6592⁹⁴² - HPX_HAVE_THREADS_GET_STACK_POINTER to match builtin_frame_address feature test
- PR #6591⁹⁴³ - Feature test for __builtin_frame_address
- PR #6590⁹⁴⁴ - Add device guard for noexcept
- PR #6587⁹⁴⁵ - Fix bullet points in Quickstart
- PR #6585⁹⁴⁶ - Fixed escape characters format to handle warning due to misinterpretation of syntax
- PR #6583⁹⁴⁷ - Execute feature test for at_quick_exit
- PR #6582⁹⁴⁸ - Accommodate for CircleCI reduce available number of cores to two
- PR #6581⁹⁴⁹ - Attempting to work around a Boost.Spirit problem
- PR #6580⁹⁵⁰ - mpi pp: fix messages larger than INT_MAX
- PR #6578⁹⁵¹ - Remove leftovers from libfabric parcelport
- PR #6577⁹⁵² - Download Boost from their own archives, not from Sourceforge
- PR #6576⁹⁵³ - Fix CMake warning issued since CMake V3.30
- PR #6575⁹⁵⁴ - Replace previously downloaded CDash conv.xml with local version

⁹³² <https://github.com/TheHPXProject/hpx/pull/6608>

⁹³³ <https://github.com/TheHPXProject/hpx/pull/6607>

⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/6606>

⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/6600>

⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/6599>

⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/6598>

⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/6596>

⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/6595>

⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6594>

⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/6593>

⁹⁴² <https://github.com/TheHPXProject/hpx/pull/6592>

⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/6591>

⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6590>

⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6587>

⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6585>

⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6583>

⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6582>

⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6581>

⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6580>

⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/6578>

⁹⁵² <https://github.com/TheHPXProject/hpx/pull/6577>

⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/6576>

⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6575>

- PR #6570⁹⁵⁵ - Update exception_list.hpp
- PR #6569⁹⁵⁶ - Update exception_list.hpp
- PR #6567⁹⁵⁷ - Fix vectorization error on copy algorithm
- PR #6566⁹⁵⁸ - lci pp: fix messages larger than INT_MAX
- PR #6565⁹⁵⁹ - Moving most of APIs from hpx::parallel::execution to hpx::execution::experimental
- PR #6564⁹⁶⁰ - Remove superfluous HPX_MOVE()
- PR #6562⁹⁶¹ - Fix doc return type of broadcast_to
- PR #6560⁹⁶² - Fixes for bit_cast on 32bit systems
- PR #6559⁹⁶³ - Making sure that all parcelport counters are unavailable if no networking is needed or configured
- PR #6558⁹⁶⁴ - Remove CSCS CI's
- PR #6556⁹⁶⁵ - Set copyright year in generated files
- PR #6553⁹⁶⁶ - Fix omp vectorization pragma errors
- PR #6551⁹⁶⁷ - Update building_hpx.rst
- PR #6550⁹⁶⁸ - Partitioned vector updates
- PR #6549⁹⁶⁹ - Fix CMake conditionals checking ENV variables
- PR #6548⁹⁷⁰ - Update CONTRIBUTING.md
- PR #6546⁹⁷¹ - Fix incorrect signature of distributed API functions
- PR #6543⁹⁷² - Throwing an exception derived from std::bad_alloc on OOM conditions
- PR #6539⁹⁷³ - Use thread-safe cache in thread_local_caching_allocator
- PR #6537⁹⁷⁴ - Update README.rst
- PR #6531⁹⁷⁵ - More fixes for the Boost package
- PR #6527⁹⁷⁶ - Improve the LCI parcelport documentation
- PR #6525⁹⁷⁷ - Addressing cmake warnings issued starting V3.30

⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6570>

⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6569>

⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6567>

⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6566>

⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6565>

⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6564>

⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/6562>

⁹⁶² <https://github.com/TheHPXProject/hpx/pull/6560>

⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/6559>

⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6558>

⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6556>

⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6553>

⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6551>

⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6550>

⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6549>

⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6548>

⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/6546>

⁹⁷² <https://github.com/TheHPXProject/hpx/pull/6543>

⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/6539>

⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6537>

⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6531>

⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6527>

⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6525>

- PR #6522⁹⁷⁸ - Fixing distance test
- PR #6520⁹⁷⁹ - Adding optional handshakes to acknowledge the received data
- PR #6518⁹⁸⁰ - Make sure that `-hpx:ini` log settings take effect
- PR #6512⁹⁸¹ - Minor cleanup of `future_data`
- PR #6510⁹⁸² - Include Boost as CMake subproject
- PR #6509⁹⁸³ - Add components documentation
- PR #6508⁹⁸⁴ - Fix typo: `s/unititialized/uninitialized/`
- PR #6507⁹⁸⁵ - Update LSU Jenkins libraries to match Rostam 3.0 with RHEL9
- PR #6503⁹⁸⁶ - Fix 2 tests on FreeBSD by initializing `freebsd_envron`
- PR #6499⁹⁸⁷ - Fix crash in `get_executable_filename` on FreeBSD
- PR #6498⁹⁸⁸ - Avoid rewriting `defines.hpp`
- PR #6497⁹⁸⁹ - Contains and `contains_subrange` parallel algorithm implementation GSOC 2024
- PR #6496⁹⁹⁰ - Prevent usage of CMake `try_run` on crosscompiling
- PR #6494⁹⁹¹ - Add unit test cases and fixes for the S/R versions of the parallel algorithms
- PR #6487⁹⁹² - Fixing security vulnerabilities reported by MSVC security checks
- PR #6486⁹⁹³ - Create `codeql.yml`
- PR #6474⁹⁹⁴ - Remove remnants of `libfabric` `parcelport`
- PR #6473⁹⁹⁵ - Add documentation for distributed implementations of `post`, `async`, `sync` and `dataflow`
- PR #6471⁹⁹⁶ - Add `distance.cpp` test in CMake
- PR #6468⁹⁹⁷ - Small vector relocation
- PR #6448⁹⁹⁸ - Standardising Benchmarks, with support for `nanobench` as an option for its backend
- PR #6365⁹⁹⁹ - Release V1.10.0
- PR #6089¹⁰⁰⁰ - Implementing `p2079`

⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6522>

⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6520>

⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6518>

⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/6512>

⁹⁸² <https://github.com/TheHPXProject/hpx/pull/6510>

⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/6509>

⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6508>

⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6507>

⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6503>

⁹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6499>

⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6498>

⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6497>

⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6496>

⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/6494>

⁹⁹² <https://github.com/TheHPXProject/hpx/pull/6487>

⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/6486>

⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6474>

⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6473>

⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6471>

⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6468>

⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6448>

⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6365>

¹⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6089>

2.11.2 List of older releases

HPX V1.10.0 (May 29, 2024)

General changes

- The HPX documentation has seen a major overhaul for this release. We finished documenting the public local HPX API, we have added migration guides from widely used parallelization platforms to HPX (OpenMP, TBB, and MPI).
- We have added facilities enabling optimizations for trivially-relocatable types (see [P1144](https://wg21.link/p1144)¹⁰⁰¹ for more details).
- We have added (and use) the `scope_xxx` helper facilities as specified by the C++ library fundamentals TS v3 (see: [N4948](http://wg21.link/n4948)¹⁰⁰²).
- We have added configuration options that allow to build HPX without pre-installing any prerequisites. Use `HPX_WITH_FETCH_HWLOC=On` to have [Portable Hardware Locality \(HWLOC\)](https://www.open-mpi.org/projects/hwloc/)¹⁰⁰³ installed for you. Similarly, setting `HPX_WITH_FETCH_BOOST=On` during configuration time will install the necessary [Boost](https://www.boost.org/)¹⁰⁰⁴ libraries (currently V1.84.0).
- We have performed a lot of code cleanup and refactoring to improve the overall code quality and decrease compile times.
- The collective operations APIs have seen an unification, we have fixed issues and performance problems for the collectives.
- The HPX executors have seen a streamlining and some consistency changes. We have applied many performance improvements to the executor implementations that directly positively impact the performance of our parallel algorithms.
- We have added a new parcelport allowing to use Gasnet as a communication platform.
- We have added optimizations to various parcelports improving overall communication performance. This includes - amongst other things - send immediate optimizations and receiver-side zero-copy optimizations.
- Futures will now execute the associated task eagerly and inline on any wait operation if the task has not started running yet. This feature can be enabled using the `HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD=On` configuration setting (which is *Off* by default).
- We have enabled using json files to supply configuration information through the command line. This feature can be enabled with the configuration option `HPX_COMMAND_LINE_HANDLING_WITH_JSON_CONFIGURATION_FILES=On`. This functionality depends on the external [JSON library](https://github.com/nlohmann/json)¹⁰⁰⁵, which can be built at configuration time by supplying `HPX_WITH_FETCH_JSON=On` to [CMake](https://www.cmake.org)¹⁰⁰⁶.
- We have applied many fixes to our CUDA, ROCm, and SYCL build environments.

¹⁰⁰¹ <https://wg21.link/p1144>

¹⁰⁰² <http://wg21.link/n4948>

¹⁰⁰³ <https://www.open-mpi.org/projects/hwloc/>

¹⁰⁰⁴ <https://www.boost.org/>

¹⁰⁰⁵ <https://github.com/nlohmann/json>

¹⁰⁰⁶ <https://www.cmake.org>

Breaking changes

- The `CMake`¹⁰⁰⁷ configuration keys `SOMELIB_ROOT` (e.g., `BOOST_ROOT`) have been renamed to `Somelib_ROOT` (e.g., `Boost_ROOT`) to avoid warnings when using newer versions of `CMake`¹⁰⁰⁸. Please update your scripts accordingly. For now, the old variable names are re-assigned to the new names and unset in the `CMake`¹⁰⁰⁹ cache.

Closed issues

- [Issue #6466](#)¹⁰¹⁰ - No access limitations to Wiki
- [Issue #6461](#)¹⁰¹¹ - `handle_received_parcel`s may never return
- [Issue #6459](#)¹⁰¹² - Building HPX
- [Issue #6451](#)¹⁰¹³ - HPX hangs at the very end
- [Issue #6446](#)¹⁰¹⁴ - Issue on page `/manual/getting_hpx.html`
- [Issue #6443](#)¹⁰¹⁵ - PR #6435 (`parcel_layer_tweaks`) broke Octo-Tiger
- [Issue #6440](#)¹⁰¹⁶ - HPX does not compile with MSVC of Visual Studio 2022 17.9+
- [Issue #6437](#)¹⁰¹⁷ - HPX 1.9.1 does not compile on Fedora with `#pragma message: [Parallel STL message]: "Vectorized algorithm unimplemented, redirected to serial"`
- [Issue #6419](#)¹⁰¹⁸ - Enhancement of the macro functionalities within `hpx`
- [Issue #6417](#)¹⁰¹⁹ - The current HPX master branch is still not compatible with Kokkos 4.0.1
- [Issue #6414](#)¹⁰²⁰ - Current HPX master causes segfaults within Octo-Tiger
- [Issue #6412](#)¹⁰²¹ - Clangd (Language Server) throws error for `__integer_pack` at `pack.hpp`
- [Issue #6407](#)¹⁰²² - Cannot build Kokkos 4.0.01 with current HPX master
- [Issue #6405](#)¹⁰²³ - Spack Build Error with ROCm 5.7.0
- [Issue #6398](#)¹⁰²⁴ - HPX sets affinity wrong with multiple processes per node and LCI `parcelport` enabled
- [Issue #6392](#)¹⁰²⁵ - [Feature] Install dependencies using `CMake`
- [Issue #6388](#)¹⁰²⁶ - HPX error: "Host not found" when running on Expanse with 128 nodes

¹⁰⁰⁷ <https://www.cmake.org>

¹⁰⁰⁸ <https://www.cmake.org>

¹⁰⁰⁹ <https://www.cmake.org>

¹⁰¹⁰ <https://github.com/TheHPXProject/hpx/issues/6466>

¹⁰¹¹ <https://github.com/TheHPXProject/hpx/issues/6461>

¹⁰¹² <https://github.com/TheHPXProject/hpx/issues/6459>

¹⁰¹³ <https://github.com/TheHPXProject/hpx/issues/6451>

¹⁰¹⁴ <https://github.com/TheHPXProject/hpx/issues/6446>

¹⁰¹⁵ <https://github.com/TheHPXProject/hpx/issues/6443>

¹⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/6440>

¹⁰¹⁷ <https://github.com/TheHPXProject/hpx/issues/6437>

¹⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/6419>

¹⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/6417>

¹⁰²⁰ <https://github.com/TheHPXProject/hpx/issues/6414>

¹⁰²¹ <https://github.com/TheHPXProject/hpx/issues/6412>

¹⁰²² <https://github.com/TheHPXProject/hpx/issues/6407>

¹⁰²³ <https://github.com/TheHPXProject/hpx/issues/6405>

¹⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/6398>

¹⁰²⁵ <https://github.com/TheHPXProject/hpx/issues/6392>

¹⁰²⁶ <https://github.com/TheHPXProject/hpx/issues/6388>

- [Issue #6366](#)¹⁰²⁷ - serialize_buffer allocator support needs adjustments
- [Issue #6361](#)¹⁰²⁸ - HPX 1.9.1 does not compile on Fedora 40
- [Issue #6355](#)¹⁰²⁹ - Single page documentation is broken
- [Issue #6334](#)¹⁰³⁰ - Segmentation fault after adding a padding in one_size_heap_list
- [Issue #6329](#)¹⁰³¹ - Log hpx threads on forced shutdown
- [Issue #6316](#)¹⁰³² - Build breaks on FreeBSD
- [Issue #6299](#)¹⁰³³ - HPX does not use distributed localities on Fugaku
- [Issue #6298](#)¹⁰³⁴ - Update config for coroutines on ARM
- [Issue #6291](#)¹⁰³⁵ - Zero-copy receive optimization disabled the invocation of direct actions
- [Issue #6261](#)¹⁰³⁶ - Add optional reading of json files for command line options
- [Issue #6087](#)¹⁰³⁷ - Support for vcpkg on Linux is broken
- [Issue #5921](#)¹⁰³⁸ - hpx::info claims that async_mpi was not built, while cmake assures its existence
- [Issue #5893](#)¹⁰³⁹ - Tests fail on FreeBSD: Executable copyn_test does not exist
- [Issue #5833](#)¹⁰⁴⁰ - barrier lockup
- [Issue #5799](#)¹⁰⁴¹ - Investigate CUDA compilation problems
- [Issue #5340](#)¹⁰⁴² - Examples do not run on Mac OSX using the M1 chip

Closed pull requests

- [PR #6493](#)¹⁰⁴³ - Fix distributed latch documentation
- [PR #6492](#)¹⁰⁴⁴ - Fix kokkos hpx nvcc compilation
- [PR #6491](#)¹⁰⁴⁵ - More fixes to handling bool arguments for collective operations
- [PR #6490](#)¹⁰⁴⁶ - Remove the default max cpu count
- [PR #6489](#)¹⁰⁴⁷ - Ensure TCP parcelport is deactivated if not needed
- [PR #6488](#)¹⁰⁴⁸ - Fixing handling of bool value type for collective operations

¹⁰²⁷ <https://github.com/TheHPXProject/hpx/issues/6366>

¹⁰²⁸ <https://github.com/TheHPXProject/hpx/issues/6361>

¹⁰²⁹ <https://github.com/TheHPXProject/hpx/issues/6355>

¹⁰³⁰ <https://github.com/TheHPXProject/hpx/issues/6334>

¹⁰³¹ <https://github.com/TheHPXProject/hpx/issues/6329>

¹⁰³² <https://github.com/TheHPXProject/hpx/issues/6316>

¹⁰³³ <https://github.com/TheHPXProject/hpx/issues/6299>

¹⁰³⁴ <https://github.com/TheHPXProject/hpx/issues/6298>

¹⁰³⁵ <https://github.com/TheHPXProject/hpx/issues/6291>

¹⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/6261>

¹⁰³⁷ <https://github.com/TheHPXProject/hpx/issues/6087>

¹⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/5921>

¹⁰³⁹ <https://github.com/TheHPXProject/hpx/issues/5893>

¹⁰⁴⁰ <https://github.com/TheHPXProject/hpx/issues/5833>

¹⁰⁴¹ <https://github.com/TheHPXProject/hpx/issues/5799>

¹⁰⁴² <https://github.com/TheHPXProject/hpx/issues/5340>

¹⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/6493>

¹⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6492>

¹⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6491>

¹⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6490>

¹⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6489>

¹⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6488>

- PR #6485¹⁰⁴⁹ - Destructive interference size
- PR #6484¹⁰⁵⁰ - Improve performance counter error handling
- PR #6482¹⁰⁵¹ - Generalize the notion of bitwise serialization
- PR #6481¹⁰⁵² - Fixing use of HPX_WITH_CXX_STANDARD
- PR #6480¹⁰⁵³ - Remove equal_to from hpx::any
- PR #6479¹⁰⁵⁴ - Remove optimizations for certain built-in compiler intrinsics
- PR #6478¹⁰⁵⁵ - Fixing issues on MacOS
- PR #6477¹⁰⁵⁶ - lci pp: lci's github repo name changed from LC to lci
- PR #6476¹⁰⁵⁷ - Fixing binary filter test target names
- PR #6475¹⁰⁵⁸ - Fix mac os github actions
- PR #6472¹⁰⁵⁹ - Troubleshoot CI hangs
- PR #6469¹⁰⁶⁰ - improve(lci pp): more options to control the LCI parcelport
- PR #6467¹⁰⁶¹ - Bump jwlawson/actions-setup-cmake from 1.14 to 2.0
- PR #6464¹⁰⁶² - Update docs of "Writing distributed applications" page
- PR #6463¹⁰⁶³ - Revert "Always return outermost thread id"
- PR #6458¹⁰⁶⁴ - Reduce test workload to fix CI/CD time-out
- PR #6457¹⁰⁶⁵ - replace boost::array with std::array and update file name
- PR #6456¹⁰⁶⁶ - Move APEX CI to rostam
- PR #6455¹⁰⁶⁷ - Fixing compilation if HPX_HAVE_THREAD_QUEUE_WAITTIME is defined
- PR #6454¹⁰⁶⁸ - Update perftests reference measurements
- PR #6453¹⁰⁶⁹ - Update supported platforms of Manual/Prerequisites page
- PR #6452¹⁰⁷⁰ - Fix nvcc crashes in transform_stream.cu and synchronize.cu
- PR #6450¹⁰⁷¹ - Fix git tag name in Getting HPX page

¹⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6485>

¹⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6484>

¹⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/6482>

¹⁰⁵² <https://github.com/TheHPXProject/hpx/pull/6481>

¹⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/6480>

¹⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6479>

¹⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6478>

¹⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6477>

¹⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6476>

¹⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6475>

¹⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6472>

¹⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6469>

¹⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/6467>

¹⁰⁶² <https://github.com/TheHPXProject/hpx/pull/6464>

¹⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/6463>

¹⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6458>

¹⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6457>

¹⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6456>

¹⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6455>

¹⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6454>

¹⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6453>

¹⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6452>

¹⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/6450>

- PR #6449¹⁰⁷² - LCI parcelport: add yield to potentially infinite retry loop
- PR #6447¹⁰⁷³ - Use compressed ptr in schedulers when 128 atomics are not lockfree
- PR #6445¹⁰⁷⁴ - Fix agas addressing cache
- PR #6444¹⁰⁷⁵ - Update CTestConfig.cmake
- PR #6442¹⁰⁷⁶ - Update CMakeLists.txt
- PR #6441¹⁰⁷⁷ - Minor documentation fixes
- PR #6439¹⁰⁷⁸ - Optimizing use of certain #includes
- PR #6438¹⁰⁷⁹ - Bump jwlawson/actions-setup-cmake from 1.14 to 2.0
- PR #6436¹⁰⁸⁰ - Update docs
- PR #6435¹⁰⁸¹ - Parcel layer tweaks
- PR #6434¹⁰⁸² - improve termination detection: removing lock from critical path
- PR #6433¹⁰⁸³ - Use shared mutex for resolve_locality procedure
- PR #6432¹⁰⁸⁴ - Module cleanup up to level 30
- PR #6429¹⁰⁸⁵ - Making sure HPX_WITH_ASYNC_MPI is reported properly
- PR #6427¹⁰⁸⁶ - Modifying CMakeLists to copy libhwloc-15.dll to the binary folder in Windows, independently
- PR #6425¹⁰⁸⁷ - Fix macOS failing test
- PR #6424¹⁰⁸⁸ - Adding option for downloading Boost using CMake FetchContent
- PR #6423¹⁰⁸⁹ - Move adjacent_difference to numeric header file
- PR #6422¹⁰⁹⁰ - Adding steal-half functionalities to work-requesting scheduler
- PR #6421¹⁰⁹¹ - Bump actions/checkout from 2 to 4
- PR #6418¹⁰⁹² - Working around nvcc problems to use CTAD
- PR #6416¹⁰⁹³ - Change run_as_os_thread deprecation forwarding due to hipcc compilation issue
- PR #6415¹⁰⁹⁴ - Attempting to avoid segfault in OctoTiger during initialization

¹⁰⁷² <https://github.com/TheHPXProject/hpx/pull/6449>

¹⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/6447>

¹⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6445>

¹⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6444>

¹⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6442>

¹⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6441>

¹⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6439>

¹⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6438>

¹⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6436>

¹⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/6435>

¹⁰⁸² <https://github.com/TheHPXProject/hpx/pull/6434>

¹⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/6433>

¹⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6432>

¹⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6429>

¹⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6427>

¹⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6425>

¹⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6424>

¹⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6423>

¹⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6422>

¹⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/6421>

¹⁰⁹² <https://github.com/TheHPXProject/hpx/pull/6418>

¹⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/6416>

¹⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6415>

- PR #6413¹⁰⁹⁵ - Always return outermost thread id
- PR #6411¹⁰⁹⁶ - Minor refactoring and fixes to the LCI parcellport and pingpong_performance2 benchmark
- PR #6410¹⁰⁹⁷ - Adding scope_xxx from library fundamentals TS v3
- PR #6409¹⁰⁹⁸ - Working around CUDA issue
- PR #6408¹⁰⁹⁹ - Tightening up collective operation semantics
- PR #6406¹¹⁰⁰ - Working around ROCm compiler issue
- PR #6404¹¹⁰¹ - Allow to disable use of [[no_unique_address]] attribute
- PR #6403¹¹⁰² - Fixing copyright year
- PR #6402¹¹⁰³ - fix(lci pp): fix deadlocks with too many failed sends
- PR #6401¹¹⁰⁴ - fix(lci pp): fix the null_thread_id bug in the LCI parcellport
- PR #6400¹¹⁰⁵ - Fix the affinity setting bug when using LCI pp and multiple localities per node
- PR #6397¹¹⁰⁶ - Change API header titles and info
- PR #6396¹¹⁰⁷ - Making is_bitwise_serializable SFINAE-friendly
- PR #6395¹¹⁰⁸ - Adapt amount of collective testing
- PR #6394¹¹⁰⁹ - Adding option for installing Hwloc using CMake FetchContent
- PR #6393¹¹¹⁰ - Optionally disable caching allocator
- PR #6391¹¹¹¹ - Cleaning up collective operations
- PR #6390¹¹¹² - Making function local constexpr variables non-static
- PR #6389¹¹¹³ - Disable resolving hostnames if TCP is disabled
- PR #6387¹¹¹⁴ - Need to break out of the loop when searching the suffixes.
- PR #6384¹¹¹⁵ - Fixing allocation/deallocation mismatch in serialize_buffer
- PR #6383¹¹¹⁶ - Enable fork_join_executor to handle return values from scheduled functions
- PR #6381¹¹¹⁷ - Consistently treat conflicting parameters provided by executors and parameter objects

¹⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6413>

¹⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6411>

¹⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6410>

¹⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6409>

¹⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6408>

¹¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6406>

¹¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/6404>

¹¹⁰² <https://github.com/TheHPXProject/hpx/pull/6403>

¹¹⁰³ <https://github.com/TheHPXProject/hpx/pull/6402>

¹¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6401>

¹¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6400>

¹¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6397>

¹¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6396>

¹¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6395>

¹¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6394>

¹¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/6393>

¹¹¹¹ <https://github.com/TheHPXProject/hpx/pull/6391>

¹¹¹² <https://github.com/TheHPXProject/hpx/pull/6390>

¹¹¹³ <https://github.com/TheHPXProject/hpx/pull/6389>

¹¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/6387>

¹¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/6384>

¹¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/6383>

¹¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/6381>

- PR #6380¹¹¹⁸ - Fixing setting an annotation for an execution policy
- PR #6378¹¹¹⁹ - Allowing to disable signal handlers
- PR #6377¹¹²⁰ - Fix gasnet-related test failures
- PR #6375¹¹²¹ - Update LSU Jenkins with 2023-10 libraries
- PR #6374¹¹²² - Investigate builder gasnet failure
- PR #6373¹¹²³ - Fixing communicator API, adding docs
- PR #6372¹¹²⁴ - Fix resource partitioner tests for small thread count
- PR #6371¹¹²⁵ - Fix jacobi omp examples.
- PR #6370¹¹²⁶ - improve one_size_heap_list: use rwlock to speedup the allocation/free
- PR #6369¹¹²⁷ - working issue with MPI_CC / CC conflict in automake
- PR #6368¹¹²⁸ - Making sure serialize_buffer properly destroys buffer, if needed.
- PR #6367¹¹²⁹ - Fix parallel relocation test
- PR #6364¹¹³⁰ - Relocation variants
- PR #6363¹¹³¹ - Update the lci parcelport to use LCI v1.7.6
- PR #6362¹¹³² - Fixing compilation problems on 32 Linux systems
- PR #6360¹¹³³ - Fix broken links in docs: PDF, Single HTML page, Dependency report
- PR #6359¹¹³⁴ - Fix header file links in Public API page
- PR #6358¹¹³⁵ - Fix CMake find_library for HWLOC
- PR #6357¹¹³⁶ - Replace Custom Benchmarking Code with Nanobench
- PR #6356¹¹³⁷ - Fixed matrix multiplication example output
- PR #6354¹¹³⁸ - Fix broken links for header files in Public API page
- PR #6353¹¹³⁹ - Enable using std::reference_wrapper with executor parameters
- PR #6352¹¹⁴⁰ - Add Public distributed API documentation

¹¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/6380>

¹¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/6378>

¹¹²⁰ <https://github.com/TheHPXProject/hpx/pull/6377>

¹¹²¹ <https://github.com/TheHPXProject/hpx/pull/6375>

¹¹²² <https://github.com/TheHPXProject/hpx/pull/6374>

¹¹²³ <https://github.com/TheHPXProject/hpx/pull/6373>

¹¹²⁴ <https://github.com/TheHPXProject/hpx/pull/6372>

¹¹²⁵ <https://github.com/TheHPXProject/hpx/pull/6371>

¹¹²⁶ <https://github.com/TheHPXProject/hpx/pull/6370>

¹¹²⁷ <https://github.com/TheHPXProject/hpx/pull/6369>

¹¹²⁸ <https://github.com/TheHPXProject/hpx/pull/6368>

¹¹²⁹ <https://github.com/TheHPXProject/hpx/pull/6367>

¹¹³⁰ <https://github.com/TheHPXProject/hpx/pull/6364>

¹¹³¹ <https://github.com/TheHPXProject/hpx/pull/6363>

¹¹³² <https://github.com/TheHPXProject/hpx/pull/6362>

¹¹³³ <https://github.com/TheHPXProject/hpx/pull/6360>

¹¹³⁴ <https://github.com/TheHPXProject/hpx/pull/6359>

¹¹³⁵ <https://github.com/TheHPXProject/hpx/pull/6358>

¹¹³⁶ <https://github.com/TheHPXProject/hpx/pull/6357>

¹¹³⁷ <https://github.com/TheHPXProject/hpx/pull/6356>

¹¹³⁸ <https://github.com/TheHPXProject/hpx/pull/6354>

¹¹³⁹ <https://github.com/TheHPXProject/hpx/pull/6353>

¹¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6352>

- PR #6350¹¹⁴¹ - Make coverage work with Jenkins Github Branch Source plugin
- PR #6349¹¹⁴² - Moving hpx::threads::run_as_xxx to namespace hpx
- PR #6348¹¹⁴³ - Adding `--exclusive` to launching tests on rostam
- PR #6346¹¹⁴⁴ - changed chat link to discord
- PR #6344¹¹⁴⁵ - uninitialized_relocate w/ type_support primitive
- PR #6343¹¹⁴⁶ - Bump actions/checkout from 3 to 4
- PR #6342¹¹⁴⁷ - Fix HPX-APEX cmake integration
- PR #6341¹¹⁴⁸ - Fix shared_future_continuation_order regression test
- PR #6340¹¹⁴⁹ - Log alive hpx threads on exit
- PR #6339¹¹⁵⁰ - Add coverage testing on Jenkins
- PR #6338¹¹⁵¹ - Fixing HPX_CURRENT_SOURCE_LOCATION when std::source_location exists
- PR #6337¹¹⁵² - Remove aurianer, biddisco, and msimberg from codeowners
- PR #6336¹¹⁵³ - More cleaning up for module levels 19-20
- PR #6335¹¹⁵⁴ - Finalize the MPI docs of the Migration Guide
- PR #6332¹¹⁵⁵ - More fixes for CMake V3.27
- PR #6330¹¹⁵⁶ - Adding basic logging to collective operations
- PR #6328¹¹⁵⁷ - Cleanup previous patch adapting to CMake V3.27
- PR #6327¹¹⁵⁸ - Modernize modules in level 17 and 18
- PR #6324¹¹⁵⁹ - P1144 Relocation primitives
- PR #6321¹¹⁶⁰ - Ensure hpx_main is a proper thread_function
- PR #6320¹¹⁶¹ - Fixing cyclic dependencies in naming and agas modules
- PR #6319¹¹⁶² - Generate git tag if needed but it is not available
- PR #6317¹¹⁶³ - Fixing linker problem on FreeBSD

¹¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/6350>

¹¹⁴² <https://github.com/TheHPXProject/hpx/pull/6349>

¹¹⁴³ <https://github.com/TheHPXProject/hpx/pull/6348>

¹¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6346>

¹¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6344>

¹¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6343>

¹¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6342>

¹¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6341>

¹¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6340>

¹¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6339>

¹¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/6338>

¹¹⁵² <https://github.com/TheHPXProject/hpx/pull/6337>

¹¹⁵³ <https://github.com/TheHPXProject/hpx/pull/6336>

¹¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6335>

¹¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6332>

¹¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6330>

¹¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6328>

¹¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6327>

¹¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6324>

¹¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6321>

¹¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/6320>

¹¹⁶² <https://github.com/TheHPXProject/hpx/pull/6319>

¹¹⁶³ <https://github.com/TheHPXProject/hpx/pull/6317>

- PR #6315¹¹⁶⁴ - acknowledge triv-rel and nothrow-rel types
- PR #6314¹¹⁶⁵ - Relocation algorithms Clean
- PR #6313¹¹⁶⁶ - Trivial relocation of c-v-ref-array types
- PR #6312¹¹⁶⁷ - Fixing warning/error
- PR #6311¹¹⁶⁸ - Adding executor parallel invoke CPOs
- PR #6310¹¹⁶⁹ - Define HPX_COMPUTE_CODE in builds with SYCL
- PR #6309¹¹⁷⁰ - Making sure changed number of cores is propagated to executor
- PR #6308¹¹⁷¹ - openshmem-parcelport initial import
- PR #6306¹¹⁷² - The hpxcxx script was broken such that it could only compile for _release
- PR #6305¹¹⁷³ - Adapting build system for CMake V3.27
- PR #6304¹¹⁷⁴ - Fixing an integral type mismatch warning
- PR #6303¹¹⁷⁵ - omp for default vectorization
- PR #6301¹¹⁷⁶ - Add MPI migration guide
- PR #6294¹¹⁷⁷ - Add internal reference counting to semaphores
- PR #6286¹¹⁷⁸ - Simd helpers
- PR #6280¹¹⁷⁹ - Add TBB to HPX documentation in Migration Guide
- PR #6276¹¹⁸⁰ - Add dependabot.yml
- PR #6275¹¹⁸¹ - Revert “Move dependabot.yml into correct directory”
- PR #6272¹¹⁸² - set thread name for linux
- PR #6271¹¹⁸³ - Uninitialised algorithms, move using std::memcpy
- PR #6270¹¹⁸⁴ - Bump jwlawson/actions-setup-cmake from 1.9 to 1.14
- PR #6269¹¹⁸⁵ - Bump actions/checkout from 2 to 3
- PR #6268¹¹⁸⁶ - Move dependabot.yml into correct directory

¹¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6315>

¹¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6314>

¹¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6313>

¹¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6312>

¹¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6311>

¹¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6310>

¹¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6309>

¹¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/6308>

¹¹⁷² <https://github.com/TheHPXProject/hpx/pull/6306>

¹¹⁷³ <https://github.com/TheHPXProject/hpx/pull/6305>

¹¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6304>

¹¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6303>

¹¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6301>

¹¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6294>

¹¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6286>

¹¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6280>

¹¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6276>

¹¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/6275>

¹¹⁸² <https://github.com/TheHPXProject/hpx/pull/6272>

¹¹⁸³ <https://github.com/TheHPXProject/hpx/pull/6271>

¹¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6270>

¹¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6269>

¹¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6268>

- PR #6265¹¹⁸⁷ - Create dependabot.yml
- PR #6264¹¹⁸⁸ - `hpx::is_trivially_relocatable` trait implementation
- PR #6263¹¹⁸⁹ - Adding support for reading json configuration files for command line options
- PR #6249¹¹⁹⁰ - Implement the send immediate optimization for the MPI parcelport.
- PR #6237¹¹⁹¹ - Improve compilation performance
- PR #6234¹¹⁹² - Adding release notes page for next release
- PR #6233¹¹⁹³ - Moving `is_relocatable` to namespace `hpx`
- PR #6230¹¹⁹⁴ - gasnet based parcelport
- PR #6226¹¹⁹⁵ - Re-enable dependency on segmented algorithms on CircleCI
- PR #6220¹¹⁹⁶ - Add execution on
- PR #6212¹¹⁹⁷ - Initial trait definition for *relocatable*
- PR #6199¹¹⁹⁸ - added support for `unseq`, `par_unseq` for `hpx::make_heap` algorithm
- PR #6173¹¹⁹⁹ - C++ modules
- PR #6122¹²⁰⁰ - Add Module support
- PR #6099¹²⁰¹ - Futures attempt to execute threads directly if those have not started executing
- PR #6050¹²⁰² - Investigating `partitioned_vector` problems
- PR #5988¹²⁰³ - Adding CI configuration for DGX-A100 at LSU
- PR #5910¹²⁰⁴ - Improve MPI initialization
- PR #5845¹²⁰⁵ - Adding local work requesting scheduler that is based on message passing internally

¹¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6265>

¹¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6264>

¹¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6263>

¹¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6249>

¹¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/6237>

¹¹⁹² <https://github.com/TheHPXProject/hpx/pull/6234>

¹¹⁹³ <https://github.com/TheHPXProject/hpx/pull/6233>

¹¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6230>

¹¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6226>

¹¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6220>

¹¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6212>

¹¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6199>

¹¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6173>

¹²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6122>

¹²⁰¹ <https://github.com/TheHPXProject/hpx/pull/6099>

¹²⁰² <https://github.com/TheHPXProject/hpx/pull/6050>

¹²⁰³ <https://github.com/TheHPXProject/hpx/pull/5988>

¹²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5910>

¹²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5845>

HPX V1.9.1 (August 4, 2023)

General changes

This point release fixes a couple of problems reported for the V1.9.0 release. Most importantly, we fixed various occasional hanging during startup and shutdown in distributed scenarios. We also added support for zero-copy serialization on the receiving side to the TCP, MPI, and LCI parcelports. Last but not least, we have added support for Visual Studio 2019 and gcc using MINGW on Windows, and also support for gcc V13 and clang V15.

HPX headers are now made consistently named the same as their standard library counterparts, e.g. `#include <thread>` now corresponds to `#include <hpx/thread.hpp>`. This significantly simplifies porting existing standards conforming codes to HPX.

A lot of work has been done to improve and optimize our network communication layers. Primary focus of this work was on the LCI parcelport, but we have also cleaned up and improved the MPI parcelport.

Additionally, we have continued working on our documentation. The main focus here was on completing the API documentation of the most important API functions. We have started adding migration guides for people interested in moving their codes away from other, commonplace parallelization frameworks like OpenMP.

Breaking changes

None

Closed issues

- [Issue #6155](https://github.com/TheHPXProject/hpx/issues/6155)¹²⁰⁶ - `hpxcxx` and `hpxrun.py` do not work if `HPX_WITH_TESTS=OFF`
- [Issue #6164](https://github.com/TheHPXProject/hpx/issues/6164)¹²⁰⁷ - `HPX_WITH_DATAPAR_BACKEND=EVE` causes compile errors with C++17
- [Issue #6175](https://github.com/TheHPXProject/hpx/issues/6175)¹²⁰⁸ - Make sure all our parallel algorithms accept the predicates by value
- [Issue #6194](https://github.com/TheHPXProject/hpx/issues/6194)¹²⁰⁹ - `tests.regressions.threads.threads_all_1422` failed at Perlmutter
- [Issue #6198](https://github.com/TheHPXProject/hpx/issues/6198)¹²¹⁰ - `set_intersection/set_difference` fails when run with `execution::par`
- [Issue #6214](https://github.com/TheHPXProject/hpx/issues/6214)¹²¹¹ - Broken Links to the Documentation page in `readme.rst`
- [Issue #6217](https://github.com/TheHPXProject/hpx/issues/6217)¹²¹² - `hpx::make_heap` does not terminate when `exPolicy` is `par` (or `par_unseq`) and size of vector is 4
- [Issue #6246](https://github.com/TheHPXProject/hpx/issues/6246)¹²¹³ - HPX fails to compile under `cxx 20` (fresh system)
- [Issue #6247](https://github.com/TheHPXProject/hpx/issues/6247)¹²¹⁴ - HPX 1.9.0 does not compile with GCC on Windows
- [Issue #6282](https://github.com/TheHPXProject/hpx/issues/6282)¹²¹⁵ - The “attach-debugger” option is broken on the current master branch.

¹²⁰⁶ <https://github.com/TheHPXProject/hpx/issues/6155>

¹²⁰⁷ <https://github.com/TheHPXProject/hpx/issues/6164>

¹²⁰⁸ <https://github.com/TheHPXProject/hpx/issues/6175>

¹²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/6194>

¹²¹⁰ <https://github.com/TheHPXProject/hpx/issues/6198>

¹²¹¹ <https://github.com/TheHPXProject/hpx/issues/6214>

¹²¹² <https://github.com/TheHPXProject/hpx/issues/6217>

¹²¹³ <https://github.com/TheHPXProject/hpx/issues/6246>

¹²¹⁴ <https://github.com/TheHPXProject/hpx/issues/6247>

¹²¹⁵ <https://github.com/TheHPXProject/hpx/issues/6282>

Closed pull requests

- [PR #6219](#)¹²¹⁶ - Cleaning up #includes in hpx/ folder
- [PR #6223](#)¹²¹⁷ - Move documentation from README.rst to index.rst files under libs directory
- [PR #6229](#)¹²¹⁸ - Adding zero-copy support on the receiving end of the TCP and MPI parcel ports
- [PR #6231](#)¹²¹⁹ - Remove deprecated email from release procedure
- [PR #6235](#)¹²²⁰ - Modernize more modules (levels 12-16)
- [PR #6236](#)¹²²¹ - Attempt to resolve occasional shutdown hangs in distributed operation
- [PR #6239](#)¹²²² - Fix Optimizing HPX applications page of Manual
- [PR #6241](#)¹²²³ - LCI parcelport: Refactor, add more variants, zero copy receives.
- [PR #6242](#)¹²²⁴ - updated deprecated headers
- [PR #6243](#)¹²²⁵ - Adding github action builders using VS2019
- [PR #6248](#)¹²²⁶ - Fix CUDA/HIP Jenkins pipelines
- [PR #6250](#)¹²²⁷ - Resolve gcc problems on Windows
- [PR #6251](#)¹²²⁸ - Attempting to fix problems in barrier causing hangs
- [PR #6253](#)¹²²⁹ - Modernize set_thread_name on Windows
- [PR #6256](#)¹²³⁰ - Fix nvcc/gcc-10 (Octo-Tiger) compilation issue
- [PR #6257](#)¹²³¹ - Cmake Tests: Delete operator check for size_t arg
- [PR #6258](#)¹²³² - Rewriting wait_some to circumvent data races causing hangs
- [PR #6260](#)¹²³³ - Add migration guide to manual
- [PR #6262](#)¹²³⁴ - Fixing wrong command line options in local command line handling
- [PR #6266](#)¹²³⁵ - Attempt to resolve occasional hang in run_loop
- [PR #6267](#)¹²³⁶ - Attempting to fix migration tests
- [PR #6278](#)¹²³⁷ - Making sure the future's shared state doesn't go out of scope prematurely

¹²¹⁶ <https://github.com/TheHPXProject/hpx/pull/6219>

¹²¹⁷ <https://github.com/TheHPXProject/hpx/pull/6223>

¹²¹⁸ <https://github.com/TheHPXProject/hpx/pull/6229>

¹²¹⁹ <https://github.com/TheHPXProject/hpx/pull/6231>

¹²²⁰ <https://github.com/TheHPXProject/hpx/pull/6235>

¹²²¹ <https://github.com/TheHPXProject/hpx/pull/6236>

¹²²² <https://github.com/TheHPXProject/hpx/pull/6239>

¹²²³ <https://github.com/TheHPXProject/hpx/pull/6241>

¹²²⁴ <https://github.com/TheHPXProject/hpx/pull/6242>

¹²²⁵ <https://github.com/TheHPXProject/hpx/pull/6243>

¹²²⁶ <https://github.com/TheHPXProject/hpx/pull/6248>

¹²²⁷ <https://github.com/TheHPXProject/hpx/pull/6250>

¹²²⁸ <https://github.com/TheHPXProject/hpx/pull/6251>

¹²²⁹ <https://github.com/TheHPXProject/hpx/pull/6253>

¹²³⁰ <https://github.com/TheHPXProject/hpx/pull/6256>

¹²³¹ <https://github.com/TheHPXProject/hpx/pull/6257>

¹²³² <https://github.com/TheHPXProject/hpx/pull/6258>

¹²³³ <https://github.com/TheHPXProject/hpx/pull/6260>

¹²³⁴ <https://github.com/TheHPXProject/hpx/pull/6262>

¹²³⁵ <https://github.com/TheHPXProject/hpx/pull/6266>

¹²³⁶ <https://github.com/TheHPXProject/hpx/pull/6267>

¹²³⁷ <https://github.com/TheHPXProject/hpx/pull/6278>

- PR #6279¹²³⁸ - Re-expose error names
- PR #6281¹²³⁹ - Creating directory for file copy
- PR #6283¹²⁴⁰ - Consistently #include unistd.h for _POSIX_VERSION

HPX V1.9.0 (May 2, 2023)

General changes

- Added RISC-V 64bit support. HPX is now compatible with RISC-V architectures which have revolutionized the HPC world.
- LCI parcelport has been optimized to transfer parcels with fewer messages and use the HPX resource partitioner for its progress thread allocation. It should generally provide better performance than before. It also removes its dependency on the MPI library.
- HPX dependency on Boost was further relaxed by replacing headers from Boost.Range, Boost.Tokenizer and Boost.Lockfree.
- Improvements took place on our parallel algorithms implementation.
- Our Senders/Receivers (P2300) integration was extended:
 - Coroutines were integrated with senders/receivers.

`get_completion_signatures` now works with awaitable senders. - `with_awaitable_senders` allows the passed senders to retrieve the value i.e. senders are transparently awaitable from within a coroutine. - `when_all_vector` was added.
- `sync_wait` and `sync_wait_with_variant` sender consumers were added. The user can now initiate the execution of their asynchronous pipeline by blocking the current thread that executes the `main()` function until the result is retrieved.
- The combinators for futures (a.k.a. `async_combinators`) `when_*`, `wait_*`, `wait_*_nothrow` were turned into CPOs allowing for end-user customization. For more information on the `async_combinators` refer to the documentation, https://hpx-docs.stellar-group.org/latest/html/libs/core/async_combinators/docs/index.html?highlight=combinators.
- The new datapar backend SVE allows `simd` and `par_simd` execution policies to exploit dataparallelism in the processors that have SVE vector registers like A64FX and Neoverse V1.
- The documentation for parallel algorithms, container algorithms was further improved. The Public API page was vastly enriched.
- Copy button shortkey was added at the top-right of code-blocks.
- Pragma directive that reports warnings as errors on MSVC was fixed.
- Command line argument `--hpx:loopback_network` was added to facilitate debugging with networks.
- We added an HPX-SYCL integration, allowing users to obtain HPX futures for SYCL events. This effectively enables the integration of arbitrary asynchronous SYCL operations into the HPX task graph. Bolted on top of this integration, we further added an HPX-SYCL executor for ease of use.

¹²³⁸ <https://github.com/TheHPXProject/hpx/pull/6279>

¹²³⁹ <https://github.com/TheHPXProject/hpx/pull/6281>

¹²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6283>

Breaking changes

- Stopped supporting Clang V8, the minimal version supported is now Clang V10.
- Stopped supporting gcc V8, the minimal version supported is now gcc V9.
- Stopped supporting Visual Studio 2015, the minimal version supported is now Visual Studio 2019.
- `tag_policy_tag` et.al. were re-added after HPX V1.8.1 deprecation.
- `get_chunk_size` and `processing_units_count` API is now expecting the time for one iteration as an argument.
- The list of all the namespace changes can be found here: *HPX V1.9.0 Namespace changes*.

Closed issues

- Issue #6203¹²⁴¹ - Compilation error with `-mcpu=a64fx` on Oookami
- Issue #6196¹²⁴² - Incorrect log destination
- Issue #6191¹²⁴³ - installing HPX
- Issue #6184¹²⁴⁴ - Wrong `processing_units_count` of `restricted_thread_pool_executor`
- Issue #6171¹²⁴⁵ - Release Tag Name Request
- Issue #6162¹²⁴⁶ - Current master does not compile on ROSTAM
- Issue #6156¹²⁴⁷ - `hpxcxx` does not work if `HPX_WITH_PKGCONFIG=OFF`
- Issue #6108¹²⁴⁸ - `cxx17_aligned_new.cpp` on `msvc` fails due to wrong pragma directive
- Issue #6045¹²⁴⁹ - Can't call nullary callables wrapped with `hpx::unwrapping`
- Issue #6013¹²⁵⁰ - Unable to build subprojects `hpx_collectives/hpx_compute` with MSVC
- Issue #6008¹²⁵¹ - Missing `constexpr` default constructor for `hpx::mutex`
- Issue #5999¹²⁵² - Add HPX Conda package to conda-forge
- Issue #5998¹²⁵³ - Serializing multiple arguments when applying distributed action results in segfault
- Issue #5958¹²⁵⁴ - HPX 1.8.0 and Blaze issues
- Issue #5908¹²⁵⁵ - Windows: duplicated symbols in static builds
- Issue #5802¹²⁵⁶ - Lost status `is_ready` from future

¹²⁴¹ <https://github.com/TheHPXProject/hpx/issues/6203>

¹²⁴² <https://github.com/TheHPXProject/hpx/issues/6196>

¹²⁴³ <https://github.com/TheHPXProject/hpx/issues/6191>

¹²⁴⁴ <https://github.com/TheHPXProject/hpx/issues/6184>

¹²⁴⁵ <https://github.com/TheHPXProject/hpx/issues/6171>

¹²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/6162>

¹²⁴⁷ <https://github.com/TheHPXProject/hpx/issues/6156>

¹²⁴⁸ <https://github.com/TheHPXProject/hpx/issues/6108>

¹²⁴⁹ <https://github.com/TheHPXProject/hpx/issues/6045>

¹²⁵⁰ <https://github.com/TheHPXProject/hpx/issues/6013>

¹²⁵¹ <https://github.com/TheHPXProject/hpx/issues/6008>

¹²⁵² <https://github.com/TheHPXProject/hpx/issues/5999>

¹²⁵³ <https://github.com/TheHPXProject/hpx/issues/5998>

¹²⁵⁴ <https://github.com/TheHPXProject/hpx/issues/5958>

¹²⁵⁵ <https://github.com/TheHPXProject/hpx/issues/5908>

¹²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/5802>

- [Issue #5767¹²⁵⁷](#) - Performance drop on Piz Daint
- [Issue #5752¹²⁵⁸](#) - Implement `stride_view` from P1899 (experimental)
- [Issue #5744¹²⁵⁹](#) - `HPX_WITH_FETCH_ASIO` not working on Ookami
- [Issue #5561¹²⁶⁰](#) - Possible race condition in helper thread / `hpx::cout`

Closed pull requests

- [PR #6228¹²⁶¹](#) - Fixing algorithms for zero length sequences when run with s/r scheduler
- [PR #6227¹²⁶²](#) - Reliably disable background work when no networking is enabled
- [PR #6225¹²⁶³](#) - Make heap fails in par for small sized heaps #6217
- [PR #6222¹²⁶⁴](#) - Add documentation for `hpx::post`
- [PR #6221¹²⁶⁵](#) - Fix segmented algorithms tests
- [PR #6218¹²⁶⁶](#) - Creating `INSTALL` component 'runtime' to enable installing binaries only
- [PR #6216¹²⁶⁷](#) - added tests for `set_difference`, updated `set_operation.hpp` to fix #6198
- [PR #6213¹²⁶⁸](#) - Modernize and streamline MPI parcellport
- [PR #6211¹²⁶⁹](#) - Modernize modules of level 11, 12, and 13
- [PR #6210¹²⁷⁰](#) - Fixing MPI parcellport initialization if MPI is initialized outside of HPX
- [PR #6209¹²⁷¹](#) - Prevent thread stealing during scheduler shutdown
- [PR #6208¹²⁷²](#) - Fix the compilation warning in the MPI parcellport with gcc 11.2
- [PR #6207¹²⁷³](#) - Automatically enable `Boost.Context` when compiling for arm64.
- [PR #6206¹²⁷⁴](#) - Update `CMakeLists.txt`
- [PR #6205¹²⁷⁵](#) - Do not generate `hpxcxx` if support for `pkgconfig` was disabled
- [PR #6204¹²⁷⁶](#) - Use **LRT_** instead of **LAPP_** logging in barrier implementation
- [PR #6202¹²⁷⁷](#) - Fixing Fedora build errors on Power systems
- [PR #6201¹²⁷⁸](#) - Update the LCI parcellport documents

¹²⁵⁷ <https://github.com/TheHPXProject/hpx/issues/5767>

¹²⁵⁸ <https://github.com/TheHPXProject/hpx/issues/5752>

¹²⁵⁹ <https://github.com/TheHPXProject/hpx/issues/5744>

¹²⁶⁰ <https://github.com/TheHPXProject/hpx/issues/5561>

¹²⁶¹ <https://github.com/TheHPXProject/hpx/pull/6228>

¹²⁶² <https://github.com/TheHPXProject/hpx/pull/6227>

¹²⁶³ <https://github.com/TheHPXProject/hpx/pull/6225>

¹²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6222>

¹²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6221>

¹²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6218>

¹²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6216>

¹²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6213>

¹²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6211>

¹²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6210>

¹²⁷¹ <https://github.com/TheHPXProject/hpx/pull/6209>

¹²⁷² <https://github.com/TheHPXProject/hpx/pull/6208>

¹²⁷³ <https://github.com/TheHPXProject/hpx/pull/6207>

¹²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6206>

¹²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6205>

¹²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6204>

¹²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6202>

¹²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6201>

- PR #6200¹²⁷⁹ - Par link jobs
- PR #6197¹²⁸⁰ - LCI parcelport: add doc, upgrade to v1.7.4, refactor cmake autofetch.
- PR #6195¹²⁸¹ - Change the default tag of autofetch LCI to v1.7.3.
- PR #6192¹²⁸² - Fix page *Writing single-node applications*
- PR #6189¹²⁸³ - Making sure restricted_thread_pool_executor properly reports used number of cores
- PR #6187¹²⁸⁴ - Enable using for_loop with range generators
- PR #6186¹²⁸⁵ - thread_support/CMakeLists: Fix build issue
- PR #6185¹²⁸⁶ - Fix EVE datapar with cxx_standard less than 20
- PR #6183¹²⁸⁷ - Update CI integration for EVE
- PR #6182¹²⁸⁸ - Fixing performance regressions
- PR #6181¹²⁸⁹ - LCI parcelport: backlog queue, aggregation, separate devices, and more
- PR #6180¹²⁹⁰ - Fixing use of for_loop with rebound execution policy (using *.with()*)
- PR #6179¹²⁹¹ - Taking predicates for algorithms by value
- PR #6178¹²⁹² - Changes needed to make chapel_hpx examples work
- PR #6176¹²⁹³ - Fixing warnings that were generated by PVS Studio
- PR #6174¹²⁹⁴ - Replace boost::integer::gcd with std::gcd
- PR #6172¹²⁹⁵ - [Docs] Fix example of how to run single/specific test(s)
- PR #6170¹²⁹⁶ - Adding missing fallback for processing_units_count customization point
- PR #6169¹²⁹⁷ - LCI parcelport: bypass the parcel queue and connection cache.
- PR #6167¹²⁹⁸ - Add create_local_communicator API function
- PR #6166¹²⁹⁹ - Add missing header for std::intmax_t
- PR #6165¹³⁰⁰ - Attempt to work around MSVC problem
- PR #6161¹³⁰¹ - Update EVE integration

¹²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6200>

¹²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6197>

¹²⁸¹ <https://github.com/TheHPXProject/hpx/pull/6195>

¹²⁸² <https://github.com/TheHPXProject/hpx/pull/6192>

¹²⁸³ <https://github.com/TheHPXProject/hpx/pull/6189>

¹²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6187>

¹²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6186>

¹²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6185>

¹²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6183>

¹²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6182>

¹²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6181>

¹²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6180>

¹²⁹¹ <https://github.com/TheHPXProject/hpx/pull/6179>

¹²⁹² <https://github.com/TheHPXProject/hpx/pull/6178>

¹²⁹³ <https://github.com/TheHPXProject/hpx/pull/6176>

¹²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6174>

¹²⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6172>

¹²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6170>

¹²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6169>

¹²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6167>

¹²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6166>

¹³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6165>

¹³⁰¹ <https://github.com/TheHPXProject/hpx/pull/6161>

- PR #6160¹³⁰² - More cleanup for module levels 0 to 10
- PR #6159¹³⁰³ - Fix minor spelling mistake in generate_issue_pr_list.sh
- PR #6158¹³⁰⁴ - Update documentation in *writing single-node applications* page
- PR #6157¹³⁰⁵ - Improve index_queue_spawning
- PR #6154¹³⁰⁶ - Avoid performing late command line handling twice in distributed runtime
- PR #6152¹³⁰⁷ - The -rd and -mr options didn't work, and they should have been -rd and -mr
- PR #6151¹³⁰⁸ - Refactoring the Manual page in documentation
- PR #6148¹³⁰⁹ - Investigate the failure of the LCI parcelport.
- PR #6147¹³¹⁰ - Make posix co-routine stacks non-executable
- PR #6146¹³¹¹ - Avoid ambiguities wrt tag_invoke
- PR #6144¹³¹² - General improvements to scheduling and related fixes
- PR #6143¹³¹³ - Add list of new namespaces for new release
- PR #6140¹³¹⁴ - Fixing background scheduler to properly exit in the end
- PR #6139¹³¹⁵ - [P2300] execution: Cleanup coroutines integration and improve ADL isolation
- PR #6137¹³¹⁶ - Adding example of a simple master/slave distributed application
- PR #6136¹³¹⁷ - Deprecate *execution::experimental::task_group* in favor of *experimental::task_group*
- PR #6135¹³¹⁸ - Fixing warnings reported by MSVC analysis
- PR #6134¹³¹⁹ - Adding notification function for parcelports to be called after early parcel handling
- PR #6132¹³²⁰ - Fixing to_non_par() for parallel simd policies
- PR #6131¹³²¹ - modernize modules from level 25
- PR #6130¹³²² - Remove the mutex lock in the critical path of get_partitioner.
- PR #6129¹³²³ - Modernize module from levels 22, 23
- PR #6127¹³²⁴ - Working around gccV9 problem that prevent us from storing enum classes in bit fields

¹³⁰² <https://github.com/TheHPXProject/hpx/pull/6160>

¹³⁰³ <https://github.com/TheHPXProject/hpx/pull/6159>

¹³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6158>

¹³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6157>

¹³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6154>

¹³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6152>

¹³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6151>

¹³⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6148>

¹³¹⁰ <https://github.com/TheHPXProject/hpx/pull/6147>

¹³¹¹ <https://github.com/TheHPXProject/hpx/pull/6146>

¹³¹² <https://github.com/TheHPXProject/hpx/pull/6144>

¹³¹³ <https://github.com/TheHPXProject/hpx/pull/6143>

¹³¹⁴ <https://github.com/TheHPXProject/hpx/pull/6140>

¹³¹⁵ <https://github.com/TheHPXProject/hpx/pull/6139>

¹³¹⁶ <https://github.com/TheHPXProject/hpx/pull/6137>

¹³¹⁷ <https://github.com/TheHPXProject/hpx/pull/6136>

¹³¹⁸ <https://github.com/TheHPXProject/hpx/pull/6135>

¹³¹⁹ <https://github.com/TheHPXProject/hpx/pull/6134>

¹³²⁰ <https://github.com/TheHPXProject/hpx/pull/6132>

¹³²¹ <https://github.com/TheHPXProject/hpx/pull/6131>

¹³²² <https://github.com/TheHPXProject/hpx/pull/6130>

¹³²³ <https://github.com/TheHPXProject/hpx/pull/6129>

¹³²⁴ <https://github.com/TheHPXProject/hpx/pull/6127>

- PR #6126¹³²⁵ - Deprecate `hpx::parallel::task_block` in favor of `hpx::experimental::task_block`
- PR #6125¹³²⁶ - Making sure `sync_wait` compiles when used with an lvalue sender involving bulk
- PR #6124¹³²⁷ - Fixing use of `any_sender` in combination with `when_all`
- PR #6123¹³²⁸ - Fixed issues found by PVS-Studio
- PR #6121¹³²⁹ - Modernize modules of level 21, 22
- PR #6120¹³³⁰ - Use `index_queue` for parallel executors `bulk_async_execute`
- PR #6119¹³³¹ - Update `CMakeLists.txt`
- PR #6118¹³³² - Modernize modules from level 17, 18, 19, and 20
- PR #6117¹³³³ - Initialize `buffer_allocate_time_` to 0
- PR #6116¹³³⁴ - Add new command line argument `-hpx:loopback_network`
- PR #6115¹³³⁵ - Modernize modules of levels 14, 15, and 16
- PR #6114¹³³⁶ - Enhance the formatting of the documentation
- PR #6113¹³³⁷ - Modernize modules in module level 11, 12, and 13
- PR #6112¹³³⁸ - Modernize modules from levels 9 and 10
- PR #6111¹³³⁹ - Modernize all modules from module level 8
- PR #6110¹³⁴⁰ - Use pragma error directive to report warnings as errors on msvc
- PR #6109¹³⁴¹ - Modernize serialization module
- PR #6107¹³⁴² - Modernize error module
- PR #6106¹³⁴³ - Modernizing modules of levels 0 to 5
- PR #6105¹³⁴⁴ - Optimizations on LCI parcelport: merge small messages; remove sender mutex lock.
- PR #6104¹³⁴⁵ - Adding parameters API: `measure_iteration`
- PR #6103¹³⁴⁶ - Document `task_group` and include in Public API
- PR #6102¹³⁴⁷ - Prevent warnings generated by clang-cl

¹³²⁵ <https://github.com/TheHPXProject/hpx/pull/6126>

¹³²⁶ <https://github.com/TheHPXProject/hpx/pull/6125>

¹³²⁷ <https://github.com/TheHPXProject/hpx/pull/6124>

¹³²⁸ <https://github.com/TheHPXProject/hpx/pull/6123>

¹³²⁹ <https://github.com/TheHPXProject/hpx/pull/6121>

¹³³⁰ <https://github.com/TheHPXProject/hpx/pull/6120>

¹³³¹ <https://github.com/TheHPXProject/hpx/pull/6119>

¹³³² <https://github.com/TheHPXProject/hpx/pull/6118>

¹³³³ <https://github.com/TheHPXProject/hpx/pull/6117>

¹³³⁴ <https://github.com/TheHPXProject/hpx/pull/6116>

¹³³⁵ <https://github.com/TheHPXProject/hpx/pull/6115>

¹³³⁶ <https://github.com/TheHPXProject/hpx/pull/6114>

¹³³⁷ <https://github.com/TheHPXProject/hpx/pull/6113>

¹³³⁸ <https://github.com/TheHPXProject/hpx/pull/6112>

¹³³⁹ <https://github.com/TheHPXProject/hpx/pull/6111>

¹³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6110>

¹³⁴¹ <https://github.com/TheHPXProject/hpx/pull/6109>

¹³⁴² <https://github.com/TheHPXProject/hpx/pull/6107>

¹³⁴³ <https://github.com/TheHPXProject/hpx/pull/6106>

¹³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6105>

¹³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6104>

¹³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6103>

¹³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6102>

- PR #6101¹³⁴⁸ - Using more fold expressions
- PR #6100¹³⁴⁹ - Deprecate `hpx::parallel::reduce_by_key` in favor of `hpx::experimental::reduce_by_key`
- PR #6098¹³⁵⁰ - Forking Boost.Lockfree
- PR #6096¹³⁵¹ - Forking Boost.Tokenizer
- PR #6095¹³⁵² - Replacing facilities from Boost.Range
- PR #6094¹³⁵³ - Removing object_semaphore
- PR #6093¹³⁵⁴ - Replace `boost::string_ref` with `std::string_view`
- PR #6092¹³⁵⁵ - Use C++17 `static_assert` where possible
- PR #6091¹³⁵⁶ - Replace artificial sequencing with fold expressions
- PR #6090¹³⁵⁷ - Fixing use of `get_chunk_size` customization point
- PR #6088¹³⁵⁸ - Add/fix Public API documentation
- PR #6086¹³⁵⁹ - Deprecate `hpx::util::unlock_guard` in favor of `hpx::unlock_guard`
- PR #6085¹³⁶⁰ - Add experimental `sycl` integration/executor
- PR #6084¹³⁶¹ - Renaming `hpx::apply` and friends to `hpx::post`
- PR #6083¹³⁶² - Using `if constexpr` instead of tag-dispatching, where possible
- PR #6082¹³⁶³ - Replace `util::always_void_t` with `std::void_t`
- PR #6081¹³⁶⁴ - Update github actions to avoid warnings
- PR #6080¹³⁶⁵ - Disable some tests that fail on LCI
- PR #6079¹³⁶⁶ - Adding more `natvis` files, correct existing
- PR #6078¹³⁶⁷ - Changing target name of `memory_counters` component
- PR #6077¹³⁶⁸ - Making default constructor of `hpx::mutex` `constexpr`
- PR #6076¹³⁶⁹ - Cleaning up functionality that was deprecated in V1.7
- PR #6075¹³⁷⁰ - Remove conditional code for gcc V7 and below

¹³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6101>

¹³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6100>

¹³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6098>

¹³⁵¹ <https://github.com/TheHPXProject/hpx/pull/6096>

¹³⁵² <https://github.com/TheHPXProject/hpx/pull/6095>

¹³⁵³ <https://github.com/TheHPXProject/hpx/pull/6094>

¹³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6093>

¹³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6092>

¹³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6091>

¹³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6090>

¹³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6088>

¹³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6086>

¹³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6085>

¹³⁶¹ <https://github.com/TheHPXProject/hpx/pull/6084>

¹³⁶² <https://github.com/TheHPXProject/hpx/pull/6083>

¹³⁶³ <https://github.com/TheHPXProject/hpx/pull/6082>

¹³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6081>

¹³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6080>

¹³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6079>

¹³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6078>

¹³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6077>

¹³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6076>

¹³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6075>

- PR #6074¹³⁷¹ - Fixing compilation issues on gcc V8
- PR #6073¹³⁷² - Fixing PAPI counter component compilation
- PR #6072¹³⁷³ - Adding `ex::when_all_vector`
- PR #6071¹³⁷⁴ - Making `get_forward_progress_guarantee_t` specializations `constexpr`
- PR #6070¹³⁷⁵ - Implement P2690 for our algorithms
- PR #6069¹³⁷⁶ - Do not check for cancellation during each iteration but only once per partition
- PR #6068¹³⁷⁷ - Prevent using `task` and `non_task` as a CPO
- PR #6067¹³⁷⁸ - Deprecated `hpx::util::mem_fn` in favor of `hpx::mem_fn`
- PR #6066¹³⁷⁹ - Create `codeql.yml`
- PR #6064¹³⁸⁰ - Adapting `adjacent_difference` for S/R execution
- PR #6063¹³⁸¹ - Modernize `iterator_support` module
- PR #6062¹³⁸² - Make sure wrapping executor does not go out of scope prematurely
- PR #6061¹³⁸³ - Minor fix in `small_vector` (from upstream)
- PR #6060¹³⁸⁴ - Allow to disable registering signal handlers
- PR #6059¹³⁸⁵ - [P2300] Fix: `declval` cannot be ODR used
- PR #6058¹³⁸⁶ - Avoid ambiguity for `hpx::get` used with `std::variant`
- PR #6057¹³⁸⁷ - Create a dedicated thread pool to run `LCI_progress`.
- PR #6056¹³⁸⁸ - Fix coroutine test for clang
- PR #6055¹³⁸⁹ - Patches needed to be able to build HPX 1.8.1 on various platforms
- PR #6054¹³⁹⁰ - Use MSVC specific attribute `[[msvc::no_unique_address]]`
- PR #6052¹³⁹¹ - Deprecated `hpx::util::invoke_fused` in favor of `hpx::invoke_fused`
- PR #6051¹³⁹² - Add non-contiguous index queue and use it in `thread_pool_bulk_scheduler`
- PR #6049¹³⁹³ - Crosscompile arm sve

¹³⁷¹ <https://github.com/TheHPXProject/hpx/pull/6074>

¹³⁷² <https://github.com/TheHPXProject/hpx/pull/6073>

¹³⁷³ <https://github.com/TheHPXProject/hpx/pull/6072>

¹³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6071>

¹³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6070>

¹³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6069>

¹³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6068>

¹³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6067>

¹³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6066>

¹³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6064>

¹³⁸¹ <https://github.com/TheHPXProject/hpx/pull/6063>

¹³⁸² <https://github.com/TheHPXProject/hpx/pull/6062>

¹³⁸³ <https://github.com/TheHPXProject/hpx/pull/6061>

¹³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6060>

¹³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6059>

¹³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6058>

¹³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6057>

¹³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6056>

¹³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6055>

¹³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6054>

¹³⁹¹ <https://github.com/TheHPXProject/hpx/pull/6052>

¹³⁹² <https://github.com/TheHPXProject/hpx/pull/6051>

¹³⁹³ <https://github.com/TheHPXProject/hpx/pull/6049>

- PR #6048¹³⁹⁴ - Deprecated `hpx::util::invoke` in favor of `hpx::invoke`
- PR #6047¹³⁹⁵ - Separating `binary_semaphore` into its own file
- PR #6046¹³⁹⁶ - Support using unwrapping with nullary function objects
- PR #6044¹³⁹⁷ - Generalize the use of `then()` and dataflow
- PR #6043¹³⁹⁸ - Clean up `scan_partitioner`
- PR #6042¹³⁹⁹ - Modernize dataflow API
- PR #6041¹⁴⁰⁰ - docs: document semaphores
- PR #6040¹⁴⁰¹ - Add/Fix documentation of Public API page
- PR #6039¹⁴⁰² - remove MPI dependency when only using LCI parcelport
- PR #6038¹⁴⁰³ - Clean up command line handling
- PR #6037¹⁴⁰⁴ - Avoid performing parcel related background work if networking is disabled
- PR #6036¹⁴⁰⁵ - Support new datapar backend : SVE
- PR #6035¹⁴⁰⁶ - Simplify datapar replace copy if
- PR #6034¹⁴⁰⁷ - Add/Fix documentation of Public API
- PR #6033¹⁴⁰⁸ - Support for data-parallelism for `replace`, `replace_if`, `replace_copy`, `replace_copy_if` algorithms
- PR #6032¹⁴⁰⁹ - Add documentation in public API
- PR #6031¹⁴¹⁰ - Expose available cache sizes from topology object
- PR #6030¹⁴¹¹ - Adding parcelport initialization hook for resource partitioner operation
- PR #6029¹⁴¹² - Simplify startup code
- PR #6027¹⁴¹³ - Add/Fix documentation in Public API page
- PR #6026¹⁴¹⁴ - add option `hpx:force_ipv4` to force resolving hostnames to ipv4 addresses
- PR #6025¹⁴¹⁵ - build(docs): remove leftover sections
- PR #6023¹⁴¹⁶ - Minor fixes on “How to build on Windows”

¹³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6048>

¹³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6047>

¹³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6046>

¹³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6044>

¹³⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6043>

¹³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6042>

¹⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6041>

¹⁴⁰¹ <https://github.com/TheHPXProject/hpx/pull/6040>

¹⁴⁰² <https://github.com/TheHPXProject/hpx/pull/6039>

¹⁴⁰³ <https://github.com/TheHPXProject/hpx/pull/6038>

¹⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6037>

¹⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6036>

¹⁴⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6035>

¹⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6034>

¹⁴⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6033>

¹⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6032>

¹⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/6031>

¹⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/6030>

¹⁴¹² <https://github.com/TheHPXProject/hpx/pull/6029>

¹⁴¹³ <https://github.com/TheHPXProject/hpx/pull/6027>

¹⁴¹⁴ <https://github.com/TheHPXProject/hpx/pull/6026>

¹⁴¹⁵ <https://github.com/TheHPXProject/hpx/pull/6025>

¹⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/6023>

- PR #6022¹⁴¹⁷ - build(doxy): don't extract private members
- PR #6021¹⁴¹⁸ - Adding pu_mask to thread_pool_bulk_scheduler
- PR #6020¹⁴¹⁹ - docs: add cppref NamedRequirements support
- PR #6018¹⁴²⁰ - Unseq adaptation for for_each, transform, reduce, transform_reduce, etc.
- PR #6017¹⁴²¹ - loop and transform_loop unseq adaptation
- PR #6016¹⁴²² - Config and structural updates to support unseq implementation
- PR #6015¹⁴²³ - Integrating sync_wait & sync_wait_with_variant
- PR #6012¹⁴²⁴ - docs: add missing links to public api
- PR #6009¹⁴²⁵ - Fixing sender&receiver integration with for_each and for_loop
- PR #6007¹⁴²⁶ - docs: add docs for mutex.hpp
- PR #6006¹⁴²⁷ - Relax future::is_ready where possible
- PR #6005¹⁴²⁸ - reshuffle header tests to different instances
- PR #6004¹⁴²⁹ - Add documentation Public API
- PR #6003¹⁴³⁰ - Always exporting get_component_name implementations
- PR #6002¹⁴³¹ - Making sure that default constructible arguments are properly constructed during deserialization
- PR #5996¹⁴³² - Add back explicit template parameters to lock_guards for nvcc
- PR #5994¹⁴³³ - Fix CTRL+C on windows
- PR #5993¹⁴³⁴ - Using EVE requires C++20
- PR #5992¹⁴³⁵ - This properly terminates an application on Ctrl-C on Windows
- PR #5991¹⁴³⁶ - Support IPV6 on command line for explicit network initialization
- PR #5990¹⁴³⁷ - P2300 enhancements
- PR #5989¹⁴³⁸ - Fix missing documentation in Public API page
- PR #5987¹⁴³⁹ - Attempting to fix timed executor API

¹⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/6022>

¹⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/6021>

¹⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/6020>

¹⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/6018>

¹⁴²¹ <https://github.com/TheHPXProject/hpx/pull/6017>

¹⁴²² <https://github.com/TheHPXProject/hpx/pull/6016>

¹⁴²³ <https://github.com/TheHPXProject/hpx/pull/6015>

¹⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/6012>

¹⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/6009>

¹⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/6007>

¹⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/6006>

¹⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/6005>

¹⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/6004>

¹⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/6003>

¹⁴³¹ <https://github.com/TheHPXProject/hpx/pull/6002>

¹⁴³² <https://github.com/TheHPXProject/hpx/pull/5996>

¹⁴³³ <https://github.com/TheHPXProject/hpx/pull/5994>

¹⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/5993>

¹⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/5992>

¹⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/5991>

¹⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/5990>

¹⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/5989>

¹⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/5987>

- PR #5986¹⁴⁴⁰ - Fix warnings when building docs
- PR #5985¹⁴⁴¹ - Re-add deprecated tag_policy_tag et.al. types that were removed in V1.8.1
- PR #5981¹⁴⁴² - docs: add docs for condition_variable.hpp
- PR #5980¹⁴⁴³ - More work on execution::read
- PR #5979¹⁴⁴⁴ - Remove support for clang-v8 and clang-v9, switch LSU clang-v13 to C++17
- PR #5977¹⁴⁴⁵ - fix: Compilation errors for -std=c++17 builders
- PR #5975¹⁴⁴⁶ - docs: fix & improve parallel algorithms documentation 5
- PR #5974¹⁴⁴⁷ - [P2300] Adapt get completion signatures for awaitable senders
- PR #5973¹⁴⁴⁸ - defaults boost.context on riscv64
- PR #5972¹⁴⁴⁹ - Fix documentation for container algorithms
- PR #5971¹⁴⁵⁰ - added logic to detect riscv compiler configured for 64 bit target
- PR #5968¹⁴⁵¹ - adds risc-v 64 bit support
- PR #5967¹⁴⁵² - Adding missing pieces to sync_wait, adding run_loop
- PR #5966¹⁴⁵³ - docs: fix & improve parallel algorithms documentation 4
- PR #5965¹⁴⁵⁴ - Fixing inspect problems, adding missing header file
- PR #5962¹⁴⁵⁵ - Changes in html page of documentation
- PR #5961¹⁴⁵⁶ - Prevent stalling during shutdown when running hello_world_distributed
- PR #5955¹⁴⁵⁷ - Fix documentation for container algorithms
- PR #5952¹⁴⁵⁸ - docs: fix & improve parallel algorithms documentation 3
- PR #5950¹⁴⁵⁹ - Change executors to directly implement the executor CPOs
- PR #5949¹⁴⁶⁰ - Converting async combinators into CPOs
- PR #5948¹⁴⁶¹ - Adding support for pure sender/receiver based executors to parallel algorithms
- PR #5945¹⁴⁶² - [P2300] Added fundamental coroutine_traits for S/R

¹⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5986>

¹⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/5985>

¹⁴⁴² <https://github.com/TheHPXProject/hpx/pull/5981>

¹⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/5980>

¹⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5979>

¹⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5977>

¹⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5975>

¹⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5974>

¹⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5973>

¹⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5972>

¹⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5971>

¹⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/5968>

¹⁴⁵² <https://github.com/TheHPXProject/hpx/pull/5967>

¹⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/5966>

¹⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5965>

¹⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5962>

¹⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5961>

¹⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5955>

¹⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5952>

¹⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5950>

¹⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5949>

¹⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/5948>

¹⁴⁶² <https://github.com/TheHPXProject/hpx/pull/5945>

- PR #5883¹⁴⁶³ - Optimization on LCI parcelport: uses LCI_putva
- PR #5872¹⁴⁶⁴ - Block fork join executor
- PR #5855¹⁴⁶⁵ - Adding performance test Jenkins builder at LSU

HPX V1.8.1 (Aug 5, 2022)

This is a bugfix release with a few minor additions and resolved problems.

General changes

This patch release adds a number of small new features and fixes a handful of problems discovered since the last release, in particular:

- A lot of work has been done to improve vectorization support for our parallel algorithms. HPX now supports using EVE - the Expressive Vector Engine as a vectorization backend.
- Added a simple average power consumption performance counter.
- Added performance counters related to the use of zero-copy chunks in the networking layer.
- More work was done towards full compatibility with the sender/receivers proposal P2300.
- Fixing `sync_wait` to decay the result types
- Fixed collective operations to properly avoid overalapping consecutive operations on the same communicator.
- Simplified the implementation of our execution policies and added mapping functions between those.
- Fixed performance issues with our implementation of *small_vector*.
- Serialization now works with buffers of unsigned characters.
- Fixing dangling reference in serialization of non-default constructible types
- Fixed static linking on Windows.
- Fixed support for M1/MacOS based architectures.
- Fixed support for gentoo/musl.
- Fixed `hpx::counting_semaphore_var`.
- Properly check start and end bounds for `hpx::for_loop`
- A lot of changes and fixes to the documentation (see <https://hpx-docs.stellar-group.org>).

¹⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/5883>

¹⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5872>

¹⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5855>

Breaking changes

- No breaking changes have been introduced.

Closed issues

- [Issue #5964](#)¹⁴⁶⁶ - component with multiple inheritance
- [Issue #5946](#)¹⁴⁶⁷ - `dll_dlopen.hpp`: error: `RTLD_DI_ORIGIN` was not declared in this scope with `musl` libc
- [Issue #5925](#)¹⁴⁶⁸ - Simplify implementation of execution policies
- [Issue #5924](#)¹⁴⁶⁹ - `{what}`: `mmap()` failed to allocate thread stack: `HPX(unhandled_exception)`
- [Issue #5912](#)¹⁴⁷⁰ - collectives all gather hangs if rank 0 is not involved
- [Issue #5902](#)¹⁴⁷¹ - MPI `parcelport` issue on Fugaku
- [Issue #5900](#)¹⁴⁷² - Unable to build `hello_world_distributed.cpp`.
- [Issue #5892](#)¹⁴⁷³ - Problems with HPX serialization as a standalone feature. Testcase provided.
- [Issue #5886](#)¹⁴⁷⁴ - Segfault when serializing non default constructible class with `stl` containers data members
- [Issue #5832](#)¹⁴⁷⁵ - Distributed execution crash
- [Issue #5768](#)¹⁴⁷⁶ - HPX hangs on `Perlmutter`
- [Issue #5735](#)¹⁴⁷⁷ - `hpx::for_loop` executes without checking start and end bounds
- [Issue #5700](#)¹⁴⁷⁸ - `HPX(serialization_error)`

Closed pull requests

- [PR #5970](#)¹⁴⁷⁹ - Fixing component multiple inheritance
- [PR #5969](#)¹⁴⁸⁰ - Fixing `sync_wait` to avoid dangling references
- [PR #5963](#)¹⁴⁸¹ - Fixing `sync_wait` to decay the result types
- [PR #5960](#)¹⁴⁸² - docs: added name to documentation contributors list
- [PR #5959](#)¹⁴⁸³ - Fixing `sync_wait` to decay the result types

¹⁴⁶⁶ <https://github.com/TheHPXProject/hpx/issues/5964>

¹⁴⁶⁷ <https://github.com/TheHPXProject/hpx/issues/5946>

¹⁴⁶⁸ <https://github.com/TheHPXProject/hpx/issues/5925>

¹⁴⁶⁹ <https://github.com/TheHPXProject/hpx/issues/5924>

¹⁴⁷⁰ <https://github.com/TheHPXProject/hpx/issues/5912>

¹⁴⁷¹ <https://github.com/TheHPXProject/hpx/issues/5902>

¹⁴⁷² <https://github.com/TheHPXProject/hpx/issues/5900>

¹⁴⁷³ <https://github.com/TheHPXProject/hpx/issues/5892>

¹⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/5886>

¹⁴⁷⁵ <https://github.com/TheHPXProject/hpx/issues/5832>

¹⁴⁷⁶ <https://github.com/TheHPXProject/hpx/issues/5768>

¹⁴⁷⁷ <https://github.com/TheHPXProject/hpx/issues/5735>

¹⁴⁷⁸ <https://github.com/TheHPXProject/hpx/issues/5700>

¹⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5970>

¹⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5969>

¹⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/5963>

¹⁴⁸² <https://github.com/TheHPXProject/hpx/pull/5960>

¹⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/5959>

- PR #5954¹⁴⁸⁴ - refactor: rename itr to correct type (*reduce*)
- PR #5954¹⁴⁸⁵ - refactor: rename itr to correct type (*reduce*)
- PR #5953¹⁴⁸⁶ - Fixed property handling in hierarchical_spawning
- PR #5951¹⁴⁸⁷ - Fixing static linking (for Windows)
- PR #5947¹⁴⁸⁸ - Fix building on musl.
- PR #5944¹⁴⁸⁹ - added adaptive_static_chunk_size
- PR #5943¹⁴⁹⁰ - Fix sync_wait
- PR #5942¹⁴⁹¹ - Fix doc warnings
- PR #5941¹⁴⁹² - Fix sync_wait
- PR #5940¹⁴⁹³ - Protect collective operations against std::vector<bool> idiosyncrasies
- PR #5939¹⁴⁹⁴ - docs: fix & improve parallel algorithms documentation 2
- PR #5938¹⁴⁹⁵ - Properly implement generation support for collective operations
- PR #5937¹⁴⁹⁶ - Remove leftover files from PMR based small_vector
- PR #5936¹⁴⁹⁷ - Adding mapping functions between execution policies
- PR #5935¹⁴⁹⁸ - Fixing serialization to work with buffers of unsigned chars
- PR #5934¹⁴⁹⁹ - Attempting to fix datapar issues on CircleCI
- PR #5933¹⁵⁰⁰ - Fix documentation for ranges algorithms
- PR #5932¹⁵⁰¹ - Remove mimalloc version constraint
- PR #5931¹⁵⁰² - docs: fix & improve parallel algorithms documentation
- PR #5930¹⁵⁰³ - Add boost to hip builder
- PR #5929¹⁵⁰⁴ - Apply fixes to M1/MacOS related stack allocation to all relevant spots
- PR #5928¹⁵⁰⁵ - updated context_generic_context to accommodate arm64_arch_8/Apple architecture
- PR #5927¹⁵⁰⁶ - Public derivation for counting_semaphore_var

¹⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5954>

¹⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5954>

¹⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5953>

¹⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5951>

¹⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5947>

¹⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5944>

¹⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5943>

¹⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/5942>

¹⁴⁹² <https://github.com/TheHPXProject/hpx/pull/5941>

¹⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/5940>

¹⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5939>

¹⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5938>

¹⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5937>

¹⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5936>

¹⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5935>

¹⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5934>

¹⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5933>

¹⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/5932>

¹⁵⁰² <https://github.com/TheHPXProject/hpx/pull/5931>

¹⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/5930>

¹⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5929>

¹⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5928>

¹⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5927>

- PR #5926¹⁵⁰⁷ - Fix doxygen warnings when building documentation
- PR #5923¹⁵⁰⁸ - Fixing git checkout to reflect latest version tag
- PR #5922¹⁵⁰⁹ - A couple of unrelated changes in support of implementing P1673
- PR #5920¹⁵¹⁰ - [P2300] enhancements: receiver_of, sender_of improvements
- PR #5917¹⁵¹¹ - Fixing various ‘held lock while suspending’ problems
- PR #5916¹⁵¹² - Fix minor doxygen parsing typo
- PR #5915¹⁵¹³ - docs: fix broken api algo links
- PR #5914¹⁵¹⁴ - Remove CSS rules - update sphinx version
- PR #5911¹⁵¹⁵ - Removed references to hpx::vector in comments
- PR #5909¹⁵¹⁶ - Remove stuff which is defined in the header
- PR #5906¹⁵¹⁷ - Use BUILD_SHARED_LIBS correctly
- PR #5905¹⁵¹⁸ - Fix incorrect usage of generator expressions
- PR #5904¹⁵¹⁹ - Delete FindBZip2.cmake
- PR #5901¹⁵²⁰ - Fix #5900
- PR #5899¹⁵²¹ - Replace PMR based version of small_vector
- PR #5897¹⁵²² - Add missing “”
- PR #5896¹⁵²³ - Docs: Add serialization tutorial.
- PR #5895¹⁵²⁴ - Update to V1.9.0 on master
- PR #5894¹⁵²⁵ - Fix executor_with_thread_hooks example
- PR #5890¹⁵²⁶ - Adding simple average power consumption performance counter
- PR #5889¹⁵²⁷ - Par unseq/unseq adding
- PR #5888¹⁵²⁸ - Support for data-parallelism for reduce, transform reduce, transform_binary_reduce algorithms
- PR #5887¹⁵²⁹ - Fixing dangling reference in serialization of non-default constructible types

¹⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5926>

¹⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5923>

¹⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5922>

¹⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/5920>

¹⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/5917>

¹⁵¹² <https://github.com/TheHPXProject/hpx/pull/5916>

¹⁵¹³ <https://github.com/TheHPXProject/hpx/pull/5915>

¹⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/5914>

¹⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/5911>

¹⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/5909>

¹⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/5906>

¹⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/5905>

¹⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/5904>

¹⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/5901>

¹⁵²¹ <https://github.com/TheHPXProject/hpx/pull/5899>

¹⁵²² <https://github.com/TheHPXProject/hpx/pull/5897>

¹⁵²³ <https://github.com/TheHPXProject/hpx/pull/5896>

¹⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/5895>

¹⁵²⁵ <https://github.com/TheHPXProject/hpx/pull/5894>

¹⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/5890>

¹⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/5889>

¹⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/5888>

¹⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/5887>

- [PR #5879](#)¹⁵³⁰ - New performance counters related to zero-copy chunks.

HPX V1.8.0 (May 18, 2022)

With HPX parallel algorithms been fully adapted to C++20 the new release achieves full conformance with C++20 concurrency and parallelism facilities. HPX now supports all of the algorithms as specified by C++20. We have added support for vectorization to more of our algorithms. Much work has been done towards implementing P2300 (“std::execution”) and implementing the underlying senders/receivers facilities. Finally, The new release comes with a brand new documentation interface!

General changes

- The new documentation can now be found on our webpage: <https://hpx-docs.stellar-group.org>. This includes a completely new and user-friendly interface environment along with restructuring of certain components. The content in the “Quick start”, “Manual” and “Examples” was improved, while the “Build system” page was adapted to include necessary information for newcomers.
- With the vectorization support available in modern hardware architectures HPX now provides new data-parallel vector execution policies `hpx::execution::simd` and `hpx::execution::par_simd` that enable significant speed-up of our parallel algorithm implementations. The following algorithms now support SIMD execution:
 - `copy`, `copy_n`
 - `generate`
 - `adjacent_difference`, `adjacent_find`
 - `all_of`, `any_of`, `none_of`
 - `equal`, `mismatch`,
 - `inner_product`
 - `count`, `count_if`
 - `fill`, `fill_n`
 - `find`, `find_end`, `find_first_of`, `find_if`, `find_if_not`
 - `for_each`, `for_each_n`
 - `generate`, `generate_n`.
- Based on top of P2300 the HPX parallel algorithms now support the pipeline syntax towards an effort to unify their usage along with senders/receivers. The HPX parallel algorithms can now bind with senders/receivers using the pipeline operator.
- Several changes took place on the executors provided by HPX:
- The executors now support the `num_cores` options in order for the user to be able to specify the desired number of cores to be used in the corresponding execution.
- The `scheduler` executor was implemented on top of senders/receivers and can be used with all HPX facilities that schedule new work, such as parallel algorithms, `hpx::async`, `hpx::dataflow`, etc.
- The performance of `fork_join_executor` was improved.
- The following algorithms have been added/adapted to be C++20 conformant:
 - `min_element`

¹⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/5879>

- `max_element`
 - `minmax_element`
 - `starts_with`
 - `ends_with`
 - `swap_ranges`
 - `unique`
 - `unique_copy`
 - `rotate`
 - `rotate_copy`
 - `sort`
 - `shift_left`
 - `shift_right`
 - `stable_sort`
 - `partition`
 - `partition_copy`
 - `stable_partition`
 - `adjacent_difference`
 - `nth_element`
 - `partial_sort`
 - `partial_sort_copy`.
- HPX_FORWARD/HPX_MOVE macros were introduced that replaced the `std::move` and `std::forward` facilities that in the library code.
 - Hangs on distributed barrier were fixed.
 - The performance of `scan_partitioner` was improved.
 - Support was added for `thread_priority` to the `parallel_execution_policy`
 - Regarding senders/receivers and the P2300 proposal various actions took place. `stop_token` was adapted to the recent proposal version (`in_place_stop_token` was introduced). Also `hint`, `annotation`, `priority` and `stacksize` properties were added to the scheduler executor. Stop support was added to `when_all`. Support for completion signatures was added. The following schedulers and algorithms were added:
 - `get_completion_scheduler`
 - `any_sender` and `unique_any_sender`
 - `split` sender
 - `transform_mpi` sender
 - `transfer` sender
 - `let_error`, `let_stopped`
 - `get_env` and related environment queries
 - `schedule`, `set_value`, `set_error`, `set_done`, `start` and `connect` are now proper customization points as defined in P2300.

- Several namespaces were altered towards conformance with C++20. Compatibility layers have been added and the old versions will be removed in next releases. The namespace changes are the following:
 - `hpx::parallel::induction/reduction` were moved into namespace `hpx::experimental`
 - `for_loop` and friends were moved into namespace `hpx::experimental`.
 - `hpx::util::optional` and friends were moved into namespace `hpx`.
 - `hpx::lcos::barrier` has been moved into the `hpx::distributed` namespace and `hpx::lcos::local::cpp20_barrier` has been renamed to `barrier` and moved into the `hpx` namespace.
 - `hpx::lcos::latch` has been moved into the `hpx::distributed` namespace and `lcos::local::latch` has been moved into the `hpx` namespace. The `count_down_and_wait()` functionality of `latch` has been renamed to `arrive_and_wait()`.
 - `hpx::util::unique_function_nonsr` has been renamed to `hpx::move_only_function`.
 - `hpx::util::unique_function` has been renamed to `hpx::distributed::move_only_function`.
 - `hpx::util::function` has been renamed to `hpx::distributed::function`.
 - `hpx::util::function_nonsr` has been renamed to `hpx::function`.
 - `hpx::util::function_ref` have been moved to namespace `hpx`.
 - `hpx::lcos::split_future` changed namespace and is now used as `hpx::split_future`.
 - `hpx::lcos::local::counting_semaphore` has been deprecated and `hpx::lcos::local::cpp20_counting_semaphore` has been renamed to `hpx::counting_semaphore`.
 - `hpx::lcos::local::cpp20_binary_semaphore` has been renamed to `hpx::binary_semaphore`.
 - `hpx::lcos::local::sliding_semaphore` has been renamed to `hpx::sliding_semaphore` and
 - `hpx::lcos::local::sliding_semaphore_var` has been renamed to `hpx::sliding_semaphore_var`.
 - `hpx::lcos::local::spinlock` has been renamed to `hpx::spinlock`.
 - `hpx::lcos::local::mutex` has been renamed to `hpx::mutex`.
 - `hpx::lcos::local::timed_mutex` has been renamed to `hpx::timed_mutex`.
 - `hpx::lcos::local::no_mutex` has been renamed to `hpx::no_mutex`.
 - `hpx::lcos::local::recursive_mutex` has been renamed to `hpx::recursive_mutex`.
 - `hpx::lcos::local::shared_mutex` has been renamed to `hpx::shared_mutex`.
 - `hpx::lcos::local::upgrade_lock` has been renamed to `hpx::upgrade_lock`.
 - `hpx::lcos::local::upgrade_to_unique_lock` has been renamed to `hpx::upgrade_to_unique_lock`.
 - `hpx::lcos::local::condition_variable` has been renamed to `hpx::condition_variable`.
`hpx::lcos::local::condition_variable_var` has been renamed to `hpx::condition_variable_var`.
 - `hpx::lcos::local::once_flag` has been renamed to `hpx::once_flag`, and `hpx::lcos::local::call_once` has been renamed to `hpx::call_once`.
- The new LCI (Lightweight Communication Interface) `parcelport` was added that supports irregular and asynchronous applications like graph analysis, sparse linear algebra, modern parallel architectures etc. Major features include:

- Support for advanced communication primitives like two sided send/recv and one sided remote put.
- Better multi-threaded performance.
- Explicit user control of communication resource.
- Flexible signaling mechanisms (synchronizer, completion queue, active message handler).
- The following CMake flags were added, mostly to support using HPX as a backend for SHAD (<https://github.com/pnnl/SHAD>). Please note that these options enable questionable functionalities, partially they even enable undefined behavior. Please only use any of them if you know what you're doing:
 - HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION
 - HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE
 - HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS

Breaking changes

- Minimum required C++ standard library is C++17.
- Support for GCC 7 and Clang 8.0.0 and below has been removed.
- CUDA version required updated to 11.4.
- CMake version required updated to 3.18.
- The default version of Asio used was updated to 1.20.0.
- The default version of APEX used was updated to 2.5.1.
- APEX version was updated to 2.5.1.
- `tagged_pair` and `tagged_tuple` were removed.
- `tag_dispatch` was renamed to `tag_invoke`.
- `hpx.max_backgroud_threads` was renamed to `hpx.parcel.max_background_threads`.
- The following CMake flags were removed after being deprecated for at least two releases:
 - HPX_SCHEDULER_MAX_TERMINATED_THREADS
 - HPX_WITH_GOOGLE_PERFTOOLS
 - HPX_WITH_INIT_START_OVERLOADS_COMPATIBILITY
 - HPX_HAVE_{COROUTINE,PLUGIN}_GCC_HIDDEN_VISIBILITY
 - HPX_TOP_LEVEL
 - HPX_WITH_COMPUTE_CUDA
 - HPX_WITH_ASYNC_CUDA
- `annotate_function` was renamed to `scoped_annotation`.
- `execution::transform` was renamed to `execution::then`.
- `execution::detach` was renamed to `execution::start_detached`.
- `execution::on_sender` was renamed to `execution::schedule_on`.
- `execution::just_on` was renamed to `execution::just_transfer`.
- `execution::set_done` was renamed to `execution::set_stopped`.

Closed issues

- [Issue #5871](#)¹⁵³¹ - distributed::channel.regisiter_as terminates the active task.
- [Issue #5856](#)¹⁵³² - Performance counters do not compile
- [Issue #5828](#)¹⁵³³ - hpx::distributed:barrier errors
- [Issue #5812](#)¹⁵³⁴ - OctoTiger does not compile with HPX master and CUDA 11.5
- [Issue #5784](#)¹⁵³⁵ - HPX failing with co_await and hpx::when_all(futures)
- [Issue #5774](#)¹⁵³⁶ - CMake can't find HPXCacheVariables.cmake
- [Issue #5764](#)¹⁵³⁷ - Fix HIP problem
- [Issue #5724](#)¹⁵³⁸ - Missing binary filter compression header
- [Issue #5721](#)¹⁵³⁹ - Cleanup after repository split
- [Issue #5701](#)¹⁵⁴⁰ - It seems that the tcp parcelport is running, and the MPI parcelport is ignored
- [Issue #5692](#)¹⁵⁴¹ - Kokkos compilation fails when using both HPX and CUDA execution spaces with gcc 9.3.0
- [Issue #5686](#)¹⁵⁴² - Rename *annotate_function*
- [Issue #5668](#)¹⁵⁴³ - HPX does not detect the C++ 20 standard using gcc 11.2
- [Issue #5666](#)¹⁵⁴⁴ - Compilation error using boost 1.76 and gcc 11.2.1
- [Issue #5653](#)¹⁵⁴⁵ - Implement P2248 for our algorithms
- [Issue #5647](#)¹⁵⁴⁶ - [User input needed] Remove (CUDA) compute functionality?
- [Issue #5590](#)¹⁵⁴⁷ - hello_world_distributed fails on startup with HPX stable, MPICH 3.3.2, on Deep Bayou
- [Issue #5570](#)¹⁵⁴⁸ - Rename tag_dispatch to tag_invoke
- [Issue #5566](#)¹⁵⁴⁹ - can't build simple example: "Cannot use the dummy implementation of future_then_dispatch"
- [Issue #5565](#)¹⁵⁵⁰ - build failure: hpx::string_util::trim()
- [Issue #5553](#)¹⁵⁵¹ - Github action to validate the cff file refs #5471
- [Issue #5504](#)¹⁵⁵² - CMake does not work for HPX 1.7.0 on Piz Daint

¹⁵³¹ <https://github.com/TheHPXProject/hpx/issues/5871>

¹⁵³² <https://github.com/TheHPXProject/hpx/issues/5856>

¹⁵³³ <https://github.com/TheHPXProject/hpx/issues/5828>

¹⁵³⁴ <https://github.com/TheHPXProject/hpx/issues/5812>

¹⁵³⁵ <https://github.com/TheHPXProject/hpx/issues/5784>

¹⁵³⁶ <https://github.com/TheHPXProject/hpx/issues/5774>

¹⁵³⁷ <https://github.com/TheHPXProject/hpx/issues/5764>

¹⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/5724>

¹⁵³⁹ <https://github.com/TheHPXProject/hpx/issues/5721>

¹⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/5701>

¹⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/5692>

¹⁵⁴² <https://github.com/TheHPXProject/hpx/issues/5686>

¹⁵⁴³ <https://github.com/TheHPXProject/hpx/issues/5668>

¹⁵⁴⁴ <https://github.com/TheHPXProject/hpx/issues/5666>

¹⁵⁴⁵ <https://github.com/TheHPXProject/hpx/issues/5653>

¹⁵⁴⁶ <https://github.com/TheHPXProject/hpx/issues/5647>

¹⁵⁴⁷ <https://github.com/TheHPXProject/hpx/issues/5590>

¹⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/5570>

¹⁵⁴⁹ <https://github.com/TheHPXProject/hpx/issues/5566>

¹⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/5565>

¹⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/5553>

¹⁵⁵² <https://github.com/TheHPXProject/hpx/issues/5504>

- [Issue #5503](#)¹⁵⁵³ - Use contiguous index queue in bulk execution to reduce number of spawned tasks
- [Issue #5502](#)¹⁵⁵⁴ - C++20 `std::coroutine` cmake detection
- [Issue #5478](#)¹⁵⁵⁵ - `hpx.dll` built with `vcpkg` got functions pointing to the same location
- [Issue #5472](#)¹⁵⁵⁶ - Compilation error with `cuda/11.3`
- [Issue #5469](#)¹⁵⁵⁷ - Compiler warning about `HPX_NODISCARD` when building with APEX
- [Issue #5463](#)¹⁵⁵⁸ - Address minor comments of the C++17 PR bump
- [Issue #5456](#)¹⁵⁵⁹ - Use `std::ranges::iter_swap` where available
- [Issue #5404](#)¹⁵⁶⁰ - Build fails with error “Cannot open include file `asio/io_context.hpp`”
- [Issue #5381](#)¹⁵⁶¹ - Add `starts_with` and `ends_with` algorithms
- [Issue #5344](#)¹⁵⁶² - Further simplify `tag_invoke` helpers
- [Issue #5269](#)¹⁵⁶³ - Allow setting a label on executors/policies
- [Issue #5219](#)¹⁵⁶⁴ - (Re-)Implement executor API on top of sender/receiver infrastructure
- [Issue #5216](#)¹⁵⁶⁵ - Performance counter module not loading
- [Issue #5162](#)¹⁵⁶⁶ - Require C++17 support
- [Issue #5156](#)¹⁵⁶⁷ - Disentangle segmented algorithms
- [Issue #5118](#)¹⁵⁶⁸ - Lock held while suspending
- [Issue #5111](#)¹⁵⁶⁹ - Tests fail to build with `binary_filter` plugins enabled
- [Issue #5110](#)¹⁵⁷⁰ - Tests don't get built
- [Issue #5105](#)¹⁵⁷¹ - PAPI performance counters not available
- [Issue #5002](#)¹⁵⁷² - `hpx::lcos::barrier()` results in deadlock
- [Issue #4992](#)¹⁵⁷³ - Clang-format the rest of the files
- [Issue #4987](#)¹⁵⁷⁴ - Use `std::function` in public APIs
- [Issue #4871](#)¹⁵⁷⁵ - HEP: conformance to C++20

¹⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/5503>

¹⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/5502>

¹⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/5478>

¹⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/5472>

¹⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/5469>

¹⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/5463>

¹⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/5456>

¹⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/5404>

¹⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/5381>

¹⁵⁶² <https://github.com/TheHPXProject/hpx/issues/5344>

¹⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/5269>

¹⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/5219>

¹⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/5216>

¹⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/5162>

¹⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/5156>

¹⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/5118>

¹⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/5111>

¹⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/5110>

¹⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/5105>

¹⁵⁷² <https://github.com/TheHPXProject/hpx/issues/5002>

¹⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/4992>

¹⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/4987>

¹⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/4871>

- [Issue #4822](#)¹⁵⁷⁶ - Adapt parallel algorithms to C++20
- [Issue #4736](#)¹⁵⁷⁷ - Deprecate `hpx::flush` and `hpx::endl`
- [Issue #4558](#)¹⁵⁷⁸ - Prevent work-stealing from stalling
- [Issue #4495](#)¹⁵⁷⁹ - Add anchor links to table rows in documentation
- [Issue #4469](#)¹⁵⁸⁰ - New thread state: *pending_low*
- [Issue #4321](#)¹⁵⁸¹ - After the modularization the `libfabric` `parcelpoint` does not compile
- [Issue #4308](#)¹⁵⁸² - Using APEX on multinode jobs when `HPX_WITH_NETWORKING = OFF`
- [Issue #3995](#)¹⁵⁸³ - Use C++20 `std::source_location` where available, adapt ours to conform
- [Issue #3861](#)¹⁵⁸⁴ - Selected processor does not support ‘yield’ in ARM mode
- [Issue #3706](#)¹⁵⁸⁵ - Add `shift_left` and `shift_right` algorithms
- [Issue #3646](#)¹⁵⁸⁶ - Parallel algorithms should accept iterator/sentinel pairs
- [Issue #3636](#)¹⁵⁸⁷ - HPX Modularization
- [Issue #3546](#)¹⁵⁸⁸ - Modularization of HPX
- [Issue #3474](#)¹⁵⁸⁹ - Modernize CMake used in HPX
- [Issue #1836](#)¹⁵⁹⁰ - `hpx::parallel` does not have a sort implementation
- [Issue #1668](#)¹⁵⁹¹ - Adapt all parallel algorithms to Ranges TS
- [Issue #1141](#)¹⁵⁹² - Implement N4409 on top of HPX

Closed pull requests

- [PR #5885](#)¹⁵⁹³ - Testing newer ASIO version
- [PR #5884](#)¹⁵⁹⁴ - Fix miscellaneous doc sections
- [PR #5882](#)¹⁵⁹⁵ - Fixing OctoTiger incompatibility introduced recently
- [PR #5881](#)¹⁵⁹⁶ - Fixing recent patch that disables `ATOMIC_FLAG_INIT` for C++20 and up
- [PR #5880](#)¹⁵⁹⁷ - refactor: convert *counter_status* enum to enum class

¹⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/4822>

¹⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/4736>

¹⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/4558>

¹⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/4495>

¹⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/4469>

¹⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/4321>

¹⁵⁸² <https://github.com/TheHPXProject/hpx/issues/4308>

¹⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/3995>

¹⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/3861>

¹⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/3706>

¹⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/3646>

¹⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3636>

¹⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/3546>

¹⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/3474>

¹⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1836>

¹⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/1668>

¹⁵⁹² <https://github.com/TheHPXProject/hpx/issues/1141>

¹⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/5885>

¹⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5884>

¹⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5882>

¹⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5881>

¹⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5880>

- PR #5878¹⁵⁹⁸ - Docs: Replaced non-existent create_reducer function with create_communicator
- PR #5877¹⁵⁹⁹ - Doc updates hpx runtime and resources
- PR #5876¹⁶⁰⁰ - Updates to documentation; grammar edits.
- PR #5875¹⁶⁰¹ - Doc updates starting the hpx runtime
- PR #5874¹⁶⁰² - Doc updates launching configuring
- PR #5873¹⁶⁰³ - Prevent certain generated files from being deleted on reconfigure
- PR #5870¹⁶⁰⁴ - Adding support for the PJM batch environment
- PR #5867¹⁶⁰⁵ - Update CMakeLists.txt
- PR #5866¹⁶⁰⁶ - add cmake option HPX_WITH_PARCELPORNT_COUNTERS
- PR #5864¹⁶⁰⁷ - ATOMIC_INIT_FLAG is deprecated starting C++20
- PR #5863¹⁶⁰⁸ - Adding llvm 14.0.0 with boost 1.79.0 to Jenkins
- PR #5861¹⁶⁰⁹ - Let install step proceed on CircleCI even if the segmented algorithms fail
- PR #5860¹⁶¹⁰ - Updating APEX tag
- PR #5859¹⁶¹¹ - Splitting documentation generation steps on CircleCI
- PR #5854¹⁶¹² - Fixing left-overs from changing counter_type to enum class
- PR #5853¹⁶¹³ - Adding HPX dependency tool (adapted from Boostdep tool)
- PR #5852¹⁶¹⁴ - Optimize LCI parcellport
- PR #5851¹⁶¹⁵ - Forking dynamic_bitset from Boost
- PR #5850¹⁶¹⁶ - Convert perf_counters::counter_type enum to enum class.
- PR #5849¹⁶¹⁷ - Update LCI parcellport to LCI v1.7.1
- PR #5848¹⁶¹⁸ - Fedora related fixes
- PR #5847¹⁶¹⁹ - Fix API, troubleshooting & people
- PR #5844¹⁶²⁰ - Attempting to fix timeouts of segmented iterator tests

¹⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5878>

¹⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5877>

¹⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5876>

¹⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/5875>

¹⁶⁰² <https://github.com/TheHPXProject/hpx/pull/5874>

¹⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/5873>

¹⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5870>

¹⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5867>

¹⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5866>

¹⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5864>

¹⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5863>

¹⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5861>

¹⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/5860>

¹⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/5859>

¹⁶¹² <https://github.com/TheHPXProject/hpx/pull/5854>

¹⁶¹³ <https://github.com/TheHPXProject/hpx/pull/5853>

¹⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/5852>

¹⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/5851>

¹⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/5850>

¹⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/5849>

¹⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/5848>

¹⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/5847>

¹⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/5844>

- PR #5842¹⁶²¹ - change the default value of HPX_WITH_LCI_TAG to v1.7
- PR #5841¹⁶²² - Move the split_future facilities into the namespace hpx
- PR #5840¹⁶²³ - wait_XXX_nothrow functions return whether one of the futures is exceptional
- PR #5839¹⁶²⁴ - Moving a list of synchronization primitives into namespace hpx
- PR #5837¹⁶²⁵ - Moving latch types to hpx and hpx::distributed namespaces
- PR #5835¹⁶²⁶ - Add missing compatibility layer for id_type::management_type values
- PR #5834¹⁶²⁷ - API docs changes
- PR #5831¹⁶²⁸ - Further improvement actions to rotate
- PR #5830¹⁶²⁹ - Exposing zero-copy serialization threshold through configuration option
- PR #5829¹⁶³⁰ - Attempting to fix failing barrier test
- PR #5827¹⁶³¹ - Add back explicit template parameter to *ignore_while_checking* to compile with nvcc
- PR #5826¹⁶³² - Reduce number of allocations while calling *async_bulk_execute*
- PR #5825¹⁶³³ - Steal from neighboring NUMA domain only
- PR #5823¹⁶³⁴ - Remove obsolete directories and adjust build system
- PR #5822¹⁶³⁵ - Clang-format remaining files
- PR #5821¹⁶³⁶ - Enable permissive- flag on Windows GitHub actions builders
- PR #5820¹⁶³⁷ - Convert throwmode enum to enum class
- PR #5819¹⁶³⁸ - Marking customization points for intrusive_ptr as noexcept
- PR #5818¹⁶³⁹ - Unconditionally use C++17 attributes
- PR #5817¹⁶⁴⁰ - Modernize naming modules
- PR #5816¹⁶⁴¹ - Modernize cache module
- PR #5815¹⁶⁴² - Reapply flyby changes from #5467
- PR #5814¹⁶⁴³ - Avoid test timeouts by reducing test sizes

¹⁶²¹ <https://github.com/TheHPXProject/hpx/pull/5842>

¹⁶²² <https://github.com/TheHPXProject/hpx/pull/5841>

¹⁶²³ <https://github.com/TheHPXProject/hpx/pull/5840>

¹⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/5839>

¹⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/5837>

¹⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/5835>

¹⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/5834>

¹⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/5831>

¹⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/5830>

¹⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/5829>

¹⁶³¹ <https://github.com/TheHPXProject/hpx/pull/5827>

¹⁶³² <https://github.com/TheHPXProject/hpx/pull/5826>

¹⁶³³ <https://github.com/TheHPXProject/hpx/pull/5825>

¹⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/5823>

¹⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/5822>

¹⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/5821>

¹⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/5820>

¹⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/5819>

¹⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/5818>

¹⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5817>

¹⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/5816>

¹⁶⁴² <https://github.com/TheHPXProject/hpx/pull/5815>

¹⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/5814>

- PR #5813¹⁶⁴⁴ - The CUDA problem is not fixed in V11.5 yet...
- PR #5811¹⁶⁴⁵ - Make sure reduction value is properly moved, when possible
- PR #5810¹⁶⁴⁶ - Improve error reporting during device initialization in HIP environments
- PR #5809¹⁶⁴⁷ - Converting scheduler enums into enum class
- PR #5808¹⁶⁴⁸ - Deprecate `hpx::flush` and friends
- PR #5807¹⁶⁴⁹ - Use C++20 `std::source_location`, if available
- PR #5806¹⁶⁵⁰ - Moving `promise` and `packaged_task` to new namespaces
- PR #5805¹⁶⁵¹ - Attempting to fix a test failure when using the LCI `parcelpor`
- PR #5803¹⁶⁵² - Attempt to fix CUDA related `OctoTiger` problems
- PR #5800¹⁶⁵³ - Add option to restrict MPI background work to subset of cores
- PR #5798¹⁶⁵⁴ - Adding MPI as a dependency to APEX
- PR #5797¹⁶⁵⁵ - Extend Sphinx role to support arbitrary text to display on a link
- PR #5796¹⁶⁵⁶ - Disable CUDA tests that cause NVCC to silently fail without error messages
- PR #5795¹⁶⁵⁷ - Avoid writing path and directories into `HPXCacheVariables.cmake`
- PR #5793¹⁶⁵⁸ - Remove features that are deprecated since V1.6
- PR #5792¹⁶⁵⁹ - Making sure `num_cores` is properly handled by `parallel_executor`
- PR #5791¹⁶⁶⁰ - Moving `bind`, `bind_front`, `bind_back` to namespace `hpx`
- PR #5790¹⁶⁶¹ - Moving serializable function/`move_only_function` into namespace `hpx::distributed`
- PR #5787¹⁶⁶² - Remove unneeded (and commented) tests
- PR #5786¹⁶⁶³ - Attempting to fix hangs in distributed barrier
- PR #5785¹⁶⁶⁴ - add `cmake` code to detect `arm64` on `macOS`
- PR #5783¹⁶⁶⁵ - Moving `function` and `function_ref` into namespace `hpx`
- PR #5781¹⁶⁶⁶ - Updating used version of Visual Studio

¹⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5813>

¹⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5811>

¹⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5810>

¹⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5809>

¹⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5808>

¹⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5807>

¹⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5806>

¹⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/5805>

¹⁶⁵² <https://github.com/TheHPXProject/hpx/pull/5803>

¹⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/5800>

¹⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5798>

¹⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5797>

¹⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5796>

¹⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5795>

¹⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5793>

¹⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5792>

¹⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5791>

¹⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/5790>

¹⁶⁶² <https://github.com/TheHPXProject/hpx/pull/5787>

¹⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/5786>

¹⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5785>

¹⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5783>

¹⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5781>

- PR #5780¹⁶⁶⁷ - Update Piz Daint Jenkins configurations from gcc/clang 7 to 8
- PR #5778¹⁶⁶⁸ - Updated for_loop.hpp
- PR #5777¹⁶⁶⁹ - Update reference for foreach benchmark
- PR #5775¹⁶⁷⁰ - Move optional into namespace hpx
- PR #5773¹⁶⁷¹ - Moving barrier to consolidated namespaces
- PR #5772¹⁶⁷² - Adding missing docs for ranges::find_if and find_if_not algorithms
- PR #5771¹⁶⁷³ - Moving for_loop into namespace hpx::experimental
- PR #5770¹⁶⁷⁴ - Fixing HIP issues
- PR #5769¹⁶⁷⁵ - Slight improvement of small_vector performance
- PR #5766¹⁶⁷⁶ - Fixing a integral conversion warning
- PR #5765¹⁶⁷⁷ - Adding a sphinx role allowing to link to a file directly in github
- PR #5763¹⁶⁷⁸ - add num_cores facility
- PR #5762¹⁶⁷⁹ - Fix Public API main page
- PR #5761¹⁶⁸⁰ - Add missing inline to mpi_exception.hpp error_message function
- PR #5760¹⁶⁸¹ - Update cdash build url
- PR #5759¹⁶⁸² - Switch to use generic rostam SLURM partitions
- PR #5758¹⁶⁸³ - Adding support for P2300 completion signatures
- PR #5757¹⁶⁸⁴ - Fix missing links in Public API
- PR #5756¹⁶⁸⁵ - Add stop support to when_all
- PR #5755¹⁶⁸⁶ - Support for data-parallelism for mismatch algorithm
- PR #5754¹⁶⁸⁷ - Support for data-parallelism for equal algorithm
- PR #5751¹⁶⁸⁸ - Propagate MPI dependencies to command line handling
- PR #5750¹⁶⁸⁹ - Make sure required MPI initialization flags are properly applied and supported

¹⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5780>

¹⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5778>

¹⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5777>

¹⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5775>

¹⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/5773>

¹⁶⁷² <https://github.com/TheHPXProject/hpx/pull/5772>

¹⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/5771>

¹⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5770>

¹⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5769>

¹⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5766>

¹⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5765>

¹⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5763>

¹⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5762>

¹⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5761>

¹⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/5760>

¹⁶⁸² <https://github.com/TheHPXProject/hpx/pull/5759>

¹⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/5758>

¹⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5757>

¹⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5756>

¹⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5755>

¹⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5754>

¹⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5751>

¹⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5750>

- PR #5749¹⁶⁹⁰ - P2300 stop token
- PR #5748¹⁶⁹¹ - Adding environmental query CPOs
- PR #5747¹⁶⁹² - Renaming set_done to set_stopped (as per P2300)
- PR #5745¹⁶⁹³ - Modernize serialization module
- PR #5743¹⁶⁹⁴ - Add check for MPICH and set the correct env to support multi-threaded
- PR #5742¹⁶⁹⁵ - Remove obsolete files related to cpuid, etc.
- PR #5741¹⁶⁹⁶ - Support for data-parallelism for adjacent find
- PR #5740¹⁶⁹⁷ - Support for data-parallelism for find algorithms
- PR #5739¹⁶⁹⁸ - Enable the option to attach a debugger on a segmentation fault (linux)
- PR #5738¹⁶⁹⁹ - Fixing spell-checking errors
- PR #5737¹⁷⁰⁰ - Attempt to fix migrate_component issue
- PR #5736¹⁷⁰¹ - Set commit status from Jenkins also for special branches
- PR #5734¹⁷⁰² - Revert #5586
- PR #5732¹⁷⁰³ - Attempt to improve build-id reporting to cdash
- PR #5731¹⁷⁰⁴ - Randomly delay execution of bash scripts launched by Jenkins
- PR #5729¹⁷⁰⁵ - Workaround for CMake/Ninja generator OOM problem
- PR #5727¹⁷⁰⁶ - Moving compression plugins to components directory
- PR #5726¹⁷⁰⁷ - Moving/consolidating parcel coalescing plugin sources
- PR #5725¹⁷⁰⁸ - Making sure headers for serialization filters are being installed
- PR #5723¹⁷⁰⁹ - Moving more tests to modules
- PR #5722¹⁷¹⁰ - Removing superfluous semicolons
- PR #5720¹⁷¹¹ - Moving parcelports into modules
- PR #5719¹⁷¹² - Moving more files to parcelset module

¹⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5749>

¹⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/5748>

¹⁶⁹² <https://github.com/TheHPXProject/hpx/pull/5747>

¹⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/5745>

¹⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5743>

¹⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5742>

¹⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5741>

¹⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5740>

¹⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5739>

¹⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5738>

¹⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5737>

¹⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/5736>

¹⁷⁰² <https://github.com/TheHPXProject/hpx/pull/5734>

¹⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/5732>

¹⁷⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5731>

¹⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5729>

¹⁷⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5727>

¹⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5726>

¹⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5725>

¹⁷⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5723>

¹⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/5722>

¹⁷¹¹ <https://github.com/TheHPXProject/hpx/pull/5720>

¹⁷¹² <https://github.com/TheHPXProject/hpx/pull/5719>

- PR #5718¹⁷¹³ - build: refactor sphinx config file
- PR #5717¹⁷¹⁴ - Creating parcelset modules
- PR #5716¹⁷¹⁵ - Avoid duplicate definition error
- PR #5715¹⁷¹⁶ - The new LCI parcelport for HPX
- PR #5714¹⁷¹⁷ - Refine propagation of **HPX_WITH**... options
- PR #5713¹⁷¹⁸ - Significantly reduce CI jobs run on Piz Daint
- PR #5712¹⁷¹⁹ - Updating jenkins configuration for Rostam2.2
- PR #5711¹⁷²⁰ - Refactor manual sections
- PR #5710¹⁷²¹ - Making task_group serializable
- PR #5709¹⁷²² - Update the MPI cmake setup
- PR #5707¹⁷²³ - Better diagnose parcel bootstrap problems
- PR #5704¹⁷²⁴ - Test with hwloc 2.7.0 with GCC 11
- PR #5703¹⁷²⁵ - Fix *counting_iterator* container tests
- PR #5702¹⁷²⁶ - Attempting to fix CircleCI timeouts
- PR #5699¹⁷²⁷ - Update CI to use Boost 1.78.0
- PR #5697¹⁷²⁸ - Adding fork_join_executor to foreach_benchmark
- PR #5696¹⁷²⁹ - Modernize when_all and friends (when_any, when_some, when_each)
- PR #5693¹⁷³⁰ - Fix test errors with *_GLIBCXX_DEBUG* defined
- PR #5691¹⁷³¹ - Rename *annotate_function* to *scoped_annotation*
- PR #5690¹⁷³² - Replace tag_dispatch with tag_invoke in minmax segmented
- PR #5688¹⁷³³ - Remove more deprecated macros
- PR #5687¹⁷³⁴ - Add most important CMake options
- PR #5685¹⁷³⁵ - Fix future API

¹⁷¹³ <https://github.com/TheHPXProject/hpx/pull/5718>

¹⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/5717>

¹⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/5716>

¹⁷¹⁶ <https://github.com/TheHPXProject/hpx/pull/5715>

¹⁷¹⁷ <https://github.com/TheHPXProject/hpx/pull/5714>

¹⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/5713>

¹⁷¹⁹ <https://github.com/TheHPXProject/hpx/pull/5712>

¹⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/5711>

¹⁷²¹ <https://github.com/TheHPXProject/hpx/pull/5710>

¹⁷²² <https://github.com/TheHPXProject/hpx/pull/5709>

¹⁷²³ <https://github.com/TheHPXProject/hpx/pull/5707>

¹⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/5704>

¹⁷²⁵ <https://github.com/TheHPXProject/hpx/pull/5703>

¹⁷²⁶ <https://github.com/TheHPXProject/hpx/pull/5702>

¹⁷²⁷ <https://github.com/TheHPXProject/hpx/pull/5699>

¹⁷²⁸ <https://github.com/TheHPXProject/hpx/pull/5697>

¹⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/5696>

¹⁷³⁰ <https://github.com/TheHPXProject/hpx/pull/5693>

¹⁷³¹ <https://github.com/TheHPXProject/hpx/pull/5691>

¹⁷³² <https://github.com/TheHPXProject/hpx/pull/5690>

¹⁷³³ <https://github.com/TheHPXProject/hpx/pull/5688>

¹⁷³⁴ <https://github.com/TheHPXProject/hpx/pull/5687>

¹⁷³⁵ <https://github.com/TheHPXProject/hpx/pull/5685>

- PR #5684¹⁷³⁶ - Move lock registration to separate module and remove global lock registration
- PR #5683¹⁷³⁷ - Make `hpx::wait_all` etc. throw exceptions when waited futures hold exceptions and deprecate `hpx::lcos::wait_all[_n]` in favor of `hpx::wait_all[_n]`
- PR #5682¹⁷³⁸ - Fix macOS test exceptions
- PR #5681¹⁷³⁹ - docs: add links to hpx recepies
- PR #5680¹⁷⁴⁰ - Embed base execution policies to datapar execution policies
- PR #5679¹⁷⁴¹ - Fix *fork_join_executor* with dynamic schedule
- PR #5678¹⁷⁴² - Fix compilation of service executors with nvcc
- PR #5677¹⁷⁴³ - Remove `compute_cuda` module
- PR #5676¹⁷⁴⁴ - Don't require up-to-date approvals for bors
- PR #5675¹⁷⁴⁵ - Add default template type parameters for algorithms
- PR #5674¹⁷⁴⁶ - Allow using *any_sender* in global variables
- PR #5671¹⁷⁴⁷ - Making sure `task_group` can be reused
- PR #5670¹⁷⁴⁸ - Relax constraints on *execution::when_all*
- PR #5669¹⁷⁴⁹ - Use `HPX_WITH_CXX_STANDARD` for controlling C++ version
- PR #5667¹⁷⁵⁰ - Attempt to fix compilation issues with Boost V1.76
- PR #5664¹⁷⁵¹ - Change logging errors to warnings in schedulers
- PR #5663¹⁷⁵² - Use dynamic bitsets by default for CPU masks
- PR #5662¹⁷⁵³ - Disambiguate namespace for MSVC
- PR #5660¹⁷⁵⁴ - Replacing remaining `std::forward` and `std::move` with `HPX_FORWARD` and `HPX_MOVE`
- PR #5659¹⁷⁵⁵ - Modernize `hpx::future` and related facilities
- PR #5658¹⁷⁵⁶ - Replace `HPX_INLINE_CONSTEXPR_VARIABLE` with `inline constexpr`
- PR #5657¹⁷⁵⁷ - Remove `tagged`, `tagged_pair` and `tagged_tuple`, remove tuple/pair specializations
- PR #5656¹⁷⁵⁸ - Rename `on_execution::schedule_from`, rename `just_on` to `just_transfer`, and add `transfer`

¹⁷³⁶ <https://github.com/TheHPXProject/hpx/pull/5684>

¹⁷³⁷ <https://github.com/TheHPXProject/hpx/pull/5683>

¹⁷³⁸ <https://github.com/TheHPXProject/hpx/pull/5682>

¹⁷³⁹ <https://github.com/TheHPXProject/hpx/pull/5681>

¹⁷⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5680>

¹⁷⁴¹ <https://github.com/TheHPXProject/hpx/pull/5679>

¹⁷⁴² <https://github.com/TheHPXProject/hpx/pull/5678>

¹⁷⁴³ <https://github.com/TheHPXProject/hpx/pull/5677>

¹⁷⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5676>

¹⁷⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5675>

¹⁷⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5674>

¹⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5671>

¹⁷⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5670>

¹⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5669>

¹⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5667>

¹⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/5664>

¹⁷⁵² <https://github.com/TheHPXProject/hpx/pull/5663>

¹⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/5662>

¹⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5660>

¹⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5659>

¹⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5658>

¹⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5657>

¹⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5656>

- [PR #5655](#)¹⁷⁵⁹ - Avoid for module lists to grow indefinitely in cmake cache
- [PR #5649](#)¹⁷⁶⁰ - build: replace usage of Python's reserved words and functions as variable names
- [PR #5648](#)¹⁷⁶¹ - Modernize action modules and related code
- [PR #5646](#)¹⁷⁶² - Fix ends_with test
- [PR #5645](#)¹⁷⁶³ - Add matrix multiplication example
- [PR #5644](#)¹⁷⁶⁴ - Rename execution::transform to execution::then and execution::detach to execution::start_detached
- [PR #5643](#)¹⁷⁶⁵ - Update performance test references
- [PR #5642](#)¹⁷⁶⁶ - Adapting adjacent_difference to work with proxy iterators
- [PR #5641](#)¹⁷⁶⁷ - Factorize perf tests scripts
- [PR #5640](#)¹⁷⁶⁸ - Fixed links to sources in Sphinx documentation
- [PR #5639](#)¹⁷⁶⁹ - Fix generate datapar tests for Vc
- [PR #5638](#)¹⁷⁷⁰ - Simd all any none
- [PR #5637](#)¹⁷⁷¹ - Use bors for merging pull requests
- [PR #5636](#)¹⁷⁷² - Fix leftover std::holds_alternative usage
- [PR #5635](#)¹⁷⁷³ - Update container image tag in GitHub actions HIP configuration
- [PR #5633](#)¹⁷⁷⁴ - Moving packaged_task to module futures
- [PR #5632](#)¹⁷⁷⁵ - Tell Asio to use std::aligned_new only if available
- [PR #5631](#)¹⁷⁷⁶ - Adding tag parameter to channel communicator get/set
- [PR #5630](#)¹⁷⁷⁷ - Add partial_sort_copy and adapt partial sort to c++ 20
- [PR #5629](#)¹⁷⁷⁸ - Set HPX_WITH_FETCH_ASIO to OFF as available in the docker image
- [PR #5628](#)¹⁷⁷⁹ - Add Clang 13 CI configuration
- [PR #5627](#)¹⁷⁸⁰ - Replace alternative keyword
- [PR #5626](#)¹⁷⁸¹ - docs: add support for BibTeX references in Sphinx docs

¹⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5655>

¹⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5649>

¹⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/5648>

¹⁷⁶² <https://github.com/TheHPXProject/hpx/pull/5646>

¹⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/5645>

¹⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5644>

¹⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5643>

¹⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5642>

¹⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5641>

¹⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5640>

¹⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5639>

¹⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5638>

¹⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/5637>

¹⁷⁷² <https://github.com/TheHPXProject/hpx/pull/5636>

¹⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/5635>

¹⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5633>

¹⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5632>

¹⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5631>

¹⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5630>

¹⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5629>

¹⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5628>

¹⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5627>

¹⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/5626>

- PR #5624¹⁷⁸² - Fix pkgconfig replacements involving CMAKE_INSTALL_PREFIX
- PR #5623¹⁷⁸³ - build: remove unused import from conf.py.in
- PR #5622¹⁷⁸⁴ - Remove HPX_WITH_VCPKG CMake option
- PR #5621¹⁷⁸⁵ - Replacing boost::container::small_vector
- PR #5620¹⁷⁸⁶ - Update Asio tag from 1.18.2 to 1.20.0
- PR #5619¹⁷⁸⁷ - Fix block_os_threads_1036 test
- PR #5618¹⁷⁸⁸ - Make sure condition variables are notified under a lock in the thread_pool_scheduler test
- PR #5617¹⁷⁸⁹ - Use advance_and_get_distance where required
- PR #5616¹⁷⁹⁰ - Remove separately building segmented algorithms on CircleCI
- PR #5613¹⁷⁹¹ - Fix Vc datapar adjacent_difference
- PR #5609¹⁷⁹² - docs: add anchor links to performance counter tables
- PR #5608¹⁷⁹³ - Fix header test error by adding missing numeric
- PR #5607¹⁷⁹⁴ - Fix simd adj diff
- PR #5605¹⁷⁹⁵ - Fix usage of HPX_INVOKE macro
- PR #5604¹⁷⁹⁶ - Make use of shell-session to allow non-copyable \$
- PR #5603¹⁷⁹⁷ - Suppress some MSVC warnings in C++20 mode
- PR #5602¹⁷⁹⁸ - Test HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE=OFF to one CI configuration
- PR #5601¹⁷⁹⁹ - Test case for any_sender should use hpx::tuple
- PR #5600¹⁸⁰⁰ - Rename tag_dispatch back to tag_invoke
- PR #5599¹⁸⁰¹ - Change theme, fix Quickstart & Examples
- PR #5596¹⁸⁰² - Use precompiled headers in tests
- PR #5595¹⁸⁰³ - Drop semicolons for macro calls
- PR #5594¹⁸⁰⁴ - Adapt datapar generate

¹⁷⁸² <https://github.com/TheHPXProject/hpx/pull/5624>

¹⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/5623>

¹⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5622>

¹⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5621>

¹⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5620>

¹⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5619>

¹⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5618>

¹⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5617>

¹⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5616>

¹⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/5613>

¹⁷⁹² <https://github.com/TheHPXProject/hpx/pull/5609>

¹⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/5608>

¹⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5607>

¹⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5605>

¹⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5604>

¹⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5603>

¹⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5602>

¹⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5601>

¹⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5600>

¹⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/5599>

¹⁸⁰² <https://github.com/TheHPXProject/hpx/pull/5596>

¹⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/5595>

¹⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5594>

- [PR #5593](#)¹⁸⁰⁵ - Update any_sender to use tag_dispatch for execution customizations
- [PR #5592](#)¹⁸⁰⁶ - Add nth_element
- [PR #5591](#)¹⁸⁰⁷ - Remove unnecessary checks for C++17 for tests
- [PR #5589](#)¹⁸⁰⁸ - Add HPX_FORWARD/HPX_MOVE macros
- [PR #5588](#)¹⁸⁰⁹ - Fixing the output formatting for id_types
- [PR #5586](#)¹⁸¹⁰ - Remove local functionality
- [PR #5585](#)¹⁸¹¹ - Delete GitExternal.cmake
- [PR #5584](#)¹⁸¹² - Serialization of hpx::tuple must use hpx::get
- [PR #5583](#)¹⁸¹³ - fix coroutine_traits allocate calls, add unhandled_exception() implementation.
- [PR #5582](#)¹⁸¹⁴ - Make more examples work with local runtime
- [PR #5581](#)¹⁸¹⁵ - Add support for several performance tests in CI
- [PR #5580](#)¹⁸¹⁶ - Adapt simd adj diff
- [PR #5579](#)¹⁸¹⁷ - Split absolute paths for generated pkg-config files into -L/-I parts
- [PR #5577](#)¹⁸¹⁸ - fix unit fill test for datapar with Vc
- [PR #5576](#)¹⁸¹⁹ - Update forgotten “Full” names
- [PR #5575](#)¹⁸²⁰ - Change scan partitioner implementation
- [PR #5574](#)¹⁸²¹ - Remove a few deprecated and unused CMake options
- [PR #5572](#)¹⁸²² - Remove more guards for the distributed runtime
- [PR #5571](#)¹⁸²³ - Add workaround for libstc++ in string_util trim
- [PR #5569](#)¹⁸²⁴ - Use no_unique_address in sender adaptors
- [PR #5568](#)¹⁸²⁵ - Change try catch block to try_catch_exception_ptr
- [PR #5567](#)¹⁸²⁶ - Make default_agent::yield actually yield
- [PR #5564](#)¹⁸²⁷ - Adjacent

¹⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5593>

¹⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5592>

¹⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5591>

¹⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5589>

¹⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5588>

¹⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/5586>

¹⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/5585>

¹⁸¹² <https://github.com/TheHPXProject/hpx/pull/5584>

¹⁸¹³ <https://github.com/TheHPXProject/hpx/pull/5583>

¹⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/5582>

¹⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/5581>

¹⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/5580>

¹⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/5579>

¹⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/5577>

¹⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/5576>

¹⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/5575>

¹⁸²¹ <https://github.com/TheHPXProject/hpx/pull/5574>

¹⁸²² <https://github.com/TheHPXProject/hpx/pull/5572>

¹⁸²³ <https://github.com/TheHPXProject/hpx/pull/5571>

¹⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/5569>

¹⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/5568>

¹⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/5567>

¹⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/5564>

- PR #5562¹⁸²⁸ - More changes to overcome build problems on Windows after recent module rearrangements
- PR #5560¹⁸²⁹ - Update tests and examples
- PR #5559¹⁸³⁰ - Fixing cmake folder names after module restructuring
- PR #5558¹⁸³¹ - Fixing wrong module dependencies
- PR #5557¹⁸³² - Adding an example for the new channel_communicator API
- PR #5556¹⁸³³ - Remove leftover thread pool os executor tests
- PR #5555¹⁸³⁴ - Add option enabling serializing raw pointers
- PR #5554¹⁸³⁵ - Make sure command line aliasing is properly handled
- PR #5552¹⁸³⁶ - Modernizing some of the async facilities
- PR #5551¹⁸³⁷ - Fixing for local executions of actions to properly set task names
- PR #5550¹⁸³⁸ - Update CUDA module in clang-cuda configuration
- PR #5549¹⁸³⁹ - Fixing agent_ref::yield_k to actually call yield_k
- PR #5548¹⁸⁴⁰ - Making get_action_name() noexcept
- PR #5547¹⁸⁴¹ - Fixing communication set
- PR #5546¹⁸⁴² - Fixing shutdown problems caused by missing ref-counting
- PR #5545¹⁸⁴³ - Remove wrong move in thread_pool_scheduler_bulk.hpp
- PR #5543¹⁸⁴⁴ - Extend launch policy to carry stack size and scheduling hint in addition to priority
- PR #5542¹⁸⁴⁵ - Simplify execution CPOs
- PR #5540¹⁸⁴⁶ - Adapt partition, partition_copy and stable_partition to C++ 20
- PR #5539¹⁸⁴⁷ - Adapt mismatch to support sentinels
- PR #5538¹⁸⁴⁸ - Document specific sphinx version required for the documentation
- PR #5537¹⁸⁴⁹ - Test release and debug builds on Piz Daint
- PR #5536¹⁸⁵⁰ - This fixes referencing stale iterators during the execution of binary mismatch

¹⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/5562>

¹⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/5560>

¹⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/5559>

¹⁸³¹ <https://github.com/TheHPXProject/hpx/pull/5558>

¹⁸³² <https://github.com/TheHPXProject/hpx/pull/5557>

¹⁸³³ <https://github.com/TheHPXProject/hpx/pull/5556>

¹⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/5555>

¹⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/5554>

¹⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/5552>

¹⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/5551>

¹⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/5550>

¹⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/5549>

¹⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5548>

¹⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/5547>

¹⁸⁴² <https://github.com/TheHPXProject/hpx/pull/5546>

¹⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/5545>

¹⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5543>

¹⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5542>

¹⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5540>

¹⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5539>

¹⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5538>

¹⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5537>

¹⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5536>

- PR #5535¹⁸⁵¹ - Rename `simdpar` to `par_simd`
- PR #5534¹⁸⁵² - Fix Quick start & Manual Docs
- PR #5533¹⁸⁵³ - Fix `annotate_function` for `std::string`
- PR #5532¹⁸⁵⁴ - Update two remaining apex links from khuck to UO-OACISS
- PR #5531¹⁸⁵⁵ - Use `contiguous_index_queue` in `thread_pool_scheduler`
- PR #5530¹⁸⁵⁶ - Eagerly initialize a configurable number of threads on scheduler/thread queue init
- PR #5529¹⁸⁵⁷ - Update benchmarks and add support for `scheduler_executor`
- PR #5528¹⁸⁵⁸ - Add missing properties to executors/schedulers
- PR #5527¹⁸⁵⁹ - Set local thread/pool number in `local/static_queue_scheduler`
- PR #5526¹⁸⁶⁰ - Update Rostam HIP configuration to use 4.3.0
- PR #5525¹⁸⁶¹ - Fix Building HPX in Quick start
- PR #5524¹⁸⁶² - Upload image on cdash
- PR #5523¹⁸⁶³ - Modernize facilities related to `hpx::sync`
- PR #5522¹⁸⁶⁴ - Add sender overloads for remaining algorithms
- PR #5521¹⁸⁶⁵ - Minor changes that improve performance
- PR #5520¹⁸⁶⁶ - Update reference as perftests failing regularly
- PR #5519¹⁸⁶⁷ - Add `transform_mpi` sender adapter
- PR #5518¹⁸⁶⁸ - Add sender overloads to `rotate/rotate_copy`
- PR #5517¹⁸⁶⁹ - Fix coroutine integration
- PR #5515¹⁸⁷⁰ - Avoid deadlock in `ignore_while_locked_1485` test
- PR #5514¹⁸⁷¹ - Add split sender adapter
- PR #5512¹⁸⁷² - Update Rostam HIP configuration
- PR #5511¹⁸⁷³ - Fix Asio target name for precompiled headers

¹⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/5535>

¹⁸⁵² <https://github.com/TheHPXProject/hpx/pull/5534>

¹⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/5533>

¹⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5532>

¹⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5531>

¹⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5530>

¹⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5529>

¹⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5528>

¹⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5527>

¹⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5526>

¹⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/5525>

¹⁸⁶² <https://github.com/TheHPXProject/hpx/pull/5524>

¹⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/5523>

¹⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5522>

¹⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5521>

¹⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5520>

¹⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5519>

¹⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5518>

¹⁸⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5517>

¹⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5515>

¹⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/5514>

¹⁸⁷² <https://github.com/TheHPXProject/hpx/pull/5512>

¹⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/5511>

- PR #5510¹⁸⁷⁴ - Add any_sender and unique_any_sender
- PR #5509¹⁸⁷⁵ - Test with Boost 1.77 on gcc/clang-newest configurations
- PR #5508¹⁸⁷⁶ - Minor release changes from 1.7.1
- PR #5507¹⁸⁷⁷ - Add missing commits from scheduler_executor PR
- PR #5506¹⁸⁷⁸ - Fix condition for checking if we should use our own variant
- PR #5501¹⁸⁷⁹ - Attempt to fix thread_pool_scheduler test
- PR #5493¹⁸⁸⁰ - Update Jenkins GitHub token to use StellarBot GitHub account
- PR #5490¹⁸⁸¹ - Fix clang-format error on master
- PR #5487¹⁸⁸² - Add get_completion_scheduler CPO and customize bulk for thread_pool_scheduler
- PR #5484¹⁸⁸³ - Add missing header to jacobi_component/server/solver.hpp
- PR #5481¹⁸⁸⁴ - Changing the APEX repository to the new location
- PR #5479¹⁸⁸⁵ - Fix version check for CUDA noexcept/result_of bug
- PR #5477¹⁸⁸⁶ - Require cxx17 minor comments
- PR #5476¹⁸⁸⁷ - Fix cmake format error
- PR #5475¹⁸⁸⁸ - Require CMake 3.18 as it is already a requirement for CUDA
- PR #5474¹⁸⁸⁹ - Make the cuda parameters of try_compile optional
- PR #5473¹⁸⁹⁰ - Update cuda arch and change cuda version
- PR #5471¹⁸⁹¹ - Add corrected citation.cff
- PR #5470¹⁸⁹² - Adapt stable_sort to C++ 20
- PR #5468¹⁸⁹³ - Experimentation to make the perfctest report public
- PR #5466¹⁸⁹⁴ - Add shift_left and shift_right algorithms
- PR #5465¹⁸⁹⁵ - Adapt datapar fill
- PR #5464¹⁸⁹⁶ - Moving tag_dispatch to separate module

¹⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5510>

¹⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5509>

¹⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5508>

¹⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5507>

¹⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5506>

¹⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5501>

¹⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5493>

¹⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/5490>

¹⁸⁸² <https://github.com/TheHPXProject/hpx/pull/5487>

¹⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/5484>

¹⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5481>

¹⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5479>

¹⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5477>

¹⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5476>

¹⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5475>

¹⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5474>

¹⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5473>

¹⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/5471>

¹⁸⁹² <https://github.com/TheHPXProject/hpx/pull/5470>

¹⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/5468>

¹⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5466>

¹⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5465>

¹⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5464>

- PR #5461¹⁸⁹⁷ - Rename HPX_WITH_CUDA_COMPUTE with HPX_WITH_COMPUTE_CUDA
- PR #5460¹⁸⁹⁸ - Adapt sort to C++ 20
- PR #5459¹⁸⁹⁹ - Adapt rotate/rotate_copy to C++20
- PR #5458¹⁹⁰⁰ - Adapt unique and unique_copy to C++ 20
- PR #5455¹⁹⁰¹ - Remove and clean up fallback sender implementations
- PR #5454¹⁹⁰² - Make performance plot show even if similar performance
- PR #5453¹⁹⁰³ - Post 1.7.0 version bump
- PR #5452¹⁹⁰⁴ - Fix find_end parallel overload
- PR #5450¹⁹⁰⁵ - Change the print-bind output to be more precise
- PR #5449¹⁹⁰⁶ - Adapt swap_ranges to C++ 20
- PR #5446¹⁹⁰⁷ - Use more verbose names in sender algorithms
- PR #5443¹⁹⁰⁸ - Properly support ASAN with MSVC
- PR #5441¹⁹⁰⁹ - Adding reference counting to thread_data
- PR #5429¹⁹¹⁰ - Scheduler executor
- PR #5428¹⁹¹¹ - Adapt datapar copy
- PR #5421¹⁹¹² - Update CI base image to use clang-format 11
- PR #5410¹⁹¹³ - Add ranges starts_with and ends_with algorithms
- PR #5383¹⁹¹⁴ - Tentatively remove runtime_registration_wrapper from cuda futures
- PR #5377¹⁹¹⁵ - Fewer Asio includes and more precompiled headers
- PR #5329¹⁹¹⁶ - Sender overloads for parallel algorithms
- PR #5313¹⁹¹⁷ - Rearrange modules between libraries
- PR #5283¹⁹¹⁸ - Require minimum C++17 and change CUDA handling
- PR #5241¹⁹¹⁹ - Adapt min_element, max_element and minmax_element to C++20

¹⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5461>

¹⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5460>

¹⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5459>

¹⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5458>

¹⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/5455>

¹⁹⁰² <https://github.com/TheHPXProject/hpx/pull/5454>

¹⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/5453>

¹⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5452>

¹⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5450>

¹⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5449>

¹⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5446>

¹⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5443>

¹⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5441>

¹⁹¹⁰ <https://github.com/TheHPXProject/hpx/pull/5429>

¹⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/5428>

¹⁹¹² <https://github.com/TheHPXProject/hpx/pull/5421>

¹⁹¹³ <https://github.com/TheHPXProject/hpx/pull/5410>

¹⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/5383>

¹⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/5377>

¹⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/5329>

¹⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/5313>

¹⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/5283>

¹⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/5241>

HPX V1.7.1 (Aug 12, 2021)

This is a bugfix release with a few minor fixes.

General changes

- Added a CMake option to assume that all types are bitwise serializable by default: `HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE`. The default value `OFF` corresponds to the old behaviour.
- Added a version check for Asio. The minimum Asio version supported by *HPX* is 1.12.0.
- Fixed a bug affecting usage of actions, where the internals of *HPX* relied on function addresses being unique. This was fixed by relying on variable addresses being unique instead.
- Made `hpx::util::bind` more strict in checking the validity of placeholders.
- Small performance improvement to spinlocks.
- Adapted the following parallel algorithms to C++20: `inclusive_scan`, `exclusive_scan`, `transform_inclusive_scan`, `transform_exclusive_scan`.

Breaking changes

- The experimental `hpx::execution::simdpair` execution policy (introduced in 1.7.0) was renamed to `hpx::execution::par_simd` for consistency with the other parallel policies.

Closed issues

- [Issue #5494](#)¹⁹²⁰ - Rename *simdpair* execution policy to *par_simd*
- [Issue #5488](#)¹⁹²¹ - `hpx::util::bind` doesn't bounds-check placeholders
- [Issue #5486](#)¹⁹²² - Possible V1.7.1 release

Closed pull requests

- [PR #5500](#)¹⁹²³ - Minor bug fix in transform exclusive and inclusive scan tests
- [PR #5499](#)¹⁹²⁴ - Rename *simdpair* to *par_simd*
- [PR #5489](#)¹⁹²⁵ - Adding bound-checking for bind placeholders
- [PR #5485](#)¹⁹²⁶ - Add Asio version check
- [PR #5482](#)¹⁹²⁷ - Change extra archive data to rely on uniqueness of a variable address, not a function address
- [PR #5448](#)¹⁹²⁸ - More fixes to enable for all types to be assumed to be bitwise copyable

¹⁹²⁰ <https://github.com/TheHPXProject/hpx/issues/5494>

¹⁹²¹ <https://github.com/TheHPXProject/hpx/issues/5488>

¹⁹²² <https://github.com/TheHPXProject/hpx/issues/5486>

¹⁹²³ <https://github.com/TheHPXProject/hpx/pull/5500>

¹⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/5499>

¹⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/5489>

¹⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/5485>

¹⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/5482>

¹⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/5448>

- [PR #5445](#)¹⁹²⁹ - Improve performance of Spinlocks
- [PR #5444](#)¹⁹³⁰ - Adapt transform_inclusive_scan to C++ 20
- [PR #5440](#)¹⁹³¹ - Adapt transform_exclusive_scan to C++ 20
- [PR #5439](#)¹⁹³² - Adapt inclusive_scan to C++ 20
- [PR #5436](#)¹⁹³³ - Adapt exclusive_scan to C++20

HPX V1.7.0 (Jul 14, 2021)

This release is again focused on C++20 conformance of algorithms. Additionally, many new experimental sender-based algorithms have been added based on the latest proposals.

General changes

- The following algorithms have been adapted to be C++20 conformant:
 - `remove`,
 - `remove_if`,
 - `remove_copy`,
 - `remove_copy_if`,
 - `replace`,
 - `replace_if`,
 - `reverse`, and
 - `lexicographical_compare`.
- When the compiler and standard library support the standard execution policies `std::execution::seq`, `std::execution::par`, and `std::execution::par_unseq` they can now be used in all *HPX* parallel algorithms with equivalent behaviour to the non-task policies `hpx::execution::seq`, `hpx::execution::par`, and `hpx::execution::par_unseq`.
- Vc support has been fixed, after being broken in 1.6.0. In addition, *HPX* now experimentally supports GCC's SIMD implementation, when available. The implementation can be used through the `hpx::execution::simd` and `hpx::execution::simdpair` execution policies.
- The customization points `sync_execute`, `async_execute`, `then_execute`, `post`, `bulk_sync_execute`, `bulk_async_execute`, and `bulk_then_execute` are now implemented using `tag_dispatch` (previously `tag_invoke`). Executors can still be implemented by providing the aforementioned functions as member functions of an executor.
- New functionality, enhancements, and fixes based on P0443r14 (executors proposal) and P1897 (sender-based algorithms) have been added to the `hpx::execution::experimental` namespace. These can be accessed through the `hpx/execution.hpp` and `hpx/local/execution.hpp` headers. In particular, the following sender-based algorithms have been added:
 - `detach`,

¹⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/5445>

¹⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/5444>

¹⁹³¹ <https://github.com/TheHPXProject/hpx/pull/5440>

¹⁹³² <https://github.com/TheHPXProject/hpx/pull/5439>

¹⁹³³ <https://github.com/TheHPXProject/hpx/pull/5436>

- `ensure_started`,
- `just`,
- `just_on`,
- `let_error`,
- `let_value`,
- `on`,
- `transform`, and
- `when_all`.

Additionally, futures now implement the sender concept. `make_future` can be used to turn a sender into a future. All functionality is experimental and can change without notice.

- All `hpx::init` and `hpx::start` overloads now take `std::functions` instead of `hpx::util::function_nonser`. No changes should be required in user code to accommodate this change.
- `hpx::util::unwrapping` and other related unwrapping functionality has been moved up into the `hpx` namespace. Names in `hpx::util` are still usable with a deprecation warning. This functionality can now be accessed through the `hpx/unwrap.hpp` and `hpx/local/unwrap.hpp` headers.
- The default tag for APEX has been update from 2.3.1 to 2.4.0. In particular, this fixes a bug which could lead to hangs in distributed runs.
- The dependency on Boost.Asio has been replaced with the standalone Asio available at <https://github.com/chriskohlhoff/asio>. By default, a system-installed Asio will be used. `ASIO_ROOT` can be given as a hint to tell CMake where to find Asio. Alternatively, Asio can be fetched automatically using CMake's `fetchcontent` by setting `HPX_WITH_FETCH_ASIO=ON`. In general, dependencies on Boost have again been reduced.
- Modularization of the library has continued. In this release almost all functionality has been moved into modules. These changes do not generally affect user code. Warnings are still issued for headers that have moved.
- `hipBLAS` is now optional when compiling with `hipcc`. A warning instead of an error will be printed if `hipBLAS` is not found during configuration.
- Previously `HPX_COMPUTE_HOST_CODE` was defined in host code only if HPX was configured with CUDA or HIP. In this release `HPX_COMPUTE_HOST_CODE` is always defined in host code.
- An experimental `HPX_WITH_PRECOMPILED_HEADERS` CMake option has been added to use precompiled headers when building *HPX*. This option should not be used on Windows.
- Numerous bug fixes.

Breaking changes

- The minimum required CMake version is now 3.17.
- The minimum required Boost version is now 1.71.0.
- The customization mechanism used to implement and extend sender functionality and algorithms has been renamed from `tag_invoke` to `tag_dispatch`. All customization of sender functionality should be done by overloading `tag_dispatch`.
- The following compatibility options have been removed, along with their compatibility implementations:
 - `HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY`
 - `HPX_WITH_ACTION_BASE_COMPATIBILITY`
 - `HPX_WITH_EMBEDDED_THREAD_POOLS_COMPATIBILITY`
 - `HPX_WITH_POOL_EXECUTOR_COMPATIBILITY`
 - `HPX_WITH_PROMISE_ALIAS_COMPATIBILITY`

HPX_WITH_REGISTER_THREAD_COMPATIBILITY - HPX_WITH_REGISTER_THREAD_OVERLOADS_COMPATIBILITY
- HPX_WITH_THREAD_AWARE_TIMER_COMPATIBILITY - HPX_WITH_THREAD_EXECUTORS_COMPATIBILITY -
HPX_WITH_THREAD_POOL_OS_EXECUTOR_COMPATIBILITY

- The HPX_WITH_THREAD_SCHEDULERS CMake option has been removed. All schedulers are now enabled when possible.
- HPX_WITH_INIT_START_OVERLOADS_COMPATIBILITY has been turned off by default.

Closed issues

- [Issue #5423](#)¹⁹³⁴ - Fix lvalue-ref qualified connect for when_all-sender
- [Issue #5412](#)¹⁹³⁵ - Link error
- [Issue #5397](#)¹⁹³⁶ - Performance regression in thread annotations
- [Issue #5395](#)¹⁹³⁷ - HPX 1.7.0-rc1 fails to build icw APEX + OTF2
- [Issue #5385](#)¹⁹³⁸ - HPX 1.7 crashes on Piz Daint > 64 nodes
- [Issue #5380](#)¹⁹³⁹ - CMake should search for asio package installed on the system
- [Issue #5378](#)¹⁹⁴⁰ - HPX 1.7.0 stopped building on Fedora
- [Issue #5369](#)¹⁹⁴¹ - HPX 1.6 and master hangs on Summit for > 64 nodes
- [Issue #5358](#)¹⁹⁴² - HPX init fails for single-core environments
- [Issue #5345](#)¹⁹⁴³ - Rename P2220 property CPOs?
- [Issue #5333](#)¹⁹⁴⁴ - HPX does not compile on the new Mac OSX using the M1 chip
- [Issue #5317](#)¹⁹⁴⁵ - Consider making hipblas optional
- [Issue #5306](#)¹⁹⁴⁶ - asio fails to build with CUDA 10.0
- [Issue #5294](#)¹⁹⁴⁷ - `execution::on` should be based on `execution::schedule`
- [Issue #5275](#)¹⁹⁴⁸ - HPX V1.6.0 fails on Fedora release
- [Issue #5270](#)¹⁹⁴⁹ - HPX-1.6.0 fails to build on Windows 10
- [Issue #5257](#)¹⁹⁵⁰ - Allow triggering the output of OS thread affinity from configuration settings
- [Issue #5246](#)¹⁹⁵¹ - HPX fails to build on ppc64le

¹⁹³⁴ <https://github.com/TheHPXProject/hpx/issues/5423>

¹⁹³⁵ <https://github.com/TheHPXProject/hpx/issues/5412>

¹⁹³⁶ <https://github.com/TheHPXProject/hpx/issues/5397>

¹⁹³⁷ <https://github.com/TheHPXProject/hpx/issues/5395>

¹⁹³⁸ <https://github.com/TheHPXProject/hpx/issues/5385>

¹⁹³⁹ <https://github.com/TheHPXProject/hpx/issues/5380>

¹⁹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/5378>

¹⁹⁴¹ <https://github.com/TheHPXProject/hpx/issues/5369>

¹⁹⁴² <https://github.com/TheHPXProject/hpx/issues/5358>

¹⁹⁴³ <https://github.com/TheHPXProject/hpx/issues/5345>

¹⁹⁴⁴ <https://github.com/TheHPXProject/hpx/issues/5333>

¹⁹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/5317>

¹⁹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/5306>

¹⁹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/5294>

¹⁹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/5275>

¹⁹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/5270>

¹⁹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/5257>

¹⁹⁵¹ <https://github.com/TheHPXProject/hpx/issues/5246>

- [Issue #5232](#)¹⁹⁵² - Annotation using `hpx::util::annotated_function` not working
- [Issue #5222](#)¹⁹⁵³ - Build and link errors with `itnotify` enabled
- [Issue #5204](#)¹⁹⁵⁴ - Move algorithms to `tag_fallback_dispatch`
- [Issue #5163](#)¹⁹⁵⁵ - Remove module-specific compatibility and deprecation options
- [Issue #5161](#)¹⁹⁵⁶ - Bump required CMake version to 3.17
- [Issue #5143](#)¹⁹⁵⁷ - Searching for HPX-Application to generate work on multiple Nodes

Closed pull requests

- [PR #5438](#)¹⁹⁵⁸ - Delete `datapar/foreach_tests.hpp`
- [PR #5437](#)¹⁹⁵⁹ - Add back explicit `-pthread` flags when available
- [PR #5435](#)¹⁹⁶⁰ - This adds support for systems that assume all types are bitwise serializable by default
- [PR #5434](#)¹⁹⁶¹ - Update CUDA polling logging to be more verbose
- [PR #5433](#)¹⁹⁶² - Fix `when_all_sender` connect for references
- [PR #5432](#)¹⁹⁶³ - Add deprecation warnings for v1.8
- [PR #5431](#)¹⁹⁶⁴ - Rename the new P0443/P2300 executor to `thread_pool_scheduler`
- [PR #5430](#)¹⁹⁶⁵ - Revert “Adding the missing defined for `HPX_HAVE_DEPRECATED_WARNINGS`”
- [PR #5427](#)¹⁹⁶⁶ - Removing unneeded `typedef`
- [PR #5426](#)¹⁹⁶⁷ - Adding more concept checks for sender/receiver algorithms
- [PR #5425](#)¹⁹⁶⁸ - Adding the missing defined for `HPX_HAVE_DEPRECATED_WARNINGS`
- [PR #5424](#)¹⁹⁶⁹ - Disable Vc in final docker image created in CI
- [PR #5422](#)¹⁹⁷⁰ - Adding `execution::experimental::bulk` algorithm
- [PR #5420](#)¹⁹⁷¹ - Update logic to find threading library
- [PR #5418](#)¹⁹⁷² - Reduce max size and number of files in `ccache` cache

¹⁹⁵² <https://github.com/TheHPXProject/hpx/issues/5232>

¹⁹⁵³ <https://github.com/TheHPXProject/hpx/issues/5222>

¹⁹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/5204>

¹⁹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/5163>

¹⁹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/5161>

¹⁹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/5143>

¹⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5438>

¹⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5437>

¹⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5435>

¹⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/5434>

¹⁹⁶² <https://github.com/TheHPXProject/hpx/pull/5433>

¹⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/5432>

¹⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5431>

¹⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5430>

¹⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5427>

¹⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5426>

¹⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5425>

¹⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5424>

¹⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5422>

¹⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/5420>

¹⁹⁷² <https://github.com/TheHPXProject/hpx/pull/5418>

- [PR #5417](#)¹⁹⁷³ - Final release notes for 1.7.0
- [PR #5416](#)¹⁹⁷⁴ - Adapt `uninitialized_value_construct` and `uninitialized_value_construct_n` to C++ 20
- [PR #5415](#)¹⁹⁷⁵ - Adapt `uninitialized_default_construct` and `uninitialized_default_construct_n` to C++ 20
- [PR #5414](#)¹⁹⁷⁶ - Improve integration of futures and senders
- [PR #5413](#)¹⁹⁷⁷ - Fixing sender/receiver code base to compile with MSVC
- [PR #5407](#)¹⁹⁷⁸ - Handle exceptions thrown during initialization of parcel handler
- [PR #5406](#)¹⁹⁷⁹ - Simplify dispatching to annotation handlers
- [PR #5405](#)¹⁹⁸⁰ - Fetch Asio automatically in perf tests CI
- [PR #5403](#)¹⁹⁸¹ - Create generic executor that adds annotations to any other executor
- [PR #5402](#)¹⁹⁸² - Adapt `uninitialized_fill` and `uninitialized_fill_n` to C++ 20
- [PR #5401](#)¹⁹⁸³ - Modernize a variety of facilities related to parallel algorithms
- [PR #5400](#)¹⁹⁸⁴ - Fix sliding semaphore test
- [PR #5399](#)¹⁹⁸⁵ - Rename leftover `tag_fallback_invoke` to `tag_fallback_dispatch`
- [PR #5398](#)¹⁹⁸⁶ - Improve logging in AGAS symbol namespace
- [PR #5396](#)¹⁹⁸⁷ - Introduce compatibility layer for collective operations
- [PR #5394](#)¹⁹⁸⁸ - Enable OTF2 in APEX CI configuration
- [PR #5393](#)¹⁹⁸⁹ - Update APEX tag
- [PR #5392](#)¹⁹⁹⁰ - Fixing wrong usage of `std::forward`
- [PR #5391](#)¹⁹⁹¹ - Fix forwarding in `transform_receiver` constructor
- [PR #5390](#)¹⁹⁹² - Make sure shared priority scheduler steals tasks on the current NUMA domain when (core) stealing is enabled
- [PR #5389](#)¹⁹⁹³ - Adapt `uninitialized_move` and `uninitialized_move_n` to C++ 20
- [PR #5388](#)¹⁹⁹⁴ - Fixing `gather_there` for used with lvalue reference argument

¹⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/5417>

¹⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5416>

¹⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5415>

¹⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5414>

¹⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5413>

¹⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5407>

¹⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5406>

¹⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5405>

¹⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/5403>

¹⁹⁸² <https://github.com/TheHPXProject/hpx/pull/5402>

¹⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/5401>

¹⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5400>

¹⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5399>

¹⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5398>

¹⁹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5396>

¹⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5394>

¹⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5393>

¹⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5392>

¹⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/5391>

¹⁹⁹² <https://github.com/TheHPXProject/hpx/pull/5390>

¹⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/5389>

¹⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5388>

- PR #5387¹⁹⁹⁵ - Extend thread state logging and change default stealing parameters
- PR #5386¹⁹⁹⁶ - Attempt to fix the startup hang with nodes > 32
- PR #5384¹⁹⁹⁷ - Remove HPX 1.5.0 deprecations
- PR #5382¹⁹⁹⁸ - Prefer installed Asio before considering FetchContent
- PR #5379¹⁹⁹⁹ - Allow using pre-downloaded (not installed) versions of Asio and/or Apex
- PR #5376²⁰⁰⁰ - Remove unnecessary explicit listing of library modules.rst files in CMakeLists.txt
- PR #5375²⁰⁰¹ - Slight performance improvement for `hpx::copy` and `hpx::move` et.al.
- PR #5374²⁰⁰² - Remove unnecessary moves from future sender implementations
- PR #5373²⁰⁰³ - More changes to clang-cuda Jenkins configuration
- PR #5372²⁰⁰⁴ - Slight improvements to `min/max/minmax_element` algorithms
- PR #5371²⁰⁰⁵ - Adapt `uninitialized_copy` and `uninitialized_copy_n` to C++ 20
- PR #5370²⁰⁰⁶ - Decay types in `just_sender` `value_types` to match stored types
- PR #5367²⁰⁰⁷ - Disable `pkgconfig` by default again on macOS
- PR #5365²⁰⁰⁸ - Use `ccache` for Jenkins builds on Piz Daint
- PR #5363²⁰⁰⁹ - Update `cuda toolkit` module name in clang-cuda Jenkins configuration
- PR #5362²⁰¹⁰ - Adding `channel_communicator`
- PR #5361²⁰¹¹ - Fix compilation with MPI enabled
- PR #5360²⁰¹² - Update APEX and asio tags
- PR #5359²⁰¹³ - Fix check for `pu-step` in single-core case
- PR #5357²⁰¹⁴ - Making sure collective operations can be reused by preallocating communicator
- PR #5356²⁰¹⁵ - Update API documentation
- PR #5355²⁰¹⁶ - Make the `sequenced_executor` `processing_units_count` member function `const`
- PR #5354²⁰¹⁷ - Making sure `default_stack_size` is defined whenever declared

¹⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5387>

¹⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5386>

¹⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5384>

¹⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5382>

¹⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5379>

²⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5376>

²⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/5375>

²⁰⁰² <https://github.com/TheHPXProject/hpx/pull/5374>

²⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/5373>

²⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5372>

²⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5371>

²⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5370>

²⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5367>

²⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5365>

²⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5363>

²⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/5362>

²⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/5361>

²⁰¹² <https://github.com/TheHPXProject/hpx/pull/5360>

²⁰¹³ <https://github.com/TheHPXProject/hpx/pull/5359>

²⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/5357>

²⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/5356>

²⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/5355>

²⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/5354>

- [PR #5353](#)²⁰¹⁸ - Add CUDA timestamp support to HPX Hardware Clock
- [PR #5352](#)²⁰¹⁹ - Adding missing includes
- [PR #5351](#)²⁰²⁰ - Adding `enable_logging/disable_logging` API functions
- [PR #5350](#)²⁰²¹ - Adapt `lexicographical_compare` to C++20
- [PR #5349](#)²⁰²² - Update minimum boost version needed on the docs
- [PR #5348](#)²⁰²³ - Rename `tag_invoke` and related facilities to `tag_dispatch`
- [PR #5347](#)²⁰²⁴ - Remove `make_` prefix for executor properties
- [PR #5346](#)²⁰²⁵ - Remove and disable compatibility options for 1.7.0
- [PR #5343](#)²⁰²⁶ - Fix `timed_executor` static cast conversion
- [PR #5342](#)²⁰²⁷ - Refactor CUDA event polling
- [PR #5341](#)²⁰²⁸ - Adding `make_with_annotation` and `get_annotation` properties
- [PR #5339](#)²⁰²⁹ - Making sure `hpx::util::hardware::timestamp()` is always defined
- [PR #5338](#)²⁰³⁰ - Fixing `timed_executor` specializations of customization points
- [PR #5335](#)²⁰³¹ - Make `partial_algorithm` work with any number of arguments
- [PR #5334](#)²⁰³² - Follow up `iter_sent` include on #5225
- [PR #5332](#)²⁰³³ - Simplify `tag_invoke` and friends
- [PR #5331](#)²⁰³⁴ - More work on cleaning up executor CPOs
- [PR #5330](#)²⁰³⁵ - Add option to disable `pkgconfig` generation
- [PR #5328](#)²⁰³⁶ - Adapt data parallel support using `std-simd`
- [PR #5327](#)²⁰³⁷ - Fix missing `ifdef HPX_SMT_PAUSE`
- [PR #5326](#)²⁰³⁸ - Adding `resize()` to `serialize_buffer` allowing to shrink its size
- [PR #5324](#)²⁰³⁹ - Add get member functions to `async_rw_mutex` proxy objects for explicitly getting the wrapped value
- [PR #5323](#)²⁰⁴⁰ - Add `keep_future` algorithm

²⁰¹⁸ <https://github.com/TheHPXProject/hpx/pull/5353>

²⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/5352>

²⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/5351>

²⁰²¹ <https://github.com/TheHPXProject/hpx/pull/5350>

²⁰²² <https://github.com/TheHPXProject/hpx/pull/5349>

²⁰²³ <https://github.com/TheHPXProject/hpx/pull/5348>

²⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/5347>

²⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/5346>

²⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/5343>

²⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/5342>

²⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/5341>

²⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/5339>

²⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/5338>

²⁰³¹ <https://github.com/TheHPXProject/hpx/pull/5335>

²⁰³² <https://github.com/TheHPXProject/hpx/pull/5334>

²⁰³³ <https://github.com/TheHPXProject/hpx/pull/5332>

²⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/5331>

²⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/5330>

²⁰³⁶ <https://github.com/TheHPXProject/hpx/pull/5328>

²⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/5327>

²⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/5326>

²⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/5324>

²⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5323>

- PR #5322²⁰⁴¹ - Replace executor customization point implementations with `tag_invoke`
- PR #5321²⁰⁴² - Seperate segmented algorithms for reduce
- PR #5320²⁰⁴³ - Fix `is_sender` trait and other small fixes to p0443 traits
- PR #5319²⁰⁴⁴ - gcc 11.1 c++20 build fixes
- PR #5318²⁰⁴⁵ - Make hipblas dependency optional as not always available
- PR #5316²⁰⁴⁶ - Attempt to fix checking for libatomic
- PR #5315²⁰⁴⁷ - Add explicit keyword to fixture constructor
- PR #5314²⁰⁴⁸ - Fix a race condition in async mpi affecting limiting executor
- PR #5312²⁰⁴⁹ - Use local runtime and local headers in local-only modules and tests
- PR #5311²⁰⁵⁰ - Add GCC 11 builder to jenkins
- PR #5310²⁰⁵¹ - Adding `hpx::execution::experimental::task_group`
- PR #5309²⁰⁵² - Seperate datapar
- PR #5308²⁰⁵³ - Seperate segmented algorithms for `find`, `find_if`, `find_if_not`
- PR #5307²⁰⁵⁴ - Seperate segmented algorithms for `fill` and `generate`
- PR #5304²⁰⁵⁵ - Fix compilation of sender CPOs with nvcc
- PR #5300²⁰⁵⁶ - Remove PRIVATE flag that was propagated into the LANGUAGES
- PR #5298²⁰⁵⁷ - Seperate datapar
- PR #5297²⁰⁵⁸ - Specify exact cmake and ninja versions when loading them in jenkins jobs
- PR #5295²⁰⁵⁹ - Update clang-newest configuration to use clang 12 and Boost 1.76.0
- PR #5293²⁰⁶⁰ - Fix Clang 11 cuda_future test bug
- PR #5292²⁰⁶¹ - Add `async_rw_mutex` based on senders
- PR #5291²⁰⁶² - “Fix” termination detection
- PR #5290²⁰⁶³ - Fixed source file line statements in examples documentation

²⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/5322>

²⁰⁴² <https://github.com/TheHPXProject/hpx/pull/5321>

²⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/5320>

²⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5319>

²⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5318>

²⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5316>

²⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5315>

²⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5314>

²⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5312>

²⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5311>

²⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/5310>

²⁰⁵² <https://github.com/TheHPXProject/hpx/pull/5309>

²⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/5308>

²⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5307>

²⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5304>

²⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5300>

²⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5298>

²⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5297>

²⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5295>

²⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5293>

²⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/5292>

²⁰⁶² <https://github.com/TheHPXProject/hpx/pull/5291>

²⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/5290>

- [PR #5289](#)²⁰⁶⁴ - Allow splitting of futures holding `std::tuple`
- [PR #5288](#)²⁰⁶⁵ - Move algorithms to `tag_fallback_invoke`
- [PR #5287](#)²⁰⁶⁶ - Move algorithms to `tag_fallback_invoke`
- [PR #5285](#)²⁰⁶⁷ - Fix clang-format failure on master
- [PR #5284](#)²⁰⁶⁸ - Replacing `util::function_nonsr` on `std::function` in `hpx_init`
- [PR #5282](#)²⁰⁶⁹ - Update Boost for daint 20.11 after update
- [PR #5281](#)²⁰⁷⁰ - Fix Segmentation fault on `foreach_datapar_zipiter`
- [PR #5280](#)²⁰⁷¹ - Avoid modulo by zero in `counting_iterator` test
- [PR #5279](#)²⁰⁷² - Fix more GCC 10 deprecation warnings
- [PR #5277](#)²⁰⁷³ - Small fixes and improvements to CUDA/MPI polling
- [PR #5276](#)²⁰⁷⁴ - Fix typo in docs
- [PR #5274](#)²⁰⁷⁵ - More P1897 algorithms
- [PR #5273](#)²⁰⁷⁶ - Retry CDash submissions on failure
- [PR #5272](#)²⁰⁷⁷ - Fix bogus deprecation warnings with GCC 10
- [PR #5271](#)²⁰⁷⁸ - Correcting target ids for `symbol_namespace::iterate`
- [PR #5268](#)²⁰⁷⁹ - Adding generic `require`, `require_concept`, and `query` properties
- [PR #5267](#)²⁰⁸⁰ - Support annotations in `hpx::transform_reduce`
- [PR #5266](#)²⁰⁸¹ - Making late command line options available for local runtime
- [PR #5265](#)²⁰⁸² - Leverage `no_unique_address` for `member_pack`
- [PR #5264](#)²⁰⁸³ - Adopt format in more places
- [PR #5262](#)²⁰⁸⁴ - Install HPX in Rostam Jenkins jobs
- [PR #5261](#)²⁰⁸⁵ - Limit Rostam Jenkins jobs to marvin partition temporarily
- [PR #5260](#)²⁰⁸⁶ - Separate segmented algorithms for `transform_reduce`

²⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5289>

²⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5288>

²⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5287>

²⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5285>

²⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5284>

²⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5282>

²⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5281>

²⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/5280>

²⁰⁷² <https://github.com/TheHPXProject/hpx/pull/5279>

²⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/5277>

²⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5276>

²⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5274>

²⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5273>

²⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5272>

²⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5271>

²⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5268>

²⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5267>

²⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/5266>

²⁰⁸² <https://github.com/TheHPXProject/hpx/pull/5265>

²⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/5264>

²⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5262>

²⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5261>

²⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5260>

- PR #5259²⁰⁸⁷ - Making sure late command line options are recognized as configuration options
- PR #5258²⁰⁸⁸ - Allow for HPX algorithms being invoked with std execution policies
- PR #5256²⁰⁸⁹ - Separate segmented algorithms for transform
- PR #5255²⁰⁹⁰ - Future/sender adapters
- PR #5254²⁰⁹¹ - Fixing datapar
- PR #5253²⁰⁹² - Add utility to format ranges
- PR #5252²⁰⁹³ - Remove uses of Boost.Bimap
- PR #5251²⁰⁹⁴ - Banish <iostream> from library headers
- PR #5250²⁰⁹⁵ - Try fixing vc circle ci
- PR #5249²⁰⁹⁶ - Adding missing header
- PR #5248²⁰⁹⁷ - Use old Piz Daint modules after upgrade
- PR #5247²⁰⁹⁸ - Significantly speedup simple for_each, for_loop, and transform
- PR #5245²⁰⁹⁹ - P1897 operator| overloads
- PR #5244²¹⁰⁰ - P1897 when_all
- PR #5243²¹⁰¹ - Make sure HPX_DEBUG is set based on HPX's build type, not consuming project's build type
- PR #5242²¹⁰² - Moving last files unrelated to parcel layer to modules
- PR #5240²¹⁰³ - change namespace for transform_loop.hpp
- PR #5238²¹⁰⁴ - Make sure annotations are used in the binary transform
- PR #5237²¹⁰⁵ - Add P1897 just, just_on, and on algorithms
- PR #5236²¹⁰⁶ - Add an example demonstrating the use of the invoke_function_action facility
- PR #5235²¹⁰⁷ - Attempting to fix datapar compilation issues
- PR #5234²¹⁰⁸ - Fix small typo in --hpx:local option description
- PR #5233²¹⁰⁹ - Only find Boost.Iostreams if required for plugins

²⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5259>

²⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5258>

²⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5256>

²⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5255>

²⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/5254>

²⁰⁹² <https://github.com/TheHPXProject/hpx/pull/5253>

²⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/5252>

²⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5251>

²⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5250>

²⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5249>

²⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5248>

²⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5247>

²⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5245>

²¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5244>

²¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/5243>

²¹⁰² <https://github.com/TheHPXProject/hpx/pull/5242>

²¹⁰³ <https://github.com/TheHPXProject/hpx/pull/5240>

²¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5238>

²¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5237>

²¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5236>

²¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5235>

²¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5234>

²¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5233>

- PR #5231²¹¹⁰ - Sort printed config options
- PR #5230²¹¹¹ - Fix C++20 replace algo adaptation misses
- PR #5229²¹¹² - Remove leftover Boost include from `sync_wait.hpp`
- PR #5228²¹¹³ - Print module name only if it has custom configuration settings
- PR #5227²¹¹⁴ - Update `.codespell_whitelist`
- PR #5226²¹¹⁵ - Use new docker image in all CircleCI steps
- PR #5225²¹¹⁶ - Adapt reverse to C++20
- PR #5224²¹¹⁷ - Separate segmented algorithms for `none_of`, `any_of` and `all_of`
- PR #5223²¹¹⁸ - Fixing build system for `itnotify`
- PR #5221²¹¹⁹ - Moving LCO related files to modules
- PR #5220²¹²⁰ - Separate segmented algorithms for `count` and `count_if`
- PR #5218²¹²¹ - Separate segmented algorithms for `adjacent_find`
- PR #5217²¹²² - Add a HIP github action
- PR #5215²¹²³ - Update ROCm to 4.0.1 on Rostam
- PR #5214²¹²⁴ - Fix clang-format error in `sender.hpp`
- PR #5213²¹²⁵ - Removing ESSENTIAL option to the doc example
- PR #5212²¹²⁶ - Separate segmented algorithms for `for_each_n`
- PR #5211²¹²⁷ - Minor adapted algos fixes
- PR #5210²¹²⁸ - Fixing `is_invocable` deprecation warnings
- PR #5209²¹²⁹ - Moving more files into modules (actions, components, `init_runtime`, etc.)
- PR #5208²¹³⁰ - Add examples and explanation on when `tag_fallback/priority` are useful
- PR #5207²¹³¹ - Always define `HPX_COMPUTE_HOST_CODE` for host code
- PR #5206²¹³² - Add formatting exceptions for `libhpx` to `create_module_skeleton.py`

²¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/5231>

²¹¹¹ <https://github.com/TheHPXProject/hpx/pull/5230>

²¹¹² <https://github.com/TheHPXProject/hpx/pull/5229>

²¹¹³ <https://github.com/TheHPXProject/hpx/pull/5228>

²¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/5227>

²¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/5226>

²¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/5225>

²¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/5224>

²¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/5223>

²¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/5221>

²¹²⁰ <https://github.com/TheHPXProject/hpx/pull/5220>

²¹²¹ <https://github.com/TheHPXProject/hpx/pull/5218>

²¹²² <https://github.com/TheHPXProject/hpx/pull/5217>

²¹²³ <https://github.com/TheHPXProject/hpx/pull/5215>

²¹²⁴ <https://github.com/TheHPXProject/hpx/pull/5214>

²¹²⁵ <https://github.com/TheHPXProject/hpx/pull/5213>

²¹²⁶ <https://github.com/TheHPXProject/hpx/pull/5212>

²¹²⁷ <https://github.com/TheHPXProject/hpx/pull/5211>

²¹²⁸ <https://github.com/TheHPXProject/hpx/pull/5210>

²¹²⁹ <https://github.com/TheHPXProject/hpx/pull/5209>

²¹³⁰ <https://github.com/TheHPXProject/hpx/pull/5208>

²¹³¹ <https://github.com/TheHPXProject/hpx/pull/5207>

²¹³² <https://github.com/TheHPXProject/hpx/pull/5206>

- PR #5205²¹³³ - Moving all distribution policies into modules
- PR #5203²¹³⁴ - Move copy algorithms to tag_fallback_invoke
- PR #5202²¹³⁵ - Make HPX_WITH_PSEUDO_DEPENDENCIES a cache variable
- PR #5201²¹³⁶ - Replaced tag_invoke with tag_fallback_invoke for adjacent_find algorithm
- PR #5200²¹³⁷ - Moving files to (distributed) runtime module
- PR #5199²¹³⁸ - Update ICC module name on Piz Daint Jenkins configuration
- PR #5198²¹³⁹ - Add doxygen documentation for thread_schedule_hint
- PR #5197²¹⁴⁰ - Attempt to fix compilation of context implementations with unity build enabled
- PR #5196²¹⁴¹ - Re-enable component tests
- PR #5195²¹⁴² - Moving files related to colocation logic
- PR #5194²¹⁴³ - Another attempt at fixing the Fedora 35 problem
- PR #5193²¹⁴⁴ - Components module
- PR #5192²¹⁴⁵ - Adapt replace(_if) to C++20
- PR #5190²¹⁴⁶ - Set compatibility headers by default to on
- PR #5188²¹⁴⁷ - Bump Boost minimum version to 1.71.0
- PR #5187²¹⁴⁸ - Force CMake to set the -std=c++XX flag
- PR #5186²¹⁴⁹ - Remove message to print .cu extension whenever .cu files are encountered
- PR #5185²¹⁵⁰ - Remove some minor unnecessary CMake options
- PR #5184²¹⁵¹ - Remove some leftover HPX_WITH_*_SCHEDULER uses
- PR #5183²¹⁵² - Remove dependency on boost/iterators/iterator_categories.hpp
- PR #5182²¹⁵³ - Fixing Fedora 35 for Power architectures
- PR #5181²¹⁵⁴ - Bump version number and tag post 1.6.0 release
- PR #5180²¹⁵⁵ - Fix https_v2 tests linking

²¹³³ <https://github.com/TheHPXProject/hpx/pull/5205>

²¹³⁴ <https://github.com/TheHPXProject/hpx/pull/5203>

²¹³⁵ <https://github.com/TheHPXProject/hpx/pull/5202>

²¹³⁶ <https://github.com/TheHPXProject/hpx/pull/5201>

²¹³⁷ <https://github.com/TheHPXProject/hpx/pull/5200>

²¹³⁸ <https://github.com/TheHPXProject/hpx/pull/5199>

²¹³⁹ <https://github.com/TheHPXProject/hpx/pull/5198>

²¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5197>

²¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/5196>

²¹⁴² <https://github.com/TheHPXProject/hpx/pull/5195>

²¹⁴³ <https://github.com/TheHPXProject/hpx/pull/5194>

²¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5193>

²¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5192>

²¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5190>

²¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5188>

²¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5187>

²¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5186>

²¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5185>

²¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/5184>

²¹⁵² <https://github.com/TheHPXProject/hpx/pull/5183>

²¹⁵³ <https://github.com/TheHPXProject/hpx/pull/5182>

²¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5181>

²¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5180>

- [PR #5179](#)²¹⁵⁶ - Make sure `--hpx:local` command line option is respected with networking is off but distributed runtime is on
- [PR #5177](#)²¹⁵⁷ - Remove module cmake options
- [PR #5176](#)²¹⁵⁸ - Starting to separate segmented algorithms: `for_each`
- [PR #5174](#)²¹⁵⁹ - Don't run segmented algorithms twice on CircleCI
- [PR #5173](#)²¹⁶⁰ - Fetching APEX using cmake `FetchContent`
- [PR #5172](#)²¹⁶¹ - Add separate local-only entry point
- [PR #5171](#)²¹⁶² - Remove `HPX_WITH_THREAD_SCHEDULERS` CMake option
- [PR #5170](#)²¹⁶³ - Add `HPX_WITH_PRECOMPILED_HEADERS` option
- [PR #5166](#)²¹⁶⁴ - Moving some action tests to modules
- [PR #5165](#)²¹⁶⁵ - Require cmake 3.17
- [PR #5164](#)²¹⁶⁶ - Move `thread_pool_suspension_helper` files to small utility module
- [PR #5160](#)²¹⁶⁷ - Adding checks ensuring modules are not cross-referenced from other module categories
- [PR #5158](#)²¹⁶⁸ - Replace `boost::asio` with standalone `asio`
- [PR #5155](#)²¹⁶⁹ - Allow logging when distributed runtime is off
- [PR #5153](#)²¹⁷⁰ - Components module
- [PR #5152](#)²¹⁷¹ - Move more files to performance counter module
- [PR #5150](#)²¹⁷² - Adapt `remove_copy(_if)` to C++20
- [PR #5144](#)²¹⁷³ - AGAS module
- [PR #5125](#)²¹⁷⁴ - Adapt `remove` and `remove_if` to C++20
- [PR #5117](#)²¹⁷⁵ - Attempt to fix segfaults assumed to be caused by `future_data` instances going out of scope.
- [PR #5099](#)²¹⁷⁶ - Allow mixing debug and release builds
- [PR #5092](#)²¹⁷⁷ - Replace `spirit.qi` with `x3`
- [PR #5053](#)²¹⁷⁸ - Add P0443r14 executor and a few P1897 algorithms

²¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5179>

²¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5177>

²¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5176>

²¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5174>

²¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5173>

²¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/5172>

²¹⁶² <https://github.com/TheHPXProject/hpx/pull/5171>

²¹⁶³ <https://github.com/TheHPXProject/hpx/pull/5170>

²¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5166>

²¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5165>

²¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5164>

²¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5160>

²¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5158>

²¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5155>

²¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5153>

²¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/5152>

²¹⁷² <https://github.com/TheHPXProject/hpx/pull/5150>

²¹⁷³ <https://github.com/TheHPXProject/hpx/pull/5144>

²¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5125>

²¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5117>

²¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5099>

²¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5092>

²¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5053>

- [PR #5044](#)²¹⁷⁹ - Add performance test in jenkins and reports

HPX V1.6.0 (Feb 17, 2021)

General changes

This release continues the focus on C++20 conformance with multiple new algorithms adapted to be C++20 conformant and becoming customization point objects (CPOs). We have also added experimental support for HIP, allowing previous CUDA features to now be compiled with `hipcc` and run on AMD GPUs.

- The following algorithms have been adapted to be C++20 conformant: `adjacent_find`, `includes`, `inplace_merge`, `is_heap`, `is_heap_until`, `is_partitioned`, `is_sorted`, `is_sorted_until`, `merge`, `set_difference`, `set_intersection`, `set_symmetric_difference`, `set_union`.
- Experimental HIP support can be enabled by compiling *HPX* with `hipcc`. All CUDA functionality in *HPX* can now be used with HIP. The HIP functionality is for the time being exposed through the same API as the CUDA functionality, i.e. no changes are required in user code. The CUDA, and now HIP, functionality is in the `hpx::cuda` namespace.
- We have added `partial_sort` based on Francisco Tapia's implementation.
- `hpx::init` and `hpx::start` gained new overloads taking an `hpx::init_params` struct in 1.5.0. All overloads not taking an `hpx::init_params` are now deprecated.
- We have added an experimental `fork_join_executor`. This executor can be used for OpenMP-style fork-join parallelism, where the latency of a parallel region is important for performance.
- The `parallel_executor` now uses a hierarchical spawning scheme for bulk execution, which improves data locality and performance.
- `hpx::dataflow` can now be used with executors that inject additional parameters into the call of the user-provided function.
- We have added experimental support for properties as proposed in [P2220](#)²¹⁸⁰. Currently the only supported property is the scheduling hint on `parallel_executor`.
- `hpx::util::annotated_function` can now be passed a dynamically generated `std::string`.
- In moving functionality to new namespaces, old names have been deprecated. A deprecation warning will be issued if you are using deprecated functionality, with instructions on how to correct or ignore the warning.
- We have removed all support for C and Fortran from our build system.
- We have further reduced the use of Boost types within *HPX* (`boost::system::error_code` and `boost::detail::spinlock`).
- We have enabled more warnings in our CI builds (unused variables and unused typedefs).

²¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5044>

²¹⁸⁰ <https://wg21.link/p2220>

Breaking changes

- hpxMP support has been completely removed.
- The verbs parcelport has been removed.
- The following compatibility options have been disabled by default: `HPX_WITH_ACTION_BASE_COMPATIBILITY`, `HPX_WITH_REGISTER_THREAD_COMPATIBILITY`, `HPX_WITH_PROMISE_ALIAS_COMPATIBILITY`, `HPX_WITH_UNSCOPED_ENUM_COMPATIBILITY`, `HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY`, `HPX_WITH_EMBEDDED_THREAD_POOLS_COMPATIBILITY`, `HPX_WITH_THREAD_POOL_OS_EXECUTOR_COMPATIBILITY`, `HPX_WITH_THREAD_EXECUTORS_COMPATIBILITY`, `HPX_THREAD_AWARE_TIMER_COMPATIBILITY`, `HPX_WITH_POOL_EXECUTOR_COMPATIBILITY`. Unless noted here, the above functionalities do not come with replacements. Unscoped enumerations have been replaced by scoped enumerations. Previously deprecated unscoped enumerations are disabled by `HPX_WITH_UNSCOPED_ENUM_COMPATIBILITY`. Newly deprecated unscoped enumerations have been given deprecation warnings and replaced by scoped enumerations. `hpx::promise` has been replaced with `hpx::distributed::promise`. `hpx::program_options` is a drop-in replacement for `boost::program_options`. `hpx::execution::parallel_executor` now has constructors which take a thread pool, covering the use case of `hpx::threads::executors::pool_executor`. A pool can be supplied with `hpx::resource::get_thread_pool`.

Closed issues

- Issue #5148²¹⁸¹ - `runtime_support.hpp` does not work with newer cling
- Issue #5147²¹⁸² - Wrong results with parallel reduce
- Issue #5129²¹⁸³ - Missing specialization for `std::hash<hpx::thread::id>`
- Issue #5126²¹⁸⁴ - Use `std::string` for task annotations
- Issue #5115²¹⁸⁵ - Don't expect `hwloc` to always report Cores
- Issue #5113²¹⁸⁶ - Handle threadmanager exceptions during startup
- Issue #5112²¹⁸⁷ - libatomic problems causing unexpected fails
- Issue #5089²¹⁸⁸ - Remove non-BSL files
- Issue #5088²¹⁸⁹ - Unwrapping problem
- Issue #5087²¹⁹⁰ - Remove hpxMP support
- Issue #5077²¹⁹¹ - PAPI counters are not accessible when HPX is installed
- Issue #5075²¹⁹² - Make the structs in all `iter_sent.hpp` lower case
- Issue #5067²¹⁹³ - Bug `string_util/split.hpp`

²¹⁸¹ <https://github.com/TheHPXProject/hpx/issues/5148>

²¹⁸² <https://github.com/TheHPXProject/hpx/issues/5147>

²¹⁸³ <https://github.com/TheHPXProject/hpx/issues/5129>

²¹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/5126>

²¹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/5115>

²¹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/5113>

²¹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/5112>

²¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/5089>

²¹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/5088>

²¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/5087>

²¹⁹¹ <https://github.com/TheHPXProject/hpx/issues/5077>

²¹⁹² <https://github.com/TheHPXProject/hpx/issues/5075>

²¹⁹³ <https://github.com/TheHPXProject/hpx/issues/5067>

- [Issue #5049](#)²¹⁹⁴ - Change back the hipcc jenkins config to the fury partition on rostam
- [Issue #5038](#)²¹⁹⁵ - Not all examples link in the latest HPX master
- [Issue #5035](#)²¹⁹⁶ - Build with HPX_WITH_EXAMPLES fails
- [Issue #5019](#)²¹⁹⁷ - Broken help string for hpx
- [Issue #5016](#)²¹⁹⁸ - `hpx::parallel::fill` fails compiling
- [Issue #5014](#)²¹⁹⁹ - Rename all `.cc` to `.cpp` and `.hh` to `.hpp`
- [Issue #4988](#)²²⁰⁰ - MPI is not finalized if running with only one locality
- [Issue #4978](#)²²⁰¹ - Change feature test macros to expand to zero/one
- [Issue #4949](#)²²⁰² - Crash when not enabling TCP parcelport
- [Issue #4933](#)²²⁰³ - Improve test coverage for unused variable warnings etc.
- [Issue #4878](#)²²⁰⁴ - HPX mpi async might call `MPI_FINALIZE` before app calls it
- [Issue #4127](#)²²⁰⁵ - Local runtime entry-points

Closed pull requests

- [PR #5178](#)²²⁰⁶ - Fix parallel `remove/remove_copy/transform` namespace references in docs
- [PR #5169](#)²²⁰⁷ - Attempt to get Piz Daint jenkins setup running after maintenance
- [PR #5168](#)²²⁰⁸ - Remove include of itself
- [PR #5167](#)²²⁰⁹ - Fixing deprecation warnings that slipped through the net
- [PR #5159](#)²²¹⁰ - Update APEX tag to 2.3.1
- [PR #5154](#)²²¹¹ - Splitting unit tests on circleci to avoid timeouts
- [PR #5151](#)²²¹² - Use C++20 on clang-newest Jenkins CI configuration
- [PR #5149](#)²²¹³ - Rename 'module' symbols to avoid keyword conflict
- [PR #5145](#)²²¹⁴ - Adjust handling of CUDA/HIP options in CMake
- [PR #5142](#)²²¹⁵ - Store annotated_function annotations as `std::strings`

²¹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/5049>

²¹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/5038>

²¹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/5035>

²¹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/5019>

²¹⁹⁸ <https://github.com/TheHPXProject/hpx/issues/5016>

²¹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/5014>

²²⁰⁰ <https://github.com/TheHPXProject/hpx/issues/4988>

²²⁰¹ <https://github.com/TheHPXProject/hpx/issues/4978>

²²⁰² <https://github.com/TheHPXProject/hpx/issues/4949>

²²⁰³ <https://github.com/TheHPXProject/hpx/issues/4933>

²²⁰⁴ <https://github.com/TheHPXProject/hpx/issues/4878>

²²⁰⁵ <https://github.com/TheHPXProject/hpx/issues/4127>

²²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5178>

²²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5169>

²²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5168>

²²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5167>

²²¹⁰ <https://github.com/TheHPXProject/hpx/pull/5159>

²²¹¹ <https://github.com/TheHPXProject/hpx/pull/5154>

²²¹² <https://github.com/TheHPXProject/hpx/pull/5151>

²²¹³ <https://github.com/TheHPXProject/hpx/pull/5149>

²²¹⁴ <https://github.com/TheHPXProject/hpx/pull/5145>

²²¹⁵ <https://github.com/TheHPXProject/hpx/pull/5142>

- PR #5140²²¹⁶ - Scheduler mode
- PR #5139²²¹⁷ - Fix path problem in pre-commit hook, add summary commit line
- PR #5138²²¹⁸ - Add program options variable map to resource partitioner init
- PR #5137²²¹⁹ - Remove the use of `boost::throw_exception`
- PR #5136²²²⁰ - Make sure codespell checks run on CircleCI
- PR #5132²²²¹ - Fixing spelling errors
- PR #5131²²²² - Mark `counting_iterator` member functions as `HPX_HOST_DEVICE`
- PR #5130²²²³ - Adding specialization for `std::hash<hpx::thread::id>`
- PR #5128²²²⁴ - Fixing environment handling for FreeBSD
- PR #5127²²²⁵ - Fix typo in fibonacci documentation
- PR #5123²²²⁶ - Reduce vector sizes in partial sort benchmarks when running in debug mode
- PR #5122²²²⁷ - Making sure exceptions during runtime initialization are correctly reported
- PR #5121²²²⁸ - Working around hwloc limitation on certain platforms
- PR #5120²²²⁹ - Fixing compatibility warnings in `hpx::transform` implementation
- PR #5119²²³⁰ - Use `sequential_find` and friends from separate detail header
- PR #5116²²³¹ - Fix compilation with timer pool off
- PR #5114²²³² - Fix 5112 - make sure `libatomic` is used when needed
- PR #5109²²³³ - Remove default runtime mode argument from `init` overload, again
- PR #5108²²³⁴ - Refactor `iter_sent.hpp` to make structs lowercase
- PR #5107²²³⁵ - Relax `dataflow` internals
- PR #5106²²³⁶ - Change initialization of property CPOs to satisfy older `nvcc` versions
- PR #5104²²³⁷ - Fix regeneration of two files that trigger unnecessary rebuilds
- PR #5103²²³⁸ - Remove default runtime mode argument from `start/init` overloads

²²¹⁶ <https://github.com/TheHPXProject/hpx/pull/5140>

²²¹⁷ <https://github.com/TheHPXProject/hpx/pull/5139>

²²¹⁸ <https://github.com/TheHPXProject/hpx/pull/5138>

²²¹⁹ <https://github.com/TheHPXProject/hpx/pull/5137>

²²²⁰ <https://github.com/TheHPXProject/hpx/pull/5136>

²²²¹ <https://github.com/TheHPXProject/hpx/pull/5132>

²²²² <https://github.com/TheHPXProject/hpx/pull/5131>

²²²³ <https://github.com/TheHPXProject/hpx/pull/5130>

²²²⁴ <https://github.com/TheHPXProject/hpx/pull/5128>

²²²⁵ <https://github.com/TheHPXProject/hpx/pull/5127>

²²²⁶ <https://github.com/TheHPXProject/hpx/pull/5123>

²²²⁷ <https://github.com/TheHPXProject/hpx/pull/5122>

²²²⁸ <https://github.com/TheHPXProject/hpx/pull/5121>

²²²⁹ <https://github.com/TheHPXProject/hpx/pull/5120>

²²³⁰ <https://github.com/TheHPXProject/hpx/pull/5119>

²²³¹ <https://github.com/TheHPXProject/hpx/pull/5116>

²²³² <https://github.com/TheHPXProject/hpx/pull/5114>

²²³³ <https://github.com/TheHPXProject/hpx/pull/5109>

²²³⁴ <https://github.com/TheHPXProject/hpx/pull/5108>

²²³⁵ <https://github.com/TheHPXProject/hpx/pull/5107>

²²³⁶ <https://github.com/TheHPXProject/hpx/pull/5106>

²²³⁷ <https://github.com/TheHPXProject/hpx/pull/5104>

²²³⁸ <https://github.com/TheHPXProject/hpx/pull/5103>

- PR #5102²²³⁹ - Untie deprecated thread enums from the CMake option
- PR #5101²²⁴⁰ - Update APEX tag for 1.6.0
- PR #5100²²⁴¹ - Bump minimum required Boost version to 1.66 and update CI configurations
- PR #5098²²⁴² - Minor fixes to public API listing
- PR #5097²²⁴³ - Remove hpxMP support
- PR #5096²²⁴⁴ - Remove fractals examples
- PR #5095²²⁴⁵ - Use all AMD nodes again on rostam
- PR #5094²²⁴⁶ - Attempt to remove macOS workaround for GH actions environment
- PR #5093²²⁴⁷ - Remove verbs parcelport
- PR #5091²²⁴⁸ - Avoid moving from lvalues
- PR #5090²²⁴⁹ - Adopt C++20 `std::endian`
- PR #5085²²⁵⁰ - Update daint CI to use Boost 1.75.0
- PR #5084²²⁵¹ - Disable compatibility options for 1.6.0 release
- PR #5083²²⁵² - Remove duplicated call to the `limiting_executor` in `future_overhead` test
- PR #5079²²⁵³ - Add checks to make sure that MPI/CUDA polling is enabled/not disabled too early
- PR #5078²²⁵⁴ - Add install lib directory to list of component search paths
- PR #5076²²⁵⁵ - Fix a typo in the jenkins `clang-newest` cmake config
- PR #5074²²⁵⁶ - Fixing warnings generated by MSVC
- PR #5073²²⁵⁷ - Allow using noncopyable types with unwrapping
- PR #5072²²⁵⁸ - Fix `is_convertible` args in `result_types`
- PR #5071²²⁵⁹ - Fix unused parameters
- PR #5070²²⁶⁰ - Fix unused variables warnings in `hipcc`
- PR #5069²²⁶¹ - Add support for sentinels to `adjacent_find`

²²³⁹ <https://github.com/TheHPXProject/hpx/pull/5102>

²²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5101>

²²⁴¹ <https://github.com/TheHPXProject/hpx/pull/5100>

²²⁴² <https://github.com/TheHPXProject/hpx/pull/5098>

²²⁴³ <https://github.com/TheHPXProject/hpx/pull/5097>

²²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5096>

²²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5095>

²²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5094>

²²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5093>

²²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5091>

²²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5090>

²²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5085>

²²⁵¹ <https://github.com/TheHPXProject/hpx/pull/5084>

²²⁵² <https://github.com/TheHPXProject/hpx/pull/5083>

²²⁵³ <https://github.com/TheHPXProject/hpx/pull/5079>

²²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5078>

²²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5076>

²²⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5074>

²²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5073>

²²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5072>

²²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5071>

²²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5070>

²²⁶¹ <https://github.com/TheHPXProject/hpx/pull/5069>

- PR #5068²²⁶² - Fix string split function
- PR #5066²²⁶³ - Adapt search to C++20 and Range TS
- PR #5065²²⁶⁴ - Fix `hpx::range::adjacent_find` doxygen function signatures
- PR #5064²²⁶⁵ - Refactor runtime configuration, command line handling, and resource partitioner
- PR #5063²²⁶⁶ - Limit the device code guards to the distributed parts of the `future_overhead` bench
- PR #5061²²⁶⁷ - Remove hipcc guards in examples and tests
- PR #5060²²⁶⁸ - Fix deprecation warnings generated by msvc
- PR #5059²²⁶⁹ - Add warning about suspending/resuming the runtime in multi-locality scenarios
- PR #5057²²⁷⁰ - Fix unused variable warnings
- PR #5056²²⁷¹ - Fix `hpx::util::get`
- PR #5055²²⁷² - Remove hipcc guards
- PR #5054²²⁷³ - Fix typo
- PR #5051²²⁷⁴ - Adapt transform to C++20
- PR #5050²²⁷⁵ - Replace old init overloads in tests and examples
- PR #5048²²⁷⁶ - Limit jenkins hipcc to the reno node
- PR #5047²²⁷⁷ - Limit cuda jenkins run to nodes with exclusively Nvidia GPUs
- PR #5046²²⁷⁸ - Convert thread and future enums to class enums
- PR #5043²²⁷⁹ - Improve `hpxrun.py` for Phylanx
- PR #5042²²⁸⁰ - Add missing header to partial sort test
- PR #5041²²⁸¹ - Adding Francisco Tapia's implementation of `partial_sort`
- PR #5040²²⁸² - Remove generated headers left behind from a previous configuration
- PR #5039²²⁸³ - Fix GCC 10 release builds
- PR #5037²²⁸⁴ - Add `is_invocable` typedefs to top-level `hpx` namespace and public API list

²²⁶² <https://github.com/TheHPXProject/hpx/pull/5068>

²²⁶³ <https://github.com/TheHPXProject/hpx/pull/5066>

²²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5065>

²²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5064>

²²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5063>

²²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5061>

²²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5060>

²²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5059>

²²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5057>

²²⁷¹ <https://github.com/TheHPXProject/hpx/pull/5056>

²²⁷² <https://github.com/TheHPXProject/hpx/pull/5055>

²²⁷³ <https://github.com/TheHPXProject/hpx/pull/5054>

²²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5051>

²²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5050>

²²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5048>

²²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5047>

²²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5046>

²²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5043>

²²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5042>

²²⁸¹ <https://github.com/TheHPXProject/hpx/pull/5041>

²²⁸² <https://github.com/TheHPXProject/hpx/pull/5040>

²²⁸³ <https://github.com/TheHPXProject/hpx/pull/5039>

²²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5037>

- PR #5036²²⁸⁵ - Deprecate `hpx::util::decay` in favor of `std::decay`
- PR #5034²²⁸⁶ - Use versioned container image on CircleCI
- PR #5033²²⁸⁷ - Implement P2220 properties module
- PR #5032²²⁸⁸ - Do codespell comparison only on files changed from common ancestor
- PR #5031²²⁸⁹ - Moving traits files to `actions_base`
- PR #5030²²⁹⁰ - Add codespell version print in circleci
- PR #5029²²⁹¹ - Work around problems in GitHub actions macOS builder
- PR #5028²²⁹² - Moving move files to `naming` and `naming_base`
- PR #5027²²⁹³ - Lessen constraints on certain algorithm arguments
- PR #5025²²⁹⁴ - Adapt `is_sorted` and `is_sorted_until` to C++20
- PR #5024²²⁹⁵ - Moving `naming_base` to full modules
- PR #5022²²⁹⁶ - Remove C language from `CMakeLists.txt`
- PR #5021²²⁹⁷ - Warn about unused arguments given to `add_hpx_module`
- PR #5020²²⁹⁸ - Fixing help string
- PR #5018²²⁹⁹ - Update CSCS jenkins configuration to clang 11
- PR #5017²³⁰⁰ - Fixing broken backwards compatibility for `hpx::parallel::fill`
- PR #5015²³⁰¹ - Detect if generated global header conflicts with explicitly listed module headers
- PR #5012²³⁰² - Properly reset pointer tracking data in `output_archive`
- PR #5011²³⁰³ - Inspect command line tweaks
- PR #5010²³⁰⁴ - Creating AGAS module
- PR #5009²³⁰⁵ - Replace `boost::system::error_code` with `std::error_code`
- PR #5008²³⁰⁶ - Replace uses of `boost::detail::spinlock`
- PR #5007²³⁰⁷ - Bump minimal Boost version to 1.65.0

²²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5036>

²²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5034>

²²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5033>

²²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5032>

²²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5031>

²²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5030>

²²⁹¹ <https://github.com/TheHPXProject/hpx/pull/5029>

²²⁹² <https://github.com/TheHPXProject/hpx/pull/5028>

²²⁹³ <https://github.com/TheHPXProject/hpx/pull/5027>

²²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5025>

²²⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5024>

²²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5022>

²²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5021>

²²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5020>

²²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5018>

²³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5017>

²³⁰¹ <https://github.com/TheHPXProject/hpx/pull/5015>

²³⁰² <https://github.com/TheHPXProject/hpx/pull/5012>

²³⁰³ <https://github.com/TheHPXProject/hpx/pull/5011>

²³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5010>

²³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5009>

²³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5008>

²³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5007>

- PR #5006²³⁰⁸ - Adapt `is_partitioned` to C++20
- PR #5005²³⁰⁹ - Making sure `reduce_by_key` compiles again
- PR #5004²³¹⁰ - Fixing template specializations that make extra archive data types unique across module boundaries
- PR #5003²³¹¹ - Relax `dataflow` argument constraints
- PR #5001²³¹² - Add `<random>` inspect check
- PR #4999²³¹³ - Attempt to fix MacOS Github action error
- PR #4997²³¹⁴ - Fix unused variable and typedef warnings
- PR #4996²³¹⁵ - Adapt `adjacent_find` to C++20
- PR #4995²³¹⁶ - Test all schedulers in `cross_pool_injection` test except `shared_priority_queue_scheduler`
- PR #4993²³¹⁷ - Fix deprecation warnings
- PR #4991²³¹⁸ - Avoid unnecessarily including entire modules
- PR #4990²³¹⁹ - Fixing some warnings from HPX complaining about use of obsolete types
- PR #4989²³²⁰ - add a `*destroy*` trait for `ParcelPort` plugins
- PR #4986²³²¹ - Remove serialization to functional module dependency
- PR #4985²³²² - Compatibility header generation
- PR #4980²³²³ - Add ranges overloads to `for_loop` (and variants)
- PR #4979²³²⁴ - Actually enable unity builds on Jenkins
- PR #4977²³²⁵ - Cleaning up `debug::print` functionalities
- PR #4976²³²⁶ - Remove indirection layer in `at_index_impl`
- PR #4975²³²⁷ - Remove indirection layer in `at_index_impl`
- PR #4973²³²⁸ - Avoid warnings/errors for older gcc complaining about multi-line comments
- PR #4970²³²⁹ - Making set algorithms conform to C++20

²³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5006>

²³⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5005>

²³¹⁰ <https://github.com/TheHPXProject/hpx/pull/5004>

²³¹¹ <https://github.com/TheHPXProject/hpx/pull/5003>

²³¹² <https://github.com/TheHPXProject/hpx/pull/5001>

²³¹³ <https://github.com/TheHPXProject/hpx/pull/4999>

²³¹⁴ <https://github.com/TheHPXProject/hpx/pull/4997>

²³¹⁵ <https://github.com/TheHPXProject/hpx/pull/4996>

²³¹⁶ <https://github.com/TheHPXProject/hpx/pull/4995>

²³¹⁷ <https://github.com/TheHPXProject/hpx/pull/4993>

²³¹⁸ <https://github.com/TheHPXProject/hpx/pull/4991>

²³¹⁹ <https://github.com/TheHPXProject/hpx/pull/4990>

²³²⁰ <https://github.com/TheHPXProject/hpx/pull/4989>

²³²¹ <https://github.com/TheHPXProject/hpx/pull/4986>

²³²² <https://github.com/TheHPXProject/hpx/pull/4985>

²³²³ <https://github.com/TheHPXProject/hpx/pull/4980>

²³²⁴ <https://github.com/TheHPXProject/hpx/pull/4979>

²³²⁵ <https://github.com/TheHPXProject/hpx/pull/4977>

²³²⁶ <https://github.com/TheHPXProject/hpx/pull/4976>

²³²⁷ <https://github.com/TheHPXProject/hpx/pull/4975>

²³²⁸ <https://github.com/TheHPXProject/hpx/pull/4973>

²³²⁹ <https://github.com/TheHPXProject/hpx/pull/4970>

- PR #4969²³³⁰ - Moving `is_execution_policy` and friends into namespace `hpx`
- PR #4968²³³¹ - Enable deprecation warnings for 1.6.0 and move any functionality to `hpx` namespace
- PR #4967²³³² - Define deprecation macros conditionally
- PR #4966²³³³ - Add `clang-format` and `cmake-format` version prints
- PR #4965²³³⁴ - Making `is_heap` and `is_heap_until` conforming to C++20
- PR #4964²³³⁵ - Adding parallel `make_heap`
- PR #4962²³³⁶ - Fix external timer function pointer exports
- PR #4960²³³⁷ - Fixing folder names for module tests and examples
- PR #4959²³³⁸ - Adding communications set
- PR #4958²³³⁹ - Deprecate tuple and timing functionality in `hpx::util`
- PR #4957²³⁴⁰ - Fixing unity build option for `parcelpoints`
- PR #4953²³⁴¹ - Fixing MSVC problems after recent restructurings
- PR #4952²³⁴² - Make `parallel_executor` use `thread_pool_executor` spawning mechanism
- PR #4948²³⁴³ - Clean up old artifacts better and more aggressively on Jenkins
- PR #4947²³⁴⁴ - Add HIP support for AMD GPUs
- PR #4945²³⁴⁵ - Enable `HPX_WITH_UNITY_BUILD` option on one of the Jenkins configurations
- PR #4943²³⁴⁶ - Move public `hpx::parallel::execution` functionality to `hpx::execution`
- PR #4938²³⁴⁷ - Post release cleanup
- PR #4858²³⁴⁸ - Extending resilience APIs to support distributed invocations
- PR #4744²³⁴⁹ - Fork-join executor
- PR #4665²³⁵⁰ - Implementing sender, receiver, and `operation_state` concepts in terms of P0443r13
- PR #4649²³⁵¹ - Split `libhpx` into multiple libraries
- PR #4642²³⁵² - Implementing `operation_state` concept in terms of P0443r13

²³³⁰ <https://github.com/TheHPXProject/hpx/pull/4969>

²³³¹ <https://github.com/TheHPXProject/hpx/pull/4968>

²³³² <https://github.com/TheHPXProject/hpx/pull/4967>

²³³³ <https://github.com/TheHPXProject/hpx/pull/4966>

²³³⁴ <https://github.com/TheHPXProject/hpx/pull/4965>

²³³⁵ <https://github.com/TheHPXProject/hpx/pull/4964>

²³³⁶ <https://github.com/TheHPXProject/hpx/pull/4962>

²³³⁷ <https://github.com/TheHPXProject/hpx/pull/4960>

²³³⁸ <https://github.com/TheHPXProject/hpx/pull/4959>

²³³⁹ <https://github.com/TheHPXProject/hpx/pull/4958>

²³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4957>

²³⁴¹ <https://github.com/TheHPXProject/hpx/pull/4953>

²³⁴² <https://github.com/TheHPXProject/hpx/pull/4952>

²³⁴³ <https://github.com/TheHPXProject/hpx/pull/4948>

²³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4947>

²³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4945>

²³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4943>

²³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4938>

²³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4858>

²³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4744>

²³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4665>

²³⁵¹ <https://github.com/TheHPXProject/hpx/pull/4649>

²³⁵² <https://github.com/TheHPXProject/hpx/pull/4642>

- [PR #4640²³⁵³](#) - Implementing receiver concept in terms of P0443r13
- [PR #4622²³⁵⁴](#) - Sanitizer fixes

HPX V1.5.1 (Sep 30, 2020)

General changes

This is a patch release. It contains the following changes:

- Remove restriction on suspending runtime with multiple localities, users are now responsible for synchronizing work between localities before suspending.
- Fixes several compilation problems and warnings.
- Adds notes in the documentation explaining how to cite HPX.

Closed issues

- [Issue #4971²³⁵⁵](#) - Parallel sort fails to compile with C++20
- [Issue #4950²³⁵⁶](#) - Build with `HPX_WITH_PARCELPORT_ACTION_COUNTERS_ON` fails
- [Issue #4940²³⁵⁷](#) - Codespell report for “HPX” (on fossies.org)
- [Issue #4937²³⁵⁸](#) - Allow suspension of runtime for multiple localities

Closed pull requests

- [PR #4982²³⁵⁹](#) - Add page about citing HPX to documentation
- [PR #4981²³⁶⁰](#) - Adding the missing include
- [PR #4974²³⁶¹](#) - Remove leftover format export hack
- [PR #4972²³⁶²](#) - Removing use of `get_temporary_buffer` and `return_temporary_buffer`
- [PR #4963²³⁶³](#) - Renaming files to avoid warnings from the vs build system
- [PR #4951²³⁶⁴](#) - Fixing build if `HPX_WITH_PARCELPORT_ACTION_COUNTERS=On`
- [PR #4946²³⁶⁵](#) - Allow suspension on multiple localities
- [PR #4944²³⁶⁶](#) - Fix typos reported by fossies codespell report
- [PR #4941²³⁶⁷](#) - Adding some explanation to README about how to cite HPX

²³⁵³ <https://github.com/TheHPXProject/hpx/pull/4640>
²³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4622>
²³⁵⁵ <https://github.com/TheHPXProject/hpx/issues/4971>
²³⁵⁶ <https://github.com/TheHPXProject/hpx/issues/4950>
²³⁵⁷ <https://github.com/TheHPXProject/hpx/issues/4940>
²³⁵⁸ <https://github.com/TheHPXProject/hpx/issues/4937>
²³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4982>
²³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4981>
²³⁶¹ <https://github.com/TheHPXProject/hpx/pull/4974>
²³⁶² <https://github.com/TheHPXProject/hpx/pull/4972>
²³⁶³ <https://github.com/TheHPXProject/hpx/pull/4963>
²³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4951>
²³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4946>
²³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4944>
²³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4941>

- [PR #4939](#)²³⁶⁸ - Small changes

HPX V1.5.0 (Sep 02, 2020)

General changes

The main focus of this release is on APIs and C++20 conformance. We have added many new C++20 features and adapted multiple algorithms to be fully C++20 conformant. As part of the modularization we have begun specifying the public API of HPX in terms of headers and functionality, and aligning it more closely to the C++ standard. All non-distributed modules are now in place, along with an experimental option to completely disable distributed features in HPX. We have also added experimental asynchronous MPI and CUDA executors. Lastly this release introduces CMake targets for depending projects, performance improvements, and many bug fixes.

- We have added the C++20 features `hpx::jthread` and `hpx::stop_token`. `hpx::condition_variable_any` now exposes new functions supporting `hpx::stop_token`.
- We have added `hpx::stable_sort` based on Francisco Tapia's implementation.
- We have adapted existing synchronization primitives to be fully conformant C++20: `hpx::barrier`, `hpx::latch`, `hpx::counting_semaphore`, and `hpx::binary_semaphore`.
- We have started using customization point objects (CPOs) to make the corresponding algorithms fully conformant to C++20 as well as to make algorithm extension easier for the user. `all_of/any_of/none_of`, `copy`, `count`, `destroy`, `equal`, `fill`, `find`, `for_each`, `generate`, `mismatch`, `move`, `reduce`, `transform_reduce` are using those CPOs (all in namespace `hpx`). We also have adapted their corresponding `hpx::ranges` versions to be conforming to C++20 in this release.
- We have adapted support for `co_await` to C++20, in addition to `hpx::future` it now also supports `hpx::shared_future`. We have also added allocator support for futures returned by `co_return`. It is no longer in the `experimental` namespace.
- We added serialization support for `std::variant` and `std::tuple`.
- `result_of` and `is_callable` are now deprecated and replaced by `invoke_result` and `is_invocable` to conform to C++20.
- We continued with the modularization, making it easier for us to add the new experimental `HPX_WITH_DISTRIBUTED_RUNTIME` CMake option (see below) . A significant amount of headers have been deprecated. We adapted the namespaces and headers we could to be closer to the standard ones (*Public API*). Depending code should still compile, however warnings are now generated instructing to change the include statements accordingly.
- It is now possible to have a basic CUDA support including a helper function to get a future from a CUDA stream and target handling. They are available under the `hpx::cuda::experimental` namespace and they can be enabled with the `-DHPX_WITH_ASYNC_CUDA=ON` CMake option.
- We added a new `hpx::mpi::experimental` namespace for getting futures from an asynchronous MPI call and a new minimal MPI executor `hpx::mpi::experimental::executor`. These can be enabled with the `-DHPX_WITH_ASYNC_MPI=On` CMake option.
- A polymorphic executor has been implemented to reduce compile times as a function accepting executors can potentially be instantiated only once instead of multiple times with different executors. It accepts the function signature as a template argument. It needs to be constructed from any other executor. Please note, that the function signatures that can be scheduled using `then_execute`, `bulk_sync_execute`, `bulk_async_execute` and `bulk_then_execute` are slightly different (See the comment in [PR #4514](#)²³⁶⁹ for more details).
- The underlying executor of `block_executor` has been updated to a newer one.

²³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4939>

²³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4514>

- We have added a parameter to `auto_chunk_size` to control the amount of iterations to measure.
- All executor parameter hooks can now be exposed through the executor itself. This will allow to deprecate the `.with()` functionality on execution policies in the future. This is also a first step towards simplifying our executor APIs in preparation for the upcoming C++23 executors (senders/receivers).
- We have moved all of the existing APIs related to resiliency into the namespace `hpx::resiliency::experimental`. Please note this is a breaking change without backwards-compatibility option. We have converted all of those APIs to be based on customization point objects. Two new executors have been added to enable easy integration of the existing resiliency features with other facilities (like the parallel algorithms): `replay_executor` and `replicate_executor`.
- We have added performance counters type information (aggregating, monotonically increasing, average count, average timer, etc.).
- HPX threads are now re-scheduled on the same worker thread they were suspended on to avoid cache misses from moving from one thread to the other. This behavior doesn't prevent the thread from being stolen, however.
- We have added a new configuration option `hpx.exception_verbosity` to allow to control the level of verbosity of the exceptions (3 levels available).
- `broadcast_to`, `broadcast_from`, `scatter_to` and `scatter_from` have been added to the collectives, modernization of `gather_here` and `gather_there` with futures taken by rvalue references. See the breaking change on `all_to_all` in the next section. None of the collectives need supporting macros anymore (e.g. specifying the data types used for a collective operation using `HPX_REGISTER_ALLGATHER` and similar is not needed anymore).
- New API functions have been added: a) to get the number of cores which are idle (`hpx::get_idle_core_count`) and b) returning a bitmask representing the currently idle cores (`hpx::get_idle_core_mask`).
- We have added an experimental option to only enable the local runtime, you can disable the distributed runtime with `HPX_WITH_DISTRIBUTED_RUNTIME=OFF`. You can also enable the local runtime by using the `--hpx:local` runtime option.
- We fixed task annotations for actions.
- The alias `hpx::promise` to `hpx::lcos::promise` is now deprecated. You can use `hpx::lcos::promise` directly instead. `hpx::promise` will refer to the local-only promise in the future.
- We have added a `prepare_checkpoint` API function that calculates the amount of necessary buffer space for a particular set of arguments checkpointed.
- We have added `hpx::upgrade_lock` and `hpx::upgrade_to_unique_lock`, which make `hpx::shared_mutex` (and similar) usable in more flexible ways.
- We have changed the CMake targets exposed to the user, it now includes `HPX:hpx`, `HPX:wrap_main` (int main as the first *HPX* thread of the application, see *Starting the HPX runtime*), `HPX:plugin`, `HPX:component`. The CMake variables `HPX_INCLUDE_DIRS` and `HPX_LIBRARIES` are deprecated and will be removed in a future release, you should now link directly to the `HPX:hpx` CMake target.
- A new example is demonstrating how to create and use a wrapping executor (`quickstart/executor_with_thread_hooks.cpp`)
- A new example is demonstrating how to disable thread stealing during the execution of parallel algorithms (`quickstart/disable_thread_stealing_executor.cpp`)
- We now require for our CMake build system configuration files to be formatted using `cmake-format`.
- We have removed more dependencies on various Boost libraries.
- We have added an experimental option enabling unity builds of HPX using the `-DHPX_WITH_UNITY_BUILD=On` CMake option.

- Many bug fixes.

Breaking changes

- *HPX* now requires a C++14 capable compiler. We have set the *HPX* C++ standard automatically to C++14 and if it needs to be set explicitly, it should be specified through the `CMAKE_CXX_STANDARD` setting as mandated by CMake. The `HPX_WITH_CXX*` variables are now deprecated and will be removed in the future.
- Building and using *HPX* is now supported only when using CMake V3.13 or later, Boost V1.64 or newer, and when compiling with clang V5, gcc V7, or VS2019, or later. Other compilers might still work but have not been tested thoroughly.
- We have added a `hpx::init_params` struct to pass parameters for *HPX* initialization e.g. the resource partitioner callback to initialize thread pools (*Using the resource partitioner*).
- The `all_to_all` algorithm is renamed to `all_gather`, and the new `all_to_all` algorithm is not compatible with the old one.
- We have moved all of the existing APIs related to resiliency into the namespace `hpx::resiliency::experimental`.

Closed issues

- [Issue #4918²³⁷⁰](#) - Rename distributed_executors module
- [Issue #4900²³⁷¹](#) - Adding JOSS status badge to README
- [Issue #4897²³⁷²](#) - Compiler warning, deprecated header used by *HPX* itself
- [Issue #4886²³⁷³](#) - A future bound to an action executing on a different locality doesn't capture exception state
- [Issue #4880²³⁷⁴](#) - Undefined reference to main build error when `HPX_WITH_DYNAMIC_HP_X_MAIN=OFF`
- [Issue #4877²³⁷⁵](#) - `hpx_main` might not able to start *hpx* runtime properly
- [Issue #4850²³⁷⁶](#) - Issues creating templated component
- [Issue #4829²³⁷⁷](#) - Spack package & `HPX_WITH_GENERIC_CONTEXT_COROUTINES`
- [Issue #4820²³⁷⁸](#) - PAPI counters don't work
- [Issue #4818²³⁷⁹](#) - *HPX* can't be used with IO pool turned off
- [Issue #4816²³⁸⁰](#) - Build of *HPX* fails when `find_package(Boost)` is called before `FetchContent_MakeAvailable(hpx)`
- [Issue #4813²³⁸¹](#) - *HPX* MPI Future failed
- [Issue #4811²³⁸²](#) - Remove `HPX::hpx_no_wrap_main` target before 1.5.0 release

²³⁷⁰ <https://github.com/TheHPXProject/hpx/issues/4918>

²³⁷¹ <https://github.com/TheHPXProject/hpx/issues/4900>

²³⁷² <https://github.com/TheHPXProject/hpx/issues/4897>

²³⁷³ <https://github.com/TheHPXProject/hpx/issues/4886>

²³⁷⁴ <https://github.com/TheHPXProject/hpx/issues/4880>

²³⁷⁵ <https://github.com/TheHPXProject/hpx/issues/4877>

²³⁷⁶ <https://github.com/TheHPXProject/hpx/issues/4850>

²³⁷⁷ <https://github.com/TheHPXProject/hpx/issues/4829>

²³⁷⁸ <https://github.com/TheHPXProject/hpx/issues/4820>

²³⁷⁹ <https://github.com/TheHPXProject/hpx/issues/4818>

²³⁸⁰ <https://github.com/TheHPXProject/hpx/issues/4816>

²³⁸¹ <https://github.com/TheHPXProject/hpx/issues/4813>

²³⁸² <https://github.com/TheHPXProject/hpx/issues/4811>

- [Issue #4810](#)²³⁸³ - In `hpx::for_each::invoke_projected` the `hpx::util::decay` is misguided
- [Issue #4787](#)²³⁸⁴ - `transform_inclusive_scan` gives incorrect results for non-commutative operator
- [Issue #4786](#)²³⁸⁵ - `transform_inclusive_scan` tries to implicitly convert between types, instead of using the provided `conv` function
- [Issue #4779](#)²³⁸⁶ - HPX build error with GCC 10.1
- [Issue #4766](#)²³⁸⁷ - Move HPX.Compute functionality to experimental namespace
- [Issue #4763](#)²³⁸⁸ - License file name
- [Issue #4758](#)²³⁸⁹ - CMake profiling results
- [Issue #4755](#)²³⁹⁰ - Building HPX with support for PAPI fails
- [Issue #4754](#)²³⁹¹ - CMake cache creation breaks when using HPX with mimalloc
- [Issue #4752](#)²³⁹² - HPX MPI Future build failed
- [Issue #4746](#)²³⁹³ - Memory leak when using dataflow icw components
- [Issue #4731](#)²³⁹⁴ - Bug in stencil example, calculation of locality IDs
- [Issue #4723](#)²³⁹⁵ - Build fail with NETWORKING OFF
- [Issue #4720](#)²³⁹⁶ - Add compatibility headers for modules that had their module headers implicitly generated in 1.4.1
- [Issue #4719](#)²³⁹⁷ - Undeprecate some module headers
- [Issue #4712](#)²³⁹⁸ - Rename `HPX_MPI_WITH_FUTURES` option
- [Issue #4709](#)²³⁹⁹ - Make deprecation warnings overridable in dependent projects
- [Issue #4691](#)²⁴⁰⁰ - Suggestion to fix and enhance the `thread_mapper` API
- [Issue #4686](#)²⁴⁰¹ - Fix tutorials examples
- [Issue #4685](#)²⁴⁰² - HPX distributed map fails to compile
- [Issue #4680](#)²⁴⁰³ - Build error with `HPX_WITH_DYNAMIC_HPX_MAIN=OFF`
- [Issue #4679](#)²⁴⁰⁴ - Build error for hpx w/ Apex on Summit

²³⁸³ <https://github.com/TheHPXProject/hpx/issues/4810>

²³⁸⁴ <https://github.com/TheHPXProject/hpx/issues/4787>

²³⁸⁵ <https://github.com/TheHPXProject/hpx/issues/4786>

²³⁸⁶ <https://github.com/TheHPXProject/hpx/issues/4779>

²³⁸⁷ <https://github.com/TheHPXProject/hpx/issues/4766>

²³⁸⁸ <https://github.com/TheHPXProject/hpx/issues/4763>

²³⁸⁹ <https://github.com/TheHPXProject/hpx/issues/4758>

²³⁹⁰ <https://github.com/TheHPXProject/hpx/issues/4755>

²³⁹¹ <https://github.com/TheHPXProject/hpx/issues/4754>

²³⁹² <https://github.com/TheHPXProject/hpx/issues/4752>

²³⁹³ <https://github.com/TheHPXProject/hpx/issues/4746>

²³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/4731>

²³⁹⁵ <https://github.com/TheHPXProject/hpx/issues/4723>

²³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/4720>

²³⁹⁷ <https://github.com/TheHPXProject/hpx/issues/4719>

²³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/4712>

²³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/4709>

²⁴⁰⁰ <https://github.com/TheHPXProject/hpx/issues/4691>

²⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/4686>

²⁴⁰² <https://github.com/TheHPXProject/hpx/issues/4685>

²⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/4680>

²⁴⁰⁴ <https://github.com/TheHPXProject/hpx/issues/4679>

- Issue #4675²⁴⁰⁵ - build error with HPX_WITH_NETWORKING=OFF
- Issue #4674²⁴⁰⁶ - Error running Quickstart tests on OS X
- Issue #4662²⁴⁰⁷ - MPI initialization broken when networking off
- Issue #4652²⁴⁰⁸ - How to fix distributed action annotation
- Issue #4650²⁴⁰⁹ - thread descriptions are broken... again
- Issue #4648²⁴¹⁰ - Thread stacksize not properly set
- Issue #4647²⁴¹¹ - Rename generated collective headers in modules
- Issue #4639²⁴¹² - Update deprecation warnings in compatibility headers to point to collective headers
- Issue #4628²⁴¹³ - mpi parcellport totally broken
- Issue #4619²⁴¹⁴ - Fully document hpx_wrap behaviour and targets
- Issue #4612²⁴¹⁵ - Compilation issue with HPX 1.4.1 and 1.4.0
- Issue #4594²⁴¹⁶ - Rename modules
- Issue #4578²⁴¹⁷ - Default value for HPX_WITH_THREAD_BACKTRACE_DEPTH
- Issue #4572²⁴¹⁸ - Thread manager should be given a runtime_configuration
- Issue #4571²⁴¹⁹ - Add high-level documentation to new modules
- Issue #4569²⁴²⁰ - Annoying warning when compiling - pls suppress or fix it.
- Issue #4555²⁴²¹ - HPX_HAVE_THREAD_BACKTRACE_ON_SUSPENSION compilation error
- Issue #4543²⁴²² - Segfaults in Release builds using *sleep_for*
- Issue #4539²⁴²³ - Compilation Error when HPX_MPI_WITH_FUTURES=ON
- Issue #4537²⁴²⁴ - Linking issue with libhpx_initd.a
- Issue #4535²⁴²⁵ - API for checking if pool with a given name exists
- Issue #4523²⁴²⁶ - Build of PR #4311 (git tag 9955e8e) fails
- Issue #4519²⁴²⁷ - Documentation problem

²⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/4675>

²⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/4674>

²⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/4662>

²⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/4652>

²⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/4650>

²⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/4648>

²⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/4647>

²⁴¹² <https://github.com/TheHPXProject/hpx/issues/4639>

²⁴¹³ <https://github.com/TheHPXProject/hpx/issues/4628>

²⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/4619>

²⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/4612>

²⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/4594>

²⁴¹⁷ <https://github.com/TheHPXProject/hpx/issues/4578>

²⁴¹⁸ <https://github.com/TheHPXProject/hpx/issues/4572>

²⁴¹⁹ <https://github.com/TheHPXProject/hpx/issues/4571>

²⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/4569>

²⁴²¹ <https://github.com/TheHPXProject/hpx/issues/4555>

²⁴²² <https://github.com/TheHPXProject/hpx/issues/4543>

²⁴²³ <https://github.com/TheHPXProject/hpx/issues/4539>

²⁴²⁴ <https://github.com/TheHPXProject/hpx/issues/4537>

²⁴²⁵ <https://github.com/TheHPXProject/hpx/issues/4535>

²⁴²⁶ <https://github.com/TheHPXProject/hpx/issues/4523>

²⁴²⁷ <https://github.com/TheHPXProject/hpx/issues/4519>

- [Issue #4513](#)²⁴²⁸ - HPXConfig.cmake contains ill-formed paths when library paths use backslashes
- [Issue #4507](#)²⁴²⁹ - User-polling introduced by MPI futures module should be more generally usable
- [Issue #4506](#)²⁴³⁰ - Make sure force_linking.hpp is not included in main module header
- [Issue #4501](#)²⁴³¹ - Fix compilation of PAPI tests
- [Issue #4497](#)²⁴³² - Add modules CI checks
- [Issue #4489](#)²⁴³³ - Polymorphic executor
- [Issue #4476](#)²⁴³⁴ - Use CMake targets defined by FindBoost
- [Issue #4473](#)²⁴³⁵ - Add vcpkg installation instructions
- [Issue #4470](#)²⁴³⁶ - Adapt hpx::future to C++20 co_await
- [Issue #4468](#)²⁴³⁷ - Compile error on Raspberry Pi 4
- [Issue #4466](#)²⁴³⁸ - Compile error on Windows, current stable:
- [Issue #4453](#)²⁴³⁹ - Installing HPX on fedora with dnf is not adding cmake files
- [Issue #4448](#)²⁴⁴⁰ - New std::variant serialization broken
- [Issue #4438](#)²⁴⁴¹ - Add performance counter flag is monotonically increasing
- [Issue #4436](#)²⁴⁴² - Build problem: same code build and works with 1.4.0 but it doesn't with 1.4.1
- [Issue #4429](#)²⁴⁴³ - Function descriptions not supported in distributed
- [Issue #4423](#)²⁴⁴⁴ - `-hpx:ini=hpx.lock_detection=0` has no effect
- [Issue #4422](#)²⁴⁴⁵ - Add performance counter metadata
- [Issue #4419](#)²⁴⁴⁶ - Weird behavior for `-hpx:print-counter-interval` with large numbers
- [Issue #4401](#)²⁴⁴⁷ - Create module repository
- [Issue #4400](#)²⁴⁴⁸ - Command line options conflict related to performance counters
- [Issue #4349](#)²⁴⁴⁹ - `-hpx:use-process-mask` option throw an exception on OS X
- [Issue #4345](#)²⁴⁵⁰ - Move gh-pages branch out of hpx repo

²⁴²⁸ <https://github.com/TheHPXProject/hpx/issues/4513>

²⁴²⁹ <https://github.com/TheHPXProject/hpx/issues/4507>

²⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/4506>

²⁴³¹ <https://github.com/TheHPXProject/hpx/issues/4501>

²⁴³² <https://github.com/TheHPXProject/hpx/issues/4497>

²⁴³³ <https://github.com/TheHPXProject/hpx/issues/4489>

²⁴³⁴ <https://github.com/TheHPXProject/hpx/issues/4476>

²⁴³⁵ <https://github.com/TheHPXProject/hpx/issues/4473>

²⁴³⁶ <https://github.com/TheHPXProject/hpx/issues/4470>

²⁴³⁷ <https://github.com/TheHPXProject/hpx/issues/4468>

²⁴³⁸ <https://github.com/TheHPXProject/hpx/issues/4466>

²⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/4453>

²⁴⁴⁰ <https://github.com/TheHPXProject/hpx/issues/4448>

²⁴⁴¹ <https://github.com/TheHPXProject/hpx/issues/4438>

²⁴⁴² <https://github.com/TheHPXProject/hpx/issues/4436>

²⁴⁴³ <https://github.com/TheHPXProject/hpx/issues/4429>

²⁴⁴⁴ <https://github.com/TheHPXProject/hpx/issues/4423>

²⁴⁴⁵ <https://github.com/TheHPXProject/hpx/issues/4422>

²⁴⁴⁶ <https://github.com/TheHPXProject/hpx/issues/4419>

²⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/4401>

²⁴⁴⁸ <https://github.com/TheHPXProject/hpx/issues/4400>

²⁴⁴⁹ <https://github.com/TheHPXProject/hpx/issues/4349>

²⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/4345>

- Issue #4323²⁴⁵¹ - Const-correctness error in assignment operator of `compute::vector`
- Issue #4318²⁴⁵² - ASIO breaks with C++2a concepts
- Issue #4317²⁴⁵³ - Application runs even if `-hpx:help` is specified
- Issue #4063²⁴⁵⁴ - Document `hpxcxx` compiler wrapper
- Issue #3983²⁴⁵⁵ - Implement the C++20 Synchronization Library
- Issue #3696²⁴⁵⁶ - C++11 `constexpr` support is now required
- Issue #3623²⁴⁵⁷ - Modular HPX branch and an alternative project layout
- Issue #2836²⁴⁵⁸ - The worst-case time complexity of `parallel::sort` seems to be $O(N^2)$.

Closed pull requests

- PR #4936²⁴⁵⁹ - Minor documentation fixes part 2
- PR #4935²⁴⁶⁰ - Add copyright and license to joss paper file
- PR #4934²⁴⁶¹ - Adding Semicolon in Documentation
- PR #4932²⁴⁶² - Fixing compiler warnings
- PR #4931²⁴⁶³ - Small documentation formatting fixes
- PR #4930²⁴⁶⁴ - Documentation Distributed HPX applications `localvv` with `local_vv`
- PR #4929²⁴⁶⁵ - Add final version of the JOSS paper
- PR #4928²⁴⁶⁶ - Add `HPX_NODISCARD` to `enable_user_polling` structs
- PR #4926²⁴⁶⁷ - Rename `distributed_executors` module to `executors_distributed`
- PR #4925²⁴⁶⁸ - Making `transform_reduce` conforming to C++20
- PR #4923²⁴⁶⁹ - Don't acquire lock if not needed
- PR #4921²⁴⁷⁰ - Update the release notes for the release candidate 3
- PR #4920²⁴⁷¹ - Disable `libcdis` release
- PR #4919²⁴⁷² - Make `cuda` event pool dynamic instead of fixed size

²⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/4323>

²⁴⁵² <https://github.com/TheHPXProject/hpx/issues/4318>

²⁴⁵³ <https://github.com/TheHPXProject/hpx/issues/4317>

²⁴⁵⁴ <https://github.com/TheHPXProject/hpx/issues/4063>

²⁴⁵⁵ <https://github.com/TheHPXProject/hpx/issues/3983>

²⁴⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3696>

²⁴⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3623>

²⁴⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2836>

²⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4936>

²⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4935>

²⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/4934>

²⁴⁶² <https://github.com/TheHPXProject/hpx/pull/4932>

²⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/4931>

²⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4930>

²⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4929>

²⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4928>

²⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4926>

²⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4925>

²⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4923>

²⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4921>

²⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/4920>

²⁴⁷² <https://github.com/TheHPXProject/hpx/pull/4919>

- PR #4917²⁴⁷³ - Move chrono functionality to hpx::chrono namespace
- PR #4916²⁴⁷⁴ - HPX_HAVE_DEPRECATED_WARNINGS needs to be set even when disabled
- PR #4915²⁴⁷⁵ - Moving more action related files to actions modules
- PR #4914²⁴⁷⁶ - Add alias targets with namespaces used for exporting
- PR #4912²⁴⁷⁷ - Aggregate initialize CPOs
- PR #4910²⁴⁷⁸ - Explicitly specify hwloc root on Jenkins CSCS builds
- PR #4908²⁴⁷⁹ - Fix algorithms documentation
- PR #4907²⁴⁸⁰ - Remove HPX::hpx_no_wrap_main target
- PR #4906²⁴⁸¹ - Fixing unused variable warning
- PR #4905²⁴⁸² - Adding specializations for simple for_loops
- PR #4904²⁴⁸³ - Update boost to 1.74.0 for the newest jenkins configs
- PR #4903²⁴⁸⁴ - Hide GITHUB_TOKEN environment variables from environment variable output
- PR #4902²⁴⁸⁵ - Cancel previous pull requests builds before starting a new one with Jenkins
- PR #4901²⁴⁸⁶ - Update public API list with updated algorithms
- PR #4899²⁴⁸⁷ - Suggested changes for HPX V1.5 release notes
- PR #4898²⁴⁸⁸ - Minor tweak to hpx::equal implementation
- PR #4896²⁴⁸⁹ - Making generate() and generate_n conforming to C++20
- PR #4895²⁴⁹⁰ - Update apex tag
- PR #4894²⁴⁹¹ - Fix exception handling for tasks
- PR #4893²⁴⁹² - Remove last use of std::result_of, removed in C++20
- PR #4892²⁴⁹³ - Adding replay_executor and replicate_executor
- PR #4889²⁴⁹⁴ - Restore old behaviour of not requiring linking to hpx_wrap when HPX_WITH_DYNAMIC_HPX_MAIN=OFF
- PR #4887²⁴⁹⁵ - Making sure remotely thrown (non-hpx) exceptions are properly marshaled back to invocation

²⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/4917>

²⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4916>

²⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4915>

²⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4914>

²⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4912>

²⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4910>

²⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4908>

²⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4907>

²⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/4906>

²⁴⁸² <https://github.com/TheHPXProject/hpx/pull/4905>

²⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/4904>

²⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4903>

²⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4902>

²⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4901>

²⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4899>

²⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4898>

²⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4896>

²⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4895>

²⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/4894>

²⁴⁹² <https://github.com/TheHPXProject/hpx/pull/4893>

²⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/4892>

²⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4889>

²⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4887>

site

- [PR #4885²⁴⁹⁶](#) - Adapting `hpx::find` and `friends` to C++20
- [PR #4884²⁴⁹⁷](#) - Adapting `mismatch` to C++20
- [PR #4883²⁴⁹⁸](#) - Adapting `hpx::equal` to be conforming to C++20
- [PR #4882²⁴⁹⁹](#) - Fixing exception handling for `hpx::copy` and adding missing tests
- [PR #4881²⁵⁰⁰](#) - Adds different runtime exception when registering thread with the HPX runtime
- [PR #4876²⁵⁰¹](#) - Adding example demonstrating how to disable thread stealing during the execution of parallel algorithms
- [PR #4874²⁵⁰²](#) - Adding non-policy tests to `all_of`, `any_of`, and `none_of`
- [PR #4873²⁵⁰³](#) - Set CUDA compute capability on rostam Jenkins builds
- [PR #4872²⁵⁰⁴](#) - Force partitioned vector scan tests to run serially
- [PR #4870²⁵⁰⁵](#) - Making move conforming with C++20
- [PR #4869²⁵⁰⁶](#) - Making `destroy` and `destroy_n` conforming to C++20
- [PR #4868²⁵⁰⁷](#) - Fix miscellaneous header problems
- [PR #4867²⁵⁰⁸](#) - Add CPOs for `for_each`
- [PR #4865²⁵⁰⁹](#) - Adapting `count` and `count_if` to be conforming to C++20
- [PR #4864²⁵¹⁰](#) - Release notes 1.5.0
- [PR #4863²⁵¹¹](#) - adding `libcds-hpx` tag to prepare for `hpx1.5` release
- [PR #4862²⁵¹²](#) - Adding version specific deprecation options
- [PR #4861²⁵¹³](#) - Limiting executor improvements
- [PR #4860²⁵¹⁴](#) - Making `fill` and `fill_n` compatible with C++20
- [PR #4859²⁵¹⁵](#) - Adapting `all_of`, `any_of`, and `none_of` to C++20
- [PR #4857²⁵¹⁶](#) - Improve `libCDS` integration
- [PR #4856²⁵¹⁷](#) - Correct typos in the documentation of the `hpx` performance counters

²⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4885>

²⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4884>

²⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4883>

²⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4882>

²⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4881>

²⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/4876>

²⁵⁰² <https://github.com/TheHPXProject/hpx/pull/4874>

²⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/4873>

²⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4872>

²⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4870>

²⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4869>

²⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4868>

²⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4867>

²⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4865>

²⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/4864>

²⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/4863>

²⁵¹² <https://github.com/TheHPXProject/hpx/pull/4862>

²⁵¹³ <https://github.com/TheHPXProject/hpx/pull/4861>

²⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/4860>

²⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/4859>

²⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/4857>

²⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/4856>

- PR #4854²⁵¹⁸ - Removing obsolete code
- PR #4853²⁵¹⁹ - Adding test that derives component from two other components
- PR #4852²⁵²⁰ - Fix mpi_ring test in distributed mode by ensuring all ranks run hpx_main
- PR #4851²⁵²¹ - Converting resiliency APIs to tag_invoke based CPOs
- PR #4849²⁵²² - Enable use of future_overhead test when DISTRIBUTED_RUNTIME is OFF
- PR #4847²⁵²³ - Fixing 'error prone' constructs as reported by Codacy
- PR #4846²⁵²⁴ - Disable Boost.Asio concepts support
- PR #4845²⁵²⁵ - Fix PAPI counters
- PR #4843²⁵²⁶ - Remove dependency on various Boost headers
- PR #4841²⁵²⁷ - Rearrange public API headers
- PR #4840²⁵²⁸ - Fixing TSS problems during thread termination
- PR #4839²⁵²⁹ - Fix async_cuda build problems when distributed runtime is disabled
- PR #4837²⁵³⁰ - Restore compatibility for old (now deprecated) copy algorithms
- PR #4836²⁵³¹ - Adding CPOs for hpx::reduce
- PR #4835²⁵³² - Remove *using util::result_of* from namespace hpx
- PR #4834²⁵³³ - Fixing the calculation of the number of idle cores and the corresponding idle masks
- PR #4833²⁵³⁴ - Allow thread function destructors to yield
- PR #4832²⁵³⁵ - Fixing assertion in split_gids and memory leaks in 1d_stencil_7
- PR #4831²⁵³⁶ - Making sure MPI_CXX_COMPILE_FLAGS is interpreted as a sequence of options
- PR #4830²⁵³⁷ - Update documentation on using HPX::wrap_main
- PR #4827²⁵³⁸ - Update clang-newest configuration to use clang 10
- PR #4826²⁵³⁹ - Add Jenkins configuration for rostam
- PR #4825²⁵⁴⁰ - Move all CUDA functionality to hpx::cuda::experimental namespace

²⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/4854>

²⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/4853>

²⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/4852>

²⁵²¹ <https://github.com/TheHPXProject/hpx/pull/4851>

²⁵²² <https://github.com/TheHPXProject/hpx/pull/4849>

²⁵²³ <https://github.com/TheHPXProject/hpx/pull/4847>

²⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/4846>

²⁵²⁵ <https://github.com/TheHPXProject/hpx/pull/4845>

²⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/4843>

²⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/4841>

²⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/4840>

²⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/4839>

²⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/4837>

²⁵³¹ <https://github.com/TheHPXProject/hpx/pull/4836>

²⁵³² <https://github.com/TheHPXProject/hpx/pull/4835>

²⁵³³ <https://github.com/TheHPXProject/hpx/pull/4834>

²⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/4833>

²⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/4832>

²⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/4831>

²⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/4830>

²⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/4827>

²⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/4826>

²⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4825>

- PR #4824²⁵⁴¹ - Add support for building master/release branches to Jenkins configuration
- PR #4821²⁵⁴² - Implement customization point for `hpx::copy` and `hpx::ranges::copy`
- PR #4819²⁵⁴³ - Allow finding Boost components before finding HPX
- PR #4817²⁵⁴⁴ - Adding range version of stable sort
- PR #4815²⁵⁴⁵ - Fix a wrong `#ifdef` for IO/TIMER pools causing build errors
- PR #4814²⁵⁴⁶ - Replace `hpx::function_nonsr` with `std::function` in error module
- PR #4809²⁵⁴⁷ - Foreach adapt
- PR #4808²⁵⁴⁸ - Make internal algorithms functions const
- PR #4807²⁵⁴⁹ - Add Jenkins configuration for running on Piz Daint
- PR #4806²⁵⁵⁰ - Update documentation links to new domain name
- PR #4805²⁵⁵¹ - Applying changes that resolve time complexity issues in sort
- PR #4803²⁵⁵² - Adding implementation of `stable_sort`
- PR #4802²⁵⁵³ - Fix datapar header paths
- PR #4801²⁵⁵⁴ - Replace `boost::shared_array<T>` with `std::shared_ptr<T[]>` if supported
- PR #4799²⁵⁵⁵ - Fixing `#include` paths in compatibility headers
- PR #4798²⁵⁵⁶ - Include the main module header (fixes partially #4488)
- PR #4797²⁵⁵⁷ - Change cmake targets
- PR #4794²⁵⁵⁸ - Removing 128bit integer emulation
- PR #4793²⁵⁵⁹ - Make sure global variable is handled properly
- PR #4792²⁵⁶⁰ - Replace `enable_if` with **HPX_CONCEPT_REQUIRES_** and add `is_sentinel_for` constraint
- PR #4790²⁵⁶¹ - Move deprecation warnings from base template to template specializations for `result_of` etc. structs
- PR #4789²⁵⁶² - Fix hangs during assertion handling and distributed runtime construction
- PR #4788²⁵⁶³ - Fixing inclusive transform scan algorithm to properly handle initial value

²⁵⁴¹ <https://github.com/TheHPXProject/hpx/pull/4824>

²⁵⁴² <https://github.com/TheHPXProject/hpx/pull/4821>

²⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/4819>

²⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4817>

²⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4815>

²⁵⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4814>

²⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4809>

²⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4808>

²⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4807>

²⁵⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4806>

²⁵⁵¹ <https://github.com/TheHPXProject/hpx/pull/4805>

²⁵⁵² <https://github.com/TheHPXProject/hpx/pull/4803>

²⁵⁵³ <https://github.com/TheHPXProject/hpx/pull/4802>

²⁵⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4801>

²⁵⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4799>

²⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4798>

²⁵⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4797>

²⁵⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4794>

²⁵⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4793>

²⁵⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4792>

²⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/4790>

²⁵⁶² <https://github.com/TheHPXProject/hpx/pull/4789>

²⁵⁶³ <https://github.com/TheHPXProject/hpx/pull/4788>

- PR #4785²⁵⁶⁴ - Fixing barrier test
- PR #4784²⁵⁶⁵ - Fixing deleter argument bindings in `serialize_buffer`
- PR #4783²⁵⁶⁶ - Add coveralls badge
- PR #4782²⁵⁶⁷ - Make header tests parallel again
- PR #4780²⁵⁶⁸ - Remove outdated comment about `hpx::stop` in documentation
- PR #4776²⁵⁶⁹ - debug print improvements
- PR #4775²⁵⁷⁰ - Checkpoint cleanup
- PR #4771²⁵⁷¹ - Fix compilation with `HPX_WITH_NETWORKING=OFF`
- PR #4767²⁵⁷² - Remove all force linking leftovers
- PR #4765²⁵⁷³ - Fix 1d stencil index calculation
- PR #4764²⁵⁷⁴ - Force some tests to run serially
- PR #4762²⁵⁷⁵ - Update pointees in compatibility headers
- PR #4761²⁵⁷⁶ - Fix running and building of execution module tests on CircleCI
- PR #4760²⁵⁷⁷ - Storing `hpx_options` in global property to speed up summary report
- PR #4759²⁵⁷⁸ - Reduce memory requirements for our main shared state
- PR #4757²⁵⁷⁹ - Fix `mimalloc` linking on Windows
- PR #4756²⁵⁸⁰ - Fix compilation issues
- PR #4753²⁵⁸¹ - Re-adding API functions that were lost during merges
- PR #4751²⁵⁸² - Revert “Create coverage reports and upload them to `codecov.io`”
- PR #4750²⁵⁸³ - Fixing possible race condition during termination detection
- PR #4749²⁵⁸⁴ - Deprecate `result_of` and friends
- PR #4748²⁵⁸⁵ - Create coverage reports and upload them to `codecov.io`
- PR #4747²⁵⁸⁶ - Changing `#include` for MPI `parcelpport`

²⁵⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4785>

²⁵⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4784>

²⁵⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4783>

²⁵⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4782>

²⁵⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4780>

²⁵⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4776>

²⁵⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4775>

²⁵⁷¹ <https://github.com/TheHPXProject/hpx/pull/4771>

²⁵⁷² <https://github.com/TheHPXProject/hpx/pull/4767>

²⁵⁷³ <https://github.com/TheHPXProject/hpx/pull/4765>

²⁵⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4764>

²⁵⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4762>

²⁵⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4761>

²⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4760>

²⁵⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4759>

²⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4757>

²⁵⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4756>

²⁵⁸¹ <https://github.com/TheHPXProject/hpx/pull/4753>

²⁵⁸² <https://github.com/TheHPXProject/hpx/pull/4751>

²⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/4750>

²⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4749>

²⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4748>

²⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4747>

- PR #4745²⁵⁸⁷ - Add *is_sentinel_for* trait implementation and test
- PR #4743²⁵⁸⁸ - Fix *init_globally* example after runtime mode changes
- PR #4742²⁵⁸⁹ - Update SUPPORT.md
- PR #4741²⁵⁹⁰ - Fixing a warning generated for unity builds with msvc
- PR #4740²⁵⁹¹ - Rename *local_lcos* and *basic_execution* modules
- PR #4739²⁵⁹² - Undeprecate a couple of *hpx/modulename.hpp* headers
- PR #4738²⁵⁹³ - Conditionally test schedulers in *thread_stacksize_current* test
- PR #4734²⁵⁹⁴ - Fixing a bunch of codacy warnings
- PR #4733²⁵⁹⁵ - Add experimental unity build option to CMake configuration
- PR #4730²⁵⁹⁶ - Fixing compilation problems with *unordered_map*
- PR #4729²⁵⁹⁷ - Fix APEX build
- PR #4727²⁵⁹⁸ - Fix missing runtime includes for distributed runtime
- PR #4726²⁵⁹⁹ - Add more API headers
- PR #4725²⁶⁰⁰ - Add more compatibility headers for deprecated module headers
- PR #4724²⁶⁰¹ - Fix 4723
- PR #4721²⁶⁰² - Attempt to fixing migration tests
- PR #4717²⁶⁰³ - Make the compatibility headers macro conditional
- PR #4716²⁶⁰⁴ - Add *hpx/runtime.hpp* and *hpx/distributed/runtime.hpp* API headers
- PR #4714²⁶⁰⁵ - Add *hpx/future.hpp* header
- PR #4713²⁶⁰⁶ - Remove *hpx/runtime/threads_fwd.hpp* and *hpx/util_fwd.hpp*
- PR #4711²⁶⁰⁷ - Make module deprecation warnings overridable
- PR #4710²⁶⁰⁸ - Add compatibility headers and other fixes after module header renaming
- PR #4708²⁶⁰⁹ - Add termination handler for parallel algorithms

²⁵⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4745>

²⁵⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4743>

²⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4742>

²⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4741>

²⁵⁹¹ <https://github.com/TheHPXProject/hpx/pull/4740>

²⁵⁹² <https://github.com/TheHPXProject/hpx/pull/4739>

²⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/4738>

²⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4734>

²⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4733>

²⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4730>

²⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4729>

²⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4727>

²⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4726>

²⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4725>

²⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/4724>

²⁶⁰² <https://github.com/TheHPXProject/hpx/pull/4721>

²⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/4717>

²⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4716>

²⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4714>

²⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4713>

²⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4711>

²⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4710>

²⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4708>

- PR #4707²⁶¹⁰ - Use `hpx::function_nonser` instead of `std::function` internally
- PR #4706²⁶¹¹ - Move header file to module
- PR #4705²⁶¹² - Fix incorrect behaviour of `cmake-format` check
- PR #4704²⁶¹³ - Fix resource tests
- PR #4701²⁶¹⁴ - Fix missing includes for `future::then` specializations
- PR #4700²⁶¹⁵ - Removing obsolete memory component
- PR #4699²⁶¹⁶ - Add short descriptions to modules missing documentation
- PR #4696²⁶¹⁷ - Rename generated modules headers
- PR #4693²⁶¹⁸ - Overhauling `thread_mapper` for public consumption
- PR #4688²⁶¹⁹ - Fix thread stack size handling
- PR #4687²⁶²⁰ - Adding `all_gather` and fixing `all_to_all`
- PR #4684²⁶²¹ - Miscellaneous compilation fixes
- PR #4683²⁶²² - Fix `HPX_WITH_DYNAMIC_HPX_MAIN=OFF`
- PR #4682²⁶²³ - Fix compilation of `pack_traversal_rebind_container.hpp`
- PR #4681²⁶²⁴ - Add missing `hpx/execution.hpp` includes for `future::then`
- PR #4678²⁶²⁵ - Typeless communicator
- PR #4677²⁶²⁶ - Forcing registry option to be accepted without checks.
- PR #4676²⁶²⁷ - Adding `scatter_to/scatter_from` collective operations
- PR #4673²⁶²⁸ - Fix PAPI counters compilation
- PR #4671²⁶²⁹ - Deprecate `hpx::promise` alias to `hpx::lcos::promise`
- PR #4670²⁶³⁰ - Explicitly instantiate `get_exception`
- PR #4667²⁶³¹ - Add `stopValue` in *Sentinel* struct instead of *Iterator*
- PR #4666²⁶³² - Add release build on Windows to GitHub actions

²⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/4707>

²⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/4706>

²⁶¹² <https://github.com/TheHPXProject/hpx/pull/4705>

²⁶¹³ <https://github.com/TheHPXProject/hpx/pull/4704>

²⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/4701>

²⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/4700>

²⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/4699>

²⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/4696>

²⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/4693>

²⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/4688>

²⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/4687>

²⁶²¹ <https://github.com/TheHPXProject/hpx/pull/4684>

²⁶²² <https://github.com/TheHPXProject/hpx/pull/4683>

²⁶²³ <https://github.com/TheHPXProject/hpx/pull/4682>

²⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/4681>

²⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/4678>

²⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/4677>

²⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/4676>

²⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/4673>

²⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/4671>

²⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/4670>

²⁶³¹ <https://github.com/TheHPXProject/hpx/pull/4667>

²⁶³² <https://github.com/TheHPXProject/hpx/pull/4666>

- PR #4664²⁶³³ - Creating itt_notify module.
- PR #4663²⁶³⁴ - Mpi fixes
- PR #4659²⁶³⁵ - Making sure declarations match definitions in register_locks implementation
- PR #4655²⁶³⁶ - Fixing task annotations for actions
- PR #4653²⁶³⁷ - Making sure APEX is linked into every application, if needed
- PR #4651²⁶³⁸ - Update get_function_annotation.hpp
- PR #4646²⁶³⁹ - Runtime type
- PR #4645²⁶⁴⁰ - Add a few more API headers
- PR #4644²⁶⁴¹ - Fixing support for mpirun (and similar)
- PR #4643²⁶⁴² - Fixing the fix for get_idle_core_count() API
- PR #4638²⁶⁴³ - Remove HPX_API_EXPORT missed in previous cleanup
- PR #4636²⁶⁴⁴ - Adding C++20 barrier
- PR #4635²⁶⁴⁵ - Adding C++20 latch API
- PR #4634²⁶⁴⁶ - Adding C++20 counting semaphore API
- PR #4633²⁶⁴⁷ - Unify execution parameters customization points
- PR #4632²⁶⁴⁸ - Adding missing bulk_sync_execute wrapper to example executor
- PR #4631²⁶⁴⁹ - Updates to documentation; grammar edits.
- PR #4630²⁶⁵⁰ - Updates to documentation; moved hyperlink
- PR #4624²⁶⁵¹ - Export set_self_ptr in thread_data.hpp instead of with forward declarations where used
- PR #4623²⁶⁵² - Clean up export macros
- PR #4621²⁶⁵³ - Trigger an error for older boost versions on power architectures
- PR #4617²⁶⁵⁴ - Ignore user-set compatibility header options if the module does not have compatibility headers
- PR #4616²⁶⁵⁵ - Fix cmake-format warning

²⁶³³ <https://github.com/TheHPXProject/hpx/pull/4664>

²⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/4663>

²⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/4659>

²⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/4655>

²⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/4653>

²⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/4651>

²⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/4646>

²⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4645>

²⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/4644>

²⁶⁴² <https://github.com/TheHPXProject/hpx/pull/4643>

²⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/4638>

²⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4636>

²⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4635>

²⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4634>

²⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4633>

²⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4632>

²⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4631>

²⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4630>

²⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/4624>

²⁶⁵² <https://github.com/TheHPXProject/hpx/pull/4623>

²⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/4621>

²⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4617>

²⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4616>

- [PR #4615](#)²⁶⁵⁶ - Add handler for serializing custom exceptions
- [PR #4614](#)²⁶⁵⁷ - Fix error message when HPX_IGNORE_CMAKE_BUILD_TYPE_COMPATIBILITY=OFF
- [PR #4613](#)²⁶⁵⁸ - Make partitioner constructor private
- [PR #4611](#)²⁶⁵⁹ - Making auto_chunk_size execute the given function using the given executor
- [PR #4610](#)²⁶⁶⁰ - Making sure the thread-local lock registration data is moving to the core the suspended HPX thread is resumed on
- [PR #4609](#)²⁶⁶¹ - Adding an API function that exposes the number of idle cores
- [PR #4608](#)²⁶⁶² - Fixing moodycamel namespace
- [PR #4607](#)²⁶⁶³ - Moving winsocket initialization to core library
- [PR #4606](#)²⁶⁶⁴ - Local runtime module etc.
- [PR #4604](#)²⁶⁶⁵ - Add config_registry module
- [PR #4603](#)²⁶⁶⁶ - Deal with distributed modules in their respective CMakeLists.txt
- [PR #4602](#)²⁶⁶⁷ - Small module fixes
- [PR #4598](#)²⁶⁶⁸ - Making sure current_executor and service_executor functions are linked into the core library
- [PR #4597](#)²⁶⁶⁹ - Adding broadcast_to/broadcast_from to collectives module
- [PR #4596](#)²⁶⁷⁰ - Fix performance regression in block_executor
- [PR #4595](#)²⁶⁷¹ - Making sure main.cpp is built as a library if HPX_WITH_DYNAMIC_MAIN=OFF
- [PR #4592](#)²⁶⁷² - Futures module
- [PR #4591](#)²⁶⁷³ - Adapting co_await support for C++20
- [PR #4590](#)²⁶⁷⁴ - Adding missing exception test for for_loop()
- [PR #4587](#)²⁶⁷⁵ - Move traits headers to hpx/modulename/traits directory
- [PR #4586](#)²⁶⁷⁶ - Remove Travis CI config
- [PR #4585](#)²⁶⁷⁷ - Update macOS test blacklist
- [PR #4584](#)²⁶⁷⁸ - Attempting to fix missing symbols in stack trace

²⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4615>

²⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4614>

²⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4613>

²⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4611>

²⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4610>

²⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/4609>

²⁶⁶² <https://github.com/TheHPXProject/hpx/pull/4608>

²⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/4607>

²⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4606>

²⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4604>

²⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4603>

²⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4602>

²⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4598>

²⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4597>

²⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4596>

²⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/4595>

²⁶⁷² <https://github.com/TheHPXProject/hpx/pull/4592>

²⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/4591>

²⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4590>

²⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4587>

²⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4586>

²⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4585>

²⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4584>

- PR #4583²⁶⁷⁹ - Fixing bad static_cast
- PR #4582²⁶⁸⁰ - Changing download url for Windows prerequisites to circumvent bandwidth limitations
- PR #4581²⁶⁸¹ - Adding missing using placeholder::_X
- PR #4579²⁶⁸² - Move get_stack_size_name and related functions
- PR #4575²⁶⁸³ - Excluding unconditional definition of class backtrace from global header
- PR #4574²⁶⁸⁴ - Changing return type of hardware_concurrency() to unsigned int
- PR #4570²⁶⁸⁵ - Move tests to modules
- PR #4564²⁶⁸⁶ - Reshuffle internal targets and add HPX::hpx_no_wrap_main target
- PR #4563²⁶⁸⁷ - fix CMake option typo
- PR #4562²⁶⁸⁸ - Unregister lock earlier to avoid holding it while suspending
- PR #4561²⁶⁸⁹ - Adding test macros supporting custom output stream
- PR #4560²⁶⁹⁰ - Making sure hash_any::operator() is linked into core library
- PR #4559²⁶⁹¹ - Fixing compilation if HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION=On
- PR #4557²⁶⁹² - Improve spinlock implementation to perform better in high-contention situations
- PR #4553²⁶⁹³ - Fix a runtime_ptr problem at shutdown when apex is enabled
- PR #4552²⁶⁹⁴ - Add configuration option for making exceptions less noisy
- PR #4551²⁶⁹⁵ - Clean up thread creation parameters
- PR #4549²⁶⁹⁶ - Test FetchContent build on GitHub actions
- PR #4548²⁶⁹⁷ - Fix stack size
- PR #4545²⁶⁹⁸ - Fix header tests
- PR #4544²⁶⁹⁹ - Fix a typo in sanitizer build
- PR #4541²⁷⁰⁰ - Add API to check if a thread pool exists
- PR #4540²⁷⁰¹ - Making sure MPI support is enabled if MPI futures are used but networking is disabled

²⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4583>

²⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4582>

²⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/4581>

²⁶⁸² <https://github.com/TheHPXProject/hpx/pull/4579>

²⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/4575>

²⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4574>

²⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4570>

²⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4564>

²⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4563>

²⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4562>

²⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4561>

²⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4560>

²⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/4559>

²⁶⁹² <https://github.com/TheHPXProject/hpx/pull/4557>

²⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/4553>

²⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4552>

²⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4551>

²⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4549>

²⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4548>

²⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4545>

²⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4544>

²⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4541>

²⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/4540>

- PR #4538²⁷⁰² - Move channel documentation examples to examples directory
- PR #4536²⁷⁰³ - Add generic allocator for execution policies
- PR #4534²⁷⁰⁴ - Enable compatibility headers for thread_executors module
- PR #4532²⁷⁰⁵ - Fixing broken url in README.rst
- PR #4531²⁷⁰⁶ - Update scripts
- PR #4530²⁷⁰⁷ - Make sure module API docs show up in correct order
- PR #4529²⁷⁰⁸ - Adding missing template code to module creation script
- PR #4528²⁷⁰⁹ - Make sure version module uses HPX's binary dir, not the parent's
- PR #4527²⁷¹⁰ - Creating actions_base and actions module
- PR #4526²⁷¹¹ - Shared state for cv
- PR #4525²⁷¹² - Changing sub-name sequencing for experimental namespace
- PR #4524²⁷¹³ - Add API guarantee notes to API reference documentation
- PR #4522²⁷¹⁴ - Enable and fix deprecation warnings in execution module
- PR #4521²⁷¹⁵ - Moves more miscellaneous files to modules
- PR #4520²⁷¹⁶ - Skip execution customization points when executor is known
- PR #4518²⁷¹⁷ - Module distributed lcos
- PR #4516²⁷¹⁸ - Fix various builds
- PR #4515²⁷¹⁹ - Replace backslashes by slashes in windows paths
- PR #4514²⁷²⁰ - Adding polymorphic_executor
- PR #4512²⁷²¹ - Adding C++20 jthread and stop_token
- PR #4510²⁷²² - Attempt to fix APEX linking in external packages again
- PR #4508²⁷²³ - Only test pull requests (not all branches) with GitHub actions
- PR #4505²⁷²⁴ - Fix duplicate linking in tests (ODR violations)

²⁷⁰² <https://github.com/TheHPXProject/hpx/pull/4538>

²⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/4536>

²⁷⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4534>

²⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4532>

²⁷⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4531>

²⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4530>

²⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4529>

²⁷⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4528>

²⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/4527>

²⁷¹¹ <https://github.com/TheHPXProject/hpx/pull/4526>

²⁷¹² <https://github.com/TheHPXProject/hpx/pull/4525>

²⁷¹³ <https://github.com/TheHPXProject/hpx/pull/4524>

²⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/4522>

²⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/4521>

²⁷¹⁶ <https://github.com/TheHPXProject/hpx/pull/4520>

²⁷¹⁷ <https://github.com/TheHPXProject/hpx/pull/4518>

²⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/4516>

²⁷¹⁹ <https://github.com/TheHPXProject/hpx/pull/4515>

²⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/4514>

²⁷²¹ <https://github.com/TheHPXProject/hpx/pull/4512>

²⁷²² <https://github.com/TheHPXProject/hpx/pull/4510>

²⁷²³ <https://github.com/TheHPXProject/hpx/pull/4508>

²⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/4505>

- PR #4504²⁷²⁵ - Fix C++ standard handling
- PR #4503²⁷²⁶ - Add CMakeLists file check
- PR #4500²⁷²⁷ - Fix .clang-format version requirement comment
- PR #4499²⁷²⁸ - Attempting to fix hpx_init linking on macOS
- PR #4498²⁷²⁹ - Fix compatibility of *pool_executor*
- PR #4496²⁷³⁰ - Removing superfluous SPDX tags
- PR #4494²⁷³¹ - Module executors
- PR #4493²⁷³² - Pack traversal module
- PR #4492²⁷³³ - Update copyright year in documentation
- PR #4491²⁷³⁴ - Add missing current_executor header
- PR #4490²⁷³⁵ - Update GitHub actions configs
- PR #4487²⁷³⁶ - Properly dispatch exceptions thrown from hpx_main to be rethrown from hpx::init/hpx::stop
- PR #4486²⁷³⁷ - Fixing an initialization order problem
- PR #4485²⁷³⁸ - Move miscellaneous files to their rightful modules
- PR #4483²⁷³⁹ - Clean up imported CMake target naming
- PR #4481²⁷⁴⁰ - Add vcpkg installation instructions
- PR #4479²⁷⁴¹ - Add hints to allow to specify MIMALLOC_ROOT
- PR #4478²⁷⁴² - Async modules
- PR #4475²⁷⁴³ - Fix rp init changes
- PR #4474²⁷⁴⁴ - Use #pragma once in headers
- PR #4472²⁷⁴⁵ - Add more descriptive error message when using x86 coroutines on non-x86 platforms
- PR #4467²⁷⁴⁶ - Add mimalloc find cmake script
- PR #4465²⁷⁴⁷ - Add thread_executors module

²⁷²⁵ <https://github.com/TheHPXProject/hpx/pull/4504>

²⁷²⁶ <https://github.com/TheHPXProject/hpx/pull/4503>

²⁷²⁷ <https://github.com/TheHPXProject/hpx/pull/4500>

²⁷²⁸ <https://github.com/TheHPXProject/hpx/pull/4499>

²⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/4498>

²⁷³⁰ <https://github.com/TheHPXProject/hpx/pull/4496>

²⁷³¹ <https://github.com/TheHPXProject/hpx/pull/4494>

²⁷³² <https://github.com/TheHPXProject/hpx/pull/4493>

²⁷³³ <https://github.com/TheHPXProject/hpx/pull/4492>

²⁷³⁴ <https://github.com/TheHPXProject/hpx/pull/4491>

²⁷³⁵ <https://github.com/TheHPXProject/hpx/pull/4490>

²⁷³⁶ <https://github.com/TheHPXProject/hpx/pull/4487>

²⁷³⁷ <https://github.com/TheHPXProject/hpx/pull/4486>

²⁷³⁸ <https://github.com/TheHPXProject/hpx/pull/4485>

²⁷³⁹ <https://github.com/TheHPXProject/hpx/pull/4483>

²⁷⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4481>

²⁷⁴¹ <https://github.com/TheHPXProject/hpx/pull/4479>

²⁷⁴² <https://github.com/TheHPXProject/hpx/pull/4478>

²⁷⁴³ <https://github.com/TheHPXProject/hpx/pull/4475>

²⁷⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4474>

²⁷⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4472>

²⁷⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4467>

²⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4465>

- PR #4464²⁷⁴⁸ - Include module
- PR #4462²⁷⁴⁹ - Merge hpx_init and hpx_wrap into one static library
- PR #4461²⁷⁵⁰ - Making thread_data test more realistic
- PR #4460²⁷⁵¹ - Suppress MPI warnings in version.cpp
- PR #4459²⁷⁵² - Make sure pkgconfig applications link with hpx_init
- PR #4458²⁷⁵³ - Added example demonstrating how to create and use a wrapping executor
- PR #4457²⁷⁵⁴ - Fixing execution of thread exit functions
- PR #4456²⁷⁵⁵ - Move backtrace files to debugging module
- PR #4455²⁷⁵⁶ - Move deadlock_detection and maintain_queue_wait_times source files into schedulers module
- PR #4450²⁷⁵⁷ - Fixing compilation with std::filesystem enabled
- PR #4449²⁷⁵⁸ - Fixing build system to actually build variant test
- PR #4447²⁷⁵⁹ - This fixes an obsolete #include
- PR #4446²⁷⁶⁰ - Resume tasks where they were suspended
- PR #4444²⁷⁶¹ - Minor CUDA fixes
- PR #4443²⁷⁶² - Add missing tests to CircleCI config
- PR #4442²⁷⁶³ - Adding a tag to all auto-generated files allowing for tools to visually distinguish those
- PR #4441²⁷⁶⁴ - Adding performance counter type information
- PR #4440²⁷⁶⁵ - Fixing MSVC build
- PR #4439²⁷⁶⁶ - Link HPX::plugin and component privately in hpx_setup_target
- PR #4437²⁷⁶⁷ - Adding a test that verifies the problem can be solved using a trait specialization
- PR #4434²⁷⁶⁸ - Clean up Boost dependencies and copy string algorithms to new module
- PR #4433²⁷⁶⁹ - Fixing compilation issues (!) if MPI parcelport is enabled
- PR #4431²⁷⁷⁰ - Ignore warnings about name mangling changing

²⁷⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4464>

²⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4462>

²⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4461>

²⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/4460>

²⁷⁵² <https://github.com/TheHPXProject/hpx/pull/4459>

²⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/4458>

²⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4457>

²⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4456>

²⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4455>

²⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4450>

²⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4449>

²⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4447>

²⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4446>

²⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/4444>

²⁷⁶² <https://github.com/TheHPXProject/hpx/pull/4443>

²⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/4442>

²⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4441>

²⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4440>

²⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4439>

²⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4437>

²⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4434>

²⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4433>

²⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4431>

- PR #4430²⁷⁷¹ - Add performance_counters module
- PR #4428²⁷⁷² - Don't add compatibility headers to module API reference
- PR #4426²⁷⁷³ - Add currently failing tests on GitHub actions to blacklist
- PR #4425²⁷⁷⁴ - Clean up and correct minimum required versions
- PR #4424²⁷⁷⁵ - Making sure hpx.lock_detection=0 works as advertized
- PR #4421²⁷⁷⁶ - Making sure interval time stops underlying timer thread on termination
- PR #4417²⁷⁷⁷ - Adding serialization support for std::variant (if available) and std::tuple
- PR #4415²⁷⁷⁸ - Partially reverting changes applied by PR 4373
- PR #4414²⁷⁷⁹ - Added documentation for the compiler-wrapper script hpxcxx.in in creating_hpx_projects.rst
- PR #4413²⁷⁸⁰ - Merging from V1.4.1 release
- PR #4412²⁷⁸¹ - Making sure to issue a warning if a file specified using -hpx:options-file is not found
- PR #4411²⁷⁸² - Make test specific to HPX_WITH_SHARED_PRIORITY_SCHEDULER
- PR #4407²⁷⁸³ - Adding minimal MPI executor
- PR #4405²⁷⁸⁴ - Fix cross pool injection test, use default scheduler as fallback
- PR #4404²⁷⁸⁵ - Fix a race condition and clean-up usage of scheduler mode
- PR #4399²⁷⁸⁶ - Add more threading modules
- PR #4398²⁷⁸⁷ - Add CODEOWNERS file
- PR #4395²⁷⁸⁸ - Adding a parameter to auto_chunk_size allowing to control the amount of iterations to measure
- PR #4393²⁷⁸⁹ - Use appropriate cache-line size defaults for different platforms
- PR #4391²⁷⁹⁰ - Fixing use of allocator for C++20
- PR #4390²⁷⁹¹ - Making -hpx:help behavior consistent
- PR #4388²⁷⁹² - Change the resource partitioner initialization
- PR #4387²⁷⁹³ - Fix roll_release.sh

²⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/4430>

²⁷⁷² <https://github.com/TheHPXProject/hpx/pull/4428>

²⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/4426>

²⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4425>

²⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4424>

²⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4421>

²⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4417>

²⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4415>

²⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4414>

²⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4413>

²⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/4412>

²⁷⁸² <https://github.com/TheHPXProject/hpx/pull/4411>

²⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/4407>

²⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4405>

²⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4404>

²⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4399>

²⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4398>

²⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4395>

²⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4393>

²⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4391>

²⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/4390>

²⁷⁹² <https://github.com/TheHPXProject/hpx/pull/4388>

²⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/4387>

- [PR #4386](#)²⁷⁹⁴ - Add warning messages for using thread binding options on macOS
- [PR #4385](#)²⁷⁹⁵ - Cuda futures
- [PR #4384](#)²⁷⁹⁶ - Make enabling dynamic `hpx_main` on non-Linux systems a configuration error
- [PR #4383](#)²⁷⁹⁷ - Use `configure_file` for `HPXCacheVariables.cmake`
- [PR #4382](#)²⁷⁹⁸ - Update spellchecking whitelist and fix more typos
- [PR #4380](#)²⁷⁹⁹ - Add a helper function to get a future from a cuda stream
- [PR #4379](#)²⁸⁰⁰ - Add Windows and macOS CI with GitHub actions
- [PR #4378](#)²⁸⁰¹ - Change C++ standard handling
- [PR #4377](#)²⁸⁰² - Remove Python scripts
- [PR #4374](#)²⁸⁰³ - Adding overload for `hpx::init/hpx::start` for use with resource partitioner
- [PR #4373](#)²⁸⁰⁴ - Adding test that verifies for 4369 to be fixed
- [PR #4372](#)²⁸⁰⁵ - Another attempt at fixing the integral mismatch and conversion warnings
- [PR #4370](#)²⁸⁰⁶ - Doc updates quick start
- [PR #4368](#)²⁸⁰⁷ - Add a whitelist of words for weird spelling suggestions
- [PR #4366](#)²⁸⁰⁸ - Suppress or fix clang-tidy-9 warnings
- [PR #4365](#)²⁸⁰⁹ - Removing more Boost dependencies
- [PR #4363](#)²⁸¹⁰ - Update clang-format config file for version 9
- [PR #4362](#)²⁸¹¹ - Fix indices typo
- [PR #4361](#)²⁸¹² - Boost cleanup
- [PR #4360](#)²⁸¹³ - Move plugins
- [PR #4358](#)²⁸¹⁴ - Doc updates; generating documentation. Will likely need heavy editing.
- [PR #4356](#)²⁸¹⁵ - Remove some minor unused and unnecessary Boost includes
- [PR #4355](#)²⁸¹⁶ - Fix spellcheck step in CircleCI config

²⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4386>

²⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4385>

²⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4384>

²⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4383>

²⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4382>

²⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4380>

²⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4379>

²⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/4378>

²⁸⁰² <https://github.com/TheHPXProject/hpx/pull/4377>

²⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/4374>

²⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4373>

²⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4372>

²⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4370>

²⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4368>

²⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4366>

²⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4365>

²⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/4363>

²⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/4362>

²⁸¹² <https://github.com/TheHPXProject/hpx/pull/4361>

²⁸¹³ <https://github.com/TheHPXProject/hpx/pull/4360>

²⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/4358>

²⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/4356>

²⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/4355>

- PR #4354²⁸¹⁷ - Lightweight utility to hold a pack as members
- PR #4352²⁸¹⁸ - Minor fixes to the C++ standard detection for MSVC
- PR #4351²⁸¹⁹ - Move generated documentation to hpx-docs repo
- PR #4347²⁸²⁰ - Add cmake policy - CMP0074
- PR #4346²⁸²¹ - Remove file committed by mistake
- PR #4342²⁸²² - Remove HCC and SYCL options from CMakeLists.txt
- PR #4341²⁸²³ - Fix launch process test with APEX enabled
- PR #4340²⁸²⁴ - Testing Cirrus CI
- PR #4339²⁸²⁵ - Post 1.4.0 updates
- PR #4338²⁸²⁶ - Spelling corrections and CircleCI spell check
- PR #4333²⁸²⁷ - Flatten bound callables
- PR #4332²⁸²⁸ - This is a collection of mostly minor (cleanup) fixes
- PR #4331²⁸²⁹ - This adds the missing tests for `async_colocated` and `async_continue_colocated`
- PR #4330²⁸³⁰ - Remove `HPX.Compute` host default_executor
- PR #4328²⁸³¹ - Generate global header for `basic_execution` module
- PR #4327²⁸³² - Use `INTERNAL_FLAGS` option for all examples and components
- PR #4326²⁸³³ - Usage of temporary allocator in assignment operator of `compute::vector`
- PR #4325²⁸³⁴ - Use `hpx::threads::get_cache_line_size` in `prefetching.hpp`
- PR #4324²⁸³⁵ - Enable compatibility headers option for execution module
- PR #4316²⁸³⁶ - Add clang format indentppdirectives
- PR #4313²⁸³⁷ - Introduce `index_pack` alias to pack of `size_t`
- PR #4312²⁸³⁸ - Fixing compatibility header for `pack.hpp`
- PR #4311²⁸³⁹ - Dataflow annotations for APEX

²⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/4354>

²⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/4352>

²⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/4351>

²⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/4347>

²⁸²¹ <https://github.com/TheHPXProject/hpx/pull/4346>

²⁸²² <https://github.com/TheHPXProject/hpx/pull/4342>

²⁸²³ <https://github.com/TheHPXProject/hpx/pull/4341>

²⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/4340>

²⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/4339>

²⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/4338>

²⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/4333>

²⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/4332>

²⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/4331>

²⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/4330>

²⁸³¹ <https://github.com/TheHPXProject/hpx/pull/4328>

²⁸³² <https://github.com/TheHPXProject/hpx/pull/4327>

²⁸³³ <https://github.com/TheHPXProject/hpx/pull/4326>

²⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/4325>

²⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/4324>

²⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/4316>

²⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/4313>

²⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/4312>

²⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/4311>

- PR #4309²⁸⁴⁰ - Update launching_and_configuring_hpx_applications.rst
- PR #4306²⁸⁴¹ - Fix schedule hint not being taken from executor
- PR #4305²⁸⁴² - Implementing *hpx::functional::tag_invoke*
- PR #4304²⁸⁴³ - Improve pack support utilities
- PR #4303²⁸⁴⁴ - Remove errors module dependency on datastructures
- PR #4301²⁸⁴⁵ - Clean up thread executors
- PR #4294²⁸⁴⁶ - Logging revamp
- PR #4292²⁸⁴⁷ - Remove SPDX tag from Boost License file to allow for github to recognize it
- PR #4291²⁸⁴⁸ - Add format support for std::tm
- PR #4290²⁸⁴⁹ - Simplify compatible tuples check
- PR #4288²⁸⁵⁰ - A lightweight take on boost::lexical_cast
- PR #4287²⁸⁵¹ - Forking boost::lexical_cast as a new module
- PR #4277²⁸⁵² - MPI_futures
- PR #4270²⁸⁵³ - Refactor future implementation
- PR #4265²⁸⁵⁴ - Threading module
- PR #4259²⁸⁵⁵ - Module naming base
- PR #4251²⁸⁵⁶ - Local workrequesting scheduler
- PR #4250²⁸⁵⁷ - Inline execution of scoped tasks, if possible
- PR #4247²⁸⁵⁸ - Add execution in module headers
- PR #4246²⁸⁵⁹ - Expose CMake targets officially
- PR #4239²⁸⁶⁰ - Doc updates miscellaneous (partially completed during Google Season of Docs)
- PR #4233²⁸⁶¹ - Remove project() from modules + fix CMAKE_SOURCE_DIR issue
- PR #4231²⁸⁶² - Module local lcos

²⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4309>

²⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/4306>

²⁸⁴² <https://github.com/TheHPXProject/hpx/pull/4305>

²⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/4304>

²⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4303>

²⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4301>

²⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4294>

²⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4292>

²⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4291>

²⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4290>

²⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4288>

²⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/4287>

²⁸⁵² <https://github.com/TheHPXProject/hpx/pull/4277>

²⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/4270>

²⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4265>

²⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4259>

²⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4251>

²⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4250>

²⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4247>

²⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4246>

²⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4239>

²⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/4233>

²⁸⁶² <https://github.com/TheHPXProject/hpx/pull/4231>

- PR #4207²⁸⁶³ - Command line handling module
- PR #4206²⁸⁶⁴ - Runtime configuration module
- PR #4141²⁸⁶⁵ - Doc updates examples local to remote (partially completed during Google Season of Docs)
- PR #4091²⁸⁶⁶ - Split runtime into local and distributed parts
- PR #4017²⁸⁶⁷ - Require C++14

HPX V1.4.1 (Feb 12, 2020)

General changes

This is a bugfix release. It contains the following changes:

- Fix compilation issues on Windows, macOS, FreeBSD, and with gcc 10
- Install missing pdb files on Windows
- Allow running tests using an installed version of *HPX*
- Skip MPI finalization if HPX has not initialized MPI
- Give a hard error when attempting to use IO counters on Windows

Closed issues

- Issue #4320²⁸⁶⁸ - HPX 1.4.0 does not compile with gcc 10
- Issue #4336²⁸⁶⁹ - Building HPX 1.4.0 with IO Counters breaks (Windows)
- Issue #4334²⁸⁷⁰ - HPX Debug and RelWithDebinfo builds on Windows not installing .pdb files
- Issue #4322²⁸⁷¹ - Undefine VT1 and VT2 after boost includes
- Issue #4314²⁸⁷² - Compile error on 1.4.0
- Issue #4307²⁸⁷³ - ld: error: duplicate symbol: freebsd_envIRON

²⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/4207>
²⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4206>
²⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4141>
²⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4091>
²⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4017>
²⁸⁶⁸ <https://github.com/TheHPXProject/hpx/issues/4320>
²⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/4336>
²⁸⁷⁰ <https://github.com/TheHPXProject/hpx/issues/4334>
²⁸⁷¹ <https://github.com/TheHPXProject/hpx/issues/4322>
²⁸⁷² <https://github.com/TheHPXProject/hpx/issues/4314>
²⁸⁷³ <https://github.com/TheHPXProject/hpx/issues/4307>

Closed pull requests

- [PR #4376²⁸⁷⁴](#) - Attempt to fix some test build errors on Windows
- [PR #4357²⁸⁷⁵](#) - Adding missing `#includes` to fix gcc V10 linker problems
- [PR #4353²⁸⁷⁶](#) - Skip `MPI_Finalize` if `MPI_Init` is not called from HPX
- [PR #4343²⁸⁷⁷](#) - Give a hard error if IO counters are enabled on non-Linux systems
- [PR #4337²⁸⁷⁸](#) - Installing `pdb` files on Windows
- [PR #4335²⁸⁷⁹](#) - Adding capability to `buildsystem` to use an installed version of HPX
- [PR #4315²⁸⁸⁰](#) - Forcing exported symbols from `composable_guard` to be linked into core library
- [PR #4310²⁸⁸¹](#) - Remove environment handling from `exception.cpp`

HPX V1.4.0 (January 15, 2020)

General changes

- We have added the collectives `all_to_all` and `all_reduce`.
- We have added APIs for resiliency, which allows replication and replay for failed tasks. See the *documentation* for more details.
- Components can now be checkpointed.
- Performance improvements to schedulers and coroutines. A significant change is the addition of stackless coroutines. These are to be used for tasks that do not need to be suspended and can reduce overheads noticeably in applications with short tasks. A stackless coroutine can be created with the new `stack_size_thread_stacksize_nostack`.
- We have added an implementation of `unique_any`, which is a non-copyable version of `any`.
- The `shared_priority_queue_scheduler` has been improved. It now has lower overheads than the default scheduler in many situations. Unlike the default scheduler it fully supports NUMA scheduling hints. Enable it with the command line option `--hpx:queuing=shared-priority`. This scheduler should still be considered experimental, but its use is encouraged in real applications to help us make it production ready.
- We have added the performance counters `background-receive-duration` and `background-receive-overhead` for inspecting the time and overhead spent on receiving parcels in the background.
- Compilation time has been further improved when `HPX_WITH_NETWORKING=OFF`.
- We no longer require compiled Boost dependencies in certain configurations. This requires at least Boost 1.70, compiling on x86 with GCC 9, clang (libc++) 9, or VS2019 in C++17 mode. The dependency on `Boost.Filesystem` can explicitly be turned on with `HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY=ON` (it is off by default if the standard library supports `std::filesystem`). `Boost.ProgramOptions` has been copied into the HPX repository. We have a compatibility layer for users who must explicitly use

²⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4376>

²⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4357>

²⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4353>

²⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4343>

²⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4337>

²⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4335>

²⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4315>

²⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/4310>

Boost.ProgramOptions instead of the ProgramOptions provided by HPX. To remove the dependency HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY must be explicitly set to OFF. This option will be removed in a future release. We have also removed several other header-only dependencies on Boost.

- It is now possible to use the process affinity mask set by tools like `numactl` and various batch environments with the command line option `--hpx:use-process-mask`. Enabling this option implies `--hpx:ignore-batch-env`.
- It is now possible to create standalone thread pools without starting the runtime. See the `standalone_thread_pool_executor.cpp` test in the `execution` module for an example.
- Tasks annotated with `hpx::util::annotated_function` now have their correct name when using APEX to generate OTF2 files.
- Cloning of APEX was defective in previous releases (it required manual intervention to check out the correct tag or branch). This has been fixed.
- The option `HPX_WITH_MORE_THAN_64_THREADS` is now ignored and will be removed in a future release. The value is instead derived directly from `HPX_WITH_MAX_CPU_COUNT` option.
- We have deprecated compiling in C++11 mode. The next release will require a C++14 capable compiler.
- We have deprecated support for the Vc library. This option will be replaced with SIMD support from the standard library in a future release.
- We have significantly refactored our CMake setup. This is intended to be a non-breaking change and will allow for using HPX through CMake targets in the future.
- We have continued modularizing the HPX library. In the process we have rearranged many header files into module-specific directories. All moved headers have compatibility headers which forward from the old location to the new location, together with a deprecation warning. The compatibility headers will eventually be removed.
- We now enforce formatting with `clang-format` on the majority of our source files.
- We have added SPDX license tags to all files.
- Many bugfixes.

Breaking changes

- The `HPX_WITH_THREAD_COMPATIBILITY` option and the associated compatibility layer has been removed.
- The `HPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY` option and the associated compatibility layer has been removed.
- The `HPX_WITH_UNWRAPPED_COMPATIBILITY` option and the associated compatibility layer has been removed.

Closed issues

- [Issue #4282²⁸⁸²](https://github.com/TheHPXProject/hpx/issues/4282) - Build Issues with Release on Windows
- [Issue #4278²⁸⁸³](https://github.com/TheHPXProject/hpx/issues/4278) - Build Issues with CMake 3.14.4
- [Issue #4273²⁸⁸⁴](https://github.com/TheHPXProject/hpx/issues/4273) - Clients of HPX 1.4.0-rc2 with APEX are not linked to libhpx-apex
- [Issue #4269²⁸⁸⁵](https://github.com/TheHPXProject/hpx/issues/4269) - Building HPX 1.4.0-rc2 with support for APEX fails

²⁸⁸² <https://github.com/TheHPXProject/hpx/issues/4282>

²⁸⁸³ <https://github.com/TheHPXProject/hpx/issues/4278>

²⁸⁸⁴ <https://github.com/TheHPXProject/hpx/issues/4273>

²⁸⁸⁵ <https://github.com/TheHPXProject/hpx/issues/4269>

- [Issue #4263](#)²⁸⁸⁶ - Compilation fail on latest master
- [Issue #4232](#)²⁸⁸⁷ - Configure of HPX project using CMake FetchContent fails
- [Issue #4223](#)²⁸⁸⁸ - “Re-using the main() function as the main HPX entry point” doesn’t work
- [Issue #4220](#)²⁸⁸⁹ - HPX won’t compile - error building resource_partitioner
- [Issue #4215](#)²⁸⁹⁰ - HPX 1.4.0rc1 does not link on s390x
- [Issue #4204](#)²⁸⁹¹ - Trouble compiling HPX with Intel compiler
- [Issue #4199](#)²⁸⁹² - Refactor APEX to eliminate circular dependency
- [Issue #4187](#)²⁸⁹³ - HPX can’t build on OSX
- [Issue #4185](#)²⁸⁹⁴ - Simple debug output for development
- [Issue #4182](#)²⁸⁹⁵ - @HPX_CONF_PREFIX@ is the empty string
- [Issue #4169](#)²⁸⁹⁶ - HPX won’t build with APEX
- [Issue #4163](#)²⁸⁹⁷ - Add back HPX_LIBRARIES and HPX_INCLUDE_DIRS
- [Issue #4161](#)²⁸⁹⁸ - It should be possible to call find_package(HPX) multiple times
- [Issue #4155](#)²⁸⁹⁹ - get_self_id() for stackless threads returns invalid_thread_id
- [Issue #4151](#)²⁹⁰⁰ - build error with MPI code
- [Issue #4150](#)²⁹⁰¹ - hpx won’t build on POWER9 with clang 8
- [Issue #4148](#)²⁹⁰² - cacheline_data delivers poor performance with C++17 compared to C++14
- [Issue #4144](#)²⁹⁰³ - target general in HPX_LIBRARIES does not exist
- [Issue #4134](#)²⁹⁰⁴ - CMake Error when -DHPX_WITH_HPXM=ON
- [Issue #4132](#)²⁹⁰⁵ - parallel fill leaves elements unfilled
- [Issue #4123](#)²⁹⁰⁶ - PAPI performance counters are inaccessible
- [Issue #4118](#)²⁹⁰⁷ - static_chunk_size is not obeyed in scan algorithms
- [Issue #4115](#)²⁹⁰⁸ - dependency chaining error with APEX

²⁸⁸⁶ <https://github.com/TheHPXProject/hpx/issues/4263>

²⁸⁸⁷ <https://github.com/TheHPXProject/hpx/issues/4232>

²⁸⁸⁸ <https://github.com/TheHPXProject/hpx/issues/4223>

²⁸⁸⁹ <https://github.com/TheHPXProject/hpx/issues/4220>

²⁸⁹⁰ <https://github.com/TheHPXProject/hpx/issues/4215>

²⁸⁹¹ <https://github.com/TheHPXProject/hpx/issues/4204>

²⁸⁹² <https://github.com/TheHPXProject/hpx/issues/4199>

²⁸⁹³ <https://github.com/TheHPXProject/hpx/issues/4187>

²⁸⁹⁴ <https://github.com/TheHPXProject/hpx/issues/4185>

²⁸⁹⁵ <https://github.com/TheHPXProject/hpx/issues/4182>

²⁸⁹⁶ <https://github.com/TheHPXProject/hpx/issues/4169>

²⁸⁹⁷ <https://github.com/TheHPXProject/hpx/issues/4163>

²⁸⁹⁸ <https://github.com/TheHPXProject/hpx/issues/4161>

²⁸⁹⁹ <https://github.com/TheHPXProject/hpx/issues/4155>

²⁹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/4151>

²⁹⁰¹ <https://github.com/TheHPXProject/hpx/issues/4150>

²⁹⁰² <https://github.com/TheHPXProject/hpx/issues/4148>

²⁹⁰³ <https://github.com/TheHPXProject/hpx/issues/4144>

²⁹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/4134>

²⁹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/4132>

²⁹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/4123>

²⁹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/4118>

²⁹⁰⁸ <https://github.com/TheHPXProject/hpx/issues/4115>

- [Issue #4107](#)²⁹⁰⁹ - Initializing runtime without entry point function and command line arguments
- [Issue #4105](#)²⁹¹⁰ - Bug in `hpx:bind=numa-balanced`
- [Issue #4101](#)²⁹¹¹ - Bound tasks
- [Issue #4100](#)²⁹¹² - Add SPDX identifier to all files
- [Issue #4085](#)²⁹¹³ - `hpx_topology` library should depend on `hwloc`
- [Issue #4067](#)²⁹¹⁴ - HPX fails to build on macOS
- [Issue #4056](#)²⁹¹⁵ - Building without thread manager idle backoff fails
- [Issue #4052](#)²⁹¹⁶ - Enforce `clang-format` style for modules
- [Issue #4032](#)²⁹¹⁷ - Simple hello world fails to launch correctly
- [Issue #4030](#)²⁹¹⁸ - Allow threads to skip context switching
- [Issue #4029](#)²⁹¹⁹ - Add support for `mimalloc`
- [Issue #4005](#)²⁹²⁰ - Can't link HPX when APEX enabled
- [Issue #4002](#)²⁹²¹ - Missing header for algorithm module
- [Issue #3989](#)²⁹²² - conversion from `long` to `unsigned int` requires a narrowing conversion on MSVC
- [Issue #3958](#)²⁹²³ - `/statistics/average@` perf counter can't be created
- [Issue #3953](#)²⁹²⁴ - CMake errors from `HPX_AddPseudoDependencies`
- [Issue #3941](#)²⁹²⁵ - CMake error for APEX install target
- [Issue #3940](#)²⁹²⁶ - Convert pseudo-doxygen function documentation into actual doxygen documentation
- [Issue #3935](#)²⁹²⁷ - HPX compiler match too strict?
- [Issue #3929](#)²⁹²⁸ - Buildbot failures on latest HPX stable
- [Issue #3912](#)²⁹²⁹ - I recommend publishing a version that does not depend on the boost library
- [Issue #3890](#)²⁹³⁰ - `hpx.ini` not working
- [Issue #3883](#)²⁹³¹ - cuda compilation fails because of `-faligned-new`

²⁹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/4107>

²⁹¹⁰ <https://github.com/TheHPXProject/hpx/issues/4105>

²⁹¹¹ <https://github.com/TheHPXProject/hpx/issues/4101>

²⁹¹² <https://github.com/TheHPXProject/hpx/issues/4100>

²⁹¹³ <https://github.com/TheHPXProject/hpx/issues/4085>

²⁹¹⁴ <https://github.com/TheHPXProject/hpx/issues/4067>

²⁹¹⁵ <https://github.com/TheHPXProject/hpx/issues/4056>

²⁹¹⁶ <https://github.com/TheHPXProject/hpx/issues/4052>

²⁹¹⁷ <https://github.com/TheHPXProject/hpx/issues/4032>

²⁹¹⁸ <https://github.com/TheHPXProject/hpx/issues/4030>

²⁹¹⁹ <https://github.com/TheHPXProject/hpx/issues/4029>

²⁹²⁰ <https://github.com/TheHPXProject/hpx/issues/4005>

²⁹²¹ <https://github.com/TheHPXProject/hpx/issues/4002>

²⁹²² <https://github.com/TheHPXProject/hpx/issues/3989>

²⁹²³ <https://github.com/TheHPXProject/hpx/issues/3958>

²⁹²⁴ <https://github.com/TheHPXProject/hpx/issues/3953>

²⁹²⁵ <https://github.com/TheHPXProject/hpx/issues/3941>

²⁹²⁶ <https://github.com/TheHPXProject/hpx/issues/3940>

²⁹²⁷ <https://github.com/TheHPXProject/hpx/issues/3935>

²⁹²⁸ <https://github.com/TheHPXProject/hpx/issues/3929>

²⁹²⁹ <https://github.com/TheHPXProject/hpx/issues/3912>

²⁹³⁰ <https://github.com/TheHPXProject/hpx/issues/3890>

²⁹³¹ <https://github.com/TheHPXProject/hpx/issues/3883>

- Issue #3879²⁹³² - HPX fails to configure with `-DHPX_WITH_TESTS=OFF`
- Issue #3871²⁹³³ - `dataflow` does not support void allocators
- Issue #3867²⁹³⁴ - Latest HTML docs placed in wrong directory on GitHub pages
- Issue #3866²⁹³⁵ - Make sure all tests use `HPX_TEST*` macros and not `HPX_ASSERT`
- Issue #3857²⁹³⁶ - CMake all-keyword or all-plain for `target_link_libraries`
- Issue #3856²⁹³⁷ - `hpx_setup_target` adds rogue flags
- Issue #3850²⁹³⁸ - HPX fails to build on POWER8 with Clang7
- Issue #3848²⁹³⁹ - Remove `lva` member from `thread_init_data`
- Issue #3838²⁹⁴⁰ - `hpx::parallel::count/count_if` failing tests
- Issue #3651²⁹⁴¹ - `hpx::parallel::transform_reduce` with non const reference as lambda parameter
- Issue #3560²⁹⁴² - Apex integration with HPX not working properly
- Issue #3322²⁹⁴³ - No warning when mixing debug/release builds

Closed pull requests

- PR #4300²⁹⁴⁴ - Checks for `MPI_Init` being called twice
- PR #4299²⁹⁴⁵ - Small CMake fixes
- PR #4298²⁹⁴⁶ - Remove extra call to annotate function that messes up traces
- PR #4296²⁹⁴⁷ - Fixing collectives locking problem
- PR #4295²⁹⁴⁸ - Do not check `LICENSE_1_0.txt` for inspect violations
- PR #4293²⁹⁴⁹ - Applying two small changes fixing carious MSVC/Windows problems
- PR #4285²⁹⁵⁰ - Delete `apex.hpp`
- PR #4276²⁹⁵¹ - Disable doxygen generation for `hpx/debugging/print.hpp` file
- PR #4275²⁹⁵² - Make sure APEX is linked to even when not explicitly referenced
- PR #4272²⁹⁵³ - Fix pushing of documentation

²⁹³² <https://github.com/TheHPXProject/hpx/issues/3879>

²⁹³³ <https://github.com/TheHPXProject/hpx/issues/3871>

²⁹³⁴ <https://github.com/TheHPXProject/hpx/issues/3867>

²⁹³⁵ <https://github.com/TheHPXProject/hpx/issues/3866>

²⁹³⁶ <https://github.com/TheHPXProject/hpx/issues/3857>

²⁹³⁷ <https://github.com/TheHPXProject/hpx/issues/3856>

²⁹³⁸ <https://github.com/TheHPXProject/hpx/issues/3850>

²⁹³⁹ <https://github.com/TheHPXProject/hpx/issues/3848>

²⁹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/3838>

²⁹⁴¹ <https://github.com/TheHPXProject/hpx/issues/3651>

²⁹⁴² <https://github.com/TheHPXProject/hpx/issues/3560>

²⁹⁴³ <https://github.com/TheHPXProject/hpx/issues/3322>

²⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4300>

²⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4299>

²⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4298>

²⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4296>

²⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4295>

²⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4293>

²⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4285>

²⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/4276>

²⁹⁵² <https://github.com/TheHPXProject/hpx/pull/4275>

²⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/4272>

- PR #4271²⁹⁵⁴ - Updating APEX tag, don't create new task_wrapper on operator= of hpx_thread object
- PR #4268²⁹⁵⁵ - Testing for noexcept function specializations in C++11/14 mode
- PR #4267²⁹⁵⁶ - Fixing MSVC warning
- PR #4266²⁹⁵⁷ - Make sure macOS Travis CI fails if build step fails
- PR #4264²⁹⁵⁸ - Clean up compatibility header options
- PR #4262²⁹⁵⁹ - Cleanup modules CMakeLists.txt
- PR #4261²⁹⁶⁰ - Fixing HPX/APEX linking and dependencies for external projects like Phylanx
- PR #4260²⁹⁶¹ - Fix docs compilation problems
- PR #4258²⁹⁶² - Couple of minor changes
- PR #4257²⁹⁶³ - Fix apex annotation for async dispatch
- PR #4256²⁹⁶⁴ - Remove lambdas from assert expressions
- PR #4255²⁹⁶⁵ - Ignoring lock in all_to_all and all_reduce
- PR #4254²⁹⁶⁶ - Adding action specializations for noexcept functions
- PR #4253²⁹⁶⁷ - Move partlit.hpp to affinity module
- PR #4252²⁹⁶⁸ - Make mismatching build types a hard error in CMake
- PR #4249²⁹⁶⁹ - Scheduler improvement
- PR #4248²⁹⁷⁰ - update hpxmp tag to v0.3.0
- PR #4245²⁹⁷¹ - Adding high performance channels
- PR #4244²⁹⁷² - Ignore lock in ignore_while_locked_1485 test
- PR #4243²⁹⁷³ - Fix PAPI command line option documentation
- PR #4242²⁹⁷⁴ - Ignore lock in target_distribution_policy
- PR #4241²⁹⁷⁵ - Fix start_stop_callbacks test
- PR #4240²⁹⁷⁶ - Mostly fix clang CUDA compilation

²⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4271>

²⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4268>

²⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4267>

²⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4266>

²⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4264>

²⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4262>

²⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4261>

²⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/4260>

²⁹⁶² <https://github.com/TheHPXProject/hpx/pull/4258>

²⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/4257>

²⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4256>

²⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4255>

²⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4254>

²⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4253>

²⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4252>

²⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4249>

²⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4248>

²⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/4245>

²⁹⁷² <https://github.com/TheHPXProject/hpx/pull/4244>

²⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/4243>

²⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4242>

²⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4241>

²⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4240>

- [PR #4238²⁹⁷⁷](#) - Google Season of Docs updates to documentation; grammar edits.
- [PR #4237²⁹⁷⁸](#) - fixing annotated task to use the name, not the desc
- [PR #4236²⁹⁷⁹](#) - Move module print summary to modules
- [PR #4235²⁹⁸⁰](#) - Don't use alignas in `cache_{aligned,line}_data`
- [PR #4234²⁹⁸¹](#) - Add basic overview sentence to all modules
- [PR #4230²⁹⁸²](#) - Add OS X builds to Travis CI
- [PR #4229²⁹⁸³](#) - Remove leftover queue compatibility checks
- [PR #4226²⁹⁸⁴](#) - Fixing APEX shutdown by explicitly shutting down throttling
- [PR #4225²⁹⁸⁵](#) - Allow `CMAKE_INSTALL_PREFIX` to be a relative path
- [PR #4224²⁹⁸⁶](#) - Deprecate verbs parcelport
- [PR #4222²⁹⁸⁷](#) - Update `register_{thread,work}` namespaces
- [PR #4221²⁹⁸⁸](#) - Changing `HPX_GCC_VERSION` check from `70000` to `70300`
- [PR #4218²⁹⁸⁹](#) - Google Season of Docs updates to documentation; grammar edits.
- [PR #4217²⁹⁹⁰](#) - Google Season of Docs updates to documentation; grammar edits.
- [PR #4216²⁹⁹¹](#) - Fixing gcc warning on 32bit platforms (integer truncation)
- [PR #4214²⁹⁹²](#) - Apex callback refactoring
- [PR #4213²⁹⁹³](#) - Clean up allocator checks for dependent projects
- [PR #4212²⁹⁹⁴](#) - Google Season of Docs updates to documentation; grammar edits.
- [PR #4211²⁹⁹⁵](#) - Google Season of Docs updates to documentation; contributing to hpx
- [PR #4210²⁹⁹⁶](#) - Attempting to fix Intel compilation
- [PR #4209²⁹⁹⁷](#) - Fix CUDA 10 build
- [PR #4205²⁹⁹⁸](#) - Making sure that differences in `CMAKE_BUILD_TYPE` are not reported on multi-configuration cmake generators
- [PR #4203²⁹⁹⁹](#) - Deprecate Vc

²⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4238>

²⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4237>

²⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4236>

²⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4235>

²⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/4234>

²⁹⁸² <https://github.com/TheHPXProject/hpx/pull/4230>

²⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/4229>

²⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4226>

²⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4225>

²⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4224>

²⁹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4222>

²⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4221>

²⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4218>

²⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4217>

²⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/4216>

²⁹⁹² <https://github.com/TheHPXProject/hpx/pull/4214>

²⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/4213>

²⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4212>

²⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4211>

²⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4210>

²⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4209>

²⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4205>

²⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4203>

- PR #4202³⁰⁰⁰ - Fix CUDA configuration
- PR #4200³⁰⁰¹ - Making sure `hpx_wrap` is not passed on to linker on non-Linux systems
- PR #4198³⁰⁰² - Fix `execution_agent.cpp` compilation with GCC 5
- PR #4197³⁰⁰³ - Remove deprecated options for 1.4.0 release
- PR #4196³⁰⁰⁴ - minor fixes for building on OSX Darwin
- PR #4195³⁰⁰⁵ - Use full clone on CircleCI for pushing stable tag
- PR #4193³⁰⁰⁶ - Add scheduling hints to `hello_world_distributed`
- PR #4192³⁰⁰⁷ - Set up CUDA in `HPXConfig.cmake`
- PR #4191³⁰⁰⁸ - Export allocators root variables
- PR #4190³⁰⁰⁹ - Don't use `constexpr` in `thread_data` with GCC <= 6
- PR #4189³⁰¹⁰ - Only use `quick_exit` if available
- PR #4188³⁰¹¹ - Google Season of Docs updates to documentation; writing single node hpx applications
- PR #4186³⁰¹² - correct `vc` to `cuda` in `cuda` `cmake`
- PR #4184³⁰¹³ - Resetting some cached variables to make sure those are re-filled
- PR #4183³⁰¹⁴ - Fix `hpxcxx` configuration
- PR #4181³⁰¹⁵ - Rename base libraries var
- PR #4180³⁰¹⁶ - Move header left behind earlier to plugin module
- PR #4179³⁰¹⁷ - Moving `zip_iterator` and `transform_iterator` to `iterator_support` module
- PR #4178³⁰¹⁸ - Move checkpointing support to its own module
- PR #4177³⁰¹⁹ - Small `const` fix to `basic_execution` module
- PR #4176³⁰²⁰ - Add back `HPX_LIBRARIES` and friends to `HPXConfig.cmake`
- PR #4175³⁰²¹ - Make `Vc` public and add it to `HPXConfig.cmake`
- PR #4173³⁰²² - Wait for runtime to be running before returning from `hpx::start`

³⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4202>

³⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/4200>

³⁰⁰² <https://github.com/TheHPXProject/hpx/pull/4198>

³⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/4197>

³⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4196>

³⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4195>

³⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4193>

³⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4192>

³⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4191>

³⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4190>

³⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/4189>

³⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/4188>

³⁰¹² <https://github.com/TheHPXProject/hpx/pull/4186>

³⁰¹³ <https://github.com/TheHPXProject/hpx/pull/4184>

³⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/4183>

³⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/4181>

³⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/4180>

³⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/4179>

³⁰¹⁸ <https://github.com/TheHPXProject/hpx/pull/4178>

³⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/4177>

³⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/4176>

³⁰²¹ <https://github.com/TheHPXProject/hpx/pull/4175>

³⁰²² <https://github.com/TheHPXProject/hpx/pull/4173>

- PR #4172³⁰²³ - More protection against shutdown problems in error handling scenarios.
- PR #4171³⁰²⁴ - Ignore lock in `condition_variable::wait`
- PR #4170³⁰²⁵ - Adding APEX dependency to MPI parcellport
- PR #4168³⁰²⁶ - Adding utility include
- PR #4167³⁰²⁷ - Add a condition to setup the external libraries
- PR #4166³⁰²⁸ - Add an `INTERNAL_FLAGS` option to link to `hpx_internal_flags`
- PR #4165³⁰²⁹ - Forward `HPX_*` cmake cache variables to external projects
- PR #4164³⁰³⁰ - Affinity and batch environment modules
- PR #4162³⁰³¹ - Handle quick `exit`
- PR #4160³⁰³² - Using `target_link_libraries` for cmake versions ≥ 3.12
- PR #4159³⁰³³ - Make sure `HPX_WITH_NATIVE_TLS` is forwarded to dependent projects
- PR #4158³⁰³⁴ - Adding allocator imported target as a dependency of allocator module
- PR #4157³⁰³⁵ - Add `hpx_memory` as a dependency of parcellport plugins
- PR #4156³⁰³⁶ - Stackless coroutines now can refer to themselves (through `get_self()` and friends)
- PR #4154³⁰³⁷ - Added CMake policy CMP0060 for HPX applications.
- PR #4153³⁰³⁸ - add header `iomanip` to tests and tool
- PR #4152³⁰³⁹ - Casting MPI tag value
- PR #4149³⁰⁴⁰ - Add back private `m_desc` member variable in `program_options` module
- PR #4147³⁰⁴¹ - Resource partitioner and threadmanager modules
- PR #4146³⁰⁴² - Google Season of Docs updates to documentation; creating hpx projects
- PR #4145³⁰⁴³ - Adding basic support for stackless threads
- PR #4143³⁰⁴⁴ - Exclude `test_client_1950` from all target
- PR #4142³⁰⁴⁵ - Add a new `thread_pool_executor`

³⁰²³ <https://github.com/TheHPXProject/hpx/pull/4172>

³⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/4171>

³⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/4170>

³⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/4168>

³⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/4167>

³⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/4166>

³⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/4165>

³⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/4164>

³⁰³¹ <https://github.com/TheHPXProject/hpx/pull/4162>

³⁰³² <https://github.com/TheHPXProject/hpx/pull/4160>

³⁰³³ <https://github.com/TheHPXProject/hpx/pull/4159>

³⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/4158>

³⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/4157>

³⁰³⁶ <https://github.com/TheHPXProject/hpx/pull/4156>

³⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/4154>

³⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/4153>

³⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/4152>

³⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4149>

³⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/4147>

³⁰⁴² <https://github.com/TheHPXProject/hpx/pull/4146>

³⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/4145>

³⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4143>

³⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4142>

- PR #4140³⁰⁴⁶ - Google Season of Docs updates to documentation; why hpx
- PR #4139³⁰⁴⁷ - Remove runtime includes from coroutines module
- PR #4138³⁰⁴⁸ - Forking boost::intrusive_ptr and adding it as hpx::intrusive_ptr
- PR #4137³⁰⁴⁹ - Fixing TSS destruction
- PR #4136³⁰⁵⁰ - HPX.Compute modules
- PR #4133³⁰⁵¹ - Fix block_executor
- PR #4131³⁰⁵² - Applying fixes based on reports from PVS Studio
- PR #4130³⁰⁵³ - Adding missing header to build system
- PR #4129³⁰⁵⁴ - Fixing compilation if HPX_WITH_DATAPAR_VC is enabled
- PR #4128³⁰⁵⁵ - Renaming moveonly_any to unique_any
- PR #4126³⁰⁵⁶ - Attempt to fix basic_any constructor for gcc 7
- PR #4125³⁰⁵⁷ - Changing extra_archive_data implementation
- PR #4124³⁰⁵⁸ - Don't link to Boost.System unless required
- PR #4122³⁰⁵⁹ - Add kernel launch helper utility (+saxpy demo) and merge in octotiger changes
- PR #4121³⁰⁶⁰ - Fixing migration test if networking is disabled.
- PR #4120³⁰⁶¹ - Google Season of Docs updates to documentation; hpx build system v1
- PR #4119³⁰⁶² - Making sure chunk_size and max_chunk are actually applied to parallel algorithms if specified
- PR #4117³⁰⁶³ - Make CircleCI formatting check store diff
- PR #4116³⁰⁶⁴ - Fix automatically setting C++ standard
- PR #4114³⁰⁶⁵ - Module serialization
- PR #4113³⁰⁶⁶ - Module datastructures
- PR #4111³⁰⁶⁷ - Fixing performance regression introduced earlier
- PR #4110³⁰⁶⁸ - Adding missing SPDX tags

³⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4140>

³⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4139>

³⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4138>

³⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4137>

³⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4136>

³⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/4133>

³⁰⁵² <https://github.com/TheHPXProject/hpx/pull/4131>

³⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/4130>

³⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4129>

³⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4128>

³⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4126>

³⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4125>

³⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4124>

³⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4122>

³⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4121>

³⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/4120>

³⁰⁶² <https://github.com/TheHPXProject/hpx/pull/4119>

³⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/4117>

³⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4116>

³⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4114>

³⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4113>

³⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4111>

³⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4110>

- PR #4109³⁰⁶⁹ - Overload for start without entry point/argv.
- PR #4108³⁰⁷⁰ - Making sure C++ standard is properly detected and propagated
- PR #4106³⁰⁷¹ - use `std::round` for guaranteed rounding without errors
- PR #4104³⁰⁷² - Extend `scheduler_mode` with new `work_stealing` and task assignment modes
- PR #4103³⁰⁷³ - Add this to lambda capture list
- PR #4102³⁰⁷⁴ - Add spdx license and check
- PR #4099³⁰⁷⁵ - Module coroutines
- PR #4098³⁰⁷⁶ - Fix append module path in module CMakeLists template
- PR #4097³⁰⁷⁷ - Function tests
- PR #4096³⁰⁷⁸ - Removing return of `thread_result_type` from functions not needing them
- PR #4095³⁰⁷⁹ - Stop-gap measure until cmake overhaul is in place
- PR #4094³⁰⁸⁰ - Deprecate `HPX_WITH_MORE_THAN_64_THREADS`
- PR #4093³⁰⁸¹ - Fix initialization of `global_num_tasks` in `parallel_executor`
- PR #4092³⁰⁸² - Add support for mi-malloc
- PR #4090³⁰⁸³ - Execution context
- PR #4089³⁰⁸⁴ - Make counters in coroutines optional
- PR #4087³⁰⁸⁵ - Making `hpx::util::any` compatible with C++17
- PR #4084³⁰⁸⁶ - Making sure destination array for `std::transform` is properly resized
- PR #4083³⁰⁸⁷ - Adapting `thread_queue_mc` to behave even if no 128bit atomics are available
- PR #4082³⁰⁸⁸ - Fix compilation on GCC 5
- PR #4081³⁰⁸⁹ - Adding option allowing to force using Boost.FileSystem
- PR #4080³⁰⁹⁰ - Updating module dependencies
- PR #4079³⁰⁹¹ - Add missing tests for `iterator_support` module

³⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4109>

³⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4108>

³⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/4106>

³⁰⁷² <https://github.com/TheHPXProject/hpx/pull/4104>

³⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/4103>

³⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4102>

³⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4099>

³⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4098>

³⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4097>

³⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4096>

³⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4095>

³⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4094>

³⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/4093>

³⁰⁸² <https://github.com/TheHPXProject/hpx/pull/4092>

³⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/4090>

³⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4089>

³⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4087>

³⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4084>

³⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4083>

³⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4082>

³⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4081>

³⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4080>

³⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/4079>

- PR #4078³⁰⁹² - Disable parcel-layer if networking is disabled
- PR #4077³⁰⁹³ - Add missing include that causes build fails
- PR #4076³⁰⁹⁴ - Enable compatibility headers for functional module
- PR #4075³⁰⁹⁵ - Coroutines module
- PR #4073³⁰⁹⁶ - Use `configure_file` for generated files in modules
- PR #4071³⁰⁹⁷ - Fixing MPI detection for PMIx
- PR #4070³⁰⁹⁸ - Fix macOS builds
- PR #4069³⁰⁹⁹ - Moving more facilities to the collectives module
- PR #4068³¹⁰⁰ - Adding main HPX `#include` directory to modules
- PR #4066³¹⁰¹ - Switching the use of `message(STATUS "...")` to `hpx_info`
- PR #4065³¹⁰² - Move Boost.Filesystem handling to filesystem module
- PR #4064³¹⁰³ - Fix program_options test with older boost versions
- PR #4062³¹⁰⁴ - The `cpu_features` tool fails to compile on anything but x86 architectures
- PR #4061³¹⁰⁵ - Add `clang-format` checking step for modules
- PR #4060³¹⁰⁶ - Making sure `HPX_IDLE_BACKOFF_TIME_MAX` is always defined (even if its unused)
- PR #4059³¹⁰⁷ - Renaming module `hpx_parallel_executors` into `hpx_execution`
- PR #4058³¹⁰⁸ - Do not build networking tests when networking disabled
- PR #4057³¹⁰⁹ - Printing configuration summary for modules as well
- PR #4055³¹¹⁰ - Google Season of Docs updates to documentation; hpx build systems
- PR #4054³¹¹¹ - Add troubleshooting section to manual
- PR #4051³¹¹² - Add more variations to `future_overhead` test
- PR #4050³¹¹³ - Creating plugin module
- PR #4049³¹¹⁴ - Move missing modules tests

³⁰⁹² <https://github.com/TheHPXProject/hpx/pull/4078>

³⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/4077>

³⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4076>

³⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4075>

³⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4073>

³⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4071>

³⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4070>

³⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4069>

³¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4068>

³¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/4066>

³¹⁰² <https://github.com/TheHPXProject/hpx/pull/4065>

³¹⁰³ <https://github.com/TheHPXProject/hpx/pull/4064>

³¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4062>

³¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4061>

³¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4060>

³¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4059>

³¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4058>

³¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4057>

³¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/4055>

³¹¹¹ <https://github.com/TheHPXProject/hpx/pull/4054>

³¹¹² <https://github.com/TheHPXProject/hpx/pull/4051>

³¹¹³ <https://github.com/TheHPXProject/hpx/pull/4050>

³¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/4049>

- PR #4047³¹¹⁵ - Add boost/filesystem headers to inspect deprecated headers
- PR #4045³¹¹⁶ - Module functional
- PR #4043³¹¹⁷ - Fix preconditions and error messages for suspension functions
- PR #4041³¹¹⁸ - Pass HPX_STANDARD on to dependent projects via HPXConfig.cmake
- PR #4040³¹¹⁹ - Program options module
- PR #4039³¹²⁰ - Moving non-serializable any (any_nonser) to datastructures module
- PR #4038³¹²¹ - Adding MPark's variant (V1.4.0) to HPX
- PR #4037³¹²² - Adding resiliency module
- PR #4036³¹²³ - Add C++17 filesystem compatibility header
- PR #4035³¹²⁴ - Fixing support for mpirun
- PR #4028³¹²⁵ - CMake to target based directives
- PR #4027³¹²⁶ - Remove GitLab CI configuration
- PR #4026³¹²⁷ - Threading refactoring
- PR #4025³¹²⁸ - Refactoring thread queue configuration options
- PR #4024³¹²⁹ - Fix padding calculation in cache_aligned_data.hpp
- PR #4023³¹³⁰ - Fixing Codacy issues
- PR #4022³¹³¹ - Make sure process mask option is passed to affinity_data
- PR #4021³¹³² - Warn about compiling in C++11 mode
- PR #4020³¹³³ - Module concurrency
- PR #4019³¹³⁴ - Module topology
- PR #4018³¹³⁵ - Update deprecated header in thread_queue_mc.hpp
- PR #4015³¹³⁶ - Avoid overwriting artifacts
- PR #4014³¹³⁷ - Future overheads

³¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/4047>

³¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/4045>

³¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/4043>

³¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/4041>

³¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/4040>

³¹²⁰ <https://github.com/TheHPXProject/hpx/pull/4039>

³¹²¹ <https://github.com/TheHPXProject/hpx/pull/4038>

³¹²² <https://github.com/TheHPXProject/hpx/pull/4037>

³¹²³ <https://github.com/TheHPXProject/hpx/pull/4036>

³¹²⁴ <https://github.com/TheHPXProject/hpx/pull/4035>

³¹²⁵ <https://github.com/TheHPXProject/hpx/pull/4028>

³¹²⁶ <https://github.com/TheHPXProject/hpx/pull/4027>

³¹²⁷ <https://github.com/TheHPXProject/hpx/pull/4026>

³¹²⁸ <https://github.com/TheHPXProject/hpx/pull/4025>

³¹²⁹ <https://github.com/TheHPXProject/hpx/pull/4024>

³¹³⁰ <https://github.com/TheHPXProject/hpx/pull/4023>

³¹³¹ <https://github.com/TheHPXProject/hpx/pull/4022>

³¹³² <https://github.com/TheHPXProject/hpx/pull/4021>

³¹³³ <https://github.com/TheHPXProject/hpx/pull/4020>

³¹³⁴ <https://github.com/TheHPXProject/hpx/pull/4019>

³¹³⁵ <https://github.com/TheHPXProject/hpx/pull/4018>

³¹³⁶ <https://github.com/TheHPXProject/hpx/pull/4015>

³¹³⁷ <https://github.com/TheHPXProject/hpx/pull/4014>

- PR #4013³¹³⁸ - Update URL to test output conversion script
- PR #4012³¹³⁹ - Fix CUDA compilation
- PR #4011³¹⁴⁰ - Fixing cyclic dependencies between modules
- PR #4010³¹⁴¹ - Ignore stable tag on CircleCI
- PR #4009³¹⁴² - Check circular dependencies in a circle ci step
- PR #4008³¹⁴³ - Extend cache aligned data to handle tuple-like data
- PR #4007³¹⁴⁴ - Fixing migration for components that have actions returning a client
- PR #4006³¹⁴⁵ - Move is_value_proxy.hpp to algorithms module
- PR #4004³¹⁴⁶ - Shorten CTest timeout on CircleCI
- PR #4003³¹⁴⁷ - Refactoring to remove (internal) dependencies
- PR #4001³¹⁴⁸ - Exclude tests from all target
- PR #4000³¹⁴⁹ - Module errors
- PR #3999³¹⁵⁰ - Enable support for compatibility headers for logging module
- PR #3998³¹⁵¹ - Add process thread binding option
- PR #3997³¹⁵² - Export handle_assert function
- PR #3996³¹⁵³ - Attempt to solve issue where -latomic does not support 128bit atomics
- PR #3993³¹⁵⁴ - Make sure __LINE__ is an unsigned
- PR #3991³¹⁵⁵ - Fix dependencies and flags for header tests
- PR #3990³¹⁵⁶ - Documentation tags fixes
- PR #3988³¹⁵⁷ - Adding missing solution folder for format module test
- PR #3987³¹⁵⁸ - Move runtime-dependent functions out of command line handling
- PR #3986³¹⁵⁹ - Fix CMake configuration with PAPI on
- PR #3985³¹⁶⁰ - Module timing

³¹³⁸ <https://github.com/TheHPXProject/hpx/pull/4013>

³¹³⁹ <https://github.com/TheHPXProject/hpx/pull/4012>

³¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4011>

³¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/4010>

³¹⁴² <https://github.com/TheHPXProject/hpx/pull/4009>

³¹⁴³ <https://github.com/TheHPXProject/hpx/pull/4008>

³¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4007>

³¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4006>

³¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4004>

³¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4003>

³¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4001>

³¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4000>

³¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3999>

³¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/3998>

³¹⁵² <https://github.com/TheHPXProject/hpx/pull/3997>

³¹⁵³ <https://github.com/TheHPXProject/hpx/pull/3996>

³¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3993>

³¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3991>

³¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3990>

³¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3988>

³¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3987>

³¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3986>

³¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3985>

- PR #3984³¹⁶¹ - Fix default behaviour of paths in `add_hpx_component`
- PR #3982³¹⁶² - Parallel executors module
- PR #3981³¹⁶³ - Segmented algorithms module
- PR #3980³¹⁶⁴ - Module logging
- PR #3979³¹⁶⁵ - Module util
- PR #3978³¹⁶⁶ - Fix `clang-tidy` step on CircleCI
- PR #3977³¹⁶⁷ - Fixing solution folders for moved components
- PR #3976³¹⁶⁸ - Module format
- PR #3975³¹⁶⁹ - Enable deprecation warnings on CircleCI
- PR #3974³¹⁷⁰ - Fix typos in documentation
- PR #3973³¹⁷¹ - Fix compilation with GCC 9
- PR #3972³¹⁷² - Add condition to clone apex + use of new cmake var `APEX_ROOT`
- PR #3971³¹⁷³ - Add testing module
- PR #3968³¹⁷⁴ - Remove unneeded file in hardware module
- PR #3967³¹⁷⁵ - Remove leftover PIC settings from main `CMakeLists.txt`
- PR #3966³¹⁷⁶ - Add missing export option in `add_hpx_module`
- PR #3965³¹⁷⁷ - Change `current_function_helper` back to non-constexpr
- PR #3964³¹⁷⁸ - Fixing merge problems
- PR #3962³¹⁷⁹ - Add a trait for `std::array` for unwrapping
- PR #3961³¹⁸⁰ - Making `hpx::util::tuple<Ts...>` and `std::tuple<Ts...>` convertible
- PR #3960³¹⁸¹ - fix compilation with CUDA 10 and GCC 6
- PR #3959³¹⁸² - Fix C++11 incompatibility
- PR #3957³¹⁸³ - Algorithms module

³¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/3984>

³¹⁶² <https://github.com/TheHPXProject/hpx/pull/3982>

³¹⁶³ <https://github.com/TheHPXProject/hpx/pull/3981>

³¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3980>

³¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3979>

³¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3978>

³¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3977>

³¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3976>

³¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3975>

³¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3974>

³¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/3973>

³¹⁷² <https://github.com/TheHPXProject/hpx/pull/3972>

³¹⁷³ <https://github.com/TheHPXProject/hpx/pull/3971>

³¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3968>

³¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3967>

³¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3966>

³¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3965>

³¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3964>

³¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3962>

³¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3961>

³¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/3960>

³¹⁸² <https://github.com/TheHPXProject/hpx/pull/3959>

³¹⁸³ <https://github.com/TheHPXProject/hpx/pull/3957>

- PR #3956³¹⁸⁴ - [HPX_AddModule] Fix lower name var to upper
- PR #3955³¹⁸⁵ - Fix CMake configuration with examples off and tests on
- PR #3954³¹⁸⁶ - Move components to separate subdirectory in root of repository
- PR #3952³¹⁸⁷ - Update `papi.cpp`
- PR #3951³¹⁸⁸ - Exclude modules header tests from all target
- PR #3950³¹⁸⁹ - Adding `all_reduce` facility to collectives module
- PR #3949³¹⁹⁰ - This adds a configuration file that will cause for stale issues to be automatically closed
- PR #3948³¹⁹¹ - Fixing ALPS environment
- PR #3947³¹⁹² - Add major compiler version check for building hpx as a binary package
- PR #3946³¹⁹³ - [Modules] Move the location of the generated headers
- PR #3945³¹⁹⁴ - Simplify tests and examples cmake
- PR #3943³¹⁹⁵ - Remove example module
- PR #3942³¹⁹⁶ - Add `NOEXPORT` option to `add_hpx_{component,library}`
- PR #3938³¹⁹⁷ - Use https for CDash submissions
- PR #3937³¹⁹⁸ - Add `HPX_WITH_BUILD_BINARY_PACKAGE` to the compiler check (refs #3935)
- PR #3936³¹⁹⁹ - Fixing installation of binaries on windows
- PR #3934³²⁰⁰ - Add set function for `sliding_semaphore_max_difference`
- PR #3933³²⁰¹ - Remove `cuaddevrt` from compile/link flags as it breaks downstream projects
- PR #3932³²⁰² - Fixing 3929
- PR #3931³²⁰³ - Adding `all_to_all`
- PR #3930³²⁰⁴ - Add test demonstrating the use of broadcast with component actions
- PR #3928³²⁰⁵ - fixed number of tasks and number of threads for heterogeneous slurm environments
- PR #3927³²⁰⁶ - Moving Cache module's tests into separate solution folder

³¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3956>

³¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3955>

³¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3954>

³¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3952>

³¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3951>

³¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3950>

³¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3949>

³¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/3948>

³¹⁹² <https://github.com/TheHPXProject/hpx/pull/3947>

³¹⁹³ <https://github.com/TheHPXProject/hpx/pull/3946>

³¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3945>

³¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3943>

³¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3942>

³¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3938>

³¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3937>

³¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3936>

³²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3934>

³²⁰¹ <https://github.com/TheHPXProject/hpx/pull/3933>

³²⁰² <https://github.com/TheHPXProject/hpx/pull/3932>

³²⁰³ <https://github.com/TheHPXProject/hpx/pull/3931>

³²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3930>

³²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3928>

³²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3927>

- PR #3926³²⁰⁷ - Move unit tests to cache module
- PR #3925³²⁰⁸ - Move version check to config module
- PR #3924³²⁰⁹ - Add schedule hint executor parameters
- PR #3923³²¹⁰ - Allow aligning objects bigger than the cache line size
- PR #3922³²¹¹ - Add Windows builds with Travis CI
- PR #3921³²¹² - Add ccls cache directory to gitignore
- PR #3920³²¹³ - Fix `git_external` fetching of tags
- PR #3905³²¹⁴ - Correct rostambod url. Fix typo in doc
- PR #3904³²¹⁵ - Fix bug in `context_base.hpp`
- PR #3903³²¹⁶ - Adding new performance counters
- PR #3902³²¹⁷ - Add `add_hpx_module` function
- PR #3901³²¹⁸ - Factoring out container remapping into a separate trait
- PR #3900³²¹⁹ - Making sure errors during command line processing are properly reported and will not cause assertions
- PR #3899³²²⁰ - Remove old compatibility bases from `make_action`
- PR #3898³²²¹ - Make parameter size be of type `size_t`
- PR #3897³²²² - Making sure all tests are disabled if `HPX_WITH_TESTS=OFF`
- PR #3895³²²³ - Add documentation for `annotated_function`
- PR #3894³²²⁴ - Working around VS2019 problem with `make_action`
- PR #3892³²²⁵ - Avoid MSVC compatibility warning in internal allocator
- PR #3891³²²⁶ - Removal of the default intel config include
- PR #3888³²²⁷ - Fix `async_customization` dataflow example and Clarify what's being tested
- PR #3887³²²⁸ - Add Doxygen documentation
- PR #3882³²²⁹ - Minor docs fixes

³²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3926>

³²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3925>

³²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3924>

³²¹⁰ <https://github.com/TheHPXProject/hpx/pull/3923>

³²¹¹ <https://github.com/TheHPXProject/hpx/pull/3922>

³²¹² <https://github.com/TheHPXProject/hpx/pull/3921>

³²¹³ <https://github.com/TheHPXProject/hpx/pull/3920>

³²¹⁴ <https://github.com/TheHPXProject/hpx/pull/3905>

³²¹⁵ <https://github.com/TheHPXProject/hpx/pull/3904>

³²¹⁶ <https://github.com/TheHPXProject/hpx/pull/3903>

³²¹⁷ <https://github.com/TheHPXProject/hpx/pull/3902>

³²¹⁸ <https://github.com/TheHPXProject/hpx/pull/3901>

³²¹⁹ <https://github.com/TheHPXProject/hpx/pull/3900>

³²²⁰ <https://github.com/TheHPXProject/hpx/pull/3899>

³²²¹ <https://github.com/TheHPXProject/hpx/pull/3898>

³²²² <https://github.com/TheHPXProject/hpx/pull/3897>

³²²³ <https://github.com/TheHPXProject/hpx/pull/3895>

³²²⁴ <https://github.com/TheHPXProject/hpx/pull/3894>

³²²⁵ <https://github.com/TheHPXProject/hpx/pull/3892>

³²²⁶ <https://github.com/TheHPXProject/hpx/pull/3891>

³²²⁷ <https://github.com/TheHPXProject/hpx/pull/3888>

³²²⁸ <https://github.com/TheHPXProject/hpx/pull/3887>

³²²⁹ <https://github.com/TheHPXProject/hpx/pull/3882>

- PR #3880³²³⁰ - Updating APEX version tag
- PR #3878³²³¹ - Making sure symbols are properly exported from modules (needed for Windows/MacOS)
- PR #3877³²³² - Documentation
- PR #3876³²³³ - Module hardware
- PR #3875³²³⁴ - Converted typedefs in actions submodule to using directives
- PR #3874³²³⁵ - Allow one to suppress target keywords in `hpx_setup_target` for backwards compatibility
- PR #3873³²³⁶ - Add scripts to create releases and generate lists of PRs and issues
- PR #3872³²³⁷ - Fix latest HTML docs location
- PR #3870³²³⁸ - Module cache
- PR #3869³²³⁹ - Post 1.3.0 version bumps
- PR #3868³²⁴⁰ - Replace the macro `HPX_ASSERT` by `HPX_TEST` in tests
- PR #3845³²⁴¹ - Assertion module
- PR #3839³²⁴² - Make tuple serialization non-intrusive
- PR #3832³²⁴³ - Config module
- PR #3799³²⁴⁴ - Remove compat namespace and its contents
- PR #3701³²⁴⁵ - MoodyCamel lockfree
- PR #3496³²⁴⁶ - Disabling MPI's (deprecated) C++ interface
- PR #3192³²⁴⁷ - Move type info into `hpx::debug` namespace and add print helper functions
- PR #3159³²⁴⁸ - Support Checkpointing Components

³²³⁰ <https://github.com/TheHPXProject/hpx/pull/3880>

³²³¹ <https://github.com/TheHPXProject/hpx/pull/3878>

³²³² <https://github.com/TheHPXProject/hpx/pull/3877>

³²³³ <https://github.com/TheHPXProject/hpx/pull/3876>

³²³⁴ <https://github.com/TheHPXProject/hpx/pull/3875>

³²³⁵ <https://github.com/TheHPXProject/hpx/pull/3874>

³²³⁶ <https://github.com/TheHPXProject/hpx/pull/3873>

³²³⁷ <https://github.com/TheHPXProject/hpx/pull/3872>

³²³⁸ <https://github.com/TheHPXProject/hpx/pull/3870>

³²³⁹ <https://github.com/TheHPXProject/hpx/pull/3869>

³²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3868>

³²⁴¹ <https://github.com/TheHPXProject/hpx/pull/3845>

³²⁴² <https://github.com/TheHPXProject/hpx/pull/3839>

³²⁴³ <https://github.com/TheHPXProject/hpx/pull/3832>

³²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3799>

³²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3701>

³²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3496>

³²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3192>

³²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3159>

HPX V1.3.0 (May 23, 2019)

General changes

- Performance improvements: the schedulers have significantly reduced overheads from removing false sharing and the parallel executor has been updated to create fewer futures.
- HPX now defaults to not turning on networking when running on one locality. This means that you can run multiple instances on the same system without adding command line options.
- Multiple issues reported by Clang sanitizers have been fixed.
- We have added (back) single-page HTML documentation and PDF documentation.
- We have started modularizing the HPX library. This is useful both for developers and users. In the long term users will be able to consume only parts of the HPX libraries if they do not require all the functionality that HPX currently provides.
- We have added an implementation of `function_ref`.
- The `barrier` and `latch` classes have gained a few additional member functions.

Breaking changes

- Executable and library targets are now created without the `_exe` and `_lib` suffix respectively. For example, the target `1d_stencil_1_exe` is now simply called `1d_stencil_1`.
- We have removed the following deprecated functionality: `queue`, `scoped_unlock`, and support for input iterators in algorithms.
- We have turned off the compatibility layer for `unwrapped` by default. The functionality will be removed in the next release. The option can still be turned on using the [CMake](https://www.cmake.org)³²⁴⁹ option `HPX_WITH_UNWRAPPED_SUPPORT`. Likewise, `inclusive_scan` compatibility overloads have been turned off by default. They can still be turned on with `HPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY`.
- The minimum compiler and dependency versions have been updated. We now support GCC from version 5 onwards, Clang from version 4 onwards, and Boost from version 1.61.0 onwards.
- The headers for preprocessor macros have moved as a result of the functionality being moved to a separate module. The old headers are deprecated and will be removed in a future version of HPX. You can turn off the warnings by setting `HPX_PREPROCESSOR_WITH_DEPRECATION_WARNINGS=OFF` or turn off the compatibility headers completely with `HPX_PREPROCESSOR_WITH_COMPATIBILITY_HEADERS=OFF`.

Closed issues

- [Issue #3863](https://github.com/TheHPXProject/hpx/issues/3863)³²⁵⁰ - shouldn't “-faligned-new” be a usage requirement?
- [Issue #3841](https://github.com/TheHPXProject/hpx/issues/3841)³²⁵¹ - Build error with msvc 19 caused by SFINAE and C++17
- [Issue #3836](https://github.com/TheHPXProject/hpx/issues/3836)³²⁵² - master branch does not build with idle rate counters enabled
- [Issue #3819](https://github.com/TheHPXProject/hpx/issues/3819)³²⁵³ - Add debug suffix to modules built in debug mode

³²⁴⁹ <https://www.cmake.org>

³²⁵⁰ <https://github.com/TheHPXProject/hpx/issues/3863>

³²⁵¹ <https://github.com/TheHPXProject/hpx/issues/3841>

³²⁵² <https://github.com/TheHPXProject/hpx/issues/3836>

³²⁵³ <https://github.com/TheHPXProject/hpx/issues/3819>

- Issue #3817³²⁵⁴ - HPX_INCLUDE_DIRS contains non-existent directory
- Issue #3810³²⁵⁵ - Source groups are not created for files in modules
- Issue #3805³²⁵⁶ - HPX won't compile with -DHPX_WITH_APEX=TRUE
- Issue #3792³²⁵⁷ - Barrier Hangs When Locality Zero not included
- Issue #3778³²⁵⁸ - Replace throw() with noexcept
- Issue #3763³²⁵⁹ - configurable sort limit per task
- Issue #3758³²⁶⁰ - dataflow doesn't convert future<future<T>> to future<T>
- Issue #3757³²⁶¹ - When compiling undefined reference to hpx::hpx_check_version_1_2 HPX V1.2.1, Ubuntu 18.04.01 Server Edition
- Issue #3753³²⁶² - --hpx:list-counters=full crashes
- Issue #3746³²⁶³ - Detection of MPI with pmix
- Issue #3744³²⁶⁴ - Separate spinlock from same cacheline as internal data for all LCOs
- Issue #3743³²⁶⁵ - hpxcxx's shebang doesn't specify the python version
- Issue #3738³²⁶⁶ - Unable to debug parcellport on a single node
- Issue #3735³²⁶⁷ - Latest master: Can't compile in MSVC
- Issue #3731³²⁶⁸ - util::bound seems broken on Clang with older libstdc++
- Issue #3724³²⁶⁹ - Allow to pre-set command line options through environment
- Issue #3723³²⁷⁰ - examples/resource_partitioner build issue on master branch / ubuntu 18
- Issue #3721³²⁷¹ - faced a building error
- Issue #3720³²⁷² - Hello World example fails to link
- Issue #3719³²⁷³ - pkg-config produces invalid output: -l-pthread
- Issue #3718³²⁷⁴ - Please make the python executable configurable through cmake
- Issue #3717³²⁷⁵ - interested to contribute to the organisation
- Issue #3699³²⁷⁶ - Remove 'HPX runtime' executable

³²⁵⁴ <https://github.com/TheHPXProject/hpx/issues/3817>

³²⁵⁵ <https://github.com/TheHPXProject/hpx/issues/3810>

³²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3805>

³²⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3792>

³²⁵⁸ <https://github.com/TheHPXProject/hpx/issues/3778>

³²⁵⁹ <https://github.com/TheHPXProject/hpx/issues/3763>

³²⁶⁰ <https://github.com/TheHPXProject/hpx/issues/3758>

³²⁶¹ <https://github.com/TheHPXProject/hpx/issues/3757>

³²⁶² <https://github.com/TheHPXProject/hpx/issues/3753>

³²⁶³ <https://github.com/TheHPXProject/hpx/issues/3746>

³²⁶⁴ <https://github.com/TheHPXProject/hpx/issues/3744>

³²⁶⁵ <https://github.com/TheHPXProject/hpx/issues/3743>

³²⁶⁶ <https://github.com/TheHPXProject/hpx/issues/3738>

³²⁶⁷ <https://github.com/TheHPXProject/hpx/issues/3735>

³²⁶⁸ <https://github.com/TheHPXProject/hpx/issues/3731>

³²⁶⁹ <https://github.com/TheHPXProject/hpx/issues/3724>

³²⁷⁰ <https://github.com/TheHPXProject/hpx/issues/3723>

³²⁷¹ <https://github.com/TheHPXProject/hpx/issues/3721>

³²⁷² <https://github.com/TheHPXProject/hpx/issues/3720>

³²⁷³ <https://github.com/TheHPXProject/hpx/issues/3719>

³²⁷⁴ <https://github.com/TheHPXProject/hpx/issues/3718>

³²⁷⁵ <https://github.com/TheHPXProject/hpx/issues/3717>

³²⁷⁶ <https://github.com/TheHPXProject/hpx/issues/3699>

- Issue #3698³²⁷⁷ - Ignore all locks while handling asserts
- Issue #3689³²⁷⁸ - Incorrect and inconsistent website structure <http://stellar.cct.lsu.edu/downloads/>.
- Issue #3681³²⁷⁹ - Broken links on <http://stellar.cct.lsu.edu/2015/05/hpx-archives-now-on-gmane/>
- Issue #3676³²⁸⁰ - HPX master built from source, cmake fails to link main.cpp example in docs
- Issue #3673³²⁸¹ - HPX build fails with `std::atomic` missing error
- Issue #3670³²⁸² - Generate PDF again from documentation (with Sphinx)
- Issue #3643³²⁸³ - Warnings when compiling HPX 1.2.1 with gcc 9
- Issue #3641³²⁸⁴ - Trouble with using ranges-v3 and `hpx::parallel::reduce`
- Issue #3639³²⁸⁵ - `util::unwrapping` does not work well with member functions
- Issue #3634³²⁸⁶ - The build fails if `shared_future<>::then` is called with a thread executor
- Issue #3622³²⁸⁷ - VTune Amplifier 2019 not working with `use_itt_notify=1`
- Issue #3616³²⁸⁸ - HPX Fails to Build with CUDA 10
- Issue #3612³²⁸⁹ - False sharing of scheduling counters
- Issue #3609³²⁹⁰ - `executor_parameters` timeout with gcc <= 7 and Debug mode
- Issue #3601³²⁹¹ - Misleading error message on power pc for `rdtsc` and `rdtscp`
- Issue #3598³²⁹² - Build of some examples fails when using Vc
- Issue #3594³²⁹³ - Error: The number of OS threads requested (20) does not match the number of threads to bind (12): HPX(bad_parameter)
- Issue #3592³²⁹⁴ - Undefined Reference Error
- Issue #3589³²⁹⁵ - include could not find load file: HPX_Utils.cmake
- Issue #3587³²⁹⁶ - HPX won't compile on POWER8 with Clang 7
- Issue #3583³²⁹⁷ - Fedora and openSUSE instructions missing on "Distribution Packages" page
- Issue #3578³²⁹⁸ - Build error when configuring with `HPX_HAVE_ALGORITHM_INPUT_ITERATOR_SUPPORT=ON`
- Issue #3575³²⁹⁹ - Merge openSUSE reproducible patch

³²⁷⁷ <https://github.com/TheHPXProject/hpx/issues/3698>

³²⁷⁸ <https://github.com/TheHPXProject/hpx/issues/3689>

³²⁷⁹ <https://github.com/TheHPXProject/hpx/issues/3681>

³²⁸⁰ <https://github.com/TheHPXProject/hpx/issues/3676>

³²⁸¹ <https://github.com/TheHPXProject/hpx/issues/3673>

³²⁸² <https://github.com/TheHPXProject/hpx/issues/3670>

³²⁸³ <https://github.com/TheHPXProject/hpx/issues/3643>

³²⁸⁴ <https://github.com/TheHPXProject/hpx/issues/3641>

³²⁸⁵ <https://github.com/TheHPXProject/hpx/issues/3639>

³²⁸⁶ <https://github.com/TheHPXProject/hpx/issues/3634>

³²⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3622>

³²⁸⁸ <https://github.com/TheHPXProject/hpx/issues/3616>

³²⁸⁹ <https://github.com/TheHPXProject/hpx/issues/3612>

³²⁹⁰ <https://github.com/TheHPXProject/hpx/issues/3609>

³²⁹¹ <https://github.com/TheHPXProject/hpx/issues/3601>

³²⁹² <https://github.com/TheHPXProject/hpx/issues/3598>

³²⁹³ <https://github.com/TheHPXProject/hpx/issues/3594>

³²⁹⁴ <https://github.com/TheHPXProject/hpx/issues/3592>

³²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/3589>

³²⁹⁶ <https://github.com/TheHPXProject/hpx/issues/3587>

³²⁹⁷ <https://github.com/TheHPXProject/hpx/issues/3583>

³²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/3578>

³²⁹⁹ <https://github.com/TheHPXProject/hpx/issues/3575>

- [Issue #3570](#)³³⁰⁰ - Update HPX to work with the latest VC version
- [Issue #3567](#)³³⁰¹ - Build succeed and make failed for `hpx:cout`
- [Issue #3565](#)³³⁰² - Polymorphic simple component destructor not getting called
- [Issue #3559](#)³³⁰³ - 1.2.0 is missing from download page
- [Issue #3554](#)³³⁰⁴ - Clang 6.0 warning of hiding overloaded virtual function
- [Issue #3510](#)³³⁰⁵ - Build on ppc64 fails
- [Issue #3482](#)³³⁰⁶ - Improve error message when `HPX_WITH_MAX_CPU_COUNT` is too low for given system
- [Issue #3453](#)³³⁰⁷ - Two HPX applications can't run at the same time.
- [Issue #3452](#)³³⁰⁸ - Scaling issue on the change to 2 NUMA domains
- [Issue #3442](#)³³⁰⁹ - HPX `set_difference`, `set_intersection` failure cases
- [Issue #3437](#)³³¹⁰ - Ensure `parent_task` pointer when child task is created and child/parent are on same locality
- [Issue #3255](#)³³¹¹ - Suspension with lock for `--hpx:list-component-types`
- [Issue #3034](#)³³¹² - Use C++17 structured bindings for serialization
- [Issue #2999](#)³³¹³ - Change thread scheduling use of `size_t` for thread indexing

Closed pull requests

- [PR #3865](#)³³¹⁴ - adds `hpx_target_compile_option_if_available`
- [PR #3864](#)³³¹⁵ - Helper functions that are useful in numa binding and testing of allocator
- [PR #3862](#)³³¹⁶ - Temporary fix to `local_dataflow_boost_small_vector` test
- [PR #3860](#)³³¹⁷ - Add cache line padding to intermediate results in for loop reduction
- [PR #3859](#)³³¹⁸ - Remove `HPX_TLL_PUBLIC` and `HPX_TLL_PRIVATE` from CMake files
- [PR #3858](#)³³¹⁹ - Add compile flags and definitions to modules
- [PR #3851](#)³³²⁰ - update `hpxmp` release tag to v0.2.0
- [PR #3849](#)³³²¹ - Correct `BOOST_ROOT` variable name in quick start guide

³³⁰⁰ <https://github.com/TheHPXProject/hpx/issues/3570>

³³⁰¹ <https://github.com/TheHPXProject/hpx/issues/3567>

³³⁰² <https://github.com/TheHPXProject/hpx/issues/3565>

³³⁰³ <https://github.com/TheHPXProject/hpx/issues/3559>

³³⁰⁴ <https://github.com/TheHPXProject/hpx/issues/3554>

³³⁰⁵ <https://github.com/TheHPXProject/hpx/issues/3510>

³³⁰⁶ <https://github.com/TheHPXProject/hpx/issues/3482>

³³⁰⁷ <https://github.com/TheHPXProject/hpx/issues/3453>

³³⁰⁸ <https://github.com/TheHPXProject/hpx/issues/3452>

³³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/3442>

³³¹⁰ <https://github.com/TheHPXProject/hpx/issues/3437>

³³¹¹ <https://github.com/TheHPXProject/hpx/issues/3255>

³³¹² <https://github.com/TheHPXProject/hpx/issues/3034>

³³¹³ <https://github.com/TheHPXProject/hpx/issues/2999>

³³¹⁴ <https://github.com/TheHPXProject/hpx/pull/3865>

³³¹⁵ <https://github.com/TheHPXProject/hpx/pull/3864>

³³¹⁶ <https://github.com/TheHPXProject/hpx/pull/3862>

³³¹⁷ <https://github.com/TheHPXProject/hpx/pull/3860>

³³¹⁸ <https://github.com/TheHPXProject/hpx/pull/3859>

³³¹⁹ <https://github.com/TheHPXProject/hpx/pull/3858>

³³²⁰ <https://github.com/TheHPXProject/hpx/pull/3851>

³³²¹ <https://github.com/TheHPXProject/hpx/pull/3849>

- PR #3847³³²² - Fix attach_debugger configuration option
- PR #3846³³²³ - Add tests for libs header tests
- PR #3844³³²⁴ - Fixing source_groups in preprocessor module to properly handle compatibility headers
- PR #3843³³²⁵ - This fixes the launch_process/launched_process pair of tests
- PR #3842³³²⁶ - Fix macro call with ITTNOTIFY enabled
- PR #3840³³²⁷ - Fixing SLURM environment parsing
- PR #3837³³²⁸ - Fixing misplaced #endif
- PR #3835³³²⁹ - make all latch members protected for consistency
- PR #3834³³³⁰ - Disable transpose_block_numa example on CircleCI
- PR #3833³³³¹ - make latch **counter_** protected for deriving latch in hpxmp
- PR #3831³³³² - Fix CircleCI config for modules
- PR #3830³³³³ - minor fix: option HPX_WITH_TEST was not working correctly
- PR #3828³³³⁴ - Avoid for binaries that depend on HPX to directly link against internal modules
- PR #3827³³³⁵ - Adding shortcut for `hpx::get_ptr<>(sync, id)` for a local, non-migratable objects
- PR #3826³³³⁶ - Fix and update modules documentation
- PR #3825³³³⁷ - Updating default APEX version to 2.1.3 with HPX
- PR #3823³³³⁸ - Fix pkgconfig libs handling
- PR #3822³³³⁹ - Change includes in hpx_wrap.cpp to more specific includes
- PR #3821³³⁴⁰ - Disable barrier_3792 test when networking is disabled
- PR #3820³³⁴¹ - Assorted CMake fixes
- PR #3815³³⁴² - Removing left-over debug output
- PR #3814³³⁴³ - Allow setting default scheduler mode via the configuration database
- PR #3813³³⁴⁴ - Make the deprecation warnings issued by the old pp headers optional

³³²² <https://github.com/TheHPXProject/hpx/pull/3847>

³³²³ <https://github.com/TheHPXProject/hpx/pull/3846>

³³²⁴ <https://github.com/TheHPXProject/hpx/pull/3844>

³³²⁵ <https://github.com/TheHPXProject/hpx/pull/3843>

³³²⁶ <https://github.com/TheHPXProject/hpx/pull/3842>

³³²⁷ <https://github.com/TheHPXProject/hpx/pull/3840>

³³²⁸ <https://github.com/TheHPXProject/hpx/pull/3837>

³³²⁹ <https://github.com/TheHPXProject/hpx/pull/3835>

³³³⁰ <https://github.com/TheHPXProject/hpx/pull/3834>

³³³¹ <https://github.com/TheHPXProject/hpx/pull/3833>

³³³² <https://github.com/TheHPXProject/hpx/pull/3831>

³³³³ <https://github.com/TheHPXProject/hpx/pull/3830>

³³³⁴ <https://github.com/TheHPXProject/hpx/pull/3828>

³³³⁵ <https://github.com/TheHPXProject/hpx/pull/3827>

³³³⁶ <https://github.com/TheHPXProject/hpx/pull/3826>

³³³⁷ <https://github.com/TheHPXProject/hpx/pull/3825>

³³³⁸ <https://github.com/TheHPXProject/hpx/pull/3823>

³³³⁹ <https://github.com/TheHPXProject/hpx/pull/3822>

³³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3821>

³³⁴¹ <https://github.com/TheHPXProject/hpx/pull/3820>

³³⁴² <https://github.com/TheHPXProject/hpx/pull/3815>

³³⁴³ <https://github.com/TheHPXProject/hpx/pull/3814>

³³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3813>

- PR #3812³³⁴⁵ - Windows requires to handle symlinks to directories differently from those linking files
- PR #3811³³⁴⁶ - Clean up PP module and library skeleton
- PR #3806³³⁴⁷ - Moving include path configuration to before APEX
- PR #3804³³⁴⁸ - Fix latch
- PR #3803³³⁴⁹ - Update hpxcxx to look at lib64 and use python3
- PR #3802³³⁵⁰ - Numa binding allocator
- PR #3801³³⁵¹ - Remove duplicated includes
- PR #3800³³⁵² - Attempt to fix Posix context switching after lazy init changes
- PR #3798³³⁵³ - count and count_if accepts different iterator types
- PR #3797³³⁵⁴ - Adding a couple of `override` keywords to overloaded virtual functions
- PR #3796³³⁵⁵ - Re-enable testing all schedulers in `shutdown_suspended_test`
- PR #3795³³⁵⁶ - Change `std::terminate` to `std::abort` in SIGSEGV handler
- PR #3794³³⁵⁷ - Fixing #3792
- PR #3793³³⁵⁸ - Extending `migrate_polymorphic_component` unit test
- PR #3791³³⁵⁹ - Change `throw()` to `noexcept`
- PR #3790³³⁶⁰ - Remove deprecated options for 1.3.0 release
- PR #3789³³⁶¹ - Remove Boost filesystem compatibility header
- PR #3788³³⁶² - Disabled even more spots that should not execute if networking is disabled
- PR #3787³³⁶³ - Bump minimal boost supported version to 1.61.0
- PR #3786³³⁶⁴ - Bump minimum required versions for 1.3.0 release
- PR #3785³³⁶⁵ - Explicitly set number of jobs for all ninja invocations on CircleCI
- PR #3784³³⁶⁶ - Fix leak and address sanitizer problems
- PR #3783³³⁶⁷ - Disabled even more spots that should not execute is networking is disabled

³³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3812>

³³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3811>

³³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3806>

³³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3804>

³³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3803>

³³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3802>

³³⁵¹ <https://github.com/TheHPXProject/hpx/pull/3801>

³³⁵² <https://github.com/TheHPXProject/hpx/pull/3800>

³³⁵³ <https://github.com/TheHPXProject/hpx/pull/3798>

³³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3797>

³³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3796>

³³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3795>

³³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3794>

³³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3793>

³³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3791>

³³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3790>

³³⁶¹ <https://github.com/TheHPXProject/hpx/pull/3789>

³³⁶² <https://github.com/TheHPXProject/hpx/pull/3788>

³³⁶³ <https://github.com/TheHPXProject/hpx/pull/3787>

³³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3786>

³³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3785>

³³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3784>

³³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3783>

- PR #3782³³⁶⁸ - Cherry-picked tuple and thread_init_data fixes from #3701
- PR #3781³³⁶⁹ - Fix generic context coroutines after lazy stack allocation changes
- PR #3780³³⁷⁰ - Rename hello world examples
- PR #3776³³⁷¹ - Sort algorithms now use the supplied chunker to determine the required minimal chunk size
- PR #3775³³⁷² - Disable Boost auto-linking
- PR #3774³³⁷³ - Tag and push stable builds
- PR #3773³³⁷⁴ - Enable migration of polymorphic components
- PR #3771³³⁷⁵ - Fix link to stackoverflow in documentation
- PR #3770³³⁷⁶ - Replacing constexpr if in brace-serialization code
- PR #3769³³⁷⁷ - Fix SIGSEGV handler
- PR #3768³³⁷⁸ - Adding flags to scheduler allowing to control thread stealing and idle back-off
- PR #3767³³⁷⁹ - Fix help formatting in hpxrun.py
- PR #3765³³⁸⁰ - Fix a couple of bugs in the thread test
- PR #3764³³⁸¹ - Workaround for SFINAE regression in msvc14.2
- PR #3762³³⁸² - Prevent MSVC from prematurely instantiating things
- PR #3761³³⁸³ - Update python scripts to work with python 3
- PR #3760³³⁸⁴ - Fix callable vtable for GCC4.9
- PR #3759³³⁸⁵ - Rename PAGE_SIZE to PAGE_SIZE_ because AppleClang
- PR #3755³³⁸⁶ - Making sure locks are not held during suspension
- PR #3754³³⁸⁷ - Disable more code if networking is not available/not enabled
- PR #3752³³⁸⁸ - Move util::format implementation to source file
- PR #3751³³⁸⁹ - Fixing problems with lcos::barrier and iostreams
- PR #3750³³⁹⁰ - Change error message to take into account use_guard_page setting

³³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3782>

³³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3781>

³³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3780>

³³⁷¹ <https://github.com/TheHPXProject/hpx/pull/3776>

³³⁷² <https://github.com/TheHPXProject/hpx/pull/3775>

³³⁷³ <https://github.com/TheHPXProject/hpx/pull/3774>

³³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3773>

³³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3771>

³³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3770>

³³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3769>

³³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3768>

³³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3767>

³³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3765>

³³⁸¹ <https://github.com/TheHPXProject/hpx/pull/3764>

³³⁸² <https://github.com/TheHPXProject/hpx/pull/3762>

³³⁸³ <https://github.com/TheHPXProject/hpx/pull/3761>

³³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3760>

³³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3759>

³³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3755>

³³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3754>

³³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3752>

³³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3751>

³³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3750>

- PR #3749³³⁹¹ - Fix lifetime problem in `run_as_hpx_thread`
- PR #3748³³⁹² - Fixed unusable behavior of the clang code analyzer.
- PR #3747³³⁹³ - Added `PMIX_RANK` to the defaults of `HPX_WITH_PARCELPOR MPI_ENV`.
- PR #3745³³⁹⁴ - Introduced `cache_aligned_data` and `cache_line_data` helper structure
- PR #3742³³⁹⁵ - Remove more unused functionality from `util/logging`
- PR #3740³³⁹⁶ - Fix includes in partitioned vector tests
- PR #3739³³⁹⁷ - More fixes to make sure that `std::flush` really flushes all output
- PR #3737³³⁹⁸ - Fix potential shutdown problems
- PR #3736³³⁹⁹ - Fix `guided_pool_executor` after dataflow changes caused compilation fail
- PR #3734³⁴⁰⁰ - Limiting executor
- PR #3732³⁴⁰¹ - More constrained bound constructors
- PR #3730³⁴⁰² - Attempt to fix deadlocks during component loading
- PR #3729³⁴⁰³ - Add latch member function `count_up` and `reset`, requested by `hpxMP`
- PR #3728³⁴⁰⁴ - Send even empty buffers on `hpx::endl` and `hpx::flush`
- PR #3727³⁴⁰⁵ - Adding example demonstrating how to customize the memory management for a component
- PR #3726³⁴⁰⁶ - Adding support for passing command line options through the `HPX_COMMANDLINE_OPTIONS` environment variable
- PR #3722³⁴⁰⁷ - Document known broken OpenMPI builds
- PR #3716³⁴⁰⁸ - Add barrier reset function, requested by `hpxMP` for reusing barrier
- PR #3715³⁴⁰⁹ - More work on functions and vttables
- PR #3714³⁴¹⁰ - Generate single-page HTML, PDF, manpage from documentation
- PR #3713³⁴¹¹ - Updating default APEX version to 2.1.2
- PR #3712³⁴¹² - Update release procedure
- PR #3710³⁴¹³ - Fix the C++11 build, after #3704

³³⁹¹ <https://github.com/TheHPXProject/hpx/pull/3749>

³³⁹² <https://github.com/TheHPXProject/hpx/pull/3748>

³³⁹³ <https://github.com/TheHPXProject/hpx/pull/3747>

³³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3745>

³³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3742>

³³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3740>

³³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3739>

³³⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3737>

³³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3736>

³⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3734>

³⁴⁰¹ <https://github.com/TheHPXProject/hpx/pull/3732>

³⁴⁰² <https://github.com/TheHPXProject/hpx/pull/3730>

³⁴⁰³ <https://github.com/TheHPXProject/hpx/pull/3729>

³⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3728>

³⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3727>

³⁴⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3726>

³⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3722>

³⁴⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3716>

³⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3715>

³⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/3714>

³⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/3713>

³⁴¹² <https://github.com/TheHPXProject/hpx/pull/3712>

³⁴¹³ <https://github.com/TheHPXProject/hpx/pull/3710>

- PR #3709³⁴¹⁴ - Move some component_registry functionality to source file
- PR #3708³⁴¹⁵ - Ignore all locks while handling assertions
- PR #3707³⁴¹⁶ - Remove obsolete hpx runtime executable
- PR #3705³⁴¹⁷ - Fix and simplify make_ready_future overload sets
- PR #3704³⁴¹⁸ - Reduce use of binders
- PR #3703³⁴¹⁹ - Ini
- PR #3702³⁴²⁰ - Fixing CUDA compiler errors
- PR #3700³⁴²¹ - Added barrier::increment function to increase total number of thread
- PR #3697³⁴²² - One more attempt to fix migration...
- PR #3694³⁴²³ - Fixing component migration
- PR #3693³⁴²⁴ - Print thread state when getting disallowed value in set_thread_state
- PR #3692³⁴²⁵ - Only disable constexpr with clang-cuda, not nvcc+gcc
- PR #3691³⁴²⁶ - Link with libsupc++ if needed for thread_local
- PR #3690³⁴²⁷ - Remove thousands separators in set_operations_3442 to comply with C++11
- PR #3688³⁴²⁸ - Decouple serialization from function vtables
- PR #3687³⁴²⁹ - Fix a couple of test failures
- PR #3686³⁴³⁰ - Make sure tests.unit.build are run after install on CircleCI
- PR #3685³⁴³¹ - Revise quickstart CMakeLists.txt explanation
- PR #3684³⁴³² - Provide concept emulation for Ranges-TS concepts
- PR #3683³⁴³³ - Ignore uninitialized chunks
- PR #3682³⁴³⁴ - Ignore uninitialized chunks. Check proper indices.
- PR #3680³⁴³⁵ - Ignore uninitialized chunks. Check proper range indices
- PR #3679³⁴³⁶ - Simplify basic action implementations

³⁴¹⁴ <https://github.com/TheHPXProject/hpx/pull/3709>

³⁴¹⁵ <https://github.com/TheHPXProject/hpx/pull/3708>

³⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/3707>

³⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/3705>

³⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/3704>

³⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/3703>

³⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/3702>

³⁴²¹ <https://github.com/TheHPXProject/hpx/pull/3700>

³⁴²² <https://github.com/TheHPXProject/hpx/pull/3697>

³⁴²³ <https://github.com/TheHPXProject/hpx/pull/3694>

³⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/3693>

³⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/3692>

³⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/3691>

³⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/3690>

³⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/3688>

³⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/3687>

³⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/3686>

³⁴³¹ <https://github.com/TheHPXProject/hpx/pull/3685>

³⁴³² <https://github.com/TheHPXProject/hpx/pull/3684>

³⁴³³ <https://github.com/TheHPXProject/hpx/pull/3683>

³⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/3682>

³⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/3680>

³⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/3679>

- PR #3678³⁴³⁷ - Making sure HPX_HAVE_LIBATOMIC is unset before checking
- PR #3677³⁴³⁸ - Fix generated full version number to be usable in expressions
- PR #3674³⁴³⁹ - Reduce functional utilities call depth
- PR #3672³⁴⁴⁰ - Change new build system to use existing macros related to pseudo dependencies
- PR #3669³⁴⁴¹ - Remove indirection in `function_ref` when thread description is disabled
- PR #3668³⁴⁴² - Unbreaking `async_*cb*` tests
- PR #3667³⁴⁴³ - Generate `version.hpp`
- PR #3665³⁴⁴⁴ - Enabling MPI parcelport for gitlab runners
- PR #3664³⁴⁴⁵ - making clang-tidy work properly again
- PR #3662³⁴⁴⁶ - Attempt to fix exception handling
- PR #3661³⁴⁴⁷ - Move `lcos::latch` to source file
- PR #3660³⁴⁴⁸ - Fix accidentally explicit `gid_type` default constructor
- PR #3659³⁴⁴⁹ - Parallel executor latch
- PR #3658³⁴⁵⁰ - Fixing `execution_parameters`
- PR #3657³⁴⁵¹ - Avoid dangling references in `wait_all`
- PR #3656³⁴⁵² - Avoiding lifetime problems with `sync_put_parcel`
- PR #3655³⁴⁵³ - Fixing `nullptr` dereference inside of function
- PR #3652³⁴⁵⁴ - Attempt to fix `thread_map_type` definition with C++11
- PR #3650³⁴⁵⁵ - Allowing for end iterator being different from begin iterator
- PR #3649³⁴⁵⁶ - Added architecture identification to cmake to be able to detect timestamp support
- PR #3645³⁴⁵⁷ - Enabling sanitizers on gitlab runner
- PR #3644³⁴⁵⁸ - Attempt to tackle timeouts during startup
- PR #3642³⁴⁵⁹ - Cleanup parallel partitioners

³⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/3678>

³⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/3677>

³⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/3674>

³⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3672>

³⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/3669>

³⁴⁴² <https://github.com/TheHPXProject/hpx/pull/3668>

³⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/3667>

³⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3665>

³⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3664>

³⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3662>

³⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3661>

³⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3660>

³⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3659>

³⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3658>

³⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/3657>

³⁴⁵² <https://github.com/TheHPXProject/hpx/pull/3656>

³⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/3655>

³⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3652>

³⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3650>

³⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3649>

³⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3645>

³⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3644>

³⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3642>

- PR #3640³⁴⁶⁰ - Dataflow now works with functions that return a reference
- PR #3637³⁴⁶¹ - Merging the executor-enabled overloads of `shared_future<>::then`
- PR #3633³⁴⁶² - Replace deprecated boost endian macros
- PR #3632³⁴⁶³ - Add instructions on getting HPX to documentation
- PR #3631³⁴⁶⁴ - Simplify parcel creation
- PR #3630³⁴⁶⁵ - Small additions and fixes to release procedure
- PR #3629³⁴⁶⁶ - Modular pp
- PR #3627³⁴⁶⁷ - Implement `util::function_ref`
- PR #3626³⁴⁶⁸ - Fix cancelable_action_client example
- PR #3625³⁴⁶⁹ - Added automatic serialization for simple structs (see #3034)
- PR #3624³⁴⁷⁰ - Updating the default order of priority for `thread_description`
- PR #3621³⁴⁷¹ - Update copyright year and other small formatting fixes
- PR #3620³⁴⁷² - Adding support for gitlab runner
- PR #3619³⁴⁷³ - Store debug logs and core dumps on CircleCI
- PR #3618³⁴⁷⁴ - Various optimizations
- PR #3617³⁴⁷⁵ - Fix link to the gpg key (#2)
- PR #3615³⁴⁷⁶ - Fix unused variable warnings with networking off
- PR #3614³⁴⁷⁷ - Restructuring counter data in scheduler to reduce false sharing
- PR #3613³⁴⁷⁸ - Adding support for gitlab runners
- PR #3610³⁴⁷⁹ - Don't wait for `stop_condition` in main thread
- PR #3608³⁴⁸⁰ - Add inline keyword to `invalid_thread_id` definition for nvcc
- PR #3607³⁴⁸¹ - Adding configuration key that allows one to explicitly add a directory to the component search path
- PR #3606³⁴⁸² - Add nvcc to exclude constexpress since is it not supported by nvcc

³⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3640>

³⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/3637>

³⁴⁶² <https://github.com/TheHPXProject/hpx/pull/3633>

³⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/3632>

³⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3631>

³⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3630>

³⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3629>

³⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3627>

³⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3626>

³⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3625>

³⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3624>

³⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/3621>

³⁴⁷² <https://github.com/TheHPXProject/hpx/pull/3620>

³⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/3619>

³⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3618>

³⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3617>

³⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3615>

³⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3614>

³⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3613>

³⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3610>

³⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3608>

³⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/3607>

³⁴⁸² <https://github.com/TheHPXProject/hpx/pull/3606>

- PR #3605³⁴⁸³ - Add `inline` to definition of checkpoint stream operators to fix link error
- PR #3604³⁴⁸⁴ - Use format for string formatting
- PR #3603³⁴⁸⁵ - Improve the error message for using to less `MAX_CPU_COUNT`
- PR #3602³⁴⁸⁶ - Improve the error message for to small values of `MAX_CPU_COUNT`
- PR #3600³⁴⁸⁷ - Parallel executor aggregated
- PR #3599³⁴⁸⁸ - Making sure networking is disabled for default one-locality-runs
- PR #3596³⁴⁸⁹ - Store thread exit functions in `forward_list` instead of `deque` to avoid allocations
- PR #3590³⁴⁹⁰ - Fix typo/mistake in thread queue `cleanup_terminated`
- PR #3588³⁴⁹¹ - Fix formatting errors in `launching_and_configuring_hpx_applications.rst`
- PR #3586³⁴⁹² - Make `bind` propagate value category
- PR #3585³⁴⁹³ - Extend Cmake for building `hpx` as distribution packages (refs #3575)
- PR #3584³⁴⁹⁴ - Untangle function storage from object pointer
- PR #3582³⁴⁹⁵ - Towards Modularized HPX
- PR #3580³⁴⁹⁶ - Remove extra `||` in `merge.hpp`
- PR #3577³⁴⁹⁷ - Partially revert “Remove vtable empty flag”
- PR #3576³⁴⁹⁸ - Make sure empty startup/shutdown functions are not being used
- PR #3574³⁴⁹⁹ - Make sure `DATAPAR` settings are conveyed to depending projects
- PR #3573³⁵⁰⁰ - Make sure HPX is usable with latest released version of Vc (V1.4.1)
- PR #3572³⁵⁰¹ - Adding test ensuring ticket 3565 is fixed
- PR #3571³⁵⁰² - Make empty `[unique_]` function vtable non-dependent
- PR #3566³⁵⁰³ - Fix compilation with dynamic bitset for CPU masks
- PR #3563³⁵⁰⁴ - Drop `util::[unique_]function target_type`
- PR #3562³⁵⁰⁵ - Removing the target suffixes

³⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/3605>

³⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3604>

³⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3603>

³⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3602>

³⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3600>

³⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3599>

³⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3596>

³⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3590>

³⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/3588>

³⁴⁹² <https://github.com/TheHPXProject/hpx/pull/3586>

³⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/3585>

³⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3584>

³⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3582>

³⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3580>

³⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3577>

³⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3576>

³⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3574>

³⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3573>

³⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/3572>

³⁵⁰² <https://github.com/TheHPXProject/hpx/pull/3571>

³⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/3566>

³⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3563>

³⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3562>

- PR #3561³⁵⁰⁶ - Replace executor traits return type deduction (keep non-SFINAE)
- PR #3557³⁵⁰⁷ - Replace the last usages of `boost::atomic`
- PR #3556³⁵⁰⁸ - Replace `boost::scoped_array` with `std::unique_ptr`
- PR #3552³⁵⁰⁹ - (Re)move APEX readme
- PR #3548³⁵¹⁰ - Replace `boost::scoped_ptr` with `std::unique_ptr`
- PR #3547³⁵¹¹ - Remove last use of `Boost.Signals2`
- PR #3544³⁵¹² - Post 1.2.0 version bumps
- PR #3543³⁵¹³ - added Ubuntu dependency list to readme
- PR #3531³⁵¹⁴ - Warnings, warnings...
- PR #3527³⁵¹⁵ - Add CircleCI filter for building all tags
- PR #3525³⁵¹⁶ - Segmented algorithms
- PR #3517³⁵¹⁷ - Replace `boost::regex` with C++11 `<regex>`
- PR #3514³⁵¹⁸ - Cleaning up the build system
- PR #3505³⁵¹⁹ - Fixing type attribute warning for `transfer_action`
- PR #3504³⁵²⁰ - Add support for rpm packaging
- PR #3499³⁵²¹ - Improving spinlock pools
- PR #3498³⁵²² - Remove thread specific ptr
- PR #3486³⁵²³ - Fix comparison for `expect_connecting_localities` config entry
- PR #3469³⁵²⁴ - Enable (existing) code for extracting stack pointer on Power platform

³⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3561>

³⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3557>

³⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3556>

³⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3552>

³⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/3548>

³⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/3547>

³⁵¹² <https://github.com/TheHPXProject/hpx/pull/3544>

³⁵¹³ <https://github.com/TheHPXProject/hpx/pull/3543>

³⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/3531>

³⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/3527>

³⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/3525>

³⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/3517>

³⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/3514>

³⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/3505>

³⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/3504>

³⁵²¹ <https://github.com/TheHPXProject/hpx/pull/3499>

³⁵²² <https://github.com/TheHPXProject/hpx/pull/3498>

³⁵²³ <https://github.com/TheHPXProject/hpx/pull/3486>

³⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/3469>

HPX V1.2.1 (Feb 19, 2019)

General changes

This is a bugfix release. It contains the following changes:

- Fix compilation on ARM, s390x and 32-bit architectures.
- Fix a critical bug in the `future` implementation.
- Fix several problems in the CMake configuration which affects external projects.
- Add support for Boost 1.69.0.

Closed issues

- Issue #3638³⁵²⁵ - Build HPX 1.2 with boost 1.69
- Issue #3635³⁵²⁶ - Non-deterministic crashing on Stampede2
- Issue #3550³⁵²⁷ - `1>e:000workhpxsrcthrow_exception.cpp(54): error C2440: '<function-style-cast>': cannot convert from 'boost::system::error_code' to 'hpx::exception'`
- Issue #3549³⁵²⁸ - HPX 1.2.0 does not build on i686, but release candidate did
- Issue #3511³⁵²⁹ - Build on s390x fails
- Issue #3509³⁵³⁰ - Build on armv7l fails

Closed pull requests

- PR #3695³⁵³¹ - Don't install CMake templates and packaging files
- PR #3666³⁵³² - Fixing yet another race in `future_data`
- PR #3663³⁵³³ - Fixing race between setting and getting the value inside `future_data`
- PR #3648³⁵³⁴ - Adding timestamp option for S390x platform
- PR #3647³⁵³⁵ - Blind attempt to fix warnings issued by gcc V9
- PR #3611³⁵³⁶ - Include `GNUInstallDirs` earlier to have it available for subdirectories
- PR #3595³⁵³⁷ - Use `GNUInstallDirs` lib path in `pkgconfig` config file
- PR #3593³⁵³⁸ - Add `include(GNUInstallDirs)` to `HPXMacros.cmake`

³⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/3638>

³⁵²⁶ <https://github.com/TheHPXProject/hpx/issues/3635>

³⁵²⁷ <https://github.com/TheHPXProject/hpx/issues/3550>

³⁵²⁸ <https://github.com/TheHPXProject/hpx/issues/3549>

³⁵²⁹ <https://github.com/TheHPXProject/hpx/issues/3511>

³⁵³⁰ <https://github.com/TheHPXProject/hpx/issues/3509>

³⁵³¹ <https://github.com/TheHPXProject/hpx/pull/3695>

³⁵³² <https://github.com/TheHPXProject/hpx/pull/3666>

³⁵³³ <https://github.com/TheHPXProject/hpx/pull/3663>

³⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/3648>

³⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/3647>

³⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/3611>

³⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/3595>

³⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/3593>

- PR #3591³⁵³⁹ - Fix compilation error on arm7 architecture. Compiles and runs on Fedora 29 on Pi 3.
- PR #3558³⁵⁴⁰ - Adding constructor *exception(boost::system::error_code const&)*
- PR #3555³⁵⁴¹ - cmake: make install locations configurable
- PR #3551³⁵⁴² - Fix uint64_t causing compilation fail on i686

HPX V1.2.0 (Nov 12, 2018)

General changes

Here are some of the main highlights and changes for this release:

- Thanks to the work of our Google Summer of Code student, Nikunj Gupta, we now have a new implementation of `hpx_main.hpp` on supported platforms (Linux, BSD and MacOS). This is intended to be a less fragile drop-in replacement for the old implementation relying on preprocessor macros. The new implementation does not require changes if you are using the `CMake`³⁵⁴³ or `pkg-config`. The old behaviour can be restored by setting `HPX_WITH_DYNAMIC_HPX_MAIN=OFF` during `CMake`³⁵⁴⁴ configuration. The implementation on Windows is unchanged.
- We have added functionality to allow passing scheduling hints to our schedulers. These will allow us to create executors that for example target a specific NUMA domain or allow for *HPX* threads to be pinned to a particular worker thread.
- We have significantly improved the performance of our futures implementation by making the shared state atomic.
- We have replaced Boostbook by Sphinx for our documentation. This means the documentation is easier to navigate with built-in search and table of contents. We have also added a quick start section and restructured the documentation to be easier to follow for new users.
- We have added a new option to the `--hpx:threads` command line option. It is now possible to use `cores` to tell *HPX* to only use one worker thread per core, unlike the existing option `all` which uses one worker thread per processing unit (processing unit can be a hyperthread if hyperthreads are available). The default value of `--hpx:threads` has also been changed to `cores` as this leads to better performance in most cases.
- All command line options can now be passed alongside configuration options when initializing *HPX*. This means that some options that were previously only available on the command line can now be set as configuration options.
- *HPXMP* is a portable, scalable, and flexible application programming interface using the OpenMP specification that supports multi-platform shared memory multiprocessing programming in C and C++. *HPXMP* can be enabled within *HPX* by setting `DHPX_WITH_HPXMP=ON` during `CMake`³⁵⁴⁵ configuration.
- Two new performance counters were added for measuring the time spent doing background work. `/threads/time/background-work-duration` returns the time spent doing background on a given thread or locality, while `/threads/time/background-overhead` returns the fraction of time spent doing background work with respect to the overall time spent running the scheduler. The new performance counters are disabled by default and can be turned on by setting `HPX_WITH_BACKGROUND_THREAD_COUNTERS=ON` during `CMake`³⁵⁴⁶ configuration.

³⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/3591>

³⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3558>

³⁵⁴¹ <https://github.com/TheHPXProject/hpx/pull/3555>

³⁵⁴² <https://github.com/TheHPXProject/hpx/pull/3551>

³⁵⁴³ <https://www.cmake.org>

³⁵⁴⁴ <https://www.cmake.org>

³⁵⁴⁵ <https://www.cmake.org>

³⁵⁴⁶ <https://www.cmake.org>

- The idling behaviour of *HPX* has been tweaked to allow for faster idling. This is useful in interactive applications where the *HPX* worker threads may not have work all the time. This behaviour can be tweaked and turned off as before with `HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF=OFF` during [CMake](#)³⁵⁴⁷ configuration.
- It is now possible to register callback functions for *HPX* worker thread events. Callbacks can be registered for starting and stopping worker threads, and for when errors occur.

Breaking changes

- The implementation of `hpx_main.hpp` has changed. If you are using custom Makefiles you will need to make changes. Please see the documentation on *using Makefiles* for more details.
- The default value of `--hpx:threads` has changed from `all` to `cores`. The new option `cores` only starts one worker thread per core.
- We have dropped support for Boost 1.56 and 1.57. The minimal version of Boost we now test is 1.58.
- Our `boost::format`-based formatting implementation has been revised and replaced with a custom implementation. This changes the formatting syntax and requires changes if you are relying on `hpx::util::format` or `hpx::util::format_to`. The pull request for this change contains more information: [PR #3266](#)³⁵⁴⁸.
- The following deprecated options have now been completely removed:
`HPX_WITH_ASYNC_FUNCTION_COMPATIBILITY`, `HPX_WITH_LOCAL_DATAFLOW`,
`HPX_WITH_GENERIC_EXECUTION_POLICY`, `HPX_WITH_BOOST_CHRONO_COMPATIBILITY`,
`HPX_WITH_EXECUTOR_COMPATIBILITY`, `HPX_WITH_EXECUTION_POLICY_COMPATIBILITY`, and
`HPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY`.

Closed issues

- [Issue #3538](#)³⁵⁴⁹ - numa handling incorrect for hwloc 2
- [Issue #3533](#)³⁵⁵⁰ - Cmake version 3.5.1 does not work (git ff26b35 2018-11-06)
- [Issue #3526](#)³⁵⁵¹ - Failed building hpx-1.2.0-rc1 on Ubuntu16.04 x86-64 Virtualbox VM
- [Issue #3512](#)³⁵⁵² - Build on aarch64 fails
- [Issue #3475](#)³⁵⁵³ - HPX fails to link if the MPI parcellport is enabled
- [Issue #3462](#)³⁵⁵⁴ - CMake configuration shows a minor and inconsequential failure to create a symlink
- [Issue #3461](#)³⁵⁵⁵ - Compilation Problems with the most recent Clang
- [Issue #3460](#)³⁵⁵⁶ - Deadlock when create_partitioner fails (assertion fails) in debug mode
- [Issue #3455](#)³⁵⁵⁷ - HPX build failing with HWLOC errors on POWER8 with hwloc 1.8
- [Issue #3438](#)³⁵⁵⁸ - HPX no longer builds on IBM POWER8

³⁵⁴⁷ <https://www.cmake.org>

³⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3266>

³⁵⁴⁹ <https://github.com/TheHPXProject/hpx/issues/3538>

³⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/3533>

³⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/3526>

³⁵⁵² <https://github.com/TheHPXProject/hpx/issues/3512>

³⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/3475>

³⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/3462>

³⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/3461>

³⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3460>

³⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3455>

³⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/3438>

- Issue #3426³⁵⁵⁹ - hpx build failed on MacOS
- Issue #3424³⁵⁶⁰ - CircleCI builds broken for forked repositories
- Issue #3422³⁵⁶¹ - Benchmarks in tests.performance.local are not run nightly
- Issue #3408³⁵⁶² - CMake Targets for HPX
- Issue #3399³⁵⁶³ - processing unit out of bounds
- Issue #3395³⁵⁶⁴ - Floating point bug in hpx/runtime/threads/policies/scheduler_base.hpp
- Issue #3378³⁵⁶⁵ - compile error with lcos::communicator
- Issue #3376³⁵⁶⁶ - Failed to build HPX with APEX using clang
- Issue #3366³⁵⁶⁷ - Adapted Safe_Object example fails for `-hpx:threads > 1`
- Issue #3360³⁵⁶⁸ - Segmentation fault when passing component id as parameter
- Issue #3358³⁵⁶⁹ - HPX runtime hangs after multiple (~thousands) start-stop sequences
- Issue #3352³⁵⁷⁰ - Support TCP provider in libfabric ParcelPort
- Issue #3342³⁵⁷¹ - undefined reference to `__atomic_load_16`
- Issue #3339³⁵⁷² - setting command line options/flags from init cfg is not obvious
- Issue #3325³⁵⁷³ - AGAS migrates components prematurely
- Issue #3321³⁵⁷⁴ - hpx bad_parameter handling is awful
- Issue #3318³⁵⁷⁵ - Benchmarks fail to build with C++11
- Issue #3304³⁵⁷⁶ - `hpx::threads::run_as_hpx_thread` does not properly handle exceptions
- Issue #3300³⁵⁷⁷ - Setting pu step or offset results in no threads in default pool
- Issue #3297³⁵⁷⁸ - Crash with APEX when running Phylaxx lra_csv with > 1 thread
- Issue #3296³⁵⁷⁹ - Building HPX with APEX configuration gives compiler warnings
- Issue #3290³⁵⁸⁰ - make tests failing at hello_world_component
- Issue #3285³⁵⁸¹ - possible compilation error when “using namespace std;” is defined before including “hpx” headers files

³⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/3426>

³⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/3424>

³⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/3422>

³⁵⁶² <https://github.com/TheHPXProject/hpx/issues/3408>

³⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/3399>

³⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/3395>

³⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/3378>

³⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/3376>

³⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/3366>

³⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/3360>

³⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/3358>

³⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/3352>

³⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/3342>

³⁵⁷² <https://github.com/TheHPXProject/hpx/issues/3339>

³⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/3325>

³⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/3321>

³⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/3318>

³⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/3304>

³⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/3300>

³⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/3297>

³⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/3296>

³⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/3290>

³⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/3285>

- Issue #3280³⁵⁸² - HPX fails on OSX
- Issue #3272³⁵⁸³ - CircleCI does not upload generated docker image any more
- Issue #3270³⁵⁸⁴ - Error when compiling CUDA examples
- Issue #3267³⁵⁸⁵ - `tests.unit.host_.block_allocator` fails occasionally
- Issue #3264³⁵⁸⁶ - Possible move to Sphinx for documentation
- Issue #3263³⁵⁸⁷ - Documentation improvements
- Issue #3259³⁵⁸⁸ - `set_parcel_write_handler` test fails occasionally
- Issue #3258³⁵⁸⁹ - Links to source code in documentation are broken
- Issue #3247³⁵⁹⁰ - Rare `tests.unit.host_.block_allocator` test failure on 1.1.0-rc1
- Issue #3244³⁵⁹¹ - Slowing down and speeding up an `interval_timer`
- Issue #3215³⁵⁹² - Cannot build both tests and examples on MSVC with pseudo-dependencies enabled
- Issue #3195³⁵⁹³ - Unnecessary customization point route causing performance penalty
- Issue #3088³⁵⁹⁴ - A strange thing in `parallel::sort`.
- Issue #2650³⁵⁹⁵ - libfabric support for passive endpoints
- Issue #1205³⁵⁹⁶ - TSS is broken

Closed pull requests

- PR #3542³⁵⁹⁷ - Fix numa lookup from pu when using hwloc 2.x
- PR #3541³⁵⁹⁸ - Fixing the build system of the MPI parcelport
- PR #3540³⁵⁹⁹ - Updating HPX people section
- PR #3539³⁶⁰⁰ - Splitting test to avoid OOM on CircleCI
- PR #3537³⁶⁰¹ - Fix guided exec
- PR #3536³⁶⁰² - Updating grants which support the LSU team
- PR #3535³⁶⁰³ - Fix hiding of docker credentials

³⁵⁸² <https://github.com/TheHPXProject/hpx/issues/3280>

³⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/3272>

³⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/3270>

³⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/3267>

³⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/3264>

³⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3263>

³⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/3259>

³⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/3258>

³⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/3247>

³⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/3244>

³⁵⁹² <https://github.com/TheHPXProject/hpx/issues/3215>

³⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/3195>

³⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/3088>

³⁵⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2650>

³⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1205>

³⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3542>

³⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3541>

³⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3540>

³⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3539>

³⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/3537>

³⁶⁰² <https://github.com/TheHPXProject/hpx/pull/3536>

³⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/3535>

- PR #3534³⁶⁰⁴ - Fixing #3533
- PR #3532³⁶⁰⁵ - fixing minor doc typo `-hpx:print-counter-at` arg
- PR #3530³⁶⁰⁶ - Changing APEX default tag to v2.1.0
- PR #3529³⁶⁰⁷ - Remove leftover security options and documentation
- PR #3528³⁶⁰⁸ - Fix hwloc version check
- PR #3524³⁶⁰⁹ - Do not build guided pool examples with older GCC compilers
- PR #3523³⁶¹⁰ - Fix logging regression
- PR #3522³⁶¹¹ - Fix more warnings
- PR #3521³⁶¹² - Fixing argument handling in induction and reduction clauses for `parallel::for_loop`
- PR #3520³⁶¹³ - Remove docs symlink and versioned docs folders
- PR #3519³⁶¹⁴ - hpxMP release
- PR #3518³⁶¹⁵ - Change all steps to use new docker image on CircleCI
- PR #3516³⁶¹⁶ - Drop usage of deprecated facilities removed in C++17
- PR #3515³⁶¹⁷ - Remove remaining uses of `Boost.TypeTraits`
- PR #3513³⁶¹⁸ - Fixing a CMake problem when trying to use `libfabric`
- PR #3508³⁶¹⁹ - Remove `memory_block` component
- PR #3507³⁶²⁰ - Propagating the MPI compile definitions to all relevant targets
- PR #3503³⁶²¹ - Update documentation colors and logo
- PR #3502³⁶²² - Fix bogus ``throws`` bindings in `scheduled_thread_pool_impl`
- PR #3501³⁶²³ - Split `parallel::remove_if` tests to avoid OOM on CircleCI
- PR #3500³⁶²⁴ - Support `NONAMEPREFIX` in `add_hpx_library()`
- PR #3497³⁶²⁵ - Note that cuda support requires cmake 3.9
- PR #3495³⁶²⁶ - Fixing dataflow

³⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3534>

³⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3532>

³⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3530>

³⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3529>

³⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3528>

³⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3524>

³⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/3523>

³⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/3522>

³⁶¹² <https://github.com/TheHPXProject/hpx/pull/3521>

³⁶¹³ <https://github.com/TheHPXProject/hpx/pull/3520>

³⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/3519>

³⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/3518>

³⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/3516>

³⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/3515>

³⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/3513>

³⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/3508>

³⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/3507>

³⁶²¹ <https://github.com/TheHPXProject/hpx/pull/3503>

³⁶²² <https://github.com/TheHPXProject/hpx/pull/3502>

³⁶²³ <https://github.com/TheHPXProject/hpx/pull/3501>

³⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/3500>

³⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/3497>

³⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/3495>

- PR #3493³⁶²⁷ - Remove deprecated options for 1.2.0 part 2
- PR #3492³⁶²⁸ - Add CUDA_LINK_LIBRARIES_KEYWORD to allow PRIVATE keyword in linkage t...
- PR #3491³⁶²⁹ - Changing Base docker image
- PR #3490³⁶³⁰ - Don't create tasks immediately with hpx::apply
- PR #3489³⁶³¹ - Remove deprecated options for 1.2.0
- PR #3488³⁶³² - Revert "Use BUILD_INTERFACE generator expression to fix cmake flag exports"
- PR #3487³⁶³³ - Revert "Fixing type attribute warning for transfer_action"
- PR #3485³⁶³⁴ - Use BUILD_INTERFACE generator expression to fix cmake flag exports
- PR #3483³⁶³⁵ - Fixing type attribute warning for transfer_action
- PR #3481³⁶³⁶ - Remove unused variables
- PR #3480³⁶³⁷ - Towards a more lightweight transfer action
- PR #3479³⁶³⁸ - Fix FLAGS - Use correct version of target_compile_options
- PR #3478³⁶³⁹ - Making sure the application's exit code is properly propagated back to the OS
- PR #3476³⁶⁴⁰ - Don't print docker credentials as part of the environment.
- PR #3473³⁶⁴¹ - Fixing invalid cmake code if no jemalloc prefix was given
- PR #3472³⁶⁴² - Attempting to work around recent clang test compilation failures
- PR #3471³⁶⁴³ - Enable jemalloc on windows
- PR #3470³⁶⁴⁴ - Updates readme
- PR #3468³⁶⁴⁵ - Avoid hang if there is an exception thrown during startup
- PR #3467³⁶⁴⁶ - Add compiler specific fallback attributes if C++17 attribute is not available
- PR #3466³⁶⁴⁷ - - bugfix : fix compilation with llvm-7.0
- PR #3465³⁶⁴⁸ - This patch adds various optimizations extracted from the thread_local_allocator work
- PR #3464³⁶⁴⁹ - Check for forked repos in CircleCI docker push step

³⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/3493>

³⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/3492>

³⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/3491>

³⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/3490>

³⁶³¹ <https://github.com/TheHPXProject/hpx/pull/3489>

³⁶³² <https://github.com/TheHPXProject/hpx/pull/3488>

³⁶³³ <https://github.com/TheHPXProject/hpx/pull/3487>

³⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/3485>

³⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/3483>

³⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/3481>

³⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/3480>

³⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/3479>

³⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/3478>

³⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3476>

³⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/3473>

³⁶⁴² <https://github.com/TheHPXProject/hpx/pull/3472>

³⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/3471>

³⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3470>

³⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3468>

³⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3467>

³⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3466>

³⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3465>

³⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3464>

- PR #3463³⁶⁵⁰ - - cmake : create the parent directory before symlinking
- PR #3459³⁶⁵¹ - Remove unused/incomplete functionality from util/logging
- PR #3458³⁶⁵² - Fix a problem with scope of CMAKE_CXX_FLAGS and hpx_add_compile_flag
- PR #3457³⁶⁵³ - Fixing more size_t -> int16_t (and similar) warnings
- PR #3456³⁶⁵⁴ - Add #ifdefs to topology.cpp to support old hwloc versions again
- PR #3454³⁶⁵⁵ - Fixing warnings related to silent conversion of size_t -> int16_t
- PR #3451³⁶⁵⁶ - Add examples as unit tests
- PR #3450³⁶⁵⁷ - Constexpr-fying bind and other functional facilities
- PR #3446³⁶⁵⁸ - Fix some thread suspension timeouts
- PR #3445³⁶⁵⁹ - Fix various warnings
- PR #3443³⁶⁶⁰ - Only enable service pool config options if pools are enabled
- PR #3441³⁶⁶¹ - Fix missing closing brackets in documentation
- PR #3439³⁶⁶² - Use correct MPI CXX libraries for MPI parcelport
- PR #3436³⁶⁶³ - Add projection function to find_* (and fix very bad bug)
- PR #3435³⁶⁶⁴ - Fixing 1205
- PR #3434³⁶⁶⁵ - Fix threads cores
- PR #3433³⁶⁶⁶ - Add Heise Online to release announcement list
- PR #3432³⁶⁶⁷ - Don't track task dependencies for distributed runs
- PR #3431³⁶⁶⁸ - Circle CI setting changes for hpxMP
- PR #3430³⁶⁶⁹ - Fix unused params warning
- PR #3429³⁶⁷⁰ - One thread per core
- PR #3428³⁶⁷¹ - This suppresses a deprecation warning that is being issued by MSVC 19.15.26726
- PR #3427³⁶⁷² - Fixes #3426

³⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3463>

³⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/3459>

³⁶⁵² <https://github.com/TheHPXProject/hpx/pull/3458>

³⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/3457>

³⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3456>

³⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3454>

³⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3451>

³⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3450>

³⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3446>

³⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3445>

³⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3443>

³⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/3441>

³⁶⁶² <https://github.com/TheHPXProject/hpx/pull/3439>

³⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/3436>

³⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3435>

³⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3434>

³⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3433>

³⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3432>

³⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3431>

³⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3430>

³⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3429>

³⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/3428>

³⁶⁷² <https://github.com/TheHPXProject/hpx/pull/3427>

- PR #3425³⁶⁷³ - Use source cache and workspace between job steps on CircleCI
- PR #3421³⁶⁷⁴ - Add CDash timing output to future overhead test (for graphs)
- PR #3420³⁶⁷⁵ - Add guided_pool_executor
- PR #3419³⁶⁷⁶ - Fix typo in CircleCI config
- PR #3418³⁶⁷⁷ - Add sphinx documentation
- PR #3415³⁶⁷⁸ - Scheduler NUMA hint and shared priority scheduler
- PR #3414³⁶⁷⁹ - Adding step to synchronize the APEX release
- PR #3413³⁶⁸⁰ - Fixing multiple defines of APEX_HAVE_HPX
- PR #3412³⁶⁸¹ - Fixes linking with libhpx_wrap error with BSD and Windows based systems
- PR #3410³⁶⁸² - Fix typo in CMakeLists.txt
- PR #3409³⁶⁸³ - Fix brackets and indentation in existing_performance_counters.qbk
- PR #3407³⁶⁸⁴ - Fix unused param and extra ; warnings emitted by gcc 8.x
- PR #3406³⁶⁸⁵ - Adding thread local allocator and use it for future shared states
- PR #3405³⁶⁸⁶ - Adding DHPX_HAVE_THREAD_LOCAL_STORAGE=ON to builds
- PR #3404³⁶⁸⁷ - fixing multiple definition of main() in linux
- PR #3402³⁶⁸⁸ - Allow debug option to be enabled only for Linux systems with dynamic main on
- PR #3401³⁶⁸⁹ - Fix cuda_future_helper.h when compiling with C++11
- PR #3400³⁶⁹⁰ - Fix floating point exception scheduler_base idle backoff
- PR #3398³⁶⁹¹ - Atomic future state
- PR #3397³⁶⁹² - Fixing code for older gcc versions
- PR #3396³⁶⁹³ - Allowing to register thread event functions (start/stop/error)
- PR #3394³⁶⁹⁴ - Fix small mistake in primary_namespace_server.cpp
- PR #3393³⁶⁹⁵ - Explicitly instantiate configured schedulers

³⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/3425>

³⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3421>

³⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3420>

³⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3419>

³⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3418>

³⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3415>

³⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3414>

³⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3413>

³⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/3412>

³⁶⁸² <https://github.com/TheHPXProject/hpx/pull/3410>

³⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/3409>

³⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3407>

³⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3406>

³⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3405>

³⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3404>

³⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3402>

³⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3401>

³⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3400>

³⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/3398>

³⁶⁹² <https://github.com/TheHPXProject/hpx/pull/3397>

³⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/3396>

³⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3394>

³⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3393>

- PR #3392³⁶⁹⁶ - Add performance counters background overhead and background work duration
- PR #3391³⁶⁹⁷ - Adapt integration of HPXMP to latest build system changes
- PR #3390³⁶⁹⁸ - Make AGAS measurements optional
- PR #3389³⁶⁹⁹ - Fix deadlock during shutdown
- PR #3388³⁷⁰⁰ - Add several functionalities allowing to optimize synchronous action invocation
- PR #3387³⁷⁰¹ - Add cmake option to opt out of fail-compile tests
- PR #3386³⁷⁰² - Adding support for boost::container::small_vector to dataflow
- PR #3385³⁷⁰³ - Adds Debug option for hpx initializing from main
- PR #3384³⁷⁰⁴ - This hopefully fixes two tests that occasionally fail
- PR #3383³⁷⁰⁵ - Making sure thread local storage is enable for hpxMP
- PR #3382³⁷⁰⁶ - Fix usage of HPX_CAPTURE together with default value capture [=]
- PR #3381³⁷⁰⁷ - Replace undefined instantiations of uniform_int_distribution
- PR #3380³⁷⁰⁸ - Add missing semicolons to uses of HPX_COMPILER_FENCE
- PR #3379³⁷⁰⁹ - Fixing #3378
- PR #3377³⁷¹⁰ - Adding build system support to integrate hpxmp into hpx at the user's machine
- PR #3375³⁷¹¹ - Replacing wrapper for __libc_start_main with main
- PR #3374³⁷¹² - Adds hpx_wrap to HPX_LINK_LIBRARIES which links only when specified.
- PR #3373³⁷¹³ - Forcing cache settings in HPXConfig.cmake to guarantee updated values
- PR #3372³⁷¹⁴ - Fix some more c++11 build problems
- PR #3371³⁷¹⁵ - Adds HPX_LINKER_FLAGS to HPX applications without editing their source codes
- PR #3370³⁷¹⁶ - util::format: add type_specifier<> specializations for %!s(MISSING) and %!l(MISSING)s
- PR #3369³⁷¹⁷ - Adding configuration option to allow explicit disable of the new hpx_main feature on Linux
- PR #3368³⁷¹⁸ - Updates doc with recent hpx_wrap implementation

³⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3392>

³⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3391>

³⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3390>

³⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3389>

³⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3388>

³⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/3387>

³⁷⁰² <https://github.com/TheHPXProject/hpx/pull/3386>

³⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/3385>

³⁷⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3384>

³⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3383>

³⁷⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3382>

³⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3381>

³⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3380>

³⁷⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3379>

³⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/3377>

³⁷¹¹ <https://github.com/TheHPXProject/hpx/pull/3375>

³⁷¹² <https://github.com/TheHPXProject/hpx/pull/3374>

³⁷¹³ <https://github.com/TheHPXProject/hpx/pull/3373>

³⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/3372>

³⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/3371>

³⁷¹⁶ <https://github.com/TheHPXProject/hpx/pull/3370>

³⁷¹⁷ <https://github.com/TheHPXProject/hpx/pull/3369>

³⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/3368>

- PR #3367³⁷¹⁹ - Adds Mac OS implementation to hpx_main.hpp
- PR #3365³⁷²⁰ - Fix order of hpx libs in HPX_CONF_LIBRARIES.
- PR #3363³⁷²¹ - Apex fixing null wrapper
- PR #3361³⁷²² - Making sure all parcels get destroyed on an HPX thread (TCP pp)
- PR #3359³⁷²³ - Feature/improve error for compiler
- PR #3357³⁷²⁴ - Static/dynamic executable implementation
- PR #3355³⁷²⁵ - Reverting changes introduced by #3283 as those make applications hang
- PR #3354³⁷²⁶ - Add external dependencies to HPX_LIBRARY_DIR
- PR #3353³⁷²⁷ - Fix libfabric tcp
- PR #3351³⁷²⁸ - Move obsolete header to tests directory.
- PR #3350³⁷²⁹ - Renaming two functions to avoid problem described in #3285
- PR #3349³⁷³⁰ - Make idle backoff exponential with maximum sleep time
- PR #3347³⁷³¹ - Replace *simple_component** with *component** in the Documentation
- PR #3346³⁷³² - Fix CMakeLists.txt example in quick start
- PR #3345³⁷³³ - Fix automatic setting of HPX_MORE_THAN_64_THREADS
- PR #3344³⁷³⁴ - Reduce amount of information printed for unknown command line options
- PR #3343³⁷³⁵ - Safeguard HPX against destruction in global contexts
- PR #3341³⁷³⁶ - Allowing for all command line options to be used as configuration settings
- PR #3340³⁷³⁷ - Always convert inspect results to JUnit XML
- PR #3336³⁷³⁸ - Only run docker push on master on CircleCI
- PR #3335³⁷³⁹ - Update description of hpx.os_threads config parameter.
- PR #3334³⁷⁴⁰ - Making sure early logging settings don't get mixed with others
- PR #3333³⁷⁴¹ - Update CMake links and versions in documentation

³⁷¹⁹ <https://github.com/TheHPXProject/hpx/pull/3367>

³⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/3365>

³⁷²¹ <https://github.com/TheHPXProject/hpx/pull/3363>

³⁷²² <https://github.com/TheHPXProject/hpx/pull/3361>

³⁷²³ <https://github.com/TheHPXProject/hpx/pull/3359>

³⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/3357>

³⁷²⁵ <https://github.com/TheHPXProject/hpx/pull/3355>

³⁷²⁶ <https://github.com/TheHPXProject/hpx/pull/3354>

³⁷²⁷ <https://github.com/TheHPXProject/hpx/pull/3353>

³⁷²⁸ <https://github.com/TheHPXProject/hpx/pull/3351>

³⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/3350>

³⁷³⁰ <https://github.com/TheHPXProject/hpx/pull/3349>

³⁷³¹ <https://github.com/TheHPXProject/hpx/pull/3347>

³⁷³² <https://github.com/TheHPXProject/hpx/pull/3346>

³⁷³³ <https://github.com/TheHPXProject/hpx/pull/3345>

³⁷³⁴ <https://github.com/TheHPXProject/hpx/pull/3344>

³⁷³⁵ <https://github.com/TheHPXProject/hpx/pull/3343>

³⁷³⁶ <https://github.com/TheHPXProject/hpx/pull/3341>

³⁷³⁷ <https://github.com/TheHPXProject/hpx/pull/3340>

³⁷³⁸ <https://github.com/TheHPXProject/hpx/pull/3336>

³⁷³⁹ <https://github.com/TheHPXProject/hpx/pull/3335>

³⁷⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3334>

³⁷⁴¹ <https://github.com/TheHPXProject/hpx/pull/3333>

- PR #3332³⁷⁴² - Add notes on target suffixes to CMake documentation
- PR #3331³⁷⁴³ - Add quickstart section to documentation
- PR #3330³⁷⁴⁴ - Rename resource_partitioner test to avoid conflicts with pseudodependencies
- PR #3328³⁷⁴⁵ - Making sure object is pinned while executing actions, even if action returns a future
- PR #3327³⁷⁴⁶ - Add missing std::forward to tuple.hpp
- PR #3326³⁷⁴⁷ - Make sure logging is up and running while modules are being discovered.
- PR #3324³⁷⁴⁸ - Replace C++14 overload of std::equal with C++11 code.
- PR #3323³⁷⁴⁹ - Fix a missing apex thread data (wrapper) initialization
- PR #3320³⁷⁵⁰ - Adding support for -std=c++2a (define *HPX_WITH_CXX2A=On*)
- PR #3319³⁷⁵¹ - Replacing C++14 feature with equivalent C++11 code
- PR #3317³⁷⁵² - Fix compilation with VS 15.7.1 and /std:c++latest
- PR #3316³⁷⁵³ - Fix includes for 1d_stencil_*_omp examples
- PR #3314³⁷⁵⁴ - Remove some unused parameter warnings
- PR #3313³⁷⁵⁵ - Fix pu-step and pu-offset command line options
- PR #3312³⁷⁵⁶ - Add conversion of inspect reports to JUnit XML
- PR #3311³⁷⁵⁷ - Fix escaping of closing braces in format specification syntax
- PR #3310³⁷⁵⁸ - Don't overwrite user settings with defaults in registration database
- PR #3309³⁷⁵⁹ - Fixing potential stack overflow for dataflow
- PR #3308³⁷⁶⁰ - This updates the .clang-format configuration file to utilize newer features
- PR #3306³⁷⁶¹ - Marking migratable objects in their gid to allow not handling migration in AGAS
- PR #3305³⁷⁶² - Add proper exception handling to run_as_hpx_thread
- PR #3303³⁷⁶³ - Changed std::rand to a better inbuilt PRNG Generator
- PR #3302³⁷⁶⁴ - All non-migratable (simple) components now encode their lva and component type in their gid

³⁷⁴² <https://github.com/TheHPXProject/hpx/pull/3332>

³⁷⁴³ <https://github.com/TheHPXProject/hpx/pull/3331>

³⁷⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3330>

³⁷⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3328>

³⁷⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3327>

³⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3326>

³⁷⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3324>

³⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3323>

³⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3320>

³⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/3319>

³⁷⁵² <https://github.com/TheHPXProject/hpx/pull/3317>

³⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/3316>

³⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3314>

³⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3313>

³⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3312>

³⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3311>

³⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3310>

³⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3309>

³⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3308>

³⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/3306>

³⁷⁶² <https://github.com/TheHPXProject/hpx/pull/3305>

³⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/3303>

³⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3302>

- PR #3301³⁷⁶⁵ - Add nullptr_t overloads to resource partitioner
- PR #3298³⁷⁶⁶ - Apex task wrapper memory bug
- PR #3295³⁷⁶⁷ - Fix mistakes after merge of CircleCI config
- PR #3294³⁷⁶⁸ - Fix partitioned vector include in partitioned_vector_find tests
- PR #3293³⁷⁶⁹ - Adding emplace support to promise and make_ready_future
- PR #3292³⁷⁷⁰ - Add new cuda kernel synchronization with hpx::future demo
- PR #3291³⁷⁷¹ - Fixes #3290
- PR #3289³⁷⁷² - Fixing Docker image creation
- PR #3288³⁷⁷³ - Avoid allocating shared state for wait_all
- PR #3287³⁷⁷⁴ - Fixing /scheduler/utilization/instantaneous performance counter
- PR #3286³⁷⁷⁵ - dataflow() and future::then() use sync policy where possible
- PR #3284³⁷⁷⁶ - Background thread can use relaxed atomics to manipulate thread state
- PR #3283³⁷⁷⁷ - Do not unwrap ready future
- PR #3282³⁷⁷⁸ - Fix virtual method override warnings in static schedulers
- PR #3281³⁷⁷⁹ - Disable set_area_membind_nodeset for OSX
- PR #3279³⁷⁸⁰ - Add two variations to the future_overhead benchmark
- PR #3278³⁷⁸¹ - Fix circleci workspace
- PR #3277³⁷⁸² - Support external plugins
- PR #3276³⁷⁸³ - Fix missing parenthesis in hello_compute.cu.
- PR #3274³⁷⁸⁴ - Reinit counters synchronously in reinit_counters test
- PR #3273³⁷⁸⁵ - Splitting tests to avoid compiler OOM
- PR #3271³⁷⁸⁶ - Remove leftover code from context_generic_context.hpp
- PR #3269³⁷⁸⁷ - Fix bulk_construct with count = 0

³⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3301>

³⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3298>

³⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3295>

³⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3294>

³⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3293>

³⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3292>

³⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/3291>

³⁷⁷² <https://github.com/TheHPXProject/hpx/pull/3289>

³⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/3288>

³⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3287>

³⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3286>

³⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3284>

³⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3283>

³⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3282>

³⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3281>

³⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3279>

³⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/3278>

³⁷⁸² <https://github.com/TheHPXProject/hpx/pull/3277>

³⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/3276>

³⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3274>

³⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3273>

³⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3271>

³⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3269>

- [PR #3268³⁷⁸⁸](#) - Replace `constexpr` with `HPX_CXX14_CONSTEXPR` and `HPX_CONSTEXPR`
- [PR #3266³⁷⁸⁹](#) - Replace `boost::format` with custom `sprintf`-based implementation
- [PR #3265³⁷⁹⁰](#) - Split parallel tests on CircleCI
- [PR #3262³⁷⁹¹](#) - Making sure documentation correctly links to source files
- [PR #3261³⁷⁹²](#) - Apex refactoring fix rebind
- [PR #3260³⁷⁹³](#) - Isolate performance counter parser into a separate TU
- [PR #3256³⁷⁹⁴](#) - Post 1.1.0 version bumps
- [PR #3254³⁷⁹⁵](#) - Adding trait for actions allowing to make runtime decision on whether to execute it directly
- [PR #3253³⁷⁹⁶](#) - Bump minimal supported Boost to 1.58.0
- [PR #3251³⁷⁹⁷](#) - Adds new feature: changing interval used in `interval_timer` (issue 3244)
- [PR #3239³⁷⁹⁸](#) - Changing `std::rand()` to a better inbuilt PRNG generator.
- [PR #3234³⁷⁹⁹](#) - Disable background thread when networking is off
- [PR #3232³⁸⁰⁰](#) - Clean up suspension tests
- [PR #3230³⁸⁰¹](#) - Add optional scheduler mode parameter to `create_thread_pool` function
- [PR #3228³⁸⁰²](#) - Allow suspension also on static schedulers
- [PR #3163³⁸⁰³](#) - libfabric parcelport w/o `HPX_PARCELPORTR_LIBFABRIC_ENDPOINT_RDM`
- [PR #3036³⁸⁰⁴](#) - Switching to CircleCI 2.0

HPX V1.1.0 (Mar 24, 2018)

General changes

Here are some of the main highlights and changes for this release (in no particular order):

- We have changed the way *HPX* manages the processing units on a node. We do not longer implicitly bind all available cores to a single thread pool. The user has now full control over what processing units are bound to what thread pool, each with a separate scheduler. It is now also possible to create your own scheduler implementation and control what processing units this scheduler should use. We added the `hpx::resource::partitioner` that manages all available processing units and assigns resources to the used thread pools. Thread pools can be

³⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3268>

³⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3266>

³⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3265>

³⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/3262>

³⁷⁹² <https://github.com/TheHPXProject/hpx/pull/3261>

³⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/3260>

³⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3256>

³⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3254>

³⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3253>

³⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3251>

³⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3239>

³⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3234>

³⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3232>

³⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/3230>

³⁸⁰² <https://github.com/TheHPXProject/hpx/pull/3228>

³⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/3163>

³⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3036>

now be suspended/resumed independently. This functionality helps in running *HPX* concurrently to code that is directly relying on [OpenMP](https://openmp.org/wp/)³⁸⁰⁵ and/or [MPI](https://en.wikipedia.org/wiki/Message_Passing_Interface)³⁸⁰⁶.

- We have continued to implement various parallel algorithms. *HPX* now almost completely implements all of the parallel algorithms as specified by the [C++17 Standard](http://www.open-std.org/jtc1/sc22/wg21)³⁸⁰⁷. We have also continued to implement these algorithms for the distributed use case (for segmented data structures, such as `hpx::partitioned_vector`).
- Added a compatibility layer for `std::thread`, `std::mutex`, and `std::condition_variable` allowing for the code to use those facilities where available and to fall back to the corresponding Boost facilities otherwise. The [CMake](https://www.cmake.org)³⁸⁰⁸ configuration option `-DHPX_WITH_THREAD_COMPATIBILITY=On` can be used to force using the Boost equivalents.
- The parameter sequence for the `hpx::parallel::transform_inclusive_scan` overload taking one iterator range has changed (again) to match the changes this algorithm has undergone while being moved to C++17. The old overloads can be still enabled at configure time by passing `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to [CMake](https://www.cmake.org)³⁸⁰⁹.
- The parameter sequence for the `hpx::parallel::inclusive_scan` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17. The old overloads can be still enabled at configure time by passing `-DHPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY=On` to [CMake](https://www.cmake.org).
- Added a helper facility `hpx::local_new` which is equivalent to `hpx::new_` except that it creates components locally only. As a consequence, the used component constructor may accept non-serializable argument types and/or non-const references or pointers.
- Removed the (broken) component type `hpx::lcos::queue<T>`. The old type is still available at configure time by passing `-DHPX_WITH_QUEUE_COMPATIBILITY=On` to [CMake](https://www.cmake.org).
- The parallel algorithms adopted for C++17 restrict the iterator categories usable with those to at least forward iterators. Our implementation of the parallel algorithms was supporting input iterators (and output iterators) as well by simply falling back to sequential execution. We have now made our implementations conforming by requiring at least forward iterators. In order to enable the old behavior use the compatibility option `-DHPX_WITH_ALGORITHM_INPUT_ITERATOR_SUPPORT=On` on the [CMake](https://www.cmake.org)³⁸¹⁰ command line.
- We have added the functionalities allowing for LCOs being implemented using (simple) components. Before LCOs had to always be implemented using managed components.
- User defined components don't have to be default-constructible anymore. Return types from actions don't have to be default-constructible anymore either. Our serialization layer now in general supports non-default-constructible types.
- We have added a new launch policy `hpx::launch::lazy` that allows one to defer the decision on what launch policy to use to the point of execution. This policy is initialized with a function (object) that – when invoked – is expected to produce the desired launch policy.

³⁸⁰⁵ <https://openmp.org/wp/>

³⁸⁰⁶ https://en.wikipedia.org/wiki/Message_Passing_Interface

³⁸⁰⁷ <http://www.open-std.org/jtc1/sc22/wg21>

³⁸⁰⁸ <https://www.cmake.org>

³⁸⁰⁹ <https://www.cmake.org>

³⁸¹⁰ <https://www.cmake.org>

Breaking changes

- We have dropped support for the gcc compiler version V4.8. The minimal gcc version we now test on is gcc V4.9. The minimally required version of [CMake](https://www.cmake.org)³⁸¹¹ is now V3.3.2.
- We have dropped support for the Visual Studio 2013 compiler version. The minimal Visual Studio version we now test on is Visual Studio 2015.5.
- We have dropped support for the Boost V1.51-V1.54. The minimal version of Boost we now test is Boost V1.55.
- We have dropped support for the `hpx::util::unwrapped` API. `hpx::util::unwrapped` will stay functional to some degree, until it finally gets removed in a later version of HPX. The functional usage of `hpx::util::unwrapped` should be changed to the new `hpx::util::unwrapping` function whereas the immediate usage should be replaced to `hpx::util::unwrap`.
- The performance counter names referring to properties as exposed by the threading subsystem have changes as those now additionally have to specify the thread-pool. See the corresponding documentation for more details.
- The overloads of `hpx::async` that invoke an action do not perform implicit unwrapping of the returned future anymore in case the invoked function does return a future in the first place. In this case `hpx::async` now returns a `hpx::future<future<T>>` making its behavior conforming to its local counterpart.
- We have replaced the use of `boost::exception_ptr` in our APIs with the equivalent `std::exception_ptr`. Please change your codes accordingly. No compatibility settings are provided.
- We have removed the compatibility settings for `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` and `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY` as their life-cycle has reached its end.
- We have removed the experimental thread schedulers `hierarchy_scheduler`, `periodic_priority_scheduler` and `throttling_scheduler` in an effort to clean up and consolidate our thread schedulers.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #3250](#)³⁸¹² - Apex refactoring with guides
- [PR #3249](#)³⁸¹³ - Updating People.qbk
- [PR #3246](#)³⁸¹⁴ - Assorted fixes for CUDA
- [PR #3245](#)³⁸¹⁵ - Apex refactoring with guides
- [PR #3242](#)³⁸¹⁶ - Modify task counting in `thread_queue.hpp`
- [PR #3240](#)³⁸¹⁷ - Fixed typos
- [PR #3238](#)³⁸¹⁸ - Readding accidentally removed `std::abort`
- [PR #3237](#)³⁸¹⁹ - Adding Pipeline example
- [PR #3236](#)³⁸²⁰ - Fixing `memory_block`

³⁸¹¹ <https://www.cmake.org>

³⁸¹² <https://github.com/TheHPXProject/hpx/pull/3250>

³⁸¹³ <https://github.com/TheHPXProject/hpx/pull/3249>

³⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/3246>

³⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/3245>

³⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/3242>

³⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/3240>

³⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/3238>

³⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/3237>

³⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/3236>

- PR #3233³⁸²¹ - Make `schedule_thread` take suspended threads into account
- Issue #3226³⁸²² - `memory_block` is breaking, signaling SIGSEGV on a thread on creation and freeing
- PR #3225³⁸²³ - Applying quick fix for `hwloc-2.0`
- Issue #3224³⁸²⁴ - HPX counters crashing the application
- PR #3223³⁸²⁵ - Fix returns when setting config entries
- Issue #3222³⁸²⁶ - Errors linking `libhpx.so`
- Issue #3221³⁸²⁷ - HPX on Mac OS X with `HWLoc 2.0.0` fails to run
- PR #3216³⁸²⁸ - Reorder a variadic array to satisfy VS 2017 15.6
- PR #3214³⁸²⁹ - Changed `prerequisites.qbk` to avoid confusion while building boost
- PR #3213³⁸³⁰ - Relax locks for thread suspension to avoid holding locks when yielding
- PR #3212³⁸³¹ - Fix check in `sequenced_executor` test
- PR #3211³⁸³² - Use `preinit_array` to set `argc/argv` in `init_globally` example
- PR #3210³⁸³³ - Adapted `parallel::{search | search_n}` for Ranges TS (see #1668)
- PR #3209³⁸³⁴ - Fix locking problems during shutdown
- Issue #3208³⁸³⁵ - `init_globally` throwing a run-time error
- PR #3206³⁸³⁶ - Addition of new arithmetic performance counter “Count”
- PR #3205³⁸³⁷ - Fixing return type calculation for `bulk_then_execute`
- PR #3204³⁸³⁸ - Changing `std::rand()` to a better inbuilt PRNG generator
- PR #3203³⁸³⁹ - Resolving problems during shutdown for VS2015
- PR #3202³⁸⁴⁰ - Making sure resource partitioner is not accessed if its not valid
- PR #3201³⁸⁴¹ - Fixing `optional::swap`
- Issue #3200³⁸⁴² - `hpx::util::optional` fails
- PR #3199³⁸⁴³ - Fix `sliding_semaphore` test

³⁸²¹ <https://github.com/TheHPXProject/hpx/pull/3233>

³⁸²² <https://github.com/TheHPXProject/hpx/issues/3226>

³⁸²³ <https://github.com/TheHPXProject/hpx/pull/3225>

³⁸²⁴ <https://github.com/TheHPXProject/hpx/issues/3224>

³⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/3223>

³⁸²⁶ <https://github.com/TheHPXProject/hpx/issues/3222>

³⁸²⁷ <https://github.com/TheHPXProject/hpx/issues/3221>

³⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/3216>

³⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/3214>

³⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/3213>

³⁸³¹ <https://github.com/TheHPXProject/hpx/pull/3212>

³⁸³² <https://github.com/TheHPXProject/hpx/pull/3211>

³⁸³³ <https://github.com/TheHPXProject/hpx/pull/3210>

³⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/3209>

³⁸³⁵ <https://github.com/TheHPXProject/hpx/issues/3208>

³⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/3206>

³⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/3205>

³⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/3204>

³⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/3203>

³⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3202>

³⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/3201>

³⁸⁴² <https://github.com/TheHPXProject/hpx/issues/3200>

³⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/3199>

- PR #3198³⁸⁴⁴ - Set pre_main status before launching run_helper
- PR #3197³⁸⁴⁵ - Update README.rst
- PR #3194³⁸⁴⁶ - parallel::fill updated for Ranges TS
- PR #3193³⁸⁴⁷ - Updating Runtime.cpp by adding correct description of Performance counters during register
- PR #3191³⁸⁴⁸ - Fix sliding_semaphore_2338 test
- PR #3190³⁸⁴⁹ - Topology improvements
- PR #3189³⁸⁵⁰ - Deleting one include of median from BOOST library to arithmetics_counter file
- PR #3188³⁸⁵¹ - Optionally disable printing of diagnostics during terminate
- PR #3187³⁸⁵² - Suppressing cmake warning issued by cmake > V3.11
- PR #3185³⁸⁵³ - Remove unused scoped_unlock, unlock_guard_try
- PR #3184³⁸⁵⁴ - Fix nqueen example
- PR #3183³⁸⁵⁵ - Add runtime start/stop, resume/suspend and OpenMP benchmarks
- Issue #3182³⁸⁵⁶ - bulk_then_execute has unexpected return type/does not compile
- Issue #3181³⁸⁵⁷ - hwloc 2.0 breaks topo class and cannot be used
- Issue #3180³⁸⁵⁸ - Schedulers that don't support suspend/resume are unusable
- PR #3179³⁸⁵⁹ - Various minor changes to support FLeCSI
- PR #3178³⁸⁶⁰ - Fix #3124
- PR #3177³⁸⁶¹ - Removed allgather
- PR #3176³⁸⁶² - Fixed Documentation for "using_hpx_pkgconfig"
- PR #3174³⁸⁶³ - Add hpx::iostream::ostream overload to format_to
- PR #3172³⁸⁶⁴ - Fix lifo queue backend
- PR #3171³⁸⁶⁵ - adding the missing unset() function to cpu_mask() for case of more than 64 threads
- PR #3170³⁸⁶⁶ - Add cmake flag -DHPX_WITH_FAULT_TOLERANCE=ON (OFF by default)

³⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3198>
³⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3197>
³⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3194>
³⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3193>
³⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3191>
³⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3190>
³⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3189>
³⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/3188>
³⁸⁵² <https://github.com/TheHPXProject/hpx/pull/3187>
³⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/3185>
³⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3184>
³⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3183>
³⁸⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3182>
³⁸⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3181>
³⁸⁵⁸ <https://github.com/TheHPXProject/hpx/issues/3180>
³⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3179>
³⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3178>
³⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/3177>
³⁸⁶² <https://github.com/TheHPXProject/hpx/pull/3176>
³⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/3174>
³⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3172>
³⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3171>
³⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3170>

- PR #3169³⁸⁶⁷ - Adapted parallel::count/count_if for Ranges TS (see #1668)
- PR #3168³⁸⁶⁸ - Changing used namespace for seq execution policy
- Issue #3167³⁸⁶⁹ - Update GSoC projects
- Issue #3166³⁸⁷⁰ - Application (Octotiger) gets stuck on hpx::finalize when only using one thread
- Issue #3165³⁸⁷¹ - Compilation of parallel algorithms with HPX_WITH_DATAPAR is broken
- PR #3164³⁸⁷² - Fixing component migration
- PR #3162³⁸⁷³ - regex_from_pattern: escape regex special characters to avoid misinterpretation
- Issue #3161³⁸⁷⁴ - Building HPX with hwloc 2.0.0 fails
- PR #3160³⁸⁷⁵ - Fixing the handling of quoted command line arguments.
- PR #3158³⁸⁷⁶ - Fixing a race with timed suspension (second attempt)
- PR #3157³⁸⁷⁷ - Revert “Fixing a race with timed suspension”
- PR #3156³⁸⁷⁸ - Fixing serialization of classes with incompatible serialize signature
- PR #3154³⁸⁷⁹ - More refactorings based on clang-tidy reports
- PR #3153³⁸⁸⁰ - Fixing a race with timed suspension
- PR #3152³⁸⁸¹ - Documentation for runtime suspension
- PR #3151³⁸⁸² - Use small_vector only from boost version 1.59 onwards
- PR #3150³⁸⁸³ - Avoiding more stack overflows
- PR #3148³⁸⁸⁴ - Refactoring component_base and base_action/transfer_base_action
- PR #3147³⁸⁸⁵ - Move yield_while out of detail namespace and into own file
- PR #3145³⁸⁸⁶ - Remove a leftover of the cxx11 std array cleanup
- PR #3144³⁸⁸⁷ - Minor changes to how actions are executed
- PR #3143³⁸⁸⁸ - Fix stack overhead
- PR #3142³⁸⁸⁹ - Fix typo in config.hpp

³⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3169>
³⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3168>
³⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/3167>
³⁸⁷⁰ <https://github.com/TheHPXProject/hpx/issues/3166>
³⁸⁷¹ <https://github.com/TheHPXProject/hpx/issues/3165>
³⁸⁷² <https://github.com/TheHPXProject/hpx/pull/3164>
³⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/3162>
³⁸⁷⁴ <https://github.com/TheHPXProject/hpx/issues/3161>
³⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3160>
³⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3158>
³⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3157>
³⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3156>
³⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3154>
³⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3153>
³⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/3152>
³⁸⁸² <https://github.com/TheHPXProject/hpx/pull/3151>
³⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/3150>
³⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3148>
³⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3147>
³⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3145>
³⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3144>
³⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3143>
³⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3142>

- PR #3141³⁸⁹⁰ - Fixing small_vector compatibility with older boost version
- PR #3140³⁸⁹¹ - is_heap_text fix
- Issue #3139³⁸⁹² - Error in is_heap_tests.hpp
- PR #3138³⁸⁹³ - Partially reverting #3126
- PR #3137³⁸⁹⁴ - Suspend speedup
- PR #3136³⁸⁹⁵ - Revert “Fixing #2325”
- PR #3135³⁸⁹⁶ - Improving destruction of threads
- Issue #3134³⁸⁹⁷ - HPX_SERIALIZATION_SPLIT_FREE does not stop compiler from looking for serialize() method
- PR #3133³⁸⁹⁸ - Make hwloc compulsory
- PR #3132³⁸⁹⁹ - Update CXX14 constexpr feature test
- PR #3131³⁹⁰⁰ - Fixing #2325
- PR #3130³⁹⁰¹ - Avoid completion handler allocation
- PR #3129³⁹⁰² - Suspend runtime
- PR #3128³⁹⁰³ - Make docbook dtd and xsl path names consistent
- PR #3127³⁹⁰⁴ - Add hpx::start nullptr overloads
- PR #3126³⁹⁰⁵ - Cleaning up coroutine implementation
- PR #3125³⁹⁰⁶ - Replacing nullptr with hpx::threads::invalid_thread_id
- Issue #3124³⁹⁰⁷ - Add hello_world_component to CI builds
- PR #3123³⁹⁰⁸ - Add new constructor.
- PR #3122³⁹⁰⁹ - Fixing #3121
- Issue #3121³⁹¹⁰ - HPX_SMT_PAUSE is broken on non-x86 platforms when __GNUC__ is defined
- PR #3120³⁹¹¹ - Don't use boost::intrusive_ptr for thread_id_type
- PR #3119³⁹¹² - Disable default executor compatibility with V1 executors

³⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3141>

³⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/3140>

³⁸⁹² <https://github.com/TheHPXProject/hpx/issues/3139>

³⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/3138>

³⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3137>

³⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3136>

³⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3135>

³⁸⁹⁷ <https://github.com/TheHPXProject/hpx/issues/3134>

³⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3133>

³⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3132>

³⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3131>

³⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/3130>

³⁹⁰² <https://github.com/TheHPXProject/hpx/pull/3129>

³⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/3128>

³⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3127>

³⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3126>

³⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3125>

³⁹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/3124>

³⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3123>

³⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3122>

³⁹¹⁰ <https://github.com/TheHPXProject/hpx/issues/3121>

³⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/3120>

³⁹¹² <https://github.com/TheHPXProject/hpx/pull/3119>

- PR #3118³⁹¹³ - Adding performance_counter::reinit to allow for dynamically changing counter sets
- PR #3117³⁹¹⁴ - Replace uses of boost/experimental::optional with util::optional
- PR #3116³⁹¹⁵ - Moving background thread APEX timer #2980
- PR #3115³⁹¹⁶ - Fixing race condition in channel test
- PR #3114³⁹¹⁷ - Avoid using util::function for thread function wrappers
- PR #3113³⁹¹⁸ - cmake V3.10.2 has changed the variable names used for MPI
- PR #3112³⁹¹⁹ - Minor fixes to exclusive_scan algorithm
- PR #3111³⁹²⁰ - Revert “fix detection of cxx11_std_atomic”
- PR #3110³⁹²¹ - Suspend thread pool
- PR #3109³⁹²² - Fixing thread scheduling when yielding a thread id
- PR #3108³⁹²³ - Revert “Suspend thread pool”
- PR #3107³⁹²⁴ - Remove UB from thread::id relational operators
- PR #3106³⁹²⁵ - Add cmake test for std::decay_t to fix cuda build
- PR #3105³⁹²⁶ - Fixing refcount for async traversal frame
- PR #3104³⁹²⁷ - Local execution of direct actions is now actually performed directly
- PR #3103³⁹²⁸ - Adding support for generic counter_raw_values performance counter type
- Issue #3102³⁹²⁹ - Introduce generic performance counter type returning an array of values
- PR #3101³⁹³⁰ - Revert “Adapting stack overhead limit for gcc 4.9”
- PR #3100³⁹³¹ - Fix #3068 (condition_variable deadlock)
- PR #3099³⁹³² - Fixing lock held during suspension in papi counter component
- PR #3098³⁹³³ - Unbreak broadcast_wait_for_2822 test
- PR #3097³⁹³⁴ - Adapting stack overhead limit for gcc 4.9
- PR #3096³⁹³⁵ - fix detection of cxx11_std_atomic

³⁹¹³ <https://github.com/TheHPXProject/hpx/pull/3118>

³⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/3117>

³⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/3116>

³⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/3115>

³⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/3114>

³⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/3113>

³⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/3112>

³⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/3111>

³⁹²¹ <https://github.com/TheHPXProject/hpx/pull/3110>

³⁹²² <https://github.com/TheHPXProject/hpx/pull/3109>

³⁹²³ <https://github.com/TheHPXProject/hpx/pull/3108>

³⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/3107>

³⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/3106>

³⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/3105>

³⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/3104>

³⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/3103>

³⁹²⁹ <https://github.com/TheHPXProject/hpx/issues/3102>

³⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/3101>

³⁹³¹ <https://github.com/TheHPXProject/hpx/pull/3100>

³⁹³² <https://github.com/TheHPXProject/hpx/pull/3099>

³⁹³³ <https://github.com/TheHPXProject/hpx/pull/3098>

³⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/3097>

³⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/3096>

- PR #3095³⁹³⁶ - Add ciso646 header to get `_LIBCPP_VERSION` for testing inplace merge
- PR #3094³⁹³⁷ - Relax atomic operations on performance counter values
- PR #3093³⁹³⁸ - Short-circuit `all_of/any_of/none_of` instantiations
- PR #3092³⁹³⁹ - Take advantage of C++14 lambda capture initialization syntax, where possible
- PR #3091³⁹⁴⁰ - Remove more references to Boost from logging code
- PR #3090³⁹⁴¹ - Unify use of `yield/yield_k`
- PR #3089³⁹⁴² - Fix a strange thing in `parallel::detail::handle_exception`. (Fix #2834.)
- Issue #3088³⁹⁴³ - A strange thing in `parallel::sort`.
- PR #3087³⁹⁴⁴ - Fixing assertion in `default_distribution_policy`
- PR #3086³⁹⁴⁵ - Implement `parallel::remove` and `parallel::remove_if`
- PR #3085³⁹⁴⁶ - Addressing breaking changes in Boost V1.66
- PR #3084³⁹⁴⁷ - Ignore build warnings round 2
- PR #3083³⁹⁴⁸ - Fix typo `HPX_WITH_MM_PREFECTH`
- PR #3081³⁹⁴⁹ - Pre-decay template arguments early
- PR #3080³⁹⁵⁰ - Suspend thread pool
- PR #3079³⁹⁵¹ - Ignore build warnings
- PR #3078³⁹⁵² - Don't test `inplace_merge` with `libc++`
- PR #3076³⁹⁵³ - Fixing 3075: Part 1
- PR #3074³⁹⁵⁴ - Fix more build warnings
- PR #3073³⁹⁵⁵ - Suspend thread cleanup
- PR #3072³⁹⁵⁶ - Change existing `symbol_namespace::iterate` to return all data instead of invoking a callback
- PR #3071³⁹⁵⁷ - Fixing `pack_traversal_async` test
- PR #3070³⁹⁵⁸ - Fix `dynamic_counters_loaded_1508` test by adding dependency to `memory_component`

³⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/3095>

³⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/3094>

³⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/3093>

³⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/3092>

³⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3091>

³⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/3090>

³⁹⁴² <https://github.com/TheHPXProject/hpx/pull/3089>

³⁹⁴³ <https://github.com/TheHPXProject/hpx/issues/3088>

³⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3087>

³⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3086>

³⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3085>

³⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3084>

³⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3083>

³⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3081>

³⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3080>

³⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/3079>

³⁹⁵² <https://github.com/TheHPXProject/hpx/pull/3078>

³⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/3076>

³⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3074>

³⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3073>

³⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3072>

³⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3071>

³⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3070>

- PR #3069³⁹⁵⁹ - Fix scheduling loop exit
- Issue #3068³⁹⁶⁰ - `hpx::lcos::condition_variable` could be suspect to deadlocks
- PR #3067³⁹⁶¹ - `#ifdef` out `random_shuffle` deprecated in later c++
- PR #3066³⁹⁶² - Make coalescing test depend on coalescing library to ensure it gets built
- PR #3065³⁹⁶³ - Workaround for `minimal_timed_async_executor_test` compilation failures, attempts to copy a deferred call (in unevaluated context)
- PR #3064³⁹⁶⁴ - Fixing wrong condition in `wrapper_heap`
- PR #3062³⁹⁶⁵ - Fix exception handling for `execution::seq`
- PR #3061³⁹⁶⁶ - Adapt MSVC C++ mode handling to VS15.5
- PR #3060³⁹⁶⁷ - Fix compiler problem in MSVC release mode
- PR #3059³⁹⁶⁸ - Fixing #2931
- Issue #3058³⁹⁶⁹ - `minimal_timed_async_executor_test_exe` fails to compile on master (d6f505c)
- PR #3057³⁹⁷⁰ - Fix `stable_merge_2964` compilation problems
- PR #3056³⁹⁷¹ - Fix some build warnings caused by unused variables/unnecessary tests
- PR #3055³⁹⁷² - Update documentation for running tests
- Issue #3054³⁹⁷³ - Assertion failure when using bulk `hpx::new_` in asynchronous mode
- PR #3052³⁹⁷⁴ - Do not bind test running to `cmake` test build rule
- PR #3051³⁹⁷⁵ - Fix HPX-Qt interaction in Qt example.
- Issue #3048³⁹⁷⁶ - `nqueen` example fails occasionally
- PR #3047³⁹⁷⁷ - Fixing #3044
- PR #3046³⁹⁷⁸ - Add OS thread suspension
- PR #3042³⁹⁷⁹ - PyCicle - first attempt at a build tool for checking PR's
- PR #3041³⁹⁸⁰ - Fix a problem about asynchronous execution of `parallel::merge` and `parallel::partition`.
- PR #3040³⁹⁸¹ - Fix a mistake about exception handling in asynchronous execution of `scan_partitioner`.

³⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3069>

³⁹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/3068>

³⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/3067>

³⁹⁶² <https://github.com/TheHPXProject/hpx/pull/3066>

³⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/3065>

³⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3064>

³⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3062>

³⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3061>

³⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3060>

³⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3059>

³⁹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/3058>

³⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3057>

³⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/3056>

³⁹⁷² <https://github.com/TheHPXProject/hpx/pull/3055>

³⁹⁷³ <https://github.com/TheHPXProject/hpx/issues/3054>

³⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3052>

³⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3051>

³⁹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/3048>

³⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3047>

³⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3046>

³⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3042>

³⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3041>

³⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/3040>

- PR #3039³⁹⁸² - Consistently use executors to schedule work
- PR #3038³⁹⁸³ - Fixing local direct function execution and lambda actions perfect forwarding
- PR #3035³⁹⁸⁴ - Make parallel unit test names match build target/folder names
- PR #3033³⁹⁸⁵ - Fix setting of default build type
- Issue #3032³⁹⁸⁶ - Fix partitioner arg copy found in #2982
- Issue #3031³⁹⁸⁷ - Errors linking libhpx.so due to missing references (master branch, commit 6679a8882)
- PR #3030³⁹⁸⁸ - Revert “implement executor then interface with && forwarding reference”
- PR #3029³⁹⁸⁹ - Run CI inspect checks before building
- PR #3028³⁹⁹⁰ - Added range version of parallel::move
- Issue #3027³⁹⁹¹ - Implement all scheduling APIs in terms of executors
- PR #3026³⁹⁹² - implement executor then interface with && forwarding reference
- PR #3025³⁹⁹³ - Fix typo uninitialized to uninitialized
- PR #3024³⁹⁹⁴ - Inspect fixes
- PR #3023³⁹⁹⁵ - P0356 Simplified partial function application
- PR #3022³⁹⁹⁶ - Master fixes
- PR #3021³⁹⁹⁷ - Segfault fix
- PR #3020³⁹⁹⁸ - Disable command-line aliasing for applications that use user_main
- PR #3019³⁹⁹⁹ - Adding enable_elasticity option to pool configuration
- PR #3018⁴⁰⁰⁰ - Fix stack overflow detection configuration in header files
- PR #3017⁴⁰⁰¹ - Speed up local action execution
- PR #3016⁴⁰⁰² - Unify stack-overflow detection options, remove reference to libsigsegv
- PR #3015⁴⁰⁰³ - Speeding up accessing the resource partitioner and the topology info
- Issue #3014⁴⁰⁰⁴ - HPX does not compile on POWER8 with gcc 5.4

³⁹⁸² <https://github.com/TheHPXProject/hpx/pull/3039>

³⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/3038>

³⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3035>

³⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3033>

³⁹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/3032>

³⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3031>

³⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3030>

³⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3029>

³⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3028>

³⁹⁹¹ <https://github.com/TheHPXProject/hpx/issues/3027>

³⁹⁹² <https://github.com/TheHPXProject/hpx/pull/3026>

³⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/3025>

³⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3024>

³⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3023>

³⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3022>

³⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3021>

³⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3020>

³⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3019>

⁴⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3018>

⁴⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/3017>

⁴⁰⁰² <https://github.com/TheHPXProject/hpx/pull/3016>

⁴⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/3015>

⁴⁰⁰⁴ <https://github.com/TheHPXProject/hpx/issues/3014>

- [Issue #3013](#)⁴⁰⁰⁵ - hello_world occasionally prints multiple lines from a single OS-thread
- [PR #3012](#)⁴⁰⁰⁶ - Silence warning about casting away qualifiers in itt_notify.hpp
- [PR #3011](#)⁴⁰⁰⁷ - Fix cpuset leak in hwloc_topology_info.cpp
- [PR #3010](#)⁴⁰⁰⁸ - Remove useless decay_copy
- [PR #3009](#)⁴⁰⁰⁹ - Fixing 2996
- [PR #3008](#)⁴⁰¹⁰ - Remove unused internal function
- [PR #3007](#)⁴⁰¹¹ - Fixing wrapper_heap alignment problems
- [Issue #3006](#)⁴⁰¹² - hwloc memory leak
- [PR #3004](#)⁴⁰¹³ - Silence C4251 (needs to have dll-interface) for future_data_void
- [Issue #3003](#)⁴⁰¹⁴ - Suspension of runtime
- [PR #3001](#)⁴⁰¹⁵ - Attempting to avoid data races in async_traversal while evaluating dataflow()
- [PR #3000](#)⁴⁰¹⁶ - Adding hpx::util::optional as a first step to replace experimental::optional
- [PR #2998](#)⁴⁰¹⁷ - Cleanup up and Fixing component creation and deletion
- [Issue #2996](#)⁴⁰¹⁸ - Build fails with HPX_WITH_HWLOC=OFF
- [PR #2995](#)⁴⁰¹⁹ - Push more future_data functionality to source file
- [PR #2994](#)⁴⁰²⁰ - WIP: Fix throttle test
- [PR #2993](#)⁴⁰²¹ - Making sure -hpx:help does not throw for required (but missing) arguments
- [PR #2992](#)⁴⁰²² - Adding non-blocking (on destruction) service executors
- [Issue #2991](#)⁴⁰²³ - run_as_os_thread locks up
- [Issue #2990](#)⁴⁰²⁴ - -help will not work until all required options are provided
- [PR #2989](#)⁴⁰²⁵ - Improve error messages caused by misuse of dataflow
- [PR #2988](#)⁴⁰²⁶ - Improve error messages caused by misuse of .then
- [Issue #2987](#)⁴⁰²⁷ - stack overflow detection producing false positives

⁴⁰⁰⁵ <https://github.com/TheHPXProject/hpx/issues/3013>

⁴⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3012>

⁴⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3011>

⁴⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3010>

⁴⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3009>

⁴⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/3008>

⁴⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/3007>

⁴⁰¹² <https://github.com/TheHPXProject/hpx/issues/3006>

⁴⁰¹³ <https://github.com/TheHPXProject/hpx/pull/3004>

⁴⁰¹⁴ <https://github.com/TheHPXProject/hpx/issues/3003>

⁴⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/3001>

⁴⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/3000>

⁴⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/2998>

⁴⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/2996>

⁴⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/2995>

⁴⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/2994>

⁴⁰²¹ <https://github.com/TheHPXProject/hpx/pull/2993>

⁴⁰²² <https://github.com/TheHPXProject/hpx/pull/2992>

⁴⁰²³ <https://github.com/TheHPXProject/hpx/issues/2991>

⁴⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/2990>

⁴⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/2989>

⁴⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/2988>

⁴⁰²⁷ <https://github.com/TheHPXProject/hpx/issues/2987>

- [PR #2986](#)⁴⁰²⁸ - Deduplicate non-dependent thread_info logging types
- [PR #2985](#)⁴⁰²⁹ - Adapted parallel::{all_of|any_of|none_of} for Ranges TS (see #1668)
- [PR #2984](#)⁴⁰³⁰ - Refactor one_size_heap code to simplify code
- [PR #2983](#)⁴⁰³¹ - Fixing local_new_component
- [PR #2982](#)⁴⁰³² - Clang tidy
- [PR #2981](#)⁴⁰³³ - Simplify allocator rebinding in pack traversal
- [PR #2979](#)⁴⁰³⁴ - Fixing integer overflows
- [PR #2978](#)⁴⁰³⁵ - Implement parallel::inplace_merge
- [Issue #2977](#)⁴⁰³⁶ - Make hwloc compulsory instead of optional
- [PR #2976](#)⁴⁰³⁷ - Making sure client_base instance that registered the component does not unregister it when being destructed
- [PR #2975](#)⁴⁰³⁸ - Change version of pulled APEX to master
- [PR #2974](#)⁴⁰³⁹ - Fix domain not being freed at the end of scheduling loop
- [PR #2973](#)⁴⁰⁴⁰ - Fix small typos
- [PR #2972](#)⁴⁰⁴¹ - Adding uintstd.h header
- [PR #2971](#)⁴⁰⁴² - Fall back to creating local components using local_new
- [PR #2970](#)⁴⁰⁴³ - Improve is_tuple_like trait
- [PR #2969](#)⁴⁰⁴⁴ - Fix HPX_WITH_MORE_THAN_64_THREADS default value
- [PR #2968](#)⁴⁰⁴⁵ - Cleaning up dataflow overload set
- [PR #2967](#)⁴⁰⁴⁶ - Make parallel::merge is stable. (Fix #2964.)
- [PR #2966](#)⁴⁰⁴⁷ - Fixing a couple of held locks during exception handling
- [PR #2965](#)⁴⁰⁴⁸ - Adding missing #include
- [Issue #2964](#)⁴⁰⁴⁹ - parallel merge is not stable
- [PR #2963](#)⁴⁰⁵⁰ - Making sure any function object passed to dataflow is released after being invoked

⁴⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/2986>

⁴⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/2985>

⁴⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/2984>

⁴⁰³¹ <https://github.com/TheHPXProject/hpx/pull/2983>

⁴⁰³² <https://github.com/TheHPXProject/hpx/pull/2982>

⁴⁰³³ <https://github.com/TheHPXProject/hpx/pull/2981>

⁴⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/2979>

⁴⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/2978>

⁴⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/2977>

⁴⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/2976>

⁴⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/2975>

⁴⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/2974>

⁴⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2973>

⁴⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/2972>

⁴⁰⁴² <https://github.com/TheHPXProject/hpx/pull/2971>

⁴⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/2970>

⁴⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2969>

⁴⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2968>

⁴⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2967>

⁴⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2966>

⁴⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2965>

⁴⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/2964>

⁴⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2963>

- PR #2962⁴⁰⁵¹ - Partially reverting #2891
- PR #2961⁴⁰⁵² - Attempt to fix the gcc 4.9 problem with the async pack traversal
- Issue #2959⁴⁰⁵³ - Program terminates during error handling
- Issue #2958⁴⁰⁵⁴ - HPX_PLAIN_ACTION breaks due to missing include
- PR #2957⁴⁰⁵⁵ - Fixing errors generated by mixing different attribute syntaxes
- Issue #2956⁴⁰⁵⁶ - Mixing attribute syntaxes leads to compiler errors
- Issue #2955⁴⁰⁵⁷ - Fix OS-Thread throttling
- PR #2953⁴⁰⁵⁸ - Making sure any hpx.os_threads=N supplied through a -hpx::config file is taken into account
- PR #2952⁴⁰⁵⁹ - Removing wrong call to cleanup_terminated_locked
- PR #2951⁴⁰⁶⁰ - Revert “Make sure the function vtables are initialized before use”
- PR #2950⁴⁰⁶¹ - Fix a namespace compilation error when some schedulers are disabled
- Issue #2949⁴⁰⁶² - master branch giving lockups on shutdown
- Issue #2947⁴⁰⁶³ - hpx.ini is not used correctly at initialization
- PR #2946⁴⁰⁶⁴ - Adding explicit feature test for thread_local
- PR #2945⁴⁰⁶⁵ - Make sure the function vtables are initialized before use
- PR #2944⁴⁰⁶⁶ - Attempting to solve affinity problems on CircleCI
- PR #2943⁴⁰⁶⁷ - Changing channel actions to be direct
- PR #2942⁴⁰⁶⁸ - Adding split_future for std::vector
- PR #2941⁴⁰⁶⁹ - Add a feature test to test for CXX11 override
- Issue #2940⁴⁰⁷⁰ - Add split_future for future<vector<T>>
- PR #2939⁴⁰⁷¹ - Making error reporting during problems with setting affinity masks more verbose
- PR #2938⁴⁰⁷² - Fix this various executors
- PR #2937⁴⁰⁷³ - Fix some typos in documentation

⁴⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/2962>

⁴⁰⁵² <https://github.com/TheHPXProject/hpx/pull/2961>

⁴⁰⁵³ <https://github.com/TheHPXProject/hpx/issues/2959>

⁴⁰⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2958>

⁴⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2957>

⁴⁰⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2956>

⁴⁰⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2955>

⁴⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2953>

⁴⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2952>

⁴⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2951>

⁴⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/2950>

⁴⁰⁶² <https://github.com/TheHPXProject/hpx/issues/2949>

⁴⁰⁶³ <https://github.com/TheHPXProject/hpx/issues/2947>

⁴⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2946>

⁴⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2945>

⁴⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2944>

⁴⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2943>

⁴⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2942>

⁴⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2941>

⁴⁰⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2940>

⁴⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/2939>

⁴⁰⁷² <https://github.com/TheHPXProject/hpx/pull/2938>

⁴⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/2937>

- PR #2934⁴⁰⁷⁴ - Remove the need for “complete” SFINAE checks
- PR #2933⁴⁰⁷⁵ - Making sure parallel::for_loop is executed in parallel if requested
- PR #2932⁴⁰⁷⁶ - Classify chunk_size_iterator to input iterator tag. (Fix #2866)
- Issue #2931⁴⁰⁷⁷ - --hpx:help triggers unusual error with clang build
- PR #2930⁴⁰⁷⁸ - Add #include files needed to set _POSIX_VERSION for debug check
- PR #2929⁴⁰⁷⁹ - Fix a couple of deprecated c++ features
- PR #2928⁴⁰⁸⁰ - Fixing execution parameters
- Issue #2927⁴⁰⁸¹ - CMake warning: ... cycle in constraint graph
- PR #2926⁴⁰⁸² - Default pool rename
- Issue #2925⁴⁰⁸³ - Default pool cannot be renamed
- Issue #2924⁴⁰⁸⁴ - hpx:attach-debugger=startup does not work any more
- PR #2923⁴⁰⁸⁵ - Alloc membind
- PR #2922⁴⁰⁸⁶ - This fixes CircleCI errors when running with --hpx:bind=none
- PR #2921⁴⁰⁸⁷ - Custom pool executor was missing priority and stacksize options
- PR #2920⁴⁰⁸⁸ - Adding test to trigger problem reported in #2916
- PR #2919⁴⁰⁸⁹ - Make sure the resource_partitioner is properly destructed on hpx::finalize
- Issue #2918⁴⁰⁹⁰ - hpx::init calls wrong (first) callback when called multiple times
- PR #2917⁴⁰⁹¹ - Adding util::checkpoint
- Issue #2916⁴⁰⁹² - Weird runtime failures when using a channel and chained continuations
- PR #2915⁴⁰⁹³ - Introduce executor parameters customization points
- Issue #2914⁴⁰⁹⁴ - Task assignment to current Pool has unintended consequences
- PR #2913⁴⁰⁹⁵ - Fix rp hang
- PR #2912⁴⁰⁹⁶ - Update contributors

⁴⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2934>

⁴⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2933>

⁴⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2932>

⁴⁰⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2931>

⁴⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2930>

⁴⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2929>

⁴⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2928>

⁴⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/2927>

⁴⁰⁸² <https://github.com/TheHPXProject/hpx/pull/2926>

⁴⁰⁸³ <https://github.com/TheHPXProject/hpx/issues/2925>

⁴⁰⁸⁴ <https://github.com/TheHPXProject/hpx/issues/2924>

⁴⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2923>

⁴⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2922>

⁴⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2921>

⁴⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2920>

⁴⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2919>

⁴⁰⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2918>

⁴⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/2917>

⁴⁰⁹² <https://github.com/TheHPXProject/hpx/issues/2916>

⁴⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/2915>

⁴⁰⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2914>

⁴⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2913>

⁴⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2912>

- [PR #2911⁴⁰⁹⁷](#) - Fixing CUDA problems
- [PR #2910⁴⁰⁹⁸](#) - Improve error reporting for process component on POSIX systems
- [PR #2909⁴⁰⁹⁹](#) - Fix typo in include path
- [PR #2908⁴¹⁰⁰](#) - Use proper container according to iterator tag in benchmarks of parallel algorithms
- [PR #2907⁴¹⁰¹](#) - Optionally force-delete remaining channel items on close
- [PR #2906⁴¹⁰²](#) - Making sure generated performance counter names are correct
- [Issue #2905⁴¹⁰³](#) - collecting idle-rate performance counters on multiple localities produces an error
- [Issue #2904⁴¹⁰⁴](#) - build broken for Intel 17 compilers
- [PR #2903⁴¹⁰⁵](#) - Documentation Updates– Adding New People
- [PR #2902⁴¹⁰⁶](#) - Fixing service_executor
- [PR #2901⁴¹⁰⁷](#) - Fixing partitioned_vector creation
- [PR #2900⁴¹⁰⁸](#) - Add numa-balanced mode to hpx::bind, spread cores over numa domains
- [Issue #2899⁴¹⁰⁹](#) - hpx::bind does not have a mode that balances cores over numa domains
- [PR #2898⁴¹¹⁰](#) - Adding missing #include and missing guard for optional code section
- [PR #2897⁴¹¹¹](#) - Removing dependency on Boost.ICL
- [Issue #2896⁴¹¹²](#) - Debug build fails without -fpermissive with GCC 7.1 and Boost 1.65
- [PR #2895⁴¹¹³](#) - Fixing SLURM environment parsing
- [PR #2894⁴¹¹⁴](#) - Fix incorrect handling of compile definition with value 0
- [Issue #2893⁴¹¹⁵](#) - Disabling schedulers causes build errors
- [PR #2892⁴¹¹⁶](#) - added list serializer
- [PR #2891⁴¹¹⁷](#) - Resource Partitioner Fixes
- [Issue #2890⁴¹¹⁸](#) - Destroying a non-empty channel causes an assertion failure
- [PR #2889⁴¹¹⁹](#) - Add check for libatomic

⁴⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2911>

⁴⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2910>

⁴⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2909>

⁴¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2908>

⁴¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/2907>

⁴¹⁰² <https://github.com/TheHPXProject/hpx/pull/2906>

⁴¹⁰³ <https://github.com/TheHPXProject/hpx/issues/2905>

⁴¹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/2904>

⁴¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2903>

⁴¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2902>

⁴¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2901>

⁴¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2900>

⁴¹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2899>

⁴¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/2898>

⁴¹¹¹ <https://github.com/TheHPXProject/hpx/pull/2897>

⁴¹¹² <https://github.com/TheHPXProject/hpx/issues/2896>

⁴¹¹³ <https://github.com/TheHPXProject/hpx/pull/2895>

⁴¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/2894>

⁴¹¹⁵ <https://github.com/TheHPXProject/hpx/issues/2893>

⁴¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/2892>

⁴¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/2891>

⁴¹¹⁸ <https://github.com/TheHPXProject/hpx/issues/2890>

⁴¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/2889>

- PR #2888⁴¹²⁰ - Fix compilation problems if HPX_WITH_ITT_NOTIFY=ON
- PR #2887⁴¹²¹ - Adapt broadcast() to non-unwrapping async<Action>
- PR #2886⁴¹²² - Replace Boost.Random with C++11 <random>
- Issue #2885⁴¹²³ - regression in broadcast?
- Issue #2884⁴¹²⁴ - linking -latomic is not portable
- PR #2883⁴¹²⁵ - Explicitly set -pthread flag if available
- PR #2882⁴¹²⁶ - Wrap boost::format uses
- Issue #2881⁴¹²⁷ - hpx not compiling with HPX_WITH_ITTNOTIFY=On
- Issue #2880⁴¹²⁸ - hpx::bind scatter/balanced give wrong pu masks
- PR #2878⁴¹²⁹ - Fix incorrect pool usage masks setup in RP/thread manager
- PR #2877⁴¹³⁰ - Require std::array by default
- PR #2875⁴¹³¹ - Deprecate use of BOOST_ASSERT
- PR #2874⁴¹³² - Changed serialization of boost.variant to use variadic templates
- Issue #2873⁴¹³³ - building with parcelport_mpi fails on cori
- PR #2871⁴¹³⁴ - Adding missing support for throttling scheduler
- PR #2870⁴¹³⁵ - Disambiguate use of base_lco_with_value macros with channel
- Issue #2869⁴¹³⁶ - Difficulty compiling HPX_REGISTER_CHANNEL_DECLARATION(double)
- PR #2868⁴¹³⁷ - Removing unneeded assert
- PR #2867⁴¹³⁸ - Implement parallel::unique
- Issue #2866⁴¹³⁹ - The chunk_size_iterator violates multipass guarantee
- PR #2865⁴¹⁴⁰ - Only use sched_getcpu on linux machines
- PR #2864⁴¹⁴¹ - Create redistribution archive for successful builds
- PR #2863⁴¹⁴² - Replace casts/assignments with hard-coded memcpy operations

⁴¹²⁰ <https://github.com/TheHPXProject/hpx/pull/2888>

⁴¹²¹ <https://github.com/TheHPXProject/hpx/pull/2887>

⁴¹²² <https://github.com/TheHPXProject/hpx/pull/2886>

⁴¹²³ <https://github.com/TheHPXProject/hpx/issues/2885>

⁴¹²⁴ <https://github.com/TheHPXProject/hpx/issues/2884>

⁴¹²⁵ <https://github.com/TheHPXProject/hpx/pull/2883>

⁴¹²⁶ <https://github.com/TheHPXProject/hpx/pull/2882>

⁴¹²⁷ <https://github.com/TheHPXProject/hpx/issues/2881>

⁴¹²⁸ <https://github.com/TheHPXProject/hpx/issues/2880>

⁴¹²⁹ <https://github.com/TheHPXProject/hpx/pull/2878>

⁴¹³⁰ <https://github.com/TheHPXProject/hpx/pull/2877>

⁴¹³¹ <https://github.com/TheHPXProject/hpx/pull/2875>

⁴¹³² <https://github.com/TheHPXProject/hpx/pull/2874>

⁴¹³³ <https://github.com/TheHPXProject/hpx/issues/2873>

⁴¹³⁴ <https://github.com/TheHPXProject/hpx/pull/2871>

⁴¹³⁵ <https://github.com/TheHPXProject/hpx/pull/2870>

⁴¹³⁶ <https://github.com/TheHPXProject/hpx/issues/2869>

⁴¹³⁷ <https://github.com/TheHPXProject/hpx/pull/2868>

⁴¹³⁸ <https://github.com/TheHPXProject/hpx/pull/2867>

⁴¹³⁹ <https://github.com/TheHPXProject/hpx/issues/2866>

⁴¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2865>

⁴¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/2864>

⁴¹⁴² <https://github.com/TheHPXProject/hpx/pull/2863>

- Issue #2862⁴¹⁴³ - sched_getcpu not available on MacOS
- PR #2861⁴¹⁴⁴ - Fixing unmatched header defines and recursive inclusion of threadmanager
- Issue #2860⁴¹⁴⁵ - Master program fails with assertion 'type == data_type_address' failed: HPX(assertion_failure)
- Issue #2852⁴¹⁴⁶ - Support for ARM64
- PR #2858⁴¹⁴⁷ - Fix misplaced #if #endif's that cause build failure without THREAD_CUMULATIVE_COUNTS
- PR #2857⁴¹⁴⁸ - Fix some listing in documentation
- PR #2856⁴¹⁴⁹ - Fixing component handling for lcos
- PR #2855⁴¹⁵⁰ - Add documentation for coarrays
- PR #2854⁴¹⁵¹ - Support ARM64 in timestamps
- PR #2853⁴¹⁵² - Update Table 17. Non-modifying Parallel Algorithms in Documentation
- PR #2851⁴¹⁵³ - Allowing for non-default-constructible component types
- PR #2850⁴¹⁵⁴ - Enable returning future<R> from actions where R is not default-constructible
- PR #2849⁴¹⁵⁵ - Unify serialization of non-default-constructable types
- Issue #2848⁴¹⁵⁶ - Components have to be default constructible
- Issue #2847⁴¹⁵⁷ - Returning a future<R> where R is not default-constructable broken
- Issue #2846⁴¹⁵⁸ - Unify serialization of non-default-constructible types
- PR #2845⁴¹⁵⁹ - Add Visual Studio 2015 to the tested toolchains in Appveyor
- Issue #2844⁴¹⁶⁰ - Change the appveyor build to use the minimal required MSVC version
- Issue #2843⁴¹⁶¹ - multi node hello_world hangs
- PR #2842⁴¹⁶² - Correcting Spelling mistake in docs
- PR #2841⁴¹⁶³ - Fix usage of std::aligned_storage
- PR #2840⁴¹⁶⁴ - Remove constexpr from a void function
- Issue #2839⁴¹⁶⁵ - memcpy buffer overflow: load_construct_data() and std::complex members

⁴¹⁴³ <https://github.com/TheHPXProject/hpx/issues/2862>

⁴¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2861>

⁴¹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2860>

⁴¹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2852>

⁴¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2858>

⁴¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2857>

⁴¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2856>

⁴¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2855>

⁴¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/2854>

⁴¹⁵² <https://github.com/TheHPXProject/hpx/pull/2853>

⁴¹⁵³ <https://github.com/TheHPXProject/hpx/pull/2851>

⁴¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2850>

⁴¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2849>

⁴¹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2848>

⁴¹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2847>

⁴¹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2846>

⁴¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2845>

⁴¹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/2844>

⁴¹⁶¹ <https://github.com/TheHPXProject/hpx/issues/2843>

⁴¹⁶² <https://github.com/TheHPXProject/hpx/pull/2842>

⁴¹⁶³ <https://github.com/TheHPXProject/hpx/pull/2841>

⁴¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2840>

⁴¹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2839>

- [Issue #2835](#)⁴¹⁶⁶ - `constexpr` functions with void return type break compilation with CUDA 8.0
- [Issue #2834](#)⁴¹⁶⁷ - One suspicion in `parallel::detail::handle_exception`
- [PR #2833](#)⁴¹⁶⁸ - Implement `parallel::merge`
- [PR #2832](#)⁴¹⁶⁹ - Fix a strange thing in `parallel::util::detail::handle_local_exceptions`. (Fix #2818)
- [PR #2830](#)⁴¹⁷⁰ - Break the debugger when a test failed
- [Issue #2831](#)⁴¹⁷¹ - `parallel/executors/execution_fwd.hpp` causes compilation failure in C++11 mode.
- [PR #2829](#)⁴¹⁷² - Implement an API for asynchronous pack traversal
- [PR #2828](#)⁴¹⁷³ - Split unit test builds on CircleCI to avoid timeouts
- [Issue #2827](#)⁴¹⁷⁴ - failure to compile `hello_world` example with `-Werror`
- [PR #2824](#)⁴¹⁷⁵ - Making sure promises are marked as started when used as continuations
- [PR #2823](#)⁴¹⁷⁶ - Add documentation for `partitioned_vector_view`
- [Issue #2822](#)⁴¹⁷⁷ - Yet another issue with `wait_for` similar to #2796
- [PR #2821](#)⁴¹⁷⁸ - Fix bugs and improve that about `HPX_HAVE_CXX11_AUTO_RETURN_VALUE` of CMake
- [PR #2820](#)⁴¹⁷⁹ - Support C++11 in benchmark codes of `parallel::partition` and `parallel::partition_copy`
- [PR #2819](#)⁴¹⁸⁰ - Fix compile errors in unit test of container version of `parallel::partition`
- [Issue #2818](#)⁴¹⁸¹ - A strange thing in `parallel::util::detail::handle_local_exceptions`
- [Issue #2815](#)⁴¹⁸² - HPX fails to compile with `HPX_WITH_CUDA=ON` and the new CUDA 9.0 RC
- [Issue #2814](#)⁴¹⁸³ - Using 'gmakeN' after 'cmake' produces error in `src/CMakeFiles/hpx.dir/runtime/agas/addressing_service.cpp.o`
- [PR #2813](#)⁴¹⁸⁴ - Properly support `[[noreturn]]` attribute if available
- [Issue #2812](#)⁴¹⁸⁵ - Compilation fails with gcc 7.1.1
- [PR #2811](#)⁴¹⁸⁶ - Adding `hpx::launch::lazy` and support for `async`, `dataflow`, and `future::then`
- [PR #2810](#)⁴¹⁸⁷ - Add option allowing to disable deprecation warning
- [PR #2809](#)⁴¹⁸⁸ - Disable throttling scheduler if HWLOC is not found/used

⁴¹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/2835>

⁴¹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/2834>

⁴¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2833>

⁴¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2832>

⁴¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2830>

⁴¹⁷¹ <https://github.com/TheHPXProject/hpx/issues/2831>

⁴¹⁷² <https://github.com/TheHPXProject/hpx/pull/2829>

⁴¹⁷³ <https://github.com/TheHPXProject/hpx/pull/2828>

⁴¹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/2827>

⁴¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2824>

⁴¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2823>

⁴¹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2822>

⁴¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2821>

⁴¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2820>

⁴¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2819>

⁴¹⁸¹ <https://github.com/TheHPXProject/hpx/issues/2818>

⁴¹⁸² <https://github.com/TheHPXProject/hpx/issues/2815>

⁴¹⁸³ <https://github.com/TheHPXProject/hpx/issues/2814>

⁴¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2813>

⁴¹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2812>

⁴¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2811>

⁴¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2810>

⁴¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2809>

- PR #2808⁴¹⁸⁹ - Fix compile errors on some environments of `parallel::partition`
- Issue #2807⁴¹⁹⁰ - Difficulty building with `HPX_WITH_HWLOC=Off`
- PR #2806⁴¹⁹¹ - Partitioned vector
- PR #2805⁴¹⁹² - Serializing collections with non-default constructible data
- PR #2802⁴¹⁹³ - Fix FreeBSD 11
- Issue #2801⁴¹⁹⁴ - Rate limiting techniques in `io_service`
- Issue #2800⁴¹⁹⁵ - New Launch Policy: `async_if`
- PR #2799⁴¹⁹⁶ - Fix a unit test failure on GCC in `tuple_cat`
- PR #2798⁴¹⁹⁷ - bump minimum required `cmake` to 3.0 in test
- PR #2797⁴¹⁹⁸ - Making sure `future::wait_for` et.al. work properly for action results
- Issue #2796⁴¹⁹⁹ - `wait_for` does always in “deferred” state for calls on remote localities
- Issue #2795⁴²⁰⁰ - Serialization of types without default constructor
- PR #2794⁴²⁰¹ - Fixing test for `partitioned_vector` iteration
- PR #2792⁴²⁰² - Implemented segmented find and its variations for partitioned vector
- PR #2791⁴²⁰³ - Circumvent scary warning about placement new
- PR #2790⁴²⁰⁴ - Fix OSX build
- PR #2789⁴²⁰⁵ - Resource partitioner
- PR #2788⁴²⁰⁶ - Adapt `parallel::is_heap` and `parallel::is_heap_until` to Ranges TS
- PR #2787⁴²⁰⁷ - Unwrap hotfixes
- PR #2786⁴²⁰⁸ - Update CMake Minimum Version to 3.3.2 (refs #2565)
- Issue #2785⁴²⁰⁹ - Issues with masks and `cpuset`
- PR #2784⁴²¹⁰ - Error with reduce and transform reduce fixed
- PR #2783⁴²¹¹ - StackOverflow integration with `libsigsegv`

⁴¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2808>

⁴¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2807>

⁴¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/2806>

⁴¹⁹² <https://github.com/TheHPXProject/hpx/pull/2805>

⁴¹⁹³ <https://github.com/TheHPXProject/hpx/pull/2802>

⁴¹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2801>

⁴¹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2800>

⁴¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2799>

⁴¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2798>

⁴¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2797>

⁴¹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/2796>

⁴²⁰⁰ <https://github.com/TheHPXProject/hpx/issues/2795>

⁴²⁰¹ <https://github.com/TheHPXProject/hpx/pull/2794>

⁴²⁰² <https://github.com/TheHPXProject/hpx/pull/2792>

⁴²⁰³ <https://github.com/TheHPXProject/hpx/pull/2791>

⁴²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2790>

⁴²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2789>

⁴²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2788>

⁴²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2787>

⁴²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2786>

⁴²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2785>

⁴²¹⁰ <https://github.com/TheHPXProject/hpx/pull/2784>

⁴²¹¹ <https://github.com/TheHPXProject/hpx/pull/2783>

- PR #2782⁴²¹² - Replace boost::atomic with std::atomic (where possible)
- PR #2781⁴²¹³ - Check for and optionally use [[deprecated]] attribute
- PR #2780⁴²¹⁴ - Adding empty (but non-trivial) destructor to circumvent warnings
- PR #2779⁴²¹⁵ - Exception info tweaks
- PR #2778⁴²¹⁶ - Implement parallel::partition
- PR #2777⁴²¹⁷ - Improve error handling in gather_here/gather_there
- PR #2776⁴²¹⁸ - Fix a bug in compiler version check
- PR #2775⁴²¹⁹ - Fix compilation when HPX_WITH_LOGGING is OFF
- PR #2774⁴²²⁰ - Removing dependency on Boost.Date_Time
- PR #2773⁴²²¹ - Add sync_images() method to spmd_block class
- PR #2772⁴²²² - Adding documentation for PAPI counters
- PR #2771⁴²²³ - Removing boost preprocessor dependency
- PR #2770⁴²²⁴ - Adding test, fixing deadlock in config registry
- PR #2769⁴²²⁵ - Remove some other warnings and errors detected by clang 5.0
- Issue #2768⁴²²⁶ - Is there iterator tag for HPX?
- PR #2767⁴²²⁷ - Improvements to continuation annotation
- PR #2765⁴²²⁸ - gcc split stack support for HPX threads #620
- PR #2764⁴²²⁹ - Fix some uses of begin/end, remove unnecessary includes
- PR #2763⁴²³⁰ - Bump minimal Boost version to 1.55.0
- PR #2762⁴²³¹ - hpx::partitioned_vector serializer
- PR #2761⁴²³² - Adding configuration summary to cmake output and -hpx:info
- PR #2760⁴²³³ - Removing 1d_hydro example as it is broken
- PR #2758⁴²³⁴ - Remove various warnings detected by clang 5.0

⁴²¹² <https://github.com/TheHPXProject/hpx/pull/2782>
⁴²¹³ <https://github.com/TheHPXProject/hpx/pull/2781>
⁴²¹⁴ <https://github.com/TheHPXProject/hpx/pull/2780>
⁴²¹⁵ <https://github.com/TheHPXProject/hpx/pull/2779>
⁴²¹⁶ <https://github.com/TheHPXProject/hpx/pull/2778>
⁴²¹⁷ <https://github.com/TheHPXProject/hpx/pull/2777>
⁴²¹⁸ <https://github.com/TheHPXProject/hpx/pull/2776>
⁴²¹⁹ <https://github.com/TheHPXProject/hpx/pull/2775>
⁴²²⁰ <https://github.com/TheHPXProject/hpx/pull/2774>
⁴²²¹ <https://github.com/TheHPXProject/hpx/pull/2773>
⁴²²² <https://github.com/TheHPXProject/hpx/pull/2772>
⁴²²³ <https://github.com/TheHPXProject/hpx/pull/2771>
⁴²²⁴ <https://github.com/TheHPXProject/hpx/pull/2770>
⁴²²⁵ <https://github.com/TheHPXProject/hpx/pull/2769>
⁴²²⁶ <https://github.com/TheHPXProject/hpx/issues/2768>
⁴²²⁷ <https://github.com/TheHPXProject/hpx/pull/2767>
⁴²²⁸ <https://github.com/TheHPXProject/hpx/pull/2765>
⁴²²⁹ <https://github.com/TheHPXProject/hpx/pull/2764>
⁴²³⁰ <https://github.com/TheHPXProject/hpx/pull/2763>
⁴²³¹ <https://github.com/TheHPXProject/hpx/pull/2762>
⁴²³² <https://github.com/TheHPXProject/hpx/pull/2761>
⁴²³³ <https://github.com/TheHPXProject/hpx/pull/2760>
⁴²³⁴ <https://github.com/TheHPXProject/hpx/pull/2758>

- [Issue #2757](#)⁴²³⁵ - In case of a “raw thread” is needed per core for implementing parallel algorithm, what is good practice in HPX?
- [PR #2756](#)⁴²³⁶ - Allowing for LCOs to be simple components
- [PR #2755](#)⁴²³⁷ - Removing make_index_pack_unrolled
- [PR #2754](#)⁴²³⁸ - Implement parallel::unique_copy
- [PR #2753](#)⁴²³⁹ - Fixing detection of [[fallthrough]] attribute
- [PR #2752](#)⁴²⁴⁰ - New thread priority names
- [PR #2751](#)⁴²⁴¹ - Replace boost::exception with proposed exception_info
- [PR #2750](#)⁴²⁴² - Replace boost::iterator_range
- [PR #2749](#)⁴²⁴³ - Fixing hdf5 examples
- [Issue #2748](#)⁴²⁴⁴ - HPX fails to build with enabled hdf5 examples
- [Issue #2747](#)⁴²⁴⁵ - Inherited task priorities break certain DAG optimizations
- [Issue #2746](#)⁴²⁴⁶ - HPX segfaulting with valgrind
- [PR #2745](#)⁴²⁴⁷ - Adding extended arithmetic performance counters
- [PR #2744](#)⁴²⁴⁸ - Adding ability to statistics counters to reset base counter
- [Issue #2743](#)⁴²⁴⁹ - Statistics counter does not support resetting
- [PR #2742](#)⁴²⁵⁰ - Making sure Vc V2 builds without additional HPX configuration flags
- [PR #2741](#)⁴²⁵¹ - Deprecate unwrapped and implement unwrap and unwrapping
- [PR #2740](#)⁴²⁵² - Coroutine stackoverflow detection for linux/posix; [Issue #2408](#)
- [PR #2739](#)⁴²⁵³ - Add files via upload
- [PR #2738](#)⁴²⁵⁴ - Appveyor support
- [PR #2737](#)⁴²⁵⁵ - Fixing 2735
- [Issue #2736](#)⁴²⁵⁶ - 1d_hydro example doesn't work
- [Issue #2735](#)⁴²⁵⁷ - partitioned_vector_subview test failing

⁴²³⁵ <https://github.com/TheHPXProject/hpx/issues/2757>

⁴²³⁶ <https://github.com/TheHPXProject/hpx/pull/2756>

⁴²³⁷ <https://github.com/TheHPXProject/hpx/pull/2755>

⁴²³⁸ <https://github.com/TheHPXProject/hpx/pull/2754>

⁴²³⁹ <https://github.com/TheHPXProject/hpx/pull/2753>

⁴²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2752>

⁴²⁴¹ <https://github.com/TheHPXProject/hpx/pull/2751>

⁴²⁴² <https://github.com/TheHPXProject/hpx/pull/2750>

⁴²⁴³ <https://github.com/TheHPXProject/hpx/pull/2749>

⁴²⁴⁴ <https://github.com/TheHPXProject/hpx/issues/2748>

⁴²⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2747>

⁴²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2746>

⁴²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2745>

⁴²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2744>

⁴²⁴⁹ <https://github.com/TheHPXProject/hpx/issues/2743>

⁴²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2742>

⁴²⁵¹ <https://github.com/TheHPXProject/hpx/pull/2741>

⁴²⁵² <https://github.com/TheHPXProject/hpx/pull/2740>

⁴²⁵³ <https://github.com/TheHPXProject/hpx/pull/2739>

⁴²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2738>

⁴²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2737>

⁴²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2736>

⁴²⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2735>

- PR #2734⁴²⁵⁸ - Add C++11 range utilities
- PR #2733⁴²⁵⁹ - Adapting iterator requirements for parallel algorithms
- PR #2732⁴²⁶⁰ - Integrate C++ Co-arrays
- PR #2731⁴²⁶¹ - Adding on_migrated event handler to migratable component instances
- Issue #2729⁴²⁶² - Add on_migrated() event handler to migratable components
- Issue #2728⁴²⁶³ - Why Projection is needed in parallel algorithms?
- PR #2727⁴²⁶⁴ - Cmake files for StackOverflow Detection
- PR #2726⁴²⁶⁵ - CMake for Stack Overflow Detection
- PR #2725⁴²⁶⁶ - Implemented segmented algorithms for partitioned vector
- PR #2724⁴²⁶⁷ - Fix examples in Action documentation
- PR #2723⁴²⁶⁸ - Enable lcos::channel<T>::register_as
- Issue #2722⁴²⁶⁹ - channel register_as() failing on compilation
- PR #2721⁴²⁷⁰ - Mind map
- PR #2720⁴²⁷¹ - reorder forward declarations to get rid of C++14-only auto return types
- PR #2719⁴²⁷² - Add documentation for partitioned_vector and add features in pack.hpp
- Issue #2718⁴²⁷³ - Some forward declarations in execution_fwd.hpp aren't C++11-compatible
- PR #2717⁴²⁷⁴ - Config support for fallthrough attribute
- PR #2716⁴²⁷⁵ - Implement parallel::partition_copy
- PR #2715⁴²⁷⁶ - initial import of icu string serializer
- PR #2714⁴²⁷⁷ - initial import of valarray serializer
- PR #2713⁴²⁷⁸ - Remove slashes before CMAKE_FILES_DIRECTORY variables
- PR #2712⁴²⁷⁹ - Fixing wait for 1751
- PR #2711⁴²⁸⁰ - Adjust code for minimal supported GCC having being bumped to 4.9

⁴²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2734>

⁴²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2733>

⁴²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2732>

⁴²⁶¹ <https://github.com/TheHPXProject/hpx/pull/2731>

⁴²⁶² <https://github.com/TheHPXProject/hpx/issues/2729>

⁴²⁶³ <https://github.com/TheHPXProject/hpx/issues/2728>

⁴²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2727>

⁴²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2726>

⁴²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2725>

⁴²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2724>

⁴²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2723>

⁴²⁶⁹ <https://github.com/TheHPXProject/hpx/issues/2722>

⁴²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2721>

⁴²⁷¹ <https://github.com/TheHPXProject/hpx/pull/2720>

⁴²⁷² <https://github.com/TheHPXProject/hpx/pull/2719>

⁴²⁷³ <https://github.com/TheHPXProject/hpx/issues/2718>

⁴²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2717>

⁴²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2716>

⁴²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2715>

⁴²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2714>

⁴²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2713>

⁴²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2712>

⁴²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2711>

- PR #2710⁴²⁸¹ - Adding code of conduct
- PR #2709⁴²⁸² - Fixing UB in destroy tests
- PR #2708⁴²⁸³ - Add inline to prevent multiple definition issue
- Issue #2707⁴²⁸⁴ - Multiple defined symbols for task_block.hpp in VS2015
- PR #2706⁴²⁸⁵ - Adding .clang-format file
- PR #2704⁴²⁸⁶ - Add a synchronous mapping API
- Issue #2703⁴²⁸⁷ - Request: Add the .clang-format file to the repository
- Issue #2702⁴²⁸⁸ - STELLAR-GROUP/Vc slower than VCv1 possibly due to wrong instructions generated
- Issue #2701⁴²⁸⁹ - Datapar with STELLAR-GROUP/Vc requires obscure flag
- Issue #2700⁴²⁹⁰ - Naming inconsistency in parallel algorithms
- Issue #2699⁴²⁹¹ - Iterator requirements are different from standard in parallel copy_if.
- PR #2698⁴²⁹² - Properly releasing parcelport write handlers
- Issue #2697⁴²⁹³ - Compile error in addressing_service.cpp
- Issue #2696⁴²⁹⁴ - Building and using HPX statically: undefined references from runtime_support_server.cpp
- Issue #2695⁴²⁹⁵ - Executor changes cause compilation failures
- PR #2694⁴²⁹⁶ - Refining C++ language mode detection for MSVC
- PR #2693⁴²⁹⁷ - P0443 r2
- PR #2692⁴²⁹⁸ - Partially reverting changes to parcel_await
- Issue #2689⁴²⁹⁹ - HPX build fails when HPX_WITH_CUDA is enabled
- PR #2688⁴³⁰⁰ - Make Cuda Clang builds pass
- PR #2687⁴³⁰¹ - Add an is_tuple_like trait for sequenceable type detection
- PR #2686⁴³⁰² - Allowing throttling scheduler to be used without idle backoff
- PR #2685⁴³⁰³ - Add support of std::array to hpx::util::tuple_size and tuple_element

⁴²⁸¹ <https://github.com/TheHPXProject/hpx/pull/2710>

⁴²⁸² <https://github.com/TheHPXProject/hpx/pull/2709>

⁴²⁸³ <https://github.com/TheHPXProject/hpx/pull/2708>

⁴²⁸⁴ <https://github.com/TheHPXProject/hpx/issues/2707>

⁴²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2706>

⁴²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2704>

⁴²⁸⁷ <https://github.com/TheHPXProject/hpx/issues/2703>

⁴²⁸⁸ <https://github.com/TheHPXProject/hpx/issues/2702>

⁴²⁸⁹ <https://github.com/TheHPXProject/hpx/issues/2701>

⁴²⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2700>

⁴²⁹¹ <https://github.com/TheHPXProject/hpx/issues/2699>

⁴²⁹² <https://github.com/TheHPXProject/hpx/pull/2698>

⁴²⁹³ <https://github.com/TheHPXProject/hpx/issues/2697>

⁴²⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2696>

⁴²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2695>

⁴²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2694>

⁴²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2693>

⁴²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2692>

⁴²⁹⁹ <https://github.com/TheHPXProject/hpx/issues/2689>

⁴³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2688>

⁴³⁰¹ <https://github.com/TheHPXProject/hpx/pull/2687>

⁴³⁰² <https://github.com/TheHPXProject/hpx/pull/2686>

⁴³⁰³ <https://github.com/TheHPXProject/hpx/pull/2685>

- PR #2684⁴³⁰⁴ - Adding new statistics performance counters
- PR #2683⁴³⁰⁵ - Replace boost::exception_ptr with std::exception_ptr
- Issue #2682⁴³⁰⁶ - HPX does not compile with HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF=OFF
- PR #2681⁴³⁰⁷ - Attempt to fix problem in managed_component_base
- PR #2680⁴³⁰⁸ - Fix bad size during archive creation
- Issue #2679⁴³⁰⁹ - Mismatch between size of archive and container
- Issue #2678⁴³¹⁰ - In parallel algorithm, other tasks are executed to the end even if an exception occurs in any task.
- PR #2677⁴³¹¹ - Adding include check for std::addressof
- PR #2676⁴³¹² - Adding parallel::destroy and destroy_n
- PR #2675⁴³¹³ - Making sure statistics counters work as expected
- PR #2674⁴³¹⁴ - Turning assertions into exceptions
- PR #2673⁴³¹⁵ - Inhibit direct conversion from future<future<T>> -> future<void>
- PR #2672⁴³¹⁶ - C++17 invoke forms
- PR #2671⁴³¹⁷ - Adding uninitialized_value_construct and uninitialized_value_construct_n
- PR #2670⁴³¹⁸ - Integrate spmd multidimensional views for partitioned_vectors
- PR #2669⁴³¹⁹ - Adding uninitialized_default_construct and uninitialized_default_construct_n
- PR #2668⁴³²⁰ - Fixing documentation index
- Issue #2667⁴³²¹ - Ambiguity of nested hpx::future<void>'s
- Issue #2666⁴³²² - Statistics Performance counter is not working
- PR #2664⁴³²³ - Adding uninitialized_move and uninitialized_move_n
- Issue #2663⁴³²⁴ - Seg fault in managed_component::get_base_gid, possibly cause by util::reinitializable_static
- Issue #2662⁴³²⁵ - Crash in managed_component::get_base_gid due to problem with util::reinitializable_static
- PR #2665⁴³²⁶ - Hide the detail namespace in doxygen per default

⁴³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2684>

⁴³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2683>

⁴³⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2682>

⁴³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2681>

⁴³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2680>

⁴³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2679>

⁴³¹⁰ <https://github.com/TheHPXProject/hpx/issues/2678>

⁴³¹¹ <https://github.com/TheHPXProject/hpx/pull/2677>

⁴³¹² <https://github.com/TheHPXProject/hpx/pull/2676>

⁴³¹³ <https://github.com/TheHPXProject/hpx/pull/2675>

⁴³¹⁴ <https://github.com/TheHPXProject/hpx/pull/2674>

⁴³¹⁵ <https://github.com/TheHPXProject/hpx/pull/2673>

⁴³¹⁶ <https://github.com/TheHPXProject/hpx/pull/2672>

⁴³¹⁷ <https://github.com/TheHPXProject/hpx/pull/2671>

⁴³¹⁸ <https://github.com/TheHPXProject/hpx/pull/2670>

⁴³¹⁹ <https://github.com/TheHPXProject/hpx/pull/2669>

⁴³²⁰ <https://github.com/TheHPXProject/hpx/pull/2668>

⁴³²¹ <https://github.com/TheHPXProject/hpx/issues/2667>

⁴³²² <https://github.com/TheHPXProject/hpx/issues/2666>

⁴³²³ <https://github.com/TheHPXProject/hpx/pull/2664>

⁴³²⁴ <https://github.com/TheHPXProject/hpx/issues/2663>

⁴³²⁵ <https://github.com/TheHPXProject/hpx/issues/2662>

⁴³²⁶ <https://github.com/TheHPXProject/hpx/pull/2665>

- PR #2660⁴³²⁷ - Add documentation to `hpx::util::unwrapped` and `hpx::util::unwrapped2`
- PR #2659⁴³²⁸ - Improve integration with `vcpkg`
- PR #2658⁴³²⁹ - Unify `access_data` trait for use in both, serialization and de-serialization
- PR #2657⁴³³⁰ - Removing `hpx::lcos::queue<T>`
- PR #2656⁴³³¹ - Reduce `MAX_TERMINATED_THREADS` default, improve memory use on manycore cpus
- PR #2655⁴³³² - Maintenance for emulate-deleted macros
- PR #2654⁴³³³ - Implement parallel `is_heap` and `is_heap_until`
- PR #2653⁴³³⁴ - Drop support for VS2013
- PR #2652⁴³³⁵ - This patch makes sure that all parcels in a batch are properly handled
- PR #2649⁴³³⁶ - Update docs (Table 18) - move `transform` to end
- Issue #2647⁴³³⁷ - `hpx::parcels::detail::parcel_data::has_continuation_` is uninitialized
- Issue #2644⁴³³⁸ - Some `.vcxproj` in the `HPX.sln` fail to build
- Issue #2641⁴³³⁹ - `hpx::lcos::queue` should be deprecated
- PR #2640⁴³⁴⁰ - A new throttling policy with public APIs to suspend/resume
- PR #2639⁴³⁴¹ - Fix a tiny typo in tutorial.
- Issue #2638⁴³⁴² - Invalid return type 'void' of `constexpr` function
- PR #2636⁴³⁴³ - Add and use `HPX_MSVC_WARNING_PRAGMA` for `#pragma` warning
- PR #2633⁴³⁴⁴ - Distributed `define_spmc_block`
- PR #2632⁴³⁴⁵ - Making sure container serialization uses size-compatible types
- PR #2631⁴³⁴⁶ - Add `lcos::local::one_element_channel`
- PR #2629⁴³⁴⁷ - Move `unordered_map` out of `parcels` into `hpx/concurrent`
- PR #2628⁴³⁴⁸ - Making sure that shutdown does not hang
- PR #2627⁴³⁴⁹ - Fix serialization

⁴³²⁷ <https://github.com/TheHPXProject/hpx/pull/2660>
⁴³²⁸ <https://github.com/TheHPXProject/hpx/pull/2659>
⁴³²⁹ <https://github.com/TheHPXProject/hpx/pull/2658>
⁴³³⁰ <https://github.com/TheHPXProject/hpx/pull/2657>
⁴³³¹ <https://github.com/TheHPXProject/hpx/pull/2656>
⁴³³² <https://github.com/TheHPXProject/hpx/pull/2655>
⁴³³³ <https://github.com/TheHPXProject/hpx/pull/2654>
⁴³³⁴ <https://github.com/TheHPXProject/hpx/pull/2653>
⁴³³⁵ <https://github.com/TheHPXProject/hpx/pull/2652>
⁴³³⁶ <https://github.com/TheHPXProject/hpx/pull/2649>
⁴³³⁷ <https://github.com/TheHPXProject/hpx/issues/2647>
⁴³³⁸ <https://github.com/TheHPXProject/hpx/issues/2644>
⁴³³⁹ <https://github.com/TheHPXProject/hpx/issues/2641>
⁴³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2640>
⁴³⁴¹ <https://github.com/TheHPXProject/hpx/pull/2639>
⁴³⁴² <https://github.com/TheHPXProject/hpx/issues/2638>
⁴³⁴³ <https://github.com/TheHPXProject/hpx/pull/2636>
⁴³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2633>
⁴³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2632>
⁴³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2631>
⁴³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2629>
⁴³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2628>
⁴³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2627>

- PR #2626⁴³⁵⁰ - Generate `cmake_variables.qbk` and `cmake_toolchains.qbk` outside of the source tree
- PR #2625⁴³⁵¹ - Supporting `-std=c++17` flag
- PR #2624⁴³⁵² - Fixing a small `cmake` typo
- PR #2622⁴³⁵³ - Update CMake minimum required version to 3.0.2 (closes #2621)
- Issue #2621⁴³⁵⁴ - Compiling `hpx` master fails with `/usr/bin/ld: final link failed: Bad value`
- PR #2620⁴³⁵⁵ - Remove warnings due to some captured variables
- PR #2619⁴³⁵⁶ - LF multiple parcels
- PR #2618⁴³⁵⁷ - Some fixes to `libfabric` that didn't get caught before the merge
- PR #2617⁴³⁵⁸ - Adding `hpx::local_new`
- PR #2616⁴³⁵⁹ - Documentation: Extract all entities in order to autolink functions correctly
- Issue #2615⁴³⁶⁰ - Documentation: Linking functions is broken
- PR #2614⁴³⁶¹ - Adding serialization for `std::deque`
- PR #2613⁴³⁶² - We need to link with `boost.thread` and `boost.chrono` if we use `boost.context`
- PR #2612⁴³⁶³ - Making sure `for_loop_n(par, ...)` is actually executed in parallel
- PR #2611⁴³⁶⁴ - Add documentation to `invoke_fused` and `friends NFC`
- PR #2610⁴³⁶⁵ - Added reduction templates using an identity value
- PR #2608⁴³⁶⁶ - Fixing some unused vars in `inspect`
- PR #2607⁴³⁶⁷ - Fixed build for `mingw`
- PR #2606⁴³⁶⁸ - Supporting generic context for `boost >= 1.61`
- PR #2605⁴³⁶⁹ - `Parcelport libfabric3`
- PR #2604⁴³⁷⁰ - Adding allocator support to `promise` and `friends`
- PR #2603⁴³⁷¹ - Barrier hang
- PR #2602⁴³⁷² - Changes to scheduler to steal from one high-priority queue

⁴³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2626>
⁴³⁵¹ <https://github.com/TheHPXProject/hpx/pull/2625>
⁴³⁵² <https://github.com/TheHPXProject/hpx/pull/2624>
⁴³⁵³ <https://github.com/TheHPXProject/hpx/pull/2622>
⁴³⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2621>
⁴³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2620>
⁴³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2619>
⁴³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2618>
⁴³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2617>
⁴³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2616>
⁴³⁶⁰ <https://github.com/TheHPXProject/hpx/issues/2615>
⁴³⁶¹ <https://github.com/TheHPXProject/hpx/pull/2614>
⁴³⁶² <https://github.com/TheHPXProject/hpx/pull/2613>
⁴³⁶³ <https://github.com/TheHPXProject/hpx/pull/2612>
⁴³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2611>
⁴³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2610>
⁴³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2608>
⁴³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2607>
⁴³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2606>
⁴³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2605>
⁴³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2604>
⁴³⁷¹ <https://github.com/TheHPXProject/hpx/pull/2603>
⁴³⁷² <https://github.com/TheHPXProject/hpx/pull/2602>

- Issue #2601⁴³⁷³ - High priority tasks are not executed first
- PR #2600⁴³⁷⁴ - Compat fixes
- PR #2599⁴³⁷⁵ - Compatibility layer for threading support
- PR #2598⁴³⁷⁶ - V1.1
- PR #2597⁴³⁷⁷ - Release V1.0
- PR #2592⁴³⁷⁸ - First attempt to introduce `spmd_block` in `hpx`
- PR #2586⁴³⁷⁹ - `local_segment` in `segmented_iterator_traits`
- Issue #2584⁴³⁸⁰ - Add allocator support to `promise`, `packaged_task` and friends
- PR #2576⁴³⁸¹ - Add missing dependencies of `cuda` based tests
- PR #2575⁴³⁸² - Remove warnings due to some captured variables
- Issue #2574⁴³⁸³ - MSVC 2015 Compiler crash when building HPX
- Issue #2568⁴³⁸⁴ - Remove `throttle_scheduler` as it has been abandoned
- Issue #2566⁴³⁸⁵ - Add an inline versioning namespace before 1.0 release
- Issue #2565⁴³⁸⁶ - Raise minimal `cmake` version requirement
- PR #2556⁴³⁸⁷ - Fixing scan partitioner
- PR #2546⁴³⁸⁸ - Broadcast async
- Issue #2543⁴³⁸⁹ - `make install` fails due to a non-existing `.so` file
- PR #2495⁴³⁹⁰ - `wait_or_add_new` returning `thread_id_type`
- Issue #2480⁴³⁹¹ - Unable to register new performance counter
- Issue #2471⁴³⁹² - no type named `'fcontext_t'` in namespace
- Issue #2456⁴³⁹³ - Re-implement `hpx::util::unwrapped`
- Issue #2455⁴³⁹⁴ - Add more arithmetic performance counters
- PR #2454⁴³⁹⁵ - Fix a couple of warnings and compiler errors

⁴³⁷³ <https://github.com/TheHPXProject/hpx/issues/2601>

⁴³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2600>

⁴³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2599>

⁴³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2598>

⁴³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2597>

⁴³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2592>

⁴³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2586>

⁴³⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2584>

⁴³⁸¹ <https://github.com/TheHPXProject/hpx/pull/2576>

⁴³⁸² <https://github.com/TheHPXProject/hpx/pull/2575>

⁴³⁸³ <https://github.com/TheHPXProject/hpx/issues/2574>

⁴³⁸⁴ <https://github.com/TheHPXProject/hpx/issues/2568>

⁴³⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2566>

⁴³⁸⁶ <https://github.com/TheHPXProject/hpx/issues/2565>

⁴³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2556>

⁴³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2546>

⁴³⁸⁹ <https://github.com/TheHPXProject/hpx/issues/2543>

⁴³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2495>

⁴³⁹¹ <https://github.com/TheHPXProject/hpx/issues/2480>

⁴³⁹² <https://github.com/TheHPXProject/hpx/issues/2471>

⁴³⁹³ <https://github.com/TheHPXProject/hpx/issues/2456>

⁴³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2455>

⁴³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2454>

- PR #2453⁴³⁹⁶ - Timed executor support
- PR #2447⁴³⁹⁷ - Implementing new executor API (P0443)
- Issue #2439⁴³⁹⁸ - Implement executor proposal
- Issue #2408⁴³⁹⁹ - Stackoverflow detection for linux, e.g. based on libsigsegv
- PR #2377⁴⁴⁰⁰ - Add a customization point for put_parcel so we can override actions
- Issue #2368⁴⁴⁰¹ - HPX_ASSERT problem
- Issue #2324⁴⁴⁰² - Change default number of threads used to the maximum of the system
- Issue #2266⁴⁴⁰³ - hpx_0.9.99 make tests fail
- PR #2195⁴⁴⁰⁴ - Support for code completion in VIM
- Issue #2137⁴⁴⁰⁵ - Hpx does not compile over osx
- Issue #2092⁴⁴⁰⁶ - make tests should just build the tests
- Issue #2026⁴⁴⁰⁷ - Build HPX with Apple's clang
- Issue #1932⁴⁴⁰⁸ - hpx with PBS fails on multiple localities
- PR #1914⁴⁴⁰⁹ - Parallel heap algorithm implementations WIP
- Issue #1598⁴⁴¹⁰ - Disconnecting a locality results in segfault using heartbeat example
- Issue #1404⁴⁴¹¹ - unwrapped doesn't work with movable only types
- Issue #1400⁴⁴¹² - hpx::util::unwrapped doesn't work with non-future types
- Issue #1205⁴⁴¹³ - TSS is broken
- Issue #1126⁴⁴¹⁴ - vector<future<T> > does not work gracefully with dataflow, when_all and unwrapped
- Issue #1056⁴⁴¹⁵ - Thread manager cleanup
- Issue #863⁴⁴¹⁶ - Futures should not require a default constructor
- Issue #856⁴⁴¹⁷ - Allow runtime_mode_connect to be used with security enabled
- Issue #726⁴⁴¹⁸ - Valgrind

⁴³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2453>

⁴³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2447>

⁴³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/2439>

⁴³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/2408>

⁴⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2377>

⁴⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/2368>

⁴⁴⁰² <https://github.com/TheHPXProject/hpx/issues/2324>

⁴⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/2266>

⁴⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2195>

⁴⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/2137>

⁴⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2092>

⁴⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/2026>

⁴⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1932>

⁴⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1914>

⁴⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/1598>

⁴⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/1404>

⁴⁴¹² <https://github.com/TheHPXProject/hpx/issues/1400>

⁴⁴¹³ <https://github.com/TheHPXProject/hpx/issues/1205>

⁴⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/1126>

⁴⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/1056>

⁴⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/863>

⁴⁴¹⁷ <https://github.com/TheHPXProject/hpx/issues/856>

⁴⁴¹⁸ <https://github.com/TheHPXProject/hpx/issues/726>

- [Issue #701](#)⁴⁴¹⁹ - Add RCR performance counter component
- [Issue #528](#)⁴⁴²⁰ - Add support for known failures and warning count/comparisons to `hpx_run_tests.py`

HPX V1.0.0 (Apr 24, 2017)

General changes

Here are some of the main highlights and changes for this release (in no particular order):

- Added the facility `hpx::split_future` which allows one to convert a `future<tuple<Ts...>>` into a `tuple<future<Ts>...>`. This functionality is not available when compiling *HPX* with VS2012.
- Added a new type of performance counter which allows one to return a list of values for each invocation. We also added a first counter of this type which collects a histogram of the times between parcels being created.
- Added new LCOs: `hpx::lcos::channel` and `hpx::lcos::local::channel` which are very similar to the well known channel constructs used in the Go language.
- Added new performance counters reporting the amount of data handled by the networking layer on a action-by-action basis (please see [PR #2289](#)⁴⁴²¹ for more details).
- Added a new facility `hpx::lcos::barrier`, replacing the equally named older one. The new facility has a slightly changed API and is much more efficient. Most notable, the new facility exposes a (global) function `hpx::lcos::barrier::synchronize()` which represents a global barrier across all localities.
- We have started to add support for vectorization to our parallel algorithm implementations. This support depends on using an external library, currently either Vc Library or `|boost_simd|`. Please see [Issue #2333](#)⁴⁴²² for a list of currently supported algorithms. This is an experimental feature and its implementation and/or API might change in the future. Please see this [blog-post](#)⁴⁴²³ for more information.
- The parameter sequence for the `hpx::parallel::transform_reduce` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17. The old overload can be still enabled at configure time by specifying `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to CMake.
- The algorithm `hpx::parallel::inner_product` has been renamed to `hpx::parallel::transform_reduce` to match the changes this algorithm has undergone while being moved to C++17. The old `inner_product` names can be still enabled at configure time by specifying `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to CMake.
- Added versions of `hpx::get_ptr` taking client side representations for component instances as their parameter (instead of a global id).
- Added the helper utility `hpx::performance_counters::performance_counter_set` helping to encapsulate a set of performance counters to be managed concurrently.
- All execution policies and related classes have been renamed to be consistent with the naming changes applied for C++17. All policies now live in the namespace `hpx::parallel::execution`. The old names can be still enabled at configure time by specifying `-DHPX_WITH_EXECUTION_POLICY_COMPATIBILITY=On` to CMake.
- The thread scheduling subsystem has undergone a major refactoring which results in significant performance improvements. We have also improved the performance of creating `hpx::future` and of various facilities handling those.

⁴⁴¹⁹ <https://github.com/TheHPXProject/hpx/issues/701>

⁴⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/528>

⁴⁴²¹ <https://github.com/TheHPXProject/hpx/pull/2289>

⁴⁴²² <https://github.com/TheHPXProject/hpx/issues/2333>

⁴⁴²³ <http://stellar-group.org/2016/09/vectorized-cpp-parallel-algorithms-with-hpx/>

- We have consolidated all of the code in `HPX.Compute` related to the integration of CUDA. `hpx::partitioned_vector` has been enabled to be usable with `hpx::compute::vector` which allows one to place the partitions on one or more GPU devices.
- Added new performance counters exposing various internals of the thread scheduling subsystem, such as the current idle- and busy-loop counters and instantaneous scheduler utilization.
- Extended and improved the use of the ITTNotify hooks allowing to collect performance counter data and function annotation information from within the Intel Amplifier tool.

Breaking changes

- We have dropped support for the gcc compiler versions V4.6 and 4.7. The minimal gcc version we now test on is gcc V4.8.
- We have removed (default) support for `boost::chrono` in interfaces, uses of it have been replaced with `std::chrono`. This facility can be still enabled at configure time by specifying `-DHPX_WITH_BOOST_CHRONO_COMPATIBILITY=On` to CMake.
- The parameter sequence for the `hpx::parallel::transform_reduce` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17.
- The algorithm `hpx::parallel::inner_product` has been renamed to `hpx::parallel::transform_reduce` to match the changes this algorithm has undergone while being moved to C++17.
- the build options `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` and `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY` are now disabled by default. Please change your code still depending on the deprecated interfaces.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #2596](#)⁴⁴²⁴ - Adding apex data
- [PR #2595](#)⁴⁴²⁵ - Remove obsolete file
- [Issue #2594](#)⁴⁴²⁶ - FindOpenCL.cmake mismatch with the official cmake module
- [PR #2592](#)⁴⁴²⁷ - First attempt to introduce `spmd_block` in `hpx`
- [Issue #2591](#)⁴⁴²⁸ - Feature request: continuation (then) which does not require the callable object to take a `future<R>` as parameter
- [PR #2588](#)⁴⁴²⁹ - Daint fixes
- [PR #2587](#)⁴⁴³⁰ - Fixing `transfer_(continuation)_action::schedule`
- [PR #2585](#)⁴⁴³¹ - Work around MSVC having an ICE when compiling with `-Ob2`
- [PR #2583](#)⁴⁴³² - changing 7zip command to 7za in `roll_release.sh`

⁴⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/2596>

⁴⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/2595>

⁴⁴²⁶ <https://github.com/TheHPXProject/hpx/issues/2594>

⁴⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/2592>

⁴⁴²⁸ <https://github.com/TheHPXProject/hpx/issues/2591>

⁴⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/2588>

⁴⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/2587>

⁴⁴³¹ <https://github.com/TheHPXProject/hpx/pull/2585>

⁴⁴³² <https://github.com/TheHPXProject/hpx/pull/2583>

- PR #2582⁴⁴³³ - First attempt to introduce `spmd_block` in `hpx`
- PR #2581⁴⁴³⁴ - Enable annotated function for parallel algorithms
- PR #2580⁴⁴³⁵ - First attempt to introduce `spmd_block` in `hpx`
- PR #2579⁴⁴³⁶ - Make thread NICE level setting an option
- PR #2578⁴⁴³⁷ - Implementing `enqueue` instead of busy wait when no sender is available
- PR #2577⁴⁴³⁸ - Retrieve `-std=c++11` consistent `nvcc` flag
- PR #2576⁴⁴³⁹ - Add missing dependencies of `cuda` based tests
- PR #2575⁴⁴⁴⁰ - Remove warnings due to some captured variables
- PR #2573⁴⁴⁴¹ - Attempt to resolve `resolve_locality`
- PR #2572⁴⁴⁴² - Adding APEX hooks to background thread
- PR #2571⁴⁴⁴³ - Pick up `hpx.ignore_batch_env` from config map
- PR #2570⁴⁴⁴⁴ - Add cmdline options `-hpx:print-counters-locally`
- PR #2569⁴⁴⁴⁵ - Fix `computeapi` unit tests
- PR #2567⁴⁴⁴⁶ - This adds another `barrier::synchronize` before registering performance counters
- PR #2564⁴⁴⁴⁷ - Cray static toolchain support
- PR #2563⁴⁴⁴⁸ - Fixed unhandled exception during startup
- PR #2562⁴⁴⁴⁹ - Remove `partitioned_vector.cu` from build tree when `nvcc` is used
- Issue #2561⁴⁴⁵⁰ - octo-tiger crash with commit `6e921495ff6c26f125d62629cbaad0525f14f7ab`
- PR #2560⁴⁴⁵¹ - Prevent `-Wundef` warnings on `Vc` version checks
- PR #2559⁴⁴⁵² - Allowing `CUDA` callback to set the future directly from an OS thread
- PR #2558⁴⁴⁵³ - Remove warnings due to float precisions
- PR #2557⁴⁴⁵⁴ - Removing bogus handling of compile flags for `CUDA`
- PR #2556⁴⁴⁵⁵ - Fixing scan partitioner

⁴⁴³³ <https://github.com/TheHPXProject/hpx/pull/2582>

⁴⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/2581>

⁴⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/2580>

⁴⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/2579>

⁴⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/2578>

⁴⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/2577>

⁴⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/2576>

⁴⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2575>

⁴⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/2573>

⁴⁴⁴² <https://github.com/TheHPXProject/hpx/pull/2572>

⁴⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/2571>

⁴⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2570>

⁴⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2569>

⁴⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2567>

⁴⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2564>

⁴⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2563>

⁴⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2562>

⁴⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/2561>

⁴⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/2560>

⁴⁴⁵² <https://github.com/TheHPXProject/hpx/pull/2559>

⁴⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/2558>

⁴⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2557>

⁴⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2556>

- [PR #2554](#)⁴⁴⁵⁶ - Add more diagnostics to error thrown from `find_appropriate_destination`
- [Issue #2555](#)⁴⁴⁵⁷ - No valid parcellport configured
- [PR #2553](#)⁴⁴⁵⁸ - Add `cmake cuda_arch` option
- [PR #2552](#)⁴⁴⁵⁹ - Remove incomplete datapar bindings to `libflatarray`
- [PR #2551](#)⁴⁴⁶⁰ - Rename `hwloc_topology` to `hwloc_topology_info`
- [PR #2550](#)⁴⁴⁶¹ - Apex api updates
- [PR #2549](#)⁴⁴⁶² - Pre-include `defines.hpp` to get the macro `HPX_HAVE_CUDA` value
- [PR #2548](#)⁴⁴⁶³ - Fixing issue with `disconnect`
- [PR #2546](#)⁴⁴⁶⁴ - Some fixes around `cuda clang partitioned_vector` example
- [PR #2545](#)⁴⁴⁶⁵ - Fix uses of the `Vc2` datapar flags; the value, not the type, should be passed to functions
- [PR #2542](#)⁴⁴⁶⁶ - Make `HPX_WITH_MALLOC` easier to use
- [PR #2541](#)⁴⁴⁶⁷ - avoid recompiles when enabling/disabling examples
- [PR #2540](#)⁴⁴⁶⁸ - Fixing usage of `target_link_libraries()`
- [PR #2539](#)⁴⁴⁶⁹ - fix `RPATH` behaviour
- [Issue #2538](#)⁴⁴⁷⁰ - `HPX_WITH_CUDA` corrupts compilation flags
- [PR #2537](#)⁴⁴⁷¹ - Add output of a Bazel Skylark extension for paths and compile options
- [PR #2536](#)⁴⁴⁷² - Add counter exposing total available memory to Windows as well
- [PR #2535](#)⁴⁴⁷³ - Remove obsolete support for security
- [Issue #2534](#)⁴⁴⁷⁴ - Remove command line option `--hpx:run-agas-server`
- [PR #2533](#)⁴⁴⁷⁵ - Pre-cache locality endpoints during bootstrap
- [PR #2532](#)⁴⁴⁷⁶ - Fixing handling of GIDs during serialization preprocessing
- [PR #2531](#)⁴⁴⁷⁷ - Amend uses of the term “functor”
- [PR #2529](#)⁴⁴⁷⁸ - added counter for reading available memory

⁴⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2554>

⁴⁴⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2555>

⁴⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2553>

⁴⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2552>

⁴⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2551>

⁴⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/2550>

⁴⁴⁶² <https://github.com/TheHPXProject/hpx/pull/2549>

⁴⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/2548>

⁴⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2546>

⁴⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2545>

⁴⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2542>

⁴⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2541>

⁴⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2540>

⁴⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2539>

⁴⁴⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2538>

⁴⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/2537>

⁴⁴⁷² <https://github.com/TheHPXProject/hpx/pull/2536>

⁴⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/2535>

⁴⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/2534>

⁴⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2533>

⁴⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2532>

⁴⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2531>

⁴⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2529>

- PR #2527⁴⁴⁷⁹ - Facilities to create actions from lambdas
- PR #2526⁴⁴⁸⁰ - Updated docs: HPX_WITH_EXAMPLES
- PR #2525⁴⁴⁸¹ - Remove warnings related to unused captured variables
- Issue #2524⁴⁴⁸² - CMAKE failed because it is missing: TCMALLOC_LIBRARY TCMALLOC_INCLUDE_DIR
- PR #2523⁴⁴⁸³ - Fixing compose_cb stack overflow
- PR #2522⁴⁴⁸⁴ - Instead of unlocking, ignore the lock while creating the message handler
- PR #2521⁴⁴⁸⁵ - Create LPROGRESS_ logging macro to simplify progress tracking and timings
- PR #2520⁴⁴⁸⁶ - Intel 17 support
- PR #2519⁴⁴⁸⁷ - Fix components example
- PR #2518⁴⁴⁸⁸ - Fixing parcel scheduling
- Issue #2517⁴⁴⁸⁹ - Race condition during Parcel Coalescing Handler creation
- Issue #2516⁴⁴⁹⁰ - HPX locks up when using at least 256 localities
- Issue #2515⁴⁴⁹¹ - error: Install cannot find “/lib/hpx/libparcel_coalescing.so.0.9.99” but I can see that file
- PR #2514⁴⁴⁹² - Making sure that all continuations of a shared_future are invoked in order
- PR #2513⁴⁴⁹³ - Fixing locks held during suspension
- PR #2512⁴⁴⁹⁴ - MPI Parcelport improvements and fixes related to the background work changes
- PR #2511⁴⁴⁹⁵ - Fixing bit-wise (zero-copy) serialization
- Issue #2509⁴⁴⁹⁶ - Linking errors in hwloc_topology
- PR #2508⁴⁴⁹⁷ - Added documentation for debugging with core files
- PR #2506⁴⁴⁹⁸ - Fixing background work invocations
- PR #2505⁴⁴⁹⁹ - Fix tuple serialization
- Issue #2504⁴⁵⁰⁰ - Ensure continuations are called in the order they have been attached
- PR #2503⁴⁵⁰¹ - Adding serialization support for Vc v2 (datapar)

⁴⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2527>

⁴⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2526>

⁴⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/2525>

⁴⁴⁸² <https://github.com/TheHPXProject/hpx/issues/2524>

⁴⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/2523>

⁴⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2522>

⁴⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2521>

⁴⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2520>

⁴⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2519>

⁴⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2518>

⁴⁴⁸⁹ <https://github.com/TheHPXProject/hpx/issues/2517>

⁴⁴⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2516>

⁴⁴⁹¹ <https://github.com/TheHPXProject/hpx/issues/2515>

⁴⁴⁹² <https://github.com/TheHPXProject/hpx/pull/2514>

⁴⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/2513>

⁴⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2512>

⁴⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2511>

⁴⁴⁹⁶ <https://github.com/TheHPXProject/hpx/issues/2509>

⁴⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2508>

⁴⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2506>

⁴⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2505>

⁴⁵⁰⁰ <https://github.com/TheHPXProject/hpx/issues/2504>

⁴⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/2503>

- PR #2502⁴⁵⁰² - Resolve various, minor compiler warnings
- PR #2501⁴⁵⁰³ - Some other fixes around cuda examples
- Issue #2500⁴⁵⁰⁴ - nvcc / cuda clang issue due to a missing -DHPX_WITH_CUDA flag
- PR #2499⁴⁵⁰⁵ - Adding support for std::array to wait_all and friends
- PR #2498⁴⁵⁰⁶ - Execute background work as HPX thread
- PR #2497⁴⁵⁰⁷ - Fixing configuration options for spinlock-deadlock detection
- PR #2496⁴⁵⁰⁸ - Accounting for different compilers in CrayKNL toolchain file
- PR #2494⁴⁵⁰⁹ - Adding component base class which ties a component instance to a given executor
- PR #2493⁴⁵¹⁰ - Enable controlling amount of pending threads which must be available to allow thread stealing
- PR #2492⁴⁵¹¹ - Adding new command line option -hpx:print-counter-reset
- PR #2491⁴⁵¹² - Resolve ambiguities when compiling with APEX
- PR #2490⁴⁵¹³ - Resuming threads waiting on future with higher priority
- Issue #2489⁴⁵¹⁴ - nvcc issue because -std=c++11 appears twice
- PR #2488⁴⁵¹⁵ - Adding performance counters exposing the internal idle and busy-loop counters
- PR #2487⁴⁵¹⁶ - Allowing for plain suspend to reschedule thread right away
- PR #2486⁴⁵¹⁷ - Only flag HPX code for CUDA if HPX_WITH_CUDA is set
- PR #2485⁴⁵¹⁸ - Making thread-queue parameters runtime-configurable
- PR #2484⁴⁵¹⁹ - Added atomic counter for parcel-destinations
- PR #2483⁴⁵²⁰ - Added priority-queue lifo scheduler
- PR #2482⁴⁵²¹ - Changing scheduler to steal only if more than a minimal number of tasks are available
- PR #2481⁴⁵²² - Extending command line option -hpx:print-counter-destination to support value 'none'
- PR #2479⁴⁵²³ - Added option to disable signal handler
- PR #2478⁴⁵²⁴ - Making sure the sine performance counter module gets loaded only for the corresponding example

⁴⁵⁰² <https://github.com/TheHPXProject/hpx/pull/2502>

⁴⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/2501>

⁴⁵⁰⁴ <https://github.com/TheHPXProject/hpx/issues/2500>

⁴⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2499>

⁴⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2498>

⁴⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2497>

⁴⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2496>

⁴⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2494>

⁴⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/2493>

⁴⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/2492>

⁴⁵¹² <https://github.com/TheHPXProject/hpx/pull/2491>

⁴⁵¹³ <https://github.com/TheHPXProject/hpx/pull/2490>

⁴⁵¹⁴ <https://github.com/TheHPXProject/hpx/issues/2489>

⁴⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/2488>

⁴⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/2487>

⁴⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/2486>

⁴⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/2485>

⁴⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/2484>

⁴⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/2483>

⁴⁵²¹ <https://github.com/TheHPXProject/hpx/pull/2482>

⁴⁵²² <https://github.com/TheHPXProject/hpx/pull/2481>

⁴⁵²³ <https://github.com/TheHPXProject/hpx/pull/2479>

⁴⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/2478>

- Issue #2477⁴⁵²⁵ - Breaking at a throw statement
- PR #2476⁴⁵²⁶ - Annotated function
- PR #2475⁴⁵²⁷ - Ensure that using `%osthread%` during logging will not throw for non-hpx threads
- PR #2474⁴⁵²⁸ - Remove now superficial `non_direct` actions from `base_lco` and friends
- PR #2473⁴⁵²⁹ - Refining support for `ITTNotify`
- PR #2472⁴⁵³⁰ - Some fixes around hpx compute
- Issue #2470⁴⁵³¹ - redefinition of `boost::detail::spinlock`
- Issue #2469⁴⁵³² - Dataflow performance issue
- PR #2468⁴⁵³³ - Perf docs update
- PR #2466⁴⁵³⁴ - Guarantee to execute remote direct actions on HPX-thread
- PR #2465⁴⁵³⁵ - Improve demo : Async copy and fixed device handling
- PR #2464⁴⁵³⁶ - Adding performance counter exposing instantaneous scheduler utilization
- PR #2463⁴⁵³⁷ - Downcast to `future<void>`
- PR #2462⁴⁵³⁸ - Fixed usage of `ITT-Notify` API with Intel Amplifier
- PR #2461⁴⁵³⁹ - Cublas demo
- PR #2460⁴⁵⁴⁰ - Fixing thread bindings
- PR #2459⁴⁵⁴¹ - Make `-std=c++11` nvcc flag consistent for in-build and installed versions
- Issue #2457⁴⁵⁴² - Segmentation fault when registering a partitioned vector
- PR #2452⁴⁵⁴³ - Properly releasing global barrier for unhandled exceptions
- PR #2451⁴⁵⁴⁴ - Fixing long shutdown times
- PR #2450⁴⁵⁴⁵ - Attempting to fix initialization errors on newer platforms (Boost V1.63)
- PR #2449⁴⁵⁴⁶ - Replace `BOOST_COMPILER_FENCE` with an HPX version
- PR #2448⁴⁵⁴⁷ - This fixes a possible race in the migration code

⁴⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/2477>

⁴⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/2476>

⁴⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/2475>

⁴⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/2474>

⁴⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/2473>

⁴⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/2472>

⁴⁵³¹ <https://github.com/TheHPXProject/hpx/issues/2470>

⁴⁵³² <https://github.com/TheHPXProject/hpx/issues/2469>

⁴⁵³³ <https://github.com/TheHPXProject/hpx/pull/2468>

⁴⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/2466>

⁴⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/2465>

⁴⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/2464>

⁴⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/2463>

⁴⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/2462>

⁴⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/2461>

⁴⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2460>

⁴⁵⁴¹ <https://github.com/TheHPXProject/hpx/pull/2459>

⁴⁵⁴² <https://github.com/TheHPXProject/hpx/issues/2457>

⁴⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/2452>

⁴⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2451>

⁴⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2450>

⁴⁵⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2449>

⁴⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2448>

- **PR #2445[?]** - Fixing dataflow et.al. for futures or future-ranges wrapped into ref()
- PR #2444⁴⁵⁴⁹ - Fix segfaults
- PR #2443⁴⁵⁵⁰ - Issue 2442
- Issue #2442⁴⁵⁵¹ - Mismatch between #if/#endif and namespace scope brackets in this_thread_executors.hpp
- Issue #2441⁴⁵⁵² - undeclared identifier BOOST_COMPILER_FENCE
- PR #2440⁴⁵⁵³ - Knl build
- PR #2438⁴⁵⁵⁴ - Datapar backend
- PR #2437⁴⁵⁵⁵ - Adapt algorithm parameter sequence changes from C++17
- PR #2436⁴⁵⁵⁶ - Adapt execution policy name changes from C++17
- Issue #2435⁴⁵⁵⁷ - Trunk broken, undefined reference to hpx::thread::interrupt(hpx::thread::id, bool)
- PR #2434⁴⁵⁵⁸ - More fixes to resource manager
- PR #2433⁴⁵⁵⁹ - Added versions of hpx::get_ptr taking client side representations
- PR #2432⁴⁵⁶⁰ - Warning fixes
- PR #2431⁴⁵⁶¹ - Adding facility representing set of performance counters
- PR #2430⁴⁵⁶² - Fix parallel_executor thread spawning
- PR #2429⁴⁵⁶³ - Fix attribute warning for gcc
- Issue #2427⁴⁵⁶⁴ - Seg fault running octo-tiger with latest HPX commit
- Issue #2426⁴⁵⁶⁵ - Bug in 9592f5c0bc29806fce0dbe73f35b6ca7e027edcb causes immediate crash in Octo-tiger
- PR #2425⁴⁵⁶⁶ - Fix nvcc errors due to constexpr specifier
- Issue #2424⁴⁵⁶⁷ - Async action on component present on hpx::find_here is executing synchronously
- PR #2423⁴⁵⁶⁸ - Fix nvcc errors due to constexpr specifier
- PR #2422⁴⁵⁶⁹ - Implementing hpx::this_thread thread data functions
- PR #2421⁴⁵⁷⁰ - Adding benchmark for wait_all

⁴⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2445>
⁴⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2444>
⁴⁵⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2443>
⁴⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/2442>
⁴⁵⁵² <https://github.com/TheHPXProject/hpx/issues/2441>
⁴⁵⁵³ <https://github.com/TheHPXProject/hpx/pull/2440>
⁴⁵⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2438>
⁴⁵⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2437>
⁴⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2436>
⁴⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2435>
⁴⁵⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2434>
⁴⁵⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2433>
⁴⁵⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2432>
⁴⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/2431>
⁴⁵⁶² <https://github.com/TheHPXProject/hpx/pull/2430>
⁴⁵⁶³ <https://github.com/TheHPXProject/hpx/pull/2429>
⁴⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2427>
⁴⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2426>
⁴⁵⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2425>
⁴⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/2424>
⁴⁵⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2423>
⁴⁵⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2422>
⁴⁵⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2421>

- Issue #2420⁴⁵⁷¹ - Returning object of a component client from another component action fails
- PR #2419⁴⁵⁷² - Infiniband parcellport
- Issue #2418⁴⁵⁷³ - gcc + nvcc fails to compile code that uses `partitioned_vector`
- PR #2417⁴⁵⁷⁴ - Fixing context switching
- PR #2416⁴⁵⁷⁵ - Adding fixes and workarounds to allow compilation with nvcc/msvc (VS2015up3)
- PR #2415⁴⁵⁷⁶ - Fix errors coming from hpx compute examples
- PR #2414⁴⁵⁷⁷ - Fixing msvc12
- PR #2413⁴⁵⁷⁸ - Enable cuda/nvcc or cuda/clang when using `add_hpx_executable()`
- PR #2412⁴⁵⁷⁹ - Fix issue in `HPX_SetupTarget.cmake` when cuda is used
- PR #2411⁴⁵⁸⁰ - This fixes the core compilation issues with MSVC12
- Issue #2410⁴⁵⁸¹ - `undefined reference to opal_hwloc191_hwloc_.....`
- PR #2409⁴⁵⁸² - Fixing locking for channel and `receive_buffer`
- PR #2407⁴⁵⁸³ - Solving #2402 and #2403
- PR #2406⁴⁵⁸⁴ - Improve guards
- PR #2405⁴⁵⁸⁵ - Enable `parallel::for_each` for iterators returning proxy types
- PR #2404⁴⁵⁸⁶ - Forward the explicitly given `result_type` in the hpx invoke
- Issue #2403⁴⁵⁸⁷ - `datapar_execution + zip iterator: lambda arguments aren't references`
- Issue #2402⁴⁵⁸⁸ - `datapar` algorithm instantiated with wrong type #2402
- PR #2401⁴⁵⁸⁹ - Added support for imported libraries to `HPX_Libraries.cmake`
- PR #2400⁴⁵⁹⁰ - Use CMake policy CMP0060
- Issue #2399⁴⁵⁹¹ - Error trying to push back vector of futures to vector
- PR #2398⁴⁵⁹² - Allow config `#defines` to be written out to custom `config/defines.hpp`
- Issue #2397⁴⁵⁹³ - CMake generated config defines can cause tedious rebuilds category

⁴⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/2420>

⁴⁵⁷² <https://github.com/TheHPXProject/hpx/pull/2419>

⁴⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/2418>

⁴⁵⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2417>

⁴⁵⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2416>

⁴⁵⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2415>

⁴⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2414>

⁴⁵⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2413>

⁴⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2412>

⁴⁵⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2411>

⁴⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/2410>

⁴⁵⁸² <https://github.com/TheHPXProject/hpx/pull/2409>

⁴⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/2407>

⁴⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2406>

⁴⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2405>

⁴⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2404>

⁴⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/2403>

⁴⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/2402>

⁴⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2401>

⁴⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2400>

⁴⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/2399>

⁴⁵⁹² <https://github.com/TheHPXProject/hpx/pull/2398>

⁴⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/2397>

- [Issue #2396](#)⁴⁵⁹⁴ - BOOST_ROOT paths are not used at link time
- [PR #2395](#)⁴⁵⁹⁵ - Fix target_link_libraries() issue when HPX Cuda is enabled
- [Issue #2394](#)⁴⁵⁹⁶ - Template compilation error using HPX_WITH_DATAPAR_LIBFLATARRAY
- [PR #2393](#)⁴⁵⁹⁷ - Fixing lock registration for recursive mutex
- [PR #2392](#)⁴⁵⁹⁸ - Add keywords in target_link_libraries in hpx_setup_target
- [PR #2391](#)⁴⁵⁹⁹ - Clang goroutines
- [Issue #2390](#)⁴⁶⁰⁰ - Adapt execution policy name changes from C++17
- [PR #2389](#)⁴⁶⁰¹ - Chunk allocator and pool are not used and are obsolete
- [PR #2388](#)⁴⁶⁰² - Adding functionalities to datapar needed by octotiger
- [PR #2387](#)⁴⁶⁰³ - Fixing race condition for early parcels
- [Issue #2386](#)⁴⁶⁰⁴ - Lock registration broken for recursive_mutex
- [PR #2385](#)⁴⁶⁰⁵ - Datapar zip iterator
- [PR #2384](#)⁴⁶⁰⁶ - Fixing race condition in for_loop_reduction
- [PR #2383](#)⁴⁶⁰⁷ - Continuations
- [PR #2382](#)⁴⁶⁰⁸ - add LibFlatArray-based backend for datapar
- [PR #2381](#)⁴⁶⁰⁹ - remove unused typedef to get rid of compiler warnings
- [PR #2380](#)⁴⁶¹⁰ - Tau cleanup
- [PR #2379](#)⁴⁶¹¹ - Can send immediate
- [PR #2378](#)⁴⁶¹² - Renaming copy_helper/copy_n_helper/move_helper/move_n_helper
- [Issue #2376](#)⁴⁶¹³ - Boost trunk's spinlock initializer fails to compile
- [PR #2375](#)⁴⁶¹⁴ - Add support for minimal thread local data
- [PR #2374](#)⁴⁶¹⁵ - Adding API functions set_config_entry_callback
- [PR #2373](#)⁴⁶¹⁶ - Add a simple utility for debugging that gives suspended task backtraces

⁴⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2396>

⁴⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2395>

⁴⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/2394>

⁴⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2393>

⁴⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2392>

⁴⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2391>

⁴⁶⁰⁰ <https://github.com/TheHPXProject/hpx/issues/2390>

⁴⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/2389>

⁴⁶⁰² <https://github.com/TheHPXProject/hpx/pull/2388>

⁴⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/2387>

⁴⁶⁰⁴ <https://github.com/TheHPXProject/hpx/issues/2386>

⁴⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2385>

⁴⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2384>

⁴⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2383>

⁴⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2382>

⁴⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2381>

⁴⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/2380>

⁴⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/2379>

⁴⁶¹² <https://github.com/TheHPXProject/hpx/pull/2378>

⁴⁶¹³ <https://github.com/TheHPXProject/hpx/issues/2376>

⁴⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/2375>

⁴⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/2374>

⁴⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/2373>

- PR #2372⁴⁶¹⁷ - Barrier Fixes
- Issue #2370⁴⁶¹⁸ - Can't wait on a wrapped future
- PR #2369⁴⁶¹⁹ - Fixing stable_partition
- PR #2367⁴⁶²⁰ - Fixing find_prefixes for Windows platforms
- PR #2366⁴⁶²¹ - Testing for experimental/optional only in C++14 mode
- PR #2364⁴⁶²² - Adding set_config_entry
- PR #2363⁴⁶²³ - Fix papi
- PR #2362⁴⁶²⁴ - Adding missing macros for new non-direct actions
- PR #2361⁴⁶²⁵ - Improve cmake output to help debug compiler incompatibility check
- PR #2360⁴⁶²⁶ - Fixing race condition in condition_variable
- PR #2359⁴⁶²⁷ - Fixing shutdown when parcels are still in flight
- Issue #2357⁴⁶²⁸ - failed to insert console_print_action into typename_to_id_t registry
- PR #2356⁴⁶²⁹ - Fixing return type of get_iterator_tuple
- PR #2355⁴⁶³⁰ - Fixing compilation against Boost 1.62
- PR #2354⁴⁶³¹ - Adding serialization for mask_type if CPU_COUNT > 64
- PR #2353⁴⁶³² - Adding hooks to tie in APEX into the parcel layer
- Issue #2352⁴⁶³³ - Compile errors when using intel 17 beta (for KNL) on edison
- PR #2351⁴⁶³⁴ - Fix function vtable get_function_address implementation
- Issue #2350⁴⁶³⁵ - Build failure - master branch (4de09f5) with Intel Compiler v17
- PR #2349⁴⁶³⁶ - Enabling zero-copy serialization support for std::vector<>
- PR #2348⁴⁶³⁷ - Adding test to verify #2334 is fixed
- PR #2347⁴⁶³⁸ - Bug fixes for hpx.compute and hpx::lcos::channel
- PR #2346⁴⁶³⁹ - Removing cmake "find" files that are in the APEX cmake Modules

⁴⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/2372>

⁴⁶¹⁸ <https://github.com/TheHPXProject/hpx/issues/2370>

⁴⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/2369>

⁴⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/2367>

⁴⁶²¹ <https://github.com/TheHPXProject/hpx/pull/2366>

⁴⁶²² <https://github.com/TheHPXProject/hpx/pull/2364>

⁴⁶²³ <https://github.com/TheHPXProject/hpx/pull/2363>

⁴⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/2362>

⁴⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/2361>

⁴⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/2360>

⁴⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/2359>

⁴⁶²⁸ <https://github.com/TheHPXProject/hpx/issues/2357>

⁴⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/2356>

⁴⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/2355>

⁴⁶³¹ <https://github.com/TheHPXProject/hpx/pull/2354>

⁴⁶³² <https://github.com/TheHPXProject/hpx/pull/2353>

⁴⁶³³ <https://github.com/TheHPXProject/hpx/issues/2352>

⁴⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/2351>

⁴⁶³⁵ <https://github.com/TheHPXProject/hpx/issues/2350>

⁴⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/2349>

⁴⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/2348>

⁴⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/2347>

⁴⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/2346>

- PR #2345⁴⁶⁴⁰ - Implemented `parallel::stable_partition`
- PR #2344⁴⁶⁴¹ - Making `hpx::lcos::channel` usable with basename registration
- PR #2343⁴⁶⁴² - Fix a couple of examples that failed to compile after recent api changes
- Issue #2342⁴⁶⁴³ - Enabling APEX causes link errors
- PR #2341⁴⁶⁴⁴ - Removing cmake “find” files that are in the APEX cmake Modules
- PR #2340⁴⁶⁴⁵ - Implemented all existing datapar algorithms using Boost.SIMD
- PR #2339⁴⁶⁴⁶ - Fixing 2338
- PR #2338⁴⁶⁴⁷ - Possible race in sliding semaphore
- PR #2337⁴⁶⁴⁸ - Adjust `osu_latency` test to measure `window_size` parcels in flight at once
- PR #2336⁴⁶⁴⁹ - Allowing remote direct actions to be executed without spawning a task
- PR #2335⁴⁶⁵⁰ - Making sure multiple components are properly initialized from arguments
- Issue #2334⁴⁶⁵¹ - Cannot construct component with large vector on a remote locality
- PR #2332⁴⁶⁵² - Fixing `hpx::lcos::local::barrier`
- PR #2331⁴⁶⁵³ - Updating APEX support to include OTF2
- PR #2330⁴⁶⁵⁴ - Support for data-parallelism for parallel algorithms
- Issue #2329⁴⁶⁵⁵ - Coordinate settings in cmake
- PR #2328⁴⁶⁵⁶ - fix LibGeoDecomp builds with HPX + GCC 5.3.0 + CUDA 8RC
- PR #2326⁴⁶⁵⁷ - Making `scan_partitioner` work (for now)
- Issue #2323⁴⁶⁵⁸ - Constructing a vector of components only correctly initializes the first component
- PR #2322⁴⁶⁵⁹ - Fix problems that bubbled up after merging #2278
- PR #2321⁴⁶⁶⁰ - Scalable barrier
- PR #2320⁴⁶⁶¹ - Std flag fixes
- Issue #2319⁴⁶⁶² - `-std=c++14` and `-std=c++1y` with Intel can't build recent Boost builds due to insufficient C++14 support; don't enable these flags by default for Intel

⁴⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2345>

⁴⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/2344>

⁴⁶⁴² <https://github.com/TheHPXProject/hpx/pull/2343>

⁴⁶⁴³ <https://github.com/TheHPXProject/hpx/issues/2342>

⁴⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2341>

⁴⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2340>

⁴⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2339>

⁴⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2338>

⁴⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2337>

⁴⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2336>

⁴⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2335>

⁴⁶⁵¹ <https://github.com/TheHPXProject/hpx/issues/2334>

⁴⁶⁵² <https://github.com/TheHPXProject/hpx/pull/2332>

⁴⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/2331>

⁴⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2330>

⁴⁶⁵⁵ <https://github.com/TheHPXProject/hpx/issues/2329>

⁴⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2328>

⁴⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2326>

⁴⁶⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2323>

⁴⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2322>

⁴⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2321>

⁴⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/2320>

⁴⁶⁶² <https://github.com/TheHPXProject/hpx/issues/2319>

- PR #2318⁴⁶⁶³ - Improve handling of `-hpx:bind=<bind-spec>`
- PR #2317⁴⁶⁶⁴ - Making sure command line warnings are printed once only
- PR #2316⁴⁶⁶⁵ - Fixing command line handling for default bind mode
- PR #2315⁴⁶⁶⁶ - Set `id_retrieved` if `set_id` is present
- Issue #2314⁴⁶⁶⁷ - Warning for requested/allocated thread discrepancy is printed twice
- Issue #2313⁴⁶⁶⁸ - `-hpx:print-bind` doesn't work with `-hpx:pu-step`
- Issue #2312⁴⁶⁶⁹ - `-hpx:bind` range specifier restrictions are overly restrictive
- Issue #2311⁴⁶⁷⁰ - `hpx_0.9.99` out of project build fails
- PR #2310⁴⁶⁷¹ - Simplify function registration
- PR #2309⁴⁶⁷² - Spelling and grammar revisions in documentation (and some code)
- PR #2306⁴⁶⁷³ - Correct minor typo in the documentation
- PR #2305⁴⁶⁷⁴ - Cleaning up and fixing parcel coalescing
- PR #2304⁴⁶⁷⁵ - Inspect checks for stream related includes
- PR #2303⁴⁶⁷⁶ - Add functionality allowing to enumerate threads of given state
- PR #2301⁴⁶⁷⁷ - Algorithm overloads fix for VS2013
- PR #2300⁴⁶⁷⁸ - Use `<stdint>`, add inspect checks
- PR #2299⁴⁶⁷⁹ - Replace `boost::[c]ref` with `std::[c]ref`, add inspect checks
- PR #2297⁴⁶⁸⁰ - Fixing compilation with no `hw_loc`
- PR #2296⁴⁶⁸¹ - Hpx compute
- PR #2295⁴⁶⁸² - Making sure `for_loop(execution::par, 0, N, ...)` is actually executed in parallel
- PR #2294⁴⁶⁸³ - Throwing exceptions if the runtime is not up and running
- PR #2293⁴⁶⁸⁴ - Removing unused parcel port code
- PR #2292⁴⁶⁸⁵ - Refactor function vttables

⁴⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/2318>

⁴⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2317>

⁴⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2316>

⁴⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2315>

⁴⁶⁶⁷ <https://github.com/TheHPXProject/hpx/issues/2314>

⁴⁶⁶⁸ <https://github.com/TheHPXProject/hpx/issues/2313>

⁴⁶⁶⁹ <https://github.com/TheHPXProject/hpx/issues/2312>

⁴⁶⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2311>

⁴⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/2310>

⁴⁶⁷² <https://github.com/TheHPXProject/hpx/pull/2309>

⁴⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/2306>

⁴⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2305>

⁴⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2304>

⁴⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2303>

⁴⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2301>

⁴⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2300>

⁴⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2299>

⁴⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2297>

⁴⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/2296>

⁴⁶⁸² <https://github.com/TheHPXProject/hpx/pull/2295>

⁴⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/2294>

⁴⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2293>

⁴⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2292>

- PR #2291⁴⁶⁸⁶ - Fixing 2286
- PR #2290⁴⁶⁸⁷ - Simplify algorithm overloads
- PR #2289⁴⁶⁸⁸ - Adding performance counters reporting parcel related data on a per-action basis
- Issue #2288⁴⁶⁸⁹ - Remove dormant parcelports
- Issue #2286⁴⁶⁹⁰ - adjustments to parcel handling to support parcelports that do not need a connection cache
- PR #2285⁴⁶⁹¹ - add CMake option to disable package export
- PR #2283⁴⁶⁹² - Add more inspect checks for use of deprecated components
- Issue #2282⁴⁶⁹³ - Arithmetic exception in executor static chunker
- Issue #2281⁴⁶⁹⁴ - For loop doesn't parallelize
- PR #2280⁴⁶⁹⁵ - Fixing 2277: build failure with PAPI
- PR #2279⁴⁶⁹⁶ - Child vs parent stealing
- Issue #2277⁴⁶⁹⁷ - master branch build failure (53c5b4f) with papi
- PR #2276⁴⁶⁹⁸ - Compile time launch policies
- PR #2275⁴⁶⁹⁹ - Replace boost::chrono with std::chrono in interfaces
- PR #2274⁴⁷⁰⁰ - Replace most uses of Boost.Assign with initializer list
- PR #2273⁴⁷⁰¹ - Fixed typos
- PR #2272⁴⁷⁰² - Inspect checks
- PR #2270⁴⁷⁰³ - Adding test verifying -lhp.os_threads=all
- PR #2269⁴⁷⁰⁴ - Added inspect check for now obsolete boost type traits
- PR #2268⁴⁷⁰⁵ - Moving more code into source files
- Issue #2267⁴⁷⁰⁶ - Add inspect support to deprecate Boost.TypeTraits
- PR #2265⁴⁷⁰⁷ - Adding channel LCO
- PR #2264⁴⁷⁰⁸ - Make support for std::ref mandatory

⁴⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2291>

⁴⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2290>

⁴⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2289>

⁴⁶⁸⁹ <https://github.com/TheHPXProject/hpx/issues/2288>

⁴⁶⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2286>

⁴⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/2285>

⁴⁶⁹² <https://github.com/TheHPXProject/hpx/pull/2283>

⁴⁶⁹³ <https://github.com/TheHPXProject/hpx/issues/2282>

⁴⁶⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2281>

⁴⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2280>

⁴⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2279>

⁴⁶⁹⁷ <https://github.com/TheHPXProject/hpx/issues/2277>

⁴⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2276>

⁴⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2275>

⁴⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2274>

⁴⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/2273>

⁴⁷⁰² <https://github.com/TheHPXProject/hpx/pull/2272>

⁴⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/2270>

⁴⁷⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2269>

⁴⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2268>

⁴⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2267>

⁴⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2265>

⁴⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2264>

- PR #2263⁴⁷⁰⁹ - Constrain tuple_member forwarding constructor
- Issue #2262⁴⁷¹⁰ - Test hpx.os_threads=all
- Issue #2261⁴⁷¹¹ - OS X: Error: no matching constructor for initialization of 'hpx::lcos::local::condition_variable_any'
- Issue #2260⁴⁷¹² - Make support for std::ref mandatory
- PR #2259⁴⁷¹³ - Remove most of Boost.MPL, Boost.EnableIf and Boost.TypeTraits
- PR #2258⁴⁷¹⁴ - Fixing #2256
- PR #2257⁴⁷¹⁵ - Fixing launch process
- Issue #2256⁴⁷¹⁶ - Actions are not registered if not invoked
- PR #2255⁴⁷¹⁷ - Coalescing histogram
- PR #2254⁴⁷¹⁸ - Silence explicit initialization in copy-constructor warnings
- PR #2253⁴⁷¹⁹ - Drop support for GCC 4.6 and 4.7
- PR #2252⁴⁷²⁰ - Prepare V1.0
- PR #2251⁴⁷²¹ - Convert to 0.9.99
- PR #2249⁴⁷²² - Adding iterator_facade and iterator_adaptor
- Issue #2248⁴⁷²³ - Need a feature to yield to a new task immediately
- PR #2246⁴⁷²⁴ - Adding split_future
- PR #2245⁴⁷²⁵ - Add an example for handing over a component instance to a dynamically launched locality
- Issue #2243⁴⁷²⁶ - Add example demonstrating AGAS symbolic name registration
- Issue #2242⁴⁷²⁷ - pkgconfig test broken on CentOS 7 / Boost 1.61
- Issue #2241⁴⁷²⁸ - Compilation error for partitioned vector in hpx_compute branch
- PR #2240⁴⁷²⁹ - Fixing termination detection on one locality
- Issue #2239⁴⁷³⁰ - Create a new facility lcos::split_all
- Issue #2236⁴⁷³¹ - hpx::cout vs. std::cout

⁴⁷⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2263>

⁴⁷¹⁰ <https://github.com/TheHPXProject/hpx/issues/2262>

⁴⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/2261>

⁴⁷¹² <https://github.com/TheHPXProject/hpx/issues/2260>

⁴⁷¹³ <https://github.com/TheHPXProject/hpx/pull/2259>

⁴⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/2258>

⁴⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/2257>

⁴⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/2256>

⁴⁷¹⁷ <https://github.com/TheHPXProject/hpx/pull/2255>

⁴⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/2254>

⁴⁷¹⁹ <https://github.com/TheHPXProject/hpx/pull/2253>

⁴⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/2252>

⁴⁷²¹ <https://github.com/TheHPXProject/hpx/pull/2251>

⁴⁷²² <https://github.com/TheHPXProject/hpx/pull/2249>

⁴⁷²³ <https://github.com/TheHPXProject/hpx/issues/2248>

⁴⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/2246>

⁴⁷²⁵ <https://github.com/TheHPXProject/hpx/pull/2245>

⁴⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/2243>

⁴⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/2242>

⁴⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/2241>

⁴⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/2240>

⁴⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/2239>

⁴⁷³¹ <https://github.com/TheHPXProject/hpx/issues/2236>

- PR #2232⁴⁷³² - Implement local-only primary namespace service
- Issue #2147⁴⁷³³ - would like to know how much data is being routed by particular actions
- Issue #2109⁴⁷³⁴ - Warning while compiling hpx
- Issue #1973⁴⁷³⁵ - Setting INTERFACE_COMPILE_OPTIONS for hpx_init in CMake taints Fortran_FLAGS
- Issue #1864⁴⁷³⁶ - run_guarded using bound function ignores reference
- Issue #1754⁴⁷³⁷ - Running with TCP parcelport causes immediate crash or freeze
- Issue #1655⁴⁷³⁸ - Enable zip_iterator to be used with Boost traversal iterator categories
- Issue #1591⁴⁷³⁹ - Optimize AGAS for shared memory only operation
- Issue #1401⁴⁷⁴⁰ - Need an efficient infiniband parcelport
- Issue #1125⁴⁷⁴¹ - Fix the IPC parcelport
- Issue #839⁴⁷⁴² - Refactor ibverbs and shmем parcelport
- Issue #702⁴⁷⁴³ - Add instrumentation of parcel layer
- Issue #668⁴⁷⁴⁴ - Implement ispc task interface
- Issue #533⁴⁷⁴⁵ - Thread queue/dequeue internal parameters should be runtime configurable
- Issue #475⁴⁷⁴⁶ - Create a means of combining performance counters into querysets

HPX V0.9.99 (Jul 15, 2016)

General changes

As the version number of this release hints, we consider this release to be a preview for the upcoming *HPX* V1.0. All of the functionalities we set out to implement for V1.0 are in place; all of the features we wanted to have exposed are ready. We are very happy with the stability and performance of *HPX* and we would like to present this release to the community in order for us to gather broad feedback before releasing V1.0. We still expect for some minor details to change, but on the whole this release represents what we would like to have in a V1.0.

Overall, since the last release we have had almost 1600 commits while closing almost 400 tickets. These numbers reflect the incredible development activity we have seen over the last couple of months. We would like to express a big ‘Thank you!’ to all contributors and those who helped to make this release happen.

The most notable addition in terms of new functionality available with this release is the full implementation of object migration (i.e. the ability to transparently move *HPX* components to a different compute node). Additionally, this release of *HPX* cleans up many minor issues and some API inconsistencies.

Here are some of the main highlights and changes for this release (in no particular order):

- ⁴⁷³² <https://github.com/TheHPXProject/hpx/pull/2232>
- ⁴⁷³³ <https://github.com/TheHPXProject/hpx/issues/2147>
- ⁴⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/2109>
- ⁴⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/1973>
- ⁴⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/1864>
- ⁴⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/1754>
- ⁴⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/1655>
- ⁴⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/1591>
- ⁴⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1401>
- ⁴⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/1125>
- ⁴⁷⁴² <https://github.com/TheHPXProject/hpx/issues/839>
- ⁴⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/702>
- ⁴⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/668>
- ⁴⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/533>
- ⁴⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/475>

- We have fixed a couple of issues in AGAS and the parcel layer which have caused hangs, segmentation faults at exit, and a slowdown of applications over time. Fixing those has significantly increased the overall stability and performance of distributed runs.
- We have started to add parallel algorithm overloads based on the C++ Extensions for Ranges (N4560⁴⁷⁴⁷) proposal. This also includes the addition of projections to the existing algorithms. Please see Issue #1668⁴⁷⁴⁸ for a list of algorithms which have been adapted to N4560⁴⁷⁴⁹.
- We have implemented index-based parallel for-loops based on a corresponding standardization proposal (P0075R1⁴⁷⁵⁰). Please see Issue #2016⁴⁷⁵¹ for a list of available algorithms.
- We have added implementations for more parallel algorithms as proposed for the upcoming C++ 17 Standard. See Issue #1141⁴⁷⁵² for an overview of which algorithms are available by now.
- We have started to implement a new prototypical functionality with *HPX.Compute* which uniformly exposes some of the higher level APIs to heterogeneous architectures (currently CUDA). This functionality is an early preview and should not be considered stable. It may change considerably in the future.
- We have pervasively added (optional) executor arguments to all API functions which schedule new work. Executors are now used throughout the code base as the main means of executing tasks.
- Added `hpx::make_future<R>(future<T> &&)` allowing to convert a future of any type T into a future of any other type R, either based on default conversion rules of the embedded types or using a given explicit conversion function.
- We finally finished the implementation of transparent migration of components to another locality. It is now possible to trigger a migration operation without ‘stopping the world’ for the object to migrate. *HPX* will make sure that no work is being performed on an object before it is migrated and that all subsequently scheduled work for the migrated object will be transparently forwarded to the new locality. Please note that the global id of the migrated object does not change, thus the application will not have to be changed in any way to support this new functionality. Please note that this feature is currently considered experimental. See Issue #559⁴⁷⁵³ and PR #1966⁴⁷⁵⁴ for more details.
- The `hpx::dataflow` facility is now usable with actions. Similarly to `hpx::async`, actions can be specified as an explicit template argument (`hpx::dataflow<Action>(target, ...)`) or as the first argument (`hpx::dataflow(Action(), target, ...)`). We have also enabled the use of distribution policies as the target for dataflow invocations. Please see Issue #1265⁴⁷⁵⁵ and PR #1912⁴⁷⁵⁶ for more information.
- Adding overloads of `gather_here` and `gather_there` to accept the plain values of the data to gather (in addition to the existing overloads expecting futures).
- We have cleaned up and refactored large parts of the code base. This helped reducing compile and link times of *HPX* itself and also of applications depending on it. We have further decreased the dependency of *HPX* on the Boost libraries by replacing part of those with facilities available from the standard libraries.
- Wherever possible we have removed dependencies of our API on Boost by replacing those with the equivalent facility from the C++11 standard library.
- We have added new performance counters for parcel coalescing, file-IO, the AGAS cache, and overall scheduler time. Resetting performance counters has been overhauled and fixed.

⁴⁷⁴⁷ <http://wg21.link/n4560>

⁴⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1668>

⁴⁷⁴⁹ <http://wg21.link/n4560>

⁴⁷⁵⁰ <http://wg21.link/p0075r1>

⁴⁷⁵¹ <https://github.com/TheHPXProject/hpx/issues/2016>

⁴⁷⁵² <https://github.com/TheHPXProject/hpx/issues/1141>

⁴⁷⁵³ <https://github.com/TheHPXProject/hpx/issues/559>

⁴⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1966>

⁴⁷⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1265>

⁴⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1912>

- We have introduced a generic client type `hpx::components::client<>` and added support for using it with `hpx::async`. This removes the necessity to implement specific client types for every component type without losing type safety. This deemphasizes the need for using the low level `hpx::id_type` for referencing (possibly remote) component instances. The plan is to deprecate the direct use of `hpx::id_type` in user code in the future.
- We have added a special iterator which supports automatic prefetching of one or more arrays for speeding up loop-like code (see `hpx::parallel::util::make_prefetcher_context()`).
- We have extended the interfaces exposed from executors (as proposed by [N4406](http://wg21.link/n4406)⁴⁷⁵⁷) to accept an arbitrary number of arguments.

Breaking changes

- In order to move the dataflow facility to namespace `hpx` we added a definition of `hpx::dataflow` which might create ambiguities in existing codes. The previous definition of this facility (`hpx::lcos::local::dataflow`) has been deprecated and is available only if the constant `-DHPX_WITH_LOCAL_DATAFLOW_COMPATIBILITY=On` to `CMake`⁴⁷⁵⁸ is defined at configuration time. Please explicitly qualify all uses of the dataflow facility if you enable this compatibility setting and encounter ambiguities.
- The adaptation of the C++ Extensions for Ranges ([N4560](http://wg21.link/n4560)⁴⁷⁵⁹) proposal imposes some breaking changes related to the return types of some of the parallel algorithms. Please see [Issue #1668](https://github.com/TheHPXProject/hpx/issues/1668)⁴⁷⁶⁰ for a list of algorithms which have already been adapted.
- The facility `hpx::lcos::make_future_void()` has been replaced by `hpx::make_future<void>()`.
- We have removed support for Intel V13 and gcc 4.4.x.
- We have removed (default) support for the generic `hpx::parallel::execution_policy` because it was removed from the Parallelism TS (`__cpp11_n4104__`) while it was being added to the upcoming C++17 Standard. This facility can be still enabled at configure time by specifying `-DHPX_WITH_GENERIC_EXECUTION_POLICY=On` to `CMake`.
- Uses of `boost::shared_ptr` and related facilities have been replaced with `std::shared_ptr` and friends. Uses of `boost::unique_lock`, `boost::lock_guard` etc. have also been replaced by the equivalent (and equally named) tools available from the C++11 standard library.
- Facilities that used to expect an explicit `boost::unique_lock` now take an `std::unique_lock`. Additionally, `condition_variable` no longer aliases `condition_variable_any`; its interface now only works with `std::unique_lock<local::mutex>`.
- Uses of `boost::function`, `boost::bind`, `boost::tuple` have been replaced by the corresponding facilities in *HPX* (`hpx::util::function`, `hpx::util::bind`, and `hpx::util::tuple`, respectively).

⁴⁷⁵⁷ <http://wg21.link/n4406>

⁴⁷⁵⁸ <https://www.cmake.org>

⁴⁷⁵⁹ <http://wg21.link/n4560>

⁴⁷⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1668>

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #2250⁴⁷⁶¹](#) - change default chunker of parallel executor to static one
- [PR #2247⁴⁷⁶²](#) - HPX on ppc64le
- [PR #2244⁴⁷⁶³](#) - Fixing MSVC problems
- [PR #2238⁴⁷⁶⁴](#) - Fixing small typos
- [PR #2237⁴⁷⁶⁵](#) - Fixing small typos
- [PR #2234⁴⁷⁶⁶](#) - Fix broken add test macro when extra args are passed in
- [PR #2231⁴⁷⁶⁷](#) - Fixing possible race during future awaiting in serialization
- [PR #2230⁴⁷⁶⁸](#) - Fix stream nvcc
- [PR #2229⁴⁷⁶⁹](#) - Fixed run_as_hpx_thread
- [PR #2228⁴⁷⁷⁰](#) - On prefetching_test branch : adding prefetching_iterator and related tests used for prefetching containers within lambda functions
- [PR #2227⁴⁷⁷¹](#) - Support for HPXCL's opencil::event
- [PR #2226⁴⁷⁷²](#) - Preparing for release of V0.9.99
- [PR #2225⁴⁷⁷³](#) - fix issue when compiling components with hpxcxx
- [PR #2224⁴⁷⁷⁴](#) - Compute alloc fix
- [PR #2223⁴⁷⁷⁵](#) - Simplify promise
- [PR #2222⁴⁷⁷⁶](#) - Replace last uses of boost::function by util::function_nonsr
- [PR #2221⁴⁷⁷⁷](#) - Fix config tests
- [PR #2220⁴⁷⁷⁸](#) - Fixing gcc 4.6 compilation issues
- [PR #2219⁴⁷⁷⁹](#) - nullptr support for [unique_] function
- [PR #2218⁴⁷⁸⁰](#) - Introducing clang tidy
- [PR #2216⁴⁷⁸¹](#) - Replace NULL with nullptr

⁴⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/2250>

⁴⁷⁶² <https://github.com/TheHPXProject/hpx/pull/2247>

⁴⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/2244>

⁴⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2238>

⁴⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2237>

⁴⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2234>

⁴⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2231>

⁴⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2230>

⁴⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2229>

⁴⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2228>

⁴⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/2227>

⁴⁷⁷² <https://github.com/TheHPXProject/hpx/pull/2226>

⁴⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/2225>

⁴⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2224>

⁴⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2223>

⁴⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2222>

⁴⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2221>

⁴⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2220>

⁴⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2219>

⁴⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2218>

⁴⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/2216>

- [Issue #2214](#)⁴⁷⁸² - Let inspect flag use of NULL, suggest nullptr instead
- [PR #2213](#)⁴⁷⁸³ - Require support for nullptr
- [PR #2212](#)⁴⁷⁸⁴ - Properly find jemalloc through pkg-config
- [PR #2211](#)⁴⁷⁸⁵ - Disable a couple of warnings reported by Intel on Windows
- [PR #2210](#)⁴⁷⁸⁶ - Fixed host::block_allocator::bulk_construct
- [PR #2209](#)⁴⁷⁸⁷ - Started to clean up new sort algorithms, made things compile for sort_by_key
- [PR #2208](#)⁴⁷⁸⁸ - A couple of fixes that were exposed by a new sort algorithm
- [PR #2207](#)⁴⁷⁸⁹ - Adding missing includes in /hpx/include/serialization.hpp
- [PR #2206](#)⁴⁷⁹⁰ - Call package_action::get_future before package_action::apply
- [PR #2205](#)⁴⁷⁹¹ - The indirect_packaged_task::operator() needs to be run on a HPX thread
- [PR #2204](#)⁴⁷⁹² - Variadic executor parameters
- [PR #2203](#)⁴⁷⁹³ - Delay-initialize members of partitioned iterator
- [PR #2202](#)⁴⁷⁹⁴ - Added segmented fill for hpx::vector
- [Issue #2201](#)⁴⁷⁹⁵ - Null Thread id encountered on partitioned_vector
- [PR #2200](#)⁴⁷⁹⁶ - Fix hangs
- [PR #2199](#)⁴⁷⁹⁷ - Deprecating hpx/traits.hpp
- [PR #2198](#)⁴⁷⁹⁸ - Making explicit inclusion of external libraries into build
- [PR #2197](#)⁴⁷⁹⁹ - Fix typo in QT CMakeLists
- [PR #2196](#)⁴⁸⁰⁰ - Fixing a gcc warning about attributes being ignored
- [PR #2194](#)⁴⁸⁰¹ - Fixing partitioned_vector_spmf_foreach example
- [Issue #2193](#)⁴⁸⁰² - partitioned_vector_spmf_foreach seg faults
- [PR #2192](#)⁴⁸⁰³ - Support Boost.Thread v4
- [PR #2191](#)⁴⁸⁰⁴ - HPX.Compute prototype

⁴⁷⁸² <https://github.com/TheHPXProject/hpx/issues/2214>

⁴⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/2213>

⁴⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2212>

⁴⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2211>

⁴⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2210>

⁴⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2209>

⁴⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2208>

⁴⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2207>

⁴⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2206>

⁴⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/2205>

⁴⁷⁹² <https://github.com/TheHPXProject/hpx/pull/2204>

⁴⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/2203>

⁴⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2202>

⁴⁷⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2201>

⁴⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2200>

⁴⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2199>

⁴⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2198>

⁴⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2197>

⁴⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2196>

⁴⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/2194>

⁴⁸⁰² <https://github.com/TheHPXProject/hpx/issues/2193>

⁴⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/2192>

⁴⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2191>

- PR #2190⁴⁸⁰⁵ - Spawning operation on new thread if remaining stack space becomes too small
- PR #2189⁴⁸⁰⁶ - Adding callback taking index and future to when_each
- PR #2188⁴⁸⁰⁷ - Adding new example demonstrating receive_buffer
- PR #2187⁴⁸⁰⁸ - Mask 128-bit ints if CUDA is being used
- PR #2186⁴⁸⁰⁹ - Make startup & shutdown functions unique_function
- PR #2185⁴⁸¹⁰ - Fixing logging output not to cause hang on shutdown
- PR #2184⁴⁸¹¹ - Allowing component clients as action return types
- Issue #2183⁴⁸¹² - Enabling logging output causes hang on shutdown
- Issue #2182⁴⁸¹³ - 1d_stencil seg fault
- Issue #2181⁴⁸¹⁴ - Setting small stack size does not change default
- PR #2180⁴⁸¹⁵ - Changing default bind mode to balanced
- PR #2179⁴⁸¹⁶ - adding prefetching_iterator and related tests used for prefetching containers within lambda functions
- PR #2177⁴⁸¹⁷ - Fixing 2176
- Issue #2176⁴⁸¹⁸ - Launch process test fails on OSX
- PR #2175⁴⁸¹⁹ - Fix unbalanced config/warnings includes, add some new ones
- PR #2174⁴⁸²⁰ - Fix test categorization : regression not unit
- Issue #2172⁴⁸²¹ - Different performance results
- Issue #2171⁴⁸²² - “negative entry in reference count table” running octotiger on 32 nodes on queenbee
- Issue #2170⁴⁸²³ - Error while compiling on Mac + boost 1.60
- PR #2168⁴⁸²⁴ - Fixing problems with is_bitwise_serializable
- Issue #2167⁴⁸²⁵ - startup & shutdown function should accept unique_function
- Issue #2166⁴⁸²⁶ - Simple receive_buffer example
- PR #2165⁴⁸²⁷ - Fix wait all

⁴⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2190>

⁴⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2189>

⁴⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2188>

⁴⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2187>

⁴⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2186>

⁴⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/2185>

⁴⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/2184>

⁴⁸¹² <https://github.com/TheHPXProject/hpx/issues/2183>

⁴⁸¹³ <https://github.com/TheHPXProject/hpx/issues/2182>

⁴⁸¹⁴ <https://github.com/TheHPXProject/hpx/issues/2181>

⁴⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/2180>

⁴⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/2179>

⁴⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/2177>

⁴⁸¹⁸ <https://github.com/TheHPXProject/hpx/issues/2176>

⁴⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/2175>

⁴⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/2174>

⁴⁸²¹ <https://github.com/TheHPXProject/hpx/issues/2172>

⁴⁸²² <https://github.com/TheHPXProject/hpx/issues/2171>

⁴⁸²³ <https://github.com/TheHPXProject/hpx/issues/2170>

⁴⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/2168>

⁴⁸²⁵ <https://github.com/TheHPXProject/hpx/issues/2167>

⁴⁸²⁶ <https://github.com/TheHPXProject/hpx/issues/2166>

⁴⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/2165>

- PR #2164⁴⁸²⁸ - Fix wait all
- PR #2163⁴⁸²⁹ - Fix some typos in config tests
- PR #2162⁴⁸³⁰ - Improve #includes
- PR #2160⁴⁸³¹ - Add inspect check for missing #include <list>
- PR #2159⁴⁸³² - Add missing finalize call to stop test hanging
- PR #2158⁴⁸³³ - Algo fixes
- PR #2157⁴⁸³⁴ - Stack check
- Issue #2156⁴⁸³⁵ - OSX reports stack space incorrectly (generic context coroutines)
- Issue #2155⁴⁸³⁶ - Race condition suspected in runtime
- PR #2154⁴⁸³⁷ - Replace boost::detail::atomic_count with the new util::atomic_count
- PR #2153⁴⁸³⁸ - Fix stack overflow on OSX
- PR #2152⁴⁸³⁹ - Define is_bitwise_serializable as is_trivially_copyable when available
- PR #2151⁴⁸⁴⁰ - Adding missing <cstring> for std::mem* functions
- Issue #2150⁴⁸⁴¹ - Unable to use component clients as action return types
- PR #2149⁴⁸⁴² - std::memmove copies bytes, use bytes*sizeof(type) when copying larger types
- PR #2146⁴⁸⁴³ - Adding customization point for parallel copy/move
- PR #2145⁴⁸⁴⁴ - Applying changes to address warnings issued by latest version of PVS Studio
- Issue #2148⁴⁸⁴⁵ - hpx::parallel::copy is broken after trivially copyable changes
- PR #2144⁴⁸⁴⁶ - Some minor tweaks to compute prototype
- PR #2143⁴⁸⁴⁷ - Added Boost version support information over OSX platform
- PR #2142⁴⁸⁴⁸ - Fixing memory leak in example
- PR #2141⁴⁸⁴⁹ - Add missing specializations in execution policies
- PR #2139⁴⁸⁵⁰ - This PR fixes a few problems reported by Clang's Undefined Behavior sanitizer

⁴⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/2164>

⁴⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/2163>

⁴⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/2162>

⁴⁸³¹ <https://github.com/TheHPXProject/hpx/pull/2160>

⁴⁸³² <https://github.com/TheHPXProject/hpx/pull/2159>

⁴⁸³³ <https://github.com/TheHPXProject/hpx/pull/2158>

⁴⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/2157>

⁴⁸³⁵ <https://github.com/TheHPXProject/hpx/issues/2156>

⁴⁸³⁶ <https://github.com/TheHPXProject/hpx/issues/2155>

⁴⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/2154>

⁴⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/2153>

⁴⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/2152>

⁴⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2151>

⁴⁸⁴¹ <https://github.com/TheHPXProject/hpx/issues/2150>

⁴⁸⁴² <https://github.com/TheHPXProject/hpx/pull/2149>

⁴⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/2146>

⁴⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2145>

⁴⁸⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2148>

⁴⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2144>

⁴⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2143>

⁴⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2142>

⁴⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2141>

⁴⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2139>

- PR #2138⁴⁸⁵¹ - Revert “Adding fedora docs”
- PR #2136⁴⁸⁵² - Removed double semicolon
- PR #2135⁴⁸⁵³ - Add deprecated #include check for hpx_fwd.hpp
- PR #2134⁴⁸⁵⁴ - Resolved memory leak in stencil_8
- PR #2133⁴⁸⁵⁵ - Replace uses of boost pointer containers
- PR #2132⁴⁸⁵⁶ - Removing unused typedef
- PR #2131⁴⁸⁵⁷ - Add several include checks for std facilities
- PR #2130⁴⁸⁵⁸ - Fixing parcel compression, adding test
- PR #2129⁴⁸⁵⁹ - Fix invalid attribute warnings
- Issue #2128⁴⁸⁶⁰ - hpx::init seems to segfault
- PR #2127⁴⁸⁶¹ - Making executor_traits N-nary
- PR #2126⁴⁸⁶² - GCC 4.6 fails to deduce the correct type in lambda
- PR #2125⁴⁸⁶³ - Making parcel coalescing test actually test something
- Issue #2124⁴⁸⁶⁴ - Make a testcase for parcel compression
- Issue #2123⁴⁸⁶⁵ - hpx/hpx/runtime/applier_fwd.hpp - Multiple defined types
- Issue #2122⁴⁸⁶⁶ - Exception in primary_namespace::resolve_free_list
- Issue #2121⁴⁸⁶⁷ - Possible memory leak in 1d_stencil_8
- PR #2120⁴⁸⁶⁸ - Fixing 2119
- Issue #2119⁴⁸⁶⁹ - reduce_by_key compilation problems
- Issue #2118⁴⁸⁷⁰ - Premature unwrapping of boost::ref'ed arguments
- PR #2117⁴⁸⁷¹ - Added missing initializer on last constructor for thread_description
- PR #2116⁴⁸⁷² - Use a lightweight bind implementation when no placeholders are given
- PR #2115⁴⁸⁷³ - Replace boost::shared_ptr with std::shared_ptr

⁴⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/2138>
⁴⁸⁵² <https://github.com/TheHPXProject/hpx/pull/2136>
⁴⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/2135>
⁴⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2134>
⁴⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2133>
⁴⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2132>
⁴⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2131>
⁴⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2130>
⁴⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2129>
⁴⁸⁶⁰ <https://github.com/TheHPXProject/hpx/issues/2128>
⁴⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/2127>
⁴⁸⁶² <https://github.com/TheHPXProject/hpx/pull/2126>
⁴⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/2125>
⁴⁸⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2124>
⁴⁸⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2123>
⁴⁸⁶⁶ <https://github.com/TheHPXProject/hpx/issues/2122>
⁴⁸⁶⁷ <https://github.com/TheHPXProject/hpx/issues/2121>
⁴⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2120>
⁴⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/2119>
⁴⁸⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2118>
⁴⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/2117>
⁴⁸⁷² <https://github.com/TheHPXProject/hpx/pull/2116>
⁴⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/2115>

- [PR #2114](#)⁴⁸⁷⁴ - Adding hook functions for `executor_parameter_traits` supporting timers
- [Issue #2113](#)⁴⁸⁷⁵ - Compilation error with gcc version 4.9.3 (MacPorts gcc49 4.9.3_0)
- [PR #2112](#)⁴⁸⁷⁶ - Replace uses of `safe_bool` with explicit operator `bool`
- [Issue #2111](#)⁴⁸⁷⁷ - Compilation error on QT example
- [Issue #2110](#)⁴⁸⁷⁸ - Compilation error when passing non-future argument to unwrapped continuation in dataflow
- [Issue #2109](#)⁴⁸⁷⁹ - Warning while compiling hpx
- [Issue #2109](#)⁴⁸⁸⁰ - Stack trace of last bug causing issues with octotiger
- [Issue #2108](#)⁴⁸⁸¹ - Stack trace of last bug causing issues with octotiger
- [PR #2107](#)⁴⁸⁸² - Making sure that a missing `parcel_coalescing` module does not cause startup exceptions
- [PR #2106](#)⁴⁸⁸³ - Stop using `hpx_fwd.hpp`
- [Issue #2105](#)⁴⁸⁸⁴ - coalescing plugin handler is not optional any more
- [Issue #2104](#)⁴⁸⁸⁵ - Make `executor_traits` N-nary
- [Issue #2103](#)⁴⁸⁸⁶ - Build error with octotiger and hpx commit e657426d
- [PR #2102](#)⁴⁸⁸⁷ - Combining thread data storage
- [PR #2101](#)⁴⁸⁸⁸ - Added repartition version of 1d stencil that uses any performance counter
- [PR #2100](#)⁴⁸⁸⁹ - Drop obsolete TR1 `result_of` protocol
- [PR #2099](#)⁴⁸⁹⁰ - Replace uses of `boost::bind` with `util::bind`
- [PR #2098](#)⁴⁸⁹¹ - Deprecated inspect checks
- [PR #2097](#)⁴⁸⁹² - Reduce by key, extends #1141
- [PR #2096](#)⁴⁸⁹³ - Moving local cache from external to `hpx/util`
- [PR #2095](#)⁴⁸⁹⁴ - Bump minimum required Boost to 1.50.0
- [PR #2094](#)⁴⁸⁹⁵ - Add include checks for several Boost utilities
- [Issue #2093](#)⁴⁸⁹⁶ - `./.../local_cache.hpp(89): error #303: explicit type is missing ("int" assumed)`

⁴⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2114>

⁴⁸⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2113>

⁴⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2112>

⁴⁸⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2111>

⁴⁸⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2110>

⁴⁸⁷⁹ <https://github.com/TheHPXProject/hpx/issues/2109>

⁴⁸⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2109>

⁴⁸⁸¹ <https://github.com/TheHPXProject/hpx/issues/2108>

⁴⁸⁸² <https://github.com/TheHPXProject/hpx/pull/2107>

⁴⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/2106>

⁴⁸⁸⁴ <https://github.com/TheHPXProject/hpx/issues/2105>

⁴⁸⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2104>

⁴⁸⁸⁶ <https://github.com/TheHPXProject/hpx/issues/2103>

⁴⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2102>

⁴⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2101>

⁴⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2100>

⁴⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2099>

⁴⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/2098>

⁴⁸⁹² <https://github.com/TheHPXProject/hpx/pull/2097>

⁴⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/2096>

⁴⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2095>

⁴⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2094>

⁴⁸⁹⁶ <https://github.com/TheHPXProject/hpx/issues/2093>

- PR #2091⁴⁸⁹⁷ - Fix for Raspberry pi build
- PR #2090⁴⁸⁹⁸ - Fix storage size for util::function<>
- PR #2089⁴⁸⁹⁹ - Fix #2088
- Issue #2088⁴⁹⁰⁰ - More verbose output from cmake configuration
- PR #2087⁴⁹⁰¹ - Making sure init_globally always executes hpx_main
- Issue #2086⁴⁹⁰² - Race condition with recent HPX
- PR #2085⁴⁹⁰³ - Adding #include checker
- PR #2084⁴⁹⁰⁴ - Replace boost lock types with standard library ones
- PR #2083⁴⁹⁰⁵ - Simplify packaged task
- PR #2082⁴⁹⁰⁶ - Updating APEX version for testing
- PR #2081⁴⁹⁰⁷ - Cleanup exception headers
- PR #2080⁴⁹⁰⁸ - Make call_once variadic
- Issue #2079⁴⁹⁰⁹ - With GNU C++, line 85 of hpx/config/version.hpp causes link failure when linking application
- Issue #2078⁴⁹¹⁰ - Simple test fails with _GLIBCXX_DEBUG defined
- PR #2077⁴⁹¹¹ - Instantiate board in nqueen client
- PR #2076⁴⁹¹² - Moving coalescing registration to TUs
- PR #2075⁴⁹¹³ - Fixed some documentation typos
- PR #2074⁴⁹¹⁴ - Adding flush-mode to message handler flush
- PR #2073⁴⁹¹⁵ - Fixing performance regression introduced lately
- PR #2072⁴⁹¹⁶ - Refactor local::condition_variable
- PR #2071⁴⁹¹⁷ - Timer based on boost::asio::deadline_timer
- PR #2070⁴⁹¹⁸ - Refactor tuple based functionality
- PR #2069⁴⁹¹⁹ - Fixed typos

⁴⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2091>

⁴⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2090>

⁴⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2089>

⁴⁹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/2088>

⁴⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/2087>

⁴⁹⁰² <https://github.com/TheHPXProject/hpx/issues/2086>

⁴⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/2085>

⁴⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2084>

⁴⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2083>

⁴⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2082>

⁴⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2081>

⁴⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2080>

⁴⁹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2079>

⁴⁹¹⁰ <https://github.com/TheHPXProject/hpx/issues/2078>

⁴⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/2077>

⁴⁹¹² <https://github.com/TheHPXProject/hpx/pull/2076>

⁴⁹¹³ <https://github.com/TheHPXProject/hpx/pull/2075>

⁴⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/2074>

⁴⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/2073>

⁴⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/2072>

⁴⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/2071>

⁴⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/2070>

⁴⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/2069>

- Issue #2068⁴⁹²⁰ - Seg fault with octotiger
- PR #2067⁴⁹²¹ - Algorithm cleanup
- PR #2066⁴⁹²² - Split credit fixes
- PR #2065⁴⁹²³ - Rename HPX_MOVABLE_BUT_NOT_COPYABLE to HPX_MOVABLE_ONLY
- PR #2064⁴⁹²⁴ - Fixed some typos in docs
- PR #2063⁴⁹²⁵ - Adding example demonstrating template components
- Issue #2062⁴⁹²⁶ - Support component templates
- PR #2061⁴⁹²⁷ - Replace some uses of lexical_cast<string> with C++11 std::to_string
- PR #2060⁴⁹²⁸ - Replace uses of boost::noncopyable with HPX_NON_COPYABLE
- PR #2059⁴⁹²⁹ - Adding missing for_loop algorithms
- PR #2058⁴⁹³⁰ - Move several definitions to more appropriate headers
- PR #2057⁴⁹³¹ - Simplify assert_owns_lock and ignore_while_checking
- PR #2056⁴⁹³² - Replacing std::result_of with util::result_of
- PR #2055⁴⁹³³ - Fix process launching/connecting back
- PR #2054⁴⁹³⁴ - Add a forwarding coroutine header
- PR #2053⁴⁹³⁵ - Replace uses of boost::unordered_map with std::unordered_map
- PR #2052⁴⁹³⁶ - Rewrite tuple unwrap
- PR #2050⁴⁹³⁷ - Replace uses of BOOST_SCOPED_ENUM with C++11 scoped enums
- PR #2049⁴⁹³⁸ - Attempt to narrow down split_credit problem
- PR #2048⁴⁹³⁹ - Fixing gcc startup hangs
- PR #2047⁴⁹⁴⁰ - Fixing when_xxx and wait_xxx for MSVC12
- PR #2046⁴⁹⁴¹ - adding persistent_auto_chunk_size and related tests for for_each
- PR #2045⁴⁹⁴² - Fixing HPX_HAVE_THREAD_BACKTRACE_DEPTH build time configuration

⁴⁹²⁰ <https://github.com/TheHPXProject/hpx/issues/2068>

⁴⁹²¹ <https://github.com/TheHPXProject/hpx/pull/2067>

⁴⁹²² <https://github.com/TheHPXProject/hpx/pull/2066>

⁴⁹²³ <https://github.com/TheHPXProject/hpx/pull/2065>

⁴⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/2064>

⁴⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/2063>

⁴⁹²⁶ <https://github.com/TheHPXProject/hpx/issues/2062>

⁴⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/2061>

⁴⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/2060>

⁴⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/2059>

⁴⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/2058>

⁴⁹³¹ <https://github.com/TheHPXProject/hpx/pull/2057>

⁴⁹³² <https://github.com/TheHPXProject/hpx/pull/2056>

⁴⁹³³ <https://github.com/TheHPXProject/hpx/pull/2055>

⁴⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/2054>

⁴⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/2053>

⁴⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/2052>

⁴⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/2050>

⁴⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/2049>

⁴⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/2048>

⁴⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2047>

⁴⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/2046>

⁴⁹⁴² <https://github.com/TheHPXProject/hpx/pull/2045>

- PR #2044⁴⁹⁴³ - Adding missing service executor types
- PR #2043⁴⁹⁴⁴ - Removing ambiguous definitions for `is_future_range` and `future_range_traits`
- PR #2042⁴⁹⁴⁵ - Clarify that HPX builds can use (much) more than 2GB per process
- PR #2041⁴⁹⁴⁶ - Changing `future_iterator_traits` to support pointers
- Issue #2040⁴⁹⁴⁷ - Improve documentation memory usage warning?
- PR #2039⁴⁹⁴⁸ - Coroutine cleanup
- PR #2038⁴⁹⁴⁹ - Fix cmake policy CMP0042 warning MACOSX_RPATH
- PR #2037⁴⁹⁵⁰ - Avoid redundant specialization of `[unique_]function_nonser`
- PR #2036⁴⁹⁵¹ - nvcc dies with an internal error upon pushing/popping warnings inside templates
- Issue #2035⁴⁹⁵² - Use a less restrictive iterator definition in `hpx::lcos::detail::future_iterator_traits`
- PR #2034⁴⁹⁵³ - Fixing compilation error with thread queue wait time performance counter
- Issue #2033⁴⁹⁵⁴ - Compilation error when compiling with thread queue waittime performance counter
- Issue #2032⁴⁹⁵⁵ - Ambiguous template instantiation for `is_future_range` and `future_range_traits`.
- PR #2031⁴⁹⁵⁶ - Don't restart timer on every incoming parcel
- PR #2030⁴⁹⁵⁷ - Unify handling of execution policies in parallel algorithms
- PR #2029⁴⁹⁵⁸ - Make pkg-config .pc files use .dylib on OSX
- PR #2028⁴⁹⁵⁹ - Adding process component
- PR #2027⁴⁹⁶⁰ - Making check for compiler compatibility independent on compiler path
- PR #2025⁴⁹⁶¹ - Fixing inspect tool
- PR #2024⁴⁹⁶² - Intel13 removal
- PR #2023⁴⁹⁶³ - Fix errors related to older boost versions and parameter pack expansions in lambdas
- Issue #2022⁴⁹⁶⁴ - gmake fail: "No rule to make target /usr/lib46/libboost_context-mt.so"
- PR #2021⁴⁹⁶⁵ - Added Sudoku example

⁴⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/2044>

⁴⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2043>

⁴⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2042>

⁴⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2041>

⁴⁹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/2040>

⁴⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2039>

⁴⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2038>

⁴⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2037>

⁴⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/2036>

⁴⁹⁵² <https://github.com/TheHPXProject/hpx/issues/2035>

⁴⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/2034>

⁴⁹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2033>

⁴⁹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/2032>

⁴⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2031>

⁴⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2030>

⁴⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2029>

⁴⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2028>

⁴⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2027>

⁴⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/2025>

⁴⁹⁶² <https://github.com/TheHPXProject/hpx/pull/2024>

⁴⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/2023>

⁴⁹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2022>

⁴⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2021>

- [Issue #2020⁴⁹⁶⁶](#) - Make errors related to `init_globally.cpp` example while building HPX out of the box
- [PR #2019⁴⁹⁶⁷](#) - Fixed some compilation and cmake errors encountered in `nqueen` example
- [PR #2018⁴⁹⁶⁸](#) - For loop algorithms
- [PR #2017⁴⁹⁶⁹](#) - Non-recursive `at_index` implementation
- [Issue #2016⁴⁹⁷⁰](#) - Add index-based for-loops
- [Issue #2015⁴⁹⁷¹](#) - Change default bind-mode to balanced
- [PR #2014⁴⁹⁷²](#) - Fixed dataflow if invoked action returns a future
- [PR #2013⁴⁹⁷³](#) - Fixing compilation issues with external example
- [PR #2012⁴⁹⁷⁴](#) - Added Sierpinski Triangle example
- [Issue #2011⁴⁹⁷⁵](#) - Compilation error while running sample `hello_world_component` code
- [PR #2010⁴⁹⁷⁶](#) - Segmented move implemented for `hpx::vector`
- [Issue #2009⁴⁹⁷⁷](#) - pkg-config order incorrect on 14.04 / GCC 4.8
- [Issue #2008⁴⁹⁷⁸](#) - Compilation error in dataflow of action returning a future
- [PR #2007⁴⁹⁷⁹](#) - Adding new performance counter exposing overall scheduler time
- [PR #2006⁴⁹⁸⁰](#) - Function includes
- [PR #2005⁴⁹⁸¹](#) - Adding an example demonstrating how to initialize HPX from a global object
- [PR #2004⁴⁹⁸²](#) - Fixing 2000
- [PR #2003⁴⁹⁸³](#) - Adding generation parameter to `gather` to enable using it more than once
- [PR #2002⁴⁹⁸⁴](#) - Turn on position independent code to solve link problem with `hpx_init`
- [Issue #2001⁴⁹⁸⁵](#) - Gathering more than once segfaults
- [Issue #2000⁴⁹⁸⁶](#) - Undefined reference to `hpx::assertion_failed`
- [Issue #1999⁴⁹⁸⁷](#) - Seg fault in `hpx::lcos::base_lco_with_value<*>::set_value_nonvirt()` when running `octo-tiger`
- [PR #1998⁴⁹⁸⁸](#) - Detect unknown command line options

⁴⁹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/2020>

⁴⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2019>

⁴⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2018>

⁴⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2017>

⁴⁹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2016>

⁴⁹⁷¹ <https://github.com/TheHPXProject/hpx/issues/2015>

⁴⁹⁷² <https://github.com/TheHPXProject/hpx/pull/2014>

⁴⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/2013>

⁴⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2012>

⁴⁹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2011>

⁴⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2010>

⁴⁹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2009>

⁴⁹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2008>

⁴⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2007>

⁴⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2006>

⁴⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/2005>

⁴⁹⁸² <https://github.com/TheHPXProject/hpx/pull/2004>

⁴⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/2003>

⁴⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2002>

⁴⁹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2001>

⁴⁹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/2000>

⁴⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1999>

⁴⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1998>

- PR #1997⁴⁹⁸⁹ - Extending thread description
- PR #1996⁴⁹⁹⁰ - Adding natvis files to solution (MSVC only)
- Issue #1995⁴⁹⁹¹ - Command line handling does not produce error
- PR #1994⁴⁹⁹² - Possible missing include in test_utils.hpp
- PR #1993⁴⁹⁹³ - Add missing LANGUAGES tag to a hpx_add_compile_flag_if_available() call in CMakeLists.txt
- PR #1992⁴⁹⁹⁴ - Fixing shared_executor_test
- PR #1991⁴⁹⁹⁵ - Making sure the winsock library is properly initialized
- PR #1990⁴⁹⁹⁶ - Fixing bind_test placeholder ambiguity coming from boost-1.60
- PR #1989⁴⁹⁹⁷ - Performance tuning
- PR #1987⁴⁹⁹⁸ - Make configurable size of internal storage in util::function
- PR #1986⁴⁹⁹⁹ - AGAS Refactoring+1753 Cache mods
- PR #1985⁵⁰⁰⁰ - Adding missing task_block::run() overload taking an executor
- PR #1984⁵⁰⁰¹ - Adding an optimized LRU Cache implementation (for AGAS)
- PR #1983⁵⁰⁰² - Avoid invoking migration table look up for all objects
- PR #1981⁵⁰⁰³ - Replacing uintptr_t (which is not defined everywhere) with std::size_t
- PR #1980⁵⁰⁰⁴ - Optimizing LCO continuations
- PR #1979⁵⁰⁰⁵ - Fixing Cori
- PR #1978⁵⁰⁰⁶ - Fix test check that got broken in hasty fix to memory overflow
- PR #1977⁵⁰⁰⁷ - Refactor action traits
- PR #1976⁵⁰⁰⁸ - Fixes typo in README.rst
- PR #1975⁵⁰⁰⁹ - Reduce size of benchmark timing arrays to fix test failures
- PR #1974⁵⁰¹⁰ - Add action to update data owned by the partitioned_vector component
- PR #1972⁵⁰¹¹ - Adding partitioned_vector SPMD example

⁴⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1997>
⁴⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1996>
⁴⁹⁹¹ <https://github.com/TheHPXProject/hpx/issues/1995>
⁴⁹⁹² <https://github.com/TheHPXProject/hpx/pull/1994>
⁴⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/1993>
⁴⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1992>
⁴⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1991>
⁴⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1990>
⁴⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1989>
⁴⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1987>
⁴⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1986>
⁵⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1985>
⁵⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/1984>
⁵⁰⁰² <https://github.com/TheHPXProject/hpx/pull/1983>
⁵⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/1981>
⁵⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1980>
⁵⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1979>
⁵⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1978>
⁵⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1977>
⁵⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1976>
⁵⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1975>
⁵⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/1974>
⁵⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/1972>

- PR #1971⁵⁰¹² - Fixing 1965
- PR #1970⁵⁰¹³ - Papi fixes
- PR #1969⁵⁰¹⁴ - Fixing continuation recursions to not depend on fixed amount of recursions
- PR #1968⁵⁰¹⁵ - More segmented algorithms
- Issue #1967⁵⁰¹⁶ - Simplify component implementations
- PR #1966⁵⁰¹⁷ - Migrate components
- Issue #1964⁵⁰¹⁸ - fatal error: 'boost/lockfree/detail/branch_hints.hpp' file not found
- Issue #1962⁵⁰¹⁹ - parallel::copy_if has race condition when used on in place arrays
- PR #1963⁵⁰²⁰ - Fixing Static Parcelport initialization
- PR #1961⁵⁰²¹ - Fix function target
- Issue #1960⁵⁰²² - Papi counters don't reset
- PR #1959⁵⁰²³ - Fixing 1958
- Issue #1958⁵⁰²⁴ - inclusive_scan gives incorrect results with non-commutative operator
- PR #1957⁵⁰²⁵ - Fixing #1950
- PR #1956⁵⁰²⁶ - Sort by key example
- PR #1955⁵⁰²⁷ - Adding regression test for #1946: Hang in wait_all() in distributed run
- Issue #1954⁵⁰²⁸ - HPX releases should not use -Werror
- PR #1953⁵⁰²⁹ - Adding performance analysis for AGAS cache
- PR #1952⁵⁰³⁰ - Adapting test for explicit variadics to fail for gcc 4.6
- PR #1951⁵⁰³¹ - Fixing memory leak
- Issue #1950⁵⁰³² - Simplify external builds
- PR #1949⁵⁰³³ - Fixing yet another lock that is being held during suspension
- PR #1948⁵⁰³⁴ - Fixed container algorithms for Intel

⁵⁰¹² <https://github.com/TheHPXProject/hpx/pull/1971>

⁵⁰¹³ <https://github.com/TheHPXProject/hpx/pull/1970>

⁵⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/1969>

⁵⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/1968>

⁵⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/1967>

⁵⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/1966>

⁵⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/1964>

⁵⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/1962>

⁵⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/1963>

⁵⁰²¹ <https://github.com/TheHPXProject/hpx/pull/1961>

⁵⁰²² <https://github.com/TheHPXProject/hpx/issues/1960>

⁵⁰²³ <https://github.com/TheHPXProject/hpx/pull/1959>

⁵⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/1958>

⁵⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/1957>

⁵⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/1956>

⁵⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/1955>

⁵⁰²⁸ <https://github.com/TheHPXProject/hpx/issues/1954>

⁵⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/1953>

⁵⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/1952>

⁵⁰³¹ <https://github.com/TheHPXProject/hpx/pull/1951>

⁵⁰³² <https://github.com/TheHPXProject/hpx/issues/1950>

⁵⁰³³ <https://github.com/TheHPXProject/hpx/pull/1949>

⁵⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/1948>

- PR #1947⁵⁰³⁵ - Adding workaround for tagged_tuple
- Issue #1946⁵⁰³⁶ - Hang in wait_all() in distributed run
- PR #1945⁵⁰³⁷ - Fixed container algorithm tests
- Issue #1944⁵⁰³⁸ - assertion 'p.destination_locality() == hpx::get_locality()' failed
- PR #1943⁵⁰³⁹ - Fix a couple of compile errors with clang
- PR #1942⁵⁰⁴⁰ - Making parcel coalescing functional
- Issue #1941⁵⁰⁴¹ - Re-enable parcel coalescing
- PR #1940⁵⁰⁴² - Touching up make_future
- PR #1939⁵⁰⁴³ - Fixing problems in over-subscription management in the resource manager
- PR #1938⁵⁰⁴⁴ - Removing use of unified Boost.Thread header
- PR #1937⁵⁰⁴⁵ - Cleaning up the use of Boost.Accumulator headers
- PR #1936⁵⁰⁴⁶ - Making sure interval timer is started for aggregating performance counters
- PR #1935⁵⁰⁴⁷ - Tagged results
- PR #1934⁵⁰⁴⁸ - Fix remote async with deferred launch policy
- Issue #1933⁵⁰⁴⁹ - Floating point exception in statistics_counter<boost::accumulators::tag::mean>::get_counter_v
- PR #1932⁵⁰⁵⁰ - Removing superfluous includes of boost/lockfree/detail/branch_hints.hpp
- PR #1931⁵⁰⁵¹ - fix compilation with clang 3.8.0
- Issue #1930⁵⁰⁵² - Missing online documentation for HPX 0.9.11
- PR #1929⁵⁰⁵³ - LWG2485: get() should be overloaded for const tuple&&
- PR #1928⁵⁰⁵⁴ - Revert “Using ninja for circle-ci builds”
- PR #1927⁵⁰⁵⁵ - Using ninja for circle-ci builds
- PR #1926⁵⁰⁵⁶ - Fixing serialization of std::array
- Issue #1925⁵⁰⁵⁷ - Issues with static HPX libraries

⁵⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/1947>

⁵⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/1946>

⁵⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/1945>

⁵⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/1944>

⁵⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/1943>

⁵⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1942>

⁵⁰⁴¹ <https://github.com/TheHPXProject/hpx/issues/1941>

⁵⁰⁴² <https://github.com/TheHPXProject/hpx/pull/1940>

⁵⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/1939>

⁵⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1938>

⁵⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1937>

⁵⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1936>

⁵⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1935>

⁵⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1934>

⁵⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1933>

⁵⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1932>

⁵⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/1931>

⁵⁰⁵² <https://github.com/TheHPXProject/hpx/issues/1930>

⁵⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/1929>

⁵⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1928>

⁵⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1927>

⁵⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1926>

⁵⁰⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1925>

- [Issue #1924⁵⁰⁵⁸](#) - Performance degrading over time
- [Issue #1923⁵⁰⁵⁹](#) - serialization of `std::array` appears broken in latest commit
- [PR #1922⁵⁰⁶⁰](#) - Container algorithms
- [PR #1921⁵⁰⁶¹](#) - Tons of smaller quality improvements
- [Issue #1920⁵⁰⁶²](#) - Seg fault in `hpx::serialization::output_archive::add_gid` when running octotiger
- [Issue #1919⁵⁰⁶³](#) - Intel 15 compiler bug preventing HPX build
- [PR #1918⁵⁰⁶⁴](#) - Address sanitizer fixes
- [PR #1917⁵⁰⁶⁵](#) - Fixing compilation problems of `parallel::sort` with Intel compilers
- [PR #1916⁵⁰⁶⁶](#) - Making sure code compiles if `HPX_WITH_HWLOC=Off`
- [Issue #1915⁵⁰⁶⁷](#) - `max_cores` undefined if `HPX_WITH_HWLOC=Off`
- [PR #1913⁵⁰⁶⁸](#) - Add utility member functions for `partitioned_vector`
- [PR #1912⁵⁰⁶⁹](#) - Adding support for invoking actions to dataflow
- [PR #1911⁵⁰⁷⁰](#) - Adding first batch of container algorithms
- [PR #1910⁵⁰⁷¹](#) - Keep `cmake_module_path`
- [PR #1909⁵⁰⁷²](#) - Fix `mpirun` with `pbs`
- [PR #1908⁵⁰⁷³](#) - Changing `parallel::sort` to return the last iterator as proposed by N4560
- [PR #1907⁵⁰⁷⁴](#) - Adding a minimum version for Open MPI
- [PR #1906⁵⁰⁷⁵](#) - Updates to the Release Procedure
- [PR #1905⁵⁰⁷⁶](#) - Fixing #1903
- [PR #1904⁵⁰⁷⁷](#) - Making sure `std` containers are cleared before serialization loads data
- [Issue #1903⁵⁰⁷⁸](#) - When running octotiger, I get: `assertion '(*new_gids_)[gid].size() == 1' failed: HPX(assertion_failure)`
- [Issue #1902⁵⁰⁷⁹](#) - Immediate crash when running `hpx/octotiger` with `_GLIBCXX_DEBUG` defined.
- [PR #1901⁵⁰⁸⁰](#) - Making non-serializable classes non-serializable

⁵⁰⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1924>

⁵⁰⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1923>

⁵⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1922>

⁵⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/1921>

⁵⁰⁶² <https://github.com/TheHPXProject/hpx/issues/1920>

⁵⁰⁶³ <https://github.com/TheHPXProject/hpx/issues/1919>

⁵⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1918>

⁵⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1917>

⁵⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1916>

⁵⁰⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1915>

⁵⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1913>

⁵⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1912>

⁵⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1911>

⁵⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/1910>

⁵⁰⁷² <https://github.com/TheHPXProject/hpx/pull/1909>

⁵⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/1908>

⁵⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1907>

⁵⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1906>

⁵⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/1905>

⁵⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1904>

⁵⁰⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1903>

⁵⁰⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1902>

⁵⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1901>

- [Issue #1900](#)⁵⁰⁸¹ - Two possible issues with `std::list` serialization
- [PR #1899](#)⁵⁰⁸² - Fixing a problem with credit splitting as revealed by #1898
- [Issue #1898](#)⁵⁰⁸³ - Accessing component from locality where it was not created segfaults
- [PR #1897](#)⁵⁰⁸⁴ - Changing `parallel::sort` to return the last iterator as proposed by N4560
- [Issue #1896](#)⁵⁰⁸⁵ - version 1.0?
- [Issue #1895](#)⁵⁰⁸⁶ - Warning comment on `numa_allocator` is not very clear
- [PR #1894](#)⁵⁰⁸⁷ - Add support for compilers that have `thread_local`
- [PR #1893](#)⁵⁰⁸⁸ - Fixing 1890
- [PR #1892](#)⁵⁰⁸⁹ - Adds typed `future_type` for `executor_traits`
- [PR #1891](#)⁵⁰⁹⁰ - Fix wording in certain parallel algorithm docs
- [Issue #1890](#)⁵⁰⁹¹ - Invoking `papi` counters give segfault
- [PR #1889](#)⁵⁰⁹² - Fixing problems as reported by `clang-check`
- [PR #1888](#)⁵⁰⁹³ - WIP `parallel is_heap`
- [PR #1887](#)⁵⁰⁹⁴ - Fixed resetting performance counters related to idle-rate, etc
- [Issue #1886](#)⁵⁰⁹⁵ - Run `hpx` with `qsub` does not work
- [PR #1885](#)⁵⁰⁹⁶ - Warning cleaning pass
- [PR #1884](#)⁵⁰⁹⁷ - Add missing parallel algorithm header
- [PR #1883](#)⁵⁰⁹⁸ - Add feature test for `thread_local` on Clang for TLS
- [PR #1882](#)⁵⁰⁹⁹ - Fix some redundant qualifiers
- [Issue #1881](#)⁵¹⁰⁰ - Unable to compile Octotiger using HPX and Intel MPI on SuperMIC
- [Issue #1880](#)⁵¹⁰¹ - `clang` with `libc++` on Linux needs TLS case
- [PR #1879](#)⁵¹⁰² - Doc fixes for #1868
- [PR #1878](#)⁵¹⁰³ - Simplify functions

⁵⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/1900>

⁵⁰⁸² <https://github.com/TheHPXProject/hpx/pull/1899>

⁵⁰⁸³ <https://github.com/TheHPXProject/hpx/issues/1898>

⁵⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1897>

⁵⁰⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1896>

⁵⁰⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1895>

⁵⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1894>

⁵⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1893>

⁵⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1892>

⁵⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1891>

⁵⁰⁹¹ <https://github.com/TheHPXProject/hpx/issues/1890>

⁵⁰⁹² <https://github.com/TheHPXProject/hpx/pull/1889>

⁵⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/1888>

⁵⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1887>

⁵⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1886>

⁵⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1885>

⁵⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1884>

⁵⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1883>

⁵⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1882>

⁵¹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1881>

⁵¹⁰¹ <https://github.com/TheHPXProject/hpx/issues/1880>

⁵¹⁰² <https://github.com/TheHPXProject/hpx/pull/1879>

⁵¹⁰³ <https://github.com/TheHPXProject/hpx/pull/1878>

- PR #1877⁵¹⁰⁴ - Removing most usage of Boost.Config
- PR #1876⁵¹⁰⁵ - Add missing parallel algorithms to algorithm.hpp
- PR #1875⁵¹⁰⁶ - Simplify callables
- PR #1874⁵¹⁰⁷ - Address long standing FIXME on using `std::unique_ptr` with incomplete types
- PR #1873⁵¹⁰⁸ - Fixing 1871
- PR #1872⁵¹⁰⁹ - Making sure PBS environment uses specified node list even if no PBS_NODEFILE env is available
- Issue #1871⁵¹¹⁰ - Fortran checks should be optional
- PR #1870⁵¹¹¹ - Touch local::mutex
- PR #1869⁵¹¹² - Documentation refactoring based off #1868
- PR #1867⁵¹¹³ - Embrace static_assert
- PR #1866⁵¹¹⁴ - Fix #1803 with documentation refactoring
- PR #1865⁵¹¹⁵ - Setting OUTPUT_NAME as target properties
- PR #1863⁵¹¹⁶ - Use SYSTEM for boost includes
- PR #1862⁵¹¹⁷ - Minor cleanups
- PR #1861⁵¹¹⁸ - Minor Corrections for Release
- PR #1860⁵¹¹⁹ - Fixing hpx gdb script
- Issue #1859⁵¹²⁰ - reset_active_counters resets times and thread counts before some of the counters are evaluated
- PR #1858⁵¹²¹ - Release V0.9.11
- PR #1857⁵¹²² - removing diskperf example from 9.11 release
- PR #1856⁵¹²³ - fix return in packaged_task_base::reset()
- Issue #1842⁵¹²⁴ - Install error: file INSTALL cannot find libhpx_parcel_coalescing.so.0.9.11
- PR #1839⁵¹²⁵ - Adding fedora docs
- PR #1824⁵¹²⁶ - Changing version on master to V0.9.12

⁵¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1877>
⁵¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1876>
⁵¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1875>
⁵¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1874>
⁵¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1873>
⁵¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1872>
⁵¹¹⁰ <https://github.com/TheHPXProject/hpx/issues/1871>
⁵¹¹¹ <https://github.com/TheHPXProject/hpx/pull/1870>
⁵¹¹² <https://github.com/TheHPXProject/hpx/pull/1869>
⁵¹¹³ <https://github.com/TheHPXProject/hpx/pull/1867>
⁵¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/1866>
⁵¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/1865>
⁵¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/1863>
⁵¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/1862>
⁵¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/1861>
⁵¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/1860>
⁵¹²⁰ <https://github.com/TheHPXProject/hpx/issues/1859>
⁵¹²¹ <https://github.com/TheHPXProject/hpx/pull/1858>
⁵¹²² <https://github.com/TheHPXProject/hpx/pull/1857>
⁵¹²³ <https://github.com/TheHPXProject/hpx/pull/1856>
⁵¹²⁴ <https://github.com/TheHPXProject/hpx/issues/1842>
⁵¹²⁵ <https://github.com/TheHPXProject/hpx/pull/1839>
⁵¹²⁶ <https://github.com/TheHPXProject/hpx/pull/1824>

- PR #1818⁵¹²⁷ - Fixing #1748
- Issue #1815⁵¹²⁸ - seg fault in AGAS
- Issue #1803⁵¹²⁹ - wait_all documentation
- Issue #1796⁵¹³⁰ - Outdated documentation to be revised
- Issue #1759⁵¹³¹ - glibc munmap_chunk or free(): invalid pointer on SuperMIC
- Issue #1753⁵¹³² - HPX performance degrades with time since execution begins
- Issue #1748⁵¹³³ - All public HPX headers need to be self contained
- PR #1719⁵¹³⁴ - How to build HPX with Visual Studio
- Issue #1684⁵¹³⁵ - Race condition when using -hpx:connect?
- PR #1658⁵¹³⁶ - Add serialization for std::set (as there is for std::vector and std::map)
- PR #1641⁵¹³⁷ - Generic client
- Issue #1632⁵¹³⁸ - heartbeat example fails on separate nodes
- PR #1603⁵¹³⁹ - Adds preferred namespace check to inspect tool
- Issue #1559⁵¹⁴⁰ - Extend inspect tool
- Issue #1523⁵¹⁴¹ - Remote async with deferred launch policy never executes
- Issue #1472⁵¹⁴² - Serialization issues
- Issue #1457⁵¹⁴³ - Implement N4392: C++ Latches and Barriers
- PR #1444⁵¹⁴⁴ - Enabling usage of moveonly types for component construction
- Issue #1407⁵¹⁴⁵ - The Intel 13 compiler has failing unit tests
- Issue #1405⁵¹⁴⁶ - Allow component constructors to take movable only types
- Issue #1265⁵¹⁴⁷ - Enable dataflow() to be usable with actions
- Issue #1236⁵¹⁴⁸ - NUMA aware allocators
- Issue #802⁵¹⁴⁹ - Fix Broken Examples

⁵¹²⁷ <https://github.com/TheHPXProject/hpx/pull/1818>

⁵¹²⁸ <https://github.com/TheHPXProject/hpx/issues/1815>

⁵¹²⁹ <https://github.com/TheHPXProject/hpx/issues/1803>

⁵¹³⁰ <https://github.com/TheHPXProject/hpx/issues/1796>

⁵¹³¹ <https://github.com/TheHPXProject/hpx/issues/1759>

⁵¹³² <https://github.com/TheHPXProject/hpx/issues/1753>

⁵¹³³ <https://github.com/TheHPXProject/hpx/issues/1748>

⁵¹³⁴ <https://github.com/TheHPXProject/hpx/pull/1719>

⁵¹³⁵ <https://github.com/TheHPXProject/hpx/issues/1684>

⁵¹³⁶ <https://github.com/TheHPXProject/hpx/pull/1658>

⁵¹³⁷ <https://github.com/TheHPXProject/hpx/pull/1641>

⁵¹³⁸ <https://github.com/TheHPXProject/hpx/issues/1632>

⁵¹³⁹ <https://github.com/TheHPXProject/hpx/pull/1603>

⁵¹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1559>

⁵¹⁴¹ <https://github.com/TheHPXProject/hpx/issues/1523>

⁵¹⁴² <https://github.com/TheHPXProject/hpx/issues/1472>

⁵¹⁴³ <https://github.com/TheHPXProject/hpx/issues/1457>

⁵¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1444>

⁵¹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1407>

⁵¹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1405>

⁵¹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1265>

⁵¹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1236>

⁵¹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/802>

- [Issue #559](#)⁵¹⁵⁰ - Add `hpx::migrate` facility
- [Issue #449](#)⁵¹⁵¹ - Make actions with template arguments usable and add documentation
- [Issue #279](#)⁵¹⁵² - Refactor `addressing_service` into a base class and two derived classes
- [Issue #224](#)⁵¹⁵³ - Changing thread state metadata is not thread safe
- [Issue #55](#)⁵¹⁵⁴ - Uniform syntax for enums should be implemented

HPX V0.9.11 (Nov 11, 2015)

Our main focus for this release was the design and development of a coherent set of higher-level APIs exposing various types of parallelism to the application programmer. We introduced the concepts of an `executor`, which can be used to customize the `where` and `when` of execution of tasks in the context of parallelizing codes. We extended all APIs related to managing parallel tasks to support executors which gives the user the choice of either using one of the predefined executor types or to provide its own, possibly application specific, executor. We paid very close attention to align all of these changes with the existing C++ Standards documents or with the ongoing proposals for standardization.

This release is the first after our change to a new development policy. We switched all development to be strictly performed on branches only, all direct commits to our main branch (`master`) are prohibited. Any change has to go through a peer review before it will be merged to `master`. As a result the overall stability of our code base has significantly increased, the development process itself has been simplified. This change manifests itself in a large number of pull-requests which have been merged (please see below for a full list of closed issues and pull-requests). All in all for this release, we closed almost 100 issues and merged over 290 pull-requests. There have been over 1600 commits to the master branch since the last release.

General changes

- We are moving into the direction of unifying managed and simple components. As such, the classes `hpx::components::component` and `hpx::components::component_base` have been added which currently just forward to the currently existing simple component facilities. The examples have been converted to only use those two classes.
- Added integration with the [CircleCI](#)⁵¹⁵⁵ hosted continuous integration service. This gives us constant and immediate feedback on the health of our master branch.
- The compiler configuration subsystem in the build system has been reimplemented. Instead of using `Boost.Config` we now use our own lightweight set of `cmake` scripts to determine the available language and library features supported by the used compiler.
- The API for creating instances of components has been consolidated. All component instances should be created using the `hpx::new_` only. It allows one to instantiate both, single component instances and multiple component instances. The placement of the created components can be controlled by special distribution policies. Please see the corresponding documentation outlining the use of `hpx::new_`.
- Introduced four new distribution policies which can be used with many API functions which traditionally expected to be used with a locality id. The new distribution policies are:
 - `hpx::components::default_distribution_policy` which tries to place multiple component instances as evenly as possible.

⁵¹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/559>

⁵¹⁵¹ <https://github.com/TheHPXProject/hpx/issues/449>

⁵¹⁵² <https://github.com/TheHPXProject/hpx/issues/279>

⁵¹⁵³ <https://github.com/TheHPXProject/hpx/issues/224>

⁵¹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/55>

⁵¹⁵⁵ <https://circleci.com/gh/TheHPXProject/hpx>

- `hpx::components::colocating_distribution_policy` which will refer to the locality where a given component instance is currently placed.
 - `hpx::components::binpacking_distribution_policy` which will place multiple component instances as evenly as possible based on any performance counter.
 - `hpx::components::target_distribution_policy` which allows one to represent a given locality in the context of a distribution policy.
- The new distribution policies can now be also used with `hpx::async`. This change also deprecates `hpx::async_colocated(id, ...)` which now is replaced by a distribution policy: `hpx::async(hpx::colocated(id), ...)`.
 - The `hpx::vector` and `hpx::unordered_map` data structures can now be used with the new distribution policies as well.
 - The parallel facility `hpx::parallel::task_region` has been renamed to `hpx::parallel::task_block` based on the changes in the corresponding standardization proposal [N4411](#)⁵¹⁵⁶.
 - Added extensions to the parallel facility `hpx::parallel::task_block` allowing to combine a `task_block` with an execution policy. This implies a minor breaking change as the `hpx::parallel::task_block` is now a template.
 - Added new LCOs: `hpx::lcos::latch` and `hpx::lcos::local::latch` which semantically conform to the proposed `std::latch` (see [N4399](#)⁵¹⁵⁷).
 - Added performance counters exposing data related to data transferred by input/output (filesystem) operations (thanks to Maciej Brodowicz).
 - Added performance counters allowing to track the number of action invocations (local and remote invocations).
 - Added new command line options `-hpx:print-counter-at` and `-hpx:reset-counters`.
 - The `hpx::vector` component has been renamed to `hpx::partitioned_vector` to make it explicit that the underlying memory is not contiguous.
 - Introduced a completely new and uniform higher-level parallelism API which is based on executors. All existing parallelism APIs have been adapted to this. We have added a large number of different executor types, such as a numa-aware executor, a this-thread executor, etc.
 - Added support for the MingW toolchain on Windows (thanks to Eric Lemanissier).
 - HPX now includes support for APEX, (Autonomic Performance Environment for eXascale). APEX is an instrumentation and software adaptation library that provides an interface to TAU profiling / tracing as well as runtime adaptation of HPX applications through policy definitions. For more information and documentation, please see <https://github.com/UO-OACISS/xpress-apex>. To enable APEX at configuration time, specify `-DHPX_WITH_APEX=On`. To also include support for TAU profiling, specify `-DHPX_WITH_TAU=On` and specify the `-DTAU_ROOT`, `-DTAU_ARCH` and `-DTAU_OPTIONS` cmake parameters.
 - We have implemented many more of the *Using parallel algorithms*. Please see [Issue #1141](#)⁵¹⁵⁸ for the list of all available parallel algorithms (thanks to Daniel Bourgeois and John Biddiscombe for contributing their work).

⁵¹⁵⁶ <http://wg21.link/n4411>⁵¹⁵⁷ <http://wg21.link/n4399>⁵¹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1141>

Breaking changes

- We are moving into the direction of unifying managed and simple components. In order to stop exposing the old facilities, all examples have been converted to use the new classes. The breaking change in this release is that performance counters are now a `hpx::components::component_base` instead of `hpx::components::managed_component_base`.
- We removed the support for stackless threads. It turned out that there was no performance benefit when using stackless threads. As such, we decided to clean up our codebase. This feature was not documented.
- The CMake project name has changed from 'hpx' to 'HPX' for consistency and compatibility with naming conventions and other CMake projects. Generated config files go into `<prefix>/lib/cmake/HPX` and not `<prefix>/lib/cmake/hpx`.
- The macro `HPX_REGISTER_MINIMAL_COMPONENT_FACTORY` has been deprecated. Please use `HPX_REGISTER_COMPONENT` instead. The old macro will be removed in the next release.
- The obsolete `distributing_factory` and `binpacking_factory` components have been removed. The corresponding functionality is now provided by the `hpx::new_` API function in conjunction with the `hpx::default_layout` and `hpx::binpacking` distribution policies (`hpx::components::default_distribution_policy` and `hpx::components::binpacking_distribution_policy`).
- The API function `hpx::new_colocated` has been deprecated. Please use the consolidated API `hpx::new_` in conjunction with the new `hpx::colocated` distribution policy (`hpx::components::colocating_distribution_policy`) instead. The old API function will still be available for at least one release of HPX if the configuration variable `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` is enabled.
- The API function `hpx::async_colocated` has been deprecated. Please use the consolidated API `hpx::async` in conjunction with the new `hpx::colocated` distribution policy (`hpx::components::colocating_distribution_policy`) instead. The old API function will still be available for at least one release of HPX if the configuration variable `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` is enabled.
- The obsolete `remote_object` component has been removed.
- Replaced the use of Boost.Serialization with our own solution. While the new version is mostly compatible with Boost.Serialization, this change requires some minor code modifications in user code. For more information, please see the corresponding [announcement⁵¹⁵⁹](http://thread.gmane.org/gmane.comp.lib.hpx.devel/196) on the `hpx-users@stellar.cct.lsu.edu` mailing list.
- The names used by cmake to influence various configuration options have been unified. The new naming scheme relies on all configuration constants to start with `HPX_WITH_...`, while the preprocessor constant which is used at build time starts with `HPX_HAVE_...`. For instance, the former cmake command line `-DHPX_MALLOC=...` now has to be specified as `-DHPX_WITH_MALLOC=...` and will cause the preprocessor constant `HPX_HAVE_MALLOC` to be defined. The actual name of the constant (i.e. `MALLOC`) has not changed. Please see the corresponding documentation for more details (*CMake options*).
- The `get_gid()` functions exposed by the component base classes `hpx::components::server::simple_component_base`, `hpx::components::server::managed_component_base`, and `hpx::components::server::fixed_component_base` have been replaced by two new functions: `get_unmanaged_id()` and `get_id()`. To enable the old function name for backwards compatibility, use the cmake configuration option `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY=On`.
- All functions which were named `get_gid()` but were returning `hpx::id_type` have been renamed to `get_id()`. To enable the old function names for backwards compatibility, use the cmake configuration option `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY=On`.

⁵¹⁵⁹ <http://thread.gmane.org/gmane.comp.lib.hpx.devel/196>

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #1855](#)⁵¹⁶⁰ - Completely removing external/endian
- [PR #1854](#)⁵¹⁶¹ - Don't pollute CMAKE_CXX_FLAGS through find_package()
- [PR #1853](#)⁵¹⁶² - Updating CMake configuration to get correct version of TAU library
- [PR #1852](#)⁵¹⁶³ - Fixing Performance Problems with MPI Parcelport
- [PR #1851](#)⁵¹⁶⁴ - Fixing hpx_add_link_flag() and hpx_remove_link_flag()
- [PR #1850](#)⁵¹⁶⁵ - Fixing 1836, adding parallel::sort
- [PR #1849](#)⁵¹⁶⁶ - Fixing configuration for use of more than 64 cores
- [PR #1848](#)⁵¹⁶⁷ - Change default APEX version for release
- [PR #1847](#)⁵¹⁶⁸ - Fix client_base::then on release
- [PR #1846](#)⁵¹⁶⁹ - Removing broken lcos::local::channel from release
- [PR #1845](#)⁵¹⁷⁰ - Adding example demonstrating a possible safe-object implementation to release
- [PR #1844](#)⁵¹⁷¹ - Removing stubs from accumulator examples
- [PR #1843](#)⁵¹⁷² - Don't pollute CMAKE_CXX_FLAGS through find_package()
- [PR #1841](#)⁵¹⁷³ - Fixing client_base<>::then
- [PR #1840](#)⁵¹⁷⁴ - Adding example demonstrating a possible safe-object implementation
- [PR #1838](#)⁵¹⁷⁵ - Update version rc1
- [PR #1837](#)⁵¹⁷⁶ - Removing broken lcos::local::channel
- [PR #1835](#)⁵¹⁷⁷ - Adding explicit move constructor and assignment operator to hpx::lcos::promise
- [PR #1834](#)⁵¹⁷⁸ - Making hpx::lcos::promise move-only
- [PR #1833](#)⁵¹⁷⁹ - Adding fedora docs
- [Issue #1832](#)⁵¹⁸⁰ - hpx::lcos::promise<> must be move-only

⁵¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1855>

⁵¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/1854>

⁵¹⁶² <https://github.com/TheHPXProject/hpx/pull/1853>

⁵¹⁶³ <https://github.com/TheHPXProject/hpx/pull/1852>

⁵¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1851>

⁵¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1850>

⁵¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1849>

⁵¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1848>

⁵¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1847>

⁵¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1846>

⁵¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1845>

⁵¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/1844>

⁵¹⁷² <https://github.com/TheHPXProject/hpx/pull/1843>

⁵¹⁷³ <https://github.com/TheHPXProject/hpx/pull/1841>

⁵¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1840>

⁵¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1838>

⁵¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/1837>

⁵¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1835>

⁵¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1834>

⁵¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1833>

⁵¹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1832>

- PR #1831⁵¹⁸¹ - Fixing resource manager gcc5.2
- PR #1830⁵¹⁸² - Fix intel13
- PR #1829⁵¹⁸³ - Unbreaking thread test
- PR #1828⁵¹⁸⁴ - Fixing #1620
- PR #1827⁵¹⁸⁵ - Fixing a memory management issue for the Parquet application
- Issue #1826⁵¹⁸⁶ - Memory management issue in hpx::lcos::promise
- PR #1825⁵¹⁸⁷ - Adding hpx::components::component and hpx::components::component_base
- PR #1823⁵¹⁸⁸ - Adding git commit id to circleci build
- PR #1822⁵¹⁸⁹ - applying fixes suggested by clang 3.7
- PR #1821⁵¹⁹⁰ - Hyperlink fixes
- PR #1820⁵¹⁹¹ - added parallel multi-locality sanity test
- PR #1819⁵¹⁹² - Fixing #1667
- Issue #1817⁵¹⁹³ - Hyperlinks generated by inspect tool are wrong
- PR #1816⁵¹⁹⁴ - Support hpxrx
- PR #1814⁵¹⁹⁵ - Fix async to dispatch to the correct locality in all cases
- Issue #1813⁵¹⁹⁶ - async(launch::..., action(), ...) always invokes locally
- PR #1812⁵¹⁹⁷ - fixed syntax error in CMakeLists.txt
- PR #1811⁵¹⁹⁸ - Agas optimizations
- PR #1810⁵¹⁹⁹ - drop superfluous typedefs
- PR #1809⁵²⁰⁰ - Allow HPX to be used as an optional package in 3rd party code
- PR #1808⁵²⁰¹ - Fixing #1723
- PR #1807⁵²⁰² - Making sure resolve_localities does not hang during normal operation
- Issue #1806⁵²⁰³ - Spinlock no longer movable and deletes operator '=', breaks MiniGhost

⁵¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/1831>
⁵¹⁸² <https://github.com/TheHPXProject/hpx/pull/1830>
⁵¹⁸³ <https://github.com/TheHPXProject/hpx/pull/1829>
⁵¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1828>
⁵¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1827>
⁵¹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1826>
⁵¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1825>
⁵¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1823>
⁵¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1822>
⁵¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1821>
⁵¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/1820>
⁵¹⁹² <https://github.com/TheHPXProject/hpx/pull/1819>
⁵¹⁹³ <https://github.com/TheHPXProject/hpx/issues/1817>
⁵¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1816>
⁵¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1814>
⁵¹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1813>
⁵¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1812>
⁵¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1811>
⁵¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1810>
⁵²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1809>
⁵²⁰¹ <https://github.com/TheHPXProject/hpx/pull/1808>
⁵²⁰² <https://github.com/TheHPXProject/hpx/pull/1807>
⁵²⁰³ <https://github.com/TheHPXProject/hpx/issues/1806>

- Issue #1804⁵²⁰⁴ - register_with_basename causes hangs
- PR #1801⁵²⁰⁵ - Enhanced the inspect tool to take user directly to the problem with hyperlinks
- Issue #1800⁵²⁰⁶ - Problems compiling application on smic
- PR #1799⁵²⁰⁷ - Fixing cv exceptions
- PR #1798⁵²⁰⁸ - Documentation refactoring & updating
- PR #1797⁵²⁰⁹ - Updating the activeharmony CMake module
- PR #1795⁵²¹⁰ - Fixing cv
- PR #1794⁵²¹¹ - Fix connect with hpx::runtime_mode_connect
- PR #1793⁵²¹² - fix a wrong use of HPX_MAX_CPU_COUNT instead of HPX_HAVE_MAX_CPU_COUNT
- PR #1792⁵²¹³ - Allow for default constructed parcel instances to be moved
- PR #1791⁵²¹⁴ - Fix connect with hpx::runtime_mode_connect
- Issue #1790⁵²¹⁵ - assertion action_.get() failed: HPX(assertion_failure) when running Octotiger with pull request 1786
- PR #1789⁵²¹⁶ - Fixing discover_counter_types API function
- Issue #1788⁵²¹⁷ - connect with hpx::runtime_mode_connect
- Issue #1787⁵²¹⁸ - discover_counter_types not working
- PR #1786⁵²¹⁹ - Changing addressing_service to use std::unordered_map instead of std::map
- PR #1785⁵²²⁰ - Fix is_iterator for container algorithms
- PR #1784⁵²²¹ - Adding new command line options:
- PR #1783⁵²²² - Minor changes for APEX support
- PR #1782⁵²²³ - Drop legacy forwarding action traits
- PR #1781⁵²²⁴ - Attempt to resolve the race between cv::wait_xxx and cv::notify_all
- PR #1780⁵²²⁵ - Removing serialize_sequence
- PR #1779⁵²²⁶ - Fixed #1501: hwloc configuration options are wrong for MIC

⁵²⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1804>

⁵²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1801>

⁵²⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1800>

⁵²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1799>

⁵²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1798>

⁵²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1797>

⁵²¹⁰ <https://github.com/TheHPXProject/hpx/pull/1795>

⁵²¹¹ <https://github.com/TheHPXProject/hpx/pull/1794>

⁵²¹² <https://github.com/TheHPXProject/hpx/pull/1793>

⁵²¹³ <https://github.com/TheHPXProject/hpx/pull/1792>

⁵²¹⁴ <https://github.com/TheHPXProject/hpx/pull/1791>

⁵²¹⁵ <https://github.com/TheHPXProject/hpx/issues/1790>

⁵²¹⁶ <https://github.com/TheHPXProject/hpx/pull/1789>

⁵²¹⁷ <https://github.com/TheHPXProject/hpx/issues/1788>

⁵²¹⁸ <https://github.com/TheHPXProject/hpx/issues/1787>

⁵²¹⁹ <https://github.com/TheHPXProject/hpx/pull/1786>

⁵²²⁰ <https://github.com/TheHPXProject/hpx/pull/1785>

⁵²²¹ <https://github.com/TheHPXProject/hpx/pull/1784>

⁵²²² <https://github.com/TheHPXProject/hpx/pull/1783>

⁵²²³ <https://github.com/TheHPXProject/hpx/pull/1782>

⁵²²⁴ <https://github.com/TheHPXProject/hpx/pull/1781>

⁵²²⁵ <https://github.com/TheHPXProject/hpx/pull/1780>

⁵²²⁶ <https://github.com/TheHPXProject/hpx/pull/1779>

- PR #1778⁵²²⁷ - Removing ability to enable/disable parcel handling
- PR #1777⁵²²⁸ - Completely removing stackless threads
- PR #1776⁵²²⁹ - Cleaning up util/plugin
- PR #1775⁵²³⁰ - Agas fixes
- PR #1774⁵²³¹ - Action invocation count
- PR #1773⁵²³² - replaced MSVC variable with WIN32
- PR #1772⁵²³³ - Fixing Problems in MPI parcellport and future serialization.
- PR #1771⁵²³⁴ - Fixing intel 13 compiler errors related to variadic template template parameters for `lcos::when_` tests
- PR #1770⁵²³⁵ - Forwarding decay to `std::`
- PR #1769⁵²³⁶ - Add more characters with special regex meaning to the existing patch
- PR #1768⁵²³⁷ - Adding test for `receive_buffer`
- PR #1767⁵²³⁸ - Making sure that uptime counter throws exception on any attempt to be reset
- PR #1766⁵²³⁹ - Cleaning up code related to throttling scheduler
- PR #1765⁵²⁴⁰ - Restricting `thread_data` to creating only with `intrusive_pointers`
- PR #1764⁵²⁴¹ - Fixing 1763
- Issue #1763⁵²⁴² - UB in `thread_data::operator delete`
- PR #1762⁵²⁴³ - Making sure all serialization registries/factories are unique
- PR #1761⁵²⁴⁴ - Fixed #1751: `hpx::future::wait_for` fails a simple test
- PR #1758⁵²⁴⁵ - Fixing #1757
- Issue #1757⁵²⁴⁶ - pinning not correct using `-hpx:bind`
- Issue #1756⁵²⁴⁷ - compilation error with MinGW
- PR #1755⁵²⁴⁸ - Making output serialization const-correct
- Issue #1753⁵²⁴⁹ - HPX performance degrades with time since execution begins

⁵²²⁷ <https://github.com/TheHPXProject/hpx/pull/1778>
⁵²²⁸ <https://github.com/TheHPXProject/hpx/pull/1777>
⁵²²⁹ <https://github.com/TheHPXProject/hpx/pull/1776>
⁵²³⁰ <https://github.com/TheHPXProject/hpx/pull/1775>
⁵²³¹ <https://github.com/TheHPXProject/hpx/pull/1774>
⁵²³² <https://github.com/TheHPXProject/hpx/pull/1773>
⁵²³³ <https://github.com/TheHPXProject/hpx/pull/1772>
⁵²³⁴ <https://github.com/TheHPXProject/hpx/pull/1771>
⁵²³⁵ <https://github.com/TheHPXProject/hpx/pull/1770>
⁵²³⁶ <https://github.com/TheHPXProject/hpx/pull/1769>
⁵²³⁷ <https://github.com/TheHPXProject/hpx/pull/1768>
⁵²³⁸ <https://github.com/TheHPXProject/hpx/pull/1767>
⁵²³⁹ <https://github.com/TheHPXProject/hpx/pull/1766>
⁵²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1765>
⁵²⁴¹ <https://github.com/TheHPXProject/hpx/pull/1764>
⁵²⁴² <https://github.com/TheHPXProject/hpx/issues/1763>
⁵²⁴³ <https://github.com/TheHPXProject/hpx/pull/1762>
⁵²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1761>
⁵²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1758>
⁵²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1757>
⁵²⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1756>
⁵²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1755>
⁵²⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1753>

- Issue #1752⁵²⁵⁰ - Error in AGAS
- Issue #1751⁵²⁵¹ - `hpx::future::wait_for` fails a simple test
- PR #1750⁵²⁵² - Removing `hpx_fwd.hpp` includes
- PR #1749⁵²⁵³ - Simplify `result_of` and friends
- PR #1747⁵²⁵⁴ - Removed superfluous code from `message_buffer.hpp`
- PR #1746⁵²⁵⁵ - Tuple dependencies
- Issue #1745⁵²⁵⁶ - Broken when `_some` which takes iterators
- PR #1744⁵²⁵⁷ - Refining archive interface
- PR #1743⁵²⁵⁸ - Fixing when `_all` when only a single future is passed
- PR #1742⁵²⁵⁹ - Config includes
- PR #1741⁵²⁶⁰ - Os executors
- Issue #1740⁵²⁶¹ - `hpx::promise` has some problems
- PR #1739⁵²⁶² - Parallel composition with generic containers
- Issue #1738⁵²⁶³ - After building program and successfully linking to a version of `hpx` `DHPX_DIR` seems to be ignored
- Issue #1737⁵²⁶⁴ - Uptime problems
- PR #1736⁵²⁶⁵ - added convenience `c-tor` and `begin()/end()` to `serialize_buffer`
- PR #1735⁵²⁶⁶ - Config includes
- PR #1734⁵²⁶⁷ - Fixed #1688: Add timer counters for `tfunc_total` and `exec_total`
- Issue #1733⁵²⁶⁸ - Add unit test for `hpx/lcos/local/receive_buffer.hpp`
- PR #1732⁵²⁶⁹ - Renaming `get_os_thread_count`
- PR #1731⁵²⁷⁰ - Basename registration
- Issue #1730⁵²⁷¹ - Use after move of `thread_init_data`
- PR #1729⁵²⁷² - Rewriting channel based on new gate component

⁵²⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1752>

⁵²⁵¹ <https://github.com/TheHPXProject/hpx/issues/1751>

⁵²⁵² <https://github.com/TheHPXProject/hpx/pull/1750>

⁵²⁵³ <https://github.com/TheHPXProject/hpx/pull/1749>

⁵²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1747>

⁵²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1746>

⁵²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1745>

⁵²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1744>

⁵²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1743>

⁵²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1742>

⁵²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1741>

⁵²⁶¹ <https://github.com/TheHPXProject/hpx/issues/1740>

⁵²⁶² <https://github.com/TheHPXProject/hpx/pull/1739>

⁵²⁶³ <https://github.com/TheHPXProject/hpx/issues/1738>

⁵²⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1737>

⁵²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1736>

⁵²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1735>

⁵²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1734>

⁵²⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1733>

⁵²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1732>

⁵²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1731>

⁵²⁷¹ <https://github.com/TheHPXProject/hpx/issues/1730>

⁵²⁷² <https://github.com/TheHPXProject/hpx/pull/1729>

- PR #1728⁵²⁷³ - Fixing #1722
- PR #1727⁵²⁷⁴ - Fixing compile problems with `apply_collocated`
- PR #1726⁵²⁷⁵ - Apex integration
- PR #1725⁵²⁷⁶ - fixed test timeouts
- PR #1724⁵²⁷⁷ - Renaming vector
- Issue #1723⁵²⁷⁸ - Drop support for intel compilers and gcc 4.4. based standard libs
- Issue #1722⁵²⁷⁹ - Add support for detecting non-ready futures before serialization
- PR #1721⁵²⁸⁰ - Unifying parallel executors, initializing from launch policy
- PR #1720⁵²⁸¹ - dropped superfluous typedef
- Issue #1718⁵²⁸² - Windows 10 x64, VS 2015 - Unknown CMake command “`add_hpx_pseudo_target`”.
- PR #1717⁵²⁸³ - Timed executor traits for thread-executors
- PR #1716⁵²⁸⁴ - serialization of arrays didn’t work with non-pod types. fixed
- PR #1715⁵²⁸⁵ - List serialization
- PR #1714⁵²⁸⁶ - changing misspellings
- PR #1713⁵²⁸⁷ - Fixed distribution policy executors
- PR #1712⁵²⁸⁸ - Moving library detection to be executed after feature tests
- PR #1711⁵²⁸⁹ - Simplify parcel
- PR #1710⁵²⁹⁰ - Compile only tests
- PR #1709⁵²⁹¹ - Implemented timed executors
- PR #1708⁵²⁹² - Implement `parallel::executor_traits` for thread-executors
- PR #1707⁵²⁹³ - Various fixes to `threads::executors` to make custom schedulers work
- PR #1706⁵²⁹⁴ - Command line option `-hpx:cores` does not work as expected
- Issue #1705⁵²⁹⁵ - command line option `-hpx:cores` does not work as expected

⁵²⁷³ <https://github.com/TheHPXProject/hpx/pull/1728>
⁵²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1727>
⁵²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1726>
⁵²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/1725>
⁵²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1724>
⁵²⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1723>
⁵²⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1722>
⁵²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1721>
⁵²⁸¹ <https://github.com/TheHPXProject/hpx/pull/1720>
⁵²⁸² <https://github.com/TheHPXProject/hpx/issues/1718>
⁵²⁸³ <https://github.com/TheHPXProject/hpx/pull/1717>
⁵²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1716>
⁵²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1715>
⁵²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1714>
⁵²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1713>
⁵²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1712>
⁵²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1711>
⁵²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1710>
⁵²⁹¹ <https://github.com/TheHPXProject/hpx/pull/1709>
⁵²⁹² <https://github.com/TheHPXProject/hpx/pull/1708>
⁵²⁹³ <https://github.com/TheHPXProject/hpx/pull/1707>
⁵²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1706>
⁵²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1705>

- PR #1704⁵²⁹⁶ - vector deserialization is speeded up a little
- PR #1703⁵²⁹⁷ - Fixing shared_mutes
- Issue #1702⁵²⁹⁸ - Shared_mutex does not compile with no_mutex cond_var
- PR #1701⁵²⁹⁹ - Add distribution_policy_executor
- PR #1700⁵³⁰⁰ - Executor parameters
- PR #1699⁵³⁰¹ - Readers writer lock
- PR #1698⁵³⁰² - Remove leftovers
- PR #1697⁵³⁰³ - Fixing held locks
- PR #1696⁵³⁰⁴ - Modified Scan Partitioner for Algorithms
- PR #1695⁵³⁰⁵ - This thread executors
- PR #1694⁵³⁰⁶ - Fixed #1688: Add timer counters for tfunc_total and exec_total
- PR #1693⁵³⁰⁷ - Fix #1691: is_executor template specification fails for inherited executors
- PR #1692⁵³⁰⁸ - Fixed #1662: Possible exception source in coalescing_message_handler
- Issue #1691⁵³⁰⁹ - is_executor template specification fails for inherited executors
- PR #1690⁵³¹⁰ - added macro for non-intrusive serialization of classes without a default c-tor
- PR #1689⁵³¹¹ - Replace value_or_error with custom storage, unify future_data state
- Issue #1688⁵³¹² - Add timer counters for tfunc_total and exec_total
- PR #1687⁵³¹³ - Fixed interval timer
- PR #1686⁵³¹⁴ - Fixing cmake warnings about not existing pseudo target dependencies
- PR #1685⁵³¹⁵ - Converting partitioners to use bulk async execute
- PR #1683⁵³¹⁶ - Adds a tool for inspect that checks for character limits
- PR #1682⁵³¹⁷ - Change project name to (uppercase) HPX
- PR #1681⁵³¹⁸ - Counter shortnames

⁵²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1704>

⁵²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1703>

⁵²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1702>

⁵²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1701>

⁵³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1700>

⁵³⁰¹ <https://github.com/TheHPXProject/hpx/pull/1699>

⁵³⁰² <https://github.com/TheHPXProject/hpx/pull/1698>

⁵³⁰³ <https://github.com/TheHPXProject/hpx/pull/1697>

⁵³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1696>

⁵³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1695>

⁵³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1694>

⁵³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1693>

⁵³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1692>

⁵³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1691>

⁵³¹⁰ <https://github.com/TheHPXProject/hpx/pull/1690>

⁵³¹¹ <https://github.com/TheHPXProject/hpx/pull/1689>

⁵³¹² <https://github.com/TheHPXProject/hpx/issues/1688>

⁵³¹³ <https://github.com/TheHPXProject/hpx/pull/1687>

⁵³¹⁴ <https://github.com/TheHPXProject/hpx/pull/1686>

⁵³¹⁵ <https://github.com/TheHPXProject/hpx/pull/1685>

⁵³¹⁶ <https://github.com/TheHPXProject/hpx/pull/1683>

⁵³¹⁷ <https://github.com/TheHPXProject/hpx/pull/1682>

⁵³¹⁸ <https://github.com/TheHPXProject/hpx/pull/1681>

- PR #1680⁵³¹⁹ - Extended Non-intrusive Serialization to Ease Usage for Library Developers
- PR #1679⁵³²⁰ - Working on 1544: More executor changes
- PR #1678⁵³²¹ - Transpose fixes
- PR #1677⁵³²² - Improve Boost compatibility check
- PR #1676⁵³²³ - 1d stencil fix
- Issue #1675⁵³²⁴ - hpx project name is not HPX
- PR #1674⁵³²⁵ - Fixing the MPI parcellport
- PR #1673⁵³²⁶ - added move semantics to map/vector deserialization
- PR #1672⁵³²⁷ - Vs2015 await
- PR #1671⁵³²⁸ - Adapt transform for #1668
- PR #1670⁵³²⁹ - Started to work on #1668
- PR #1669⁵³³⁰ - Add this_thread_executors
- Issue #1667⁵³³¹ - Apple build instructions in docs are out of date
- PR #1666⁵³³² - Apex integration
- PR #1665⁵³³³ - Fixes an error with the whitespace check that showed the incorrect location of the error
- Issue #1664⁵³³⁴ - Inspect tool found incorrect endline whitespace
- PR #1663⁵³³⁵ - Improve use of locks
- Issue #1662⁵³³⁶ - Possible exception source in coalescing_message_handler
- PR #1661⁵³³⁷ - Added support for 128bit number serialization
- PR #1660⁵³³⁸ - Serialization 128bits
- PR #1659⁵³³⁹ - Implemented inner_product and adjacent_diff algos
- PR #1658⁵³⁴⁰ - Add serialization for std::set (as there is for std::vector and std::map)
- PR #1657⁵³⁴¹ - Use of shared_ptr in io_service_pool changed to unique_ptr

⁵³¹⁹ <https://github.com/TheHPXProject/hpx/pull/1680>
⁵³²⁰ <https://github.com/TheHPXProject/hpx/pull/1679>
⁵³²¹ <https://github.com/TheHPXProject/hpx/pull/1678>
⁵³²² <https://github.com/TheHPXProject/hpx/pull/1677>
⁵³²³ <https://github.com/TheHPXProject/hpx/pull/1676>
⁵³²⁴ <https://github.com/TheHPXProject/hpx/issues/1675>
⁵³²⁵ <https://github.com/TheHPXProject/hpx/pull/1674>
⁵³²⁶ <https://github.com/TheHPXProject/hpx/pull/1673>
⁵³²⁷ <https://github.com/TheHPXProject/hpx/pull/1672>
⁵³²⁸ <https://github.com/TheHPXProject/hpx/pull/1671>
⁵³²⁹ <https://github.com/TheHPXProject/hpx/pull/1670>
⁵³³⁰ <https://github.com/TheHPXProject/hpx/pull/1669>
⁵³³¹ <https://github.com/TheHPXProject/hpx/issues/1667>
⁵³³² <https://github.com/TheHPXProject/hpx/pull/1666>
⁵³³³ <https://github.com/TheHPXProject/hpx/pull/1665>
⁵³³⁴ <https://github.com/TheHPXProject/hpx/issues/1664>
⁵³³⁵ <https://github.com/TheHPXProject/hpx/pull/1663>
⁵³³⁶ <https://github.com/TheHPXProject/hpx/issues/1662>
⁵³³⁷ <https://github.com/TheHPXProject/hpx/pull/1661>
⁵³³⁸ <https://github.com/TheHPXProject/hpx/pull/1660>
⁵³³⁹ <https://github.com/TheHPXProject/hpx/pull/1659>
⁵³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1658>
⁵³⁴¹ <https://github.com/TheHPXProject/hpx/pull/1657>

- Issue #1656⁵³⁴² - 1d_stencil codes all have wrong factor
- PR #1654⁵³⁴³ - When using runtime_mode_connect, find the correct localhost public ip address
- PR #1653⁵³⁴⁴ - Fixing 1617
- PR #1652⁵³⁴⁵ - Remove traits::action_may_require_id_splitting
- PR #1651⁵³⁴⁶ - Fixed performance counters related to AGAS cache timings
- PR #1650⁵³⁴⁷ - Remove leftovers of traits::type_size
- PR #1649⁵³⁴⁸ - Shorten target names on Windows to shorten used path names
- PR #1648⁵³⁴⁹ - Fixing problems introduced by merging #1623 for older compilers
- PR #1647⁵³⁵⁰ - Simplify running automatic builds on Windows
- Issue #1646⁵³⁵¹ - Cache insert and update performance counters are broken
- Issue #1644⁵³⁵² - Remove leftovers of traits::type_size
- Issue #1643⁵³⁵³ - Remove traits::action_may_require_id_splitting
- PR #1642⁵³⁵⁴ - Adds spell checker to the inspect tool for qbk and doxygen comments
- PR #1640⁵³⁵⁵ - First step towards fixing 688
- PR #1639⁵³⁵⁶ - Re-apply remaining changes from limit_dataflow_recursion branch
- PR #1638⁵³⁵⁷ - This fixes possible deadlock in the test ignore_while_locked_1485
- PR #1637⁵³⁵⁸ - Fixing hpx::wait_all() invoked with two vector<future<T>>
- PR #1636⁵³⁵⁹ - Partially re-apply changes from limit_dataflow_recursion branch
- PR #1635⁵³⁶⁰ - Adding missing test for #1572
- PR #1634⁵³⁶¹ - Revert “Limit recursion-depth in dataflow to a configurable constant”
- PR #1633⁵³⁶² - Add command line option to ignore batch environment
- PR #1631⁵³⁶³ - hpx::lcos::queue exhibits strange behavior
- PR #1630⁵³⁶⁴ - Fixed endline_whitespace_check.cpp to detect lines with only whitespace

⁵³⁴² <https://github.com/TheHPXProject/hpx/issues/1656>

⁵³⁴³ <https://github.com/TheHPXProject/hpx/pull/1654>

⁵³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1653>

⁵³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1652>

⁵³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1651>

⁵³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1650>

⁵³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1649>

⁵³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1648>

⁵³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1647>

⁵³⁵¹ <https://github.com/TheHPXProject/hpx/issues/1646>

⁵³⁵² <https://github.com/TheHPXProject/hpx/issues/1644>

⁵³⁵³ <https://github.com/TheHPXProject/hpx/issues/1643>

⁵³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1642>

⁵³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1640>

⁵³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1639>

⁵³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1638>

⁵³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1637>

⁵³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1636>

⁵³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1635>

⁵³⁶¹ <https://github.com/TheHPXProject/hpx/pull/1634>

⁵³⁶² <https://github.com/TheHPXProject/hpx/pull/1633>

⁵³⁶³ <https://github.com/TheHPXProject/hpx/pull/1631>

⁵³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1630>

- [Issue #1629](#)⁵³⁶⁵ - Inspect trailing whitespace checker problem
- [PR #1628](#)⁵³⁶⁶ - Removed meaningless const qualifiers. Minor icpc fix.
- [PR #1627](#)⁵³⁶⁷ - Fixing the queue LCO and add example demonstrating its use
- [PR #1626](#)⁵³⁶⁸ - Deprecating `get_gid()`, add `get_id()` and `get_unmanaged_id()`
- [PR #1625](#)⁵³⁶⁹ - Allowing to specify whether to send credits along with message
- [Issue #1624](#)⁵³⁷⁰ - Lifetime issue
- [Issue #1623](#)⁵³⁷¹ - `hpx::wait_all()` invoked with two `vector<future<T>>` fails
- [PR #1622](#)⁵³⁷² - Executor partitioners
- [PR #1621](#)⁵³⁷³ - Clean up coroutines implementation
- [Issue #1620](#)⁵³⁷⁴ - Revert #1535
- [PR #1619](#)⁵³⁷⁵ - Fix result type calculation for `hpx::make_continuation`
- [PR #1618](#)⁵³⁷⁶ - Fixing RDTSC on Xeon/Phi
- [Issue #1617](#)⁵³⁷⁷ - `hpx cmake` not working when run as a subproject
- [Issue #1616](#)⁵³⁷⁸ - `cmake` problem resulting in RDTSC not working correctly for Xeon Phi creates very strange results for duration counters
- [Issue #1615](#)⁵³⁷⁹ - `hpx::make_continuation` requires input and output to be the same
- [PR #1614](#)⁵³⁸⁰ - Fixed remove copy test
- [Issue #1613](#)⁵³⁸¹ - Dataflow causes stack overflow
- [PR #1612](#)⁵³⁸² - Modified foreach partitioner to use bulk execute
- [PR #1611](#)⁵³⁸³ - Limit recursion-depth in dataflow to a configurable constant
- [PR #1610](#)⁵³⁸⁴ - Increase timeout for CircleCI
- [PR #1609](#)⁵³⁸⁵ - Refactoring thread manager, mainly extracting thread pool
- [PR #1608](#)⁵³⁸⁶ - Fixed running multiple localities without localities parameter
- [PR #1607](#)⁵³⁸⁷ - More algorithm fixes to `adjacentfind`

⁵³⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1629>

⁵³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1628>

⁵³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1627>

⁵³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1626>

⁵³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1625>

⁵³⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1624>

⁵³⁷¹ <https://github.com/TheHPXProject/hpx/issues/1623>

⁵³⁷² <https://github.com/TheHPXProject/hpx/pull/1622>

⁵³⁷³ <https://github.com/TheHPXProject/hpx/pull/1621>

⁵³⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1620>

⁵³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1619>

⁵³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/1618>

⁵³⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1617>

⁵³⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1616>

⁵³⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1615>

⁵³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1614>

⁵³⁸¹ <https://github.com/TheHPXProject/hpx/issues/1613>

⁵³⁸² <https://github.com/TheHPXProject/hpx/pull/1612>

⁵³⁸³ <https://github.com/TheHPXProject/hpx/pull/1611>

⁵³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1610>

⁵³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1609>

⁵³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1608>

⁵³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1607>

- [Issue #1606](#)⁵³⁸⁸ - Running without localities parameter binds to bogus port range
- [Issue #1605](#)⁵³⁸⁹ - Too many serializations
- [PR #1604](#)⁵³⁹⁰ - Changes the HPX image into a hyperlink
- [PR #1601](#)⁵³⁹¹ - Fixing problems with remove_copy algorithm tests
- [PR #1600](#)⁵³⁹² - Actions with ids cleanup
- [PR #1599](#)⁵³⁹³ - Duplicate binding of global ids should fail
- [PR #1598](#)⁵³⁹⁴ - Fixing array access
- [PR #1597](#)⁵³⁹⁵ - Improved the reliability of connecting/disconnecting localities
- [Issue #1596](#)⁵³⁹⁶ - Duplicate id binding should fail
- [PR #1595](#)⁵³⁹⁷ - Fixing more cmake config constants
- [PR #1594](#)⁵³⁹⁸ - Fixing preprocessor constant used to enable C++11 chrono
- [PR #1593](#)⁵³⁹⁹ - Adding operator|() for hpx::launch
- [Issue #1592](#)⁵⁴⁰⁰ - Error (typo) in the docs
- [Issue #1590](#)⁵⁴⁰¹ - CMake fails when CMAKE_BINARY_DIR contains '+'
- [Issue #1589](#)⁵⁴⁰² - Disconnecting a locality results in segfault using heartbeat example
- [PR #1588](#)⁵⁴⁰³ - Fix doc string for config option HPX_WITH_EXAMPLES
- [PR #1586](#)⁵⁴⁰⁴ - Fixing 1493
- [PR #1585](#)⁵⁴⁰⁵ - Additional Check for Inspect Tool to detect Endline Whitespace
- [Issue #1584](#)⁵⁴⁰⁶ - Clean up coroutines implementation
- [PR #1583](#)⁵⁴⁰⁷ - Adding a check for end line whitespace
- [PR #1582](#)⁵⁴⁰⁸ - Attempt to fix assert firing after scheduling loop was exited
- [PR #1581](#)⁵⁴⁰⁹ - Fixed adjacentfind_binary test
- [PR #1580](#)⁵⁴¹⁰ - Prevent some of the internal cmake lists from growing indefinitely

⁵³⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1606>

⁵³⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1605>

⁵³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1604>

⁵³⁹¹ <https://github.com/TheHPXProject/hpx/pull/1601>

⁵³⁹² <https://github.com/TheHPXProject/hpx/pull/1600>

⁵³⁹³ <https://github.com/TheHPXProject/hpx/pull/1599>

⁵³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1598>

⁵³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1597>

⁵³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1596>

⁵³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1595>

⁵³⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1594>

⁵³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1593>

⁵⁴⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1592>

⁵⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/1590>

⁵⁴⁰² <https://github.com/TheHPXProject/hpx/issues/1589>

⁵⁴⁰³ <https://github.com/TheHPXProject/hpx/pull/1588>

⁵⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1586>

⁵⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1585>

⁵⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1584>

⁵⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1583>

⁵⁴⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1582>

⁵⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1581>

⁵⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/1580>

- [PR #1579](#)⁵⁴¹¹ - Removing type_size trait, replacing it with special archive type
- [Issue #1578](#)⁵⁴¹² - Remove demangle_helper
- [PR #1577](#)⁵⁴¹³ - Get ptr problems
- [Issue #1576](#)⁵⁴¹⁴ - Refactor async, dataflow, and future::then
- [PR #1575](#)⁵⁴¹⁵ - Fixing tests for parallel rotate
- [PR #1574](#)⁵⁴¹⁶ - Cleaning up schedulers
- [PR #1573](#)⁵⁴¹⁷ - Fixing thread pool executor
- [PR #1572](#)⁵⁴¹⁸ - Fixing number of configured localities
- [PR #1571](#)⁵⁴¹⁹ - Reimplement decay
- [PR #1570](#)⁵⁴²⁰ - Refactoring async, apply, and dataflow APIs
- [PR #1569](#)⁵⁴²¹ - Changed range for mach-o library lookup
- [PR #1568](#)⁵⁴²² - Mark decltype support as required
- [PR #1567](#)⁵⁴²³ - Removed const from algorithms
- [Issue #1566](#)⁵⁴²⁴ - CMAKE Configuration Test Failures for clang 3.5 on debian
- [PR #1565](#)⁵⁴²⁵ - Dylib support
- [PR #1564](#)⁵⁴²⁶ - Converted partitioners and some algorithms to use executors
- [PR #1563](#)⁵⁴²⁷ - Fix several #includes for Boost.Preprocessor
- [PR #1562](#)⁵⁴²⁸ - Adding configuration option disabling/enabling all message handlers
- [PR #1561](#)⁵⁴²⁹ - Removed all occurrences of boost::move replacing it with std::move
- [Issue #1560](#)⁵⁴³⁰ - Leftover HPX_REGISTER_ACTION_DECLARATION_2
- [PR #1558](#)⁵⁴³¹ - Revisit async/apply SFINAE conditions
- [PR #1557](#)⁵⁴³² - Removing type_size trait, replacing it with special archive type
- [PR #1556](#)⁵⁴³³ - Executor algorithms

⁵⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/1579>

⁵⁴¹² <https://github.com/TheHPXProject/hpx/issues/1578>

⁵⁴¹³ <https://github.com/TheHPXProject/hpx/pull/1577>

⁵⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/1576>

⁵⁴¹⁵ <https://github.com/TheHPXProject/hpx/pull/1575>

⁵⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/1574>

⁵⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/1573>

⁵⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/1572>

⁵⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/1571>

⁵⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/1570>

⁵⁴²¹ <https://github.com/TheHPXProject/hpx/pull/1569>

⁵⁴²² <https://github.com/TheHPXProject/hpx/pull/1568>

⁵⁴²³ <https://github.com/TheHPXProject/hpx/pull/1567>

⁵⁴²⁴ <https://github.com/TheHPXProject/hpx/issues/1566>

⁵⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/1565>

⁵⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/1564>

⁵⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/1563>

⁵⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/1562>

⁵⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/1561>

⁵⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/1560>

⁵⁴³¹ <https://github.com/TheHPXProject/hpx/pull/1558>

⁵⁴³² <https://github.com/TheHPXProject/hpx/pull/1557>

⁵⁴³³ <https://github.com/TheHPXProject/hpx/pull/1556>

- PR #1555⁵⁴³⁴ - Remove the necessity to specify archive flags on the receiving end
- PR #1554⁵⁴³⁵ - Removing obsolete Boost.Serialization macros
- PR #1553⁵⁴³⁶ - Properly fix HPX_DEFINE_*_ACTION macros
- PR #1552⁵⁴³⁷ - Fixed algorithms relying on copy_if implementation
- PR #1551⁵⁴³⁸ - Pxfs - Modifying FindOrangeFS.cmake based on OrangeFS 2.9.X
- Issue #1550⁵⁴³⁹ - Passing plain identifier inside HPX_DEFINE_PLAIN_ACTION_1
- PR #1549⁵⁴⁴⁰ - Fixing intel14/libstdc++4.4
- PR #1548⁵⁴⁴¹ - Moving raw_ptr to detail namespace
- PR #1547⁵⁴⁴² - Adding support for executors to future.then
- PR #1546⁵⁴⁴³ - Executor traits result types
- PR #1545⁵⁴⁴⁴ - Integrate executors with dataflow
- PR #1543⁵⁴⁴⁵ - Fix potential zero-copy for primarynamespace::bulk_service_async et.al.
- PR #1542⁵⁴⁴⁶ - Merging HPX0.9.10 into pxfs branch
- PR #1541⁵⁴⁴⁷ - Removed stale cmake tests, unused since the great cmake refactoring
- PR #1540⁵⁴⁴⁸ - Fix idle-rate on platforms without TSC
- PR #1539⁵⁴⁴⁹ - Reporting situation if zero-copy-serialization was performed by a parcel generated from a plain apply/async
- PR #1538⁵⁴⁵⁰ - Changed return type of bulk executors and added test
- Issue #1537⁵⁴⁵¹ - Incorrect cpuid config tests
- PR #1536⁵⁴⁵² - Changed return type of bulk executors and added test
- PR #1535⁵⁴⁵³ - Make sure promise::get_gid() can be called more than once
- PR #1534⁵⁴⁵⁴ - Fixed async_callback with bound callback
- PR #1533⁵⁴⁵⁵ - Updated the link in the documentation to a publically- accessible URL
- PR #1532⁵⁴⁵⁶ - Make sure sync primitives are not copyable nor movable

⁵⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/1555>
⁵⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/1554>
⁵⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/1553>
⁵⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/1552>
⁵⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/1551>
⁵⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/1550>
⁵⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1549>
⁵⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/1548>
⁵⁴⁴² <https://github.com/TheHPXProject/hpx/pull/1547>
⁵⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/1546>
⁵⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1545>
⁵⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1543>
⁵⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1542>
⁵⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1541>
⁵⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1540>
⁵⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1539>
⁵⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1538>
⁵⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/1537>
⁵⁴⁵² <https://github.com/TheHPXProject/hpx/pull/1536>
⁵⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/1535>
⁵⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1534>
⁵⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1533>
⁵⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1532>

- PR #1531⁵⁴⁵⁷ - Fix unwrapped issue with future ranges of void type
- PR #1530⁵⁴⁵⁸ - Serialization complex
- Issue #1528⁵⁴⁵⁹ - Unwrapped issue with future<void>
- Issue #1527⁵⁴⁶⁰ - HPX does not build with Boost 1.58.0
- PR #1526⁵⁴⁶¹ - Added support for boost.multi_array serialization
- PR #1525⁵⁴⁶² - Properly handle deferred futures, fixes #1506
- PR #1524⁵⁴⁶³ - Making sure invalid action argument types generate clear error message
- Issue #1522⁵⁴⁶⁴ - Need serialization support for boost multi array
- Issue #1521⁵⁴⁶⁵ - Remote async and zero-copy serialization optimizations don't play well together
- PR #1520⁵⁴⁶⁶ - Fixing UB while registering polymorphic classes for serialization
- PR #1519⁵⁴⁶⁷ - Making detail::condition_variable safe to use
- PR #1518⁵⁴⁶⁸ - Fix when_some bug missing indices in its result
- Issue #1517⁵⁴⁶⁹ - Typo may affect CMake build system tests
- PR #1516⁵⁴⁷⁰ - Fixing Posix context
- PR #1515⁵⁴⁷¹ - Fixing Posix context
- PR #1514⁵⁴⁷² - Correct problems with loading dynamic components
- PR #1513⁵⁴⁷³ - Fixing intel glibc4 4
- Issue #1508⁵⁴⁷⁴ - memory and papi counters do not work
- Issue #1507⁵⁴⁷⁵ - Unrecognized Command Line Option Error causing exit status 0
- Issue #1506⁵⁴⁷⁶ - Properly handle deferred futures
- PR #1505⁵⁴⁷⁷ - Adding #include - would not compile without this
- Issue #1502⁵⁴⁷⁸ - boost::filesystem::exists throws unexpected exception
- Issue #1501⁵⁴⁷⁹ - hwloc configuration options are wrong for MIC

⁵⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1531>

⁵⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1530>

⁵⁴⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1528>

⁵⁴⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1527>

⁵⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/1526>

⁵⁴⁶² <https://github.com/TheHPXProject/hpx/pull/1525>

⁵⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/1524>

⁵⁴⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1522>

⁵⁴⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1521>

⁵⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1520>

⁵⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1519>

⁵⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1518>

⁵⁴⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1517>

⁵⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1516>

⁵⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/1515>

⁵⁴⁷² <https://github.com/TheHPXProject/hpx/pull/1514>

⁵⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/1513>

⁵⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1508>

⁵⁴⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1507>

⁵⁴⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1506>

⁵⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1505>

⁵⁴⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1502>

⁵⁴⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1501>

- PR #1504⁵⁴⁸⁰ - Making sure `boost::filesystem::exists()` does not throw
- PR #1500⁵⁴⁸¹ - Exit application on `--hpx:version/-v` and `--hpx:info`
- PR #1498⁵⁴⁸² - Extended task block
- PR #1497⁵⁴⁸³ - Unique ptr serialization
- PR #1496⁵⁴⁸⁴ - Unique ptr serialization (closed)
- PR #1495⁵⁴⁸⁵ - Switching `circuleci` build type to debug
- Issue #1494⁵⁴⁸⁶ - `--hpx:version/-v` does not exit after printing version information
- Issue #1493⁵⁴⁸⁷ - add an `hpx_` prefix to libraries and components to avoid name conflicts
- Issue #1492⁵⁴⁸⁸ - Define and ensure limitations for arguments to `async/apply`
- PR #1489⁵⁴⁸⁹ - Enable idle rate counter on demand
- PR #1488⁵⁴⁹⁰ - Made sure `detail::condition_variable` can be safely destroyed
- PR #1487⁵⁴⁹¹ - Introduced default (main) template implementation for `ignore_while_checking`
- PR #1486⁵⁴⁹² - Add HPX inspect tool
- Issue #1485⁵⁴⁹³ - `ignore_while_locked` doesn't support all Lockable types
- PR #1484⁵⁴⁹⁴ - Docker image generation
- PR #1483⁵⁴⁹⁵ - Move external endian library into HPX
- PR #1482⁵⁴⁹⁶ - Actions with integer type ids
- Issue #1481⁵⁴⁹⁷ - Sync primitives safe destruction
- Issue #1480⁵⁴⁹⁸ - Move external/boost/endian into `hpx/util`
- Issue #1478⁵⁴⁹⁹ - Boost inspect violations
- PR #1479⁵⁵⁰⁰ - Adds serialization for arrays; some further/minor fixes
- PR #1477⁵⁵⁰¹ - Fixing problems with the Intel compiler using a GCC 4.4 std library
- PR #1476⁵⁵⁰² - Adding `hpx::lcos::latch` and `hpx::lcos::local::latch`

⁵⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1504>

⁵⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/1500>

⁵⁴⁸² <https://github.com/TheHPXProject/hpx/pull/1498>

⁵⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/1497>

⁵⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1496>

⁵⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1495>

⁵⁴⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1494>

⁵⁴⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1493>

⁵⁴⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1492>

⁵⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1489>

⁵⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1488>

⁵⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/1487>

⁵⁴⁹² <https://github.com/TheHPXProject/hpx/pull/1486>

⁵⁴⁹³ <https://github.com/TheHPXProject/hpx/issues/1485>

⁵⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1484>

⁵⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1483>

⁵⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1482>

⁵⁴⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1481>

⁵⁴⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1480>

⁵⁴⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1478>

⁵⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1479>

⁵⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/1477>

⁵⁵⁰² <https://github.com/TheHPXProject/hpx/pull/1476>

- [Issue #1475](#)⁵⁵⁰³ - Boost inspect violations
- [PR #1473](#)⁵⁵⁰⁴ - Fixing action move tests
- [Issue #1471](#)⁵⁵⁰⁵ - Sync primitives should not be movable
- [PR #1470](#)⁵⁵⁰⁶ - Removing `hpx::util::polymorphic_factory`
- [PR #1468](#)⁵⁵⁰⁷ - Fixed container creation
- [Issue #1467](#)⁵⁵⁰⁸ - HPX application fail during finalization
- [Issue #1466](#)⁵⁵⁰⁹ - HPX doesn't pick up Torque's nodefile on SuperMIC
- [Issue #1464](#)⁵⁵¹⁰ - HPX option for pre and post bootstrap performance counters
- [PR #1463](#)⁵⁵¹¹ - Replacing `async_colocated(id, ...)` with `async(colocated(id), ...)`
- [PR #1462](#)⁵⁵¹² - Consolidated `task_region` with N4411
- [PR #1461](#)⁵⁵¹³ - Consolidate inconsistent CMake option names
- [Issue #1460](#)⁵⁵¹⁴ - Which `malloc` is actually used? or at least which one is HPX built with
- [Issue #1459](#)⁵⁵¹⁵ - Make `cmake` configure step fail explicitly if compiler version is not supported
- [Issue #1458](#)⁵⁵¹⁶ - Update `parallel::task_region` with N4411
- [PR #1456](#)⁵⁵¹⁷ - Consolidating `new_<>()`
- [Issue #1455](#)⁵⁵¹⁸ - Replace `async_colocated(id, ...)` with `async(colocated(id), ...)`
- [PR #1454](#)⁵⁵¹⁹ - Removed harmful `std::moves` from return statements
- [PR #1453](#)⁵⁵²⁰ - Use range-based for-loop instead of `Boost.Foreach`
- [PR #1452](#)⁵⁵²¹ - C++ feature tests
- [PR #1451](#)⁵⁵²² - When serializing, pass archive flags to `traits::get_type_size`
- [Issue #1450](#)⁵⁵²³ - `traits::get_type_size` needs archive flags to enable `zero_copy` optimizations
- [Issue #1449](#)⁵⁵²⁴ - "couldn't create performance counter" - AGAS
- [Issue #1448](#)⁵⁵²⁵ - Replace distributing factories with `new_<T[]>(...)`

⁵⁵⁰³ <https://github.com/TheHPXProject/hpx/issues/1475>

⁵⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1473>

⁵⁵⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1471>

⁵⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1470>

⁵⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1468>

⁵⁵⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1467>

⁵⁵⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1466>

⁵⁵¹⁰ <https://github.com/TheHPXProject/hpx/issues/1464>

⁵⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/1463>

⁵⁵¹² <https://github.com/TheHPXProject/hpx/pull/1462>

⁵⁵¹³ <https://github.com/TheHPXProject/hpx/pull/1461>

⁵⁵¹⁴ <https://github.com/TheHPXProject/hpx/issues/1460>

⁵⁵¹⁵ <https://github.com/TheHPXProject/hpx/issues/1459>

⁵⁵¹⁶ <https://github.com/TheHPXProject/hpx/issues/1458>

⁵⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/1456>

⁵⁵¹⁸ <https://github.com/TheHPXProject/hpx/issues/1455>

⁵⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/1454>

⁵⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/1453>

⁵⁵²¹ <https://github.com/TheHPXProject/hpx/pull/1452>

⁵⁵²² <https://github.com/TheHPXProject/hpx/pull/1451>

⁵⁵²³ <https://github.com/TheHPXProject/hpx/issues/1450>

⁵⁵²⁴ <https://github.com/TheHPXProject/hpx/issues/1449>

⁵⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/1448>

- PR #1447⁵⁵²⁶ - Removing obsolete remote_object component
- PR #1446⁵⁵²⁷ - Hpx serialization
- PR #1445⁵⁵²⁸ - Replacing travis with circleci
- PR #1443⁵⁵²⁹ - Always stripping HPX command line arguments before executing start function
- PR #1442⁵⁵³⁰ - Adding `-hpx:bind=none` to disable thread affinities
- Issue #1439⁵⁵³¹ - Libraries get linked in multiple times, RPATH is not properly set
- PR #1438⁵⁵³² - Removed superfluous typedefs
- Issue #1437⁵⁵³³ - `hpx::init()` should strip HPX-related flags from argv
- Issue #1436⁵⁵³⁴ - Add strong scaling option to https
- PR #1435⁵⁵³⁵ - Adding `async_cb`, `async_continue_cb`, and `async_colocated_cb`
- PR #1434⁵⁵³⁶ - Added missing install rule, removed some dead CMake code
- PR #1433⁵⁵³⁷ - Add GitExternal and SubProject cmake scripts from eyescale/cmake repo
- Issue #1432⁵⁵³⁸ - Add command line flag to disable thread pinning
- PR #1431⁵⁵³⁹ - Fix #1423
- Issue #1430⁵⁵⁴⁰ - Inconsistent CMake option names
- Issue #1429⁵⁵⁴¹ - Configure setting `HPX_HAVE_PARCELPOR_MPI` is ignored
- PR #1428⁵⁵⁴² - Fixes #1419 (closed)
- PR #1427⁵⁵⁴³ - Adding `stencil_iterator` and `transform_iterator`
- PR #1426⁵⁵⁴⁴ - Fixes #1419
- PR #1425⁵⁵⁴⁵ - During serialization memory allocation should honour allocator chunk size
- Issue #1424⁵⁵⁴⁶ - chunk allocation during serialization does not use memory pool/allocator chunk size
- Issue #1423⁵⁵⁴⁷ - Remove `HPX_STD_UNIQUE_PTR`
- Issue #1422⁵⁵⁴⁸ - `hpx:threads=all` allocates too many os threads

⁵⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/1447>

⁵⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/1446>

⁵⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/1445>

⁵⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/1443>

⁵⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/1442>

⁵⁵³¹ <https://github.com/TheHPXProject/hpx/issues/1439>

⁵⁵³² <https://github.com/TheHPXProject/hpx/pull/1438>

⁵⁵³³ <https://github.com/TheHPXProject/hpx/issues/1437>

⁵⁵³⁴ <https://github.com/TheHPXProject/hpx/issues/1436>

⁵⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/1435>

⁵⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/1434>

⁵⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/1433>

⁵⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/1432>

⁵⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/1431>

⁵⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1430>

⁵⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/1429>

⁵⁵⁴² <https://github.com/TheHPXProject/hpx/pull/1428>

⁵⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/1427>

⁵⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1426>

⁵⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1425>

⁵⁵⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1424>

⁵⁵⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1423>

⁵⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1422>

- PR #1420⁵⁵⁴⁹ - added .travis.yml
- Issue #1419⁵⁵⁵⁰ - Unify enums: `hpx::runtime::state` and `hpx::state`
- PR #1416⁵⁵⁵¹ - Adding travis builder
- Issue #1414⁵⁵⁵² - Correct directory for `dispatch_gcc46.hpp` iteration
- Issue #1410⁵⁵⁵³ - Set operation algorithms
- Issue #1389⁵⁵⁵⁴ - Parallel algorithms relying on scan partitioner break for small number of elements
- Issue #1325⁵⁵⁵⁵ - Exceptions thrown during parcel handling are not handled correctly
- Issue #1315⁵⁵⁵⁶ - Errors while running performance tests
- Issue #1309⁵⁵⁵⁷ - `hpx::vector` partitions are not easily extendable by applications
- PR #1300⁵⁵⁵⁸ - Added serialization/de-serialization to `examples.tuplespace`
- Issue #1251⁵⁵⁵⁹ - `hpx::threads::get_thread_count` doesn't consider pending threads
- Issue #1008⁵⁵⁶⁰ - Decrease in application performance overtime; occasional spikes of major slowdown
- Issue #1001⁵⁵⁶¹ - Zero copy serialization raises assert
- Issue #721⁵⁵⁶² - Make HPX usable for Xeon Phi
- Issue #524⁵⁵⁶³ - Extend scheduler to support threads which can't be stolen

HPX V0.9.10 (Mar 24, 2015)

General changes

This is the 12th official release of *HPX*. It coincides with the 7th anniversary of the first commit to our source code repository. Since then, we have seen over 12300 commits amounting to more than 220000 lines of C++ code.

The major focus of this release was to improve the reliability of large scale runs. We believe to have achieved this goal as we now can reliably run *HPX* applications on up to ~24k cores. We have also shown that HPX can be used with success for symmetric runs (applications using both, host cores and Intel Xeon/Phi coprocessors). This is a huge step forward in terms of the usability of *HPX*. The main focus of this work involved isolating the causes of the segmentation faults at start up and shut down. Many of these issues were discovered to be the result of the suspension of threads which hold locks.

A very important improvement introduced with this release is the refactoring of the code representing our parcel-port implementation. Parcel- ports can now be implemented by 3rd parties as independent plugins which are dynamically loaded at runtime (static linking of parcel-ports is also supported). This refactoring also includes a massive improvement of the performance of our existing parcel-ports. We were able to significantly reduce the networking latencies

⁵⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1420>

⁵⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1419>

⁵⁵⁵¹ <https://github.com/TheHPXProject/hpx/pull/1416>

⁵⁵⁵² <https://github.com/TheHPXProject/hpx/issues/1414>

⁵⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/1410>

⁵⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1389>

⁵⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1325>

⁵⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1315>

⁵⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1309>

⁵⁵⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1300>

⁵⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1251>

⁵⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1008>

⁵⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/1001>

⁵⁵⁶² <https://github.com/TheHPXProject/hpx/issues/721>

⁵⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/524>

and to improve the available networking bandwidth. Please note that in this release we disabled the ibverbs and ipc parcel ports as those have not been ported to the new plugin system yet (see [Issue #839](#)⁵⁵⁶⁴).

Another corner stone of this release is our work towards a complete implementation of `__cpp11_n4104__` (Working Draft, Technical Specification for C++ Extensions for Parallelism). This document defines a set of parallel algorithms to be added to the C++ standard library. We now have implemented about 75% of all specified parallel algorithms (see [\[link hpx.manual.parallel.parallel_algorithms Parallel Algorithms\]](#) for more details). We also implemented some extensions to `__cpp11_n4104__` allowing to invoke all of the algorithms asynchronously.

This release adds a first implementation of `hpx::vector` which is a distributed data structure closely aligned to the functionality of `std::vector`. The difference is that `hpx::vector` stores the data in partitions where the partitions can be distributed over different localities. We started to work on allowing to use the parallel algorithms with `hpx::vector`. At this point we have implemented only a few of the parallel algorithms to support distributed data structures (like `hpx::vector`) for testing purposes (see [Issue #1338](#)⁵⁵⁶⁵ for a documentation of our progress).

Breaking changes

With this release we put a lot of effort into changing the code base to be more compatible to C++11. These changes have caused the following issues for backward compatibility:

- Move to Variadics- All of the API now uses variadic templates. However, this change required to modify the argument sequence for some of the exiting API functions (`hpx::async_continue`, `hpx::apply_continue`, `hpx::when_each`, `hpx::wait_each`, synchronous invocation of actions).
- Changes to Macros- We also removed the macros `HPX_STD_FUNCTION` and `HPX_STD_TUPLE`. This shouldn't affect any user code as we replaced `HPX_STD_FUNCTION` with `hpx::util::function_nonser` which was the default expansion used for this macro. All `HPX` API functions which expect a `hpx::util::function_nonser` (or a `hpx::util::unique_function_nonser`) can now be transparently called with a compatible `std::function` instead. Similarly, `HPX_STD_TUPLE` was replaced by its default expansion as well: `hpx::util::tuple`.
- Changes to `hpx::unique_future`- `hpx::unique_future`, which was deprecated in the previous release for `hpx::future` is now completely removed from `HPX`. This completes the transition to a completely standards conforming implementation of `hpx::future`.
- Changes to Supported Compilers. Finally, in order to utilize more C++11 semantics, we have officially dropped support for GCC 4.4 and MSVC 2012. Please see our *Prerequisites* page for more details.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1402](#)⁵⁵⁶⁶ - Internal shared_future serialization copies
- [Issue #1399](#)⁵⁵⁶⁷ - Build takes unusually long time...
- [Issue #1398](#)⁵⁵⁶⁸ - Tests using the scan partitioner are broken on at least gcc 4.7 and intel compiler
- [Issue #1397](#)⁵⁵⁶⁹ - Completely remove `hpx::unique_future`
- [Issue #1396](#)⁵⁵⁷⁰ - Parallel scan algorithms with different initial values

⁵⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/839>

⁵⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1338>

⁵⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1402>

⁵⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1399>

⁵⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1398>

⁵⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1397>

⁵⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1396>

- [Issue #1395](#)⁵⁵⁷¹ - Race Condition - 1d_stencil_8 - SuperMIC
- [Issue #1394](#)⁵⁵⁷² - “suspending thread while at least one lock is being held” - 1d_stencil_8 - SuperMIC
- [Issue #1393](#)⁵⁵⁷³ - SEGFAULT in 1d_stencil_8 on SuperMIC
- [Issue #1392](#)⁵⁵⁷⁴ - Fixing #1168
- [Issue #1391](#)⁵⁵⁷⁵ - Parallel Algorithms for scan partitioner for small number of elements
- [Issue #1387](#)⁵⁵⁷⁶ - Failure with more than 4 localities
- [Issue #1386](#)⁵⁵⁷⁷ - Dispatching unhandled exceptions to outer user code
- [Issue #1385](#)⁵⁵⁷⁸ - Adding Copy algorithms, fixing `parallel::copy_if`
- [Issue #1384](#)⁵⁵⁷⁹ - Fixing 1325
- [Issue #1383](#)⁵⁵⁸⁰ - Fixed #504: Refactor Dataflow LCO to work with futures, this removes the dataflow component as it is obsolete
- [Issue #1382](#)⁵⁵⁸¹ - `is_sorted`, `is_sorted_until` and `is_partitioned` algorithms
- [Issue #1381](#)⁵⁵⁸² - fix for CMake versions prior to 3.1
- [Issue #1380](#)⁵⁵⁸³ - resolved warning in CMake 3.1 and newer
- [Issue #1379](#)⁵⁵⁸⁴ - Compilation error with papi
- [Issue #1378](#)⁵⁵⁸⁵ - Towards safer migration
- [Issue #1377](#)⁵⁵⁸⁶ - HPXConfig.cmake should include `TCMALLOC_LIBRARY` and `TCMALLOC_INCLUDE_DIR`
- [Issue #1376](#)⁵⁵⁸⁷ - Warning on uninitialized member
- [Issue #1375](#)⁵⁵⁸⁸ - Fixing 1163
- [Issue #1374](#)⁵⁵⁸⁹ - Fixing the MSVC 12 release builder
- [Issue #1373](#)⁵⁵⁹⁰ - Modifying parallel search algorithm for zero length searches
- [Issue #1372](#)⁵⁵⁹¹ - Modifying parallel search algorithm for zero length searches
- [Issue #1371](#)⁵⁵⁹² - Avoid holding a lock during `agas::incfref` while doing a credit split
- [Issue #1370](#)⁵⁵⁹³ - `--hpx:bind` throws unexpected error

⁵⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/1395>

⁵⁵⁷² <https://github.com/TheHPXProject/hpx/issues/1394>

⁵⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/1393>

⁵⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1392>

⁵⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1391>

⁵⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1387>

⁵⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1386>

⁵⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1385>

⁵⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1384>

⁵⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1383>

⁵⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/1382>

⁵⁵⁸² <https://github.com/TheHPXProject/hpx/issues/1381>

⁵⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/1380>

⁵⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1379>

⁵⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1378>

⁵⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1377>

⁵⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1376>

⁵⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1375>

⁵⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1374>

⁵⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1373>

⁵⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/1372>

⁵⁵⁹² <https://github.com/TheHPXProject/hpx/issues/1371>

⁵⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/1370>

- Issue #1369⁵⁵⁹⁴ - Getting rid of (void) in loops
- Issue #1368⁵⁵⁹⁵ - Variadic templates support for tuple
- Issue #1367⁵⁵⁹⁶ - One last batch of variadic templates support
- Issue #1366⁵⁵⁹⁷ - Fixing symbolic namespace hang
- Issue #1365⁵⁵⁹⁸ - More held locks
- Issue #1364⁵⁵⁹⁹ - Add counters 1363
- Issue #1363⁵⁶⁰⁰ - Add thread overhead counters
- Issue #1362⁵⁶⁰¹ - Std config removal
- Issue #1361⁵⁶⁰² - Parcelport plugins
- Issue #1360⁵⁶⁰³ - Detuplify transfer_action
- Issue #1359⁵⁶⁰⁴ - Removed obsolete checks
- Issue #1358⁵⁶⁰⁵ - Fixing 1352
- Issue #1357⁵⁶⁰⁶ - Variadic templates support for runtime_support and components
- Issue #1356⁵⁶⁰⁷ - fixed coordinate test for intel13
- Issue #1355⁵⁶⁰⁸ - fixed coordinate.hpp
- Issue #1354⁵⁶⁰⁹ - Lexicographical Compare completed
- Issue #1353⁵⁶¹⁰ - HPX should set Boost_ADDITIONAL_VERSIONS flags
- Issue #1352⁵⁶¹¹ - Error: Cannot find action “ in type registry: HPX(bad_action_code)
- Issue #1351⁵⁶¹² - Variadic templates support for appliers
- Issue #1350⁵⁶¹³ - Actions simplification
- Issue #1349⁵⁶¹⁴ - Variadic when and wait functions
- Issue #1348⁵⁶¹⁵ - Added hpx_init header to test files
- Issue #1347⁵⁶¹⁶ - Another batch of variadic templates support

⁵⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1369>

⁵⁵⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1368>

⁵⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1367>

⁵⁵⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1366>

⁵⁵⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1365>

⁵⁵⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1364>

⁵⁶⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1363>

⁵⁶⁰¹ <https://github.com/TheHPXProject/hpx/issues/1362>

⁵⁶⁰² <https://github.com/TheHPXProject/hpx/issues/1361>

⁵⁶⁰³ <https://github.com/TheHPXProject/hpx/issues/1360>

⁵⁶⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1359>

⁵⁶⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1358>

⁵⁶⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1357>

⁵⁶⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1356>

⁵⁶⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1355>

⁵⁶⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1354>

⁵⁶¹⁰ <https://github.com/TheHPXProject/hpx/issues/1353>

⁵⁶¹¹ <https://github.com/TheHPXProject/hpx/issues/1352>

⁵⁶¹² <https://github.com/TheHPXProject/hpx/issues/1351>

⁵⁶¹³ <https://github.com/TheHPXProject/hpx/issues/1350>

⁵⁶¹⁴ <https://github.com/TheHPXProject/hpx/issues/1349>

⁵⁶¹⁵ <https://github.com/TheHPXProject/hpx/issues/1348>

⁵⁶¹⁶ <https://github.com/TheHPXProject/hpx/issues/1347>

- Issue #1346⁵⁶¹⁷ - Segmented copy
- Issue #1345⁵⁶¹⁸ - Attempting to fix hangs during shutdown
- Issue #1344⁵⁶¹⁹ - Std config removal
- Issue #1343⁵⁶²⁰ - Removing various distribution policies for `hpx::vector`
- Issue #1342⁵⁶²¹ - Inclusive scan
- Issue #1341⁵⁶²² - Exclusive scan
- Issue #1340⁵⁶²³ - Adding `parallel::count` for distributed data structures, adding tests
- Issue #1339⁵⁶²⁴ - Update argument order for `transform_reduce`
- Issue #1337⁵⁶²⁵ - Fix dataflow to handle properly ranges of futures
- Issue #1336⁵⁶²⁶ - dataflow needs to hold onto futures passed to it
- Issue #1335⁵⁶²⁷ - Fails to compile with `msvc14`
- Issue #1334⁵⁶²⁸ - Examples build problem
- Issue #1333⁵⁶²⁹ - Distributed transform reduce
- Issue #1332⁵⁶³⁰ - Variadic templates support for actions
- Issue #1331⁵⁶³¹ - Some ambiguous calls of `map::erase` have been prevented by adding additional check in locality constructor.
- Issue #1330⁵⁶³² - Defining Plain Actions does not work as described in the documentation
- Issue #1329⁵⁶³³ - Distributed vector cleanup
- Issue #1328⁵⁶³⁴ - Sync docs and comments with code in `hello_world` example
- Issue #1327⁵⁶³⁵ - Typos in docs
- Issue #1326⁵⁶³⁶ - Documentation and code diverged in Fibonacci tutorial
- Issue #1325⁵⁶³⁷ - Exceptions thrown during parcel handling are not handled correctly
- Issue #1324⁵⁶³⁸ - fixed bandwidth calculation
- Issue #1323⁵⁶³⁹ - `mmap()` failed to allocate thread stack due to insufficient resources

⁵⁶¹⁷ <https://github.com/TheHPXProject/hpx/issues/1346>

⁵⁶¹⁸ <https://github.com/TheHPXProject/hpx/issues/1345>

⁵⁶¹⁹ <https://github.com/TheHPXProject/hpx/issues/1344>

⁵⁶²⁰ <https://github.com/TheHPXProject/hpx/issues/1343>

⁵⁶²¹ <https://github.com/TheHPXProject/hpx/issues/1342>

⁵⁶²² <https://github.com/TheHPXProject/hpx/issues/1341>

⁵⁶²³ <https://github.com/TheHPXProject/hpx/issues/1340>

⁵⁶²⁴ <https://github.com/TheHPXProject/hpx/issues/1339>

⁵⁶²⁵ <https://github.com/TheHPXProject/hpx/issues/1337>

⁵⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/1336>

⁵⁶²⁷ <https://github.com/TheHPXProject/hpx/issues/1335>

⁵⁶²⁸ <https://github.com/TheHPXProject/hpx/issues/1334>

⁵⁶²⁹ <https://github.com/TheHPXProject/hpx/issues/1333>

⁵⁶³⁰ <https://github.com/TheHPXProject/hpx/issues/1332>

⁵⁶³¹ <https://github.com/TheHPXProject/hpx/issues/1331>

⁵⁶³² <https://github.com/TheHPXProject/hpx/issues/1330>

⁵⁶³³ <https://github.com/TheHPXProject/hpx/issues/1329>

⁵⁶³⁴ <https://github.com/TheHPXProject/hpx/issues/1328>

⁵⁶³⁵ <https://github.com/TheHPXProject/hpx/issues/1327>

⁵⁶³⁶ <https://github.com/TheHPXProject/hpx/issues/1326>

⁵⁶³⁷ <https://github.com/TheHPXProject/hpx/issues/1325>

⁵⁶³⁸ <https://github.com/TheHPXProject/hpx/issues/1324>

⁵⁶³⁹ <https://github.com/TheHPXProject/hpx/issues/1323>

- [Issue #1322](#)⁵⁶⁴⁰ - HPX fails to build aa182cf
- [Issue #1321](#)⁵⁶⁴¹ - Limiting size of outgoing messages while coalescing parcels
- [Issue #1320](#)⁵⁶⁴² - passing a future with `launch::deferred` in remote function call causes hang
- [Issue #1319](#)⁵⁶⁴³ - An exception when tries to specify number high priority threads with `abp-priority`
- [Issue #1318](#)⁵⁶⁴⁴ - Unable to run program with `abp-priority` and `numa-sensitivity` enabled
- [Issue #1317](#)⁵⁶⁴⁵ - N4071 `Search/Search_n` finished, minor changes
- [Issue #1316](#)⁵⁶⁴⁶ - Add config option to make `-lhp.run_hpx_main!=1` the default
- [Issue #1314](#)⁵⁶⁴⁷ - Variadic support for `async` and `apply`
- [Issue #1313](#)⁵⁶⁴⁸ - Adjust `when_any/some` to the latest proposed interfaces
- [Issue #1312](#)⁵⁶⁴⁹ - Fixing #857: `hpx::naming::locality` leaks `parcelport` specific information into the public interface
- [Issue #1311](#)⁵⁶⁵⁰ - Distributed `get'er/set'er_values` for distributed vector
- [Issue #1310](#)⁵⁶⁵¹ - Crashing in `hpx::parcelset::policies::mpi::connection_handler::handle_messages()` on Super-MIC
- [Issue #1308](#)⁵⁶⁵² - Unable to execute an application with `-hpx:threads`
- [Issue #1307](#)⁵⁶⁵³ - `merge_graph` linking issue
- [Issue #1306](#)⁵⁶⁵⁴ - First batch of variadic templates support
- [Issue #1305](#)⁵⁶⁵⁵ - Create a compiler wrapper
- [Issue #1304](#)⁵⁶⁵⁶ - Provide a compiler wrapper for `hpx`
- [Issue #1303](#)⁵⁶⁵⁷ - Drop support for GCC44
- [Issue #1302](#)⁵⁶⁵⁸ - Fixing #1297
- [Issue #1301](#)⁵⁶⁵⁹ - Compilation error when tried to use `boost range` iterators with `wait_all`
- [Issue #1298](#)⁵⁶⁶⁰ - Distributed vector
- [Issue #1297](#)⁵⁶⁶¹ - Unable to invoke component actions recursively

⁵⁶⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1322>

⁵⁶⁴¹ <https://github.com/TheHPXProject/hpx/issues/1321>

⁵⁶⁴² <https://github.com/TheHPXProject/hpx/issues/1320>

⁵⁶⁴³ <https://github.com/TheHPXProject/hpx/issues/1319>

⁵⁶⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1318>

⁵⁶⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1317>

⁵⁶⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1316>

⁵⁶⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1314>

⁵⁶⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1313>

⁵⁶⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1312>

⁵⁶⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1311>

⁵⁶⁵¹ <https://github.com/TheHPXProject/hpx/issues/1310>

⁵⁶⁵² <https://github.com/TheHPXProject/hpx/issues/1308>

⁵⁶⁵³ <https://github.com/TheHPXProject/hpx/issues/1307>

⁵⁶⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1306>

⁵⁶⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1305>

⁵⁶⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1304>

⁵⁶⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1303>

⁵⁶⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1302>

⁵⁶⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1301>

⁵⁶⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1298>

⁵⁶⁶¹ <https://github.com/TheHPXProject/hpx/issues/1297>

- Issue #1294⁵⁶⁶² - HDF5 build error
- Issue #1275⁵⁶⁶³ - The parcelport implementation is non-optimal
- Issue #1267⁵⁶⁶⁴ - Added classes and unit tests for local_file, orangefs_file and pxfs_file
- Issue #1264⁵⁶⁶⁵ - Error “assertion ‘!m_fun’ failed” randomly occurs when using TCP
- Issue #1254⁵⁶⁶⁶ - thread binding seems to not work properly
- Issue #1220⁵⁶⁶⁷ - parallel::copy_if is broken
- Issue #1217⁵⁶⁶⁸ - Find a better way of fixing the issue patched by #1216
- Issue #1168⁵⁶⁶⁹ - Starting HPX on Cray machines using aprun isn’t working correctly
- Issue #1085⁵⁶⁷⁰ - Replace startup and shutdown barriers with broadcasts
- Issue #981⁵⁶⁷¹ - With SLURM, -hpx:threads=8 should not be necessary
- Issue #857⁵⁶⁷² - hpx::naming::locality leaks parcelport specific information into the public interface
- Issue #850⁵⁶⁷³ - “flush” not documented
- Issue #763⁵⁶⁷⁴ - Create buildbot instance that uses std::bind as HPX_STD_BIND
- Issue #680⁵⁶⁷⁵ - Convert parcel ports into a plugin system
- Issue #582⁵⁶⁷⁶ - Make exception thrown from HPX threads available from `hpx::init`
- Issue #504⁵⁶⁷⁷ - Refactor Dataflow LCO to work with futures
- Issue #196⁵⁶⁷⁸ - Don’t store copies of the locality network metadata in the gva table

HPX V0.9.9 (Oct 31, 2014, codename Spooky)

General changes

We have had over 1500 commits since the last release and we have closed over 200 tickets (bugs, feature requests, pull requests, etc.). These are by far the largest numbers of commits and resolved issues for any of the *HPX* releases so far. We are especially happy about the large number of people who contributed for the first time to *HPX*.

- We completed the transition from the older (non-conforming) implementation of `hpx::future` to the new and fully conforming version by removing the old code and by renaming the type `hpx::unique_future` to `hpx::future`. In order to maintain backwards compatibility with existing code which uses the type `hpx::unique_future` we support the configuration variable `HPX_UNIQUE_FUTURE_ALIAS`. If this variable is set to ON while running cmake it will additionally define a template alias for this type.

⁵⁶⁶² <https://github.com/TheHPXProject/hpx/issues/1294>

⁵⁶⁶³ <https://github.com/TheHPXProject/hpx/issues/1275>

⁵⁶⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1267>

⁵⁶⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1264>

⁵⁶⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1254>

⁵⁶⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1220>

⁵⁶⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1217>

⁵⁶⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1168>

⁵⁶⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1085>

⁵⁶⁷¹ <https://github.com/TheHPXProject/hpx/issues/981>

⁵⁶⁷² <https://github.com/TheHPXProject/hpx/issues/857>

⁵⁶⁷³ <https://github.com/TheHPXProject/hpx/issues/850>

⁵⁶⁷⁴ <https://github.com/TheHPXProject/hpx/issues/763>

⁵⁶⁷⁵ <https://github.com/TheHPXProject/hpx/issues/680>

⁵⁶⁷⁶ <https://github.com/TheHPXProject/hpx/issues/582>

⁵⁶⁷⁷ <https://github.com/TheHPXProject/hpx/issues/504>

⁵⁶⁷⁸ <https://github.com/TheHPXProject/hpx/issues/196>

- We rewrote and significantly changed our build system. Please have a look at the new (now generated) documentation here: *Building HPX*. Please revisit your build scripts to adapt to the changes. The most notable changes are:
 - HPX_NO_INSTALL is no longer necessary.
 - For external builds, you need to set HPX_DIR instead of HPX_ROOT as described here: *Using HPX with CMake-based projects*.
 - IDEs that support multiple configurations (Visual Studio and XCode) can now be used as intended. that means no build dir.
 - Building HPX statically (without dynamic libraries) is now supported (-DHPX_STATIC_LINKING=On).
 - Please note that many variables used to configure the build process have been renamed to unify the naming conventions (see the section *CMake options* for more information).
 - This also fixes a long list of issues, for more information see [Issue #1204](#)⁵⁶⁷⁹.
- We started to implement various proposals to the C++ Standardization committee related to parallelism and concurrency, most notably [N4409](#)⁵⁶⁸⁰ (Working Draft, Technical Specification for C++ Extensions for Parallelism), [N4411](#)⁵⁶⁸¹ (Task Region Rev. 3), and [N4313](#)⁵⁶⁸² (Working Draft, Technical Specification for C++ Extensions for Concurrency).
- We completely remodeled our automatic build system to run builds and unit tests on various systems and compilers. This allows us to find most bugs right as they were introduced and helps to maintain a high level of quality and compatibility. The newest build logs can be found at [HPX Buildbot Website](#)⁵⁶⁸³.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1296](#)⁵⁶⁸⁴ - Rename make_error_future to make_exceptional_future, adjust to N4123
- [Issue #1295](#)⁵⁶⁸⁵ - building issue
- [Issue #1293](#)⁵⁶⁸⁶ - Transpose example
- [Issue #1292](#)⁵⁶⁸⁷ - Wrong abs() function used in example
- [Issue #1291](#)⁵⁶⁸⁸ - non-synchronized shift operators have been removed
- [Issue #1290](#)⁵⁶⁸⁹ - RDTSCP is defined as true for Xeon Phi build
- [Issue #1289](#)⁵⁶⁹⁰ - Fixing 1288
- [Issue #1288](#)⁵⁶⁹¹ - Add new performance counters
- [Issue #1287](#)⁵⁶⁹² - Hierarchy scheduler broken performance counters

⁵⁶⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1204>

⁵⁶⁸⁰ <http://wg21.link/n4409>

⁵⁶⁸¹ <http://wg21.link/n4411>

⁵⁶⁸² <http://wg21.link/n4313>

⁵⁶⁸³ <http://roostam.cct.lsu.edu/>

⁵⁶⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1296>

⁵⁶⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1295>

⁵⁶⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1293>

⁵⁶⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1292>

⁵⁶⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1291>

⁵⁶⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1290>

⁵⁶⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1289>

⁵⁶⁹¹ <https://github.com/TheHPXProject/hpx/issues/1288>

⁵⁶⁹² <https://github.com/TheHPXProject/hpx/issues/1287>

- Issue #1286⁵⁶⁹³ - Algorithm cleanup
- Issue #1285⁵⁶⁹⁴ - Broken Links in Documentation
- Issue #1284⁵⁶⁹⁵ - Uninitialized copy
- Issue #1283⁵⁶⁹⁶ - missing boost::scoped_ptr includes
- Issue #1282⁵⁶⁹⁷ - Update documentation of build options for schedulers
- Issue #1281⁵⁶⁹⁸ - reset idle rate counter
- Issue #1280⁵⁶⁹⁹ - Bug when executing on Intel MIC
- Issue #1279⁵⁷⁰⁰ - Add improved when_all/wait_all
- Issue #1278⁵⁷⁰¹ - Implement improved when_all/wait_all
- Issue #1277⁵⁷⁰² - feature request: get access to argc argv and variables_map
- Issue #1276⁵⁷⁰³ - Remove merging map
- Issue #1274⁵⁷⁰⁴ - Weird (wrong) string code in papi.cpp
- Issue #1273⁵⁷⁰⁵ - Sequential task execution policy
- Issue #1272⁵⁷⁰⁶ - Avoid CMake name clash for Boost.Thread library
- Issue #1271⁵⁷⁰⁷ - Updates on HPX Test Units
- Issue #1270⁵⁷⁰⁸ - hpx/util/safe_lexical_cast.hpp is added
- Issue #1269⁵⁷⁰⁹ - Added default value for “LIB” cmake variable
- Issue #1268⁵⁷¹⁰ - Memory Counters not working
- Issue #1266⁵⁷¹¹ - FindHPX.cmake is not installed
- Issue #1263⁵⁷¹² - apply_remote test takes too long
- Issue #1262⁵⁷¹³ - Chrono cleanup
- Issue #1261⁵⁷¹⁴ - Need make install for papi counters and this builds all the examples
- Issue #1260⁵⁷¹⁵ - Documentation of Stencil example claims

⁵⁶⁹³ <https://github.com/TheHPXProject/hpx/issues/1286>

⁵⁶⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1285>

⁵⁶⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1284>

⁵⁶⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1283>

⁵⁶⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1282>

⁵⁶⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1281>

⁵⁶⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1280>

⁵⁷⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1279>

⁵⁷⁰¹ <https://github.com/TheHPXProject/hpx/issues/1278>

⁵⁷⁰² <https://github.com/TheHPXProject/hpx/issues/1277>

⁵⁷⁰³ <https://github.com/TheHPXProject/hpx/issues/1276>

⁵⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1274>

⁵⁷⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1273>

⁵⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1272>

⁵⁷⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1271>

⁵⁷⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1270>

⁵⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1269>

⁵⁷¹⁰ <https://github.com/TheHPXProject/hpx/issues/1268>

⁵⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/1266>

⁵⁷¹² <https://github.com/TheHPXProject/hpx/issues/1263>

⁵⁷¹³ <https://github.com/TheHPXProject/hpx/issues/1262>

⁵⁷¹⁴ <https://github.com/TheHPXProject/hpx/issues/1261>

⁵⁷¹⁵ <https://github.com/TheHPXProject/hpx/issues/1260>

- Issue #1259⁵⁷¹⁶ - Avoid double-linking Boost on Windows
- Issue #1257⁵⁷¹⁷ - Adding additional parameter to create_thread
- Issue #1256⁵⁷¹⁸ - added buildbot changes to release notes
- Issue #1255⁵⁷¹⁹ - Cannot build MiniGhost
- Issue #1253⁵⁷²⁰ - hpx::thread defects
- Issue #1252⁵⁷²¹ - HPX_PREFIX is too fragile
- Issue #1250⁵⁷²² - switch_to_fiber_emulation does not work properly
- Issue #1249⁵⁷²³ - Documentation is generated under Release folder
- Issue #1248⁵⁷²⁴ - Fix usage of hpx_generic_coroutine_context and get tests passing on powerpc
- Issue #1247⁵⁷²⁵ - Dynamic linking error
- Issue #1246⁵⁷²⁶ - Make cpuid.cpp C++11 compliant
- Issue #1245⁵⁷²⁷ - HPX fails on startup (setting thread affinity mask)
- Issue #1244⁵⁷²⁸ - HPX_WITH_RDTSC configure test fails, but should succeed
- Issue #1243⁵⁷²⁹ - CTest dashboard info for CSCS CDash drop location
- Issue #1242⁵⁷³⁰ - Mac fixes
- Issue #1241⁵⁷³¹ - Failure in Distributed with Boost 1.56
- Issue #1240⁵⁷³² - fix a race condition in examples.diskperf
- Issue #1239⁵⁷³³ - fix wait_each in examples.diskperf
- Issue #1238⁵⁷³⁴ - Fixed #1237: hpx::util::portable_binary_iarchive failed
- Issue #1237⁵⁷³⁵ - hpx::util::portable_binary_iarchive faileds
- Issue #1235⁵⁷³⁶ - Fixing clang warnings and errors
- Issue #1234⁵⁷³⁷ - TCP runs fail: Transport endpoint is not connected
- Issue #1233⁵⁷³⁸ - Making sure the correct number of threads is registered with AGAS

⁵⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/1259>

⁵⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/1257>

⁵⁷¹⁸ <https://github.com/TheHPXProject/hpx/issues/1256>

⁵⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/1255>

⁵⁷²⁰ <https://github.com/TheHPXProject/hpx/issues/1253>

⁵⁷²¹ <https://github.com/TheHPXProject/hpx/issues/1252>

⁵⁷²² <https://github.com/TheHPXProject/hpx/issues/1250>

⁵⁷²³ <https://github.com/TheHPXProject/hpx/issues/1249>

⁵⁷²⁴ <https://github.com/TheHPXProject/hpx/issues/1248>

⁵⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/1247>

⁵⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/1246>

⁵⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/1245>

⁵⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/1244>

⁵⁷²⁹ <https://github.com/TheHPXProject/hpx/issues/1243>

⁵⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/1242>

⁵⁷³¹ <https://github.com/TheHPXProject/hpx/issues/1241>

⁵⁷³² <https://github.com/TheHPXProject/hpx/issues/1240>

⁵⁷³³ <https://github.com/TheHPXProject/hpx/issues/1239>

⁵⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/1238>

⁵⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/1237>

⁵⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/1235>

⁵⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/1234>

⁵⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/1233>

- Issue #1232⁵⁷³⁹ - Fixing race in wait_XXX
- Issue #1231⁵⁷⁴⁰ - Parallel minmax
- Issue #1230⁵⁷⁴¹ - Distributed run of 1d_stencil_8 uses less threads than spec. & sometimes gives errors
- Issue #1229⁵⁷⁴² - Unstable number of threads
- Issue #1228⁵⁷⁴³ - HPX link error (cmake / MPI)
- Issue #1226⁵⁷⁴⁴ - Warning about struct/class thread_counters
- Issue #1225⁵⁷⁴⁵ - Adding parallel::replace etc
- Issue #1224⁵⁷⁴⁶ - Extending dataflow to pass through non-future arguments
- Issue #1223⁵⁷⁴⁷ - Remaining find algorithms implemented, N4071
- Issue #1222⁵⁷⁴⁸ - Merging all the changes
- Issue #1221⁵⁷⁴⁹ - No error output when using mpirun with hpx
- Issue #1219⁵⁷⁵⁰ - Adding new AGAS cache performance counters
- Issue #1216⁵⁷⁵¹ - Fixing using futures (clients) as arguments to actions
- Issue #1215⁵⁷⁵² - Error compiling simple component
- Issue #1214⁵⁷⁵³ - Stencil docs
- Issue #1213⁵⁷⁵⁴ - Using more than a few dozen MPI processes on SuperMike results in a seg fault before getting to hpx_main
- Issue #1212⁵⁷⁵⁵ - Parallel rotate
- Issue #1211⁵⁷⁵⁶ - Direct actions cause the future's shared_state to be leaked
- Issue #1210⁵⁷⁵⁷ - Refactored local::promise to be standard conformant
- Issue #1209⁵⁷⁵⁸ - Improve command line handling
- Issue #1208⁵⁷⁵⁹ - Adding parallel::reverse and parallel::reverse_copy
- Issue #1207⁵⁷⁶⁰ - Add copy_backward and move_backward
- Issue #1206⁵⁷⁶¹ - N4071 additional algorithms implemented

⁵⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/1232>

⁵⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1231>

⁵⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/1230>

⁵⁷⁴² <https://github.com/TheHPXProject/hpx/issues/1229>

⁵⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/1228>

⁵⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1226>

⁵⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1225>

⁵⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1224>

⁵⁷⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1223>

⁵⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1222>

⁵⁷⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1221>

⁵⁷⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1219>

⁵⁷⁵¹ <https://github.com/TheHPXProject/hpx/issues/1216>

⁵⁷⁵² <https://github.com/TheHPXProject/hpx/issues/1215>

⁵⁷⁵³ <https://github.com/TheHPXProject/hpx/issues/1214>

⁵⁷⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1213>

⁵⁷⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1212>

⁵⁷⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1211>

⁵⁷⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1210>

⁵⁷⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1209>

⁵⁷⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1208>

⁵⁷⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1207>

⁵⁷⁶¹ <https://github.com/TheHPXProject/hpx/issues/1206>

- [Issue #1204⁵⁷⁶²](#) - Cmake simplification and various other minor changes
- [Issue #1203⁵⁷⁶³](#) - Implementing new launch policy for (local) `async: hpx::launch::fork`.
- [Issue #1202⁵⁷⁶⁴](#) - Failed assertion in `connection_cache.hpp`
- [Issue #1201⁵⁷⁶⁵](#) - `pkg-config` doesn't add `mpi` link directories
- [Issue #1200⁵⁷⁶⁶](#) - Error when querying time performance counters
- [Issue #1199⁵⁷⁶⁷](#) - library path is now configurable (again)
- [Issue #1198⁵⁷⁶⁸](#) - Error when querying performance counters
- [Issue #1197⁵⁷⁶⁹](#) - tests fail with intel compiler
- [Issue #1196⁵⁷⁷⁰](#) - Silence several warnings
- [Issue #1195⁵⁷⁷¹](#) - Rephrase initializers to work with VC++ 2012
- [Issue #1194⁵⁷⁷²](#) - Simplify parallel algorithms
- [Issue #1193⁵⁷⁷³](#) - Adding `parallel::equal`
- [Issue #1192⁵⁷⁷⁴](#) - `HPX(out_of_memory)` on including `<hpx/hpx.hpp>`
- [Issue #1191⁵⁷⁷⁵](#) - Fixing #1189
- [Issue #1190⁵⁷⁷⁶](#) - Chrono cleanup
- [Issue #1189⁵⁷⁷⁷](#) - Deadlock .. somewhere? (probably serialization)
- [Issue #1188⁵⁷⁷⁸](#) - Removed `future::get_status()`
- [Issue #1186⁵⁷⁷⁹](#) - Fixed `FindOpenCL` to find current AMD APP SDK
- [Issue #1184⁵⁷⁸⁰](#) - Tweaking future unwrapping
- [Issue #1183⁵⁷⁸¹](#) - Extended `parallel::reduce`
- [Issue #1182⁵⁷⁸²](#) - `future::unwrap` hangs for `launch::deferred`
- [Issue #1181⁵⁷⁸³](#) - Adding `all_of`, `any_of`, and `none_of` and corresponding documentation
- [Issue #1180⁵⁷⁸⁴](#) - `hpx::cout` defect

⁵⁷⁶² <https://github.com/TheHPXProject/hpx/issues/1204>

⁵⁷⁶³ <https://github.com/TheHPXProject/hpx/issues/1203>

⁵⁷⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1202>

⁵⁷⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1201>

⁵⁷⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1200>

⁵⁷⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1199>

⁵⁷⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1198>

⁵⁷⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1197>

⁵⁷⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1196>

⁵⁷⁷¹ <https://github.com/TheHPXProject/hpx/issues/1195>

⁵⁷⁷² <https://github.com/TheHPXProject/hpx/issues/1194>

⁵⁷⁷³ <https://github.com/TheHPXProject/hpx/issues/1193>

⁵⁷⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1192>

⁵⁷⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1191>

⁵⁷⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1190>

⁵⁷⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1189>

⁵⁷⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1188>

⁵⁷⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1186>

⁵⁷⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1184>

⁵⁷⁸¹ <https://github.com/TheHPXProject/hpx/issues/1183>

⁵⁷⁸² <https://github.com/TheHPXProject/hpx/issues/1182>

⁵⁷⁸³ <https://github.com/TheHPXProject/hpx/issues/1181>

⁵⁷⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1180>

- [Issue #1179⁵⁷⁸⁵](#) - `hpx::async` does not work for member function pointers when called on types with self-defined unary operator*
- [Issue #1178⁵⁷⁸⁶](#) - Implemented variadic `hpx::util::zip_iterator`
- [Issue #1177⁵⁷⁸⁷](#) - MPI parcelport defect
- [Issue #1176⁵⁷⁸⁸](#) - `HPX_DEFINE_COMPONENT_CONST_ACTION_TPL` does not have a 2-argument version
- [Issue #1175⁵⁷⁸⁹](#) - Create `util::zip_iterator` working with `util::tuple<>`
- [Issue #1174⁵⁷⁹⁰](#) - Error Building HPX on linux, `root_certificate_authority.cpp`
- [Issue #1173⁵⁷⁹¹](#) - `hpx::cout` output lost
- [Issue #1172⁵⁷⁹²](#) - HPX build error with Clang 3.4.2
- [Issue #1171⁵⁷⁹³](#) - `CMAKE_INSTALL_PREFIX` ignored
- [Issue #1170⁵⁷⁹⁴](#) - Close `hpx_benchmarks` repository on Github
- [Issue #1169⁵⁷⁹⁵](#) - Buildbot emails have syntax error in url
- [Issue #1167⁵⁷⁹⁶](#) - Merge partial implementation of standards proposal N3960
- [Issue #1166⁵⁷⁹⁷](#) - Fixed several compiler warnings
- [Issue #1165⁵⁷⁹⁸](#) - `cmake` warns: “`tests.regressions.actions`” does not exist
- [Issue #1164⁵⁷⁹⁹](#) - Want my own serialization of `hpx::future`
- [Issue #1162⁵⁸⁰⁰](#) - Segfault in `hello_world` example
- [Issue #1161⁵⁸⁰¹](#) - Use `HPX_ASSERT` to aid the compiler
- [Issue #1160⁵⁸⁰²](#) - Do not put `-DNDEBUG` into `hpx_application.pc`
- [Issue #1159⁵⁸⁰³](#) - Support Clang 3.4.2
- [Issue #1158⁵⁸⁰⁴](#) - Fixed #1157: Rename `when_n/wait_n`, add `when_xxx_n/wait_xxx_n`
- [Issue #1157⁵⁸⁰⁵](#) - Rename `when_n/wait_n`, add `when_xxx_n/wait_xxx_n`
- [Issue #1156⁵⁸⁰⁶](#) - Force inlining fails
- [Issue #1155⁵⁸⁰⁷](#) - changed header of `printout` to be compatible with python csv module

⁵⁷⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1179>

⁵⁷⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1178>

⁵⁷⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1177>

⁵⁷⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1176>

⁵⁷⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1175>

⁵⁷⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1174>

⁵⁷⁹¹ <https://github.com/TheHPXProject/hpx/issues/1173>

⁵⁷⁹² <https://github.com/TheHPXProject/hpx/issues/1172>

⁵⁷⁹³ <https://github.com/TheHPXProject/hpx/issues/1171>

⁵⁷⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1170>

⁵⁷⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1169>

⁵⁷⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1167>

⁵⁷⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1166>

⁵⁷⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1165>

⁵⁷⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1164>

⁵⁸⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1162>

⁵⁸⁰¹ <https://github.com/TheHPXProject/hpx/issues/1161>

⁵⁸⁰² <https://github.com/TheHPXProject/hpx/issues/1160>

⁵⁸⁰³ <https://github.com/TheHPXProject/hpx/issues/1159>

⁵⁸⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1158>

⁵⁸⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1157>

⁵⁸⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1156>

⁵⁸⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1155>

- Issue #1154⁵⁸⁰⁸ - Fixing iostreams
- Issue #1153⁵⁸⁰⁹ - Standard manipulators (like `std::endl`) do not work with `hpx::ostream`
- Issue #1152⁵⁸¹⁰ - Functions revamp
- Issue #1151⁵⁸¹¹ - Suppressing cmake 3.0 policy warning for CMP0026
- Issue #1150⁵⁸¹² - Client Serialization error
- Issue #1149⁵⁸¹³ - Segfault on Stampede
- Issue #1148⁵⁸¹⁴ - Refactoring mini-ghost
- Issue #1147⁵⁸¹⁵ - N3960 `copy_if` and `copy_n` implemented and tested
- Issue #1146⁵⁸¹⁶ - Stencil print
- Issue #1145⁵⁸¹⁷ - N3960 `hpx::parallel::copy` implemented and tested
- Issue #1144⁵⁸¹⁸ - OpenMP examples `1d_stencil` do not build
- Issue #1143⁵⁸¹⁹ - `1d_stencil` OpenMP examples do not build
- Issue #1142⁵⁸²⁰ - Cannot build HPX with gcc 4.6 on OS X
- Issue #1140⁵⁸²¹ - Fix OpenMP lookup, enable usage of config tests in external CMake projects.
- Issue #1139⁵⁸²² - `hpx/hpx/config/compiler_specific.hpp`
- Issue #1138⁵⁸²³ - clean up pkg-config files
- Issue #1137⁵⁸²⁴ - Improvements to create binary packages
- Issue #1136⁵⁸²⁵ - `HPX_GCC_VERSION` not defined on all compilers
- Issue #1135⁵⁸²⁶ - Avoiding collision between `winsock2.h` and `windows.h`
- Issue #1134⁵⁸²⁷ - Making sure, that `hpx::finalize` can be called from any locality
- Issue #1133⁵⁸²⁸ - `1d stencil` examples
- Issue #1131⁵⁸²⁹ - Refactor `unique_function` implementation
- Issue #1130⁵⁸³⁰ - Unique function

⁵⁸⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1154>

⁵⁸⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1153>

⁵⁸¹⁰ <https://github.com/TheHPXProject/hpx/issues/1152>

⁵⁸¹¹ <https://github.com/TheHPXProject/hpx/issues/1151>

⁵⁸¹² <https://github.com/TheHPXProject/hpx/issues/1150>

⁵⁸¹³ <https://github.com/TheHPXProject/hpx/issues/1149>

⁵⁸¹⁴ <https://github.com/TheHPXProject/hpx/issues/1148>

⁵⁸¹⁵ <https://github.com/TheHPXProject/hpx/issues/1147>

⁵⁸¹⁶ <https://github.com/TheHPXProject/hpx/issues/1146>

⁵⁸¹⁷ <https://github.com/TheHPXProject/hpx/issues/1145>

⁵⁸¹⁸ <https://github.com/TheHPXProject/hpx/issues/1144>

⁵⁸¹⁹ <https://github.com/TheHPXProject/hpx/issues/1143>

⁵⁸²⁰ <https://github.com/TheHPXProject/hpx/issues/1142>

⁵⁸²¹ <https://github.com/TheHPXProject/hpx/issues/1140>

⁵⁸²² <https://github.com/TheHPXProject/hpx/issues/1139>

⁵⁸²³ <https://github.com/TheHPXProject/hpx/issues/1138>

⁵⁸²⁴ <https://github.com/TheHPXProject/hpx/issues/1137>

⁵⁸²⁵ <https://github.com/TheHPXProject/hpx/issues/1136>

⁵⁸²⁶ <https://github.com/TheHPXProject/hpx/issues/1135>

⁵⁸²⁷ <https://github.com/TheHPXProject/hpx/issues/1134>

⁵⁸²⁸ <https://github.com/TheHPXProject/hpx/issues/1133>

⁵⁸²⁹ <https://github.com/TheHPXProject/hpx/issues/1131>

⁵⁸³⁰ <https://github.com/TheHPXProject/hpx/issues/1130>

- Issue #1129⁵⁸³¹ - Some fixes to the Build system on OS X
- Issue #1128⁵⁸³² - Action future args
- Issue #1127⁵⁸³³ - Executor causes segmentation fault
- Issue #1124⁵⁸³⁴ - Adding new API functions: `register_id_with_basename`, `unregister_id_with_basename`, `find_ids_from_basename`; adding test
- Issue #1123⁵⁸³⁵ - Reduce nesting of try-catch construct in `encode_parcel`s?
- Issue #1122⁵⁸³⁶ - Client base fixes
- Issue #1121⁵⁸³⁷ - Update `hpxrun.py.in`
- Issue #1120⁵⁸³⁸ - HTTPS2 tests compile errors on v110 (VS2012)
- Issue #1119⁵⁸³⁹ - Remove references to `boost::atomic` in accumulator example
- Issue #1118⁵⁸⁴⁰ - Only build test `thread_pool_executor_1114_test` if `HPX_SCHEDULER` is set
- Issue #1117⁵⁸⁴¹ - `local_queue_executor` linker error on vc110
- Issue #1116⁵⁸⁴² - Disabled performance counter should give runtime errors, not invalid data
- Issue #1115⁵⁸⁴³ - Compile error with Intel C++ 13.1
- Issue #1114⁵⁸⁴⁴ - Default constructed executor is not usable
- Issue #1113⁵⁸⁴⁵ - Fast compilation of logging causes ABI incompatibilities between different `NDEBUG` values
- Issue #1112⁵⁸⁴⁶ - Using `thread_pool_executors` causes segfault
- Issue #1111⁵⁸⁴⁷ - `hpx::threads::get_thread_data` always returns zero
- Issue #1110⁵⁸⁴⁸ - Remove unnecessary null pointer checks
- Issue #1109⁵⁸⁴⁹ - More tests adjustments
- Issue #1108⁵⁸⁵⁰ - Clarify build rules for “`libboost_atomic-mt.so`”?
- Issue #1107⁵⁸⁵¹ - Remove unnecessary null pointer checks
- Issue #1106⁵⁸⁵² - `network_storage` benchmark improvements, adding legends to plots and tidying layout
- Issue #1105⁵⁸⁵³ - Add more plot outputs and improve instructions doc

⁵⁸³¹ <https://github.com/TheHPXProject/hpx/issues/1129>

⁵⁸³² <https://github.com/TheHPXProject/hpx/issues/1128>

⁵⁸³³ <https://github.com/TheHPXProject/hpx/issues/1127>

⁵⁸³⁴ <https://github.com/TheHPXProject/hpx/issues/1124>

⁵⁸³⁵ <https://github.com/TheHPXProject/hpx/issues/1123>

⁵⁸³⁶ <https://github.com/TheHPXProject/hpx/issues/1122>

⁵⁸³⁷ <https://github.com/TheHPXProject/hpx/issues/1121>

⁵⁸³⁸ <https://github.com/TheHPXProject/hpx/issues/1120>

⁵⁸³⁹ <https://github.com/TheHPXProject/hpx/issues/1119>

⁵⁸⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1118>

⁵⁸⁴¹ <https://github.com/TheHPXProject/hpx/issues/1117>

⁵⁸⁴² <https://github.com/TheHPXProject/hpx/issues/1116>

⁵⁸⁴³ <https://github.com/TheHPXProject/hpx/issues/1115>

⁵⁸⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1114>

⁵⁸⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1113>

⁵⁸⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1112>

⁵⁸⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1111>

⁵⁸⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1110>

⁵⁸⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1109>

⁵⁸⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1108>

⁵⁸⁵¹ <https://github.com/TheHPXProject/hpx/issues/1107>

⁵⁸⁵² <https://github.com/TheHPXProject/hpx/issues/1106>

⁵⁸⁵³ <https://github.com/TheHPXProject/hpx/issues/1105>

- Issue #1104⁵⁸⁵⁴ - Complete quoting for parameters of some CMake commands
- Issue #1103⁵⁸⁵⁵ - Work on test/scripts
- Issue #1102⁵⁸⁵⁶ - Changed minimum requirement of window install to 2012
- Issue #1101⁵⁸⁵⁷ - Changed minimum requirement of window install to 2012
- Issue #1100⁵⁸⁵⁸ - Changed readme to no longer specify using MSVC 2010 compiler
- Issue #1099⁵⁸⁵⁹ - Error returning futures from component actions
- Issue #1098⁵⁸⁶⁰ - Improve storage test
- Issue #1097⁵⁸⁶¹ - data_actions quickstart example calls missing function decorate_action of data_get_action
- Issue #1096⁵⁸⁶² - MPI parcelport broken with new zero copy optimization
- Issue #1095⁵⁸⁶³ - Warning C4005: _WIN32_WINNT: Macro redefinition
- Issue #1094⁵⁸⁶⁴ - Syntax error for -DHPX_UNIQUE_FUTURE_ALIAS in master
- Issue #1093⁵⁸⁶⁵ - Syntax error for -DHPX_UNIQUE_FUTURE_ALIAS
- Issue #1092⁵⁸⁶⁶ - Rename unique_future<> back to future<>
- Issue #1091⁵⁸⁶⁷ - Inconsistent error message
- Issue #1090⁵⁸⁶⁸ - On windows 8.1 the examples crashed if using more than one os thread
- Issue #1089⁵⁸⁶⁹ - Components should be allowed to have their own executor
- Issue #1088⁵⁸⁷⁰ - Add possibility to select a network interface for the ibverbs parcelport
- Issue #1087⁵⁸⁷¹ - ibverbs and ipc parcelport uses zero copy optimization
- Issue #1083⁵⁸⁷² - Make shell examples copyable in docs
- Issue #1082⁵⁸⁷³ - Implement proper termination detection during shutdown
- Issue #1081⁵⁸⁷⁴ - Implement thread_specific_ptr for hpx::threads
- Issue #1072⁵⁸⁷⁵ - make install not working properly
- Issue #1070⁵⁸⁷⁶ - Complete quoting for parameters of some CMake commands

⁵⁸⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1104>

⁵⁸⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1103>

⁵⁸⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1102>

⁵⁸⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1101>

⁵⁸⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1100>

⁵⁸⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1099>

⁵⁸⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1098>

⁵⁸⁶¹ <https://github.com/TheHPXProject/hpx/issues/1097>

⁵⁸⁶² <https://github.com/TheHPXProject/hpx/issues/1096>

⁵⁸⁶³ <https://github.com/TheHPXProject/hpx/issues/1095>

⁵⁸⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1094>

⁵⁸⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1093>

⁵⁸⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1092>

⁵⁸⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1091>

⁵⁸⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1090>

⁵⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1089>

⁵⁸⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1088>

⁵⁸⁷¹ <https://github.com/TheHPXProject/hpx/issues/1087>

⁵⁸⁷² <https://github.com/TheHPXProject/hpx/issues/1083>

⁵⁸⁷³ <https://github.com/TheHPXProject/hpx/issues/1082>

⁵⁸⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1081>

⁵⁸⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1072>

⁵⁸⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1070>

- [Issue #1059](#)⁵⁸⁷⁷ - Fix more unused variable warnings
- [Issue #1051](#)⁵⁸⁷⁸ - Implement when_each
- [Issue #973](#)⁵⁸⁷⁹ - Would like option to report hwloc bindings
- [Issue #970](#)⁵⁸⁸⁰ - Bad flags for Fortran compiler
- [Issue #941](#)⁵⁸⁸¹ - Create a proper user level context switching class for BG/Q
- [Issue #935](#)⁵⁸⁸² - Build error with gcc 4.6 and Boost 1.54.0 on hpx trunk and 0.9.6
- [Issue #934](#)⁵⁸⁸³ - Want to build HPX without dynamic libraries
- [Issue #927](#)⁵⁸⁸⁴ - Make hpx/lcos/reduce.hpp accept futures of id_type
- [Issue #926](#)⁵⁸⁸⁵ - All unit tests that are run with more than one thread with CTest/hpx_run_test should configure hpx.os_threads
- [Issue #925](#)⁵⁸⁸⁶ - regression_dataflow_791 needs to be brought in line with HPX standards
- [Issue #899](#)⁵⁸⁸⁷ - Fix race conditions in regression tests
- [Issue #879](#)⁵⁸⁸⁸ - Hung test leads to cascading test failure; make tests should support the MPI parcelport
- [Issue #865](#)⁵⁸⁸⁹ - future<T> and friends shall work for movable only Ts
- [Issue #847](#)⁵⁸⁹⁰ - Dynamic libraries are not installed on OS X
- [Issue #816](#)⁵⁸⁹¹ - First Program tutorial pull request
- [Issue #799](#)⁵⁸⁹² - Wrap lexical_cast to avoid exceptions
- [Issue #720](#)⁵⁸⁹³ - broken configuration when using cmake on Ubuntu
- [Issue #622](#)⁵⁸⁹⁴ - --hpx:hpx and --hpx:debug-hpx-log is nonsensical
- [Issue #525](#)⁵⁸⁹⁵ - Extend barrier LCO test to run in distributed
- [Issue #515](#)⁵⁸⁹⁶ - Multi-destination version of hpx::apply is broken
- [Issue #509](#)⁵⁸⁹⁷ - Push Boost.Atomic changes upstream
- [Issue #503](#)⁵⁸⁹⁸ - Running HPX applications on Windows should not require setting %PATH%
- [Issue #461](#)⁵⁸⁹⁹ - Add a compilation sanity test

⁵⁸⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1059>

⁵⁸⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1051>

⁵⁸⁷⁹ <https://github.com/TheHPXProject/hpx/issues/973>

⁵⁸⁸⁰ <https://github.com/TheHPXProject/hpx/issues/970>

⁵⁸⁸¹ <https://github.com/TheHPXProject/hpx/issues/941>

⁵⁸⁸² <https://github.com/TheHPXProject/hpx/issues/935>

⁵⁸⁸³ <https://github.com/TheHPXProject/hpx/issues/934>

⁵⁸⁸⁴ <https://github.com/TheHPXProject/hpx/issues/927>

⁵⁸⁸⁵ <https://github.com/TheHPXProject/hpx/issues/926>

⁵⁸⁸⁶ <https://github.com/TheHPXProject/hpx/issues/925>

⁵⁸⁸⁷ <https://github.com/TheHPXProject/hpx/issues/899>

⁵⁸⁸⁸ <https://github.com/TheHPXProject/hpx/issues/879>

⁵⁸⁸⁹ <https://github.com/TheHPXProject/hpx/issues/865>

⁵⁸⁹⁰ <https://github.com/TheHPXProject/hpx/issues/847>

⁵⁸⁹¹ <https://github.com/TheHPXProject/hpx/issues/816>

⁵⁸⁹² <https://github.com/TheHPXProject/hpx/issues/799>

⁵⁸⁹³ <https://github.com/TheHPXProject/hpx/issues/720>

⁵⁸⁹⁴ <https://github.com/TheHPXProject/hpx/issues/622>

⁵⁸⁹⁵ <https://github.com/TheHPXProject/hpx/issues/525>

⁵⁸⁹⁶ <https://github.com/TheHPXProject/hpx/issues/515>

⁵⁸⁹⁷ <https://github.com/TheHPXProject/hpx/issues/509>

⁵⁸⁹⁸ <https://github.com/TheHPXProject/hpx/issues/503>

⁵⁸⁹⁹ <https://github.com/TheHPXProject/hpx/issues/461>

- Issue #456⁵⁹⁰⁰ - hpx_run_tests.py should log output from tests that timeout
- Issue #454⁵⁹⁰¹ - Investigate threadmanager performance
- Issue #345⁵⁹⁰² - Add more versatile environmental/cmake variable support to hpx_find_* CMake macros
- Issue #209⁵⁹⁰³ - Support multiple configurations in generated build files
- Issue #190⁵⁹⁰⁴ - hpx::cout should be a std::ostream
- Issue #189⁵⁹⁰⁵ - iostreams component should use startup/shutdown functions
- Issue #183⁵⁹⁰⁶ - Use Boost.ICL for correctness in AGAS
- Issue #44⁵⁹⁰⁷ - Implement real futures

HPX V0.9.8 (Mar 24, 2014)

We have had over 800 commits since the last release and we have closed over 65 tickets (bugs, feature requests, etc.).

With the changes below, *HPX* is once again leading the charge of a whole new era of computation. By intrinsically breaking down and synchronizing the work to be done, *HPX* insures that application developers will no longer have to fret about where a segment of code executes. That allows coders to focus their time and energy to understanding the data dependencies of their algorithms and thereby the core obstacles to an efficient code. Here are some of the advantages of using *HPX*:

- *HPX* is solidly rooted in a sophisticated theoretical execution model – ParalleX
- *HPX* exposes an API fully conforming to the C++11 and the draft C++14 standards, extended and applied to distributed computing. Everything programmers know about the concurrency primitives of the standard C++ library is still valid in the context of *HPX*.
- It provides a competitive, high performance implementation of modern, future-proof ideas which gives an smooth migration path from today's mainstream techniques
- There is no need for the programmer to worry about lower level parallelization paradigms like threads or message passing; no need to understand pthreads, MPI, OpenMP, or Windows threads, etc.
- There is no need to think about different types of parallelism such as tasks, pipelines, or fork-join, task or data parallelism.
- The same source of your program compiles and runs on Linux, BlueGene/Q, Mac OS X, Windows, and Android.
- The same code runs on shared memory multi-core systems and supercomputers, on handheld devices and Intel® Xeon Phi™ accelerators, or a heterogeneous mix of those.

⁵⁹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/456>

⁵⁹⁰¹ <https://github.com/TheHPXProject/hpx/issues/454>

⁵⁹⁰² <https://github.com/TheHPXProject/hpx/issues/345>

⁵⁹⁰³ <https://github.com/TheHPXProject/hpx/issues/209>

⁵⁹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/190>

⁵⁹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/189>

⁵⁹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/183>

⁵⁹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/44>

General changes

- A major API breaking change for this release was introduced by implementing `hpx::future` and `hpx::shared_future` fully in conformance with the C++11 Standard⁵⁹⁰⁸. While `hpx::shared_future` is new and will not create any compatibility problems, we revised the interface and implementation of the existing `hpx::future`. For more details please see the [mailing list archive](#)⁵⁹⁰⁹. To avoid any incompatibilities for existing code we named the type which implements the `std::future` interface as `hpx::unique_future`. For the next release this will be renamed to `hpx::future`, making it full conforming to C++11 Standard⁵⁹¹⁰.
- A large part of the code base of *HPX* has been refactored and partially re-implemented. The main changes were related to
 - The threading subsystem: these changes significantly reduce the amount of overheads caused by the schedulers, improve the modularity of the code base, and extend the variety of available scheduling algorithms.
 - The parcel subsystem: these changes improve the performance of the *HPX* networking layer, modularize the structure of the parcelports, and simplify the creation of new parcelports for other underlying networking libraries.
 - The API subsystem: these changes improved the conformance of the API to C++11 Standard, extend and unify the available API functionality, and decrease the overheads created by various elements of the API.
 - The robustness of the component loading subsystem has been improved significantly, allowing to more portably and more reliably register the components needed by an application as startup. This additionally speeds up general application initialization.
- We added new API functionality like `hpx::migrate` and `hpx::copy_component` which are the basic building blocks necessary for implementing higher level abstractions for system-wide load balancing, runtime-adaptive resource management, and object-oriented checkpointing and state-management.
- We removed the use of C++11 move emulation (using `Boost.Move`), replacing it with C++11 rvalue references. This is the first step towards using more and more native C++11 facilities which we plan to introduce in the future.
- We improved the reference counting scheme used by *HPX* which helps managing distributed objects and memory. This improves the overall stability of *HPX* and further simplifies writing real world applications.
- The minimal Boost version required to use *HPX* is now V1.49.0.
- This release coincides with the first release of HPXPI (V0.1.0), the first implementation of the [XPI specification](#)⁵⁹¹¹.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1086](#)⁵⁹¹² - Expose internal `boost::shared_array` to allow user management of array lifetime
- [Issue #1083](#)⁵⁹¹³ - Make shell examples copyable in docs
- [Issue #1080](#)⁵⁹¹⁴ - `/threads{locality#*/total}/count/cumulative` broken
- [Issue #1079](#)⁵⁹¹⁵ - Build problems on OS X

⁵⁹⁰⁸ <http://www.open-std.org/jtc1/sc22/wg21>

⁵⁹⁰⁹ <http://mail.cct.lsu.edu/pipermail/hpx-users/2014-January/000141.html>

⁵⁹¹⁰ <http://www.open-std.org/jtc1/sc22/wg21>

⁵⁹¹¹ <https://github.com/STELLAR-GROUP/hpxpi/blob/master/spec.pdf?raw=true>

⁵⁹¹² <https://github.com/TheHPXProject/hpx/issues/1086>

⁵⁹¹³ <https://github.com/TheHPXProject/hpx/issues/1083>

⁵⁹¹⁴ <https://github.com/TheHPXProject/hpx/issues/1080>

⁵⁹¹⁵ <https://github.com/TheHPXProject/hpx/issues/1079>

- Issue #1078⁵⁹¹⁶ - Improve robustness of component loading
- Issue #1077⁵⁹¹⁷ - Fix a missing enum definition for ‘take’ mode
- Issue #1076⁵⁹¹⁸ - Merge Jb master
- Issue #1075⁵⁹¹⁹ - Unknown CMake command “add_hpx_pseudo_target”
- Issue #1074⁵⁹²⁰ - Implement `apply_continue_callback` and `apply_colocated_callback`
- Issue #1073⁵⁹²¹ - The new `apply_colocated` and `async_colocated` functions lead to automatic registered functions
- Issue #1071⁵⁹²² - Remove `deferred_packaged_task`
- Issue #1069⁵⁹²³ - `serialize_buffer` with allocator fails at destruction
- Issue #1068⁵⁹²⁴ - Coroutine include and forward declarations missing
- Issue #1067⁵⁹²⁵ - Add allocator support to `util::serialize_buffer`
- Issue #1066⁵⁹²⁶ - Allow for `MPI_Init` being called before HPX launches
- Issue #1065⁵⁹²⁷ - AGAS cache isn’t used/populated on worker localities
- Issue #1064⁵⁹²⁸ - Reorder includes to ensure `ws2` includes early
- Issue #1063⁵⁹²⁹ - Add `hpx::runtime::suspend` and `hpx::runtime::resume`
- Issue #1062⁵⁹³⁰ - Fix `async_continue` to properly handle return types
- Issue #1061⁵⁹³¹ - Implement `async_colocated` and `apply_colocated`
- Issue #1060⁵⁹³² - Implement minimal component migration
- Issue #1058⁵⁹³³ - Remove `HPX_UTIL_TUPLE` from code base
- Issue #1057⁵⁹³⁴ - Add performance counters for threading subsystem
- Issue #1055⁵⁹³⁵ - Thread allocation uses two memory pools
- Issue #1053⁵⁹³⁶ - Work stealing flawed
- Issue #1052⁵⁹³⁷ - Fix a number of warnings
- Issue #1049⁵⁹³⁸ - Fixes for TLS on OSX and more reliable test running

⁵⁹¹⁶ <https://github.com/TheHPXProject/hpx/issues/1078>

⁵⁹¹⁷ <https://github.com/TheHPXProject/hpx/issues/1077>

⁵⁹¹⁸ <https://github.com/TheHPXProject/hpx/issues/1076>

⁵⁹¹⁹ <https://github.com/TheHPXProject/hpx/issues/1075>

⁵⁹²⁰ <https://github.com/TheHPXProject/hpx/issues/1074>

⁵⁹²¹ <https://github.com/TheHPXProject/hpx/issues/1073>

⁵⁹²² <https://github.com/TheHPXProject/hpx/issues/1071>

⁵⁹²³ <https://github.com/TheHPXProject/hpx/issues/1069>

⁵⁹²⁴ <https://github.com/TheHPXProject/hpx/issues/1068>

⁵⁹²⁵ <https://github.com/TheHPXProject/hpx/issues/1067>

⁵⁹²⁶ <https://github.com/TheHPXProject/hpx/issues/1066>

⁵⁹²⁷ <https://github.com/TheHPXProject/hpx/issues/1065>

⁵⁹²⁸ <https://github.com/TheHPXProject/hpx/issues/1064>

⁵⁹²⁹ <https://github.com/TheHPXProject/hpx/issues/1063>

⁵⁹³⁰ <https://github.com/TheHPXProject/hpx/issues/1062>

⁵⁹³¹ <https://github.com/TheHPXProject/hpx/issues/1061>

⁵⁹³² <https://github.com/TheHPXProject/hpx/issues/1060>

⁵⁹³³ <https://github.com/TheHPXProject/hpx/issues/1058>

⁵⁹³⁴ <https://github.com/TheHPXProject/hpx/issues/1057>

⁵⁹³⁵ <https://github.com/TheHPXProject/hpx/issues/1055>

⁵⁹³⁶ <https://github.com/TheHPXProject/hpx/issues/1053>

⁵⁹³⁷ <https://github.com/TheHPXProject/hpx/issues/1052>

⁵⁹³⁸ <https://github.com/TheHPXProject/hpx/issues/1049>

- Issue #1048⁵⁹³⁹ - Fixing after 588 hang
- Issue #1047⁵⁹⁴⁰ - Use port '0' for networking when using one locality
- Issue #1046⁵⁹⁴¹ - `composable_guard` test is broken when having more than one thread
- Issue #1045⁵⁹⁴² - Security missing headers
- Issue #1044⁵⁹⁴³ - Native TLS on FreeBSD via `__thread`
- Issue #1043⁵⁹⁴⁴ - `async` et.al. compute the wrong result type
- Issue #1042⁵⁹⁴⁵ - `async` et.al. implicitly unwrap `reference_wrappers`
- Issue #1041⁵⁹⁴⁶ - Remove redundant costly Kleene stars from regex searches
- Issue #1040⁵⁹⁴⁷ - CMake script regex match patterns has unnecessary kleenes
- Issue #1039⁵⁹⁴⁸ - Remove use of `Boost.Move` and replace with `std::move` and real rvalue refs
- Issue #1038⁵⁹⁴⁹ - Bump minimal required Boost to 1.49.0
- Issue #1037⁵⁹⁵⁰ - Implicit unwrapping of futures in `async` broken
- Issue #1036⁵⁹⁵¹ - Scheduler hangs when user code attempts to “block” OS-threads
- Issue #1035⁵⁹⁵² - Idle-rate counter always reports 100% idle rate
- Issue #1034⁵⁹⁵³ - Symbolic name registration causes application hangs
- Issue #1033⁵⁹⁵⁴ - Application options read in from an options file generate an error message
- Issue #1032⁵⁹⁵⁵ - `hpx::id_type` local reference counting is wrong
- Issue #1031⁵⁹⁵⁶ - Negative entry in reference count table
- Issue #1030⁵⁹⁵⁷ - Implement `condition_variable`
- Issue #1029⁵⁹⁵⁸ - Deadlock in thread scheduling subsystem
- Issue #1028⁵⁹⁵⁹ - HPX-thread cumulative count performance counters report incorrect value
- Issue #1027⁵⁹⁶⁰ - Expose `hpx::thread_interrupted` error code as a separate exception type
- Issue #1026⁵⁹⁶¹ - Exceptions thrown in asynchronous calls can be lost if the value of the future is never queried

⁵⁹³⁹ <https://github.com/TheHPXProject/hpx/issues/1048>

⁵⁹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1047>

⁵⁹⁴¹ <https://github.com/TheHPXProject/hpx/issues/1046>

⁵⁹⁴² <https://github.com/TheHPXProject/hpx/issues/1045>

⁵⁹⁴³ <https://github.com/TheHPXProject/hpx/issues/1044>

⁵⁹⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1043>

⁵⁹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1042>

⁵⁹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1041>

⁵⁹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1040>

⁵⁹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1039>

⁵⁹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1038>

⁵⁹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1037>

⁵⁹⁵¹ <https://github.com/TheHPXProject/hpx/issues/1036>

⁵⁹⁵² <https://github.com/TheHPXProject/hpx/issues/1035>

⁵⁹⁵³ <https://github.com/TheHPXProject/hpx/issues/1034>

⁵⁹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1033>

⁵⁹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1032>

⁵⁹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1031>

⁵⁹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1030>

⁵⁹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1029>

⁵⁹⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1028>

⁵⁹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1027>

⁵⁹⁶¹ <https://github.com/TheHPXProject/hpx/issues/1026>

- Issue #1025⁵⁹⁶² - `future::wait_for/wait_until` do not remove callback
- Issue #1024⁵⁹⁶³ - Remove dependence to boost assert and create hpx assert
- Issue #1023⁵⁹⁶⁴ - Segfaults with `tcmalloc`
- Issue #1022⁵⁹⁶⁵ - prerequisites link in readme is broken
- Issue #1020⁵⁹⁶⁶ - HPX Deadlock on external synchronization
- Issue #1019⁵⁹⁶⁷ - Convert using `BOOST_ASSERT` to `HPX_ASSERT`
- Issue #1018⁵⁹⁶⁸ - compiling bug with gcc 4.8.1
- Issue #1017⁵⁹⁶⁹ - Possible crash in `io_pool` executor
- Issue #1016⁵⁹⁷⁰ - Crash at startup
- Issue #1014⁵⁹⁷¹ - Implement Increment/Decrement Merging
- Issue #1013⁵⁹⁷² - Add more logging channels to enable greater control over logging granularity
- Issue #1012⁵⁹⁷³ - `--hpx:debug-hpx-log` and `--hpx:debug-agas-log` lead to non-thread safe writes
- Issue #1011⁵⁹⁷⁴ - After installation, running applications from the build/staging directory no longer works
- Issue #1010⁵⁹⁷⁵ - Mergeable decrement requests are not being merged
- Issue #1009⁵⁹⁷⁶ - `--hpx:list-symbolic-names` crashes
- Issue #1007⁵⁹⁷⁷ - Components are not properly destroyed
- Issue #1006⁵⁹⁷⁸ - Segfault/hang in `set_data`
- Issue #1003⁵⁹⁷⁹ - Performance counter naming issue
- Issue #982⁵⁹⁸⁰ - Race condition during startup
- Issue #912⁵⁹⁸¹ - OS X: component type not found in map
- Issue #663⁵⁹⁸² - Create a buildbot slave based on Clang 3.2/OSX
- Issue #636⁵⁹⁸³ - Expose `this_locality::apply<act>(p1, p2);` for local execution
- Issue #197⁵⁹⁸⁴ - Add `--console=address` option for PBS runs

⁵⁹⁶² <https://github.com/TheHPXProject/hpx/issues/1025>

⁵⁹⁶³ <https://github.com/TheHPXProject/hpx/issues/1024>

⁵⁹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1023>

⁵⁹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1022>

⁵⁹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1020>

⁵⁹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1019>

⁵⁹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1018>

⁵⁹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1017>

⁵⁹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1016>

⁵⁹⁷¹ <https://github.com/TheHPXProject/hpx/issues/1014>

⁵⁹⁷² <https://github.com/TheHPXProject/hpx/issues/1013>

⁵⁹⁷³ <https://github.com/TheHPXProject/hpx/issues/1012>

⁵⁹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1011>

⁵⁹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1010>

⁵⁹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1009>

⁵⁹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1007>

⁵⁹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1006>

⁵⁹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1003>

⁵⁹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/982>

⁵⁹⁸¹ <https://github.com/TheHPXProject/hpx/issues/912>

⁵⁹⁸² <https://github.com/TheHPXProject/hpx/issues/663>

⁵⁹⁸³ <https://github.com/TheHPXProject/hpx/issues/636>

⁵⁹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/197>

- [Issue #175⁵⁹⁸⁵](#) - Asynchronous AGAS API

HPX V0.9.7 (Nov 13, 2013)

We have had over 1000 commits since the last release and we have closed over 180 tickets (bugs, feature requests, etc.).

General changes

- Ported HPX to BlueGene/Q
- Improved HPX support for Xeon/Phi accelerators
- Reimplemented `hpx::bind`, `hpx::tuple`, and `hpx::function` for better performance and better compliance with the C++11 Standard. Added `hpx::mem_fn`.
- Reworked `hpx::when_all` and `hpx::when_any` for better compliance with the ongoing C++ standardization effort, added heterogeneous version for those functions. Added `hpx::when_any_swapped`.
- Added `hpx::copy` as a precursor for a migrate functionality
- Added `hpx::get_ptr` allowing to directly access the memory underlying a given component
- Added the `hpx::lcos::broadcast`, `hpx::lcos::reduce`, and `hpx::lcos::fold` collective operations
- Added `hpx::get_locality_name` allowing to retrieve the name of any of the localities for the application.
- Added support for more flexible thread affinity control from the HPX command line, such as new modes for `--hpx:bind` (balanced, scattered, compact), improved default settings when running multiple localities on the same node.
- Added experimental executors for simpler thread pooling and scheduling. This API may change in the future as it will stay aligned with the ongoing C++ standardization efforts.
- Massively improved the performance of the HPX serialization code. Added partial support for zero copy serialization of array and bitwise-copyable types.
- General performance improvements of the code related to threads and futures.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1005⁵⁹⁸⁶](#) - Allow one to disable array optimizations and zero copy optimizations for each parcelport
- [Issue #1004⁵⁹⁸⁷](#) - Generate new HPX logo image for the docs
- [Issue #1002⁵⁹⁸⁸](#) - If MPI parcelport is not available, running HPX under mpirun should fail
- [Issue #1001⁵⁹⁸⁹](#) - Zero copy serialization raises assert
- [Issue #1000⁵⁹⁹⁰](#) - Can't connect to a HPX application running with the MPI parcelport from a non MPI parcelport locality
- [Issue #999⁵⁹⁹¹](#) - Optimize `hpx::when_n`

⁵⁹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/175>

⁵⁹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1005>

⁵⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1004>

⁵⁹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1002>

⁵⁹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1001>

⁵⁹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1000>

⁵⁹⁹¹ <https://github.com/TheHPXProject/hpx/issues/999>

- Issue #998⁵⁹⁹² - Fixed const-correctness
- Issue #997⁵⁹⁹³ - Making `serialize_buffer::data()` type save
- Issue #996⁵⁹⁹⁴ - Memory leak in `hpx::lcos::promise`
- Issue #995⁵⁹⁹⁵ - Race while registering pre-shutdown functions
- Issue #994⁵⁹⁹⁶ - `thread_rescheduling` regression test does not compile
- Issue #992⁵⁹⁹⁷ - Correct comments and messages
- Issue #991⁵⁹⁹⁸ - `setcap cap_sys_rawio=ep` for power profiling causes an HPX application to abort
- Issue #989⁵⁹⁹⁹ - Jacobi hangs during execution
- Issue #988⁶⁰⁰⁰ - `multiple_init` test is failing
- Issue #986⁶⁰⁰¹ - Can't call a function called "init" from "main" when using `<hpx/hpx_main.hpp>`
- Issue #984⁶⁰⁰² - Reference counting tests are failing
- Issue #983⁶⁰⁰³ - `thread_suspension_executor` test fails
- Issue #980⁶⁰⁰⁴ - Terminating HPX threads don't leave stack in virgin state
- Issue #979⁶⁰⁰⁵ - Static scheduler not in documents
- Issue #978⁶⁰⁰⁶ - Preprocessing limits are broken
- Issue #977⁶⁰⁰⁷ - Make `tests.regressions.lcos.future_hang_on_get` shorter
- Issue #976⁶⁰⁰⁸ - Wrong library order in `pkgconfig`
- Issue #975⁶⁰⁰⁹ - Please reopen #963
- Issue #974⁶⁰¹⁰ - Option `pu-offset` ignored in `fixing_588` branch
- Issue #972⁶⁰¹¹ - Cannot use MKL with HPX
- Issue #969⁶⁰¹² - Non-existent INI files requested on the command line via `--hpx:config` do not cause warnings or errors.
- Issue #968⁶⁰¹³ - Cannot build examples in `fixing_588` branch
- Issue #967⁶⁰¹⁴ - Command line description of `--hpx:queuing` seems wrong

⁵⁹⁹² <https://github.com/TheHPXProject/hpx/issues/998>

⁵⁹⁹³ <https://github.com/TheHPXProject/hpx/issues/997>

⁵⁹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/996>

⁵⁹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/995>

⁵⁹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/994>

⁵⁹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/992>

⁵⁹⁹⁸ <https://github.com/TheHPXProject/hpx/issues/991>

⁵⁹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/989>

⁶⁰⁰⁰ <https://github.com/TheHPXProject/hpx/issues/988>

⁶⁰⁰¹ <https://github.com/TheHPXProject/hpx/issues/986>

⁶⁰⁰² <https://github.com/TheHPXProject/hpx/issues/984>

⁶⁰⁰³ <https://github.com/TheHPXProject/hpx/issues/983>

⁶⁰⁰⁴ <https://github.com/TheHPXProject/hpx/issues/980>

⁶⁰⁰⁵ <https://github.com/TheHPXProject/hpx/issues/979>

⁶⁰⁰⁶ <https://github.com/TheHPXProject/hpx/issues/978>

⁶⁰⁰⁷ <https://github.com/TheHPXProject/hpx/issues/977>

⁶⁰⁰⁸ <https://github.com/TheHPXProject/hpx/issues/976>

⁶⁰⁰⁹ <https://github.com/TheHPXProject/hpx/issues/975>

⁶⁰¹⁰ <https://github.com/TheHPXProject/hpx/issues/974>

⁶⁰¹¹ <https://github.com/TheHPXProject/hpx/issues/972>

⁶⁰¹² <https://github.com/TheHPXProject/hpx/issues/969>

⁶⁰¹³ <https://github.com/TheHPXProject/hpx/issues/968>

⁶⁰¹⁴ <https://github.com/TheHPXProject/hpx/issues/967>

- [Issue #966](#)⁶⁰¹⁵ - `--hpx:print-bind` physical core numbers are wrong
- [Issue #965](#)⁶⁰¹⁶ - Deadlock when building in Release mode
- [Issue #963](#)⁶⁰¹⁷ - Not all worker threads are working
- [Issue #962](#)⁶⁰¹⁸ - Problem with SLURM integration
- [Issue #961](#)⁶⁰¹⁹ - `--hpx:print-bind` outputs incorrect information
- [Issue #960](#)⁶⁰²⁰ - Fix cut and paste error in documentation of `get_thread_priority`
- [Issue #959](#)⁶⁰²¹ - Change link to `boost.atomic` in documentation to point to `boost.org`
- [Issue #958](#)⁶⁰²² - Undefined reference to `intrusive_ptr_release`
- [Issue #957](#)⁶⁰²³ - Make tuple standard compliant
- [Issue #956](#)⁶⁰²⁴ - Segfault with `a3382fb`
- [Issue #955](#)⁶⁰²⁵ - `--hpx:nodes` and `--hpx:nodefiles` do not work with foreign nodes
- [Issue #954](#)⁶⁰²⁶ - Make order of arguments for `hpx::async` and `hpx::broadcast` consistent
- [Issue #953](#)⁶⁰²⁷ - Cannot use MKL with HPX
- [Issue #952](#)⁶⁰²⁸ - `register_[pre_]shutdown_function` never throw
- [Issue #951](#)⁶⁰²⁹ - Assert when number of threads is greater than hardware concurrency
- [Issue #948](#)⁶⁰³⁰ - `HPX_HAVE_GENERIC_CONTEXT_COROUTINES` conflicts with `HPX_HAVE_FIBER_BASED_COROUTINES`
- [Issue #947](#)⁶⁰³¹ - Need `MPI_THREAD_MULTIPLE` for backward compatibility
- [Issue #946](#)⁶⁰³² - HPX does not call `MPI_Finalize`
- [Issue #945](#)⁶⁰³³ - Segfault with `hpx::lcos::broadcast`
- [Issue #944](#)⁶⁰³⁴ - OS X: assertion `pu_offset_ < hardware_concurrency` failed
- [Issue #943](#)⁶⁰³⁵ - `#include <hpx/hpx_main.hpp>` does not work
- [Issue #942](#)⁶⁰³⁶ - Make the BG/Q work with `-O3`
- [Issue #940](#)⁶⁰³⁷ - Use separator when concatenating locality name

⁶⁰¹⁵ <https://github.com/TheHPXProject/hpx/issues/966>

⁶⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/965>

⁶⁰¹⁷ <https://github.com/TheHPXProject/hpx/issues/963>

⁶⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/962>

⁶⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/961>

⁶⁰²⁰ <https://github.com/TheHPXProject/hpx/issues/960>

⁶⁰²¹ <https://github.com/TheHPXProject/hpx/issues/959>

⁶⁰²² <https://github.com/TheHPXProject/hpx/issues/958>

⁶⁰²³ <https://github.com/TheHPXProject/hpx/issues/957>

⁶⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/956>

⁶⁰²⁵ <https://github.com/TheHPXProject/hpx/issues/955>

⁶⁰²⁶ <https://github.com/TheHPXProject/hpx/issues/954>

⁶⁰²⁷ <https://github.com/TheHPXProject/hpx/issues/953>

⁶⁰²⁸ <https://github.com/TheHPXProject/hpx/issues/952>

⁶⁰²⁹ <https://github.com/TheHPXProject/hpx/issues/951>

⁶⁰³⁰ <https://github.com/TheHPXProject/hpx/issues/948>

⁶⁰³¹ <https://github.com/TheHPXProject/hpx/issues/947>

⁶⁰³² <https://github.com/TheHPXProject/hpx/issues/946>

⁶⁰³³ <https://github.com/TheHPXProject/hpx/issues/945>

⁶⁰³⁴ <https://github.com/TheHPXProject/hpx/issues/944>

⁶⁰³⁵ <https://github.com/TheHPXProject/hpx/issues/943>

⁶⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/942>

⁶⁰³⁷ <https://github.com/TheHPXProject/hpx/issues/940>

- [Issue #939](#)⁶⁰³⁸ - Refactor MPI parcellport to use `MPI_Wait` instead of multiple `MPI_Test` calls
- [Issue #938](#)⁶⁰³⁹ - Want to officially access `client_base::gid_`
- [Issue #937](#)⁶⁰⁴⁰ - `client_base::gid_` should be private`
- [Issue #936](#)⁶⁰⁴¹ - Want doxygen-like source code index
- [Issue #935](#)⁶⁰⁴² - Build error with gcc 4.6 and Boost 1.54.0 on hpx trunk and 0.9.6
- [Issue #933](#)⁶⁰⁴³ - Cannot build HPX with Boost 1.54.0
- [Issue #932](#)⁶⁰⁴⁴ - Components are destructed too early
- [Issue #931](#)⁶⁰⁴⁵ - Make HPX work on BG/Q
- [Issue #930](#)⁶⁰⁴⁶ - make git-docs is broken
- [Issue #929](#)⁶⁰⁴⁷ - Generating index in docs broken
- [Issue #928](#)⁶⁰⁴⁸ - Optimize `hpx::util::static_` for C++11 compilers supporting magic statics
- [Issue #924](#)⁶⁰⁴⁹ - Make `kill_process_tree` (in `process.py`) more robust on Mac OSX
- [Issue #923](#)⁶⁰⁵⁰ - Correct BLAS and RNPL cmake tests
- [Issue #922](#)⁶⁰⁵¹ - Cannot link against BLAS
- [Issue #921](#)⁶⁰⁵² - Implement `hpx::mem_fn`
- [Issue #920](#)⁶⁰⁵³ - Output locality with `--hpx:print-bind`
- [Issue #919](#)⁶⁰⁵⁴ - Correct grammar; simplify boolean expressions
- [Issue #918](#)⁶⁰⁵⁵ - Link to `hello_world.cpp` is broken
- [Issue #917](#)⁶⁰⁵⁶ - adapt cmake file to new boostbook version
- [Issue #916](#)⁶⁰⁵⁷ - fix problem building documentation with `xsltproc` $\geq$ 1.1.27
- [Issue #915](#)⁶⁰⁵⁸ - Add another TBBMalloc library search path
- [Issue #914](#)⁶⁰⁵⁹ - Build problem with Intel compiler on Stampede (TACC)
- [Issue #913](#)⁶⁰⁶⁰ - fix error messages in fibonacci examples

⁶⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/939>

⁶⁰³⁹ <https://github.com/TheHPXProject/hpx/issues/938>

⁶⁰⁴⁰ <https://github.com/TheHPXProject/hpx/issues/937>

⁶⁰⁴¹ <https://github.com/TheHPXProject/hpx/issues/936>

⁶⁰⁴² <https://github.com/TheHPXProject/hpx/issues/935>

⁶⁰⁴³ <https://github.com/TheHPXProject/hpx/issues/933>

⁶⁰⁴⁴ <https://github.com/TheHPXProject/hpx/issues/932>

⁶⁰⁴⁵ <https://github.com/TheHPXProject/hpx/issues/931>

⁶⁰⁴⁶ <https://github.com/TheHPXProject/hpx/issues/930>

⁶⁰⁴⁷ <https://github.com/TheHPXProject/hpx/issues/929>

⁶⁰⁴⁸ <https://github.com/TheHPXProject/hpx/issues/928>

⁶⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/924>

⁶⁰⁵⁰ <https://github.com/TheHPXProject/hpx/issues/923>

⁶⁰⁵¹ <https://github.com/TheHPXProject/hpx/issues/922>

⁶⁰⁵² <https://github.com/TheHPXProject/hpx/issues/921>

⁶⁰⁵³ <https://github.com/TheHPXProject/hpx/issues/920>

⁶⁰⁵⁴ <https://github.com/TheHPXProject/hpx/issues/919>

⁶⁰⁵⁵ <https://github.com/TheHPXProject/hpx/issues/918>

⁶⁰⁵⁶ <https://github.com/TheHPXProject/hpx/issues/917>

⁶⁰⁵⁷ <https://github.com/TheHPXProject/hpx/issues/916>

⁶⁰⁵⁸ <https://github.com/TheHPXProject/hpx/issues/915>

⁶⁰⁵⁹ <https://github.com/TheHPXProject/hpx/issues/914>

⁶⁰⁶⁰ <https://github.com/TheHPXProject/hpx/issues/913>

- Issue #911⁶⁰⁶¹ - Update OS X build instructions
- Issue #910⁶⁰⁶² - Want like to specify MPI_ROOT instead of compiler wrapper script
- Issue #909⁶⁰⁶³ - Warning about void* arithmetic
- Issue #908⁶⁰⁶⁴ - Buildbot for MIC is broken
- Issue #906⁶⁰⁶⁵ - Can't use --hpx:bind=balanced with multiple MPI processes
- Issue #905⁶⁰⁶⁶ - --hpx:bind documentation should describe full grammar
- Issue #904⁶⁰⁶⁷ - Add hpx::lcos::fold and hpx::lcos::inverse_fold collective operation
- Issue #903⁶⁰⁶⁸ - Add hpx::when_any_swapped()
- Issue #902⁶⁰⁶⁹ - Add hpx::lcos::reduce collective operation
- Issue #901⁶⁰⁷⁰ - Web documentation is not searchable
- Issue #900⁶⁰⁷¹ - Web documentation for trunk has no index
- Issue #898⁶⁰⁷² - Some tests fail with GCC 4.8.1 and MPI parcel port
- Issue #897⁶⁰⁷³ - HWLOC causes failures on Mac
- Issue #896⁶⁰⁷⁴ - pu-offset leads to startup error
- Issue #895⁶⁰⁷⁵ - hpx::get_locality_name not defined
- Issue #894⁶⁰⁷⁶ - Race condition at shutdown
- Issue #893⁶⁰⁷⁷ - --hpx:print-bind switches std::cout to hexadecimal mode
- Issue #892⁶⁰⁷⁸ - hwloc_topology_load can be expensive – don't call multiple times
- Issue #891⁶⁰⁷⁹ - The documentation for get_locality_name is wrong
- Issue #890⁶⁰⁸⁰ - --hpx:print-bind should not exit
- Issue #889⁶⁰⁸¹ - --hpx:debug-hpx-log=FILE does not work
- Issue #888⁶⁰⁸² - MPI parcelport does not exit cleanly for --hpx:print-bind
- Issue #887⁶⁰⁸³ - Choose thread affinities more cleverly

⁶⁰⁶¹ <https://github.com/TheHPXProject/hpx/issues/911>

⁶⁰⁶² <https://github.com/TheHPXProject/hpx/issues/910>

⁶⁰⁶³ <https://github.com/TheHPXProject/hpx/issues/909>

⁶⁰⁶⁴ <https://github.com/TheHPXProject/hpx/issues/908>

⁶⁰⁶⁵ <https://github.com/TheHPXProject/hpx/issues/906>

⁶⁰⁶⁶ <https://github.com/TheHPXProject/hpx/issues/905>

⁶⁰⁶⁷ <https://github.com/TheHPXProject/hpx/issues/904>

⁶⁰⁶⁸ <https://github.com/TheHPXProject/hpx/issues/903>

⁶⁰⁶⁹ <https://github.com/TheHPXProject/hpx/issues/902>

⁶⁰⁷⁰ <https://github.com/TheHPXProject/hpx/issues/901>

⁶⁰⁷¹ <https://github.com/TheHPXProject/hpx/issues/900>

⁶⁰⁷² <https://github.com/TheHPXProject/hpx/issues/898>

⁶⁰⁷³ <https://github.com/TheHPXProject/hpx/issues/897>

⁶⁰⁷⁴ <https://github.com/TheHPXProject/hpx/issues/896>

⁶⁰⁷⁵ <https://github.com/TheHPXProject/hpx/issues/895>

⁶⁰⁷⁶ <https://github.com/TheHPXProject/hpx/issues/894>

⁶⁰⁷⁷ <https://github.com/TheHPXProject/hpx/issues/893>

⁶⁰⁷⁸ <https://github.com/TheHPXProject/hpx/issues/892>

⁶⁰⁷⁹ <https://github.com/TheHPXProject/hpx/issues/891>

⁶⁰⁸⁰ <https://github.com/TheHPXProject/hpx/issues/890>

⁶⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/889>

⁶⁰⁸² <https://github.com/TheHPXProject/hpx/issues/888>

⁶⁰⁸³ <https://github.com/TheHPXProject/hpx/issues/887>

- Issue #886⁶⁰⁸⁴ - Logging documentation is confusing
- Issue #885⁶⁰⁸⁵ - Two threads are slower than one
- Issue #884⁶⁰⁸⁶ - `is_callable` failing with member pointers in C++11
- Issue #883⁶⁰⁸⁷ - Need help with `is_callable_test`
- Issue #882⁶⁰⁸⁸ - `tests.regressions.lcos.future_hang_on_get` does not terminate
- Issue #881⁶⁰⁸⁹ - `tests.regressions/block_matrix/matrix.hh` won't compile with GCC 4.8.1
- Issue #880⁶⁰⁹⁰ - HPX does not work on OS X
- Issue #878⁶⁰⁹¹ - `future::unwrap` triggers assertion
- Issue #877⁶⁰⁹² - “make tests” has build errors on Ubuntu 12.10
- Issue #876⁶⁰⁹³ - `tcmalloc` is used by default, even if it is not present
- Issue #875⁶⁰⁹⁴ - `global_fixture` is defined in a header file
- Issue #874⁶⁰⁹⁵ - Some tests take very long
- Issue #873⁶⁰⁹⁶ - Add block-matrix code as regression test
- Issue #872⁶⁰⁹⁷ - HPX documentation does not say how to run tests with detailed output
- Issue #871⁶⁰⁹⁸ - All tests fail with “make test”
- Issue #870⁶⁰⁹⁹ - Please explicitly disable serialization in classes that don't support it
- Issue #868⁶¹⁰⁰ - `boost_any` test failing
- Issue #867⁶¹⁰¹ - Reduce the number of copies of `hpx::function` arguments
- Issue #863⁶¹⁰² - Futures should not require a default constructor
- Issue #862⁶¹⁰³ - `value_or_error` shall not default construct its result
- Issue #861⁶¹⁰⁴ - `HPX_UNUSED` macro
- Issue #860⁶¹⁰⁵ - Add functionality to copy construct a component
- Issue #859⁶¹⁰⁶ - `hpx::endl` should flush

⁶⁰⁸⁴ <https://github.com/TheHPXProject/hpx/issues/886>

⁶⁰⁸⁵ <https://github.com/TheHPXProject/hpx/issues/885>

⁶⁰⁸⁶ <https://github.com/TheHPXProject/hpx/issues/884>

⁶⁰⁸⁷ <https://github.com/TheHPXProject/hpx/issues/883>

⁶⁰⁸⁸ <https://github.com/TheHPXProject/hpx/issues/882>

⁶⁰⁸⁹ <https://github.com/TheHPXProject/hpx/issues/881>

⁶⁰⁹⁰ <https://github.com/TheHPXProject/hpx/issues/880>

⁶⁰⁹¹ <https://github.com/TheHPXProject/hpx/issues/878>

⁶⁰⁹² <https://github.com/TheHPXProject/hpx/issues/877>

⁶⁰⁹³ <https://github.com/TheHPXProject/hpx/issues/876>

⁶⁰⁹⁴ <https://github.com/TheHPXProject/hpx/issues/875>

⁶⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/874>

⁶⁰⁹⁶ <https://github.com/TheHPXProject/hpx/issues/873>

⁶⁰⁹⁷ <https://github.com/TheHPXProject/hpx/issues/872>

⁶⁰⁹⁸ <https://github.com/TheHPXProject/hpx/issues/871>

⁶⁰⁹⁹ <https://github.com/TheHPXProject/hpx/issues/870>

⁶¹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/868>

⁶¹⁰¹ <https://github.com/TheHPXProject/hpx/issues/867>

⁶¹⁰² <https://github.com/TheHPXProject/hpx/issues/863>

⁶¹⁰³ <https://github.com/TheHPXProject/hpx/issues/862>

⁶¹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/861>

⁶¹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/860>

⁶¹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/859>

- [Issue #858](#)⁶¹⁰⁷ - Create `hpx::get_ptr<>` allowing to access component implementation
- [Issue #855](#)⁶¹⁰⁸ - Implement `hpx::INVOKE`
- [Issue #854](#)⁶¹⁰⁹ - `hpx/hpx.hpp` does not include `hpx/include/iostreams.hpp`
- [Issue #853](#)⁶¹¹⁰ - Feature request: null future
- [Issue #852](#)⁶¹¹¹ - Feature request: Locality names
- [Issue #851](#)⁶¹¹² - `hpx::cout` output does not appear on screen
- [Issue #849](#)⁶¹¹³ - All tests fail on OS X after installing
- [Issue #848](#)⁶¹¹⁴ - Update OS X build instructions
- [Issue #846](#)⁶¹¹⁵ - Update `hpx_external_example`
- [Issue #845](#)⁶¹¹⁶ - Issues with having both debug and release modules in the same directory
- [Issue #844](#)⁶¹¹⁷ - Create configuration header
- [Issue #843](#)⁶¹¹⁸ - Tests should use CTest
- [Issue #842](#)⁶¹¹⁹ - Remove `buffer_pool` from MPI parcelport
- [Issue #841](#)⁶¹²⁰ - Add possibility to broadcast an index with `hpx::lcos::broadcast`
- [Issue #838](#)⁶¹²¹ - Simplify `util::tuple`
- [Issue #837](#)⁶¹²² - Adopt `boost::tuple` tests for `util::tuple`
- [Issue #836](#)⁶¹²³ - Adopt `boost::function` tests for `util::function`
- [Issue #835](#)⁶¹²⁴ - Tuple interface missing pieces
- [Issue #833](#)⁶¹²⁵ - Partially preprocessing files not working
- [Issue #832](#)⁶¹²⁶ - Native papi counters do not work with wild cards
- [Issue #831](#)⁶¹²⁷ - Arithmetics counter fails if only one parameter is given
- [Issue #830](#)⁶¹²⁸ - Convert `hpx::util::function` to use new scheme for serializing its base pointer
- [Issue #829](#)⁶¹²⁹ - Consistently use `decay<T>` instead of `remove_const< remove_reference<T>>`

⁶¹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/858>

⁶¹⁰⁸ <https://github.com/TheHPXProject/hpx/issues/855>

⁶¹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/854>

⁶¹¹⁰ <https://github.com/TheHPXProject/hpx/issues/853>

⁶¹¹¹ <https://github.com/TheHPXProject/hpx/issues/852>

⁶¹¹² <https://github.com/TheHPXProject/hpx/issues/851>

⁶¹¹³ <https://github.com/TheHPXProject/hpx/issues/849>

⁶¹¹⁴ <https://github.com/TheHPXProject/hpx/issues/848>

⁶¹¹⁵ <https://github.com/TheHPXProject/hpx/issues/846>

⁶¹¹⁶ <https://github.com/TheHPXProject/hpx/issues/845>

⁶¹¹⁷ <https://github.com/TheHPXProject/hpx/issues/844>

⁶¹¹⁸ <https://github.com/TheHPXProject/hpx/issues/843>

⁶¹¹⁹ <https://github.com/TheHPXProject/hpx/issues/842>

⁶¹²⁰ <https://github.com/TheHPXProject/hpx/issues/841>

⁶¹²¹ <https://github.com/TheHPXProject/hpx/issues/838>

⁶¹²² <https://github.com/TheHPXProject/hpx/issues/837>

⁶¹²³ <https://github.com/TheHPXProject/hpx/issues/836>

⁶¹²⁴ <https://github.com/TheHPXProject/hpx/issues/835>

⁶¹²⁵ <https://github.com/TheHPXProject/hpx/issues/833>

⁶¹²⁶ <https://github.com/TheHPXProject/hpx/issues/832>

⁶¹²⁷ <https://github.com/TheHPXProject/hpx/issues/831>

⁶¹²⁸ <https://github.com/TheHPXProject/hpx/issues/830>

⁶¹²⁹ <https://github.com/TheHPXProject/hpx/issues/829>

- Issue #828⁶¹³⁰ - Update future implementation to N3721 and N3722
- Issue #827⁶¹³¹ - Enable MPI parcellport for bootstrapping whenever application was started using mpirun
- Issue #826⁶¹³² - Support command line option `--hpx:print-bind` even if `--hpx::bind` was not used
- Issue #825⁶¹³³ - Memory counters give segfault when attempting to use thread wild cards or numbers only total works
- Issue #824⁶¹³⁴ - Enable lambda functions to be used with `hpx::async/hpx::apply`
- Issue #823⁶¹³⁵ - Using a hashing filter
- Issue #822⁶¹³⁶ - Silence unused variable warning
- Issue #821⁶¹³⁷ - Detect if a function object is callable with given arguments
- Issue #820⁶¹³⁸ - Allow wildcards to be used for performance counter names
- Issue #819⁶¹³⁹ - Make the AGAS symbolic name registry distributed
- Issue #818⁶¹⁴⁰ - Add `future::then()` overload taking an executor
- Issue #817⁶¹⁴¹ - Fixed typo
- Issue #815⁶¹⁴² - Create an lco that is performing an efficient broadcast of actions
- Issue #814⁶¹⁴³ - Papi counters cannot specify `thread#*` to get the counts for all threads
- Issue #813⁶¹⁴⁴ - Scoped unlock
- Issue #811⁶¹⁴⁵ - `simple_central_tuplespace_client` run error
- Issue #810⁶¹⁴⁶ - ostream error when `<<` any objects
- Issue #809⁶¹⁴⁷ - Optimize parcel serialization
- Issue #808⁶¹⁴⁸ - HPX applications throw exception when executed from the build directory
- Issue #807⁶¹⁴⁹ - Create performance counters exposing overall AGAS statistics
- Issue #795⁶¹⁵⁰ - Create timed `make_ready_future`
- Issue #794⁶¹⁵¹ - Create heterogeneous `when_all/when_any/etc.`
- Issue #721⁶¹⁵² - Make HPX usable for Xeon Phi

⁶¹³⁰ <https://github.com/TheHPXProject/hpx/issues/828>

⁶¹³¹ <https://github.com/TheHPXProject/hpx/issues/827>

⁶¹³² <https://github.com/TheHPXProject/hpx/issues/826>

⁶¹³³ <https://github.com/TheHPXProject/hpx/issues/825>

⁶¹³⁴ <https://github.com/TheHPXProject/hpx/issues/824>

⁶¹³⁵ <https://github.com/TheHPXProject/hpx/issues/823>

⁶¹³⁶ <https://github.com/TheHPXProject/hpx/issues/822>

⁶¹³⁷ <https://github.com/TheHPXProject/hpx/issues/821>

⁶¹³⁸ <https://github.com/TheHPXProject/hpx/issues/820>

⁶¹³⁹ <https://github.com/TheHPXProject/hpx/issues/819>

⁶¹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/818>

⁶¹⁴¹ <https://github.com/TheHPXProject/hpx/issues/817>

⁶¹⁴² <https://github.com/TheHPXProject/hpx/issues/815>

⁶¹⁴³ <https://github.com/TheHPXProject/hpx/issues/814>

⁶¹⁴⁴ <https://github.com/TheHPXProject/hpx/issues/813>

⁶¹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/811>

⁶¹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/810>

⁶¹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/809>

⁶¹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/808>

⁶¹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/807>

⁶¹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/795>

⁶¹⁵¹ <https://github.com/TheHPXProject/hpx/issues/794>

⁶¹⁵² <https://github.com/TheHPXProject/hpx/issues/721>

- [Issue #694](#)⁶¹⁵³ - CMake should complain if you attempt to build an example without its dependencies
- [Issue #692](#)⁶¹⁵⁴ - SLURM support broken
- [Issue #683](#)⁶¹⁵⁵ - python/hpx/process.py imports epoll on all platforms
- [Issue #619](#)⁶¹⁵⁶ - Automate the doc building process
- [Issue #600](#)⁶¹⁵⁷ - GTC performance broken
- [Issue #577](#)⁶¹⁵⁸ - Allow for zero copy serialization/networking
- [Issue #551](#)⁶¹⁵⁹ - Change executable names to have debug postfix in Debug builds
- [Issue #544](#)⁶¹⁶⁰ - Write a custom .lib file on Windows pulling in hpx_init and hpx.dll, phase out hpx_init
- [Issue #534](#)⁶¹⁶¹ - `hpx::init` should take functions by `std::function` and should accept all forms of `hpx_main`
- [Issue #508](#)⁶¹⁶² - FindPackage fails to set FOO_LIBRARY_DIR
- [Issue #506](#)⁶¹⁶³ - Add cmake support to generate ini files for external applications
- [Issue #470](#)⁶¹⁶⁴ - Changing build-type after configure does not update boost library names
- [Issue #453](#)⁶¹⁶⁵ - Document `hpx_run_tests.py`
- [Issue #445](#)⁶¹⁶⁶ - Significant performance mismatch between MPI and HPX in SMP for allgather example
- [Issue #443](#)⁶¹⁶⁷ - Make docs viewable from build directory
- [Issue #421](#)⁶¹⁶⁸ - Support multiple HPX instances per node in a batch environment like PBS or SLURM
- [Issue #316](#)⁶¹⁶⁹ - Add message size limitation
- [Issue #249](#)⁶¹⁷⁰ - Clean up locking code in big boot barrier
- [Issue #136](#)⁶¹⁷¹ - Persistent CMake variables need to be marked as cache variables

⁶¹⁵³ <https://github.com/TheHPXProject/hpx/issues/694>

⁶¹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/692>

⁶¹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/683>

⁶¹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/619>

⁶¹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/600>

⁶¹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/577>

⁶¹⁵⁹ <https://github.com/TheHPXProject/hpx/issues/551>

⁶¹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/544>

⁶¹⁶¹ <https://github.com/TheHPXProject/hpx/issues/534>

⁶¹⁶² <https://github.com/TheHPXProject/hpx/issues/508>

⁶¹⁶³ <https://github.com/TheHPXProject/hpx/issues/506>

⁶¹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/470>

⁶¹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/453>

⁶¹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/445>

⁶¹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/443>

⁶¹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/421>

⁶¹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/316>

⁶¹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/249>

⁶¹⁷¹ <https://github.com/TheHPXProject/hpx/issues/136>

HPX V0.9.6 (Jul 30, 2013)

We have had over 1200 commits since the last release and we have closed roughly 140 tickets (bugs, feature requests, etc.).

General changes

The major new features in this release are:

- We further consolidated the API exposed by *HPX*. We aligned our APIs as much as possible with the existing [C++11 Standard](http://www.open-std.org/jtc1/sc22/wg21)⁶¹⁷² and related proposals to the C++ standardization committee (such as [N3632](http://wg21.link/n3632)⁶¹⁷³ and [N3857](http://wg21.link/n3857)⁶¹⁷⁴).
- We implemented a first version of a distributed AGAS service which essentially eliminates all explicit AGAS network traffic.
- We created a native *ibverbs* *parcelport* allowing to take advantage of the superior latency and bandwidth characteristics of *Infiniband* networks.
- We successfully ported *HPX* to the Xeon Phi platform.
- Support for the SLURM scheduling system was implemented.
- Major efforts have been dedicated to improving the performance counter framework, numerous new counters were implemented and new APIs were added.
- We added a modular parcel compression system allowing to improve bandwidth utilization (by reducing the overall size of the transferred data).
- We added a modular parcel coalescing system allowing to combine several parcels into larger messages. This reduces latencies introduced by the communication layer.
- Added an experimental executors API allowing to use different scheduling policies for different parts of the code. This API has been modelled after the Standards proposal [N3562](http://wg21.link/n3562)⁶¹⁷⁵. This API is bound to change in the future, though.
- Added minimal security support for localities which is enforced on the *parcelport* level. This support is preliminary and experimental and might change in the future.
- We created a *parcelport* using low level MPI functions. This is in support of legacy applications which are to be gradually ported and to support platforms where MPI is the only available portable networking layer.
- We added a preliminary and experimental implementation of a tuple-space object which exposes an interface similar to such systems described in the literature (see for instance [The Linda Coordination Language](https://en.wikipedia.org/wiki/Linda_(coordination_language))⁶¹⁷⁶).

⁶¹⁷² <http://www.open-std.org/jtc1/sc22/wg21>

⁶¹⁷³ <http://wg21.link/n3632>

⁶¹⁷⁴ <http://wg21.link/n3857>

⁶¹⁷⁵ <http://wg21.link/n3562>

⁶¹⁷⁶ [https://en.wikipedia.org/wiki/Linda_\(coordination_language\)](https://en.wikipedia.org/wiki/Linda_(coordination_language))

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release. This is again a very long list of newly implemented features and fixed issues.

- [Issue #806](#)⁶¹⁷⁷ - make (all) in examples folder does nothing
- [Issue #805](#)⁶¹⁷⁸ - Adding the introduction and fixing DOCTEST dependencies for Windows use
- [Issue #804](#)⁶¹⁷⁹ - Add stackless (non-suspendable) thread type
- [Issue #803](#)⁶¹⁸⁰ - Create proper serialization support functions for util::tuple
- [Issue #800](#)⁶¹⁸¹ - Add possibility to disable array optimizations during serialization
- [Issue #798](#)⁶¹⁸² - HPX_LIMIT does not work for local dataflow
- [Issue #797](#)⁶¹⁸³ - Create a parcelport which uses MPI
- [Issue #796](#)⁶¹⁸⁴ - Problem with Large Numbers of Threads
- [Issue #793](#)⁶¹⁸⁵ - Changing dataflow test case to hang consistently
- [Issue #792](#)⁶¹⁸⁶ - CMake Error
- [Issue #791](#)⁶¹⁸⁷ - Problems with local::dataflow
- [Issue #790](#)⁶¹⁸⁸ - wait_for() doesn't compile
- [Issue #789](#)⁶¹⁸⁹ - HPX with Intel compiler segfaults
- [Issue #788](#)⁶¹⁹⁰ - Intel compiler support
- [Issue #787](#)⁶¹⁹¹ - Fixed SFINAE specializations
- [Issue #786](#)⁶¹⁹² - Memory issues during benchmarking.
- [Issue #785](#)⁶¹⁹³ - Create an API allowing to register external threads with HPX
- [Issue #784](#)⁶¹⁹⁴ - util::plugin is throwing an error when a symbol is not found
- [Issue #783](#)⁶¹⁹⁵ - How does hpx::bind work?
- [Issue #782](#)⁶¹⁹⁶ - Added quotes around STRING REPLACE potentially empty arguments
- [Issue #781](#)⁶¹⁹⁷ - Make sure no exceptions propagate into the thread manager

⁶¹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/806>

⁶¹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/805>

⁶¹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/804>

⁶¹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/803>

⁶¹⁸¹ <https://github.com/TheHPXProject/hpx/issues/800>

⁶¹⁸² <https://github.com/TheHPXProject/hpx/issues/798>

⁶¹⁸³ <https://github.com/TheHPXProject/hpx/issues/797>

⁶¹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/796>

⁶¹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/793>

⁶¹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/792>

⁶¹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/791>

⁶¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/790>

⁶¹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/789>

⁶¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/788>

⁶¹⁹¹ <https://github.com/TheHPXProject/hpx/issues/787>

⁶¹⁹² <https://github.com/TheHPXProject/hpx/issues/786>

⁶¹⁹³ <https://github.com/TheHPXProject/hpx/issues/785>

⁶¹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/784>

⁶¹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/783>

⁶¹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/782>

⁶¹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/781>

- [Issue #780](#)⁶¹⁹⁸ - Allow arithmetics performance counters to expand its parameters
- [Issue #779](#)⁶¹⁹⁹ - Test case for 778
- [Issue #778](#)⁶²⁰⁰ - Swapping futures segfaults
- [Issue #777](#)⁶²⁰¹ - `hpx::lcos::details::when_XXX` don't restore completion handlers
- [Issue #776](#)⁶²⁰² - Compiler chokes on dataflow overload with launch policy
- [Issue #775](#)⁶²⁰³ - Runtime error with local dataflow (copying futures?)
- [Issue #774](#)⁶²⁰⁴ - Using local dataflow without explicit namespace
- [Issue #773](#)⁶²⁰⁵ - Local dataflow with unwrap: functor operators need to be const
- [Issue #772](#)⁶²⁰⁶ - Allow (remote) actions to return a future
- [Issue #771](#)⁶²⁰⁷ - Setting `HPX_LIMIT` gives huge boost MPL errors
- [Issue #770](#)⁶²⁰⁸ - Add launch policy to (local) dataflow
- [Issue #769](#)⁶²⁰⁹ - Make compile time configuration information available
- [Issue #768](#)⁶²¹⁰ - Const correctness problem in local dataflow
- [Issue #767](#)⁶²¹¹ - Add launch policies to async
- [Issue #766](#)⁶²¹² - Mark data structures for optimized (array based) serialization
- [Issue #765](#)⁶²¹³ - Align `hpx::any` with N3508: Any Library Proposal (Revision 2)
- [Issue #764](#)⁶²¹⁴ - Align `hpx::future` with newest N3558: A Standardized Representation of Asynchronous Operations
- [Issue #762](#)⁶²¹⁵ - added a human readable output for the ping pong example
- [Issue #761](#)⁶²¹⁶ - Ambiguous typename when constructing derived component
- [Issue #760](#)⁶²¹⁷ - Simple components can not be derived
- [Issue #759](#)⁶²¹⁸ - make install doesn't give a complete install
- [Issue #758](#)⁶²¹⁹ - Stack overflow when using `locking_hook<>`
- [Issue #757](#)⁶²²⁰ - copy paste error; unsupported function overloading

⁶¹⁹⁸ <https://github.com/TheHPXProject/hpx/issues/780>

⁶¹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/779>

⁶²⁰⁰ <https://github.com/TheHPXProject/hpx/issues/778>

⁶²⁰¹ <https://github.com/TheHPXProject/hpx/issues/777>

⁶²⁰² <https://github.com/TheHPXProject/hpx/issues/776>

⁶²⁰³ <https://github.com/TheHPXProject/hpx/issues/775>

⁶²⁰⁴ <https://github.com/TheHPXProject/hpx/issues/774>

⁶²⁰⁵ <https://github.com/TheHPXProject/hpx/issues/773>

⁶²⁰⁶ <https://github.com/TheHPXProject/hpx/issues/772>

⁶²⁰⁷ <https://github.com/TheHPXProject/hpx/issues/771>

⁶²⁰⁸ <https://github.com/TheHPXProject/hpx/issues/770>

⁶²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/769>

⁶²¹⁰ <https://github.com/TheHPXProject/hpx/issues/768>

⁶²¹¹ <https://github.com/TheHPXProject/hpx/issues/767>

⁶²¹² <https://github.com/TheHPXProject/hpx/issues/766>

⁶²¹³ <https://github.com/TheHPXProject/hpx/issues/765>

⁶²¹⁴ <https://github.com/TheHPXProject/hpx/issues/764>

⁶²¹⁵ <https://github.com/TheHPXProject/hpx/issues/762>

⁶²¹⁶ <https://github.com/TheHPXProject/hpx/issues/761>

⁶²¹⁷ <https://github.com/TheHPXProject/hpx/issues/760>

⁶²¹⁸ <https://github.com/TheHPXProject/hpx/issues/759>

⁶²¹⁹ <https://github.com/TheHPXProject/hpx/issues/758>

⁶²²⁰ <https://github.com/TheHPXProject/hpx/issues/757>

- Issue #756⁶²²¹ - GTCX runtime issue in Gordon
- Issue #755⁶²²² - Papi counters don't work with reset and evaluate API's
- Issue #753⁶²²³ - cmake bugfix and improved component action docs
- Issue #752⁶²²⁴ - hpx simple component docs
- Issue #750⁶²²⁵ - Add hpx::util::any
- Issue #749⁶²²⁶ - Thread phase counter is not reset
- Issue #748⁶²²⁷ - Memory performance counter are not registered
- Issue #747⁶²²⁸ - Create performance counters exposing arithmetic operations
- Issue #745⁶²²⁹ - apply_callback needs to invoke callback when applied locally
- Issue #744⁶²³⁰ - CMake fixes
- Issue #743⁶²³¹ - Problem Building github version of HPX
- Issue #742⁶²³² - Remove HPX_STD_BIND
- Issue #741⁶²³³ - assertion 'px != 0' failed: HPX(assertion_failure) for low numbers of OS threads
- Issue #739⁶²³⁴ - Performance counters do not count to the end of the program or evaluation
- Issue #738⁶²³⁵ - Dedicated AGAS server runs don't work; console ignores -a option.
- Issue #737⁶²³⁶ - Missing bind overloads
- Issue #736⁶²³⁷ - Performance counter wildcards do not always work
- Issue #735⁶²³⁸ - Create native ibverbs parcelport based on rdma operations
- Issue #734⁶²³⁹ - Threads stolen performance counter total is incorrect
- Issue #733⁶²⁴⁰ - Test benchmarks need to be checked and fixed
- Issue #732⁶²⁴¹ - Build fails with Mac, using mac ports clang-3.3 on latest git branch
- Issue #731⁶²⁴² - Add global start/stop API for performance counters
- Issue #730⁶²⁴³ - Performance counter values are apparently incorrect

⁶²²¹ <https://github.com/TheHPXProject/hpx/issues/756>

⁶²²² <https://github.com/TheHPXProject/hpx/issues/755>

⁶²²³ <https://github.com/TheHPXProject/hpx/issues/753>

⁶²²⁴ <https://github.com/TheHPXProject/hpx/issues/752>

⁶²²⁵ <https://github.com/TheHPXProject/hpx/issues/750>

⁶²²⁶ <https://github.com/TheHPXProject/hpx/issues/749>

⁶²²⁷ <https://github.com/TheHPXProject/hpx/issues/748>

⁶²²⁸ <https://github.com/TheHPXProject/hpx/issues/747>

⁶²²⁹ <https://github.com/TheHPXProject/hpx/issues/745>

⁶²³⁰ <https://github.com/TheHPXProject/hpx/issues/744>

⁶²³¹ <https://github.com/TheHPXProject/hpx/issues/743>

⁶²³² <https://github.com/TheHPXProject/hpx/issues/742>

⁶²³³ <https://github.com/TheHPXProject/hpx/issues/741>

⁶²³⁴ <https://github.com/TheHPXProject/hpx/issues/739>

⁶²³⁵ <https://github.com/TheHPXProject/hpx/issues/738>

⁶²³⁶ <https://github.com/TheHPXProject/hpx/issues/737>

⁶²³⁷ <https://github.com/TheHPXProject/hpx/issues/736>

⁶²³⁸ <https://github.com/TheHPXProject/hpx/issues/735>

⁶²³⁹ <https://github.com/TheHPXProject/hpx/issues/734>

⁶²⁴⁰ <https://github.com/TheHPXProject/hpx/issues/733>

⁶²⁴¹ <https://github.com/TheHPXProject/hpx/issues/732>

⁶²⁴² <https://github.com/TheHPXProject/hpx/issues/731>

⁶²⁴³ <https://github.com/TheHPXProject/hpx/issues/730>

- Issue #729⁶²⁴⁴ - Unhandled switch
- Issue #728⁶²⁴⁵ - Serialization of `hpx::util::function` between two localities causes seg faults
- Issue #727⁶²⁴⁶ - Memory counters on Mac OS X
- Issue #725⁶²⁴⁷ - Restore original thread priority on resume
- Issue #724⁶²⁴⁸ - Performance benchmarks do not depend on main HPX libraries
- Issue #723⁶²⁴⁹ - `[teletype]-hpx:nodes=`cat $PBS_NODEFILE`` works; `-hpx:nodefile=$PBS_NODEFILE` does not.`[c++]`
- Issue #722⁶²⁵⁰ - Fix binding `const` member functions as actions
- Issue #719⁶²⁵¹ - Create performance counter exposing compression ratio
- Issue #718⁶²⁵² - Add possibility to compress parcel data
- Issue #717⁶²⁵³ - `strip_credit_from_gid` has misleading semantics
- Issue #716⁶²⁵⁴ - Non-option arguments to programs run using `pbsdsh` must be before `--hpx:nodes`, contrary to directions
- Issue #715⁶²⁵⁵ - Re-thrown exceptions should retain the original call site
- Issue #714⁶²⁵⁶ - failed assertion in debug mode
- Issue #713⁶²⁵⁷ - Add performance counters monitoring connection caches
- Issue #712⁶²⁵⁸ - Adjust parcel related performance counters to be connection type specific
- Issue #711⁶²⁵⁹ - configuration failure
- Issue #710⁶²⁶⁰ - Error “timed out while trying to find room in the connection cache” when trying to start multiple localities on a single computer
- Issue #709⁶²⁶¹ - Add new thread state ‘staged’ referring to task descriptions
- Issue #708⁶²⁶² - Detect/mitigate bad non-system installs of GCC on Redhat systems
- Issue #707⁶²⁶³ - Many examples do not link with Git HEAD version
- Issue #706⁶²⁶⁴ - `hpx::init` removes portions of non-option command line arguments before last = sign
- Issue #705⁶²⁶⁵ - Create rolling average and median aggregating performance counters

⁶²⁴⁴ <https://github.com/TheHPXProject/hpx/issues/729>

⁶²⁴⁵ <https://github.com/TheHPXProject/hpx/issues/728>

⁶²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/727>

⁶²⁴⁷ <https://github.com/TheHPXProject/hpx/issues/725>

⁶²⁴⁸ <https://github.com/TheHPXProject/hpx/issues/724>

⁶²⁴⁹ <https://github.com/TheHPXProject/hpx/issues/723>

⁶²⁵⁰ <https://github.com/TheHPXProject/hpx/issues/722>

⁶²⁵¹ <https://github.com/TheHPXProject/hpx/issues/719>

⁶²⁵² <https://github.com/TheHPXProject/hpx/issues/718>

⁶²⁵³ <https://github.com/TheHPXProject/hpx/issues/717>

⁶²⁵⁴ <https://github.com/TheHPXProject/hpx/issues/716>

⁶²⁵⁵ <https://github.com/TheHPXProject/hpx/issues/715>

⁶²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/714>

⁶²⁵⁷ <https://github.com/TheHPXProject/hpx/issues/713>

⁶²⁵⁸ <https://github.com/TheHPXProject/hpx/issues/712>

⁶²⁵⁹ <https://github.com/TheHPXProject/hpx/issues/711>

⁶²⁶⁰ <https://github.com/TheHPXProject/hpx/issues/710>

⁶²⁶¹ <https://github.com/TheHPXProject/hpx/issues/709>

⁶²⁶² <https://github.com/TheHPXProject/hpx/issues/708>

⁶²⁶³ <https://github.com/TheHPXProject/hpx/issues/707>

⁶²⁶⁴ <https://github.com/TheHPXProject/hpx/issues/706>

⁶²⁶⁵ <https://github.com/TheHPXProject/hpx/issues/705>

- [Issue #704](#)⁶²⁶⁶ - Create performance counter to expose thread queue waiting time
- [Issue #703](#)⁶²⁶⁷ - Add support to HPX build system to find librcrttool.a and related headers
- [Issue #699](#)⁶²⁶⁸ - Generalize instrumentation support
- [Issue #698](#)⁶²⁶⁹ - compilation failure with hwloc absent
- [Issue #697](#)⁶²⁷⁰ - Performance counter counts should be zero indexed
- [Issue #696](#)⁶²⁷¹ - Distributed problem
- [Issue #695](#)⁶²⁷² - Bad perf counter time printed
- [Issue #693](#)⁶²⁷³ - --help doesn't print component specific command line options
- [Issue #692](#)⁶²⁷⁴ - SLURM support broken
- [Issue #691](#)⁶²⁷⁵ - exception while executing any application linked with hwloc
- [Issue #690](#)⁶²⁷⁶ - thread_id_test and thread_launcher_test failing
- [Issue #689](#)⁶²⁷⁷ - Make the buildbots use hwloc
- [Issue #687](#)⁶²⁷⁸ - compilation error fix (hwloc_topology)
- [Issue #686](#)⁶²⁷⁹ - Linker Error for Applications
- [Issue #684](#)⁶²⁸⁰ - Pinning of service thread fails when number of worker threads equals the number of cores
- [Issue #682](#)⁶²⁸¹ - Add performance counters exposing number of stolen threads
- [Issue #681](#)⁶²⁸² - Add apply_continue for asynchronous chaining of actions
- [Issue #679](#)⁶²⁸³ - Remove obsolete async_callback API functions
- [Issue #678](#)⁶²⁸⁴ - Add new API for setting/triggering LCOs
- [Issue #677](#)⁶²⁸⁵ - Add async_continue for true continuation style actions
- [Issue #676](#)⁶²⁸⁶ - Buildbot for gcc 4.4 broken
- [Issue #675](#)⁶²⁸⁷ - Partial preprocessing broken
- [Issue #674](#)⁶²⁸⁸ - HPX segfaults when built with gcc 4.7

⁶²⁶⁶ <https://github.com/TheHPXProject/hpx/issues/704>

⁶²⁶⁷ <https://github.com/TheHPXProject/hpx/issues/703>

⁶²⁶⁸ <https://github.com/TheHPXProject/hpx/issues/699>

⁶²⁶⁹ <https://github.com/TheHPXProject/hpx/issues/698>

⁶²⁷⁰ <https://github.com/TheHPXProject/hpx/issues/697>

⁶²⁷¹ <https://github.com/TheHPXProject/hpx/issues/696>

⁶²⁷² <https://github.com/TheHPXProject/hpx/issues/695>

⁶²⁷³ <https://github.com/TheHPXProject/hpx/issues/693>

⁶²⁷⁴ <https://github.com/TheHPXProject/hpx/issues/692>

⁶²⁷⁵ <https://github.com/TheHPXProject/hpx/issues/691>

⁶²⁷⁶ <https://github.com/TheHPXProject/hpx/issues/690>

⁶²⁷⁷ <https://github.com/TheHPXProject/hpx/issues/689>

⁶²⁷⁸ <https://github.com/TheHPXProject/hpx/issues/687>

⁶²⁷⁹ <https://github.com/TheHPXProject/hpx/issues/686>

⁶²⁸⁰ <https://github.com/TheHPXProject/hpx/issues/684>

⁶²⁸¹ <https://github.com/TheHPXProject/hpx/issues/682>

⁶²⁸² <https://github.com/TheHPXProject/hpx/issues/681>

⁶²⁸³ <https://github.com/TheHPXProject/hpx/issues/679>

⁶²⁸⁴ <https://github.com/TheHPXProject/hpx/issues/678>

⁶²⁸⁵ <https://github.com/TheHPXProject/hpx/issues/677>

⁶²⁸⁶ <https://github.com/TheHPXProject/hpx/issues/676>

⁶²⁸⁷ <https://github.com/TheHPXProject/hpx/issues/675>

⁶²⁸⁸ <https://github.com/TheHPXProject/hpx/issues/674>

- Issue #673⁶²⁸⁹ - `use_guard_pages` has inconsistent preprocessor guards
- Issue #672⁶²⁹⁰ - External build breaks if library path has spaces
- Issue #671⁶²⁹¹ - release tarballs are tarbombs
- Issue #670⁶²⁹² - CMake won't find Boost headers in layout=versioned install
- Issue #669⁶²⁹³ - Links in docs to source files broken if not installed
- Issue #667⁶²⁹⁴ - Not reading ini file properly
- Issue #664⁶²⁹⁵ - Adapt new meanings of 'const' and 'mutable'
- Issue #661⁶²⁹⁶ - Implement BTL Parcel port
- Issue #655⁶²⁹⁷ - Make HPX work with the "decltype" result_of
- Issue #647⁶²⁹⁸ - documentation for specifying the number of high priority threads
--hpx:high-priority-threads
- Issue #643⁶²⁹⁹ - Error parsing host file
- Issue #642⁶³⁰⁰ - HWLoc issue with TAU
- Issue #639⁶³⁰¹ - Logging potentially suspends a running thread
- Issue #634⁶³⁰² - Improve error reporting from parcel layer
- Issue #627⁶³⁰³ - Add tests for async and apply overloads that accept regular C++ functions
- Issue #626⁶³⁰⁴ - hpx/future.hpp header
- Issue #601⁶³⁰⁵ - Intel support
- Issue #557⁶³⁰⁶ - Remove action codes
- Issue #531⁶³⁰⁷ - AGAS request and response classes should use switch statements
- Issue #529⁶³⁰⁸ - Investigate the state of hwloc support
- Issue #526⁶³⁰⁹ - Make HPX aware of hyper-threading
- Issue #518⁶³¹⁰ - Create facilities allowing to use plain arrays as action arguments
- Issue #473⁶³¹¹ - hwloc thread binding is broken on CPUs with hyperthreading

⁶²⁸⁹ <https://github.com/TheHPXProject/hpx/issues/673>

⁶²⁹⁰ <https://github.com/TheHPXProject/hpx/issues/672>

⁶²⁹¹ <https://github.com/TheHPXProject/hpx/issues/671>

⁶²⁹² <https://github.com/TheHPXProject/hpx/issues/670>

⁶²⁹³ <https://github.com/TheHPXProject/hpx/issues/669>

⁶²⁹⁴ <https://github.com/TheHPXProject/hpx/issues/667>

⁶²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/664>

⁶²⁹⁶ <https://github.com/TheHPXProject/hpx/issues/661>

⁶²⁹⁷ <https://github.com/TheHPXProject/hpx/issues/655>

⁶²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/647>

⁶²⁹⁹ <https://github.com/TheHPXProject/hpx/issues/643>

⁶³⁰⁰ <https://github.com/TheHPXProject/hpx/issues/642>

⁶³⁰¹ <https://github.com/TheHPXProject/hpx/issues/639>

⁶³⁰² <https://github.com/TheHPXProject/hpx/issues/634>

⁶³⁰³ <https://github.com/TheHPXProject/hpx/issues/627>

⁶³⁰⁴ <https://github.com/TheHPXProject/hpx/issues/626>

⁶³⁰⁵ <https://github.com/TheHPXProject/hpx/issues/601>

⁶³⁰⁶ <https://github.com/TheHPXProject/hpx/issues/557>

⁶³⁰⁷ <https://github.com/TheHPXProject/hpx/issues/531>

⁶³⁰⁸ <https://github.com/TheHPXProject/hpx/issues/529>

⁶³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/526>

⁶³¹⁰ <https://github.com/TheHPXProject/hpx/issues/518>

⁶³¹¹ <https://github.com/TheHPXProject/hpx/issues/473>

- [Issue #383](#)⁶³¹² - Change result type detection for `hpx::util::bind` to use `result_of` protocol
- [Issue #341](#)⁶³¹³ - Consolidate route code
- [Issue #219](#)⁶³¹⁴ - Only copy arguments into actions once
- [Issue #177](#)⁶³¹⁵ - Implement distributed AGAS
- [Issue #43](#)⁶³¹⁶ - Support for Darwin (Xcode + Clang)

HPX V0.9.5 (Jan 16, 2013)

We have had over 1000 commits since the last release and we have closed roughly 150 tickets (bugs, feature requests, etc.).

General changes

This release is continuing along the lines of code and API consolidation, and overall usability improvements. We dedicated much attention to performance and we were able to significantly improve the threading and networking subsystems.

We successfully ported *HPX* to the Android platform. *HPX* applications now not only can run on mobile devices, but we support heterogeneous applications running across architecture boundaries. At the Supercomputing Conference 2012 we demonstrated connecting Android tablets to simulations running on a Linux cluster. The Android tablet was used to query performance counters from the Linux simulation and to steer its parameters.

We successfully ported *HPX* to Mac OSX (using the Clang compiler). Thanks to Pyry Jähkölä for contributing the corresponding patches. Please see the section `macos_installation` for more details.

We made a special effort to make *HPX* usable in highly concurrent use cases. Many of the *HPX* API functions which possibly take longer than 100 microseconds to execute now can be invoked asynchronously. We added uniform support for composing futures which simplifies to write asynchronous code. *HPX* actions (function objects encapsulating possibly concurrent remote function invocations) are now well integrated with all other API facilities such like `hpx::bind`.

All of the API has been aligned as much as possible with established paradigms. *HPX* now mirrors many of the facilities as defined in the C++11 Standard, such as `hpx::thread`, `hpx::function`, `hpx::future`, etc.

A lot of work has been put into improving the documentation. Many of the API functions are documented now, concepts are explained in detail, and examples are better described than before. The new documentation index enables finding information with lesser effort.

This is the first release of *HPX* we perform after the move to [Github](#)⁶³¹⁷. This step has enabled a wider participation from the community and further encourages us in our decision to release *HPX* as a true open source library (*HPX* is licensed under the very liberal [Boost Software License](#)⁶³¹⁸).

⁶³¹² <https://github.com/TheHPXProject/hpx/issues/383>

⁶³¹³ <https://github.com/TheHPXProject/hpx/issues/341>

⁶³¹⁴ <https://github.com/TheHPXProject/hpx/issues/219>

⁶³¹⁵ <https://github.com/TheHPXProject/hpx/issues/177>

⁶³¹⁶ <https://github.com/TheHPXProject/hpx/issues/43>

⁶³¹⁷ <https://github.com/TheHPXProject/hpx/>

⁶³¹⁸ https://www.boost.org/LICENSE_1_0.txt

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release. This is by far the longest list of newly implemented features and fixed issues for any of HPX' releases so far.

- [Issue #666](#)⁶³¹⁹ - Segfault on calling `hpx::finalize` twice
- [Issue #665](#)⁶³²⁰ - Adding declaration `num_of_cores`
- [Issue #662](#)⁶³²¹ - `pkgconfig` is building wrong
- [Issue #660](#)⁶³²² - Need `uninterrupt` function
- [Issue #659](#)⁶³²³ - Move our logging library into a different namespace
- [Issue #658](#)⁶³²⁴ - Dynamic performance counter types are broken
- [Issue #657](#)⁶³²⁵ - HPX v0.9.5 (RC1) `hello_world` example segfaulting
- [Issue #656](#)⁶³²⁶ - Define the affinity of `parcel-pool`, `io-pool`, and `timer-pool` threads
- [Issue #654](#)⁶³²⁷ - Integrate the Boost `auto_index` tool with documentation
- [Issue #653](#)⁶³²⁸ - Make HPX build on OS X + Clang + `libc++`
- [Issue #651](#)⁶³²⁹ - Add fine-grained control for thread pinning
- [Issue #650](#)⁶³³⁰ - Command line no error message when using `-hpx:(anything)`
- [Issue #645](#)⁶³³¹ - Command line aliases don't work in `[teletype]`@file`[c++]`
- [Issue #644](#)⁶³³² - Terminated threads are not always properly cleaned up
- [Issue #640](#)⁶³³³ - `future_data<T>::set_on_completed_` used without locks
- [Issue #638](#)⁶³³⁴ - `hpx` build with intel compilers fails on linux
- [Issue #637](#)⁶³³⁵ - `-copy-dt-needed-entries` breaks with gold
- [Issue #635](#)⁶³³⁶ - Boost V1.53 will add `Boost.Lockfree` and `Boost.Atomic`
- [Issue #633](#)⁶³³⁷ - Re-add examples to final 0.9.5 release
- [Issue #632](#)⁶³³⁸ - Example `thread_aware_timer` is broken
- [Issue #631](#)⁶³³⁹ - FFT application throws error in `parcellayer`

⁶³¹⁹ <https://github.com/TheHPXProject/hpx/issues/666>

⁶³²⁰ <https://github.com/TheHPXProject/hpx/issues/665>

⁶³²¹ <https://github.com/TheHPXProject/hpx/issues/662>

⁶³²² <https://github.com/TheHPXProject/hpx/issues/660>

⁶³²³ <https://github.com/TheHPXProject/hpx/issues/659>

⁶³²⁴ <https://github.com/TheHPXProject/hpx/issues/658>

⁶³²⁵ <https://github.com/TheHPXProject/hpx/issues/657>

⁶³²⁶ <https://github.com/TheHPXProject/hpx/issues/656>

⁶³²⁷ <https://github.com/TheHPXProject/hpx/issues/654>

⁶³²⁸ <https://github.com/TheHPXProject/hpx/issues/653>

⁶³²⁹ <https://github.com/TheHPXProject/hpx/issues/651>

⁶³³⁰ <https://github.com/TheHPXProject/hpx/issues/650>

⁶³³¹ <https://github.com/TheHPXProject/hpx/issues/645>

⁶³³² <https://github.com/TheHPXProject/hpx/issues/644>

⁶³³³ <https://github.com/TheHPXProject/hpx/issues/640>

⁶³³⁴ <https://github.com/TheHPXProject/hpx/issues/638>

⁶³³⁵ <https://github.com/TheHPXProject/hpx/issues/637>

⁶³³⁶ <https://github.com/TheHPXProject/hpx/issues/635>

⁶³³⁷ <https://github.com/TheHPXProject/hpx/issues/633>

⁶³³⁸ <https://github.com/TheHPXProject/hpx/issues/632>

⁶³³⁹ <https://github.com/TheHPXProject/hpx/issues/631>

- [Issue #630](#)⁶³⁴⁰ - Event synchronization example is broken
- [Issue #629](#)⁶³⁴¹ - Waiting on futures hangs
- [Issue #628](#)⁶³⁴² - Add an HPX_ALWAYS_ASSERT macro
- [Issue #625](#)⁶³⁴³ - Port coroutines context switch benchmark
- [Issue #621](#)⁶³⁴⁴ - New INI section for stack sizes
- [Issue #618](#)⁶³⁴⁵ - pkg_config support does not work with a HPX debug build
- [Issue #617](#)⁶³⁴⁶ - hpx/external/logging/boost/logging/detail/cache_before_init.hpp:139:67: error: 'get_thread_id' was not declared in this scope
- [Issue #616](#)⁶³⁴⁷ - Change wait_xxx not to use locking
- [Issue #615](#)⁶³⁴⁸ - Revert visibility 'fix' (fb0b6b8245dad1127b0c25ebafd9386b3945cca9)
- [Issue #614](#)⁶³⁴⁹ - Fix Dataflow linker error
- [Issue #613](#)⁶³⁵⁰ - find_here should throw an exception on failure
- [Issue #612](#)⁶³⁵¹ - Thread phase doesn't show up in debug mode
- [Issue #611](#)⁶³⁵² - Make stack guard pages configurable at runtime (initialization time)
- [Issue #610](#)⁶³⁵³ - Co-Locate Components
- [Issue #609](#)⁶³⁵⁴ - future_overhead
- [Issue #608](#)⁶³⁵⁵ - --hpx:list-counter-infos problem
- [Issue #607](#)⁶³⁵⁶ - Update Boost.Context based backend for coroutines
- [Issue #606](#)⁶³⁵⁷ - 1d_wave_equation is not working
- [Issue #605](#)⁶³⁵⁸ - Any C++ function that has serializable arguments and a serializable return type should be re-motable
- [Issue #604](#)⁶³⁵⁹ - Connecting localities isn't working anymore
- [Issue #603](#)⁶³⁶⁰ - Do not verify any ini entries read from a file
- [Issue #602](#)⁶³⁶¹ - Rename argument_size to type_size/ added implementation to get parcel size

⁶³⁴⁰ <https://github.com/TheHPXProject/hpx/issues/630>

⁶³⁴¹ <https://github.com/TheHPXProject/hpx/issues/629>

⁶³⁴² <https://github.com/TheHPXProject/hpx/issues/628>

⁶³⁴³ <https://github.com/TheHPXProject/hpx/issues/625>

⁶³⁴⁴ <https://github.com/TheHPXProject/hpx/issues/621>

⁶³⁴⁵ <https://github.com/TheHPXProject/hpx/issues/618>

⁶³⁴⁶ <https://github.com/TheHPXProject/hpx/issues/617>

⁶³⁴⁷ <https://github.com/TheHPXProject/hpx/issues/616>

⁶³⁴⁸ <https://github.com/TheHPXProject/hpx/issues/615>

⁶³⁴⁹ <https://github.com/TheHPXProject/hpx/issues/614>

⁶³⁵⁰ <https://github.com/TheHPXProject/hpx/issues/613>

⁶³⁵¹ <https://github.com/TheHPXProject/hpx/issues/612>

⁶³⁵² <https://github.com/TheHPXProject/hpx/issues/611>

⁶³⁵³ <https://github.com/TheHPXProject/hpx/issues/610>

⁶³⁵⁴ <https://github.com/TheHPXProject/hpx/issues/609>

⁶³⁵⁵ <https://github.com/TheHPXProject/hpx/issues/608>

⁶³⁵⁶ <https://github.com/TheHPXProject/hpx/issues/607>

⁶³⁵⁷ <https://github.com/TheHPXProject/hpx/issues/606>

⁶³⁵⁸ <https://github.com/TheHPXProject/hpx/issues/605>

⁶³⁵⁹ <https://github.com/TheHPXProject/hpx/issues/604>

⁶³⁶⁰ <https://github.com/TheHPXProject/hpx/issues/603>

⁶³⁶¹ <https://github.com/TheHPXProject/hpx/issues/602>

- Issue #599⁶³⁶² - Enable locality specific command line options
- Issue #598⁶³⁶³ - Need an API that accesses the performance counter reporting the system uptime
- Issue #597⁶³⁶⁴ - compiling on ranger
- Issue #595⁶³⁶⁵ - I need a place to store data in a thread self pointer
- Issue #594⁶³⁶⁶ - 32/64 interoperability
- Issue #593⁶³⁶⁷ - Warn if logging is disabled at compile time but requested at runtime
- Issue #592⁶³⁶⁸ - Add optional argument value to `--hpx:list-counters` and `--hpx:list-counter-infos`
- Issue #591⁶³⁶⁹ - Allow for wildcards in performance counter names specified with `--hpx:print-counter`
- Issue #590⁶³⁷⁰ - Local promise semantic differences
- Issue #589⁶³⁷¹ - Create API to query performance counter names
- Issue #587⁶³⁷² - Add `get_num_localities` and `get_num_threads` to AGAS API
- Issue #586⁶³⁷³ - Adjust local AGAS cache size based on number of localities
- Issue #585⁶³⁷⁴ - Error while using counters in HPX
- Issue #584⁶³⁷⁵ - counting argument size of actions, initial pass.
- Issue #581⁶³⁷⁶ - Remove `RemoteResult` template parameter for `future<>`
- Issue #580⁶³⁷⁷ - Add possibility to hook into actions
- Issue #578⁶³⁷⁸ - Use angle brackets in HPX error dumps
- Issue #576⁶³⁷⁹ - Exception incorrectly thrown when `--help` is used
- Issue #575⁶³⁸⁰ - `HPX(bad_component_type)` with gcc 4.7.2 and boost 1.51
- Issue #574⁶³⁸¹ - `--hpx:connect` command line parameter not working correctly
- Issue #571⁶³⁸² - `hpx::wait()` (callback version) should pass the future to the callback function
- Issue #570⁶³⁸³ - `hpx::wait` should operate on `boost::arrays` and `std::lists`
- Issue #569⁶³⁸⁴ - Add a logging sink for Android

⁶³⁶² <https://github.com/TheHPXProject/hpx/issues/599>

⁶³⁶³ <https://github.com/TheHPXProject/hpx/issues/598>

⁶³⁶⁴ <https://github.com/TheHPXProject/hpx/issues/597>

⁶³⁶⁵ <https://github.com/TheHPXProject/hpx/issues/595>

⁶³⁶⁶ <https://github.com/TheHPXProject/hpx/issues/594>

⁶³⁶⁷ <https://github.com/TheHPXProject/hpx/issues/593>

⁶³⁶⁸ <https://github.com/TheHPXProject/hpx/issues/592>

⁶³⁶⁹ <https://github.com/TheHPXProject/hpx/issues/591>

⁶³⁷⁰ <https://github.com/TheHPXProject/hpx/issues/590>

⁶³⁷¹ <https://github.com/TheHPXProject/hpx/issues/589>

⁶³⁷² <https://github.com/TheHPXProject/hpx/issues/587>

⁶³⁷³ <https://github.com/TheHPXProject/hpx/issues/586>

⁶³⁷⁴ <https://github.com/TheHPXProject/hpx/issues/585>

⁶³⁷⁵ <https://github.com/TheHPXProject/hpx/issues/584>

⁶³⁷⁶ <https://github.com/TheHPXProject/hpx/issues/581>

⁶³⁷⁷ <https://github.com/TheHPXProject/hpx/issues/580>

⁶³⁷⁸ <https://github.com/TheHPXProject/hpx/issues/578>

⁶³⁷⁹ <https://github.com/TheHPXProject/hpx/issues/576>

⁶³⁸⁰ <https://github.com/TheHPXProject/hpx/issues/575>

⁶³⁸¹ <https://github.com/TheHPXProject/hpx/issues/574>

⁶³⁸² <https://github.com/TheHPXProject/hpx/issues/571>

⁶³⁸³ <https://github.com/TheHPXProject/hpx/issues/570>

⁶³⁸⁴ <https://github.com/TheHPXProject/hpx/issues/569>

- [Issue #568](#)⁶³⁸⁵ - 2-argument version of HPX_DEFINE_COMPONENT_ACTION
- [Issue #567](#)⁶³⁸⁶ - Connecting to a running HPX application works only once
- [Issue #565](#)⁶³⁸⁷ - HPX doesn't shutdown properly
- [Issue #564](#)⁶³⁸⁸ - Partial preprocessing of new component creation interface
- [Issue #563](#)⁶³⁸⁹ - Add `hpx::start/hpx::stop` to avoid blocking main thread
- [Issue #562](#)⁶³⁹⁰ - All command line arguments swallowed by hpx
- [Issue #561](#)⁶³⁹¹ - Boost.Tuple is not move aware
- [Issue #558](#)⁶³⁹² - `boost::shared_ptr<>` style semantics/syntax for client classes
- [Issue #556](#)⁶³⁹³ - Creation of partially preprocessed headers should be enabled for Boost newer than V1.50
- [Issue #555](#)⁶³⁹⁴ - BOOST_FORCEINLINE does not name a type
- [Issue #554](#)⁶³⁹⁵ - Possible race condition in thread `get_id()`
- [Issue #552](#)⁶³⁹⁶ - Move enable `client_base`
- [Issue #550](#)⁶³⁹⁷ - Add stack size category 'huge'
- [Issue #549](#)⁶³⁹⁸ - ShenEOS run seg-faults on single or distributed runs
- [Issue #545](#)⁶³⁹⁹ - AUTOGLOB broken for `add_hpx_component`
- [Issue #542](#)⁶⁴⁰⁰ - FindHPX_HDF5 still searches multiple times
- [Issue #541](#)⁶⁴⁰¹ - Quotes around application name in `hpx::init`
- [Issue #539](#)⁶⁴⁰² - Race condition occurring with new lightweight threads
- [Issue #535](#)⁶⁴⁰³ - `hpx_run_tests.py` exits with no error code when tests are missing
- [Issue #530](#)⁶⁴⁰⁴ - Thread description(<unknown>) in logs
- [Issue #523](#)⁶⁴⁰⁵ - Make thread objects more lightweight
- [Issue #521](#)⁶⁴⁰⁶ - `hpx::error_code` is not usable for lightweight error handling
- [Issue #520](#)⁶⁴⁰⁷ - Add full user environment to HPX logs

⁶³⁸⁵ <https://github.com/TheHPXProject/hpx/issues/568>

⁶³⁸⁶ <https://github.com/TheHPXProject/hpx/issues/567>

⁶³⁸⁷ <https://github.com/TheHPXProject/hpx/issues/565>

⁶³⁸⁸ <https://github.com/TheHPXProject/hpx/issues/564>

⁶³⁸⁹ <https://github.com/TheHPXProject/hpx/issues/563>

⁶³⁹⁰ <https://github.com/TheHPXProject/hpx/issues/562>

⁶³⁹¹ <https://github.com/TheHPXProject/hpx/issues/561>

⁶³⁹² <https://github.com/TheHPXProject/hpx/issues/558>

⁶³⁹³ <https://github.com/TheHPXProject/hpx/issues/556>

⁶³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/555>

⁶³⁹⁵ <https://github.com/TheHPXProject/hpx/issues/554>

⁶³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/552>

⁶³⁹⁷ <https://github.com/TheHPXProject/hpx/issues/550>

⁶³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/549>

⁶³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/545>

⁶⁴⁰⁰ <https://github.com/TheHPXProject/hpx/issues/542>

⁶⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/541>

⁶⁴⁰² <https://github.com/TheHPXProject/hpx/issues/539>

⁶⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/535>

⁶⁴⁰⁴ <https://github.com/TheHPXProject/hpx/issues/530>

⁶⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/523>

⁶⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/521>

⁶⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/520>

- [Issue #519](#)⁶⁴⁰⁸ - Build succeeds, running fails
- [Issue #517](#)⁶⁴⁰⁹ - Add a guard page to linux coroutine stacks
- [Issue #516](#)⁶⁴¹⁰ - `hpx::thread::detach` suspends while holding locks, leads to hang in debug
- [Issue #514](#)⁶⁴¹¹ - Preprocessed headers for `<hpx/apply.hpp>` don't compile
- [Issue #513](#)⁶⁴¹² - Buildbot configuration problem
- [Issue #512](#)⁶⁴¹³ - Implement action based stack size customization
- [Issue #511](#)⁶⁴¹⁴ - Move action priority into a separate type trait
- [Issue #510](#)⁶⁴¹⁵ - trunk broken
- [Issue #507](#)⁶⁴¹⁶ - no matching function for call to `boost::scoped_ptr<hpx::threads::topology>::scoped_ptr(hpx::threads::topology)`
- [Issue #505](#)⁶⁴¹⁷ - `undefined_symbol` regression test currently failing
- [Issue #502](#)⁶⁴¹⁸ - Adding OpenCL and OCLM support to HPX for Windows and Linux
- [Issue #501](#)⁶⁴¹⁹ - `find_package(HPX)` sets cmake output variables
- [Issue #500](#)⁶⁴²⁰ - `wait_any/wait_all` are badly named
- [Issue #499](#)⁶⁴²¹ - Add support for disabling pbs support in pbs runs
- [Issue #498](#)⁶⁴²² - Error during no-cache runs
- [Issue #496](#)⁶⁴²³ - Add partial preprocessing support to cmake
- [Issue #495](#)⁶⁴²⁴ - Support HPX modules exporting startup/shutdown functions only
- [Issue #494](#)⁶⁴²⁵ - Allow modules to specify when to run startup/shutdown functions
- [Issue #493](#)⁶⁴²⁶ - Avoid constructing a string in `make_success_code`
- [Issue #492](#)⁶⁴²⁷ - Performance counter creation is no longer synchronized at startup
- [Issue #491](#)⁶⁴²⁸ - Performance counter creation is no longer synchronized at startup
- [Issue #490](#)⁶⁴²⁹ - Sheneos on `_completed_bulk` seg fault in distributed
- [Issue #489](#)⁶⁴³⁰ - compiling issue with `g++44`

⁶⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/519>

⁶⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/517>

⁶⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/516>

⁶⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/514>

⁶⁴¹² <https://github.com/TheHPXProject/hpx/issues/513>

⁶⁴¹³ <https://github.com/TheHPXProject/hpx/issues/512>

⁶⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/511>

⁶⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/510>

⁶⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/507>

⁶⁴¹⁷ <https://github.com/TheHPXProject/hpx/issues/505>

⁶⁴¹⁸ <https://github.com/TheHPXProject/hpx/issues/502>

⁶⁴¹⁹ <https://github.com/TheHPXProject/hpx/issues/501>

⁶⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/500>

⁶⁴²¹ <https://github.com/TheHPXProject/hpx/issues/499>

⁶⁴²² <https://github.com/TheHPXProject/hpx/issues/498>

⁶⁴²³ <https://github.com/TheHPXProject/hpx/issues/496>

⁶⁴²⁴ <https://github.com/TheHPXProject/hpx/issues/495>

⁶⁴²⁵ <https://github.com/TheHPXProject/hpx/issues/494>

⁶⁴²⁶ <https://github.com/TheHPXProject/hpx/issues/493>

⁶⁴²⁷ <https://github.com/TheHPXProject/hpx/issues/492>

⁶⁴²⁸ <https://github.com/TheHPXProject/hpx/issues/491>

⁶⁴²⁹ <https://github.com/TheHPXProject/hpx/issues/490>

⁶⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/489>

- Issue #488⁶⁴³¹ - Adding OpenCL and OCLM support to HPX for the MSVC platform
- Issue #487⁶⁴³² - FindHPX.cmake problems
- Issue #485⁶⁴³³ - Change distributing_factory and binpacking_factory to use bulk creation
- Issue #484⁶⁴³⁴ - Change HPX_DONT_USE_PREPROCESSED_FILES to HPX_USE_PREPROCESSED_FILES
- Issue #483⁶⁴³⁵ - Memory counter for Windows
- Issue #479⁶⁴³⁶ - strange errors appear when requesting performance counters on multiple nodes
- Issue #477⁶⁴³⁷ - Create (global) timer for multi-threaded measurements
- Issue #472⁶⁴³⁸ - Add partial preprocessing using Wave
- Issue #471⁶⁴³⁹ - Segfault stack traces don't show up in release
- Issue #468⁶⁴⁴⁰ - External projects need to link with internal components
- Issue #462⁶⁴⁴¹ - Startup/shutdown functions are called more than once
- Issue #458⁶⁴⁴² - Consolidate hpx::util::high_resolution_timer and hpx::util::high_resolution_clock
- Issue #457⁶⁴⁴³ - index out of bounds in allgather_and_gate on 4 cores or more
- Issue #448⁶⁴⁴⁴ - Make HPX compile with clang
- Issue #447⁶⁴⁴⁵ - 'make tests' should execute tests on local installation
- Issue #446⁶⁴⁴⁶ - Remove SVN-related code from the codebase
- Issue #444⁶⁴⁴⁷ - race condition in smp
- Issue #441⁶⁴⁴⁸ - Patched Boost.Serialization headers should only be installed if needed
- Issue #439⁶⁴⁴⁹ - Components using HPX_REGISTER_STARTUP_MODULE fail to compile with MSVC
- Issue #436⁶⁴⁵⁰ - Verify that no locks are being held while threads are suspended
- Issue #435⁶⁴⁵¹ - Installing HPX should not clobber existing Boost installation
- Issue #434⁶⁴⁵² - Logging external component failed (Boost 1.50)
- Issue #433⁶⁴⁵³ - Runtime crash when building all examples

⁶⁴³¹ <https://github.com/TheHPXProject/hpx/issues/488>

⁶⁴³² <https://github.com/TheHPXProject/hpx/issues/487>

⁶⁴³³ <https://github.com/TheHPXProject/hpx/issues/485>

⁶⁴³⁴ <https://github.com/TheHPXProject/hpx/issues/484>

⁶⁴³⁵ <https://github.com/TheHPXProject/hpx/issues/483>

⁶⁴³⁶ <https://github.com/TheHPXProject/hpx/issues/479>

⁶⁴³⁷ <https://github.com/TheHPXProject/hpx/issues/477>

⁶⁴³⁸ <https://github.com/TheHPXProject/hpx/issues/472>

⁶⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/471>

⁶⁴⁴⁰ <https://github.com/TheHPXProject/hpx/issues/468>

⁶⁴⁴¹ <https://github.com/TheHPXProject/hpx/issues/462>

⁶⁴⁴² <https://github.com/TheHPXProject/hpx/issues/458>

⁶⁴⁴³ <https://github.com/TheHPXProject/hpx/issues/457>

⁶⁴⁴⁴ <https://github.com/TheHPXProject/hpx/issues/448>

⁶⁴⁴⁵ <https://github.com/TheHPXProject/hpx/issues/447>

⁶⁴⁴⁶ <https://github.com/TheHPXProject/hpx/issues/446>

⁶⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/444>

⁶⁴⁴⁸ <https://github.com/TheHPXProject/hpx/issues/441>

⁶⁴⁴⁹ <https://github.com/TheHPXProject/hpx/issues/439>

⁶⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/436>

⁶⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/435>

⁶⁴⁵² <https://github.com/TheHPXProject/hpx/issues/434>

⁶⁴⁵³ <https://github.com/TheHPXProject/hpx/issues/433>

- Issue #432⁶⁴⁵⁴ - Dataflow hangs on 512 cores/64 nodes
- Issue #430⁶⁴⁵⁵ - Problem with distributing factory
- Issue #424⁶⁴⁵⁶ - File paths referring to XSL-files need to be properly escaped
- Issue #417⁶⁴⁵⁷ - Make dataflow LCOs work out of the box by using partial preprocessing
- Issue #413⁶⁴⁵⁸ - hpx_svnversion.py fails on Windows
- Issue #412⁶⁴⁵⁹ - Make hpx::error_code equivalent to hpx::exception
- Issue #398⁶⁴⁶⁰ - HPX clobbers out-of-tree application specific CMake variables (specifically CMAKE_BUILD_TYPE)
- Issue #394⁶⁴⁶¹ - Remove code generating random port numbers for network
- Issue #378⁶⁴⁶² - ShenEOS scaling issues
- Issue #354⁶⁴⁶³ - Create a coroutines wrapper for Boost.Context
- Issue #349⁶⁴⁶⁴ - Commandline option --localities=N/-lN should be necessary only on AGAS locality
- Issue #334⁶⁴⁶⁵ - Add auto_index support to cmake based documentation toolchain
- Issue #318⁶⁴⁶⁶ - Network benchmarks
- Issue #317⁶⁴⁶⁷ - Implement network performance counters
- Issue #310⁶⁴⁶⁸ - Duplicate logging entries
- Issue #230⁶⁴⁶⁹ - Add compile time option to disable thread debugging info
- Issue #171⁶⁴⁷⁰ - Add an INI option to turn off deadlock detection independently of logging
- Issue #170⁶⁴⁷¹ - OSHL internal counters are incorrect
- Issue #103⁶⁴⁷² - Better diagnostics for multiple component/action registrations under the same name
- Issue #48⁶⁴⁷³ - Support for Darwin (Xcode + Clang)
- Issue #21⁶⁴⁷⁴ - Build fails with GCC 4.6

⁶⁴⁵⁴ <https://github.com/TheHPXProject/hpx/issues/432>

⁶⁴⁵⁵ <https://github.com/TheHPXProject/hpx/issues/430>

⁶⁴⁵⁶ <https://github.com/TheHPXProject/hpx/issues/424>

⁶⁴⁵⁷ <https://github.com/TheHPXProject/hpx/issues/417>

⁶⁴⁵⁸ <https://github.com/TheHPXProject/hpx/issues/413>

⁶⁴⁵⁹ <https://github.com/TheHPXProject/hpx/issues/412>

⁶⁴⁶⁰ <https://github.com/TheHPXProject/hpx/issues/398>

⁶⁴⁶¹ <https://github.com/TheHPXProject/hpx/issues/394>

⁶⁴⁶² <https://github.com/TheHPXProject/hpx/issues/378>

⁶⁴⁶³ <https://github.com/TheHPXProject/hpx/issues/354>

⁶⁴⁶⁴ <https://github.com/TheHPXProject/hpx/issues/349>

⁶⁴⁶⁵ <https://github.com/TheHPXProject/hpx/issues/334>

⁶⁴⁶⁶ <https://github.com/TheHPXProject/hpx/issues/318>

⁶⁴⁶⁷ <https://github.com/TheHPXProject/hpx/issues/317>

⁶⁴⁶⁸ <https://github.com/TheHPXProject/hpx/issues/310>

⁶⁴⁶⁹ <https://github.com/TheHPXProject/hpx/issues/230>

⁶⁴⁷⁰ <https://github.com/TheHPXProject/hpx/issues/171>

⁶⁴⁷¹ <https://github.com/TheHPXProject/hpx/issues/170>

⁶⁴⁷² <https://github.com/TheHPXProject/hpx/issues/103>

⁶⁴⁷³ <https://github.com/TheHPXProject/hpx/issues/48>

⁶⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/21>

HPX V0.9.0 (Jul 5, 2012)

We have had roughly 800 commits since the last release and we have closed approximately 80 tickets (bugs, feature requests, etc.).

General changes

- Significant improvements made to the usability of *HPX* in large-scale, distributed environments.
- Renamed `hpx::lcos::packaged_task` to `hpx::lcos::packaged_action` to reflect the semantic differences to a `packaged_task` as defined by the C++11 Standard⁶⁴⁷⁵.
- *HPX* now exposes `hpx::thread` which is compliant to the C++11 `std::thread` type except that it (purely locally) represents an *HPX* thread. This new type does not expose any of the remote capabilities of the underlying *HPX*-thread implementation.
- The type `hpx::lcos::future` is now compliant to the C++11 `std::future<>` type. This type can be used to synchronize both, local and remote operations. In both cases the control flow will ‘return’ to the future in order to trigger any continuation.
- The types `hpx::lcos::local::promise` and `hpx::lcos::local::packaged_task` are now compliant to the C++11 `std::promise<>` and `std::packaged_task<>` types. These can be used to create a future representing local work only. Use the types `hpx::lcos::promise` and `hpx::lcos::packaged_action` to wrap any (possibly remote) action into a future.
- `hpx::thread` and `hpx::lcos::future` are now cancelable.
- Added support for sequential and logic composition of `hpx::lcos::futures`. The member function `hpx::lcos::future::when` permits futures to be sequentially composed. The helper functions `hpx::wait_all`, `hpx::wait_any`, and `hpx::wait_n` can be used to wait for more than one future at a time.
- *HPX* now exposes `hpx::apply` and `hpx::async` as the preferred way of creating (or invoking) any deferred work. These functions are usable with various types of functions, function objects, and actions and provide a uniform way to spawn deferred tasks.
- *HPX* now utilizes `hpx::util::bind` to (partially) bind local functions and function objects, and also actions. Remote bound actions can have placeholders as well.
- *HPX* continuations are now fully polymorphic. The class `hpx::actions::forwarding_continuation` is an example of how the user can write its own types of continuations. It can be used to execute any function as an continuation of a particular action.
- Reworked the action invocation API to be fully conformant to normal functions. Actions can now be invoked using `hpx::apply`, `hpx::async`, or using the `operator()` implemented on actions. Actions themselves can now be cheaply instantiated as they do not have any members anymore.
- Reworked the lazy action invocation API. Actions can now be directly bound using `hpx::util::bind` by passing an action instance as the first argument.
- A minimal *HPX* program now looks like this:

```
#include <hpx/hpx_init.hpp>

int hpx_main()
{
    return hpx::finalize();
}
```

(continues on next page)

⁶⁴⁷⁵ <http://www.open-std.org/jtc1/sc22/wg21>

(continued from previous page)

```
int main()
{
    return hpx::init();
}
```

This removes the immediate dependency on the `Boost.Program_options`⁶⁴⁷⁶ library.

Note: This minimal version of an *HPX* program does not support any of the default command line arguments (such as `-help`, or command line options related to PBS). It is suggested to always pass `argc` and `argv` to *HPX* as shown in the example below.

- In order to support those, but still not to depend on `Boost.Program_options`⁶⁴⁷⁷, the minimal program can be written as:

```
#include <hpx/hpx_init.hpp>

// The arguments for hpx_main can be left off, which very similar to the
// behavior of ``main()`` as defined by C++.
int hpx_main(int argc, char* argv[])
{
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::init(argc, argv);
}
```

- Added performance counters exposing the number of component instances which are alive on a given locality.
- Added performance counters exposing then number of messages sent and received, the number of parcels sent and received, the number of bytes sent and received, the overall time required to send and receive data, and the overall time required to serialize and deserialize the data.
- Added a new component: `hpx::components::binpacking_factory` which is equivalent to the existing `hpx::components::distributing_factory` component, except that it equalizes the overall population of the components to create. It exposes two factory methods, one based on the number of existing instances of the component type to create, and one based on an arbitrary performance counter which will be queried for all relevant localities.
- Added API functions allowing to access elements of the diagnostic information embedded in the given exception: `hpx::get_locality_id`, `hpx::get_host_name`, `hpx::get_process_id`, `hpx::get_function_name`, `hpx::get_file_name`, `hpx::get_line_number`, `hpx::get_os_thread`, `hpx::get_thread_id`, and `hpx::get_thread_description`.

⁶⁴⁷⁶ https://www.boost.org/doc/html/program_options.html

⁶⁴⁷⁷ https://www.boost.org/doc/html/program_options.html

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #71](#)⁶⁴⁷⁸ - GIDs that are not serialized via `handle_gid<>` should raise an exception
- [Issue #105](#)⁶⁴⁷⁹ - Allow for `hpx::util::functions` to be registered in the AGAS symbolic namespace
- [Issue #107](#)⁶⁴⁸⁰ - Nasty threadmanger race condition (reproducible in `sheneos_test`)
- [Issue #108](#)⁶⁴⁸¹ - Add millisecond resolution to *HPX* logs on Linux
- [Issue #110](#)⁶⁴⁸² - Shutdown hang in distributed with release build
- [Issue #116](#)⁶⁴⁸³ - Don't use TSS for the applier and runtime pointers
- [Issue #162](#)⁶⁴⁸⁴ - Move local synchronous execution shortcut from `hpx::function` to the applier
- [Issue #172](#)⁶⁴⁸⁵ - Cache sources in CMake and check if they change manually
- [Issue #178](#)⁶⁴⁸⁶ - Add an INI option to turn off ranged-based AGAS caching
- [Issue #187](#)⁶⁴⁸⁷ - Support for disabling performance counter deployment
- [Issue #202](#)⁶⁴⁸⁸ - Support for sending performance counter data to a specific file
- [Issue #218](#)⁶⁴⁸⁹ - `boost.coroutines` allows different stack sizes, but stack pool is unaware of this
- [Issue #231](#)⁶⁴⁹⁰ - Implement movable `boost::bind`
- [Issue #232](#)⁶⁴⁹¹ - Implement movable `boost::function`
- [Issue #236](#)⁶⁴⁹² - Allow binding `hpx::util::function` to actions
- [Issue #239](#)⁶⁴⁹³ - Replace `hpx::function` with `hpx::util::function`
- [Issue #240](#)⁶⁴⁹⁴ - Can't specify `RemoteResult` with `lcos::async`
- [Issue #242](#)⁶⁴⁹⁵ - `REGISTER_TEMPLATE` support for plain actions
- [Issue #243](#)⁶⁴⁹⁶ - `handle_gid<>` support for `hpx::util::function`
- [Issue #245](#)⁶⁴⁹⁷ - `*_c_cache` code throws an exception if the queried GID is not in the local cache
- [Issue #246](#)⁶⁴⁹⁸ - Undefined references in `dataflow/adaptive1d` example

⁶⁴⁷⁸ <https://github.com/TheHPXProject/hpx/issues/71>

⁶⁴⁷⁹ <https://github.com/TheHPXProject/hpx/issues/105>

⁶⁴⁸⁰ <https://github.com/TheHPXProject/hpx/issues/107>

⁶⁴⁸¹ <https://github.com/TheHPXProject/hpx/issues/108>

⁶⁴⁸² <https://github.com/TheHPXProject/hpx/issues/110>

⁶⁴⁸³ <https://github.com/TheHPXProject/hpx/issues/116>

⁶⁴⁸⁴ <https://github.com/TheHPXProject/hpx/issues/162>

⁶⁴⁸⁵ <https://github.com/TheHPXProject/hpx/issues/172>

⁶⁴⁸⁶ <https://github.com/TheHPXProject/hpx/issues/178>

⁶⁴⁸⁷ <https://github.com/TheHPXProject/hpx/issues/187>

⁶⁴⁸⁸ <https://github.com/TheHPXProject/hpx/issues/202>

⁶⁴⁸⁹ <https://github.com/TheHPXProject/hpx/issues/218>

⁶⁴⁹⁰ <https://github.com/TheHPXProject/hpx/issues/231>

⁶⁴⁹¹ <https://github.com/TheHPXProject/hpx/issues/232>

⁶⁴⁹² <https://github.com/TheHPXProject/hpx/issues/236>

⁶⁴⁹³ <https://github.com/TheHPXProject/hpx/issues/239>

⁶⁴⁹⁴ <https://github.com/TheHPXProject/hpx/issues/240>

⁶⁴⁹⁵ <https://github.com/TheHPXProject/hpx/issues/242>

⁶⁴⁹⁶ <https://github.com/TheHPXProject/hpx/issues/243>

⁶⁴⁹⁷ <https://github.com/TheHPXProject/hpx/issues/245>

⁶⁴⁹⁸ <https://github.com/TheHPXProject/hpx/issues/246>

- Issue #252⁶⁴⁹⁹ - Problems configuring sheneos with CMake
- Issue #254⁶⁵⁰⁰ - Lifetime of components doesn't end when client goes out of scope
- Issue #259⁶⁵⁰¹ - CMake does not detect that MSVC10 has lambdas
- Issue #260⁶⁵⁰² - io_service_pool segfault
- Issue #261⁶⁵⁰³ - Late parcel executed outside of pxtread
- Issue #263⁶⁵⁰⁴ - Cannot select allocator with CMake
- Issue #264⁶⁵⁰⁵ - Fix allocator select
- Issue #267⁶⁵⁰⁶ - Runtime error for hello_world
- Issue #269⁶⁵⁰⁷ - pthread_affinity_np test fails to compile
- Issue #270⁶⁵⁰⁸ - Compiler noise due to -Wcast-qual
- Issue #275⁶⁵⁰⁹ - Problem with configuration tests/include paths on Gentoo
- Issue #325⁶⁵¹⁰ - Sheneos is 200-400 times slower than the fortran equivalent
- Issue #331⁶⁵¹¹ - `hpx::init` and `hpx_main()` should not depend on `program_options`
- Issue #333⁶⁵¹² - Add doxygen support to CMake for doc toolchain
- Issue #340⁶⁵¹³ - Performance counters for parcels
- Issue #346⁶⁵¹⁴ - Component loading error when running hello_world in distributed on MSVC2010
- Issue #362⁶⁵¹⁵ - Missing initializer error
- Issue #363⁶⁵¹⁶ - Parcel port serialization error
- Issue #366⁶⁵¹⁷ - Parcel buffering leads to types incompatible exception
- Issue #368⁶⁵¹⁸ - Scalable alternative to `rand()` needed for *HPX*
- Issue #369⁶⁵¹⁹ - IB over IP is substantially slower than just using standard TCP/IP
- Issue #374⁶⁵²⁰ - `hpx::lcos::wait` should work with dataflows and arbitrary classes meeting the future interface
- Issue #375⁶⁵²¹ - Conflicting/ambiguous overloads of `hpx::lcos::wait`

⁶⁴⁹⁹ <https://github.com/TheHPXProject/hpx/issues/252>

⁶⁵⁰⁰ <https://github.com/TheHPXProject/hpx/issues/254>

⁶⁵⁰¹ <https://github.com/TheHPXProject/hpx/issues/259>

⁶⁵⁰² <https://github.com/TheHPXProject/hpx/issues/260>

⁶⁵⁰³ <https://github.com/TheHPXProject/hpx/issues/261>

⁶⁵⁰⁴ <https://github.com/TheHPXProject/hpx/issues/263>

⁶⁵⁰⁵ <https://github.com/TheHPXProject/hpx/issues/264>

⁶⁵⁰⁶ <https://github.com/TheHPXProject/hpx/issues/267>

⁶⁵⁰⁷ <https://github.com/TheHPXProject/hpx/issues/269>

⁶⁵⁰⁸ <https://github.com/TheHPXProject/hpx/issues/270>

⁶⁵⁰⁹ <https://github.com/TheHPXProject/hpx/issues/275>

⁶⁵¹⁰ <https://github.com/TheHPXProject/hpx/issues/325>

⁶⁵¹¹ <https://github.com/TheHPXProject/hpx/issues/331>

⁶⁵¹² <https://github.com/TheHPXProject/hpx/issues/333>

⁶⁵¹³ <https://github.com/TheHPXProject/hpx/issues/340>

⁶⁵¹⁴ <https://github.com/TheHPXProject/hpx/issues/346>

⁶⁵¹⁵ <https://github.com/TheHPXProject/hpx/issues/362>

⁶⁵¹⁶ <https://github.com/TheHPXProject/hpx/issues/363>

⁶⁵¹⁷ <https://github.com/TheHPXProject/hpx/issues/366>

⁶⁵¹⁸ <https://github.com/TheHPXProject/hpx/issues/368>

⁶⁵¹⁹ <https://github.com/TheHPXProject/hpx/issues/369>

⁶⁵²⁰ <https://github.com/TheHPXProject/hpx/issues/374>

⁶⁵²¹ <https://github.com/TheHPXProject/hpx/issues/375>

- [Issue #376](#)⁶⁵²² - Find_HPX.cmake should set CMake variable HPX_FOUND for out of tree builds
- [Issue #377](#)⁶⁵²³ - ShenEOS interpolate bulk and interpolate_one_bulk are broken
- [Issue #379](#)⁶⁵²⁴ - Add support for distributed runs under SLURM
- [Issue #382](#)⁶⁵²⁵ - _Unwind_Word not declared in boost.backtrace
- [Issue #387](#)⁶⁵²⁶ - Doxygen should look only at list of specified files
- [Issue #388](#)⁶⁵²⁷ - Running make install on an out-of-tree application is broken
- [Issue #391](#)⁶⁵²⁸ - Out-of-tree application segfaults when running in qsub
- [Issue #392](#)⁶⁵²⁹ - Remove HPX_NO_INSTALL option from cmake build system
- [Issue #396](#)⁶⁵³⁰ - Pragma related warnings when compiling with older gcc versions
- [Issue #399](#)⁶⁵³¹ - Out of tree component build problems
- [Issue #400](#)⁶⁵³² - Out of source builds on Windows: linker should not receive compiler flags
- [Issue #401](#)⁶⁵³³ - Out of source builds on Windows: components need to be linked with hpx_serialization
- [Issue #404](#)⁶⁵³⁴ - gfortran fails to link automatically when fortran files are present
- [Issue #405](#)⁶⁵³⁵ - Inability to specify linking order for external libraries
- [Issue #406](#)⁶⁵³⁶ - Adapt action limits such that dataflow applications work without additional defines
- [Issue #415](#)⁶⁵³⁷ - locality_results is not a member of hpx::components::server
- [Issue #425](#)⁶⁵³⁸ - Breaking changes to traits::*result wrt std::vector<id_type>
- [Issue #426](#)⁶⁵³⁹ - AUTOGLOB needs to be updated to support fortran

HPX V0.8.1 (Apr 21, 2012)

This is a point release including important bug fixes for *HPX V0.8.0 (Mar 23, 2012)*.

- ⁶⁵²² <https://github.com/TheHPXProject/hpx/issues/376>
- ⁶⁵²³ <https://github.com/TheHPXProject/hpx/issues/377>
- ⁶⁵²⁴ <https://github.com/TheHPXProject/hpx/issues/379>
- ⁶⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/382>
- ⁶⁵²⁶ <https://github.com/TheHPXProject/hpx/issues/387>
- ⁶⁵²⁷ <https://github.com/TheHPXProject/hpx/issues/388>
- ⁶⁵²⁸ <https://github.com/TheHPXProject/hpx/issues/391>
- ⁶⁵²⁹ <https://github.com/TheHPXProject/hpx/issues/392>
- ⁶⁵³⁰ <https://github.com/TheHPXProject/hpx/issues/396>
- ⁶⁵³¹ <https://github.com/TheHPXProject/hpx/issues/399>
- ⁶⁵³² <https://github.com/TheHPXProject/hpx/issues/400>
- ⁶⁵³³ <https://github.com/TheHPXProject/hpx/issues/401>
- ⁶⁵³⁴ <https://github.com/TheHPXProject/hpx/issues/404>
- ⁶⁵³⁵ <https://github.com/TheHPXProject/hpx/issues/405>
- ⁶⁵³⁶ <https://github.com/TheHPXProject/hpx/issues/406>
- ⁶⁵³⁷ <https://github.com/TheHPXProject/hpx/issues/415>
- ⁶⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/425>
- ⁶⁵³⁹ <https://github.com/TheHPXProject/hpx/issues/426>

General changes

- *HPX* does not need to be installed anymore to be functional.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this point release:

- [Issue #295⁶⁵⁴⁰](https://github.com/TheHPXProject/hpx/issues/295) - Don't require install path to be known at compile time.
- [Issue #371⁶⁵⁴¹](https://github.com/TheHPXProject/hpx/issues/371) - Add `hpx::iostreams` to standard build.
- [Issue #384⁶⁵⁴²](https://github.com/TheHPXProject/hpx/issues/384) - Fix compilation with GCC 4.7.
- [Issue #390⁶⁵⁴³](https://github.com/TheHPXProject/hpx/issues/390) - Remove `keep_factory_alive` startup call from ShenEOS; add shutdown call to `H5close`.
- [Issue #393⁶⁵⁴⁴](https://github.com/TheHPXProject/hpx/issues/393) - Thread affinity control is broken.

Bug fixes (commits)

Here is a list of the important commits included in this point release:

- `r7642` - External: Fix backtrace memory violation.
- **`r7775` - Components: Fix symbol visibility bug with component startup providers.** This prevents one components providers from overriding another components.
- `r7778` - Components: Fix startup/shutdown provider shadowing issues.

HPX V0.8.0 (Mar 23, 2012)

We have had roughly 1000 commits since the last release and we have closed approximately 70 tickets (bugs, feature requests, etc.).

General changes

- Improved PBS support, allowing for arbitrary naming schemes of node-hostnames.
- Finished verification of the reference counting framework.
- Implemented decrement merging logic to optimize the distributed reference counting system.
- Restructured the LCO framework. Renamed `hpx::lcos::eager_future<>` and `hpx::lcos::lazy_future<>` into `hpx::lcos::packaged_task` and `hpx::lcos::deferred_packaged_task`. Split `hpx::lcos::promise` into `hpx::lcos::packaged_task` and `hpx::lcos::future`. Added 'local' futures (in namespace `hpx::lcos::local`).
- Improved the general performance of local and remote action invocations. This (under certain circumstances) drastically reduces the number of copies created for each of the parameters and return values.

⁶⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/295>

⁶⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/371>

⁶⁵⁴² <https://github.com/TheHPXProject/hpx/issues/384>

⁶⁵⁴³ <https://github.com/TheHPXProject/hpx/issues/390>

⁶⁵⁴⁴ <https://github.com/TheHPXProject/hpx/issues/393>

- Reworked the performance counter framework. Performance counters are now created only when needed, which reduces the overall resource requirements. The new framework allows for much more flexible creation and management of performance counters. The new sine example application demonstrates some of the capabilities of the new infrastructure.
- Added a buildbot-based continuous build system which gives instant, automated feedback on each commit to SVN.
- Added more automated tests to verify proper functioning of *HPX*.
- Started to create documentation for *HPX* and its API.
- Added documentation toolchain to the build system.
- Added dataflow LCO.
- Changed default *HPX* command line options to have `hpx:` prefix. For instance, the former option `--threads` is now `--hpx:threads`. This has been done to make ambiguities with possible application specific command line options as unlikely as possible. See the section *HPX Command Line Options* for a full list of available options.
- Added the possibility to define command line aliases. The former short (one-letter) command line options have been predefined as aliases for backwards compatibility. See the section *HPX Command Line Options* for a detailed description of command line option aliasing.
- Network connections are now cached based on the connected host. The number of simultaneous connections to a particular host is now limited. Parcels are buffered and bundled if all connections are in use.
- Added more refined thread affinity control. This is based on the external library Portable Hardware Locality (HWLOC).
- Improved support for Windows builds with CMake.
- Added support for components to register their own command line options.
- Added the possibility to register custom startup/shutdown functions for any component. These functions are guaranteed to be executed by an *HPX* thread.
- Added two new experimental thread schedulers: `hierarchy_scheduler` and `periodic_priority_scheduler`. These can be activated by using the command line options `--hpx:queuing=hierarchy` or `--hpx:queuing=periodic`.

Example applications

- [Graph500 performance benchmark](http://www.graph500.org/)⁶⁵⁴⁵ (thanks to Matthew Anderson for contributing this application).
- [GTC \(Gyrokinetic Toroidal Code\)](http://www.nersc.gov/research-and-development/benchmarking-and-workload-characterization/nersc-6-benchmarks/gtc/)⁶⁵⁴⁶: a skeleton for particle in cell type codes.
- Random Memory Access: an example demonstrating random memory accesses in a large array
- [ShenEOS example](http://stellarcollapse.org/equationofstate)⁶⁵⁴⁷, demonstrating partitioning of large read-only data structures and exposing an interpolation API.
- Sine performance counter demo.
- Accumulator examples demonstrating how to write and use *HPX* components.
- Quickstart examples (like `hello_world`, `fibonacci`, `quicksort`, `factorial`, etc.) demonstrating simple *HPX* concepts which introduce some of the concepts in *HPX*.
- Load balancing and work stealing demos.

⁶⁵⁴⁵ <http://www.graph500.org/>

⁶⁵⁴⁶ <http://www.nersc.gov/research-and-development/benchmarking-and-workload-characterization/nersc-6-benchmarks/gtc/>

⁶⁵⁴⁷ <http://stellarcollapse.org/equationofstate>

API changes

- Moved all local LCOs into a separate namespace `hpx::lcos::local` (for instance, `hpx::lcos::local_mutex` is now `hpx::lcos::local::mutex`).
- Replaced `hpx::actions::function` with `hpx::util::function`. Cleaned up related code.
- Removed `hpx::traits::handle_gid` and moved handling of global reference counts into the corresponding serialization code.
- Changed terminology: `prefix` is now called `locality_id`, renamed the corresponding API functions (such as `hpx::get_prefix`, which is now called `hpx::get_locality_id`).
- Adding `hpx::find_remote_localities`, and `hpx::get_num_localities`.
- Changed performance counter naming scheme to make it more bash friendly. The new performance counter naming scheme is now

```
/object{parentname#parentindex/instance#index}/counter#parameters
```

- Added `hpx::get_worker_thread_num` replacing `hpx::threadmanager_base::get_thread_num`.
- Renamed `hpx::get_num_os_threads` to `hpx::get_os_threads_count`.
- Added `hpx::threads::get_thread_count`.
- Restructured the Futures sub-system, renaming types in accordance with the terminology used by the C++11 ISO standard.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #31](#)⁶⁵⁴⁸ - Specialize `handle_gid<>` for examples and tests
- [Issue #72](#)⁶⁵⁴⁹ - Fix AGAS reference counting
- [Issue #104](#)⁶⁵⁵⁰ - heartbeat throws an exception when decrefing the performance counter it's watching
- [Issue #111](#)⁶⁵⁵¹ - throttle causes an exception on the target application
- [Issue #142](#)⁶⁵⁵² - One failed component loading causes an unrelated component to fail
- [Issue #165](#)⁶⁵⁵³ - Remote exception propagation bug in AGAS reference counting test
- [Issue #186](#)⁶⁵⁵⁴ - Test credit exhaustion/splitting (e.g. `prepare_gid` and symbol NS)
- [Issue #188](#)⁶⁵⁵⁵ - Implement remaining AGAS reference counting test cases
- [Issue #258](#)⁶⁵⁵⁶ - No type checking of GIDs in stubs classes
- [Issue #271](#)⁶⁵⁵⁷ - Seg fault/shared pointer assertion in distributed code

⁶⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/31>

⁶⁵⁴⁹ <https://github.com/TheHPXProject/hpx/issues/72>

⁶⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/104>

⁶⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/111>

⁶⁵⁵² <https://github.com/TheHPXProject/hpx/issues/142>

⁶⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/165>

⁶⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/186>

⁶⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/188>

⁶⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/258>

⁶⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/271>

- [Issue #281](#)⁶⁵⁵⁸ - CMake options need descriptive text
- [Issue #283](#)⁶⁵⁵⁹ - AGAS caching broken (gva_cache needs to be rewritten with ICL)
- [Issue #285](#)⁶⁵⁶⁰ - HPX_INSTALL root directory not the same as CMAKE_INSTALL_PREFIX
- [Issue #286](#)⁶⁵⁶¹ - New segfault in dataflow applications
- [Issue #289](#)⁶⁵⁶² - Exceptions should only be logged if not handled
- [Issue #290](#)⁶⁵⁶³ - c++11 tests failure
- [Issue #293](#)⁶⁵⁶⁴ - Build target for component libraries
- [Issue #296](#)⁶⁵⁶⁵ - Compilation error with Boost V1.49rc1
- [Issue #298](#)⁶⁵⁶⁶ - Illegal instructions on termination
- [Issue #299](#)⁶⁵⁶⁷ - gravity aborts with multiple threads
- [Issue #301](#)⁶⁵⁶⁸ - Build error with Boost trunk
- [Issue #303](#)⁶⁵⁶⁹ - Logging assertion failure in distributed runs
- [Issue #304](#)⁶⁵⁷⁰ - Exception ‘what’ strings are lost when exceptions from decode_parcel are reported
- [Issue #306](#)⁶⁵⁷¹ - Performance counter user interface issues
- [Issue #307](#)⁶⁵⁷² - Logging exception in distributed runs
- [Issue #308](#)⁶⁵⁷³ - Logging deadlocks in distributed
- [Issue #309](#)⁶⁵⁷⁴ - Reference counting test failures and exceptions
- [Issue #311](#)⁶⁵⁷⁵ - Merge AGAS remote_interface with the runtime_support object
- [Issue #314](#)⁶⁵⁷⁶ - Object tracking for id_types
- [Issue #315](#)⁶⁵⁷⁷ - Remove handle_gid and handle credit splitting in id_type serialization
- [Issue #320](#)⁶⁵⁷⁸ - applier::get_locality_id() should return an error value (or throw an exception)
- [Issue #321](#)⁶⁵⁷⁹ - Optimization for id_types which are never split should be restored
- [Issue #322](#)⁶⁵⁸⁰ - Command line processing ignored with Boost 1.47.0

⁶⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/281>

⁶⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/283>

⁶⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/285>

⁶⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/286>

⁶⁵⁶² <https://github.com/TheHPXProject/hpx/issues/289>

⁶⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/290>

⁶⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/293>

⁶⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/296>

⁶⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/298>

⁶⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/299>

⁶⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/301>

⁶⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/303>

⁶⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/304>

⁶⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/306>

⁶⁵⁷² <https://github.com/TheHPXProject/hpx/issues/307>

⁶⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/308>

⁶⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/309>

⁶⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/311>

⁶⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/314>

⁶⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/315>

⁶⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/320>

⁶⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/321>

⁶⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/322>

- Issue #323⁶⁵⁸¹ - Credit exhaustion causes object to stay alive
- Issue #324⁶⁵⁸² - Duplicate exception messages
- Issue #326⁶⁵⁸³ - Integrate Quickbook with CMake
- Issue #329⁶⁵⁸⁴ - --help and --version should still work
- Issue #330⁶⁵⁸⁵ - Create pkg-config files
- Issue #337⁶⁵⁸⁶ - Improve usability of performance counter timestamps
- Issue #338⁶⁵⁸⁷ - Non-std exceptions deriving from std::exceptions in tfunc may be sliced
- Issue #339⁶⁵⁸⁸ - Decrease the number of send_pending_parcel threads
- Issue #343⁶⁵⁸⁹ - Dynamically setting the stack size doesn't work
- Issue #351⁶⁵⁹⁰ - 'make install' does not update documents
- Issue #353⁶⁵⁹¹ - Disable FIXMEs in the docs by default; add a doc developer CMake option to enable FIXMEs
- Issue #355⁶⁵⁹² - 'make' doesn't do anything after correct configuration
- Issue #356⁶⁵⁹³ - Don't use `hpx::util::static_` in topology code
- Issue #359⁶⁵⁹⁴ - Infinite recursion in `hpx::tuple` serialization
- Issue #361⁶⁵⁹⁵ - Add compile time option to disable logging completely
- Issue #364⁶⁵⁹⁶ - Installation seriously broken in r7443

HPX V0.7.0 (Dec 12, 2011)

We have had roughly 1000 commits since the last release and we have closed approximately 120 tickets (bugs, feature requests, etc.).

⁶⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/323>
⁶⁵⁸² <https://github.com/TheHPXProject/hpx/issues/324>
⁶⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/326>
⁶⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/329>
⁶⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/330>
⁶⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/337>
⁶⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/338>
⁶⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/339>
⁶⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/343>
⁶⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/351>
⁶⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/353>
⁶⁵⁹² <https://github.com/TheHPXProject/hpx/issues/355>
⁶⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/356>
⁶⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/359>
⁶⁵⁹⁵ <https://github.com/TheHPXProject/hpx/issues/361>
⁶⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/364>

General changes

- Completely removed code related to deprecated AGAS V1, started to work on AGAS V2.1.
- Started to clean up and streamline the exposed APIs (see ‘API changes’ below for more details).
- Revamped and unified performance counter framework, added a lot of new performance counter instances for monitoring of a diverse set of internal *HPX* parameters (queue lengths, access statistics, etc.).
- Improved general error handling and logging support.
- Fixed several race conditions, improved overall stability, decreased memory footprint, improved overall performance (major optimizations include native TLS support and ranged-based AGAS caching).
- Added support for running *HPX* applications with PBS.
- Many updates to the build system, added support for gcc 4.5.x and 4.6.x, added C++11 support.
- Many updates to default command line options.
- Added many tests, set up buildbot for continuous integration testing.
- Better shutdown handling of distributed applications.

Example applications

- quickstart/factorial and quickstart/fibonacci, future-recursive parallel algorithms.
- quickstart/hello_world, distributed hello world example.
- quickstart/rma, simple remote memory access example
- quickstart/quicksort, parallel quicksort implementation.
- gtc, gyrokinetic torodial code.
- bfs, breadth-first-search, example code for a graph application.
- sheneos, partitioning of large data sets.
- accumulator, simple component example.
- balancing/os_thread_num, balancing/px_thread_phase, examples demonstrating load balancing and work stealing.

API changes

- Added `hpx::find_all_localities`.
- Added `hpx::terminate` for non-graceful termination of applications.
- Added `hpx::lcos::async` functions for simpler asynchronous programming.
- Added new AGAS interface for handling of symbolic namespace (`hpx::agas::*`).
- Renamed `hpx::components::wait` to `hpx::lcos::wait`.
- Renamed `hpx::lcos::future_value` to `hpx::lcos::promise`.
- Renamed `hpx::lcos::recursive_mutex` to `hpx::lcos::local_recursive_mutex`, `hpx::lcos::mutex` to `hpx::lcos::local_mutex`
- Removed support for Boost versions older than V1.38, recommended Boost version is now V1.47 and newer.

- Removed `hpx::process` (this will be replaced by a real process implementation in the future).
- Removed non-functional LCO code (`hpx::lcos::dataflow`, `hpx::lcos::thunk`, `hpx::lcos::dataflow_variable`).
- Removed deprecated `hpx::naming::full_address`.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #28⁶⁵⁹⁷](#) - Integrate Windows/Linux CMake code for *HPX* core
- [Issue #32⁶⁵⁹⁸](#) - `hpx::cout()` should be `hpx::cout`
- [Issue #33⁶⁵⁹⁹](#) - AGAS V2 legacy client does not properly handle `error_code`
- [Issue #60⁶⁶⁰⁰](#) - AGAS: allow for `registerid` to optionally take ownership of the `gid`
- [Issue #62⁶⁶⁰¹](#) - `adaptive1d` compilation failure in Fusion
- [Issue #64⁶⁶⁰²](#) - Parcel subsystem doesn't resolve domain names
- [Issue #83⁶⁶⁰³](#) - No error handling if no console is available
- [Issue #84⁶⁶⁰⁴](#) - No error handling if a hosted locality is treated as the bootstrap server
- [Issue #90⁶⁶⁰⁵](#) - Add general commandline option `-N`
- [Issue #91⁶⁶⁰⁶](#) - Add possibility to read command line arguments from file
- [Issue #92⁶⁶⁰⁷](#) - Always log exceptions/errors to the log file
- [Issue #93⁶⁶⁰⁸](#) - Log the command line/program name
- [Issue #95⁶⁶⁰⁹](#) - Support for distributed launches
- [Issue #97⁶⁶¹⁰](#) - Attempt to create a bad component type in AMR examples
- [Issue #100⁶⁶¹¹](#) - `factorial` and `factorial_get` examples trigger AGAS component type assertions
- [Issue #101⁶⁶¹²](#) - Segfault when `hpx::process::here()` is called in `fibonacci2`
- [Issue #102⁶⁶¹³](#) - `unknown_component_address` in `int_object_semaphore_client`
- [Issue #114⁶⁶¹⁴](#) - `marduk` raises assertion with default parameters

⁶⁵⁹⁷ <https://github.com/TheHPXProject/hpx/issues/28>

⁶⁵⁹⁸ <https://github.com/TheHPXProject/hpx/issues/32>

⁶⁵⁹⁹ <https://github.com/TheHPXProject/hpx/issues/33>

⁶⁶⁰⁰ <https://github.com/TheHPXProject/hpx/issues/60>

⁶⁶⁰¹ <https://github.com/TheHPXProject/hpx/issues/62>

⁶⁶⁰² <https://github.com/TheHPXProject/hpx/issues/64>

⁶⁶⁰³ <https://github.com/TheHPXProject/hpx/issues/83>

⁶⁶⁰⁴ <https://github.com/TheHPXProject/hpx/issues/84>

⁶⁶⁰⁵ <https://github.com/TheHPXProject/hpx/issues/90>

⁶⁶⁰⁶ <https://github.com/TheHPXProject/hpx/issues/91>

⁶⁶⁰⁷ <https://github.com/TheHPXProject/hpx/issues/92>

⁶⁶⁰⁸ <https://github.com/TheHPXProject/hpx/issues/93>

⁶⁶⁰⁹ <https://github.com/TheHPXProject/hpx/issues/95>

⁶⁶¹⁰ <https://github.com/TheHPXProject/hpx/issues/97>

⁶⁶¹¹ <https://github.com/TheHPXProject/hpx/issues/100>

⁶⁶¹² <https://github.com/TheHPXProject/hpx/issues/101>

⁶⁶¹³ <https://github.com/TheHPXProject/hpx/issues/102>

⁶⁶¹⁴ <https://github.com/TheHPXProject/hpx/issues/114>

- [Issue #115](#)⁶⁶¹⁵ - Logging messages for SMP runs (on the console) shouldn't be buffered
- [Issue #119](#)⁶⁶¹⁶ - marduk linking strategy breaks other applications
- [Issue #121](#)⁶⁶¹⁷ - pbsdsh problem
- [Issue #123](#)⁶⁶¹⁸ - marduk, dataflow and adaptive1d fail to build
- [Issue #124](#)⁶⁶¹⁹ - Lower default preprocessing arity
- [Issue #125](#)⁶⁶²⁰ - Move hpx::detail::diagnostic_information out of the detail namespace
- [Issue #126](#)⁶⁶²¹ - Test definitions for AGAS reference counting
- [Issue #128](#)⁶⁶²² - Add averaging performance counter
- [Issue #129](#)⁶⁶²³ - Error with endian.hpp while building adaptive1d
- [Issue #130](#)⁶⁶²⁴ - Bad initialization of performance counters
- [Issue #131](#)⁶⁶²⁵ - Add global startup/shutdown functions to component modules
- [Issue #132](#)⁶⁶²⁶ - Avoid using auto_ptr
- [Issue #133](#)⁶⁶²⁷ - On Windows hpx.dll doesn't get installed
- [Issue #134](#)⁶⁶²⁸ - HPX_LIBRARY does not reflect real library name (on Windows)
- [Issue #135](#)⁶⁶²⁹ - Add detection of unique_ptr to build system
- [Issue #137](#)⁶⁶³⁰ - Add command line option allowing to repeatedly evaluate performance counters
- [Issue #139](#)⁶⁶³¹ - Logging is broken
- [Issue #140](#)⁶⁶³² - CMake problem on windows
- [Issue #141](#)⁶⁶³³ - Move all non-component libraries into \$PREFIX/lib/hpx
- [Issue #143](#)⁶⁶³⁴ - adaptive1d throws an exception with the default command line options
- [Issue #146](#)⁶⁶³⁵ - Early exception handling is broken
- [Issue #147](#)⁶⁶³⁶ - Sheneos doesn't link on Linux
- [Issue #149](#)⁶⁶³⁷ - sheneos_test hangs

⁶⁶¹⁵ <https://github.com/TheHPXProject/hpx/issues/115>

⁶⁶¹⁶ <https://github.com/TheHPXProject/hpx/issues/119>

⁶⁶¹⁷ <https://github.com/TheHPXProject/hpx/issues/121>

⁶⁶¹⁸ <https://github.com/TheHPXProject/hpx/issues/123>

⁶⁶¹⁹ <https://github.com/TheHPXProject/hpx/issues/124>

⁶⁶²⁰ <https://github.com/TheHPXProject/hpx/issues/125>

⁶⁶²¹ <https://github.com/TheHPXProject/hpx/issues/126>

⁶⁶²² <https://github.com/TheHPXProject/hpx/issues/128>

⁶⁶²³ <https://github.com/TheHPXProject/hpx/issues/129>

⁶⁶²⁴ <https://github.com/TheHPXProject/hpx/issues/130>

⁶⁶²⁵ <https://github.com/TheHPXProject/hpx/issues/131>

⁶⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/132>

⁶⁶²⁷ <https://github.com/TheHPXProject/hpx/issues/133>

⁶⁶²⁸ <https://github.com/TheHPXProject/hpx/issues/134>

⁶⁶²⁹ <https://github.com/TheHPXProject/hpx/issues/135>

⁶⁶³⁰ <https://github.com/TheHPXProject/hpx/issues/137>

⁶⁶³¹ <https://github.com/TheHPXProject/hpx/issues/139>

⁶⁶³² <https://github.com/TheHPXProject/hpx/issues/140>

⁶⁶³³ <https://github.com/TheHPXProject/hpx/issues/141>

⁶⁶³⁴ <https://github.com/TheHPXProject/hpx/issues/143>

⁶⁶³⁵ <https://github.com/TheHPXProject/hpx/issues/146>

⁶⁶³⁶ <https://github.com/TheHPXProject/hpx/issues/147>

⁶⁶³⁷ <https://github.com/TheHPXProject/hpx/issues/149>

- Issue #154⁶⁶³⁸ - Compilation fails for r5661
- Issue #155⁶⁶³⁹ - Sine performance counters example chokes on chrono headers
- Issue #156⁶⁶⁴⁰ - Add build type to `--version`
- Issue #157⁶⁶⁴¹ - Extend AGAS caching to store gid ranges
- Issue #158⁶⁶⁴² - r5691 doesn't compile
- Issue #160⁶⁶⁴³ - Re-add AGAS function for resolving a locality to its prefix
- Issue #168⁶⁶⁴⁴ - Managed components should be able to access their own GID
- Issue #169⁶⁶⁴⁵ - Rewrite AGAS future pool
- Issue #179⁶⁶⁴⁶ - Complete switch to request class for AGAS server interface
- Issue #182⁶⁶⁴⁷ - Sine performance counter is loaded by other examples
- Issue #185⁶⁶⁴⁸ - Write tests for symbol namespace reference counting
- Issue #191⁶⁶⁴⁹ - Assignment of read-only variable in `point_geometry`
- Issue #200⁶⁶⁵⁰ - Seg faults when querying performance counters
- Issue #204⁶⁶⁵¹ - `--ifnames` and suffix stripping needs to be more generic
- Issue #205⁶⁶⁵² - `--list-*` and `--print-counter-*` options do not work together and produce no warning
- Issue #207⁶⁶⁵³ - Implement decrement entry merging
- Issue #208⁶⁶⁵⁴ - Replace the spinlocks in AGAS with `hpx::lcos::local_mutexes`
- Issue #210⁶⁶⁵⁵ - Add an `--ifprefix` option
- Issue #214⁶⁶⁵⁶ - Performance test for PX-thread creation
- Issue #216⁶⁶⁵⁷ - VS2010 compilation
- Issue #222⁶⁶⁵⁸ - r6045 `context_linux_x86.hpp`
- Issue #223⁶⁶⁵⁹ - fibonacci hangs when changing the state of an active thread
- Issue #225⁶⁶⁶⁰ - Active threads end up in the FEB wait queue

⁶⁶³⁸ <https://github.com/TheHPXProject/hpx/issues/154>

⁶⁶³⁹ <https://github.com/TheHPXProject/hpx/issues/155>

⁶⁶⁴⁰ <https://github.com/TheHPXProject/hpx/issues/156>

⁶⁶⁴¹ <https://github.com/TheHPXProject/hpx/issues/157>

⁶⁶⁴² <https://github.com/TheHPXProject/hpx/issues/158>

⁶⁶⁴³ <https://github.com/TheHPXProject/hpx/issues/160>

⁶⁶⁴⁴ <https://github.com/TheHPXProject/hpx/issues/168>

⁶⁶⁴⁵ <https://github.com/TheHPXProject/hpx/issues/169>

⁶⁶⁴⁶ <https://github.com/TheHPXProject/hpx/issues/179>

⁶⁶⁴⁷ <https://github.com/TheHPXProject/hpx/issues/182>

⁶⁶⁴⁸ <https://github.com/TheHPXProject/hpx/issues/185>

⁶⁶⁴⁹ <https://github.com/TheHPXProject/hpx/issues/191>

⁶⁶⁵⁰ <https://github.com/TheHPXProject/hpx/issues/200>

⁶⁶⁵¹ <https://github.com/TheHPXProject/hpx/issues/204>

⁶⁶⁵² <https://github.com/TheHPXProject/hpx/issues/205>

⁶⁶⁵³ <https://github.com/TheHPXProject/hpx/issues/207>

⁶⁶⁵⁴ <https://github.com/TheHPXProject/hpx/issues/208>

⁶⁶⁵⁵ <https://github.com/TheHPXProject/hpx/issues/210>

⁶⁶⁵⁶ <https://github.com/TheHPXProject/hpx/issues/214>

⁶⁶⁵⁷ <https://github.com/TheHPXProject/hpx/issues/216>

⁶⁶⁵⁸ <https://github.com/TheHPXProject/hpx/issues/222>

⁶⁶⁵⁹ <https://github.com/TheHPXProject/hpx/issues/223>

⁶⁶⁶⁰ <https://github.com/TheHPXProject/hpx/issues/225>

- [Issue #226⁶⁶⁶¹](#) - VS Build Error for Accumulator Client
- [Issue #228⁶⁶⁶²](#) - Move all traits into namespace `hpx::traits`
- [Issue #229⁶⁶⁶³](#) - Invalid initialization of reference in `thread_init_data`
- [Issue #235⁶⁶⁶⁴](#) - Invalid GID in `iostreams`
- [Issue #238⁶⁶⁶⁵](#) - Demangle type names for the default implementation of `get_action_name`
- [Issue #241⁶⁶⁶⁶](#) - C++11 support breaks GCC 4.5
- [Issue #247⁶⁶⁶⁷](#) - Reference to temporary with GCC 4.4
- [Issue #248⁶⁶⁶⁸](#) - Seg fault at shutdown with GCC 4.4
- [Issue #253⁶⁶⁶⁹](#) - Default component action registration kills compiler
- [Issue #272⁶⁶⁷⁰](#) - G++ unrecognized command line option
- [Issue #273⁶⁶⁷¹](#) - quicksort example doesn't compile
- [Issue #277⁶⁶⁷²](#) - Invalid CMake logic for Windows

2.11.3 Namespace changes

HPX V1.9.0 Namespace changes

The latest release includes amongst others changes in the namespaces so that *HPX* facilities correspond to the C++ Standard Library. The old namespaces are deprecated. Below is a comprehensive list of the namespace changes.

Table 2.189: Namespace changes in V1.9.0

Old namespace	New namespace
<code>hpx::util::mem_fn</code>	<code>hpx::mem_fn</code>
<code>hpx::util::invoke</code>	<code>hpx::invoke</code>
<code>hpx::util::invoke_r</code>	<code>hpx::invoke_r</code>
<code>hpx::util::invoke_fused</code>	<code>hpx::invoke_fused</code>
<code>hpx::util::invoke_fused_r</code>	<code>hpx::invoke_fused_r</code>
<code>hpx::util::unlock_guard</code>	<code>hpx::unlock_guard</code>
<code>hpx::parallel::v1::reduce_by_key</code>	<code>hpx::experimental::reduce_by_key</code>
<code>hpx::parallel::v1::sort_by_key</code>	<code>hpx::experimental::sort_by_key</code>
<code>hpx::parallel::task_canceled_exception</code>	<code>hpx::experimental::task_canceled_exception</code>
<code>hpx::parallel::task_block</code>	<code>hpx::experimental::task_block</code>
<code>hpx::parallel::define_task_block</code>	<code>hpx::experimental::define_task_block</code>
<code>hpx::parallel::define_task_block_restore_thread</code>	<code>hpx::experimental::define_task_block_restore_thread</code>
<code>hpx::execution::experimental::task_group</code>	<code>hpx::experimental::task_group</code>

⁶⁶⁶¹ <https://github.com/TheHPXProject/hpx/issues/226>

⁶⁶⁶² <https://github.com/TheHPXProject/hpx/issues/228>

⁶⁶⁶³ <https://github.com/TheHPXProject/hpx/issues/229>

⁶⁶⁶⁴ <https://github.com/TheHPXProject/hpx/issues/235>

⁶⁶⁶⁵ <https://github.com/TheHPXProject/hpx/issues/238>

⁶⁶⁶⁶ <https://github.com/TheHPXProject/hpx/issues/241>

⁶⁶⁶⁷ <https://github.com/TheHPXProject/hpx/issues/247>

⁶⁶⁶⁸ <https://github.com/TheHPXProject/hpx/issues/248>

⁶⁶⁶⁹ <https://github.com/TheHPXProject/hpx/issues/253>

⁶⁶⁷⁰ <https://github.com/TheHPXProject/hpx/issues/272>

⁶⁶⁷¹ <https://github.com/TheHPXProject/hpx/issues/273>

⁶⁶⁷² <https://github.com/TheHPXProject/hpx/issues/277>

2.12 Citing HPX

Please cite *HPX* whenever you use it for publications. Use our paper in The Journal of Open Source Software as the main citation for *HPX*: ⁶⁶⁷³. Use the Zenodo entry for referring to the latest version of *HPX*: ⁶⁶⁷⁴. Entries for citing specific versions of *HPX* can also be found at ⁶⁶⁷⁵.

2.13 HPX users

A list of institutions and projects using *HPX* can be found on the *HPX Users*⁶⁶⁷⁶ page.

2.14 About HPX

2.14.1 History

The development of High Performance ParalleX (*HPX*) began in 2007. At that time, Hartmut Kaiser became interested in the work done by the ParalleX group at the [Center for Computation and Technology \(CCT\)](https://www.cct.lsu.edu)⁶⁶⁷⁷, a multi-disciplinary research institute at [Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁶⁷⁸. The ParalleX group was working to develop a new and experimental execution model for future high performance computing architectures. This model was christened ParalleX. The first implementations of ParalleX were crude, and many of those designs had to be discarded entirely. However, over time the team learned quite a bit about how to design a parallel, distributed runtime system which implements the concepts of ParalleX.

From the very beginning, this endeavour has been a group effort. In addition to a handful of interested researchers, there have always been graduate and undergraduate students participating in the discussions, design, and implementation of *HPX*. In 2011 we decided to formalize our collective research efforts by creating the [STE||AR](https://stellar-group.org)⁶⁶⁷⁹ group (Systems Technology, Emergent Parallelism, and Algorithm Research). Over time, the team grew to include researchers around the country and the world. In 2014, the [STE||AR](https://stellar-group.org)⁶⁶⁸⁰ Group was reorganized to become the international community it is today. This consortium of researchers aims to develop stable, sustainable, and scalable tools which will enable application developers to exploit the parallelism latent in the machines of today and tomorrow. Our goal of the *HPX* project is to create a high quality, freely available, open source implementation of ParalleX concepts for conventional and future systems by building a modular and standards conforming runtime system for SMP and distributed application environments. The API exposed by *HPX* is conformant to the interfaces defined by the C++ ISO Standard and adheres to the programming guidelines used by the [Boost](https://www.boost.org/)⁶⁶⁸¹ collection of C++ libraries. We steer the development of *HPX* with real world applications and aim to provide a smooth migration path for domain scientists.

To learn more about [STE||AR](https://stellar-group.org)⁶⁶⁸² and ParalleX, see *People* and *Why HPX?*.

⁶⁶⁷³ <https://joss.theoj.org/papers/022e5917b95517dff20cd3742ab95eca>

⁶⁶⁷⁴ <https://doi.org/10.5281/zenodo.598202>

⁶⁶⁷⁵ <https://doi.org/10.5281/zenodo.598202>

⁶⁶⁷⁶ <https://hpx.stellar-group.org/hpx-users/>

⁶⁶⁷⁷ <https://www.cct.lsu.edu>

⁶⁶⁷⁸ <https://www.lsu.edu>

⁶⁶⁷⁹ <https://stellar-group.org>

⁶⁶⁸⁰ <https://stellar-group.org>

⁶⁶⁸¹ <https://www.boost.org/>

⁶⁶⁸² <https://stellar-group.org>

2.14.2 People

The **STE||AR**⁶⁶⁸³ Group (pronounced as stellar) stands for “**S**ystems **T**echnology, **E**mergent **P**arallelism, and **A**lgorithm **R**esearch”. We are an international group of faculty, researchers, and students working at various institutions around the world. The goal of the **STE||AR**⁶⁶⁸⁴ Group is to promote the development of scalable parallel applications by providing a community for ideas, a framework for collaboration, and a platform for communicating these concepts to the broader community.

Our work is focused on building technologies for scalable parallel applications. *HPX*, our general purpose C++ runtime system for parallel and distributed applications, is no exception. We use *HPX* for a broad range of scientific applications, helping scientists and developers to write code which scales better and shows better performance compared to more conventional programming models such as MPI.

HPX is based on *ParalleX* which is a new (and still experimental) parallel execution model aiming to overcome the limitations imposed by the current hardware and the techniques we use to write applications today. Our group focuses on two types of applications - those requiring excellent strong scaling, allowing for a dramatic reduction of execution time for fixed workloads and those needing highest level of sustained performance through massive parallelism. These applications are presently unable (through conventional practices) to effectively exploit a relatively small number of cores in a multi-core system. By extension, these application will not be able to exploit high-end exascale computing systems which are likely to employ hundreds of millions of such cores by the end of this decade.

Critical bottlenecks to the effective use of new generation high performance computing (HPC) systems include:

- *Starvation*: due to lack of usable application parallelism and means of managing it,
- *Overhead*: reduction to permit strong scalability, improve efficiency, and enable dynamic resource management,
- *Latency*: from remote access across system or to local memories,
- *Contention*: due to multicore chip I/O pins, memory banks, and system interconnects.

The *ParalleX* model has been devised to address these challenges by enabling a new computing dynamic through the application of message-driven computation in a global address space context with lightweight synchronization. The work on *HPX* is centered around implementing the concepts as defined by the *ParalleX* model. *HPX* is currently targeted at conventional machines, such as classical Linux based Beowulf clusters and SMP nodes.

We fully understand that the success of *HPX* (and *ParalleX*) is very much the result of the work of many people. To see a list of who is contributing see our tables below.

⁶⁶⁸³ <https://stellar-group.org>

⁶⁶⁸⁴ <https://stellar-group.org>

HPX contributors

Table 2.190: Contributors

Name	Institution	Email
Hartmut Kaiser	Center for Computation and Technology (CCT) ⁶⁶⁸⁵ , Louisiana State University (LSU) ⁶⁶⁸⁶	hkaiser@cct.lsu.edu
Thomas Heller	Department of Computer Science 3 - Computer Architecture ⁶⁶⁸⁷ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁶⁸⁸	thom.heller@gmail.com
Agustin Berge		agustinberge@gmail.com
Mikael Simberg	Swiss National Supercomputing Centre ⁶⁶⁸⁹	simbergm@cscs.ch
John Biddiscombe	Swiss National Supercomputing Centre ⁶⁶⁹⁰	biddisco@cscs.ch
Anton Bikiineev	Center for Computation and Technology (CCT) ⁶⁶⁹¹ , Louisiana State University (LSU) ⁶⁶⁹²	ant.bikineev@gmail.com
Martin Stumpf	Department of Computer Science 3 - Computer Architecture ⁶⁶⁹³ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁶⁹⁴	martin.h.stumpf@gmail.com
Bryce Adelstein Lelbach		brycelelbach@gmail.com
Shuangyang Yang	Center for Computation and Technology (CCT) ⁶⁶⁹⁵ , Louisiana State University (LSU) ⁶⁶⁹⁶	syang16@cct.lsu.edu
Jeroen Habraken		vexocide@gmail.com
Steven Brandt	Center for Computation and Technology (CCT) ⁶⁶⁹⁷ , Louisiana State University (LSU) ⁶⁶⁹⁸	sbrandt@cct.lsu.edu
Antoine Tran Tan	Paris-Saclay University ⁶⁶⁹⁹ ,	antoine.trantan@universite-paris-saclay.fr
Adrian S. Lemoine	AMD ⁶⁷⁰⁰	Adrian.Lemoine@amd.com
Maciej Brodowicz		maciekab@gmail.com
Giannis Gonidellis	Center for Computation and Technology (CCT) ⁶⁷⁰¹ , Louisiana State University (LSU) ⁶⁷⁰²	gonidellis@hotmail.com

⁶⁶⁸⁵ <https://www.cct.lsu.edu>⁶⁶⁸⁶ <https://www.lsu.edu>⁶⁶⁸⁷ <https://www3.cs.fau.de>⁶⁶⁸⁸ <https://www.fau.de>⁶⁶⁸⁹ <https://www.cscs.ch>⁶⁶⁹⁰ <https://www.cscs.ch>⁶⁶⁹¹ <https://www.cct.lsu.edu>⁶⁶⁹² <https://www.lsu.edu>⁶⁶⁹³ <https://www3.cs.fau.de>⁶⁶⁹⁴ <https://www.fau.de>⁶⁶⁹⁵ <https://www.cct.lsu.edu>⁶⁶⁹⁶ <https://www.lsu.edu>⁶⁶⁹⁷ <https://www.cct.lsu.edu>⁶⁶⁹⁸ <https://www.lsu.edu>⁶⁶⁹⁹ <https://www.universite-paris-saclay.fr/en>⁶⁷⁰⁰ <https://www.amd.com/en>⁶⁷⁰¹ <https://www.cct.lsu.edu>⁶⁷⁰² <https://www.lsu.edu>

Contributors to this document

Table 2.191: Documentation authors

Name	Institution	Email
Hartmut Kaiser	Center for Computation and Technology (CCT) ⁶⁷⁰³ , Louisiana State University (LSU) ⁶⁷⁰⁴	hkaiser@cct.lsu.edu
Thomas Heller	Department of Computer Science 3 - Computer Architecture ⁶⁷⁰⁵ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁷⁰⁶	thom.heller@gmail.com
Bryce Adelstein Lelbach		brycelelbach@gmail.com
Vinay C Amatya	Center for Computation and Technology (CCT) ⁶⁷⁰⁷ , Louisiana State University (LSU) ⁶⁷⁰⁸	vamatya@cct.lsu.edu
Steven Brandt	Center for Computation and Technology (CCT) ⁶⁷⁰⁹ , Louisiana State University (LSU) ⁶⁷¹⁰	sbrandt@cct.lsu.edu
Maciej Brodowicz		maciekab@gmail.com
Adrian S. Lemoine	AMD ⁶⁷¹¹	Adrian.Lemoine@amd.com
Rebecca Stobaugh		rstobaugh1@gmail.com
Dimitra Karatza	Faculty of Electrical Engineering, Mathematics & Computer Science ⁶⁷¹² , Delft University of Technology ⁶⁷¹³	dimitra.karatza11@gmail.com
Bhumit Attarde		bhumitattarde2@gmail.com

Acknowledgements

Thanks also to the following people who contributed directly or indirectly to the project through discussions, pull requests, documentation patches, etc.

- Panos Syskakis for benchmarking and optimizing our parallel algorithms.
- Shreyas Atre, for contributing fixes to our implementation of senders/receivers and extending our coroutines integration with senders/receivers.
- Alexander Neumann, for contributing fixes to the cmake build system.
- Dimitra Karatza, for her work on refactoring the documentation and providing a new user-friendly environment during and after Google Season of Docs 2021.

⁶⁷⁰³ <https://www.cct.lsu.edu>

⁶⁷⁰⁴ <https://www.lsu.edu>

⁶⁷⁰⁵ <https://www3.cs.fau.de>

⁶⁷⁰⁶ <https://www.fau.de>

⁶⁷⁰⁷ <https://www.cct.lsu.edu>

⁶⁷⁰⁸ <https://www.lsu.edu>

⁶⁷⁰⁹ <https://www.cct.lsu.edu>

⁶⁷¹⁰ <https://www.lsu.edu>

⁶⁷¹¹ <https://www.amd.com/en>

⁶⁷¹² <https://www.tudelft.nl/en/eemcs>

⁶⁷¹³ <https://www.tudelft.nl/en/>

- Srinivas Yadav, for his work on SIMD support in algorithms before and during Google Summer of Code 2021.
- Akhil Nair, for his work on adapting algorithms to C++20 before and during Google Summer of Code 2021.
- Alexander Toktarev, for updating the parallel algorithm customization points to use `tag_fallback_invoke` for the default implementations.
- Brice Goglin, for reporting and helping fix issues related to the integration of `hwloc` in *HPX*.
- Giannis Gonidelis, for his work on the ranges adaptation during the Google Summer of Code 2020.
- Auriane Reverdell ([Swiss National Supercomputing Centre](https://www.cscs.ch)⁶⁷¹⁴), for her tireless work on refactoring our CMake setup and modularizing *HPX*.
- Christopher Hinz, for his work on refactoring our CMake setup.
- Weile Wei, for fixing *HPX* builds with CUDA on Summit.
- Severin Strobl, for fixing our CMake setup related to linking and adding new entry points to the *HPX* runtime.
- Rebecca Stobaugh, for her major documentation review and contributions during and after the 2019 Google Season of Documentation.
- Jan Melech, for adding automatic serialization of simple structs.
- Austin McCartney, for adding concept emulation of the Ranges TS bidirectional and random access iterator concepts.
- Marco Diers, reporting and fixing issues related PMIx.
- Maximilian Bremer, for reporting multiple issues and extending the component migration tests.
- Piotr Mikolajczyk, for his improvements and fixes to the set and count algorithms.
- Grant Rostig, for reporting several deficiencies on our web pages.
- Jakub Golinowski, for implementing an *HPX* backend for OpenCV and in the process improving documentation and reporting issues.
- Mikael Simberg ([Swiss National Supercomputing Centre](https://www.cscs.ch)⁶⁷¹⁵), for his tireless help cleaning up and maintaining *HPX*.
- Tianyi Zhang, for his work on HPXMP.
- Shahrzad Shirzad, for her contributions related to Phylanx.
- Christopher Ogle, for his contributions to the parallel algorithms.
- Surya Priy, for his work with statistic performance counters.
- Anushi Maheshwari, for her work on random number generation.
- Bruno Pitrus, for his work with parallel algorithms.
- Nikunj Gupta, for rewriting the implementation of `hpx_main.hpp` and for his fixes for tests.
- Christopher Taylor, for his interest in *HPX* and the fixes he provided. Chris also contributed support for RISC-V architectures.
- Shoshana Jakobovits, for her work on the resource partitioner.
- Denis Blank, who re-wrote our unwrapped function to accept plain values arbitrary containers, and properly deal with nested futures.
- Ajai V. George, who implemented several of the parallel algorithms.

⁶⁷¹⁴ <https://www.cscs.ch>

⁶⁷¹⁵ <https://www.cscs.ch>

- Taeguk Kwon, who worked on implementing parallel algorithms as well as adapting the parallel algorithms to the Ranges TS.
- Zach Byerly ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷¹⁶), who in his work developing applications on top of *HPX* opened tickets and contributed to the *HPX* examples.
- Daniel Estermann, for his work porting *HPX* to the Raspberry Pi.
- Alireza Kheirkhahan ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷¹⁷), who built and administered our local cluster as well as his work in distributed IO.
- Abhimanyu Rawat, who worked on stack overflow detection.
- David Pfander, who improved signal handling in *HPX*, provided his optimization expertise, and worked on incorporating the Vc vectorization into *HPX*.
- Denis Demidov, who contributed his insights with VexCL.
- Khalid Hasanov, who contributed changes which allowed to run *HPX* on 64Bit power-pc architectures.
- Zahra Khatami ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷¹⁸), who contributed the prefetching iterators and the persistent auto chunking executor parameters implementation.
- Marcin Copik, who worked on implementing GPU support for C++AMP and HCC. He also worked on implementing a HCC backend for *HPX.Compute*.
- Minh-Khanh Do, who contributed the implementation of several segmented algorithms.
- Bibek Wagle ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷¹⁹), who worked on fixing and analyzing the performance of the *parcel* coalescing plugin in *HPX*.
- Lukas Troska, who reported several problems and contributed various test cases allowing to reproduce the corresponding issues.
- Andreas Schaefer, who worked on integrating his library ([LibGeoDecomp](https://www.libgeodecomp.org/)⁶⁷²⁰) with *HPX*. He reported various problems and submitted several patches to fix issues allowing for a better integration with [LibGeoDecomp](https://www.libgeodecomp.org/)⁶⁷²¹.
- Satyaki Upadhyay, who contributed several examples to *HPX*.
- Brandon Cordes, who contributed several improvements to the inspect tool.
- Harris Brakmic, who contributed an extensive build system description for building *HPX* with Visual Studio.
- Parsa Amini ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷²²), who refactored and simplified the implementation of AGAS in *HPX* and who works on its implementation and optimization.
- Luis Martinez de Bartolome who implemented a build system extension for *HPX* integrating it with the [Conan](https://www.conan.io/)⁶⁷²³ C/C++ package manager.
- Vinay C Amatya ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁷²⁴), who contributed to the documentation and provided some of the *HPX* examples.
- Kevin Huck and Nick Chaimov ([University of Oregon](https://uoregon.edu/)⁶⁷²⁵), who contributed the integration of APEX (Autonomic Performance Environment for eXascale) with *HPX*.
- Francisco Jose Tapia, who helped with implementing the parallel sort algorithm for *HPX*.

⁶⁷¹⁶ <https://www.lsu.edu>

⁶⁷¹⁷ <https://www.lsu.edu>

⁶⁷¹⁸ <https://www.lsu.edu>

⁶⁷¹⁹ <https://www.lsu.edu>

⁶⁷²⁰ <https://www.libgeodecomp.org/>

⁶⁷²¹ <https://www.libgeodecomp.org/>

⁶⁷²² <https://www.lsu.edu>

⁶⁷²³ <https://www.conan.io/>

⁶⁷²⁴ <https://www.lsu.edu>

⁶⁷²⁵ <https://uoregon.edu/>

- Patrick Diehl, who worked on implementing CUDA support for our companion library targeting GPGPUs ([HPXCL](#)⁶⁷²⁶).
- Eric Lemanissier contributed fixes to allow compilation using the MingW toolchain.
- Nidhi Makhijani who helped cleaning up some enum consistencies in *HPX* and contributed to the resource manager used in the thread scheduling subsystem. She also worked on *HPX* in the context of the Google Summer of Code 2015.
- Larry Xiao, Devang Bacharwar, Marcin Copik, and Konstantin Kronfeldner who worked on *HPX* in the context of the Google Summer of Code program 2015.
- Daniel Bourgeois ([Center for Computation and Technology \(CCT\)](#)⁶⁷²⁷) who contributed to *HPX* the implementation of several parallel algorithms (as proposed by [N4313](#)⁶⁷²⁸).
- Anuj Sharma and Christopher Bross ([Department of Computer Science 3 - Computer Architecture](#)⁶⁷²⁹), who worked on *HPX* in the context of the [Google Summer of Code](#)⁶⁷³⁰ program 2014.
- Martin Stumpf ([Department of Computer Science 3 - Computer Architecture](#)⁶⁷³¹), who rebuilt our contiguous testing infrastructure (see the [HPX Buildbot Website](#)⁶⁷³²). Martin is also working on [HPXCL](#)⁶⁷³³ (mainly all work related to [OpenCL](#)⁶⁷³⁴) and implementing an *HPX* backend for [POCL](#)⁶⁷³⁵, a portable computing language solution based on [OpenCL](#)⁶⁷³⁶.
- Grant Mercer ([University of Nevada, Las Vegas](#)⁶⁷³⁷), who helped creating many of the parallel algorithms (as proposed by [N4313](#)⁶⁷³⁸).
- Damond Howard ([Louisiana State University \(LSU\)](#)⁶⁷³⁹), who works on [HPXCL](#)⁶⁷⁴⁰ (mainly all work related to [CUDA](#)⁶⁷⁴¹).
- Christoph Junghans (Los Alamos National Lab), who helped making our buildsystem more portable.
- Antoine Tran Tan (Laboratoire de Recherche en Informatique, Paris), who worked on integrating *HPX* as a backend for [NT2](#)⁶⁷⁴². He also contributed an implementation of an API similar to Fortran co-arrays on top of *HPX*.
- John Biddiscombe ([Swiss National Supercomputing Centre](#)⁶⁷⁴³), who helped with the BlueGene/Q port of *HPX*, implemented the parallel sort algorithm, and made several other contributions.
- Erik Schnetter (Perimeter Institute for Theoretical Physics), who greatly helped to make *HPX* more robust by submitting a large amount of problem reports, feature requests, and made several direct contributions.
- Mathias Gaunard (Metascale), who contributed several patches to reduce compile time warnings generated while compiling *HPX*.
- Andreas Buhr, who helped with improving our documentation, especially by suggesting some fixes for inconsistencies.

⁶⁷²⁶ <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁷²⁷ <https://www.cct.lsu.edu>

⁶⁷²⁸ <http://wg21.link/n4313>

⁶⁷²⁹ <https://www3.cs.fau.de>

⁶⁷³⁰ <https://developers.google.com/open-source/soc/>

⁶⁷³¹ <https://www3.cs.fau.de>

⁶⁷³² <http://rostam.cct.lsu.edu/>

⁶⁷³³ <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁷³⁴ <https://www.khronos.org/opencv/>

⁶⁷³⁵ <https://portablecl.org/>

⁶⁷³⁶ <https://www.khronos.org/opencv/>

⁶⁷³⁷ <https://www.unlv.edu>

⁶⁷³⁸ <http://wg21.link/n4313>

⁶⁷³⁹ <https://www.lsu.edu>

⁶⁷⁴⁰ <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁷⁴¹ https://www.nvidia.com/object/cuda_home_new.html

⁶⁷⁴² <https://www.numscale.com/nt2/>

⁶⁷⁴³ <https://www.cscs.ch>

- Patricia Grubel ([New Mexico State University](https://www.nmsu.edu)⁶⁷⁴⁴), who contributed the description of the different *HPX* thread scheduler policies and is working on the performance analysis of our thread scheduling subsystem.
- Lars Viklund, whose wit, passion for testing, and love of odd architectures has been an amazing contribution to our team. He has also contributed platform specific patches for FreeBSD and MSVC12.
- Agustin Berge, who contributed patches fixing some very nasty hidden template meta-programming issues. He rewrote large parts of the API elements ensuring strict conformance with the C++ ISO Standard.
- Anton Bikineev for contributing changes to make using `boost::lexical_cast` safer, he also contributed a thread safety fix to the `iostreams` module. He also contributed a complete rewrite of the serialization infrastructure replacing `Boost.Serialization` inside *HPX*.
- Pyry Jähkölä, who contributed the Mac OS build system and build documentation on how to build *HPX* using Clang and `libc++`.
- Mario Mulansky, who created an *HPX* backend for his `Boost.Odeint` library, and who submitted several test cases allowing us to reproduce and fix problems in *HPX*.
- Rekha Raj, who contributed changes to the description of the Windows build instructions.
- Jeremy Kemp how worked on an *HPX* OpenMP backend and added regression tests.
- Alex Nagelberg for his work on implementing a C wrapper API for *HPX*.
- Chen Guo, helvihartmann, Nicholas Pezolano, and John West who added and improved examples in *HPX*.
- Joseph Kleinhenz, Markus Elfring, Kirill Kropivnyansky, Alexander Neundorff, Bryant Lam, and Alex Hirsch who improved our CMake.
- Tapasweni Pathak, Praveen Velliengiri, Jean-Loup Tastet, Michael Levine, Aalekh Nigam, HadrienG2, Prayag Verma, Islada, Alex Myczko, and Avyav Kumar who improved the documentation.
- Jayesh Badwaik, J. F. Bastien, Christoph Garth, Christopher Hinz, Brandon Kohn, Mario Lang, Maikel Nadolski, pierrele, hendrx, Dekken, woodmeister123, xaguilar, Andrew Kemp, Dylan Stark, Matthew Anderson, Jeremy Wilke, Jiazheng Yuan, CyberDrudge, david8dixon, Maxwell Reeser, Raffaele Solca, Marco Ippolito, Jules Penuchot, Weile Wei, Severin Strobl, Kor de Jong, albestro, Jeff Trull, Yuri Victorovich, and Gregor Daiss who contributed to the general improvement of *HPX*.

HPX Funding Acknowledgements⁶⁷⁴⁵ lists current and past funding sources for *HPX*. Special thanks to [Google Summer of Code](https://developers.google.com/open-source/soc/)⁶⁷⁴⁶ and [Google Season of Docs](https://developers.google.com/season-of-docs)⁶⁷⁴⁷ for the continuous support they provide which helps us enhance both our code and our documentation.

⁶⁷⁴⁴ <https://www.nmsu.edu>

⁶⁷⁴⁵ <https://hpx.stellar-group.org/funding-acknowledgements/>

⁶⁷⁴⁶ <https://developers.google.com/open-source/soc/>

⁶⁷⁴⁷ <https://developers.google.com/season-of-docs>

INDEX

- genindex