



## Default Diagram

### Table ack

Idx	Name	Data Type
* Unq	guid	CHAR(36) DEFAULT uuid()
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP
* Pk	id	BIGINT AUTO_INCREMENT
Indexes		
Type	Name	On
Pk	pk_ack	id
Unq	uniq_ack	guid
Options		
engine=InnoDB		

### Table ack\_consumer

Idx	Name	Data Type	Description
* Pk	id	BIGINT AUTO_INCREMENT	
* Unq	consumer	BIGINT DEFAULT 0	
* Idx	status	INT DEFAULT 1	Flag: Pending =1, Delivered=2, Processed=3, Failed=4
* Unq	ack_id	BIGINT	
*	last_trigger	DATETIME DEFAULT CURRENT_TIMESTAMP	when was the last time, this trigger was initiated.. Whenever we send the ack to consumer, we mark it.
*	trigger_count	INT DEFAULT 0	how many times did we try to send this acknowledgement to the consumer
Idx	next_due	DATETIME	
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
*	modified	DATETIME ON UPDATE CURRENT_TIMESTAMP DEFAULT CURRENT_TIMESTAMP	
Indexes			
Type	Name	On	Description
Pk	pk_ack_log	id	
Unq	uniq_ack_consumer	ack_id, consumer	
	idx_ack_consumer	next_due, status	
	idx_ack_consumer_0	consumer, next_due, status	
Foreign Keys			
Type	Name	On	Description
	fk_ack_consumer_ack ( ack_id )	ref ack ( id )	
Options			
engine=InnoDB			

### Table activity

Idx	Name	Data Type	Description
These are minor applicatoin managed activities which the statemachine doesn't have any awareness about.. like, send_email, firstreview, escalatedreview, finalcheck, etc..			
*	display_name	VARCHAR(140)	

## Table activity

* Pk	id	INT AUTO_INCREMENT
	name	VARCHAR(140) GENERATED ALWAYS AS ( lower(trim(display_name)) ) PERSISTENT

### Indexes

Type	Name	On	Description
Pk	pk_runtime_activity	id	

### Options

engine=InnoDB

## Table activity\_status

Idx	Name	Data Type	Description
-----	------	-----------	-------------

These are all execution or activity status, which WorkFlow engine has no visibility about. Like, 'Pending' 'Completed' 'approved', 'Rejected' 'Returned'.. Reason is, we dont know what kind of state each runtime activity might follow.. For instance, one of the runtime activity can have 'Approved', 'Rejected' state.. another can only have 'Sent' 'Pendin' (like, email delivery)

* Pk	id	INT AUTO_INCREMENT
*	display_name	VARCHAR(120)
	name	VARCHAR(120) GENERATED ALWAYS AS ( lower(trim(display_name)) ) PERSISTENT

### Indexes

Type	Name	On	Description
Pk	pk_ext_state	id	

### Options

engine=InnoDB

## Table category

Idx	Name	Data Type
* Pk	id	INT AUTO_INCREMENT
*	display_name	VARCHAR(120)
Unq	name	VARCHAR(120) GENERATED ALWAYS AS (lower(trim(display_name))) PERSISTENT

### Indexes

Type	Name	On
Pk	pk_tbl	id
Unq	unq_category	name

### Options

engine=InnoDB

## Table def\_policies

Idx	Name	Data Type
* Pk	definition	INT
* Pk	policy	INT
*	modified	DATETIME DEFAULT CURRENT_TIMESTAMP

### Indexes

Type	Name	On
Pk	pk_definition_policy	definition, policy

### Foreign Keys

## Table def\_policies

Type	Name	On
------	------	----

	fk_def_policies_definition ( definition ) ref definition ( id )	
--	---	--

	fk_def_policies_policy ( policy ) ref policy ( id )	
--	---	--

### Options

engine=InnoDB

## Table def\_version

Idx	Name	Data Type
* Unq	guid	CHAR(36) DEFAULT uuid()
* Pk	id	INT AUTO_INCREMENT
* Unq	version	INT DEFAULT 1
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP
*	modified	DATETIME ON UPDATE CURRENT_TIMESTAMP DEFAULT CURRENT_TIMESTAMP
* Unq	parent	INT
*	data	LONGTEXT
* Unq	hash	VARCHAR(48)

### Indexes

Type	Name	On
Unq	unq_def_version	parent, version
	fk_def_version_definition	parent
Unq	unq_def_version_0	guid
Pk	pk_def_version	id
Unq	unq_def_version_1	parent, hash

### Foreign Keys

Type	Name	On
	fk_def_version_definition ( parent ) ref definition ( id )	

### Constraints

Name	Definition
cns_def_version	`version` > 0
cns_def_version_0	json_valid(`data`)

### Options

AUTO\_INCREMENT 1990

## Table definition

Idx	Name	Data Type	Description
* Pk	id	INT AUTO_INCREMENT	it should be a code provided by the user.
* Unq	guid	CHAR(36) DEFAULT uuid()	
*	display_name	VARCHAR(200)	
Unq	name	VARCHAR(200) GENERATED ALWAYS AS (lower(trim(display_name)) ) PERSISTENT	
	description	TEXT	
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
* Unq	env	INT DEFAULT 0	

### Indexes

Table definition			
Type	Name	On	Description
Pk	pk_definition	id	
Unq	unq_definition	env, name	
Unq	unq_definition_0	guid	
	idx_definition	name	
Foreign Keys			
Type	Name	On	Description
	fk_definition_environment ( env ) ref environment ( id )		
Options			
AUTO_INCREMENT 1998			

Table environment			
Idx	Name	Data Type	Description
environment code //Doesnt' need to be like dev/prod/test.. It can be an work-group environmetn as well..  //like preq-app (is one environment), so all preq-app (wherever it runs, local, production etc) will be able to read definitions.  //we can even extend it as , preq-app-dev, preq-app-prod etc.			
* Pk	id	INT AUTO_INCREMENT	
*	display_name	VARCHAR(120)	
Unq	name	VARCHAR(120) GENERATED ALWAYS AS (lower(trim(display_name)) ) PERSISTENT	
* Unq	code	INT	
* Unq	guid	VARCHAR(42) DEFAULT uuid()	
Indexes			
Type	Name	On	Description
Pk	pk_environment	id	
Unq	unq_environment	code	
Unq	unq_environment_0	name	
Unq	unq_environment_1	guid	
Options			
engine=InnoDB			

Table events		
Idx	Name	Data Type
* Pk	id	INT AUTO_INCREMENT
*	display_name	VARCHAR(120)
* Unq	code	INT
Unq	name	VARCHAR(120) GENERATED ALWAYS AS (lower(trim(display_name))) PERSISTENT
* Unq	def_version	INT
Indexes		
Type	Name	On
Pk	pk_events	id
Unq	unq_events	def_version, code, name
Unq	unq_events_0	def_version, code
Foreign Keys		

## Table events

Type	Name	On
------	------	----

fk\_events\_def\_version ( def\_version ) ref def\_version ( id )

### Options

engine=InnoDB

## Table hook

Idx	Name	Data Type	Description
-----	------	-----------	-------------

hooks are raised based on policy.. we just check the policy and then raise these hooks

* Pk	id	BIGINT AUTO_INCREMENT
------	----	--------------------------

* Unq	state_id	INT
-------	----------	-----

* Unq	via_event	INT
-------	-----------	-----

* Unq	on_entry	BIT DEFAULT 1	by default, the hooks are for entry.. we can also, setup on leave. 0 - on leaving 1 - on entry
-------	----------	---------------	--

* Unq	route	VARCHAR(180)	event or the route name that needs to be triggered or hooked.
-------	-------	--------------	---

*	created	DATETIME DEFAULT CURRENT_TIMESTAMP
---	---------	---------------------------------------

* Unq	instance_id	BIGINT
-------	-------------	--------

### Indexes

Type	Name	On	Description
------	------	----	-------------

Pk	pk_hooks	id
----	----------	----

Unq	unq_hooks	instance_id, state_id, via_event, on_entry, route
-----	-----------	--

### Foreign Keys

Type	Name	On	Description
------	------	----	-------------

fk\_hooks\_instance ( instance\_id ) ref instance ( id )

### Options

engine=InnoDB

## Table hook\_ack

Idx	Name	Data Type
-----	------	-----------

* Unq	ack_id	BIGINT
-------	--------	--------

* Pk	hook_id	BIGINT
------	---------	--------

### Indexes

Type	Name	On
------	------	----

Pk	pk_hook_ack	hook_id
----	-------------	---------

Unq	unq_hook_ack	ack_id
-----	--------------	--------

### Foreign Keys

Type	Name	On
------	------	----

fk\_hook\_ack\_hook ( hook\_id ) ref hook ( id )

fk\_hook\_ack\_ack ( ack\_id ) ref ack ( id )

### Options

engine=InnoDB

## Table instance

Idx	Name	Data Type	Description
-----	------	-----------	-------------

* Idx	current_state	INT DEFAULT 0
-------	---------------	---------------

Idx	last_event	INT
-----	------------	-----

## Table instance

* Unq	guid	CHAR(36) DEFAULT uuid()	
	policy_id	INT DEFAULT 0	
Unq	external_ref	CHAR(36)	like external workflow id or submission id or transmittal id.. Expected value is a GUID
*	flags	INT UNSIGNED DEFAULT 0	active =1, suspended =2 , completed = 4, failed = 8, archive = 16
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
* Unq	def_version	INT	
*	modified	DATETIME ON UPDATE CURRENT_TIMESTAMP DEFAULT CURRENT_TIMESTAMP	
* Pk	id	BIGINT AUTO_INCREMENT	

### Indexes

Type	Name	On	Description
Pk	pk_instance	id	
Unq	unq_instance	guid	
	fk_instance_state	current_state	
	fk_instance_events	last_event	
	fk_instance_def_version	def_version	
Unq	unq_instance_0	def_version, external_ref	
	idx_instance	external_ref	

### Foreign Keys

Type	Name	On	Description
	fk_instance_def_version ( def_version ) ref def_version ( id )		

### Options

engine=InnoDB

## Table lc\_ack

Idx	Name	Data Type
* Unq	ack_id	BIGINT
* Pk	lc_id	BIGINT

### Indexes

Type	Name	On
Pk	pk_lc_ack	lc_id
Unq	idx_lc_ack	ack_id

### Foreign Keys

Type	Name	On
	fk_lc_ack_lifecycle ( lc_id ) ref lifecycle ( id )	
	fk_lc_ack_ack ( ack_id ) ref ack ( id )	

### Options

engine=InnoDB

## Table lc\_data

Idx	Name	Data Type	Description
* Pk	lc_id	BIGINT	
	actor	VARCHAR(60)	

## Table lc\_data

	payload	LONGTEXT	Could be any data that was the result of this transition (which could be later used as a reference or input for other items)
<b>Indexes</b>			
Type	Name	On	Description
Pk	pk_transition_data	lc_id	
<b>Foreign Keys</b>			
Type	Name	On	Description
	fk_transition_data_transition_log ( lc_id )	ref lifecycle ( id )	
<b>Options</b>			
engine=InnoDB			

## Table lc\_timeout

Idx	Name	Data Type
* Pk	lc_id	BIGINT
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP
<b>Indexes</b>		
Type	Name	On
Pk	pk_timeout	lc_id
<b>Foreign Keys</b>		
Type	Name	On
	fk_timeout_lifecycle ( lc_id )	ref lifecycle ( id )
<b>Options</b>		
engine=InnoDB		

## Table lifecycle

Idx	Name	Data Type	Description
Contains the major states which are controlled by the statemachine			
* Pk	id	BIGINT AUTO_INCREMENT	
*	from_state	INT	
*	to_state	INT	
*	event	INT	
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
* Idx	instance_id	BIGINT	
<b>Indexes</b>			
Type	Name	On	Description
Pk	pk_transition_log	id	
	fk_transition_log_instance	instance_id	
<b>Foreign Keys</b>			
Type	Name	On	Description
	fk_transition_log_instance ( instance_id )	ref instance ( id )	
<b>Options</b>			
engine=InnoDB			

## Table policy

Idx	Name	Data Type	Description
* Pk	id	INT AUTO_INCREMENT	
* Unq	hash	VARCHAR(48)	hash of the policy contents (states, attach modes, routes)



## Table policy

*	content	TEXT	supposedly the policy json
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	

### Indexes

Type	Name	On	Description
Pk	pk_policy	id	
Unq	unq_policy	hash	

### Options

engine=InnoDB

## Table runtime

Idx	Name	Data Type	Description
-----	------	-----------	-------------

Remember, runtime state (or activity track) doesn't need an acknowledgement, because, this information itself is managed in application side and we are only receiving it directly from the app itself.. But, there might be some events that we need to raise for each state based on the policy.. those has to be properly acknowledge.d

*	Unq instance_id	BIGINT	
*	Unq activity	INT	
*	Unq state_id	INT	
*	Unq actor_id	VARCHAR(60) DEFAULT 0	
*	status	INT	
*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
*	modified	DATETIME DEFAULT CURRENT_TIMESTAMP	
*	frozen	BIT DEFAULT 0	For instance, this specific item may have some status, but we might freeze it, meaning, it cannot change status anymore.. unless we unlock the freeze state..
*	lc_id	BIGINT DEFAULT 0	
* Pk	id	BIGINT AUTO_INCREMENT	

### Indexes

Type	Name	On	Description
Pk	pk_micro_log	id	
Unq	unq_execution	instance_id, state_id, activity, actor_id	

### Foreign Keys

Type	Name	On	Description
	fk_execution_runtime_state ( status )	ref activity_status ( id )	
	fk_runtime_instance ( instance_id )	ref instance ( id )	
	fk_runtime_activity ( activity )	ref activity ( id )	

### Options

engine=InnoDB

## Table runtime\_data

Idx	Name	Data Type	Description
	data	LONGTEXT	data that needs to be displayed.. For instance, I can send in a json value, which can then be displayed in the UI with property name/value pair.. So that parsing during display can be reduced ..
	payload	LONGTEXT	Some data associate with this transition.. may or may not be present, which can then be reused or used for idempotency.
* Pk	runtime	BIGINT	

### Indexes

## Table runtime\_data

Type	Name	On	Description
------	------	----	-------------

Pk	pk_runtime_data	runtime	
----	-----------------	---------	--

### Foreign Keys

Type	Name	On	Description
------	------	----	-------------

	fk_runtime_data_runtime ( runtime )	ref runtime ( id )	
--	-------------------------------------	--------------------	--

### Options

engine=InnoDB

## Table state

Idx	Name	Data Type	Description
-----	------	-----------	-------------

* Pk	id	INT AUTO_INCREMENT	
------	----	--------------------	--

*	display_name	VARCHAR(200)	
---	--------------	--------------	--

Unq	name	VARCHAR(200) GENERATED ALWAYS AS (lower(trim(display_name)) ) PERSISTENT	
-----	------	--	--

*	flags	INT UNSIGNED DEFAULT 0	none = 0 is_initial = 1 is_final = 2 is_system = 4 is_error = 8
---	-------	------------------------	---

*	created	DATETIME DEFAULT CURRENT_TIMESTAMP	
---	---------	---------------------------------------	--

	timeout_minutes	INT	in minutes
--	-----------------	-----	------------

*	timeout_mode	INT DEFAULT 0	0 = Once 1 = Repeat
---	--------------	---------------	------------------------

Idx	timeout_event	INT	
-----	---------------	-----	--

* Unq	def_version	INT	
-------	-------------	-----	--

* Idx	category	INT DEFAULT 0	
-------	----------	---------------	--

### Indexes

Type	Name	On	Description
------	------	----	-------------

Pk	pk_state	id	
----	----------	----	--

Unq	unq_state	def_version, name	
-----	-----------	-------------------	--

	fk_state_category	category	
--	-------------------	----------	--

	fk_state_events	timeout_event	
--	-----------------	---------------	--

### Foreign Keys

Type	Name	On	Description
------	------	----	-------------

	fk_state_def_version ( def_version )	ref def_version ( id )	
--	--------------------------------------	------------------------	--

	fk_state_category ( category )	ref category ( id )	
--	--------------------------------	---------------------	--

### Options

engine=InnoDB  
AUTO\_INCREMENT 2014

## Table transition

Idx	Name	Data Type
-----	------	-----------

* Pk	id	INT AUTO_INCREMENT
------	----	--------------------

* Unq	from_state	INT
-------	------------	-----

* Unq	to_state	INT
-------	----------	-----

*	created	DATETIME DEFAULT CURRENT_TIMESTAMP
---	---------	------------------------------------

* Unq	def_version	INT
-------	-------------	-----

* Unq	event	INT
-------	-------	-----

### Indexes

Table transition

Type	Name	On
Pk	pk_transition	id
Unq	uniq_transition	def_version, from_state, to_state, event
	fk_transition_state	from_state
	fk_transition_state_0	to_state
	fk_transition_events	event

Foreign Keys

Type	Name	On
	fk_transition_state ( from_state ) ref state ( id )	
	fk_transition_state_0 ( to_state ) ref state ( id )	
	fk_transition_def_version ( def_version ) ref def_version ( id )	
	fk_transition_events ( event ) ref events ( id )	

Options

engine=InnoDB