

DataStructures-Quiz1(S2 AIE B)

Hi, POOJA S PILLAI. When you submit this form, the owner will see your name and email address.

1

 (2 Points)

In a competition, four different functions are observed. All the functions use a single for loop, same set of statements are executed. Consider the following for loops:

A) for($i = 0; i < n; i++$)

B) for($i = 0; i < n; i += 2$)

C) for($i = 1; i < n; i *= 2$)

D) for($i = n; i <= n; i /= 2$)

If n is the size of input(positive), which function is most efficient(if the task to be performed

☒ A

☐ B

☐ C

☐ D

2

 (2 Points)

Which of the following is not $O(n^2)$?

☐ $(15) * n^2$

- ☐ $n^{1.98}$
- ☒ n^3 / \sqrt{n}
- ☐ $(20) * n^2$

3

 (2 Points)

What does it mean when we say that an algorithm X is asymptotically more effi

- ☐ X will be a better choice for all inputs except possibly small inputs
- ☐ X will be a better choice for all inputs except possibly large inputs
- ☐ Y will be a better choice for small inputs
- ☒ X will be a better choice for all input

4

 (2 Points)

```
int fun1 (int n)
{
    int i, j, k, p, q = 0;
    for (i = 1; i < n; ++i)
    {
        p = 0;
        for (j = n; j > 1; j = j/2)
            ++p;
        for (k = 1; k < p; k = k*2)
            ++q;
    }
    return q;
}
```

Find Time complexity?

- ☐ n^3
- ☐ $n (\log n)^2$
- ☐ $n \log n$

☒ $n\log(\log n)$

5

 (1 Point)

Consider a two dimensional array $A[20][10]$. Assume 4 words per memory cell, the base address is 100, elements are stored in row-major order and first element is $A[0][0]$. What is the address of $A[10][5]$?

☐ 560

☒ 460

☐ 570

☐ 575

6

 (2 Points)

Find the time complexity?

```
int fun(int n)
{
    int count = 0;
    for (int i = 0; i < n; i++)
        for (int j = i; j > 0; j--)
            count = count + 1;
    return count;
}
```

☒ $O(n^2)$

☐ $O(n \cdot \log(n))$

☐ $O(n)$

☐ $O(n \cdot \log(n \cdot \log(n)))$

7

 (1 Point)

Let $w(n)$ and $A(n)$ denote respectively, the worst case and average case running time of an algorithm on an input of size n . which of the following is ALWAYS TRUE?

- ☐ $A(n) = \Omega(W(n))$
- ☒ $A(n) = \Theta(W(n))$
- ☐ $A(n) = O(W(n))$
- ☐ $A(n) = o(W(n))$

8

 (1 Point)

```
double foo (int n){  
    int i;  
    double sum;  
    if (n == 0) return 1.0;  
    else{  
        sum = 0.0;  
        for (i = 0; i < n; i++)  
            sum += foo (i);  
        return sum;  
    }  
}
```

What is the space complexity?

- ☐ $O(1)$
- ☒ $O(n)$
- ☐ $O(n!)$
- ☐ $O(n^n)$

9

 (2 Points)

Consider the following functions:

$$f(n) = 2n$$

$$g(n) = n!$$

$$h(n) = n \log(n)$$

Which of the following statements about the asymptotic behavior of $f(n)$, $g(n)$, and $h(n)$ is true?

- ☐ $f(n) = O(g(n)); g(n) = O(h(n))$
- ☐ $f(n) = \Omega(g(n)); g(n) = O(h(n))$
- ☒ $g(n) = O(f(n)); h(n) = O(f(n))$
- ☐ $h(n) = O(f(n)); g(n) = \Omega(f(n))$

10

 (1 Point)

Suppose you are given an array $s[1..n]$ and a procedure $\text{reverse}(s, i, j)$ which reverses the order of elements in s between positions i and j (both inclusive). What does the following sequence do, where k is a constant?

$\text{reverse}(s, 1, k);$

$\text{reverse}(s, k + 1, n);$

$\text{reverse}(s, 1, n);$

- ☒ Rotates s left by k positions
- ☐ Leaves s unchanged
- ☐ Reverses all elements of s
- ☐ None of the above

11

 (2 Points)

Let A be a two dimensional array declared as follows:

A: array [1 ... 10] [1 ... 15] of integer;

Assuming that each integer takes one memory location, the array is stored in row-major order. If the first element of the array is stored at location 100, what is the address of the element $a[i][j]$?

☒ $15i + j + 84$

☐ $15j + i + 84$

☐ $10i + j + 89$

☐ $10j + i + 89$

12

 (2 Points)

Find out the time complexity?

```
int fun(int n)
{
    int count = 0;
    for (int i = n; i > 0; i /= 2)
        for (int j = 0; j < i; j++)
            count += 1;
    return count;
}
```

☐ $O(n^2)$

☒ $O(n \cdot \log(n))$

☐ $O(n)$

☐ $O(n \cdot \log(n \cdot \log(n)))$

13

 (2 Points)

A three dimensional array is declared as `int A[x][y][z]`. Consider that array elements are stored in row-major order and indexing begins from 0. Here, the address of an item at the location `A[p][q][r]` can be calculated as follows (where w is the word length of an integer):

- ☐ $\&A[0][0][0] + w(y * z * p + z * q + r)$
- ☒ $\&A[0][0][0] + w(x * y * p + z * q + r)$
- ☐ $\&A[0][0][0] + w(x * y * q + z * p + r)$
- ☐ $\&A[0][0][0] + w(y * z * q + z * p + r)$

14

 (1 Point)

Consider the following function,

```
int fun(int n)
{
    int i, j, k = 0;
    for (i = n/2; i <= n; i++)
        for (j = 2; j <= n; j = j * 2)
            k = k + n/2;
    return k;
}
```

What is the time complexity of the function?

- ☐ n^2
- ☒ $n \log n$
- ☐ n^3
- ☐ $n^3 \log n$

15

 (1 Point)

A program P reads in 500 integers in the range $[0..100]$ representing the scores of 500 students. The program P also computes the frequency of each score above 50. What would be the best way for P to store the frequency of each score above 50?

- ☒ An array of 50 numbers
- ☐ An array of 100 numbers

- ☐ An array of 500 numbers
- ☐ A dynamically allocated array of 550 numbers

16

 (1 Point)

Which of the given options provides the increasing order of asymptotic complexity of fun f4?

$f1(n) = 2^n$ $f2(n) = n^{3/2}$ $f3(n) = n \cdot \log(n)$ $f4(n) = n^{\log(n)}$

- ☒ f3, f2, f4, f1
- ☐ f3, f2, f1, f4
- ☐ f2, f3, f1, f4
- ☐ f2, f3, f4, f1

 This form is currently not accepting responses.

This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Powered by Microsoft Forms | [Privacy and cookies](#) | [Terms of use](#)