AVL Trees

* Not confusing
* A lot of moving parts
  → very simple.

→ For every single node in binary Tree must be +1, 0, -1, or 0.



O(N)

= 3 - 0

= 3

→ Balanced binary tree
For every single node in binary Tree must be +1, 0, -1, or 0.
Example:



2 - 1

= 1

Difference ≤ 1
+1, -1 or 0

For every node, $h(l) - h(r)$
$= +1, -1, \text{or } 0$

$h(r) - h(l)$ or $= +1, -1, 0$



* For every Node in the tree, the difference in height of left and right subtree of that node, $\leq 1 \Rightarrow$ Balanced Tree.



$= 3-1$
$= 2$

Not a balanced Tree

Solution?

→ Self balancing binary Tree.

Example: AVL

(Adelson-Velski & Landis)

Algorithm:

① Insert normally node (n)

② Start from node (n) & find the node that makes the tree unbalanced; from bottom up.



③ Using one of the four Rules; rotate

④ On solve the subtree, entire tree above

should be balanced in AVL trees.

We can solve the above problem either by Right rotation or left rotation



* Binary Search Tree properties are holding true for this case

4 Rules :

① Parent, left Child, left Grandchild

Right Rotate (P)



left - left case



Left - Right Case

left Rotate (C)



(Subtrees) $\{t_1, t_2, t_3, t_4\}$

After this Right Rotate p.



Right - Right Case

left rotate on (P)



(4) Right - left Case



this

after left rotate (p)



Example :-

i)



Now, insert node with value 3

This node made it unbalanced. so AVL.

(2-4=-2)



Right Rotate, node with value 10 as pivot.



ii)



insert 45



Left rotate, with value 30 taken as a pivot g



iii)



insert node 7



left rotation 5 as a pivot


13
10
15
6
11
16
5
7
4
Right-Rotation taking
10 as a pivot
13
6
15
5
10
16
4
7
11


iv)
5
2
7
1
4
6
9
3
16
Insert 15
5
2
7
1
4
6
9
3
16
15
R
L
Right-Rotation
16 as a pivot
Solve this
Then whole tree
will be
balanced
5
2
7
1
4
6
9
3
15
16



→ Time Complexity for adding a node.

→ log (N) as the tree is balanced.

→ Rotation Time complexity is constant because we only fixing a subtree and cause of this whole tree will be solved automatically. O(1).

$$= \log(N) + O(1)$$

$$\text{Ans} = O(\log N)$$

Code : for left - left case

```
node height = Math max(
    height(node left), height(
    node. right)) + 1;
return rotate (node);
```

```
private Node rotate (Node node){
    if (height(node.left) - height(node.right)
                                    > 1 ){
    // left heavy case
```




```
    if (height (node left. left) -
        height(node left.right) > 0){
        // left - left case
        return rightRotate (node)
    }
    if (height (node left.left) - height
        (node. left. right) < 0){
        node left = leftRotate (node left);
        return rightRotate (node)
    }
```



left rotate on child.



return node;



if (height(node.left) − height (node.right) <−1) {
// right heavy
if (height(node.right.left) − height(node.right.right) <0) {
// right - right case
return leftRotate(node);
}
if (height(node.right.left) − height(node.right.right) >0){
node.right = rightRotate(node.right);
return leftRotate(node);
}
}
return node;



// How create left rotate or right rotate.



((c.left, c.right)+1)



t_2 will change to diff node

((p.left; P.right+1))

```
public Node rightRotate (Node p){
    Node c = p.left;
    Node t = c.right;

    c.right = p;
    p.left = t;

// Now update the height.

p.height = Math.max(height(p.left),
                    height(p.right) + 1);

c.height = Math.max(height(c.left),
                    height(c.right) + 1);
return c;
}
public Node leftRotate (Node c){
    Node p = c.right;
    Node t = p.left;

    p.left = c;
    c.right = t;

// Now update the height
c.height = Math.max(height(c.left),
                    height(c.right) + 1)
p.height = Math.max(height(p.left),
```

```
        height(p.right) + 1);
    return p;
}

class Main {

    public static void main(String[] args) {
        AVL tree = new AVL();

        for(int i = 0, i < 1000; i++) {
            tree.insert(i);
        }
        System.out.println(tree.height());
    }
}
```