

12

CSS SELECTORS

DIV & SPAN TAGS

Block-level Elements

A block-level element always starts on a new line and takes up the full width available (stretches out to the left and right as far as it can).

The `<div>` element is a block-level element.

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<div>Hello</div>
```

```
<div>World</div>
```

```
<p>The DIV element is a block element, and will start on a new line.</p>
```

```
</body>
```

```
</html>
```

Hello
World

The DIV element is a block element, and will start on a new line.

Inline Elements

An inline element does not start on a new line and only takes up as much width as necessary.

This is an inline element inside a paragraph.

```
<!DOCTYPE html>
<html>
<body>

<span>Hello</span>
<span>World</span>
```

```
<p>The SPAN element is an inline element, and will not start on a new line.</p>
```

```
</body>
</html>
```

Hello World

The SPAN element is an inline element, and will not start on a new line.

The <div> Element

The `<div>` element is often used as a container for other HTML elements.

The `<div>` element has no required attributes, but `style`, `class` and `id` are common.

When used together with CSS, the `<div>` element can be used to style blocks of content:

```
<!DOCTYPE html>
<html>
<body>

<div style="background-color:black;color:white;padding:20px;">
  <h2>London</h2>
  <p>London is the capital city of England. It is the most populous city in the
United Kingdom, with a metropolitan area of over 13 million inhabitants.</p>
  <p>Standing on the River Thames, London has been a major settlement for two
millennia, its history going back to its founding by the Romans, who named it
Londinium.</p>
</div>

</body>
</html>
```

London

London is the capital city of England. It is the most populous city in the United Kingdom, with a metropolitan area of over 13 million inhabitants.

Standing on the River Thames, London has been a major settlement for two millennia, its history going back to its founding by the Romans, who named it Londinium.

The `<span>` tag is used to group inline-elements in a document.

The `<span>` tag provides no visual change by itself.

The `<span>` tag provides a way to add a hook to a part of a text or a part of a document.

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<p>My mother has <span style="color:blue;font-weight:bold">blue</span> eyes and  
my father has <span style="color:darkolivegreen;font-weight:bold">dark  
green</span> eyes.</p>
```

```
</body>
```

```
</html>
```

My mother has blue eyes and my father has dark green eyes.

Contextual

Child $li > a \quad \{ \}$

Descendent $p \ a \quad \{ \}$

Adjacent sibling $h1 + p \quad \{ \}$

General $h1 \sim p \quad \{ \}$

```
<style>
div > p {
    background-color: yellow;
}
```

```
</style>
</head>
<body>
```

```
<h1>Welcome to My Homepage</h1>
```

```
<div>
    <h2>My name is Donald</h2>
    <p>I live in Duckburg.</p>
</div>
```

```
..
```

CHILD

div > p

Welcome to My Homepage

My name is Donald

I live in Duckburg.

DESCENDANT

div p

```
<!DOCTYPE html>
<html>
<head>
<style>
div p {
    background-color: yellow;
}
</style>
</head>
<body>

<h1>Welcome to My Homepage</h1>

<div>
    <h2>My name is Donald</h2>
    <p>I live in Duckburg.</p>
</div>

<p>My best friend is Mickey.</p>

</body>
</html>
```

Welcome to My Homepage

My name is Donald

I live in Duckburg.

My best friend is Mickey.

```
<html>
<head>
<style>
div + p {
    background-color: yellow;
}
</style>
</head>
<body>

<h1>Welcome to My Homepage</h1>

<div>
    <h2>My name is Donald</h2>
    <p>I live in Duckburg.</p>
</div>

<p>My best friend is Mickey.</p>

<p>I will not be styled.</p>

</body>
</html>
```

ADJACENT SIBLING div+p

Welcome to My Homepage

My name is Donald

I live in Duckburg.

My best friend is Mickey.

I will not be styled.

```

p ~ ul {
    background: #ff0000;
}
</style>
</head>
<body>

<div>A div element.</div>
<ul>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>

<p>The first paragraph.</p>
<ul>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>

<h2>Another list</h2>
<ul>
  <li>Coffee</li>

```

GENERAL SIBLING

p~ul

A div element.

- Coffee
- Tea
- Milk

The first paragraph.

- Coffee
- Tea
- Milk

Another list

- Coffee
- Tea
- Milk

Attribute Selectors

Targets elements based on attribute names or values. There are eight types:

Simple attribute selector

Matches an element with a given attribute:

`E[attribute]`

```
img[title] { border: 3px solid; }
```

(Matches every `img` element that has a `title` attribute)

Attribute Selectors (cont'd)

Exact attribute value selector

Matches an element with a specific value for an attribute:

`E[attribute="exact value"]`

`img[title="first grade"] {border: 3px solid;}`

(matches only if the title value is "first grade")

Partial attribute value selector (~)

Matches an element by one part of an attribute value.:

`E[attribute~="value"]`

`img[title~="grade"] {border: 3px solid;}`

(matches "first grade", "second grade", and so on)

Simple

```
<!DOCTYPE html>
<html>
<head>
<style>
a[target] {
    background-color: yellow;
}
</style>
</head>
<body>
```

```
<p>The links with a target attribute gets a yellow background:</p>
```

```
<a href="http://www.w3schools.com">w3schools.com</a>
<a href="http://www.disney.com" target="_blank">disney.com</a>
<a href="http://www.wikipedia.org" target="_top">wikipedia.org</a>
```

```
<p><b>Note:</b> For [<i>attribute</i>] to work in IE8 and earlier, a DOCTYPE must be
declared.</p>
```

```
</body>
</html>
```

The links with a target attribute gets a yellow background:

w3schools.com disney.com wikipedia.org

Exact attribute value

```
<!DOCTYPE html>
<html>
<head>
<style>
a[target=_blank] {
    background-color: yellow;
}
</style>
</head>
<body>

<p>The link with target="_blank" gets a yellow background:</p>

<a href="http://www.w3schools.com">w3schools.com</a>
<a href="http://www.disney.com" target="_blank">disney.com</a>
<a href="http://www.wikipedia.org" target="_top">wikipedia.org</a>

<p><b>Note:</b> For [attribute] to work in IE8 and earlier, a DOCTYPE must be
declared.</p>
</body>
</html>
```

The link with target="_blank" gets a yellow background:

w3schools.com disney.com wikipedia.org

Partial

```
<!DOCTYPE html>
<html>
<head>
<style>
[title~=flower] {
    border: 5px solid yellow;
}
</style>
</head>
<body>

<p>All images with the title attribute containing the word "flower" get a yellow border.</p>





<p><b>Note:</b> For [<i>attribute</i>~=<i>value</i>] to work in IE8 and earlier, a DOCTYPE
must be declared.</p>

</body>
</html>
```

All images with the title attribute containing the word "flower" get a yellow border.

