

PROGRAMMING FUNDAMENTALS

Spring 2024

22nd May

Function to create a text file

```
void OutFunc()
{
    ofstream MyOutFile;
    MyOutFile.open("E:\\TextFiles\\values.txt");
    //now writing data to the file
    MyOutFile << "100\n";
    MyOutFile << "20\n";
    MyOutFile << "15\n";
    MyOutFile << "30\n";
    MyOutFile.close();
}
```

Function to read text file

```
void InFunc()  
{  
  
    ifstream MyInFile;  
    int num[4];  
    MyInFile.open("E:\\TextFiles\\values.txt");  
    int i;  
    for (i = 0; i < 4; i++)  
    {  
        MyInFile >> num[i];  
    }  
}
```

Finding the maximum in the file

```
int max = num[0];
for (i = 0; i < 4; i++)
{
    if (num[i] > max)
    {
        max = num[i];
    }
}
cout<<"The maximum value in the file = "<<max<<endl<<endl;
MyInFile.close();
}
```

Calling functions in main()

```
void OutFunc();
void InFunc();
#include <iostream>
#include <fstream>
using namespace std;
int main()
{
    OutFunc();
    InFunc();
    cout<< "DONE.....\n";
    return 0;
}
```

Question - In class Assignment

- Write a function that generates 15 random numbers from 1 to 100 and stores in a text file
- Write another function that reads the stored values into an integer array. It displays the array and then finds out the maximum value in the array. The maximum value is also displayed.
- The main() function calls both functions and then displays “I AM DONE.....”

Book Ref

- Tony Gaddis
- CH-5