

PPL LAB-4 EXERCISES

📅 Date	@January 30, 2026
--------	-------------------

NAME : DEVADATHAN N R

ROLL NO : 04

SECTION : CSE A1

REG NO : 230905010

Question 1:

Write a MPI program using N processes to find $1! + 2! + \dots + N!$ Use scan.

Code:

```
/*Name : Devadathan N R
Class: CSE A1
Reg No : 230905010
Roll No : 04
*/

#include <stdio.h>
#include <mpi.h>

int main(int argc, char *argv[])
{
    int rank, size, i;
    int fact = 1, sum;

    MPI_Init(&argc, &argv);
```

```

MPI_Comm_rank(MPI_COMM_WORLD, &rank);
MPI_Comm_size(MPI_COMM_WORLD, &size);

for (i = 1; i <= rank + 1; i++)
    fact = fact * i;

MPI_Scan(&fact, &sum, 1, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

if (rank == size - 1)
    printf("Sum of factorials = %d\n", sum);

MPI_Finalize();
return 0;
}

```

Output:

```

STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpicc l4q1.c -o l4q1
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpirun -n 4 ./l4q1
Sum of factorials = 33
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ █

```

Question 2:

Write a MPI program to read a 3 X 3 matrix. Enter an element to be searched in the root process. Find the number of occurrences of this element in the matrix using three processes.

Code:

```

/*
Name : Devadathan N R
Class: CSE A1

```

Reg No : 230905010

Roll No : 04

*/

```
#include <stdio.h>
```

```
#include <mpi.h>
```

```
int main(int argc, char *argv[])
```

```
{
```

```
    int pid, nprocs;
```

```
    int mat[3][3];
```

```
    int key;
```

```
    int part[3];
```

```
    int count_local = 0, count_total = 0;
```

```
    MPI_Init(&argc, &argv);
```

```
    MPI_Comm_rank(MPI_COMM_WORLD, &pid);
```

```
    MPI_Comm_size(MPI_COMM_WORLD, &nprocs);
```

```
    if (nprocs != 3)
```

```
    {
```

```
        if (pid == 0)
```

```
            printf("This program requires exactly 3 processes.\n");
```

```
            MPI_Finalize();
```

```
            return 0;
```

```
    }
```

```
    if (pid == 0)
```

```
    {
```

```
        printf("Enter 3×3 matrix:\n");
```

```
        for (int i = 0; i < 3; i++)
```

```
            for (int j = 0; j < 3; j++)
```

```
                scanf("%d", &mat[i][j]);
```

```
        printf("Enter element to search: ");
```

```
        scanf("%d", &key);
```

```

}

MPI_Bcast(&key, 1, MPI_INT, 0, MPI_COMM_WORLD);

MPI_Scatter(mat, 3, MPI_INT, part, 3, MPI_INT, 0, MPI_COMM_WORLD);

for (int i = 0; i < 3; i++)
    if (part[i] == key)
        count_local++;

MPI_Reduce(&count_local, &count_total, 1, MPI_INT, MPI_SUM, 0, MPI_COMM_WORLD);

if (pid == 0)
    printf("Number of occurrences of %d = %d\n", key, count_total);

MPI_Finalize();
return 0;
}

```

Output:

```

STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpicc l4q2.c -o l4q2
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpirun -n 3 ./l4q2
Enter 3x3 matrix:
1 2 3
4 2 5
2 6 2
Enter element to search: 2
Number of occurrences of 2 = 4
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ █

```

Question 3:

Write a MPI program to read 4 X 4 matrix and display the following output using four processes.

Code:

```
/*
Name : Devadathan N R
Class: CSE A1
Reg No : 230905010
Roll No : 04
*/

#include <stdio.h>
#include <mpi.h>

int main(int argc, char *argv[])
{
    int pid, nprocs;
    int mat[4][4], out[4][4];
    int block[4], prefix[4];

    MPI_Init(&argc, &argv);
    MPI_Comm_rank(MPI_COMM_WORLD, &pid);
    MPI_Comm_size(MPI_COMM_WORLD, &nprocs);

    if (nprocs != 4)
    {
        if (pid == 0)
            printf("This program requires exactly 4 processes.\n");
        MPI_Finalize();
        return 0;
    }

    if (pid == 0)
    {
        printf("Enter 4x4 matrix:\n");
```

```

    for (int i = 0; i < 4; i++)
        for (int j = 0; j < 4; j++)
            scanf("%d", &mat[i][j]);
}

MPI_Scatter(mat, 4, MPI_INT, block, 4, MPI_INT, 0, MPI_COMM_WORLD);

MPI_Scan(block, prefix, 4, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

MPI_Gather(prefix, 4, MPI_INT, out, 4, MPI_INT, 0, MPI_COMM_WORLD);

if (pid == 0)
{
    printf("Output Matrix:\n");
    for (int i = 0; i < 4; i++)
    {
        for (int j = 0; j < 4; j++)
            printf("%d ", out[i][j]);
        printf("\n");
    }
}

MPI_Finalize();
return 0;
}

```

Output:

```

STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpicc l4q3.c -o l4q3
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpirun -n 4 ./l4q3
Enter 4x4 matrix:
1 2 3 4
1 2 3 1
1 1 1 1
2 1 2 1
Output Matrix:
1 2 3 4
2 4 6 5
3 5 7 6
5 6 9 7

```

Question 4:

Write a MPI program to read a word of length N. Using N processes including the root get output word with the pattern as shown.

Code:

```

/*Name : Devadathan N R
Class: CSE A1
Reg No : 230905010
Roll No : 04
*/

#include <stdio.h>
#include <string.h>
#include <mpi.h>

int main(int argc, char *argv[])
{
    int pid, nprocs, length;
    char str[100];

    MPI_Init(&argc, &argv);
    MPI_Comm_rank(MPI_COMM_WORLD, &pid);
    MPI_Comm_size(MPI_COMM_WORLD, &nprocs);

```

```

if (pid == 0)
{
    printf("Enter the word: ");
    scanf("%s", str);
    length = strlen(str);
}

MPI_Bcast(&length, 1, MPI_INT, 0, MPI_COMM_WORLD);

if (nprocs != length)
{
    if (pid == 0)
        printf("Number of processes must be equal to word length\n");
    MPI_Finalize();
    return 0;
}

char letter;
MPI_Scatter(str, 1, MPI_CHAR, &letter, 1, MPI_CHAR, 0, MPI_COMM_WORLD);

char local_buf[100];
int repeat = pid + 1;

for (int i = 0; i < repeat; i++)
    local_buf[i] = letter;
local_buf[repeat] = '\0';

int recv_cnt[100], disp[100];
int total_len = 0;

if (pid == 0)
{
    for (int i = 0; i < nprocs; i++)
    {
        recv_cnt[i] = i + 1;
    }
}

```



```

        disp[i] = total_len;
        total_len += recv_cnt[i];
    }
}

char final_str[500];

MPI_Gatherv(local_buf, repeat, MPI_CHAR, final_str, recv_cnt, disp, MPI_CHAR, 0, MPI_COMM_WORLD);

if (pid == 0)
{
    final_str[total_len] = '\0';
    printf("Output: %s\n", final_str);
}

MPI_Finalize();
return 0;
}

```

Output:

```

STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpicc l4q4.c -o l4q4
STUDENT@MIT-ICT-LAB5-4:~/Desktop/230905010/WEEK4$ mpirun -n 4 ./l4q4
Enter the word: PCAP
Output: PCCAAAPPPP

```