



L^AT_EX Workshop Handout

Debayan Sarkar *
22MS002

Gautam Singh
22MS023

Piyush Kumar Singh †
22MS027

Sabarno Saha
22MS037

*Indian Institute of Science Education and Research, Kolkata,
Mohanpur, West Bengal, 741246, India.*

*[TheSillyCoder.github.io](https://github.com/TheSillyCoder)

†[iamPiyushKrSingh.github.io](https://github.com/iamPiyushKrSingh)

Contents

1 What is L^AT_EX?

L^AT_EX is a software system for high-quality typesetting. It's commonly used for academic papers, scientific reports, books, and other documents that require precise formatting and complex layouts. It is based on the T_EX typesetting system created by Donald Knuth. Unlike word processors like LibreOffice Writer, whose philosophy is based on "WYSIWYG", L^AT_EX focuses on the content of your document and then automatically takes care of the formatting based on a set of instructions you provide. This can be more time-consuming to learn initially, but it can save you time and frustration in the long run, especially for long and complex documents.

Here are some key features of L^AT_EX:

- Document Classes
- Packages
- Mathematics and Equations
- Cross-Referencing
- Bibliography Management
- Professional Typesetting

2 Structure of .tex file

This section will discuss the following part of a generic .tex file.

2.1 Document Class

In a typical .tex file, the first line declares documentclass.

```
\documentclass[12pt, a4paper, two columns]{article}
```

2.2 Preamble

The preamble in a \LaTeX document is the section between the `\documentclass` declaration and the `\begin{document}` command. It plays a crucial role in setting up the document's overall formatting, style, and additional features.

In this section, we do the following things:

1. Package Inclusion
2. Title, Author and Date

For this document we have defined the variable in preamble as follows:

```
\title{\Huge \LaTeX{} Workshop Handout}

\author{\large
Debayan Sarkar
\thanks{{\href{https://thesillycoder.github.io}{TheSillyCoder.github.io}}}
\\ \href{mailto:ds22ms002@iiserkol.ac.in}{22MS002} \and
Gautam Singh
\\ \href{mailto:gs22ms023@iiserkol.ac.in}{22MS023} \and
Piyush Kumar Singh
\thanks{{\href{https://iampiyushkrsingh.github.io}{iamPiyushKrSingh.github.io}}}
\\ \href{mailto:pks22ms027@iiserkol.ac.in}{22MS027} \and
Sabarno Saha
\\ \href{mailto:ss22ms037@iiserkol.ac.in}{22MS037}
}

\date{
\normalsize
\textit{Indian Institute of Science Education and Research, Kolkata, \\
Mohanpur, West Bengal, 741246, India.}
}
```

And for the title page we used the following way:

```
\begin{titlepage}
\% Remove the watermark
\backgroundsetup{contents={}, scale=0.5, opacity=0.05}
```

```

\begin{figure}
\centering
\includegraphics[width = \textwidth]{banner-w.png}
\end{figure}

\vspace{10ex}

\maketitle

\end{titlepage}

```

3. Custom Commands and Settings

4. Bibliography Setup (if using BibLaTeX)

2.3 Main Body

The main body of a \LaTeX document is the enclosed portion between `\begin{document}` and `\end{document}` command. It is where you write the actual content of your document, such as text, sections, mathematical equations, figures, and tables.

3 Document Sectioning

The document sectioning can be done up to 7 levels:

- Part : `\part`
- Chapter : `\chapter`
- Section : `\section`
- Sub-Section : `\subsection`
- Sub-Sub-Section : `\subsubsection`
- Paragraph : `\paragraph`
- Sub-Paragraph : `\subparagraph`

Note: To use part and chapter commands, you must use `report` or `book` documentclass.

You can force a line break by using `\\`. Use `\pagebreak` to force a page break.

4 Font Style, Size and Color

4.1 Font Style

We can stylize the fonts used in our document by following commands:

- **Bold Face:**

```
This is \textbf{bold text}.
```

- *Italics:*

```
This is \textit{italic text}.
```

image

- Underline:

```
\usepackage[normalem]{ulem} % put in preamble
```

```
---
```

```
This is \uline{underlined text}.
```

- *Emphasis:* It is a very context-dependent command but is very useful when we want to emphasize a part of text (without worrying about the formatting)

4.2 Font Size

We have an extensive range of font sizes in L^AT_EX.

- ⊙ `\tiny{Tiny Size}` : Tiny Size
- ⊙ `\scriptsize{Script Size}` : Script Size
- ⊙ `\footnotesize{Footnote Size}` : Footnote Size
- ⊙ `\small{Small Size}` : Small Size
- ⊙ `\normalsize{Normal Size}` : Normal Size
- ⊙ `\large{large Size}` : large Size
- ⊙ `\Large{Large Size}` : Large Size
- ⊙ `\LARGE{LARGE Size}` : LARGE Size
- ⊙ `\huge{huge Size}` : huge Size
- ⊙ `\Huge{Huge Size}` : Huge Size

4.3 Font Color

Use the `xcolor` package to set the text colour. Include `\usepackage{xcolor}` in the preamble.

```
\usepackage{xcolor} % put this in preamble
```

```
\textcolor{red}{This is red text.}
```

This is red text.

5 Math

While writing math in L^AT_EX, there are two environments via which math can be displayed, namely Inline math and Display math

Inline Math Inline math is the environment used when Math is displayed inside a paragraph. The syntax for inline math is `$... $` or `\(... \)`.

Display Math Display Math is the environment used when math is displayed not in a paragraph but on its own. The syntax for display math is multiple `$$... $$` or `\[... \]`.

Here is an example of display versus inline math. So $(a + b)^2 = a^2 + 2ab + b^2$ is inline math whereas

$$(a + b)^2 = a^2 + 2ab + b^2$$

is display math.

5.1 Important Functions

Listed here are some important functions:

- `\frac{355}{113}` $\rightarrow \frac{355}{113}$
- `\int_{0}^{\infty} dx` $\rightarrow \int_0^\infty dx$
- `\int\limits_{0}^{\infty} dx` $\rightarrow \int_0^\infty dx$
- `\iiint dv` $\rightarrow \iiint dv$
- `\oint dr` $\rightarrow \oint dr$
- `\sum_{n=1}^{\infty}` $\rightarrow \sum_{n=1}^\infty$
- `\sum\limits_{n=1}^{\infty}` $\rightarrow \sum_{n=1}^\infty$

$$\bullet \prod_{n=1}^{\infty} \lim_{n \rightarrow \infty} \rightarrow \prod_{n=1}^{\infty}$$

5.2 Greek Symbols

Here is a ready reference for Greek symbols:

α	<code>\alpha</code>	θ	<code>\theta</code>	o	<code>o</code>	τ	<code>\tau</code>
β	<code>\beta</code>	ϑ	<code>\vartheta</code>	π	<code>\pi</code>	υ	<code>\upsilon</code>
γ	<code>\gamma</code>	ι	<code>\iota</code>	ϖ	<code>\varpi</code>	ϕ	<code>\phi</code>
δ	<code>\delta</code>	κ	<code>\kappa</code>	ρ	<code>\rho</code>	φ	<code>\varphi</code>
ϵ	<code>\epsilon</code>	λ	<code>\lambda</code>	ϱ	<code>\varrho</code>	χ	<code>\chi</code>
ε	<code>\varepsilon</code>	μ	<code>\mu</code>	σ	<code>\sigma</code>	ψ	<code>\psi</code>
ζ	<code>\zeta</code>	ν	<code>\nu</code>	ς	<code>\varsigma</code>	ω	<code>\omega</code>
η	<code>\eta</code>	ξ	<code>\xi</code>				
Γ	<code>\Gamma</code>	Λ	<code>\Lambda</code>	Σ	<code>\Sigma</code>	Ψ	<code>\Psi</code>
Δ	<code>\Delta</code>	Ξ	<code>\Xi</code>	Υ	<code>\Upsilon</code>	Ω	<code>\Omega</code>
Θ	<code>\Theta</code>	Π	<code>\Pi</code>	Φ	<code>\Phi</code>		

5.3 \mathcal{AMS} packages

The `amsmath` package enhances the capabilities of LaTeX for mathematical typesetting. It provides various environments for aligning equations, creating multiline equations, and more.

For all environments please read through [documentation](#).

5.3.1 Environments

There are some important environments to encapsulate mathematics: `equation`, `gather` and `align`.

Equation If you want to include an equation in display-style math mode, use the `equation` environment. The syntax is:

```
\begin{equation}
  n > \frac{1}{2} + \sqrt{2m \log \left( \frac{1}{1-p} \right)} + \frac{1}{4}
\end{equation}
```

$$n > \frac{1}{2} + \sqrt{2m \log \left(\frac{1}{1-p} \right) + \frac{1}{4}} \quad (1)$$

Align If you have multiple equations, the align environment aligns equations based on the & delimiter. An example below:

```
\begin{align}
a^4 + 4b^4 &= (a^2+2b^2)^2 - 2(a^2)(2b^2) \nonumber \\
&\tag{Sophie Germain Identity} \\
&= (a^2 - 2ab + 2b^2)(a^2 + 2ab + 2b^2)
\end{align}
```

$$\begin{aligned} a^4 + 4b^4 &= (a^2 + 2b^2)^2 - 2(a^2)(2b^2) \\ &= (a^2 - 2ab + 2b^2)(a^2 + 2ab + 2b^2) \\ &\hspace{10em} \text{(Sophie Germain Identity)} \end{aligned}$$

Gather This environment aligns multiple equations to the centre of the text width. An example :

```
\begin{gather*}
F_n = F_{n-1} + F_{n-2} \\
F_n = \frac{\left(\frac{1+\sqrt{5}}{2}\right)^n - \left(\frac{1-\sqrt{5}}{2}\right)^n}{\sqrt{5}}
\end{gather*}
```

$$\begin{aligned} F_n &= F_{n-1} + F_{n-2} \\ F_n &= \frac{\left(\frac{1+\sqrt{5}}{2}\right)^n - \left(\frac{1-\sqrt{5}}{2}\right)^n}{\sqrt{5}} \end{aligned}$$

5.3.2 AMS Fonts

Math Symbols We use multiple symbols in math and physics.

\mathcal{L} : Lagrangian \mathbb{I}_n : Identity Matrix of dimension n

\Im : Imaginary Part of a complex number

5.4 Physics Package

The physics package is just a list of macros to make writing physics and math easier, i.e. less cumbersome notation.

demaine2023author

For better understanding of these commands read through the [documentation](#).

5.4.1 Automatic bracing

This is very helpful when you write complicated math equations.

$$A = \left(\frac{A + A^T}{2}\right) + \left(\frac{A - A^T}{2}\right) \quad ; \quad A = \left(\frac{A + A^T}{2}\right) + \left(\frac{A - A^T}{2}\right)$$

5.4.2 Vectors

Vectors are typically represented in two ways in books using vector-bold notation or accenting it with an arrow or the unit vectors. Here are both of them:

- `\vb{a}` $\rightarrow \mathbf{a}$. However, this does not work for Greek symbols, so instead of using `\vb{}`, `\vb*{}` needs to be used. However, that also italicizes your letter.
For example `\vb*{\theta}` $\rightarrow \boldsymbol{\theta}$. However it does not italicize Capital Greek Letters eg: `\vb*{\Theta}` $\rightarrow \boldsymbol{\Theta}$.
- `\va{a}` $\rightarrow \vec{a}$. The same conditions apply to Greek Letters.
- `\vu{a}` $\rightarrow \hat{a}$. This can also be done using the `\hat{}` command, which gives \hat{a} .

5.4.3 Derivatives or Partial Derivatives

Partial Derivatives have very useful macros when it comes to the physics package. Here are some syntaxes with certain arguments for differential calculus.

Derivative The standard derivative in Leibniz Notation is written like $\text{\dv{x}} \rightarrow \frac{d}{dx}$. Here are certain variations of it:

- $\text{\dv{f}}{x} \rightarrow \frac{df}{dx}$
- $\text{\dv[n]{y}}{x} \rightarrow \frac{d^n y}{dx^n}$

We can also write in Newton's Notation using $\text{\dot{x}} \rightarrow \dot{x}$. And we have $\text{\ddot{x}} \rightarrow \ddot{x}$.

Partial Dv. We write partial derivatives with some variations in the following syntaxes:

- $\text{\pdv{x}} \rightarrow \frac{\partial}{\partial x}$
- $\text{\pdv{f}}{x} \rightarrow \frac{\partial f}{\partial x}$
- $\text{\pdv[n]{f}}{x} \rightarrow \frac{\partial^n f}{\partial x^n}$
- $\text{\pdv{f}}{x}{y} \rightarrow \frac{\partial^2 f}{\partial x \partial y}$
- $\text{\pdv*{f}}{y} \rightarrow \partial f / \partial y$

Vector Calc. The following syntaxes are useful to define most differential vector calculus.

Grad $\text{\grad{A}} \rightarrow \nabla A$

Divergence $\text{\div{\vb{A}}} \rightarrow \nabla \cdot \mathbf{A}$

Curl $\text{\curl{\vb{A}}} \rightarrow \nabla \times \mathbf{A}$

Laplacian $\text{\laplacian{A}} \rightarrow \nabla^2 A$

Here is a simple example of the use case of the physics package:

$$\begin{aligned}\nabla \cdot \vec{\mathbf{E}} &= \frac{\rho}{\epsilon_0} \\ \nabla \cdot \vec{\mathbf{B}} &= 0 \\ \nabla \times \vec{\mathbf{E}} &= -\frac{\partial \vec{\mathbf{B}}}{\partial t} \\ \nabla \times \vec{\mathbf{B}} &= \mu_0 \vec{\mathbf{J}} + \frac{1}{c^2} \frac{\partial \vec{\mathbf{E}}}{\partial t}\end{aligned}$$

5.4.4 Matrices

For writing matrices, `physics` package provides simple commands like we can write VANDERMONDE MATRIX

```
\mqty(  
1 & 1 & 1 & \cdots & 1 \\  
x_0 & x_1 & x_2 & \cdots & x_n \\  
x_0^2 & x_1^2 & x_2^2 & \cdots & x_n^2 \\  
\vdots & \vdots & \vdots & & \vdots \\  
x_0^n & x_1^n & x_2^n & \cdots & x_n^n  
)
```

$$\begin{vmatrix} 1 & 1 & 1 & \cdots & 1 \\ x_0 & x_1 & x_2 & \cdots & x_n \\ x_0^2 & x_1^2 & x_2^2 & \cdots & x_n^2 \\ \vdots & \vdots & \vdots & & \vdots \\ x_0^n & x_1^n & x_2^n & \cdots & x_n^n \end{vmatrix}$$

6 Images, Floats, Captions

In LaTeX, figures (images) are typically handled as floats. Floats are containers for things in a document that cannot be broken over a page. They are "floated" to a location, such as the top or bottom of a page, and can include images, tables, and other similar elements.

```
\begin{figure}[H]  
  \centering  
  \includegraphics[width=0.48\textwidth]{guatam-lol.jpeg}  
  \caption{Gautam Singh (22MS023) CP}  
  \label{fig:gautam}  
\end{figure}
```



Figure 1: Gautam Singh (22MS023) CP

6.1 Adding Multiple Images

To add multiple images in LaTeX, you can use the `subfigure` environment from the `subcaption` package.

```
\begin{figure}[H]

\begin{subfigure}{0.5\textwidth}
\centering
\includegraphics[scale=0.12]{vikash-lol.jpeg}
\caption{Vikash Kumar (22MS036) \cite{gato2011schroedingers}}
\label{fig:vikash}
\end{subfigure}
\begin{subfigure}{0.5\textwidth}
\centering
\includegraphics[width=0.9\linewidth]{ronit-lol.jpeg}
\caption{Ronit Bhuyan (22MS025)}
```

```

\label{fig:ronit}
\end{subfigure}

\begin{subfigure}{0.5\textwidth}
\centering
\includegraphics[width = 0.9\linewidth]{sabarno-lol.jpeg}
\caption{Sabarno Saha (22MS037)}
\label{fig:sabarno}
\end{subfigure}
\begin{subfigure}{0.5\textwidth}
\centering
\includegraphics[width=0.9\linewidth]{debayan-lol.jpeg}
\caption{Debayan Sarkar (22MS002)}
\label{fig:debayan}
\end{subfigure}

\caption{People who helped in this handout}
\label{fig:multipleImg}
\end{figure}

```

Here we will discuss how to refer this images:

You can reference individual subfigures using `\autoref{fig:vikash}` and `\autoref{fig:sabarno}`. The overall figure is referenced using `\autoref{fig:multipleImg}`.

You can reference individual subfigures using `??` and `??`. The overall figure is referenced using `??`.



(a) Vikash Kumar (22MS036)
gato2011schroedingers



(b) Ronit Bhuyan (22MS025)



(c) Sabarno Saha (22MS037)



(d) Debayan Sarkar (22MS002)

Figure 2: People who helped in this handout

7 Lists

7.1 Unordered List

To create unordered lists in \LaTeX , one can use the `itemize` environment. Individual items are added using the `\item` command. Shown below is an easy example of how to create unordered (bulleted) lists:

```
\begin{itemize}
  \item Diane
  \item Todd
  \item Carolyn
  \item[\textbf{Sarah}] Lynn
\end{itemize}
```

- Diane
- Todd
- Carolyn

Sarah Lynn

7.2 Ordered List

One can create Ordered Lists using the `enumerate` environment. Again, each item in the list is created using the `\item` command. Below is a simple example showing the same:

```
\begin{enumerate}
  \item Ted
  \item Barney
  \item Robin
  \item Lilly
  \item Marshall
\end{enumerate}
```

1. Ted
2. Barney

3. Robin
4. Lilly
5. Marshall

7.3 Nested Lists

Sometimes, you may want to create lists inside lists. To create one in L^AT_EX, you do just that! i.e., create another `enumerate` environment inside the existing one. Here's an example:

```
\begin{enumerate}
  \item King
  \item S-Class
  \begin{enumerate}
    \item Blast
    \item Tornado
  \end{enumerate}
  \item A-Class
  \begin{enumerate}
    \item Sweet Mask
    \item Caped Baldy
  \end{enumerate}
\end{enumerate}
```

1. King
2. S-Class
 - (a) Blast
 - (b) Tornado
3. A-Class
 - (a) Sweet Mask
 - (b) Caped Baldy

7.4 Custom Labels

Sometimes, you may not want to use the default symbols or numberings for the labels in the lists. You may want to customize them. You can also do that in L^AT_EX using the `enumitem` package. For instance, if you're typing out some questions and you want the questions to be labelled as Q1, Q2, and so on instead of the default 1,2, etc., you could do this:

```
\begin{enumerate}[label=Q\arabic*.]
  \item This is question 1.
  \item This is question 2.
\end{enumerate}
```

- Q1. Let a and b be two positive integers such that $ab + 1$ divides $\frac{a^2 + b^2}{ab + 1}$. Show that $\frac{a^2 + b^2}{ab + 1}$ is the square of an integer.
- Q2. Show that every even integer can be written as the sum of two primes.

8 Table

This is the simplest way to create a table in L^AT_EX using the `tabular` environment:

```
\begin{center}
\begin{tabular}{c c c }
  cell1 & cell2 & cell3 \\
  cell4 & cell5 & cell6 \\
  cell7 & cell8 & cell9
\end{tabular}
\end{center}
```

cell1	cell2	cell3
cell4	cell5	cell6
cell7	cell8	cell9

8.1 Column and Row borders

However, as you can see, this doesn't have column borders. The `{c c c}` implies that the table generated will have three columns, without any column borders, and the text will be centre-aligned in each of the cells. The cell contents are separated by `&`, and the rows are separated by `\\`. To create a table with column borders, you can use `{| c | c | c |}` as shown below:

```
\begin{center}
\begin{tabular}{| c | c | c |}
  cell1 & cell2 & cell3 \\
  cell4 & cell5 & cell6 \\
  cell7 & cell8 & cell9
\end{tabular}
\end{center}
```

cell1	cell2	cell3
cell4	cell5	cell6
cell7	cell8	cell9

Still, there aren't any row borders. To add those, you can add `\hline` in the appropriate line. An example is shown below:

```
\begin{center}
\begin{tabular}{| c | c | c |}
\hline
  cell1 & cell2 & cell3 \\
\hline
  cell4 & cell5 & cell6 \\
\hline
  cell7 & cell8 & cell9 \\
\hline
\end{tabular}
\end{center}
```

cell1	cell2	cell3
cell4		
cell7		_

8.2 Merged Rows and Columns

You may want to merge some rows or columns. In other words, you may want some cells to span across multiple rows/columns. You can do that after including the `multirow` package in the preamble, as shown in the example below:

```
\begin{table}[h]
  \centering
  \begin{tabular}{|c|c|c|}
    \hline
    col1 & col2 & col3 \\
    \hline
    \multicolumn{2}{|c|}{Spans 2 columns} & no span \\
    \hline
    \multirow{3}{3em}{Spans 2 rows} & cell2 & cell3 \\
    & cell5 & cell6 \\
    & cell8 & cell9 \\
    \hline
  \end{tabular}
  \caption{This is a table caption}
  \label{Table:merge}
\end{table}
```

col1	col2	col3
Spans 2 columns		no span
Spans 2 rows	cell2	cell3
	cell5	cell6
	cell8	cell9

Table 1: This is a table caption

This also adds a caption and a label to the table using the `table` environment.

That ends our discussion on the basics of \LaTeX tables. With some further styling, you can create stuff like this.

Method of undetermined coefficients	
$f_i(t)$	y_{p_i}
Ke^{at}	ke^{at}
Kt^m	$k_mt^m + k_{m-1}t^{m-1} + \dots + k_0$
$K \cos(bt)$ or $K \sin(bt)$	$k_1 \sin(bt) + k_2 \cos(bt)$
$Ke^{at} \sin(bt)$ or $Ke^{at} \cos(bt)$	$e^{at}(k_1 \sin(bt) + k_2 \cos(bt))$
$Kt^m e^{at}$	$e^{at}(k_mt^m + k_{m-1}t^{m-1} + \dots + k_0)$
$Kt^m \cos(bt)$ or $Kt^m \sin(bt)$	$(k_mt^m + \dots + k_0)(a_1 \sin(bt) + a_2 \cos(bt))$

9 Adding Bibliography

As there are multiple methodologies to add BIBLIOGRAPHY, we have decided to go with Biber backend and Biblatex as formatting packages for this discussion. The other options are the Bibtex backend and natbib package [timokhin2020novel](#). Adding a bibliography is a very big discussion, so we recommend you go through: [overleaf blog](#). Or for a detailed introduction, read through [biblatex guide](#).

And to better understand the decision we made, please go through this [Stack Exchange](#) answer.

10 Extra Useful Packages

10.1 Geometry

The `geometry` package in L^AT_EX is a powerful tool that allows users to customize the layout of their documents by adjusting page dimensions, margins, and other related parameters. It provides a convenient interface for controlling the overall geometry of a page.

To get very good idea of useability of this package read through the [documentation](#).

```
\usepackage{geometry}
```

```
\geometry{left=1in, right=1in, top=1in, bottom=1in}
```

10.2 Hyperref

The `hyperref` package is a powerful tool in \LaTeX that allows you to create hyperlinks within your documents. It is commonly used for adding hyperlinks to sections, figures, citations, URLs, and internal references. The `hyperref` package also provides options for customizing the appearance of links and other interactive features.

To get very good idea of useability of this package read through the [documentation](#).

10.2.1 Hyperlinks

The `\href{URL}{text}` command is used to create hyperlinks. For example:

```
\href{https://www.example.com}{Visit our website}
```

[Visit our website](#)

The `\url{}` command is available for typesetting URLs, and `hyperref` allows you to customize the appearance of these links:

```
\url{gnu.org}
```

[gnu.org](#)

10.2.2 Cross Referencing

`hyperref` provides commands like `\autoref`, `\nameref` and `\ref` that automatically generate the appropriate prefix for cross-references. For example:

This is an example `\autoref{Table:merge}`. And this works `\nameref{Table:merge}`.

This is an example `??`. And this works `??`.

10.2.3 PDF Metadata

The `hyperref` package allows you to set metadata for the PDF file, such as the title, author, and keywords:

```
\hypersetup{
  pdftitle={LaTeX Handout Slashdot},
  pdfauthor={Piyush, Sabarno, Debayan, Gautam},
  pdfsubject={Slashdot},
  pdfkeywords={handout, latex, slashdot},
  pdfpagemode=FullScreen,
}
```

10.2.4 Customizing Link Colors

You can customize the color of hyperlinks using the `colorlinks` option and related options such as `linkcolor`, `citecolor`, and `urlcolor`:

```
\hypersetup{
  draft = false,
  linktocpage = true,
  colorlinks=true,
  linkcolor=DeepSkyBlue4,
  filecolor=magenta,
  urlcolor=teal,
  citecolor=Green4,
}
```

10.3 tcolorbox, mdframed

10.4 tikz, pgfplots

An example using Tikz:

```
\tikzset{every picture/.style={line width=0.75pt}} %set default line
width to 0.75pt

\begin{center}

\begin{tikzpicture}[x=0.75pt,y=0.75pt,yscale=-1,xscale=1]
uncomment if require: \path (0,300); %set diagram left start at 0,
```


and has height of 300

```
Straight Lines [id:da5022345784814793]
\draw (170,158.81) -- (203.13,158.42) ;
Straight Lines [id:da015487184503324869]
\draw (486.86,159.97) -- (519.99,159.58) ;
Shape: Inductor (Air Core) [id:dp6825263183809437]
\draw (203.13,159.97) -- (228.66,159.97) ..
controls (229.03,155.88) and (232.58,152.38) ..
(237.59,151.15) .. controls (242.61,149.93) and
(248.08,151.23) .. (251.36,154.43) ..
controls (253.9,156.93) and (254.93,160.16) .. (254.2,163.3) ..
controls (254.2,164.52) and (252.93,165.51) ..
(251.36,165.51) .. controls (249.8,165.51) and
(248.53,164.52) ..
(248.53,163.3) .. controls (247.8,160.16) and (248.83,156.93) ..
(251.36,154.43) .. controls (254.31,151.77) and (258.42,150.26) ..
(262.71,150.26) .. controls (267.01,150.26) and (271.11,151.77) ..
(274.06,154.43) .. controls (276.6,156.93) and (277.63,160.16) ..
(276.9,163.3) .. controls (276.9,164.52) and (275.63,165.51) ..
(274.06,165.51) .. controls (272.5,165.51) and (271.22,164.52) ..
(271.22,163.3) .. controls (270.49,160.16) and (271.53,156.93) ..
(274.06,154.43) .. controls (277.01,151.77) and (281.12,150.26) ..
(285.41,150.26) ..
controls (289.71,150.26) and (293.81,151.77) .. (296.76,154.43) ..
controls (299.3,156.93) and (300.33,160.16) .. (299.6,163.3) ..
controls (299.6,164.52) and (298.33,165.51) .. (296.76,165.51) ..
controls (295.2,165.51) and (293.92,164.52) .. (293.92,163.3) ..
controls (293.19,160.16) and (294.23,156.93) .. (296.76,154.43) ..
controls (300.05,151.23) and (305.51,149.93) .. (310.53,151.15) ..
controls (315.55,152.38) and (319.09,155.88) .. (319.46,159.97)
-- (345,159.97) ;
Shape: Inductor (Air Core) [id:dp8148657217032366]
\draw (345,159.97) -- (370.53,159.97) .. controls (370.9,155.88)
and (374.44,152.38) .. (379.46,151.15) .. controls (384.48,149.93)
and (389.94,151.23) .. (393.23,154.43) .. controls (395.77,156.93)
and (396.8,160.16) .. (396.07,163.3) .. controls (396.07,164.52)
and (394.8,165.51) .. (393.23,165.51) .. controls (391.67,165.51)
and (390.39,164.52) .. (390.39,163.3) .. controls (389.66,160.16)
and (390.7,156.93) .. (393.23,154.43) .. controls (396.18,151.77)
and (400.29,150.26) .. (404.58,150.26) .. controls (408.88,150.26)
and (412.98,151.77) .. (415.93,154.43) .. controls (418.46,156.93)
and (419.5,160.16) .. (418.77,163.3) .. controls (418.77,164.52)
```

```

and (417.5,165.51) .. (415.93,165.51) .. controls (414.36,165.51)
and (413.09,164.52) .. (413.09,163.3) .. controls (412.36,160.16)
and (413.4,156.93) .. (415.93,154.43) .. controls (418.88,151.77)
and (422.98,150.26) .. (427.28,150.26) .. controls
and (435.68,151.77) .. (438.63,154.43) .. controls (441.16,156.93)
and (442.2,160.16) .. (441.47,163.3) .. controls (441.47,164.52)
and (440.19,165.51) .. (438.63,165.51) .. controls (437.06,165.51)
and (435.79,164.52) .. (435.79,163.3) .. controls (435.06,160.16)
and (436.09,156.93) .. (438.63,154.43) .. controls (441.92,151.23)
and (447.38,149.93) .. (452.4,151.15) .. controls (457.42,152.38)
and (460.96,155.88) .. (461.33,159.97) -- (486.86,159.97) ;
Shape: Ellipse [id:dp8047912166467549]
\draw [fill={rgb, 255:red, 208; green, 2; blue, 27 } ,fill opacity=1 ]
(194.55,158.42) .. controls (194.55,153.68) and (198.39,149.84) ..
(203.13,149.84) .. controls (207.86,149.84) and (211.7,153.68) ..
(211.7,158.42) .. controls (211.7,163.15) and (207.86,166.99) ..
(203.13,166.99) .. controls (198.39,166.99) and (194.55,163.15)
.. (194.55,158.42) -- cycle ;
Shape: Circle [id:dp49546281137757386]
\draw [fill={rgb, 255:red, 208; green, 2; blue, 27 }
,fill opacity=1 ] (336.42,159.97) .. controls (336.42,155.24)
and (340.26,151.4) .. (345,151.4) .. controls (349.73,151.4) and
(353.57,155.24) .. (353.57,159.97) .. controls (353.57,164.71) and
(349.73,168.55) .. (345,168.55) .. controls (340.26,168.55) and
(336.42,164.71) .. (336.42,159.97) -- cycle ;
Shape: Circle [id:dp9959933438432824]
\draw [fill={rgb, 255:red, 208; green, 2; blue, 27 } ,fill opacity=1 ]
(476.73,159.97) .. controls (476.73,155.24) and
(480.57,151.4) .. (485.3,151.4) .. controls (490.04,151.4)
and (493.88,155.24) .. (493.88,159.97) .. controls (493.88,164.71)
and (490.04,168.55) .. (485.3,168.55) .. controls (480.57,168.55)
and (476.73,164.71) .. (476.73,159.97) -- cycle ;
Straight Lines [id:da16493973175062104]
\draw (213.7,190.37) -- (334.42,190.37) ;
\draw [shift={(336.42,190.37)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (10.93,-3.29) ..
controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) .. controls (3.31,0.3) and (6.95,1.4) ..
\draw [shift={(211.7,190.37)}, rotate = 0]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (10.93,-3.29) ..
controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) ..
controls (3.31,0.3) and (6.95,1.4) .. (10.93,3.29) ;

```

```

Straight Lines [id:da6883373457143276]
\draw (354.01,190.37) -- (474.73,190.37) ;
\draw [shift={(476.73,190.37)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (10.93,-3.29) ..
controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) ..
controls (3.31,0.3) and (6.95,1.4) .. (10.93,3.29) ;
\draw [shift={(352.01,190.37)}, rotate = 0]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (10.93,-3.29) .. controls (6.95,-1.4)
and (3.31,-0.3) .. (0,0) .. controls (3.31,0.3)
and (6.95,1.4) .. (10.93,3.29) ;
Straight Lines [id:da45630246419082066]
\draw (196.11,135.81) -- (240.88,135.81) ;
\draw [shift={(242.88,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (10.93,-3.29) ..
controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) ..
controls (3.31,0.3) and (6.95,1.4) .. (10.93,3.29) ;
\draw [shift={(196.11,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ]
[line width=0.75] (0,5.59) -- (0,-5.59) ;
Straight Lines [id:da01247346381592962]
\draw (336.42,135.81) -- (396.78,135.81) ;
\draw [shift={(398.78,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ][line width=0.75]
(10.93,-3.29) .. controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) ..
controls (3.31,0.3) and (6.95,1.4) .. (10.93,3.29) ;
\draw [shift={(336.42,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ][line width=0.75]
(0,5.59) -- (0,-5.59) ;
Straight Lines [id:da9085291482549834]
\draw (476.73,135.81) -- (521.5,135.81) ;
\draw [shift={(523.5,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ][line width=0.75]
(10.93,-3.29) .. controls (6.95,-1.4) and (3.31,-0.3) .. (0,0) ..
controls (3.31,0.3) and (6.95,1.4) .. (10.93,3.29) ;
\draw [shift={(476.73,135.81)}, rotate = 180]
[color={rgb, 255:red, 0; green, 0; blue, 0 } ][line width=0.75]
(0,5.59) -- (0,-5.59) ;


Text Node
\draw (268.06,197.59) node [anchor=north west][inner sep=0.75pt]

```

```

{$a$};
Text Node
\draw (409.93,198.36) node [anchor=north west][inner sep=0.75pt]
{$a$};
Text Node
\draw (200.72,112.4) node [anchor=north west][inner sep=0.75pt]
{$x_{n-1}$};
Text Node
\draw (350.59,112.4) node [anchor=north west][inner sep=0.75pt]
{$x_n$};
Text Node
\draw (481.34,112.4) node [anchor=north west][inner sep=0.75pt]
{$x_{n+1}$};
Text Node
\draw (182.24,167.19) node [anchor=north west][inner sep=0.75pt]
{$n-1$};
Text Node
\draw (340.56,167.19) node [anchor=north west][inner sep=0.75pt]
{$n$};
Text Node
\draw (465.19,167.19) node [anchor=north west][inner sep=0.75pt]
{$n+1$};
\end{tikzpicture}
\end{center}

```



Here are some things you can plot with ease using pgfplots(All of these are from Projects in IISER-K)(Code provided above):

Bar Graph

```


\begin{tikzpicture}
  \begin{axis}
    [
      ybar,
      enlargelimits=0.15,
      ylabel={\ No of Votes},

```

```

symbolic x coords={1,2,3,4,5,6,7,8,9,10},
xtick=data,
nodes near coords,
nodes near coords align={vertical},
]
\addplot coordinates {(1,11) (2,7) (3,3) (4,8)
(5,22) (6,8) (7,10) (8,18) (9,11) (10,19)};
\end{axis}
\end{tikzpicture}

```



Line Graph

```


\begin{center}
\begin{tikzpicture}
\begin{axis}[
width =4.5 in,
xlabel=\textbf{Generation},
ylabel=\textbf{Prey Population},
grid=major,
xtick={1,2,3,4,5,6,7}]
\addplot[color=red,mark=*] coordinates {
(1,20)
(2,12)
(3,20)
(4,30)
(5,48)
(6,84)
(7,154)
};
\end{axis}
\end{tikzpicture}
\end{center}

```

```

\end{tikzpicture}
\end{center}

```




Pie Chart

```

\begin{center}
\begin{tikzpicture}
\pie[sum =43,scale font, radius = 3,text=legend]
{3/White Bean - 3,7/Black Bean - 7,33/Pasta - 33}
\end{tikzpicture}
\end{center}

```



11 Appendix

Here are some links to help you out with further \LaTeX questions:

- [Google.com](#) :)
- [Overleaf.com](#) This is a link to fairly well documented \LaTeX tutorials.
- [r/Latex](#)
- [\text{\LaTeX} Stack Exchange](#)
- [The Comprehensive Tex Archive Network\(CTAN\)](#) It is a very useful resource if you need to study the syntax of a particular package.
- [The \text{\LaTeX} Companion](#) A book.

List of Figures

List of Tables