

# Module 05: CS31003: Compilers: Machine Independent Translation

Pralay Mitra  
Partha P Das

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*pralay@cse.iitkgp.ac.in*  
*ppd@cse.iitkgp.ac.in*

August 19, 20, 26 & 31 and  
September 02, 03, 09 & 30, 2019

# Module Objectives

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Understand Intermediate Representations
- Symbol Tables
- Understand Syntax Directed Translation
- Understand how Semantic Actions be guided by Syntactic Translation (using Attributed Grammars)

# Module Outline

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Three Address Codes
- Symbol Table
  - Notion and Purpose
  - Scope Management Examples
  - Interface
  - Implementation
- Syntax-Directed Translation to Intermediate Codes for:
  - Arithmetic Expressions (and simple assignment)
  - Boolean Expressions (and elementary control flow)
  - Control Constructs (if, if-else, while, do-while, for, switch)
  - Variable declarations and datatypes
  - Translation by type
  - Arrays in Expressions
  - Type Expressions
  - Functions (definition, invocation, and computations)
  - Scope Management (nested lexical scopes)

# Intermediate Representations

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Three Address Code

# Intermediate Representations (IR)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Each compiler uses 2-3 IRs
- Multi-Level Intermediate Representations
  - High-Level Representations (HIR)
    - Preserves loop structure and array bounds
    - **Abstract Syntax Tree (AST) / DAG**
      - Condensed form of parse tree
      - Useful for representing language constructs
      - Depicts the natural hierarchical structure of the source program
      - \* Each internal node represents an operator
      - \* Children of the nodes represent operands
      - \* Leaf nodes represent operands
    - DAG is more compact than AST because common sub expressions are eliminated
  - Mid-Level Representations (MIR):
    - Reflects range of features in a set of source languages
    - Language independent
    - Good for code generation for a number of architectures
    - Appropriate for most optimization opportunities
    - **Three-Address Code (TAC)**
  - Low-Level Representations (LIR):
    - Corresponds one to one to target machine instructions
    - **Assembly Language of x86**

# Alternate Intermediate Representations

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- SSA: Single Static Assignment
- RTL: Register transfer language
- Stack machines: P-code
- CFG: Control Flow Graph
- Dominator Trees
- DJ-graph: dominator tree augmented with join edges
- PDG: Program Dependence Graph
- VDG: Value Dependence Graph
- GURRR: Global unified resource requirement representation. Combines PDG with resource requirements
- Java intermediate bytecodes
- ...

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Concepts

- Address
- Instruction

In general these could be classes, specializing for every specific type.

- Uses only up to 3 addresses in every instruction
- Every 3 address instruction is represented by a quad – opcode, argument 1, argument 2, and result

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Address Types

- *Name:*

Source program names appear as addresses in 3-Address Codes.

- *Constant:*

Many different types and their (implicit) conversions are allowed as deemed addresses.

- *Compiler-Generated Temporary:*

Create a distinct name each time a temporary is needed - good for optimization.



# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Instruction Types

For Addresses  $x$ ,  $y$ ,  $z$ , and Label  $L$

- *Binary Assignment Instruction*: For a binary op (including arithmetic, logical, or bit operators):

$$x = y \text{ op } z$$

- *Unary Assignment Instruction*: For a unary operator op (including unary minus, logical negation, shift operators, conversion operators):

$$x = \text{op } y$$

- *Copy Assignment Instruction*:

$$x = y$$

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Instruction Types

For Addresses x, y, and Label L

- *Unconditional Jump:*

goto L

- *Conditional Jump:*

- *Value-based:*

if x goto L

ifFalse x goto L

- *Comparison-based:* For a relational operator op (including <, >, ==, !=, ≤, ≥):

if x relop y goto L

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Instruction Types

For Addresses  $p$ ,  $x_1$ ,  $x_2$ , and  $x_N$

- Procedure Call: A procedure call  $p(x_1, x_2, \dots, x_N)$  having  $N \geq 0$  parameters is coded as:

```
param x1
param x2
...
param xN
y = call p, N
```

Note that  $N$  is not redundant as procedure calls can be nested.

- Return Value: Returning a return value and /or assigning it is optional. If there is a return value it is returned from the procedure  $p$  as:

```
return n
```

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Instruction Types

For Addresses  $x$ ,  $y$ , and  $i$

- *Indexed Copy Instructions:*

$x = y[i]$

$x[i] = y$

- *Address and Pointer Assignment Instructions:*

$x = \&y$

$x = *y$

$*x = y$

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Example

```
do i = i + 1; while (a[i] < v);
```

translates to

```
L: t1 = i + 1
   i = t1
   t2 = i * 8
   t3 = a[t2]
   if t3 < v goto L
```

The symbolic label is then given positional numbers as:

```
100: t1 = i + 1
101: i = t1
102: t2 = i * 8
103: t3 = a[t2]
104: if t3 < v goto 100
```

# Three Address Code

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- For

```
L: t1 = i + 1
    i = t1
    t2 = i * 8
    t3 = a[t2]
    if t3 < v goto L
```

quads are represented as:

	op	arg 1	arg 2	result
0	+	i	1	t1
1	=	t1	null	i
2	*	i	8	t2
3	=[]	a	t2	t3
4	<	t3	v	L

# Handling Symbols in a Program

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

**Sym. Tab.**

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Symbol Table

# Symbol Table

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- When identifiers are found by the lexical analyzer, they are entered into a **Symbol Table**, which will hold all relevant information about identifiers.
- This information is updated later by Syntax Analyzer, and used & updated even later by the Semantic Analyzer and the Code Generator.





# Symbol Table: Entries

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- An ST stores varied information about identifiers:
  - Name (as a string)
    - Name may be qualified for scope or overload resolution
  - Data type (explicit or pointer to Type Table)
  - Block level
  - Scope (global, local, parameter, or temporary)
  - Offset from the base pointer (for local variables and parameters only)
  - Initial value (for global and local variables), default value (for parameters)
  - Others (depending on the context)
- A Name (Symbol) may be any one of:
  - Variable (user-define / unnamed temporary)
  - Constant (String and non-String)
  - Function / Method (Global / Class)
  - Alias
  - Type – Class / Structure / Union
  - Namespace

# Symbol Table: Scope Rules

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Scoping of Symbols may be static (compile time) or dynamic (run time)

### Static Scoping

```
const int b = 5;
```

```
int foo() {  
    int a = b + 5;  
    return a;  
}
```

```
int bar() {  
    int b = 2;  
    return foo();  
}
```

```
int main() {  
    foo(); // returns 10  
    bar(); // returns 10  
  
    return 0;  
}
```

### Dynamic Scoping

```
const int b = 5;
```

```
int foo() {  
    int a = b + 5;  
    return a;  
}
```

```
int bar() {  
    int b = 2;  
    return foo();  
}
```

```
int main() {  
    foo(); // returns 10  
    bar(); // returns 7  
  
    return 0;  
}
```

# Symbol Table: Scope and Visibility

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Scope (visibility) of identifier = portion of program where identifier can be referred to
- Lexical scope = textual region in the program
  - Statement block
  - Method body
  - Class body
  - Module / package / file
  - Whole program (multiple modules)

# Symbol Table: Scope and Visibility

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Global scope
  - Names of all classes defined in the program
  - Names of all global functions defined in the program
- Class scope
  - Instance scope: all fields and methods of the class
  - Static scope: all static methods
  - Scope of subclass nested in scope of its superclass
- Method scope
  - Formal parameters and local variables in code block of body method
- Code block scope
  - Variables defined in block

# Symbol Table: Interface

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Create Symbol Table
- Search (lookup)
- Insert
- Search & Insert
- Update Attribute

# Symbol Table: Implementation

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

**Sym. Tab.**

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- Linear List
- Hash Table
- Binary Search Tree

# Example: Global & Function Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int m_dist(int x1, int y1, int x2, int y2) { m_dist:           // global initialization
    int d, x_diff, y_diff;                                     if x1 > x2 goto L1      x1_g = 0
    x_diff = (x1 > x2) ? x1 - x2 : x2 - x1;                   t1 = x2 - x1           y1_g = 0
    y_diff = (y1 > y2) ? y1 - y2 : y2 - y1;                   goto L2                main:
    d = x_diff + y_diff;                                       L1:t1 = x1 - x2         x2 = -2
    return d;                                                  L2:x_diff = t1          y2 = 3
}                                                            if y1 > y2 goto L3     dist = 0
int x1 = 0, y1 = 0; // Global static                          t2 = y1 - y2           param y2
int main(int argc, char *argv[]) {                            goto L4                param x2
    int x2 = -2, y2 = 3, dist = 0;                             L3:t2 = y2 - y1        param y1_g
    dist = m_dist(x1, y1, x2, y2);                             L4:y_diff = t2         param x1_g
    return 0;                                                  d = x_diff + y_diff    dist = call m_dist, 4
}                                                            return d               return 0
```

<i>ST.glb</i>	Parent: <i>Null</i>			
m_dist	int × int × int × int → int			
	func	0	0	
x1_g	int	global	4	
y1_g	int	global	4	
main	int × arr(*,char*) → int			
	func	0	0	

<i>ST.m_dist()</i>	Parent: <i>ST.glb</i>			
y2	int	param	4	+20
x2	int	param	4	+16
y1	int	param	4	+12
x1	int	param	4	+8
d	int	local	4	-4
x_diff	int	local	4	-8
y_diff	int	local	4	-12
t1	int	temp	4	-16
t2	int	temp	4	-20

<i>ST.main()</i>	Parent: <i>ST.glb</i>			
argv	arr(*,char*)			
	param	4	+8	
argc	int	param	4	+4
x2	int	local	4	-4
y2	int	local	4	-8
dist	int	local	4	-12

*Cols: Name, Type, Category, Size, Offset*

# Example: Global, Function & Block Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int m_dist(int x1, int y1, int x2, int y2) { m_dist:           // global initialization
    int d, { int x_diff, \\ Nested block                if x1 > x2 goto L1    x1_g = 0
    { int y_diff; \\ Nested nested block                t1 = x2 - x1        y1_g = 0
    x_diff = (x1 > x2) ? x1 - x2 : x2 - x1;                goto L2            main:
    y_diff = (y1 > y2) ? y1 - y2 : y2 - y1; L1:t1 = x1 - x2      x2 = -2
    } }                                                    L2:x_diff_$2 = t1    y2 = 3
    d = x_diff + y_diff;                                if y1 > y2 goto L3  dist = 0
    return d;                                           t2 = y1 - y2        param y2
}                                                         goto L4              param x2
int x1 = 0, y1 = 0; // Global static                    L3:t2 = y2 - y1      param y1_g
int main(int argc, char *argv[]) {                      L4:y_diff_$1 = t2    param x1_g
    int x2 = -2, y2 = 3, dist = 0;                      d = x_diff + y_diff dist = call m_dist, 4
    dist = m_dist(x1, y1, x2, y2);                      return d            return 0
    return 0;
}
```

<i>ST.glb</i>	Parent: <i>Null</i>			
m_dist	int × int × int × int → int			
	func	0	0	
x1_g	int global	4	0	
y1_g	int global	4	-4	
main	int × arr(*,char*) → int			
	func	0	0	

<i>ST.m-dist()</i>	Parent: <i>ST.glb</i>			
y2	int param	4	+20	
x2	int param	4	+16	
y1	int param	4	+12	
x1	int param	4	+8	
d	int local	4	-4	
x_diff_\$2	int local	4	-8	
y_diff_\$1	int local	4	-12	
t1	int temp	4	-16	
t2	int temp	4	-20	

<i>ST.m-dist()\$.2</i>	Parent: <i>ST.m-dist()</i>			
x_diff	int local	4	0	
<i>ST.m-dist()\$.1</i>	Parent: <i>ST.m-dist()\$.2</i>			
y_diff	int local	4	0	
<i>ST.main()</i>	Parent: <i>ST.glb</i>			
argv	arr(*,char*)			
	param	4	+8	
argc	int param	4	+4	
x2	int local	4	-4	
y2	int local	4	-8	
dist	int local	4	-12	

Cols: Name, Type, Category, Size, Offset

- Static Allocation
- Automatic Allocation
- Embedded Automatic Allocation



# Example: Global & Function Scopes, typedef

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
typedef struct { int _x, _y; } Point;
int m_dist(Point p, Point q) {
    int d, x_diff, y_diff;
    x_diff=(p._x>q._x)?p._x-q._x: q._x-p._x;
    y_diff=(p._y>q._y)?p._y-q._y: q._y-p._y;
    d = x_diff + y_diff;
    return d;
}
Point p = { 0, 0 };
int main() {
    Point q = { -2, 3 };
    int dist = 0;
    dist = m_dist(p, q);
    return 0;
}
```

```
m_dist:                                // global initialization
    if p._x > q._x goto L1             x1_g = 0
    t1 = q._x - p._x                    y1_g = 0
    goto L2                             main:
L1:t1 = p._x - q._x                    q._x = -2 // Offset(q)
L2:x_diff = t1                         q._y = 3 // Offset(q+4)
    if p._y > q._y goto L3             dist = 0
    t2 = q._y - p._y                   param q
    goto L4                             param p
L3:t2 = p._y - q._y                   dist = call m_dist, 2
L4:y_diff = t2                         return 0
    d = x_diff + y_diff
    return d
```

<i>ST.glb</i>		Parent: <i>Null</i>		
m_dist	struct Point × struct Point → int	func	0	0
p-g	struct Point	global	8	
main	int × arr(*,char*) → int	func	0	0
<i>ST.m_dist()</i>		Parent: <i>ST.glb</i>		
q	struct Point	param	8	+16
p	struct Point	param	8	+8
d	int	local	4	-4
x_diff	int	local	4	-8
y_diff	int	local	4	-12
t1	int	temp	4	-16
t2	int	temp	4	-20

<i>ST.type.struct Point</i>		Parent: <i>ST.glb</i>		
_x	int	member	4	0
_y	int	member	4	-4
<i>ST.main()</i>		Parent: <i>ST.glb</i>		
argv	arr(*,char*)			
		param	4	+8
argc	int	param	4	+4
q	struct Point	local	8	-12
dist	int	local	4	-20

*Cols: Name, Type, Category, Size, Offset*

# Example: Global, Function & Class Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

```
class Point { public: int _x, _y;
    Point(int x, int y) : _x(x), _y(y) { }
    ~Point() {} ;
};
int m_dist(Point p, Point q) {
    int d, x_diff, y_diff;
    x_diff=(p._x>q._x)?p._x-q._x:q._x-p._x;
    y_diff=(p._y>q._y)?p._y-q._y:q._y-p._y;
    d = x_diff + y_diff;
    return d;
}
Point p = { 0, 0 };
int main(int argc, char *argv[]) {
    Point q = { -2, 3 };
    int dist = m_dist(p, q);
    return 0;
}
```

```
m_dist:
    if p._x > q._x goto L1
    t1 = q._x - p._x
    goto L2
L1:t1 = p._x - q._x
L2:x_diff = t1
    if p._y > q._y goto L3
    t2 = q._y - p._y
    goto L4
L3:t2 = p._y - q._y
L4:y_diff = t2
    d = x_diff + y_diff
    return d
```

C-tor / D-tor during Call /  
Return are not shown

```
crt: param 0 // Sys Caller
    param 0
    &p_g = call Point, 2
    param argv
    param argc
    result = call main, 2
    param &p_g
    call ~Point, 1
    return
main: param 3
    param -2
    &q = call Point, 2
    param q
    param p_g
    dist = call m_dist, 2
    param &q
    call ~Point, 1
    return 0
```

ST.glb		Parent: Null		
m_dist	class Point × class Point → int			
	func	0	0	
p-g	class Point	global	8	
main	int × arr(*,char*) → int			
	func	0	0	
ST.m_dist()		Parent: ST.glb		
q	class Point	param	8	+16
p	class Point	param	8	+8
d	int	local	4	-4
x_diff	int	local	4	-8
y_diff	int	local	4	-12
t1	int	temp	4	-16
t2	int	temp	4	-20

ST.type.class Point		Parent: ST.glb		
_x	int	member	4	0
_y	int	member	4	-4
Point	int × int → class Point			
	method	0	0	
~Point	class Point* → void			
	method	0	0	
ST.main()		Parent: ST.glb		
argv	arr(*,char*)	param	4	+8
argc	int	param	4	+4
q	class Point	local	8	-24
dist	int	local	4	-32

Cols: Name, Type, Category, Size, Offset



# More Uses of Symbols Tables

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- **String Table:** Various string constants
- **Constant Table:** Various non-string constants, constant objects
- **Label Table:** Target labels
- **Keywords Table:** Initialized with keywords (KW)
  - KWs tokenized as id's and later marked as KWs on parsing
    - Simplifies lexical analysis
    - Good for languages where keywords are not reserved. *Note:* Keywords in C/C++ are reserved, while those in FORTRAN are not (how to know if an 'IF' is a keyword or an identifier?)
    - Good for languages like EDIF with user-defined keywords
- **Type Table:**
  - *Built-in Types:* int, float, double, char, void etc.
  - *Derived Types:* Types built with type builders like array, struct, pointer, enum etc. May need equivalence of type expressions like int[] & int\*, separate tables etc.
  - *User-defined Types:* class, struct and union as types
  - *Type Alias:* typedef
  - *Named Scopes:* namespace

# Example: Type Symbol Table

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturt in Expr.

Addl. Features

```
class Point { public: int _x, _y;
    Point(int x, int y) : _x(x), _y(y) {}
    ~Point() {};}
class Rect { Point _lt, _rb; public:
    Rect(Point& lt, Point& rb):
        _lt(lt), _rb(rb) {}
    ~Rect() {}
    Point get_LT() { return _lt; }
    Point get_RB() { return _rb; }
};
```

ST.glb		Parent: Null		
m_dist	class Point × class Point → int			
	func	0	0	
p-g	class Point	global	8	
main	int × T_2d_Arr → int			
	func	0	0	
ST.m_dist()		Parent: ST.glb		
q	class Point	param	8	+16
p	class Point	param	8	+8
d	int	local	4	-4
x_diff	int	local	4	-8
y_diff	int	local	4	-12
t1	int	temp	4	-16
t2	int	temp	4	-20
ST.main()		Parent: ST.glb		
argv	T_2d_Arr	param	4	+8
argc	int	param	4	+4
q	class Point	local	8	-24
dist	int	local	4	-32

```
int m_dist(Point p, Point q) {
    int d, x_diff, y_diff;
    x_diff=(p._x>q._x)?p._x-q._x:q._x-p._x;
    y_diff=(p._y>q._y)?p._y-q._y:q._y-p._y;
    d = x_diff + y_diff;
    return d;
}
Point p = { 0, 0 };
int main(int argc, char *argv[]) {
    Point q = { -2, 3 }; Rect r(p, q);
    int dist = m_dist(r.get_LT(), r.get_RB());
    return 0;
}
```

ST.type.glb		Parent: Null		
Point	class Point		8	
Rect	class Rect		16	
T_2d_Arr	arr(*,char*)		4	
ST.type.class Point		Parent: ST.type.glb		
_x	int	member	4	0
_y	int	member	4	-4
Point	int × int → class Point			
~Point	class Point* → void			
ST.type.class Rect		Parent: ST.type.glb		
_lt	class Point	member	8	0
_rb	class Point	member	8	-8
Rect	class Point& × class Point& → class Rect			
	class Rect	method	0	0
~Rect	class Rect* → void			
get_LT	class Rect* → class Point			
get_RB	class Rect* → class Point			

Cols: Name, Type, Category, Size, Offset

# Handling Arithmetic Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

**Arith. Expr.**

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Arithmetic Expressions

# A Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $L \rightarrow L S \backslash n$
- 2:  $L \rightarrow S \backslash n$
- 3:  $S \rightarrow \mathbf{id} = E$
- 4:  $E \rightarrow E + E$
- 5:  $E \rightarrow E - E$
- 6:  $E \rightarrow E * E$
- 7:  $E \rightarrow E / E$
- 8:  $E \rightarrow (E)$
- 9:  $E \rightarrow - E$
- 10:  $E \rightarrow \mathbf{num}$
- 11:  $E \rightarrow \mathbf{id}$

# Attributes for Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- E.loc*:      – Location to store the value of the expression.  
                 – This will exist in the Symbol Table.
- id.loc**:      – Location to store the value of the identifier **id**.  
                 – This will exist in the Symbol Table.
- num.val**:    – Value of the numeric (integer) constant.

# Auxiliary Methods for Translation

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*gentemp()*: – Generates a new temporary and inserts it in the Symbol Table  
– Returns a pointer to the new entry in the Symbol Table

*emit(result, arg1, op, arg2)*:

- Spits a 3 Address Code of the form:  
$$\text{result} = \text{arg1 op arg2}$$
- op usually is a binary operator. If arg2 is missing, op is unary. If op also is missing, this is a copy instruction.



# Expression Grammar with Actions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- |     |     |               |                   |  |
|-----|-----|---------------|-------------------|--|
| 1:  | $L$ | $\rightarrow$ | $L S \setminus n$ | { }  |
| 2:  | $L$ | $\rightarrow$ | $S \setminus n$   | { }  |
| 3:  | $S$ | $\rightarrow$ | <b>id</b> = $E$   | { $\text{emit}(\text{id.loc} = E.\text{loc});$ } // No new temporary, copy code                          |
| 4:  | $E$ | $\rightarrow$ | $E_1 + E_2$       | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = E_1.\text{loc} + E_2.\text{loc});$ } |
| 5:  | $E$ | $\rightarrow$ | $E_1 - E_2$       | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = E_1.\text{loc} - E_2.\text{loc});$ } |
| 6:  | $E$ | $\rightarrow$ | $E_1 * E_2$       | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = E_1.\text{loc} * E_2.\text{loc});$ } |
| 7:  | $E$ | $\rightarrow$ | $E_1 / E_2$       | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = E_1.\text{loc} / E_2.\text{loc});$ } |
| 8:  | $E$ | $\rightarrow$ | $(E_1)$           | { $E.\text{loc} = E_1.\text{loc};$ } // No new temporary, no code  |
| 9:  | $E$ | $\rightarrow$ | $- E_1$           | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = -E_1.\text{loc});$ }                 |
| 10: | $E$ | $\rightarrow$ | <b>num</b>        | { $E.\text{loc} = \text{gentemp}();$<br>$\text{emit}(E.\text{loc} = \text{num.val});$ }                  |
| 11: | $E$ | $\rightarrow$ | <b>id</b>         | { $E.\text{loc} = \text{id.loc};$ } // No new temporary, no code   |

*Intermediate 3 address codes are emitted as soon as they are formed.*

# Translation Example

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

\$ ./a.out

a = 2 + 3 \* 4

t00 = 2

t01 = 3

t02 = 4

t03 = t01 \* t02

t04 = t00 + t03

a = t04

\$

\$

### Reductions

$E \rightarrow \text{num}$

$E \rightarrow \text{num}$

$E \rightarrow \text{num}$

$E \rightarrow E_1 * E_2$

$E \rightarrow E_1 + E_2$

$S \rightarrow \text{id} = E$

### TAC

t00 = 2



t01 = 3

t02 = 4

t03 = t01 \* t02

t04 = t00 + t03

a = t04



# Yacc Specs (calc.y) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
%{
#include <string.h>
#include <iostream>
#include "parser.h"
extern int yylex();
void yyerror(const char *s);
#define NSYMS 20 /* max # of symbols */
symboltable symltab[NSYMS];
}%

%union {
    int intval;
    struct symltab *symp;
}

%token <symp> NAME
%token <intval> NUMBER

%left '+' '-'
%left '*' '/'
%nonassoc UMINUS

%type <symp> expression
%%

stmt_list: statement '\n'
        | stmt_list statement '\n'
        ;
```

```
statement: NAME '=' expression
        { emit($1->name, $3->name); }
        ;

expression: expression '+' expression
        { $$ = gentemp();
          emit($$->name, $1->name, '+', $3->name); }
        | expression '-' expression
        { $$ = gentemp();
          emit($$->name, $1->name, '-', $3->name); }
        | expression '*' expression
        { $$ = gentemp();
          emit($$->name, $1->name, '*', $3->name); }
        | expression '/' expression
        { $$ = gentemp();
          emit($$->name, $1->name, '/', $3->name); }
        | '(' expression ')'
        { $$ = $2; }
        | '-' expression %prec UMINUS
        { $$ = gentemp();
          emit($$->name, $2->name, '-'); }
        | NAME { $$ = $1; }
        | NUMBER
        { $$ = gentemp();
          printf("\t%s = %d\n", $$->name, $1); }
        ;

%%
```

# Yacc Specs (calc.y) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
/* Look-up Symbol Table */
symboltable *symlook(char *s) {
    char *p;
    struct symtab *sp;
    for(sp = symtab;
        sp < &symtab[NSYMS]; sp++) {
        /* is it already here? */
        if (sp->name &&
            !strcmp(sp->name, s))
            return sp;
        if (!sp->name) {
            /* is it free */
            sp->name = strdup(s);
            return sp;
        }
        /* otherwise continue to next */
    }
    yyerror("Too many symbols");
    exit(1); /* cannot continue */
} /* symlook */

/* Generate temporary variable */
symboltable *gentemp() {
    static int c = 0; /* Temp counter */
    char str[10]; /* Temp name */
    /* Generate temp name */
    sprintf(str, "t%02d", c++);
    /* Add temporary to symtab */
    return symlook(str);
}
```

```
/* Output 3-address codes */
void emit(char *s1,      // Result
          char *s2,      // Arg 1
          char c = 0,    // Operator
          char *s3 = 0) // Arg 2
{
    if (s3)
        /* Assignment with Binary operator */
        printf("\t%s = %s %c %s\n", s1, s2, c, s3);
    else
        if (c)
            /* Assignment with Unary operator */
            printf("\t%s = %c %s\n", s1, c, s2);
        else
            /* Simple Assignment */
            printf("\t%s = %s\n", s1, s2);
}

void yyerror(const char *s) {
    std::cout << s << std::endl;
}

int main() {
    yyparse();
}
```

# Header (y.tab.h) for Calculator

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
/* A Bison parser, made by GNU Bison 2.5.  */
/* Tokens.  */
#ifndef YYTOKENTYPE
# define YYTOKENTYPE
    /* Put the tokens into the symbol table, so that GDB and other debuggers know about them.  */
    enum yytokentype {
        NAME = 258,
        NUMBER = 259,
        UMINUS = 260
    };
#endif
/* Tokens.  */
#define NAME 258
#define NUMBER 259
#define UMINUS 260

#if ! defined YYSTYPE && ! defined YYSTYPE_IS_DECLARED
typedef union YYSTYPE {
#line 11 "calc.y" /* Line 2068 of yacc.c  */

    int intval;
    struct symtab *symp;

#line 67 "y.tab.h" /* Line 2068 of yacc.c  */
} YYSTYPE;
# define YYSTYPE_IS_TRIVIAL 1
# define yystype YYSTYPE /* obsolescent; will be withdrawn */
# define YYSTYPE_IS_DECLARED 1
#endif
```

# Header (parser.h) for Calculator

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
#ifndef __PARSER_H
#define __PARSER_H

/* Symbol Table Entry */
typedef struct symtab {
    char *name;
    int value;
} symboltable;

/* Look-up Symbol Table */
symboltable *symlook(char *);

/* Generate temporary variable */
symboltable *gentemp();

/* Output 3-address codes */
/* if s3 != 0 ==> Assignment with Binary operator */
/* if s3 == 0 && c != 0 ==> Assignment with Unary operator */
/* if s3 == 0 && c == 0 ==> Simple Assignment */
void emit(char *s1, char *s2, char c = 0, char *s3 = 0);

#endif // __PARSER_H
```

# Flex Specs (calc.l) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

```
%{
#include <math.h>
#include "y.tab.h"
#include "parser.h"
%}

ID      [A-Za-z][A-Za-z0-9]*

%%
[0-9]+  {
        yylval.intval = atoi(yytext);
        return NUMBER;
}

[ \t]   ;          /* ignore white space */

{ID}    { /* return symbol pointer */
        yylval.symp = symlook(yytext);
        return NAME;
}

"$"     { return 0; /* end of input */ }

\n|.    return yytext[0];
%%
```

# Sample Run

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.


Addl. Features

```
$ ./a.out
a = 2 + 3 * 4
t00 = 2
t01 = 3
t02 = 4
t03 = t01 * t02
t04 = t00 + t03
a = t04
```

```
b = (a + 5) / 6
t05 = 5
t06 = a + t05
t07 = 6
t08 = t06 / t07
b = t08
```

```
c = (a + b) * (a - b) * -1
t09 = a + b
t10 = a - b
t11 = t09 * t10
t12 = 1
t13 = - t12
t14 = t11 * t13
c = t14
```

```
$
$
```





# Translation with Lazy Spitting

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

**Arith. Expr.**

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

Intermediate 3 address codes are formed as quads and stored in an array. The quads are spit at the end to output. This can help optimization later.

# Note on Yacc Specs (calc.y)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- class quad is used to represent a quad
- It has the following fields:

Name	Type	Remarks
op	opcodeType	Specifies the type of 3-address instruction. This can be binary operator, unary operator or copy
arg1	char *	First argument. If the actual argument is a numeric constant, we use decimal form as a string
arg2	char *	Second argument
result	char *	Result

# Yacc Specs (calc.y) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
%{
#include <string.h>
#include <iostream>
#include "parser.h"
extern int yylex();
void yyerror(const char *s);
#define NSYMS 20 // max # of symbols
symboltable syntab[NSYMS];
quad *qArray[NSYMS]; // Store of Quads
int quadPtr = 0; // Index of next quad
}%

%union {
    int intval;
    struct syntab *symp;
}

%token <symp> NAME
%token <intval> NUMBER

%left '+' '-'
%left '*' '/'
%nonassoc UMINUS

%type <symp> expression
%%

start: statement_list
    { for(int i = 0; i < quadPtr; i++)
        qArray[i]->print(); }
    ;
```

```
statement_list:    statement '\n'
                  |    statement_list statement '\n'
                  ;
statement: NAME '=' expression
    { qArray[quadPtr++] =
        new quad(COPY, $1->name, $3->name); }
    ;
expression: expression '+' expression
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(PLUS, $$->name, $1->name, $3->name); }
    | expression '-' expression
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(MINUS, $$->name, $1->name, $3->name); }
    | expression '*' expression
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(MULT, $$->name, $1->name, $3->name); }
    | expression '/' expression
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(DIV, $$->name, $1->name, $3->name); }
    | '(' expression ')' { $$ = $2; }
    | '-' expression %prec UMINUS
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(UNARYMINUS, $$->name, $2->name); }
    | NAME { $$ = $1; }
    | NUMBER
    { $$ = gentemp(); qArray[quadPtr++] =
        new quad(COPY, $$->name, $1); }
    ;
%%
```

# Yacc Specs (calc.y) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
/* Look-up Symbol Table */
symboltable *symlook(char *s) {
    char *p;
    struct symtab *sp;
    for(sp = symtab;
        sp < &syntab[NSYMS]; sp++) {
        /* is it already here? */
        if (sp->name &&
            !strcmp(sp->name, s))
            return sp;
        if (!sp->name) {
            /* is it free */
            sp->name = strdup(s);
            return sp;
        }
        /* otherwise continue to next */
    }
    yyerror("Too many symbols");
    exit(1); /* cannot continue */
} /* symlook */

/* Generate temporary variable */
symboltable *gentemp() {
    static int c = 0; /* Temp counter */
    char str[10]; /* Temp name */
    /* Generate temp name */
    sprintf(str, "t%02d", c++);
    /* Add temporary to syntab */
    return symlook(str);
}
```

```
void yyerror(const char *s) {
    std::cout << s << std::endl;
}

int main() {
    yyparse();
}
```

# Header (y.tab.h) for Calculator

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
/* A Bison parser, made by GNU Bison 2.5.  */
/* Tokens.  */
#ifndef YYTOKENTYPE
# define YYTOKENTYPE
    /* Put the tokens into the symbol table, so that GDB and other debuggers know about them.  */
    enum yytokentype {
        NAME = 258,
        NUMBER = 259,
        UMINUS = 260
    };
#endif
/* Tokens.  */
#define NAME 258
#define NUMBER 259
#define UMINUS 260

#if ! defined YYSTYPE && ! defined YYSTYPE_IS_DECLARED
typedef union YYSTYPE {
#line 13 "calc.y" /* Line 2068 of yacc.c  */

    int intval;
    struct symtab *symp;

#line 67 "y.tab.h" /* Line 2068 of yacc.c  */
} YYSTYPE;
# define YYSTYPE_IS_TRIVIAL 1
# define yystype YYSTYPE /* obsolescent; will be withdrawn */
# define YYSTYPE_IS_DECLARED 1
#endif
```

# Header (parser.h) for Calculator

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
#ifndef __PARSER_H
#define __PARSER_H

#include<stdio.h>

/* Symbol Table Entry */
typedef struct symtab {
    char *name;
    int value;
}symboltable;

/* Look-up Symbol Table */
symboltable *symlook(char *);

/* Generate temporary variable */
symboltable *gentemp();

typedef enum {
    PLUS = 1,
    MINUS,
    MULT,
    DIV,
    UNARYMINUS,
    COPY,
} opcodeType;
```

```
class quad {
    opcodeType op;
    char *result, *arg1, *arg2;
public:
    quad(opcodeType op1, char *s1, char *s2, char *s3=0):
        op(op1), result(s1), arg1(s2), arg2(s3) { }
    quad(opcodeType op1, char *s, int num):
        op(op1), result(s1), arg1(0), arg2(0)
    {
        arg1 = new char[15];
        sprintf(arg1, "%d", num);
    }
    void print() {
        if ((op <= DIV) && (op >= PLUS)) { // Binary Op
            printf("%s = %s ",result, arg1);
            switch (op) {
                case PLUS: printf("+"); break;
                case MINUS: printf("-"); break;
                case MULT: printf("*"); break;
                case DIV: printf("/"); break;
            }
            printf(" %s\n",arg2);
        }
        else
            if (op == UNARYMINUS) // Unary Op
                printf("%s = - %s\n",result, arg1);
            else // Copy
                printf("%s = %s\n",result, arg1);
    }
};
#endif // __PARSER_H
```

# Flex Specs (calc.l) for Calculator Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

```
%{
#include <math.h>
#include "y.tab.h"
#include "parser.h"
}%

ID      [A-Za-z][A-Za-z0-9]*

%%

[0-9]+  {
    yylval.intval = atoi(yytext);
    return NUMBER;
}

[ \t]   ;          /* ignore white space */

{ID}    { /* return symbol pointer */
    yylval.symp = symlook(yytext);
    return NAME;
}

"$"     { return 0; /* end of input */ }

\n|.    return yytext[0];
%%
```

# Sample Run

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

## Output

```
$ ./a.out
a = 2 + 3 * 4
b = (a + 5) / 6
c = (a + b) * (a - b) * -1
  t00 = 2
  t01 = 3
  t02 = 4
  t03 = t01 * t02
  t04 = t00 + t03
  a = t04
  t05 = 5
  t06 = a + t05
  t07 = 6
  t08 = t06 / t07
  b = t08
  t09 = a + b
  t10 = a - b
  t11 = t09 * t10
  t12 = 1
  t13 = - t12
  t14 = t11 * t13
  c = t14
$
```



# Handling Boolean Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

**Bool. Expr.**

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Boolean Expressions

# Boolean Expression Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $B \rightarrow B_1 \parallel B_2$
- 2:  $B \rightarrow B_1 \ \&\& \ B_2$
- 3:  $B \rightarrow !B_1$
- 4:  $B \rightarrow (B_1)$
- 5:  $B \rightarrow E_1 \text{ relop } E_2$
- 6:  $B \rightarrow \text{true}$
- 7:  $B \rightarrow \text{false}$

relop is any one of:

$<, <=, >, >=, ==, !=$

# Boolean Expression Example: Translation by Value

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions


Scope Mgmt.

sturct in Expr.

Addl. Features

$a > b \ || \ c == d \ \&\& \ !(e < f)$

```
100: t1 = a > b
101: t2 = c == d
102: t3 = e < f
103: t4 = !t3
104: t5 = t3 && t4
105: t6 = t1 || t5
```



## Translation by Value:

- May not be very useful, as Boolean values are typically used for control flow
- May not use short-cut of computation

# Boolean Expression Example: Translation by Control Flow

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

$a > b \ || \ c == d \ \&\& \ !(e < f)$

100: if a > b goto 106  
101: goto 102


106: goto 000  
**(true)**

102: if c==d goto 104  
103: goto 107

107: goto 000  
**(false)**

104: if e < f goto 107  
105: goto 106

100: if a > b goto 106  
101: goto 102  
102: if c==d goto 104  
103: goto 107  
104: if e < f goto 107  
105: goto 106  
106: goto 000 **(true)**  
107: goto 000 **(false)**



## Translation by Control:

- Useful for control flow
- Uses short-cut of computation

# Boolean Expression Example: Translation by Control Flow

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

`a > b || c == d && !(e < f)`

100: if a > b goto ?  
101: goto ?

106: goto ?  
**(true)**

102: if c == d goto ?  
103: goto ?


107: goto ?  
**(false)**

104: if e < f goto ?  
105: goto ?

100: if a > b goto ?  
101: goto ?  
102: if c == d goto ?  
103: goto ?  
104: if e < f goto ?  
105: goto ?  
106: goto ? **(true)**  
107: goto ? **(false)**

true exit: →

false exit: →



## Translation by Control:

- How to get the target address of goto's?
- Can we optimize goto to goto's / fall-through's

# Boolean Expression Example: Translation by Control Flow: Abstracted

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.


struct in Expr.

Addl. Features

$a > b \ || \ c == d \ \&\& \ !(e < f)$



true exit: 

false exit: 

# Boolean Expression: Scheme of Translation by Control Flow

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Attributes / Global for Boolean Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

*B.truelist*: – List of (indices of) quads having dangling **true exits** for the Boolean expression.

*B.falselist*: – List of (indices of) quads having dangling **false exits** for the Boolean expression.

*B.loc*: – Location to store the value of the Boolean expression (optional).

*nextinstr*: – Global counter to the array of quads – the index of the next quad to be generated.

*M.instr*: – Index of the quad generated at *M*.



# Auxiliary Methods for Back-patching

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*makelist( $i$ ):* – Creates a new list containing only  $i$ , an index into the array of quad's.  
– Returns a pointer to the newly created list

*merge( $p_1, p_2$ ):* – Concatenates the lists pointed to by  $p_1$  and  $p_2$ .  
– Returns a pointer to the concatenated list

*backpatch( $p, i$ ):* – Inserts  $i$  as the target label for each of the quads on the list pointed to by  $p$ .

# Back-patching Boolean Expression Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $B \rightarrow B_1 \parallel M B_2$
- 2:  $B \rightarrow B_1 \&\& M B_2$
- 3:  $B \rightarrow !B_1$
- 4:  $B \rightarrow (B_1)$
- 5:  $B \rightarrow E_1 \text{ relop } E_2$
- 6:  $B \rightarrow \text{true}$
- 7:  $B \rightarrow \text{false}$
- 8:  $M \rightarrow \epsilon // \text{Marker rule}$

# Back-patching Boolean Expression Grammar with Actions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $B \rightarrow B_1 \parallel M B_2$   
 $\{ \text{backpatch}(B_1.\text{falselist}, M.\text{instr});$   
 $B.\text{truelist} = \text{merge}(B_1.\text{truelist}, B_2.\text{truelist});$   
 $B.\text{falselist} = B_2.\text{falselist}; \}$
- 2:  $B \rightarrow B_1 \&\& M B_2$   
 $\{ \text{backpatch}(B_1.\text{truelist}, M.\text{instr});$   
 $B.\text{truelist} = B_2.\text{truelist};$   
 $B.\text{falselist} = \text{merge}(B_1.\text{falselist}, B_2.\text{falselist}); \}$
- 3:  $B \rightarrow !B_1$   $\{ B.\text{truelist} = B_1.\text{falselist};$   
 $B.\text{falselist} = B_1.\text{truelist}; \}$
- 4:  $B \rightarrow (B_1)$   $\{ B.\text{truelist} = B_1.\text{truelist};$   
 $B.\text{falselist} = B_1.\text{falselist}; \}$
- 5:  $B \rightarrow E_1 \text{ relop } E_2$   
 $\{ B.\text{truelist} = \text{makelist}(\text{nextinstr});$   
 $B.\text{falselist} = \text{makelist}(\text{nextinstr} + 1);$   
 $\text{emit}(\text{" if"}, E_1.\text{loc}, \text{relop.op}, E_2.\text{loc}, \text{" goto"}, \text{" ....."}); \}$   
 $\text{emit}(\text{" goto"}, \text{" ....."}); \}$
- 6:  $B \rightarrow \text{true}$   $\{ B.\text{truelist} = \text{makelist}(\text{nextinstr});$   
 $\text{emit}(\text{" goto"}, \text{" ....."}); \}$
- 7:  $B \rightarrow \text{false}$   $\{ B.\text{falselist} = \text{makelist}(\text{nextinstr});$   
 $\text{emit}(\text{" goto"}, \text{" ....."}); \}$
- 8:  $M \rightarrow \epsilon$   $\{ M.\text{instr} = \text{nextinstr}; \}$

# Back-patching Boolean Expression Grammar with Actions – Home Assignment

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

9:  $B \rightarrow B_1 \wedge M B_2$

```
{ backpatch(B1.truelist, nextinstr);  
  emit(B1.loc, " = ", true);  
  emit(" goto", M.instr);  
  backpatch(B1.falselist, nextinstr);  
  emit(B1.loc, " = ", false);  
  emit(" goto", M.instr);
```

```
B.truelist = makelist(nextinstr);  
backpatch(B2.falselist, nextinstr);  
emit(" if", B1.loc, " goto", " .....");  
B.falselist = makelist(nextinstr);  
emit(" goto", " .....");
```

```
temp = makelist(nextinstr);  
B.falselist = merge(B.falselist, temp);  
backpatch(B2.truelist, nextinstr);  
emit(" if", B1.loc, " goto", " .....");  
temp = makelist(nextinstr);  
B.truelist = merge(B.truelist, temp);  
emit(" goto", " ....."); }
```

# Example: Boolean Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

$a > b \ || \ c == d \ \&\& \ !(e < f)$



## Order of Reductions

Seq. #:  
(Prod. #)

Production

1:(5)	$B_2$	$\rightarrow$	$E_1 \text{ relop } E_2$
2:(8)	$M_1$	$\rightarrow$	$\epsilon$
3:(5)	$B_4$	$\rightarrow$	$E_3 \text{ relop } E_4$
4:(8)	$M_2$	$\rightarrow$	$\epsilon$
5:(5)	$B_7$	$\rightarrow$	$E_5 \text{ relop } E_6$
6:(4)	$B_6$	$\rightarrow$	$(B_7)$
7:(3)	$B_5$	$\rightarrow$	$!B_6$
8:(2)	$B_3$	$\rightarrow$	$B_4 \ \&\& \ M_2 \ B_5$
9:(1)	$B_1$	$\rightarrow$	$B_2 \    \ M_1 \ B_3$

```
[1] 100: if a > b goto ?
[1] 101: goto 102 // [8] BP(B2.FL, M1.I)
[3] 102: if c == d goto 104 // [9] BP(B4.TL, M2.I)
[3] 103: goto ?
[5] 104: if e < f goto ?
[5] 105: goto ?
```

```
[1] B2.TL = {100}
[1] B2.FL = {101}
[2] M1.I = 102
[3] B4.TL = {102}
[3] B4.FL = {103}
[4] M2.I = 104
[5] B7.TL = {104}
[5] B7.FL = {105}
[6] B6.TL = B7.TL = {104}
[6] B6.FL = B7.FL = {105}
[7] B5.TL = B6.FL = {105}
[7] B5.FL = B6.TL = {104}
[8] B3.TL = B5.TL = {105}
[8] B3.FL = B4.FL U B5.FL = {103, 104}
[9] B1.TL = B2.TL U B3.TL = {100, 105}
[9] B1.FL = B3.FL = {103, 104}
```

[#] Reduction Sequence #

# Handling Control Constructs

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

**Control Flow**

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Control Constructs

# Control Construct Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $S \rightarrow \{ L \}$
- 2:  $S \rightarrow \mathbf{id} = E ;$
- 3:  $S \rightarrow \mathbf{if} (B) S$
- 4:  $S \rightarrow \mathbf{if} (B) S \mathbf{else} S$
- 5:  $S \rightarrow \mathbf{while} (B) S$
- 6:  $L \rightarrow L S$
- 7:  $L \rightarrow S$

# Attributes for Control Construct

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*S.nextlist*: – List of (indices of) quads having dangling **exits** for statement *S*.

*L.nextlist*: – List of (indices of) quads having dangling **exits** for (list of) statements *L*.



# Back-patching Control Construct Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $S \rightarrow \{ L \}$
- 2:  $S \rightarrow \mathbf{id} = E ;$
- 3:  $S \rightarrow \mathbf{if} (B) M S_1$
- 4:  $S \rightarrow \mathbf{if} (B) M_1 S_1 N \mathbf{else} M_2 S_2$
- 5:  $S \rightarrow \mathbf{while} M_1 (B) M_2 S_1$
- 6:  $L \rightarrow L_1 M S$
- 7:  $L \rightarrow S$
- 8:  $M \rightarrow \epsilon // \text{Marker rule}$
- 9:  $N \rightarrow \epsilon // \text{Fall-through Guard rule}$

# Back-patching Control Construct Grammar with Actions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $S \rightarrow \{ L \} \quad \{ S.nextlist = L.nextlist; \}$
- 2:  $S \rightarrow id = E ; \quad \{ S.nextlist = null; \}$   
 $\quad \quad \quad emit(id.loc, " = ", E.loc); \}$
- 3:  $S \rightarrow if (B) M S_1 \quad \{ backpatch(B.truelist, M.instr); \}$   
 $\quad \quad \quad S.nextlist = merge(B.falselist, S_1.nextlist); \}$
- 4:  $S \rightarrow if (B) M_1 S_1 N else M_2 S_2$   
 $\quad \quad \quad \{ backpatch(B.truelist, M_1.instr); \}$   
 $\quad \quad \quad backpatch(B.falselist, M_2.instr);$   
 $\quad \quad \quad temp = merge(S_1.nextlist, N.nextlist); \}$   
 $\quad \quad \quad S.nextlist = merge(temp, S_2.nextlist); \}$
- 5:  $S \rightarrow while M_1 (B) M_2 S_1$   
 $\quad \quad \quad \{ backpatch(S_1.nextlist, M_1.instr);$   
 $\quad \quad \quad backpatch(B.truelist, M_2.instr);$   
 $\quad \quad \quad S.nextlist = B.falselist;$   
 $\quad \quad \quad emit(" goto", M_1.instr); \}$
- 6:  $L \rightarrow L_1 M S \quad \{ backpatch(L_1.nextlist, M.instr); \}$   
 $\quad \quad \quad L.nextlist = S.nextlist; \}$

# Back-patching Control Construct Grammar with Actions – Class Assignment

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 7:  $L \rightarrow S \quad \{ L.nextlist = S.nextlist; \}$
- 8:  $M \rightarrow \epsilon \quad \{ M.instr = nextinstr; \}$
- 9:  $N \rightarrow \epsilon \quad \{ N.nextlist = makelist(nextinstr);$   
 $\quad emit("goto", "....."); \}$
- 10:  $S \rightarrow \text{do } M_1 \text{ } S_1 \text{ } M_2 \text{ while } ( B );$   
 $\quad \{ backpatch(B.truelist, M_1.instr);$   
 $\quad \quad backpatch(S_1.nextlist, M_2.instr);$   
 $\quad \quad S.nextlist = B.falselist; \}$
- 11:  $S \rightarrow \text{for } ( E_1 ; M_1 \text{ } B ; M_2 \text{ } E_2 \text{ } N ) M_3 \text{ } S_1$   
 $\quad \{ backpatch(B.truelist, M_3.instr);$   
 $\quad \quad backpatch(N.nextlist, M_1.instr);$   
 $\quad \quad backpatch(S_1.nextlist, M_2.instr);$   
 $\quad \quad emit("goto" M_2.instr);$   
 $\quad \quad S.nextlist = B.falselist; \}$
- 12:  $E \rightarrow \text{id} \quad \{ E.loc = idid.loc; \}$
- 13:  $E \rightarrow \text{num} \quad \{ E.loc = gentemp();$   
 $\quad \quad emit(E.loc, " = ", num.val); \}$

# Example: $S \rightarrow \text{if } (B) M_1 S_1 N \text{ else } M_2 S_2$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

surst in Expr.


Addl. Features

if (x > 0) if (x < 100) m = 1; else m = 2; else m = 3;

S#	Order of Reductions	Production
01:	$B_1 \rightarrow E_1 \text{ relop } E_2$	
02:	$M_1 \rightarrow \epsilon$	
03:	$B_2 \rightarrow E_3 \text{ relop } E_4$	
04:	$M_2 \rightarrow \epsilon$	
05:	$S_3 \rightarrow id_m = E_5$	
06:	$N_1 \rightarrow \epsilon$	
07:	$M_3 \rightarrow \epsilon$	
08:	$S_4 \rightarrow id_m = E_6$	
09:	$S_2 \rightarrow \text{if } (B_2) M_2 S_3 N_1 \text{ else } M_3 S_4$	
10:	$N_2 \rightarrow \epsilon$	
11:	$M_4 \rightarrow \epsilon$	
12:	$S_5 \rightarrow id_m = E_7$	
13:	$S_1 \rightarrow \text{if } (B_1) M_1 S_2 N_2 \text{ else } M_4 S_5$	

```
[01] 100: if x > 0 goto 102 // [13] BP(B1.TL, M1.I)
[01] 101: goto 108 // [13] BP(B1.FL, M4.I)
[03] 102: if x < 100 goto 104 // [09] BP(B2.TL, M2.I)
[03] 103: goto 106 // [09] BP(B2.FL, M3.I)
[05] 104: m = 1
[06] 105: goto ---
[08] 106: m = 2
[10] 107: goto ---
[12] 108: m = 3
```

```
[01] B1.TL= {100} [07] M3.I = 106
[01] B1.FL= {101} [08] S4.NL= {}
[02] M1.I = 102 [09] S2.NL= S3.NL U N1.NL U S4.NL= {105}
[03] B2.TL= {102} [10] N2.NL= {107}
[03] B2.FL= {103} [11] M4.I = 108
[04] M2.I = 104 [12] S5.NL= {}
[05] S3.NL= {} [13] S1.NL= S2.NL U N2.NL U S5.NL= {105, 107}
[06] N1.NL= {105}
```



# Handling goto

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

Maintain a Label Table having the following information and lookup(Label) method:

- ID of Label – This will be entered to Label Table either when a label is defined or it is used as a target for a **goto** before being defined. So if this ID exists in the table, it has been encountered already
- ADDR, Address of Label (index of quad) – This is set from the definition of a label. Hence it will be null as long as a label has been encountered in one or more **goto**'s but not defined yet
- LST, List of dangling **goto**'s for this label – This will be null if ADDR is not null

```
L1: ...      // If L1 exists in Label Table
              //   if (ADDR = null)
              //       ADDR = nextinstr
              //       backpatch LST with ADDR
              //       LST = null
              //   else
              //       duplicate definition of label L1 - an error
              // If L1 does not exist, make an entry
              //   ADDR = nextinstr
              //   LST = null
```

# Handling goto

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
goto L1; // If L1 exists in Label Table
        //   if (ADDR = null) // Forward jump already seen
        //       LST = merge(LST, makelist(nextinstr));
        //   else // Target crossed - a backward jump
        //       use ADDR
        // If L1 does not exist, make an entry
        //   ADDR = null // New forward jump
        //   LST = makelist(nextinstr);
```

# Back-patching Control Construct Grammar with Actions – Home Assignment

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

$S \rightarrow \text{switch} ( E ) S_1$

$S \rightarrow \text{case num: } S_1$

$S \rightarrow \text{default: } S_1$

### Using Mutually Exclusive "case" Clauses - Unlike C

#### Synthesized Attributes

Code to Evaluate  $E$  into  $t$   
**goto test**  
 $L_1$ : Code for  $S_1$   
**goto next**  
 $L_2$ : Code for  $S_2$   
**goto next**  
 ...  
 $L_{n-1}$ : Code for  $S_{n-1}$   
**goto next**  
 $L_n$ : Code for  $S_n$   
**goto next**  
**test:** if  $t = V_1$  goto  $L_1$   
 if  $t = V_2$  goto  $L_2$   
 ...  
 if  $t = V_{n-1}$  goto  $L_{n-1}$   
**goto  $L_n$**   
**next:**

#### Inherited Attributes

Code to Evaluate  $E$  into  $t$   
 if  $t \neq V_1$  goto  $L_1$   
 Code for  $S_1$   
**goto next**  
 $L_1$ : if  $t \neq V_2$  goto  $L_2$   
 Code for  $S_2$   
**goto next**  
 ...  
 $L_{n-2}$ : if  $t \neq V_{n-1}$  goto  $L_{n-1}$   
 Code for  $S_{n-1}$   
**goto next**  
 $L_{n-1}$ : Code for  $S_n$   
**next:**

# Back-patching Control Construct Grammar with Actions – Home Assignment

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

**Control Flow**

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

Design suitable schemes to translate **break** and **continue** statements:

$$S \rightarrow \mathbf{break};$$
$$S \rightarrow \mathbf{continue};$$



# Handling Types & Declarations

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

**Declarations**

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Types & Declarations

# Declaration Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 0:  $P \rightarrow M D$
- 1:  $D \rightarrow T V ; D$
- 2:  $D \rightarrow \epsilon$
- 3:  $V \rightarrow V , id$
- 4:  $V \rightarrow id$
- 5:  $T \rightarrow B$
- 6:  $B \rightarrow int$
- 7:  $B \rightarrow float$
- 8:  $M \rightarrow \epsilon$



**Example:** int a, b; float c;

Name	Type	Size	Offset
------	------	------	--------

a	int	4	0
b	int	4	4
c	float	8	8

# Inherited Attribute

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

Consider the following attributes for types:

*type*: Type expression for  $B$ ,  $T$ .


*width*: The width of a type ( $B$ ,  $T$ ), that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types.

In the context of:

```
int a, b;
```

```
float c;
```

when  $V \rightarrow \mathbf{id}$  (or  $V \rightarrow V, \mathbf{id}$ ) is reduced, we need to set the type (size) for  $\mathbf{id}$  in the symbol table. However, the type (size) is not available from the children of  $V$  as *Synthesized Attributes*. Rather, it is available in  $T$  ( $T.type$  or  $T.width$ ) which is a sibling of  $V$ . This is the situation of an *Inherited Attribute*.



# Inherited Attribute

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



We can handle inherited attributes in one of following ways:

- **[Global]** When we reduce by  $T \rightarrow B$ , we can remember  $T.type$  and  $T.width$  in two global variables  $t$  and  $w$  and use them subsequently
- **[Lazy Action]** Accumulate the list of variables generated from  $V$  in a list  $V.list$  and the set the type from  $T.type$  while reducing with  $D \rightarrow T V ; D_1$
- **[Bison Stack]** Use  $\$0$ ,  $\$-1$  etc. to extract the inherited attribute during reduction of  $V \rightarrow id$  (or  $V \rightarrow V , id$ )
- **[Grammar Rewrite]** Rewrite the grammar so that the inherited attributes become synthesized

# Attributes for Types: Using Global

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*type*: Type expression for  $B$ ,  $T$ . This is an inherited attribute.

*width*: The width of a type  $(B, T)$ , that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types. This is an inherited attribute.

*t*: Global to pass the *type* information from a  $B$  node to the node for production  $V \rightarrow \mathbf{id}$ .

*w*: Global to pass the *width* information from a  $B$  node to the node for production  $V \rightarrow \mathbf{id}$ .

*offset*: Global marker for Symbol Table fill-up.

# Semantic Actions using Global: Inherited Attributes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

0:	$P$	$\rightarrow$		{ <i>offset</i> = 0; }
			$D$	
1:	$D$	$\rightarrow$	$T \ V ; D_1$	
2:	$D$	$\rightarrow$	$\epsilon$	
3:	$V$	$\rightarrow$	$V , \text{ id}$	{ <i>update</i> ( <i>id.loc</i> , <i>t</i> , <i>w</i> , <i>offset</i> ); <i>offset</i> = <i>offset</i> + <i>w</i> ; }
4:	$V$	$\rightarrow$	<b>id</b>	{ <i>update</i> ( <i>id.loc</i> , <i>t</i> , <i>w</i> , <i>offset</i> ); <i>offset</i> = <i>offset</i> + <i>w</i> ; }
5:	$T$	$\rightarrow$	$B$	{ <i>t</i> = <i>B.type</i> ; <i>w</i> = <i>B.width</i> ; <i>T.type</i> = <i>B.type</i> ; <i>T.width</i> = <i>B.width</i> ; }
6:	$B$	$\rightarrow$	<b>int</b>	{ <i>B.type</i> = <i>integer</i> ; <i>B.width</i> = 4; }
7:	$B$	$\rightarrow$	<b>float</b>	{ <i>B.type</i> = <i>float</i> ; <i>B.width</i> = 8; }

*update*(*< SymbolTableEntry >*, *< type >*, *< width >*, *< offset >*) updates the symbol table entry for type, width and offset.

# Example: Using Global

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.


struct in Expr.

Addl. Features

```
int a, b;  
float c;
```

```
offset = 0  
B1.type = integer  
B1.width = 4  
T1.type = integer  
T1.width = 4  
t = integer  
w = 4  
B2.type = float  
B2.width = 8  
T2.type = float  
T2.width = 8  
t = float  
w = 8
```

Name	Type	Size	Offset
a	integer	4	0
b	integer	4	4
c	float	8	8



# Declaration Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 0:  $P \rightarrow M D$
- 1:  $D \rightarrow T V ; D$
- 2:  $D \rightarrow \epsilon$
- 3:  $V \rightarrow V , id$
- 4:  $V \rightarrow id$
- 5:  $T \rightarrow B$
- 6:  $B \rightarrow int$
- 7:  $B \rightarrow float$
- 8:  $M \rightarrow \epsilon$



**Example:** int a, b; float c;

Name	Type	Size	Offset
------	------	------	--------

Name	Type	Size	Offset
a	int	4	0
b	int	4	4
c	float	8	8



# Attributes for Types: Lazy Action

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*type*: Type expression for  $B$ ,  $T$ . This is an inherited (synthesized) attribute.

*width*: The width of a type ( $B$ ,  $T$ ), that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types. This is an inherited (synthesized) attribute.

*list*: List of variables generated from  $V$ . This is a synthesized attribute.

*offset*: Global marker for Symbol Table fill-up.

# Semantic Actions using Lazy Action: Inherited Attributes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:	$P$	$\rightarrow$	$D$	$\{ \text{offset} = 0; \text{update\_offset}(); \}$
1:	$D$	$\rightarrow$	$T \ V ; D_1$	$\{ \text{update}(V.\text{list}, T.\text{type}, T.\text{width}); \}$
2:	$D$	$\rightarrow$	$\epsilon$	
3:	$V$	$\rightarrow$	$V_1 , \text{id}$	$\{ I = \text{makelist}(\text{id.loc});$ $V.\text{list} = \text{merge}(V_1.\text{list}, I); \}$
4:	$V$	$\rightarrow$	$\text{id}$	$\{ V.\text{list} = \text{makelist}(\text{id.loc}); \}$
5:	$T$	$\rightarrow$	$B$	$\{ T.\text{type} = B.\text{type};$ $T.\text{width} = B.\text{width}; \}$
6:	$B$	$\rightarrow$	$\text{int}$	$\{ B.\text{type} = \text{integer}; B.\text{width} = 4; \}$
7:	$B$	$\rightarrow$	$\text{float}$	$\{ B.\text{type} = \text{float}; B.\text{width} = 8; \}$

*update(< ListOfSymbolTableEntry >, < type >, < width >, < offset >)* updates the symbol table entries on the list for type, width and offset.

*update\_offset();* updates the offset for all entries in the symbol table

# Example: Using Lazy Actions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int a, b;    B1.type = integer
float c;     B1.width = 4
            T1.type = integer
            T1.width = 4
            V2.list = {ST[0]}
            V1.list = {ST[0], ST[1]}
            B2.type = float
            B2.width = 8
            T2.type = float
            T2.width = 8
            V3.list = {ST[2]}
            offset = 0
```



## States of Symbol Table ST

lists created

	Name	Type	Size	Offset
0	a	?	?	?
1	b	?	?	?
2	c	?	?	?

V3.list resolved

	Name	Type	Size	Offset
0	a	?	?	?
1	b	?	?	?
2	c	float	8	?

V1.list resolved

	Name	Type	Size	Offset
0	a	integer	4	?
1	b	integer	4	?
2	c	float	8	?

offsets updated

	Name	Type	Size	Offset
0	a	integer	4	0
1	b	integer	4	4
2	c	float	8	8

# Declaration Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:  $P \rightarrow D$   
1:  $D \rightarrow T V ; D$   
2:  $D \rightarrow \epsilon$   
3:  $V \rightarrow V , id$   
4:  $V \rightarrow id$   
5:  $T \rightarrow B$   
6:  $B \rightarrow int$   
7:  $B \rightarrow float$



**Example:** `int a, b; float c;`

Name	Type	Size	Offset
------	------	------	--------

a	int	4	0
b	int	4	4
c	float	8	8

# Attributes for Types: Bison Stack

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*type*: Type expression for  $B$ ,  $T$ . This an inherited attribute.

*width*: The width of a type ( $B$ ,  $T$ ), that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types. This an inherited attribute.

*offset*: Global marker for Symbol Table fill-up.

# Bison Stack

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features


In the context of:

```
int a, b;
```

```
float c;
```

when  $V \rightarrow \text{id}$  or  $V \rightarrow V, \text{id}$  is reduced, the stack is as follows:

		<b>id</b>	\$3
		,	\$2
		<b>V</b>	\$1
		<b>T</b>	\$0
		...	\$-1
		...	\$-2
		...	
$V \rightarrow \text{id}$		$V \rightarrow V, \text{id}$	



# Semantic Actions using Bison Stack: Inherited Attributes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
0:  P  →          { offset = 0; }
      D
1:  D  →  T V ; D1
2:  D  →  ε
3:  V  →  V , id   { update(id.loc, $0.type, $0.width, offset);
                   offset = offset + $0.width; }
4:  V  →  id       { update(id.loc, $0.type, $0.width, offset);
                   offset = offset + $0.width; }
5:  T  →  B        { T.type = B.type; T.width = B.width; }
6:  B  →  int      { B.type = integer; B.width = 4; }
7:  B  →  float    { B.type = float; B.width = 8; }
```

*update*(*< SymbolTableEntry >*, *< type >*, *< width >*, *< offset >*) updates the symbol table entry for type, width and offset.

# Declaration Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.


struct in Expr.

Addl. Features

Inherited Attribute			
0:	$P$	$\rightarrow$	$D$
1:	$D$	$\rightarrow$	$T \ V ; D$
2:	$D$	$\rightarrow$	$\epsilon$
3:	$V$	$\rightarrow$	$V , id$
4:	$V$	$\rightarrow$	$id$
5:	$T$	$\rightarrow$	$B$
6:	$B$	$\rightarrow$	$int$
7:	$B$	$\rightarrow$	$float$



Synthesized Attribute			
0:	$P$	$\rightarrow$	$D$
1:	$D$	$\rightarrow$	$V ; D$
2:	$D$	$\rightarrow$	$\epsilon$
3:	$V$	$\rightarrow$	$V , id$
4:	$V$	$\rightarrow$	$T \ id$
5:	$T$	$\rightarrow$	$B$
6:	$B$	$\rightarrow$	$int$
7:	$B$	$\rightarrow$	$float$



Example: int a, b; float c;

Name	Type	Size	Offset
a	int	4	0
b	int	4	4
c	float	8	8



# Attributes for Types: Grammar Rewrite (Synthesized Attributes)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*type*: Type expression for  $B$ ,  $T$ , and  $V$ . This a synthesized attribute.

*width*: The width of a type ( $B$ ,  $T$ ) or a variable ( $V$ ), that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types. This a synthesized attribute.

*offset*: Global marker for Symbol Table fill-up.

# Semantic Actions using Grammar Rewrite: Synthesized Attributes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
0:  P  →  { offset = 0; }  
      D  
1:  D  →  V ; D1  
2:  D  →  ε  
3:  V  →  V1 , id  
      { update(id.loc, V1.type, V1.width, offset);  
        offset = offset + V1.width;  
        V.type = V1.type; V.width = V1.width; }  
4:  V  →  T id  
      { update(id.loc, T.type, T.width, offset);  
        offset = offset + T.width;  
        V.type = T.type; V.width = T.width; }  
5:  T  →  B  
      { T.type = B.type; T.width = B.width; }  
6:  B  →  int { B.type = integer; B.width = 4; }  
7:  B  →  float { B.type = float; B.width = 8; }
```

*update*(*< SymbolTableEntry >*, *< type >*, *< width >*, *< offset >*) updates the symbol table entry for type, width and offset.

# Example: Grammar Rewrite: Synthesized Attributes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.


struct in Expr.

Addl. Features

```
int a, b;  
float c;
```

```
offset = 0  
B1.type = integer  
B1.width = 4  
T1.type = integer  
T1.width = 4  
V2.type = integer  
V2.width = 4  
V1.type = integer  
V1.width = 4  
B2.type = float  
B2.width = 8  
T2.type = float  
T2.width = 8  
V3.type = float  
V3.width = 8
```

Name	Type	Size	Offset
a	integer	4	0
b	integer	4	4
c	float	8	8



## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

**Using Types**

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Translation by Type

# Use of type in Translation

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

## • Implicit Conversion

### • *Safe*

- Usually smaller type converted to larger type, called *Type Promotion*

- No data loss

- Conversions on Type Hierarchy in C:

`bool -> char -> short int -> int -> unsigned int ->`

`long -> unsigned -> long long ->`

`float -> double -> long double`

- Array – Pointer Duality

- Integer interpreted as Boolean in context

### • *Unsafe*

- Usually larger type converted to smaller type

- Potential data loss

## • Explicit Conversion

- Using cast operators

- `void* --> int, int --> void*`

## • Type Errors

- Between incompatible types

# Use of type in Translation: $\text{int} \leftrightarrow \text{double}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

## Grammar:

$$E \rightarrow E_1 + E_2$$
$$E \rightarrow \text{id}$$

## Translation:

```
int a, b, c;
```

```
a = b + c;
```

```
100: t1 = b + c
```

```
101: a = t1
```

```
int a, b; double c;
```

```
a = b + c; // warning C4244: '=' : conversion from 'double' to 'int',  
           // possible loss of data
```

```
100: t1 = int2dbl(b) // Small to Large: Okay
```

```
101: t2 = t1 + c
```

```
102: t3 = dbl2int(t2) // Large to Small: Data loss
```

```
103: a = t3
```

# Use of type in Translation: $\text{int} \leftrightarrow \text{double}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```

$$E \rightarrow E_1 + E_2 \quad \{ \begin{array}{l} E.loc = \text{gentemp}(); \\ \text{if}(E_1.type \neq E_2.type) \\ \quad \text{update}(E.loc, \text{double}, \text{sizeof}(\text{double}), \text{offset}); \\ \quad t = \text{gentemp}(); \\ \quad \text{update}(t, \text{double}, \text{sizeof}(\text{double}), \text{offset}); \\ \quad \text{if}(E_1.type == \text{integer}) // E_2.type == \text{double} \\ \quad \quad \text{emit}(t '=' \text{int2dbl}(E_1.loc)); \\ \quad \quad \text{emit}(E.loc '=' t '+' E_2.loc); \\ \quad \text{else} // E_2.type == \text{integer} \\ \quad \quad \text{emit}(t '=' \text{int2dbl}(E_2.loc)); \\ \quad \quad \text{emit}(E.loc '=' E_1.loc '+' t); \\ \quad \text{endif} \\ \text{else} \\ \quad \text{update}(E.loc, E_1.type, \text{sizeof}(E_1.type), \text{offset}); \\ \quad \text{emit}(E.loc '=' E_1.loc '+' E_2.loc); \} \\ \text{endif} \end{array}$$

$$E \rightarrow \text{id} \quad \{ E.loc = \text{id.loc}; \}$$

```

# Use of type in Translation: $\text{int} \rightarrow \text{bool}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

### Grammar:

$$E \rightarrow E_1 \text{ != } E_2$$
$$E \rightarrow E_1 \ N_1 \ ? \ M_1 \ E_2 \ N_2 \ : \ M_2 \ E_3$$
$$M \rightarrow \epsilon$$
$$N \rightarrow \epsilon$$

### Translation:

```
int a, b, c, d;  
d = a - b != 0 ? b + c : b - c;
```

```
100: t1 = a - b  
101: t2 = 0  
102: if t1 != t2 goto 105  
103: goto 107  
104: goto 111  
105: t3 = b + c  
106: goto 110  
107: t4 = b - c  
108: t5 = t4  
109: goto 111  
110: t5 = t3  
111: d = t5
```

```
int a, b, c, d;  
d = a - b ? b + c : b - c;
```

```
100: t1 = a - b  
101: goto 107  
102: t2 = b + c  
103: goto 109  
104: t3 = b - c  
105: t4 = t3  
106: goto 110  
107: if t1 = 0 goto 104  
108: goto 102  
109: t4 = t2  
110: d = t4
```



# Use of type in Translation: $\text{int} \rightarrow \text{bool}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.


Addl. Features

$E \rightarrow E_1 \text{ != } E_2 \mid E_1 \ N_1 \ ? \ M_1 \ E_2 \ N_2 \ : \ M_2 \ E_3$


$M \rightarrow \epsilon$

$N \rightarrow \epsilon$

`int a, b, c, d; d = a - b != 0 ? b + c : b - c;`



`int a, b, c, d; d = a - b ? b + c : b - c;`



# Use of type in Translation: $\text{int} \rightarrow \text{bool}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*convInt2Bool(E):*

If  $E.type$  is integer ( $E.loc$  is valid and  $E.truelist$  &  $E.falselist$  are invalid), it converts  $E.type$  to boolean and generates the required codes for it. Now  $E.truelist$  and  $E.falselist$  become valid and  $E.loc$  becomes invalid. Outline of this method is:

```
if( $E.type == \text{integer}$ )  
     $E.falselist = \text{makelist}(\text{nextinstr});$   
    emit(if  $E.loc == 0$  goto .... );  
     $E.truelist = \text{makelist}(\text{nextinstr});$   
    emit(goto .... );  
endif
```

# Use of type in Translation: $\text{int} \rightarrow \text{bool}$ , $\text{bool} \rightarrow \text{int}$

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions



Scope Mgmt.

struct in Expr.

Addl. Features

$E \rightarrow E_1 N_1 ? M_1 E_2 N_2 : M_2 E_3$

```
{
  E.loc = gentemp();
  // Assume E2.type = E3.type
  E.type = E2.type;
  // Control gets here by fall-through
  emit(E.loc '=' E3.loc);
  I = makelist(nextinstr);
  emit(goto .... );
  backpatch(N2.nextlist, nextinstr);
  emit(E.loc '=' E2.loc);
  I = merge(I, makelist(nextinstr));
  emit(goto .... );
  backpatch(N1.nextlist, nextinstr);
  convInt2Bool(E1);
  backpatch(E1.truelist, M1.instr);
  backpatch(E1.falselist, M2.instr);
  backpatch(I, nextinstr);
}
```



# Translation of ?: for bool Condition

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.


Addl. Features

```
int a, b, c, d; d = a - b != 0 ? b + c : b - c;
```

```

E5.loc = a, E5.type = int    100: t1 = a - b
E6.loc = b, E6.type = int    101: t2 = 0
E4.loc = t1, E4.type = int   102: if t1 != t2 goto 105
E7.loc = t2, E7.type = int   103: goto 107
E3.type = bool               104: goto 112
E3.truelist = {102}          105: t3 = b + c
E3.falselist = {103}         106: goto 110
N1.nextlist = {104}          107: t4 = b - c
M1.instr = 105               108: t5 = t4
E9.loc = b, E9.type = int    109: goto 112
E10.loc = c, E10.type = int  110: t5 = t3
E8.loc = t3, E8.type = int   111: goto 112
N2.nextlist = {106}          112: d = t5
M2.instr = 107               113: t6 = t5
E12.loc = b, E12.type = int
E13.loc = c, E13.type = int
E11.loc = t4, E11.type = int
E2.loc = t5, E2.type = int
E1.loc = t6, E1.type = int
    
```

Name	Type	Size	Offset
a	int	4	0
b	int	4	4
c	int	4	8
d	int	4	12
t1	int	4	16
t2	int	4	20
t3	int	4	24
t4	int	4	28
t5	int	4	32
t6	int	4	36



# Translation of ?: for int Condition

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.


struct in Expr.

Addl. Features

```
int a, b, c, d; d = a - b ? b + c : b - c;
```

```
E4.loc = a, E4.type = int      100: t1 = a - b
E5.loc = b, E5.type = int      101: goto 109
E3.loc = t1, E3.type = int     102: t2 = b + c
N1.nextlist = {101}           103: goto 107
M1.instr = 102                 104: t3 = b - c
E7.loc = b, E7.type = int      105: t4 = t3
E8.loc = c, E8.type = int      106: goto 111
E6.loc = t2, E6.type = int     107: t4 = t2
N2.nextlist = {103}           108: goto 111
M2.instr = 104                 109: if t1 = 0 goto 104
E10.loc = b, E10.type = int    110: goto 102
E11.loc = c, E11.type = int    111: d = t4
E9.loc = t3, E9.type = int     112: t5 = t4
E2.loc = t4, E2.type = int
E3.type = bool // Changed
E3.falselist = {109}
E3.truelist = {110}
E1.loc = t5, E1.type = int
```

Name	Type	Size	Offset
a	int	4	0
b	int	4	4
c	int	4	8
d	int	4	12
t1	int	4	16
t2	int	4	20
t3	int	4	24
t4	int	4	28
t5	int	4	32



# Use of type in Translation

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

**for:**

```
int i;
```

```
for(i = 10; i != 0; --i) { ... } // No conv.
```

```
for(i = 10; i; --i) { ... }      // i --> i != 0
```

# Grammar / Translation So Far ...

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

00:  $P \rightarrow O D S$

01:  $D \rightarrow V ; D$

02:  $D \rightarrow \epsilon$

03:  $V \rightarrow V , id$

04:  $V \rightarrow T id$

05:  $T \rightarrow B$

06:  $B \rightarrow int$

07:  $B \rightarrow float$

08:  $S \rightarrow \{ L \}$

09:  $S \rightarrow if (E) M S_1$

10:  $S \rightarrow if (E) M_1 S_1 N else M_2 S_2$

11:  $S \rightarrow while M_1 (E) M_2 S_1$

12:  $S \rightarrow do M_1 S_1 M_2 while (E) ;$

13:  $S \rightarrow for (E_1 ; M_1 E ; M_2 E_2 N ) M_3 S_1$

14:  $S \rightarrow E ;$

15:  $L \rightarrow L_1 M S$

16:  $L \rightarrow S$

17:  $E \rightarrow E_1 N_1 ? M_1 E_2 N_2 : M_2 E_3$

18:  $E \rightarrow E_1 = E_2$

19:  $E \rightarrow E_1 || M E_2$

20:  $E \rightarrow E_1 \&\& M E_2$

21:  $E \rightarrow !E_1$

22:  $E \rightarrow E_1 rel op E_2$

23:  $E \rightarrow E_1 + E_2$

24:  $E \rightarrow E_1 - E_2$

25:  $E \rightarrow E_1 * E_2$

26:  $E \rightarrow E_1 / E_2$

27:  $E \rightarrow (E_1)$

28:  $E \rightarrow - E_1$

29:  $E \rightarrow id$

30:  $E \rightarrow num$

31:  $E \rightarrow true$

32:  $E \rightarrow false$

33:  $O \rightarrow \epsilon$

34:  $M \rightarrow \epsilon$

35:  $N \rightarrow \epsilon$

## Attributes

- $E: E.type, E.width, E.loc$  ( $E.type = int$ ),  $E.truelist$  ( $E.type = bool$ ),  $E.falselist$  ( $E.type = bool$ )
- $S: S.nextlist$
- $L: L.nextlist$
- $N: N.nextlist$
- $V: V.type, V.width$
- $T: T.type, T.width$
- $B: B.type, B.width$
- $M: M.instr$
- $id: id.loc$
- $num: num.val$

# Handling Arrays in Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

**Arrays in Expr.**

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Arrays in Expression



# Translation of Array Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

**array:**

```
int a[10], b, i;
```

```
b = a[i]; // a[i] --> a + i * sizeof(int)
```

**Translation:**

```
t1 = i * 4
```

```
t2 = a[t1]
```

```
b = t2
```

# Expression Grammar with Arrays

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $S \rightarrow \text{id} = E ;$
- 2:  $S \rightarrow A = E ;$
- 3:  $E \rightarrow E_1 + E_2$
- 4:  $E \rightarrow \text{id}$
- 5:  $E \rightarrow A$
- 6:  $A \rightarrow \text{id} [ E ]$
- 7:  $A \rightarrow A_1 [ E ]$

ob is [ and cb is ]

Input:

```
int a[2][3], b, c;
```

```
b = c + a[i][j];
```

Array


a[0]			
a[1]			

Memory

a[0][0]	
a[0][1]	
a[0][2]	
a[1][0]	
a[1][1]	
a[1][2]	

Output:

```
t1 = i * 12  
t2 = j * 4  
t3 = t1 + t2  
t4 = a[t3]  
t5 = c + t4  
b = t5
```



# Parse Tree of Array Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

1:  $S \rightarrow \text{id} = E ;$

2:  $S \rightarrow A = E ;$

3:  $E \rightarrow E_1 + E_2$

4:  $E \rightarrow \text{id}$

5:  $E \rightarrow A$


6:  $A \rightarrow \text{id} [ E ]$

7:  $A \rightarrow A_1 [ E ]$

ob is [ and cb is ]

int a[2][3], b, c[5]; int i, j, k;

b = c[k] + a[i][j];



# Attributes for Arrays

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturct in Expr.

Addl. Features

*A.loc*: Temporary used for computing the offset for the array reference by summing the terms  $i_j \times W_j$ .

*A.array*: Pointer to the symbol-table entry for the array name. This has *base* and *type*.  
The base address of the array, say, *A.array.base* is used to determine the actual *l*-value of an array reference after all the index expressions are analysed.

*A.type*: Type of the sub-array generated by *A*. For any type *t*, the width is given by *t.width*. We use types as attributes, rather than widths, since types are needed anyway for type checking. For any array type *t*, suppose that *t.elem* gives the element type.

# Expression Grammar with Arrays

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

sturtc in Expr.

Addl. Features

- 1:  $S \rightarrow \mathbf{id} = E ; \quad \{ \text{emit}(\mathbf{id.loc} \text{'=' } E.\text{loc}); \}$
- 2:  $S \rightarrow A = E ; \quad \{ \text{emit}(A.\text{array.base} \text{'[' } A.\text{loc} \text{']' '=' } E.\text{loc}); \}$
- 3:  $E \rightarrow E_1 + E_2 \quad \{ E.\text{loc} = \text{gentemp}(); E.\text{type} = E_1.\text{type};$   
 $\quad \text{emit}(E.\text{loc} \text{'=' } E_1.\text{loc} \text{'+' } E_2.\text{loc}); \}$
- 4:  $E \rightarrow \mathbf{id} \quad \{ E.\text{loc} = \mathbf{id.loc}; E.\text{type} = \mathbf{id.type}; \}$
- 5:  $E \rightarrow A \quad \{ E.\text{loc} = \text{gentemp}(); E.\text{type} = A.\text{type};$   
 $\quad \text{emit}(E.\text{loc} \text{'=' } A.\text{array.base} \text{'[' } A.\text{loc} \text{']'}); \}$
- 6:  $A \rightarrow \mathbf{id} [ E ] \quad \{ A.\text{array} = \text{lookup}(\mathbf{id});$   
 $\quad A.\text{type} = A.\text{array.type.elem};$   
 $\quad A.\text{loc} = \text{gentemp}();$   
 $\quad \text{emit}(A.\text{loc} \text{'=' } E.\text{loc} \text{'*' } A.\text{type.width}); \}$
- 7:  $A \rightarrow A_1 [ E ] \quad \{ A.\text{array} = A_1.\text{array};$   
 $\quad A.\text{type} = A_1.\text{type.elem};$   
 $\quad t = \text{gentemp}();$   
 $\quad A.\text{loc} = \text{gentemp}();$   
 $\quad \text{emit}(t \text{'=' } E.\text{loc} \text{'*' } A.\text{type.width});$   
 $\quad \text{emit}(A.\text{loc} \text{'=' } A_1.\text{loc} \text{'+' } t); \}$

# Translation of Array Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int a[2][3], b, c[5]; int i, j, k; b = c[k] + a[i][j];
```

```

E3.loc = k, E3.type = int      .
A1.array = ST[02]              .
A1.type = T2.elem = int        .
A1.loc = t1                    .
A1.loc.type = E3.type = int    100: t1 = k * 4
E2.loc = t2, E2.type = int     101: t2 = c[t1]
E5.loc = i, E5.type = int      .
A3.array = ST[00]              .
A3.type = T1.elem = T2        .
A3.loc = t3                    .
A3.loc.type = E5.type = int    102: t3 = i * 12
E6.loc = j, E6.type = int      .
A2.array = ST[00]              .
A2.type = T2.elem = int        .
A2.loc = t5                    .
A2.loc.type = E6.type = int    103: t4 = j * 4
                                104: t5 = t3 + t4
                                105: t6 = a[t5]
                                106: t7 = t2 + t6
                                107: b = t7
E4.loc = t6, E4.type = int      .
E1.loc = t7, E1.type = int      .
    
```


No.	Name	Type	Size	Offset
00	a	T1	24	0
01	b	int	4	24
02	c	T2	20	28
03	i	int	4	48
04	j	int	4	52
05	k	int	4	56
06	t1	int	4	16
07	t2	int	4	20
08	t3	int	4	24
09	t4	int	4	28
10	t5	int	4	32
11	t6	int	4	36
12	t7	int	4	36

$T1 = \text{array}(2, \text{array}(3, \text{int})) = \text{array}(2, T1')$

$T2 = \text{array}(5, \text{int})$

$T1 = 2 * T1'.\text{width} = 2 * 12 = 24$

$T1' = 3 * \text{int}.\text{width} = 3 * 4 = 12$



# Handling Complex Types

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

**Type Expr.**

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Type Expressions

# Declaration Grammar (Inherited Attributes)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:	$P \rightarrow D$	5:	$T \rightarrow B$
1:	$D \rightarrow T V ; D_1$	6:	$B \rightarrow \text{int}$
2:	$D \rightarrow \epsilon$	7:	$B \rightarrow \text{float}$
3:	$V \rightarrow V_1 , \text{id } C$	8:	$C \rightarrow [ \text{num} ] C_1$
4:	$V \rightarrow \text{id } C$	9:	$C \rightarrow \epsilon$

## Why the rule of $C$ is right-recursive?

Since the information (of type) needs to flow from the innermost dimension of an array to its outer dimensions (right-to-left), the right recursion is natural. However, while making a reference to that array in an expression, we need to start with its type expression and parse down (left-to-right). Hence, left recursion is natural in  $A \rightarrow A [ E ]$ .



# Symbol Table

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

**Example:**    `int a, b;`  
                  `int x, y[10], z;`  
                  `float w[5];`

Name	Type	Size	Offset
a	int	4	0
b	int	4	4
x	int	4	8
y	array(10, int)	40	12
z	int	4	52
w	array(5, float)	8	56

# Type Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

Applications of types can be grouped under:

- *Type Checking*
  - Logical rules to reason about the behaviour of a program at run time.
  - The types of the operands should match the type expected by an operator. For example, the && operator in Java expects its two operands to be boolean; the result is also of type boolean
- *Translation Applications*
  - Determine the storage that will be needed for that name at run time,
  - Calculate the address denoted by an array reference,
  - Insert explicit type conversions,
  - Choose the right version of an arithmetic operator, ...

# Type Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- A *type expression* is either
  - a basic type or
  - formed by applying a *type constructor* operator to a type expression.
- The sets of basic types and constructors depend on the language to be checked.
- *Example:* Type expression of **int[2][3]** (*array of 2 arrays of 3 integers each*) is *array(2, array(3, integer))*



Operator *array* takes two parameters, a *number* and a *type*.

# Type Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- *Basic Types*

- A basic type like **bool**, **char**, **int**, **float**, **double**, or **void** is a type expression. **void** denotes *the absence of a value*.

- *Type Name*

- A type name is a type expression.

- *Cartesian Product*

- For two type expressions  $s$  and  $t$ , we write the Cartesian product type expression  $s \times t$  to represent a list or tuple of types (like function parameters).  $\times$  associates to the left and has precedence over  $\rightarrow$ .

- *Type Variables*

- Type expressions may contain variables whose values are type expressions. Compiler-generated type variables are also possible.

# Type Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- *Type Constructor*

- A type expression can be formed by applying the *array* type constructor to a number and a type expression.

```
int a[10][5];
```

Type  $\equiv$  array(10, array (5, int))

- A **struct** (or record) is a data structure with named fields. A type expression can be formed by applying the *record* type constructor to the field names and their types.

```
struct _ {  
    char name[20];  
    int height;  
}
```

Type  $\equiv$  record{name: char[20], height: int}

# struct Type Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
#include <iostream>
using namespace std;

typedef struct {    // record{ name: array (20, char), weight: int}
    char name[20];
    int weight;
} Person;

typedef struct {    // record{ name: array (20, char), weight: int}
    char s_name[20];
    int height;
} Student;

int main() {
    Person p = { "Partha", 80 };
    Student s = { "Arjun", 150 }, t = { "Priyanvada", 120 };

    cout << p.name << " " << p.weight << endl;
    cout << s.s_name << " " << s.height << endl;
    cout << t.s_name << " " << t.height << endl;

    //s = p; // Incompatible types
    s = t; // Compatible types

    cout << s.s_name << " " << s.height << endl;

    return 0;
}
```

# Type Expressions

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- *Type Constructor*

- For two type expressions  $s$  and  $t$ , we write type expression  $s \rightarrow t$  for *function from type  $s$  to type  $t$* , where  $\rightarrow$  is a function type constructor.

```
int f(int);
```

Type  $\equiv$   $\text{int} \rightarrow \text{int}$

```
int add(int, int);
```

Type  $\equiv$   $\text{int} \times \text{int} \rightarrow \text{int}$

```
int main(int argc, char *argv[]);
```

Type  $\equiv$   $\text{int} \times \text{array}(*, \text{char}*) \rightarrow \text{int}$

- For a type expression  $t$ ,  $\text{address}(t)$  is the expression for its pointer / address type

```
int *p;
```

Type  $\equiv$   $\text{address}(\text{int})$

# Type Equivalence

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- *If two type expressions are equal then return a certain type else error.*

```
typedef int * IntPtr;  
typedef IntPtr IntPtrArray[10];  
typedef int * IPtrArray[10];
```

```
IntPtrArray x;  
IPtrArray y;  
int *z[10];
```

- When type expressions are represented by graphs, two types are structurally equivalent if and only if:
  - They are the same basic type, or
  - They are formed by applying the same constructor to structurally equivalent types, or
  - One is a type name that denotes the other.



# Declaration Grammar (Inherited Attributes)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
0:   $P \rightarrow D$ 
1:   $D \rightarrow T \text{ id } ; D_1$ 
2:   $D \rightarrow \epsilon$ 
3:   $T \rightarrow B \ C$ 
4:   $T \rightarrow \text{struct } \{ D \}$ 
5:   $B \rightarrow \text{int}$ 
6:   $B \rightarrow \text{float}$ 
7:   $C \rightarrow [ \text{num} ] \ C_1$ 
8:   $C \rightarrow \epsilon$ 
```

For simplicity list of variables in a single declaration has been omitted here.

# Attributes for Types

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

*type*: – Type expression for  $B$ ,  $C$ .  
– This a synthesized attribute.

*width*: – The width of a type ( $B$ ,  $C$ ), that is, the number of storage units (bytes) needed for objects of that type. It is integral for basic types.  
– This a synthesized attribute.

*t*: – Variable to pass the *type* information from a  $B$  node to the node for production  $C \rightarrow \epsilon$ .  
– This an inherited attribute.

*w*: – Variable to pass the *width* information from a  $B$  node to the node for production  $C \rightarrow \epsilon$ .  
– This an inherited attribute.

# Computing Types and their Widths

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

3:  $T \rightarrow \begin{matrix} B \\ C \end{matrix} \quad \begin{cases} t = B.type; w = B.width; \\ T.type = C.type; T.width = C.width; \end{cases}$

5:  $B \rightarrow \mathbf{int} \quad \{ B.type = integer; B.width = 4; \}$

6:  $B \rightarrow \mathbf{float} \quad \{ B.type = float; B.width = 8; \}$

7:  $C \rightarrow [\mathbf{num}] C_1 \quad \begin{cases} C.type = array(\mathbf{num.value}, C_1.type); \\ C.width = \mathbf{num.value} \times C_1.width; \end{cases}$

8:  $C \rightarrow \epsilon \quad \{ C.type = t; C.width = w; \}$

# Computing Types and their Widths

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



## Computing Type for `int[2][3]`

*The above diagram is taken from the Dragon Book.*

*Please read the non-terminal  $N$  as non-terminal  $B$  in our grammar.*

# Sequence of Declarations

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:  $P \rightarrow \{ \text{offset} = 0; \}$

1:  $D \rightarrow \overset{D}{T} \text{ id ; } \{ \text{update}(\text{id.lexeme}, T.type, \text{offset});$   
 $\text{offset} = \text{offset} + T.width; \}$

2:  $D \rightarrow \overset{D_1}{\epsilon}$

# Declaration Grammar (Synthesized Attributes)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

The translations discussed so far use inherited attributes. We may want to re-write the grammar to use *only* synthesized attributes and in the earlier style design something like:

```
0:   $P \rightarrow D$ 
1:   $D \rightarrow V ; D_1$ 
2:   $D \rightarrow \epsilon$ 
3:   $V \rightarrow V_1 , \text{ id } C$ 
4:   $V \rightarrow T \text{ id } C$ 
5:   $T \rightarrow B$ 
6:   $B \rightarrow \text{int}$ 
7:   $B \rightarrow \text{float}$ 
8:   $C \rightarrow [ \text{ num } ] C_1$ 
9:   $C \rightarrow \epsilon$ 
```

# Declaration Grammar (Synthesized Attributes)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- It may be noted that this design is faulty because it still needs inherited attributes to compute the type of  $C$  in  $C \rightarrow \epsilon$ .
- It is rather non-trivial to re-write this grammar for synthesized attributes *only*. This is due to the right-recursive structure of the rules for handling array dimensions. For synthesis, the information naturally flows from left to right while for right recursion the information flows in the reverse order.
- Of course, it is possible to pass this type information through Symbol Table with using explicit global. But that does neither offer an elegant solution.

# Handling Function Declaration & Call

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

**Functions**

Scope Mgmt.

struct in Expr.

Addl. Features

# Functions



# Function Declaration Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

- 1:  $D \rightarrow T \text{ id } (F_{opt});$  {  $insert(ST_{gbl}, \text{id}, T.type, function, F_{opt}.ST);$   
 $insert(F_{opt}.ST, \_retVal, T.type, 0);$  }
- 2:  $F_{opt} \rightarrow F$  {  $F_{opt}.ST = F.ST;$  }
- 3:  $F_{opt} \rightarrow \epsilon$  {  $F_{opt}.ST = 0;$  }
- 4:  $F \rightarrow F_1, T \text{ id}$  {  $F.ST = F_1.ST;$   
 $insert(F.ST, \text{id}, T.type, 0);$  }
- 5:  $F \rightarrow T \text{ id}$  {  $F.ST = CreateSymbolTable();$   
 $insert(F.ST, \text{id}, T.type, 0);$  }
- 6:  $T \rightarrow \text{int}$  {  $T.type = \text{int}$  }
- 7:  $T \rightarrow \text{double}$  {  $T.type = \text{double}$  }
- 8:  $T \rightarrow \text{void}$  {  $T.type = \text{void}$  }

`int func(int i, double d);`

**ST(global)**

*This is the Symbol Table for global symbols*

Name	Type	Init. Val.	Size	Offset	Nested Table
func	function	null	0	...	ptr-to-ST(func)

**ST(func)**

*This is the Symbol Table for function func*

Name	Type	Init. Val.	Size	Offset	Nested Table
i	int	null	4	0	null
d	double	null	8	4	null
<code>\_retVal</code>	int	null	4	12	null

# Function Declaration Example

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions


Scope Mgmt.

struct in Expr.

Addl. Features

```
int func(int i, double d);
```

T1.type = int  
T2.type = int  
F2.ST = ST(func)  
T3.type = dbl  
F1.ST = ST(func)  
F\_opt.ST = ST(func)



### ST(global)

Name	Type	Size	Offset	Nested Table
func	int × dbl → int	0	...	ST(func)

### ST(func)

Name	Type	Size	Offset	Nested Table
i	int	4	0	null
d	dbl	8	4	null
...rv	int	4	12	null

# Function Invocation Grammar

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:	$D$	$\rightarrow$	$T \text{ id } ( F_{opt} ) \{ L \}$	
1   2:	$L$	$\rightarrow$	$L_1 S \mid S$	
3:	$S$	$\rightarrow$	<b>return</b> $E$ ;	{ Check if function.type matches $E.type$ ; $emit(\text{return } E.loc);$ }
4:	$E$	$\rightarrow$	<b>id</b> ( $A_{opt}$ )	{ $ST = lookup(ST_{gbl}, \text{id}).syntab$ ; For every param $p$ in $A_{opt}.list$ ; Match $p.type$ with param type in $ST$ ; $emit(\text{param } p.loc)$ ; $E.loc = gentemp(lookup(ST_{gbl}, \text{id}).type)$ ; $emit(E.loc = \text{call id, length}(A_{opt}.list));$ }
5:	$A_{opt}$	$\rightarrow$	$A$	{ $A_{opt}.list = A.list;$ }
6:	$A_{opt}$	$\rightarrow$	$\epsilon$	{ $A_{opt}.list = 0;$ }
7:	$A$	$\rightarrow$	$A_1 , E$	{ $A.list = Merge(A_1.list,$ $Makelist(E.loc, E.type));$ }
8:	$A$	$\rightarrow$	$E$	{ $A.list = Makelist(E.loc, E.type);$ }

```
int a, b, c;
double d, e;
...
a = func(b + c, d * e);
return a;
```

### List of Params

t1	int
t2	double

```
t1 = b + c
t2 = d * e
param t1
param t2
t3 = call func, 2
a = t3
```

# Function Invocation Example

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.


sturtc in Expr.

Addl. Features

```
int a, b, c;
double d, e;
...
a = func(b + c, d * e);
return a;
```

```
t1 = b + c
t2 = d * e
param t1
param t2
t3 = call func, 2
```

```
E3.loc = b, E3.type = int
E4.loc = c, E4.type = int
E2.loc = t1, E2.type = int
A2.list = {t1}
E6.loc = d, E6.type = dbl
E7.loc = e, E7.type = dbl
E5.loc = t2, E5.type = dbl
A2.list = {t1, t2}
A_opt.list = {t1, t2}
E1.loc = t3, E1.type = int
```



ST(global)

Name	Type	Size	Offset	Nested Table
func	int × dbl → int	0	...	ST(func)

ST(func)

Name	Type	Size	Offset	Nested Table
i	int	4	0	null
d	dbl	8	4	null
--rv	int	4	12	null

ST(?)

Name	Type	Size	Offset	Nested Table
a	int	4	0	null
b	int	4	4	null
c	int	4	8	null
d	dbl	8	16	null
e	dbl	8	24	null
t1	int	4	28	null
t2	dbl	8	32	null
t3	int	4	40	null

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

**Scope Mgmt.**

struct in Expr.

Addl. Features

# Lexical Scope Management

# Grammar for Global, Function and Nested Block Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

0:	<i>Pgm</i>	→	<i>TU</i>	{ <i>UpdateOffset</i> ( <i>ST<sub>gbl</sub></i> ); } // End of TAC Translate
1:	<i>TU</i>	→	<i>TU<sub>1</sub> P</i>	
2:	<i>TU</i>	→	<i>M P</i>	
3:	<i>M</i>	→	ε	{ <i>ST<sub>gbl</sub></i> = <i>CreateSymbolTable</i> (); <i>ST<sub>gbl</sub>.parent</i> = 0; <i>cST</i> = <i>ST<sub>gbl</sub></i> ; }
4:	<i>P</i>	→	<i>VD</i>	// Variable Declaration
5:	<i>P</i>	→	<i>PD</i>	// Function Prototype Declaration
6:	<i>P</i>	→	<i>FD</i>	// Function Definition
7:	<i>VD</i>	→	<i>T V ;</i>	{ <i>type<sub>gbl</sub></i> = <i>null</i> ; <i>width<sub>gbl</sub></i> = 0; }
8:	<i>V</i>	→	<i>V<sub>1</sub> , id C</i>	{ <i>Name</i> = <i>lookup</i> ( <i>cST</i> , <i>id</i> ); <i>Name.category</i> = ( <i>cST</i> == <i>ST<sub>gbl</sub></i> )? <i>global</i> : <i>local</i> ; <i>Name.type</i> = <i>C.type</i> ; <i>Name.size</i> = <i>C.width</i> ; }
9:	<i>V</i>	→	<i>id C</i>	{ <i>Name</i> = <i>lookup</i> ( <i>cST</i> , <i>id</i> ); <i>Name.category</i> = ( <i>cST</i> == <i>ST<sub>gbl</sub></i> )? <i>global</i> : <i>local</i> ; <i>Name.type</i> = <i>C.type</i> ; <i>Name.size</i> = <i>C.width</i> ; }
10:	<i>C</i>	→	[ <i>num</i> ] <i>C<sub>1</sub></i>	{ <i>C.type</i> = <i>array</i> ( <i>num.value</i> , <i>C<sub>1</sub>.type</i> ); <i>C.width</i> = <i>num.value</i> × <i>C<sub>1</sub>.width</i> ; }
11:	<i>C</i>	→	ε	{ <i>C.type</i> = <i>type<sub>gbl</sub></i> ; <i>C.width</i> = <i>width<sub>gbl</sub></i> ; }
12:	<i>T</i>	→	<i>B</i>	{ <i>type<sub>gbl</sub></i> = <i>T.type</i> = <i>B.type</i> ; <i>width<sub>gbl</sub></i> = <i>T.width</i> = <i>B.width</i> ; }
13:	<i>B</i>	→	<b>int</b>	{ <i>B.type</i> = <i>int</i> ; <i>B.width</i> = <i>sizeof</i> ( <i>B.type</i> ); }
14:	<i>B</i>	→	<b>double</b>	{ <i>B.type</i> = <i>double</i> ; <i>B.width</i> = <i>sizeof</i> ( <i>B.type</i> ); }
15:	<i>B</i>	→	<b>void</b>	{ <i>B.type</i> = <i>void</i> ; <i>B.width</i> = <i>sizeof</i> ( <i>B.type</i> ); }

# Grammar for Global, Function and Nested Block Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

16:	<i>PD</i>	→	<i>T FN ( FP<sub>opt</sub> );</i>	{ <i>UpdateOffset(cST); cST = cST.parent; }</i>
17:	<i>FD</i>	→	<i>T FN ( FP<sub>opt</sub> ) CS</i>	{ <i>UpdateOffset(cST); cST = cST.parent; }</i>
18:	<i>FN</i>	→	<b>id</b>	{ <i>Name = lookup(ST<sub>gbl</sub>, id); ST = Name.symbtab;</i> if ( <i>ST is null</i> ) <i>ST = CreateSymbolTable(); ST.parent = ST<sub>gbl</sub>;</i> <i>Name.category = function; Name.symbtab = ST;</i> endif <i>cST = ST; }</i>
19:	<i>FP<sub>opt</sub></i>	→	<i>FP</i>	
20:	<i>FP<sub>opt</sub></i>	→	ε	
21:	<i>FP</i>	→	<i>FP<sub>1</sub> , T id</i>	{ <i>Name = lookup(cST, id); Name.category = param;</i> <i>Name.type = T.type; Name.size = T.width; }</i>
22:	<i>FP</i>	→	<i>T id</i>	{ <i>Name = lookup(cST, id); Name.category = param;</i> <i>Name.type = T.type; Name.size = T.width; }</i>
23:	<i>CS</i>	→	{ <i>N L</i> }	{ <i>UpdateOffset(cST); cST = cST.parent; }</i>
24:	<i>N</i>	→	ε	{ if ( <i>cST.parent is not ST<sub>gbl</sub></i> ) // Not a function scope <i>N.ST = CreateSymbolTable();</i> <i>N.ST.parent = cST; cST = N.ST;</i> endif }
25:	<i>L</i>	→	<i>L<sub>1</sub> S</i>	// List of Statements – Statement actions not shown
26:	<i>L</i>	→	<i>LD</i>	
27:	<i>LD</i>	→	<i>LD<sub>1</sub> VD</i>	// List of Declarations
28:	<i>LD</i>	→	ε	

# Grammar for Global, Function and Nested Block Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```

29:  S    →   CS
30:  S    →   E ;
31:  S    →   return E ;    { emit(return E.loc); }
32:  S    →   return ;      { emit(return); }

33:  E    →   E1 = E2      { E.loc = gentemp();
                             emit(E1.loc '=' E2.loc); emit(E.loc '=' E1.loc); }
34:  E    →   id            { E.loc = id.loc; }
35:  E    →   num           { E.loc = gentemp(); emit(E.loc = num.val); }
36:  E    →   AR            { E.loc = gentemp();
                             emit(E.loc '=' AR.array.base '[' AR.loc ']'); }
37:  AR   →   id [ E ]      { AR.array = lookup(cST, id);
                             AR.type = AR.array.type.elem; AR.loc = gentemp();
                             emit(AR.loc '=' E.loc '*' AR.type.width); }
38:  AR   →   AR1 [ E ]    { AR.array = AR1.array; AR.type = AR1.type.elem;
                             t = gentemp(); AR.loc = gentemp();
                             emit(t '=' E.loc '*' AR.type.width);
                             emit(AR.loc '=' AR1.loc '+' t); }
    
```



# Grammar for Global, Function and Nested Block Scopes

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
39:  E      →  id ( APopt )  { ST = lookup(STgbl, id).symtab;  
                               For every param p in APopt.list;  
                               Match p.type with param type in ST;  
                               emit(param p.loc);  
                               E.loc = gentemp(lookup(STgbl, id).type);  
                               emit(E.loc = call id, length(APopt.list)); }  
  
40:  APopt →  AP      { APopt.list = AP.list; }  
41:  APopt →  ε       { APopt.list = 0; }  
  
42:  AP      →  AP1 , E  { AP.list = Merge(AP1.list,  
                               Makelist((E.loc, E.type)); }  
43:  AP      →  E       { AP.list = Makelist((E.loc, E.type)); }
```

# Example 1: Global & Function Scope: main() & add(): Source

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int x, ar[2][3], y;
int add(int x, int y);
double a, b;
int add(int x, int y) {
    int t;
    t = x + y;
    return t;
}
void main() {
    int c;
    x = 1;
    y = ar[x][x];
    c = add(x, y);
    return;
}
```

# Example 1: Global & Function Scope: Parse Tree (Pgm)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int x, ar[2][3], y;          // M
int add(int x, int y);       // VD_1
double a, b;                 // PD
int add(int x, int y) {     // FD_1
    int t;
    t = x + y;
    return t;
}
void main() {                // FD_2
    int c;
    x = 1;
    y = ar[x][x];
    c = add(x, y);
    return;
}
----
cST = ST.glb
```



# Example 1: Global & Function Scope: Parse Tree (VD<sub>1</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



```
int x, ar[2][3], y;      // VD_1
```

```
//cST = ST.glb
```

```
B.type = int, B.width = 4
```

```
T.type = int, T.width = 4
```

```
type_glb = int, width_glb = 4
```

```
C1.type = int, C1.width = 4
```

```
C4.type = int, C4.width = 4
```

```
C3.type = array(3, int), C3.width = 12
```

```
C2.type = array(2, array(3, int)), C4.width = 24
```

```
C5.type = int, C5.width = 4
```

<i>ST.gbl: ST.gbl.parent = null</i>					
x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null

*Columns: Name, Type, Category, Size, Offset, & Symtab*

# Example 1: Global & Function Scope: Parse Tree (PD<sub>1</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.


Addl. Features

```
//cST = ST.glb
B1.type = int, B1.width = 4
T1.type = int, T1.width = 4
type_glb = int, width_glb = 4
cST = ST.add // FN -> id
B2.type = int, B2.width = 4
T2.type = int, T2.width = 4
type_glb = int, width_glb = 4
B3.type = int, B3.width = 4
T3.type = int, T3.width = 4
type_glb = int, width_glb = 4
cST = ST.glb // PD -> T FN ( F_opt ) ;
```

```
int add(int x, int y); // PD
```

<i>ST.gbl: ST.gbl.parent = null</i>					
x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null
add	int × int → int				
		func	0	32	ST.add()

*Columns: Name, Type, Category, Size, Offset, & Symtab*



<i>ST.add(): ST.add.parent = ST.gbl</i>				
x	int	param	4	0
y	int	param	4	4

# Example 1: Global & Function Scope: Parse Tree (VD<sub>2</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.


Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
//cST = ST.glb
B.type = double, B.width = 8
T.type = double, T.width = 8
type_glb = double, width_glb = 8
C1.type = double, C1.width = 8
C2.type = double, C2.width = 8
```



```
double a, b;           // VD_2
```

<i>ST.gbl: ST.gbl.parent = null</i>					
x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null
add	int × int → int				
		func	0	32	ST.add()
a	double	global	8	32	null
b	double	global	8	40	null

<i>ST.add(): ST.add.parent = ST.gbl</i>					
x	int	param	4	0	
y	int	param	4	4	

*Columns: Name, Type, Category, Size, Offset, & Symtab*

# Example 1: Global & Function Scope: Parse Tree (FD<sub>1</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



*ST.gbl: ST.gbl.parent = null*

x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null
add	int × int → int				
		func	0	32	ST.add()
a	double	global	8	32	null
b	double	global	8	40	null

Columns: Name, Type, Category, Size, Offset, &

*ST.add(): ST.add.parent = ST.gbl*

x	int	param	4	0
y	int	param	4	4
t	int	local	4	8
t#1	int	temp	4	12

```
int add(int x, int y) { // FD_1
    int t;
    t = x + y;
    return t;
}
```

# Example 1: Global & Function Scope: Parse Tree (FD<sub>2</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



<i>ST.gbl: ST.gbl.parent = null</i>					
x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null
add	int × int → int				
		func	0	32	ST.add()
a	double	global	8	32	null
b	double	global	8	40	null
main	void → void				
		func	0	48	ST.main()

Columns: Name, Type, Category, Size, Offset, & Syntab

<i>ST.add(): ST.add.parent = ST.gbl</i>					
x	int	param	4	0	
y	int	param	4	4	
t	int	local	4	8	
t#1	int	temp	4	12	
<i>ST.main(): ST.main.parent = ST.gbl</i>					
c	int	local	4	0	
t#1	int	temp	4	4	
t#2	int	temp	4	8	
t#3	int	temp	4	12	
t#4	int	temp	4	16	



# Example 1: Global & Function Scope: main() & add(): Source & TAC

Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int x, ar[2][3], y;
int add(int x, int y);
double a, b;
int add(int x, int y) {
    int t;
    t = x + y;
    return t;
}
void main() {
    int c;
    x = 1;
    y = ar[x][x];
    c = add(x, y);
    return;
}
```

```
add:    t#1 = x + y
        t = t#1
        return t

main:   t#1 = 1
        x = t#1
        t#2 = x * 12
        t#3 = x * 4
        t#4 = t#2 + t#3
        y = ar[t#4]
        param x
        param y
        c = call add, 2
        return
```

<i>ST.gbl: ST.gbl.parent = null</i>					
x	int	global	4	0	null
ar	array(2, array(3, int))				
		global	24	4	null
y	int	global	4	28	null
add	int × int → int				
		func	0	32	ST.add()
a	double	global	8	32	null
b	double	global	8	40	null
main	void → void				
		func	0	48	ST.main()

*Columns: Name, Type, Category, Size, Offset, & Symtab*

<i>ST.add(): ST.add.parent = ST.gbl</i>					
x	int	param	4	0	
y	int	param	4	4	
t	int	local	4	8	
t#1	int	temp	4	12	
<i>ST.main(): ST.main.parent = ST.gbl</i>					
c	int	local	4	0	
t#1	int	temp	4	4	
t#2	int	temp	4	8	
t#3	int	temp	4	12	
t#4	int	temp	4	16	

## Example 2: Nested Blocks: Source

### Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int a;
int f(int x) { // function scope f
    int t, u;
    t = x; // t in f, x in f
    { // un-named block scope f_1
        int p, q, t;
        p = a; // p in f_1, a in global
        t = 4; // t in f_1, hides t in f
        { // un-named block scope f_1_1
            int p;
            p = 5; // p in f_1_1, hides p in f_1
        }
        q = p; // q in f_1, p in f_1
    }
    return u = t; // u in f, t in f
}
```

# Example 2: Nested Blocks: Parse Tree (Pgm)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Example 2: Nested Blocks: Parse Tree (FD)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features





# Example 2: Nested Blocks: Parse Tree (VD)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Example 2: Nested Blocks: Parse Tree (CS<sub>1</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Example 2: Nested Blocks: Parse Tree (VD<sub>1</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features





# Example 2: Nested Blocks: Parse Tree (CS<sub>2</sub>)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.



Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Example 2: Nested Blocks: Parse Tree (Pgm Whole)

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.


Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features



# Example 2: Nested Blocks: Source & TAC

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
int a;
int f(int x) { // function scope f
    int t, u;
    t = x; // t in f, x in f
    { // un-named block scope f_1
        int p, q, t;
        p = a; // p in f_1, a in global
        t = 4; // t in f_1, hides t in f
        { // un-named block scope f_1_1
            int p;
            p = 5; // p in f_1_1, hides p in f_1
        }
        q = p; // q in f_1, p in f_1
    }
    return u = t; // u in f, t in f
}
```

```
f: // function scope f
    // t in f, x in f
    t = x
    // p in f_1, a in global
    p@f_1 = a@glb
    // t in f_1, hides t in f
    t@f_1 = 4
    // p in f_1_1, hides p in f_1
    p@f_1_1 = 5
    // q in f_1, p in f_1
    q@f_1 = p@f_1
    // u in f, t in f
    u = t
```

<i>ST.gbl: ST.gbl.parent = null</i>					
a	int	global	4	0	null
f	int → int				
		func	0	0	ST.f
<i>ST.f(): ST.f.parent = ST.gbl</i>					
x	int	param	4	0	null
t	int	local	4	4	null
u	int	local	4	8	null
f_1	null	block	-		ST.f_1

<i>ST.f_1: ST.f_1.parent = ST.f</i>					
p	int	local	4	0	null
q	int	local	4	4	null
t	int	local	4	8	null
f_1_1	null	block	-		ST.f_1_1
<i>ST.f_1_1: ST.f_1_1.parent = ST.f_1</i>					
p	int	local	4	0	null

Columns: Name, Type, Category, Size, Offset, & Syntab

# Example 2: Nested Blocks Flattened

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

```
f: // function scope f
  // t in f, x in f
  t = x
  // p in f_1, a in global
  p@f_1 = a@gbl
  // t in f_1, hides t in f
  t@f_1 = 4
  // p in f_1_1, hides p in f_1
  p@f_1_1 = 5
  // q in f_1, p in f_1
  q@f_1 = p@f_1
  // u in f, t in f
  u = t
```

<i>ST.f(): ST.f.parent = ST.gbl</i>					
x	int	param	4	0	null
t	int	local	4	4	null
u	int	local	4	8	null
f_1	null	block	—		ST.f_1
<i>ST.f_1: ST.f_1.parent = ST.f</i>					
p	int	local	4	0	null
q	int	local	4	4	null
t	int	local	4	8	null
f_1_1	null	block	—		ST.f_1_1
<i>ST.f_1_1: ST.f_1_1.parent = ST.f_1</i>					
p	int	local	4	0	null

Columns: Name, Type, Category, Size, Offset, & Syntab

```
f: // function scope f
  // t in f, x in f
  t = x
  // p in f_1, a in global
  p#1 = a@gbl
  // t in f_1, hides t in f
  t#3 = 4
  // p in f_1_1, hides p in f_1
  p#4 = 5
  // q in f_1, p in f_1
  q#2 = p#1
  // u in f, t in f
  u = t
```

<i>ST.f(): ST.f.parent = ST.gbl</i>					
x	int	param	4	0	null
t	int	local	4	4	null
u	int	local	4	8	null
p#1	int	blk-local	4	0	null
q#2	int	blk-local	4	4	null
t#3	int	blk-local	4	8	null
p#4	int	blk-local	4	0	null

# Handling Structures in Expression

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

Addl. Features

# Structures in Expression

# Handling various Additional Features

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

**Addl. Features**

# Additional Features

# Additional Features

## Module 05

Pralay Mitra  
Partha P Das

Obj. & Outl.

TAC

Sym. Tab.

Arith. Expr.

Bool. Expr.

Control Flow

Declarations

Using Types

Arrays in Expr.

Type Expr.

Functions

Scope Mgmt.

struct in Expr.

**Addl. Features**

- Handling of in C Pre-Processor (CPP)
- Handling of class definitions and instantiation
- Handling Inheritance
  - Static
  - Dynamic
- Handling templates