

AFR-o

The Amlantis System Overview

Version 0.11

Markéta Lisová

August 29, 2020

Special Thanks To

Sabina Eva Lisová

Marie Strnadová

Ondřej Profant

Vojtěch Biberle

Contents

I	Introduction	1
1	A Brief Introduction to the Amlantis System	3
1.1	The Amlantis Languages	4
II	The Amlantis System Environment	5
2	Languages	7
2.1	Syntax Model	7
2.1.1	Syntax Objects	8
2.2	Readers	9
2.2.1	Root Reader Abilities	9
2.3	Expanders	9
III	The Aml/Base Language	11
3	Syntax	13
3.1	The Aml/Base.Lang.Reader	13
3.1.1	Delimiters and Dispatch	13
3.1.2	Reading Symbols	15
3.1.3	Reading Numbers	15
3.1.4	Reading Booleans	17
3.1.5	Reading Pairs, Lists & Arrays	17
3.1.6	Reading Structures	17
3.1.7	Reading Strings	17

3.1.8	Reading Characters	18
3.1.9	Reading Quotes	19
3.1.10	Reading Comments	19
3.1.11	Reading Vectors	19
3.1.12	Reading Sets	19
3.1.13	Reading Dictionaries	19
3.1.14	Reading Keywords	19
3.1.15	Reading Polymorphic Tags	20
3.1.16	Reading Labels	20
3.1.17	Reading Metadata	20
3.1.18	Reading Parameterized Reads	20
3.1.19	Reading via an Extension	20
3.1.19.1	S-Expression Reader Language	20
3.1.19.2	Chaining Reader Language	20
IV	The Amlantis System Tools	21
4	The Top-Level System or REPL – aml	23
5	The Compiler – amlc	25
6	The Runtime System – amlrun	27
7	The Debugger – amldebug	29
8	The Profiler – amlprof	31
9	The Builder – amlbuild	33
10	The Book Workspace – amlbook	35

Part I

Introduction

Chapter 1

A Brief Introduction to the Amlantis System

Amlantis System is a collection of specifications of programming and data definition languages and their related tools, runtimes and libraries.

Those specifications do not always require particular implementations, but attempt to avoid undefined behaviours as much as possible.

Amlantis also provides an open source reference implementation of those specifications, but it is indeed possible for other people to write their own implementations or forks¹ of this default implementation, probably focusing on optimising other aspects of the system, maybe exploring new options of future development to be pull-requested into the default implementation.

A Few Notes on the Name

Amlantis' name has quite some history. The project started being named *Coral*, but that collided with another language of a similar name, *CORAL 66*. Then it got renamed to *Gear*, but that again collided with another language of the same name, which seemed inactive at the time, *zippers/gear*. Then an idea was born and Aml was named *Amlantis*, which is whatever you want it to be. It could be a misspelling of *Atlantis*², it could be an acronym like *A ML Language*, or maybe even something like *A ML Language And Neat Technology Improvement System*, or maybe *Caml* without the *C*. For the meaning of the cryptic *ML* part, search for the *Standard ML* or *OCaml*.

¹Forks and pull requests are preferred way of help!

²Intentionally – because otherwise, it would be named Atlantis, but there is already a city of that name.

1.1 The Amlantis Languages

The Amlantis System is a home to more than only one programming language – in fact, it can be home to any number of languages, ones that Amlantis users can either extend from existing languages create or even create new ones entirely. Every language build within the Amlantis System shares a common type system and value models, and thus are interoperable.

The minimal Amlantis System contains these languages:

- Aml/Base, a minimal Lisp-like³ language that is easy to parse and limited in functionality.
- Aml/Core, an ML-like⁴ language that is easier to read and harder to parse, fully featured in functionality.
- Aml, an ML-like⁵ language that extends Aml/Core, is easier to read and the hardest one to parse, also fully featured in functionality, and introducing more grammar than its parent Aml/Core.

More languages may be added to this list over time.

³One might say that Aml/Base is a grandchild of Racket and Clojure.

⁴One might say that Aml/Core is a grandchild of OCaml, SML and F#.

⁵One might say that Aml is a grandchild of Aml/Core, Haskell and Ada.

Part II

The Amlantis System Environment

Chapter 2

Languages

Amlantis System provides multiple interfaces to talk to it with. Those interfaces would be:

- A REPL console, where user's text input is immediately read, evaluated, printed and requested again.
- Source code, where user's text input is stored for reuse in general, usually to either do some scripting, or building modules and complex applications.
- Bytecode or native (machine) code files, which originate from textual source code.

More ways to interact with the Amlantis System might be possible in the future.¹

Either way, for now, text-based interface to all Amlantis System tools require it to have a component that is able to read the text. We call them *Language Readers* (or shortly just *Readers* for the rest of this chapter). After reading the text, it has to be given meaning and transformed into a system of values that the Amlantis System understands by *Language Expanders* (or shortly just *Expanders* for the rest of this chapter). The result of that can be eventually evaluated.

2.1 Syntax Model

The syntax of programs in the Amlantis System is determined by the following process:

- A *read* pass, which comprise processing a text source port into a syntax object. Such syntax object does not contain any bindings. The read pass is implemented by Readers (§2.2).

¹Some ideas for that would include natural speech interface (at least in English).

- An *expand* pass, where the syntax object from previous pass is transformed into a syntax object with full program information. All bindings are defined in such syntax object. The expand pass is implemented by Expanders (§2.3).

A fully-featured language provides implementation for both read and expand passes. Such implementation may as well reuse implementation of another language. A language may as well provide just its Reader, in case the resulting value can be expanded by the expander of `Aml/Base`. Alternatively, a language may provide just its Expander, providing bindings that may differ from those in `Aml/Base`.

2.1.1 Syntax Objects

A *syntax object* is a combination of an arbitrary Amlantis System value with lexical information, source-location information and syntax properties.²

Although syntax objects may contain any value, the expand pass (§2.1) will need to be able to handle the value and any value it itself contains. Therefore, it is recommended to limit the values embedded into syntax objects to the following types:

- Atoms:
 - Booleans.
 - Numbers.
 - Characters.
 - Strings.
 - Bytes and byte strings.
 - Symbols, Labels and Keywords.
 - Unit and Undefined.
- Basic collection and composite objects:
 - Tuples.
 - Pairs and Lists.
 - Vectors.
 - Dictionaries.

²Racket, where inspiration for this mechanism comes from, also has *tamper* status within those syntax objects. We may decide to add that later.

2.2 Readers

Every Reader needs a source port to read from. Such a port could be console input for the REPL, a file on local filesystem, a TCP connection, socket, or just an in-memory string³. Reading program source starts with a top-most Reader, which we may call the *Root Reader*, which is implicitly (unless defined otherwise) `Aml/Base.Lang.Reader`.

Readers are required to implement two methods: `read` and `read-syntax`.

The `read` method must accept a source port as its only argument, and it can return any type of value.

The `read-syntax` method must accept a source name argument along with second argument of the source port, and it must return either the `System/IO.Eof` value, or a `System/Lang.Syntax_Object` value.

The Root Reader's `read-syntax` method is used on the top-most initial port.⁴

2.2.1 Root Reader Abilities

The Root Reader can recognise basic delimiters, such as all whitespace and newlines, which aid it in switching to another source code language. Given that the Root Reader is in fact `Aml/Base.Lang.Reader`, its abilities are not limited to these.

Delimited by those, it can recognise the following forms:

- Shebang, such as `#!/usr/bin/env aml`, to point to the entry-level Amlantis System tool.
- Reader switch, `#reader name ...`, which specifies a reader to use for the following forms, and switches to it. The *name* should be a simple identifier.⁵
- Language switch, `#lang name ...`, which expands right away into `#reader name.Lang.Reader ...`⁶ The *name* should be a simple identifier.⁷

2.3 Expanders

³More about strings later.

⁴Might be different in future, when we allow it to use `read` instead. That is not very useful now though.

⁵Specification for identifiers will be provided later.

⁶It may expand to other forms as well in certain order, due to be defined later.

⁷Specification for identifiers will be provided later.

Part III

The Aml/Base Language

Chapter 3

Syntax

The syntax of Aml/Base is based on Lisp-1, the so-called “S-Expressions” (shorter for “symbolic expressions”¹) and blatantly borrowing from languages such as Scheme, Racket or Clojure, while maintaining similarities with the Aml and Aml/Core languages.

3.1 The Aml/Base.Lang.Reader

3.1.1 Delimiters and Dispatch

Along with whitespace (as defined by Unicode “White_Space” property), the following characters are delimiters:

`() [] { } " ' ` ~ ;`

The # character has got a special meaning, determined by the following character or characters; see below for details.

After skipping whitespace, the Aml/Base reader dispatches based on the next character or characters in the source port this way:

¹Which we will not abbreviate further as “sexprs”.

(starts a pair or list; see Reading Pairs, Lists & Arrays.
[starts a pair, list, or array; see Reading Pairs, Lists & Arrays.
{	starts a structure; see Reading Structures.
)	matches (or raises error.
]	matches [or raises error.
}	matches { or raises error.
"	starts a string; see Reading Strings.
'	starts a quote or a type variable; see Reading Quotes.
`	starts a tag or symbol; see Reading Polymorphic Tags and Reading Symbols.
~	starts a label; see Reading Labels.
;	starts a line comment; see Reading Comments.
#y or #Y	true; see Reading Booleans.
#n or #N	false; see Reading Booleans.
#t or #T	true; see Reading Booleans.
#f or #F	false; see Reading Booleans.
#(starts a set; see Reading Sets.
#[starts a vector; see Reading Vectors.
#{	starts a dictionary; see Reading Dictionaries.
#\	starts a character; see Reading Characters.
#"	starts a byte string; see Reading Strings.
#~	starts a symbol; see Reading Symbols.
#:	starts a keyword; see Reading Keywords.
#'	starts a quote; see Reading Quotes.
#`	starts a quasi-quote; see Reading Quotes.
#,	starts a (possibly splicing) unquote; see Reading Quotes.
#s'	starts a syntax quote; see Reading Quotes.
#s`	starts a syntax quasi-quote; see Reading Quotes.
#s,	starts a syntax (possibly splicing) unquote; see Reading Quotes.
#^	starts a metadata; see Reading Metadata.
##	starts a parameterized read; see Reading Parameterized Reads.
#e or #E	starts a number; see Reading Numbers.
#i or #I	starts a number; see Reading Numbers.
#<<	starts a string; see Reading Strings.
#	starts a block comment; see Reading Comments.
#, or #_	starts an S-Expression comment; see Reading Comments.
"#! "	starts a line comment; note that the space is necessary; see Reading Comments.
#!/	starts a line comment; see Reading Comments.
#!	may start a reader extension use; see Reading via an Extension.
#reader	starts a reader extension use; see Reading via an Extension.
#lang	starts a reader extension use; see Reading via an Extension.
#other	starts a handler defined in current readtable or raises error.
otherwise	starts a symbol; see Reading Symbols.

Table 3.2: Table of Dispatches recognized by `Aml/Base.Lang.Reader`.

3.1.2 Reading Symbols

A sequence of source characters that does not start with any of the sequences defined in Delimiters and Dispatch is parsed as either a symbol or a number. The sequence “#~”² also starts a symbol. A successful number parse takes precedence over symbol parse, see Reading Numbers.

A symbol parse may continue with “#” without dispatching on it, since the form does not start with it, and becoming a part of the symbol parse.

Symbols that consist entirely of “operator” characters (Unicode character classes Sm, So, except for U+0060) are treated specially, TBD³.

Example 3.1.1 A few examples of parsing a symbol:

```

Plum    reads equal to (string->symbol "Plum")
Plu#m   reads equal to (string->symbol "Plu#m")
Pl.um   reads equal to (string->symbol "Pl.um")
#~Plum  reads equal to (string->symbol "#~Plum")
string->symbol reads equal to (string->symbol "string->symbol")

```

3.1.3 Reading Numbers

A sequence of source characters that does not start with any of the sequences defined in Delimiters and Dispatch is parsed as a number when it matches the following grammar, in which n is a variable.

A number is optionally prefixed by an exactness specifying form, case-insensitively, #e (exact) or #i (inexact), which specifies its parsing as an exact or inexact number. Such form can be followed by whitespace, which is simply ignored.

In the grammar below, each literal lowercase letter stands for both itself and its uppercase form.

Grammar:

$$\begin{aligned}
 \langle number_n \rangle &::= \langle prefix_n \rangle \langle exact_n \rangle \mid \langle inexact_n \rangle \\
 \langle exact_n \rangle &::= \langle exact-rational_n \rangle \mid \langle exact-complex_n \rangle \\
 \langle exact-rational_n \rangle &::= \langle sign \rangle_{opt} \langle unsigned-rational_n \rangle \\
 \langle unsigned-rational_n \rangle &::= \langle unsigned-integer_n \rangle \\
 &\quad \mid \langle unsigned-integer_n \rangle \text{ "/" } \langle unsigned-integer_n \rangle
 \end{aligned}$$

²We have decided to use “#~” instead of “#%” for symbols as the resulting symbol appears easier to read.

³This is yet to be properly defined, but generally a property will be added to the form marking it “operator”.

$$\begin{aligned}
\langle \text{exact-integer}_n \rangle &::= \langle \text{sign} \rangle_{\text{opt}} \langle \text{unsigned-integer}_n \rangle \\
\langle \text{unsigned-integer}_n \rangle &::= \langle \text{digits}_n \rangle^+ \\
\langle \text{exact-complex}_n \rangle &::= \langle \text{exact-rational}_n \rangle_{\text{opt}} \langle \text{sign} \rangle \langle \text{unsigned-rational}_n \rangle \text{"i"} \\
\langle \text{inexact}_n \rangle &::= \langle \text{inexact-real}_n \rangle \mid \langle \text{inexact-complex}_n \rangle \\
\langle \text{inexact-real}_n \rangle &::= \langle \text{sign} \rangle_{\text{opt}} \langle \text{inexact-simple}_n \rangle (\langle \text{exp}_n \rangle \langle \text{exact-integer}_n \rangle)_{\text{opt}} \\
\langle \text{inexact-unsigned}_n \rangle &::= \langle \text{inexact-simple}_n \rangle \\
\langle \text{inexact-simple}_n \rangle &::= \langle \text{digits}_n \rangle \text{"."} \langle \text{digits}_n \rangle \\
&\quad \mid \langle \text{digits}_n \rangle \text{" / " } \langle \text{digits}_n \rangle \\
\langle \text{inexact-complex}_n \rangle &::= \langle \text{inexact-real}_n \rangle_{\text{opt}} \langle \text{sign} \rangle \langle \text{inexact-unsigned}_n \rangle \text{"i"} \\
\langle \text{sign} \rangle &::= \text{"+"} \mid \text{"-"} \\
\langle \text{general-number}_n \rangle &::= \langle \text{exactness} \rangle_{\text{opt}} \langle \text{number}_n \rangle \\
\langle \text{exactness} \rangle &::= \text{"#e"} \mid \text{"#i"}
\end{aligned}$$

In the table below, we define the parameterized digits_n , exp_n and prefix_n for all supported ns .

Grammar:

$$\begin{aligned}
\langle \text{digit}_{16} \rangle &::= \langle \text{digit}_{12} \rangle \mid \text{"c"} \mid \text{"d"} \mid \text{"e"} \mid \text{"f"} \\
\langle \text{prefix}_{16} \rangle &::= \text{"0x"} \\
\langle \text{digit}_{12} \rangle &::= \langle \text{digit}_{10} \rangle \mid \text{"a"} \mid \text{"b"} \\
\langle \text{prefix}_{12} \rangle &::= \text{"0d"} \\
\langle \text{digit}_{10} \rangle &::= \langle \text{digit}_8 \rangle \mid \text{"8"} \mid \text{"9"} \\
\langle \text{prefix}_{10} \rangle &::= \text{empty sequence} \\
\langle \text{digit}_8 \rangle &::= \langle \text{digit}_2 \rangle \mid \text{"2"} \mid \text{"3"} \mid \text{"4"} \mid \text{"5"} \mid \text{"6"} \mid \text{"7"} \\
\langle \text{prefix}_8 \rangle &::= \text{"0o"} \\
\langle \text{digit}_2 \rangle &::= \text{"0"} \mid \text{"1"} \\
\langle \text{prefix}_2 \rangle &::= \text{"0b"} \\
\langle \text{exp}_{16} \rangle &::= \text{"p"} \\
\langle \text{exp}_{12} \rangle &::= \langle \text{exp}_{10} \rangle \\
\langle \text{exp}_{10} \rangle &::= \text{"e"} \\
\langle \text{exp}_8 \rangle &::= \langle \text{exp}_{10} \rangle \\
\langle \text{exp}_2 \rangle &::= \langle \text{exp}_{10} \rangle \\
\langle \text{digits}_n \rangle &::= \langle \text{digit}_n \rangle (\text{"_"}_{\text{opt}} \langle \text{digit}_n \rangle)^*
\end{aligned}$$

In the grammar below, we define the special case of sexagesimal numbers. Some of the rules here override those for non-sexagesimal numbers.

Grammar:

$$\begin{aligned}
\langle \text{digit}_{60} \rangle &::= (\text{"0"} \mid \text{"1"} \mid \text{"2"} \mid \text{"3"} \mid \text{"4"} \mid \text{"5"})_{\text{opt}} \langle \text{digit}_{10} \rangle \\
\langle \text{prefix}_{60} \rangle &::= \text{"0s"} \\
\langle \text{exp}_{60} \rangle &::= \langle \text{exp}_{10} \rangle \\
\langle \text{digits}_{60} \rangle &::= \langle \text{digit}_{60} \rangle (\text{" , " } \langle \text{digit}_{60} \rangle)^* \\
\langle \text{inexact-simple}_{60} \rangle &::= \langle \text{digits}_{60} \rangle \text{" ; " } \langle \text{digits}_{60} \rangle
\end{aligned}$$

3.1.4 Reading Booleans

The forms “#yes”, “#y”, “#true”, “#t” (case-insensitive) followed by a delimiter are the complete input syntax for the `System.Boolean.Yes` constant, and “#no”, “#n”, “#false”, “#f” (case-insensitive) followed by a delimiter are the complete input syntax for the `System.Boolean.No` constant.

3.1.5 Reading Pairs, Lists & Arrays

Sequences of input characters that start with “(” or “[” begin parsing characters to form a pair or a list.⁴

Parsing a pair or list form entails recursively parsing sub-forms until a matching “)” or “]” (respectively, these are not interchangeable) is found. A delimited “.” is handled specially.

3.1.6 Reading Structures

3.1.7 Reading Strings

Sequences of input characters that start with “” begin parsing characters to form a string, until another “” is found (that is not escaped by a single “\”).

Within a string sequence, the following “escape sequences” are recognized:

- “\’”: single quote
- “\””: double-quotes (does not terminate the string form)
- “\\”: backslash (the second is not an escaping backslash)
- “\0”: binary zero (NUL, U+0000)
- “\a”: BEL (alarm) character (U+0007)
- “\b”: backspace (U+0008)
- “\e”: escape (U+001B)
- “\f”: form feed (U+000C)
- “\n”: end-of-line (U+000A)
- “\r”: carriage return (U+000D)

⁴Note that in Lisp languages, not excluding Aml/Base, evaluating list forms does not necessarily produce a list - instead, many list forms are a function application form. To get a list data structure, one either needs to construct it with function applications, or quote the list form.

- “\t”: horizontal tab (character tabulation, U+0009)
- “\v”: vertical tab (line tabulation, U+000B)
- “\xnn”: Unicode for the hexadecimal number specified by *nn*, where each *n* is a $\langle digit_{16} \rangle$.
- “\unnnn”: Unicode for the hexadecimal number specified by *nnnn*, where each *n* is a $\langle digit_{16} \rangle$, the character U+*nnnn*.
- “\Unnnnnnnn”: Unicode for the hexadecimal number specified by *nnnnnnnn*, where each *n* is a $\langle digit_{16} \rangle$, the character U+*nnnnnnnn*.
- “\u{n₁...n_m}”: Unicode for the hexadecimal number specified by *n₁...n_m*, where each *n_i* is a $\langle digit_{16} \rangle$ and *m* < 8, the character U+*n₁...n_m*.
- “\<newline>”: elided, where $\langle newline \rangle$ is either an end-of-line, carriage return, or carriage return end-of-line combination. This sequence is not added to the string form.

When the sequence of input characters starts with “#” instead of just “”, the parsed string form is a byte string.

Sequences of input characters that start with “#<<” begin parsing characters to form a string, in this form called *here string*. The characters following “#<<” until a newline character define a terminator for the string. The content of the resulting string form includes all characters between the line containing “#<<” and a line whose entire content is the specified terminator. The first and last line of such form are not included in the resulting string form. No escape sequences are recognized in *here strings*.

3.1.8 Reading Characters

Sequences of input characters that start with “#\” begin parsing characters to form a character constant. The following forms are recognized:

- “#\nul”, “#\null” or “#\o”: NUL (ASCII o), the next character must not be alphabetic.
- “#\backspace”: backspace (U+0008), the next character must not be alphabetic.
- “#\tab” or “#\htab”: horizontal tab (U+0009), the next character must not be alphabetic.
- “#\newline” or “#\linefeed”: end-of-line (U+000A), the next character must not be alphabetic.
- “#\vtab”: vertical tab (U+000B), the next character must not be alphabetic.
- “#\page”: form feed (page break, U+000C), the next character must not be alphabetic.

- “#\return”: carriage return (U+000D), the next character must not be alphabetic.
- “#\space”: space (U+0020), the next character must not be alphabetic.
- “#\delete” or “#\rubout”: delete (U+007F), the next character must not be alphabetic.
- “#\quote”, “#\squote” or “#\'' ”: single quote (apostrophe, U+0027), the next character must not be alphabetic after the former two forms.
- “#\xnn”: Unicode for the hexadecimal number specified by *nn*, where each *n* is a $\langle digit_{16} \rangle$.
- “#\unnnn”: Unicode for the hexadecimal number specified by *nnnn*, where each *n* is a $\langle digit_{16} \rangle$, the character U+*nnnn*.
- “#\Unnnnnnnn”: Unicode for the hexadecimal number specified by *nnnnnnnn*, where each *n* is a $\langle digit_{16} \rangle$, the character U+*nnnnnnnn*.
- “#\u{*n*₁...*n*_{*m*} }”: Unicode for the hexadecimal number specified by *n*₁...*n*_{*m*}, where each *n*_{*i*} is a $\langle digit_{16} \rangle$ and *m* < 8, the character U+*n*₁...*n*_{*m*}.
- “#\ ' *c* ”: the character *c*, which must be a single Unicode codepoint.

3.1.9 Reading Quotes

3.1.10 Reading Comments

3.1.11 Reading Vectors

3.1.12 Reading Sets

3.1.13 Reading Dictionaries

3.1.14 Reading Keywords

The sequence “#:” starts a keyword. The parsing is the same as for a symbol preceded by “#~”, except for this initial sequence, and the part after this initial sequence is never parsed as a number.

Example 3.1.2 A few examples of parsing a keyword:

```
#:Plum  reads equal to (string->keyword "Plum")
#:42    reads equal to (string->keyword "42")
```

3.1.15 Reading Polymorphic Tags

3.1.16 Reading Labels

3.1.17 Reading Metadata

3.1.18 Reading Parameterized Reads

3.1.19 Reading via an Extension

When the reader dispatches on the `#reader` form, it recursively applies another reader to the current source port.

First, the reader recursively reads the next datum after `#reader`, and uses it as path to the another reader. Such reader is then loaded, and `read` is used when this reader is in `read` mode, or else, `read-syntax` is used when this reader is in `read-syntax` mode.

The `#lang` reader form is similar. It must be followed by a single whitespace character (preferably a single space, ASCII 32), and then followed by an identifier form. The complete form is then terminated by a new line, or end-of-file. A sequence `#lang name` is equivalent to `#reader name.Lang.Reader`.

For compatibility with e.g. R^{6RS}, `#!` is an alias for `#lang` followed by a space when it is followed by alphanumeric ASCII, `+`, `-` or `_`.

3.1.19.1 S-Expression Reader Language

```
#lang s-exp path
```

3.1.19.2 Chaining Reader Language

```
#lang reader path
```

Part IV

The Amlantis System Tools

Chapter 4

The Top-Level System or REPL – `aml`

This chapter will describe the top-level system for the Amlantis System, which serves as universal entry point for running programs designed for this system.

Without input files specified in arguments, it permits interactive use of the Amlantis System through a mechanism known as read-eval-print loop (REPL). With this mode, the system repeatedly reads user's input, evaluates it with the context of every previous input of the same REPL session, prints the inferred type of the result of such evaluation along with the text representation of the result, if any, and repeats.

Chapter 5

The Compiler – `amlc`

In this chapter, we're going to describe the Amlantis System Compiler `amlc`, which compiles source code files to bytecode files. The compilation process involves reading through the input source files, expanding them by evaluating the read programs by using the specified language, and serializing the type system's state along with modules' state to bytecode files, which are then to be run by `amlrun` (§6) or `aml` (§4).

Chapter 6

The Runtime System – `amlrun`

This chapter will describe the `amlrun` tool, which reads files output by `amlc` (§5) and executes a specified executable¹.

¹Due to be described later, but those could be e.g. a specific function, or a script file.

Chapter 7

The Debugger – `amldebug`

In this chapter, we'll describe the Amlantis System's own debugger tool.

Chapter 8

The Profiler – amlprof

This chapter will describe the Amlantis System's profiling tool.

Chapter 9

The Builder – amlbuild

In this chapter, we'll describe the Amlantis System's builder tool.

Chapter 10

The Book Workspace – amlbook

This chapter will describe the Amlantis System's "Book Workspace" tool, which is a planned addition to the whole toolchain and supposed to be accompanied by a GUI. The purpose will be to work with source texts that intertwine program source code in snippets with rich text documents, and ability to selectively execute these program source codes, seeing results right below each snippet.