

AFR-o

The Amlantis System Overview

Version 0.11

Markéta Lisová

June 27, 2020

Special Thanks To

Sabina Eva Lisová

Marie Strnadová

Ondřej Profant

Vojtěch Biberle

Contents

I Introduction 1

1 A Brief Introduction to the Amlantis System 3

1.1 The Amlantis Languages 4

II Commons 5

2 Readers 7

2.1 Language-less Root Reader Abilities 8

Part I

Introduction

Chapter 1

A Brief Introduction to the Amlantis System

Amlantis System is a collection of specifications of programming and data definition languages and their related tools, runtimes and libraries.

Those specifications do not always require particular implementations, but attempt to avoid undefined behaviours as much as possible.

Amlantis also provides an open source reference implementation of those specifications, but it is indeed possible for other people to write their own implementations or forks¹ of this default implementation, probably focusing on optimising other aspects of the system, maybe exploring new options of future development to be pull-requested into the default implementation.

A Few Notes on the Name

Amlantis' name has quite some history. The project started being named *Coral*, but that collided with another language of a similar name, *CORAL 66*. Then it got renamed to *Gear*, but that again collided with another language of the same name, which seemed inactive at the time, *zippers/gear*. Then an idea was born and Aml was named *Amlantis*, which is whatever you want it to be. It could be a misspelling of *Atlantis*², it could be an acronym like *A ML Language*, or maybe even something like *A ML Language And Neat Technology Improvement System*, or maybe *Caml* without the *C*. For the meaning of the cryptic *ML* part, search for the *Standard ML* or *OCaml*.

¹Forks and pull requests are preferred way of help!

²Intentionally – because otherwise, it would be named Atlantis, but there is already a city of that name.

1.1 The Amlantis Languages

The Amlantis System is a home to more than only one programming language – in fact, it can be home to any number of languages, ones that Amlantis users can either extend from existing languages create or even create new ones entirely. Every language build within the Amlantis System shares a common type system and value models, and thus are interoperable.

The minimal Amlantis System contains these languages:

- Aml/Base, a minimal Lisp-like³ language that is easy to parse and limited in functionality.
- Aml/Core, an ML-like⁴ language that is easier to read and harder to parse, fully featured in functionality.
- Aml, an ML-like⁵ language that extends Aml/Core, is easier to read and the hardest one to parse, also fully featured in functionality, and introducing more grammar than its parent Aml/Core.

More languages may be added to this list over time.

³One might say that Aml/Base is a grandchild of Racket and Clojure.

⁴One might say that Aml/Core is a grandchild of OCaml, SML and F#.

⁵One might say that Aml is a grandchild of Aml/Core, Haskell and Ada.

Part II

Commons

Chapter 2

Readers

Amlantis System provides multiple interfaces to talk to it with. Those interfaces would be:

- A REPL console, where user's text input is immediately read, evaluated, printed and requested again.
- Source code, where user's text input is stored for reuse in general, usually to either do some scripting, or building modules and complex applications.
- Bytecode or native (machine) code files, which originate from textual source code.

More ways to interact with the Amlantis System might be possible in the future. Some ideas for that would include natural speech interface (at least in English).

Either way, for now, text-based interface to all Amlantis System components require it to have a component that is able to read the text. We call them *Readers*.

Every Reader needs a source port to read from. Such a port could be console input for the REPL, a file on local filesystem, a TCP connection, socket, or just an in-memory string¹. Reading program source starts with a top-most Reader, which we may call the *Root Reader*. Such Reader does not know about which language it is reading (whereas recursively-descendent created Readers may inherit such knowledge), so we say it is reading in a *language-less mode*.

The Root Reader's read-language method is used on the top-most initial port.

¹More about strings later.

2.1 Language-less Root Reader Abilities

The language-less Root Reader can recognise basic delimiters, such as all whitespace and newlines.

Delimited by these, it can recognise the following forms:

- Shebang, such as `#!/usr/bin/env aml`, to point to the generic Amlantis System component.
- Reader switch, `#reader path ...`, which specifies a reader to use for the following forms, and switches to it.
- Language switch, `#lang name ...`, which expands right away into `#reader name.Lang.Reader ...`²

For now, that's it. In the next iteration, the list may include line comments or alias for `#lang` in order to support languages such as R⁶RS.

²It may expand to other forms as well in certain order, due to be defined later.