



## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member

Example

Print Task

Order of Initialization

static Member  
function

Print Task

Count Objects

Comparison

Singleton Class

Module Summary

# Module 16: Programming in C++

## static Members

Instructors: Abir Das and Sourangshu Bhattacharya

Department of Computer Science and Engineering  
Indian Institute of Technology, Kharagpur

*{ abir, sourangshu }@cse.iitkgp.ac.in*

Slides taken from NPTEL course on Programming in Modern C++

by **Prof. Partha Pratim Das**



# static Data Member

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

### static Data Member

Example

Print Task

Order of Initialization

static Member  
function

Print Task

Count Objects

Comparison

Singleton Class

Module Summary

- A **static** data member
  - is *associated with class* not with object
  - is *shared by all the objects* of a class
  - needs to be *defined outside the class scope* (in addition to the *declaration within the class scope*) to avoid linker error
  - *must be initialized* in a source file
  - is constructed before `main()` starts and destructed after `main()` ends
  - can be **private** / **public**
  - can be accessed
    - ▷ with the class-name followed by the scope resolution operator (`::`)
    - ▷ as a member of any object of the class
  - **virtually eliminates any need for global variables in OOPs environment**
- We illustrate first with a simple example and then with a Print Task where:
  - There is a printer which can be loaded with a paper from time to time
  - Several print jobs (each requiring a number of pages) may be fired on the printer



# Program 16.01: static Data Member: Example

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function  
Print Task  
Count Objects  
Comparison

Singleton Class

Module Summary

### Non static Data Member

```
#include<iostream>
using namespace std;
class MyClass { int x; // Non-static
public:
    void get() { x = 15; }
    void print() { x = x + 10;
        cout << "x =" << x << endl ;
    }
};

int main() {
    MyClass obj1, obj2; // Have distinct x
    obj1.get(); obj2.get();
    obj1.print(); obj2.print();
}

---
x = 25 , x = 25
```

- **x** is a non-**static** data member
- **x** cannot be shared between **obj1** & **obj2**
- Non-**static** data members do not need separate definitions - instantiated with the object
- Non-**static** data members are initialized during object construction

CS20202: Software Engineering

### static Data Member

```
#include<iostream>
using namespace std;
class MyClass { static int x; // Declare static
public:
    void get() { x = 15; }
    void print() { x = x + 10;
        cout << "x =" << x << endl;
    }
};

int MyClass::x = 0; // Define static data member
int main() {
    MyClass obj1, obj2; // Have same x
    obj1.get(); obj2.get();
    obj1.print(); obj2.print();
}

---
x = 25 , x = 35
```

- **x** is **static** data member
- **x** is shared by all **MyClass** objects including **obj1** & **obj2**
- **static** data members must be defined in the global scope
- **static** data members are initialized during program start-up

Instructors: Abir Das and Sourangshu Bhattacharya



# Program 16.02: static Data Member: Print Task (**Unsafe**)

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization  
static Member  
function  
Print Task  
Count Objects  
Comparison  
Singleton Class  
Module Summary

```
#include <iostream>
using namespace std;
class PrintJobs { int nPages_; /* # of pages in current job */ public:
    static int nTrayPages_; /* # of pages in the tray */ static int nJobs_; // # of print jobs executing
    PrintJobs(int nP): nPages_(nP) { ++nJobs_; cout << "Printing " << nP << " pages" << endl;
        nTrayPages_ = nTrayPages_ - nP;
    } // Job started
    ~PrintJobs() { --nJobs_; } // Job done
};
int PrintJobs::nTrayPages_ = 500; // Definition and initialization -- load paper
int PrintJobs::nJobs_ = 0; // Definition and initialization -- no job to start with
int main() {
    cout << "Jobs = " << PrintJobs::nJobs_ << endl;
    cout << "Pages= " << PrintJobs::nTrayPages_ << endl;
    PrintJobs job1(10);
    cout << "Jobs = " << PrintJobs::nJobs_ << endl;
    cout << "Pages= " << PrintJobs::nTrayPages_ << endl;
    {
        PrintJobs job1(30), job2(20); // Different job1 in block scope
        cout << "Jobs = " << PrintJobs::nJobs_ << endl;
        cout << "Pages= " << PrintJobs::nTrayPages_ << endl;
        PrintJobs::nTrayPages_ += 100; // Load 100 more pages
    }
    cout << "Jobs = " << PrintJobs::nJobs_ << endl;
    cout << "Pages= " << PrintJobs::nTrayPages_ << endl;
}
```

Output:

```
Jobs = 0
Pages= 500
Printing 10 pages
Jobs = 1 // same nJobs_, nTrayPages_
Pages= 490
Printing 30 pages
Printing 20 pages
Jobs = 3 // same nJobs_, nTrayPages_
Pages= 440
Jobs = 1 // same nJobs_, nTrayPages_
Pages= 540
```



# Program 16.03/04: Order of Initialization: Order of Definitions

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member

Example

Print Task

Order of Initialization

static Member  
function

Print Task

Count Objects

Comparison

Singleton Class

Module Summary

```
#include <iostream>
#include <string>
using namespace std;
class Data { string id_; public:
    Data(const string& id) : id_(id)
    { cout << "Construct: " << id_ << endl; }
    ~Data()
    { cout << "Destruct: " << id_ << endl; }
};
class MyClass {
    static Data d1_; // Listed 1st
    static Data d2_; // Listed 2nd
};
Data MyClass::d1_("obj_1"); // Constructed 1st
Data MyClass::d2_("obj_2"); // Constructed 2nd

int main() { }
-----
Construct: obj_1
Construct: obj_2
Destruct: obj_2
Destruct: obj_1
```

```
#include <iostream>
#include <string>
using namespace std;
class Data { string id_; public:
    Data(const string& id) : id_(id)
    { cout << "Construct: " << id_ << endl; }
    ~Data()
    { cout << "Destruct: " << id_ << endl; }
};
class MyClass {
    static Data d2_; // Order of static members swapped
    static Data d1_;
};
Data MyClass::d1_("obj_1"); // Constructed 1st
Data MyClass::d2_("obj_2"); // Constructed 2nd

int main() { }
-----
Construct: obj_1
Construct: obj_2
Destruct: obj_2
Destruct: obj_1
```

- Order of initialization of **static** data members does not depend on their order in the definition of the class. It depends on the order their definition and initialization in the source



# static Member Function

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

**static Member  
function**

Print Task  
Count Objects

Comparison

Singleton Class

Module Summary

- A **static** member function
  - does not have **this** pointer – not associated with any object
  - *cannot access* non-**static** data members
  - *cannot invoke* non-**static** member functions
  - can be accessed
    - ▷ with the class-name followed by the scope resolution operator (**::**)
    - ▷ as a member of any object of the class
  - is needed to read / write **static** data members
    - ▷ Again, for encapsulation **static** data members should be **private**
    - ▷ **get()-set()** idiom is built for access (**static** member functions in **public**)
  - *may initialize static* data members *even before any object creation*
  - *cannot co-exist with a non-static version* of the same function
  - *cannot be declared* as **const**
- We repeat the Print Task with better (safer) modeling and coding



# Program 16.05: static Data & Member Function: Print Task (Safe)

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization  
static Member  
function  
Print Task  
Count Objects  
Comparison  
Singleton Class  
Module Summary

```
// #include <iostream> using namespace std;
class PrintJobs { int nPages_; // # of pages in current job
    static int nTrayPages_; /* # of pages in the tray */ static int nJobs_; // # of print jobs executing
public: PrintJobs(int nP) : nPages_(nP) { ++nJobs_; cout << "Printing " << nP << " pages" << endl;
    nTrayPages_ = nTrayPages_ - nP; } // Job started
    ~PrintJobs() { --nJobs_; } // Job done
    static int getJobs() { return nJobs_; } // get on nJobs_. Readonly. No set provided
    static int checkPages() { return nTrayPages_; } // get on nTrayPages_
    static void loadPages(int nP) { nTrayPages_ += nP; } // set on nTrayPages_
};

int PrintJobs::nTrayPages_ = 500; // Definition and initialization -- load paper
int PrintJobs::nJobs_ = 0; // Definition and initialization -- no job to start with
int main() { cout << "Jobs = " << PrintJobs::getJobs() << endl;
    cout << "Pages= " << PrintJobs::checkPages() << endl;
    PrintJobs job1(10);
    cout << "Jobs = " << PrintJobs::getJobs() << endl;
    cout << "Pages= " << PrintJobs::checkPages() << endl;
    {
        PrintJobs job1(30), job2(20); // Different job1 in block scope
        cout << "Jobs = " << PrintJobs::getJobs() << endl;
        cout << "Pages= " << PrintJobs::checkPages() << endl;
        PrintJobs::loadPages(100); // Load 100 more pages
    }
    cout << "Jobs = " << PrintJobs::getJobs() << endl;
    cout << "Pages= " << PrintJobs::checkPages() << endl;
}
```

## Output:

```
Jobs = 0
Pages= 500
Printing 10 pages
Jobs = 1 // same nJobs_, nTrayPages_
Pages= 490
Printing 30 pages
Printing 20 pages
Jobs = 3 // same nJobs_, nTrayPages_
Pages= 440
Jobs = 1 // same nJobs_, nTrayPages_
Pages= 540
```



# Counting Objects

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member

Example

Print Task

Order of Initialization

static Member  
function

Print Task

Count Objects

Comparison

Singleton Class

Module Summary

- We illustrate another example and use for `static` data member and member function
  - Here we want to track the number of objects created and destroyed for a class at any point in the program
  - Naturally no object can keep this information. So we hold two `static` data members
    - ▷ `nObjCons_`: Number of objects created since beginning. It is *read-only and incremented in every constructor*
    - ▷ `nObjDes_`: Number of objects destroyed since beginning. It is *read-only and incremented in the destructor*
  - At any point (`nObjCons_ - nObjDes_`) gives the number of *Live* objects
  - In an alternate (less informative model) we may just maintain `static` data member `nLive_` which is *incremented in every constructor and decremented in the destructor*





# Program 16.06: Count Objects

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function

Print Task  
Count Objects

Comparison

Singleton Class

Module Summary

```
#include <iostream>
#include <string>
using namespace std;
class MyClass { string id_; // Object ID
    static int nObjCons_, nObjDes_; // Object history
public:
    MyClass(const string& id) : id_(id)
    { ++nObjCons_;
      cout << "ctor: " << id_ << " "; getObjLive(); }
    ~MyClass() { ++nObjDes_;
      cout << "dtor: " << id_ << " "; getObjLive(); }
    static int getObjConstructed()
    { return nObjCons_; }
    static int getObjDestructed()
    { return nObjDes_; }
    // Get number of live objects
    static int getObjLive() {
        int nLive = nObjCons_ - nObjDes_;
        cout << "Live Objects = " << nLive << endl;
        return nLive;
    }
};
int MyClass::nObjCons_ = 0;
int MyClass::nObjDes_ = 0;
```

```
int dummy1(MyClass::getObjLive()); // Before (main())
MyClass sObj("sObj");
int dummy2(MyClass::getObjLive()); // Before (main())
int main() { MyClass::getObjLive();
    MyClass aObj("aObj");
    MyClass *dObj = new MyClass("dObj");
    {
        MyClass bObj("bObj");
        delete dObj;
    }
    MyClass::getObjLive();
}
```

```
Live Objects = 0 // Before any object (dummy1)
ctor: sObj Live Objects = 1
Live Objects = 1 // Before main() (dummy2)
Live Objects = 1 // Enter main()
ctor: aObj Live Objects = 2
ctor: dObj Live Objects = 3
ctor: bObj Live Objects = 4
dtor: dObj Live Objects = 3
dtor: bObj Live Objects = 2
Live Objects = 2 // Exit main()
: aObj Live Objects = 1
dtor: sObj Live Objects = 0 // After all object
```



# Comparison of static vis-a-vis non-static

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function  
Print Task  
Count Objects

Comparison

Singleton Class

Module Summary

### static Data Members

- Declared using keyword **static**
- All objects of a class share the *same copy / instance*
- *Accessed* using the *class name or object*
- May be **public** or **private**
- Belongs to the **namespace** of the class
- May be **const**
- Are *constructed before* **main()** is invoked
- Are *destroyed after* (in reverse order) **main()** returns
- Are *constructed* in the order of definitions in source
- Has a *lifetime* encompassing **main()**
- *Allocated* in **static** memory

### static Member Functions

- Declared using keyword **static**
- *Has no* **this** pointer parameter
- *Invoked* using the *class name or object*
- May be **public** or **private**
- Belongs to the **namespace** of the class
- *Can access* **static** data members and methods
- *Cannot access* non-**static** data members or methods
- Can be invoked anytime during program execution
- Cannot be **virtual** or **const**
- *Constructor* is **static** though not declared **static**

### Non-static Data Members

- Declared *without* using keyword **static**
- Each object of the class gets its *own copy / instance*
- *Accessed* only through an *object* of the class
- May be **public** or **private**
- Belongs to the **namespace** of the class
- May be **const**
- Are *constructed during* object construction
- Are *destroyed during* object destruction
- Are *constructed* in the order of listing in the class
- Has a *lifetime* as of the lifetime of the object
- *Allocated* in **static**, **stack**, or **heap** memory as of the object

### Non-static Member Functions

- Declared *without* using keyword **static**
- *Has an implicit* **this** pointer parameter
- *Invoked* only through an *object* of the class
- May be **public** or **private**
- Belongs to the **namespace** of the class
- *Can access* **static** data members and methods
- *Can* access non-**static** data members and methods
- Can be invoked only during *lifetime* of the object
- May be **virtual** and / or **const**
- *There cannot be* a non-**static** Constructor



# Singleton Class

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function  
Print Task  
Count Objects

Comparison

Singleton Class

Module Summary

- **Singleton** is a *creational design pattern*
  - ensures that *only one object* of its kind exists and
  - provides a *single point of access* to it for any other code
- A class is called a Singleton if it satisfies the above conditions
- Many classes are singleton:
  - President of India
  - Prime Minister of India
  - Director of IIT Kharagpur
  - CEO of a Company
  - ...
- How to implement a Singleton Class?
- How to restrict that user can created *only one* instance?



# Program 16.07: static Data & Member Function Singleton Printer

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function  
Print Task  
Count Objects

Comparison

Singleton Class

Module Summary

```
#include <iostream>
using namespace std;

class Printer { /* THIS IS A SINGLETON PRINTER -- ONLY ONE INSTANCE */
private: bool blackAndWhite_, bothSided_;
    Printer(bool bw = false, bool bs = false) : blackAndWhite_(bw), bothSided_(bs)
    { cout << "Printer constructed" << endl; } // Private -- Printer cannot be constructed!
    static Printer *myPrinter_; // Pointer to the Instance of the Singleton Printer
public: ~Printer() { cout << "Printer destructed" << endl; }
    static const Printer& printer(bool bw = false, bool bs = false) { // Access the Printer
        if (!myPrinter_) myPrinter_ = new Printer(bw, bs); // Constructed for first call
        return *myPrinter_; // Reused from next time
    }
    void print(int nP) const { cout << "Printing " << nP << " pages" << endl; }
};

Printer *Printer::myPrinter_ = 0;

int main() {
    Printer::printer().print(10);
    Printer::printer().print(20);

    delete &Printer::printer();
}
```

Output:

```
Printer constructed
Printing 10 pages
Printing 20 pages
Printer destructed
```



# Program 16.08: Using function-local static Data Singleton Printer

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member  
Example  
Print Task  
Order of Initialization

static Member  
function  
Print Task  
Count Objects  
Comparison

Singleton Class

Module Summary

```
#include <iostream>
using namespace std;

class Printer { /* THIS IS A SINGLETON PRINTER -- ONLY ONE INSTANCE */
    bool blackAndWhite_, bothSided_;
    Printer(bool bw = false, bool bs = false) : blackAndWhite_(bw), bothSided_(bs)
    { cout << "Printer constructed" << endl; }
    ~Printer() { cout << "Printer destructed" << endl; }
public:
    static const Printer& printer(bool bw = false, bool bs = false) {
        static Printer myPrinter(bw, bs); // The Singleton -- constructed the first time

        return myPrinter;
    }
    void print(int nP) const { cout << "Printing " << nP << " pages" << endl; }
};

int main() {
    Printer::printer().print(10);
    Printer::printer().print(20);
}
```

- Function local **static** object is used
- No memory management overhead – so destructor too get **private**
- This is called **Meyer's Singleton**

Output:

Printer constructed  
Printing 10 pages  
Printing 20 pages  
Printer destructed



# Module Summary

## Module 16

Instructors: Abir  
Das and  
Sourangshu  
Bhattacharya

static Data  
Member

Example

Print Task

Order of Initialization

static Member  
function

Print Task

Count Objects

Comparison

Singleton Class

Module Summary

- Introduced `static` data member
- Introduced `static` member function
- Exposed to use of static members
- Singleton Class discussed