

Found Defects

Sign Up allows to register with missing/ambiguous data

Description: The sign up endpoint is allowing hero with empty user name

Steps to reproduce:

Scenario: Heroes can be registered with 'username' field empty

✔

Given I do not have / pass already registered in the system

SUCCESS

0.09s

✔

DELETE http://localhost:8081/waesheroes/api/v1/users

REST Query

SUCCESS

0s

When I sign-up hero with following information:

✔

| username | pw | dateOfBirth | email | isAdmin | name | superpower |
|----------|------|-------------|---------------------------|---------|---------------|---------------------|
| | pass | 1984-07-26 | aldous0@bravenewworld.com | true | Amazing Admin | Write awesome books |

SUCCESS

0.11s

✔

POST http://localhost:8081/waesheroes/api/v1/users

REST Query

SUCCESS

0s

✖

Then I should receive a 400 status code

FAILURE

0.01s

Assertion error: Expected: is <400> but: was <200>

More details

Request Headers

username=
Accept=/*/*
Content-Type=application/json; charset=utf-8

Content Body

```
{
  "dateOfBirth": "1984-07-26",
  "email": "aldous0@bravenewworld.com",
  "name": "Amazing Admin",
  "superpower": "Write awesome books",
  "username": "",
  "pw": "pass",
  "isAdmin": true
}
```


Content Body

```
{
  "dateOfBirth": "1984-07-26",
  "email": "",
  "name": "",
  "superpower": "",
  "username": "aldous3",
  "pw": "pass",
}
```







Response Body

```
{
  "dateOfBirth": "1984-07-26",
  "email": "",
  "name": "",
  "superpower": ""
}
```

ISSUE: user is being registered with empty fields

Login feature throws internal server error when trying to login with missing password

Steps to reproduce:

| Steps | Outcome | Duration |
|--|---------|---|
|  Example #1: {user=admin, password=} | FAILURE | 0.09s |
|  When I login with the following credentials: admin / | SUCCESS | 0.07s |
|  GET http://localhost:8081/waesheroes/api/v1/users/access  | SUCCESS | 0s |
|  Then I should receive a 401 status code | FAILURE | 0.01s |
| Assertion error: Expected: is <401> but: was <500> | |  |

Request Headers

```
Authorization=Basic YWRtaW46
Accept=/*/*
```

Response Body

```
<html>
  <head>
    <title>Grizzly 2.4.0</title>
    <style>&lt;!--div.header {font-family:Tahoma,Arial,sans-serif;color:white;background-color:#003300;font-size:22px;-moz-border-radius-topleft: 10px;border-top-left-radius: 10px;-moz-border-radius-topright: 10px;border-top-right-radius: 10px;padding-left: 5px}div.body {font-family:Tahoma,Arial,sans-serif;color:black;background-color:#FFFFCC;font-size:16px;padding-top:10px;padding-bottom:10px;padding-left:10px}div.footer {font-family:Tahoma,Arial,sans-serif;color:white;background-color:#666633;font-size:14px;-moz-border-radius-bottomleft: 10px;border-bottom-left-radius: 10px;-moz-border-radius-bottomright: 10px;border-bottom-right-radius: 10px;padding-left: 5px}BODY {font-family:Tahoma,Arial,sans-serif;color:black;background-color:white;}B {font-family:Tahoma,Arial,sans-serif;color:black;}A {color : black;}HR {color : #999966;}&lt;!--&gt;</style>
  </head>
  <body>
    <div class="header">Request failed.</div>
    <div class="body">Request failed.</div>
    <div class="footer">Grizzly 2.4.0</div>
  </body>
</html>
```

Issue: an empty username should return a 400 or a 401 status code but instead it is giving back a 500 Internal Server error

Delete feature throws internal server error when trying to delete without credentials

Steps to reproduce:

| Steps | Outcome | Duration | | | | | | |
|---|---|--|--------------|-----|--|---|---------|----|
|  When I try to call delete endpoint without authentication | SUCCESS | 0.49s | | | | | | |
|  Then I should receive a 401 status code | FAILURE | 0.03s | | | | | | |
| Assertion error: Expected: is <401> but: was <500> | |  More details | | | | | | |
| Then I should see the error information in the JSON response | | | | | | | | |
|  | <table><tr><th>errorCode</th><th>errorMessage</th></tr><tr><td>401</td><td>Invalid credentials: Invalid username or password.</td></tr></table> | errorCode | errorMessage | 401 | Invalid credentials: Invalid username or password. | <table><tr><td>SKIPPED</td><td>0s</td></tr></table> | SKIPPED | 0s |
| errorCode | errorMessage | | | | | | | |
| 401 | Invalid credentials: Invalid username or password. | | | | | | | |
| SKIPPED | 0s | | | | | | | |
| | | FAILURE 0.53s | | | | | | |

Request Headers

Accept= */*

Response

Status code: 500

Response Headers


Content-Type: text/html; charset=ISO-8859-1
Connection: close
Content-Length: 1031

Response Body

```
<html>
  <head>
    <title>Grizzly 2.4.0</title>
    <style>&lt;!--div.header {font-family:Tahoma,Arial,sans-serif;color:white;background-color:#003300;font-size:22px;-moz-border-radius-topleft: 10px;border-top-left-radius: 10px;-moz-border-radius-topright: 10px;border-top-right-radius: 10px;padding-left: 5px}div.body {font-family:Tahoma,Arial,sans-serif;color:black;background-color:#FFFFCC;font-size:16px;padding-top:10px;padding-bottom:10px;padding-left:10px}div.footer {font-family:Tahoma,Arial,sans-serif;color:white;background-color:#666633;font-size:14px;-moz-border-radius-bottomleft: 10px;border-bottom-left-radius: 10px;-moz-border-radius-bottomright: 10px;border-bottom-right-radius: 10px;padding-left: 5px}BODY {font-family:Tahoma,Arial,sans-serif;color:black;background-color:white;}B {font-family:Tahoma,Arial,sans-serif;color:black;}A {color : black;}HR {color : #999966;}--&gt;</style>
  </head>
  <body>
    <div class="header">Request failed.</div>
    <div class="body">Request failed.</div>
    <div class="footer">Grizzly 2.4.0</div>
  </body>
</html>
```

Update end point allows for changing email to an already existing one

Steps to reproduce:

| Steps | Outcome | Duration | | | | | | | | | | | | | | |
|---|----------|-------------|--|---------|---------|------------|------------|--------|--------|------------|-----------------------|-------|--------|------------|---------|-------|
| Given I have hero with following information already registered: | | | | | | | | | | | | | | | | |
| <div>+</div> <table><tr><th>username</th><th>pw</th><th>dateOfBirth</th><th>email</th><th>isAdmin</th><th>name</th><th>superpower</th></tr><tr><td>Trunks</td><td>Future</td><td>1910-01-01</td><td>trunks@a.com</td><td>true</td><td>Turnks</td><td>Z Sword</td></tr></table> | username | pw | dateOfBirth | email | isAdmin | name | superpower | Trunks | Future | 1910-01-01 | trunks@a.com | true | Turnks | Z Sword | SUCCESS | 0.05s |
| username | pw | dateOfBirth | email | isAdmin | name | superpower | | | | | | | | | | |
| Trunks | Future | 1910-01-01 | trunks@a.com | true | Turnks | Z Sword | | | | | | | | | | |
| And I have admin already registered in the system | | | | | | | | | | | | | | | | |
| When I update hero with credentials Trunks / Future to: | | | | | | | | | | | | | | | | |
| <div>+</div> <table><tr><th>username</th><th>pw</th><th>dateOfBirth</th><th>email</th><th>isAdmin</th><th>name</th><th>superpower</th></tr><tr><td>Trunks</td><td>Gogita</td><td>1922-02-02</td><td>a.admin@wearewaes.com</td><td>false</td><td>Gogeta</td><td>Kaioken x3</td></tr></table> | username | pw | dateOfBirth | email | isAdmin | name | superpower | Trunks | Gogita | 1922-02-02 | a.admin@wearewaes.com | false | Gogeta | Kaioken x3 | SUCCESS | 0.06s |
| username | pw | dateOfBirth | email | isAdmin | name | superpower | | | | | | | | | | |
| Trunks | Gogita | 1922-02-02 | a.admin@wearewaes.com | false | Gogeta | Kaioken x3 | | | | | | | | | | |
| Then I should receive a 409 status code | | | FAILURE | 0s | | | | | | | | | | | | |
| Assertion error: Expected: is <409> but: was <200> | | |  More details | | | | | | | | | | | | | |

Request Headers

Authorization=Basic VHJ1bmtzOkZ1dHVyZQ==
 Accept=/*/*
 Content-Type=application/json; charset=utf-8

Content Body

```
{
  "dateOfBirth": "1922-02-02",
  "email": "a.admin@wearewaes.com",
  "name": "Gogeta",
  "superpower": "Kaioken x3",
  "username": "Trunks",
  "pw": "Gogita",
  "isAdmin": false
}
```

Response

Status code: 200

Response Body

```
{
  "dateOfBirth": "1922-02-02",
  "email": "a.admin@wearewaes.com",
  "isAdmin": false,
  "name": "Gogeta",
  "superpower": "Kaioken x3"
}
```

ISSUE: user is able to be updated to an already existing email