

DELFT UNIVERSITY OF TECHNOLOGY

LITERATURE RESEARCH & PROJECT PROPOSAL

ME56010-22

Bi-threshold Gates for Mechanical Logic in Intelligent Metamaterials

Authors:

Eoinlee Bley (5216737)

Supervisors:

Dr. Davood Farhadi Machekposhti

Malte ten Wolde

in partial fulfillment of the requirements for the degree of

Master of Science

in Mechanical Engineering

September 18, 2023



Abstract

Contents

0.1	Elementary Cellular Automata Formalism	2
0.2	Wolfram Numbering Scheme for ECA	2

0.1 Elementary Cellular Automata Formalism

1. State Space: $S = \{0, 1\}$
2. Neighborhood Configuration: N
 $N = (N_{-1}, N_0, N_1)$ where $N_{-1}, N_0, N_1 \in S$
3. Rule Function: $f : S^3 \rightarrow S$
4. Rule Set: R
5. Cube Domain: $D \subset \mathbb{R}^3$
Each vertex directly corresponds to a neighborhood configuration N , and its state is
6. Separating Planes: P
Defined by a single normal vector \mathbf{n} and different offsets $\{d_1, d_2, \dots, d_n\}$.
7. Domain Classification Function: $\Delta : D \rightarrow \{0, 1, 2, 3\}$
 $\Delta(x) = \sum_{i=1}^n H(n_x \cdot x_x + n_y \cdot x_y + n_z \cdot x_z - d_i)$
 $H(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$

0.2 Wolfram Numbering Scheme for ECA

In the Wolfram numbering scheme for Elementary Cellular Automata (ECA), the rule set R can be uniquely identified by a single integer, which is the binary representation of the output states for all possible neighborhood configurations. For Rule 110, the binary representation is formed by considering all 8 possible 3-cell neighborhood configurations, starting from 111 down to 000.

For example, in Rule 110, the corresponding output states for these configurations are 01101110. Here's how it maps:

Neighborhood Configuration	Output State	Binary Position (b)
111	0	b_7
110	1	b_6
101	1	b_5
100	0	b_4
011	1	b_3
010	1	b_2
001	1	b_1
000	0	b_0

So, the Wolfram number for Rule 110 is obtained by reading the output states from b_7 to b_0 as a binary number: $01101110_2 = 110_{10}$.