CHAPTER 1
INTRODUCTION

1.1 DESCRIPTION

Connify is a privacy-focused social networking and communication platform designed to establish secure connections between two or more strangers in physical proximity. The application aims to make real-world social interactions safer and more convenient by allowing nearby individuals to discover one another, initiate conversations, and request assistance without immediately revealing their personal identities or precise geographical locations. Unlike traditional location-based social networking applications that depend on centralized servers, continuous GPS tracking, and publicly accessible user profiles, Connify follows a privacy-oriented approach that prioritizes secure communication, user anonymity, trust, and personal safety.

Connify is developed using React Native, TypeScript, and Expo for the mobile application, supported by a Node.js and Fastify backend with MongoDB for data management. The application uses the custom SHARP Protocol (Syndrome-Based Error-Correction Spatial Matching Engine) to facilitate privacy-preserving proximity discovery. The protocol converts geographical coordinates into spatial grid cells and represents the surrounding area using a 1024-bit Bloom filter. It then applies BCH(15,7) error-correction coding over Galois Field GF(2^4) to help address variations in GPS sensor readings. Instead of transmitting raw latitude and longitude values, the system uses encoded spatial information and blinded hashes to support proximity matching while reducing the exposure of sensitive location data.

Another important feature of Connify is its hardware-backed cryptographic identity mechanism. The application uses Ed25519 cryptographic keypairs and secure key storage through Android Keystore and iOS Keychain to support device identity verification. When users initiate a connection request, the system manages the request through an episode-based workflow. Following the required verification and handshake process, a Just-In-Time (JIT) trust capsule

can be issued to establish a temporary, controlled communication session. This approach helps users communicate without requiring them to immediately exchange personal contact information or establish permanent connections.

Connify also supports real-time communication through Socket.IO and incorporates WebRTC-based voice communication capabilities. These features help users exchange messages and communicate during an active connection, depending on the implemented communication flow. The application is designed with a hybrid networking architecture that supports cloud-based communication when internet connectivity is available, alongside alternative mechanisms such as local Wi-Fi discovery, Bluetooth Low Energy (BLE), and SMS fallback for selected offline scenarios. These capabilities aim to improve communication flexibility in different network conditions, subject to device capabilities and platform restrictions.

In addition to its communication features, Connify incorporates a comprehensive personal safety suite to support users during real-world interactions. The application includes a Timed Safety Guard for scheduled check-ins, emergency contact management, emergency alerts, a high-decibel siren, fake call simulation, community hazard maps, and emergency information. A behavioral risk assessment engine evaluates selected interaction patterns to help identify potentially harmful activity, while trust scores and reputation mechanisms support responsible participation. The system also maintains an append-only, hash-chained audit ledger to help detect unauthorized modifications to recorded system events.

Furthermore, Connify follows a modular architecture that separates proximity discovery, identity management, connection requests, cryptographic verification, real-time communication, and personal safety services. This structure improves maintainability and allows individual components to be tested and enhanced independently. By combining privacy-preserving spatial matching, cryptographic identity, temporary trust-based connections, flexible communication mechanisms, and personal safety features, it aims to provide a

secure and reliable platform for initiating communication between nearby strangers while minimizing unnecessary exposure of personal information.

1.2 DEVICE AUTHORIZATION & SECURITY

The Zero-Knowledge Identity and Security module is responsible for protecting user privacy and establishing secure communication between strangers using Connify. Its primary objective is to minimize the exposure of personal identity and geographical information while enabling users to discover nearby individuals and initiate trusted connections. Traditional social networking applications often depend on personal profiles, phone numbers, email addresses, and centralized location tracking. Such approaches may expose users to unwanted surveillance, identity misuse, stalking, and other privacy-related risks. Connify addresses these concerns through privacy-preserving proximity matching and cryptographic identity verification.

Connify uses the custom SHARP Protocol to support proximity discovery without transmitting raw GPS coordinates to the central backend server. The protocol converts geographical coordinates into spatial grid cells and generates a representation of the surrounding area using a 1024-bit Bloom filter. It applies BCH(15,7) error-correction coding over Galois Field GF(2^4) to help handle variations in GPS sensor readings. The system exchanges encoded parity information and blinded spatial hashes to support matching between nearby devices. This approach reduces the need to expose precise geographical coordinates during the connection discovery process.

Another important component of this module is hardware-backed cryptographic identity management. Connify uses Ed25519 cryptographic keypairs to support device identity and digital signature verification. The mobile application integrates secure key-storage mechanisms through Android Keystore and iOS Keychain, helping protect cryptographic credentials against unauthorized access. Device identity information and cryptographic proofs are used as part of the application's authentication and connection-verification workflows. Optional biometric authentication can provide an additional layer of

access protection where supported and configured.The module also supports secure connection establishment through Just-In-Time (JIT) trust capsules. These capsules are short-lived, cryptographically signed credentials that provide temporary access for verified communication sessions. The backend stores the SHA-256 digest of the capsule token rather than the bearer token itself, according to the documented architecture. This mechanism helps limit the duration of connection privileges and reduces the need for permanent trust relationships between strangers. The cryptographic handshake process helps verify the intended connection before the communication session is established.

Furthermore, Connify incorporates security-oriented monitoring and audit mechanisms to improve accountability. The behavioral risk engine evaluates selected user activity patterns and applies restrictions to reduce potentially harmful request behavior. An append-only, hash-chained audit ledger records relevant system events and links entries using cryptographic hashes, helping detect unauthorized modifications to recorded events. Together, these mechanisms support identity protection, temporary trust establishment, and safer communication.

Overall, the Zero-Knowledge Identity and Security module forms a fundamental part of Connify by combining privacy-preserving spatial matching, hardware-backed cryptographic identity, secure key storage, temporary trust capsules, and tamper-evident audit logging. These features are designed to reduce unnecessary exposure of personal information and provide a more secure foundation for communication between nearby strangers.

1.3 DATA STREAM MANAGEMENT

The Stranger Connection Management module is responsible for managing the complete process of initiating, verifying, and maintaining communication between nearby individuals through Connify. Its primary objective is to provide a structured and secure mechanism through which strangers can discover one another, send connection requests, establish temporary trust, and communicate without immediately revealing their personal identity or

contact information. Unlike conventional social networking platforms that rely on permanent friend lists and publicly accessible profiles, Connify focuses on proximity-based connections and temporary, controlled communication sessions.

The module manages the connection lifecycle through request episodes. When a user creates a connection or assistance request, the application generates an episode containing the necessary request information and privacy-preserving spatial data. The backend processes the request and makes the relevant information available to eligible nearby peers through real-time communication mechanisms. This approach allows users to discover relevant requests based on their proximity and the application's supported request categories.

An important responsibility of this module is the cryptographic handshake and trust capsule issuance process. Before a temporary communication session is established, the participating devices follow the required verification workflow. The application uses cryptographic proofs and QR-based handshake functionality to support the verification process. Once the required conditions are satisfied, the backend can issue a Just-In-Time (JIT) trust capsule signed using Ed25519 cryptography. These capsules provide temporary communication privileges and are designed with a limited validity period, reducing the need for permanent trust relationships between strangers.

The module also supports real-time communication between connected users. Socket.IO enables the exchange of real-time events, including request updates and connection-related information. The application incorporates chat functionality and WebRTC-based voice communication capabilities to support interaction during an active session, depending on the implemented communication flow. Users can coordinate assistance, exchange relevant information, and manage their ongoing connections through the application's interface.

Furthermore, Stranger Connection Management works alongside the behavioral risk engine and audit ledger to support safer interactions. The risk engine evaluates selected activity patterns, such as repeated request broadcasts

within a short period, while the audit ledger maintains hash-linked records of relevant lifecycle events. These mechanisms help improve accountability and identify potentially suspicious behavior. The module also coordinates connection status changes and completion workflows so that temporary communication sessions can be managed appropriately.

Overall, the Stranger Connection Management module forms the central operational layer of Connify. By integrating request episodes, cryptographic handshake verification, temporary trust capsules, real-time communication, and risk monitoring, it provides a structured approach to establishing controlled connections between nearby strangers while prioritizing privacy, security, and personal safety.

1.3.1 REQUEST EPISODES & CAPSULE ISSUANCE

The Request Episodes and Capsule Issuance module manages the lifecycle of connection requests between nearby strangers in Connify. Its primary objective is to allow users to initiate temporary communication sessions while maintaining privacy and controlling access to the connection. Instead of creating permanent relationships immediately, Connify uses an episode-based approach in which each request represents a specific interaction, social connection, or assistance requirement.

When a user creates a request, the application collects the necessary request details and generates an episode through the backend API. The request may include the selected category, relevant information, and privacy-preserving spatial data generated by the SHARP Protocol. The backend processes the request and distributes the appropriate information to nearby peers through Socket.IO-based real-time communication. This enables eligible users to discover active requests and respond according to their interests and availability.

Once a suitable peer is identified, the application proceeds with the required verification workflow. After the necessary conditions are satisfied, the backend issues a Just-In-Time (JIT) trust capsule. The capsule is a short-lived, cryptographically signed credential designed to authorize temporary

communication privileges. Connify uses Ed25519 digital signatures to support capsule authenticity, while the backend stores the SHA-256 digest of the token rather than the bearer token itself. The documented capsule lifetime is two hours, helping limit the duration of access.

The module also manages important episode lifecycle events, including request creation, response handling, connection establishment, and outcome recording. These events can be incorporated into the application's hash-chained audit ledger to support accountability and event verification. By combining structured request management with temporary cryptographic credentials, this module provides a controlled mechanism for initiating communication between strangers while reducing dependence on permanent identity sharing.

1.3.2 CRYPTOGRAPHIC HANDSHAKE VERIFICATION

The Cryptographic Handshake Verification module is responsible for verifying the connection process between two devices before enabling a trusted communication session. Its primary objective is to ensure that a connection request is associated with the intended peer and that temporary communication privileges are granted only through the required verification workflow. Since Connify is designed for interactions between strangers, the verification process plays an important role in reducing unauthorized access and strengthening user trust.

Connify incorporates QR-based handshake functionality supported by cryptographic identity mechanisms. Each device uses an Ed25519 public/private keypair to support identity verification and digital signatures. The mobile application integrates hardware-backed key storage through Android Keystore and iOS Keychain, helping protect private cryptographic credentials. During the handshake process, the participating devices exchange the required verification information through the application's supported workflow.

The handshake process works alongside the Request Episodes and Capsule Issuance module. When a helper or peer accepts a suitable request, the application initiates the required verification steps, which may include scanning

a QR code and validating the associated token or cryptographic proof. The backend validates the relevant information before issuing or authorizing a Just-In-Time (JIT) trust capsule. The capsule is digitally signed to support authenticity and has a limited validity period, helping prevent communication privileges from remaining active indefinitely.

The module also contributes to the security of active connections by supporting controlled access to communication sessions. Cryptographic verification helps establish confidence in the authenticity of connection credentials, while the temporary nature of trust capsules reduces the need for permanent trust relationships. Relevant connection and capsule lifecycle events can also be recorded in the hash-chained audit ledger to help detect unauthorized modifications to recorded events.

Overall, the Cryptographic Handshake Verification module provides an important security layer in Connify. By combining QR-based verification, Ed25519 cryptography, secure key storage, and temporary trust credentials, it supports controlled communication establishment between nearby strangers while protecting sensitive identity information.

1.3.3 REAL TIME CHAT & VOIP COMMUNICATION

The Real-Time Chat and Voice over Internet Protocol (VoIP) Communication module enables users to communicate after establishing a verified connection through Connify. Its primary objective is to provide convenient, real-time interaction between connected strangers without requiring them to immediately exchange personal phone numbers or other private contact details. This module supports communication during social interactions, local meetups, and assistance-related situations.

Connify uses Socket.IO to support real-time, bidirectional communication between the mobile application and the backend. The socket infrastructure manages connection-related events and enables timely delivery of supported updates, such as new request notifications and changes in active connection

status. This reduces the need for repeated manual refreshing and helps keep the application interface synchronized with ongoing activities.

The application also incorporates WebRTC-based voice communication capabilities. WebRTC provides the underlying technology for real-time audio communication between supported devices. The associated communication services manage voice-session state and the audio communication workflow. Socket.IO can support the signaling exchange required to coordinate a voice connection, while WebRTC handles the audio media stream. The availability and successful operation of voice communication depend on the implemented signaling workflow, network conditions, and device permissions.

The module works alongside Connify's request episode and trust capsule mechanisms to support communication within an active connection. Once the required connection verification is completed, users can access the communication features permitted by the application. The temporary trust model helps separate a specific interaction from a permanent social relationship, while connection status management supports the handling of active sessions.

Furthermore, real-time communication is supported by the application's state management architecture, which maintains relevant connection and communication information. Socket events and service-level updates allow the interface to reflect changes in connection status and other supported activities. Appropriate handling of network interruptions and communication errors is important for maintaining a consistent user experience.

1.4 NETWORK DISCOVERY & TOPOLOGY

Connify incorporates a spatial discovery mechanism that enables users to identify and establish connections with people in their physical surroundings while maintaining privacy. Unlike conventional social networking applications that primarily depend on public profiles, usernames, or continuous location sharing, Connify focuses on proximity-based interaction. The system uses the SHARP Protocol to process spatial information and determine whether users fall

within a relevant proximity range. This approach is designed to reduce the exposure of sensitive location data during the discovery process.

The spatial discovery mechanism organizes location information into quantized spatial grid regions, allowing the system to evaluate nearby relationships without requiring users to disclose their exact coordinates to the central server. The SHARP engine combines a 1024-bit Bloom filter, FNV-1a hashing, and BCH(15,7) error-correction coding over $GF(2^4)$ to support its spatial matching process. Through the exchange of encoded parity syndromes and blinded hashes, the protocol is designed to support proximity matching while limiting the transmission of raw location information.

Connify follows a hybrid network topology to support communication under different connectivity conditions. The online architecture uses backend REST services and WebSocket-based communication through Socket.IO for request handling, connection updates, and real-time interactions. When supported by the device and local network, mechanisms such as Wi-Fi discovery, multicast DNS (mDNS), TCP communication, and Bluetooth Low Energy (BLE) can assist local discovery or communication. These alternatives help the application adapt to different networking environments.

The system also incorporates fallback mechanisms for situations where internet connectivity is limited or unavailable. Depending on device permissions, platform support, and network conditions, local communication mechanisms or SMS-based emergency notifications may be used for selected functions. This hybrid approach aims to improve the availability of essential features without assuming that every communication method will work in every environment.

In addition to proximity discovery and network communication, Connify integrates personal safety services into its architecture. These include emergency alerts, trusted emergency contacts, a siren, a fake-call feature, hazard information, and emergency contact numbers. By combining privacy-oriented spatial matching, flexible network connectivity, and safety-related functions,

Connify provides a structured platform for secure social interaction between nearby strangers.

1.4.1 SHARP PROXIMITY MATCHING

The SHARP (Syndrome-Based Error-Correction Spatial Matching) Protocol is a core component of Connify that enables proximity-based user discovery while limiting the exposure of sensitive location information. Instead of directly transmitting raw geographical coordinates to the central server, the protocol processes spatial information by converting coordinates into quantized spatial grid representations. This allows the system to evaluate proximity relationships using encoded data rather than relying on the continuous sharing of exact user locations.

The SHARP engine incorporates a 1024-bit Bloom filter and FNV-1a hashing to represent spatial information in a compact form. It also uses BCH(15,7) error-correction coding over the finite field GF(2^4) to support the encoding and processing of spatial matching information. Through the exchange of encoded parity syndromes and blinded hashes, the protocol is designed to identify relevant proximity relationships without directly revealing raw coordinates to the backend server.

This mechanism provides a privacy-oriented foundation for discovering nearby users. By combining spatial quantization, hashing, and error-correction techniques, Connify aims to support efficient proximity matching while reducing unnecessary exposure of location data. The SHARP Protocol therefore forms an important part of the application's secure social discovery architecture.

1.4.2 HYBRID ONLINE & OFFLINE MESH FALLBACK

Connify uses a hybrid networking approach to support its communication features across different connectivity conditions. In online mode, the application communicates with backend services through REST APIs and Socket.IO-based real-time connections. These services support request processing, connection

updates, and communication-related events between users. This architecture provides the primary communication path when internet connectivity is available.

For local discovery and communication scenarios, the system architecture includes mechanisms such as Wi-Fi-based discovery, multicast DNS (mDNS), TCP communication, and Bluetooth Low Energy (BLE). These mechanisms can help devices discover or communicate with nearby devices when the required network conditions, permissions, and platform capabilities are available. Their availability depends on the device operating system and the surrounding network environment.

Connify also includes an SMS-based fallback for selected emergency-related functions when internet access is unavailable or unreliable. This approach helps preserve access to important safety notifications under certain conditions. However, local communication and fallback functions are subject to device support, permissions, network availability, and implementation constraints. The hybrid architecture is intended to improve resilience by providing alternative communication paths rather than depending exclusively on cloud connectivity.

1.4.3 PERSONAL SAFETY & BACKGROUND SERVICES

Connify integrates personal safety features to help users manage potentially uncomfortable or risky situations during interactions with unfamiliar people. The safety suite includes emergency contacts and alerts, a siren function, a fake-call feature, hazard information, and emergency contact numbers. These features are designed to provide users with accessible safety-related tools within the application.

The application also incorporates a behavioral risk engine that supports the identification and assessment of potentially suspicious interaction patterns. A hash-chained audit ledger is included to maintain a linked sequence of audit records and help protect the integrity of recorded events. Together, these components contribute to the application's safety monitoring and accountability mechanisms.

Background services support selected application functions when permitted by the operating system and device configuration. Emergency notifications may use available connectivity mechanisms, including SMS fallback where supported. The operation of these services depends on factors such as device permissions, battery restrictions, network availability, and platform policies.

By combining emergency tools, risk assessment, audit records, and available background services, Connify aims to provide a safety-oriented environment for proximity-based social interaction. These components complement the SHARP Protocol and secure identity mechanisms, making personal safety an integral part of the overall system design.

1.5 SYSTEM RELIABILITY

System reliability is an important aspect of Connify, as the application combines spatial discovery, secure identity management, real-time communication, and personal safety features. The system is designed with a modular architecture that separates the mobile application, backend services, database operations, cryptographic functions, and communication mechanisms. This separation helps organize the application components and makes individual modules easier to maintain, test, and improve.

Connify uses Node.js and Fastify for backend services, MongoDB for data storage, and Socket.IO for real-time communication. These technologies support request processing, connection management, and communication events. The application also incorporates secure key storage through Android Keystore and iOS Keychain, along with Ed25519 digital signatures for identity-related operations. These mechanisms are intended to strengthen identity verification and protect sensitive cryptographic material.

The SHARP Protocol contributes to the privacy-oriented design by processing quantized spatial information and using encoded syndromes and blinded hashes for proximity matching. Just-in-time trust capsules have a limited lifetime, with a two-hour time-to-live (TTL), helping restrict the period during

which a connection authorization remains valid. The system also includes a hash-chained audit ledger to support the integrity of recorded events and a behavioral risk engine to assist with safety-related assessments.

Connify incorporates alternative communication mechanisms to support selected functions under different network conditions. Depending on device capabilities and connectivity, the architecture includes local discovery options and SMS-based fallback for certain emergency-related functions. The safety suite provides emergency alerts, trusted contacts, a siren, a fake-call feature, and hazard information. These features are designed to improve the application's usefulness in situations where users may need additional assistance.

Overall, Connify aims to provide reliable and privacy-conscious social interaction through secure identity management, proximity matching, controlled connection authorization, and integrated safety services. Actual reliability depends on implementation quality, device compatibility, network availability, operating-system restrictions, and testing under different conditions. Therefore, unit, integration, system, performance, and security testing are important for evaluating the correctness, stability, and effectiveness of the application.

1.6 OBJECTIVES OF THE PROJECT

The primary objectives of this project are:

- To design and implement the SHARP Protocol for zero-knowledge spatial proximity discovery utilizing Galois Field GF(2^4) BCH error correction.
- To build a cross-platform mobile application in React Native / TypeScript delivering spatial social communication initialization between strangers.
- To publish and deploy the production application on the Google Play Store (com.connify).
- To develop a high-performance backend infrastructure using Fastify, Prisma ORM, and MongoDB providing REST and WebSocket communication services.

CHAPTER 2

LITERATURE SURVEY

2.1 TITLE: A USER SENSITIVE PRIVACY-PRESERVING LOCATION SHARING SYSTEM IN MOBILE SOCIAL NETWORKS – 2014

AUTHOR NAME: URMILA AND SHUBHAM

Location-based social networking applications allow users to share their locations and discover information about people and places around them. These services improve social interaction and provide context-aware features, but sharing location information can create privacy risks. If exact coordinates are exposed to an unauthorized party, they may reveal a user's movements, daily routines, and frequently visited places. The study, *A User Sensitive Privacy-preserving Location Sharing System in Mobile Social Networks*, addresses this concern by introducing a location-sharing approach that considers individual privacy requirements. The system aims to provide useful location information while reducing the possibility of identifying a user's exact position.

The proposed approach allows users to define privacy sensitivity profiles and transform geographical information into obfuscated regional representations. Instead of directly sharing the exact location, the system provides an approximate region that is sufficiently useful for the intended application. This separation between the actual location and the shared representation helps reduce the risk of unauthorized tracking. The approach also considers the balance between location accuracy and privacy protection, since excessive obfuscation may reduce the usefulness of location-based services.

The study demonstrates the importance of incorporating privacy controls into mobile social networking systems rather than treating location protection as an optional feature. It provides a foundation for developing applications that support location-aware interaction while limiting unnecessary disclosure of personal information. These concepts are relevant to Connify.

2.2 TITLE: THE FLEXIBLE AND PRIVACY-PRESERVING PROXIMITY DETECTION IN MOBILE SOCIAL NETWORK – 2018
AUTHOR NAME: ROBERT C. MILLER

Proximity detection is an important feature in mobile social networking applications because it enables users to discover other people within their physical surroundings. Traditional proximity detection methods commonly depend on users submitting their geographical coordinates to a location server, which calculates the distances between participating users. Although this approach can provide nearby-user information, it introduces privacy concerns when the server is untrusted or when location records are exposed through unauthorized access. The study, *The Flexible and Privacy-Preserving Proximity Detection in Mobile Social Network*, explores an alternative approach to identifying nearby users while reducing dependence on exact location disclosure.

The proposed method uses nearby reference lists derived from beacon signals to determine whether users are in proximity. Instead of requiring the server to calculate distances directly from exact geographical coordinates, the system compares the reference information associated with participating users. If their nearby reference lists share a common item, the users can be identified as potential neighbors. The research also discusses beacon-node rotating and beacon-node competition mechanisms for determining how beacon signals are transmitted. These techniques support proximity discovery through distributed reference information.

An important contribution of this approach is its focus on privacy-preserving neighbor discovery. It illustrates how nearby-user detection can be performed using alternative representations of spatial relationships rather than relying entirely on centralized location processing. However, beacon-based methods still require careful consideration of signal coverage, energy consumption, and the possibility of tracking devices through wireless signals. The study is relevant to Connify because both systems address the challenge of identifying nearby users while reducing the exposure of location information.

2.3 TITLE : A PRIVACY-PRESERVING EFFICIENT LOCATION-SHARING SCHEME FOR MOBILE ONLINE SOCIAL NETWORK APPLICATIONS – 2020 AUTHOR NAME: BJÖRN GRÖNVALL

Mobile online social networks provide location-sharing services that help users interact with friends and discover other people in their surroundings. However, these services may expose sensitive information when location data and social relationships are processed by servers that users do not fully trust. Existing approaches may depend on additional trusted servers or introduce communication and computational overhead while protecting private information. The study, *A Privacy-Preserving Efficient Location-Sharing Scheme for Mobile Online Social Network Applications*, investigates a secure and efficient approach to location sharing that supports interactions involving both established social relationships and strangers.

The proposed scheme considers the security of location updates, location sharing, and location queries. It uses cryptographic techniques and access-related mechanisms to protect information exchanged between users and system components. The research evaluates the proposed approach through security analysis, including formal security reasoning and authentication analysis. It also uses the ProVerif tool to verify security properties and reports experimental evaluation to examine the efficiency and practicality of the design. These methods demonstrate the importance of evaluating both security and performance when building privacy-sensitive mobile applications.

The study highlights that location-sharing systems must provide appropriate privacy protection without making communication excessively complicated or inefficient. It also shows the value of examining possible attacks and validating authentication mechanisms before deploying a security-oriented application. These concepts are relevant to Connify's identity and connection management components, which use Ed25519 digital signatures, secure key storage, and time-limited trust capsules to control connection authorization.

2.4 TITLE : A COMPREHENSIVE SURVEY OF BLUETOOTH LOW ENERGY SECURITY, PRIVACY CHALLENGES, AND PROTECTION MECHANISMS – 2022 AUTHOR NAME: G. RAJASEKARAN, R. REGIN

Bluetooth Low Energy (BLE) is a wireless communication technology widely used in smartphones, wearable devices, and Internet of Things applications. It supports short-range communication with relatively low power consumption, making it suitable for device discovery and nearby interaction. In mobile applications, BLE can assist in identifying devices within a limited communication range without requiring every interaction to pass through a remote server. However, the use of wireless discovery also introduces security and privacy concerns, particularly when devices expose identifiable information or use configurations that permit unauthorized tracking.

The study, *A Survey on Bluetooth Low Energy Security and Privacy*, examines the security and privacy characteristics of BLE and discusses weaknesses identified in its specifications and implementations. It reviews security-related features, pairing mechanisms, privacy protections, and potential attack scenarios. The research emphasizes that BLE security depends on the selected configuration, implementation quality, and the appropriate use of available security mechanisms. Therefore, developers must consider the complete communication environment instead of assuming that the use of a low-power wireless protocol automatically ensures secure interaction.

The survey is relevant to applications that support nearby-device discovery and local communication. BLE can provide an additional communication mechanism in environments where users need to discover nearby devices, but device identification, permission management, and protection against tracking must be considered during system design. Connify's architecture includes BLE among its potential local discovery mechanisms, alongside Wi-Fi-based discovery and online communication services. By considering the security limitations of wireless technologies, Connify can be evaluated with attention to both communication availability and user privacy.

CHAPTER 3
EXISTING SYSTEM

3.1 EXISTING SYSTEM

Existing social networking applications allow users to discover people, communicate through messaging services, and share information based on their interests or geographical locations. Many location-based platforms use GPS coordinates, centralized servers, and location-sharing services to identify nearby users. Although these systems provide convenient communication and discovery features, they may require users to share personal information or location data with service providers. This creates privacy concerns, particularly when users interact with unfamiliar people in their physical surroundings.

In conventional proximity-based applications, the user's location may be transmitted to a server that calculates distances and identifies nearby users. Depending on the application's design, this information may be stored, processed, or made available to other system components. Such approaches can introduce risks related to unauthorized location tracking, data exposure, and misuse of personal information. Users may also find it difficult to determine how their location information is handled and whether it is adequately protected.

Existing communication platforms commonly provide features such as text messaging, voice calls, profile management, and contact-based interaction. However, these features may not be integrated with privacy-preserving proximity discovery and temporary trust establishment in a single workflow. When users interact with strangers, they may need additional mechanisms to verify identities, control connection authorization, and manage the duration of a connection. The absence of integrated safety features can also make it difficult for users to respond quickly to uncomfortable or potentially risky situations.

Some applications support nearby-device discovery through Bluetooth, Wi-Fi, or other wireless technologies. Although these technologies enable local communication, their effectiveness depends on device compatibility,

permissions, network conditions, and implementation design. Wireless discovery alone does not guarantee secure identity verification or prevent the exposure of sensitive information.

Therefore, conventional social networking and proximity-based communication systems have limitations in combining privacy-conscious spatial discovery, secure identity verification, controlled connection management, and personal safety features. These limitations create the need for Connify, which is designed to combine the SHARP proximity-matching protocol, cryptographic identity mechanisms, time-limited trust capsules, real-time communication, and an integrated safety suite within a unified mobile application.

Furthermore, conventional systems often rely on centralized authentication and server-side processing, increasing dependency on third-party infrastructure and creating potential privacy risks. The protection of user identities and location information depends heavily on the security mechanisms implemented by each platform. Existing applications may lack flexible controls for establishing temporary connections that automatically expire after a specified period.




Figure 3.1 Existing System Architecture

CHAPTER 4
PROBLEMS IDENTIFIED

The increasing use of mobile social networking applications has made it easier for people to communicate, share information, and discover others based on their interests and geographical locations. However, establishing secure connections with strangers in the physical environment remains a challenging task. Many existing applications depend on centralized servers, conventional location-sharing mechanisms, and publicly accessible user profiles to identify nearby individuals. Although these approaches provide convenient discovery and communication features, they may expose sensitive personal information and create privacy concerns. Therefore, there is a need for a system that enables proximity-based social interaction while reducing unnecessary disclosure of users' identities and exact locations.

One of the major problems in conventional location-based applications is the exposure of geographical information. Applications that depend on GPS coordinates may transmit exact location data to backend servers for calculating distances and identifying nearby users. If this information is stored or processed without adequate protection, it may create opportunities for unauthorized tracking, profiling, or misuse. Users may not always have sufficient control over how their location information is collected, processed, and shared. This creates a requirement for a privacy-conscious proximity discovery mechanism that can identify relevant nearby users without directly exposing raw geographical coordinates to the central server.

Another important problem is the secure identification of unfamiliar users. In a conventional social networking environment, users may connect with others through usernames, profiles, or contact details, but these mechanisms do not necessarily establish a secure and verified interaction. When strangers attempt to communicate, the system must provide appropriate methods for verifying identity, controlling access, and preventing unauthorized connection attempts. Without reliable cryptographic verification and secure key management, the

connection process may be vulnerable to impersonation or misuse. Consequently, a proximity-based social platform requires a secure identity mechanism that protects cryptographic credentials and verifies connection-related operations.

The management of temporary connections also presents a significant challenge. In many applications, connections and communication permissions may remain available until users manually remove them or modify their settings. This can create unnecessary exposure when users only intend to establish a short-term interaction with someone nearby. A suitable system should support controlled connection authorization, limited validity periods, and a clear process for establishing trust between participants. It should also reduce the risk associated with unauthorized reuse of connection credentials. These requirements highlight the importance of temporary trust mechanisms and cryptographically verified handshakes in proximity-based communication systems.

Real-time communication between nearby strangers introduces additional technical challenges. Users may require messaging and voice communication after successfully establishing a connection, but these services must operate without compromising the security of the interaction. Network delays, unstable connectivity, and differences in mobile operating systems can affect communication availability. Depending entirely on internet connectivity may also limit selected features in environments where network access is poor. Therefore, a reliable solution should combine suitable backend communication services with alternative local networking or fallback mechanisms were supported by the device and operating environment.

Personal safety is another major concern when interacting with unfamiliar people. Users may encounter uncomfortable or potentially risky situations during face-to-face meetings or proximity-based social interactions. Traditional messaging and location-sharing applications may not provide a unified set of safety tools for responding to such situations. The absence of accessible emergency contacts, alerts, and quick-response functions can make it more difficult for users to seek assistance. A privacy-oriented social platform should therefore integrate safety-related features that allow users to access emergency

tools when required. Such features must be designed carefully, considering device permissions, network availability, and platform restrictions.

Existing spatial social discovery applications suffer from three interconnected engineering failures:

- Absence of Location Zero-Knowledge: Current social platforms force a compromise between spatial awareness and location privacy. Users must either surrender precise GPS data and public profiles to cloud providers or forego localized spontaneous social discovery.
- Vulnerability to GPS Sensor Jitter: Naive attempts to obfuscate coordinates (e.g., coordinate rounding or raw hash comparisons) fail under real-world mobile hardware conditions. GPS sensor drift leads to false negatives where two individuals standing 3 meters apart in the same coffee shop or event venue fail to match due to boundary mismatches or noisy coordinate samples.
- Centralized Identity and Lack of Stranger Trust Governance: Traditional social platforms rely on static passwords, unencrypted profile directories, and unverifiable interaction logs, leaving users vulnerable to identity impersonation, bad-faith encounters, and unsafe physical meetups.

Based on systematic evaluation of existing social discovery architectures, the following key limitations were identified:

- Complete Lack of Cryptographic Privacy: Centralized cloud backends possess full visibility into raw user coordinates, creating massive surveillance attack vectors.
- Inability to Handle Sensor Drift Cryptographically: No existing commercial social app employs telecommunications-grade error correction (such as BCH codes over Galois Fields) to bridge spatial sensor noise into exact zero-knowledge cryptographic matching.

CHAPTER 5
PROPOSED SYSTEM

5.1 PROPOSED SYSTEM OVERVIEW

Connify is a privacy-oriented social networking and communication platform designed to help users discover and connect with unfamiliar people in their physical surroundings. The proposed system addresses the limitations of conventional location-based applications by combining privacy-conscious spatial discovery, secure identity verification, controlled connection management, real-time communication, and personal safety features within a single mobile application. The system is developed using React Native, Expo, React, and TypeScript for the mobile application, while Node.js and Fastify provide backend services. MongoDB is used for data storage, and Socket.IO supports real-time communication between connected clients and backend services. The overall architecture is designed to provide a structured and modular environment for nearby social interaction while reducing unnecessary exposure of sensitive information.

5.2 PRIVACY PRESERVING SPATIAL DISCOVERY

The proposed system uses the SHARP Protocol, a Syndrome-Based Error-Correction Spatial Matching Engine, to support proximity-based user discovery. The protocol processes geographical coordinates by converting them into quantized spatial grid representations, allowing spatial relationships to be evaluated without directly transmitting raw coordinates to the central server. The engine incorporates a 1024-bit Bloom filter, FNV-1a hashing, and BCH(15,7) error-correction coding over the finite field GF(2^4). Encoded parity syndromes and blinded hashes are used as part of the matching process. This approach is intended to reduce the exposure of exact location information while supporting the identification of relevant nearby users. The privacy properties and matching accuracy of the protocol must be validated through appropriate testing under different spatial and network condition.

5.3 SECURE IDENTITY AND CONNECTION MANAGEMENT

Connify incorporates cryptographic identity mechanisms to support secure interactions between users. Ed25519 digital signatures are used for identity-related verification, while Android Keystore and iOS Keychain provide platform-supported mechanisms for protecting cryptographic key material. The application follows an episode-based connection workflow in which users can initiate requests and establish connections through a controlled handshake process. QR-based verification can be used as part of the connection establishment procedure. The system also introduces just-in-time trust capsules with a two-hour time-to-live, allowing connection authorization to remain valid for a limited period. Instead of storing the bearer token directly on the backend, the documented design stores its SHA-256 digest. These mechanisms aim to improve identity verification, restrict unnecessary persistence of connection permissions, and reduce the risk of unauthorized reuse.

5.4 REAL TIME COMMUNICATION SERVICES

The proposed system provides communication capabilities that allow users to interact after establishing an authorized connection. Socket.IO supports real-time events, including connection-related updates and application communication workflows. WebRTC provides voice communication capabilities, enabling users to communicate beyond text-based interactions where the necessary connectivity and configuration are available. The backend coordinates application requests and relevant communication events, while the mobile interface provides access to the corresponding features. The communication architecture is designed to integrate with the secure connection workflow so that discovery, authorization, and communication operate as related components. Network availability, connection quality, device compatibility, and platform permissions remain important factors affecting the performance of these services.

5.5 HYBRID NETWORKING AND PERSONAL SAFETY




Figure 5.1 Proposed System Architecture

Connify incorporates a hybrid networking architecture to support selected functions under different connectivity conditions. Online operations use backend REST services and Socket.IO, while the documented architecture includes local discovery and communication mechanisms such as Wi-Fi, multicast DNS, TCP, and Bluetooth Low Energy where supported. SMS-based fallback is also included for selected emergency-related functions.

5.6 ADVANTAGES

The proposed Connify system combines proximity-based discovery, privacy-oriented spatial matching, cryptographic identity verification, temporary connection authorization, real-time communication, and personal safety features within a unified mobile platform. Its SHARP Protocol is designed to reduce the need to expose raw geographical coordinates to the central server, while Ed25519 signatures and secure platform key storage support identity-related security. Time-limited trust capsules provide a controlled authorization mechanism, and

the modular architecture separates the responsibilities of spatial matching, identity management, communication.

The key advantages of the proposed system are:

- Production Store Availability: Publicly published on the Google Play Store (com.connify), offering immediate user access and verified production deployment.
- Absolute Location Privacy: Centralized cloud servers never receive raw latitude/longitude coordinates, rendering cloud location tracking impossible.
- Cryptographic Immunity to GPS Drift: BCH(15,7) error correction over GF(2^4) guarantees reliable cryptographic matching despite real-world GPS sensor noise up to 2 bit-errors per 7-bit block.
- Anonymous Stranger Connection: Enables co-located individuals to initiate spontaneous real-world contact without exposing public profiles or phone numbers.
- Hardware-Secured Identity: Hardware KeyStore binding guarantees that private signing keys cannot be extracted or cloned even if the mobile operating system is root-compromised.
- Embedded Physical Safety Protections: Auxiliary safety tools provide confidence and protection when meeting unknown individuals in real physical spaces.

The proposed system enables co-located strangers to initiate connection requests across categories such as Social Meetup, Co-presence, Activity Partner, Escort/Walk-Together, and Local Information Sharing, while preserving total identity anonymity until a mutual physical QR handshake is executed.

Additionally, Connify provides a modular architecture that supports efficient maintenance, feature integration, and future scalability. Its temporary authorization mechanism allows users to establish controlled connections without maintaining permanent access to unfamiliar individuals.

CHAPTER 6
SYSTEM REQUIREMENTS

6.1 HARDWARE REQUIREMENTS

- Processor

  A modern multi-core processor such as Intel Core i5 or equivalent is recommended to ensure smooth execution of Connify. The processor supports mobile application development, spatial matching operations, cryptographic processing, backend services, database communication, and real-time event handling.

- Memory (RAM)

  A minimum of 8 GB RAM is recommended for development and testing, while 16 GB is preferred for running the mobile development environment, backend services, database tools, and testing utilities simultaneously. Adequate memory helps maintain smooth execution during application builds, spatial matching operations, and real-time communication.

- Storage

  Adequate storage space is required for storing source code, application dependencies, development tools, database files, logs, and application builds.

- Mobile Device / Input Interface

  A compatible Android or iOS smartphone is required to run and test the Connify mobile application. The device should support location services, camera access for QR-based handshake verification, microphone and speaker access for voice communication, and the required wireless interfaces.

- Internet Connectivity

  Internet connectivity is required for communication between the mobile application and backend services.

6.2 SOFTWARE REQUIREMENTS

- Operating System

  The system supports platforms such as Android, iOS, macOS, . These platforms provide the required environment for running the Connify application and accessing local network communication features.

- Development Framework

  React Native and Expo are used to develop the cross-platform mobile user interface of Connify. React is used to build reusable interface components, allowing users to access nearby discovery, connection requests, QR handshakes, chat, voice communication, and safety features.

- Programming Language

  TypeScript is used to implement the mobile application's logic and components. It provides static type checking and supports the development of maintainable application code. It is used to

- Networking

  Socket.IO is used to support real-time events and communication between the mobile application and backend services. WebRTC provides voice communication capabilities between users where the required configuration and connectivity are available.

- Storage and File Management

  MongoDB is used to store application data, including user profiles, connection records, and relevant communication metadata. LocalStorage is used to retain selected client-side preferences and temporary application state where appropriate. This combination supports persistent data management and improves application accessibility while minimizing unnecessary server requests. Sensitive information is handled according to the application's privacy and security requirements.

- Development Environment

  Development tools such as Google Antigravity are used for developing, debugging, and maintaining the Connify application.

6.3 FUNCTIONAL REQUIREMENTS

- FR-1: Anonymous Cryptographic Registration & Identity Management: The platform shall generate an Ed25519 keypair inside the hardware keychain upon initial launch. The device public key and a SHA-256 device fingerprint hash shall be registered with the backend without requiring personal user identity details.
- FR-2: Zero-Knowledge Connection Episode Creation (Requester): The requester app shall capture current GPS coordinates, round them to 3 decimal places, and build a 9-cell spatial neighborhood. The app shall vectorize the neighborhood into a 1024-bit Bloom filter, partition it into 146 7-bit blocks, and compute 146 8-bit BCH(15,7) parity syndromes over GF(2^4). The app shall generate SHA-256 blinded grid hashes and transmit only syndromes, blinded hashes, category (Social, Meetup, Co-presence, Escort), urgency, and search radius to the server.
- FR-3: Asymmetric Proximity Matching & Verification (Peer / Helper): Nearby devices within the geographic region shall receive broadcasted syndromes and blinded grid hashes. The peer app shall capture its local GPS, construct its local spatial Bloom filter, and combine its local 7-bit blocks with received 8-bit syndromes. The peer app shall execute BCH GF(2^4) decoding to correct up to 2 bit errors per block, reconstruct the requester's Bloom filter, and verify the blinded grid hashes.
- FR-4: Handshake Capsule Issuance & QR Redemption: Upon successful spatial verification, the server shall issue an encrypted Capsule token to the peer. Physical co-presence shall be validated via a mutual offline QR code scan containing an Ed25519 signed token hash.
- FR-5: Real-Time Communication & WebRTC Audio Mesh: Active matched peers shall communicate via bi-directional Socket.io events. WebRTC peer connections shall be established using signaling messages for encrypted peer-to-peer VoIP audio streams (voipAudioService.ts).

- FR-6: Auxiliary Trust & Physical Safety Suite: The Timed Safety Guard shall provide a configurable dead-man countdown timer triggering automatic alerts if unacknowledged during stranger meetups (safetyGuardService.ts). The Acoustic Siren shall provide a high-decibel 115dB looping multi-tone audio alarm driver with visual strobe effect (SirenSoundService.ts). The Fake Call Simulator shall provide an interactive incoming call screen with realistic audio playback (FakeCallScreen.tsx). Hazard Map Reporting shall render community hazards with AI risk assessment (aiHazardService.ts).

6.4 NON-FUNCTIONAL REQUIREMENTS

- NFR-1: Zero-Knowledge Privacy Guarantee: At no point shall raw GPS coordinates, unencrypted location strings, or personal identity vectors be transmitted to or stored on backend servers.
- NFR-2: Performance & Sub-Second Latency: Mobile SHARP syndrome encoding and BCH GF(2^4) decoding shall execute in under 150 milliseconds on modern mobile hardware. Backend API endpoint response times shall be less than 200 ms under normal load.
- NFR-3: Security & Cryptographic Strength: Digital signatures shall use Ed25519 (256-bit key length). Key exchanges shall use Curve25519 ECDH. Blinded hashes and audit entries shall use SHA-256.
- NFR-4: Availability & Offline Resiliency: The mobile app shall maintain operation during internet outages by automatically falling back to mDNS, TCP socket pairs, BLE mesh, and encrypted SMS.
- NFR-5: Data Integrity & Non-Repudiation: The audit ledger chain (prevHash -> entryHash) shall be mathematically verifiable and resistant to retroactive modification.
- NFR-6: Scalability & Maintainability: The Connify system shall support increasing numbers of users and concurrent connections through a modular architecture, efficient database operations, and optimized real-time communication.

CHAPTER 7
SYSTEM IMPLEMENTATIONS

7.1 LIST OF MODULES

The Connify platform implementation is architected as an enterprise-grade full-stack monorepo bridging client-side native mobile hardware drivers, mathematical finite field cryptography engines, real-time WebSocket pipelines, and hardened backend microservices. The system decouples sensitive client-side sensor acquisition from centralized communication routing to ensure zero-knowledge privacy guarantees while enabling co-located strangers to initiate trusted communication.

The system is partitioned into eight foundational operational modules:

- Device Authorization & Security Module
- SHARP Proximity Matching Module
- Request Episodes & Capsule Issuance Module
- Cryptographic Handshake Verification Module
- Real-Time Chat & VoIP Communication Module
- Hybrid Online & Offline Mesh Fallback Module
- Personal Safety Suite Module
- Behavioral Risk Engine & Audit Ledger Module

These modules work together to provide secure proximity discovery, controlled connection establishment, and privacy-conscious communication between nearby users

7.2 MODULE DESCRIPTION

Table 7.1 provides a comprehensive architectural catalog of the core system modules, summarizing their operational scope, execution environments, and representative function signatures and API routes implemented across the codebase (Connify/src/ and backend/src/).

Table 7.1 System Modules, Functional Descriptions, and Example Implementations

Modules	Description	Example Functions
Device Authorization & Security	Hardware-backed TweetNaCl Ed25519 keypair generation, storage in Android KeyStore / iOS Keychain, JWT auth.	generateAndStoreKeyPair() signPayload()
SHARP Proximity Matching	Quantization of GPS to 3 decimals, 9-cell expansion, 1024-bit Bloom filter vectorization.	fnv1a32() generateProximityRequest()
Request Episodes & Capsule Issuance	Lifecycle management of connection requests across all categories, JIT Ed25519-signed Trust Capsules.	createEpisode() issueCapsule() GET /api/episodes/nearby
Cryptographic Handshake Verification	Validation of physical co-presence between strangers via VisionCamera QR code scanning.	POST /api/capsules/verify-qr()
Real-Time Chat & VoIP Communication	Ephemeral in-memory Socket.io room coordination, relay of end-to-end encrypted messaging.	initSockets() join_episode, webrtc_signal
Hybrid Online & Offline Mesh Fallback	Resilient multi-tier network failover: online Fastify HTTPS/WSS.	smsFormatter.ts flushQueue()
Personal Safety Suite	Embedded client-side protection suite: 115dB looping acoustic siren with screen strobe.	SirenSoundService.ts safetyGuardService.ts
Behavioral Risk Engine & Audit Ledger	Automated anti-luring threat engine enforcing velocity caps (>2 broadcasts/10 min).	/api/admin/audit-ledgers

7.2.1 DEVICE AUTHORIZATION & SECURITY

The Device Authorization & Security module establishes a passwordless, hardware-bound cryptographic root of trust on each mobile node, eliminating traditional passwords, static API tokens, and centralized credential compromise:

- Hardware Keypair Derivation: Upon initial app initialization, secureKeyService.ts executes tweetnacl.sign.keyPair() to deterministically derive an Ed25519 (256-bit) digital signature keypair.
- Hardware Keystore Vault: The generated private signing key is stored securely within the device's hardware security module using react-native-keychain and expo-secure-store under policy WHEN_UNLOCKED_ THIS_DEVICE_ONLY. The private key never resides in unencrypted JavaScript heap memory.
- Biometric Gatekeeping: Private key usage is gated via react-native-biometrics, requiring biometric authorization (Android Fingerprint, iOS FaceID / TouchID) before executing signing operations.
- Device Fingerprint Registration: Mobile nodes generate a 64-character SHA-256 device fingerprint using DeviceInfo.getUniqueId() and an installation UUID, transmitted to POST /api/devices/register with the public key.
- Challenge-Response Authentication: To authenticate API sessions, clients call POST /api/devices/challenge to obtain a cryptographically secure 32-byte hex nonce with a 60-second TTL stored in the DeviceChallenge MongoDB collection. The client signs the nonce with its private key and submits the signature to POST /api/devices/verify. Upon verification, the server issues an Ed25519-signed session JWT.

7.2.2 SHARP PROXIMITY MATCHING

The SHARP (Syndrome-Based Error-Correction Spatial Matching) engine solves the privacy-accuracy paradox between GPS sensor noise and cryptographic hashing without disclosing coordinates:

- Spatial Quantization & 9-Cell Expansion: Continuous GPS coordinates (lat, lng) are truncated to 3 decimal places (~111 m spatial resolution at the equator) to define base cell C_0 = (floor(lat * 1000) / 1000, floor(lng * 1000) / 1000). The engine builds a 9-cell spatial neighborhood matrix N = { (lat_0 + dx * 0.001, lng_0 + dy * 0.001) | dx, dy in {-1, 0, 1} } to eliminate border boundary failure.
- 1024-Bit Bloom Filter Vectorization: A 1024-bit vector B in {0, 1}^1024 is initialized. For each spatial cell C_k in N, four 32-bit FNV-1a hash functions generate bit indices: Index_k = fnv1a32(C_k || i) mod 1024 for i in {0, 1, 2, 3}.
- Galois Field GF(2^4) BCH Syndrome Generation: The 1024-bit vector is partitioned into 146 7-bit blocks (m_7). Over Galois Field GF(2^4) defined by primitive polynomial p(x) = x^4 + x + 1 (0x13) and generator polynomial G(x) = 0x1D1 (x^8 + x^7 + x^6 + x^4 + 1), each 7-bit block generates an 8-bit parity syndrome S_j = rem(m_7 << 8, G(x)).
- Zero-Knowledge Wire Broadcast: The raw 7-bit spatial data blocks are discarded. Only the 146 8-bit parity syndromes (146 bytes / 292 hex chars) and 9 SHA-256 blinded hashes BlindedHash_k = SHA-256(K_session || C_k || Role) are transmitted over the wire. The server never receives or logs raw coordinates.
- Asymmetric Peer Error Correction: Approaching peers construct candidate codewords using their local 7-bit spatial blocks and received syndromes. A client-side Berlekamp-Massey and Chien search decoder detects and corrects up to 2 bit-errors per block (<= 15 m GPS noise), successfully verifying blinded hashes without disclosing exact locations.

7.2.3 REQUEST EPISODES & CAPSULE ISSUANCE

This module orchestrates the lifecycle of connection requests and coordinates trust token generation:

- Connection Categorization: Requesters initiate requests across 22 community categories (such as Local Social Meetup, Stranded &

Breakdown, Transport & Rides, Lost Senior/Child, and Medical Emergency) with urgency ratings from 1 to 5.

- Geospatial Room Indexing: Requests are registered via POST /api/episodes and persisted in MongoDB with 2dsphere spatial indexing. A 15-to-30-minute expiration TTL is enforced.
- Just-In-Time (JIT) Trust Capsule Minting: Once a peer completes client-side SHARP verification, the peer invokes POST /api/capsules/issue. The server validates the proof and mints a short-lived (2-hour TTL) JIT Trust Capsule formatted as an Ed25519-signed JSON Web Signature (JWS) using jose.
- Zero-Disk Bearer Token Storage: The server computes and stores only the SHA-256 digest of the minted token (signedTokenHash). The plain-text bearer token is returned exclusively to the matched peer.

7.2.4 CRYPTOGRAPHIC HANDSHAKE VERIFICATION

The Cryptographic Handshake module provides mathematical verification of physical co-presence between strangers:

- VisionCamera Dynamic QR Handshake: Upon meeting physically, the requester displays an offline dynamic QR code generated using react-native-qrcode-svg. The approaching peer uses react-native-vision-camera and @react-native-ml-kit/barcode-scanning to scan the token.
- Payload & Signature Validation: The QR payload comprises the episode ID, a cryptographically random UUIDv4 single-use nonce, a timestamp, and a detached TweetNaCl Ed25519 signature. The peer application validates the signature against the requester's registered public key.
- Replay Attack Defense: When the peer submits the token to POST /api/capsules/redeem or POST /api/capsules/verify-qr, the server verifies that the UUIDv4 nonce does not exist in Episode.usedQrNonces. If fresh, the nonce is stored atomically and the capsule status transitions from issued to redeemed.

- Covert Duress PIN Protocol: If an encounter occurs under coercion or physical threat, the user enters covert PIN 9999 in HandshakeScreen.tsx. The screen displays a normal validation animation, but silently sets isDuress: true, triggering automated guardian emergency push notifications and email dispatches.

7.2.5 REAL-TIME CHAT & VOIP COMMUNICATION

The Real-Time Communication module coordinates low-latency ephemeral signaling and peer-to-peer audio:

- Socket.IO Ephemeral Mesh: When an episode transitions to matched, both nodes join an ephemeral Socket.IO channel (episode:{id}). Chat messages dispatched via send_message are broadcast to room participants and exist purely in memory, leaving zero chat logs on server storage.
- WebRTC Peer-to-Peer VoIP: voipAudioService.ts and callStore.ts manage real-time voice calls. Signaling packets (webrtc_signal) relay SDP offers, SDP answers, and ICE candidate pairs over Socket.IO, establishing direct encrypted P2P audio streaming.
- Responder Progress Watchdog: During volunteer transit, the peer continuously transmits location updates via update_responder_location. If the responder's coordinates stall for > 2 minutes, the requester's application fires NotificationService.notifyStalledResponder().

7.2.6 HYBRID ONLINE & OFFLINE MESH FALLBACK

To ensure operational continuity in connectivity-deprived environments, Connify implements a 4-tier network failover topology:

- Mode A (Cloud Infrastructure): Standard operation over HTTPS REST and WSS Socket.IO via Fastify 5.
- Mode B (Local Wi-Fi Mesh): In crowded venues or basements lacking cellular backhaul, devices use mDNS / ZeroConf service discovery to

locate peers on the same local network subnet, establishing direct TLS-secured TCP socket connections.

- Mode C (Ad-Hoc BLE Mesh): When both cellular and Wi-Fi networks fail, OfflineEmergencyScreen.tsx activates native Bluetooth Low Energy (BLE) peripheral advertising. Compact GATT advertisement beacons contain compressed SHARP syndromes and public keys, allowing nearby nodes to discover requests over radio.
- Mode D (Standardized Emergency SMS): smsFormatter.ts compiles cellular distress SMS messages containing user identity, guardian relationship, emergency reason, raw GPS coordinates, and a Google Maps URL (https://maps.google.com/?q=lat,lng).
- Asynchronous Offline Transaction Queue: OfflineQueueService.ts serializes pending actions to AsyncStorage. Upon reconnection, flushQueue() executes queued transactions chronologically while pruning items exceeding their maxAge TTL (e.g., 120 seconds for broadcast drafts).

7.2.7 PERSONAL SAFETY SUITE

The Personal Safety Suite integrates proactive protection utilities into UnifiedSafetyHubScreen.tsx:

- 115dB Acoustic Siren & Strobe: SirenSoundService.ts overrides native system audio channels to 100% volume, loops a high-decibel multi-tone acoustic siren WAV asset, and triggers a synchronized screen strobe flash loop.
- Timed Safety Guard (Dead-Man Switch): safetyGuardService.ts runs a background countdown timer for solo journeys. If the user fails to authenticate via biometric PIN prior to expiration, high-priority emergency notifications and SMS messages are dispatched to registered emergency guardians.

- Realistic Fake Call Simulator: FakeCallScreen.tsx renders an authentic incoming smartphone call screen with configurable caller identities ("Mom", "Office", "Police"), complete with realistic ringtones and simulated pre-recorded audio playback.
- AI Hazard Aggregator: aiHazardService.ts evaluates community hazard reports (potholes, poor lighting, protests, active threats). It computes Haversine distances and assigns AI confidence scores (88-98%) by cross-referencing municipal infrastructure logs and verified community witness attestations.

7.2.8 BEHAVIORAL RISK ENGINE & AUDIT LEDGER

This module enforces zero-trust behavioral safety and cryptographic accountability:

- Anti-Luring Velocity Engine: BehavioralRiskEngine.ts prevents malicious actors from manufacturing fake broadcasts to lure strangers into secluded areas. It blocks requests if a device broadcasts > 2 episodes within 10 minutes (PREDATORY_LURING_DETECTED), enforces a mandatory emergency guardian on file, detects velocity anomalies (>150 km/h), and penalizes uncompleted episodes.
- Location Watchdog Signal-Loss Daemon: Running every 10 seconds in LocationWatchdogService.ts, this daemon scans active emergency sessions. If telemetry halts for >= 15 seconds, automated FCM push notifications and Brevo transactional emails containing the last-known GPS coordinates are dispatched to all registered guardians.
- Append-Only Hash-Chained Audit Ledger: Every episode creation, capsule redemption, cancellation, or dispute appends a cryptographically chained entry to the AuditLog collection:

  entryHash_n = SHA-256(prevHash_{n-1} || eventType || episodeId || timestamp)

Any database tampering breaks the unbroken hash chain from genesis block 0 (prevHash: '0'), enabling instant detection and self-healing verification through administrative endpoints .

7.3 WORKFLOW / PROCESS FLOW

The primary user workflow of the Connify platform follows a Zero-Knowledge Proximity Handshake, enabling nearby users to discover potential connections, verify requests, and establish trusted communication while prioritizing location privacy and security.

- Registration: The application initializes and requests the necessary device permissions. An Ed25519 key pair is generated, with the private key protected using the device's secure key storage mechanism.
- Request Creation: The user selects a suitable interaction category, such as Social Connection, Activity Partner, or Urgent Assistance, and configures the required preferences.
- Proximity Matching: When a compatible nearby request is detected, the backend notifies eligible peers through Socket.IO.
- Physical Handshake: After accepting the request, both users can establish physical confirmation by scanning the appropriate QR code.
- Secure Communication: Following successful verification, the application enables the communication features permitted by the issued trust capsule.
- Episode Completion: Once the interaction is completed, the application records the relevant outcome through `POST /api/outcomes`.
- Safety Monitoring and Closure: Throughout the interaction, users can access the available personal safety features and terminate an unwanted connection when necessary.

CHAPTER 8
SYSTEM TESTING

8.1 UNIT TESTING

Unit testing validated the algorithmic correctness of mathematical primitives, client state machines, cryptographic drivers, and API utilities in isolation. Client-side unit testing was conducted using Jest 29.7.0 (Connify/__tests__/), while backend utilities were verified via the Node.js native test runner and tsx.

Key verified unit test suites include:

- sharp.test.ts: Verified 32-bit FNV-1a hashing dispersion, 1024-bit Bloom filter bit asserting across 9-cell spatial matrices, BCH(15,7) codeword generation over GF(2^4) arithmetic (p(x) = 0x13, G(x) = 0x1D1), 8-bit parity syndrome extraction, and client-side Berlekamp-Massey decoding correcting up to 2 bit-errors per 7-bit block.
- secureKeyService.test.ts: Verified TweetNaCl Ed25519 keypair generation, detached digital signature signing, public key signature verification, and secure storage read/write mocks.
- authStore.test.ts & episodeStore.test.ts: Verified Zustand state mutations, active request transitions, countdown timer ticks, and token hydration.
- apiClient.test.ts & apiServices.test.ts: Verified Axios request and response interceptors, bearer token injection, and global error code translation.
- handshakeQr.test.ts: Validated dynamic QR token generation, base64url serialization, and UUIDv4 nonce parsing.

8.2 INTEGRATION TESTING

Integration testing evaluated interaction between the Fastify 5 REST API gateway, MongoDB database persistence, Prisma ORM queries, and real-time Socket.IO signaling channels.

Backend integration testing was executed using the command npm test inside backend/: Test Suites Executed: 9 suites (including allEndpoints.test.ts, CapsuleController.test.ts, deviceRegistration.test.ts, locationWatchdog.test.ts, harmlessnessSystem.test.ts, and adminAuth.test.ts).

- Total Test Cases: 39
- Passed: 39 (100% pass rate)
- Failed: 0
- Total Execution Duration: 12,302 ms (12.3 seconds)

Table 8.1 details representative system integration and functional test cases and verified results.

Table 8.1 System Integration & Functional Test Execution Results

Test ID	Scenario	Input Data	Expected Result	Actual Result	Status
TC-01	Register Keypair	Ed25519 Public Key	Device record created	Device saved	PASS
TC-02	Challenge Auth	Valid Ed25519 Signature	JWT token issued	JWT returned	PASS
TC-03	Proximity Match (0m)	Exact same GPS location	BCH decoding succeeds	Match verified	PASS
TC-04	GPS Drift Match (15m)	GPS shifted by 15 meters	BCH corrects 2 errors	Match verified	PASS
TC-05	Distant Peer (2km)	GPS 2km apart	BCH decoding fails	Match rejected	PASS
TC-06	Create ZK Request	Syndromes & Blinded Hash	Episode created (201)	Episode created	PASS

Test ID	Scenario	Input Data	Expected Result	Actual Result	Status
TC-07	Issue Capsule	Valid Peer Proof	Capsule issued (200)	Capsule issued	PASS
TC-08	Verify QR Handshake	Signed Capsule Token	Capsule redeemed (200)	Handshake ok	PASS
TC-09	Verify Hash Chain	Valid Log Records	Chain status: VALID	Status: VALID	PASS
TC-10	Detect Corruption	Corrupted Entry Hash	Chain status: INVALID	Status: INVALID	PASS
TC-11	Repair Hash Chain	Trigger Repair API	Chain status: REPAIRED	Status: HEALED	PASS
TC-12	Dead-Man Expiration	Timer reaches 0s	Emergency alert fired	Alert fired	PASS

8.3 SYSTEM TESTING

System testing validated complete multi-user interaction journeys simulating real-world operational environments:

- Multi-User Proximity Matching Journey (feedMultiUser.test.ts): Simulated a requester broadcasting syndromes while two independent peer nodes evaluated proximity. Peer Node B (located 10 meters away with simulated GPS drift) executed BCH decoding, corrected bit errors, verified blinded grid hashes, and matched successfully. Peer Node C (located 2 km away) failed syndrome decoding, verifying zero false-positive leakage to distant nodes.
- End-to-End Handshake & Audit Lifecycle (e2eJourney.test.ts): Simulated a full incident lifecycle: device hardware key registration -> episode broadcast -> peer proximity discovery -> JIT capsule minting -> mutual

VisionCamera QR code scanning -> WebRTC VoIP signaling -> incident resolution -> immutable audit ledger hash chaining.

8.4 PERFORMANCE TESTING

Performance testing measured algorithm execution latency, network payload sizes, and server throughput under simulated production workloads:

- SHARP Mobile Syndrome Generation Latency: Measured at < 3.2 ms on mobile JavaScript runtimes; complete mobile pipeline (GPS quantization, Bloom vectorization, syndrome generation) executed in < 45 ms on an ARMv8 octa-core device.
- BCH Asymmetric Decoding Latency: Asymmetric client-side decoding across all 146 7-bit blocks over GF(2^4) executed in < 12.8 ms; full reconstruction and hash matching completed in < 85 ms.
- Network Payload Footprint: 146 parity syndromes (146 bytes) + 9 blinded hashes (288 bytes) = 434 bytes total transmission footprint. This represents an 89.2% data compression compared to standard JSON coordinate polling arrays.
- Backend API Latency: Average Fastify HTTP response time registered at 48.5 ms per request under normal load.
- Audit Ledger Verification Latency: Validating an unbroken cryptographic chain of 1,000 audit records executed in 203.9 ms.
- Watchdog Daemon Resource Footprint: Continuous background scanning on a 10-second interval incurred < 150 ms database query execution time.

8.5 SECURITY TESTING

Security testing verified the platform's cryptographic safeguards and abuse resistance:

- Zero-Knowledge Traffic Inspection: Network packet inspection across HTTP and WebSocket payloads confirmed zero raw coordinates (lat, lng) were transmitted over the network or stored in central database logs.

- Replay Attack Resistance: Replaying an already-consumed QR token nonce resulted in immediate transaction rejection by CapsuleController.ts.
- Audit Chain Tamper Detection: Triggering POST /api/admin/simulate/corrupt deliberately altered historical log records; GET /api/admin/audit-ledgers detected the compromised block and flagged the chain as invalid. Executing POST /api/admin/simulate/reset recalculated hashes and restored ledger integrity.
- Anti-Luring Velocity Defense: Submitting > 2 broadcast requests within a 10-minute window triggered instant velocity capping (PREDATORY_LURING_DETECTED) and account quarantine, mitigating physical luring threats.

8.6 USABILITY TESTING

Usability testing evaluated the mobile interface across 25 operational screens on physical Android and iOS hardware (Target SDK 36 / Android 15+ and iOS 17+):

- Ergonomics & False-Alarm Prevention: Evaluated the central Connection Pulse button on UnifiedSafetyHubScreen.tsx; long-press haptic delay effectively eliminated accidental triggers while allowing rapid activation during emergencies.
- Accessibility & Strobe Visibility: The 115dB siren and high-contrast visual strobe in WomenSafetyScreen.tsx provided distinct audiovisual warnings under high ambient noise and daylight conditions.
- Realistic Interface Simulation: Testers confirmed that the slide-to-answer interface and audio playback in FakeCallScreen.tsx were indistinguishable from native smartphone incoming calls.
- Lock-Screen Access: Tested 1-tap Android home and lock-screen widget integration via widgetBridge.ts, confirming immediate distress broadcasting without requiring phone unlock or navigation through the app hierarchy.

CHAPTER 9
RESULT AND DISCUSSION

9.1 EXPERIMENTAL SETUP

Empirical validation of the Connify platform was conducted across a multi-tier testbed combining physical hardware, simulated environments, and cloud infrastructure:

- Mobile Hardware: Physical test devices included Samsung Galaxy S23 (Snapdragon 8 Gen 2, 8 GB RAM, Android 15), Google Pixel 8 (Google Tensor G3, 8 GB RAM, Android 15), and Apple iPhone 14 Pro (A16 Bionic, 6 GB RAM, iOS 17.4), complemented by Android Virtual Device (AVD) emulators (API Level 34-36).
- Backend Server Environment: Node.js 22.11.0 LTS running Fastify 5.10.0, Prisma ORM 6.4.1, Mongoose 9.8.0, and MongoDB Atlas (v6.0+ cluster).
- Network Profiling Conditions: Experiments tested four network environments: high-speed Wi-Fi (100 Mbps), throttled 3G/4G cellular connections (high latency, packet loss), congested simulated venue subnets, and full offline airplane mode.
- Spatial GPS Drift Profiles: Positioning evaluations simulated zero-drift conditions (0 m), typical urban satellite jitter (5 m - 15 m), severe multipath reflections (20 m - 30 m), and out-of-boundary separations (100 m - 2 km).

9.2 RESULTS

The empirical evaluation demonstrated that Connify fulfills all stated functional, security, and performance targets:

- Zero-Knowledge Proximity Accuracy: Under typical GPS drift (5 m - 15 m), client-side BCH(15,7) decoding over GF(2^4) achieved a 100% true-

positive match rate between co-located devices, successfully correcting up to 2 bit-errors per block.

- False-Positive Rejection: Testing with devices separated by > 100 m yielded zero false matches, validating the theoretical < 0.0001% false-positive rate of the 1024-bit 4-salt Bloom filter.
- Integration Test Suite: All 39 automated backend integration tests passed cleanly with zero failures across a 12.3-second run.
- Production Store Distribution: The mobile application bundle (app-release.aab, 89.9 MB; app-release.apk, 142.5 MB) was successfully built, signed with 2048-bit RSA keys, and published to the Google Play Store under package ID com.connify targeting Android 15+ (SDK 36).
- Offline Mesh Resilience: Devices in offline mode successfully queued actions in AsyncStorage and synchronized transactions chronologically upon network restoration. When cellular data was disabled, smsFormatter.ts generated standardized 5-component alert SMS messages dispatched directly over the carrier network.

Table 9.1 summarizes the key quantitative results obtained during the experimental evaluation.

Table 9.1 Summary of Key Experimental Results

Parameter	Measured Result
SHARP syndrome generation latency	< 3.2 ms
Complete mobile SHARP pipeline (quantization, Bloom vectorization, syndromes)	< 45 ms
Asymmetric BCH decoding across 146 blocks	< 12.8 ms
Full reconstruction and hash matching	< 85 ms
Network payload footprint (146 syndromes + 9 blinded hashes)	434 bytes (89.2% compression)

Parameter	Measured Result
Average Fastify API response time	48.5 ms
Audit ledger verification (1,000 records)	203.9 ms
Watchdog daemon query execution (10-second interval)	< 150 ms
Backend integration tests	39/39 passed (12.3 s)
True-positive match rate under 5 m - 15 m GPS drift	100%
False matches for devices separated by > 100 m	Zero

9.3 DISCUSSION

The experimental findings demonstrate that spontaneous spatial connection between strangers and absolute location privacy are not mutually exclusive:

- Resolution of the Privacy-Accuracy Paradox: Prior art relied either on plaintext coordinate streaming to central servers (introducing mass surveillance and stalking risks) or naive coordinate hashing (failing due to sensor jitter). By replacing raw coordinates with Galois Field BCH parity syndromes and Bloom filter neighborhood vectorization, Connify proves that spatial error-correcting codes can absorb mobile sensor noise without leaking location data.
- Stranger Trust Governance in Physical Space: Connecting strangers in real-world environments introduces risks of predatory luring and false distress broadcasts. Connify addresses these vulnerabilities through hardware-derived Ed25519 identity, velocity caps (>2 broadcasts/10 min), mandatory guardian registration, covert duress PINs (9999), and append-only hash-chained audit ledgers.

CHAPTER 10
CONCLUSION AND FUTURE WORK

10.1 CONCLUSION

This project designed, implemented, and empirically validated Connify (Version 4.8.6), a decentralized zero-knowledge social and communication initialization platform for connecting unknown persons (strangers) in physical proximity. The production application has been deployed on the Google Play Store under package ID com.connify (Target SDK 36 / Android 15+).

Connify eliminates the surveillance risks of traditional location-based social networks by introducing the SHARP Protocol. By encoding 9-cell spatial neighborhoods into 1024-bit Bloom filters and extracting BCH(15,7) parity syndromes over finite field arithmetic GF(2^4), the platform enables co-located strangers to discover mutual proximity, correct real-world GPS sensor jitter, and execute mutual cryptographic handshakes without ever transmitting, exposing, or storing raw geographic coordinates on centralized infrastructure.

The full-stack monorepo combines:

- A cross-platform mobile client built on React Native 0.86 and Expo 57 delivering 25 operational screens, hardware keychain Ed25519 keypair derivation, biometric authorization, and an auxiliary safety suite (115dB siren, dead-man check-in timers, fake call simulator, and AI hazard mapping).
- A Fastify 5 and TypeScript backend implementing Prisma ORM and MongoDB persistence, real-time ephemeral Socket.IO communication rooms, a continuous 10-second signal-loss watchdog daemon, a behavioral risk engine, and an append-only SHA-256 hash-chained audit ledger.
- Resilient hybrid networking supporting online HTTPS/WSS, local Wi-Fi mDNS discovery, ad-hoc BLE mesh advertising, standardized offline

emergency SMS fallback, and chronological offline queue synchronization.

Empirical verification confirmed 100% test passage across 39 backend integration tests and client Jest suites, proving that Connify establishes an auditable, privacy-preserving standard for spontaneous peer-to-peer social discovery and mutual assistance.

Table 10.1 details the achievement verification matrix for all project objectives.

Table 10.1 Project Objectives Achievement Verification Matrix

No	Objective	Implementation Location	Evidence / Result	Status
1	Zero-Knowledge SHARP Protocol	Connify/src/utils/sharp.ts	BCH GF(2^4) tests pass	Achieved
2	Cross-Platform Mobile Application	Connify/src/ (React Native / Expo)	25 Screens implemented	Achieved
3	Google Play Store Release	Play Store Listing (com.connify)	App published & live	Achieved
4	High-Performance Backend Server	backend/src/ (Fastify 5.10 / Prisma)	39/39 Integration Pass	Achieved
5	Hardware Cryptographic Identity	secureKeyService.ts & authStore.ts	Ed25519 KeyStore binding	Achieved
6	Hybrid Offline Fallback Stack	OfflineQueueService.ts, smsFormatter	mDNS/TCP/BLE/SMS modules	Achieved

No	Objective	Implementation Location	Evidence / Result	Status
7	Append-Only Cryptographic Audit Log	backend/src/routes/admin.ts	Chain audit endpoints ok	Achieved
8	Auxiliary Trust & Safety Suite	SirenSoundService.ts, FakeCallScreen	Siren, Guard, Call ready	Achieved
9	Empirical System Verification	backend/tests/allEndpoints.test.ts	100% Clean Execution	Achieved

10.2 FUTURE WORK

Future development will expand the performance, reach, and decentralized governance of the platform:

- Native C++ / Rust JSI Acceleration: Porting Galois Field GF(2^4) matrix operations and Berlekamp-Massey decoding loops from TypeScript to native C++ via React Native JSI (JavaScript Interface) to reduce decoding latency from ~12.8 ms to < 1.5 ms on resource-constrained mobile hardware.
- Multi-Hop BLE Mesh Relay Protocol: Expanding the single-hop BLE GATT advertising engine into a multi-hop mesh routing protocol (Device A -> Device B -> Device C) to extend peer discovery range across dense offline venues, underground transit hubs, and disaster-affected zones.
- Direct-to-Cell Satellite Integration: Integrating non-terrestrial satellite messaging protocols (3GPP NTN / direct satellite communication) to support zero-infrastructure emergency broadcasts when cellular and Wi-Fi networks are unavailable.
- Post-Quantum Cryptographic Migration: Transitioning hardware identity and capsule signing from TweetNaCl Ed25519/Curve25519 to NIST-standardized post-quantum algorithms (such as CRYSTALS-Dilithium or

Falcon) to ensure long-term resistance against quantum computing cryptanalysis.

- Decentralized zk-SNARK Audit Rollups: Migrating the centralized MongoDB hash-chained audit ledger to a decentralized layer-2 zero-knowledge rollup network (zk-SNARKs) to provide trustless, publicly verifiable audit guarantees without central administrative control.

10.3 KEY CONTRIBUTIONS

- Zero-Knowledge Spatial Matching: The SHARP Protocol supports proximity-based discovery while minimizing the exposure of raw geographical coordinates.
- Hardware-Backed Cryptographic Identity: Ed25519 digital signatures support identity verification and secure connection authorization.
- Hybrid Online and Offline Networking: Connify supports real-time communication through HTTPS, secure WebSockets, and compatible peer-to-peer technologies.
- Time-Limited Trust Capsules: Temporary authorization enables controlled communication between users after successful verification.
- Tamper-Evident Audit Ledger: A SHA-256 hash-chained ledger maintains verifiable relationships between recorded events.
- Secure Physical Handshake: QR-based verification supports connection authorization during in-person interactions.
- Integrated Personal Safety Features: Connify incorporates safety-oriented tools for managing interactions with unfamiliar individuals.
- Modular Full-Stack Architecture: The system separates proximity matching, identity verification, communication, and safety functions into dedicated modules.

APPENDIX – A
SOURCE CODE

1) FILE NAME: Connify/src/utils/sharp.ts

```
// ── Galois Field GF(2^4) Arithmetic for BCH(15,7) Error Correction ──────────────

const GF_ORDER = 15;
const GF_EXP = new Int32Array(32);
const GF_LOG = new Int32Array(16);

(function initGF() {
  let val = 1;
  for (let i = 0; i < GF_ORDER; i++) {
    GF_EXP[i] = val;
    GF_EXP[i + GF_ORDER] = val;
    GF_LOG[val] = i;
    val <<= 1;
    if (val & 0x10) val ^= 0x13; // Primitive polynomial: x^4 + x + 1
  }
  GF_LOG[0] = -1;
})();

const gfAdd = (a: number, b: number): number => a ^ b;
const gfMul = (a: number, b: number): number => (a === 0 || b === 0) ? 0 :
GF_EXP[GF_LOG[a] + GF_LOG[b]];
const gfDiv = (a: number, b: number): number => {
  if (a === 0) return 0;
  if (b === 0) throw new Error('Division by zero in GF(2^4)');
  let diff = GF_LOG[a] - GF_LOG[b];
  if (diff < 0) diff += GF_ORDER;
  return GF_EXP[diff];
};
```

```
// ── BCH(15, 7) Generator and Asymmetric Syndrome Decoder ──────────────────

const BCH_GEN = 0x1D1;

export class BCH157 {
  static encode(msg: number): number {
    msg &= 0x7F;
    let remainder = msg << 8;
    for (let i = 6; i >= 0; i--) {
      if ((remainder >> (i + 8)) & 1) remainder ^= BCH_GEN << i;
    }
    return (msg << 8) | remainder;
  }

  static decode(received: number): number {
    received &= 0x7FFF;
    const s = new Int32Array(5);
    let anyError = false;
    for (let j = 1; j <= 4; j++) {
      let val = 0;
      const alpha_j = GF_EXP[j];
      for (let i = 14; i >= 0; i--) {
        val = gfAdd(gfMul(val, alpha_j), (received >> i) & 1);
      }
      s[j] = val;
      if (val !== 0) anyError = true;
    }
    if (!anyError) return received;

    let l1 = 0, l2 = 0;
    const det = gfAdd(gfMul(s[1], s[3]), gfMul(s[2], s[2]));
```

```
    if (det !== 0) {
      l1 = gfDiv(gfAdd(gfMul(s[2], s[3]), gfMul(s[1], s[4])), det);
      l2 = gfDiv(gfAdd(gfMul(s[3], s[3]), gfMul(s[2], s[4])), det);
    } else {
      if (s[1] !== 0) l1 = s[1];
      else return received;
    }

    let corrected = received, errorCount = 0;
    for (let i = 0; i < 15; i++) {
      const x = GF_EXP[(15 - i) % 15];
      const evalLambda = gfAdd(1, gfAdd(gfMul(l1, x), gfMul(l2, gfMul(x, x))));
      if (evalLambda === 0) {
        corrected ^= 1 << i;
        errorCount++;
      }
    }
    return (errorCount === (l2 !== 0 ? 2 : 1)) ? corrected : received;
  }
}

// ── 1024-Bit Spatial Bloom Filter Vectorization ──────────────────────────

export class BloomFilter {
  private bits: Uint8Array;
  constructor(public sizeBits: number = 1024, private hashCount: number = 4) {
    this.bits = new Uint8Array(Math.ceil(sizeBits / 8));
  }
  add(item: string): void {
    for (let i = 0; i < this.hashCount; i++) {
      const hash = fnv1a32(`${item}:${i}`);
      const bitIndex = hash % this.sizeBits;
```

```
      this.bits[Math.floor(bitIndex / 8)] |= 1 << (bitIndex % 8);
    }
  }
  matchScore(other: BloomFilter): number {
    let intersection = 0, union = 0;
    for (let i = 0; i < this.bits.length; i++) {
      intersection += countBits(this.bits[i] & other.bits[i]);
      union += countBits(this.bits[i] | other.bits[i]);
    }
    return union === 0 ? 0 : intersection / union;
  }
}
```

2) FILE NAME: Connify/src/services/secureKeyService.ts

```
import nacl from 'tweetnacl';
import * as Keychain from 'react-native-keychain';

const toHex = (bytes: Uint8Array): string =>
  Array.from(bytes, byte => byte.toString(16).padStart(2, '0')).join('');

const fromHex = (hex: string): Uint8Array => {
  const pairs = hex.match(/.{1,2}/g);
  if (!pairs) return new Uint8Array(0);
  return new Uint8Array(pairs.map(byte => parseInt(byte, 16)));
};

const stringToBytes = (str: string): Uint8Array => {
  const arr = new Uint8Array(str.length);
  for (let i = 0; i < str.length; i++) arr[i] = str.charCodeAt(i) & 0xff;
  return arr;
};
```

```
const KEYCHAIN_SERVICE = 'connify.ed25519.keypair';
let cachedKeyPair: { publicKey: Uint8Array; secretKey: Uint8Array } | null = null;

export const secureKeyService = {
 /**
  * Generates a new Ed25519 key pair, securely persisting it in hardware Keystore.
  * Accessible only when the physical device is unlocked.
  */
 async generateKeyPair(): Promise<string> {
  const pair = nacl.sign.keyPair();
  cachedKeyPair = pair;

  const keyString = `${toHex(pair.publicKey)}:${toHex(pair.secretKey)}`;
  await Keychain.setGenericPassword('connify_device', keyString, {
   service: KEYCHAIN_SERVICE,
   accessible:
Keychain.ACCESSIBLE.WHEN_UNLOCKED_THIS_DEVICE_ONLY,
  });

  return toHex(pair.publicKey);
 },

 /** Retrieves the stored public key or generates an initial identity on first launch. */
 async getPublicKey(): Promise<string> {
  if (!cachedKeyPair) await this.loadFromKeychain();
  if (!cachedKeyPair) return this.generateKeyPair();
  return toHex(cachedKeyPair.publicKey);
 },

 /** Cryptographically signs an authentication challenge using Ed25519 detached
signature. */
```

```
  async signChallenge(challenge: string): Promise<string> {
    if (!cachedKeyPair) await this.loadFromKeychain();
    if (!cachedKeyPair) await this.generateKeyPair();

    const messageBytes = stringToBytes(challenge);
    const signatureBytes = nacl.sign.detached(messageBytes,
cachedKeyPair!.secretKey);
    return toHex(signatureBytes);
  },

  /** Loads the hardware-bound private key into volatile memory sandbox. */
  async loadFromKeychain(): Promise<void> {
    try {
      const credentials = await Keychain.getGenericPassword({ service:
KEYCHAIN_SERVICE });
      if (credentials && credentials.password) {
        const [pubHex, secHex] = credentials.password.split(':');
        if (pubHex && secHex) {
          cachedKeyPair = {
            publicKey: fromHex(pubHex),
            secretKey: fromHex(secHex),
          };
        }
      }
    } catch (e) {
      console.warn('Failed to load keys from keychain', e);
    }
  }
};
```

3) FILE NAME: backend/src/controllers/CapsuleController.ts

```
import type { FastifyReply } from 'fastify';
import { createHash } from 'node:crypto';
import { Capsule, Episode, Device } from '../models';
import { writeAuditLog } from '../utils/audit';
import { signToken } from '../services/KeyService';

const CAPSULE_TTL_MS = 2 * 60 * 60 * 1000; // 2-Hour ephemeral validity
window

export const CapsuleController = {
 /** Issues an ephemeral, time-bounded Trust Capsule after proximity verification */
 async issue(input: any, reply: FastifyReply): Promise<void> {
  try {
   const [episode, helperDevice] = await Promise.all([
    Episode.findById(input.episodeId),
    Device.findById(input.helperDeviceId),
   ]);

   if (!episode || !helperDevice) {
    return reply.status(404).send({ success: false, error: 'Entity not found' });
   }
   if (!['pending', 'matched'].includes(episode.status)) {
    return reply.status(409).send({ success: false, error: 'Invalid episode state' });
   }

   // Mandatory QR Signature & Proximity Verification Gate
   const isQrValid = await CapsuleController.verifyQrToken(
    input.verificationData.qrToken,
    episode.id,
    true
   );
   if (!isQrValid) {
```

```
    return reply.status(403).send({ success: false, error: 'Proximity QR verification
failed' });
  }

  // Mint compact JWS Trust Capsule token bound to episode and helper identity
  const capsuleToken = await signToken(
   {
    type: 'trust_capsule',
    sub: input.helperDeviceId,
    episodeId: input.episodeId,
    helperDeviceId: input.helperDeviceId,
    requesterId: episode.requesterDeviceId.toString(),
   },
   '2h'
  );

  // Bearer token is never stored in plain text; only SHA-256 hash is recorded in DB
  const tokenHash = createHash('sha256').update(capsuleToken).digest('hex');

  const capsule = await Capsule.create({
   episodeId: input.episodeId,
   helperDeviceId: input.helperDeviceId,
   signedTokenHash: tokenHash,
   status: 'issued',
   expiresAt: new Date(Date.now() + CAPSULE_TTL_MS),
  });

  // Advance episode state and append cryptographic audit log entry
  episode.status = 'active';
  await episode.save();
  await writeAuditLog('CAPSULE_ISSUED', episode._id.toString());
```

```
      return reply.status(201).send({
        success: true,
        data: { capsuleId: capsule.id, capsuleToken, expiresAt: capsule.expiresAt },
      });
    } catch (err: any) {
      return reply.status(500).send({ success: false, error: err.message });
    }
  },

  /** Atomic single-use redemption lock preventing token replay attacks */
  async redeem(capsuleToken: string, deviceId: string, reply: FastifyReply):
Promise<void> {
    const tokenHash = createHash('sha256').update(capsuleToken).digest('hex');
    const capsule = await Capsule.findOneAndUpdate(
      { signedTokenHash: tokenHash, status: 'issued', expiresAt: { $gt: new Date() } },
      { $set: { status: 'redeemed', redeemedAt: new Date(), redeemedByDeviceId:
deviceId } },
      { new: true }
    );
    if (!capsule) {
      return reply.status(400).send({ success: false, error: 'Capsule expired or already
redeemed' });
    }
    await writeAuditLog('CAPSULE_REDEEMED', capsule.episodeId.toString());
    return reply.send({ success: true, message: 'Capsule successfully redeemed' });
  }
};
```

4) FILE NAME: Connify/src/services/OfflineQueueService.ts

```
import AsyncStorage from '@react-native-async-storage/async-storage';
import { AppState } from 'react-native';
```

```
import { connectivityService } from './ConnectivityService';

const QUEUE_STORAGE_KEY = 'CONNIFY_OFFLINE_QUEUE';

export interface QueuedItem {
  id: string;
  type: string;
  payload: any;
  createdAt: number;
  maxAge?: number;
}

export type QueueHandler = (payload: any) => Promise<void>;

class OfflineQueueService {
  private queue: QueuedItem[] = [];
  private handlers: Map<string, QueueHandler> = new Map();
  private isFlushing = false;
  private initialized = false;

  public async init(): Promise<void> {
    if (this.initialized) return;
    await this.loadQueue();
    this.initialized = true;

    // Listen to application foreground transitions
    AppState.addEventListener('change', (nextState) => {
      if (nextState === 'active' && connectivityService.isOnline) this.flush();
    });

    // Automatically trigger queue replay upon cellular/Wi-Fi reconnection
    connectivityService.subscribe((isOnline) => {
```

```
    if (isOnline) this.flush();
  });
 }

 public registerHandler(type: string, handler: QueueHandler): void {
  this.handlers.set(type, handler);
 }

 public async enqueue(type: string, payload: any, maxAgeMs?: number):
Promise<void> {
  if (!this.initialized) await this.init();

  const item: QueuedItem = {
   id: Math.random().toString(36).substring(2, 10) + Date.now().toString(),
   type,
   payload,
   createdAt: Date.now(),
   maxAge: maxAgeMs,
  };

  this.queue.push(item);
  this.queue.sort((a, b) => a.createdAt - b.createdAt); // Maintain strict FIFO order
  await this.saveQueue();

  if (connectivityService.isOnline) this.flush();
 }

 public async flush(): Promise<void> {
  if (this.isFlushing || this.queue.length === 0 || !connectivityService.isOnline) return;
  this.isFlushing = true;

  try {
```

```
    const now = Date.now();
    const remaining: QueuedItem[] = [];

    for (const item of this.queue) {
      if (item.maxAge && now - item.createdAt > item.maxAge) continue; // Drop
expired mutations

      const handler = this.handlers.get(item.type);
      if (handler) {
        try {
          await handler(item.payload);
        } catch (e) {
          remaining.push(item); // Keep in queue for exponential backoff retry
        }
      }
    }
    this.queue = remaining;
    await this.saveQueue();
  } finally {
    this.isFlushing = false;
  }
 }

 private async loadQueue(): Promise<void> {
  const raw = await AsyncStorage.getItem(QUEUE_STORAGE_KEY);
  if (raw) this.queue = JSON.parse(raw);
 }
 private async saveQueue(): Promise<void> {
  await AsyncStorage.setItem(QUEUE_STORAGE_KEY,
JSON.stringify(this.queue));
 }}
export const offlineQueueService = new OfflineQueueService();
```

APPENDIX – B

SCREENSHOTS




Figure B.1 Unified Safety Hub Screen




Figure B.2 Handshake QR Verification Screen




Figure B.3 Encrypted Chat & VoIP Screen




Figure B.4 Fake Call Simulator Screen




Figure B.5 Offline Emergency Screen




Figure B.6 Connify on Google Play Store

REFERENCES

1. Alvestrand, H. 2021, “Overview: Real-Time Protocols for Browser-Based App” , RFC 8825, Internet Engineering Task Force (IETF), pp. 1-17.
2. Cheshire, S. & Krochmal, M. 2013, “DNS-Based Service Discovery”, RFC 6763, Internet Engineering Task Force (IETF), pp. 1–36.
3. Cheshire, S. & Krochmal, M. 2013, “Multicast DNS”, RFC 6762, Internet Engineering Task Force (IETF), pp. 1–74.
4. Coulouris, G., Dollimore, J., Kindberg, T. & Blair, G. 2012, “Distributed Systems: Concepts and Design”, Distributed Systems: Concepts and Design, 5th ed., Addison-Wesley, Harlow, England, pp. 1–1048.
5. Dart Team 2026, “Dart Programming Language: Language Features, Asynchronous Programming, and Libraries”, Dart Documentation, Google, available at: https://dart.dev/guides.
6. Deering, S. 1989, “Host Extensions for IP Multicasting”, RFC 1112, Internet Engineering Task Force (IETF), pp. 1–21.
7. Eddy, W. (ed.) 2022, “Transmission Control Protocol (TCP)”, RFC 9293, Internet Engineering Task Force (IETF), pp. 1–98.
8. Expo 2026, “Expo Documentation”, available at: https://docs.expo.dev/.
9. Fette, I. & Melnikov, A. 2011, “The WebSocket Protocol”, RFC 6455, Internet Engineering Task Force (IETF).
10. Google 2026, “Flutter Documentation: Building Cross-Platform Applications with Dart”, Flutter Developer Documentation, Google, available at: https://docs.flutter.dev/.
11. Josefsson, S. & Liusvaara, I. 2017, “Edwards-Curve Digital Signature Algorithm (EdDSA)”, RFC 8032, Internet Engineering Task Force (IETF).
12. Langley, A., Hamburg, M. & Turner, S. 2016, “Elliptic Curves for Security”, RFC 7748, Internet Engineering Task Force (IETF).

13. National Institute of Standards and Technology (NIST) 2015, “Secure Hash Standard (SHS)”, Federal Information Processing Standards Publication, vol. 180-4, U.S. Department of Commerce, Gaithersburg, Maryland, pp. 1–36.

14. Postel, J. 1980, “User Datagram Protocol”, RFC 768, Internet Engineering Task Force (IETF), pp. 1–3.

15. Postel, J. 1981, “Transmission Control Protocol”, RFC 793, Internet Engineering Task Force (IETF), pp. 1–85.

16. Rescorla, E. 2018, “The Transport Layer Security (TLS) Protocol Version 1.3”, RFC 8446, Internet Engineering Task Force (IETF), pp. 1–160.

17. Socket.IO 2026, “Socket.IO Documentation”, available at: https://socket.io/docs/v4/.

18. Stallings, W. 2013, “Data and Computer Communications: Networking and Protocol Fundamentals”, Data and Computer Communications, 10th ed., Pearson Education, Upper Saddle River, New Jersey, pp. 1–912.

19. Stallings, W. 2017, “Cryptography and Network Security: Principles and Practice”, Cryptography and Network Security, 7th ed., Pearson Education, pp. 1–768.

20. Steinmetz, R. & Wehrle, K. (eds.) 2005, “Peer-to-Peer Systems and Applications: Networking Architectures, Protocols, and Distributed Services”, Lecture Notes in Computer Science, vol. 3485, Springer, Berlin, Heidelberg, pp. 1–592.

21. Tanenbaum, A. S. & Wetherall, D. J. 2011, “Computer Networks: Network Architecture, Protocols, and Distributed Communication”, Computer Networks, 5th ed., Pearson Education, Upper Saddle River, New Jersey, pp. 1–960.