



Please subscribe to the official Codeforces channel in Telegram via the link: https://t.me/codeforces_official.


[PROBLEMS](#) [SUBMIT CODE](#) [MY SUBMISSIONS](#) [STATUS](#) [HACKS](#) [ROOM](#) [STANDINGS](#) [CUSTOM INVOCATION](#)

D. Ehab and another xor problem

time limit per test: 1 second

memory limit per test: 256 megabytes

input: standard input

output: standard output

This is an interactive problem!

Ehab plays a game with Laggy. Ehab has 2 hidden integers (a, b) . Laggy can ask a pair of integers (c, d) and Ehab will reply with:

- 1 if $a \oplus c > b \oplus d$.
- 0 if $a \oplus c = b \oplus d$.
- -1 if $a \oplus c < b \oplus d$.

Operation $a \oplus b$ is the [bitwise-xor operation](#) of two numbers a and b .

Laggy should guess (a, b) with **at most 62 questions**. You'll play this game. You're Laggy and the interactor is Ehab.

It's guaranteed that $0 \leq a, b < 2^{30}$.

Input

See the interaction section.

Output

To print the answer, print "! a b" (without quotes). **Don't forget to flush the output after printing the answer.**

Interaction

To ask a question, print "? c d" (without quotes). Both c and d must be non-negative integers less than 2^{30} . **Don't forget to flush the output after printing any question.**

After each question, you should read the answer as mentioned in the legend. If the interactor replies with -2, that means you asked more than 62 queries and your program should terminate.

To flush the output, you can use:-

- `fflush(stdout)` in C++.
- `System.out.flush()` in Java.
- `stdout.flush()` in Python.
- `flush(output)` in Pascal.
- See the documentation for other languages.

Hacking:

To hack someone, print the 2 space-separated integers a and b ($0 \leq a, b < 2^{30}$).

Example

input	Copy
1 -1 0	
output	Copy
? 2 1 ? 1 2 ? 2 0	

Codeforces Round #525 (Div. 2)

Finished

→ Practice?

Want to solve the contest problems after the official contest ends? Just register for practice and you will be able to submit solutions.

Register for practice

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Problem tags

bitmasks

constructive algorithms

No tag edit access

→ Contest materials

- Tutorial



Note

In the sample:

The hidden numbers are $a = 3$ and $b = 1$.

In the first query: $3 \oplus 2 = 1$ and $1 \oplus 1 = 0$, so the answer is 1.

In the second query: $3 \oplus 1 = 2$ and $1 \oplus 2 = 3$, so the answer is -1.

In the third query: $3 \oplus 2 = 1$ and $1 \oplus 0 = 1$, so the answer is 0.

Then, we printed the answer.

[Codeforces](#) (c) Copyright 2010-2018 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Dec/05/2018 15:54:31^{UTC+5.5} (d1).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)

Supported by



ITMO UNIVERSITY