1. Coffee Order

```
import java.util.Scanner;

public class CoffeeOrderSimple {
   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      String[] drinks = {"Espresso", "Latte", "Cappuccino",
"Mocha", "Americano"};
      double basePrice = 100;
      System.out.println("Drinks: 1.Espresso 2.Latte
3.Cappuccino 4.Mocha 5.Americano");
      System.out.print("Choose drink (1-5): ");
      int choice = sc.nextInt();
      System.out.print("Enter size (Small/Medium/Large): ");
      String size = sc.next();
      System.out.print("Extra shot? (yes/no): ");
      String extraShot = sc.next();
      System.out.print("Milk foam? (yes/no): ");
      String milkFoam = sc.next();
      double total = basePrice;
      if (size.equalsIgnoreCase("Medium")) total += 20;
      else if (size.equalsIgnoreCase("Large")) total += 40;
      if (extraShot.equalsIgnoreCase("yes")) total += 30;
      if (milkFoam.equalsIgnoreCase("yes")) total += 10;
      System.out.println("\nOrder:");
      System.out.println("Drink: " + drinks[choice - 1]);
      System.out.println("Size: " + size);
      System.out.println("Extra shot: " + extraShot);
      System.out.println("Milk foam: " + milkFoam);
      System.out.println("Total price: " + total);
      sc.close();
   }
}
```

2. Simple Calculator

```
import java.util.Scanner;
public class Calculator {

   static double calculate(double a, double b, char op) {
      double result = 0;
      switch (op) {
         case '+': result = a + b; break;
         case '-': result = a - b; break;
         case '*': result = a * b; break;
         case '/':
            if (b != 0) result = a / b;
            else System.out.println("Cannot divide by zero!");
            break;
         default: System.out.println("Invalid operator!");
      }
      return result;
   }

   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter first number: ");
      double num1 = sc.nextDouble();
      System.out.print("Enter second number: ");
      double num2 = sc.nextDouble();
      System.out.print("Enter operation (+, -, *, /): ");
      char op = sc.next().charAt(0);
      double res = calculate(num1, num2, op);
      System.out.println("Result: " + res);
      sc.close();
   }
}
```

3.Character Counter

```
import java.util.Scanner;

public class CharCounter {
   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter a string: ");
      String str = sc.nextLine();
      int vowels = 0, consonants = 0, digits = 0, special = 0;
      for (int i = 0; i < str.length(); i++) {
         char c = str.charAt(i);
         if (Character.isDigit(c)) {
            digits++;
         } else if (Character.isLetter(c)) {
            if ("AEIOUaeiou".indexOf(c) != -1) {
               vowels++;
            } else {
               consonants++;
            }
         } else {
            special++;
         }
      }
      System.out.println("Vowels: " + vowels);
      System.out.println("Consonants: " + consonants);
      System.out.println("Digits: " + digits);
      System.out.println("Special Characters: " + special);
      sc.close();
   }
}
```

4. Customer Interest

```
import java.util.Scanner;

public class CustomerInterest {
   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter number of customers: ");
      int n = sc.nextInt();
      sc.nextLine(); // consume newline
      String[] names = new String[n];
      String[] accType = new String[n];
      double[] balance = new double[n];

      for (int i = 0; i < n; i++) {
         System.out.print("\nEnter customer name: ");
         names[i] = sc.nextLine();
         System.out.print("Enter account type
(Savings/Fixed): ");
         accType[i] = sc.nextLine();
         System.out.print("Enter balance: ");
         balance[i] = sc.nextDouble();
         sc.nextLine(); // consume newline
      }

      for (int i = 0; i < n; i++) {
         if (accType[i].equalsIgnoreCase("Savings")) {
            balance[i] += balance[i] * 0.04;
         } else if (accType[i].equalsIgnoreCase("Fixed")) {
            balance[i] += balance[i] * 0.06;
         }
      }

      System.out.println("\nUpdated Customer Balances:");
      for (int i = 0; i < n; i++) {
         System.out.printf("%s (%s): %.2f\n", names[i],
accType[i], balance[i]);
      }
      sc.close();
   }
}
```

5. Temperature Converter

```
import java.util.Scanner;

public class TempConverter {
   static double toFahrenheit(double celsius) {
      return (celsius * 9 / 5) + 32;
   }

   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      double[] temps = new double[5];
      for (int i = 0; i < 5; i++) {
         System.out.print("Enter temperature for day " + (i +
1) + " in Celsius: ");
         temps[i] = sc.nextDouble();
      }
      System.out.println("\nCelsius -> Fahrenheit:");
      for (int i = 0; i < 5; i++) {
         double f = toFahrenheit(temps[i]);
         System.out.printf("%.2f°C -> %.2f°F\n", temps[i], f);
      }
      sc.close();
   }
}
```

6.Electricity Bill

```
import java.util.Scanner;

public class ElectricityBill {
   static double calculateBill(int units) {
      double bill = 0;
      if (units <= 100) {
         bill = units * 5;
      } else if (units <= 200) {
         bill = 100 * 5 + (units - 100) * 7;
      } else if (units <= 300) {
         bill = 100 * 5 + 100 * 7 + (units - 200) * 10;
      } else {
         bill = 100 * 5 + 100 * 7 + 100 * 10 + (units - 300) * 15;
      }
      return bill;
   }

   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter number of units consumed: ");
      int units = sc.nextInt();
      double totalBill = calculateBill(units);
      System.out.printf("Total bill for %d units: ₹%.2f\n",
units, totalBill);
      sc.close();
   }
}
```

7. Palindrome Check

```
import java.util.Scanner;

public class PalindromeCheck {
   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      try {
         System.out.print("Enter a string: ");
         String str = sc.nextLine();
         if (str.isEmpty()) {
            throw new Exception("Empty string not
allowed!");
         }
         String cleanStr = str.replaceAll("\\s+",
"").toLowerCase();
         String reversed = new
StringBuilder(cleanStr).reverse().toString();
         if (cleanStr.equals(reversed)) {
            System.out.println("The string is a palindrome.");
         } else {
            System.out.println("The string is not a
palindrome.");
         }
      } catch (Exception e) {
         System.out.println("Error: " + e.getMessage());
      } finally {
         sc.close();
      }
   }
}
```

8. Character Replacer

```
import java.util.Scanner;

public class CharReplace {
   public static void main(String[] args) {
      Scanner sc = new Scanner(System.in);
      System.out.print("Enter a word: ");
      String word = sc.nextLine();
      String result = "";
      for (int i = 0; i < word.length(); i++) {
         char c = word.charAt(i);
         switch (c) {
            case 'a': case 'A':
               result += '4';
               break;
            case 'e': case 'E':
               result += '3';
               break;
            case 'o': case 'O':
               result += '0';
               break;
            default:
               result += c;
         }
      }
      System.out.println("Modified word: " + result);
      sc.close();
   }
}
```