

More Boolean and Relational Topics

Class 14

Overlapping

- consider the bank loan rate, but with slightly different rules
- illustrated by this two-dimensional chart

		Employed	
		No	Yes
Grad	No	good	better
	Yes	better	best

- because the cases overlap, you **could** use a nested-if structure
- but it's simpler and more natural to use a **logical operator**

Logical Operators

- C++ has three logical operators
- and
 - `&&` **logical-and** is a binary operator
 - its operands are both Boolean values
 - its return value is Boolean
- or
 - `||` **logical-or** is a binary operator
 - its operands are both Boolean values
 - its return value is Boolean
- not
 - `!` **logical-not** is a unary operator
 - its operand is a Boolean value
 - its return value is Boolean

Truth Tables

- computer scientists use truth tables to explain the behavior of logical operators

a	b	a && b
f	f	f
f	t	f
t	f	f
t	t	t

a	b	a b
f	f	f
f	t	t
t	f	t
t	t	t

a	!a
f	t
t	f

Using Logical Operators

- `string brandName;`
`int price;`
`bool hdmiPort;`
- I will only buy if the brand is apple, price is less than one thousand dollars
- I will buy a windows surface computer, price should be less than 700 dollars

Using Logical Operators

- `bool homeWork;`
`string thingsToDo;`
`bool isWeekEnd;`
- I will go to sleep early if I have homework and its weekdays
- I will go shopping if I do not have homework and its a weekend
- I will watch a movie if its the weekend and have no homework

Using Logical Operators

- for the bank loan, in English
- if the customer is **neither** employed **nor** graduated, the rate is good
- if the customer is employed **or** graduated, but **not both**, the rate is better
- if the customer is **both** employed **and** graduated, the rate is best

Using Logical Operators

- for the bank loan, in English
- if the customer is neither employed nor graduated, the rate is good
- if the customer is employed or graduated, but not both, the rate is better
- if the customer is both employed and graduated, the rate is best
- this can be expressed in C++ in various ways

Loan Version 1

```
if (graduated == 'Y' && employed == 'Y')
{
    rate = "best";
}
else if (graduated == 'Y')
{
    rate = "better";
}
else if (employed == 'Y')
{
    rate = "better";
}
else
{
    rate = "good";
}
```

Loan Version 2

```
if (graduated == 'Y' && employed == 'Y')
{
    rate = "best";
}
else if (graduated == 'Y' || employed == 'Y')
{
    rate = "better";
}
else
{
    rate = "good";
}
```

Or

- in English, **or** can have two different meanings
 1. do you want fries **or** onion rings with that burger?
 2. to help as a volunteer, you can carry boxes **or** set up signs
- in case 1, you can choose fries or onion rings, but **not both**
- in case 2, you can help by carrying boxes, by setting up signs, or by **doing both**
- case 1 is called **exclusive or**
- case 2 is called **inclusive or**
- the C++ logical or operator is the inclusive or operator

Equality of Characters and Strings

- testing the equality of characters is obvious
- one letter is either exactly the same as another, or not
- `'A' == 'A'` is true while `'A' == 'a'` is false

Equality of Characters and Strings

- testing the equality of characters is obvious
- one letter is either exactly the same as another, or not
- `'A' == 'A'` is true while `'A' == 'a'` is false
- two string objects are equal if they have exactly the same characters in exactly the same order, and are the same length
- assuming `string word = "Extra";` has been initialized:
- `word == "Extra"` is true
- `word == "Extravagant"` is false

Order of Characters

- the less-than and greater-than relops apply to characters
- based on the ASCII chart (Gaddis page 1287)
- a character that is listed in the chart is **less than** one that is listed later, and **greater than** one that is listed earlier

Order of Characters

- the less-than and greater-than relops apply to characters
- based on the ASCII chart (Gaddis page 1287)
- a character that is listed in the chart is less than one that is listed later, and greater than one that is listed earlier
- thus, 'a' < 'b' is true
- and 'a' > 'A' is true — this one is not intuitive
- and 'a' > '9' is true — also not intuitive

Order of Characters

- the less-than and greater-than relops apply to characters
- based on the ASCII chart (Gaddis page 1287)
- a character that is listed in the chart is less than one that is listed later, and greater than one that is listed earlier
- thus, 'a' < 'b' is true
- and 'a' > 'A' is true — this one is not intuitive
- and 'a' > '9' is true — also not intuitive
- but you should know its general structure
 - the ASCII value for 'A' is 65 (so for 'B' it is 66, ...)
 - the ASCII value for 'a' is 97 (so for 'b' it is 98, ...)
 - the ASCII value for '0' is 48 (so for '1' it is 49, ...)
 - the ASCII value for space character is 32

Comparing Strings

- the less-than and greater-than relops apply to string objects
- strings are compared character-by-character down the length of both strings
- the first character at which they differ determines which string is less-than the other
- if two strings have different lengths and contain exactly the same characters as far as the shorter one, the shorter one is less than the larger

f	o	o	t				
f	o	o	t	b	a	l	l

Comparing Strings Warning

- you **can** compare two C++ strings using relops
- you **can** compare a C++ string and string literals by using the relops
- but you **should not** compare two string literals by using the relops

Comparing Strings Warning

- you **can** compare two C++ strings using relops
- you **can** compare a C++ string and string literals by using the relops
- but you **should not** compare two string literals by using the relops

- assuming `string first = "Bill";`
and `string last = "Monroe";`
 - legal: `first == last`
 - legal: `first >= "Bill"`
 - illegal and may not work: `"Monroe" > "Bill"`

The Conditional Operator

- a very common programming construct has this structure:
- this construct will definitely give y a value
- the value of y will be either the opposite of x or double x, depending on the value of x
- this is so common that there is a shortcut form

```
if (x < 0)
{
    y = x * -1;
}
else
{
    y = 2 * x;
}
```

```
y = x < 0 ? x * -1 : 2 * x;
```

The Conditional Operator

```
y = x < 0 ? x * -1 : 2 * x;
```

- the conditional operator is **ternary**
 1. first part: a Boolean expression
 2. second part: value if the Boolean expression is true
 3. third part: value if the Boolean expression is false

Flag Variables

Flag

A Boolean variable that stores the state of some condition in the program. When set to true, it indicates the condition exists. When set to false, it indicates the condition does not exist.

Flag Variables

Flag

A Boolean variable that stores the state of some condition in the program. When set to true, it indicates the condition exists. When set to false, it indicates the condition does not exist.

- in a program that calculates sales commissions, we can create the flag variable:

```
bool sales_quota_met = sale_amount >= QUOTA;
```

- later in the program we can check the state of the flag:

```
if (sales_quota_met)  
{ ...
```

Flag Variables

Flag

A Boolean variable that stores the state of some condition in the program. When set to true, it indicates the condition exists. When set to false, it indicates the condition does not exist.

- in a program that calculates sales commissions, we can create the flag variable:

```
bool sales_quota_met = sale_amount >= QUOTA;
```

- later in the program we can check the state of the flag:

```
if (sales_quota_met)
{ ...
```

- this is more readable than not using the flag:

```
if (sale_amount >= QUOTA)
{ ...
```


Scope

Scope

A variable's scope is the region of the program in which the variable exists and in which its name can be legally used.

- a variable's scope extends from declaration to the end of the closest containing block
- some scopes:
 1. MIN_INCOME's scope is all of lines 8 – 36
 2. income's scope is lines 12 – 36
 3. years's scope is lines 18 – 30
 4. years_remaining's scope is lines 27 – 29

Variables With the Same Name

- on page 215 Gaddis shows a program that has two variables with the same name in **nested scopes**
- as he points out, this is legal but a bad idea
- to emphasize the point, **never do this!**

```
int number;  
...  
if (...)  
{  
    int number; // the outer number is no longer visible  
    ...  
}  
// now outer number is again visible
```

Variables With the Same Name

- Let us try to determine the output of the following program

```
1  #include <iostream>
2  using namespace std;
3
4  int main()
5  {
6      int value = 10;
7
8      int foo = 13;
9
10     if(foo>12)
11     {
12         int value = 20;
13         cout<<" " << value;
14     }
15
16     cout<<" " << value;
17 }
```

Variables With the Same Name

- however, it is fine to have two variables with the same name in **parallel** scopes
- because only one side of the if statement can run, only one variable named number ever exists
- there is no ambiguity

```
if (...)
{
    int number;
    ...
}
else
{
    int number;
    ...
}
```

Not Included

- note: we will not cover Gaddis Section 4.14 The switch Statement at this time