

Main Page:

<https://developers.cjdropshipping.cn/en/api/introduction>
(<https://developers.cjdropshipping.cn/en/api/introduction>)

Introduction | CJ Docs

Introduction

Update Announcements

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 1745 Global Error Codes

Appendix 2 1745 Country Code

Appendix 3 1745 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Introduction

CJ API enables developers to access CJ system.

Update Announcements

Update Time

Update Content

STATUS

JUMP URL

2025-11-19

« » Inventory Query Enhancement »

The "Query Inventory by Product ID" interface adds a new returned field: Sub-warehouse List, supporting queries for the detailed inventory distribution of products across all sub-warehouses.

Function Enhancement

View Details

2025-11-18

« » Warehouse Management »

Add a new interface "Get Storage Info".

New Interface

View Details

2025-12-02

« » Logistics Process »

Add complete documentation for the "Platform Logistics Order Processing", detailing the full-process status flow from order placement to receipt.

Documentation Added

View Details

Development

« »

Sub-link:

<https://developers.cjdropshipping.cn/en/api/start/webhook.html>
(<https://developers.cjdropshipping.cn/en/api/start/webhook.html>)

Webhook Mechanism | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Introduction

Setup Procedure

Webhook Configuration Requirements

List of topics

Product Message: PRODUCT

Stock Message

Order message

Logistics message

Listening example

Example

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 117410 Global Error Codes

Appendix 217410 Country Code

Appendix 317410 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Webhook Mechanism

Introduction

Product details including addition, deletion & modification of variants.

Setup Procedure

117410 Set up message monitoring and reference.

webhook

217410 Set up client monitoring interface, example as below(Java).

317410 Test monitoring.

Webhook Configuration Requirements

1. Protocol Requirements

Supported Protocols

: HTTPS

Encryption

: TLS 1.2 or TLS 1.3 recommended for secure transmission

Request Method

: POST

Content Type

:

Content-Type: application/json

2. Response Specifications

Success Status Code
:
200 OK
Timeout
: Response must be returned within
3 seconds
(Avoid long-running or complex business logic to ensure prompt response)
List of topics
Product Message:
PRODUCT
Occurs when a product is created or updated.
Sample Payload
{ "messageId": "ca72a4834cd14b9588e88ce206f614a0", "type": "PRODUCT", "messageType": "UPDATE", "params": { "categoryId": null, "categoryName": null, "pid": "1424608189734850560", "productDescription": "xxxxxx", "productImage": null, "productName": null, "productNameEn": null, "productProperty1": null, "productProperty2": null, "productProperty3": null, "productSellPrice": null, "productSku": null, "productStatus": null, "fields" : ["productDescription"] } }
Parameter
Definition
Type
Required
Length
Note
messageId
Message Id
string
Y
200
Message Id
type
Data Type
string
Y
20
PRODUCT
messageType
Message type
string
Y
15
INSERTã()UPDATEã()DELETE

	params
	object
	Y
	5
• categoryId	category Id
	string
	Y
	200
• categoryName	category Name
	string
	Y
	200
• pid	product id
	string
	Y
	200
• productDescription	product description
	string
	Y
	2000
• productImage	product image
	string
	Y
	200
• productName	product name
	string
	Y
	200
• productNameEn	product name(english)
	string
	Y
	200

- productProperty1

product property
string
Y
200

- productProperty2

product property
string
Y
200

- productProperty3

product property
string
Y
200

- productSellPrice

product sell price
double
Y
20

- productSku

product sku
string
Y
200

- productStatus

product status
int
Y
5
status:2-Off sale, 3-On Sale

- fields

fields list
list
Y
5
Product Status
ProductStatus
Description

2

Off sale

3

On Sale

Inbound message for Variant

```
{ "messageId": "7cceede817dc47ed9748328b64353c5c", "type": "VARIANT", "messageType": "UPDATE", "params": { "vid": "1424608152007086080", "variantName": null, "variantWeight": null, "variantLength": null, "variantWidth": null, "variantHeight": null, "variantImage": null, "variantSku": null, "variantKey": null, "variantSellPrice": null, "variantStatus": null, "variantValue1": null, "variantValue2": null, "variantValue3": null, "fields" : [ "variantLength" ], } }
```

Parameter

Definition

Type

Required

Length

Note

messageId

Message id

string

Y

50

Message Id

type

Data Type

string

Y

20

VARIANT

messageType

Message Type

string

Y

15

INSERTâUPDATEâDELETE

params

object

Y

- vid

variant Id

string

Y

50

• variantName	variant name
	string
	Y
	200
• variantWeight	variant weight, unit:g
	int
	Y
• variantLength	variant length, unit:mm
	int
	Y
• variantWidth	variant width, unit:mm
	int
	Y
• variantHeight	variant height, unit:mm
	int
	Y
• variantImage	variant image
	string
	Y
	200
• variantSku	variant sku
	string
	Y
	200
• variantKey	variant key
	string
	Y
	200
• variantSellPrice	variant sell price, USD
	double
	Y

- variantStatus

variant status

int

Y

5

- variantValue1

variant value1

string

Y

100

- variantValue2

variant value2

string

Y

100

- variantValue3

variant value3

string

Y

100

- fields

fields list

list

Y

5

Variant Status

variantStatus

Description

0

Off sale

1

On sale

Stock Message

{ "messageId": "ca72a4834cd14b9588e88ce206f614a0", "type": "STOCK", "messageType": "UPDATE", "params": { "1424608152007086080": [{ "vid": "1424608152007086080", "areald": "2", "areaEn": "US Warehouse", "countryCode": "US", "storageNum": 12 }], "AE7DB9BC-4290-4C85-B8A6-F8957F3DB053": [{ "vid": "AE7DB9BC-4290-4C85-B8A6-F8957F3DB053", "areald": "2", "areaEn": "US Warehouse", "countryCode": "US", "storageNum": 1 }] } }

Order message

{ "messageId": "7cceede817dc47ed9748328b64353c5c", "type": "ORDER", "messageType": "UPDATE", "params": { "orderNumber": "api_52f268d40b8d460e82c0683955e63cc9", "cjOrderId": 210823100016290555, "orderStatus": "CREATED", "logisticName": "CJPacket Ordinary", "trackNumber": null, "createDate": "2021-08-23 11:31:45", "updateDate": "2021-08-23 11:31:45", "payDate": null, "deliveryDate": null, "completeDate": null } }

Parameter

	Definition
	Type
	Required
	Length
	Note
	messageId
	Message id
	string
	Y
	50
	Message Id
	type
	Data Type
	string
	Y
	20
	ORDER
	messageType
	Message Type
	string
	Y
	15
INSERTã()UPDATEã()DELETEã()ORDER_CONNECTED: This type requires special attention! ^{1/4} ☞The product has been re-associated in the CJ system, and the order status has been updated from incomplete to complete. At this point, The actual CJ order id is returned in this message.	
	params
	object
	Y
• cjOrderId	CJ order id
	string
	Y
	200
• orderNum	Customer order number
	string
	Y
	200
	Will be deprecated, please use orderNumber instead
• orderNumber	

	Customer order number
	string
	Y
	200
• orderStatus	
	CJ order status
	string
	Y
	200
• logisticName	
	logistic name
	string
	Y
	200
• trackNumber	
	track number
	string
	Y
	200
• trackingUrl	
	tracking URL
	string
	N
	200
• updateDate	
	update date
	string
	Y
	200
• createDate	
	create date
	string
	Y
	200
• payDate	
	pay date
	string
	Y
	200

- deliveryDate

delivery date

string

Y

200

- completeDate

complete date

string

Y

200

Order splitting message

```
{ "messageId": "7cceede817dc47ed9748328b64353c5c", "type": "ORDERSPLIT", "messageType": "UPDATE", "params": { "originalOrderId": "original order id", "splitOrderList": [ {
"createAt":1673490845706, "orderCode":"SD1613355441583259648-2", "orderStatus":300, "productList":[ { "sku":"CJNSSYLY01043-Claret-S", "vid":"2547992D-CEE1-4BFD-99AC-
9E30354F771F", "quantity":1, "productCode":"1613355657229205504" }, { "sku":"CJNSAQXF00016-Orange", "vid":"A9C95BCB-D824-4AA1-A389-E86F3CCB10EF", "quantity":1,
"productCode":"1613355657229205506" }, { "sku":"CJNSSYCS03214-Photo Color-XXL", "vid":"E5FED43E-F9DE-483F-ADCE-8C95D3380315", "quantity":1,
"productCode":"1613355657229205507" } ] }, { "createAt":1673490845706, "orderCode":"SD1613355441583259648-1", "orderStatus":300, "productList":[ { "sku":"CJNSSYLY01043-
White-M", "vid":"0550DFC6-7FF7-4662-AE7D-B4DF0E4EB24A", "quantity":1, "productCode":"1613355657229205505" } ] }, { "orderSplitTime": "æKâI \ æ●¶é●:" } }
```

Parameter

Definition

Type

Required

Length

Note

messageId

Message id

string

Y

50

Message Id

type

Data Type

string

Y

20

ORDERSPLIT

messageType

Message Type

string

Y

15

INSERTã()UPDATEã()DELETE

	params
	Object
	Y
• originalOrderId	Original CJ order id
	string
	N
	200
• orderSplitTime	Order Split Date
	string
	N
	200
• splitOrderList	Order List
	Order[]
	N
•	
◦ orderCode	CJ order id
	string
	N
	200
•	
◦ createAt	Create date
	string
	N
	200
•	
◦ orderStatus	Order status
	int
	N
	11
•	
◦ productList	Product Information List
	Product[]
	N
	200

- 200

- 200

- 10

- 50

50

	Message Id
	type
	Data Type
	string
	Y
	20
	ORDERSPLIT
	messageType
	Message Type
	string
	Y
	15
	INSERTa()UPDATEa()DELETE
	params
	Object
	Y
• cjProductId	
	CJ product id
	string
	N
	100
• cjVariantId	
	CJ variant id
	string
	N
	100
• cjVariantSku	
	CJ variant sku
	string
	N
	50
• cjSourcingId	
	CJ sourcing Id
	string
	N
	50
• status	
	status
	string

	N
	20
<ul style="list-style-type: none"> failReason 	
	fail reason
	string
	N
	20
<ul style="list-style-type: none"> createDate 	
	create date
	String
	N
	50
	Logistics message
	<pre>{ "messageId": "7cceede817dc47ed9748328b64353c5c", "type": "LOGISTIC", "messageType": "UPDATE", "openId": 12312, "params": { "orderId": 210823100016290555, "logisticName": "CJPacket Ordinary", "trackingNumber": "number12345678", "trackingStatus": 12, "logisticsTrackEvents": "[{"status":12,"activity":" Delivered, PO Box","location":" NENANA,AK 99760","eventTime":"2024-01-18 07:59:22","statusDesc":"Delivered","thirdActivity":"Delivered, PO Box","thirdLocation":"NENANA,AK 99760","thirdEventTime":"2024-01-18 07:59:22"}]" }</pre>
	Parameter
	Definition
	Type
	Required
	Length
	Note
	messageId
	Message Id
	string
	Y
	200
	Message Id
	type
	Data Type
	string
	Y
	200
	LOGISTIC
	messageType
	Message Type
	string
	Y
	15

	INSERT	UPDATE	DELETE
	params		
	object		
	Y		
• orderId	CJ order id		
	string		
	Y		
	200		
	210823100016290555		
• logisticName	logistic name		
	string		
	Y		
	200		
	CJPacket Ordinary		
• trackingNumber	tracking number		
	string		
	Y		
	200		
	number12345678		
• trackingUrl	tracking URL		
	string		
	N		
	200		
• trackingStatus	tracking status		
	int		
	Y		
	20		
	0- No tracking information available at the moment 1- Warehouse outbound 2- Freight forwarder inbound 3- Freight forwarder return 4- Freight forwarder outbound 5- First leg transportation 6- Arrival at destination country 7- Starting customs clearance 8- Customs clearance completed 9- Terminal retrieval 10- Delivery 11- Arrival waiting for retrieval 12- Sign for 13- Failure/abnormality 14- Return		
• logisticsTrackEvents	logistics track events		
	string		
	Y		
	200		

```
[{"status":12,"activity":" Delivered, PO Box","location":" NENANA,AK 99760","eventTime":"2024-01-18 07:59:22","statusDesc":"Delivered","thirdActivity":"Delivered, PO Box","thirdLocation":"NENANA,AK 99760","thirdEventTime":"2024-01-18 07:59:22"}]
```

Listening example

Example

```
package com.cj.cn.controller;
```

```
import com.alibaba.fastjson.JSON; import com.cj.cn.constant.callback.domain.CallbackParams; import com.cj.cn.util.result.Result; import lombok.extern.slf4j.Slf4j; import org.springframework.validation.annotation.Validated; import org.springframework.web.bind.annotation.PostMapping; import org.springframework.web.bind.annotation.RequestBody; import org.springframework.web.bind.annotation.RequestMapping; import org.springframework.web.bind.annotation.RestController;
```

```
/**
```

- CJ Webhook Listening Example

-

- @author : kay */ @RestController @RequestMapping("/webhookListener") @Slf4j public class TestController {

```
@PostMapping("/productMessage") public Result productMessage(@RequestBody @Validated CallbackParams query) { log.info("product message:", JSON.toJSONString(query)); return Result.success(Boolean.TRUE); }
```

```
package com.cj.cn.constant.callback.domain;
```

```
import lombok.Data;
```

```
/**
```

- @author : kay */ @Data public class CallbackParams { private String messageId; private String type; private Object params; }

```
package com.cj.cn.constant.callback.domain;
```

```
import lombok.Getter; import org.springframework.util.StringUtils;
```

```
/**
```

- @author : kay */ @Getter public enum CallbackBusinessTypeEnum { PRODUCT, VARIANT, STOCK;

```
public static CallbackBusinessTypeEnum create(String name) { if (!StringUtils.isEmpty(name)) { for (CallbackBusinessTypeEnum typeEnum: CallbackBusinessTypeEnum.values()) { if (typeEnum.name().equals(name.toUpperCase())) { return typeEnum; } } } return null; }
```

```
â€‹
```

Platform Waybill Order Processing

Sandbox

â€‹

Sub-link: <https://developers.cjdropshipping.cn/en/api/api2/>
(<https://developers.cjdropshipping.cn/en/api/api2/>)

API V2.0 (recommended) | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 11%4#57Global Error Codes

Appendix 2 11%4#57Country Code

Appendix 3 11%4#57Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

API V2.0 (recommended)

1 Interface List

Module

Function

No.

URL

Interface Name

00-Authentication

Auth

1

/api2.0/v1/authentication/getAccessToken

Get Token

2

/api2.0/v1/authentication/refreshAccessToken

Refresh Token

3

/api2.0/v1/authentication/logout

Logout

01-Settings

Settings

1

/api2.0/v1/setting/get

Get Settings

Account

1

/api2.0/v1/setting/account/set

Account Settings

2

/api2.0/v1/setting/account/delete

Delete Settings

02-Product

Product

1

/api2.0/v1/product/list

Get All Products

2

/api2.0/v1/product/query

Product Query

Listing

1

/api2.0/v1/product/publish/listing

Product Listing

Variant

1

/api2.0/v1/product/variant/queryByPid

Get Variants

2

/api2.0/v1/product/variant/queryByVid

Get Variants

Stock

1

/api2.0/v1/product/stock/queryByVid

Get Stock

03-Warehouse

Warehouse

04-Shopping

Order

1

/api2.0/v1/shopping/order/batchCreateOrder

Batch Create Orders

2

/api2.0/v1/shopping/order/queryById

Get Order Details

3

/api2.0/v1/shopping/order/confirm

Order Confirmation

Payment

1

/api2.0/v1/shopping/pay/getBalance

Get Balance

2

/api2.0/v1/shopping/pay/payBalance

Balance Payment

05-Logistics

Calculate

1

/api2.0/v1/logistic/freightCalculate

Freight Calculate

Tracking

2

/api2.0/v1/logistic/getTrackInfo

Track Query

2 Interface Usage

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/webhook.htm>
(<https://developers.cjdropshipping.cn/en/api/api2/api/webhook.htm>)

8. Webhook | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 Global Error Codes

Appendix 2 Country Code

Appendix 3 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

1 Setting

1.1 Message Setting (POST)

8. Webhook

1 Setting

Webhook Configuration Requirements

1. Protocol Requirements

Supported Protocols

: HTTPS

Encryption

: TLS 1.2 or TLS 1.3 recommended for secure transmission

Request Method

: POST

Content Type

:

Content-Type: application/json

2. Response Specifications

Success Status Code

:

200 OK

Timeout

: Response must be returned within

3 seconds

(Avoid long-running or complex business logic to ensure prompt response)

1.1 Message Setting (POST)

URL

<https://developers.cjdropshipping.com/api2.0/v1/webhook/set> (<https://developers.cjdropshipping.com/api2.0/v1/webhook/set>)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/webhook/set'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--header 'Content-Type: application/json'
--data-raw '{ "product": { "type": "ENABLE", "callbackUrls": [ "https://your-host/api2.0/" ] }, "stock": { "type": "ENABLE", "callbackUrls": [ "https://your-host/api2.0/" ] }, "order": { "type":
"ENABLE", "callbackUrls": [ "https://your-host/api2.0/" ] }, "logistics": { "type": "ENABLE", "callbackUrls": [ "https://your-host/api2.0/" ] } }'
```

Parameter

Definition

Type

Required

Length

Note

product

Product Message

object

Y

200

Product Message Setting

- type

Product Message type

string

Y

200

ENABLE¼CANCEL

- callbackUrls

callback url

string[]

Y

1

stock

Stock Message

object

Y

200

Stock Message Setting

- type

Stock Message type

string

Y

200

ENABLE¼CANCEL

- callbackUrls

callback url

string[]

Y

1

order

Order Message

object

Y

200

Order Message Setting

- type

Message type

string

Y

200

ENABLE?%ICANCEL

- callbackUrls

callback url

string[]

Y

1

logistics

Logistics Message

object

Y

200

Logistics Message Setting

- type

Message type

string

Y

200

ENABLE?%ICANCEL

- callbackUrls

callback url

string[]

Y

1

Result

success

```
{ "code": 200, "result": true, "message": "Success", "data": true, "requestId": "97367e0f-cf3a-4c9b-acea-a36fb56f81b8" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

error

```
{ "code": 1601000, "result": false, "message": "User not find", "data": null, "requestId": "a18c9793-7c99-42f9-970b-790eecdceba2" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

7 Dispute

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/storage.html>
(<https://developers.cjdropshipping.cn/en/api/api2/api/storage.html>)

4. Storage | C.J Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 174157 Global Error Codes

Appendix 2 174157 Country Code

Appendix 3 174157 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

1 Storage Info

1.1 Get Storage Info (GET)

5 Shopping

6 Logistic

7 Dispute

8 Webhook

4. Storage

1 Storage Info

1.1 Get Storage Info (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/warehouse/detail> (<https://developers.cjdropshipping.com/api2.0/v1/warehouse/detail>)

CURL

```
curl --location 'https://developers.cjdropshipping.com/api2.0/v1/warehouse/detail?id=201e67f6ba4644c0a36d63bf4989dd70'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx' \
```

Parameter

Definition

Type

Required

Length

Note

id

Storage ID

string

Y

200

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "id": "201e67f6ba4644c0a36d63bf4989dd70", "name": "Cranbury Warehouse", "areald": 2, "areaCountryCode": "US",  
"address1": "Cranbury, New Jersey ", "address2": null, "contacts": null, "phone": "+1-9095862127", "city": "Cranbury", "province": "New Jersey", "logisticsBrandList": [ { "id": "USPS",  
"name": "USPS" }, { "id": "FedEx", "name": "FedEx" }, { "id": "UPS", "name": "UPS" }, { "id": "GOFO", "name": "GOFO" }, { "id": "DHL", "name": "DHL" }, { "id": "UniUni", "name":  
"UniUni" }, { "id": "CBT", "name": "CBT" } ], "isSelfPickup": null, "zipCode": null, "requestId": "2b97f15603384fe4832e85617cf07d9c", "success": true }
```

Field

Definition

Type
Length
Note
id
Storage Id
string
200
name
name
string
200
areald
area id
integer
200
areaCountryCode
country code
string
200
province
province
string
200
city
city
string
200
address1
address1
string
200
address2
address2
string
200
contacts
contacts
string
200

	phone
	phone number
	string
	200
	isSelfPickup
	Is support self pickup
	integer
	1
	1: support 0: not supported
	zipCode
	zip Code
	string
	200
	logisticsBrandList
	Supported logistics brands
	list
	200
• id	
	Logistics brand ID
	string
	200
• name	
	Logistics brand Name
	string
	200
	error
	{ "code": 1608001, "result": false, "message": "Warehouse info not found", "data": null, "requestId": "c5d92fbc9c794c5caa0ce453dd9c9236", "success": false }
	Field
	Definition
	Type
	Length
	Note
	code
	error code
	int
	20
	Reference error code
	result
	Whether or not the return is normal

boolean
1
message
return message
string
200
data
return data
object
interface data return
requestId
requestId
string
48
Flag request for logging errors
⌂
3 Product
5 Shopping
⌂

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/product.html>
(<https://developers.cjdropshipping.cn/en/api/api2/api/product.htm>

3 Product | CJ Docs
Introduction
Start
Development
Get Access-token
Practical Tool
Platform Waybill Order Processing
Webhook
Sandbox
API
Standard
Interface Definition
Interface Field Definition
Interface Call Restrictions
Appendix 1 全球通用错误码
Appendix 2 国家代码

Appendix 3174127 Platforms

Interface

1 Authentication

2 Setting

3 Product

1 Products

1.1 Category List(GET)

1.2 Product List V2(GET)

1.3 Global Warehouse List(GET)

1.4 Product List(GET)

1.3 Product Details(GET)

1.4 Add to My Product (POST)

1.3 My Product List(GET)

2 Variant

2.1 Inquiry Of All Variants (GET)

2.2 Variant Id Inquiry (GET)

3 Inventory

3.1 Inventory Inquiry(GET)

3.2 Query Inventory by SKU (GET)

3.3 Query inventory by product ID (GET)

4 Product Reviews

4.1 Inquiry Reviews (GET)

4.2 Inquiry Reviews (GET)

5 Sourcing

5.1 Create Sourcing (POST)

5.2 Query Sourcing(POST)

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

3 Product

1 Products

1.1 Category List(GET)

Get product categories from CJ.

URL

https://developers.cjdropshipping.com/api2.0/v1/product/getCategory_(<https://developers.cjdropshipping.com/api2.0/v1/product/getCategory>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/getCategory'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "categoryFirstName": "Computer & Office", "categoryFirstList": [ { "categorySecondName": "Office Electronics",
"categorySecondList": [ { "categoryId": "2252588B-72E3-4397-8C92-7D9967161084", "categoryName": "Office & School Supplies" }, ... ] }
], "requestId": "ae543fd1-cdd7-4a61-974a-1340fea678c6" }
```

Field

Definition

Type

Length

Note

categoryFirstName

First level category name

string

200

categoryFirstList

First level category list

Array

-

categorySecondName

Second level category name

string

200

categorySecondList

Second level category list

Array

-

categoryId

Third level category ID

string

200

categoryName

Third level category name

string

200

error

```
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.2 Product List V2(GET)

Get all available products from CJ with criteria inquiry supported. V2 version uses elasticsearch search engine for higher performance product search capabilities.

Note:

Supports keyword search

Supports multiple filter conditions such as price range, category, country, etc.

Supports sorting functionality

Through the features parameter, you can selectively return product details and category information

page minimum value 1, maximum value 1000; size minimum value 1, maximum value 100

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/listV2> (<https://developers.cjdropshipping.com/api2.0/v1/product/listV2>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/listV2?page=1&size=20&keyWord=hoodie'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

keyWord

Search keyword

string

N

200

Product name or SKU keyword search

page

Page number

int

N

20

Default 1, minimum 1, maximum 1000

size

Quantity of results on each page

int

N

20

Default 10, minimum 1, maximum 100

categoryId

Category ID

string

N

200

Filter products by third level category ID

lv2categoryList

Second level category ID list

array

N

Filter products by second level category ID list

lv3categoryList

Third level category ID list

array

N

Filter products by third level category ID list

countryCode

Country code

string

N

200

Format: CN,US,GB,FR etc., filter products with inventory in specified countries

startSellPrice

Start sell price

decimal

N

Price filter start value

endSellPrice

End sell price

decimal

N

Price filter end value

addMarkStatus

Is free shipping

int

N

1

0-not free shipping, 1-free shipping

productType

Product type

int

N

15

4-Supplier product, 10-Video product, 11-Non-video product

productFlag

Product flag

int

N

1

0-Trending products, 1-New products, 2-Video products, 3-Slow-moving products

startWarehouseInventory

Start warehouse inventory

int

N

Filter products with inventory greater than or equal to this value

endWarehouseInventory

End warehouse inventory

int

N

Filter products with inventory less than or equal to this value

verifiedWarehouse

Verified warehouse type

int

N

1

null/0-All(default), 1-Verified inventory, 2-Unverified inventory

timeStart

Listing time filter start

long

N

Listing start time timestamp (milliseconds)

timeEnd

Listing time filter end

long

N

Listing end time timestamp (milliseconds)

zonePlatform

Zone platform suggestion

string

N

200

Such as: shopify,ebay,amazon,tiktok,etsy etc.

isWarehouse

Is global warehouse search

boolean

N

1

true=yes, false=no

currency

Currency

string

N

10

Such as: USD,AUD,EUR etc.

sort

Sort direction

string

N

4

desc-descending(default) / asc-ascending

orderBy

Sort field

int

N

20

0=best match(default); 1=listing count; 2=sell price; 3=create time; 4=inventory

features

Features list

array

N

200

Supported values: enable_description(return product details), enable_category(return product category information), enable_combine(return combine product info), enable_video(return video IDs)

supplierId

Supplier ID

string

N

200

Filter products by supplier ID

hasCertification

Has certification

int

N

1

0-No, 1-Yes

isSelfPickup

Is self pickup

int

N

1

0-No, 1-Yes

customization

Is customization product

int

N

1

0-No, 1-Yes

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "pageSize": 20, "pageNumber": 1, "totalRecords": 1000, "totalPages": 50, "content": [ { "productList": [ { "id": "04A22450-67F0-4617-A132-E7AE7F8963B0", "nameEn": "Personalized Belly-baring Cat Ear Hoody Coat", "sku": "CJNSSYWY01847", "spu": "CJNSSYWY01847", "bigImage": "https://cc-west-usa.oss-us-west-1.aliyuncs.com/20210129/2167381084610.png", "sellPrice": "11.85", "nowPrice": "9.50", "listedNum": 100, "categoryId": "5E656DFB-9BAE-44DD-A755-40AFA2E0E686", "threeCategoryName": "Hoodies & Sweatshirts", "twoCategoryId": "5E656DFB-9BAE-44DD-A755-40AFA2E0E685", "twoCategoryName": "Tops & Sets", "oneCategoryId": "5E656DFB-9BAE-44DD-A755-40AFA2E0E684", "oneCategoryName": "Women's Clothing", "addMarkStatus": 1, "isVideo": 0, "videoList": [], "productType": "ORDINARY_PRODUCT", "supplierName": "", "createAt": 1609228800000, "warehouseInventoryNum": 500, "totalVerifiedInventory": 500, "totalUnVerifiedInventory": 0, "verifiedWarehouse": 1, "customization": 0, "hasCECertification": 0, "isCollect": 0, "myProduct": false, "currency": "USD", "discountPrice": "9.50", "discountPriceRate": "20", "description": "Product description...", "deliveryCycle": "3-5", "saleStatus": "3", "authorityStatus": "1", "isPersonalized": 0 }, { "categoryId": "xxx", "categoryName": "Hoodies" } ], "keyWord": "hoodie", "keyWordOld": "hoodie" } ] }, "requestId": "f95cd31d-3907-47ce-ac1a-dfdee4315960" }
```

Field

Definition

Type

Length

Note

pageSize

Page size

long

20

Number of products per page

pageNumber

Current page number

long

20

Current requested page number, starts from 1

totalRecords

Total records

long

20

Total number of products matching criteria

totalPages

Total pages

long

20

Total pages

content

Content list

array

Product data list

CjProductInfoSearchV2DTO object in content:

Field

Definition

Type

Length

Note

productList

Product list

array

Product information array

relatedCategoryList

Related category list

array

Related categories matched by search keyword list

keyWord

Search keyword

string

200

Actual search keyword used

keyWordOld

Original search keyword

string

200

Original search keyword entered by user

Product object in productList:

Field

Definition

Type

Length

Note

id

Product ID

string

200

Unique product identifier

nameEn

Product name (English)

string

200

Product English name

sku

Product SKU

string

200

Product SKU code

spu

Product SPU

string

200

Product SPU code, same as SKU

bigImage

Product main image

string

200

Product main image URL

sellPrice

Sell price

string

20

Product sell price, unit: USD

nowPrice

Discount price

string

20

Product discount price

discountPrice

Best discount price

string

20

Best discount price

discountPriceRate

Discount rate

string

20

Discount percentage

listedNum

Listed number	int	20
Number of times this product is listed on the platform	isCollect	Is collected
	int	1
	0-not collected, 1-collected	
	categoryId	Third level category ID
	string	200
	Product third level category ID	
	threeCategoryName	Third level category name
	string	200
Third level category name (returned only when features contains enable_category)	twoCategoryId	Second level category ID
	string	200
	Product second level category ID	
	twoCategoryName	Second level category name
	string	200
Second level category name (returned only when features contains enable_category)	oneCategoryId	First level category ID
	string	200
	Product first level category ID	
	oneCategoryName	First level category name
	string	200
First level category name (returned only when features contains enable_category)		

addMarkStatus

Is free shipping

int

1

0-not free shipping, 1-free shipping

isVideo

Has video

int

1

0-no video, 1-has video

videoList

Video ID list

array

Product video ID collection (returned only when features contains enable_video)

productType

Product type

string

20

Product type code

supplierName

Supplier name

string

200

Product supplier name

createAt

Create time

long

20

Product create timestamp (milliseconds)

setRecommendedTime

Recommended time

long

20

Set recommended timestamp

warehouseInventoryNum

Warehouse inventory number

long

20

Total inventory number

totalVerifiedInventory

Total verified inventory

int

20

Total verified inventory

totalUnVerifiedInventory

Total unverified inventory

int

20

Total unverified inventory

verifiedWarehouse

Verified warehouse identifier

int

1

1-Verified inventory, 2-Unverified inventory

customization

Is customization product

int

1

0-No, 1-Yes

isPersonalized

Is personalized customization

int

1

0-No, 1-Yes

hasCECertification

Has CE certification

int

1

0-No, 1-Yes

myProduct

Is added to my products

boolean

1

true-added, false-not added

currency

Currency

string

10

Such as: USD, AUD, EUR etc.

description

Product description

string

2000

Detailed product description (returned only when features contains enable_description)

deliveryCycle

Delivery cycle

string

20

Product delivery cycle in days

saleStatus

Sale status

string

2

3-approved for sale

authorityStatus

User visible permission

string

1

0-private visible, 1-all visible

autStatus

Product visibility

string

1

Product visibility status

isAut

Is permanent private

string

1

0-not permanent private, 1-permanent private

isList

Is listed

int

1

0-not listed, 1-listed

syncListedProductStatus

Listing status

string

1

0-pending, 1-listing, 2-failed, 3-success, 4-cancelled

isAd

Is advertisement product

int

1

0-not ad, 1-ad product

activityId

Advertisement product ID

string

200

Advertisement activity ID

directMinOrderNum

Minimum order quantity

string

20

Minimum order quantity

zoneRecommend.Json

Zone recommend list

set

Zone recommend tag collection

inventoryInfo

Warehouse inventory info

string

Warehouse inventory details JSON

variantKeyEn

Variant property

string

200

Variant property English description

variantInventories

Variant inventory info

string

Variant inventory details JSON

propertyKey

Product logistics property key

string

200

Product logistics property keywords

Product Type

Product Type

Description

Note

ORDINARY_PRODUCT

Ordinary product, managed by CJ for inventory management

Managed by CJ for inventory and shipping

SERVICE_PRODUCT

Service product, If you need to transfer your own goods to CJ warehouse and CJ provides warehousing services, we will mark it as a service item

Your own products with CJ warehousing services

PACKAGING_PRODUCT

Packaging product are used for packaging when shipped from the warehouse. They do not support separate shipping and need to be shipped together with other goods

For packaging only, cannot be sold separately

SUPPLIER_PRODUCT

Supplier product, It is a merchant that collaborates with CJ to manage inventory of goods

Supplier products, managed and shipped by CJ

SUPPLIER_SHIPPED_PRODUCT

Shipped by supplier management

Supplier products, managed and shipped by suppliers

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

Error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

Return message

string

200

data

Return data

object

Business data

requestId

Request ID

string

48

Flag request for logging errors

1.3 Global Warehouse List(GET)

Get the list of all available global warehouses.

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/globalWarehouseList> (<https://developers.cjdropshipping.com/api2.0/v1/product/globalWarehouseList>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/globalWarehouseList'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Request Parameters

No parameters required

Return

SUCCESS

```
{ "code": 200, "success": true, "message": "Success", "data": [ { "areaCn": "à,â,ä,ö,ü,ä,ö,ü", "areaEn": "China Warehouse", "areald": 1, "countryCode": "CN", "nameEn": "China", "valueEn": "CN", "disabled": false, "zh": "à,â,ä,ö,ü,ä,ö,ü", "en": "China Warehouse", "de": "China-Lager", "fr": "Entrepôt à Chine", "th": "à,â,ä,ö,ü,ä,ö,ü,ä,ö,ü,ä,ö,ü", "id": "1" }, { "areaCn": "ç,ç,ä,ö,ü,ä,ö,ü", "areaEn": "US Warehouse", "areald": 2, "countryCode": "US", "nameEn": "United States", "valueEn": "US", "disabled": false, "zh": "ç,ç,ä,ö,ü,ä,ö,ü", "en": "US Warehouse", "de": "US-Lager", "fr": "Entrepôt à mÄ©ricain", "th": "à,â,ä,ö,ü,ä,ö,ü,ä,ö,ü,ä,ö,ü,ä,ö,ü,ä,ö,ü", "requestId": "ae543fd1-cdd7-4a61-974a-1340f6a678c6" }
```

Field

Definition

Type

Length

Note

areaCn

Warehouse name (CN)

string

200

Chinese name of the warehouse

areaEn

Warehouse name (EN)

string

200

English name of the warehouse

areald

Warehouse ID

int

20

Unique warehouse identifier

countryCode

Country code

string

10

ISO country code, e.g., CN, US, GB

nameEn

Country name (EN)

string

200

English name of the country

valueEn

Warehouse code

string

10

Warehouse code value, usually matches country code

disabled

Is disabled

boolean

1

true-disabled, false-available

zh

Chinese name

string

200

Multi-language support - Chinese

en

English name

string

200

Multi-language support - English

de

German name

string

200

Multi-language support - German

fr
French name
string
200
Multi-language support - French
th
Thai name
string
200
Multi-language support - Thai
id
Warehouse string ID
string
20
String format of warehouse ID
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
Error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
Return message
string
200
data
Return data
object
Business data

requestId

Request ID

string

48

Flag request for logging errors

1.4 Product List(GET)

Get all available products from CJ, criteria inquiry supported. 20 results for each page, fixed.

Note:

Maximum return of 200 data per page.

Free users or v1 users are limited to a maximum of 1000 requests per day.(2024-09-30 update)

One IP is limited to a maximum of three users.(2024-09-30 update)

Query the product list and add "deliveryTime" field (hours). The values are 24, 48, 72, or null (2024-11-15 update)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/list> (<https://developers.cjdropshipping.com/api2.0/v1/product/list>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/list'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pageNum

Page number

int

N

20

Default 1, specifies the page number of the product list to retrieve

pageSize

Quantity of results on each page

int

N

20

Default 20, number of products returned per page, maximum 200

categoryId

category id

string

N

200

Inquiry criteria, filter products by category ID

pid

Product id

string

N

200

Filter products by unique product identifier

productSku

Product sku

string

N

200

Filter products by SKU

productName

Product name

string

N

200

Fuzzy match by product Chinese name

productNameEn

Product name(en)

string

N

200

Fuzzy match by product English name

productType

Product type

string

N

200

Optional values: ORDINARY_PRODUCT, SUPPLIER_PRODUCT - Returns all types if not provided

countryCode

countryCode

string

N

200

Example: CN, US - Filter products with inventory in specified countries

deliveryTime

Delivery Time (hours)

string

N

200

Optional values: 24 (ships within 24 hours), 48 (ships within 48 hours), 72 (ships within 72 hours) - Returns only products meeting the specified delivery time

verifiedWarehouse

Verified Inventory Type

number

N

1

Optional values: 1 (Verified), 2 (Unverified) - Not passing values means not restricting queries based on that type

startInventory

the minimum inventory

number

N

eg: 2, filter products with inventory greater than or equal to this value

endInventory

the highest inventory

number

N

eg: 10, filter products with inventory less than or equal to this value

createTimeFrom

create time(start)

string

N

200

format: yyyy-MM-dd hh:mm:ss, filter products created after this time

createTimeTo

create time(end)

string

N

200

format: yyyy-MM-dd hh:mm:ss, filter products created before this time

brandOpenId

brand id

long

N

200

Inquiry criteria, filter by brand ID

minPrice

minimum price

number

N

200

Example: 1.0 - Filter products with price greater than or equal to this value

maxPrice

maximum price

number

N

200

Example: 2.5 - Filter products with price less than or equal to this value

searchType

Search Type

number

N

5

Optional values: 0 (All products), 2 (Trending Products), 21 (Trending Products View More) - Default is 0

minListedNum

Minimum Listed Num

number

N

10

Example: 1 - Returns products with listing count greater than or equal to this value

maxListedNum

Maximum Listed Num

number

N

10

Example: 10 - Returns products with listing count less than or equal to this value

sort

Sort Type

string

N

4

Optional values: desc (descending order), asc (ascending order) - Default: desc

orderBy

Sort field

string

N

20

Optional values: createAt (sort by creation time), listedNum (sort by listing count) - Default: createAt

isSelfPickup

Does the product support self pickup

number

N

1

Optional values: 1 (supported), 0 (not supported)

supplierId

Supplier Id

string

N

40

Filter products by supplier ID

isFreeShipping

Is Free Shipping?

int

N

1

Optional values: 0 (not free), 1 (free shipping)

customizationVersion

Customization Version

int

N

1

Optional values: 1 (Platform Customized Version V1), 2 (Platform Customized Version V2), 3 (Customer Customized Version V1), 4 (Customer Customized Version V2), 5 (POD 3.0 Platform Customized) - Filter POD products by customization version

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "pageNum": 1, "pageSize": 20, "total": 1, "list": [ { "pid": "04A22450-67F0-4617-A132-E7AE7F8963B0", "productName": "[\"çf«è(²æçµâ)«èj£\", \"â@r-â¶jâ)«èj£\", \"â, \"æ($âf«â@r-â¶jâ)\"], \"productNameEn\": \"Personalized Belly-baring Cat Ear Hoody Coat\", \"productSku\": \"CJNSSYWY01847\", \"productImage\": \"https://cc-west-usa.oss-us-west-1.aliyuncs.com/20210129/2167381084610.png\", \"productWeight\": 0, \"productType\": null, \"productUnit\": \"unit(s)\", \"sellPrice\": 11.85, \"categoryId\": \"5E656DFB-9BAE-44DD-A755-40AFA2E0E686\", \"categoryName\": \"Women's Clothing / Tops & Sets / Hoodies & Sweatshirts\", \"remark\": \"\", \"createTime\": null, \"customizationVersion\": 1 } ] }, \"requestId\": \"f95cd31d-3907-47ce-ac1a-dfdee4315960\" }
```

Field

Definition

Type

Length

Note

pageNum

Page number	
int	
20	
Current page number	
pageSize	
Quantity of results on each page	
int	
20	
Number of products per page	
total	
Total quantity of results	
int	
20	
Total number of products matching criteria	
list	
Product list	
Product[]	
List of product data	
pid	
Product ID	
string	
200	
Unique product identifier	
productName	
Product name	
string	
200	
Product Chinese name, may be a JSON array string with multiple names	
productNameEn	
Product name(EN)	
string	
200	
Product English name	
productSku	
Product sku	
string	
200	
Product SKU code	
productImage	

Product image	
string	
200	
Product main image URL	
productWeight	
Product weight	
int	
200	
Unit: g	
productType	
Product type	
byte	
200	
Product type code	
productUnit	
Product unit	
string	
48	
Product selling unit	
categoryId	
Category id	
string	
200	
Product category ID	
categoryName	
Category name	
string	
200	
Product category name	
remark	
Remark	
string	
200	
Product remark information	
addMarkStatus	
Is shipping free? (Deprecated, please use isFreeShipping)	
int	
1	
0=Not free shipping, 1=free shipping	

isFreeShipping

Is shipping free?

boolean

1

true for free shipping, false for paid shipping

listedNum

Listed number

int

200

Number of listings for this product on the platform

supplierName

Supplier name

string

200

Product supplier name

supplierId

Supplier id

string

200

Product supplier ID

sellPrice

Sell price

decimal

-

Product selling price

createTime

Create time

string

-

Product creation time on the platform

isVideo

Has video

int

1

1 means includes video, 0 means no video

saleStatus

Sale status

int

20

3 means approved for sale

customizationVersion

Customization Version

int

1

Custom product version number

Product Type

Product Type

Description

ORDINARY_PRODUCT

Ordinary product, If managed by CJ for inventory management

SERVICE_PRODUCT

Service product, If you need to transfer your own goods to CJ warehouse and CJ provides warehousing services, we will mark it as a service item;

PACKAGING_PRODUCT

Packaging product are used for packaging when shipped from the warehouse. They do not support separate shipping and need to be shipped together with other goods;

SUPPLIER_PRODUCT

Supplier product, It is a merchant that collaborates with CJ to manage inventory of goods

SUPPLIER_SHIPPED_PRODUCT

shipped by supplier management

Product Status

Status Code

Description

3

On Sale

Customization Version

Customization Version

remark

0

Non-pod products

1

Platform Customized Version V1

2

Platform Customized Version V2

3

Customer Customized Version V1

4

Customer Customized Version V2

5

POD 3.0 Platform Customized

Error

```
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.3 Product Details(GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/query> (<https://developers.cjdropshipping.com/api2.0/v1/product/query>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/query?pid=000B9312-456A-4D31-94BD-B083E2A198E8'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pid

Product id

string

Choose one of pid, productSku, variantSku

200

Inquiry criteria, unique product identifier

productSku

Product sku

string

Choose one of pid, productSku, variantSku

200

Inquiry criteria, product SPU code

variantSku

variant sku

string

Choose one of pid, productSku, variantSku

200

Inquiry criteria, variant SKU code

features

features

List

N

200

Optional values: `enable_combine` (includes combination variants, returns combination product info when passed), `enable_video` (includes videos, returns product video info when passed), `enable_inventory` (includes inventory, returns variant inventory info (include storage id) when passed)

countryCode

Country Code

string

N

2

Country code such as CN, US - Only returns variants with inventory in that country, no restriction if not passed

Return

Success

```

{"code": 200, "result": true, "message": "Success", "data": {"pid": "000B9312-456A-4D31-94BD-B083E2A198E8", "productName": "【小拖车】拖车", "productNameEn": "Small trailer model", "productSku": "CJJJJJT05843", "productImage": "https://cc-west-usa.oss-us-west-1.aliyuncs.com/2054/1672872416690.jpg", "productWeight": "1500.0", "productUnit": "unit(s)", "productType": "ORDINARY_PRODUCT", "categoryId": "87CF251F-8D11-4DE0-A154-9694D9858EB3", "categoryName": "Home & Garden, Furniture / Home Storage / Home Office Storage", "entryCode": "8712008900", "entryName": "拖车", "entryNameEn": "model", "materialName": "【塑料】", "materialNameEn": "plastic", "materialKey": "METAL", "packingWeight": "1580.0", "packingName": "拖车", "packingNameEn": "plastic_bag", "packingKey": "PLASTIC_BAG", "productKey": "拖车", "productKeyEn": "Color", "productPro": "拖车", "productProSet": "拖车", "productProEn": "COMMON", "productProEnSet": "COMMON", "sellPrice": 58.09, "description": "...", "suggestSellPrice": "0.97-4.08", "listNum": 392, "status": "3",

```

"supplierName": "", "supplierId": "", "customizationVersion": 1, "customizationJson1": "", "customizationJson2": "", "customizationJson3": "", "customizationJson4": "", "variants": [{
"vid": "D4057F56-3F09-4541-8461-9D76D014846D", "pid": "000B9312-456A-4D31-94BD-B083E2A198E8", "variantName": null, "variantNameEn": "Small trailer model Black",
"variantSku": "CJJJJTJT05843-Black", "variantUnit": null, "variantProperty": null, "variantKey": "Black", "variantLength": 300, "variantWidth": 200, "variantHeight": 100,
"variantVolume": 6000000, "variantWeight": 1580.00, "variantSellPrice": 58.09, "createTime": "2019-12-31T11:14:12.000+00:00" "variantStandard": "long=110,width=110,height=30",
"variantSugSellPrice": 0.97 "combineVariants":[], "inventories": [{ { "countryCode": "CN", "totalInventory": 12912, "cjInventory": 0, "factoryInventory": 12912, "verifiedWarehouse": 2,
"stock": [{ { "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}", "inventory": 0, "factoryInventory": 12912 } }] } }], "creatorTime": "2019-12-24T01:06:37+08:00" },
"requestId": "d8dc0b6d-0ed8-4e19-8f63-3f207ac39832" }

Product

Field

Definition

Type

Length

Note

pid

Product ID

string

200

Unique product identifier

productName

Product name

string

20

Product Chinese name, in JSON array format

productNameEn

Product name(EN)

string

200

Product English name

productSku

Product sku

string

200

Product SKU code

productImage

Product image

string

200

Product main image URL

productWeight

Product weight

int

200	
Unit: g	
productType	
Product type	
byte	
200	
Product type code	
productUnit	
Product unit	
string	
48	
Product selling unit	
categoryId	
Category id	
string	
200	
Product category ID	
categoryName	
Category name	
string	
200	
Product category name	
entryCode	
HS code	
string	
200	
Product customs code	
entryName	
Customs name	
string	
200	
Product customs Chinese name	
entryNameEn	
Customs name (EN)	
string	
200	
Product customs English name	
materialName	
Material	

string

200

Product material Chinese name

materialNameEn

Material (EN)

string

200

Product material English name

materialKey

Material attribute

string

200

Product material attribute keywords

packWeight

Package weight

int

200

Unit: g, total weight including packaging

packingName

Package name

string

200

Packaging material Chinese name

packingNameEn

Package name (EN)

string

200

Packaging material English name

packingKey

Package attribute

string

200

Packaging material attribute keywords

productKey

Product attribute

string

200

Product attribute keywords

productKeyEn

Product attribute (EN)	
	string
	200
Product attribute English keywords	
	productProSet
Product logistics attributes(Chinese)	
	string[]
Chinese description of product logistics attributes	
	productProEnSet
Product logistics attributes(English)	
	string[]
English description of product logistics attributes	
	addMarkStatus
Is Free Shipping?	
	int
	1
0=not Free, 1=Free	
	description
	Description
	string
	200
Detailed product description	
	sellPrice
	sell price
	string
	200
Product selling price	
	creatorTime
	creator time
	string
	20
Product creation time on the platform	
	productVideo
Product video ID list	
	string[]
	200
If the product contains videos and features are passed in enable_video, it will return	
	status
	status

string

20

3 means approved for sale

suggestSellPrice

suggest sell price

string

20

Suggested retail price range

listedNum

listed number

int

20

Number of listings for this product

supplierName

supplier name

string

20

Product supplier name

supplierId

supplier Id

string

20

Product supplier ID

customizationVersion

customization version

int

20

Custom product version number

customizationJson1

customization json

string

200

Custom information JSON data 1

customizationJson2

customization json

string

200

Custom information JSON data 2

customizationJson3

customization json

string

200

Custom information JSON data 3

customizationJson4

customization json

string

200

Custom information JSON data 4

variants

Variants

Variant[]

List of product variants

Variant

Field

Definition

Type

Length

Note

vid

Variant Id

string

200

Unique variant identifier

pid

Product Id

string

20

Parent product identifier

variantName

Variant Name

string

200

Variant Chinese name

variantNameEn

Variant Name(en)

string

200

Variant English name

variantSku	
Variant SKU	
string	
200	
Variant SKU code	
variantImage	
Variant Image	
string	
200	
Variant image URL	
variantStandard	
Variant Standard	
string	
200	
Variant specification description	
variantUnit	
Variant Unit	
string	
200	
Variant selling unit	
variantProperty	
Variant Property	
string	
200	
Variant property type	
variantKey	
Variant Key	
string	
200	
Variant attribute keywords	
variantLength	
Variant Length	
int	
200	
Unit: mm	
variantWidth	
Variant Width	
int	
200	

	Unit: mm
variantHeight	
Variant Height	
	int
	200
	Unit: mm
variantVolume	
Variant Volume	
	int
	200
	Unit: mm3
variantWeight	
Variant Weight	
	double
	200
	Unit: g
variantSellPrice	
Variant SellPrice	
	double
	200
	unit: \$ (USD)
variantSugSellPrice	
Variant Suggest SellPrice	
	double
	200
	unit: \$ (USD)
createTime	
Vreater Time	
	string
	200
Variant creation time	
combineNum	
number of Combine Variants	
	int
Number of sub-variants in combined products	
combineVariants	
Combine Variants	
Variant[]	
	200

List of sub-variants for combined products

inventories

Variant inventory

Inventory[]

200

List of variant inventory (include storage id)

- countryCode

inventory country code

string

200

Two-letter code of the country where the warehouse is located.for example:US

- totalInventory

total inventory number

integer

200

- cjInventory

Inventory management in CJ warehouse

integer

200

- factoryInventory

Inventory management in factory

integer

200

- verifiedWarehouse

Verified Inventory type

string

200

1: verified, 2: unverified

- stock

Sub warehouse inventory info

Stock[]

200

-- stockId

Sub warehouse ID

string

200

-- inventory

Sub warehouse Inventory management in CJ warehouse

integer

200

-- factoryInventory

Sub warehouse Inventory management in factory

integer

200

Product Type

Product Type

Description

ORDINARY_PRODUCT

Ordinary product

SERVICE_PRODUCT

Service product

PACKAGING_PRODUCT

Packaging product

SUPPLIER_PRODUCT

Supplier product

SUPPLIER_SHIPPED_PRODUCT

Supplier shipped product

Product Status

product status

remark

3

On Sale

Customization Version

Customization Version

remark

0

Non-pod products

1

Platform Customized Version V1

2

Platform Customized Version V2

3

Customer Customized Version V1

4

Customer Customized Version V2

5

POD 3.0 Platform Customized

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.4 Add to My Product (POST)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/addToMyProduct> (<https://developers.cjdropshipping.com/api2.0/v1/product/addToMyProduct>)

CURL

```
curl --location 'http://localhost:8081/api2.0/v1/product/addToMyProduct'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--header 'Content-Type: application/json'
--data '{ "productId": "1658748072937136128" }'
```

Parameter

Definition

Type

Required

Length
Note
productId
CJ product id
string
Y
100
Return
success
{ "code": 200, "result": true, "message": "Success", "data": true, "requestId": "a7d4d01b1eed4db9ac2cc1ab7903c98c", "success": true }
error
{ "code": 1600000, "result": false, "message": "The product has been added to My Products.", "data": null, "requestId": "b626475ff68242c3abfea562f9d4f899", "success": false }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
return message
string
200
data
return data
object
interface data return
requestId
requestId
string
48
Flag request for logging errors

1.3 My Product List(GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/myProduct/query> (<https://developers.cjdropshipping.com/api2.0/v1/product/myProduct/query>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/myProduct/query?keyword=CJWJWJYZ02543'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

keyword

sku/spu/product name

string

N

200

categoryId

category id

string

N

200

startAt

start time

string

N

200

endAt

ent time

string

N

200

isListed

isListed

int

N

200

visiable

visiable

int
N
200
hasPacked
hasPacked
int
N
200
hasVirPacked
hasVirPacked
int
N
200
Return
success
{ "code": 200, "result": true, "message": "Success", "data": { "pageSize": 10, "pageNumber": 1, "totalRecords": 536, "totalPages": 54, "content": [{ "productId": "01118E21-A8B9-45CE-A16C-75232FB8A14A", "packWeight": "530.0", "weight": "480.0", "productType": "0", "propertyKeyList": ["COMMON"], "bigImage": "https://cf.cjdropshipping.com/15926688/9714688036284.jpg", "nameEn": "3D wooden three-dimensional puzzle", "sku": "CJWJWJMJM00719", "hasPacked": 0, "sellPrice": "2.4", "discountPrice": null, "discountPriceRate": null, "defaultArea": "China Warehouse", "shopMethod": "CAI NIAO", "trialFreight": "0", "totalPrice": "2.40", "listedShopNum": "0", "vid": "7986724D-7214-4B4B-A184-493E7BD78F47", "areald": "1", "areaCountryCode": "CN", "freightDiscount": "0", "createAt": 1743218214000, "lengthList": [335, 335], "heightList": [200, 200], "widthList": [225, 225], "volumeList": [15075000, 15075000], "hasVirPacked": 1 }] }, "requestId": "b0f251412bd0446cb56ba5988706d964", "success": true }
product
Field
Definition
Type
Length
Note
productId
Product ID
string
200
productName
Product name
list
20
nameEn
Product name(EN)
string
200
sku
Product sku

string
200
bigImage
Product image
string
200
totalPrice
Product weight
double
200
unit: \$ (USD)
productType
Product type
byte
200
listedShopNum
listed Shop Num
string
48
createAt
Added Time
string
200
trialFreight
trial Freight
string
200
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

2 Variant

2.1 Inquiry Of All Variants (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/variant/query> (<https://developers.cjdropshipping.com/api2.0/v1/product/variant/query>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/variant/query?pid=00006BC5-E1F5-4C65-BE2B-3FE0956DA21C'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pid

Product id

string

Choose one of three

200

Inquiry criteria

productSku

Product sku

string

200

Inquiry criteria

variantSku

variant sku

string

200
Inquiry criteria
countryCode
Country Code
string

2

Return

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "vid": "1D72A0DA-D113-4FAB-B4BA-8FE1A6A14A3A", "pid": "77501FB4-7146-452E-9889-CDF416975ECF",  
    "variantName": null, "variantNameEn": "Wwerwieurieowursklfjskldjfskjlsdjkflsdjksjdsklfdsfdfg XS", "variantSku": "CJJSBGBG01517-XS", "variantStandard":  
    "long=5,width=5,height=5", "variantUnit": null, "variantProperty": null, "variantKey": "[\"XS\"]", "variantLength": 5, "variantWidth": 5, "variantHeight": 5, "variantVolume": 27,  
    "variantWeight": 3.00, "variantSellPrice": 3.00, "createTime": null } ], "requestId": "00765963-35d0-4a6a-b5cf-a6731793b10" }
```

Definition

Type

Length

Note

vid

Variant ID

string

200

pid

Product ID

string

200

variantName

Variant name

string

200

variantNameEn

Variant name (EN)

string

200

variantImage

Variant image

string

200

variantSku

Variant sku

string

200

variantUnit

Variant unit

string

200

variantProperty

Variant property

string

200

variantKey

Variant Key

string

200

variantLength

Variant length

int

200

Unit: mm

variantWidth

Variant width

int

200

Unit: mm

variantHeight

Variant height

int

200

Unit: mm

variantVolume

Variant volume

int
200
Unit: mm3
variantWeight
Variant weight
int
200
Unit: g
variantSellPrice
Variant sell price
BigDecimal
200
Unit: \$ (USD)
createTime
Create time
string
200
variantStandard
variant standard
string
200
variantSugSellPrice
variant suggest sell price
BigDecimal
200
Unit: \$ (USD)
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

2.2 Variant Id Inquiry (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/variant/queryByVid> (<https://developers.cjdropshipping.com/api2.0/v1/product/variant/queryByVid>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/variant/queryByVid?vid=1371342252697325568'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

vid

Variant ID

string

Y

200

Inquiry criteria

features

features

string

N

200

enable_inventory (includes inventory, returns variant inventory info (include storage id) when passed)

Return
success
{ "code": 200, "result": true, "message": "Success", "data": { "vid": "1371342252697325568", "pid": "00006BC5-E1F5-4C65-BE2B-3FE0956DA21C", "variantName": null, "variantNameEn": "a-Baby pacifier chain test1 Grey", "variantSku": "CJJSBGDY00002-Grey", "variantUnit": null, "variantProperty": "[]", "variantKey": "Grey", "variantLength": 3, "variantWidth": 3, "variantHeight": 3, "variantVolume": 27, "variantWeight": 3.00, "variantSellPrice": 3.00, "createTime": "2021-03-15T14:07:26.000+00:00", "inventories": [{ "countryCode": "CN", "totalInventory": 11092, "cjlInventory": 0, "factoryInventory": 11092, "verifiedWarehouse": 2, "stock": [{ "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}", "inventory": 0, "factoryInventory": 11092 }] }] }, "requestId": "9b86a5e2-40c3-492c-92b2-4634fa4c4a21" }
Field
Definition
Type
Length
Note
vid
Variant id
string
200
pid
Product id
string
200
variantName
Variant name
string
200
variantNameEn
Variant name (EN)
string
200
variantImage
Variant image
string
200
variantSku
Variant sku
string
200
variantUnit
Variant unit
string

200

variantProperty

Variant property

string

200

variantKey

Variant key

string

200

variantLength

Variant length

int

200

Unit: mm

variantWidth

Variant width

int

200

Unit: mm

variantHeight

Variant height

int

200

Unit: mm

variantVolume

Variant volume

int

200

Unit: mm³

variantWeight

Variant weight

int

200

Unit: g

variantSellPrice

Variant sell price

BigDecimal

200

Unit: \$ (USD)

	createTime
	Create time
	string
	200
	variantStandard
	Variant standard
	string
	200
	inventories
	Variant inventory
	Inventory[]
	200
	List of variant inventory (include storage id)
• countryCode	
	inventory country code
	string
	200
	Two-letter code of the country where the warehouse is located.for example:US
• totalInventory	
	total inventory number
	integer
	200
• cjInventory	
	Inventory management in CJ warehouse
	integer
	200
• factoryInventory	
	Inventory management in factory
	integer
	200
• verifiedWarehouse	
	Verified Inventory type
	string
	200
	1: verified, 2: unverified
• stock	
	Sub warehouse inventory info
	Stock[]
	200

```
-- stockId

Sub warehouse ID

string

200

-- inventory

Sub warehouse Inventory management in CJ warehouse

integer

200

-- factoryInventory

Sub warehouse Inventory management in factory

integer

200

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string
```

Flag request for logging errors

3 Inventory

3.1 Inventory Inquiry(GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryByVid?vid=7874B45D-E971-4DC8-8F59-40530B0F6B77>
(<https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryByVid?vid=7874B45D-E971-4DC8-8F59-40530B0F6B77>).

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryByVid?vid=7874B45D-E971-4DC8-8F59-40530B0F6B77'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

vid

Variant id

string

Y

200

Unique variant identifier

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "vid": "7874B45D-E971-4DC8-8F59-40530B0F6B77", "areald": "1", "areaEn": "China Warehouse", "countryCode": "CN",  
"storageNum": 10877, "totalInventoryNum": 10877, "cjInventoryNum": 700, "factoryInventoryNum": 10177, "stock": [ { "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}",  
"inventory": 0, "factoryInventory": 11092 } ] }, ... ], "requestId": "bcde45ac-da31-4fc7-a05e-e3b23a1e6694" }
```

Field

Definition

Type

Length

Note

vid

Variant id

bigint

200

Unique variant identifier

areald

Warehouse id

int

20

Warehouse area ID

areaEn

Warehouse name

string

200

Warehouse area name

countryCode

Country code(EN)

string

20

Country code where warehouse is located

storageNum

total inventory number, please use totalInventoryNum

int

20

Deprecated, please use totalInventoryNum

totalInventoryNum

total inventory number

int

20

Total inventory quantity of this variant in the warehouse

cjInventoryNum

Inventory management in CJ warehouse

int

20

Inventory quantity managed directly by CJ

factoryInventoryNum

Inventory management in factory

int

20

Inventory quantity managed by the factory

stock

Sub warehouse inventory info

Stock[]

200

-- stockId

Sub warehouse ID

string

200

-- inventory

Sub warehouse Inventory management in CJ warehouse

integer

200

-- factoryInventory

Sub warehouse Inventory management in factory

integer

200

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

3.2 Query Inventory by SKU (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryBySku?sku=CJDS2012593> (<https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryBySku?sku=CJDS2012593>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/stock/queryBySku?sku=CJDS2012593'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

sku

SKU or SPU

string

Y

200

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "areaEn": "China Warehouse", "areald": 1, "countryCode": "CN", "totalInventoryNum": 777566, "cjInventoryNum": 0, "factoryInventoryNum": 777566, "countryNameEn": "China", "stock": [ { "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}", "inventory": 0, "factoryInventory": 11092 } ] }, { "areaEn": "US Warehouse", "areald": 2, "countryCode": "US", "totalInventoryNum": 36, "cjInventoryNum": 36, "factoryInventoryNum": 0, "countryNameEn": "United States of America (the)", "stock": [ { "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}", "inventory": 0, "factoryInventory": 11092 } ] }, "requestId": "dd4c7d122df24b80a094a4aba073724f", "success": true }
```

Field

Definition

Type

Length

Note

vid

Variant id

bigint

200

areald

Warehouse id

int

20

areaEn

Warehouse name

string

200

countryCode

Country code(EN)

string

200

countryNameEn

Country name

string

200

totalInventoryNum

total inventory number

int

20

cjInventoryNum

Inventory management in CJ warehouse

int

20

factoryInventoryNum

Inventory management in factory

int

20

stock

Sub warehouse inventory info

Stock[]

200

-- stockId

Sub warehouse ID

string

200

-- inventory

Sub warehouse Inventory management in CJ warehouse

integer

200

-- factoryInventory

Sub warehouse Inventory management in factory

integer

200

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

3.3 Query inventory by product ID (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/stock/getInventoryByPid?pid=1444929719182168064>
(<https://developers.cjdropshipping.com/api2.0/v1/product/stock/getInventoryByPid?pid=1444929719182168064>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/stock/getInventoryByPid?pid=1444929719182168064'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pid

Product Id

string

Y

40

Return

success

```
{ "success": true, "code": 200, "message": "", "data": { "inventories": [ { "areaEn": "US Warehouse", "areald": 2, "countryCode": "US", "totalInventoryNum": 264, "cjInventoryNum": 264, "factoryInventoryNum": 0, "countryNameEn": "US Warehouse" } ], "variantInventories": [ { "vid": "1796078021431009280", "inventory": [ { "countryCode": "CN", "totalInventory": 10044, "cjInventory": 0, "factoryInventory": 10044, "verifiedWarehouse": 2, "stock": [ { "stockId": "{6709CCD7-0DC7-43B1-B310-17AB499E9B0A}", "inventory": 0, "factoryInventory": 11092 } ] } ] } ], "requestId": "cb927bfa8400421e923a55f81eaafce0" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

Product Inventory Object

object

- inventories

product inventory list

list

-- areaEn

Warehouse Name

string

20

China Warehouse

-- areald

Warehouse id

int

1

1

-- countryCode

Country Code

string

2

CN

-- totalInventoryNum

total inventory number

int

20

-- cjInventoryNum

Inventory management in CJ warehouse

int

20

-- factoryInventoryNum

Inventory management in factory

int

20

-- countryNameEn

Country Name

string

200

China Warehouse

- variantInventories

variant inventory list

list

-- vid

variant id

string

20

China Warehouse

-- inventory

inventory list

list

1

--- countryCode

Country Code

string

2

CN

--- totalInventoryNum

total inventory number

int

20

--- cjInventoryNum

Inventory management in CJ warehouse

int

20

--- factoryInventoryNum

Inventory management in factory

int

20

--- verifiedWarehouse

Verified Inventory type

int

200

1: verified, 2: unverified

--- stock

Sub warehouse inventory info

Stock[]

200

---- stockId

Sub warehouse ID

string

200

---- inventory

Sub warehouse Inventory management in CJ warehouse

integer

200

---- factoryInventory

Sub warehouse Inventory management in factory

integer

200

requestId

requestId

string

48

Flag request for logging errors

4 Product Reviews

4.1 Inquiry Reviews (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/comments> (<https://developers.cjdropshipping.com/api2.0/v1/product/comments>).

Will be deprecated on June 1, 2024, Please use the new api

Inquiry Reviews

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/comments?pid=7874B45D-E971-4DC8-8F59-40530B0F6B77'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pid

Product id

string

Y

200

Inquiry criteria

score

score

integer

N

20

Inquiry criteria

pageNum

page number

int

N

20

default: 1

pageSize

page size

int

N

20

default: 20

Return

success

```
{ "success": true, "code": 0, "message": null, "data": { "pageNum": "1", "pageSize": "1", "total": "285", "list": [ { "commentId": 1536993287524069376, "pid": "1534092419615174656",  
"comment": "excelente estado, llegÃ³ en una semana, cumple con lo descrito.\nBuena calidad de audio.", "commentDate": "2022-06-13T00:00:00+08:00", "commentUser": "F***o",  
"score": "5", "commentUrls": [ "https://cc-west-usa.oss-us-west-1.aliyuncs.com/comment/additional/0001/image/2022-06-15/1126211e-ca15-45ed-95f2-880567ebba37.jpg", "https://cc-  
west-usa.oss-us-west-1.aliyuncs.com/comment/additional/0001/image/2022-06-15/291ab894-068f-4f4e-b01f-57df72902f58.jpg" ], "countryCode": "MX", "flagIconUri": "https://cc-west-  
usa.oss-us-west-1.aliyuncs.com/national-flags/phone/US.png" } ], "requestId": "bcde45ac-da31-4fc7-a05e-e3b23a1e6694" }
```

Field

Definition

Type

Length

Note

pid

Product id

String

200

commentId

Comment id

long

20

comment

Comment

string

200

commentUrls

Comment url

string[]

200

commentUser

Comment user

string

200

score

score

int

20

countryCode

Country code
string
20
commentDate
Comment date
string
200
flagIconUrl
FlagIcon url
string
200
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
return message
string
200
data
return data
object
interface data return
requestId
requestId
string
48

Flag request for logging errors

4.2 Inquiry Reviews (GET)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/productComments> (<https://developers.cjdropshipping.com/api2.0/v1/product/productComments>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/product/productComments?pid=7874B45D-E971-4DC8-8F59-40530B0F6B77'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

pid

Product id

string

Y

200

Inquiry criteria

score

score

integer

N

20

Inquiry criteria

pageNum

page number

int

N

20

default: 1

pageSize

page size

int

N

20

default: 20

Return

success

```
{ "success": true, "code": 0, "message": null, "data": { "pageNum": "1", "pageSize": "1", "total": "285", "list": [ { "commentId": 1536993287524069376, "pid": "1534092419615174656",  
"comment": "excelente estado, llegÃ³ en una semana, cumple con lo descrito.\nBuena calidad de audio.", "commentDate": "2022-06-13T00:00:00+08:00", "commentUser": "F***o",  
"score": "5", "commentUrls": [ "https://cc-west-usa.oss-us-west-1.aliyuncs.com/comment/additional/0001/image/2022-06-15/1126211e-ca15-45ed-95f2-880567ebba37.jpg", "https://cc-  
west-usa.oss-us-west-1.aliyuncs.com/comment/additional/0001/image/2022-06-15/291ab894-068f-4f4e-b01f-57df72902f58.jpg" ], "countryCode": "MX", "flagIconUrl": "https://cc-west-  
usa.oss-us-west-1.aliyuncs.com/national-flags/phone/US.png" } ], "requestId": "bcde45ac-da31-4fc7-a05e-e3b23a1e6694" }
```

Field
Definition
Type
Length
Note
pid
Product id
String
200
commentId
Comment id
long
20
comment
Comment
string
200
commentUrls
Comment url
string[]
200
commentUser
Comment user
string
200
score
score
int
20
countryCode
Country code
string
20
commentDate
Comment date

string

200

flagIconUrl

FlagIcon url

string

200

error

```
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

5 Sourcing

5.1 Create Sourcing (POST)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/create> (<https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/create>)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/create'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx' --header 'Content-Type: application/json'  
--data-raw '{ "thirdProductId": "", "thirdVariantId": "", "thirdProductSku": "", "productName": "", "productImage": "", "productUrl": "", "remark": "", "price": "" }'
```

Parameter

Definition

Type

Required

Length

Note

thirdProductId

third product id

string

N

200

thirdVariantId

third variant id

string

N

200

thirdProductSku

third product sku

string

N

200

productName

product name

string

Y

200

productImage

product image

string

Y

200

productUrl

product url

string

N

200

remark
remark
string
N
200
price
price
BigDecimal
200
Unit: \$ (USD)
Return
success
{ "success": true, "code": 0, "message": null, "data": { "cjSourcingId": "285", "result": "success", }, "requestId": "bcde45ac-da31-4fc7-a05e-e3b23a1e6694" }
Field
Definition
Type
Length
Note
cjSourcingId
CJ sourcing id
string
50
result
search results
string
20
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

5.2 Query Sourcing(POST)

URL

<https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/query> (<https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/query>).

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/product/sourcing/query'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx' --header 'Content-Type: application/json'
--data-raw '{ "sourceIds": [] }'
```

Parameter

Definition

Type

Required

Length

Note

sourceIds

CJ sourcing id

string[]

Y

200

Return

success

```
{ "success": true, "code": 0, "message": null, "data": { "sourceId": "285", "sourceNumber": "223333", "productId": "3324343434", "variantId": "4545456", "shopId": "285",
"shopName": "aaaaaaa", "sourceStatus": "5", "sourceStatusStr": "æ", "cjProductId": "285", "cjVariantSku": "CJ287690900", "requestId": "bcde45ac-da31-
4fc7-a05e-e3b23a1e6694" }
```

Field

Definition
Type
Length
Note
sourceId
CJ sourcing id
string
50
sourceNumber
Search short code
string
20
productId
product id
string
50
variantId
variant id
string
50
shopId
shop id
string
50
shopName
shop name
string
50
sourceStatus
status
string
10
sourceStatusStr
status (chinese)
string
50
cjProductId
CJ product id
string

50

cjVariantSku

CJ variant sku

string

50

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

2 Setting

4 Storage

â€œ

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/standard/ps-Platforms.html>

[\(https://developers.cjdropshipping.cn/en/api/api2/standard/ps-Platforms.html\)](https://developers.cjdropshipping.cn/en/api/api2/standard/ps-Platforms.html)

Appendix 31%[支持平台](#)Support Platforms | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 11%[全局错误码](#)Global Error Codes

Appendix 21%[国家代码](#)Country Code

Appendix 31%[平台](#)Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Appendix 31%[支持平台](#)Support Platforms

Platform Name

Definition

shopify

Temu

Temu_us_local

tiktok

tiktok_us_cross

tiktok_us

Woocommerce

ebay

prestashop

shein

nuvemshop

mercado

bigcommerce

allvalue

aliexpress

api

shoplazza

magento

squarespace

Shipstation

wix

Lazada

etsy

shopee

â€œ

Appendix 217457Country Code

1 Authentication

â€œ

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/standard/ps-code.html>

<https://developers.cjdropshipping.cn/en/api/api2/standard/ps-code.html>),

Appendix 117457Global Error Codes | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 17%4E57Global Error Codes

Description

Error Code Description

Troubleshooting methods

Error code: 1600200

Error code: 1600300

Appendix 2 17%4E57Country Code

Appendix 3 17%4E57Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Appendix 1 17%4E57Global Error Codes

Description

Each time the interface is called, a code may be returned. Based on the return, you can debug the interface and troubleshoot errors.

Notes.

You are supposed to troubleshoot by codes instead of error messages as they may be adjusted.

If the request parameters do not conform to the json specification, this may result in the CJ server parsing the parameters incompletely, in which the interface will return "The request parameter is not in a correct JSON format". You need to check the request parameters of json.

Error Code Description

Return Code

Error Description

Troubleshooting

200

Success

Success

1600000

System busy, please contact CJ IT

System busy, please contact CJ IT

1600001

Invalid API key or access token. How to get access token: https://developers.cjdropshipping.cn/en/api/api2/api/auth.html#_1-1-get-access-token-post
(https://developers.cjdropshipping.cn/en/api/api2/api/auth.html#_1-1-get-access-token-post)

Get new access token,

[View Docs](#)

1600002

access token cannot be empty

Access token cannot be empty! Please input the correct token

1600003

Invalid Refresh token

Use the correct Refresh token or Get new access token,

[View Docs](#)

1600031

Invalid platform token

Invalid platform token, Get new platform access token,

[View Docs](#)

1600030

token invalidation fail

token invalidation fail, Get new access token,

[View Docs](#)

1600004

Authorization failed, Please check cj account

Please check if your email and API key are correct, or if your API store is Authorized

1600005

APIkey is wrong, please check and try again

Please check if API key are correct, or if your API store is Authorized

1600006

Developer account not found

Please check if your email and API key are correct, or if your API store is Authorized

1600007

The user has been bound to another developer account

The user has been bound to another developer account

1600008

Authorization failed, Please check cj account

Please check if your email and API key are correct, or if your API store is Authorized

1600009

Token exchange failed because the code does not exist.

Token exchange failed because the code does not exist.

1600010

RedirectUri must be not empty.

RedirectUri must be not empty.

1600011

CallbackUri must be not empty.

CallbackUri must be not empty.

1600012

The account creation authorization has been disabled, and cj authorization cannot be created. Contact the CJ account manager.

The account creation authorization has been disabled, and cj authorization cannot be created. Contact the CJ account manager.

1600013

Store info does not exist,please check and try again.

Store info does not exist,please check and try again.

1600100

Interface is offline

Interface is offline

1600101

Interface not found

Interface not found

1600200

Too much request

Regulate the rate of your requests for smoother distribution. Refer to:

Access Frequency Restrictions

1600201

Quota has been used up

Regulate the rate of your requests for smoother distribution. Refer to:

Access Frequency Restrictions

1600300

Param error

Check your parameters and enter correct value.

1600301

Read timed out

Read timed out, Wait a moment and try again

1601000

User not found

Please check if your email and API key are correct, or if your API store is Authorized

1602000

Variant not found

Variant not found

1602001

Product not found

Product not found

1602002

Product has been removed from shelves

Order confirm fail, Please contact CJ Agent

1602003

Variant has been removed from shelves

Variant has been removed from shelves

1602004

Failed to create infringement report

Failed to create infringement report

1603000

Order create fail

Order create fail

1603001

Order confirm fail

Order confirm fail

1603002

Order delete fail

Order delete fail

1603003

Order exist, please do not duplicate create

Order exist, please do not duplicate create

1603100

Order not found, please check the CJ order id

Order not found, please check the CJ order id

1603101

Order pay fail, please contact CJ order center

Order pay fail, please contact CJ Agent

1603102

Inventory deduction fail, please contact CJ order center

Inventory deduction fail, please contact CJ Agent

1604000

Balance is insufficient

Balance is insufficient

1604001

The balance payment function is temporarily restricted. Please log in to My CJ and make the order payment on the page

please contact CJ Agent

1605000

Logistic not found

Logistic not found

1605001

Logistic invalid, please reference freight calculate.

Logistic invalid, please reference freight calculate.

1605002

country code not found

country code not found

1606000

Webhook setting add fail, Webhook already have settings

Webhook setting add fail, Webhook already have settings

1606001

You do not meet our service requirements, Please check and try again. 1.Request Protocols: HTTPS, 2. Request Method: POST, 3.Content-Type: application/json, 4. Response Status Code: 200, 5. Response must be returned within 3 seconds.

Fix and retry

1607000

You do not meet our service requirements, Please check and try again. 1.Request Protocols: HTTPS, 2. Request Method: POST, 3.Content-Type: application/json, 4. Response Status Code: 200, 5. Response must be returned within 3 seconds.

Fix and retry

1607001

Please do not use domain names such as localhost, 127.0.0.1

Fix and retry

1607002

Webhook url error, Please ensure URL starts with https://

Fix and retry

1607003

Webhook url error, Http Status must be 200

Webhook url error, Http Status must be 200

1607002

The CJ page type is not supported

The CJ page type is not supported

1607004

Freight calculation request failed

Freight calculation request failed

1607006

Query dispute product request failed

Query dispute product request failed

1607007

dispute confirm fail

dispute confirm fail

1607008

dispute create fail

dispute create fail

1607009

dispute cancel fail

dispute cancel fail

1607010

product update fail

product update fail

16900202

Request method " " not supported

Please check the API documentation to confirm which HTTP method is required for this request, update it and retry.

16900203

Content type not supported[]

Please check the API documentation to confirm which Content-Type is required for this request, update it and retry.

16900204

Required request body is missing

Check the API documentation and add request body.

16900205

The request parameter is not in a correct JSON format

Check the API documentation use the correct JSON data

16900403

can not be empty

Check your parameters and enter correct value.

Troubleshooting methods

Error code: 1600200

Interface call exceeds limit.

For specific frequency policy, Refer to:

Access Frequency Restrictions

The time is the same. For example, if you beyond the minutes limits, you can request again after minutes, while it will be hours if you beyond the hours limits.

Our rate limit is not strict. For the calls, the following optimizations are considered.

When the interface is implemented, only system failures need call again. For other error codes, the specific failure shall figured out.

The call is reasonable or not. For a real-time synchronization, it can be changed to a timed task call as too many calls of one user will cause a bad experience.

Error code: 1600300

Invalid Parameter. It doesn't meet the system requirements. You can refer to the specific API interface instruction. Also, you need to confirm:

It is a correct Http request method. For example, if the interface requires the Post method, you cannot use the Get method.

It is a correct Http request parameter. For example, if the interface requires a json structure, it cannot be passed as an url parameter or form-data.

Interface Call Restrictions

Appendix 21%Country Code

â

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/logistic.html>
(<https://developers.cjdropshipping.cn/en/api/api2/api/logistic.html>)

6 Logistics | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 11%Global Error Codes

Appendix 21%Country Code

Appendix 31%Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

1 Logistics

1.1 Freight Calculation (POST)

1.2 Freight Calculation Tip(POST)

2 Tracking Number

2.1 Get Tracking Information (GET) Deprecated

2.2 Get Tracking Information (GET)

7 Dispute

8 Webhook

6 Logistics

1 Logistics

1.1 Freight Calculation (POST)

Freight calculation. Bulk purchase products will have designated shipping methods, while dropshipping products will usually have more options.

URL

<https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculate> (<https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculate>).

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculate'
--header 'Content-Type: application/json'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--data-raw '{ "startCountryCode": "US", "endCountryCode": "US", "products": [ { "quantity": 2, "vid": "439FC05B-1311-4349-87FA-1E1EF942C418" } ] }'
```

Parameter

Definition

Type

Required

Length

Note

startCountryCode

Country of origin

string

Y

200

endCountryCode

Country of destination

string

Y

200

zip

zip

string

N

200

taxId

tax id

string

N

200

houseNumber

house number

string

N
200
lossNumber
loss number
string
N
200
quantity
Quantity
int
Y
10
vid
Variant id
string
Y
200
Return
success

{ "code": 200, "result": true, "message": "Success", "data": [{ "logisticAging": "2-5", "logisticPrice": 4.71, "logisticPriceCn": 30.54, "logisticName": "USPS+" }, "requestId": "0242ad78-
eea2-481d-876a-7cf64398f07f" }

Field
Definition
Type
Length
Note
logisticPrice
Shipping cost in USD
BigDecimal
18(18)
Unit: \$ (USD)
logisticPriceCn
Shipping cost in CNY
BigDecimal
18(18)
Unit: ¥ (CNY)
logisticAging
Shipping time
string

20
logisticName
Carrier name
string
20
taxesFee
taxes fee
BigDecimal
(18, 2)
Unit"%#=#\$(USD)
clearanceOperationFee
customs clearance fee
BigDecimal
(18, 2)
Unit"%#=#\$(USD)
totalPostageFee
total postage
BigDecimal
(18, 2)
Unit"%#=#\$(USD)
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
return message
string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.2 Freight Calculation Tip(POST)

Freight calculation. Bulk purchase products will have designated shipping methods, while dropshipping products will usually have more options.

URL

<https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculateTip> (<https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculateTip>)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/logistic/freightCalculateTip'
--header 'Content-Type: application/json'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--data-raw '{ "reqDTOS": [ { "srcAreaCode": "CN", "destAreaCode": "US", "length": 0.3, "width": 0.4, "height": 0.5, "volume": 0.06, "totalGoodsAmount": 123.2, "productProp": [
"COMMON" ], "freightTrialSkuList": [ { "skuQuantity": 1, "sku": "CJCF104237201AZ" } ], "skuList": [ "CJCF104237201AZ" ], "platforms": [ "Shopify" ] } ] }'
```

Parameter

Definition

Type

Required

Length

Note

srcAreaCode

Country of origin

string

Y

200

destAreaCode

Country of destination

string

Y

200

customerCode

customer code

string

N

200

zip

zip

string

N

200

houseNumber

house number

string

N

100

iossNumber

ioss number

string

N

200

storageIdList

Storage id List

string[]

N

100

recipientAddress

Recipient address

string

N

200

city

City

string

N

50

recipientName

Recipient name

String

N

200

skuList

Sku list

String[]

Y

200

town

Town

String

N

100

phone

Phone

String

N

50

wrapWeight

wrap weight,Unit:g

int

Y

200

volume

Volume,Unit:cm³

BigDecimal

Y

200

station

station

String

N

200

Referer:

Country Code

, Please use The two-letter code

platforms

Platform List

String[]

N

200

Referer

Platforms

dutyNo

dutyNo

String
N
200
email
email
String
N
100
province
province
String
N
100
recipientAddress1
recipient address1
String
N
200
uid
uid
String
N
200
recipientId
recipient id
String
N
200
recipientAddress2
recipient address2
String
N
200
amount
amount
BigDecimal
N
50
productTypes

product type

String[]

N

100

weight

weight,Unit:g

int

Y

100

productProp

product prop

String

Y

100

optionName

option name

String

N

200

volumeWeight

volume weight,Unit:g

BigDecimal

N

100

orderType

order type

String

N

100

totalGoodsAmount

total value of goods

BigDecimal

N

100

freightTrialSkuList

freight trial sku list

Object[]

Y

- productCode

	product code
	String
	N
	100
• sku	
	sku
	String
	N
	100
• productPropList	
	Product attributes
	String[]
	N
	100
• productTypeList	
	product type (0: normal goods, 1: service goods, 3: packaged goods, 4: supplier goods, 5: supplier self-delivered goods, 6: virtual goods, 7: pod personalized goods)
	String[]
	N
	100
• vid	
	variant id
	String
	N
	100
• skuQuantity	
	sku quantity
	int
	N
	50
• skuWeight	
	sku weight,Unit:g
	BigDecimal
	N
	100
• skuVolume	
	sku volume,Unit:cm³
	BigDecimal
	N
	100

- parentVid

int

50

String

50

- int

10

- int

10

- int

10

success

```
{
    "discountFee": 4.09, "discountFeeCN¥": 25.30, "volumeWeight": null, "option": {
        "arrivalTime": "12-1938719199233" },
    "ruleTips": [ {
        "expression": "%{s[%d]*%f}%+[%6.2$]", "interceptType": "0", "max": null,
        "faces are supported": true, "type": "phone" } ],
    "ruleTipTypes": [ "phone" ], "channelId": "1564543005939785730", "error": {
        "prclnIncreases": "115", "reSort": "62", "remoteFee": 0, "remoteFeeCN¥": 0, "tip": "", "uid": "", "orderId": null,
        "null", "message": "Hi, CJ will not accept any disputes when you choose the shipping method, which is not trackable
        25.30, "wrapWeight": 0, "stopWords": [], "channel": {
            "cnName": "%{a}[%f]*%+[%6.2$]", "countryId": "48", "enName": "China", "id":
            "postCode": "", "shortCode": "US", "srcArea": {
                "cnName": "%{a}[%f]*%", "countryId": "48", "enName": "China", "id":
                "expression": "%{s[%d]*%f}%+[%6.2$]", "interceptType": "0", "max": null, "min": null, "msgCode":
                "faces are supported": true, "type": "phone" }, "taxesFee": null, "clearanceOperationFee": null ] },
    "499f061582dbdb989b", "success": true }
```

Definition

Type

Length

Note

arrivalTime

arrival time

string

200

discountFee

discount Fee

BigDecimal

1/41181/4121/41

Unit: \$ (USD1/41)

discountFeeCNY

discount Fee CNY

BigDecimal

1/41181/4121/41

volumeWeight

volume weight

BigDecimal

1/41181/4121/41

Unit: \$ (USD1/41)

channelId

channel id

String

200

error

error

String

200

errorEn

errorEn

String

200

optionId

option id

String

100

postage

postage

BigDecimal

1/41181/4121/41

Unit: \$ (USD1/41)

postageCNY

postage CNY

BigDecimal

1/4(181/4121/4)

Unit: \$ (USD1/4)

priceIncreases

price increases

String

100

reSort

reSort

String

100

remoteFee

remoteFee

BigDecimal

1/4(181/4121/4)

Unit: \$ (USD1/4)

remoteFeeCNY

remoteFee CNY

BigDecimal

1/4(181/4121/4)

Unit: \$ (USD1/4)

tip

tip

string

200

uid

uid

String

200

orderId

order id

String

100

unWeightChargeTarget

unWeightChargeTarget

BigDecimal

1/4(181/4121/4)

Unit: \$ (USD1/4)

floatMaxPrice

floatMaxPrice

BigDecimal

181214

Unit: \$ (USD1)

floatMinPrice

floatMinPrice

BigDecimal

181214

Unit: \$ (USD1)

logisticsParamRespDTO

logisticsParamRespDTO

String

200

message

message

String

200

wrapPostage

wrap postage

BigDecimal

181214

Unit: \$ (USD1)

wrapPostageCNY

wrap postage CNY

BigDecimal

181214

Unit: \$ (USD1)

wrapWeight

wrap weight

BigDecimal

181214

Unit: \$ (USD1)

stopWords

stop Words

String

200

channel

channel

Object
cnName
name(CN)
String
200
enName
name(EN)
String
200
id
id
String
200
option
option
Object
arrivalTime
arrival time
String
100
cnName
name(CN)
String
100
enName
name(EN)
String
100
id
id
String
100
taxesFee
taxes fee
BigDecimal
Unit: \$ (USD)
clearanceOperationFee
customs clearance fee

BigDecimal

18, 2

Unit: \$ (USD)

totalPostageFee

total postage

BigDecimal

(18, 2)

Unit: \$(USD)

allRuleTips

all rule tips

String

200

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

Flag request for logging errors

2 Tracking Number

2.1 Get Tracking Information (GET)

Deprecated

Shipping information can be found upon tracking numbers. You can also visit

CJ Logistic Platform

(opens new window)

Has deprecated on June 1, 2024, Please use the new api

Get Tracking Information

URL

[\(https://developers.cjdropshipping.com/api2.0/v1/logistic/getTrackInfo?trackNumber=CJPKL7160102171YQ\)](https://developers.cjdropshipping.com/api2.0/v1/logistic/getTrackInfo?trackNumber=CJPKL7160102171YQ) (https://developers.cjdropshipping.com/api2.0/v1/logistic/getTrackInfo?trackNumber=CJPKL7160102171YQ)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/logistic/getTrackInfo?trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ'
```

Parameter

Definition

Type

Required

Length

Note

trackNumber

trackNumber

string

Y

200

batch query

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "trackingNumber": "CJPKL7160102171YQ", "logisticName": "CJPacket Sensitive", "trackingFrom": "CN", "trackingTo": "US", "deliveryDay": "13", "deliveryTime": "2021-06-17 07:04:04", "trackingStatus": "In transit", "lastMileCarrier": "CJPacket", "lastTrackNumber": "926112903032124" }, { "requestId": "3426e927-8c50-4687-9ced-623e77d55bd0" } ] }
```

Field

Definition

Type

Length

Note

trackingNumber

tracking number

string
200
trackingFrom
from
string
20
trackingTo
to
string
20
deliveryDay
Delivery day
string
200
deliveryTime
Delivery time
string
200
trackingStatus
tracking status
string
200
lastMileCarrier
last mile carrier
string
200
lastTrackNumber
last mile tracking number
string
200
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note
code
error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

2.2 Get Tracking Information (GET)

Shipping information can be found upon tracking numbers. You can also visit

CJ Logistic Platform

(opens new window)

URL

[\(https://developers.cjdropshipping.com/api2.0/v1/logistic/trackInfo?trackNumber=CJPKL7160102171YQ\)](https://developers.cjdropshipping.com/api2.0/v1/logistic/trackInfo?trackNumber=CJPKL7160102171YQ) ([\(https://developers.cjdropshipping.com/api2.0/v1/logistic/trackInfo?trackNumber=CJPKL7160102171YQ\)](https://developers.cjdropshipping.com/api2.0/v1/logistic/trackInfo?trackNumber=CJPKL7160102171YQ))

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/logistic/trackInfo?trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ &trackNumber=CJPKL7160102171YQ'
```

Parameter

Definition

Type

Required

Length

Note

trackNumber

trackNumber

string

Y

200

batch query

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": [ { "trackingNumber": "CJPKL7160102171YQ", "logisticName": "CJPacket Sensitive", "trackingFrom": "CN", "trackingTo": "US", "deliveryDay": "13", "deliveryTime": "2021-06-17 07:04:04", "trackingStatus": "In transit", "lastMileCarrier": "CJPacket", "lastTrackNumber": "926112903032124" } ], "requestId": "3426e927-8c50-4687-9ced-623e77d55bd0" }
```

Field

Definition

Type

Length

Note

trackingNumber

tracking number

string

200

trackingFrom

from

string

20

trackingTo

to

string

20

deliveryDay

Delivery day

string

200

deliveryTime

Delivery time

string

200

trackingStatus

tracking status

string

200

lastMileCarrier

last mile carrier

string

200

lastTrackNumber

last mile tracking number

string

200

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

5 Shopping

7 Dispute

â€œ

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/standard/field.ht>
(<https://developers.cjdropshipping.cn/en/api/api2/standard/field.h>

Interface Field Definitions | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Field Definitions

1 Base Fields

1 System Fields

2 Public Fields

2 Transaction Fields

1 Authentication Fields

2 Settings Fields

3 Product Fields

4 Storage Fields

5 Transaction Fields

6 Logistics Fields

Interface Call Restrictions

Appendix 1 1741 Global Error Codes

Appendix 2 1741 Country Code

Appendix 3 1741 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Interface Field Definitions

1 Base Fields

1 System Fields

1.1 Return

Field

Field Meaning

Field Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.2 Paging

Field

Field Meaning

Field Type

Length

Note

pageNum

Number of current pages

int

20

pageSize

Number of items returned per page

int

20

total

total

int

20

list

list

2 Public Fields

2.1 Region

Field

Field Meaning

Field Type

Length

Note

areald

area id

string

200

areaEn

area name

string

200

countryCode

country code

string

200

2.2 People

Field

Field Meaning

Field Type

Length

Note

creator

creator

string

200

createTime

create time

string

200

updater

modifier

string

200

updateTime

modify time

string

200

2.3 Other

Field

Field Meaning

Field Type

Length

Note

sourceFrom

source

byte

4

comment

comment

string

200

Remarks:

sourceFrom: 0-erp entry, 1-store search entry, 2-cj search entry

2 Transaction Fields

1 Authentication Fields

1.1 Authorization

Field

Definition

Type

Length

Note

email

Email

string

200

password

Password

string

200

1.2 Token

Field

Definition

Type

Length

Note

accessToken

Access Token

string

200

accessTokenExpiryDate

Access Token expiry time

string

200

Default 15 days

refreshToken

Refresh Token

string

200

refreshTokenExpiryDate

Refresh Token expiry time

string

200

Default 180 days

2 Settings Fields

2.1 Account

Field

Definition

Type

Length

Note

openId

Account ID

string

200

openName

Account Name

string

200

openEmail

Account Email

string

200

root

Root access

string

200

root!%#%NO_PERMISSION - not authorized

GENERAL - general account

VIP - VIP account

ADMIN - administrator

isSandbox

(Whether) Sandbox account

byte

4

2.2 API Setting

Field

Definition

Type

Length

Note

setting

Settings

list

200

quotaLimits

Quota limits

list

Applicable on specific URLs

quotaUrl

Quota URL

string

200

quotaLimit

Quota limit

int

20

quotaType

Quota Type

byte

4

0-total/1-per year/2-per year/3-per quarter/4-per day/5-per hour

qpsLimit

QPS limit

int

20

Account queries per second

3 Product Fields

3.1 Product

Field

Definition

Type

Length

Note

pid

Product ID

string

200

productName

Product name

string

200

productNameEn

Product name/EN

string

200

productSku

Product sku

string
200
productImage
Product image
string
200
productWeight
Product weight
int
200
unit: g
productType
Product type
byte
200
productUnit
Product unit
string
48
categoryId
Category id
string
200
categoryName
Category name
string
200
entryCode
HS code
string
200
entryName
Customs name
string
200
entryNameEn
Customs name (EN)
string
200

materialName

Material

string

200

materialNameEn

Material (EN)

string

200

materialKey

Material attribute

string

200

packWeight

Package weight

int

200

unit: g

packingName

Package name

string

200

packingNameEn

Package name (EN)

string

200

packingKey

Package attribute

string

200

isActive

(Whether) Active

boolean

1

description

Description

string

200

Product Type

Product Type

Type
ORDINARY_PRODUCT
Ordinary product
SERVICE_PRODUCT
Service product
PACKAGING_PRODUCT
Packaging product
SUPPLIER_PRODUCT
Supplier product
SUPPLIER_SHIPPED_PRODUCT
Supplier shipped product
3.2 Variant
Field
Definition
Type
Length
Note
vid
Variant ID
string
200
variantName
Variant name
string
200
variantNameEn
Variant name (EN)
string
200
variantSku
Variant SKU
string
200
variantUnit
Variant Unit
string
200
variantProperty
Variant Property

string

200

variantKey

Variant Key

string

200

variantLength

Variant Length

int

200

unit: mm

variantWidth

Variant Width

int

200

unit: mm

variantHeight

Variant Height

int

200

unit: mm

variantVolume

Variant Volume

int

200

unit: mm3

variantWeight

Variant Weight

int

200

unit: g

variantSellPrice

Variant Sell Price

double

200

unit: \$ (USD)

3.3 Supplier

Field

Definition

Type

Length

Note

3.4 Storage

Field

Definition

Type

Length

Note

storageNum

Available inventory

int

20

queryTime

Refresh rate

string

200

4 Storage Fields

4.1 Warehouse

Field

Definition

Type

Length

Note

storageId

Warehouse id

string

200

storageName

Warehouse Name

string

200

5 Transaction Fields

5.1 Order

Field

Definition

Type

Length

Note

orderId	
Order Id	
string	
200	
orderWeight	
order weight	
int	
200	
orderAmount	
order amount	
double	
200	
unit: \$ (USD)	
orderStatus	
order status	
string	
200	
Order Status	
Order Status	
Status	
CREATED	
Order create	
IN_CART	
in cart	
UNPAID	
unpaid	
UNSHIPPED	
unshipped	
SHIPPED	
shipped	
DELIVERED	
delivered	
CANCELLED	
cancelled	
5.2 Amount	
Field	
Definition	
Type	
Length	

Note

noWithdrawalAmount

Bonus amount

BigDecimal

(18,2)

unit: \$ (USD)

freezeAmount

Frozen amount

BigDecimal

(18,2)

unit: \$ (USD)

amount

Amount

BigDecimal

(18,2)

unit: \$ (USD)

psi74E7

174BigDecimal11814214 Length:20, 2 decimal digits.

214CJ Supported international currency: USD (\$)

5.3 Shipping

Field

Definition

Type

Length

Note

shippingCountryCode

shipping country code

string

200

shippingCountry

shipping country

string

200

shippingProvince

shipping province

string

200

shippingCity

shipping city

string

200

shippingAddress

shipping address

string

200

shippingZip

shipping zip

string

200

shippingPhone

shipping phone

string

200

6 Logistics Fields

6.1 Logistics

Field

Definition

Type

Length

Note

logisticPrice

Shipping cost

BigDecimal

(18,2)

unit: \$ (USD)

logisticPriceCn

Shipping cost

BigDecimal

$$\bar{I}^{1/4}(18\bar{I}^{1/4}\{2\bar{I}^{1/4}\})$$

unit: 人民币 (CNY)

logisticAging

Estimated delivery timespan

string

20

logisticName

Shipping method

string

20

6.2 Tracking Number

Field

Definition

Type

Length

Note

trackingNumber

Tracking number

string

200

trackingFrom

From

string

20

trackingTo

To

string

20

deliveryDay

Delivery timespan

string

200

deliveryTime

Delivered time

string

200

trackingStatus

Tracking status

string

200

⚡

Interface Definition

Interface Call Restrictions

⚡

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/dispute.html>
(<https://developers.cjdropshipping.cn/en/api/api2/api/dispute.htm>

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 1 Global Error Codes

Appendix 2 1 Country Code

Appendix 3 1 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

1 Select the list of disputed products 1 GET 1

2 Confirm the dispute 1 POST 1

3 Create dispute 1 POST 1

4 Cancel dispute 1 post 1

5 Query the list of disputes 1 GET 1

8 Webhook

7 Dispute

1 Select the list of disputed products 1 GET 1

URL

<https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeProducts> (<https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeProducts>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeProducts?orderId=CJPKL7160102171YQ'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type	
Required	
Length	
Note	
orderId	
CJ order id	
string	
Y	
100	
Return	
success	
{ "code": 200, "result": true, "message": "Success", "data": { "orderId": "75727832844206081", "orderNumber": "1627572766607937536", "productInfoList": [{ "lineItemId": "27572784056172547", "cjProductId": "70030020423733248", "cjVariantId": "70030020612476928", "canChoose": true, "price": 23.00, "quantity": 1, "cjProductName": "Hellpoo", "cjImage": "http://d847fcac-392f-4168-8b06-a580a8368dff.jpg", "sku": "CJSJ1041743", "supplierName": "banggood" }] }, "requestId": "11edc6cc84254bb4b3ac74299d5db197", "success": true }	
Field	
Definition	
Type	
Length	
Note	
orderId	
CJ order id	
string	
200	
orderNumber	
customer order number	
string	
200	
productInfoList	
Product information list	
Object[]	
lineItemId	
lineItem id	
string	
100	
cjProductId	
CJ product id	
string	
100	
cjVariantId	

CJ variant id
string
100
canChoose
Is it possible to check to open a dispute
boolean
true:yes, false?no
price
product price
BigDecimal
(18,2)
Unit: \$ (USD)
quantity
quantity
integer
20
cjProductName
CJ product name
string
200
cjImage
CJ product image
string
100
sku
sku
string
100
supplierName
supplier name
string
200
error
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
Field
Definition
Type
Length
Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

2 Confirm the dispute14(POST14)

URL

<https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeConfirmInfo> (<https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeConfirmInfo>)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/disputes/disputeConfirmInfo'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--data-raw '{ "orderId": "62650625018974208", "productInfoList": [ { "lineItemId": "1626506252349808640", "quantity": "1" } ] }'
```

Parameter

Definition

Type

Required

Length

Note

orderId

CJ order id

string

Y

100

productInfoList

product information

object[]

Y

lineItemId

lineItem id

string

N

quantity

quantity

integer

Y

price

price

BigDecimal

Y

(18,2)

Unit: \$ (USD)¥(RMB)

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "orderId": "265062501897420801", "orderNumber": "1626506237791440896", "maxProductPrice": 23.00, "maxPostage": 0.00, "maxlossTaxAmount": 0, "maxlossHandTaxAmount": 0, "maxAmount": 23.00, "expectResultOptionList": [ "1" ], "productInfoList": [ { { "lineItemId": "1626506252349808640", "cjProductId": "1570030020423733248", "cjVariantId": "1570030020612476928", "canChoose": false, "price": 23.00, "quantity": 1, "cjProductName": "Hellpoo", "cjImage": "https://d847fcac-392f-4168-8b06-a580a8368dff.jpg", "sku": "CJSJ1041743-A", "supplierName": "banggood" } ], "disputeReasonList": [ { { "disputeReasonId": 1, "reasonName": "Unfulfilled Order Cancellation" } } ], "requestId": "af336b7bdc364e6391b9d558690b1521", "success": true }
```

Field

Definition

Type

Length

Note

orderId

CJ order id

string

200

orderNumber

customer order number

string

200

expectResultOptionList

expected result

string[]

1: Refund , 2:Reissue

maxProductPrice

Product price

BigDecimal

(18,2)

Unit: \$ (USD¥¼)

maxPostage

Postage

BigDecimal

(18,2)

Unit: \$ (USD¥¼)

maxlossTaxAmount

loss tax amount

BigDecimal

(18,2)

Unit: \$ (USD¥¼)

maxlossHandTaxAmount

loss tax fee amount

BigDecimal

(18,2)

Unit: \$ (USD¥¼)

maxAmount

Apply for refund amount

BigDecimal

(18,2)

Unit: \$ (USD¥¼)

productInfoList

product information

Object[]

canChoose

Whether to check open dispute

boolean

2

false or ture

price

price

BigDecimal

(18,2)

Unit: \$ (USD)1%

quantity

quantity

integer

20

lineItemId

lineItem id

string

100

cjProductId

CJ product id

string

100

cjVariantId

CJ variant id

string

100

cjProductName

CJ product name

string

200

cjImage

CJ product image

string

100

sku

CJ sku

string

100

supplierName

supplier name

string

200

disputeReasonList

dispute reason

object []

disputeReasonId

dispute reason id

integer

20

reasonName

dispute reason name (EN)

string

200

error

```
{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

3 Create dispute?<[POST]>

URL

<https://developers.cjdropshipping.com/api2.0/v1/disputes/create> (<https://developers.cjdropshipping.com/api2.0/v1/disputes/create>).

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/disputes/create'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--data-raw '{ "orderId": "275727832844206081", "businessDisputelId": "0000001266", "disputeReasonId": 1, "expectType": 1, "refundType": 1, "messageText": "gfhfghfghfgh",
"imageUrl": [], "productInfoList": [ { "lineItemId": "1627572784056172547", "quantity": "1" } ] }'
```

Parameter

Definition

Type

Required

Length

Note

businessDisputelId

customer business id, 0~9, a~z, A~Z, _

string

Y

100

orderId

CJ order id

string

Y

100

disputeReasonId

dispute reason id

integer

Y

10

expectType

expect type

integer

Y

20

1: Refund , 2:Reissue

refundType

Refund type

integer

Y

20

1:balance , 2:platform

messageText

text message

string

	Y
	500
	imageUrl
	image url
	string []
	N
	200
	videoUrl
	video url
	string []
	N
	200
	productInfoList
	product information
	object[]
	price
	price
	BigDecimal
	Y
	(18,2)
	Unit: \$ (USD¥%)
	lineItemId
	lineItem id
	string
	N
	100
	quantity
	quantity
	integer
	Y
	10
	Return
	success
	{ "code": 200, "result": true, "message": "Success", "data": "true", "redirectUri": "0242ad78-eea2-481d-876a-7cf64398f07f" }
	error
	{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }
	Field
	Definition
	Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

4 Cancel dispute!%4(post!%4)

URL

<https://developers.cjdropshipping.com/api2.0/v1/disputes/cancel> (https://developers.cjdropshipping.com/api2.0/v1/disputes/cancel)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/disputes/cancel'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
--data-raw '{ "orderId": "J1623672949997490176", "disputeId": "SH1623673863466725376" }'
```

Parameter

Definition

Type

Required

Length

Note

orderId

CJ order id

string

Y

100

disputeId

CJ dispute id

string

Y

100

è¿åä¸

success

{ "code": 200, "result": true, "message": "Success", "data": "true", "redirectUri": "0242ad78-eea2-481d-876a-7cf64398f07f" }

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

5 Query the list of disputes¼(GET¼)

URL

<https://developers.cjdropshipping.com/api2.0/v1/disputes/getDisputeList> (<https://developers.cjdropshipping.com/api2.0/v1/disputes/getDisputeList>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/disputes/getDisputeList'  
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Parameter

Definition

Type

Required

Length

Note

orderId

CJ order id

string

N

100

disputeId

dispute id

integer

N

10

orderNumber

customer order number

string

N

100

pageNum

page number

integer

N

10

default: 1

pageSize

page size

integer

N

10

default: 10



Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": "", "redirectUri": "0242ad78-eea2-481d-876a-7cf64398f07f" }
```

[illegible]

å ð æ ® µ æ æ

å ðæ®µç±»å  

é\ ıâ°!

$$a \gg \lambda^3$$

pageNum

page number

int

20

pageSize

page size

int

20

total

total

int

20

list

List

status

dispute status

string

20

id

dispute id

string

disputeReason

dispute reason

string

replacementAmount

Reissue amount

BigDecimal

(18,2)

Unit: \$ (USD 1/4)

resendOrderCode

Reissue order id

string

money

final refund amount

BigDecimal

(18,2)

Unit: \$ (USD¥%)

finallyDeal

final negotiation result

integer

1:Refund, 2: Reissue, 3: Reject

createDate

create date

productList

product information

Object[]

image

product image

string

price

product price

lineItemId

lineItem id

string

100

cjProductId

CJ product id

string

cjVariantId

CJ variant id

string

100

productName

product name

string

supplierName

supplier name

string

error

{ "code": 1600100, "result": false, "message": "Param error", "data": null, "requestId": "323fda9d-3c94-41dc-a944-5cc1b8baf5b1" }

Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
return message
string
200
data
return data
object
interface data return
requestId
requestId
string
48
Flag request for logging errors
â
6 Logistic
8 Webhook
â

Sub-link:

<https://developers.cjdropshipping.cn/en/api/start/development.html>
(<https://developers.cjdropshipping.cn/en/api/start/development.html>)

Introduction
Interface call flow
Basic debugging methods
Limitations on the frequency of calls
Get Access-token
Practical Tool
Platform Waybill Order Processing
Webhook
Sandbox
API
Standard
Interface Definition
Interface Field Definition
Interface Call Restrictions
Appendix 1 全球通用错误码
Appendix 2 国家代码
Appendix 3 平台
Interface
1 Authentication
2 Setting
3 Product
4 Storage
5 Shopping
6 Logistic
7 Dispute
8 Webhook
Development Documentation
Introduction
Call Flow
Debugging Methods
Rate Limits
Introduction

The CJ API offers a rich set of capability interfaces that developers can use to achieve integration of enterprise services and enterprise WeChat with the help of interface capabilities which can be quickly previewed by directory navigation. The navigation is aggregated and grouped by functional blocks, such as address book, push, etc..

For the API development, the guideline is Development Documentation > Get Access Token > API 2.0.

All interfaces must use the HTTPS protocol, JSON data format and UTF8 encoding. The interface description format is as follows.

Request method: POST (HTTPS) Request address: ... Request package body. ... Parameter description. ... Permission Description. ... Return results. ... Description of parameters. ...

The request method. All requests shall meet the https protocol, distinguishing HttpGet and HttpPost requests.

The request address. Case matters.

The request package body and parameter description. You should indicate the request parameter example and description, which includes field meanings and value ranges. You should refer to this definition scope when designing data structures.

The permission description. You should indicate the use range of the interface. By default, it can only view the data under the current account. No invocation scenario needs your special attention.

The return results and description of parameters. You should indicate the request parameter example and description.

Important

: To determine if an API call was successful:

Success

: HTTP status 200 AND (code=200 OR no code field present)

Failure

: HTTP status 200 OR code field present with value 200 Please refer to the global error code documentation for specific error meanings.

The message is for reference only and is subject to change, so it cannot be used to determine whether the call was successful.

Interface call flow

Find the access token. Reference:

documentation note

.

Cache and refresh access_token.

You need to cache the access_token for subsequent calls to the interface. When the access_token is invalid or expired, it needs to be retrieved.

Calling a specific business interface.

Basic debugging methods

Tools, such as postman, can be used to troubleshoot problems. Reference:

documentation note

Limitations on the frequency of calls

To ensure our platform remains stable and fair for everyone, all APIs are rate-limited. Reference:

Active call frequency limit

â€‹

Introduction

Get Access-token

â€‹

Sub-link:

<https://developers.cjdropshipping.cn/en/api/start/token.html>
(<https://developers.cjdropshipping.cn/en/api/start/token.html>)

Get Token | CJ Docs

Introduction

Start

Development

Get Access-token

Token Mechanism

Get Access_token

Storage & Examination of Token

Access Token

Refresh Token

Token Refresh

Reauthorization

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 174 Global Error Codes

Appendix 2 174 Country Code

Appendix 3 174 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Get Token

Token Mechanism

Tokens can be obtained upon Auth2.0 protocol. Each Access Token and Refresh Token has its timestamp.

Get Access_token

For security reasons, the Access Token shall always be stored in the backend, and shall never be returned to front end, as all API access requests shall be initiated from backend.

Access Token must be obtained to create a login credential before calling API interface, as caller ID of other API interfaces will be authenticated with Access Token.

CJ-Access-Token:

Get CJ-Access-Token

Storage & Examination of Token

Access Token

An Access Token which contains login information must be created before API can be called. Access Tokens are required before servers can be accessed. In general, the life of an Access Token is 15 days.

Refresh Token

An Access Token can be refreshed with a Refresh Token. Access Tokens will be returned after Refresh Tokens are imported to the authentication server. In general, the life of a Refresh Token is 180 days.

Regular examination on validity of Tokens is recommended: Examination of expiry date of each Token before use: if Access_Token is expired, Refresh_Token can be applied to refresh.

Token Refresh

Get new Access Token and Refresh Token when expiry date of Access Token is near, and store new tokens as before. Delay queue is recommended when refreshing tokens.

Reauthorization

If both Access Token and Refresh Token are expired, new tokens can be obtained via reauthorization.



Development

Practical Tool



Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/standard/definition>
(<https://developers.cjdropshipping.cn/en/api/api2/standard/definition>)

Interface Definition | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

11%4IRequest Header

1.1 url

1.2 header

1.3 curl

21%4IReturn

Interface Field Definition

Interface Call Restrictions

Appendix 11%4I%5CGlobal Error Codes

Appendix 21%4I%5CCountry Code

Appendix 31%4I%5CPlatforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Interface Definition

1!%IRequest Header

1.1 url

<https://developers.cjdropshipping.com/api2.0/v1/setting/account/set> (<https://developers.cjdropshipping.com/api2.0/v1/setting/account/set>).

url!%I=https://developers.cjdropshipping.com identification!%I=api2.0 version!%I=v1 uri: /setting/account/set

1.2 header

Name

Required

Note

Content-Type

Y

default : application/json

CJ-Access-Token

Y

default :

Your secret key in CJ

1.3 curl

```
curl --location --request PATCH 'https://developers.cjdropshipping.com/api2.0/v1/setting/account/set'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxx'
--header 'Content-Type: application/json'
--data-raw '{ "openName": "", "openEmail": "" }'
```

2!%IReturn

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

Sandbox

Interface Field Definition

â€œ

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/standard/limit.ht>
(<https://developers.cjdropshipping.cn/en/api/api2/standard/limit.h>

Access Frequency Restrictions | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Base Frequency

Special Frequency

Appendix 1 全球错误码

Appendix 2 国家代码

Appendix 3 平台

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Access Frequency Restrictions

Once you got the access token, your application can successfully call the various interfaces provided by the CJ backend to manage or access the resources of the CJ backend.

In order to prevent application errors from causing an abnormal load on the CJ server, by default, each CJ user is limited to a certain rate of interface calls, and when this limit is exceeded, the corresponding interface call will receive a error code.

The following is the current default frequency limit, which may be adjusted by the CJ backend depending on operational conditions.

Base Frequency

No more than 10 requests/second per IP address;

The maximum call frequency for non-login interfaces is 30 requests/second.

Specific interfaces have separate settings:

/api2.0/v1/authentication/getAccessToken

Once every 5 minutes

/api2.0/v1/authentication/refreshAccessToken

5 times per minute

Special Frequency

Special settings:

The interface restricts user access frequency based on user level:

For Free users or the sales level is 0 or 1, it is limited to 1 request/second;

For Plus users or the sales level is 2, it is limited to 2 requests/second;

For Prime users or the sales level is 3, it is limited to 4 requests/second;

For Advanced users or the sales level is 4 or 5, it is limited to 6 requests/second.



Interface Field Definition

Appendix 1 全球错误码



Sub-link:

<https://developers.cjdropshipping.cn/en/api/start/sandbox.html>
(<https://developers.cjdropshipping.cn/en/api/start/sandbox.html>)

Sandbox | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 全局错误码 Global Error Codes

Appendix 2 国家代码 Country Code

Appendix 3 平台 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Sandbox

1. CJ sandbox account is a test account under production environment

2. The conditions to apply for a sandbox account:

1. The sandbox account's balance should be \$0 which could be adjusted after it's created.
2. It is irreversible once the CJ account is configured as a sandbox account.

3. Creating Sandbox account currently has not open to the public, but you could reach your agent to help you apply for it.

4. Sandbox account is applied to production environment, so the token is the same with the production token.

5. It is recommended to prepare 2 accounts:

1. A production account.
2. A sandbox account



Webhook

Interface Definition



Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/setting.html>
(<https://developers.cjdropshipping.cn/en/api/api2/api/setting.html>)

2 Settings | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 11%[API](#) Global Error Codes

Appendix 21%[API](#) Country Code

Appendix 31%[API](#) Platforms

Interface

1 Authentication

2 Setting

1 Settings

1.1 Get Settings1%[GET](#)1%

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

2 Settings

1 Settings

1.1 Get Settings1%[GET](#)1%

Account settings include profile, API quota limits, general API QPS limits, sandbox account, etc.

URL

<https://developers.cjdropshipping.com/api2.0/v1/setting/get> (<https://developers.cjdropshipping.com/api2.0/v1/setting/get>)

CURL

```
curl --location --request GET 'https://developers.cjdropshipping.com/api2.0/v1/setting/get'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "openId": 1, "openName": "121 2322", "openEmail": "v0pjsw5t@linshiyouxang.net", "setting": { "quotaLimits": [ {
"quotaUrl": "/api2.0/v1/setting/account/get", "quotaLimit": 74, "quotaType": 0 }, "qpsLimit": 100 }, "callback": { "product": { "type": "ENABLE", "urls": ["https://your-domain.com/api2.0/"]
}, "order": { "type": "CANCEL", "urls": [ ] } }, "root": "GENERAL", "isSandbox": false }, "requestId": "ea5896b0-273d-4b49-8c54-ad8f025a49b8" }
```

Field

Definition

Type

Length

Note

openId

Account ID

string

200

openName

Account name

string

200

openEmail

Account Email

string

200

setting

Settings

list

200

quotaLimits

Quota limits

list

Applicable on specific URLs

quotaUrl

Quota URL

string

200

quotaLimit

Quota limit

int

20

quotaType

Quota Type

byte

4

0-total/1-per year/2-per quarter/3-per month/4-per day/5-per hour

qpsLimit

QPS limit

int

20

account Queries per second

root

Root access

string

200

root/NO_PERMISSION - not authorized

GENERAL - general account

VIP - VIP account

ADMIN - administrator

isSandbox

(Whether) Sandbox account

byte

4

error

{ "code": 1601000, "result": false, "message": "User not find", "data": null, "requestId": "a18c9793-7c99-42f9-970b-790eecdceba2" }

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

1 Authentication

3 Product

â€œ

Sub-link:

<https://developers.cjdropshipping.cn/en/api/start/utils.html>
(<https://developers.cjdropshipping.cn/en/api/start/utils.html>)

Practical Tool | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Postman API Application Example

Postman Introduction

Postman API Interface

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 174 Global Error Codes

Appendix 214 Country Code

Appendix 314 Platforms

Interface

1 Authentication

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

Practical Tool

Postman API Application Example

Postman Introduction

Postman is an API development tool which helps to build, test and modify APIs.

Download14

postman

(opens new window)

Postman API Interface

Procedure

Check C.J Docs to get interface.

Set environment variables.

Interface call.

Environment Setup

Postman Environments Setup in Postman Environments

Environment Variable

Description

Note

host

Domain Name

<https://developers.cjdropshipping.com> (<https://developers.cjdropshipping.com>).

token

For Authentication

email

Email

Required for Login

password

Password

Required for Login

Example

accessToken

Get Access-token

Platform Waybill Order Processing

accessToken

Sub-link:

<https://developers.cjdropshipping.cn/en/api/api2/api/auth.html>

(<https://developers.cjdropshipping.cn/en/api/api2/api/auth.html>)

1 Authentication | CJ Docs

Introduction

Start

Development

Get Access-token

Practical Tool

Platform Waybill Order Processing

Webhook

Sandbox

API

Standard

Interface Definition

Interface Field Definition

Interface Call Restrictions

Appendix 1 1 Global Error Codes

Appendix 2 2 Country Code

Appendix 3 3 Platforms

Interface

1 Authentication

1 Authentication

1.1 Get access token 1 POST

1.2 Refresh access token 1 POST

1.3 Logout Token 1 POST

2 Setting

3 Product

4 Storage

5 Shopping

6 Logistic

7 Dispute

8 Webhook

1 Authentication

1 Authentication

1.1 Get access token (POST)

Token-based authentication, the life of an access token is 15 days, and the life of a refresh token is 180 days. You can request new access tokens with refresh token when access token expires. You need to log in when refresh token expires.

Can only be called once every 5 minutes

URL

<https://developers.cjdropshipping.com/api2.0/v1/authentication/getAccessToken> (<https://developers.cjdropshipping.com/api2.0/v1/authentication/getAccessToken>)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/authentication/getAccessToken'  
--header 'Content-Type: application/json'  
--data-raw '{ "apiKey": "CJUserNum@api@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx" }'
```

Parameter

Definition

Type

Required

Length

Note

apiKey

CJ API Key

string

Y

200

Get API Key

(opens new window)

How to get Api Key:

Go to

Get API Key

(opens new window)

and click button "Generate"

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "openId": 123456789, "accessToken": "f59ac98193d64d62a9e887abea830369", "accessTokenExpiryDate": "2021-08-18T09:16:33+08:00", "refreshToken": "f7edabe65c3b4a198b50ca8f969e36eb", "refreshTokenExpiryDate": "2022-02-07T09:16:33+08:00", "createDate": "2021-08-11T09:16:33+08:00", "requestId": "8b3d9ea1-00c3-4d10-9e2b-d18041d98080" }
```

Field

Definition

Type

Length
Note
openId
Open Id
Long
20
accessToken
access token
string
200
accessTokenExpiryDate
access token expiry time
string
200
Default 15 days
refreshToken
Refresh Token
string
200
refreshTokenExpiryDate
Refresh Token expiry time
string
200
Default 180 days
createDate
Created date
string
200
error
{ "code": 1601000, "result": false, "message": "User not find", "data": null, "requestId": "a18c9793-7c99-42f9-970b-790eecdceba2" }
Field
Definition
Type
Length
Note
code
Error code
int
20

Return to error codes

result

Whether returned

boolean

1

message

Return message

string

200

data

Data return

requestId

Request ID

string

48

For error inquiry

1.2 Refresh access token (POST)

An API security mechanism with which the expiry date of access token can be refreshed. The life of an access token is 15 days.

URL

<https://developers.cjdropshipping.com/api2.0/v1/authentication/refreshAccessToken> (https://developers.cjdropshipping.com/api2.0/v1/authentication/refreshAccessToken)

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/authentication/refreshAccessToken'
--header 'Content-Type: application/json'
--data-raw '{ "refreshToken": "3d3b01404da04be8b6795d7e9823cee5" }'
```

Parameter

Definition

Type

Required

Length

Note

refreshToken

Refresh Token

string

Y

80

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": { "accessToken": "f59ac98193d64d62a9e887abea830369", "accessTokenExpiryDate": "2021-08-18T09:16:33+08:00",
"refreshToken": "f7edabe65c3b4a198b50ca8f969e36eb", "refreshTokenExpiryDate": "2022-02-07T09:16:33+08:00", "createDate": "2021-08-11T09:16:33+08:00" }, "requestId":
"8b3d9ea1-00c3-4d10-9e2b-d18041d98080" }
```

Field
Definition
Type
Length
Note
accessToken
access token
string
200
accessTokenExpiryDate
access token Expiry Time
string
200
Default 15 days
refreshToken
Refresh Token
string
200
refreshTokenExpiryDate
Refresh Token Expiry Time
string
200
Default 180 days
createDate
Created Date
string
200
error
{ "code": 1600003, "result": false, "message": "Refresh token is failure", "data": null, "requestId": "0b20dc1a-0043-43a7-a7c0-51ca6c61d976" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code

result

Whether or not the return is normal

boolean

1

message

return message

string

200

data

return data

object

interface data return

requestId

requestId

string

48

Flag request for logging errors

1.3 Logout Token!%(POST)!

API security mechanism. After logging out, access token and refresh token will expire.

URL

<https://developers.cjdropshipping.com/api2.0/v1/authentication/logout> (<https://developers.cjdropshipping.com/api2.0/v1/authentication/logout>).

CURL

```
curl --location --request POST 'https://developers.cjdropshipping.com/api2.0/v1/authentication/logout'
--header 'CJ-Access-Token: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'
```

Return

success

```
{ "code": 200, "result": true, "message": "Success", "data": true, "requestId": "b1d3728d-8a29-417e-9983-6df9926aaa49" }
```

Field

Definition

Type

Length

Note

code

error code

int

20

Reference error code

result

Whether or not the return is normal

boolean
1
message
return message
string
200
data
return data
object
interface data return
requestId
requestId
string
48
Flag request for logging errors
error
{ "code": 1600001, "result": false, "message": "Authentication failed", "data": null, "requestId": "5aa2bb6e-42fa-4e0a-ae88-1833c2c1c883" }
Field
Definition
Type
Length
Note
code
error code
int
20
Reference error code
result
Whether or not the return is normal
boolean
1
message
return message
string
200
data
return data
object
interface data return

requestId

requestId

string

48

Flag request for logging errors

â€œ

Appendix 317457 Platforms

2 Setting

â€œ