OpenDRIVE® 1.8.1, Static Road Network Description, 2024-11-21

List of figures

Figure	Description
Figure 1	Relationship between ASAM OpenDRIVE, ASAM OpenCRG, and ASAM OpenSCENARIO
Figure 2	UML notation (see ISO TS 19103, Geographic information - Conceptual schema language)
Figure 3	UML attribute notation
Figure 4	UML class diagram of the Core class
Figure 5	UML class diagram of the Header class
Figure 6	UML class diagram of the Core class
Figure 7	Available coordinate systems in ASAM OpenDRIVE
Figure 8	Coordinate systems in ASAM OpenDRIVE interacting with another
Figure 9	Summary of coordinate system in ASAM OpenDRIVE
Figure 10	Reference-line-based s/t-coordinate system with origin at the beginning of the road
Figure 11	Inertial coordinate system with defined rotations
Figure 12	Inertial coordinate system with defined rotations
Figure 13	Road reference line coordinate system
Figure 14	Road reference line coordinate system with defined rotations
Figure 15	Heading in road reference line

Figure	Description
Figure 16	Roll in road reference line by superelevation
Figure 17	Elevation in road reference line
Figure 18	Local coordinate system with defined rotations
Figure 19	Local coordinate systems with heading, pitch, roll
Figure 20	Local coordinate system with respect to road reference line coordinate system
Figure 21	geoReference and offset
Figure 22	Geometry elements in ASAM OpenDRIVE
Figure 23	Example for creating a road reference line from geometry elements
Figure 24	Individual parts of a road
Figure 25	UML class diagram of the RoadGeometry class, including the road reference line elements
Figure 26	A straight line
Figure 27	Road geometry described by a spiral
Figure 28	Road geometry described by an arc
Figure 29	A parametric cubic curve for interpolation of the u-coordinate
Figure 30	A parametric cubic curve for interpolation of the v-coordinate
Figure 31	A parametric cubic curve
Figure 32	A cubic polynomial
Figure 33	A curve which cannot be represented by a cubic polynomial w.r.t x parameter
Figure 34	Transformation from a u/v to a x/y coordinate system with a=b=0

Figure	Description
Figure 35	Transformation from a u/v to a x/y coordinate system with a!=0 and b!=0
Figure 36	UML class diagram of the Road class
Figure 37	UML class diagram of the RoadGeometry class
Figure 38	Allowed, prohibited, and recommended road linkage
Figure 39	Allowed cases of road linkage
Figure 40	Allowed case of road linkage within a junction
Figure 41	UML class diagram of the Link class
Figure 42	Types of elevation
Figure 43	Superelevation
Figure 44	Minimum t-definition range for road shapes
Figure 45	Road shape definition
Figure 46	Road shape definition in combination with superelevation
Figure 47	Cross section surface strips on a road
Figure 48	Cross section surface
Figure 49	Road surface as defined in a CRG file
Figure 50	ASAM OpenCRG road surface description using u/v coordinates and x/y coordinates
Figure 51	Positioning of an ASAM OpenCRG file along the reference line
Figure 52	ASAM OpenCRG attachment mode, attached
Figure 53	ASAM OpenCRG attached mode with elevation

Figure	Description
Figure 54	ASAM OpenCRG attached0 mode with elevated reference line
Figure 55	ASAM OpenCRG attachment mode, genuine
Figure 56	ASAM OpenCRG orientation
Figure 57	Center lane for road with lanes of different driving directions
Figure 58	Center lane for road with lanes of identical driving direction
Figure 59	UML class diagram of the Lanes class
Figure 60	Lane grouping with left, center, right
Figure 61	Road section with lane sections
Figure 62	Lane sections defined separately for both sides of the road
Figure 63	Lane offset
Figure 64	Lane links for road with id 10
Figure 65	Example of an ending bikeway
Figure 66	Example of a splitting driving lane
Figure 67	UML class diagram of the t_road_lanes_laneSection_lcr_lane_link element in the Lanes class
Figure 68	UML model for lane geometry in the Lanes class
Figure 69	Change of lane width per lane section
Figure 70	Lane with varying border shape
Figure 71	Lane height
Figure 72	Lanes excluded from road elevation

Figure	Description
Figure 73	UML class diagram of the Lanes class
Figure 74	Lane types for a motorway
Figure 75	Lane types for a rural road
Figure 76	Lane types for an urban road
Figure 77	Lane types for motorway exit and entry
Figure 78	Lane types for motorway connecting to another motorway
Figure 79	Lane-specific speed limits
Figure 80	Lane access, bus lane
Figure 81	UML class diagram of the RoadMark class
Figure 82	UML class diagram of the Junction class
Figure 83	Types of roads in a junction (right-hand traffic)
Figure 84	Connecting roads of junction with id 1 (left hand traffic)
Figure 85	Example of a cross path with a pedestrian crossing in a common junction
Figure 86	Direct junction
Figure 87	Direct junction with overlapping lanes
Figure 88	Junction with multiple overlapping lanes on two roads
Figure 89	Junction with multiple overlapping lanes on multiple roads
Figure 90	Junction with crossing traffic and multiple overlapping lanes on multiple roads
Figure 91	Example of a virtual junction showing a parking lot entry and exit

Figure	Description
Figure 92	Example of a cross path with a pedestrian crossing
Figure 93	Virtual junction with virtual connections
Figure 94	Example of a crossing with a railroad track
Figure 95	Junction reference line ~red arrow~
Figure 96	UML class diagram of the JunctionGeometry class
Figure 97	Junction boundary formed by segments
Figure 98	Example of a minimal elevation grid attached to a junction reference line
Figure 99	Example of an elevation grid with more points
Figure 100	Point P in the elevation grid
Figure 101	Points around P relevant for interpolations
Figure 102	Tangents and cubic splines relevant for interpolation
Figure 103	Three segments of a junction boundary and the corner points P_0, P_1, P_2, and P_3 of the polygon at an incoming road
Figure 104	Polygon and the lines AB and CD through the point P
Figure 105	Junction group with three junctions
Figure 106	UML class diagram of the JunctionGroup class
Figure 107	Example of a junction with 20 traffic lights mapped into six signal groups (IDs 42-47)
Figure 108	Circular and angular object
Figure 109	Placing objects on roads
Figure 110	UML class diagram of the Objects class

Figure	Description
Figure 111	Repeated large angular object
Figure 112	Repeated small angular objects
Figure 113	Repeated small circular objects
Figure 114	Traffic island as object
Figure 115	Object described by corner road coordinates
Figure 116	An object described by `<cornerLocal>` coordinates
Figure 117	Example of the bounding box and skeleton of a traffic light pole
Figure 118	Example of the skeleton of a tree
Figure 119	Parking spaces rectangular (left figure) and rhomboid (right figure)
Figure 120	Crosswalk in ASAM OpenDRIVE
Figure 121	Tunnel
Figure 122	Bridge
Figure 123	CRG for objects
Figure 124	Signals in ASAM OpenDRIVE
Figure 125	Width and height for signal
Figure 126	Orientation and hOffset for signal
Figure 127	UML class diagram of the Signals class
Figure 128	Lanes with signals in the shape of road marks
Figure 129	Lane and type specific speed limit

Figure	Description
Figure 130	UML model of the t_road_signals_signalReference element in the Signals class
Figure 131	Example of a junction with 20 traffic lights mapped into six signal groups (IDs 42-47)
Figure 132	Example of a signal program that defines the signal cycles for the signal groups
Figure 133	UML class diagram of the Controller class
Figure 134	multiStaticSign from XML example above
Figure 135	UML class diagram of the SignalGroup class
Figure 136	UML class diagram of the Semantics class
Figure 137	Junction with signals at physical and logical positions
Figure 138	UML class diagram of the t_physicalPosition element in the Signals class
Figure 139	UML class diagram of the Railroad class
Figure 140	Road reference lines for roads and railroads
Figure 141	Railroad switches
Figure 142	Railroad stations
Figure 143	UML class diagram of the Station class