

## Оглавление

<b>Введение</b>	<b>3</b>
<b>1 Аналитический раздел</b>	<b>4</b>
1.1 Формализация цели . . . . .	4
1.2 Структуры ядра . . . . .	4
1.2.1 task_struct . . . . .	4
<b>2 Конструкторский раздел</b>	<b>9</b>
2.1 Диаграмма вариантов использования . . . . .	9
<b>3 Технологический раздел</b>	<b>10</b>
3.1 Выбор и обоснование языка программирования и среды разработки . . . . .	10
3.2 Пример кода, да? . . . . .	10
<b>4 Исследовательский раздел</b>	<b>11</b>
4.1 Бла-бла . . . . .	11
<b>ЗАКЛЮЧЕНИЕ</b>	<b>12</b>
<b>СПИСОК ИСПОЛЬЗОВАННЫХ ИСТОЧНИКОВ</b>	<b>13</b>
<b>ПРИЛОЖЕНИЕ 1</b>	<b>14</b>

# **ВВЕДЕНИЕ**

\*\*\* Линух – сложная система со своим видением планирования процессов на выполнение и всё такое.

# 1. Аналитический раздел

В данном разделе...

## 1.1 Формализация цели

Цель работы – разработать загружаемый модуль ядра для мониторинга приоритетов, времени выполнения и простоя процессов на ОС Linux и проанализировать с использованием данного модуля воспроизведение аудиофайлов и видеофайлов.

Для достижения поставленной цели потребуется:

- 1) проанализировать структуры ядра, позволяющие определить приоритет, время выполнения и простоя процессов;
- 2) проанализировать способы доступа к выбранным структурам ядра;
- 3) проанализировать методы передачи информации из модуля ядра в пространство пользователя;
- 4) спроектировать и реализовать загружаемый модуль ядра;
- 5) проанализировать с использованием реализованного модуля воспроизведение аудиофайлов и видеофайлов.

## 1.2 Структуры ядра

Современные операционные системы предоставляют пользователю фундаментальные концепции, такие как, файл или процесс. [?]

С использованием документации представляется возможность получить доступ к данным концепциям и изучить работу системы изнутри.

### 1.2.1 task\_struct

Процесс состоит из нескольких компонентов [?]:

- стек процесса;
- регистры процессора, в которые загружены ключевые переменные (зависит от архитектуры);
- адресное пространство;
- ресурсы: дескрипторы открытых файлов, ожидающие обработки сигналы;
- управляющие структуры ядра ОС.

Структура в ядре Linux, соответствующая каждому процессу, – task\_struct. Она определена в файле include/linux/sched.h. Все процессы существующие в системе процессы объединены в кольцевой список. [?]

Стоит отметить, что данная структура занимает в памяти порядка 1.7 килобайт.

Поля структуры содержат информацию о процессе, которую можно поделить на несколько категорий [?]:

- поля, отвечающие за общую информацию о процессе (PID, exit\_code, PPID);
- поля, востребованные планировщиком задач (prio, static\_prio, timeslice);
- поля, связанные с безопасностью (uid, gid).

Структура task\_struct для Linux v5.16rc8 представлена в приложении (см. Приложение 1).

Далее будут отмечены наиболее информативные в проводимой работе поля данной структуры и их назначение.

PID (Process Identifier) – уникальный идентификатор процесса. Каждый процесс в операционной системе имеет свой уникальный идентификатор, по которому можно получить информацию об этом процессе, а также направить ему управляющий сигнал или завершить [?].

prio, static\_prio, normal\_prio, rt\_priority – приоритеты процесса.

Значение prio – это значение, которое использует планировщик задач при выборе процесса. Чем ниже значение данной переменной, тем выше приоритет процесса (может принимать значения от 0 до 139, то есть MAX\_PRIO, значение которого вычисляется с использованием переменной MAX\_RT\_PRIO со значением 100) [?]. Также данный приоритет может быть поделён на два интервала:

- от 0 до 99 – процесс реального времени;
- от 100 до 139 – обычный процесс.

Также определены функции определения приоритета процесса, которые приведены в листинге 2.

Листинг 1: Функции определения приоритета процесса, определенные в /kernel/sched.c

```
1  #include "sched_idletask.c"
2  #include "sched_fair.c"
3  #include "sched_rt.c"
4  #ifdef CONFIG_SCHED_DEBUG
5  #include "sched_debug.c"
```

```

6  #endif
7
8  /*
9   * __normal_prio - return the priority that is based on
    ↳ the static prio
10  */
11  static inline int __normal_prio(struct task_struct *p) //
    ↳ _NORMAL_PRIO function, return static priority value
12  {
13      return p->static_prio;
14  }
15
16  /*
17   * Calculate the expected normal priority: i.e. priority
18   * without taking RT-inheritance into account. Might be
19   * boosted by interactivity modifiers. Changes upon fork,
20   * setprio syscalls, and whenever the interactivity
21   * estimator recalculates.
22   */
23  static inline int normal_prio(struct task_struct *p) //
    ↳ NORMAL_PRIO function
24  {
25      int prio;
26
27      if (task_has_rt_policy(p)) // The task_has_rt_policy
        ↳ function, the determination process is a real-time
        ↳ process, if the real-time process, returns 1,
        ↳ otherwise returns 0
28          prio = MAX_RT_PRIO-1 - p->rt_priority; // The
            ↳ process is real-time process, and the PRIO
            ↳ value is related to the real-time priority
            ↳ value: PRIO = MAX_RT_PRIO -1 - P-> rt_priority
29      else
30          prio = __normal_prio(p); // The process is a
            ↳ non-real-time process, then the PRIO value is
            ↳ a static priority value, that is, PRIO = P->
            ↳ static_prio
31      return prio;
32  }
33
34  /*

```

```

35  * Calculate the current priority, i.e. the priority
36  * taken into account by the scheduler. This value might
37  * be boosted by RT tasks, or might be boosted by
38  * interactivity modifiers. Will be RT if the task got
39  * RT-boosted. If not then it returns p->normal_prio.
40  */
41  static int effective_prio(struct task_struct *p) // The
    ↳ Effective_Prio function, the effective priority of the
    ↳ calculation process, the PRIO value, this value is the
    ↳ priority value used by the final scheduler
42  {
43      p->normal_prio = normal_prio(p); // Calculate the
    ↳ value of Normal_PRIO
44      /*
45       * If we are RT tasks or we were boosted to RT
    ↳ priority,
46       * keep the priority unchanged. Otherwise, update
    ↳ priority
47       * to the normal priority:
48       */
49      if (!rt_prio(p->prio))
50          return p->normal_prio; // If the process is a
    ↳ non-real-time process, return normal_prio
    ↳ value, at this time Normal_Prio = Static_Prio
51      return p->prio; // Otherwise, the return value is
    ↳ constant, still PRIO value, at this time, PRIO =
    ↳ MAX_RT_PRIO - 1 - P-> RT_Priority
52  }
53
54  /*****/
55  void set_user_nice(struct task_struct *p, long nice)
56  {
57      ...
58      p->prio = effective_prio(p); // In the function
    ↳ set_user_nice, call the Effective_Prio function to
    ↳ set the process's PRIO value.
59      ...
60  }

```

Из предоставленного листинга видно, что для процессов реального вре-

мени значение приоритета определяется с использованием поля `prio`, а в ином случае – `static_prio`.

Значение `static_prio` не изменяется ядром при работе планировщика, однако оно может быть изменено с использованием пользовательского приоритета `nice`. Макросы для изменения данного приоритета предоставлены в листинге ??.

Листинг 2: Функции определения приоритета процесса, определенные в `/kernel/sched.c`

```
1  /*
2   * Convert user-nice values [ -20 ... 0 ... 19 ]
3   * to static priority [ MAX_RT_PRIO..MAX_PRIO-1 ],
4   * and back.
5   */
6  #define NICE_TO_PRIO(nice)      (MAX_RT_PRIO + (nice) + 20)
7  #define PRIO_TO_NICE(prio)      ((prio) - MAX_RT_PRIO - 20)
8  #define TASK_NICE(p)            PRIO_TO_NICE((p)->static_prio)
9
10 /*
11  * 'User priority' is the nice value converted to
12  * ↪ something we
13  * can work with better when scaling various scheduler
14  * ↪ parameters,
15  * it's a [ 0 ... 39 ] range.
16  */
17 #define USER_PRIO(p)            ((p) - MAX_RT_PRIO)
18 #define TASK_USER_PRIO(p)       USER_PRIO((p)->static_prio)
19 #define MAX_USER_PRIO           (USER_PRIO(MAX_PRIO))
20
21 / *** /
22 p->static_prio = NICE_TO_PRIO(nice);
```

## Вывод

В разделе...

## 2. Конструкторский раздел

В данном разделе...

### 2.1 Диаграмма вариантов использования

На рисунках 2.1–2.2 предоставлены примеры картинок.




Рис. 2.1: Какой-то пример.




Рис. 2.2: Вторая часть какого-то примера.

### Вывод

В разделе...



### 3. Технологический раздел

В данном разделе...

### 3.1 Выбор и обоснование языка программирования и среды разработки

При написании программного продукта был использован язык программирования...

Данный выбор обусловлен следующими факторами:

- бла,
- бла,
- (голосом того парня из майнкрафта) БЛЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯЯ

При разработке использовалась среда... Данный выбор обусловлен тем, что...

### 3.2 Пример кода, да?

## Вывод

В качестве средств реализации были выбраны...

В разделе были предоставлены сведения о...

Была рассмотрена...

## **4. Исследовательский раздел**

В данном разделе...

### **4.1 Бла-бла**

Мы такие умные, куча исследований...

### **Вывод**

В разделе...

# ЗАКЛЮЧЕНИЕ

Во время выполнения курсового проекта были достигнуты поставленные задачи:

- хоп,
- хоп,
- хоп,
- хоп,
- хоп.

Проведённая аналитическая работа позволила...

В результате работы, проведенной в конструкторском разделе, были приведены... Также была определена схема работы...

Для реализации в качестве используемого языка программирования был выбран ЯП ..., а в качестве среды разработки – ...

В результате работы было...

В ходе выполнения поставленных задач были получены знания в области ..., а также изучены...

# **СПИСОК ИСПОЛЬЗОВАННЫХ ИСТОЧНИКОВ**

## **Список литературы**

# ПРИЛОЖЕНИЕ 1

Листинг 3: Структура ядра task\_struct

```
1  struct task_struct {
2  #ifdef CONFIG_THREAD_INFO_IN_TASK
3      /*
4       * For reasons of header soup (see
5       * ↪ current_thread_info()), this
6       * must be the first element of task_struct.
7       */
8      struct thread_info      thread_info;
9  #endif
10     unsigned int             __state;
11
12     #ifdef CONFIG_PREEMPT_RT
13         /* saved state for "spinlock sleepers" */
14         unsigned int         saved_state;
15     #endif
16
17     /*
18      * This begins the randomizable portion of
19      * ↪ task_struct. Only
20      * scheduling-critical items should be added above
21      * ↪ here.
22      */
23     randomized_struct_fields_start
24
25     void                    *stack;
26     refcount_t              usage;
27     /* Per task flags (PF_*), defined further below: */
28     unsigned int            flags;
29     unsigned int            ptrace;
30
31     #ifdef CONFIG_SMP
32         int                 on_cpu;
33         struct __call_single_node wake_entry;
34         unsigned int         wakee_flips;
35         unsigned long         wakee_flip_decay_ts;
36         struct task_struct    *last_wakee;
```

```

34
35     /*
36     * recent_used_cpu is initially set as the last CPU
37     *   ↳ used by a task
38     * that wakes affine another task. Waker/wakee
39     *   ↳ relationships can
40     * push tasks around a CPU where each wakeup moves to
41     *   ↳ the next one.
42     * Tracking a recently used CPU allows a quick search
43     *   ↳ for a recently
44     * used CPU that may be idle.
45     */
46
47     int                recent_used_cpu;
48     int                wake_cpu;
49 #endif
50
51     int                on_rq;
52
53     int                prio;
54     int                static_prio;
55     int                normal_prio;
56     unsigned int       rt_priority;
57
58     struct sched_entity se;
59     struct sched_rt_entity rt;
60     struct sched_dl_entity dl;
61     const struct sched_class *sched_class;
62
63 #ifdef CONFIG_SCHED_CORE
64     struct rb_node      core_node;
65     unsigned long        core_cookie;
66     unsigned int         core_occupation;
67 #endif
68
69 #ifdef CONFIG_CGROUP_SCHED
70     struct task_group    *sched_task_group;
71 #endif
72
73 #ifdef CONFIG_UCLAMP_TASK
74     /*
75     * Clamp values requested for a scheduling entity.
76     * Must be updated with task_rq_lock() held.
77     */
78

```

```

71     */
72     struct uclamp_se          uclamp_req[UCLAMP_CNT];
73     /*
74     * Effective clamp values used for a scheduling
75     ↪ entity.
76     * Must be updated with task_rq_lock() held.
77     */
78     struct uclamp_se          uclamp[UCLAMP_CNT];
79 #endif
80
81     struct sched_statistics    stats;
82
83 #ifdef CONFIG_PREEMPT_NOTIFIERS
84     /* List of struct preempt_notifier: */
85     struct hlist_head          preempt_notifiers;
86 #endif
87
88 #ifdef CONFIG_BLK_DEV_IO_TRACE
89     unsigned int                btrace_seq;
90 #endif
91
92     unsigned int                policy;
93     int                          nr_cpus_allowed;
94     const cpumask_t              *cpus_ptr;
95     cpumask_t                    *user_cpus_ptr;
96     cpumask_t                    cpus_mask;
97     void                          *migration_pending;
98 #ifdef CONFIG_SMP
99     unsigned short                migration_disabled;
100 #endif
101
102     unsigned short                migration_flags;
103
104 #ifdef CONFIG_PREEMPT_RCU
105     int                          rcu_read_lock_nesting;
106     union rcu_special              rcu_read_unlock_special;
107     struct list_head              rcu_node_entry;
108     struct rcu_node                *rcu_blocked_node;
109 #endif /* #ifdef CONFIG_PREEMPT_RCU */
110
111 #ifdef CONFIG_TASKS_RCU
112     unsigned long                rcu_tasks_nvcsw;

```

```

111         u8                rcu_tasks_holdout;
112         u8                rcu_tasks_idx;
113         int               rcu_tasks_idle_cpu;
114         struct list_head   rcu_tasks_holdout_list;
115     #endif /* #ifdef CONFIG_TASKS_RCU */
116
117     #ifdef CONFIG_TASKS_TRACE_RCU
118         int               trc_reader_nesting;
119         int               trc_ipi_to_cpu;
120         union rcu_special   trc_reader_special;
121         bool              trc_reader_checked;
122         struct list_head   trc_holdout_list;
123     #endif /* #ifdef CONFIG_TASKS_TRACE_RCU */
124
125         struct sched_info   sched_info;
126
127         struct list_head    tasks;
128     #ifdef CONFIG_SMP
129         struct plist_node    pushable_tasks;
130         struct rb_node       pushable_dl_tasks;
131     #endif
132
133         struct mm_struct     *mm;
134         struct mm_struct     *active_mm;
135
136         /* Per-thread vma caching: */
137         struct vmacache      vmacache;
138
139     #ifdef SPLIT_RSS_COUNTING
140         struct task_rss_stat   rss_stat;
141     #endif
142         int                 exit_state;
143         int                 exit_code;
144         int                 exit_signal;
145         /* The signal sent when the parent dies: */
146         int                 pdeath_signal;
147         /* JOBCTL_*, siglock protected: */
148         unsigned long        jobctl;
149
150         /* Used for emulating ABI behavior of previous Linux
        ↪ versions: */

```



```

151         unsigned int                personality;
152
153         /* Scheduler bits, serialized by scheduler locks: */
154         unsigned                    sched_reset_on_fork:1;
155         unsigned                    sched_contributes_to_load:1;
156         unsigned                    sched_migrated:1;
157     #ifdef CONFIG_PSI
158         unsigned                    sched_psi_wake_requeue:1;
159     #endif
160
161         /* Force alignment to the next boundary: */
162         unsigned                    :0;
163
164         /* Unserialized, strictly 'current' */
165
166         /*
167          * This field must not be in the scheduler word above
168          * ↪ due to wakelist
169          * ↪ queueing no longer being serialized by p->on_cpu.
170          * ↪ However:
171          *
172          * p->XXX = X;                ttwu()
173          * schedule()                 if (p->on_rq && ..) //
174          * ↪ false
175          * smp_mb__after_spinlock();    if
176          * ↪ (smp_load_acquire(&p->on_cpu) && //true
177          * deactivate_task()
178          * ↪ ttwu_queue_wakelist())
179          * p->on_rq = 0;                p->sched_remote_wakeup
180          * ↪ = Y;
181          *
182          * guarantees all stores of 'current' are visible
183          * ↪ before
184          * ->sched_remote_wakeup gets used, so it can be in
185          * ↪ this word.
186          */
187         unsigned                    sched_remote_wakeup:1;
188
189         /* Bit to tell LSMs we're in execve(): */
190         unsigned                    in_execve:1;
191         unsigned                    in_iowait:1;

```

```

184 #ifndef TIF_RESTORE_SIGMASK
185     unsigned                restore_sigmask:1;
186 #endif
187 #ifdef CONFIG_MEMCG
188     unsigned                in_user_fault:1;
189 #endif
190 #ifdef CONFIG_COMPAT_BRK
191     unsigned                brk_randomized:1;
192 #endif
193 #ifdef CONFIG_CGROUPS
194     /* disallow userland-initiated cgroup migration */
195     unsigned                no_cgroup_migration:1;
196     /* task is frozen/stopped (used by the cgroup freezer)
       ↪ */
197     unsigned                frozen:1;
198 #endif
199 #ifdef CONFIG_BLK_CGROUP
200     unsigned                use_memdelay:1;
201 #endif
202 #ifdef CONFIG_PSI
203     /* Stalled due to lack of memory */
204     unsigned                in_memstall:1;
205 #endif
206 #ifdef CONFIG_PAGE_OWNER
207     /* Used by page_owner=on to detect recursion in page
       ↪ tracking. */
208     unsigned                in_page_owner:1;
209 #endif
210 #ifdef CONFIG_EVENTFD
211     /* Recursion prevention for eventfd_signal() */
212     unsigned                in_eventfd_signal:1;
213 #endif
214
215     unsigned long           atomic_flags; /* Flags
       ↪ requiring atomic access. */
216
217     struct restart_block    restart_block;
218
219     pid_t                   pid;
220     pid_t                   tgid;
221

```

```

222 #ifdef CONFIG_STACKPROTECTOR
223     /* Canary value for the -fstack-protector GCC feature:
224     ↪ */
225     unsigned long          stack_canary;
226 #endif
227     /*
228     * Pointers to the (original) parent process, youngest
229     ↪ child, younger sibling,
230     * older sibling, respectively. (p->father can be
231     ↪ replaced with
232     * p->real_parent->pid)
233     */
234
235     /* Real parent process: */
236     struct task_struct __rcu    *real_parent;
237
238     /* Recipient of SIGCHLD, wait4() reports: */
239     struct task_struct __rcu    *parent;
240
241     /*
242     * Children/sibling form the list of natural children:
243     */
244     struct list_head          children;
245     struct list_head          sibling;
246     struct task_struct        *group_leader;
247
248     /*
249     * 'ptraced' is the list of tasks this task is using
250     ↪ ptrace() on.
251     *
252     * This includes both natural children and
253     ↪ PTRACE_ATTACH targets.
254     * 'ptrace_entry' is this task's link on the
255     ↪ p->parent->ptraced list.
256     */
257     struct list_head          ptraced;
258     struct list_head          ptrace_entry;
259
260     /* PID/PID hash table linkage. */
261     struct pid                *thread_pid;
262     struct hlist_node          pid_links[PIDTYPE_MAX];

```

```

257     struct list_head      thread_group;
258     struct list_head      thread_node;
259
260     struct completion      *vfork_done;
261
262     /* CLONE_CHILD_SETTID: */
263     int __user             *set_child_tid;
264
265     /* CLONE_CHILD_CLEARTID: */
266     int __user             *clear_child_tid;
267
268     /* PF_IO_WORKER */
269     void                   *pf_io_worker;
270
271     u64                    utime;
272     u64                    stime;
273 #ifdef CONFIG_ARCH_HAS_SCALED_CPUTIME
274     u64                    utimescaled;
275     u64                    stimescaled;
276 #endif
277     u64                    gtime;
278     struct prev_cputime     prev_cputime;
279 #ifdef CONFIG_VIRT_CPU_ACCOUNTING_GEN
280     struct vtime           vtime;
281 #endif
282
283 #ifdef CONFIG_NO_HZ_FULL
284     atomic_t               tick_dep_mask;
285 #endif
286     /* Context switch counts: */
287     unsigned long          nvcs;
288     unsigned long          nivcs;
289
290     /* Monotonic time in nsecs: */
291     u64                    start_time;
292
293     /* Boot based time in nsecs: */
294     u64                    start_boottime;
295
296     /* MM fault and swap info: this can arguably be seen
    ↪ as either mm-specific or thread-specific: */

```

```

297         unsigned long             min_flt;
298         unsigned long             maj_flt;
299
300         /* Empty if CONFIG_POSIX_CPUTIMERS=n */
301         struct posix_cputimers     posix_cputimers;
302
303     #ifdef CONFIG_POSIX_CPU_TIMERS_TASK_WORK
304         struct posix_cputimers_work posix_cputimers_work;
305     #endif
306
307         /* Process credentials: */
308
309         /* Tracer's credentials at attach: */
310         const struct cred __rcu     *ptracer_cred;
311
312         /* Objective and real subjective task credentials
313          * ↪ (COW): */
314         const struct cred __rcu     *real_cred;
315
316         /* Effective (overridable) subjective task credentials
317          * ↪ (COW): */
318         const struct cred __rcu     *cred;
319
320     #ifdef CONFIG_KEYS
321         /* Cached requested key. */
322         struct key                  *cached_requested_key;
323     #endif
324
325         /*
326          * executable name, excluding path.
327          *
328          * - normally initialized setup_new_exec()
329          * - access it with [gs]et_task_comm()
330          * - lock it with task_lock()
331          */
332         char                        comm[TASK_COMM_LEN];
333
334         struct nameidata            *nameidata;
335
336     #ifdef CONFIG_SYSVIPC
337         struct sysv_sem             sysvsem;

```

```

336     struct sysv_shm                sysvshm;
337 #endif
338 #ifdef CONFIG_DETECT_HUNG_TASK
339     unsigned long                  last_switch_count;
340     unsigned long                  last_switch_time;
341 #endif
342     /* Filesystem information: */
343     struct fs_struct                *fs;
344
345     /* Open file information: */
346     struct files_struct             *files;
347
348 #ifdef CONFIG_IO_URING
349     struct io_uring_task            *io_uring;
350 #endif
351
352     /* Namespaces: */
353     struct nsproxy                  *nsproxy;
354
355     /* Signal handlers: */
356     struct signal_struct            *signal;
357     struct sighand_struct __rcu     *sighand;
358     sigset_t                        blocked;
359     sigset_t                        real_blocked;
360     /* Restored if set_restore_sigmask() was used: */
361     sigset_t                        saved_sigmask;
362     struct sigpending               pending;
363     unsigned long                   sas_ss_sp;
364     size_t                          sas_ss_size;
365     unsigned int                    sas_ss_flags;
366
367     struct callback_head            *task_works;
368
369 #ifdef CONFIG_AUDIT
370 #ifdef CONFIG_AUDITSYSCALL
371     struct audit_context            *audit_context;
372 #endif
373     kuid_t                         loginuid;
374     unsigned int                    sessionid;
375 #endif
376     struct seccomp                  seccomp;

```

```

377     struct syscall_user_dispatch    syscall_dispatch;
378
379     /* Thread group tracking: */
380     u64                parent_exec_id;
381     u64                self_exec_id;
382
383     /* Protection against (de-)allocation: mm, files, fs,
384      ↪ tty, keyrings, mems_allowed, mempolicy: */
385     spinlock_t        alloc_lock;
386
387     /* Protection of the PI data structures: */
388     raw_spinlock_t    pi_lock;
389
390     struct wake_q_node    wake_q;
391
392 #ifdef CONFIG_RT_MUTEXES
393     /* PI waiters blocked on a rt_mutex held by this task:
394      ↪ */
395     struct rb_root_cached    pi_waiters;
396     /* Updated under owner's pi_lock and rq lock */
397     struct task_struct        *pi_top_task;
398     /* Deadlock detection and priority inheritance
399      ↪ handling: */
400     struct rt_mutex_waiter    *pi_blocked_on;
401 #endif
402
403 #ifdef CONFIG_DEBUG_MUTEXES
404     /* Mutex deadlock detection: */
405     struct mutex_waiter        *blocked_on;
406 #endif
407
408 #ifdef CONFIG_DEBUG_ATOMIC_SLEEP
409     int                non_block_count;
410 #endif
411
412 #ifdef CONFIG_TRACE_IRQFLAGS
413     struct irqtrace_events    irqtrace;
414     unsigned int            hardirq_threaded;
415     u64                hardirq_chain_key;
416     int                softirqs_enabled;
417     int                softirq_context;

```

```

415         int                                irq_config;
416     #endif
417     #ifdef CONFIG_PREEMPT_RT
418         int                                softirq_disable_cnt;
419     #endif
420
421     #ifdef CONFIG_LOCKDEP
422     # define MAX_LOCK_DEPTH                48UL
423         u64                                curr_chain_key;
424         int                                lockdep_depth;
425         unsigned int                        lockdep_recursion;
426         struct held_lock                    held_locks[MAX_LOCK_DEPTH];
427     #endif
428
429     #if defined(CONFIG_UBSAN) && !defined(CONFIG_UBSAN_TRAP)
430         unsigned int                        in_ubsan;
431     #endif
432
433     /* Journalling filesystem info: */
434     void                                    *journal_info;
435
436     /* Stacked block device info: */
437     struct bio_list                        *bio_list;
438
439     /* Stack plugging: */
440     struct blk_plug                        *plug;
441
442     /* VM state: */
443     struct reclaim_state                    *reclaim_state;
444
445     struct backing_dev_info                *backing_dev_info;
446
447     struct io_context                        *io_context;
448
449     #ifdef CONFIG_COMPACTION
450         struct capture_control                *capture_control;
451     #endif
452     /* Ptrace state: */
453     unsigned long                            ptrace_message;
454     kernel_siginfo_t                        *last_siginfo;
455

```



```

456     struct task_io_accounting    ioac;
457 #ifdef CONFIG_PSI
458     /* Pressure stall state */
459     unsigned int                psi_flags;
460 #endif
461 #ifdef CONFIG_TASK_XACCT
462     /* Accumulated RSS usage: */
463     u64                          acct_rss_mem1;
464     /* Accumulated virtual memory usage: */
465     u64                          acct_vm_mem1;
466     /* stime + utime since last update: */
467     u64                          acct_timexpd;
468 #endif
469 #ifdef CONFIG_CPUSETS
470     /* Protected by ->alloc_lock: */
471     nodemask_t                  mems_allowed;
472     /* Sequence number to catch updates: */
473     seqcount_spinlock_t         mems_allowed_seq;
474     int                          cpuset_mem_spread_rotor;
475     int                          cpuset_slab_spread_rotor;
476 #endif
477 #ifdef CONFIG_CGROUPS
478     /* Control Group info protected by css_set_lock: */
479     struct css_set __rcu         *cgroups;
480     /* cg_list protected by css_set_lock and
481      ↪ tsk->alloc_lock: */
481     struct list_head            cg_list;
482 #endif
483 #ifdef CONFIG_X86_CPU_RESCTRL
484     u32                          closid;
485     u32                          rmid;
486 #endif
487 #ifdef CONFIG_FUTEX
488     struct robust_list_head __user *robust_list;
489 #ifdef CONFIG_COMPAT
490     struct compat_robust_list_head __user
491         ↪ *compat_robust_list;
491 #endif
492     struct list_head            pi_state_list;
493     struct futex_pi_state        *pi_state_cache;
494     struct mutex                futex_exit_mutex;

```

```

495         unsigned int                futex_state;
496     #endif
497     #ifdef CONFIG_PERF_EVENTS
498         struct
499             ↪ perf_event_context      *perf_event_ctxp[perf_nr_task_contexts];
500         struct mutex                perf_event_mutex;
501         struct list_head            perf_event_list;
502     #endif
503     #ifdef CONFIG_DEBUG_PREEMPT
504         unsigned long                preempt_disable_ip;
505     #endif
506     #ifdef CONFIG_NUMA
507         /* Protected by alloc_lock: */
508         struct mempolicy             *mempolicy;
509         short                        il_prev;
510         short                        pref_node_fork;
511     #endif
512     #ifdef CONFIG_NUMA_BALANCING
513         int                          numa_scan_seq;
514         unsigned int                 numa_scan_period;
515         unsigned int                 numa_scan_period_max;
516         int                          numa_preferred_nid;
517         unsigned long                 numa_migrate_retry;
518         /* Migration stamp: */
519         u64                          node_stamp;
520         u64                          last_task_numa_placement;
521         u64                          last_sum_exec_runtime;
522         struct callback_head          numa_work;
523
524         /*
525          * This pointer is only modified for current in
526          * ↪ syscall and
527          * pagefault context (and for tasks being destroyed),
528          * ↪ so it can be read
529          * from any of the following contexts:
530          * - RCU read-side critical section
531          * - current->numa_group from everywhere
532          * - task's runqueue locked, task not running
533          */
534         struct numa_group __rcu      *numa_group;
535     #endif

```

```

533     /*
534     * numa_faults is an array split into four regions:
535     * faults_memory, faults_cpu, faults_memory_buffer,
536     * ↪ faults_cpu_buffer
537     * in this precise order.
538     *
539     * faults_memory: Exponential decaying average of
540     * ↪ faults on a per-node
541     * basis. Scheduling placement decisions are made
542     * ↪ based on these
543     * counts. The values remain static for the duration
544     * ↪ of a PTE scan.
545     * faults_cpu: Track the nodes the process was running
546     * ↪ on when a NUMA
547     * hinting fault was incurred.
548     * faults_memory_buffer and faults_cpu_buffer: Record
549     * ↪ faults per node
550     * during the current scan window. When the scan
551     * ↪ completes, the counts
552     * in faults_memory and faults_cpu decay and these
553     * ↪ values are copied.
554     */
555     unsigned long          *numa_faults;
556     unsigned long          total_numa_faults;
557
558     /*
559     * numa_faults_locality tracks if faults recorded
560     * ↪ during the last
561     * scan window were remote/local or failed to migrate.
562     * ↪ The task scan
563     * period is adapted based on the locality of the
564     * ↪ faults with different
565     * weights depending on whether they were shared or
566     * ↪ private faults
567     */
568     unsigned long          numa_faults_locality[3];
569
570     unsigned long          numa_pages_migrated;
571 #endif /* CONFIG_NUMA_BALANCING */
572
573 #ifdef CONFIG_RSEQ

```

```

562     struct rseq __user *rseq;
563     u32 rseq_sig;
564     /*
565      * RmW on rseq_event_mask must be performed atomically
566      * with respect to preemption.
567      */
568     unsigned long rseq_event_mask;
569 #endif
570
571     struct tlbflush_unmap_batch    tlb_ubic;
572
573     union {
574         refcount_t                rcu_users;
575         struct rcu_head            rcu;
576     };
577
578     /* Cache last used pipe for splice(): */
579     struct pipe_inode_info         *splice_pipe;
580
581     struct page_frag              task_frag;
582
583 #ifdef CONFIG_TASK_DELAY_ACCT
584     struct task_delay_info         *delays;
585 #endif
586
587 #ifdef CONFIG_FAULT_INJECTION
588     int                            make_it_fail;
589     unsigned int                   fail_nth;
590 #endif
591     /*
592      * When (nr_dirtied >= nr_dirtied_pause), it's time to
593      ↪ call
594      * balance_dirty_pages() for a dirty throttling pause:
595      */
596     int                            nr_dirtied;
597     int                            nr_dirtied_pause;
598     /* Start of a write-and-pause period: */
599     unsigned long                   dirty_paused_when;
600
601 #ifdef CONFIG_LATENCYTOP
602     int                            latency_record_count;

```

```

602     struct
        ↳ latency_record          latency_record[LT_SAVECOUNT];
603 #endif
604     /*
605      * Time slack values; these are used to round up
        ↳ poll() and
606      * select() etc timeout values. These are in
        ↳ nanoseconds.
607      */
608     u64          timer_slack_ns;
609     u64          default_timer_slack_ns;
610
611 #if defined(CONFIG_KASAN_GENERIC) ||
        ↳ defined(CONFIG_KASAN_SW_TAGS)
612     unsigned int      kasan_depth;
613 #endif
614
615 #ifdef CONFIG_KCSAN
616     struct kcsan_ctx      kcsan_ctx;
617 #ifdef CONFIG_TRACE_IRQFLAGS
618     struct irqtrace_events      kcsan_save_irqtrace;
619 #endif
620 #endif
621
622 #if IS_ENABLED(CONFIG_KUNIT)
623     struct kunit          *kunit_test;
624 #endif
625
626 #ifdef CONFIG_FUNCTION_GRAPH_TRACER
627     /* Index of current stored address in ret_stack: */
628     int          curr_ret_stack;
629     int          curr_ret_depth;
630
631     /* Stack of return addresses for return function
        ↳ tracing: */
632     struct ftrace_ret_stack      *ret_stack;
633
634     /* Timestamp for last schedule: */
635     unsigned long long      ftrace_timestamp;
636
637     /*

```

```

638     * Number of functions that haven't been traced
639     * because of depth overrun:
640     */
641     atomic_t          trace_overrun;
642
643     /* Pause tracing: */
644     atomic_t          tracing_graph_pause;
645 #endif
646
647 #ifdef CONFIG_TRACING
648     /* State flags for use by tracers: */
649     unsigned long      trace;
650
651     /* Bitmask and counter of trace recursion: */
652     unsigned long      trace_recursion;
653 #endif /* CONFIG_TRACING */
654
655 #ifdef CONFIG_KCOV
656     /* See kernel/kcov.c for more details. */
657
658     /* Coverage collection mode enabled for this task (0
659      ↪ if disabled): */
659     unsigned int       kcov_mode;
660
661     /* Size of the kcov_area: */
662     unsigned int       kcov_size;
663
664     /* Buffer for coverage collection: */
665     void               *kcov_area;
666
667     /* KCOV descriptor wired with this task or NULL: */
668     struct kcov        *kcov;
669
670     /* KCOV common handle for remote coverage collection:
671      ↪ */
671     u64                kcov_handle;
672
673     /* KCOV sequence number: */
674     int                kcov_sequence;
675
676     /* Collect coverage from softirq context: */

```

```

677         unsigned int                kcov_softirq;
678     #endif
679
680     #ifdef CONFIG_MEMCG
681         struct mem_cgroup             *memcg_in_oom;
682         gfp_t                         memcg_oom_gfp_mask;
683         int                           memcg_oom_order;
684
685         /* Number of pages to reclaim on returning to
        ↪ userland: */
686         unsigned int                 memcg_nr_pages_over_high;
687
688         /* Used by memcontrol for targeted memcg charge: */
689         struct mem_cgroup             *active_memcg;
690     #endif
691
692     #ifdef CONFIG_BLK_CGROUP
693         struct request_queue          *throttle_queue;
694     #endif
695
696     #ifdef CONFIG_UPROBES
697         struct uprobe_task            *utask;
698     #endif
699     #if defined(CONFIG_BCACHE) ||
    ↪ defined(CONFIG_BCACHE_MODULE)
700         unsigned int                 sequential_io;
701         unsigned int                 sequential_io_avg;
702     #endif
703         struct kmap_ctrl              kmap_ctrl;
704     #ifdef CONFIG_DEBUG_ATOMIC_SLEEP
705         unsigned long                 task_state_change;
706     # ifdef CONFIG_PREEMPT_RT
707         unsigned long                 saved_state_change;
708     # endif
709     #endif
710         int                           pagefault_disabled;
711     #ifdef CONFIG_MMU
712         struct task_struct            *oom_reaper_list;
713     #endif
714     #ifdef CONFIG_VMAP_STACK
715         struct vm_struct              *stack_vm_area;

```

```

716 #endif
717 #ifdef CONFIG_THREAD_INFO_IN_TASK
718     /* A live task holds one reference: */
719     refcount_t          stack_refcount;
720 #endif
721 #ifdef CONFIG_LIVEPATCH
722     int patch_state;
723 #endif
724 #ifdef CONFIG_SECURITY
725     /* Used by LSM modules for access restriction: */
726     void                *security;
727 #endif
728 #ifdef CONFIG_BPF_SYSCALL
729     /* Used by BPF task local storage */
730     struct bpf_local_storage __rcu    *bpf_storage;
731     /* Used for BPF run context */
732     struct bpf_run_ctx      *bpf_ctx;
733 #endif
734
735 #ifdef CONFIG_GCC_PLUGIN_STACKLEAK
736     unsigned long          lowest_stack;
737     unsigned long          prev_lowest_stack;
738 #endif
739
740 #ifdef CONFIG_X86_MCE
741     void __user            *mce_vaddr;
742     __u64                  mce_kflags;
743     u64                    mce_addr;
744     __u64                  mce_ripv : 1,
745                             mce_whole_page : 1,
746                             __mce_reserved : 62;
747     struct callback_head    mce_kill_me;
748     int                    mce_count;
749 #endif
750
751 #ifdef CONFIG_KRETPROBES
752     struct llist_head       kretprobe_instances;
753 #endif
754
755 #ifdef CONFIG_ARCH_HAS_PARANOID_L1D_FLUSH
756     /*

```



```

757     * If L1D flush is supported on mm context switch
758     * then we use this callback head to queue kill work
759     * to kill tasks that are not running on SMT disabled
760     * cores
761     */
762     struct callback_head      lld_flush_kill;
763 #endif
764
765     /*
766     * New fields for task_struct should be added above
767     ↪ here, so that
768     * they are included in the randomized portion of
769     ↪ task_struct.
770     */
771     randomized_struct_fields_end
772
773     /* CPU-specific state of this task: */
774     struct thread_struct      thread;
775
776     /*
777     * WARNING: on x86, 'thread_struct' contains a
778     ↪ variable-sized
779     * structure. It *MUST* be at the end of
780     ↪ 'task_struct'.
781     *
782     * Do not put anything below here!
783     */
784 };

```