

General Purpose System Simulation

The system to be simulated in GPSS is described as a block diagram in which block represents the activities and lines joining the blocks indicate the sequence in which the activities can be executed. Where there is choice of activities more than one line leaves a block and the condition for the choice is stated at the block. Each block must give precise meaning. There are 48 specific blocks. Each of which represents a characteristic action of systems. The program should be written using these block diagrams.

Entities of the system depend upon the nature of the system. For eg in simulation of a communication system movement of messages, in road transportation moving of vehicles are entities. These entities are called transactions. The sequence of events in real time is reflected in movement of transactions from block to block in simulated time.

Transactions starts from generate block and stops at terminate block. Transaction is hold in block and most blocks can hold many transactions simultaneously. Transfer of transaction from one block to another occurs instantaneously at a specific time or when some change of system condition occurs.


Action Times

Clock time is represented by an integral number with the interval of real time corresponding to a unit of time chosen by the program user. **ADVANCE** blocks represents the expenditure of time. The program computes an interval of time called action time for each transactions as it enters an ADVANCE block, and the transaction remain at this block for this interval of simulated time before attempting to proceed.

Another block that represents action time is **GENERATE** block that creates transaction. The action time at this block controls the interval between successive arrivals of transactions.

Action time may be fixed interval or a random variable and it can depend upon the conditions in the system in various ways. An action time is defined by giving a mean and modifier as A and B fields for the block. If modifier is zero, the action time is a constant equal to mean. If modifier is a positive number greater than or equals to mean, the action time is an integer random variable chosen from the range **mean ± modifier** with equal probability of occurrence given to each number in the range.

Functions can be introduced to relate input and output variable. By specifying modifier at Advance or Generate block to be a function, the value of function controls the action time. The action time is derived by multiplying the mean by value of function.



Field A and field B in both blocks are mean and modifier. The fields c, d, e, f in generate block indicates:

c- offset (arrival time of first entity)

d- count (number of arrivals of entity)

e- priority (low and high priority of entity)

f- parameters (gives data types)

Succession of Events

The program maintains records of when each transaction in the system is due to move. It proceeds by completing all movements that are scheduled for execution at a particular instant of time. When there is more than one transactions to move, the program processes transactions in order of priority with first-come-first serve basis.

Transactions do not spend time at any block other than at an ADVANCE block. The program begins moving transaction through the block diagram until one of several circumstances arises. The transaction may enter on ADVANCE block with a non-zero action time, the program will turn its attention to other transactions in the system and return to the transaction when the action time has been expanded.

Secondly – A condition arises that the transaction is attempting to execute by entering block cannot be performed at the current time. The transaction is said to be blocked and it remains at the block it last entered. The program will automatically detect when the blocking condition is removed and will start the transaction at that time.

A third possibility is that transaction enters TERMINATE block in which case it is removed from simulation.

Fourth possibility is that a transaction may be put on a chain. When the program has moved one transaction as far it can go, it turns to other transactions that is to move at same time instant. If all such movements are complete, the program advances the clock to the time of next most imminent event and repeats the process of executing events.


Choice of path

TRANSFER block

The TRANSFER block is used for choice of path .It allows to select the location other than the next sequential block choice is between two blocks. Selection factor in field A gives the choice to next block in field B and C. If there is no choice selection factor is left blank. An unconditional transfer is then made to next block A.

Two modes of choice


- 1) A random choice can be made by setting the selection factor, S. The probability of going to next block A, is then $1-S$ and to C is S.
- 2) A conditional mode, indicated by setting field A to BOTH, allows a transaction to select an alternate path depending upon existing conditions. The transaction moves to next block B if this move is possible, or to C if it is not possible. If both are impossible, transaction waits for first to become possible, giving preference to B.



Terminate Block


Terminate block is used to end the simulation in GPSS. There may be multiple terminate block in a program but there must be at least one terminate block with nonzero field.

Terminate block is circular shape with a tail on it with field 1.



Example

A machine tool in a manufacturing shop is turning parts at the rate of one every 5 minutes. As they are finished, the parts go to an inspector who takes 4 ± 3 minutes to examine each one and rejects about 10% of the parts. Each part will be represented by one transaction and the time unit selected for the problem will be minute. Simulate it for 1000 parts.



Manufacturing shop model-1

Here, GENERATE block is used to represent the output of the machine by creating one transaction every five units of time. An ADVANCE block with a mean of 4 and modifier of 3 is used to represent inspection. The time spent on inspection will therefore be any one of the values 1, 2, 3, 4, 5, 6 or 7 with equal probability given to each value. Upon completion of inspection, transaction go to a TRANSFER block with

a selection factor of 0.1, so that 90% of the parts go to next location called ACC to represent accepted parts and 10% go to another location called REJ to represent rejected parts. There is no history thus both locations are to TERMINATE block.

Location						Operation												Operation Field										Comments															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39					

An * in column 1 results in the statement being printed in output only. A field from 2 to 6 contains location of blocks where it is necessary. The GPSS program will automatically assign sequential location as it reads the statements, so it is not necessary to assign locations. The transfer block needs to make reference to TERMINATE blocks to which it sends transactions.

The second section of coding from columns 8 to 18 contains the block type name, which must begin in column 8. From 19, a series of fields may be present each separated by commas and having no blanks. Any line following the first blank is treated as comment. The meaning of field depends upon block type.

The program accepts input in a free format in which the location field, if used, begins in column 1, but none of other fields has a fixed starting points. A single block marks the transaction from the location field to the operation field and from operation to operand field. If no location is specified an initial blank is used. The free format is very convenient hen entering input from a terminal, since it minimizes the number of characters that have to be entered. The fixed format is easier to use.

For TRANSFER block, the first field is selection factor B and C fields are exit 1 and 2 respectively. In this case exit 1 is the next sequential block, ACC can be omitted from TRANSFER and TERMINATE block. Comma must be used to show that field B is missing. So TRANSFER block would be coded as TRANSFER 1, , REJ. If there is unconditional transfer, then also a comma should be included to indicate the field i.e. TRANSFER, REJ.

Program runs until a certain count is reached terminating transactions. TERMINATE block has field A that carries a number indicating by how much termination count is incremented. The number should be

positive or zero. But there must be at least one non zero TERMINATE block. In our example there is one in both block thus 1 should be added in both bad and good inspection.

In last line of coding there is a control statement START. Here the START statement is set to 1000. When START is read, the program begins execution. When simulation is completed, the program prints an output report.

BLOCK NUMBER	*LOC	OPERATION SIMULATE	A,B,C,D,E,F,G,H,I	COMMENTS	STATEMENT NUMBER
	*	MANUFACTURING SHOP - MODEL 1			1
1		GENERATE	5	CREATE PARTS	2
2		ADVANCE	4,3	INSPECT	3
3		TRANSFER	.1,ACC,REJ	SELECT REJECTS	4
4	ACC	TERMINATE	1	ACCEPTED PARTS	5
5	REJ	TERMINATE	1	REJECTED PARTS	6
	*	START	1000	RUN 1000 PARTS	7
					8
					9
					10
					11

SYMBOL	NUMBER	CROSS-REFERENCE BLOCKS	REFERENCES
ACC	4		7
REJ	5		7

SIMULATE		
* MANUFACTURING SHOP - MODEL 1		
*		
1	GENERATE	5
2	ADVANCE	4,3
3	TRANSFER	.100,4,5
4	TERMINATE	1
5	TERMINATE	1
*		
	START	1000

RELATIVE CLOCK		5005	ABSOLUTE CLOCK	5005
BLOCK COUNTS				
BLOCK CURRENT	TOTAL			
1	0	1001		
2	1	1001		
3	0	1000		
4	0	888		
5	0	112		

Problem input is printed first, with the locations listed from left and a sequential statement number on right. Then table of symbolic location to each symbol.

The first line of output following the listings gives the time at which simulation stop. Time is followed by listing block counts. Two numbers are shown for each block. On the left is count of how many transactions were in the block at simulation stop time and on right is a figure showing total number of transactions entering the block during simulation.

The results show that the counts at block 4 and 5 were 888 and 112 respectively showing 1000 parts inspected i.e. 88.8% accepted and 11.2% rejected.

Facilities and Storages

A facility is defined as an entity that can be engaged by a single transaction at a time. A storage is defined as an entity that can be occupied by many transactions at a time, up to some predetermined limit. A transaction controlling a facility can be interrupted or preempted by another transaction.

There can be many instances of each type of entity to a limit set by the program. Entities are identified by number. 0 cannot be assigned. User may assign numbers in any order or symbolic names can also be assigned.

Eg

Types of System	Transaction	Facility	Storage
Communications	Message	Switch	Trunk
Transportation	Car	Tollbooth	Road
Data processing	Record	Key Punch	Computer Memory

SEIZE, RELEASE, ENTER and LEAVE are used for facilities and storages.




Field A in each case indicates which facility or storage is intended, and the choice is usually marked in the flag attached to the symbols of the blocks. The SEIZE block allows a transaction to engage a facility if it is available. The RELEASE block allows the transaction to disengage facility.

Enter block allows a transaction to occupy space in a storage if available and LEAVE block allows it to give up the space. If field B of the ENTER and LEAVE block are blank, the storage content are changed by 1. If there is a number ≥ 1 , then the contents change by that value. Number of blocks can be used between the points where facility is seized and released to simulate the actions. Similar is the case for storage.

Example of manufacturing shop has average inspection time 4 and average generate rates of parts 5 minutes. There will be normally one part inspected at a time. A new part can arrive before the inspection

of previous one. Thus there will be more than one transaction in ADVANCE block at one time. Assuming for only one inspector and the inspector should be represented by facility.




```

* MANUFACTURING SHOP - MODEL 2
*
1  GENERATE 5
2  SEIZE 1
3  ADVANCE 4,3
4  RELEASE 1
5  TRANSFER .1,ACC,REJ
6  TERMINATE 1
7  TERMINATE 1
ACC
REJ
*
START 1000 RUN 1000 PARTS
5435 ABSOLUTE CLOCK 5435

RELATIVE CLOCK
BLOCK COUNTS
BLOCK CURRENT TOTAL
1 1 1001
2 0 1000
3 0 1000
4 0 1000
5 0 1000
6 0 900
7 0 100


*****
* FACILITIES
*
*****

FACILITY NUMBER AVERAGE -AVERAGE UTILIZATION DURING- PERCE
ENTRIES TIME/TRAN TOTAL AVAIL. UNAVAIL. CURRENT AVAILABI
1 1000 3.995 .735 TIME TIME TIME STATUS STATUS
100.1

```

The result show inspector was busy for 73.5% of his time. If more than one inspector is available, they can be represented by storage with capacity equal to no. of inspector. SEIZE and RELEASE in the figure should be replaced by ENTER and LEAVE.

Eg Inspection time were 3 times as long as before, and there is 3 inspector, then storage should be added. STORAGE statement has location field which identifies it and operation field A has the capacity greater than or equal to 2. The difference between ENTER, LEAVE and SIEZE, RELEASE is that in facility transaction that grabs entity should free the entity but is not necessary all transactions should free storage. Entering and leaving is different actions in storage.



* MANUFACTURING SHOP - MODEL 3

RELATIVE CLOCK	BLOCK COUNTS	BLOCK CURRENT	TOTAL
1	1	1	1003
2	0	0	1002
3	2	2	1002
4	0	0	1000
5	0	0	1000
6	0	0	893
7	0	0	107

STORAGE	CAPACITY	AVERAGE CONTENTS	ENTRIES	AVERAGE TIME/UNIT	-AVERAGE TOTAL TIME	UTILIZATION AVAIL. TIME	DURING CURRENT CONTENTS	MAXIMUM CONTENTS
1	3	2.256	1002	12.059	.752		2	3


 * STORAGES *

Gathering statistics

The **QUEUE**, **DEPART**, **MARK**, **TABULATE** block are used for gathering statistics.

When the conditions for advancing a transaction are not satisfied several transactions may be kept waiting at a block. When the conditions are favorable they are moved with first-in, first-out basis. The **QUEUE** block increases and **DEPART** block decreases the queue numbered in field A. If field B is blank the change is a unit change otherwise value of B is ≥ 1 .

MARK and **TABULATE** gives the length of time taken by transactions to move through the system. The **MARK** block notes the time of arrival. The **TABULATE** block subtracts the time noted by **MARK** block from the time of arrival at **TABULATE** block. The transit time is entered in table whose number or name is indicated in field A of **TABULATE**. If transaction entering **TABULATE** block is not passed through **MARK** block, the transit time is derived by using as a base the time at which transaction was created.



```


* MANUFACTURING SHOP - MODEL 4
*
1  GENERATE      5      CREATE PARTS
2  QUEUE         1      QUEUE FOR AN INSPECTOR
3  ENTER         1      GET AN INSPECTOR
4  DEPART        1      LEAVE QUEUE
5  MARK
6  ADVANCE      12,9    INSPECT
7  LEAVE         1      FREE INSPECTOR
8  TABULATE      1      MEASURE TRANSIT TIME
9  TRANSFER      1,ACC,REJ SELECT REJECTS
10 ACC          1      ACCEPTED PARTS
11 REJ          1      REJECTED PARTS
*
1  STORAGE       3      NUMBER OF INSPECTORS
1  TABLE       M1,5,5,10 TABULATION INTERVALS
*
START          1000      RUN FOR 1000 PARTS

```

RELATIVE CLOCK			5005 ABSOLUTE CLOCK		
BLOCK COUNTS			5005		
BLOCK	CURRENT	TOTAL	BLOCK	CURRENT	TOTAL
1	0	1000	11	0	108
2	0	1000			
3	0	1000			
4	0	1000			
5	0	1000			
6	0	1000			
7	0	1000			
8	0	1000			
9	0	1000			
10	0	1000			
		892			

Conditional Transfers

Again consider the case of three inspectors and the manufactured parts are put on a conveyor which carries the parts to the inspector at intervals along the conveyor. It takes 2 minutes for a part to reach the first inspector; if it is free it takes the part for inspection else it takes further 2 minutes to reach to second inspector who will take it if its free else it passes to the part to third inspector which again takes 2 minutes otherwise they are lost. To keep the model small only the transit time of the parts are recorded and the possibility of inspector rejecting parts are ignored.



```

* MANUFACTURING
1  GENERATE 5
2  ADVANCE 2
3  TRANSFER BOTH,,CONV1
4  SEIZE 1
5  ADVANCE 12,9
6  RELEASE 1
7  TABULATE 1
8  TERMINATE 1
9  CREATE PARTS
10 PLACE ON CONVEYOR
11 MOVE TO FIRST INSPECTOR
12 GET FIRST INSPECTOR
13 INSPECT
14 FREE INSPECTOR
15 MEASURE TRANSIT TIME
16
17
18
19
20
21 CONV1 ADVANCE 2
22 TRANSFER BOTH,,CONV2
23 SEIZE 2
24 ADVANCE 12,9
25 RELEASE 2
26 TRANSFER ,TAB
27 PLACE ON CONVEYOR
28 MOVE TO SECOND INSPECTOR
29 GET SECOND INSPECTOR
30 INSPECT
31 FREE INSPECTOR
32
33
34
35
36
37
38
39
40
41 CONV2 ADVANCE 2
42 TRANSFER BOTH,,CONV2
43 SEIZE 3
44 ADVANCE 12,9
45 RELEASE 3
46 TRANSFER ,TAB
47 PLACE ON CONVEYOR
48 MOVE TO THIRD INSPECTOR
49 GET THIRD INSPECTOR
50 INSPECT
51 FREE INSPECTOR
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002

```


BLOCK COUNTS			BLOCK CURRENT			BLOCK CURRENT		
BLOCK	CURRENT	TOTAL	BLOCK	CURRENT	TOTAL	BLOCK	CURRENT	TOTAL
1	0	1117	11	0	343	21	0	118
2	0	1117	12	0	343			
3	0	1118	13	0	344			
4	0	406	14	0	344			
5	1	406	15	1	369			
6	0	406	16	0	368			
7	0	1000	17	0	250			
8	0	1000	18	0	250			
9	0	712	19	0	250			
10	0	712	20	0	250			

```

*****
*                                     *
*                               FACILITIES                               *
*                                     *
*****

```

FACILITY	NUMBER ENTRIES	AVERAGE TIME/TRAN	-AVERAGE UTILIZATION DURING-			CURRENT STATUS	PERCENT AVAILABILITY
			TOTAL TIME	AVAIL. TIME	UNAVAIL. TIME		
1	407	11.885	.865				100.0
2	344	11.956	.736				100.0
3	250	12.244	.547				100.0

Program Control Statement

The first statement of GPSS input is a control statement SIMULATE in operation field. Without this statement problem will be assembled but not in use.

Simulation run can be restart or stop and can also repeat changing value to some extent. When GPSS simulation run is finished, the program does not destroy the model immediately. It looks input following the START statements. Input following the START statement can change the model. A STORAGE statement can be inserted giving new value. The model can also be changed by changing existing block or adding new blocks. When the desired changes is made the model reruns with another START statement.

RESET is another control statement. It is used to wipe out all the statistics gathered. It will leave the system loaded with transactions to gather statistics in second run. The output of first run is then not of interest and is used as NP in field B of START. One start statement has run the model for 10 completed transactions. A RESET statement has wipe out the statistics in that run. The second START statement has restarted the simulation from the point of 10th transaction and has continued for 100 transactions.

The RESET statement also sets relative clock to zero. Absolute clock gives the time since the run began. Relative clock gives the time since the last reset statement. If reset is not used both time are same.

CLEAR statement wipes out the statistics and transactions in the system, so that rerun starts the simulation from the beginning. The CLEAR statements return the model to its initial state. It does not reset the random number generator seeds. The sequence of statements

START

CLEAR

START

would run the same problem twice but second run would use a different sets of random numbers.

JOB wipes out the entire model preceding the statement and proceed with following problem.

END terminates all simulation. SIMULATE statement appears only once even if there are multiple jobs.