

Question **1**

Correct

Danny has a possible list of passwords of Manny's facebook account. All passwords length is odd. But Danny knows that Manny is a big fan of palindromes. So, his password and reverse of his password both should be in the list.

You have to print the length of Manny's password and it's middle character.

Note: The solution will be unique.

INPUT

The first line of input contains the integer N , the number of possible passwords.

Each of the following N lines contains a single word, its length being an odd number greater than 2 and lesser than **14**. All characters are lowercase letters of the English alphabet.

OUTPUT

The first and only line of output must contain the length of the correct password and its central letter.

CONSTRAINTS

$$1 \leq N \leq 100$$

SAMPLE INPUT

4
abc
def
feg
cba

SAMPLE OUTPUT

3 b

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.


```
#include <stdio.h>
#include <string.h>

int main() {

    int n, flag = 0;
    char temp;
    scanf("%d", &n);
    char words[n][14];
    for (int i = 0; i<n; i++) {
        scanf("%s", words[i]);
    }
    char rev[14];
    for (int i = 0; i<n-1; i++) {
        strcpy(rev, words[i]);
        int size = strlen(rev);
        for (int k = 0; k<size/2; k++) {
            temp = rev[k];
            rev[k] = rev[size-k-1];
            rev[size-k-1] = temp;
        }
        for (int j = i+1; j<n; j++) {
            if (strcmp(rev, words[j]) == 0) {
                flag = 1;
                break;
            }
        }
        if (flag == 1) {
            break;
        }
    }
}
```

	Input	Expected	Got	
✓	4 abc def	3 b	3 b	✓

	Input	Expected	Got	
	feg cba			

Passed all tests! 

Question **2**

Correct

Joey loves to eat Pizza. But he is worried as the quality of pizza made by most of the restaurants is deteriorating. The last few pizzas ordered by him did not taste good 😞 . Joey is feeling extremely hungry and wants to eat pizza. But he is confused about the restaurant from where he should order. As always he asks Chandler for help.

Chandler suggests that Joey should give each restaurant some points, and then choose the restaurant having **maximum points**. If more than one restaurant has same points, Joey can choose the one with **lexicographically smallest** name.

Joey has assigned points to all the restaurants, but can't figure out which restaurant satisfies Chandler's criteria. Can you help him out?

Input:

First line has N, the total number of restaurants.

Next N lines contain Name of Restaurant and Points awarded by Joey, separated by a space. Restaurant name has **no spaces**, all lowercase letters and will not be more than 20 characters.

Output:

Print the name of the restaurant that Joey should choose.

Constraints:

$$1 \leq N \leq 10^5$$

$$1 \leq \text{Points} \leq 10^6$$

SAMPLE INPUT

3

Pizzeria 108

Dominos 145

Pizzapizza 49

SAMPLE OUTPUT

Dominos

Explanation

Dominos has maximum points.

Answer: (penalty regime: 0 %)


Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include <stdio.h>
#include <string.h>
int main() {
    int n;
    scanf("%d", &n);
    char res[n][21];
    int rate[n];
    for (int i = 0; i<n; i++) {
        scanf("%s", res[i]);
        scanf("%d", &rate[i]);
    }
    int max = rate[0];
    char ans[20];
    strcpy(ans, res[0]);
    for (int i = 1; i<n; i++) {
        if (rate[i]>max) {
            max = rate[i];
            strcpy(ans, res[i]);
        } else if (rate[i] == max) {
            if (strcmp(res[i], ans) < 0) {
                strcpy(ans, res[i]);
            }
        }
    }
}
```

	Input	Expected	Got	
✓	3 Pizzeria 108	Dominos	Dominos	✓

	Input	Expected	Got	
	Dominos 145			
	Pizzapizza 49			

Passed all tests! 

Question **3**

Correct

These days Bechan Chacha is depressed because his crush gave him list of mobile number some of them are valid and some of them are invalid. Bechan Chacha has special power that he can pick his crush number only if he has valid set of mobile numbers. Help him to determine the valid numbers.

You are given a string "S" and you have to determine whether it is Valid mobile number or not. Mobile number is valid only if it is of length 10 , consists of numeric values and it shouldn't have prefix zeroes.

Input:

First line of input is T representing total number of test cases.

Next T line each representing "S" as described in in problem statement.

Output:

Print "YES" if it is valid mobile number else print "NO".

Note: Quotes are for clarity.

Constraints:

$$1 \leq T \leq 10^3$$

$$\text{sum of string length} \leq 10^5$$

SAMPLE INPUT

3

1234567890

0123456789

0123456.87

SAMPLE OUTPUT

YES

NO

NO

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include <stdio.h>
#include <string.h>
int main() {
    int t;
    scanf("%d",&t);
    while(t--){
        int flag=1;
        char s[100000];
        scanf("%s",s);
        int k=strlen(s);
        if (k==10) {
            for(int i=0; i<10; i++){
                if (s[i]=='0') {
                    flag=0;
                    break;
                }
                if ((s[i]<'0')||(s[i]>'9')) {
                    flag=0;
                    break;
                }
            }
        } else {
            flag=0;
        }
        if (flag==1) {
            printf("YES\n");
        } else {
            printf("NO\n");
        }
    }
}
```

	Input	Expected	Got	
✓	3	YES	YES	✓
	1234567890	NO	NO	
	0123456789	NO	NO	
	0123456.87			

Passed all tests! 