


AgenticVision: 360° Wearable Perception Neckband

Ergonomically contoured edge-AI wearable delivering continuous surround perception & spoken spatial guidance



CORE PHYSICAL ARCHITECTURE

Designed to solve the fatal flaw of smart glasses (weight on nose bridge causing fatigue) and smart canes (single forward beam). Centers weight over clavicles.

Mass Distribution: 142g total, 50/50 clavicle counterweight

Chassis Core: Flexible titanium-memory alloy core

Contact Surface: Skin-safe hypo-allergenic silicone

Protection: IP54 splash & dust weather-sealed

QUAD-POD PERCEPTION STACK

Four autonomous sensor hubs positioned at 45°, 135°, 225°, and 315° headings capture 360° spherical visual data with zero blind spots.

Optical: 4× 12MP Sony IMX708 Wide HDR

Metric Ranging: 4x ST VL53L5CX (256 depth points)

Optical Overlap: 30° quadrant overlap for handoffs

POWER & COMPUTE SPINE

Rear enclosure houses the dual-core sensor aggregator, high-speed Wi-Fi transmission engine, and balanced battery pods.


Battery: Dual 900mAh Li-Po (1800mAh total)

Runtime: 8.5 Hours active continuous navigation

Charge: USB-C PD fast-charge (80% in 35 min)

Macro Anatomy: Optical Camera & Multi-Zone ToF Array

Extreme close-up on Front-Right perception pod combining 120° visual semantics with photon speed-of-light metric ranging



WHY CAMERA ALONE FAILS

Monocular RGB cameras detect 2D boxes but cannot measure distance reliably. Black shadows, clear glass doors, or low-contrast curbs fool standard vision models into dangerous false negatives.

THE METRIC GROUNDING SYNERGY

Dense neural depth models (MiDaS) provide smooth relative depth contours across the scene. The 64 ToF ground truth points act as metric anchor pins, instantly scaling the relative depth into true physical metres ($\pm 2\text{cm}$ precision).


ToF Measurement Rate: Up to 60Hz continuous
Range Distance: 4.0 Metres direct ranging
Ambient Immunity: Sunlight immune ($>100\text{k Lux}$)

SUBSYSTEM SPECIFICATIONS

PARAMETER	SPECIFICATION
Image Sensor	Sony IMX708 (12.3MP HDR)
Optical Lens	120° Diagonal Ultra-Wide
ToF Matrix	8 × 8 (64 Zones per Pod)
Laser Wavelength	940 nm (Invisible / Eye-Safe)
Pod Dimensions	26 mm dia x 14 mm depth
Pod Weight	11.5 grams each

360° Omnidirectional Coverage: Zero Blind Spots

Orthographic plan view illustrating the 4× 120° overlapping sensor cones protecting the wearer across all four quadrants



THE BLIND-SPOT DANGER

Smartphones and smart glasses only look forward with a narrow ~70° field of view. They are 100% blind to rear-approaching e-scooters, overtaking motorbikes, and flanking hazards — the #1 source of serious urban pedestrian injuries.

30° QUADRANT OVERLAP ADVANTAGE


Because each sensor has a 120° diagonal cone, adjacent cameras share a 30° overlapping field of view. Moving objects transitioning between pods are tracked continuously by the Kalman filter with zero trajectory loss.

SPATIAL GEOMETRY REFERENCE

QUADRANT	AZIMUTH	COVERAGE ZONE
Front-Right	45°	0° to 105° Path & Sidewalk
Rear-Right	135°	75° to 195° Overtaking Traffic
Rear-Left	225°	165° to 285° Blind Crossing
Front-Left	315°	255° to 15° Turn & Clearance
Total Coverage	360°	Full Continuous Circle

Rear Electronics Chamber & Microcontroller Spine

Enclosure housing the ESP32-S3 sensor multiplexer, 6-DoF inertial measurement unit, passive thermal vents, and battery hub



ESP32-S3 DUAL-CORE XTENSA LX7

Operates at 240MHz with 8MB high-speed octal PSRAM. Runs a dedicated Direct Memory Access (DMA) pipeline synchronizing all 4 camera streams with zero CPU stalling.

Processing: Dual 32-bit Xtensa LX7 cores (240MHz)

Wireless: Wi-Fi 4 (802.11 b/g/n) + BLE 5.0 (LC3 Audio)

Throughput: 150 Mbps hardware streaming link

BOSCH BMI270 6-AXIS IMU

Measures wearer walking cadence, body sway, and head tilt at 400Hz. Dynamically rotates camera coordinate frames into ground-stabilized vectors so gait bobbing does not corrupt obstacle trajectory tracking.

POWER MANAGEMENT (PMIC)


Texas Instruments BQ25895 I2C fast-charge controller balances dual 900mAh Li-Po cells housed in clavicle lobes, preventing thermal hotspots.

Battery Pack: 2× 3.7V 900mAh (1800mAh total)

Power Draw: 1.15W nominal during 4-cam stream

Non-Occluding Acoustic Architecture & Wearable Ergonomics

Macro study of directional open-ear acoustic buds engineered to deliver spatial voice cues while preserving 100% ambient hearing



THE LIFE-SAFETY HAZARD OF EARBUDS

Visually impaired navigators rely on ambient auditory echolocation — vehicle tire friction, engine pitch, pedestrian footfalls, and wall reverberations. Sealing the ear canal with silicone buds or ANC blinds their primary spatial radar, creating lethal traffic vulnerability.

ZERO-OCCLUSION ACOUSTIC SOLUTION

AgenticVision utilizes an EarPods-inspired open-concha geometry. The driver sits adjacent to the ear canal, delivering whisper-clear tactical commands while leaving ambient environmental acoustic passage 100% unimpeded.

ACOUSTIC HARDWARE BENCHMARK

COMPONENT	SPECIFICATION
Transducer	14.2mm Neodymium Dynamic Driver
Frequency Range	100 Hz – 10,000 Hz (Vocal Optimized)
Sound Pressure	84 dB Max (Safe Non-Damaging)
Ear Canal Seal	0% Occlusion (Full Ambient)
Cable Tensile	45 Newtons (Kevlar Reinforced)
Audio Latency	<15 ms (Direct Wired DAC)

End-to-End Perception Loop & Commercial Benchmark

Continuous sub-150ms cognitive loop converting multi-stream video into tactical spoken navigation instructions

ON-PHONE EDGE-AI PIPELINE (YOLOV10 + MIDAS + KALMAN + PHI-3 MINI)

AGENTIC PERCEPTION PIPELINE — REAL-TIME EDGE-AI ARCHITECTURE
Synchronized Quad-Video Ingestion to Step-by-Step Spoken Navigation (<130ms Total Pipeline Latency)



CLOSED-LOOP SPOKEN FEEDBACK (<150MS LATENCY)

CLOSED-LOOP FEEDBACK: PHONE TO DEVICE VOICE GUIDANCE TRANSMISSION



TOTAL CLOSED-LOOP LATENCY: ~135ms (Video Capture -> Inference -> Reasoning -> Voice in Ear)

DEFINITIVE COMPETITIVE COMPARISON MATRIX

EVALUATION METRIC	EXISTING APPS (SEEINGAI, BEMYEYES)	SMART GLASSES (ENVISION, RAY-BAN)	AGENTICVISION (THIS WORK)
Field of View	Narrow Single Cam (~70°)	Forward Single Cam (~75°)	4x Overlapping (360° Omnidirectional)
Distance Grounding	None (Qualitative Labels)	None / Coarse Stereo	Dual Metric Fusion: ToF (mm) + MiDaS
Dynamic Hazards	Unaware until collision	Static detections only	Kalman Filter 2-3s Trajectory Projection
Decision Making	None (Passive naming)	Generic LLM description	Phi-3 Mini Agentic Step Guidance
Auditory Safety	Standard earbuds (Canal occluded)	Open speaker (Sound leaks)	Directional Open-Ear Concha (100% Ambient)
Cloud Independence	Cloud reliant (Fails offline)	Requires cloud servers	100% Local Edge-AI (Zero Internet Needed)
End-to-End Latency	800 ms – 3,000 ms	1,200 ms – 4,000 ms	< 150 ms Closed-Loop Feedback

SOCIETAL IMPACT: 80M+ USERS

Empowers visually impaired individuals across India to independently navigate chaotic urban sidewalks, markets, and transit stations with dignified confidence.

ACCESSIBLE BILL-OF-MATERIALS

Built on scalable hardware (Raspberry Pi cameras, ST ToF sensors, ESP32-S3, consumer Android smartphone) delivering high-grade spatial robotics at <5% the cost of commercial assistive headsets.

100% OFFLINE & PRIVATE

Zero video leaves the device. Operates flawlessly inside underground metro systems, elevators, rural areas, and poor connectivity zones with total personal privacy.