

COPYRIGHT WARNING: Copyright in these original lectures is owned by Monash University. You may transcribe, take notes, download or stream lectures for the purpose of your research and study only. If used for any other purpose, (excluding exceptions in the Copyright Act 1969 (Cth)) the University may take legal action for infringement of copyright.

Do not share, redistribute, or upload the lecture to a third party without a written permission!

FIT3181/5215 Deep Learning

Tutorial 02: Feed-forward Neural Networks

Lecturer: Dr Trung Le, A/Prof Zongyuan Ge, Dr Arghya Pal

Head Tutors: Dr Ruda Nie and Leila Mahmoodi




Email: trunglm@monash.edu

Introduction

- The **purpose** of this tutorial is to practise:
 1. Understand the forward propagation
 2. How to implement feed-forward NNs in PyTorch

Mini-batch Forward and Loss

Shuffling training set and splitting to many equal batches



Optimizer uses batch loss to update model parameters

$\theta = [W^l, b^l]_{l=1}^L$

- Input X_b with mini-batch size of 32
- $h_1 = \text{ReLU}(X_b \times W^1 + b^1) \in \mathbb{R}^{32 \times 10}$
- $h_2 = \text{ReLU}(h_1 \times W^2 + b^2) \in \mathbb{R}^{32 \times 20}$
- $h_3 = \text{ReLU}(h_2 \times W^3 + b^3) \in \mathbb{R}^{32 \times 15}$
- $\text{logits} = h_3 \times W^4 + b^4 \in \mathbb{R}^{32 \times 26}$
- $p = \text{softmax}(\text{logits}) \in \mathbb{R}^{32 \times 26}$

Implementation Feed-forward NNs with PyTorch

Declare a DL model using `torch.nn.Sequential`

```
[16] device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
dnn_model = Sequential(Linear(n_features,10), nn.ReLU(),
                      Linear(10,20), nn.ReLU(),
                      Linear(20,15), nn.ReLU(),
                      Linear(15, n_classes)).to(device)
```

We print out the model summary.

```
[17] from torchsummary import summary

summary(dnn_model, (1,16))
```

```
-----
Layer (type)          Output Shape         Param #
-----
Linear-1              [-1, 1, 10]          170
ReLU-2                [-1, 1, 10]           0
Linear-3              [-1, 1, 20]          220
ReLU-4                [-1, 1, 20]           0
Linear-5              [-1, 1, 15]          315
ReLU-6                [-1, 1, 15]           0
Linear-7              [-1, 1, 26]          416
-----
Total params: 1,121
Trainable params: 1,121
Non-trainable params: 0
-----
Input size (MB): 0.00
Forward/backward pass size (MB): 0.00
Params size (MB): 0.00
Estimated Total Size (MB): 0.01
-----
```

Loss and optimizer

```
[20] # Loss and optimizer
      learning_rate = 0.005
      loss_fn = nn.CrossEntropyLoss()
      optimizer = torch.optim.Adam(dnn_model.parameters(), lr=learning_rate)
```

Train model

```
# Train the model
num_epochs = 100
history = dict() #declare the dictionary history with the keys:val_loss, val_acc, train_loss, train_acc
history['val_loss'] = list()
history['val_acc'] = list()
history['train_loss'] = list()
history['train_acc'] = list()
for epoch in range(num_epochs):
    for i, (X, y) in enumerate(train_loader):
        X, y = X.to(device), y.to(device)
        # Forward pass
        outputs = dnn_model(X.type(torch.float32))
        loss = loss_fn(outputs, y.type(torch.long))
        # Backward and optimize
        optimizer.zero_grad()
        loss.backward()
        optimizer.step()

    #losses and accuracies for epoch
    val_loss = compute_loss(dnn_model, loss_fn, valid_loader)
    val_acc = compute_acc(dnn_model, valid_loader)
    train_loss = compute_loss(dnn_model, loss_fn, train_loader)
    train_acc = compute_acc(dnn_model, train_loader)
    print(f"Epoch {epoch+1}/{num_epochs}")
    print(f"train loss= {train_loss:.4f} - train acc= {train_acc*100:.2f}% - valid loss= {val_loss:.4f} - valid acc= {val_acc*100:.2f}%")
    history['val_loss'].append(val_loss)
    history['val_acc'].append(val_acc)
    history['train_loss'].append(train_loss)
    history['train_acc'].append(train_acc)
```


Diagnosing the training

```
import pandas as pd
import matplotlib.pyplot as plt

his = history.history
fig = plt.figure(figsize=(8, 5))
ax = fig.add_subplot(111)
ln1 = ax.plot(his['loss'], 'b--', label='loss')
ln2 = ax.plot(his['val_loss'], 'b-', label='val_loss')
ax.set_ylabel('loss', color='blue')
ax.tick_params(axis='y', colors="blue")

ax2 = ax.twinx()
ln3 = ax2.plot(his['accuracy'], 'r--', label='accuracy')
ln4 = ax2.plot(his['val_accuracy'], 'r-', label='val_accuracy')
ax2.set_ylabel('accuracy', color='red')
ax2.tick_params(axis='y', colors="red")

lns = ln1 + ln2 + ln3 + ln4
labels = [l.get_label() for l in lns]
ax.legend(lns, labels)
plt.grid(True)
plt.show()
```



Fine-tune the Learning Rate using Valid Set

```
lr = [1e-2, 5e-3, 1e-3, 1e-4, 5e-4]

best_acc = 0
best_i = -1
for i in range(len(lr)):
    print(f"*Evaluating with learning rate = {lr[i]:.4f}\n")
    dnn_model = create_model().to(device)
    history = fit(dnn_model, train_loader = train_loader, valid_loader= valid_loader,
                  optimizer = torch.optim.Adam, learning_rate = lr[i], num_epochs =30, verbose= True)
    valid_acc = history["val_acc"][-1]
    print(f"==>The valid accuracy is {valid_acc*100:.2f}%\n")
    if valid_acc > best_acc:
        best_acc = valid_acc
        best_i = i
        best_model = dnn_model
print(f"The best valid accuracy is {best_acc*100:.2f}% with learning rate {lr[best_i]:.4f}")
```

⇒ *Evaluating with learning rate = 0.0100


==>The valid accuracy is 82.73%

*Evaluating with learning rate = 0.0050

==>The valid accuracy is 81.53%

*Evaluating with learning rate = 0.0010

==>The valid accuracy is 71.53%



DL Pipeline

Another Approach to Implement DL models with PyTorch

**Declare a class inherited from
`torch.nn.Module`**

```
[34] from torch import nn
import torch.nn.functional as F

class OurFFN(torch.nn.Module):
    def __init__(self, n_features, n_classes):
        super(OurFFN, self).__init__()
        self.n_features = n_features
        self.n_classes = n_classes
        self.fc1 = nn.Linear(n_features, 10)
        self.fc2 = nn.Linear(10, 20)
        self.fc3 = nn.Linear(20, 15)
        self.fc4 = nn.Linear(15, n_classes)

    def forward(self, x): #x is the mini-batch
        x = self.fc1(x)
        x = F.relu(x)
        x = self.fc2(x)
        x = F.relu(x)
        x = self.fc3(x)
        x = F.relu(x)
        x = self.fc4(x)
        return x
```

```
[37] from torchsummary import summary

ffn_model = OurFFN(n_features, n_classes).to(device)
summary(ffn_model, (1,n_features))
```



```
-----
Layer (type)           Output Shape          Param #
-----
Linear-1               [-1, 1, 10]           170
Linear-2               [-1, 1, 20]           220
Linear-3               [-1, 1, 15]           315
Linear-4               [-1, 1, 26]           416
=====
Total params: 1,121
Trainable params: 1,121
Non-trainable params: 0
-----
Input size (MB): 0.00
Forward/backward pass size (MB): 0.00
Params size (MB): 0.00
Estimated Total Size (MB): 0.00
-----
```

Thanks for your attention!
Enjoy the tutorial 2!