

Generative Information Retrieval



The Web Conference 2024 tutorial

Yubao Tang^a, Ruqing Zhang^a, **Zhaochun Ren^b**,
Weiwei Sun^c, Jiafeng Guo^a and **Maarten de Rijke^d**

<https://TheWebConf2024-generative-IR.github.io>

May 14, 2024

^a Institute of Computing Technology, Chinese Academy of Sciences & UCAS

^b Leiden University

^c Shandong University

^d University of Amsterdam


Section 2: Definitions & Preliminaries

Generative retrieval: Definition


Generative retrieval (GR) aims to directly generate the **identifiers** of information resources (e.g., docids) that are relevant to an information need (e.g., an input query) in **an autoregressive fashion**

Autoregressive formulation

$$P(x_n | x_1, x_2, \dots, x_{n-1})$$




Autoregressive models




Decoder-only

Autoregressive models




Decoder-only




Encoder-decoder

Autoregressive models



Decoder-only




Encoder-decoder

Generative retrieval: Definition

GR usually exploits a Seq2Seq encoder-decoder architecture to generate a ranked list of docids for an input query, in an autoregressive fashion

Revisit the key idea



Two basic operations in GR

- **Indexing**: To **memorize information about each document**, a GR model should learn to associate the content of each document with its corresponding docid

Two basic operations in GR

- **Indexing**: To **memorize information about each document**, a GR model should learn to associate the content of each document with its corresponding docid
- **Retrieval**: Given an input query, a GR model should **return a ranked list of candidate docids** by autoregressively generating the docid string

Indexing: Formulation

Given:

- A corpus of documents D ;
- A corresponding docid set I_D ;

Indexing: Formulation

Given:

- A corpus of documents D ;
- A corresponding docid set I_D ;

The indexing task directly takes each original document $d \in D$ as input and generates its docid $id \in I_D$ as output in a straightforward Seq2Seq fashion, i.e.,

$$\mathcal{L}_{Indexing}(D, I_D; \theta) = - \sum_{d \in D} \log P(id \mid d; \theta),$$

where θ denotes the model parameters, and $P(id \mid d; \theta)$ is the likelihood of each docid id given the document d

Retrieval: Formulation

Given:

- A query set Q ;
- A set of relevant docids I_Q ;

Retrieval: Formulation

Given:

- A query set Q ;
- A set of relevant docids I_Q ;

The retrieval task aims to generate a ranked list of relevant docids $id^q \in I_Q$ in response to a query $q \in Q$ with the indexed information, i.e.,

$$\mathcal{L}_{\text{Retrieval}}(Q, I_Q; \theta) = - \sum_{q \in Q} \sum_{id^q \in I_Q} \log P(id^q \mid q; \theta),$$

where $P(id^q \mid q; \theta)$ is the likelihood of each relevant docid id^q given the query q


Following the above two basic operations, i.e., indexing and retrieval, a single model can be optimized directly in **an end-to-end manner** towards **a global objective**,

Following the above two basic operations, i.e., indexing and retrieval, a single model can be optimized directly in **an end-to-end manner** towards **a global objective**,

$$\mathcal{L}_{Global}(Q, D, I_D, I_Q; \theta) = \mathcal{L}_{Indexing}(D, I_D; \theta) + \mathcal{L}_{Retrieval}(Q, I_Q; \theta)$$

Training: An example

Retrieval



Indexing

Joint learning the indexing and retrieval tasks

- Once such a GR model is learned, it can be used to generate candidate docids for a test query q_t , all **within a single, unified model**,

$$w_t = GR_{\theta}(q_t, w_0, w_1, \dots, w_{t-1}),$$

where w_t is the t -th token in the docid string and the generation stops when decoding a special EOS token


- Once such a GR model is learned, it can be used to generate candidate docids for a test query q_t , all **within a single, unified model**,

$$w_t = GR_{\theta}(q_t, w_0, w_1, \dots, w_{t-1}),$$

where w_t is the t -th token in the docid string and the generation stops when decoding a special EOS token

- The docids generated with the **top- K highest** likelihood (joint probability of generated tokens within a docid) form a ranking list in descending order


Research questions (1): Docid design



Unfortunately, there is no natural identifier for each document!

Research questions (1): Docid design

Traditional information retrieval




Document features

As an entry

Generative retrieval

Docid: xx xxx x




input

For generation

Research questions (1): Docid design

Traditional information retrieval




Document features

As an entry

Generative retrieval

Docid: xx xxx x



input

For generation

How to design docids for documents?

Research questions (1): Docid design

- Possible design choices


→ [geeksforgeeks.org/what-is-information-retrieval/](https://www.geeksforgeeks.org/what-is-information-retrieval/)

What is Information Retrieval?

[Read](#) [Discuss](#) [Courses](#)

Information Retrieval (IR) can be defined as a software program that deals with the organization, storage, retrieval, and evaluation of information from document repositories, particularly textual information. Information Retrieval is the activity of obtaining material that can usually be documented on an unstructured nature i.e. usually text which satisfies an information need from within large collections which is stored on computers. For example, Information Retrieval can be when a user enters a query into the system.

Not only librarians, professional searchers, etc engage themselves in the activity of information retrieval but nowadays hundreds of millions of people engage in IR every day when they use web search engines. Information Retrieval is believed to be the dominant form of



- Shall we use randomized numbers or codes as docids?

Challenges of docid design

- Shall we use randomized numbers or codes as docids?
- If not, how to obtain proper identifiers for documents?
 - Titles, URLs or ?


- **Shall we use randomized numbers or codes as docids?**
- **If not, how to obtain proper identifiers for documents?**
 - Titles, URLs or ?
- **Would the choices of different docids affect the model performance (e.g., effectiveness, capacity, etc.)?**
 - Long (e.g., 728 hash code) vs. Short docids (e.g., n-grams)
 - Single (e.g., title or URL) vs. Multiple docids (e.g., multiple keywords)

Challenges of docid design

- Shall we use randomized numbers or codes as docids?
- If not, how to obtain proper identifiers for documents?
 - Titles, URLs or ?
- Would the choices of different docids affect the model performance (e.g., effectiveness, capacity, etc.)?
 - Long (e.g., 728 hash code) vs. Short docids (e.g., n-grams)
 - Single (e.g., title or URL) vs. Multiple docids (e.g., multiple keywords)

We will tackle these questions in Section 3!

Research questions (2): Training approaches



Joint learning process of the indexing and retrieval tasks

Challenges of training approaches

- **How to memorize the whole corpus effectively and efficiently?**
 - Rich information in documents
 - Limited labeled data

Challenges of training approaches

- **How to memorize the whole corpus effectively and efficiently?**
 - Rich information in documents
 - Limited labeled data
- **How to learn heterogeneous tasks well within a single model?**
 - Different data distributions
 - Different optimization objectives

Challenges of training approaches


- **How to memorize the whole corpus effectively and efficiently?**
 - Rich information in documents
 - Limited labeled data
- **How to learn heterogeneous tasks well within a single model?**
 - Different data distributions
 - Different optimization objectives
- **How to handle a dynamically evolving document collection?**
 - Internal index: model parameters
 - High computational costs: re-training from scratch every time the underlying corpus is updated

Challenges of training approaches

- **How to memorize the whole corpus effectively and efficiently?**
 - Rich information in documents
 - Limited labeled data
- **How to learn heterogeneous tasks well within a single model?**
 - Different data distributions
 - Different optimization objectives
- **How to handle a dynamically evolving document collection?**
 - Internal index: model parameters
 - High computational costs: re-training from scratch every time the underlying corpus is updated

We will tackle these questions in Section 4!

Research questions (3): Inference strategies



The generation process is different from general language generation

- **How to generate valid docids?**
 - Limited docids vs. free generation

- **How to generate valid docids?**
 - Limited docids vs. free generation
- **How to organize the docids for large scale corpus?**
 - Data structure for docids over millions of documents

- **How to generate valid docids?**
 - Limited docids vs. free generation
- **How to organize the docids for large scale corpus?**
 - Data structure for docids over millions of documents
- **How to generate a ranked list of docids for a query?**
 - One-by-one generation: likelihood probabilities
 - One-time generation: directly decoding a sequence of docids


Challenges of model inference

- **How to generate valid docids?**
 - Limited docids vs. free generation
- **How to organize the docids for large scale corpus?**
 - Data structure for docids over millions of documents
- **How to generate a ranked list of docids for a query?**
 - One-by-one generation: likelihood probabilities
 - One-time generation: directly decoding a sequence of docids

We will tackle these questions in Section 5!


Research questions (4): Applications

How to employ generative retrieval models in different downstream tasks?



Research questions (4): Applications

How to employ generative retrieval models in different downstream tasks?



We will tackle this question in Section 6!

References

References i

- N. De Cao, G. Izacard, S. Riedel, and F. Petroni. Autoregressive entity retrieval. In *International Conference on Learning Representations*, 2021.
- L. Heck and S. Heck. Zero-shot visual slot filling as question answering. *arXiv preprint arXiv:2011.12340*, 2020.
- J. D. M.-W. C. Kenton and L. K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT*, pages 4171–4186, 2019.
- T. Murayama. Dataset of fake news detection and fact verification: a survey. *arXiv preprint arXiv:2111.03299*, 2021.
- Y. Tay, V. Q. Tran, M. Dehghani, J. Ni, D. Bahri, H. Mehta, Z. Qin, K. Hui, Z. Zhao, J. Gupta, T. Schuster, W. W. Cohen, and D. Metzler. Transformer memory as a differentiable search index. In *Advances in Neural Information Processing Systems*, volume 35, pages 21831–21843, 2022.