

CSI 4900: Honours Project Report

Wei Hu
whu061@uottawa.ca

University of Ottawa — June 4, 2019

1 Introduction

An Erdos-Selfridge-Spencer game consists of an attacker A , a defender D , and a position P . We use p_i to represent a piece that is i levels away from the top of the board. In other words, a piece at p_0 , if not destroyed by the defender this turn, will attain tenure and provide a point for the attacker.

Definition 1.1. Let v be a value function, which maps a level i to a real value representing the value of a p_i piece. A value function is represented by an array $(w_0, w_1, w_2, \dots, w_k)$ where:

$$v(i) = w_i.$$

Definition 1.2. Let S be an array $(a_0, a_1, a_2, \dots, a_k)$ representing a multiset of pieces consisting of a_i pieces on the i th level. We define the value function applied to S as:

$$v(S) = \sum_{i=0}^k a_i v(i).$$

A defender would apply its value function to the two sets partitioned by the attackers, and it would destroy the set it deems to be more valuable.

Theorem 1.1. *The optimal value function for the defender is:*

$$v_*(i) = \frac{1}{2^{i+1}}. \quad (1)$$

1.1 Project Summary

We intend to investigate using reinforcement learning to train attackers to exploit the sub-optimality of biased defenders (nearsighted and farsighted).

2 Biased Defenders

We notice that the optimal value function satisfies this property that $v(i) = 2v(i+1)$. By deviating from this equality, we create sub-optimal defenders with biases that either favour pieces that are closer to the top of the board, or those that are at the bottom, depending on the direction of the inequality.

Definition 2.1. A nearsighted (myopic) defender is a defender whose value function satisfies the property, for all defined values of i :

$$v(i) > 2v(i+1). \quad (2)$$

A nearsighted defender disproportionately values pieces that are close to the top of the board.

Definition 2.2. A farsighted defender is a defender whose values function satisfies the property, for all defined values of i :

$$v(i) < 2v(i+1). \quad (3)$$

A farsighted defender disproportionally value pieces that are close to the bottom of the board.

Theorem 2.1. *When playing against an optimal defender, the optimal approach for the attacker is to try to make the value according to v_* of the two partitioned sets as close as possible.*

In order to maximize the number of pieces tenured, it is sufficient to maximize. at each turn, the value according to v_* of the surviving pieces. This idea can be proven in two steps:

1. show that against an optimal defender, the best score that can be achieved for starting position S is $\lfloor v_*(S) \rfloor$.
2. playing according to *Theorem 2.1* achieves that best score.

2.1 Nearsighted (Myopic) Defender

Theorem 2.2. *To maximize to real value of the surviving pieces on any round against a nearsighted defender, we follow the following algorithm:*

Algorithm 1: Maximizing Real Value Playing Nearsighted Defender

Input: a board position S , and the value function of a nearsighted defender v
Result: (S_1, S_2) , such that $a + b = c + d$

if $|b| > |a|$ **then**
 | exchange a and b ;
end
 $c \leftarrow a + b$;
 $z \leftarrow c - a$;
 $d \leftarrow b - z$;
return (c, d) ;

Proof.

□

2.2 Farsighted Defender

In malesuada ullamcorper urna, sed dapibus diam sollicitudin non. Donec elit odio, accumsan ac nisl a, tempor imperdiet eros. Donec porta tortor eu risus consequat, a pharetra tortor tristique. Morbi sit amet laoreet erat. Morbi et luctus diam, quis porta ipsum. Quisque libero dolor, suscipit id facilisis eget, sodales volutpat dolor. Nullam vulputate interdum aliquam. Mauris id convallis erat, ut vehicula neque. Sed auctor nibh et elit fringilla, nec ultricies dui sollicitudin. Vestibulum vestibulum luctus metus venenatis facilisis. Suspendisse iaculis augue at vehicula ornare. Sed vel eros ut velit fermentum porttitor sed sed massa. Fusce venenatis, metus a rutrum sagittis, enim ex maximus velit, id semper nisi velit eu purus.

Algorithm 2: Maximizing Real Value Playing Nearsighted Defender

Input: a board position P , and the value function of a nearsighted defender v
Result: (c, d) , such that $a + b = c + d$

if $|b| > |a|$ **then**
 | exchange a and b ;
end
 $c \leftarrow a + b$;
 $z \leftarrow c - a$;
 $d \leftarrow b - z$;
return (c, d) ;

Fusce varius orci ac magna dapibus porttitor. In tempor leo a neque bibendum sollicitudin. Nulla pretium fermentum nisi, eget sodales magna facilisis eu. Praesent aliquet nulla ut bibendum lacinia. Donec vel mauris vulputate, commodo ligula ut, egestas orci. Suspendisse commodo odio sed hendrerit lobortis. Donec finibus eros erat, vel ornare enim mattis et.

Mauris interdum porttitor fringilla. Proin tincidunt sodales leo at ornare. Donec tempus magna non mauris gravida luctus. Cras vitae arcu vitae mauris eleifend scelerisque. Nam sem sapien, vulputate nec felis eu, blandit convallis risus. Pellentesque sollicitudin venenatis tincidunt. In et ipsum libero. Nullam tempor ligula a massa convallis pellentesque.