

# Bash Shell Scripting

test command

```
#!/bin/bash
```

*Learn how to automate common tasks using bash shell scripting*

# test command

- It is a command to judge conditions.
- Simple Syntax:
  - `test condition` or `[ condition ]` or `[[ condition ]]`
  - **Note:** `[[ ]]` works with bash/ksh/zsh shells.
  - It will return exit status as 0 or 1. (echo \$? )
  - 0 -- Condition is true or test is successful
  - 1 -- Condition is false or test is failed
- How to make condition to work with test command ?
  - Comparison Operators
  - File Test Operators

*Learn how to automate common tasks using bash shell scripting*

# Comparison Operators with test command

## ■ Numbers:

- `[[ int1 -eq int2 ]]` -- It return **true** if they are equal else **false**
- `[[ int1 -ne int2 ]]` -- It return **false** if they are not equal else **true**
- `[[ int1 -lt int2 ]]` -- It return **true** if int1 is less than int2 else **false**
- `[[ int1 -le int2 ]]` -- It return **true** if int1 is less than or equal to int2 else **false**
- `[[ int1 -gt int2 ]]` -- It return **true** if int1 is greater than int2 else **false**
- `[[ int1 -ge int2 ]]` -- It return **true** if int1 is greater than or equal to int2 else **false**
- `[[ !int1 -eq int2 ]]` -- It reverse the result

## ■ Strings:

- `[[ -z str ]]` -- It return **true** if the length of the str is zero else **false**
- `[[ -n str ]]` -- It return **true** if the length of the str is no-zero else **false**
- `[[ str1 == str2 ]]` -- It return **true** if both the strings are equal else **false**
- `[[ str1 != str2 ]]` -- It return **true** if both the strings are not equal else **false**

*Learn how to automate common tasks using bash shell scripting*

# File test Operators with test command

- `[[ -d file ]]` -- It return **true** if the file/path is directory else **false**
- `[[ -f file ]]` -- It return **true** if the file/path is a file else **false**
- `[[ -e file ]]` -- It return **true** if the file/path is exists else **false**
- `[[ -r file ]]` -- It return **true** if the file/path is readable else **false**
- `[[ -w file ]]` -- It return **true** if the file/path is writable else **false**
- `[[ -x file ]]` -- It return **true** if the file/path is executable else **false**
- Please download a text file for more file test operators

*Learn how to automate common tasks using bash shell scripting*

**Thank you**