

**Exp.no:** 3.a

**AIM:** Write a HTML program, that makes use of <article>, <aside>, <figure> <figcaption> <footer>, <header>, <main>, <nav>, <section>, <div>, <span> tags.

**DESCRIPTION:**

This HTML document is a demo webpage that showcases the use of HTML5 semantic elements such as

, , , , , , , and to structure a blog-style website.

1.DOCTYPE & Metadata

- <!DOCTYPE html> declares the document type as HTML5.
- <html lang="en"> specifies that the page is in English.
- <meta charset="UTF-8"> ensures the webpage supports special characters.
- <title> sets the title of the browser tab.

2.CSS Styling (<style>)

- Defines layout, background colors, fonts, and spacing.
- Uses flexbox in <main> to align article and aside side by side.
- Navigation links styled to look neat and user-friendly.

3.Header (<header>)

- Displays the blog's title: "My Blog Website".

4.Navigation (<nav>)

- Provides links to different sections: Home, Articles, Gallery, Contact.
- Styled with spacing and white text for readability.

5.Main Content (<main>)

- Divided into two parts:
- Article (<article>): Contains the main blog content.
- A heading: Understanding HTML5 Semantic Tags.
- A paragraph explaining semantic elements.
- Figure (<figure>): Contains an image with a caption (<figcaption>).
- Section (<section>): Explains Why Use Semantic Tags?
- Aside (<aside>): Sidebar with related posts (Introduction to HTML, CSS Basics, JavaScript).

6.Footer (<footer>)

- Displays copyright:

## **PROGRAM:**

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <title>HTML 5 Semantic elements demo</title>


  <style>

    body {

      font-family: Arial, sans-serif;

      margin: 0;

    }

    header, nav, footer {

      background-color: #333;

      color: white;

      padding: 1em;

    }

    nav a {

      color: white;

      margin: 0 10px;

      text-decoration: none;

    }

    main {

      display: flex;

      padding: 20px;

    }

    article {

      flex: 3;

      padding: 20px;

      background-color: #f9f9f9;
```

```

        }
    aside {
        flex: 1;
        padding: 20px;
        background-color: #e0e0e0;
    }
    figure {
        margin: 0;
        text-align: center;
    }
    figcaption {
        font-style: italic;
        font-size: 0.9em;
    }
    footer{
        text-align: center;
    }
</style>
</head>
<body>
    <header>
        <h1>My Blog Website (24B11CS250)</h1>
    </header>
    <nav>
        <a href="#">Home</a>
        <a href="#">Articles</a>
        <a href="https://photos.google.com/?pli=1">Gallery</a>
        <a href="#">Contact</a>
    </nav>
    <main>

```

```
<article>

    <h2> Understanding HTML 5 Semantic Tags </h2>

    <p> <span style="font-weight: bold;">HTML5</span>
    introduced semantic elements that make your code more readable and
accessible.. </p>

    <figure>

        <img src= "C:\Users\krish\Pictures\dodge car.jpg" height=500
width=800>

        <figcaption>Figure: Illustration of HTML5 layout </figcaption>

    </figure>

    <section>

        <h3>Why Use Semantics Tags?</h3>

        <p>Semantic tags help search engines and screen readers understand
the structure of your web page</p>

    </section>

</article>

<aside>

    <h3>Related posts</h3>

    <ul>

        <li><a href="#">Introduction to HTML</a></li>

        <li><a href="#">CSS Basics</a></li>

        <li><a href="#">Java Script for Beginners</a></li>

    </ul>

</aside>

</main>

<footer>

    <p>&copy; 2025 My Blog. All rights reserved.</p>

</footer>

</body>

</html>
```

## OUTPUT:

### Understanding HTML 5 Semantic Tags

HTML5 introduced semantic elements that make your code more readable and accessible..



*Figure: Illustration of HTML5 layout*

#### Why Use Semantics Tags?

Semantic tags help search engines and screen readers understand the structure of your web page

#### Related posts

- [Introduction to HTML](#)
- [CSS Basics](#)
- [Java Script for Beginners](#)

## RESULT:

### **Exp.no: 3.b**

**AIM:** Write a HTML program, to embed audio and video into HTML web page.

### **DESCRIPTION:**

This HTML page demonstrates how to embed audio and video files into a web page using the `<audio>` and `<video>` tags in HTML5.

#### 1. Document Setup

- `<!DOCTYPE html>` declares HTML5 document type.
- `<html lang="en">` specifies the language as English.
- `<meta charset="UTF-8">` ensures correct character encoding.
- `<title>` sets the title of the webpage to “Audio and Video Embedding”.

#### 2. Page Content (`<body>`)

- Main Heading (`<h1>`): "Embedded Audio and Video in HTML".

#### 3. Audio Section (`<audio>`)

- `<audio controls>` creates an audio player with built-in play, pause, volume controls.
- `<source>` elements specify different audio files (MP3 format in this case):
  - .mp3 file
  - .mp3 file
- If the browser cannot play audio, the fallback text “Your browser does not support the audio element.” is shown.

#### 4. Video Section (`<video>`)

- `<video width="640" height="360" controls>` creates a video player with playback controls and fixed size.
- `<source>` elements specify two video files (MP4 format):
  - .mp4 file
  - .mp4 file
- If the browser cannot play video, the fallback text “Your browser does not support the video element.” is shown.

## **PROGRAM:**

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <title>Audio and Video</title>

</head>

<body >

    <h1>Embedded audio and video in html (24B11CS250)</h1>

    <!-- Audio section -->

        <h2>Sample Audio</h2>

        <audio controls>

            <source src="C:\Users\krish\Downloads\Fire Storm.mp3" type="audio/mpeg">

            <source src="C:\Users\krish\Downloads\Fire Storm.mp3" type="audio/ogg">

            Your browser does not support the audio element.

        </audio >

    <!-- Video section -->

        <h2>Sample Video</h2>

        <video width="640" height="360" controls>

            <source src="C:\Users\krish\Downloads\Fire Storm.mp3" type="audio/mpeg">

            <source src="C:\Users\krish\Downloads\Fire Storm.mp3" type="audio/ogg">

            Your browser does not support the video element.

        </video >


</body>

</html>
```

## **OUTPUT:**

# Embedded audio and video in html (24B11CS250)

## Sample Audio



## Sample Video



**RESULT:**



### **Exp.no: 3.c**

**AIM:** Write a program to apply different types (or levels of styles or style specification formats) - inline, internal, external styles to HTML elements. (identify selector, property and value).

### **DESCRIPTION:**

#### Inline CSS

- Styles are applied directly to individual HTML elements using the style attribute.
- Example: a heading can have its color and alignment defined inside the tag itself.
- Advantage: Quick and easy for small changes.
- Disadvantage: Not reusable, mixes design with content, harder to maintain.

#### Internal CSS

- Styles are written inside a <style> tag within the <head> section of the HTML document.
- These styles apply only to that particular web page.
- Advantage: Better separation of content and style than inline, good for single-page sites.
- Disadvantage: Cannot be reused across multiple pages.

#### External CSS

- Styles are stored in a separate .css file and linked to the HTML document using the <link> tag.
- Allows multiple web pages to share the same stylesheet.
- Advantage: Clean separation of structure (HTML) and design (CSS), reusable, easier maintenance, consistent styling across pages.
- Disadvantage: Requires an extra file (won't work if CSS file is missing or link breaks).

#### In short:

- Inline = one-time quick style
- Internal = page-level style
- External = project-wide reusable style

## Program:

### 1) Inline Function

```
<html>
<body>
<h2>24B11CS250</h2>
<h1 style="color:blue;text-align:center;bgcolor:black;">This is a heading</h1>
<p style="color:red;">This is a paragraph.</p>
</body>
</html>
```

## OUTPUT:

**24B11CS250**

**This is a heading**

**This is a paragraph.**

### 2) Internal function

```
<html>
<head>
<style>
body {
    background-color:yellow;
}
</style>
</head>
<body>
<h2>24B11CS250</h2>
<h1 style="color:blue;text-align:center;"><strong>This is a heading</strong></h1>
<p style="color:red;font-size:30px;">This is a paragraph.</p>
</body>
```

</html>

**OUTPUT:**

**24B11CS250**

**This is a heading**

**This is a paragraph.**