1)-I

What is wrong about a XML document

A - XML Documents must have a root element

B - XML Attributes must be quoted

C - XML Elements must be properly nested

Select one or more:

- a. A Only
- b. C only
- c. B only
- d. B and C only
- e. A and B only

All answers are correct.

2)R

What is the correct OR-SQL query that retrieve the values from VARRAY?

```
CREATE TYPE price_arr AS VARRAY(10) OF NUMBER(12,2)
/
CREATE TABLE pricelist (
pno integer,
prices price_arr
)
/
```

Select one or more:

- a. SELECT pno, p.REF.price_arr.price
  FROM pricelist p
- b. SELECT pno, s.COLUMN_VALUE price
  FROM pricelist p, TABLE(p.prices) s;
- c. SELECT pno, p.s.COLUMN_VALUE price
  FROM pricelist p, TABLE(p.prices) s;
- d. SELECT pno, p.REF.price_arr.price
  FROM pricelist p, TABLE(p.prices) REF
- e. SELECT pno, p. COLUMN_VALUE.price

  FROM pricelist p

3)R

on 10
t answered
d out of
g question

What is/are **wrong** about "REF" in Oracle ORDB?

Select one or more:

- a. Accessing the object referred to by a REF is called dereferencing the REF
- b. Oracle does not allow Unique or PRIMARY KEY constraints on REF columns
- c. A REF column can be assigned a null value
- d. REF is not a built-in data type in Oracle
- e. All of them

4)I

How differ Static Hashing from Extendible Hashing?

Select one or more:

- a. Performance is not affected when file is growing
- b. Primary nodes will delete if empty
- c. Does not create long overflow chains
- d. Less complex for implementation.
- e. Allow fixed number of primary buckets to store the records

5)R

What is the Oracle command to create a VARRAY TYPE?

Select one or more:

- a. Create ROW TYPE excharray AS varray(5) of varchar(12)
- b. Create TYPE excharray AS varray(5)
- c. Create TYPE excharray AS varray(5) of varchar(12)
- d. Create ROW TYPE excharray AS varray(5)
- e. Create ROW TYPE excharray AS of varchar(12)

6)I

What is the **incorrect** line in the following code?

```
Line 1 <book>
Line 2 <Paper category="Web">
Line 3 <bname>XML Tutorials</bname>
Line 4 <pages>200</pages>
Line 5 <price>800.00</Price>
Line 6 </book>
```

Select one or more:

- a. Line 5 only
- b. Line 3 and Line 4
- c. Line 2 and Line 5
- d. Line 1 and Line 5 only
- e. Line 2 Only

7)R

Which one is **incorrect** on Indexing?

Select one or more:

- a. Clustering indexes made up with only primary keys.
- b. Secondary index has a key field
- c. Dense index facilitates to fast searching.
- d. Primary index has a key field
- e. Used to optimize the performance of access the data.

8)R

```
create type emp_t AS OBJECT(
        EMPNO CHAR(6),
        FIRSTNAME VARCHAR(12),
        LASTNAME VARCHAR(15),
        WORKDEPT REF dept_t,
        SEX CHAR(1),
        BIRTHDATE DATE,
        SALARY NUMBER(8,2)
        )
```

```
create table OREMP of emp_t (
)
/
```

Which INSERT statement is correct for inserting a row into the object table OREMP?

Select one or more:

a.
insert into OREMP values REF ORDEPT ('000010', 'Christine', 'Hass', 'Planning', 'F', '14-AUG-1953', 72

b.
insert into OREMP values REF ORDEPT('000010', 'Christine', 'Hass',
(select ref(d) from ORDEPT d where d.DEPTNO = 'A00'), 'F', '14-AUG-1953', 72750))

c.
insert into OREMP values (EMP_T ('000010', 'Christine', 'Hass',
(select ref(d) from ORDEPT d where d.DEPTNO = 'A00'), 'F', '14-AUG-1953', 72750))

d.
insert into OREMP values(EMP_T('000010', 'Christine', 'Hass',
(select Dname from ORDEPT d where d.DEPTNO = 'A00'), 'F', '14-AUG-1953', 72750))

e.
insert into OREMP values REF ORDEPT('000010', 'Christine', 'Hass',

10)R

What is/ are correct about VARRAY?

Select one or more:

- a. Can't be used as the data-type of a column of a relational table.
- b. VARRAY is a kind of data type that can't initializing as a TYPE.
- c. Creating an array type does allocate space.
- d. Can be used an attribute data-type in an object type definition.
- e. VARRAY is not only a type definition

11)R

Consider the following script.

```
CREATE TYPE Child_t AS OBJECT (
name char(20),
addr  varchar(50)
)
/
CREATE TYPE ChildTableType AS TABLE OF Child_t
/
CREATE TABLE Employee (
name char(30),
Job char(50),
Child_details ChildTableType
)
.....
```

Last line of the Employee table is.

Select one or more:

- a. NESTED TABLE Child_details STORE AS e.Child_table UNDER Employee e;
- b. NESTED TABLE Child_details STORE AS e. Child_table UNDER Employee e;
- c. NESTED TABLE Child_details STORE REF AS Child_table;
- d. NESTED TABLE Child_details STORE REF AS Child_table UNDER Employee;
- e. NESTED TABLE Child_details STORE AS Child_table;

12)i

An object in ORDB can be containing

Select one:

- a. Attributes
- b. Name identifies
- c. a, b and e
- d. a and b only
- e. Methods

13)

An object in ORDB can be containing

Select one:

- a. Attributes
- b. Name identifies
- c. a, b and e
- d. a and b only
- e. Methods

14)I

How to comment in XML?

Select one or more:

- a. < ! -- -->
- b. < !- - ?
- c. <!-- --!>
- d. < ?- - ?
- e. <!- -?>

14)I

Which includes for a "Query Block"?

Select one or more:

- a. SELECT - FROM - WHERE - GROUP BY - ORDER BY
- b. SELECT - FROM - WHERE
- c. SELECT - FROM - WHERE - GROUP BY - ORDER BY - HAVING
- d. SELECT - FROM - WHERE - ORDER BY
- e. SELECT - FROM - WHERE - GROUP BY

15)I

Which includes for a "Query Block"?

Select one or more:

- a. SELECT - FROM - WHERE - GROUP BY - ORDER BY
- b. SELECT - FROM - WHERE
- c. SELECT - FROM - WHERE - GROUP BY - ORDER BY - HAVING
- d. SELECT - FROM - WHERE - ORDER BY
- e. SELECT - FROM - WHERE - GROUP BY

16)R

Which is/are NOT a rule of creating B+ tree?

Select one or more:

- a. If search value < node value, then point to the left side
- b. If search value < node value, then point to the right side
- c. Root node has minimum one value
- d. If search value = node value, then point to left side.
- e. If search value > node value, then point to right side.

17)I

What is/are the types of built in function in Xml?

A - Number Related

B - Sequence Related

C - Error handling and trapping

D - String related

Select one or more:

- a. A, C, D only
- b. C only
- c. All of them
- d. B, C and D only
- e. A and C only

Number related functions
Example:
fn.number()
2 Sequence related functions
Example:
fn: count()
fn: distinct-values)

Error handling and trapping functions
Used to handle runtime errors.
try (risky code }
catch (what to do if error happens }
String related functions
Example:
fn: string)
fn concat()
fn: substring)

18)R

Which of the following is true relate to Object Relational Database Systems?

Select one:

- a. They have the ability to store complex data types.
- b. They are most useful for traditional, two-dimensional database tables.
- c. They are used to create tables without constraints.
- d. All of them.
- e. They are overtaking RDBMS for all applications.

19)R

Consider the following statements,

A - Let clause is **not** the convenient way to bind a variable

B - Where clause can used to filter results

C - For and Let can be repeated and combined

What is/are correct from above statements

Select one or more:

- a. A and B only
- b. A only
- c. B and C only
- d. A and C only
- e. B only

20)

Which combination is true?

Select one or more:

- a. Sequential File - sorted records
- b. Hashed file - good for equality selection
- c. Heap file - records inserted to the begin of file
- d. B+ Tree file - Dynamic Tree index
- e. Cluster file - cost effective when search records on range selections.