

Q1

```
1 usage
@SpringBootApplication
public class SpringPollApplication {

    public static void main(String[] args) { SpringApplication.run(SpringPollApplication.class, args); }

    @Bean
    public String getMessage1(){
        System.out.println("hey from message1");
        return "1";
    }
}
```

Has one output :

Hey from message1

Here just display the print statement, the return save inside container

Q2 :

```
1 usage
8 @SpringBootApplication
9 public class SpringPollApplication {
10
11     public static void main(String[] args) { SpringApplication.run(SpringPollApplication.class, args); }
12
13     @Bean
14     @Qualifier("1")
15     public String getMessage1(){
16         System.out.println("hey from message1");
17         return "1";
18     }
19
20     @Bean
21     public String getMessage2(@Qualifier("1") String data ){
22         System.out.println("hey from message2");
23         return data ;
24     }
25 }
```

Has one output :

Hey from message1

1

Use a Qualifier, Each Method is assigned the identity and print them in order

Q3 :

```
@Bean
@Qualifier("1")
public String getMessage1(){
    System.out.println("hey from message1");
    return "1";
}

@Bean
@Qualifier("2")
public String getMessage2(@Qualifier("3") String data ){
    System.out.println("hey from message2");
    return data;
}

@Bean
@Qualifier("3")
public String getMessage3(){
    System.out.println("hey from message3");
    return "3" ;
}
```

Have TOW output :

1- Can Start with

Method getMessage1

getMessage3

getMessage2

output :

hey from message1

Hey from message3

3

2 -Or Start Whit

getMessage3

getMessage2

Method getMessage1

Output:

Hey from message3

3

hey from message1

```

@Bean
@Qualifier("1")
public String getMessage1(){
    System.out.println("hey from message1");
    return "1";
}

@Bean
@Qualifier("2")
public String getMessage2(@Qualifier("3") String data ){
    System.out.println("hey from message2");
    return data;
}

@Bean
@Qualifier("3")
public String getMessage3(){
    System.out.println("hey from message3");
    return "3" ;
}

@Component
public class MainController {

    1 usage
    String data;

    public MainController(@Qualifier("1") String data){
        this.data=data;
        System.out.println("hey from Main controller");
    }
}

```

Message1 → hay from Main controller → Message3 → Message2
 Message1 → Message3 → Message2 → hay from Main controller
 Message1 → Message3 → hay from Main controller → Message2

Message3 → Message2 → Message1 → hay from Main controller
 Message3 → Message1 → Message2 → hay from Main controller
 Message3 → Message1 → hay from Main controller → Message2

Q5:

```
15
16 @Bean
17 @Qualifier("1")
18 public String getMessage1(MainController mainController){
19     System.out.println("hey from message1");
20     return "1";
21 }
22
23 @Bean
24 @Qualifier("2")
25 public String getMessage2(@Qualifier("3") String data ){
26     System.out.println("hey from message2");
27     return data;
28 }
29
30 @Bean
31 @Qualifier("3")
32 public String getMessage3(){
33     System.out.println("hey from message3");
34     return "3" ;
35 }
```

```
import org.springframework.beans.factory.annotation.Qualifier;
import org.springframework.stereotype.Component;

1 usage
@Component
public class MainController {

    1 usage
    String data;

    public MainController(@Qualifier("2") String data){
        this.data=data;
        System.out.println("hey from Main controller");
    }
}
```

Message 1→Message 3→ Message2→ hay from Main controller

Message 3→ Message2→ hay from Main controller→Message1

Message3→Message1→Message2→ hay from Main controller