

XMSN OIL P

- ▷ 70^{PSI} maximum
- 30-70^{PSI} normal
- ▷ 30^{PSI} minimum

XMSN OIL T

- ▷ 110 °C maximum
- 15-100 °C normal
- ▷ 15 °C minimum

Eng OIL P

- ▷ 130 PSI maximum
- 115-130 PSI Above 94% NG
- 90-130 PSI 78%-94% NG
- 50-130 PSI Idle - 73% NG
- ▷ 50 PSI minimum

Eng OIL T

- ▷ 107 °C maximum
- 0-107 °C Normal
- ▷ 0 °C minimum

Fuel QTY

- ▷ 100 lbs low fuel
- Fuel low on MFD → 100 ± 2.5 lbs

AIR SPEED

125 KIAS V_{NE}

NG (Gas producer)

- 106% (10s transient)
- 105% max continuous
- 63%-105% Continuous.

Eng TRQ

- 121-131% 2s transient
- 112-121% 10s transient
- 100-112% 30 min limit
- 0-100% Continuous

TRQ (Most Torq)

- 100-116% 10s transient
- (< 10s (per flight hour))
- 0-100% Continuous

% RPM - NR (rotor)

TRANSIENT

- 104-125 5s transient

CONTINUOUS OPERATION

AUTO ROTATION

- ▷ 104% maximum
- ▷ 90% minimum

POWERED FLIGHT

- 104% maximum
- 100% normal
- 33% minimum

% RPM NP (Power Turbine)

- 104-112% 15s transient

- 104% maximum

- 100% normal

- 71-91% transient operation only

TGT (Turbine Gas Temp)

STARTING

- 5 927 °C momentary peak < 1s

- 843-927 °C 10s transient

NORMAL OPERATION

- 802-905 °C 12s transient

- 716-802 °C 30 min limit

- 0-716 °C Continuous.