

Sentiment Analysis on Car Reviews

Choosing a car can be a big decision using sentiment analysis users can analyze mass amounts of reviews by determining positive and negative feedback. Creating a hassle-free way to narrow down a car company they would like to pursue. While also allowing car manufactures to determine positive and negative feedback with their car models and how they can use sentiment analysis to their advantage when creating next years models.

```
In [1]: # First I will import needed packages
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

```
In [2]: # I will check my current directory with the use of os
import os
os.getcwd()
```

Out[2]: 'C:\\Users\\Robyn\\DSC680\\Car_Review_Project'

Data Import

```
In [3]: # I will now pull my data set through pd to create a data frame
Car_Reviews = pd.read_csv("\\Users\\Robyn\\DSC680\\Car_Review_Project\\car_5_brands.csv")
Car_Reviews
```

Out[3]:

	Unnamed: 0	Rating	car_year	brand_name	date	review
0	0	5.00	2018	Audi	2018-07-11	BEST ALL AROUND PURPOSE CROSSOVER SUV I have n...
1	1	5.00	2018	Audi	2018-06-24	Best car This is a wonderful car. The technol...
2	2	5.00	2018	Audi	2018-05-02	Great Buy Do your home work
3	3	5.00	2018	Audi	2017-12-07	Fun Car Great ride. Loaded with technology. St...
4	4	5.00	2018	Audi	2017-10-25	Best luxury SUV w/ perfect comfort/sport balan...
...
31933	31933	4.75	2015	Mercedes-Benz	2015-06-04	One week in but I love it. I just got the car...
31934	31934	4.00	2015	Mercedes-Benz	2015-05-19	A delightful car I have been driving the GLA25...
31935	31935	3.00	2015	Mercedes-Benz	2015-02-21	This car is amazing but visibility is poor We ...
31936	31936	2.75	2015	Mercedes-Benz	2015-01-20	Steering Wheel Module When I first bought this...
31937	31937	4.50	2015	Mercedes-Benz	2014-10-06	Fun crossover/hatchback but not an SUV. I've h...

31938 rows x 6 columns

Variable description

- Rating - A numeric variable that gives the car brand a rating of one to five
- Car_Year – The year the car was built
- Brand_Name – Is the brand such as Audi, Lexus, Infiniti, BMW, or Mercedes-Benz
- Date – Is the date the owner of the car created the review
- Review – The review given by the costumer regard the car they purchased

Data Review

```
In [4]: # Use describe to see different statistics for the data set
Car_Reviews.describe()
```

Out[4]:

	Unnamed: 0	Rating	car_year
count	31938.000000	31938.000000	31938.000000
mean	15968.500000	4.476331	2005.959296
std	9219.850785	0.783148	5.101718
min	0.000000	1.000000	1997.000000
25%	7984.250000	4.375000	2002.000000
50%	15968.500000	4.750000	2005.000000
75%	23952.750000	5.000000	2009.000000
max	31937.000000	5.000000	2018.000000

Above it is shown that the mean rating is 4.47 while the min is 1.00 and a max of 5.00. While the mean year for all cars is 2005 while the min is 1997 and a max of 2018.

```
In [5]: # I will now use isnull and sum to check for missing data
Car_Reviews.isnull().sum()
```

Out[5]:

Unnamed: 0	0
Rating	0
car_year	0
brand_name	0
date	0
review	0
dtype:	int64

No missing values have been detected.

```
In [6]: # View how many unique values the brand_name variable has
Car_Reviews['brand_name'].unique()
```

Out[6]: array(['Audi', 'Lexus', 'INFINITI', 'BMW', 'Mercedes-Benz'], dtype=object)

Above it is shown that the five car brands within the data set are Audi, Lexus, INFINITI, BMW, and Mercedes-Benz.

```
In [7]: # Next I will use Shape to display the dimensions of the dataframe
Car_Reviews.shape
```

Out[7]: (31938, 6)

The Dataframe has 6 columns and 31,938 rows of data.

```
In [8]: # Info is now used to see further into each variable.
Car_Reviews.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 31938 entries, 0 to 31937
Data columns (total 6 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Unnamed: 0   31938 non-null  int64
1   Rating       31938 non-null  float64
2   car_year     31938 non-null  int64
3   brand_name   31938 non-null  object
4   date         31938 non-null  object
5   review       31938 non-null  object
dtypes: float64(1), int64(2), object(3)
memory usage: 1.5+ MB
```

Above it is shown that the Unnamed and car_year are both int64 while Rating is a float64. The remaining variables brand_name, date, and review are objects.

```
In [9]: # I will now count the values for each rating
Car_Reviews.Rating.value_counts()
```

```
Out[9]: 5.00000    9781
         4.87500    5447
         4.75000    3455
         4.62500    2064
         4.00000    1639
         ...
         4.70000     1
         4.09375     1
         1.56250     1
         4.72500     1
         3.52500     1
         Name: Rating, Length: 149, dtype: int64
```

```
In [10]: # View the unique values the Rating variable has
Car_Reviews.Rating.unique()
```

```
Out[10]: array([[5.      , 4.      , 1.      , 3.      , 4.75     ,
                2.      , 2.625   , 3.625   , 4.25     , 4.875     ,
                4.625   , 2.25     , 4.5      , 4.375   , 4.125     ,
                3.125   , 3.25     , 3.75     , 3.875   , 3.5      ,
                3.375   , 2.125   , 2.375   , 4.5625   , 1.75     ,
                4.78125  , 4.8125   , 4.84375  , 2.875   , 4.9375   ,
                2.5      , 4.3125   , 3.8125   , 2.75     , 4.91666667,
                4.95833333, 3.4375   , 3.16666667, 3.08333333, 4.4375   ,
                4.6875   , 3.83333333, 4.16666667, 1.875   , 4.0625   ,
                2.8125   , 4.15625  , 4.71875  , 4.83333333, 4.79166667,
                1.5      , 2.9375   , 4.1875   , 1.375   , 3.6875   ,
                3.9375   , 4.41666667, 1.25     , 4.66666667, 4.70833333,
                4.58333333, 4.90625  , 4.96875  , 4.29166667, 4.45833333,
                3.91666667, 3.58333333, 3.0625   , 4.20833333, 1.125   ,
                1.625   , 3.5625   , 3.70833333, 3.3125   , 4.59375   ,
                4.28125  , 4.34375  , 4.40625  , 4.46875  , 4.53125   ,
                4.54166667, 3.525    , 3.675    , 3.825    , 3.975    ,
                4.33333333, 4.97916667, 4.89583333, 4.575    , 4.15     ,
                3.725    , 3.3      , 4.60416667, 4.52083333, 4.21875   ,
                3.15625  , 4.65625  , 4.05     , 4.1      , 4.2      ,
                3.53125  , 3.84375  , 4.475    , 4.675    , 4.775    ,
                3.20833333, 3.54166667, 2.29166667, 3.95833333, 4.3      ,
                4.35     , 4.4      , 4.45     , 4.08333333, 3.54166667,
                3.1875   , 3.33333333, 4.8      , 4.85     , 4.9      ,
                4.95     , 4.85416667, 4.77083333, 3.29166667, 3.66666667,
                3.09375  , 4.09375  , 3.03125  , 3.70833333, 4.7      ,
                4.525    , 4.175    , 2.41666667, 2.33333333, 1.5625   ,
                4.27083333, 3.45833333, 2.91666667, 3.40625   , 4.725    ,
                4.65     , 4.765625 , 4.546875 , 4.328125 , 4.109375 ,
                3.29166667, 2.58333333, 2.66666667, 4.04166667])
```

Above it is shown that the Rating variable has many unique values that range from 1 to 5.

```
In [11]: # Change date column to datetime64 data type
Car_Reviews['date'] = pd.to_datetime(Car_Reviews['date'])
print(Car_Reviews.dtypes)
```

```
Unnamed: 0      int64
Rating          float64
car_year        int64
brand_name      object
date            datetime64[ns]
review          object
dtype: object
```

```
In [12]: # Next I will convert my ratings to be replaced with a 0 or 1
def create_sentiment(rating):

    if rating<=3.99:
        return 0
    elif rating>=4:
        return 1

Car_Reviews['Updated_Rating'] = Car_Reviews['Rating'].apply(create_sentiment)
```

```
In [13]: # Next I will view the dataframe and see the new variable Updated_Rating
Car_Reviews
```

Out[13]:

	Unnamed: 0	Rating	car_year	brand_name	date	review	Updated_Rating
0	0	5.00	2018	Audi	2018-07-11	BEST ALL AROUND PURPOSE CROSSOVER SUV I have n...	1
1	1	5.00	2018	Audi	2018-06-24	Best car This is a wonderful car. The technol...	1
2	2	5.00	2018	Audi	2018-05-02	Great Buy Do your home work	1
3	3	5.00	2018	Audi	2017-12-07	Fun Car Great ride. Loaded with technology. St...	1
4	4	5.00	2018	Audi	2017-10-25	Best luxury SUV w/ perfect comfort/sport balan...	1
...
31933	31933	4.75	2015	Mercedes-Benz	2015-06-04	One week in but I love it. I just got the car...	1
31934	31934	4.00	2015	Mercedes-Benz	2015-05-19	A delightful car I have been driving the GLA25...	1
31935	31935	3.00	2015	Mercedes-Benz	2015-02-21	This car is amazing but visibility is poor We ...	0
31936	31936	2.75	2015	Mercedes-Benz	2015-01-20	Steering Wheel Module When I first bought this...	0
31937	31937	4.50	2015	Mercedes-Benz	2014-10-06	Fun crossover/hatchback but not an SUV. I've h...	1

31938 rows × 7 columns

```
In [53]: # I will now count the values for each rating
Car_Reviews.Updated_Rating.value_counts()
```

```
Out[53]: 1    27144
         0     4794
         Name: Updated_Rating, dtype: int64
```

Above we can see that there are 27,144 positive reviews while we see 4,794 negative and neutral reviews.

```
In [15]: # Will now update Rating variable to int64
Car_Reviews['Rating'] = Car_Reviews['Rating'].apply(np.int64)
```

```
In [16]: # Next display dtypes
display(Car_Reviews.dtypes)
```

```
Unnamed: 0          int64
Rating              int64
car_year            int64
brand_name          object
date                datetime64[ns]
review              object
Updated_Rating      int64
dtype: object
```

Data Preparation and Natural language processing

```
In [17]: # First I will use info to view each variable
Car_Reviews.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 31938 entries, 0 to 31937
Data columns (total 7 columns):
#   Column          Non-Null Count  Dtype
---  -
0   Unnamed: 0      31938 non-null  int64
1   Rating          31938 non-null  int64
2   car_year        31938 non-null  int64
3   brand_name      31938 non-null  object
4   date            31938 non-null  datetime64[ns]
5   review          31938 non-null  object
6   Updated_Rating  31938 non-null  int64
dtypes: datetime64[ns](1), int64(4), object(2)
memory usage: 1.7+ MB
```

```
In [18]: # Import needed libraries
!pip install nltk
import nltk
import string
from nltk.stem import WordNetLemmatizer
from nltk.stem.porter import PorterStemmer
from nltk.corpus import stopwords
from nltk.stem.snowball import SnowballStemmer
from nltk.stem.lancaster import LancasterStemmer
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
import re
nltk.download('wordnet')
import warnings
```

Requirement already satisfied: nltk in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (3.6.7)
Requirement already satisfied: tqdm in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from nltk) (4.64.1)
Requirement already satisfied: joblib in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from nltk) (1.1.1)
Requirement already satisfied: regex>=2021.8.3 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from nltk) (2022.10.31)
Requirement already satisfied: click in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from nltk) (7.1.2)
Requirement already satisfied: colorama; platform_system == "Windows" in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from tqdm->nltk) (0.4.3)
Requirement already satisfied: importlib-resources; python_version < "3.7" in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from tqdm->nltk) (5.4.0)
Requirement already satisfied: zipp>=3.1.0; python_version < "3.10" in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from importlib-resources; python_version < "3.7"->tqdm->nltk) (3.1.0)

[nltk_data] Downloading package wordnet to
[nltk_data] C:\Users\Robyn\AppData\Roaming\nltk_data...
[nltk_data] Package wordnet is already up-to-date!

Implementing Lowercase

```
In [19]: # Next I will use Natural Language processing to edit the reviews for each car brand.By changing Review text to Lowercase
Car_Reviews['Updated_Review'] = Car_Reviews['review'].apply(lambda x: x.lower())
```

Punctuation Removal

```
In [20]: # Next remove punctuation
def punctuation_removal(text):
    text = " ".join([word.strip(string.punctuation) for word in text.split(" ")])
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(punctuation_removal)
```

Remove Imbedded Numbers

```
In [21]: # Next I will use isdigit and apply to remove imbedded numbers
def remove_number(text):
    text = "".join([word for word in text if not any(c.isdigit() for c in word)])
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(remove_number)
```

Create Tokens

```
In [22]: # Import needed Libraries
import sys
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn import metrics
warnings.filterwarnings('ignore')
if sys.version[0] == '2':
    reload(sys)
    sys.setdefaultencoding("utf-8")
```

```
In [23]: ▶ # Create tokens through the use of split
def token(text):
    text = text.split()
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(token)
```

Stop Word Removal

```
In [24]: ▶ # Import stop words
import nltk
nltk.download('stopwords')

[nltk_data] Downloading package stopwords to
[nltk_data] C:\Users\Robyn\AppData\Roaming\nltk_data...
[nltk_data] Package stopwords is already up-to-date!
```

Out[24]: True

```
In [25]: ▶ # Set stop words to english
brand_stop_words = set(stopwords.words('english'))
brand_names = ['Audi', 'Lexus', 'INFINITI', 'BMW', 'Mercedes', 'Benz']
punctuation_string = string.punctuation
```

```
In [26]: ▶ # Next I will remove the stopwords from my Review_update
def remove_stopword(text):
    stop = stopwords.words('english')
    text = [x for x in text if x not in brand_stop_words and x not in brand_names and x not in punctuation_string]
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(remove_stopword)
```

```
In [27]: ▶ # Import needed package
import nltk
nltk.download('omw-1.4')

[nltk_data] Downloading package omw-1.4 to
[nltk_data] C:\Users\Robyn\AppData\Roaming\nltk_data...
[nltk_data] Package omw-1.4 is already up-to-date!
```

Out[27]: True

Convert and Join Words

```
In [28]: ▶ # Next I will use WordNetLemmatizer convert words used in review to base words
def word_lemmatize(text):
    text = [WordNetLemmatizer().lemmatize(word) for word in text]
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(word_lemmatize)
```

```
In [29]: ▶ # Join my Review data values
def join_review_data(text):
    text = " ".join(text)
    return text
Car_Reviews['Updated_Review'] = Car_Reviews['Updated_Review'].apply(join_review_data)
```

Implement Vader

```
In [30]: # Install needed library
!pip install vaderSentiment
from vaderSentiment.vaderSentiment import SentimentIntensityAnalyzer

Requirement already satisfied: vaderSentiment in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (3.3.2)
Requirement already satisfied: requests in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from vaderSentiment) (2.2
3.0)
Requirement already satisfied: urllib3!=1.25.0,!=1.25.1,<1.26,>=1.21.1 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-pack
ages (from requests->vaderSentiment) (1.25.8)
Requirement already satisfied: idna<3,>=2.5 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from requests->vaderS
entiment) (2.9)
Requirement already satisfied: chardet<4,>=3.0.2 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from requests->v
aderSentiment) (3.0.4)
Requirement already satisfied: certifi>=2017.4.17 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from requests->
vaderSentiment) (2020.4.5.1)

In [31]: # Next I create a polarity variable
Car_Reviews['Review_Polarity'] = Car_Reviews['Rating'].apply(lambda x: 'Positive' if x > 3 else 'Neutral' if x == 3 else 'Ne
Car_Reviews
```

Out[31]:

Unnamed: 0	Rating	car_year	brand_name	date	review	Updated_Rating	Updated_Review	Review_Polarity
0	0	5	2018	Audi	2018-07-11	BEST ALL AROUND PURPOSE CROSSOVER SUV I have n...	best around purpose crossover suv never seen d...	Positive
1	1	5	2018	Audi	2018-06-24	Best car This is a wonderful car. The technol...	best car wonderful car technology adaptable ca...	Positive
2	2	5	2018	Audi	2018-05-02	Great Buy Do your home work	great buy home work	Positive
3	3	5	2018	Audi	2017-12-07	Fun Car Great ride. Loaded with technology. St...	fun car great ride loaded technology steering ...	Positive
4	4	5	2018	Audi	2017-10-25	Best luxury SUV w/ perfect comfort/sport balan...	best luxury suv w perfect comfort/sport balanc...	Positive
...
31933	31933	4	2015	Mercedes-Benz	2015-06-04	One week in but I love it. I just got the car...	one week love got car procrastinating couple w...	Positive
31934	31934	4	2015	Mercedes-Benz	2015-05-19	A delightful car I have been driving the GLA25...	delightful car driving gla half year absolutel...	Positive
31935	31935	3	2015	Mercedes-Benz	2015-02-21	This car is amazing but visibility is poor We ...	car amazing visibility poor longer car rear wi...	Neutral
31936	31936	2	2015	Mercedes-Benz	2015-01-20	Steering Wheel Module When I first bought this...	steering wheel module first bought car love wi...	Negative
31937	31937	4	2015	Mercedes-Benz	2014-10-06	Fun crossover/hatchback but not an SUV. I've h...	fun crossover/hatchback suv i've day good car ...	Positive

31938 rows x 9 columns

```
In [32]: # I will use SentimentIntensityAnalyzer to calculat the vader rating
vader_analyzer=SentimentIntensityAnalyzer()
vader = []

for i in Car_Reviews['Updated_Review']:
    score = vader_analyzer.polarity_scores(i)
    vader.append(score['compound'])
Car_Reviews['Rating_Vader'] = vader
```

```
In [33]: # I will also determine the rating of each value by setting the vader to positive, negative, or neutral
Car_Reviews['Polarity_Vader_Review'] = Car_Reviews['Rating_Vader'].apply(lambda x: 'Positive' if x > 0 else ('Neutral' if x == 0 else 'Negative'))
Car_Reviews.head()
```

Out[33]:

Unnamed: 0	Rating	car_year	brand_name	date	review	Updated_Rating	Updated_Review	Review_Polarity	Rating_Vader	Polarity_Vader_Review	
0	0	5	2018	Audi	2018-07-11	BEST ALL AROUND PURPOSE CROSSOVER SUV I have n...	1	best around purpose crossover suv never seen d...	Positive	0.9887	Positive
1	1	5	2018	Audi	2018-06-24	Best car This is a wonderful car. The technol...	1	best car wonderful car technology adaptable ca...	Positive	0.9590	Positive
2	2	5	2018	Audi	2018-05-02	Great Buy Do your home work	1	great buy home work	Positive	0.6249	Positive
3	3	5	2018	Audi	2017-12-07	Fun Car Great ride. Loaded with technology. St...	1	fun car great ride loaded technology steering ...	Positive	0.8126	Positive
4	4	5	2018	Audi	2017-10-25	Best luxury SUV w/ perfect comfort/sport balan...	1	best luxury suv w perfect comfort/sport balanc...	Positive	0.9932	Positive

Implement Label Encoder


```
In [34]: # I will now use LabelEncoder on my 'Review_Polarity', 'Polarity_Vader_Review'
label_encode = LabelEncoder()
for i in ['Review_Polarity', 'Polarity_Vader_Review']:
    Car_Reviews[i] = label_encode.fit_transform(Car_Reviews[i])
```

Data Visualizations

Average Rating by Brand Name

```
In [35]: # First I will create a barplot for each brand that shows the average rating with seaborn
import seaborn as sns
sns.barplot(x='brand_name', y='Rating', data = Car_Reviews, palette = 'plasma')
```

Out[35]: <matplotlib.axes._subplots.AxesSubplot at 0x176f6ea9cc0>




Above we can see that the average rating of each brand is around a four out of five.

Number of Reviews by Car Model Year

```
In [36]: # Next I will create a plot that shows the number of reviews per car model year
sns.set(rc={'figure.figsize':(20,10)})
sns.countplot(x='car_year', data=Car_Reviews).set(title='Count Per Ratings Per Year')
```

```
Out[36]: [Text(0.5, 1.0, 'Count Per Ratings Per Year')]
```




Above the plot shows that 2004 car brands was the year with the largest amount of reviews

Rating Count Percentage

```
In [37]: # First I will create rate value for the car reviews.
rate_value = Car_Reviews.Rating.value_counts()
```

```
In [38]: # Create a bar plot that shows the percentage of ratings
with plt.style.context('ggplot'):
    plt.figure(figsize=(10, 8))
    plt.bar(rate_value.index, rate_value.values, color='red')
    for rating, value in zip(rate_value.index, rate_value.values):
        plt.text(rating, value, str(round(value/sum(rate_value.values)*100, 2))+'%',
                 color='black', bbox=dict(facecolor='white'))
    plt.title('Car Brand Review Percentage by Rating')
    plt.xlabel('Car Brand Ratings')
    plt.ylabel('Rating Count')
    plt.yticks(np.arange(0, 20000, 5000))
```




Above we see that on the rating scale a rating of four has been given the most with 54.36% while a rating of one has only been given 1.71%.

Vader Rating by date for each Car Brand

```
In [39]: !pip install plotly
import plotly.express as px
```

Requirement already satisfied: plotly in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (5.12.0)
 Requirement already satisfied: tenacity>=6.2.0 in c:\users\robyn\anaconda3\envs\dsc650\lib\site-packages (from plotly) (8.1.0)

```
In [40]: # I will create a scatter that shows the Vader rating throughout the years for each brand
fig = px.scatter(Car_Reviews,
                 x='date',
                 y='Rating_Vader',
                 color='brand_name',
                 size='Updated_Rating')
fig.show()
```




The above scatter plot looks overwhelming when all brands are shown. But on the right side you can click each brand on and off to get a better look at each brand. When you go through each brand you will see that Mercedes has the largest number of reviews and infinity has the least. While Lexus shows the largest number of reviews from 2016 forward.

Car Brand Review Percentage by Polarity Vader Review

```
In [41]: # First I will create rate value for the car reviews.
rate_value = Car_Reviews.Polarity_Vader_Review.value_counts()
```

```
In [42]: # Create a bar plot that shows the percentage of ratings
with plt.style.context('ggplot'):
    plt.figure(figsize=(10, 8))
    plt.bar(rate_value.index, rate_value.values, color='green')
    for rating, value in zip(rate_value.index, rate_value.values):
        plt.text(rating, value, str(round(value/sum(rate_value.values)*100, 2))+'%',
                 color='black', bbox=dict(facecolor='orange'))
    plt.title('Car Brand Review Percentage by Polarity Vader Review')
    plt.xlabel('Car Brand Polarity Review')
    plt.ylabel('Review Count')
    plt.yticks(np.arange(0, 30000, 5000))
```



The above bar chart for Car Brand Polarity Vader Review Percentages shows a higher percentage for positive while negative reviews shows 11.07% with a 2.24% for neutral.

Modeling

```
In [43]: # Now I will split the Car review data into a training and test sets
Target_data = ['Updated_Review']
Predict_data = ['Review_Polarity']
X=Car_Reviews[Target_data].values
Y=Car_Reviews[Predict_data].values
x_train, x_test, y_train, y_test = train_test_split(X,Y, stratify=Y, test_size=.4, random_state=0)
```

```
In [44]: # View the shape for my training and test sets
print(x_train.shape)
print(x_test.shape)
print(y_train.shape)
print(y_test.shape)
np.unique(y_train, return_counts=True)
```

```
(19162, 1)
(12776, 1)
(19162, 1)
(12776, 1)
```

```
Out[44]: (array([0, 1, 2]), array([ 1050,  1826, 16286], dtype=int64))
```

TFIDF Training Set Data

```
In [45]: # Create TfidfVectorizer feature for the x_train
tfidf_train_data = TfidfVectorizer()
x_train_vector = tfidf_train_data.fit_transform(x_train.ravel())
```

```
In [46]: ▶ # Pull TfidfVectorizer train shape  
x_train_vector.shape
```

```
Out[46]: (19162, 21980)
```

Logistic Regression

```
In [49]: ▶ from sklearn.linear_model import LogisticRegression
```

```
In [50]: ▶ # Logistic regression model with train data  
logistic_model = LogisticRegression()  
logistic_model = logistic_model.fit(x_train_vector, y_train)  
print(logistic_model.score(x_train_vector, y_train))
```

```
0.9149358104581985
```

Random Forest Analysis

```
In [51]: ▶ from sklearn.ensemble import RandomForestClassifier
```

```
In [52]: ▶ # Random Forest Classifier accuracy on the train set  
Random_Forest = RandomForestClassifier(max_depth = 300, random_state = 80)  
Random_Forest.fit(x_train_vector, y_train.ravel())  
print(Random_Forest.score(x_train_vector, y_train.ravel()))
```

```
0.9995303204258428
```

As seen above the Random Forest had an accuracy of 99.95% and the Logistic Regression had a accuracy of 91.49%

```
In [ ]: ▶
```