

Advanced Computer Architectures

(High Performance Processors and Systems)

Dynamic Scheduling: Scoreboard

Politecnico di Milano

v1

Alessandro Verosimile <alessandro.verosimile@polimi.it>

Marco D. Santambrogio <marco.santambrogio@polimi.it>

Instruction Level Parallelism

- Two strategies to support ILP:
 - **Dynamic Scheduling:** Depend on the hardware to locate parallelism
 - **Static Scheduling:** Rely on software for identifying potential parallelism
- Hardware intensive approaches dominate desktop and server markets

Instruction Level Parallelism

- Two strategies to support ILP:
 - **Dynamic Scheduling:** Depend on the hardware to locate parallelism
 - **Static Scheduling:** Rely on software for identifying potential parallelism
- Hardware intensive approaches dominate desktop and server markets

Key Idea: dynamic scheduling

- Problem:
 - data dependences that cannot be hidden with bypassing or forwarding cause hardware stalls of the pipeline
- Solution: allow instructions behind a stall to proceed
 - HW rearranges the instruction execution to reduce stalls
- Enables out-of-order execution and completion (commit)
 - Out-of order execution introduces possibility of WAR, WAW data hazards.
- First implemented in CDC6600 (1963)

A Data Structure for Correct Issues

Keeps track of the status of Functional Units

Name	Busy	Op	Dest	Src1	Src2
Int					
Mem					
Add1					
Add2					
Add3					
Mult1					
Mult2					
Div					

The instruction *i* at the Issue stage consults this table

FU available? check the busy column

RAW? search the dest column for *i*'s sources

WAR? search the source columns for *i*'s destination

WAW? search the dest column for *i*'s destination


An entry is added to the table if no hazard is detected;

An entry is removed from the table after Write-Back

CDC6600 Scoreboard

- Instructions dispatched in-order to functional units provided no structural hazard or WAW
 - Stall on structural hazard, no functional units available
 - Only one pending write to any register
- Instructions wait for input operands (RAW hazards) before execution
 - Can execute out-of-order
- Instructions wait for output register to be read by preceding instructions (WAR)
 - Result held in functional unit until register free

Scoreboard Architecture (CDC 6600)



Scoreboard Operation

- Scoreboard centralizes hazard management
 - Every instruction goes through the scoreboard
 - Scoreboard determines when the instruction can read its operands and begin execution
 - Monitors changes in hardware and decides when a stalled instruction can execute
 - Controls when instructions can write results
- New pipeline

ID		EX	WB
Issue	Read Regs	Execution	Write

Scoreboard Scheme

- ID stage splitted in two parts:
 - **Issue** (decode and check structural hazard)
 - **Read Operands** (wait until no data hazards)
- In-order issue BUT out-of-order read-operands
- Scoreboard allows instructions without dependencies to execute

Four Stages of Scoreboard Control

1. Issue

Decode instructions & check for structural hazards.

- ✓ Instructions issued in program order (for hazard checking)
- ✓ If a functional unit for the instruction is free and no other active instruction has the same destination register (WAW), the scoreboard issues the instruction to the functional unit and updates its internal data structure.
- ✓ If a structural or a WAW hazard exists, then the instruction issue stalls, and no further instructions will issue until these hazards are cleared.

Four Stages of Scoreboard Control

2. Read Operands

Wait until no data hazards, then read operands

A source operand is available if:

- no earlier issued active instruction will write it or
- A functional unit is writing its value in a register

When the source operands are available, the scoreboard tells the functional unit to proceed to read the operands from the registers and begin execution.

RAW hazards are resolved dynamically in this step, and instructions may be sent into execution out of order.

No forwarding of data in this model

Four Stages of Scoreboard Control

3. Execution

Operate on operands

The functional unit begins execution upon receiving operands. When the result is ready, it notifies the scoreboard that it has completed execution.

FUs are characterized by:

- **latency** (the effective time used to complete one operation)
- **Initiation interval** (the number of cycles that must elapse between issuing two operations to the same functional unit).

Four Stages of Scoreboard Control

4. Write result Finish execution

Once the scoreboard is aware that the functional unit has completed execution, the scoreboard checks for WAR hazards. If none, it writes results. If WAR, then it stalls the instruction.


Assume we can overlap issue and write

WAR/WAW Example


```
DIVD  F0, F2, F4  
ADDD  F6, F0, F8  
SUBD  F8, F8, F14  
MULD  F6, F10, F8,
```

WAR/WAW Example

```
DIVD  F0, F2, F4  
ADDD  F6, F0, F8  
SUBD  F8, F8, F14  
MULD  F6, F10, F8
```




WAR/WAW Example



The scoreboard would stall:

- SUBD in the WB stage, waiting that ADDD reads F0 and F8 and


WAR/WAW Example



The scoreboard would stall:

- SUBD in the WB stage, waiting that ADDD reads F0 and F8 and
- MULDD in the issue stage until ADDD writes F6.

WAR/WAW Example



The scoreboard would stall:

- SUBD in the WB stage, waiting that ADDD reads F0 and F8 and
- MULDD in the issue stage until ADDD writes F6.

Can be solved through register renaming

Scoreboard Implications

- Solution for WAW:
 - Detect hazard and stall issue of new instruction until the other instruction completes
- No register renaming
- Need to have multiple instructions in execution phase → Multiple execution units or pipelined execution units
- Scoreboard keeps track of dependences and state of operations

Scoreboard Implications

- Solution for WAW:
 - Detect hazard and stall issue of new instruction until the other instruction completes
- No register renaming
- Need to have multiple instructions in execution phase → Multiple execution units or pipelined execution units
- Scoreboard keeps track of dependences and state of operations

Scoreboard structure: three parts

1. Instruction status

2. Functional Unit status

Indicates the state of the functional unit (FU):

Busy – Indicates whether the unit is busy or not

Op - The operation to perform in the unit (+,-, etc.)

Fi - Destination register

Fj, Fk – Source register numbers

Qj, Qk – Functional units producing source registers

Rj, Rk – Flags indicating when Fj, Fk are ready

3. Register result status

Indicates which functional unit will write each register.

Blank if no pending instructions will write that register.

Detailed Scoreboard Pipeline Control

Instruction status	Wait until	Bookkeeping
Issue	Not busy (FU) and not result(D)	$\text{Busy}(\text{FU}) \leftarrow \text{yes}; \text{Op}(\text{FU}) \leftarrow \text{op};$ $\text{Fi}(\text{FU}) \leftarrow \text{'D'}; \text{Fj}(\text{FU}) \leftarrow \text{'S1'};$ $\text{Fk}(\text{FU}) \leftarrow \text{'S2'}; \text{Qj} \leftarrow \text{Result}(\text{'S1'});$ $\text{Qk} \leftarrow \text{Result}(\text{'S2'}); \text{Rj} \leftarrow \text{not Qj};$ $\text{Rk} \leftarrow \text{not Qk}; \text{Result}(\text{'D'}) \leftarrow \text{FU};$
Read operands	Rj and Rk	$\text{Rj} \leftarrow \text{No}; \text{Rk} \leftarrow \text{No}$
Execution complete	Functional unit done	
Write result	$\forall f((\text{Fj}(f) \neq \text{Fi}(\text{FU})$ or $\text{Rj}(f) = \text{No}) \&$ $(\text{Fk}(f) \neq \text{Fi}(\text{FU})$ or $\text{Rk}(f) = \text{No}))$	$\forall f(\text{if } \text{Qj}(f) = \text{FU} \text{ then } \text{Rj}(f) \leftarrow \text{Yes});$ $\forall f(\text{if } \text{Qk}(f) = \text{FU} \text{ then } \text{Rk}(f) \leftarrow \text{Yes});$ $\text{Result}(\text{Fi}(\text{FU})) \leftarrow 0; \text{Busy}(\text{FU}) \leftarrow \text{No}$

Read Exec Write


<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

No
No
No
No
No

Clock $F0$ $F2$ $F4$ $F6$ $F8$ $F10$ $F12$... $F30$

--

Scoreboard Architecture (CDC 6600)



Execution Process

- Issue
 - Functional unit is free (structural)
 - Active instructions do not have same Rd (WAW)
- Read Operands
 - Checks availability of source operands
 - Resolves RAW hazards dynamically (out-of-order execution)
- Execution
 - Functional unit begins execution when operands arrive
 - Notifies the scoreboard when it has completed execution
- Write result
 - Scoreboard checks WAR hazards
 - Stalls the completing instruction if necessary

Read Exec Write

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$	
1	FU										

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+	R2	1		
LD	F2	45+	R3			
MULTD	F0	F2	F4			
SUBD	F8	F6	F2			
DIVD	F10	F0	F6			
ADDD	F6	F8	F2			

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>Functional unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F6		R2				Yes
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
1	FU	Integer								

Scoreboard Example: Cycle 1

28

Instruction status:

Instruction	<i>j</i>	<i>k</i>	Read	Exec	Write
			<i>Issue</i>	<i>Oper</i>	<i>Comp Result</i>
LD	F6	34+	R2		
LD	F2	45+	R3		
MULTD	F0	F2	F4		
SUBD	F8	F6	F2		
DIVD	F10	F0	F6		
ADDD	F6	F8	F2		

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

l unit status:

		<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fi?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>
	Integer	Yes	Load	F6		R2		Yes
	Mult1	No						
	Mult2	No						
	Add	No						
	Divide	No						

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
				Integer					

Read Exec Write

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F6		R2				Yes
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Clock	$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
2	FU	Integer							

Scoreboard Example: Cycle 2

30

Instruction status:

Instruction		<i>j</i>	<i>k</i>	Issue	Read Oper	Exec Comp	Write Result
LD	F6	34+	R2	1	2		
LD	F2	45+	R3				
MULTD	F0	F2	F4				
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F6		R2				Yes
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
2	Integer								

Issue 2nd LD?

Integer Pipeline Full - Cannot exec 2nd Load - Issue stalls

Read Exec Write

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

Integer	Yes	Load	F6	R2	No
Mult1	No				
Mult2	No				
Add	No				
Divide	No				

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
3	FU	Integer								

Scoreboard Example: Cycle 3

32

Instruction status:

Instruction		<i>j</i>	<i>k</i>	Issue	Read Oper	Exec Comp	Write Result
LD	F6	34+	R2	1	2	3	
LD	F2	45+	R3				
MULTD	F0	F2	F4				
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

Time	Name	Busy	Op	dest <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	Yes	Load	F6		R2				No
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
3	<i>FU</i>	Integer								

Issue MULT? Issue stalls

Load execution completes in one clock cycle

Read Exec Write

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$	\dots	$F30$
4	FU	Integer								

Scoreboard Example: Cycle 4

34

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>		Issue	Oper	Comp Result
LD	F6	34+	R2	1	2	3
LD	F2	45+	R3			
MULTD	F0	F2	F4			
SUBD	F8	F6	F2			
DIVD	F10	F0	F6			
ADDD	F6	F8	F2			

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

		<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
Time	Name	Busy	Op	Fi	Fj	Fk	Qj	Qk
	Integer	No						
	Mult1	No						
	Mult2	No						
	Add	No						
	Divide	No						

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
4	Integer								

Issue stalls

Write F6

Read Exec Write

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
-------------	-----------	-----------	-----------	-----------	------------	------------

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				Yes
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$	
5	FU	Integer									

Scoreboard Example: Cycle 5

36

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5			
MULTD	F0	F2	F4				
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

l unit status:

		<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fi?</i>	<i>Fk?</i>		
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				Yes
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
5	<i>FU</i>	Integer								

The 2nd load is issued

Scoreboard Example: Cycle 6

37

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>		Issue	Oper	Comp Result
LD	F6	34+	R2	1	2	3
LD	F2	45+	R3	5	6	
MULTD	F0	F2	F4	6		
SUBD	F8	F6	F2			
DIVD	F10	F0	F6			
ADDD	F6	F8	F2			

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

			<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
Time	Name	Busy	Op	Fi	Fj	Fk	Qj	Qk	Rj
	Integer	Yes	Load	F2		R3			
	Mult1	Yes	Mult	F0	F2	F4	Integer		No
	Mult2	No							
	Add	No							
	Divide	No							

Register result status:

Clock		F0	F2	F4	F6	F8	F10	F12	...	F30
6	FU	Mult1	Integer							

Scoreboard Example: Cycle 6

38

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>		<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6		
MULTD	F0	F2	F4	6			
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>l unit status:</i>			<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>	
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				Yes
	Mult1	Yes	Mult	F0	F2	F4	Integer		No	Yes
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		F0	F2	F4	F6	F8	F10	F12	...	F30
6	FU	Mult1	Integer							

MULT is issued but has to wait for F2 from LOAD (RAW)

Scoreboard Example: Cycle 7

39

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	
MULTD	F0	F2 F4	6			
SUBD	F8	F6 F2	7			
DIVD	F10	F0 F6				
ADDD	F6	F8 F2				

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				No
	Mult1	Yes	Mult	F0	F2	F4	Integer		No	Yes
	Mult2	No								
	Add	Yes	Sub	F8	F6	F2		Integer	Yes	No
	Divide	No								

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
7	<i>FU</i>	Mult1	Integer			Add				

Scoreboard Example: Cycle 7

40

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	
MULTD	F0	F2	F4	6			
SUBD	F8	F6	F2	7			
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>l unit status:</i>			<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>	
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				No
	Mult1	Yes	Mult	F0	F2	F4	Integer		No	Yes
	Mult2	No								
	Add	Yes	Sub	F8	F6	F2		Integer	Yes	No
	Divide	No								

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
7	<i>FU</i>	Mult1	Integer			Add				

Now SUBD can be issued but has to wait for operands
Read multiple operands?

Instruction status:

				<i>Read</i>	<i>Exec</i>	<i>Write</i>
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	
MULTD	F0	F2 F4	6			
SUBD	F8	F6 F2	7			
DIVD	F10	F0 F6	8			
ADDD	F6	F8 F2				

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>l unit status:</i>			<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>	
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				No
	Mult1	Yes	Mult	F0	F2	F4	Integer		No	Yes
	Mult2	No								
	Add	Yes	Sub	F8	F6	F2		Integer	Yes	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
8	<i>FU</i>	Mult1	Integer			Add	Divide			

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	
MULTD	F0	F2 F4	6			
SUBD	F8	F6 F2	7			
DIVD	F10	F0 F6	8			
ADDD	F6	F8 F2				

Integer: 1cc
 Multi: 10cc
 Add: 2cc
 Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	Yes	Load	F2		R3				No
	Mult1	Yes	Mult	F0	F2	F4	Integer		No	Yes
	Mult2	No								
	Add	Yes	Sub	F8	F6	F2		Integer	Yes	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
8	FU Mult1 Integer Add Divide								

DIVD is issued but there is another RAW hazard (F0) from MULTD then DIVD has to wait for F0

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6			
SUBD	F8	F6	F2	7			
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2				

Integer: 1cc
 Multi: 10cc
 Add: 2cc
 Divide: 40cc

Functional unit status:


<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
	Mult1	Yes	Mult	F0	F2	F4			Yes	Yes
	Mult2	No								
	Add	Yes	Sub	F8	F6	F2			Yes	Yes
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
8	<i>FU</i>	Mult1 Add Divide								

Load completes, and operands for MULT and SUBD are ready

Scoreboard Architecture (CDC 6600)



Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9		
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2				

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

Functional unit status:

Time	Name	Busy	Op	dest Fi	S1 Fj	S2 Fk	FU Qj	FU Qk	Fj? Rj	Fk? Rk
	Integer	No								
10	Mult1	Yes	Mult	F0	F2	F4			Yes	Yes
	Mult2	No								
2	Add	Yes	Sub	F8	F6	F2			Yes	Yes
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Note: A red arrow points from the 'Integer' row to the 'Mult1' row. A blue arrow points from the text 'Note Remaining' to the 'Mult1' row.

Register result status:

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
9	FU	Mult1				Add	Divide			

Scoreboard Example: Cycle 9

46

Instruction status:

Instruction		<i>j</i>	<i>k</i>	Issue	Read <i>Oper</i>	Exec <i>Comp</i>	Write <i>Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9		
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2				

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

Note
Remaining

Time	Name	Busy	Op	dest <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
10	Mult1	Yes	Mult	F0	F2	F4			Yes	Yes
	Mult2	No								
2	Add	Yes	Sub	F8	F6	F2			Yes	Yes
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
9	<i>FU</i>	Mult1				Add	Divide			

Read operands for MULTD & SUBD

MULTD and SUBD are sent in execution in parallel

Issue ADDD? No for structural hazard on ADD Functional Unit

Scoreboard Example: Cycle 10

47

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9		
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2				

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
9	Multi	Yes	Multi	F0	F2	F4			No	No
	Multi2	No								
1	Add	Yes	Sub	F8	F6	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Multi		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
10	<i>FU</i>	Multi				Add	Divide			

Scoreboard Example: Cycle 11

48

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2				

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
8	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
0	Add	Yes	Sub	F8	F6	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
11	<i>FU</i>	Mult1 Add Divide								

SUBD ends

Scoreboard Example: Cycle 12

49

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>		Issue	Oper	Comp Result
LD	F6	34+	R2	1	2	3 4
LD	F2	45+	R3	5	6	7 8
MULTD	F0	F2	F4	6	9	
SUBD	F8	F6	F2	7	9	11 12
DIVD	F10	F0	F6	8		
ADDD	F6	F8	F2			

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
7	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	No								
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		F0	F2	F4	F6	F8	F10	F12	...	F30
12	FU	Mult1					Divide			

Read operands for DIVD?

Scoreboard Example: Cycle 13

50

Instruction status:

Instruction		<i>j</i>	<i>k</i>	Issue	Read <i>Oper</i>	Exec <i>Comp</i>	Write <i>Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13			

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

Time	Name	Busy	Op	dest <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
6	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			Yes	Yes
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
13	<i>FU</i>	Mult1			Add		Divide			

SUBD writes results in CC12 and ADDD can be issued in CC13

Scoreboard Example: Cycle 14

51

Instruction status:

				Read	Exec	Write
Instruction		<i>j</i>	<i>k</i>	Issue	Oper	Comp Result
LD	F6	34+	R2	1	2	3 4
LD	F2	45+	R3	5	6	7 8
MULTD	F0	F2	F4	6	9	
SUBD	F8	F6	F2	7	9	11 12
DIVD	F10	F0	F6	8		
ADDD	F6	F8	F2	13	14	

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
5	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
2	Add	Yes	Add	F6	F8	F2			Yes	Yes
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
14	FU	Mult1			Add		Divide			

ADDD reads operands

(out-of-order read operands: ADDD reads operands before DIVD)

Scoreboard Example: Cycle 15

52

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	8
MULTD	F0	F2 F4	6	9		
SUBD	F8	F6 F2	7	9	11	12
DIVD	F10	F0 F6	8			
ADDD	F6	F8 F2	13	14		

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>l unit status:</i>				<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
4	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
1	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
15	<i>FU</i>	Mult1			Add		Divide			

Scoreboard Example: Cycle 16

53

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

Time	Name	Busy	Op	dest <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
3	Mult1	Yes	Multi	F0	F2	F4			No	No
	Mult2	No								
0	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Multi1		No	Yes

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
16	FU Multi1			Add		Divide			

ADDD ends execution

Scoreboard Example: Cycle 17

54

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest</i> <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
2	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
17	<i>FU</i>	Mult1			Add		Divide			

Why not write result of ADD???

Scoreboard Example: Cycle 17

55

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

WAR Hazard!

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
2	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
17	<i>FU</i>	Mult1			Add		Divide			

Why not write result of ADD???

DIVD must first read F6 but cannot read until MULTD writes F0

Scoreboard Example: Cycle 17

56

Instruction status:

Instruction		<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9		
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

WAR Hazard!

Functional unit status:

Time	Name	Busy	Op	dest <i>Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
2	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
17	<i>FU</i>	Mult1			Add		Divide			

Why not write result of ADD???

DIVD must first read F6 but cannot read until MULTD writes F0

Scoreboard Example: Cycle 18

57

Instruction status:

Instruction	<i>j</i>	<i>k</i>	<i>Read Exec Write</i>			
			<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	8
MULTD	F0	F2 F4	6	9		
SUBD	F8	F6 F2	7	9	11	12
DIVD	F10	F0 F6	8			
ADDD	F6	F8 F2	13	14	16	

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest</i>		<i>S1</i>	<i>S2</i>	<i>FU</i>		<i>Fj?</i>	<i>Fk?</i>
				<i>Fi</i>	<i>Fj</i>		<i>Fk</i>	<i>Qj</i>	<i>Qk</i>		
	Integer	No									
1	Mult1	Yes	Mult	F0	F2	F4				No	No
	Mult2	No									
	Add	Yes	Add	F6	F8	F2				No	No
	Divide	Yes	Div	F10	F0	F6	Mult1			No	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
18	<i>FU</i>	Mult1				Add		Divide		

Scoreboard Example: Cycle 19

58

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9	19	
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
0	Mult1	Yes	Mult	F0	F2	F4			No	No
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6	Mult1		No	Yes

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
19	FU Mult1			Add		Divide			

Scoreboard Example: Cycle 20

59

Instruction status:

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9	19	20
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8			
ADDD	F6	F8	F2	13	14	16	

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>
				<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
	Divide	Yes	Div	F10	F0	F6			Yes	Yes

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
					Add		Divide			

FU

Scoreboard Example: Cycle 21

60

Instruction status:

Instruction status:

Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9	19	20
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8	21		
ADDD	F6	F8	F2	13	14	16	

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

Time	Name	Busy	Op	dest <i>Fj</i>	<i>Fk</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	Yes	Add	F6	F8	F2			No	No
40	Divide	Yes	Div	F10	F0	F6			Yes	Yes

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
21	FU				Add	Divide			

WAR Hazard is now gone...

Scoreboard Example: Cycle 22

61

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>	Issue	Oper	Comp	Result
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	8
MULTD	F0	F2 F4	6	9	19	20
SUBD	F8	F6 F2	7	9	11	12
DIVD	F10	F0 F6	8	21		
ADDD	F6	F8 F2	13	14	16	22

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

l unit status:

Time	Name	Busy	Op	dest Fi	S1 Fj	S2 Fk	FU Qj	FU Qk	Fj? Rj	Fk? Rk
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
39	Divide	Yes	Div	F10	F0	F6			No	No

Register result status:

Clock		F0	F2	F4	F6	F8	F10	F12	...	F30
22	FU						Divide			

Now DIVD has read its operands, ADDD can write the result in F6

Faster than light
computation
(skip a couple of cycles)



Scoreboard Example: Cycle 61

63

Instruction status:

Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Read Oper</i>	<i>Exec Comp</i>	<i>Write Result</i>
LD	F6	34+ R2	1	2	3	4
LD	F2	45+ R3	5	6	7	8
MULTD	F0	F2 F4	6	9	19	20
SUBD	F8	F6 F2	7	9	11	12
DIVD	F10	F0 F6	8	21	61	
ADDD	F6	F8 F2	13	14	16	22

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Functional unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest Fi</i>	<i>S1 Fj</i>	<i>S2 Fk</i>	<i>FU Qj</i>	<i>FU Qk</i>	<i>Fj? Rj</i>	<i>Fk? Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
	0 Divide	Yes	Div	F10	F0	F6			No	No

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
61	FU Divide								

DIVD ends execution

Scoreboard Example: Cycle 62

64

Instruction status:

				Read	Exec	Write
Instruction	<i>j</i>	<i>k</i>		Issue	Oper	Comp Result
LD	F6	34+	R2	1	2	3 4
LD	F2	45+	R3	5	6	7 8
MULTD	F0	F2	F4	6	9	19 20
SUBD	F8	F6	F2	7	9	11 12
DIVD	F10	F0	F6	8	21	61 62
ADDD	F6	F8	F2	13	14	16 22

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

<i>l unit status:</i>		<i>dest</i>	<i>S1</i>	<i>S2</i>	<i>FU</i>	<i>FU</i>	<i>Fj?</i>	<i>Fk?</i>		
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Fi</i>	<i>Fj</i>	<i>Fk</i>	<i>Qj</i>	<i>Qk</i>	<i>Rj</i>	<i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
62	<i>FU</i>									

DIVD writes in F10

65

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
62	FU									

66

Instruction status:

Instruction status:

				<i>Read</i>	<i>Exec</i>	<i>Write</i>	
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>	
LD	F6	34+	R2	1	2	3	4
LD	F2	45+	R3	5	6	7	8
MULTD	F0	F2	F4	6	9	19	20
SUBD	F8	F6	F2	7	9	11	12
DIVD	F10	F0	F6	8	21	61	62
ADDD	F6	F8	F2	13	14	16	22

Integer: 1cc

Multi: 10cc

Add: 2cc

Divide: 40cc

Functional unit status:

l unit status:

<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>dest</i> <i>Fi</i>	<i>S1</i> <i>Fj</i>	<i>S2</i> <i>Fk</i>	<i>FU</i> <i>Qj</i>	<i>FU</i> <i>Qk</i>	<i>Fj?</i> <i>Rj</i>	<i>Fk?</i> <i>Rk</i>
	Integer	No								
	Mult1	No								
	Mult2	No								
	Add	No								
	Divide	No								

Register result status:

Clock		$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$...	$F30$
62	FU									

67

Integer: 1cc
Multi: 10cc
Add: 2cc
Divide: 40cc

Time Name

	$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$	\dots	$F30$
FU									

68

<i>Instruction status:</i>				<i>Read</i>	<i>Exec</i>	<i>Write</i>
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Oper</i>	<i>Comp</i>	<i>Result</i>
LD	F6	34+	R2	1	3	4
LD	F2	45+	R3	5	7	8
MULTD	F0	F2	F4	6	19	20
SUBD	F8	F6	F2	7	11	12
DIVD	F10	F0	F6	8	61	62
ADDD	F6	F8	F2	13	16	22

Functional unit status:

IN-ORDER ISSUE

OUT-OF-ORDER EXECUTE

QUIT

OUT-OF-ORDER COMMIT

CDC 6600 Scoreboard

- Key idea of Scoreboard: Allow instructions behind stall to proceed (Decode \Rightarrow Issue Instruction & Read Operands)
- Speedup of 2.5 w.r.t. no dynamic scheduling
- Speedup 1.7 by reorganizing instructions from compiler
- BUT slow memory (no cache) limits benefit
- Limitations of 6600 scoreboard:
 - No forwarding hardware
 - Limited to instructions in basic block (small window)
 - Small number of functional units (structural hazards), especially integer/load store units
 - Do not issue on structural hazards
 - Wait for WAR hazards
 - Prevent WAW hazards

Advanced Computer Architectures

(High Performance Processors and Systems)

Dynamic Scheduling: Scoreboard

Politecnico di Milano

v1