

Dipartimento di Elettronica e Informazione

Politecnico di Milano

20133 Milano (Italia) Piazza Leonardo da Vinci, 32 Tel. (+39) 02-2399.3400 Fax (+39) 02-2399.3411

Advanced Computer Architecture

April 06, 2022

Prof. Donatella Sciuto and Marco Santambrogio

Name	
Last Name	
Professor:	

You'll have 15' to complete the exam

Problem 1 (25% aka 1pt)	
Problem 2 (25% aka 1pt)	
Problem 3 (25% aka 1pt)	
Problem 4 (25% aka 1pt)	
Total (100%)	

Which of the following statements about branch prediction are FALSE?

We may have more than a single FALSE statement. Only correct answers will be counted for the score.

Answer 1: The behavior of each branch is always assumed independent from other branches

Answer 2: Branch prediction can only happen at compile time

Answer 3: Different techniques can be combined in order to improve prediction accuracy

Answer 4: Profile-Driven is an example of a static branch predictor

Problem 2

The "Branch Always Taken" technique is not applicable to the fivestage MIPS pipeline! Is this statement true or false?

Problem 3

What is the reason a 1 bit-BHT is usually outperformed by a 2 bit-BHT?

We may have more than a single TRUE statement. Only correct answers will be counted for the score.

Answer 1: A 2-bit BHT leverages more information about the history of a branch

Answer 2: The use of 2 bits allows to index a larger number of branch instructions

Answer 3: The difference in performance is not significant

Answer 4: The use of 2 bits improves the accuracy of the associated BTB

In the context of branch hazards, which of the following assertions are FALSE?

We may have more than a single FALSE statement. Only correct answers will be counted for the score.

Answer 1: The Early Evaluation of PC behaves in the same way regardless of the preceding instructions

Answer 2: The Early Evaluation of PC computes branch target address during the EX phase

Answer 3: With only forwarding and stalling, it requires two clock cycles until the branch decision is taken

Answer 4: The Early Evaluation of PC could need stalls in some particular cases

Which of the following statements about branch prediction are FALSE?

We may have more than a single FALSE statement. Only correct answers will be counted for the score.

Answer 1: The behavior of each branch is always assumed

independent from other branches F THIS IS VALID DNLT FOR

Answer 2: Branch prediction can only happen at compile time THE FIRSTHE SASE OF STATIC BRANCH PROJECTION "NO COUSION" APPROACE!

Answer 3: Different techniques can be combined in order to improve

Answer 4: Profile Priven is an example of a static branch predictor.

Answer 4: Profile-Driven is an example of a static branch predictor 🗸

Problem 2

The "Branch Always Taken" technique is not applicable to the fivestage MIPS pipeline! Is this statement true or false?

Problem 3 SMU NEED TO WAIT FOR OTHER INSTRUCTIONS OUTCOME

What is the reason a 1 bit-BHT is usually outperformed by a 2 bit-BHT?

We may have more than a single TRUE statement. Only correct answers will be counted for the score.

Answer 1: A 2-bit BHT leverages more information about the history of a branch

Answer 2: The use of 2 bits allows to index a larger number of branch instructions X

Answer 3: The difference in performance is not significant

✓

Answer 4: The use of 2 bits improves the accuracy of the associated BTB X

In the context of branch hazards, which of the following assertions are FALSE?

We may have more than a single FALSE statement. Only correct answers will be counted for the score.

Answer 1: The Early Evaluation of PC behaves in the same way regardless of the preceding instructions

Answer 2: The Early Evaluation of PC computes branch target address during the EX phase * DURING D

Answer 3: With only forwarding and stalling, it requires two clock cycles until the branch decision is taken ✓

Answer 4: The Early Evaluation of PC could need stalls in some particular cases