



UNIVERSITY OF GHANA
(All rights reserved)

BSc. ENGINEERING FIRST SEMESTER EXAMINATIONS: 2016/2017
SCHOOL OF ENGINEERING SCIENCES
FAEN 203: STRENGTH OF MATERIALS (3 CREDITS)

INSTRUCTIONS:
ANSWER ALL QUESTIONS
TIME ALLOWED: TWO (2) HOURS

1. (a) Differentiate between the following:
 - (i) Flexibility and Ductility.
 - (ii) Yield strength and Ultimate strength.(b) (i) Outline two importance each of flexibility and ductility in engineering design.
 - (ii) Elaborate on three factors that can affect the yield strength of a material.

[13 marks]
2. (a) Determine the maximum deflection, y in the simply supported beam in Figure 1 of span length, L carrying a concentrated load, P at mid-span. [Hint: Use double integration method].

[20 marks]




Figure 1: A beam undergoing bending under applied load, P .

- (b) Table 1 are values of load and deflection obtained from a steel strip (length = 0.15 m, width = 0.01 m and height = 0.001 m) that underwent bending similar to that illustrated in Figure 1. Determine the Young's modulus of the strip by using the values in table 1. [15 marks]

Table 1. Load and Deflection values for a steel strip during bending

Load / kg	Deflection, $y / 10^{-3}$ m
0.00	0.0
0.05	3.0
0.10	6.5
0.15	9.0
0.20	13.0
0.25	16.0

3. (a) A vertical load, $P = 2100$ N is supported by two inclined steel wires AC and BC as shown in Figure 2. Determine the required cross-sectional area, A of each wire if the allowable working stress in tension is 700 Nm^{-2} . Given, $\theta = 30^\circ$, $E = 2.0 \times 10^6 \text{ Pa}$ and $AB = 10$ m. Also calculate the vertical deflection of the point C. [15 marks]




Figure 2: A vertical load supported by two inclined steel wires AC and BC.

- (b) A solid shaft 6 m long is subjected to a torque of 12 kNm, if the angle of twist is 3° and rigidity modulus, G is 83 GPa. Calculate the minimum diameter of the shaft. [10 marks]

4. (a) Show that the strain energy density, U of a ductile material under tensile principal stresses, σ_1 , σ_2 and σ_3 is given by

$$U = \frac{1}{2E} [\sigma_1^2 + \sigma_2^2 + \sigma_3^2 - 2\nu(\sigma_1\sigma_2 + \sigma_2\sigma_3 + \sigma_3\sigma_1)] \quad [10 \text{ marks}]$$