



To-Do List

Total tasks: 2

- drink water
- hello world

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width,initial-scale=1.0">
  <title>Advanced To-Do List</title>
  <style>
    li { padding: 6px; transition: background 0.3s; }
    li:hover { background: #f0f0f0; }
    .completed span { text-decoration: line-through; color: gray; }
    button { margin-left: 5px; }
    #controls { margin-top: 10px; }
  </style>
</head>
<body>
  <h2>To-Do List</h2>
  <input type="text" id="taskInput" placeholder="Enter a task">
  <button onclick="addTask()" ">Add</button>
```

```

<div id="controls">
  <button onclick="sortTasks(true)">Sort A-Z</button>
  <button onclick="sortTasks(false)">Sort Z-A</button>
</div>
<p>Total tasks: <span id="taskCount">0</span></p>
<ul id="todoList"></ul>

<script>
  const input = document.getElementById('taskInput');
  const todoList = document.getElementById('todoList');
  const taskCount = document.getElementById('taskCount');

  // Load tasks from localStorage
  window.onload = () => {
    const saved = JSON.parse(localStorage.getItem('tasks')) || [];
    saved.forEach(t => createTaskElement(t.text, t.completed));
    updateCount();
  };

  // Add task on Enter
  input.addEventListener('keypress', e => { if (e.key === 'Enter')
addTask(); });

function addTask() {
  const taskText = input.value.trim();
  if (!taskText) return;

  // Check duplicates
  const existing = [...todoList.querySelectorAll('li span')]
    .some(span => span.textContent === taskText);
  if (existing) { alert('Task already exists!'); return; }

  createTaskElement(taskText);
  input.value = '';
  saveTasks();
  updateCount();
}

function createTaskElement(text, completed=false) {
  const li = document.createElement('li');
  if (completed) li.classList.add('completed');

  const span = document.createElement('span');

```

```

span.textContent = text;

// Complete toggle
const completeBtn = document.createElement('button');
completeBtn.textContent = 'Complete';
completeBtn.onclick = () => {
  li.classList.toggle('completed');
  saveTasks();
};

// Inline edit
const editBtn = document.createElement('button');
editBtn.textContent = 'Edit';
editBtn.onclick = () => {
  // Create input for inline edit
  const editInput = document.createElement('input');
  editInput.type = 'text';
  editInput.value = span.textContent;
  li.insertBefore(editInput, span);
  li.removeChild(span);
  editBtn.disabled = true;

  editInput.addEventListener('keypress', e => {
    if (e.key === 'Enter') finishEdit();
  });
  editInput.addEventListener('blur', finishEdit);

  function finishEdit() {
    const newText = editInput.value.trim();
    if (!newText) { alert('Task cannot be empty'); return; }

    // Check duplicates excluding this one
    const duplicate = [...todoList.querySelectorAll('li span')]
      .some(s => s.textContent === newText);
    if (duplicate) { alert('Task already exists!'); return; }

    span.textContent = newText;
    li.insertBefore(span, editInput);
    li.removeChild(editInput);
    editBtn.disabled = false;
    saveTasks();
  }

  editInput.focus();

```

```

};

// Delete with confirm
const deleteBtn = document.createElement('button');
deleteBtn.textContent = 'Delete';
deleteBtn.onclick = () => {
    if (confirm('Delete this task?')) {
        li.remove();
        saveTasks();
        updateCount();
    }
};

li.appendChild(span);
li.appendChild(completeBtn);
li.appendChild(editBtn);
li.appendChild(deleteBtn);
todoList.appendChild(li);
}

function updateCount() {
    taskCount.textContent = todoList.querySelectorAll('li').length;
}

function saveTasks() {
    const tasks = [...todoList.querySelectorAll('li')].map(li => ({
        text: li.querySelector('span').textContent,
        completed: li.classList.contains('completed')
    }));
    localStorage.setItem('tasks', JSON.stringify(tasks));
    updateCount();
}

function sortTasks(ascending=true) {
    const tasks = [...todoList.querySelectorAll('li')];
    tasks.sort((a,b) => {
        const textA =
a.querySelector('span').textContent.toLowerCase();
        const textB =
b.querySelector('span').textContent.toLowerCase();
        return ascending ? textA.localeCompare(textB) :
textB.localeCompare(textA);
    });
}

```

```
    tasks.forEach(li => todoList.appendChild(li));  
    saveTasks();  
  }  
</script>  
</body>  
</html>
```