



# SMD Aluminum Electrolytic Capacitors

VE

## Features

- 3 ~ 18  $\phi$ , 85°C, 2,000 hours assured
- Chip type large capacitance capacitors
- Designed for surface mounting on high density PC board
- RoHS Compliance



Marking color: Black

## SPECIFICATIONS

Items	Performance												
Category Temperature Range	-40℃ ~ +85℃												
Capacitance Tolerance	±20% (at 120Hz, 20℃)												
Leakage Current (at 20℃)	Rated Voltage		6.3 ~ 100V								160 ~ 450V		
	Time		after 2 minutes								after 5 minutes		
	Case size		3 ~ 10 ϕ				12.5 ~ 18 ϕ				12.5 ~ 18 ϕ		
	Leakage Current		I = 0.01CV or 3μA, whichever is greater				I = 0.03CV or 4μA, whichever is greater				I = 0.04CV +100μA		
Where, C = rated capacitance in μF      V = rated DC working voltage in V													
Dissipation Factor (Tan δ at 120Hz, 20℃)	Rated Voltage	4	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450	
	3 ~ 10 ϕ	0.42	0.28	0.24	0.20	0.14	0.12	0.10	0.10	0.10	-	-	
	12.5 ~ 16 ϕ	-	0.38	0.34	0.30	0.26	0.22	0.18	0.14	0.10	0.20	0.25	
When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.													
Low Temperature Characteristics (at 120Hz)	Impedance ratio shall not exceed the values given in the table below.												
	Rated Voltage		4.0	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450
	Impedance Ratio	Z(-25℃)	ϕ D < 12.5	7	4	4	3	2	2	2	2	-	-
		/Z(+20℃)	ϕ D ≥ 12.5	-	5	5	4	2	2	2	2	3	6
		Z(-40℃)	ϕ D < 12.5	15	8	5	4	3	3	3	3	-	-
		/Z(+20℃)	ϕ D ≥ 12.5	-	14	12	10	5	4	3	3	6	10
Endurance	Test Time		2,000 Hrs										
	Capacitance Change		Within ±20% of initial value (4V: ±30%)										
	Dissipation Factor		Less than 200% of specified value (4V: ±300%)										
	Leakage Current		Within specified value										
* The above specifications shall be satisfied when the capacitors are restored to 20℃ after the rated voltage applied for 2,000 hours at 85℃.													
Shelf Life Test	Test time: 1,000 hours; other items are the same as those for the Endurance. The rated voltage shall be applied to the capacitors before the measurements for 160 ~ 450V (Refer to JIS C 5101-4 4.1).												
Ripple Current & Frequency Multipliers	Freq. (Hz)		50				120		1k		10k up		
	Cap. ( μ F)		Under 1,000				0.80		1.00		1.40		
	1,000 < C ≤ 4,700		0.85				1.00		1.15		1.25		

## DIAGRAM OF DIMENSIONS

Fig. 1





Fig. 2



## LEAD SPACING AND DIAMETER

Unit: mm

$\phi D$	L	A	B	C	W	P $\pm 0.2$	Fig. No.
3	5.3 $\pm$ 0.2	3.3	3.3	4.1	0.45 ~ 0.75	0.8	1
4	5.3 $\pm$ 0.2	4.3	4.3	5.1	0.5 ~ 0.8	1.0	1
5	5.3 $\pm$ 0.2	5.3	5.3	6.1	0.5 ~ 0.8	1.5	1
6.3	5.3 $\pm$ 0.2	6.6	6.6	7.4	0.5 ~ 0.8	2.0	1
6.3	7.7 $\pm$ 0.3	6.6	6.6	7.4	0.5 ~ 0.8	2.0	1
8	10 $\pm$ 0.5	8.4	8.4	9.2	0.7 ~ 1.1	3.1	1
8	10.3 $\pm$ 0.5	8.4	8.4	9.2	0.7 ~ 1.1	3.1	1
10	7.7 $\pm$ 0.3	10.4	10.4	11.2	0.7 ~ 1.1	4.7	1
10	10 $\pm$ 0.5	10.4	10.4	11.2	0.7 ~ 1.1	4.7	1
10	10.3 $\pm$ 0.5	10.4	10.4	11.2	0.7 ~ 1.1	4.7	1
12.5	13.5 $\pm$ 0.5	13.0	13.0	15.0	1.1 ~ 1.4	4.4	2
12.5	16 $\pm$ 0.5	13.0	13.0	15.0	1.1 ~ 1.4	4.4	2
16	16.5 $\pm$ 0.5	17.0	17.0	19.0	1.1 ~ 1.4	6.4	2
18	16.5 $\pm$ 0.5	19.0	19.0	21.0	1.1 ~ 1.4	6.4	2




# SMD Aluminum Electrolytic Capacitors


VE

## MARKING


$\phi D = 3 \text{ mm}$




$\phi D = 4 \sim 6.3 \text{ mm}$



$\phi D = 8 \sim 10 \text{ mm}$



$\phi D \geq 12.5 \text{ mm}$



Dimension:  $\phi D \times L(\text{mm})$

## DIMENSION & PERMISSIBLE RIPPLE CURRENT

Ripple Current: mA/rms at 120 Hz, 85°C

V. DC		4V (0G)		6.3V (0J)		10V (1A)		16V (1C)		25V (1E)		35V (1V)		50V (1H)		63 (1J)	
$\mu\text{F}$	Contents	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA
0.1	0R1													4x5.3	3	4x5.3	2
0.22	R22													4x5.3	5	4x5.3	3
0.33	R33													4x5.3	6	4x5.3	4
0.47	R47													4x5.3	7	4x5.3	5
1	010													4x5.3	10	4x5.3	8
2.2	2R2													4x5.3	14	4x5.3	12
3.3	3R3									3x5.3	14	3x5.3	14	4x5.3	17	5x5.3	22
4.7	4R7					3x5.3	14	3x5.3	14	4x5.3	26	4x5.3	26	4x5.3	20	5x5.3	25
10	100			3x5.3	16	4x5.3	26	4x5.3	26	5x5.3	44	5x5.3	44	5x5.3	35	6.3x5.3	40
22	220	3x5.3	16	4x5.3	26	5x5.3	44	4x5.3	30	5x5.3	47	5x5.3	47	6.3x5.3	50	8x10	139
33	330	4x5.3	31	4x5.3	31	4x5.3	31	5x5.3	55	5x5.3	55	6.3x5.3	67	6.3x7.7	75	8x10	139
47	470	4x5.3	34	4x5.3	34	5x5.3	55	5x5.3	55	6.3x5.3	75	6.3x7.7	98	6.3x7.7	75	10x10	200
68	680	5x5.3	58	5x5.3	58	5x5.3	58	6.3x5.3	89	6.3x7.7	109	6.3x7.7	109	8x10	190	10x10	226
100	101	5x5.3	58	6.3x5.3	89	6.3x5.3	89	6.3x5.3	89	6.3x7.7	109	8x10	252	8x10	190	10x10	226
150	151											10x7.7	252				
220	221	6.3x5.3	89	6.3x5.3	89	6.3x7.7	124	6.3x7.7	124	8x10	270	8x10	270	10x10	320	12.5x13.5	500
330	331	6.3x7.7	124	6.3x7.7	124	8x10	290	8x10	290	10x10	400	10x10.3	400	12.5x13.5	600	12.5x16	600
470	471	8x10	290	8x10	290	10x7.7	400	10x10	400	10x10	400	12.5x13.5	750	12.5x16	740	16x16.5	850
680	681			10x7.7	290	10x10	410	10x10	410	12.5x13.5	680	12.5x13.5	680	16x16.5	1,000	18x16.5	1,100
1,000	102			10x10	430	10x10	430	12.5x13.5	750	12.5x13.5	750	16x16.5	1,100	18x16.5	1,350		
2,200	222			12.5x13.5	890	12.5x13.5	890	16x16.5	1,100	16x16.5	1,100	18x16.5	1,450				
3,300	332			12.5x16	1,000	16x16.5	1,300	16x16.5	1,300	18x16.5	1,450						
4,700	472			16x16.5	1,400	16x16.5	1,400	18x16.5	1,600								
6,800	682			18x16.5	1,700	18x16.5	1,700										

V. DC		100V (2A)		160V (2C)		200V (2D)		250V (2E)		400V (2G)		450V (2W)	
$\mu\text{F}$	Contents	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA
4.7	4R7									12.5x13.5	120	12.5x13.5	120
10	100	8x10	90					12.5x13.5	150	12.5x13.5	120	12.5x16	130
22	220	8x10	90			12.5x13.5	240	12.5x13.5	150	16x16.5	140	16x16.5	140
33	330	10x10	120	12.5x13.5	290	12.5x16	310	12.5x16	240	16x16.5	140	18x16.5	180
47	470	10x10	120	12.5x16	370	16x16.5	420	16x16.5	340	18x16.5	280		
68	680	12.5x13.5	380	16x16.5	500	16x16.5	420	18x16.5	440				
100	101	12.5x13.5	440	18x16.5	650	18x16.5	550						
220	221	16x16.5	600										
330	331	18x16.5	780										