

Data Mining: Concepts and Techniques

(3rd ed.)

— Chapter 10 —

Jiawei Han, Micheline Kamber, and Jian Pei

1

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

2

What is Cluster Analysis?

- Cluster: A collection of data objects
 - Similar (or related) to one another within the same group
 - Dissimilar (or unrelated) to the objects in other groups
- Cluster analysis (or *clustering*, *data segmentation*, ...)
- Finding similarities between data according to the characteristics found in the data and grouping similar data objects into clusters
- **Unsupervised learning**: NO predefined classes (i.e., learning by *observations* vs. learning by *examples*: supervised)
- Typical applications
 - As a **stand-alone tool** to get insight into data distribution
 - As a **preprocessing step** for other algorithms

3

Clustering for Data Understanding and Applications

- Biology: taxonomy of living things: kingdom, phylum, class, order, family, genus and species (界.门.纲.目.科.属.种)
- Information retrieval: document clustering
- Land use: Identification of areas of similar land use in an observation database
- Marketing: Help marketers discover groups of customers, and then use targeted programs
- City-planning: Identify different types of areas, and then use the information to plan the type, value, and location of services and facilities
- Earth-quake studies: clustered along different lines
- Climate: understanding different types of climate regions, and ocean movement
- Economic Science: m



4

Clustering as a Preprocessing Tool (Utility)

- Summarization:
 - Preprocessing for regression, PCA (why?), classification, and association analysis
- Compression:
 - Image processing: vector quantization
- **Finding K-nearest Neighbors**
 - *Localizing search* to one or a small number of clusters
- Outlier detection
 - Outliers are often viewed as those "far away" from any cluster



5

Quality: What Is Good Clustering?

- A good clustering method will produce high quality clusters
 - high intra-class similarity: **cohesive** within clusters
 - low inter-class similarity: **distinctive** between clusters
- The quality of a clustering method depends on
 - the *similarity measure* used by the method
 - its implementation, and
 - Its ability to discover some or all of the hidden patterns

6

Measure the Quality of Clustering

- **Dissimilarity/Similarity metric**
 - Similarity is expressed in terms of a distance function, typically metric: $d(i, j)$
 - The definitions of **distance functions** are usually rather **different** for interval-scaled, boolean, categorical, ordinal ratio, and vector variables
 - **Weights** should be associated with **different variables** based on applications and data sets
- **Quality of clustering:**
 - There is usually a **separate** "quality" measures the "goodness" of a clustering
 - It is hard to define "similar enough" or "good enough"
 - The answer is typically highly subjective



7

Considerations for Cluster Analysis

- **Partitioning criteria**
 - Single level vs. hierarchical partitioning (often, multi-level hierarchical partitioning is desirable)
- **Separation of clusters**
 - Exclusive (e.g., one customer belongs to only one region) vs. non-exclusive (e.g., one document may belong to more than one class) a.k.a. **multi-label** clustering (e.g., *community detection*)
- **Similarity measure**
 - **Distance-based** (e.g., Euclidian, road network, vector) vs. **connectivity-based** (e.g., density or contiguity)
- **Clustering space**
 - Full space (often when low dimensional) vs. *subspaces* (often in high-dimensional clustering)



8

Requirements and Challenges

- **Scalability**
 - Clustering all the data instead of only on some samples
- **Ability to deal with different types of attributes**
 - Numerical, binary, categorical, ordinal, linked, and mixture of these
- **Constraint-based clustering**
 - User may give inputs on constraints
 - Use domain knowledge to determine input **parameters**
- **Interpretability and usability**
- **Others**
 - Discovery of clusters with **arbitrary shapes** (e.g., Swiss swirl)
 - Ability to deal with noisy data
 - **Incremental clustering** and **insensitivity to input order**
 - High dimensionality



9

Major Clustering Approaches (I)

- **Partitioning approach:**
 - Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
 - Typical methods: k-means, k-medoids (PAM), CLARA
- **Hierarchical approach:**
 - Create a hierarchical decomposition of the set of data (or objects) using some criterion
 - Typical methods: Diana, Agnes, BIRCH, CAMELEON
- **Density-based approach:**
 - Based on connectivity and density functions
 - Typical methods: DBSCAN, OPTICS, DenClue, *GraphCut*
- **Grid-based approach:**
 - Based on a multiple-level granularity structure
 - Typical methods: STING, WaveCluster, CLIQUE

10

Major Clustering Approaches (II)

- **Model-based:**
 - A model is hypothesized for each of the clusters and tries to find the best fit of that model to each other
 - Typical methods: EM, SOM, COBWEB
- **Frequent pattern-based:**
 - Based on the analysis of frequent patterns
 - Typical methods: p-Cluster
- **User-guided or constraint-based:**
 - Clustering by considering user-specified or application-specific constraints
 - Typical methods: COD (obstacles), *constrained clustering*
- **Link-based clustering:**
 - Objects are often linked together in various ways
 - Massive links can be used to cluster objects: **SimRank**, **LinkClus**

11

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

12

Partitioning Algorithms: Basic Concept

- **Partitioning method:** Partitioning a database D of n objects into a set of k clusters, such that the sum of squared distances is minimized (where c_i is the centroid or medoid of cluster C_i)

$$E = \sum_{i=1}^k \sum_{p \in C_i} (p - c_i)^2$$

- Given k , find a partition of k clusters that optimizes the chosen partitioning criterion
 - Global optimal: exhaustively enumerate all partitions
 - Heuristic methods: k -means and k -medoids algorithms
 - k -means (MacQueen'67, Lloyd'57/82): Each cluster is represented by the center of the cluster
 - k -medoids or PAM (Partition Around Medoids) (Kaufman & Rousseeuw'87): Each cluster is represented by one of the objects in the cluster


13

The K -Means Clustering Method

- Given k , the k -means algorithm is implemented in four steps:
 - Partition objects into k nonempty subsets
 - Compute seed points as the centroids of the clusters of the current partitioning (the centroid is the center, i.e., **mean point**, of the cluster)
 - Assign each object to the cluster with the nearest seed point
 - Go back to Step 2, stop when the assignment does not change

14

An Example of K -Means Clustering



15

Comments on the K -Means Method


- **Strength:** *Efficient:* $O(tkn)$, where n is # objects, k is # clusters, and t is # iterations. Normally, $k, t \ll n$.
 - Comparing: PAM: $O(k(n-k)^2)$, CLARA: $O(ks^2 + k(n-k))$
- **Comment:** Often terminates at a *local optimum*. (initialization can matter!)
- **Weakness**
 - Applicable only to objects in a continuous n -dimensional space
 - Using the k -modes method for *categorical* data
 - In comparison, k -medoids can be applied to a *wider range* of data
 - Need to specify k , the *number* of clusters, **in advance** (there are ways to automatically determine the best k (see Hastie et al., 2009))
 - Sensitive to noisy data and *outliers*
 - Not suitable to discover clusters with *non-convex shapes*



16

Variations of the K -Means Method


- Most of the variants of the k -means which **differ** in
 - Selection of the initial k means
 - Dissimilarity calculations
 - **Strategies to calculate cluster means**
- Handling categorical data: k -modes
 - Replacing means of clusters with **modes** (most popular value)
 - Using new dissimilarity measures to deal with categorical objects
 - Using a **frequency**-based method to update modes of clusters
 - A mixture of categorical and numerical data: k -prototype method




17

What Is the Problem of the K -Means Method?

- The k -means algorithm is sensitive to outliers!
 - Since an object with an extremely large value may substantially distort the distribution of the data (thus the mean calculation)
- K -Medoids: Instead of taking the **mean** value of the object in a cluster as a reference point, **medoids** can be used, which is the **most centrally located** object in a cluster



18



19

The K-Medoid Clustering Method

- *K-Medoids* Clustering: Find *representative* objects (**medoids**) in clusters
 - **PAM** (Partitioning Around Medoids, Kaufmann & Rousseeuw 1987)
 - Starts from an initial set of medoids and iteratively replaces one of the medoids by one of the non-medoids if it improves the total distance of the resulting clustering
 - **PAM** works effectively for small data sets, but does not scale well for large data sets (due to the computational complexity)
 - Efficiency improvement on PAM
 - **CLARA** (Kaufmann & Rousseeuw, 1990): PAM on *samples*
 - **CLARANS** (Ng & Han, 1994): *Randomized re-sampling*

20

20

Do They All Look the Same?

- <http://www.vista-today.com/asianmyth>
- <http://asianlookalikes.com/>

21

21


Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

HW1-3 Graded before midterm

22

22



23

AGNES (Agglomerative Nesting)

- Introduced in Kaufmann and Rousseeuw (1990)
- Implemented in statistical packages, e.g., Splus
- Use the **single-link** method and the dissimilarity matrix
- Merge nodes that have the least dissimilarity
- Go on in a non-descending fashion
- Eventually all nodes belong to the same cluster


24

24

Dendrogram: Shows How Clusters are Merged

Decompose data objects into several levels of nested partitioning (tree of clusters), called a dendrogram


A clustering of the data objects is obtained by cutting the dendrogram at the desired level, then each connected component forms a cluster



25

DIANA (Divisive Analysis)

- Introduced in Kaufmann and Rousseeuw (1990)
- Implemented in statistical analysis packages, e.g., Splus
- Inverse order of AGNES
- Eventually each node forms a cluster on its own



26

Distance between Clusters



- **Single link:** smallest distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \min(t_{ip}, t_{jq})$
- **Complete link:** largest distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \max(t_{ip}, t_{jq})$
- **Average:** avg distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \text{avg}(t_{ip}, t_{jq})$
- **Centroid:** distance between the centroids of two clusters, i.e., $\text{dist}(K_i, K_j) = \text{dist}(C_i, C_j)$
- **Medoid:** distance between the medoids of two clusters, i.e., $\text{dist}(K_i, K_j) = \text{dist}(M_i, M_j)$
 - Medoid: a chosen, centrally located object in the cluster

27

Centroid, Radius and Diameter of a Cluster (for numerical data sets)

- **Centroid:** the "middle" of a cluster
$$C_m = \frac{\sum_{i=1}^N t_{ip}}{N}$$
- **Radius:** square root of average distance from any point of the cluster to its **centroid**
$$R_m = \sqrt{\frac{\sum_{i=1}^N (t_{ip} - c_m)^2}{N}}$$
- **Diameter:** square root of average mean squared distance between all **pairs** of points in the cluster

$$D_m = \sqrt{\frac{\sum_{i=1}^N \sum_{j=1}^N (t_{ip} - t_{jq})^2}{N(N-1)}}$$

28

Extensions to Hierarchical Clustering

- Major weakness of agglomerative clustering methods
 - Can never undo what was done previously
 - Do not scale well: time complexity of at least $O(n^2)$, where n is the number of total objects
- Integration of hierarchical & distance-based clustering
 - **BIRCH (1996):** uses CF-tree and incrementally adjusts the quality of sub-clusters
 - **CHAMELEON (1999):** hierarchical clustering using dynamic modeling

29

BIRCH (Balanced Iterative Reducing and Clustering Using Hierarchies)

- Zhang, Ramakrishnan & Livny, SIGMOD'96
- Incrementally construct a CF (Clustering Feature) tree, a hierarchical data structure for multiphase clustering
 - Phase 1: scan DB to build an initial in-memory CF tree (a multi-level compression of the data that tries to preserve the inherent clustering structure of the data)
 - Phase 2: use an **arbitrary** clustering algorithm to cluster the leaf nodes of the CF-tree
- **Scales linearly:** finds a good clustering with a single scan and improves the quality with a few additional scans
- **Weakness:** handles only numeric data, and sensitive to the order of the data record

SKIP>>>

30

Clustering Feature Vector in BIRCH


Clustering Feature (CF): $CF = (N, LS, SS)$

N : Number of data points

LS : linear sum of N points: $\sum_{i=1}^N X_i$

SS : square sum of N points

$$\sum_{i=1}^N X_i^2$$



$CF = (5, (16,30), (54,190))$

(3,4)
(2,6)
(4,5)
(4,7)
(3,8)

31

CF-Tree in BIRCH

Clustering feature:

- Summary of the statistics for a given subcluster: the 0-th, 1st, and 2nd moments of the subcluster from the statistical point of view
- Registers crucial measurements for computing cluster and utilizes storage efficiently

A CF tree is a height-balanced tree that stores the clustering features for a hierarchical clustering


- A nonleaf node in a tree has descendants or "children"
- The nonleaf nodes store **sums** of the CFs of their children

A CF tree has two parameters

- Branching factor: max # of children
- Threshold: max diameter of sub-clusters stored at the leaf nodes

32

The CF Tree Structure



33

The Birch Algorithm

Cluster Diameter

$$\sqrt{\frac{1}{n(n-1)} \sum (x_i - x_j)^2}$$

For each point in the input

- Find closest leaf entry
- Add point to leaf entry and update CF
- If entry diameter > max_diameter, then split leaf, and possibly parents

Algorithm is O(n)

Concerns

- Sensitive to insertion order of data points
- Since we fix the size of leaf nodes, so clusters may not be so natural
- Clusters tend to be spherical given the radius and diameter measures


34

CHAMELEON: Hierarchical Clustering Using Dynamic Modeling (1999)

- CHAMELEON: G. Karypis, E. H. Han, and V. Kumar, 1999
- Measures the similarity based on a *dynamic* model
 - Two clusters are merged only if the *interconnectivity* and *closeness (proximity)* between two clusters are high *relative* to the internal interconnectivity of the clusters and closeness of items within the clusters
- Graph-based**, and a two-phase algorithm
 - Use a graph-partitioning algorithm: cluster objects into a large number of relatively small sub-clusters
 - Use an agglomerative hierarchical clustering algorithm: find the genuine clusters by repeatedly combining these sub-clusters


35

Overall Framework of CHAMELEON



36

CHAMELEON (Clustering Complex Objects)



37

37

Probabilistic Hierarchical Clustering

- Algorithmic hierarchical clustering
 - Nontrivial to choose a good distance measure
 - Hard to handle missing attribute values
 - Optimization goal not clear: *heuristic, local search*
- Probabilistic hierarchical clustering
 - Use probabilistic models to measure distances between clusters
 - Generative model: Regard the set of data objects to be clustered as a sample of the underlying data generation mechanism to be analyzed
 - Easy to understand, same efficiency as algorithmic agglomerative clustering method, can handle partially observed data
- In practice, assume the generative models adopt common distributions functions, e.g., Gaussian distribution or Bernoulli distribution, governed by parameters

38

38

Generative Model

- Given a set of 1-D points $X = \{x_1, \dots, x_n\}$ for clustering analysis & assuming they are generated by a Gaussian distribution:

$$\mathcal{N}(\mu, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$
- The probability that a point $x_i \in X$ is generated by the model

$$P(x_i | \mu, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x_i - \mu)^2}{2\sigma^2}}$$
- The likelihood that X is generated by the model:

$$L(\mathcal{N}(\mu, \sigma^2) : X) = P(X | \mu, \sigma^2) = \prod_{i=1}^n \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x_i - \mu)^2}{2\sigma^2}}$$
 i.i.d.
- The task of learning the generative model: find the parameters μ and σ^2 such that **the maximum likelihood**

$$\mathcal{N}(\mu_0, \sigma_0^2) = \arg \max \{ L(\mathcal{N}(\mu, \sigma^2) : X) \}$$

39

39

A Probabilistic Hierarchical Clustering Algorithm

- For a set of objects partitioned into m clusters C_1, \dots, C_m , the quality can be measured by,

$$Q(\{C_1, \dots, C_m\}) = \prod_{i=1}^m P(C_i)$$
 where $P()$ is the maximum likelihood
- Distance** between clusters C_i and C_j : $dist(C_i, C_j) = -\log \frac{P(C_i \cup C_j)}{P(C_i)P(C_j)}$
- Algorithm: Progressively merge points and clusters

Input: $D = \{o_1, \dots, o_n\}$: a data set containing n objects

Output: A hierarchy of clusters

Method

Create a cluster for *each* object $C_i = \{o_i\}$, $1 \leq i \leq n$;

For $i = 1$ to n {

Find pair of clusters C_i and C_j such that

$C_i, C_j = \arg \max_{i \neq j} \{ \log (P(C_i \cup C_j) / (P(C_i)P(C_j))) \}$;

If $\log (P(C_i \cup C_j) / (P(C_i)P(C_j))) > 0$ then merge C_i and C_j }

40

40

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

41

41

Density-Based Clustering Methods


- Clustering based on density (local cluster criterion), such as density-connected points
- Major features:
 - Discover clusters of *arbitrary shape*
 - Handle noise
 - One scan
 - Need density parameters as termination condition
- Several interesting studies:
 - DBSCAN**: Ester, et al. (KDD'96)
 - OPTICS**: Ankerst, et al (SIGMOD'99).
 - DENCLUE**: Hinneburg & D. Keim (KDD'98)
 - CLIQUE**: Agrawal, et al. (SIGMOD'98) (more grid-based)

42

42

Density-Based Clustering: Basic Concepts


- Two parameters:
 - Eps**: Maximum radius of the neighbourhood
 - MinPts**: Minimum number of points in an Eps-neighbourhood of that point
- $N_{Eps}(p)$: $\{q \text{ belongs to } D \mid \text{dist}(p,q) \leq Eps\}$
- Directly density-reachable**: A point p is directly density-reachable from a point q w.r.t. Eps , $MinPts$ if
 - p belongs to $N_{Eps}(q)$
 - core point condition**: $|N_{Eps}(q)| \geq MinPts$



43

Density-Reachable and Density-Connected


- Density-reachable:
 - A point p is **density-reachable** from a point q w.r.t. Eps , $MinPts$ if there is a chain of points p_1, \dots, p_m $p_1 = q$, $p_n = p$ such that p_{i+1} is directly density-reachable from p_i
- Density-connected
 - A point p is **density-connected** to a point q w.r.t. Eps , $MinPts$ if there is a point o such that both, p and q are density-reachable from o w.r.t. Eps and $MinPts$



44

DBSCAN: Density-Based Spatial Clustering of Applications with Noise

- Relies on a *density-based* notion of cluster: A *cluster* is defined as a maximal set of density-connected points
- Discovers clusters of arbitrary shape in spatial databases with noise




45

DBSCAN: The Algorithm

- Arbitrary select a point p
- Retrieve all points (directly*) density-reachable from p w.r.t. Eps and $MinPts$
- If p is a core point, a cluster is formed
- If p is a border point*, (or) no points are density-reachable from p and DBSCAN visits the next point of the database
- Continue the process until all of the points have been processed

46

DBSCAN: Sensitive to Parameters



47

OPTICS: A Cluster-Ordering Method (1999)

- OPTICS: Ordering Points To Identify the Clustering Structure
 - Ankerst, Breunig, Kriegel, and Sander (SIGMOD'99)
 - Produces a special order of the database wrt its density-based clustering structure
 - This cluster-ordering contains info equiv. to the density-based clusterings corresponding to a broad range of parameter settings (s.t. insensitive to parameters)
 - Good for both automatic and interactive cluster analysis, including finding intrinsic clustering structure
 - Can be represented graphically or using visualization techniques

48

OPTICS: Some Extension from DBSCAN

Index-based:

- k = number of dimensions
- $N = 20$
- $p = 75\%$
- $M = N(1-p) = 5$

Complexity: $O(N \log N)$


Core Distance:

- min eps s.t. point is core


Reachability Distance

Max (core-distance (o), $d(o, p)$)

$r(p1, o) = 2.8\text{cm}$, $r(p2, o) = 4\text{cm}$




49



50

Density-Based Clustering: OPTICS & Its Applications



51

DENCLUE: Using Statistical Density Functions

- DENsity-based CLUstEring by Hinneburg & Keim (KDD'98)
- Using statistical density functions:

$$f_{\text{Gaussian}}(x, y) = e^{-\frac{d(x, y)^2}{2\sigma^2}}$$

influence of y on x

$$f_{\text{Gaussian}}^D(x) = \sum_{i=1}^N e^{-\frac{d(x, x_i)^2}{2\sigma^2}}$$

total influence on x

$$\nabla f_{\text{Gaussian}}^D(x, x_i) = \sum_{i=1}^N (x_i - x) \cdot e^{-\frac{d(x, x_i)^2}{2\sigma^2}}$$

gradient of x in the direction of x_i

Major features

- Solid mathematical foundation
- Good for data sets with large amounts of noise
- Allows a compact mathematical description of arbitrarily shaped clusters in high-dimensional data sets (i.e., mixture of Gaussian)
- Significantly faster than existing algorithm (e.g., DBSCAN)
- But needs a large number of parameters

52


Denclue: Technical Essence

- Uses grid cells but only keeps information about grid cells that do actually contain data points and manages these cells in a tree-based access structure
- Influence function: describes the impact of a data point within its neighborhood
- Overall density of the data space can be calculated as the sum of the influence function of all data points
- Clusters can be determined mathematically by identifying density attractors
- Density attractors are local maximal of the overall density function
- Center defined clusters: assign to each density attractor the points density attracted to it
- Arbitrarily shaped cluster: merge density attractors that are connected through paths of high density ($>$ threshold)

53


53

Density Attractor



54

Center-Defined and Arbitrary



55

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

56


Grid-Based Clustering Method

- Using multi-resolution grid data structure
- Several interesting methods
 - **STING** (a Statistical Information Grid approach) by Wang, Yang and Muntz (1997)
 - **WaveCluster** by Sheikholeslami, Chatterjee, and Zhang (VLDB'98)
 - A *multi-resolution* clustering approach using *wavelet* method
 - **CLIQUE**: Agrawal, et al. (SIGMOD'98)
 - Both grid-based and subspace clustering

57

STING: A Statistical Information Grid Approach

- Wang, Yang and Muntz (VLDB'97)
- The spatial area is divided into rectangular cells
- There are several levels of cells corresponding to different levels of resolution



58

The STING Clustering Method

- Each cell at a high level is partitioned into a number of smaller cells in the next lower level
- Statistical info of each cell is calculated and stored beforehand and is used to answer queries
- Parameters of higher level cells can be easily calculated from parameters of lower level cell
 - *count, mean, s, min, max*
 - type of distribution—*normal, uniform*, etc.
- Use a top-down approach to answer spatial data queries
- Start from a pre-selected layer—typically with a small number of cells
- For each cell in the current level compute the confidence interval

59

STING Algorithm and Its Analysis

- Remove the irrelevant cells from further consideration
- When finish examining the current layer, proceed to the next lower level
- Repeat this process until the bottom layer is reached
- Advantages:
 - Query-independent, easy to parallelize, incremental update
 - $O(K)$, where K is the number of grid cells at the lowest level
- Disadvantages:
 - All the cluster boundaries are either horizontal or vertical, and no diagonal boundary is detected

60

CLIQUE (Clustering In QUEst)


- Agrawal, Gehrke, Gunopulos, Raghavan (SIGMOD'98)
- Automatically identifying subspaces of a high dimensional data space that allow better clustering than original space
- CLIQUE can be considered as both density-based and grid-based
 - It partitions each dimension into the same number of equal length interval
 - It partitions an m-dimensional data space into non-overlapping rectangular units
 - A unit is dense if the fraction of total data points contained in the unit exceeds the input model parameter
 - A cluster is a maximal set of connected dense units within a subspace

61

CLIQUE: The Major Steps

- Partition the data space and find the number of points that lie inside each cell of the partition.
- Identify the subspaces that contain clusters using the Apriori principle
- Identify clusters
 - Determine dense units in all subspaces of interests
 - Determine connected dense units in all subspaces of interests.
- Generate minimal description for the clusters
 - Determine maximal regions that cover a cluster of *connected* dense units for each cluster
 - Determination of minimal cover for each cluster

62



63

Strength and Weakness of CLIQUE

- Strength
 - automatically finds subspaces of the highest dimensionality such that high density clusters exist in those subspaces
 - insensitive to the order of records in input and does not presume some canonical data distribution
 - scales linearly with the size of input and has good scalability as the number of dimensions in the data increases
- Weakness
 - The accuracy of the clustering result may be degraded at the expense of simplicity of the method

64

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary

65

Assessing Clustering Tendency

- Assess if non-random structure exists in the data by measuring the probability that the data is generated by a *uniform* data distribution
- Test spatial randomness by statistic test: Hopkins Statistic
 - Given a dataset D regarded as a sample of a random variable o, determine *how far away* o is from being uniformly distributed in the data space
 - Sample n points, p_1, \dots, p_n uniformly from D. For each p_i , find its nearest neighbor in D: $x_i = \min\{\text{dist}(p_i, v)\}$ where v in D
 - Sample n points, q_1, \dots, q_n uniformly from D. For each q_i , find its nearest neighbor in D - $\{q_i\}$: $y_i = \min\{\text{dist}(q_i, v)\}$ where v in D and $v \neq q_i$
 - Calculate the Hopkins Statistic: $H = \frac{\sum_{i=1}^n y_i}{\sum_{i=1}^n x_i + \sum_{i=1}^n y_i}$
 - If D is uniformly distributed, $\sum x_i$ and $\sum y_i$ will be close to each other and H is close to 0.5. If D is highly skewed, H is close to 0



66

Determine the Number of Clusters

- Empirical method
 - # of clusters $\approx \sqrt{n/2}$ for a dataset of n points
- Elbow method
 - Use the turning point in the curve of sum of within cluster variance w.r.t the # of clusters
- Cross validation method
 - Divide a given data set into m parts
 - Use $m - 1$ parts to obtain a clustering model
 - Use the remaining part to test the quality of the clustering
 - E.g., For each point in the test set, find the closest centroid, and use the sum of squared distance between all points in the test set and the closest centroids to measure how well the model fits the test set
 - For any $k > 0$, repeat it m times, compare the overall quality measure w.r.t different k 's, and find # of clusters that fits the data the best

67

67

Measuring Clustering Quality

- Two methods: extrinsic vs. intrinsic
- Extrinsic: supervised, i.e., the ground truth is *available*
 - Compare a clustering against the ground truth using certain clustering quality measure
 - Ex. BCubed *precision* and *recall* metrics
- Intrinsic: unsupervised, i.e., the ground truth is *unavailable*
 - Evaluate the goodness of a clustering by considering how well the clusters are separated, and how compact the clusters are
 - Ex. Silhouette coefficient, BIC (Bayesian Information Criterion), AIC (Akaike information criterion)

68

68


Measuring Clustering Quality: Extrinsic Methods

- Clustering quality measure: $Q(C, C_g)$, for a clustering C given the ground truth C_g .
- Q is good if it satisfies the following 4 essential criteria
 - Cluster *homogeneity*: the purer, the better
 - Cluster *completeness*: should assign objects belong to the same category in the ground truth to the same cluster
 - Rag bag: putting a heterogeneous object into a pure cluster should be penalized more than putting it into a *rag bag* (i.e., "miscellaneous" or "other" category)
 - Small cluster preservation: splitting a small category into pieces is more harmful than splitting a large category into pieces

69

69

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary 

70

70

Summary

- Cluster analysis groups objects based on their **similarity** and has wide applications
- Measure of similarity can be computed for **various types of data**
- Clustering algorithms can be **categorized** into partitioning methods, hierarchical methods, density-based methods, grid-based methods, and model-based methods
- **K-means** and **K-medoids** algorithms are popular partitioning-based clustering algorithms
- **Birch** and **Chameleon** are interesting hierarchical clustering algorithms, and there are also probabilistic hierarchical clustering algorithms
- **DBSCAN**, **OPTICS**, and **DENCLU** are interesting density-based algorithms
- **STING** and **CLIQUE** are grid-based methods, where CLIQUE is also a subspace clustering algorithm
- Quality of clustering results can be evaluated in various ways

71

71

Homework Assignment #5

- Textbook
 - 10.2, 10.4, 10.6
 - **More** after the midterm review
 - May include using some toolboxes

72

72

References (1)

- R. Agrawal, J. Gehrke, D. Gunopulos, and P. Raghavan. Automatic subspace clustering of high dimensional data for data mining applications. SIGMOD'98
- M. R. Anderberg. Cluster Analysis for Applications. Academic Press, 1973.
- M. Ankerst, M. Breunig, H.-P. Kriegel, and J. Sander. Optics: Ordering points to identify the clustering structure, SIGMOD'99.
- Beil F., Ester M., Xu X.: "Frequent Term-Based Text Clustering", KDD'02
- M. M. Breunig, H.-P. Kriegel, R. Ng, J. Sander. LOF: Identifying Density-Based Local Outliers. SIGMOD 2000.
- M. Ester, H.-P. Kriegel, J. Sander, and X. Xu. A density-based algorithm for discovering clusters in large spatial databases. KDD'96.
- M. Ester, H.-P. Kriegel, and X. Xu. Knowledge discovery in large spatial databases: Focusing techniques for efficient class identification. SSD'95.
- D. Fisher. Knowledge acquisition via incremental conceptual clustering. Machine Learning, 2:139-172, 1987.
- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. VLDB'98.
- V. Ganti, J. Gehrke, R. Ramakrishnan. CACTUS Clustering Categorical Data Using Summaries. KDD'99.

74

References (2)

- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. In Proc. VLDB'98.
- S. Guha, R. Rastogi, and K. Shim. Cure: An efficient clustering algorithm for large databases. SIGMOD'98.
- S. Guha, R. Rastogi, and K. Shim. ROCK: A robust clustering algorithm for categorical attributes. In ICDE'99, pp. 512-521, Sydney, Australia, March 1999.
- A. Hinneburg, D.I. A. Keim: An Efficient Approach to Clustering in Large Multimedia Databases with Noise. KDD'98.
- A. K. Jain and R. C. Dubes. Algorithms for Clustering Data. Printice Hall, 1988.
- G. Karypis, E.-H. Han, and V. Kumar. CHAMELEON: A Hierarchical Clustering Algorithm Using Dynamic Modeling. COMPUTER, 32(8): 68-75, 1999.
- L. Kaufman and P. J. Rousseeuw. Finding Groups in Data: an Introduction to Cluster Analysis. John Wiley & Sons, 1990.
- E. Knorr and R. Ng. Algorithms for mining distance-based outliers in large datasets. VLDB'98.

75

References (3)

- G. J. McLachlan and K.E. Bkassford. Mixture Models: Inference and Applications to Clustering. John Wiley and Sons, 1988.
- R. Ng and J. Han. Efficient and effective clustering method for spatial data mining. VLDB'94.
- L. Parsons, E. Haque and H. Liu. Subspace Clustering for High Dimensional Data: A Review, SIGKDD Explorations, 6(1), June 2004
- E. Schikuta. Grid clustering: An efficient hierarchical clustering method for very large data sets. Proc. 1996 Int. Conf. on Pattern Recognition
- G. Sheikholeslami, S. Chatterjee, and A. Zhang. WaveCluster: A multi-resolution clustering approach for very large spatial databases. VLDB'98.
- A. K. H. Tung, J. Han, L. V. S. Lakshmanan, and R. T. Ng. Constraint-Based Clustering in Large Databases, ICDE'01.
- A. K. H. Tung, J. Hou, and J. Han. Spatial Clustering in the Presence of Obstacles, ICDE'01
- H. Wang, W. Wang, J. Yang, and P.S. Yu. Clustering by pattern similarity in large data sets, SIGMOD'02
- W. Wang, Yang, R. Muntz, STING: A Statistical Information grid Approach to Spatial Data Mining, VLDB'97
- T. Zhang, R. Ramakrishnan, and M. Livny. BIRCH : An efficient data clustering method for very large databases. SIGMOD'96
- X. Yin, J. Han, and P. S. Yu, "LinkClus: Efficient Clustering via Heterogeneous Semantic Links", VLDB'06

76