

JFTSE — Native Battlemon AI level selection

Proof that JFTSE supplies the level and the unmodified Fantasy Tennis client owns AI profile selection

Branch: feature/battlemon-complete

Base: 3a0163aa (level persistence/serialization)

Validated HEAD: c3befbae

FantaTennis.exe SHA-256:

5477f0827acae66976403aecd2e9ebffeb4fa28da1fedae5f9541ec25e336c31

Validation date: 2026-08-13 UTC

Executive summary

The validated native client, not JFTSE Java code, owns Battlemon tennis AI. JFTSE persisted level 11 for `PotekoTest`, serialized `0B` in the native `0x151B` pet-data response, and the unmodified client displayed `Level : 11`. Static disassembly then establishes the remainder of the deterministic path: the native pet-AI initializer forwards its level argument unchanged to `TennisAIMgr`; `TennisAIMgr` walks the selected species vector in 88-byte steps and accepts only a record whose first integer exactly equals that level.

Proven scope: a native pet initialized with level 11 requests and copies the exact level-11 record loaded from the selected `AI_PetA ... AI_PetK` resource. No level clamp exists in this path.

Not claimed: Java `TennisAI`, stat growth from level, visual evolution, or any owned-pet mapping/fallback for levels 14–250.

Evidence classification

Class	Finding
Observed native runtime	JFTSE emitted <code>0x151B</code> with <code>PotekoTest</code> level <code>0B</code> ; the unmodified client displayed level 11.
Static client reverse engineering	Exact-level lookup, model vector selection, 88-byte profile copy, Basic and Double call sites, and missing-level failure path.
JFTSE source baseline	<code>Pet.level</code> is an independent unsigned byte and is serialized separately from <code>type</code> and <code>STR/STA/DEX/WIL</code> .
Compatibility interpretation	None added. Native behavior remains authoritative.
Implementation in this work	Reproducible binary/wire verifier, conditioned GDB capture script, curated evidence, and this report. No Java AI.

First-principles proof

```
Pet.level = 11
→ JFTSE S2C 0x151B contains 0B after PotekoTest\0
→ native client displays Level : 11
→ TennisAIPetBasic/Double forwards initializer level
→ TennisAIMgr(model, level) compares exact integer level
→ matching 88-byte [Level11] record is copied into the native AI object
```

The controlled fixture kept pet type and STR/STA/DEX/WIL unchanged. This separates level-driven profile selection from item-grown statistics.

Native binary contract

At VA `0x004F9BD0`, the validated executable receives requested level at `[ebp+0x08]`, destination AI object at `[ebp+0x0c]`, and `nPetModel` at `[ebp+0x10]`. It computes the model vector, copies each candidate record to a temporary 88-byte buffer, and compares its first dword with the requested level. On equality it copies the record's behavior flags, probabilities, timings, and movement values into the destination and returns true.

The Basic caller at `0x004F4289` and Double caller at `0x004F4CDC` both pass the initializer level directly to this lookup. The missing-record branch logs:

```
AI Level(%d) requested not found for nPetModel(%d)
```

There is no instruction clamping level to 13. Runtime memory extraction found 13 records for every owned-pet model 0-10, keyed 1-13; their hashes differ at the discriminating levels. The separate model `-1` default table is not an owned-pet fallback.

Controlled native observation

The database changed only pet ID 2's `level` from 3 to 11. JFTSE emitted:

```
... 50 00 6F 00 74 00 65 00 6B 00 6F 00 54 00 65 00 73 00 74 00 00 00
0B 03 01 00 00 C8 00 00 00 0F 0F 0F 0F ...
^^ requested level 11; next bytes retain EXP/type/alive/HP/stats
```



Reproduction

Run the verifier against the immutable executable and captured packet log:

```
python3 scripts/verify_native_pet_ai_level.py /path/to/FantaTennis.exe \
--packet-log /path/to/game-server.log \
--pet-name PotekoTest --expected-level 11
```

For an additional in-match debugger capture, attach `trace-owned-pet-ai-level.gdb` before match start. Its breakpoint is conditioned to ignore model `-1`; a hit prints requested level, matched level, owned-pet model, record address, and all 22 dwords of the selected profile before detaching.

Evidence inventory

Artifact	Claim supported
Client hash	Exact executable provenance
DB before	Controlled baseline
DB after	Only level changed to 11
Decoded packet	JFTSE sent level byte 0B
Native screenshot	Client accepted/rendered level 11
Native profile table	Owned models contain distinct level 1-13 records
Verifier output	Binary and wire checks pass
Checksums	Curated evidence integrity

Boundary and non-claims

The executable's owned-pet resources contain records 1-13, while JFTSE's displayed progression supports 1-250. This report does not bridge that gap by invention. A level above 13 reaches the native exact lookup but has no proven owned record; therefore the server must preserve the real level and must not silently clamp it. A future claim about native behavior above 13 requires a separate runtime experiment.

Conclusion

No Java decision tree is warranted. The smallest correct server contract is already the implemented one: persist and serialize the independent pet `type`, `level`, and stats. The validated client selects the exact native `[LevelN]` record and executes `TennisAIMgr` behavior itself.