

rede BT Analógico Energia 555327 v	TC-08 medidor 15000 via RS485	DG 125 A 10000, 1000 V	DPS DPS Onipac 7 20 kVA, 3F+N	QDG QDG60 gen2 (4x modulos) 50 modulos 4 x 150 W
---	--	----------------------------------	---	---

QDG — Quadro geral 84 módulos · 41 circuitos · 67 Vias (+20 % = 81) de 84

Figure 10 displays a series of 15 diagrams illustrating the evolution of the stress distribution along the length of a beam for different values of the parameter α . The diagrams are arranged in two rows. The top row shows $\alpha = 0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9$. The bottom row shows $\alpha = 1.0, 1.1, 1.2, 1.3, 1.4, 1.5, 1.6, 1.7, 1.8, 1.9$. Each diagram consists of a horizontal line representing the beam, with a vertical line indicating the position of the load. The load is represented by a blue rectangle. The stress distribution is shown as a series of vertical lines of varying heights, with the highest stress concentrated at the load position. The diagrams show that as α increases, the stress distribution becomes more localized at the load position.

ACQUOTO	QO	TEPO	VA	V	FASE	B-A	DEL	mm2	ELETTR.	L-IR	10%
TRF-V6	Q05	tar	7400	220	A-B	35.6	45.4 A-IP	6	DN25	14.4	0.76
TRF-2	Q05	tar	7400	220	A-B	33.8	45.4 A-IP	6	DN25	15.5	1.40
TRF-1	Q05	tar	4000	220	A-B	20.5	25.4 A-IP	4	DN25	15.5	1.40
TRF-2	Q05	tar	4000	220	A-B	20.5	25.4 A-IP	4	DN25	15.5	1.40
TRF-4	Q05	tar	4000	220	A-B	20.5	25.4 A-IP	4	DN25	16.8	1.34
TRF-4	Q05	tar	4000	220	A-B	20.5	25.4 A-IP	4	DN25	15.8	1.06
TRF-10	Q05	tar	2000	220	B-C	13.8	16.4 A-IP	23	DN20	30.2	2.58
TRF-10 (F-050)	Q05	tar	1700	137	B	12.3	16.4 A-IP	4	DN25	30.2	2.58
TRF-10	Q05	tar	2700	220	B-C	16.3	16.4 A-IP	23	DN20	25.7	1.82
TRF-C02	Q05	tar	2000	127	B	10.7	20.4 A-IP	64	DN25	30.2	2.58
TRF-5	Q05	tar	2300	220	A-B	10.5	16.4 A-IP	23	DN20	18.5	1.18
TRF-C09	Q05	tar	3000	127	C	10.7	20.4 A-IP	23	DN20	19.4	3.31
TRF-FLAT	Q05	tar	1000	127	B	8.4	16.4 A-IP	23	DN20	18.5	1.18
TRF-DEP	Q05	tar	1000	127	B	14.2	25.4 A-IP	23	DN20	25.7	3.87
TRF-12	Q05	tar	1000	127	B	11.8	16.4 A-IP	23	DN20	30.2	3.87
TRF-14	Q05	tar	1000	127	B	11.8	16.4 A-IP	23	DN20	30.2	3.87
TRF-6	Q05	tar	1400	220	A-B	6.4	16.4 A-IP	23	DN20	17.7	0.71
TRF-7	Q05	tar	1400	220	A-B	6.4	16.4 A-IP	23	DN20	17.7	0.71
TRF-8	Q05	tar	1400	220	A-B	6.4	16.4 A-IP	23	DN20	16.8	0.97
TRF-9	Q05	tar	1400	220	A-B	6.4	16.4 A-IP	23	DN20	15.8	0.63
TRF-S-MMS	Q05	tar	1200	127	B	8.4	16.4 A-IP	15	DN20	17.7	3.03
TRF-11	Q05	tar	1000	127	C	7.9	16.4 A-IP	23	DN20	23.7	2.03
TRF-18	Q05	tar	1000	127	C	7.9	16.4 A-IP	23	DN20	23.7	2.03
TRF-I-GAR	Q05	tar	800	127	B	7.1	16.4 A-IP	15	DN20	14.4	1.94
TRF-I-T00	Q05	tar	800	127	C	6.3	16.4 A-IP	15	DN20	16.8	0.53
TRF-23	Q05	tar	800	220	A-B	8.4	16.4 A-IP	23	DN20	13.3	0.26
TRF-14	Q05	tar	800	220	A-B	8.4	16.4 A-IP	23	DN20	17.7	1.40
TRF-I-S02	Q05	tar	800	127	C	4.7	16.4 A-IP	15	DN20	17.7	0.40
TRF-I-S02	Q05	tar	800	127	C	4.7	16.4 A-IP	15	DN20	17.7	0.40
TRF-S-B03	Q05	tar	800	127	C	4.7	16.4 A-IP	15	DN20	16.8	0.43
TRF-S-MMS	Q05	tar	800	127	A	4.7	20.4 A-IP	23	DN20	17.7	0.91
TRF-S-009	Q05	tar	500	127	C	3.9	16.4 A-IP	23	DN20	14.4	0.51
TRF-I-001	Q05	tar	500	127	C	3.9	16.4 A-IP	23	DN20	16.8	0.71
TRF-I-S0C	Q05	tar	500	127	C	3.9	20.4 A-IP	23	DN20	16.8	0.77
TRF-I-002	Q05	tar	500	127	B	3.9	16.4 A-IP	15	DN20	30.2	2.15
TRF-S-S02	Q05	tar	500	127	A	3.9	16.4 A-IP	23	DN20	17.5	0.75
TRF-S-003	Q05	tar	500	127	C	3.9	16.4 A-IP	23	DN20	16.8	0.72
TRF-15	Q05	tar	500	220	A-B	2.3	16.4 A-IP	23	DN20	20.5</	

QO	NOME	CRC	VA	VA POR FASE A/B/C	DR	VIAS	+20 %	TEM	
QOG	Quadro geral 64 módulos	41	54650	18750 / 18250 / 18250	2	67	81	04	cade
QOS	Quadro superior 48 módulos	18	24400	6950 / 9950 / 7900	1	33	43	48	cade

- DR 30 mA para banhos, cocineta, lavanderia, garagem, área externa e chuveiros; DPS classe II no QDC

- Fases equilibradas por elétrica, equilibrar (R52): a cor da fase e a do condutor.

RESIDENCIA UNIFAMILIAR | MANAUS - AM | SUITE TARUMA (H)

PROJETO ARQUITETÔNICO

BASE GEOMETRICA

Life Conditions

ESCALA

s/ escala

FORMATD A1

MANUSCRIPT ACCEPTED

ESTUDIO DEL INFIAMADO DE...

ESTUDIO DEL INFIAMADO DE...

234 ART / 1997

60

de 66 REV R24