

|                                                 |                                              |                                  |                                       |                                                                |
|-------------------------------------------------|----------------------------------------------|----------------------------------|---------------------------------------|----------------------------------------------------------------|
| <b>rede BT</b><br>Analógico Energia<br>555327 v | <b>TC-08</b><br>medidor 1500V<br>via rede BT | <b>DG 125 A</b><br>1500V, 125A C | <b>DPS</b><br>DPS Onsur 2 20 kA, 3P+N | <b>QDG</b><br>Queda geral 64 módulos<br>50 módulos 4 x 16 x 25 |
|-------------------------------------------------|----------------------------------------------|----------------------------------|---------------------------------------|----------------------------------------------------------------|

QDC — Quadro geral 84 módulos · 41 circuitos · 67 vias (+20 % = 81) de 84



Figure 10 shows the evolution of the stress distribution along the length of a beam during the curing process. The diagrams are arranged in two rows of seven. Each diagram shows a horizontal beam with a vertical axis representing stress. The stress distribution is represented by a shaded area under the beam. The diagrams are labeled with time intervals: (a) 0-10 min, (b) 10-20 min, (c) 20-30 min, (d) 30-40 min, (e) 40-50 min, (f) 50-60 min, (g) 60-70 min, (h) 70-80 min, (i) 80-90 min, (j) 90-100 min, (k) 100-110 min, (l) 110-120 min, (m) 120-130 min, (n) 130-140 min, (o) 140-150 min, (p) 150-160 min, (q) 160-170 min, (r) 170-180 min, (s) 180-190 min, (t) 190-200 min, (u) 200-210 min, (v) 210-220 min, (w) 220-230 min, (x) 230-240 min, (y) 240-250 min, (z) 250-260 min, (aa) 260-270 min, (ab) 270-280 min, (ac) 280-290 min, (ad) 290-300 min, (ae) 300-310 min, (af) 310-320 min, (ag) 320-330 min, (ah) 330-340 min, (ai) 340-350 min, (aj) 350-360 min, (ak) 360-370 min, (al) 370-380 min, (am) 380-390 min, (an) 390-400 min, (ao) 400-410 min, (ap) 410-420 min, (aq) 420-430 min, (ar) 430-440 min, (as) 440-450 min, (at) 450-460 min, (au) 460-470 min, (av) 470-480 min, (aw) 480-490 min, (ax) 490-500 min, (ay) 500-510 min, (az) 510-520 min, (ba) 520-530 min, (bb) 530-540 min, (bc) 540-550 min, (bd) 550-560 min, (be) 560-570 min, (bf) 570-580 min, (bg) 580-590 min, (bh) 590-600 min, (bi) 600-610 min, (bj) 610-620 min, (bk) 620-630 min, (bl) 630-640 min, (bm) 640-650 min, (bn) 650-660 min, (bo) 660-670 min, (bp) 670-680 min, (bq) 680-690 min, (br) 690-700 min, (bs) 700-710 min, (bt) 710-720 min, (bu) 720-730 min, (bv) 730-740 min, (bw) 740-750 min, (bx) 750-760 min, (by) 760-770 min, (bz) 770-780 min, (ca) 780-790 min, (cb) 790-800 min, (cc) 800-810 min, (cd) 810-820 min, (ce) 820-830 min, (cf) 830-840 min, (cg) 840-850 min, (ch) 850-860 min, (ci) 860-870 min, (cj) 870-880 min, (ck) 880-890 min, (cl) 890-900 min, (cm) 900-910 min, (cn) 910-920 min, (co) 920-930 min, (cp) 930-940 min, (cq) 940-950 min, (cr) 950-960 min, (cs) 960-970 min, (ct) 970-980 min, (cu) 980-990 min, (cv) 990-1000 min. The stress distribution changes from a single peak at the center to a more complex shape with multiple peaks and troughs as time progresses.

| ACQUOTO     | QO  | TEPO | VA   | V   | FASE | B-A  | DEL     | mm2 | ELETTR. | L-IR | 10%  |
|-------------|-----|------|------|-----|------|------|---------|-----|---------|------|------|
| TRF-V6      | Q05 | tar  | 7400 | 220 | A-B  | 35.6 | 45.4 2P | 6   | DN25    | 14.4 | 0.76 |
| TRF-2       | Q05 | tar  | 7400 | 220 | A-B  | 33.8 | 45.4 2P | 6   | DN25    | 15.5 | 1.40 |
| TRF-1       | Q05 | tar  | 4000 | 220 | A-B  | 20.5 | 25.4 2P | 4   | DN25    | 15.5 | 1.40 |
| TRF-2       | Q05 | tar  | 4000 | 220 | A-B  | 20.5 | 25.4 2P | 4   | DN25    | 15.5 | 1.40 |
| TRF-4       | Q05 | tar  | 4000 | 220 | A-B  | 20.5 | 25.4 2P | 4   | DN25    | 16.8 | 1.34 |
| TRF-4       | Q05 | tar  | 4000 | 220 | A-B  | 20.5 | 25.4 2P | 4   | DN25    | 15.8 | 1.06 |
| TRF-10      | Q05 | tar  | 2000 | 220 | B-C  | 13.8 | 16.4 2P | 23  | DN20    | 30.2 | 2.58 |
| TRF-10-FCO3 | Q05 | tar  | 1700 | 137 | B    | 12.3 | 16.4 2P | 4   | DN25    | 30.2 | 2.58 |
| TRF-10      | Q05 | tar  | 2700 | 220 | B-C  | 16.3 | 16.4 2P | 23  | DN20    | 30.2 | 1.82 |
| TRF-CCO2    | Q05 | tar  | 2000 | 127 | B    | 10.7 | 20.4 2P | 6 1 | DN25    | 30.2 | 2.59 |
| TRF-5       | Q05 | tar  | 2300 | 220 | A-B  | 10.5 | 16.4 2P | 23  | DN20    | 18.5 | 1.18 |
| TRF-FCO3    | Q05 | tar  | 2000 | 127 | C    | 10.7 | 20.4 2P | 23  | DN20    | 18.4 | 3.31 |
| TRF-FLAT    | Q05 | tar  | 1000 | 127 | B    | 10.7 | 20.4 2P | 23  | DN20    | 18.4 | 3.31 |
| TRF-DEP     | Q05 | tar  | 1000 | 127 | B    | 14.2 | 25.4 2P | 23  | DN20    | 25.2 | 3.87 |
| TRF-12      | Q05 | tar  | 1000 | 127 | B    | 11.8 | 16.4 2P | 23  | DN20    | 30.2 | 3.97 |
| TRF-14      | Q05 | tar  | 1000 | 127 | B    | 11.8 | 16.4 2P | 23  | DN20    | 30.2 | 3.87 |
| TRF-6       | Q05 | tar  | 1400 | 220 | A-B  | 6.4  | 16.4 2P | 23  | DN20    | 17.7 | 0.71 |
| TRF-7       | Q05 | tar  | 1400 | 220 | A-B  | 6.4  | 16.4 2P | 23  | DN20    | 17.7 | 0.71 |
| TRF-8       | Q05 | tar  | 1400 | 220 | A-B  | 6.4  | 16.4 2P | 23  | DN20    | 16.8 | 0.97 |
| TRF-9       | Q05 | tar  | 1400 | 220 | A-B  | 6.4  | 16.4 2P | 23  | DN20    | 15.8 | 0.63 |
| TRF-S-MMS   | Q05 | tar  | 1200 | 127 | B    | 8.4  | 25.4 2P | 15  | DN20    | 17.7 | 3.93 |
| TRF-11      | Q05 | tar  | 1000 | 127 | C    | 7.9  | 25.4 2P | 23  | DN20    | 23.7 | 2.03 |
| TRF-18      | Q05 | tar  | 2000 | 127 | C    | 7.9  | 25.4 2P | 23  | DN20    | 23.7 | 2.03 |
| TRF-1-GAR   | Q05 | tar  | 900  | 127 | B    | 7.1  | 25.4 2P | 15  | DN20    | 14.4 | 1.94 |
| TRF-10-GU   | Q05 | tar  | 800  | 127 | C    | 6.3  | 25.4 2P | 15  | DN20    | 16.8 | 0.53 |
| TRF-23      | Q05 | tar  | 800  | 220 | A-B  | 8.4  | 25.4 2P | 23  | DN20    | 13.3 | 0.26 |
| TRF-14      | Q05 | tar  | 800  | 220 | A-B  | 8.4  | 25.4 2P | 23  | DN20    | 17.7 | 1.40 |
| TRF-1-SO2   | Q05 | tar  | 800  | 127 | C    | 4.7  | 25.4 2P | 15  | DN20    | 17.7 | 0.90 |
| TRF-S-SO2   | Q05 | tar  | 800  | 127 | C    | 4.7  | 25.4 2P | 15  | DN20    | 17.7 | 0.90 |
| TRF-S-MMS   | Q05 | tar  | 800  | 127 | A    | 4.7  | 25.4 2P | 15  | DN20    | 16.8 | 1.43 |
| TRF-S-MMS   | Q05 | tar  | 800  | 127 | A    | 4.7  | 25.4 2P | 23  | DN20    | 17.7 | 0.91 |
| TRF-FCO3    | Q05 | tar  | 500  | 127 | C    | 3.9  | 25.4 2P | 23  | DN20    | 14.4 | 0.51 |
| TRF-FCO3    | Q05 | tar  | 500  | 127 | C    | 3.9  | 25.4 2P | 23  | DN20    | 16.8 | 0.71 |
| TRF-1-SO2   | Q05 | tar  | 500  | 127 | C    | 3.9  | 25.4 2P | 23  | DN20    | 30.2 | 2.15 |
| TRF-S-SO2   | Q05 | tar  | 500  | 127 | A    | 3.9  | 25.4 2P | 23  | DN20    | 17.5 | 0.75 |
| TRF-S-SO2   | Q05 | tar  | 500  | 127 | C    | 3.9  | 25.4 2P | 23  | DN20    | 16.8 | 0.72 |
| TRF-15      | Q05 | tar  | 500  | 220 | A-B  | 2.3  | 25.4 2P | 23  | DN20    | 20.5 | 0.20 |
| TRF-15      | Q05 | tar  | 500  | 220 | A-B  | 2.3  | 25.4 2P | 23  | DN20    | 20.5 |      |

- Entrada trifásico 220/227 V (estrela com neutro); 115,6 A de demanda, disjuntor geral 125 A, nominal 50 mm<sup>2</sup> do medidor TC-08 ao QDG em 23,8 m (3,74 % de queda).

- Iluminação 1,5 mm<sup>2</sup> / 10 A; TUG 2,5 mm<sup>2</sup> / 20 A; TUE pela corrente (tabela 36 da NBR 5410, B1). Onde a queda passa de 4 %, a secao sobe — e a tabela diz qual.

- DR 30 mA para banhos, cocineta, lavanderia, garagem, área externa e chuveiros; DPS classe II no QDC

- Fases equilibradas por elétrica, equilibrar (R52): a cor da fase e a do condutor.

## RESIDENCIA UNIFAMILIAR | MANAUS - AM | SUITE TARUMA (H)

PROJETO ARQUITETÔNICO

## BASE GEOMETRICA

### BASE GEOMETRICA

Listas Consolidadas

msl-132 Unpublished

**s/ escala**

FORMATD A1

MALHA 600/500/750

ESTUDO PRELIMINAR R73

SEMANT / SYNT

FRANCHIA

60

de 69 FIEV R77