

rede BT Analógico Energia 555327 v	TC-08 medidor 15000 via rede BT	DG 125 A 10000, 120V x 1	DPS DPS Onipar 2 20 kVA, 3F+N	QDG Queda geral (44 modulos) 50 modulos 4 x 100 20
---	--	------------------------------------	---	---

QDC — Quadro geral 84 módulos · 41 circuitos · 67 vias (+20 % = 81) de 84




Figure 1: A schematic diagram of a multi-layered system. The diagram shows a vertical stack of layers. The top layer is labeled 'a' and contains a blue box with '27' and '1.80'. Below it is a layer labeled 'b' with a blue box containing '27' and '1.80'. The next layer is labeled 'c' with a blue box containing '27' and '1.80'. Below that is a layer labeled 'd' with a blue box containing '27' and '1.80'. The bottom layer is labeled 'e' with a blue box containing '27' and '1.80'. The layers are separated by horizontal lines. The diagram is labeled 'Figure 1' at the bottom.

ACQUOTO	QO	TIPO	VA	V	FASE	RA	DEL	mm2	ELETTR.	L. W	1.0%
TR-16	000	ter	7400	220	A/B	35.6	45.4 1P	6	DN20	16.4	1.0%
TR-2	000	ter	7400	220	A/C	33.8	45.4 1P	6	DN20	16.5	1.0%
TR-1	000	ter	4000	220	A/B	20.3	25.9 1P	4	DN15	16.5	1.0%
TR-2	000	ter	4000	220	B/C	20.5	25.9 1P	4	DN15	17.0	1.0%
TR-4	000	ter	4000	220	A/B	20.5	25.9 1P	4	DN15	16.8	1.0%
TR-5	000	ter	4000	220	A/C	20.5	25.9 1P	4	DN15	16.8	1.0%
TR-10	000	ter	2000	220	B/C	13.8	16.4 1P	3	DN20	16.2	1.0%
TR-13	000	ter	1700	137	B	12.3	16.4 1P	4	DN20	16.4	1.0%
TR-16	000	ter	2700	220	B/C	18.3	16.4 1P	3	DN20	16.7	1.0%
TR-17	000	ter	2000	137	B	10.7	20.4 1P	5	DN20	16.2	2.0%
TR-18	000	ter	2300	220	A/C	10.5	16.4 1P	3	DN20	16.0	1.0%
TR-17	000	ter	2300	137	C	10.7	20.4 1P	5	DN20	16.4	3.0%
TR-18	000	ter	1000	137	B	10.5	16.4 1P	3	DN20	16.4	3.0%
TR-19	000	ter	1000	137	B	14.2	25.9 1P	3	DN20	16.2	3.0%
TR-12	000	ter	1000	137	B	11.8	16.4 1P	3	DN20	16.2	3.0%
TR-14	000	ter	1000	137	B	11.8	16.4 1P	3	DN20	16.2	3.0%
TR-6	000	ter	1400	220	A/C	6.4	16.4 1P	3	DN20	17.7	0.1%
TR-7	000	ter	1400	220	A/C	6.4	16.4 1P	3	DN20	17.5	1.0%
TR-8	000	ter	1400	220	A/B	6.4	16.4 1P	3	DN20	16.8	0.7%
TR-9	000	ter	1400	220	A/C	6.4	16.4 1P	3	DN20	16.8	0.3%
TR-5-SM5	000	tern	1200	137	B	8.4	25.9 1P	1.5	DN20	17.7	3.0%
TR-11	000	ter	1000	137	C	7.9	16.4 1P	3	DN20	16.7	3.0%
TR-12	000	ter	1000	137	C	7.9	16.4 1P	3	DN20	16.7	3.0%
TR-11	000	ter	800	137	B	7.1	16.4 1P	3	DN20	16.4	1.0%
TR-11-GAR	000	tern	800	137	B	7.1	16.4 1P	3	DN20	16.4	1.0%
TR-11-TOU	000	tern	800	137	C	6.3	16.4 1P	1.5	DN20	16.6	3.0%
TR-13	000	ter	800	220	A/C	8.4	16.4 1P	3	DN20	16.3	0.3%
TR-14	000	ter	800	220	A/B	8.4	16.4 1P	3	DN20	17.7	0.4%
TR-15	000	ter	200	137	C	4.2	16.4 1P	3	DN20	16.5	1.0%
TR-11-SOC	000	tern	800	137	B	4.7	16.4 1P	1.5	DN20	16.8	1.0%
TR-5-B2	000	tern	800	137	A	4.7	16.4 1P	1.5	DN20	17.6	1.0%
TR-5-S2	000	tern	800	137	C	4.7	16.4 1P	1.5	DN20	16.8	1.4%
TR-5-SM5	000	tern	800	137	A	4.7	16.4 1P	1.5	DN20	16.8	1.4%
TR-5-SM5	000	ter	800	137	A	7.9	20.4 1P	3	DN20	16.8	1.0%
TR-11-CH	000	ter	800	137	C	3.9	20.4 1P	3	DN20	16.8	0.7%
TR-11-SOC	000	ter	500	137	B	3.9	20.4 1P	3	DN20	16.6	1.0%
TR-11-C22	000	tern	500	137	A	3.9	16.4 1P	1.5	DN20	16.2	2.1%
TR-11-S2	000	ter	500	137	C	3.9	16.4 1P	1.5	DN20	16.5	1.0%
TR-5-S2	000	ter	800	137	A	2.9	20.4 1P				

QO	NOME	CRC	VA	VA POR FASE A/B/C	DR	VIAS	+20 %	TEM	
QOG	Quadro geral 64 módulos	41	54650	20100 / 15900 / 18650	2	67	81	04	cabé
QOS	Quadro superior 48 módulos	18	24400	6290 / 10490 / 7700	1	33	40	48	cabé

PROJETO PORTO REAL

PROJETO ARQUITETÔNICO

ELETRICA — DIAGRAMA UNIFILAR E QUADROS DE DISTRIBUICAC

BASE GEOMÉTRICA Lista Consolidada pis #32 (prevalece) UNIDADE MESTRE: 04h	ESCALA s/ escala FORMATO A1 MALHA 600/300/150	EMISSÃO ESTUDO PRELIMINAR R79 NÃO LIBERADO PARA OBRA SEM ART / RVT	PRONCHA 60 de 72 REV/07
--	--	---	---

60

de 72 REV R21