

In React, you can inject boolean data into JSX elements in several ways:

1. Conditional Rendering with if or ternary operator

- if statement:

JavaScript

```
function MyComponent() {  
  const isLoggedIn = true;  
  
  if (isLoggedIn) {  
    return (  
      <div>  
        <h1>Welcome, User!</h1>  
        <button>Logout</button>  
      </div>  
    );  
  } else {  
    return (  
      <div>  
        <h1>Please Login</h1>  
        <button>Login</button>  
      </div>  
    );  
  }  
}
```

- Ternary operator:

JavaScript

```
function MyComponent() {  
  const isLoggedIn = true;  
  
  return (  
    <div>  
      <h1>{isLoggedIn ? 'Welcome, User!' : 'Please Login'}</h1>  
      <button>{isLoggedIn ? 'Logout' : 'Login'}</button>  
    </div>  
  );  
}
```

```
}
```

2. Conditional Rendering with && operator

This approach is concise for rendering elements only when a condition is true:

JavaScript

```
function MyComponent() {  
  const isLoggedIn = true;  
  
  return (  
    <div>  
      {isLoggedIn && (  
        <>  
          <h1>Welcome, User!</h1>  
          <button>Logout</button>  
        </>  
      )}  
      {!isLoggedIn && (  
        <>  
          <h1>Please Login</h1>  
          <button>Login</button>  
        </>  
      )}  
    </div>  
  );  
}
```

3. Using the ? operator for short-circuiting

This is a more concise way to render different content based on a boolean value:

JavaScript

```
function MyComponent() {  
  const isLoggedIn = true;  
  
  return (  
    <div>  
      <h1>{isLoggedIn && 'Welcome, User!'}</h1>  
    </div>  
  );  
}
```

```
    {!isLoggedIn && 'Please Login'}  
  </div>  
);  
}
```

Example in your code:

JavaScript

```
const isAdmin = true; // Example boolean value  
  
// Injecting boolean data into JSX  
const adminPanel = (  
  <div>  
    {isAdmin && (  
      <>  
        <h2>Admin Panel</h2>  
        { /* Admin-specific content here */ }  
      </>  
    )}  
  </div>  
)  
);  
  
// Render the component  
ReactDOM.render(adminPanel, rootElement);
```

These methods allow you to dynamically control which parts of your JSX are rendered based on the value of your boolean variable. Choose the method that best suits your needs and coding style.