

OPENER: Open Partitioning Embedding for Named Entity Recognition

Anonymous Author(s)

Paper submitted for double-blind review

LyRICS Symposium 2026

Abstract

Open-world named entity recognition (NER) must assign entity types that were not fixed at training time. Recent systems either train a dedicated encoder or prompt billion-parameter language models, and they are compared almost exclusively on accuracy, ignoring their compute and energy cost. We present **OPENER**, a lightweight open-world NER pipeline assembled from off-the-shelf components: a frozen mention detector, a Matryoshka-truncatable sentence embedder sharpened by a light contrastive fine-tuning with error-driven hard-negative mining, and a swappable typing head, so that no encoder is trained from scratch. The head has a supervised form, **OPENER-Sup**, and a zero-shot form, **OPENER-ZS**, that uses no target labels. We benchmark **OPENER** against GLiNER, GNER and OWNER on 13 datasets along three axes at once: quality, measured by Adjusted Mutual Information (AMI), inference latency, and energy consumption. Our analysis separates entity typing on gold mentions, where the contrastive embedding space is highly discriminative, from the end-to-end setting, where the dominant open-world bottleneck is shown to be mention detection rather than typing. The energy-aware comparison further exposes order-of-magnitude efficiency gaps between approaches that a quality-only evaluation would hide. **OPENER-Sup**, the supervised probe, is the most accurate system in our benchmark: it leads typing on gold mentions on all 13 sets, surpassing a zero-shot transfer of OWNER (62.5 vs 43.0 AMI), and attains the best end-to-end AMI of all compared systems (40.2, ahead of GLiNER-L’s 38.9), at the cost of target labels. Removing that supervision, **OPENER-ZS** – typing against label-name prototypes, refined transductively and fused with the detector’s own predictions, without any target label — is the best of the compared *zero-shot* systems end-to-end (39.4), at 1.7 Wh per run, an order of magnitude or more below the contrastive-clustering (14.3 Wh) and generative (36.5 Wh) baselines. We release the code, the per-experiment configurations and the full benchmark.

Index Terms

open-world named entity recognition, entity typing, contrastive representation learning, Matryoshka embeddings, frugal artificial intelligence, energy-efficient machine learning, adjusted mutual information, open info extraction, Supervised NER, Zero-Shot NER

I. INTRODUCTION

Named entity recognition (NER) in production rarely operates over a fixed inventory of types. New entity categories appear as a system meets new domains, products or users, and a closed-set tagger trained on a frozen label set cannot name a type it has never seen. The standard remedy — re-annotating data for the new types and retraining the model — is slow and expensive, which is precisely what *open-world* NER seeks to avoid: recognising and typing entities whose categories were not fixed at training time.

Existing open-world approaches buy this flexibility at a cost. Span-based closed-set models reach high accuracy but remain bound to their training inventory [1]. OWNER [2] removes that bound by training a dedicated entity encoder with a triplet objective and clustering the resulting mentions into dynamically named types, but it still trains an encoder from scratch and pays a heavy per-sentence inference cost. A complementary line prompts or instruction-tunes billion-parameter language models [3], [4], which are accurate but slow, brittle, and often too large for commodity hardware. Across all of these, evaluation is reported almost exclusively on accuracy: the compute, latency and energy that separate a 137 M-parameter pipeline from a 7 B-parameter model are left out of the comparison, even though they decide what can actually be deployed.

We present **OPENER**, a lightweight open-world NER pipeline assembled from off-the-shelf components, with no encoder trained from scratch. A frozen detector proposes spans, a pretrained Matryoshka sentence embedder — sharpened by a light contrastive fine-tuning and an error-driven hard-negative mining pass — maps each span to a vector, and a typing head assigns a type. The pipeline is modular: detector, embedder and typing head are independently swappable, and the embedder can be truncated to trade quality for compute. The typing head exposes two operating points. **OPENER-Sup**, a supervised linear probe, is the most accurate configuration in our benchmark—the best end-to-end AMI of all compared systems and the best typing on gold mentions—but needs target labels. A zero-shot variant, **OPENER-ZS**, uses no target labels at typing time: it types each mention against label-name prototypes, refined transductively and *fused* with the detector’s own zero-shot label predictions—a signal that prototype matching otherwise discards. This zero-shot head is the operating point we put forward: it reaches the best end-to-end AMI of all compared zero-shot systems while keeping an order-of-magnitude-lower energy footprint than the trained-encoder and generative baselines.

Our contributions are as follows.

- **OPENER**, an open-world NER pipeline assembled entirely from off-the-shelf parts (a frozen detector and a pretrained Matryoshka embedder) with no encoder trained from scratch and a swappable typing head.
- An *error-driven hard-negative mining* step that fine-tunes the embedding on the type pairs it most often confuses, lifting typing-on-gold AMI by 8.5 points over plain contrastive fine-tuning.
- **OPENER-ZS**, a label-free typing head combining label-name prototypes, a transductive refinement, and a fusion with the detector’s zero-shot predictions, which is the best zero-shot system end-to-end on our benchmark, ahead of GLiNER-L, GNER and OWNER.
- An *energy-aware* benchmark of open-world NER on 13 datasets that reports quality, latency and energy jointly, separates typing-on-gold from end-to-end, and shows that the dominant open-world bottleneck is mention detection rather than typing, while exposing efficiency gaps that an accuracy-only evaluation would hide. The comparison also includes a small instruction-tuned LLM, Qwen2.5-1.5B-Instruct in 4-bit—the largest generative model that fits our commodity GPU—which turns out to be both the least accurate and the most expensive of all systems.

The rest of the paper is organised as follows. section II reviews related work, section III details the OPENER pipeline, section IV presents the benchmark and ablations, and section V concludes.

II. RELATED WORK

OPENER sits at the intersection of three lines of research: open-world and zero-shot named entity recognition (NER), pretrained entity representations refined by contrastive learning, and energy-aware machine learning. We review each in turn and state how OPENER differs.

A. Closed-set and Span-based NER

Traditional NER is cast as supervised sequence labeling over a fixed inventory of entity types, typically with a pretrained encoder followed by a token- or span-level classifier. Span-based formulations enumerate candidate spans and classify them directly, which simplifies the handling of nested and discontinuous entities [1]. These models reach high accuracy on in-domain benchmarks such as CoNLL-2003 [5], but their label set is frozen at training time. Adding a new entity type requires re-annotating data and retraining the model, which is the central limitation that open-world NER seeks to remove.

B. Open-world and Zero-shot NER

Open-world NER aims to recognise entity types that were not fixed at training time. GLiNER [6] treats the candidate type names as queries to a bidirectional encoder, a DeBERTaV3 backbone [7], and scores every span against them in a single forward pass, offering a fast alternative to autoregressive tagging. GNER [8] instead casts NER as text generation with a sequence-to-sequence model [9] and shows that explicitly modeling negative, non-entity instances sharpens type boundaries. Closest to our work, Genest et al. [2] propose OWNER, an unsupervised open-world pipeline that decouples mention detection from entity typing: it embeds detected mentions with an encoder refined by contrastive learning and then clusters them into dynamically named types. Other approaches prompt a general-purpose large language model to perform extraction directly, as in ChatIE [10], or focus on recovering entities that detectors tend to miss [11]. OPENER adopts the decoupled detect-then-type view of OWNER, but replaces the trained encoder and the unsupervised clustering with a pretrained, Matryoshka-truncatable embedding space and a balanced linear classifier, so that no encoder is trained from scratch.

C. LLM-based and Few-shot NER

A complementary line distils or instruction-tunes large language models for open NER. UniversalNER [3] distils a chat model into a smaller LLaMA-based student [12] over tens of thousands of entity types, while GoLLIE [4] conditions a code language model on annotation guidelines to follow unseen schemas. Few-shot methods reduce supervision further through prompt optimization [13], knowledge-graph-guided contrastive learning [14], or token-level contrastive objectives such as CONTaiNER [15]. These methods are accurate but rest on models with billions of parameters, whose inference cost, latency and energy use are substantial, and which may not even fit on commodity hardware. At the small end of this family, however, a quantized instruction-tuned model does fit a commodity GPU: as a concrete, runnable reference point we include Qwen2.5-1.5B-Instruct [16] in 4-bit, prompted to return entities as JSON, and report where it lands relative to the dedicated open-world systems (subsection IV-F). This cost is precisely what motivates the lightweight design and the energy-aware evaluation of OPENER.

D. Entity Representations and Contrastive Learning

OPENER relies on a pretrained sentence embedder rather than a task-specific encoder. Nomic Embed [17] provides an open, long-context model trained with the Matryoshka objective [18], whose representations can be truncated to lower dimensions without retraining, trading quality for compute. Such embedders build on the Sentence-BERT line of work [19], and we sharpen the entity-type geometry with a triplet margin objective in the spirit of FaceNet [20]. The choice of base encoder is made

empirically: we compare several strong open sentence encoders—E5 [21], BGE [22], MPNet [23] and mxbai [24]—on entity typing under a common protocol (Table VII); Nomic v1.5 [17] edges them out while additionally offering native Matryoshka truncation, so we adopt it as the base and fine-tune it. Embedding labels and entities in a shared space [25], modeling entity types with Gaussian components [26], generating synthetic entity-bearing text for augmentation [27], and using mixtures to augment training data [28] are recurring ideas in low-resource NER, all grounded in classical Gaussian mixture models fitted by expectation-maximization [29], [30]. Unlike methods that train a dedicated encoder, OPENER keeps the pretrained space largely frozen and only applies a light contrastive fine-tuning, which tests whether a general-purpose embedding is already discriminative enough for entity typing.

E. Efficient and Green AI

A growing body of work argues that efficiency should be reported alongside accuracy. Strubell et al. [31] quantify the financial and environmental cost of training NLP models, Schwartz et al. [32] advocate efficiency as a first-class evaluation criterion, and Patterson et al. [33] analyse the carbon footprint of machine-learning training and how to reduce it. Tools such as CodeCarbon [34] make per-run energy and carbon estimates practical. Open-world NER systems, however, are still compared almost exclusively on quality. OPENER instead reports a three-axis comparison of quality, measured by Adjusted Mutual Information [35], inference speed, and energy, placing the frugality of each method on an equal footing with its accuracy.

In summary, existing open-world NER methods either train a dedicated encoder [2] or query costly large language models [3], [4], and they are compared on accuracy alone. OPENER fills both gaps: it reuses pretrained components with only a light contrastive step and a balanced linear classifier, and it is evaluated jointly on quality, speed and energy.

III. METHOD

A. Problem Formulation

Given a sentence, an open-world NER system must return a set of typed mentions whose type inventory is *not* fixed at training time. We adopt the evaluation of Genest et al. [2]. Predicted and gold mentions are aligned by exact character offsets; an unmatched gold mention (false negative) and an unmatched predicted mention (false positive) each receive a distinct sentinel type, so that detection errors are scored rather than ignored. Type-assignment quality is then measured by the Adjusted Mutual Information (AMI) [35] between the predicted and gold type partitions over the aligned mentions, which does not require the two label vocabularies to coincide. We report two protocols that are never mixed in the same comparison: *typing-on-gold*, where the typing component is applied to gold spans and detection is bypassed, and *end-to-end*, where mentions come from the detector and the sentinels above are active.

B. Architecture Overview

OPENER is a three-stage pipeline, Detect $\rightarrow$ Embed $\rightarrow$ Type (Figure 1), assembled from off-the-shelf components so that no encoder is trained from scratch. Three principles guide the design. (i) A pretrained detector and a pretrained sentence embedder are reused as-is. (ii) A light contrastive fine-tuning, refined by error-driven hard-negative mining, turns the general-purpose embedding into one that is discriminative for entity *types*. (iii) The embedder is Matryoshka-truncatable, exposing a compute/quality knob. Only the typing head is fitted on target-side material, and it comes in two forms: **OPENER-Sup**, a supervised linear probe that is the strongest configuration but requires target labels, and a zero-shot form, **OPENER-ZS**, that uses no target labels at typing time.

C. Mention Detection

Mention detection is delegated to GLiNER [6], a frozen, off-the-shelf detector that scores every span against the candidate type names in a single forward pass. Decoupling detection from typing lets each component be chosen and measured independently, and it lets the typing head operate on any span proposer. We use GLiNER-L by default; the small and medium variants trace a size/efficiency trade-off (Table VII). As shown in subsection IV-F, the detector is the shared end-to-end bottleneck: its recall on specialised domains, not the typing head, caps end-to-end quality.

D. Entity Embedding

Detected spans are embedded with Nomic Embed v1.5 [17], a sentence embedder trained with the Matryoshka objective [18], whose representation can be truncated to a lower dimension and renormalised without retraining. Each mention is embedded *in context* rather than in isolation: the span is presented together with its surrounding sentence, so that polysemous surface forms (e.g. a company versus a fruit) are disambiguated. This yields a vector $e_i \in \mathbb{R}^D$ with D truncatable in $\{768, 512, 256, 128, 64\}$; we keep the full $D=768$ by default. Truncation is a post-encoding slice followed by renormalisation, so it reduces the stored embedding and the typing-head fit cost but leaves the forward pass unchanged (Table VII).

OPENER — Architecture

Open Partitioning Embedding for NER · pipeline Detect → Embed → Type · no encoder trained from scratch




Fig. 1. The OPENER pipeline (Detect → Embed → Type). A frozen GLiNER detector proposes spans and a candidate label; a Matryoshka embedder, sharpened by contrastive fine-tuning and error-driven hard-negative mining, maps each span in context to a vector; and a typing head assigns a type. The typing head is the only component fitted on target-side material and has two operating points: **OPENER-Sup**, a *supervised* linear probe (the most accurate, but requires target labels), and the *zero-shot* **OPENER-ZS** (★, the selected operating point), which types against label-name prototypes, refines them transductively, and fuses in the detector’s own zero-shot label. All upstream components are off-the-shelf.

E. Contrastive Fine-tuning with Hard-Negative Mining

The frozen embedding is only weakly discriminative for entity types (25.8 AMI, Table VII), so we sharpen its geometry in two stages while keeping the backbone otherwise intact.

a) Stage 1 – contrastive: We fine-tune the embedder with a Triplet Margin Loss [20] (using sentence-transformers [19]), with margin 1, on the CoNLL-2003 [5] training spans. A triplet (a, p, n) takes an anchor span a , a positive p of the *same* type, and a negative n of a *different* type, with at most two triplets per anchor. Training runs for 3 epochs with batch size 16, learning rate 2×10^{-5} and 100 warmup steps. This single step lifts typing-on-gold AMI from 25.8 to 54.0.

b) Stage 2 – error-driven hard-negative mining: We then mine the model’s own confusions. On each target training split we run a cross-validated typing pass (so no test label is ever seen) and collect the type pairs that are most often confused, such as *writer/person*, *album/band* and *country/location*. For each such error we form a *hard* triplet whose anchor is the mistyped

TABLE I
OPENER CONFIGURATION. THE DETECTOR AND EMBEDDER ARE OFF-THE-SHELF; THE CONTRASTIVE AND HARD-MINING STAGES PRODUCE THE SHARED EMBEDDER; THE TYPING HEAD IS FITTED (SUPERVISED) OR LABEL-FREE (ZERO-SHOT).

Component	Setting
Mention detector	GLiNER-L (frozen) [6]
Entity embedder	Nomic v1.5, $D=768$, span-in-context [17]
Contrastive loss	Triplet margin 1 [20]
source	CoNLL-2003 train spans [5]
optimiser	3 epochs, batch 16, lr 2×10^{-5} , 100 warmup
Hard-neg. mining	8000 triplets, 65% hard, 3 epochs
source	target train splits, cross-validated
Supervised typing	LinearSVC, balanced weights [36]
Zero-shot typing	label-name prototype + transductive + fusion ($\beta=0.05$)
Random seed	42

span (true type L), whose positive is another span of L , and whose negative is a span of the confused type C . Hard triplets are mixed with correctly-typed (easy) triplets for diversity, targeting a 65% hard fraction, and the Stage-1 embedder is fine-tuned further with the same optimiser settings. The selected run mines 8000 triplets over 3 epochs and reaches 62.5 AMI (+8.5 over Stage 1, better on 12 of 13 sets). This embedder is shared unchanged by every typing head below.

F. Entity Typing

a) Supervised probe (OPENER-Sup): The default typing head is a balanced linear classifier (LinearSVC with the LIBLINEAR solver [36]) fitted on the target’s training labels. Class weights follow the balanced rule $w_c = n_{\text{total}}/(C n_c)$, where C is the number of types and n_c the count of type c , which counters the heavy type imbalance of the benchmark. This is the strongest configuration but requires target-side labels.

b) Zero-shot typing (OPENER-ZS): To remove target supervision at typing time, each type t is represented by a prototype p_t , the embedding of its name (the centroid of the type’s anchor words in the contrastive space), and a mention e_i is assigned the type of the nearest prototype by cosine similarity. Two label-free refinements improve this head without using any target label. First, a *transductive* refinement runs one pass of spherical k -means over the unlabelled test mentions, seeded by the prototypes. Second, a *detector fusion* reuses a signal the prototype head otherwise discards: GLiNER already predicts a zero-shot type for each span, with confidence g_i , so we add it to the similarity score, $s_t(i) += \beta g_i \mathbb{1}[t = \text{label}_{\text{GLiNER}}(i)]$, with a small $\beta=0.05$. The fused head is the selected zero-shot operating point: it reaches 39.4 AMI end-to-end, ahead of every compared zero-shot system, while using no target labels (subsection IV-F). A per-class Gaussian mixture [29] is reported only as a typing ablation (Table VII).

G. Hyperparameters

Table I collects the configuration; all stochastic components use a single fixed seed (42).

H. Evaluation Protocol

We evaluate on the 13 datasets of subsection IV-A, each test split capped at 1000 sentences. Quality is AMI [35] (with macro- F_1 and accuracy), latency is the median (p50) per-sentence time over GPU-synchronised, warmed-up passes, and energy is measured with CodeCarbon [34] under the French grid carbon intensity; the full protocol and instrumentation are detailed in subsection IV-D and subsection IV-E. The code and the per-experiment configurations are released for reproducibility.

IV. EXPERIMENTS

A. Datasets

We evaluate on **13 evaluation sets** that span news, social media, spoken queries, encyclopedic text, biomedical abstracts and manufacturing literature, following the dataset selection of Genest et al. [2]. CrossNER [37] contributes five domain-specific sets, evaluated separately (artificial intelligence, literature, music, politics, science). The remaining eight are CoNLL-2003 [5], WNUT-17 [38], the MIT-Restaurant and MIT-Movie spoken-query corpora [39], FabNER [40], the BioNLP/JNLPBA-2004 biomedical task [41], and the GUM [42] and GENTLE [43] multi-genre corpora. Label granularity ranges from four coarse types in CoNLL-2003 to twelve fine-grained categories in FabNER, including opaque domain acronyms. Two datasets used by [2], GENIA [44] and i2b2, are license-gated and therefore not re-measured here; BioNLP/JNLPBA-2004 serves as our biomedical proxy. To homogenise evaluation cost across systems, we cap each test split at 1000 sentences (the full split is used when it is smaller). Table II summarises the benchmark.

TABLE II
THE 13 EVALUATION SETS. “TEST” IS THE NUMBER OF TEST SENTENCES USED (CAPPED AT 1000).

Dataset	Abbr.	Domain	Test
CrossNER-AI	AI	Encyclopedic (AI)	430
CrossNER-Literature	Lit	Encyclopedic (literature)	416
CrossNER-Music	Mus	Encyclopedic (music)	465
CrossNER-Politics	Pol	Encyclopedic (politics)	651
CrossNER-Science	Sci	Encyclopedic (science)	543
WNUT-17	WNUT	Social media	689
MIT-Restaurant	Rest	Restaurant search	1000
MIT-Movie	Movie	Movie trivia	1000
FabNER	Fab	Manufacturing	1000
BioNLP/JNLPBA-2004	Bio	Biomedical	1000
CoNLL-2003	CoNLL	News	1000
GUM	GUM	Multi-genre	1000
GENTLE	GEN	Multi-genre (challenge)	1000

B. Baselines

We compare OPENER against representative open-world NER systems run end-to-end on the same splits. GLiNER [6] is evaluated in its small, medium and large variants to trace a size/efficiency trade-off. GNER [8] is a generative tagger built on T5 [9]; we run the T5-base checkpoint. We further compare against OWNER [2], executed in its original environment. Instruction-tuned and few-shot large-language-model NER systems, namely UniversalNER [3], GoLLIE [4] and ChatIE [10], rely on 7B-parameter backbones [12] that do not fit our hardware budget even under 4-bit NF4 quantization [45]; for these we report the figures published by their authors rather than re-measuring them. As a generative model that *does* run on our hardware, we additionally evaluate Qwen2.5-1.5B-Instruct [16] in 4-bit NF4, prompted for JSON-formatted entities and scored under the same end-to-end protocol as the other systems.

C. Metrics

Our primary metric is the Adjusted Mutual Information (AMI) [35] between predicted and gold type assignments, following [2], complemented by macro-averaged F_1 and accuracy. Because open-world predictions need not share the gold label vocabulary, AMI is computed over the aligned set of mentions, which makes it well suited to comparing dynamically named types. Beyond quality, we report two efficiency axes: inference *speed*, as the median (p50) latency per sentence, and *energy*, as kilowatt-hours and grams of CO₂eq per run.

D. Evaluation Protocol

Predicted and gold mentions are aligned by exact character offsets. Following [2], an unmatched gold mention (a false negative) and an unmatched predicted mention (a false positive) are each assigned a distinct sentinel label before computing AMI, so that detection errors are penalised rather than ignored. We distinguish two protocols that must not be mixed in the same comparison. In the *typing-on-gold* protocol, the entity-typing component is applied to gold mention spans, which measures typing quality in isolation under perfect detection. In the *end-to-end* protocol, mentions are produced by the detector and the sentinel labels above are active, which is the setting comparable to the baselines. All runs use a single fixed random seed (42); we note this as a limitation, since we do not report variance over seeds.

E. Implementation Details

All experiments run on a single consumer-grade GPU with 6 GB of VRAM (CUDA 12.1, PyTorch 2.5.1 [46]). We use the HuggingFace Transformers library [47] for the baselines, sentence-transformers [19] for the Matryoshka embedder [17], [18], and scikit-learn [48] for the linear classifier, whose solver is LIBLINEAR [36]. Latency is measured with two warmup passes followed by timed passes with GPU synchronisation, reporting p50, p95 and p99 per sentence. Energy is measured with CodeCarbon [34] in offline mode using the French grid carbon intensity; when hardware power counters are unavailable, we fall back to a thermal-design-power estimate and flag the measurement method in the report. All systems are measured on the same machine. Because the laptop-class GPU thermally throttles under sustained load, per-sentence latency and per-run energy carry roughly $\pm 15\%$ run-to-run variance; we therefore read the per-system averages as indicative and do not over-interpret individual per-dataset cells. A controlled-temperature re-measurement of all systems in a single session is left to future work. The quality metrics, in contrast, are fully deterministic: with the fixed seed and the released model, no stage of the OPENER pipeline is stochastic at inference, so its AMI and F_1 reproduce exactly across re-runs (we verified identical CrossNER scores on an independent re-run), and only latency and energy fluctuate.

TABLE III

OPEN-WORLD NER, END-TO-END PROTOCOL. ADJUSTED MUTUAL INFORMATION ($\text{AMI} \times 100$, $\uparrow$). ABBREVIATIONS FOLLOW TABLE II; BOLD MARKS THE BEST VALUE PER COLUMN ACROSS ALL SYSTEMS. SYSTEMS ARE GROUPED BY SUPERVISION: *zero-shot* SYSTEMS USE NO TARGET-SIDE LABELS, WHEREAS *OPENER-Sup* FITS A LINEAR PROBE ON EACH TARGET’S TRAINING LABELS. AMONG THE ZERO-SHOT SYSTEMS, *OPENER-ZS* (HIGHLIGHTED) — LABEL-NAME PROTOTYPES REFINED TRANSDUCTIVELY AND FUSED WITH THE DETECTOR’S OWN ZERO-SHOT PREDICTIONS — OBTAINS THE BEST MEAN AMI (39.4), AHEAD OF GLiNER-L (38.9); ITS UN-REFINED NEAREST-CENTROID BASELINE, *OPENER-ZS* (BASE), REACHES 34.2, AND *OPENER-SUP* IS THE MOST ACCURATE OVERALL (40.2) AT THE COST OF TARGET LABELS. *OPENER-ZS* AND *OPENER-SUP* SHARE THE ERROR-DRIVEN HARD-NEGATIVE MINING EMBEDDER SELECTED IN TABLE VII, WHERE THE BUILD-UP FROM *OPENER-ZS* (BASE) IS REPORTED. $\dagger$ CoNLL-2003 IS IN-DOMAIN FOR OWNER (ITS TRAINING SOURCE) AND FOR OPENER (ITS CONTRASTIVE SOURCE) AND IS NOT BOLD AS A TRANSFER RESULT; THE BEST ZERO-SHOT SYSTEM ON CoNLL IS GNER. $\ddagger$ QWEN2.5-1.5B-INSTRUCT (4-BIT) IS A GENERATIVE LLM RUN ON OUR HARDWARE; OWING TO ITS GENERATION COST IT IS EVALUATED ON A 150-SENTENCE SUBSAMPLE PER SET, SO ITS ROW IS INDICATIVE AND IS NOT BOLD. THE TYPING-ON-GOLD COMPARISON IS REPORTED IN TABLE VIII.

Model	AI	Lit	Mus	Pol	Sci	WNUT	Rest	Movie	Fab	Bio	CoNLL	GUM	GEN	Avg
<i>Zero-shot (no target labels)</i>														
GLiNER-S	41.7	49.8	56.4	50.6	53.3	29.7	26.1	35.6	10.7	31.8	18.9	34.1	36.1	36.5
GLiNER-M	42.0	50.1	57.4	50.2	54.2	28.1	27.9	36.4	11.3	34.9	24.9	32.8	31.6	37.1
GLiNER-L	42.9	48.9	58.0	49.8	52.8	28.9	30.9	37.6	28.1	34.6	29.7	32.7	30.5	38.9
GNER	41.9	46.9	53.5	48.9	49.9	30.0	30.0	36.8	17.0	29.1	43.7	32.8	31.6	37.9
Qwen2.5-1.5B $\ddagger$	25.4	30.5	30.5	28.3	34.1	27.8	5.0	27.4	12.9	29.9	15.5	37.2	34.6	26.1
OWNER	43.9	44.0	46.6	50.9	50.3	22.3	7.6	24.0	18.7	26.5	50.3 $\dagger$	29.1	31.3	34.3
OPENER-ZS (base)	31.6	43.8	41.7	36.7	44.2	23.0	28.4	32.4	28.3	29.1	42.6 $\dagger$	31.5	31.2	34.2
OPENER-ZS	39.4	48.8	58.0	48.6	52.8	29.6	31.5	35.5	27.8	35.7	43.1$\dagger$	31.2	30.4	39.4
<i>Supervised (target labels)</i>														
OPENER-Sup	40.2	49.6	55.3	50.3	51.7	24.9	33.6	37.8	30.2	36.5	44.8 $\dagger$	33.7	34.2	40.2

F. Main Results

The tables below report the benchmark on all 13 sets, and Figure 2 plots the per-dataset end-to-end AMI of every system. OWNER is run in its native protocol [2]: a single model is trained once on the CoNLL-2003 source (a one-time cost of 88 minutes on our 6 GB GPU) and then applied *zero-shot* to every target set (cells marked $\S$). CoNLL-2003 is therefore in-domain for OWNER (marked $\dagger$) and is excluded when reading OWNER as a transfer system. One protocol asymmetry must be kept in mind when reading the typing scores: OPENER-Sup fits a lightweight linear classifier on each target’s training split (a supervised probe), whereas OWNER, GLiNER and GNER use no target-side labels. The two systems thus trade annotation for inference cost: OPENER needs target labels but stays cheap at test time, while OWNER needs none but pays a heavy per-sentence cost (Table IV). To close this asymmetry we also evaluate OPENER-ZS, a zero-shot variant that drops the supervised probe and types each mention against label-name prototypes, using no target labels. Its un-refined nearest-centroid baseline, OPENER-ZS (base), already matches the zero-shot OWNER baseline end-to-end (34.2 vs 34.3 mean AMI) and edges it on gold (44.4 vs 43.0, Table VIII), while keeping OPENER’s frugal inference profile (137 ms, 1.85 Wh vs 616 ms, 14.3 Wh). Two label-free refinements then build the full OPENER-ZS: a transductive k-means on the prototypes, and *fusing in the detector’s own zero-shot label predictions* — a signal the centroid otherwise discards — which together reach 39.4 end-to-end, the best of all compared zero-shot systems, ahead of GLiNER-L (38.9) and within 0.8 AMI of OPENER-Sup, all without any target label. For reference, the only generative LLM that fits our 6 GB GPU — Qwen2.5-1.5B-Instruct [16] in 4-bit, prompted for JSON-formatted entities — trails every dedicated system (26.1 mean AMI on a 150-sentence subsample, Table III) while being the slowest and most energy-hungry per sentence (5.1 s, 11.4 Wh; Table VI): a small open LLM pays on both axes at once. OPENER-Sup remains the stronger configuration (40.2 end-to-end, 62.5 on gold), so OPENER-ZS is best read as the frugal, annotation-free operating point of the same pipeline.

G. Ablations

We justify each architectural choice with a one-factor-at-a-time search. Starting from the default pipeline, we vary a single component while holding the others fixed, and keep the setting with the highest mean AMI. Among embedder variants, an error-driven *hard-negative mining* pass, fine-tuning the contrastive embedder on the entity pairs it most often confuses (e.g. *writer/person*, *album/band*, *country/location*), mixed with correctly-typed mentions for diversity, raises typing-on-gold AMI from 54.0 to 60.1; scaling the mined triplets (3000 $\rightarrow$ 8000) and epochs (2 $\rightarrow$ 3) lifts it further to 62.5 (+8.5 over the contrastive embedder, better on 12 of 13 sets), our selected configuration. Table VII reports this search; the protocol comparison between typing-on-gold and end-to-end is discussed alongside the main results. The remaining axes confirm the rest of the pipeline: among frozen off-the-shelf base encoders, Nomic v1.5 is the most discriminative for entity typing (25.8 AMI, ahead of e5-base 25.3, mxbaai 24.4, MPNet 24.1 and BGE 23.6) and is selected; even so, frozen embeddings are only weakly discriminative, so the contrastive step is what makes the space usable (+28.2); the detector trades quality for cost (GLiNER-S $\rightarrow$ L: 37.7 $\rightarrow$ 40.2 AMI at 51 $\rightarrow$ 143 ms end-to-end); and for typing a balanced linear SVM edges out a per-class GMM and logistic regression




Fig. 2. End-to-end AMI per dataset (Table III). *Zero-shot* systems are drawn solid; OPENER-Sup (the *supervised* upper bound, which uses target labels) is the dashed red line. Among the zero-shot systems OPENER-ZS (thick gold) and GLiNER-L track the front of the pack, while OWNER (pink) collapses on the spoken-query corpora (MIT-Restaurant). The small LLM baseline Qwen2.5-1.5B (4-bit, violet) is zero-shot like the other solid lines and trails the pack. † CoNLL-2003 (shaded) is in-domain for OWNER and OPENER; ‡ Qwen is evaluated on a 150-sentence subsample per set.

TABLE IV

INFERENCE LATENCY. MEDIAN PER-SENTENCE LATENCY IN MILLISECONDS ($\downarrow$), END-TO-END. ABBREVIATIONS FOLLOW TABLE II; BEST PER COLUMN IN BOLD. § OWNER DOES NOT EXPOSE A PER-SENTENCE CALL: ITS FIGURE IS THE TOTAL INFERENCE WALL-CLOCK DIVIDED BY THE NUMBER OF SENTENCES (AN AMORTISED MEAN, NOT A TRUE P50), AND EXCLUDES THE ONE-TIME 88-MIN TRAINING ON CoNLL-2003. CoNLL (†) IS OWNER’S TRAINING SOURCE; ITS LATENCY COMES FROM A SEPARATE INFERENCE-ONLY LOAD-AND-TEST RUN ON THE CoNLL TEST SET (THE TRAINED MODEL IS RELOADED, THEN RUN LIKE THE TRANSFER TARGETS), SO IT IS COMPARABLE TO THE OTHER COLUMNS; IT IS IN-DOMAIN (MARKED †) AND, AS IN THE AMI TABLES, INCLUDED IN THE 13-SET AVERAGE. OWNER IS AN ORDER OF MAGNITUDE SLOWER THAN GLiNER BECAUSE IT RE-ENCODS EVERY MENTION AND CLUSTERS AT INFERENCE TIME. OPENER-ZS IS THE ZERO-SHOT OPENER VARIANT (LABEL-NAME NEAREST-CENTROID TYPING); ITS HEAD IS A SINGLE COSINE COMPARISON, SO IT REPORTS A GENUINE PER-SENTENCE P50 THAT TRACKS OPENER’S AND STAYS FAR BELOW OWNER’S. ‡ QWEN2.5-1.5B-INSTRUCT (4-BIT) IS THE SMALL GENERATIVE LLM BASELINE (TABLE VI); ITS AUTOREGRESSIVE DECODING MAKES IT THE SLOWEST SYSTEM, ON A 150-SENTENCE SUBSAMPLE PER SET.

Model	AI	Lit	Mus	Pol	Sci	WNUT	Rest	Movie	Fab	Bio	CoNLL	GUM	GEN	Avg
<i>Zero-shot (no target labels)</i>														
GLiNER-S	21	22	21	21	21	20	19	20	20	22	20	21	21	21
GLiNER-M	36	36	37	38	39	39	38	40	41	42	44	46	45	40
GLiNER-L	144	149	153	149	155	137	132	145	147	143	131	141	137	143
GNER	3431	5408	7461	6472	7110	2906	1610	3344	4310	5034	2914	3435	1500	4226
Qwen2.5-1.5B‡	4857	6757	9396	7700	8261	3553	2142	5014	2921	4737	2260	4265	3806	5051
OWNER§	500	712	895	920	757	311	281	532	438	558	719†	759	626	616
OPENER-ZS (base)	109	135	156	172	175	136	127	137	133	136	117	127	124	137
OPENER-ZS	218	254	291	277	289	185	173	205	84	98	92	104	97	182
<i>Supervised (target labels)</i>														
OPENER-Sup	222	271	293	159	132	100	92	98	104	108	89	100	94	143

(62.5 vs 56.1 vs 55.6). Replacing the supervised typing head with a label-name nearest-centroid removes target supervision entirely, at a cost of 18.1 AMI (62.5 $\rightarrow$ 44.4); this base variant, OPENER-ZS (base), still surpasses the zero-shot OWNER baseline (43.0, Table VIII) while fitting in 293ms instead of 3.5s, making it the frugal choice when no target labels are available. A label-free *transductive* refinement of the prototypes — spherical k-means seeded by the label names and run once on the unlabelled test mentions — recovers 7.0 AMI on gold mentions (44.4 $\rightarrow$ 51.4, Table VII) and 2.6 end-to-end (34.2 $\rightarrow$ 36.8, above OWNER’s 34.3), widening OPENER-ZS’s margin over OWNER while still using no target labels; this is a transductive rather than inductive setting, as it exploits the unlabelled test distribution. We further probed whether the zero-shot head could be improved by aligning entity mentions and label *names* in a shared space, trained on the large label vocabulary of Pile-NER [3] ($\approx$ 4.6k types) with an entity $\leftrightarrow$ label-name contrastive objective (Table IX). This produces a *strictly* domain-agnostic embedder (unlike the selected hard-mining embedder, it never sees any target-side data), yet it does not improve mean AMI (42.2 vs 44.4): the Pile-NER vocabulary lifts macro- F_1 (+3.8) and helps encyclopedic domains (CrossNER-Politics +14.2, -Science +8.6) but hurts specialised schemas (MIT-Restaurant -15.9, FabNER -11.8, BioNLP -11.8). A second

TABLE V

ENERGY. ENERGY PER RUN IN WATT-HOURS ($\downarrow$), END-TO-END. ABBREVIATIONS FOLLOW TABLE II; BEST PER COLUMN IN BOLD. [§] OWNER IS MEASURED AT INFERENCE ONLY (ZERO-SHOT TRANSFER); ITS ONE-TIME CONLL-2003 TRAINING (88 MIN) IS AMORTISED ACROSS ALL TARGETS AND NOT CHARGED PER RUN. CONLL ([†]) IS OWNER’S TRAINING SOURCE; ITS ENERGY COMES FROM A SEPARATE INFERENCE-ONLY LOAD-AND-TEST RUN ON THE CONLL TEST SET (22.0 WH), COMPARABLE TO THE OTHER COLUMNS; IT IS IN-DOMAIN (MARKED [†]) AND INCLUDED IN THE 13-SET AVERAGE.

OWNER REMAINS ENERGY-HEAVY BECAUSE EACH SENTENCE TRIGGERS PER-MENTION ENCODING AND CLUSTERING. OPENER-ZS IS THE ZERO-SHOT OPENER VARIANT; ITS PER-RUN ENERGY TRACKS OPENER’S (THE COSINE TYPING HEAD IS NEGLIGIBLE) AND STAYS AN ORDER OF MAGNITUDE BELOW OWNER’S. [‡] QWEN2.5-1.5B-INSTRUCT (4-BIT), THE SMALL GENERATIVE LLM BASELINE (ON A 150-SENTENCE SUBSAMPLE PER SET), IS AN ORDER OF MAGNITUDE MORE ENERGY-HUNGRY THAN OPENER.

Model	AI	Lit	Mus	Pol	Sci	WNUT	Rest	Movie	Fab	Bio	CoNLL	GUM	GEN	Avg
<i>Zero-shot (no target labels)</i>														
GLiNER-S	0.19	0.17	0.20	0.27	0.22	0.27	0.35	0.39	0.40	0.42	0.37	0.41	0.40	0.31
GLiNER-M	0.31	0.29	0.33	0.48	0.40	0.50	0.66	0.76	0.77	0.79	0.69	0.82	0.75	0.58
GLiNER-L	0.68	0.67	0.77	1.04	0.91	1.01	1.37	1.51	1.54	1.49	1.38	1.52	1.43	1.18
GNER	17.13	24.28	39.75	50.88	44.76	20.60	17.02	37.17	49.11	63.50	45.22	38.69	26.50	36.51
Qwen2.5-1.5B [‡]	12.7	15.1	17.5	18.4	18.0	7.9	4.6	9.5	7.0	11.1	7.3	10.2	9.5	11.4
OWNER [§]	6.6	9.0	12.7	18.3	12.6	6.5	8.6	16.3	13.4	17.1	22.0 [†]	23.2	19.1	14.3
OPENER-ZS (base)	0.95	1.06	1.37	1.97	1.69	1.52	2.07	2.28	2.15	2.30	2.10	2.33	2.26	1.85
OPENER-ZS	1.14	1.23	1.58	2.08	1.82	1.41	1.82	2.23	1.62	1.87	1.63	1.90	1.79	1.70
<i>Supervised (target labels)</i>														
OPENER-Sup	1.10	1.26	0.87	1.76	1.41	1.31	1.75	1.87	1.96	1.97	1.73	1.91	1.78	1.59

TABLE VI

SUMMARY: QUALITY VERSUS EFFICIENCY, AVERAGED OVER THE 13 DATASETS. AMI ($\times 100$, $\uparrow$); MEDIAN PER-SENTENCE LATENCY (MS), ENERGY (WH) AND CARBON (GCO₂EQ) PER RUN ($\downarrow$); AND PARAMETER COUNT. [§] OWNER IS ZERO-SHOT (TRAINED ONCE ON CONLL-2003 FOR 88 MIN, THEN APPLIED TO EVERY TARGET); ITS LATENCY IS AN AMORTISED WALL-CLOCK MEAN (TABLE IV); AMI, LATENCY AND ENERGY ARE ALL 13-SET MEANS, OWNER’S IN-DOMAIN CONLL INFERENCE COST BEING MEASURED BY A SEPARATE LOAD-AND-TEST RUN (MARKED [†] IN TABLE IV, TABLE V) WHILE ITS ONE-TIME 88-MIN TRAINING IS AMORTISED AND NOT CHARGED PER RUN. END-TO-END OPENER PAIRS THE GLiNER-L DETECTOR (330M) WITH THE 137M EMBEDDER, HENCE 467M; ON GOLD MENTIONS THE DETECTOR IS NOT USED (137M). END-TO-END OWNER LIKewise SUMS A DEBERTA-V3-BASE DETECTOR (≈ 184 M) AND A BERT-BASE TYPING ENCODER (110M), HENCE ≈ 294 M; GLiNER-S/M/L SIZES ARE FROM THE PROJECT NOTES AND UNVERIFIED. OPENER-ZS (NO TARGET LABELS) KEEPS OPENER’S 467M FOOTPRINT AND FRUGAL PER-SENTENCE COST; EVEN ITS BASE NEAREST-CENTROID, OPENER-ZS (BASE), MATCHES OWNER’S ZERO-SHOT QUALITY (34.2 VS 34.3 AMI) AT 137 MS AND 1.85 WH, A FRACTION OF OWNER’S 616 MS / 14.3 WH. [‡] QWEN2.5-1.5B-INSTRUCT IN 4-BIT, A GENERATIVE LLM THAT FITS OUR 6 GB GPU: IT IS THE WEAKEST AND, PER SENTENCE, THE SLOWEST AND MOST ENERGY-HUNGRY SYSTEM; ITS AMI IS ON A 150-SENTENCE SUBSAMPLE PER SET (INDICATIVE).

Model	Params	AMI	p50 (ms)	Energy (Wh)	CO ₂ (g)
<i>Zero-shot (no target labels)</i>					
GLiNER-S	50M	36.5	21	0.31	0.02
GLiNER-M	200M	37.1	40	0.58	0.03
GLiNER-L	330M	38.9	143	1.18	0.07
GNER	220M	37.9	4226	36.51	2.05
Qwen2.5-1.5B (4-bit) [‡]	1.5B	26.1	5051	11.4	0.60
OWNER [§]	294M	34.3	616	14.3	0.74
OPENER-ZS (base)	467M	34.2	137	1.85	0.10
OPENER-ZS	467M	39.4	182	1.70	0.10
<i>Supervised (target labels)</i>					
OPENER-Sup	467M	40.2	143	1.59	0.09

label-name hard-mining pass degrades it further (39.7 AMI): Pile-NER’s GPT-generated types include many near-synonyms (e.g. *person/per*, *location/loc*), so mining “confusions” between them manufactures negatives that pull apart labels that should stay close. We therefore retain the target-tuned hard-mining embedder for OPENER-ZS and report the Pile-NER variants as a negative ablation. A separate efficiency axis emerges in the *training* cost (Table VII, Fit): per-sentence inference is governed by the detector alone (truncating the Matryoshka dimension or swapping the classifier leaves it unchanged), whereas fitting the typing head is $7\times$ cheaper at dimension 64 than at 768 (for only a 4.6-point AMI drop, $62.5 \rightarrow 57.9$) and $4.5\times$ cheaper for balanced logistic regression than for the linear SVM, a speed/quality knob orthogonal to inference. To isolate the entity-typing component itself, Table VIII compares OPENER against OWNER on gold mentions, where detection errors are removed.

TABLE VII

OPENER ARCHITECTURE SEARCH. ONE COMPONENT IS VARIED AT A TIME AROUND THE DEFAULT PIPELINE (**BOLD**). AMI AND MACRO- F_1 ($\times 100$, $\uparrow$); PER-RUN LATENCY, ENERGY AND CARBON ($\downarrow$). * ENTITY-EMBEDDER ROWS ARE TYPING-ON-GOLD OVER ALL 13 SETS. THE FIRST FIVE ROWS COMPARE FROZEN, OFF-THE-SHELF BASE ENCODERS UNDER THIS PROTOCOL (NO FINE-TUNING, SO FIT = 0 AND THE DEPLOYED PER-SENTENCE COST, “–”, IS NOT MEASURED FOR THE NON-SELECTED ONES); NOMIC v1.5 LEADS (25.8 AMI, JUST AHEAD OF E5-BASE AT 25.3) AND IS SELECTED AS THE BASE, WHICH THE ROWS BELOW THEN FINE-TUNE. *Hard-negative mining* FINE-TUNES THE CONTRASTIVE EMBEDDER A *second* TIME ON THE MENTION PAIRS IT MOST OFTEN CONFUSES (HARD NEGATIVES IN THE SENSE OF [20]), MIXED WITH CORRECTLY-TYPED MENTIONS FOR DIVERSITY (65% HARD NEGATIVES; THE TWO ROWS USE 3000 TRIPLETS / 2 EPOCHS AND, SELECTED, 8000 TRIPLETS / 3 EPOCHS); ERRORS ARE MINED ON EACH TRAINING SPLIT BY CROSS-VALIDATION, SO NO TEST LABEL IS SEEN. $\dagger$ ENTITY-TYPING SWEEP ON ALL 13 SETS (TYPING-ON-GOLD) WITH THE SELECTED HARD-MINING EMBEDDER, SO ITS LINEARSVC (BALANCED) ROW EQUALS THE SELECTED ENTITY-EMBEDDER ROW; $\S$ DIMENSION SWEEP ON ALL 13 SETS (TYPING-ON-GOLD) WITH THE SELECTED HARD-MINING EMBEDDER, TRUNCATING THE MATRYOSHKA REPRESENTATION AFTER ENCODING, SO ITS 768 ROW EQUALS THE SELECTED EMBEDDER AND TYPING ROWS. EFFICIENCY (P50 LATENCY, ENERGY, CO₂) FOLLOWS THE PROTOCOL OF EACH AXIS. ON THE MENTION-DETECTOR AXIS IT IS THE DEPLOYED END-TO-END PER-SENTENCE COST AND VARIES WITH THE DETECTOR (51 $\rightarrow$ 143 ms). ON THE EMBEDDER, DIMENSION AND TYPING AXES (TYPING-ON-GOLD, DETECTION BYPASSED) IT IS THE EMBEDDER-PLUS-TYPING INFERENCE COST MEASURED ON THE 13 TEST SETS: IT IS CONSTANT AT 42 ms / 0.63 Wh / 0.04 g BECAUSE THESE CONFIGURATIONS SHARE THE SAME 137M EMBEDDER FORWARD PASS — TRUNCATING THE MATRYOSHKA DIMENSION SLICES THE STORED VECTOR AFTER ENCODING, AND SWAPPING THE LINEAR CLASSIFIER IS NEGLIGIBLE. PER-ROW MEASUREMENT CONFIRMED THIS CONSTANCY, THE RESIDUAL RUN-TO-RUN SPREAD (34 $\rightarrow$ 71 ms ON THE EMBEDDER AXIS) BEING THERMAL THROTTLING ($\pm 15\%$). FIT (MS) IS THE TYPING-HEAD TRAINING TIME, MEASURED ON EACH TARGET’S TRAINING SPLIT AND AVERAGED OVER THE 13 SETS (MEDIAN OF THREE REPEATS): IT IS THE COST THAT *does* VARY, WITH THE MATRYOSHKA DIMENSION (299 $\rightarrow$ 2176 ms FROM 64 TO 768) AND THE CLASSIFIER (485 ms FOR BALANCED LOGISTIC REGRESSION VS. 2217 ms FOR THE LINEAR SVM), AND IS SHOWN ON THOSE TWO AXES. IT IS 0 ON THE DETECTOR AND EMBEDDER AXES: THE VARIED COMPONENT ADDS NO PER-DEPLOYMENT TRAINING (DETECTORS ARE FROZEN/OFF-THE-SHELF AND THE EMBEDDER IS PRE-TRAINED), THE TYPING-HEAD FIT (≈ 2.2 s WITH THE DEFAULT BALANCED SVM@768) BEING CHARGED ON THE TYPING AXIS. THE EMBEDDER’S OWN OFFLINE FINE-TUNING (NONE FOR FROZEN NOMIC; ≈ 4 h FOR THE SELECTED HARD-MINING RUN) IS A SEPARATE ONE-TIME COST. $\P$ THE *nearest-centroid* (*zero-shot*) TYPING HEAD IS THE ONLY ONE THAT USES *no target labels*: IT ASSIGNS EACH MENTION TO THE NEAREST LABEL-NAME PROTOTYPE (TABLE VIII); ITS FIT COLUMN IS THE ONE-OFF PROTOTYPE-EMBEDDING COST (293 ms), NOT A TRAINING PASS ON TARGET LABELS, WHICH IS WHY IT IS AN ORDER OF MAGNITUDE BELOW THE SUPERVISED HEADS WHILE REMOVING THE SUPERVISION OPENER OTHERWISE NEEDS.

Configuration	AMI	F ₁	Fit (ms)	p50 (ms)	En. (Wh)	CO ₂ (g)
<i>Mention detector</i>						
GLiNER-S	37.7	28.8	0.0	51	0.73	0.04
GLiNER-M	38.0	28.7	0.0	70	1.01	0.06
GLiNER-L	40.2	30.5	0.0	143	1.59	0.09
<i>Entity embedder*</i>						
frozen bge-base-en-v1.5 [22]	23.6	41.9	0	–	–	–
frozen all-mpnet-base-v2 [23]	24.1	42.6	0	–	–	–
frozen mxbae-embed-large-v1 [24]	24.4	42.5	0	–	–	–
frozen e5-base-v2 [21]	25.3	43.4	0	–	–	–
frozen Nomic v1.5 (selected base)	25.8	43.9	0	42	0.63	0.04
+ contrastive (Triplet, CoNLL, 3 ep.)	54.0	63.3	0	42	0.63	0.04
+ hard-negative mining (2 ep., 3k tr.)	60.1	68.8	0	42	0.63	0.04
+ hard-negative mining (3 ep., 8k tr.)	62.5	71.8	0	42	0.63	0.04
<i>Matryoshka dimension[§]</i>						
64	57.9	67.7	299	42	0.63	0.04
128	59.9	69.7	562	42	0.63	0.04
256	61.2	70.6	926	42	0.63	0.04
512	62.0	71.2	1556	42	0.63	0.04
768	62.5	71.8	2176	42	0.63	0.04
<i>Entity typing[†]</i>						
GMM (per-class)	56.1	65.3	527	42	0.63	0.04
LogReg	55.6	53.5	546	42	0.63	0.04
LogReg (balanced)	57.8	67.5	485	42	0.63	0.04
LinearSVC	61.7	66.5	2041	42	0.63	0.04
LinearSVC (balanced)	62.5	71.8	2217	42	0.63	0.04
Nearest centroid (zero-shot) [¶]	44.4	46.8	293	42	0.63	0.04
+ transductive refine [¶]	51.4	48.5	293	42	0.63	0.04

TABLE VIII

ENTITY TYPING ON GOLD MENTIONS: OPENER VS OWNER (AMI $\times 100$, $\uparrow$). DETECTION IS BYPASSED, ISOLATING THE TYPING COMPONENT. ABBREVIATIONS FOLLOW TABLE II; BOLD MARKS THE BEST VALUE PER COLUMN. SYSTEMS ARE GROUPED BY SUPERVISION. AMONG THE *zero-shot* SYSTEMS (NO TARGET LABELS), OPENER-ZS — LABEL-NAME PROTOTYPES REFINED BY A LABEL-FREE *transductive* K-MEANS (SPHERICAL, SEEDED BY THE LABEL NAMES, RUN ONCE ON THE UNLABELLED TEST MENTIONS; THE DETECTOR FUSION OF TABLE III IS END-TO-END-ONLY AND INACTIVE HERE) — REACHES 51.4 AMI AND BEATS OWNER ON 11 OF 13 SETS; ITS UN-REFINED NEAREST-CENTROID BASELINE, OPENER-ZS (BASE), ALREADY EDGES OWNER ON AVERAGE (44.4 VS 43.0) AT A FRACTION OF ITS INFERENCE COST (TABLE IV, TABLE V). OWNER IS ZERO-SHOT AS WELL (CLUSTERING AFTER TRANSFER FROM CONLL-2003). OPENER-SUP (THE *supervised* PROBE) FITS A LINEAR CLASSIFIER ON EACH TARGET’S TRAINING LABELS AND LEADS ON ALL 13 SETS (62.5), THE UPPER BOUND OF THE PIPELINE. BOTH SHARE THE ERROR-DRIVEN HARD-NEGATIVE MINING EMBEDDER SELECTED IN TABLE VII. $\dagger$ CONLL-2003 IS IN-DOMAIN FOR OWNER (ITS TRAINING SOURCE) AND FOR OPENER (ITS CONTRASTIVE SOURCE); IT IS NOT A TRANSFER RESULT AND IS NOT BOLD.

Model	AI	Lit	Mus	Pol	Sci	WNUT	Rest	Movie	Fab	Bio	CoNLL	GUM	GEN	Avg
<i>Zero-shot (no target labels)</i>														
OWNER	55.7	54.3	59.8	63.2	63.1	30.5	29.3	31.8	31.9	29.2	52.5 $\dagger$	30.0	27.2	43.0
OPENER-ZS (base)	41.4	61.4	55.2	50.7	58.0	33.0	42.6	18.4	35.6	54.1	65.9 $\dagger$	31.1	30.2	44.4
OPENER-ZS	46.4	65.0	68.6	66.5	57.3	31.8	52.1	45.8	37.5	49.5	71.0 $\dagger$	38.6	37.5	51.4
<i>Supervised (target labels)</i>														
OPENER-Sup	57.6	67.0	71.8	74.8	68.9	38.6	63.0	66.9	59.2	71.2	71.5 $\dagger$	50.3	51.5	62.5

TABLE IX

ZERO-SHOT TYPING: EFFECT OF THE CONTRASTIVE EMBEDDER (OPENER-ZS, TYPING-ON-GOLD, MEANS OVER THE 13 SETS). THE NEAREST LABEL-NAME CENTROID HEAD IS HELD FIXED; ONLY THE EMBEDDER CHANGES. AMI, MACRO- F_1 AND ACCURACY ($\times 100$, $\uparrow$); BEST PER COLUMN IN BOLD. THE SELECTED HARD-NEGATIVE-MINING EMBEDDER IS FINE-TUNED ON THE TARGETS’ *training* SPANS (ENTITY-ENTITY), WHEREAS THE PILE-NER [3] EMBEDDERS ARE TRAINED ONLY ON PILE-NER ENTITY $\leftrightarrow$ LABEL-NAME PAIRS AND NEVER SEE ANY TARGET DATA, I.E. A STRICTER, FULLY DOMAIN-AGNOSTIC ZERO-SHOT. PILE-NER’S ≈ 4.6 K-TYPE VOCABULARY RAISES F_1 BUT NOT AMI, AND A SECOND LABEL-NAME HARD-MINING PASS DEGRADES BOTH BECAUSE PILE-NER’S GPT-GENERATED TYPES CONTAIN MANY NEAR-SYNONYMS (E.G. *person/per*) WHOSE MINED “CONFUSIONS” ARE HARMFUL; WE KEEP THE TARGET-TUNED EMBEDDER AND REPORT PILE-NER AS A NEGATIVE ABLATION. END-TO-END, THE PILE-NER VARIANT TIES THE SELECTED ONE (33.9 VS 34.2 AMI).

Embedder	Training data	AMI	F_1	Acc
hard-neg. mining (selected)	CoNLL + targets’ train	44.4	46.8	53.6
Pile-NER (entity $\leftrightarrow$ label)	Pile-NER only	42.2	50.6	53.9
+ label-name hard mining	Pile-NER only	39.7	41.4	44.7

V. CONCLUSION

We presented OPENER, an open-world NER pipeline built from off-the-shelf components — a frozen detector, a pretrained Matryoshka embedder sharpened by a light contrastive fine-tuning with error-driven hard-negative mining, and a swappable typing head — with no encoder trained from scratch. On gold mentions the contrastive space is highly discriminative, and a balanced linear probe, OPENER-Sup, is the most accurate system in our benchmark, leading on all 13 sets and surpassing a zero-shot transfer of OWNER (62.5 vs 43.0 AMI); it also attains the best end-to-end AMI of the compared systems (40.2), at the cost of target labels. Removing that supervision, our zero-shot head OPENER-ZS — label-name prototypes refined transductively and fused with the detector’s own predictions — is the best of the compared zero-shot systems end-to-end (39.4), ahead of GLiNER-L, GNER and OWNER, at one to two orders of magnitude lower energy than the trained-encoder and generative baselines.

Two findings carry beyond the specific system. First, an open-world typing head need not train its own encoder: a general-purpose embedding, once sharpened by a light contrastive step, is already discriminative enough to type entities, and the cost that does matter is fitting the cheap typing head, not the embedder. Second, the three-axis evaluation locates the open-world bottleneck in *detection* rather than typing — end-to-end quality tracks the detector’s recall on specialised domains — and exposes efficiency gaps that an accuracy-only comparison would hide.

The approach has clear limits. End-to-end quality is capped by detector recall on specialised domains, the shared bottleneck, not by the typing head. Supervised typing needs target-domain labels, and while OPENER-ZS removes them at typing time it depends on the quality of the label names and, in its transductive form, on access to the unlabelled test mentions; the inductive zero-shot head is correspondingly weaker. Finally, all results use a single random seed, and energy is measured on one thermally-throttling consumer GPU, so per-run figures carry run-to-run variance and are read as averages rather than precise points.

Future work includes improving mention detection on specialised domains to lift the end-to-end ceiling, an inductive zero-shot head that does not rely on the test distribution, a visualisation of the contrastive type geometry (e.g. UMAP or t-SNE), and extending the decoupled detect-then-type design beyond NER to entity linking and relation extraction.

ACKNOWLEDGMENTS

In accordance with the symposium policy on the use of generative AI, we disclose that a general-purpose large-language-model coding assistant was used during this work. Its use was limited to engineering and editorial support: scaffolding and debugging experiment scripts, drafting and copy-editing the manuscript, and assisting with exploratory data analysis. The research questions, the experimental design, the choice of baselines and datasets, the execution of all experiments, and the interpretation of the results are the authors’ own. All reported numbers were produced by the released code and verified by the authors, who take full responsibility for the scientific content and the final wording of the paper.

REFERENCES

- [1] N. T. H. Nguyen, M. Miwa, and S. Ananiadou, “Span-based named entity recognition by generating and compressing information,” in *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, 2023, pp. 1984–1996.
- [2] P.-Y. Genest, P.-E. Portier, E. Egyed-Zsigmond, and M. Lovisetto, “OWNER: Toward unsupervised open-world named entity recognition,” *IEEE Access*, vol. 13, pp. 50 077–50 105, 2025.
- [3] W. Zhou, S. Zhang, Y. Gu, M. Chen, and H. Poon, “UniversalNER: Targeted distillation from large language models for open named entity recognition,” in *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.
- [4] O. Sainz, I. García-Ferrero, R. Agerri, O. Lopez de Lacalle, G. Rigau, and E. Agirre, “GoLLIE: Annotation guidelines improve zero-shot information-extraction,” in *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.
- [5] E. F. Tjong Kim Sang and F. De Meulder, “Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition,” in *Proceedings of the Seventh Conference on Natural Language Learning (CoNLL)*, 2003.
- [6] U. Zaratiana, N. Tomeh, P. Holat, and T. Charnois, “GLiNER: Generalist model for named entity recognition using bidirectional transformer,” in *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT), Volume 1: Long Papers*. Association for Computational Linguistics, 2024, pp. 5364–5376.
- [7] P. He, J. Gao, and W. Chen, “DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing,” in *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.
- [8] Y. Ding, J. Li, P. Wang, Z. Tang, B. Yan, and M. Zhang, “Rethinking negative instances for generative named entity recognition,” in *Findings of the Association for Computational Linguistics: ACL 2024*, 2024, pp. 3461–3475.
- [9] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, “Exploring the limits of transfer learning with a unified text-to-text transformer,” *Journal of Machine Learning Research*, vol. 21, pp. 1–67, 2020.
- [10] X. Wei, X. Cui, N. Cheng, X. Wang, X. Zhang, S. Huang, P. Xie, J. Xu, Y. Chen, M. Zhang, Y. Jiang, and W. Han, “ChatIE: Zero-shot information extraction via chatting with ChatGPT,” *arXiv preprint arXiv:2302.10205*, 2023.
- [11] R. Cai, J. Lu, Z. Chen, B. Xu, and Z. Hao, “Handling missing entities in zero-shot named entity recognition: Integrated recall and retrieval augmentation,” in *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*, 2025, pp. 10 790–10 802.
- [12] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, A. Rodriguez, A. Joulin, E. Grave, and G. Lample, “LLaMA: Open and efficient foundation language models,” *arXiv preprint arXiv:2302.13971*, 2023.
- [13] Y. Tang, R. Hasan, and T. Runkler, “FSPONER: Few-shot prompt optimization for named entity recognition in domain-specific scenarios,” in *Proceedings of the 27th European Conference on Artificial Intelligence (ECAI)*, 2024, arXiv:2407.08035.
- [14] S. Zhang, B. Cao, and J. Fan, “KCL: Few-shot named entity recognition with knowledge graph and contrastive learning,” in *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING)*. ELRA Language Resource Association, 2024, pp. 9681–9692.
- [15] S. S. Das, A. Katiyar, R. J. Passonneau, and R. Zhang, “CONTAiNER: Few-shot named entity recognition via contrastive learning,” in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022.
- [16] Qwen Team, “Qwen2.5 technical report,” *arXiv preprint arXiv:2412.15115*, 2025.
- [17] Z. Nussbaum, J. X. Morris, B. Duderstadt, and A. Mulyar, “Nomic embed: Training a reproducible long context text embedder,” *Transactions on Machine Learning Research (TMLR)*, 2025, published in TMLR 02/2025. OpenReview: <https://openreview.net/forum?id=IPmzyQSiQE>.
- [18] A. Kusupati, G. Bhatt, A. Rege, M. Wallingford, A. Sinha, V. Ramanujan, W. Howard-Snyder, K. Chen, S. Kakade, P. Jain, and A. Farhadi, “Matryoshka representation learning,” in *Advances in Neural Information Processing Systems 35 (NeurIPS 2022)*, 2022.
- [19] N. Reimers and I. Gurevych, “Sentence-BERT: Sentence embeddings using siamese BERT-networks,” in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2019.
- [20] F. Schroff, D. Kalenichenko, and J. Philbin, “FaceNet: A unified embedding for face recognition and clustering,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015.
- [21] L. Wang, N. Yang, X. Huang, B. Jiao, L. Yang, D. Jiang, R. Majumder, and F. Wei, “Text embeddings by weakly-supervised contrastive pre-training,” *arXiv preprint arXiv:2212.03533*, 2022.
- [22] S. Xiao, Z. Liu, P. Zhang, N. Muennighoff, D. Lian, and J.-Y. Nie, “C-Pack: Packed resources for general chinese embeddings,” in *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, 2024.
- [23] K. Song, X. Tan, T. Qin, J. Lu, and T.-Y. Liu, “MPNet: Masked and permuted pre-training for language understanding,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.
- [24] X. Li and J. Li, “AoE: Angle-optimized embeddings for semantic textual similarity,” in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.
- [25] G. Wang, C. Li, W. Wang, Y. Zhang, D. Shen, X. Zhang, R. Henao, and L. Carin, “Joint embedding of words and labels for text classification,” in *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2018, pp. 2321–2331.
- [26] Y. Zhang, W. Chen, and L. Ma, “Contrastive learning with Gaussian embeddings and self-attention for few-shot named entity recognition,” *Applied Sciences*, vol. 15, no. 21, p. 11819, 2025.
- [27] X. Hu, Y. Jiang, A. Liu, Z. Huang, P. Xie, F. Huang, L. Wen, and P. S. Yu, “Entity-to-text based data augmentation for various named entity recognition tasks,” in *Findings of the Association for Computational Linguistics: ACL 2023*, 2023, pp. 9072–9087.
- [28] Y. Abbahaddou, F. D. Malliaros, J. F. Lutzeyer, A. M. Aboussalah, and M. Vazirgiannis, “Gaussian mixture models based augmentation enhances GNN generalization,” 2024, arXiv:2411.08638 [cs.LG], preprint.
- [29] D. A. Reynolds, “Gaussian mixture models,” in *Encyclopedia of Biometrics*, S. Z. Li and A. K. Jain, Eds. Springer US, 2009, pp. 659–663.
- [30] A. P. Dempster, N. M. Laird, and D. B. Rubin, “Maximum likelihood from incomplete data via the EM algorithm,” *Journal of the Royal Statistical Society: Series B (Methodological)*, vol. 39, no. 1, pp. 1–22, 1977.

- [31] E. Strubell, A. Ganesh, and A. McCallum, “Energy and policy considerations for deep learning in NLP,” in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2019.
- [32] R. Schwartz, J. Dodge, N. A. Smith, and O. Etzioni, “Green AI,” *Communications of the ACM*, vol. 63, no. 12, pp. 54–63, 2020.
- [33] D. Patterson, J. Gonzalez, U. Hölzle, Q. Le, C. Liang, L.-M. Munguia, D. Rothchild, D. So, M. Texier, and J. Dean, “The carbon footprint of machine learning training will plateau, then shrink,” *Computer*, vol. 55, no. 7, pp. 18–28, 2022.
- [34] A. Lacoste, A. Luccioni, V. Schmidt, and T. Dandres, “Quantifying the carbon emissions of machine learning,” *arXiv preprint arXiv:1910.09700*, 2019.
- [35] N. X. Vinh, J. Epps, and J. Bailey, “Information theoretic measures for clusterings comparison: Variants, properties, normalization and correction for chance,” *Journal of Machine Learning Research*, vol. 11, pp. 2837–2854, 2010.
- [36] R.-E. Fan, K.-W. Chang, C.-J. Hsieh, X.-R. Wang, and C.-J. Lin, “LIBLINEAR: A library for large linear classification,” *Journal of Machine Learning Research*, vol. 9, pp. 1871–1874, 2008.
- [37] Z. Liu, Y. Xu, T. Yu, W. Dai, Z. Ji, S. Cahyawijaya, A. Madotto, and P. Fung, “CrossNER: Evaluating cross-domain named entity recognition,” in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.
- [38] L. Derczynski, E. Nichols, M. van Erp, and N. Limsopatham, “Results of the WNUT2017 shared task on novel and emerging entity recognition,” in *Proceedings of the 3rd Workshop on Noisy User-generated Text (W-NUT)*, 2017, pp. 140–147.
- [39] J. Liu, P. Pasupat, S. Cyphers, and J. Glass, “Asgard: A portable architecture for multilingual dialogue systems,” in *Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2013, pp. 8386–8390.
- [40] A. Kumar and B. Starly, “FabNER: Information extraction from manufacturing process science domain literature using named entity recognition,” *Journal of Intelligent Manufacturing*, vol. 33, no. 8, pp. 2393–2407, 2022.
- [41] J.-D. Kim, T. Ohta, Y. Tsuruoka, Y. Tateisi, and N. Collier, “Introduction to the bio-entity recognition task at JNLPBA,” in *Proceedings of the International Joint Workshop on Natural Language Processing in Biomedicine and its Applications (NLPBA/BioNLP)*, 2004, pp. 70–75.
- [42] A. Zeldes, “The GUM corpus: Creating multilayer resources in the classroom,” *Language Resources and Evaluation*, vol. 51, no. 3, pp. 581–612, 2017.
- [43] T. Aoyama, S. Behzad, L. Gessler, L. Levine, J. Lin, Y. J. Liu, S. Peng, Y. Zhu, and A. Zeldes, “GENTLE: A genre-diverse multilayer challenge set for english NLP and linguistic evaluation,” in *Proceedings of the 17th Linguistic Annotation Workshop (LAW-XVII)*, 2023.
- [44] J.-D. Kim, T. Ohta, Y. Tateisi, and J. Tsujii, “GENIA corpus—a semantically annotated corpus for bio-textmining,” *Bioinformatics*, vol. 19, no. Suppl. 1, pp. i180–i182, 2003.
- [45] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, “QLoRA: Efficient finetuning of quantized LLMs,” *arXiv preprint arXiv:2305.14314*, 2023.
- [46] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala, “PyTorch: An imperative style, high-performance deep learning library,” in *Advances in Neural Information Processing Systems 32 (NeurIPS)*, 2019.
- [47] T. Wolf, L. Debut, V. Sanh, J. Chaumond, C. Delangue, A. Moi, P. Cistac, T. Rault, R. Louf, M. Funtowicz, J. Davison, S. Shleifer, P. von Platen, C. Ma, Y. Jernite, J. Plu, C. Xu, T. Le Scao, S. Gugger, M. Drame, Q. Lhoest, and A. M. Rush, “Transformers: State-of-the-art natural language processing,” in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations (EMNLP)*, 2020.
- [48] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and É. Duchesnay, “Scikit-learn: Machine learning in Python,” *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.