Accelerated Bayesian inference of multimessenger astronomy with jax and machine learning

23 - 27 September 2024






Bayesian inference

Bayesian inference: get posterior of parameters heta from data d

$$p(\theta|d) = \frac{p(d|\theta)p(\theta)}{p(d)}$$

Problem: Computationally expensive for multimessenger data + EOS



Thibeau Wouters XMXS 23 – 27 September 2024

Nuclear Multi-Messenger Astrophysics

NMMA: Nuclear Multi-Messenger Astrophysics (Peter T.H. Pang)

 A Pythonic library for probing nuclear physics and cosmology with multimessenger analysis

Nuclear Multi-Messenger Astrophysics

- NMMA: Nuclear Multi-Messenger Astrophysics (Peter T.H. Pang)
- A Pythonic library for probing nuclear physics and cosmology with multimessenger analysis
- Used for overview of EOS constraints, with "precomputed" EOS set (arXiv:2402.04172)
 - Metamodel
 - Speed-of-sound extension scheme
 - 100 000 EOS

Nuclear Multi-Messenger Astrophysics

- NMMA: Nuclear Multi-Messenger Astrophysics (Peter T.H. Pang)
- A Pythonic library for probing nuclear physics and cosmology with multimessenger analysis
- Used for overview of EOS constraints, with "precomputed" EOS set (arXiv:2402.04172)
 - Metamodel
 - Speed-of-sound extension scheme
 - 100 000 EOS

Next step: Infer EOS parameters directly from multimessenger data, upgrade software for future detectors

JAX

- 1 Automatic differentiation
- 2 Just-in-time (JIT) compilation




- **3** GPU acceleration
- 4 Parallelization

Potential for accelerating science, without resorting to machine learning!

Normalizing flows

- Generative machine learning model
- Learn mapping between latent and parameter space
- Enable approximate sampling from complicated distributions



- Gravitational waves (arXiv:2404.11397)
 - Waveforms: $\mathcal{O}(10^3)$ faster
 - Analyze binary neutron stars in 15 30 minutes rather than $\mathcal{O}(\mathrm{hours})$

- Gravitational waves (arXiv:2404.11397)
 - Waveforms: $\mathcal{O}(10^3)$ faster
 - Analyze binary neutron stars in 15 30 minutes rather than $\mathcal{O}(\text{hours})$
- TOV solver (EOS → NS):
 - $10-100\times$ faster

- Gravitational waves (arXiv:2404.11397)
 - Waveforms: $\mathcal{O}(10^3)$ faster
 - Analyze binary neutron stars in 15-30 minutes rather than $\mathcal{O}(\text{hours})$
- TOV solver (EOS → NS):
 - $10-100\times$ faster
- Kilonovae, GRBs: 🗘 ThibeauWouters/fiesta

- Gravitational waves (arXiv:2404.11397)
 - Waveforms: $\mathcal{O}(10^3)$ faster
 - Analyze binary neutron stars in 15 30 minutes rather than $\mathcal{O}(\text{hours})$
- TOV solver (EOS → NS):
 - $10-100\times$ faster
- Kilonovae, GRBs: 🖸 ThibeauWouters/fiesta
- Future work:
 - Next-generation gravitational wave detectors
 - Combine into one multimessenger analysis pipeline

Thanks for listening!

Our JAX ecosystem:

- Normalizing flow-enhanced MCMC sampler:
 O kazewong/flowMC
- Gravitational waveforms: tedwards2412/ripple
- Gravitational waves inference toolkit:
 () kazewong/jim
- EOS code and TOV solver: tsunhopang/jose (work in progress)
- Kilonovae and GRB: **O ThibeauWouters/fiesta (work in progress)