

Accelerating gravitational wave parameter estimation with normalizing flows

Thibau Wouters

December 5, 2023



Utrecht
University

Table of Contents

① Introduction

② Why jax?

③ flowMC

④ Results

⑤ Future work & conclusion

Table of Contents

① Introduction

② Why jax?

③ flowMC

④ Results

⑤ Future work & conclusion


Parameter estimation

- Parameter estimation (PE): get **posterior** of GW parameters θ

$$p(\theta|d) = \frac{p(d|\theta)p(\theta)}{p(d)}$$

- Sampling via Markov Chain Monte Carlo (MCMC) [1]
- For binary neutron stars (BNS): computationally expensive

How to sample from high-dimensional, multi-modal posteriors?



Overview

We extend `jim` [2], based on `jax` [3], with building blocks:

- 1 Normalizing flow-enhanced, gradient-based MCMC (`flowMC` [4, 5])
- 2 Automatically-differentiable (AD) GW (`ripple` [6])
- 3 Relative binning likelihood [7]




Table of Contents

① Introduction

② Why jax?

③ flowMC

④ Results

⑤ Future work & conclusion

Why jax?

What are the benefits of `jax` for MCMC?

- ① Automatic differentiation (AD)
- ② Just-in-time (JIT) compilation
- ③ GPU acceleration
- ④ Parallelization
- ⑤ Interoperability with `numpy`



Table of Contents

① Introduction

② Why jax?

③ **flowMC**

④ Results


⑤ Future work & conclusion

① **Local sampling:** MALA (Metropolis-adjusted Langevin algorithm)

- Proposal y : Langevin diffusion


$$y = x + \frac{\epsilon^2}{2} \nabla \log p(x) + \epsilon \xi$$

- Metropolis-Hastings acceptance step




Normalizing flows (NF):

- **Latent space**: easy to sample (e.g. Gaussian)
- **Data space**: distribution learned from samples
- Enable approximate sampling from complicated distributions



② Global sampling

- Global proposal by sampling from NF
- Metropolis-Hastings acceptance step



flowMC – complete algorithm




Table of Contents

- ① Introduction
- ② Why jax?
- ③ flowMC
- ④ Results
- ⑤ Future work & conclusion

Results

- TaylorF2 in ripple
- IMRPhenomD_NRTidalv2 in ripple (ongoing)
- Reproduced PE for GW170817 & GW190425 with TaylorF2
- ~ 30 mins training, ~ 1 min sampling




Table of Contents

- ① Introduction
- ② Why jax?
- ③ flowMC
- ④ Results
- ⑤ Future work & conclusion

Future work

- Finish IMRPhenomD_NRTidalv2 in `ripple`
- Injection studies and pp-plot
- Investigate synergy with simulation-based inference

Conclusion

- `flowMC`: NF-enhanced, gradient-based MCMC
- `ripple`: automatically differentiable GW
- `jim = jax + flowMC + ripple`
- `jim` is a promising tool for fast and accurate parameter estimation
- `jim` can be used for parameter estimation of BNS and BBH
- `jim` can enhance and benefit from simulation-based inference

References

- [1] Steve Brooks et al. *Handbook of markov chain monte carlo*. CRC press, 2011.
- [2] Kaze WK Wong, Maximiliano Isi, and Thomas DP Edwards. “Fast gravitational wave parameter estimation without compromises”. In: *arXiv preprint arXiv:2302.05333* (2023).
- [3] James Bradbury et al. *JAX: composable transformations of Python+NumPy programs*. Version 0.3.13. 2018. URL: <http://github.com/google/jax>.
- [4] Marylou Gabrié, Grant M Rotskoff, and Eric Vanden-Eijnden. “Efficient bayesian sampling using normalizing flows to assist markov chain monte carlo methods”. In: *arXiv preprint arXiv:2107.08001* (2021).
- [5] Kaze WK Wong, Marylou Gabrié, and Daniel Foreman-Mackey. “flowMC: Normalizing-flow enhanced sampling package for probabilistic inference in Jax”. In: *arXiv preprint arXiv:2211.06397* (2022).
- [6] Thomas DP Edwards et al. “ripple: Differentiable and Hardware-Accelerated Waveforms for Gravitational Wave Data Analysis”. In: *arXiv preprint arXiv:2302.05329* (2023).
- [7] Barak Zackay, Liang Dai, and Tejaswi Venumadhav. “Relative binning and fast likelihood evaluation for gravitational wave parameter estimation”. In: *arXiv preprint arXiv:1806.08792* (2018).

BACK-UP SLIDES

flowMC: production loop

- After training, NF is “frozen”, and the Markov property is restored.
- We run a few “production loops” to sample from the posterior for the final PE.

