

Accelerated Bayesian inference of multimessenger astronomy with jax and machine learning

Thibea Wouters, Peter T. H. Pang, Chris Van Den Broeck

t.r.i.wouters@uu.nl



23 – 27 September 2024



**Utrecht
University**



Nuclear Multi-Messenger Astrophysics

- NMMA: Nuclear Multi-Messenger Astrophysics (Peter T.H. Pang)
- A Pythonic library for probing nuclear physics and cosmology with multimessenger analysis
- Used for overview of EOS constraints, with “precomputed” EOS set (arXiv:2402.04172)
 - Metamodel
 - Speed-of-sound extension scheme


Next step: Infer EOS parameters directly from multimessenger data

Bayesian inference

Bayesian inference: get **posterior** of parameters θ from data d

$$p(\theta|d) = \frac{p(d|\theta)p(\theta)}{p(d)} = \frac{\text{likelihood} \times \text{prior}}{\text{evidence}}$$

Problem: Prohibitively expensive with multimessenger data



JAX = NUMPY + composable transformations:


- ① Automatic differentiation
- ② Just-in-time (JIT) compilation
- ③ GPU acceleration
- ④ Parallelization






Potential for acceleration in various science areas!

Normalizing flows

- Generative machine learning model
- Learn mapping between **latent** and **parameter** space
- Enable approximate sampling from complicated distributions
- Training data: MCMC samples



Accelerating Bayesian inference for MMA: progress

- Gravitational waves:
 - Analyze binary neutron stars in **15 – 30 minutes** rather than $\mathcal{O}(\text{hours})$ (arXiv:2404.11397)
 -  kazewong/jim
- TOV solver:
 - **10 – 100× faster**
 -  tsunhopang/jose
- Kilonovae, GRBs:  ThibeuWouters/fiesta
- Ongoing:
 - Next-generation gravitational wave detectors
 - Combine into one multimessenger analysis pipeline