



**rashida** @rashida started a thread on commit b5a536a2 1 month ago  
Last updated by rashida 1 month ago

^ Toggle thread

M README.md

```
4 4
5 5  ## Mission: Parser of roman numbers
6 6
7 - Key idea: Write a (java) class with a method int convert(String) that takes a roman number such as
  "III" and gives the arabic number (here: "3").
```



**rashida** @rashida · 1 month ago

Maintainer 😊 ✎ ⋮

Should we then edit this statement to take arabic and parse Roman numeral? It then becomes the same as the first requirement.



**eric.knauss** @eric.knauss · 1 month ago

Can you please check again? I think I have up

▼ M requirements/system-requirem

```
5 5
6 6  ### [requirements id=
7 7  The system shall pro
  times 'I' (e.g. 1 --
8 +
9 +  ### [requirements id=
10 + The system shall pro
   as "11" and gives the roman number (here: "XI").
11 +
12 +  ### [requirements id=req5.1 story=US5]
13 + The system shall provide a method `String convertNum(int i)` that takes a arabic number ranges
   from 11 to 50, and gives the roman number (here: "XI" to "L").
\ No newline at end of file
```



**rashida** @rashida started a thread on commit 4b55ff0a 1 month ago

^ Toggle thread

src/se/treqs/example/numconv/NumConverter.java

```
1 + package se.treqs.example.numconv;
2 +
3 + public class NumConverter {
4 +
5 +     public String convert(int i) {
6 +         return "III";
```



**rashida** @rashida · 1 month ago

Does it then return only III?

Maintainer 😊 ✎ ⋮

Break down requirements and keep them consistent with implementation.