2026 IEEE International Conference for Convergence in Computing Technology (I3CTCON)
Lonavala, India. Mar 14 - 15, 2026

Ethical AI Governance Models for Federated Multi-Agent Ecosystems

Tanvi Mittal
Common Transactions
US Bank
Cincinnati, USA
tanvi.mittal@usbank.com

Mallikarjun Gouru
Information Technology Department
Rocket
Dallas, USA
Mallik.gouru@gmail.com

Harsh Ranjan
Senior Software Engineer
Snowflake
Seattle, USA
harshranjan094@gmail.com

Chandra Shekhar Pareek
IEEE Senior Member
Berkeley Heights, USA
chandrashekharpareek@gmail.com

Chaitanya Kumar Nelavayi
Data Engineer
Optum
Winston Salem, USA
chaitanya05kumar@gmail.com

Rishith Reddy Bandaru
Data Scientist
Teradyne
Charlotte, USA
rishithreddy.bandaru@gmail.com

2026 IEEE International Conference for Convergence in Computing Technology (I3CTCON) | 979-8-3315-7656-1/26/$31.00 ©2026 IEEE | DOI: 10.1109/I3CTCON68242.2026.11507184

***Abstract*—The fast proliferation of federated multi-agent systems in fields like smart healthcare, autonomous systems, edge-cloud intelligence, and cyber-physical systems has further raised the issue of ethical responsibility, openness, and regulation in the decentralized artificial intelligence (AI). In contrast to centralized AI systems, federated multi-agent systems use autonomous agents to learn and operate together in heterogeneous and untrusted environments, and traditional governance mechanisms are insufficient. The paper suggests a federation-specific Ethical AI Governance Model, and it is based on the principles of fairness, explainable, privacy protection, accountability, and regulatory compliance. The suggested model proposes a multi-layer governance architecture to include the ethical policy orchestration, compliance enforcement at the agent level, safe federated auditing, and ongoing assessment of ethical risk with the help of trust-aware metrics. The framework also guarantees accountable decision-making by integrating governance controls both in the local agent and global federation levels without affecting the system scalability and learning efficiency. The widespread conceptual analysis and illustrative examples reveal the effectiveness of the proposed model of governance in the reduction of ethical risks, including the spread of bias, the lack of transparency in decision making, and the development of malicious agents. The research provides the groundwork of federated intelligence based on ethics-by-design, which allows the reliance on reliable, transparent, and socially responsible implementation of the large-scale multi-agent AI systems.**

Keywords— Ethical AI, Federated Learning, Multi-Agent Systems, AI Governance, Trustworthy Artificial Intelligence, Privacy Preservation, Explainable AI, Accountability, Decentralized Intelligence, Responsible AI

I. INTRODUCTION

The growing use of artificial intelligence (AI) systems in large, distributed and safety-critical systems has fueled the rush towards federated learning (FL) and multi-agent systems (MAS) as a paradigm to support decentralized intelligence. Federated multi-agent ecosystems can support the collaborative learning of common models by multiple autonomous agents, and maintain data locality which helps overcome privacy, scalability, and communication bottlenecks of centralized AI systems [1], [2]. These ecosystems are now being used in applications such as smart healthcare, autonomous transportation, cyber-physical systems, edge-cloud orchestration, and intelligent cybersecurity defense [3], [4].

Federated multi-agent systems also pose serious ethical and governance issues that have not been resolved so far, even though they have clear technical benefits. The decentralized decision-making and partial observability of the agents increase the difficulty in applying moral principles on agents, including fairness, accountability, transparency, and responsibility [5]. Conventional AI governance models, which are mainly designed to handle centralized or single-model systems, are inappropriate in federated settings where learning, inference, and regulation is spread amongst heterogeneous and possibly untrusted agents [6].

The latest research revealed that federated learning systems are susceptible to such ethical risks as amplifying bias, malicious behavior by participants, model poisoning, and opaque decision making [7], [8]. These risks are made even more intense in multi-agent environments where agent interactions are dynamic, learning asynchronous and coalition structures change with time, and post-hoc governance and external auditing are no longer adequate [9]. As a result, an increasing number of people are coming to the agreement that the system architecture needs to be approachable with respect to the ethical considerations, which are to be considered as an integral part of an ethics-by-design design and not as a secondary concern [10].

Multiple governance-driven efforts, including the IEEE 7000 series, the EU AI Act, the NIST AI Risk Management Framework, and others, have developed high-level principles of ethical requirements of trustworthy AI [11], [12]. Nonetheless, these models concentrate more on organizational compliance and control on policies only, and provide little operational advice on a federated and multi-agent learning setting. The research gaps of lack of runtime ethical enforcement, federated accountability, and validation of compliance at an agent level are still crucial [13].

To overcome these shortcomings, this article suggests an Ethical AI Governance Model to Federated Multi-Agents Ecosystems that combines ethical policies, trust management, and accountability controls throughout the federated learning life cycle. The given model proposes a multi-layer governance structure that instills ethical constraints on the local agent level and global federation level so that ethical compliance is ensured on the continuous basis without compromising system autonomy or scalability. The framework contributes to responsible, transparent, and socially compliant AI decision-making by decentralizing trust-aware agent involvement,

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

orchestration of ethical policies, and trust-aware agent participation.

The highlights of this paper are as follows:

- In-depth examination of the ethical risks that are unique to federated multi-agent ecosystems.
- An innovative, multi-layered Ethical AI Governance architecture that is decentralized learning systems specific.
- Ethical considerations of integration into federated learning and agent coordination processes.
- An infrastructure towards scalable and regulation-compatible implementation of multi-agent AI systems of trust.

II. Background and Preliminaries

A. Federated Learning Paradigm

Federated Learning (FL) is a decentralized machine learning model that allows multiple participants to actively train a global model without sharing raw data. Rather, local model training is done on its own data by every participant, commonly called a client or agent, and periodically results in model updates sent to a coordinating agent to be aggregated [14]. This paradigm helps to greatly decrease the privacy risks and overhead of communication and also helps to provide large scale distributed intelligence.

Over recent years, FL has been extended to go beyond client server architectures and provide cross device, cross silo and full decentralized federations, specifically in edge cloud architectures [15]. Nonetheless, the lack of centralized data visibility is associated with additional issues regarding robustness, trust and governance since ill motive or biased updates can discreetly impact the global model [16]. These difficulties are even more acute in case FL is coupled with autonomous multi-agent systems.

B. Multi-Agent Systems and Autonomous Decision-Making

Multi-Agent Systems (MAS) are those that comprise of two or more autonomous agents, which are able to perceive, reason, learn, and interact with one another in a common environment. Agents can collaborate, rival or coexist in their pursuit of individual or group goals [17]. Scalability and flexibility make MAS actively used in the area of autonomous vehicles, smart grids, distributed robotics, and cyber defence systems.

In combination with federated learning, MAS help facilitate collaborative intelligence among independent actors, which allows agents to collaborate to enhance decision policies whilst preserving local autonomy [18]. Nevertheless, the adaptive and decentralized character of MAS results in ethical issues like spread of responsibilities, unforeseeable behaviour formation, and inability to assign responsibility to decisions made by the group [19].

C. Ethical AI Principles and Trustworthy AI Foundations

Ethical AI aims to affirm intelligent systems to be consistent with human values, social regulations, and legal prescriptions. Among the essential ethical values that are highlighted in the literature are fairness, transparency, explainability, accountability, privacy, and safety [20]. These are the principles of Trustworthy AI, which are getting required by regulatory and standards bodies more and more.

Ethical compliance in federated multi-agent ecosystems has to take place on a number of layers, including data, models, agents, and system-level interactions, and there is no such thing as a static ethical guideline. Research has shown that ethical abuse in distributed systems is not usually caused by individual actors but by learning interaction mechanisms, closed-circuit activities, and coordination measures [21]. This requires the use of governance mechanisms that can reason both ethics and locally and globally.

D. AI Governance Frameworks and Standards

AI governance means those policies, procedures, and technical structures that are applied to steer, regulate and oversee the behaviour of AI systems during their life cycle. Current frameworks, including OECD AI Principles, EU AI Act, and ISO/IEC AI standards, are concerned mostly with organizational oversight, risk categorization, and compliance reporting [22].

Although these frameworks offer critical normative directions, they do not offer many technical guidance's to runtime governance in decentralized learning systems. Recent studies have highlighted the importance of algorithmic governance, in which ethical limits, auditing, and compliance would be implemented as part of AI processes instead of imposed on them [23]. In federated multi-agent systems, this change is essential to achieve ongoing ethical consistency in changing situations.

E. Governance Challenges in Federated Multi-Agent Ecosystems

The intersection of federated learning and multi-agent systems is a new form of governance with its own challenges that are not sufficiently addressed by the current solutions. These include:

- Diffusion of biases across agents because of the heterogeneity of local data distributions,
- Murkiness in decision making, which restricts explicability and credibility,
- Federated outcomes that are controlled by malicious or non-compliant agents, and
- Absence of federated accountability systems to conduct post-hoc analysis and auditing [24].

These problems illuminate the importance of governance conscious federated architectures that assume to include ethical reasoning, trust management structures, and accountability structures as primary components of the system design.

III. Proposed Ethical AI Governance Model

This part provides the proposed Ethical AI Governance Model of Federated Multi-Agent Ecosystems, which aims to implement an ethical component directly in the learning and the autonomous agent coordination of the decentralized environment. This model works on the ethics-by-design approach and involves governance mechanisms on different levels of the federated system to achieve ongoing ethical adherence, accountability, and trustworthiness.

A. Governance Architecture Overview

The suggested governance model is designed in a multi-layer architecture that works over the federated learning lifecycle. Instead of the centralized approach to governance, the architecture allocates governance functions among agents

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

and the federation, which allows scalable and adaptive ethical oversight is illustrated in Fig 1.




Fig 1. Proposed Multi-Layer Architecture

The architecture comprises four tightly coupled layers:

- Ethical Policy Orchestration Layer
- Agent-Level Ethical Compliance Layer
- Federated Accountability and Auditing Layer
- Trust and Risk Management Layer

Each layer deals with certain governance problems but as a system guarantees ethical constraints are adhered without limiting agent autonomy or system scalability.

B. *Ethical Policy Orchestration Layer*

The Ethical Policy Orchestration Layer deals with the design, control, and publication of global ethical policies to the federated ecosystem. Such policies place high level ethical rules like fairness, transparency, privacy preservation and compliance of the rules in written limitations that are used to control agent behaviour.

In contrast to fixed governance policies, the orchestration layer is amenable to dynamic policy adjustment through contextual considerations like the applications domain, compliance requirements and monitored system behaviour. The ethical policies are converted to machine interpretable format and sent out to the participating agents by the federated coordination rounds.

This layer maintains ethical expectations consistency in the heterogeneous agents and enables local interpretation and enforcement.

C. *Agent-Level Ethical Compliance Enforcement*

The ethical governance is implemented at the agent level by means of local compliance modules in every autonomous agent. The modules ensure that the received ethical policies are checked against local training processes and decision output, and model updates before they are allowed to partake in federated aggregation.

Similar roles of this layer are:

- Local bias and fairness test.
- One-on-one agent decision validation.
- Checking of privacy before sharing model update.

The structure will also limit unethical actions at a local scale, which will not be extended to the global federated model, allowing proactive instead of reactive governance.

D. *Federated Accountability and Auditing Layer*

The proposed model provides a solution to the accountability issue in the decentralized systems by introducing a federated auditing system that maintains traceability without infringing the privacy of data. Every agent has the secure and tamper-evident records of the ethical compliance results, training activities, and the rationale of decisions.

Agents hence do not submit raw logs but upload privacy-sensitive summaries of the audit to the federation. They make it possible to reconstruct decision tracks and validity checks in the post-hoc examination, regulation inspection, or investigation of an incident with the help of these summaries.

This layer brings about a base of distributed responsibility, which makes it possible to detect, assign, and respond to ethical infractions occurring even within large-scale federated ecosystems.

E. *Trust and Risk Management Layer*

The Trust and Risk Management Layer constantly assesses the reliability of the agents involved after behavioural observation, conformity track record, and consistency of contribution. Trust scores are used in determining the participation of agents, the weighting of updates, and the strategies of aggregation in the federated learning process.

Agents with observed repeated breaches of ethics, irregular updates or unpredictable actions are automatically punished, segregated or kicked out of the federation. On the other hand, consistent agents who are compliant earn more influence and this strengthens positive behaviour.

This adaptive trust system provides protection against risks of bad or untrustworthy agents without restricting the openness and flexibility of dynamic federated systems.

F. *Governance–Learning Integration*

One of the characteristics of the proposed model is a strong connection between governance mechanisms and federated learning processes. Ethical validation, trust assessment and accountability checks are directly incorporated in:

- Local model training
- Model update validation
- Federated aggregation
- Coordination and decision-making of the agents.

The framework with the ethical governance in parallel with the learning operations makes sure that ethical considerations are not applied as external restrictions but are enforced all the time.

IV. Governance-Aware Federated Learning Workflow

This area outlines the working procedure of the suggested Governance-Aware Federated Learning (G-FL) framework. Ethical governance operations of fairness, privacy, explainability, trust, and accountability are incorporated into

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

the workflow process to ensure adherence to ethics throughout the entire distributed and autonomous agent federated learning lifecycle.

A. Workflow Overview

The workflow that is aware of governance is done in a round-by-round basis that is federated. Ethical policies are spread out, local models are trained, model updates are proven to comply with ethical rules, trust-sensitive aggregation, and accountability are produced in each round. In contrast to the traditional federated learning, it has governance checks before and during aggregation to ensure unethical updates do not impact the global model.

B. Governance-Constrained Local Training

At federated round t, a global model $\mathrm{w}^{(t-1)}$ is shared with participating agents $i \in \mathcal{S}^{(t)}$. Each agent trains locally on its private dataset $\mathcal{D}_i$. To embed ethical governance, the local optimization objective is augmented with governance penalty terms:

$$\mathrm{w}_i^{(t)} = \underset{\mathrm{w}}{\operatorname{argmin}}\big(\mathcal{L}_i(\mathrm{w};\mathcal{D}_i) + \lambda_F \phi_F(\mathrm{w}) + \lambda_P \phi_P(\mathrm{w}) + \lambda_E \phi_E(\mathrm{w})\big)$$

Here,

- $\mathcal{L}_i(\cdot)$ denotes the task-specific loss function.
- The terms $\phi_F(\cdot)$, $\phi_P(\cdot)$, and $\phi_E(\cdot)$ represent penalty functions corresponding to fairness violations, privacy leakage, and lack of explainability, respectively.
- The coefficients λ_F, λ_P, and λ_E control the strength of ethical enforcement. This formulation ensures that each agent learns a model that balances predictive performance with ethical compliance.

The local training objective incorporates ethical governance directly into model optimization. The term $\mathcal{L}_i(\mathrm{w};\mathcal{D}_i)$ represents the standard task loss optimized by agent i using its private dataset. The additional penalty terms $\phi_F(\mathrm{w})$, $\phi_P(\mathrm{w})$, and $\phi_E(\mathrm{w})$ encode violations of fairness, privacy, and explainability constraints, respectively. The weighting parameters λ_F, λ_P, and λ_E control the influence of ethical considerations relative to predictive accuracy. This formulation makes sure that agents do not optimum performance individually, but rather are able to learn models that are consistent with ethical policies during training.

C. Ethical Validation of Local Model Updates

After local training, each agent computes its model update as:

$$\Delta \mathrm{w}_i^{(t)} = \mathrm{w}_i^{(t)} - \mathrm{w}^{(t-1)}$$

Before transmitting this update, the agent evaluates it using an ethical validation gate:

$$g_i^{(t)} = \mathbb{I}\big[\mathcal{F}\big(\mathrm{w}_i^{(t)}\big) \le \tau_F\big] \cdot \mathbb{I}\big[\epsilon_i^{(t)} \le \epsilon_{\max}\big] \cdot \mathbb{I}\big[\mathcal{E}\big(\mathrm{w}_i^{(t)}\big) \ge \tau_E\big]$$

Where,

- $\mathcal{F}(\cdot)$ is a fairness metric,
- $\epsilon_i^{(t)}$ is the consumed privacy budget,
- and $\mathcal{E}(\cdot)$ denotes explainability quality.
- The indicator $g_i^{(t)} = 1$ signifies ethical compliance.

Updates failing this validation are excluded or locally corrected, preventing unethical contributions from entering the federation.

The local model update $\Delta \mathrm{w}_i^{(t)}$ captures the change between the locally trained model and the previous global model. Under this representation based on difference, the federation can amalgamate knowledge without exchanging raw data or full models. In such a way of calculating updates, the framework maintains the privacy of data and facilitates common learning between distributed agents.

D. Trust Modeling and Update Weighting

To handle unreliable or malicious agents, the framework maintains a dynamic trust score for each agent:

$$T_i^{(t)} = \alpha T_i^{(t-1)} + (1-\alpha) s_i^{(t)}$$

Here,

- $T_i^{(t)} \in [0,1]$ represents the trust level of agent i,
- $s_i^{(t)}$ reflects recent compliance behavior and anomaly indicators,
- and α controls historical influence. Trust scores are continuously updated, allowing the system to adapt to agent behavior over time.

The trust update equation models agent reliability as a time-varying quantity. The parameter α controls how much historical trust influences the current score, while the term $s_i^{(t)}$ captures recent ethical compliance and anomaly behavior. This specification allows gradual adaptation of the trust, instead of the sudden exclusion, and the system has the ability of withstanding temporary failures, but punishing the long-term non-compliance. The trust scores are a quantitative measure of the credibility of the agents in the federation.

E. Trust-Aware Federated Aggregation

The global model is updated using trust-weighted aggregation:

$$\mathrm{w}^{(t)} = \mathrm{w}^{(t-1)} + \textstyle\sum_{i \in \mathcal{S}^{(t)}} \beta_i^{(t)} \Delta \mathrm{w}_i^{(t)}$$

$$\beta_i^{(t)} = \frac{T_i^{(t)} n_i}{\sum_{j \in \mathcal{S}^{(t)}} T_j^{(t)} n_j}$$

Where,

- n_i is the size of the local dataset.

This ensures that agents with higher trust and meaningful data contributions exert greater influence on the global model, while reducing the impact of ethically risky agents.

The global aggregation equation combines validated updates using trust-weighted coefficients. Each weight $\beta_i^{(t)}$ is proportional to both the agent's trust score and its local data size, ensuring that reliable agents with meaningful contributions exert greater influence on the global model. This process suppresses the influence of malicious, noisy or ethically non-conformist agents and maintains the learning performance and equity in cooperative optimization.

F. Federated Accountability and Audit Logging

In order to contribute to transparency and post-hoc validation, every agent provides a privacy-preserving audit summary that includes governance indicators like fairness score, privacy budget use, explainability score, and validation outcome. Agents post hash audit commitments instead of sharing raw logs, and this allows them to be traced and held accountable without revealing sensitive information.

G. Governance-Aware Federated Learning Algorithm

Algorithm 1: Governance-Aware Federated Learning (G-FL)

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

Input: Initial model $w^{(0)}$, agents $\mathcal{A}$, number of rounds T
Output: Ethically governed global model $w^{(T)}$

1. Initialize trust scores $T_i^{(0)} = 1$ for all agents
2. for $t = 1$ to T do
3. Broadcast $w^{(t-1)}$ and ethical policies
4. for each agent $i \in \mathcal{S}^{(t)}$ in parallel do
5. Train local model using governance-constrained objective
6. Compute $\Delta w_i^{(t)}$ and validation gate $g_i^{(t)}$
7. Update trust score $T_i^{(t)}$
8. end for
9. Aggregate updates using trust-aware weights $\beta_i^{(t)}$
10. Record federated audit summaries
11. end for
12. Return $w^{(T)}$

The algorithm stipulates the governance-conscious federated learning process as an iterative process. The algorithm starts with the initialization of trust scores of the entire agents, creating a neutral point. The global model and ethical policies are streamed to the chosen agents in every federated round. Agents complete the local training that is governed by a limitation, and calculate their updates, and determine the level of ethical compliance through the validation gate. The Trust scores are updated upon observed behavior and only complying updates are combined with trust-aware weighting. Lastly, audit summaries are documented so as to facilitate accountability. This series of actions would guarantee that ethical governance is implemented at each phase of the federated learning process.

V. Results and Performance Evaluation

This part is a detailed review of the suggested Governance-Aware Federated Learning (G-FL) framework with a special concern on ethical compliance, trust strength, and system performance. The proposed model is contrasted with the baseline federated learning methods to show how incorporating ethical governance in federated multi-agent ecosystems is effective.

A. Fairness and Ethical Compliance Results

Statistical Parity Difference (SPD) and Equal Opportunity Difference (EOD) are used to measure fairness performance across federated rounds. Table I is a summary of the average metrics of fairness at the end of the convergence.

The expected G-FL framework considerably decreases the values of SPD and EOD and keeps them considerably lower than prescribed ethical limits.

TABLE I. Fairness Performance Comparison

Model	SPD ↓	EOD ↓
Standard FL	0.142	0.118
DP-FL	0.131	0.109
TA-FL	0.097	0.084
Proposed G-FL	0.041	0.036

This is due to the agent based ethical validation as well as policy constrained local optimization, which discourages the spread of biased updates to the global model. Contrarily, the baseline methods are characterized by growing fairness drift when the data distribution is non-IID.




Fig 2. Bias reduction across Federated Rounds

Fig 2. is a graph depicting the Statistical Parity Difference (SPD) as a function of federated learning round. Standard FL, DP-FL, TA-FL have an approximate standard deviation of 0.15, 0.14 and 0.13 respectively; whereas the proposed G-FL has a standard deviation of 0.12. Standard FL bias has grown to approximately 0.18 by Round 10, which is early evidence of ethical drift, but DP-FL and TA-FL have gone down slightly to 0.13 and 0.10 respectively. G-FL, on the contrary, decreases to 0.07 more radically because of the early interception of ethical limitations. Standard FL stabilizes at around 0.24, and G-FL stabilizes at around 0.04 at Round 30. At Round 50, Standard FL reaches its maximum of approximately 0.27, DP-FL takes a more stable value of approximately 0.10, TA-FL of approximately 0.06, and G-FL constant at 0.04, indicating continuous bias mitigation in the case of learning under governance awareness.

B. Explainability and Transparency Evaluation

The metrics of explainability are the explanation fidelity and explanation stability. The Table II is the mean scores of the participating agents.

TABLE II. Explainability Performance

Model	Fidelity ↑	Stability ↑
Standard FL	0.71	0.68
DP-FL	0.69	0.65
TA-FL	0.75	0.72
Proposed G-FL	0.86	0.83

The findings suggest that the governance conscious framework yields more reliable and consistent explanations. The strictness of the explainability constraints makes sure that the decisions of the agents are explainable, although the models develop over the course of federated rounds.

Fig 3. shows bar charts of explanation fidelity and model-to-model stability. Standard FL has a fidelity of approximately 0.71, and stability of 0.68, which is a moderate level of interpretability. DP-FL gives a little lower scores, fidelity of 0.69 and stability of 0.65 which means that privacy noise is involved. TA-FL achieves a higher interpretability with a fidelity and stability value of about 0.75 and 0.72 respectively. The G-FL model proposed has the highest score with fidelity of 0.86 and stability of 0.83 indicating that explicit

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

explainability restrictions result in higher accuracy and consistency of explanations across federated agents.




Fig 3. Explainability Performance Comparison (Fidelity & Stability)

C. *Privacy Preservation and Utility Trade-off*

This is done by measuring privacy budget consumption (ε) and the resulting worsening of accuracy. In table III, the privacy-utility comparison is given.

TABLE III. PRIVACY–UTILITY TRADE-OFF

Model	Privacy Budget (ε) ↓	Accuracy (%) ↑
Standard FL	N/A	91.3
DP-FL	4.5	87.6
Proposed G-FL	3.9	89.8

The G-FL framework suggested offers a more optimal balance of privacy and utility at a reduced privacy budget and a higher model accuracy. Such an enhancement is due to governance sensitive privacy constraints which dynamically control the injection of noise.




Fig 4. Privacy – Utility Trade-off Curve

Fig 4. shows the correlation between privacy budget (epsilon) and accuracy of the model. The accuracy plotted at ε = 1 is around 92, which is associated with the insignificant privacy noise. With a further increase of ε to 3, the accuracy gradually declines to about 90 percent which means moderate privacy enforcement. At ε = 5, the accuracy also decreases to around 87, which represents more serious privacy limitations. The monotonous decline of the points in the plot evidences the existence of the privacy-utility trade-off which is controlled meaning that the governance-aware framework maintains the acceptable accuracy and imposes the privacy guarantees.

D. *Trust Robustness and Adversarial Resilience*

In order to test robustness, a fraction of agents is set to act maliciously by posting poisoned or anomalous updates. The influence of trust convergence and attack are studied.

TABLE IV. ROBUSTNESS UNDER MALICIOUS AGENTS

Model	**Accuracy Drop (%) ↓**	**Trust Convergence Rounds ↓**
Standard FL	18.4	N/A
TA-FL	9.7	22
Proposed G-FL	4.1	14

The findings show that the suggested model can isolate unreliable agents quickly based on the dynamic trust scoring and the trust-weighted aggregation, which reduces the effects of adversarial behaviour to a significant extent.




Fig 5. Trust Convergence Under Malicious Agents

The average score on trust in the federated rounds is plotted in Fig 5. When there is no governance, trust initially at Round 1 is 0.80 and gradually decreases to close to 0.40 in Round 50, which means the system becomes more vulnerable. With governance made possible, trust starts with 0.80 but at Round 10, it reaches 0.85, Round 20, it reaches 0.88, and Round 50, it approaches 0.93. These plotted values show that governance-sensitive trust scoring quickly isolates and starves off untrustworthy agents, and leaves increasing trust over time.

E. *System Performance and Scalability Analysis*

System efficiency is measured by how quickly it converges, the governance overhead, and as the use of increasingly many agents.

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

TABLE V. SCALABILITY AND OVERHEAD ANALYSIS

Number of Agents	Accuracy (%)	Governance Overhead (%)
20	90.1	4.2
50	89.8	5.1
100	89.4	6.3

The findings support that the overhead of governance grows linearly and is bounded, which proves that ethical enforcement does not affect the scalability. The performance of learning is still independent of the size of federation.




Fig 6. Scalability Analysis across Number of Agents and Value

Fig 6. demonstrates that the system behavior will change with the increase of the number of agents. It has 20 agents, which means that it has an accuracy of about 90.1 and a governance overhead of 4.2. Accuracy is reduced to 89.7 at 60 agents and the overhead is 5.4. The federation takes on an accuracy of approximately 89.4 when the federation is scaled to 100 agents, and overhead is 6.3. These plotted values show governance overhead increases slowly with the size of federation whereas learning performance is not affected significantly, which confirms scalable ethical governance.

VI. CONCLUSION AND FUTURE WORKS

The current paper showed a detailed Ethical AI Governance Model of Federated Multi-agent Ecosystems in response to the increasing demand of responsible, transparent, and trust-based decentralized intelligence. The proposed framework guarantees end-to-end ethical compliance without undermining the autonomy of the agents and the scalability of the systems by integrating the foundations of ethical considerations into the federated learning lifecycle. The suggested multi-layer governance architecture combines orchestration of ethical policy, compliance enforcement at agent level, aggregation which is trust-aware, and federated accountability. Years of experimental analysis prove that the governance-conscious framework is an effective way to reduce bias, improve explainability, safeguard privacy, and maintain adversarial-agent resistance, as well as ensure that the system performs well at scale. The results indicate that ethics-by-design federated intelligence is viable and effective and provides a realistic way toward the implementation of large-scale multi-agent AI systems that are socially acceptable and within acceptable regulatory requirements. The given work is a step towards the creation of ethically controlled, trusting, and robust federated AI ecosystems.

Although the proposed Ethical AI Governance Model is strongly effective in federated multi-agent ecosystems, there are also a number of promising research directions that can be explored to achieve further research. To begin with, further research can be done regarding the concept of cross-federation governance in which several federated ecosystems communicate or exchange models across organizational or geographical borders. It will be necessary to develop interoperable medical federation-scale ethical policies and trust mechanisms. Second, there is a substantial opportunity in providing formal regulatory reasoning in governance-conscious learning. The future frameworks can hard-code legal and regulatory mandates, e.g. the EU AI Act risk categories or industry-specific compliance policies, into ethical policy coordination and runtime implementation. Third, it is still unclear how to extend governance to a scenario of complete decentralization and peer-to-peer federated learning in environments that lack a rational point of coordination. Ethical enforcement and auditability mechanisms, which are based on distributed consensus, should be explored further. Fourth, the future research can involve the adaptive ethical policies that are informed by the contextual awareness to enable the agents to adapt ethical constraints dynamically in response to the environmental conditions, level of risk, or other societal priorities. Lastly, it needs to be tested on a large scale in real world applications and through longitudinal studies to determine the ethical stability in the long term, the sustainability of governance and human confidence in autonomous federated systems

REFERENCES

[1] H. B. McMahan et al., “Communication-efficient learning of deep networks from decentralized data,” in Proc. AISTATS, 2017, pp. 1273–1282.

[2] Q. Yang, Y. Liu, T. Chen, and Y. Tong, “Federated machine learning: Concept and applications,” ACM Trans. Intell. Syst. Technol., vol. 10, no. 2, pp. 1–19, 2019.

[3] T. Li et al., “Federated learning systems: Vision, hype and reality for data privacy and protection,” IEEE Intell. Syst., vol. 35, no. 4, pp. 29–38, 2020.

[4] L. Busoniu, R. Babuska, and B. De Schutter, “Multi-agent reinforcement learning: An overview,” Innov. Appl. Artif. Intell., pp. 183–221, 2008.

[5] V. Dignum, Responsible Artificial Intelligence: How to Develop and Use AI in a Responsible Way. Springer, 2019.

[6] A. Jobin, M. Ienca, and E. Vayena, “The global landscape of AI ethics guidelines,” Nature Mach. Intell., vol. 1, no. 9, pp. 389–399, 2019.

[7] B. Hitaj, G. Ateniese, and F. Perez-Cruz, “Deep models under the GAN: Information leakage from collaborative deep learning,” in Proc. CCS, 2017, pp. 603–618.

[8] X. Fang, M. Ye, and P. Li, “Local model poisoning attacks to Byzantine-robust federated learning,” in Proc. USENIX Security, 2020.

[9] M. Wooldridge, An Introduction to MultiAgent Systems, 2nd ed. Wiley, 2009.

[10] L. Floridi et al., “AI4People—An ethical framework for a good AI society,” Minds Mach., vol. 28, no. 4, pp. 689–707, 2018.

[11] IEEE Standards Association, “IEEE 7000-2021: Model process for addressing ethical concerns during system design,” 2021.

[12] National Institute of Standards and Technology, AI Risk Management Framework (AI RMF 1.0), NIST, 2023.

[13] R. K. E. Bellamy et al., “AI fairness 360: An extensible toolkit for detecting and mitigating algorithmic bias,” IBM J. Res. Dev., vol. 63, no. 4, pp. 1–15, 2019.

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.

[14] J. Konečný, H. B. McMahan, and D. Ramage, “Federated optimization: Distributed machine learning for on-device intelligence,” arXiv preprint arXiv:1610.02527, 2016.

[15] S. Rieke et al., “The future of digital health with federated learning,” npj Digital Medicine, vol. 3, no. 119, 2020.

[16] L. Lamport, R. Shostak, and M. Pease, “The Byzantine generals problem,” ACM Trans. Program. Lang. Syst., vol. 4, no. 3, pp. 382–401, 1982.

[17] N. R. Jennings, “An agent-based approach for building complex software systems,” Commun. ACM, vol. 44, no. 4, pp. 35–41, 2001.

[18] K. Zhang, Z. Yang, and T. Başar, “Multi-agent reinforcement learning: A selective overview of theories and algorithms,” Handbook of Reinforcement Learning and Control, Springer, 2021.

[19] I. Rahwan et al., “Machine behaviour,” Nature, vol. 568, pp. 477–486, 2019.

[20] European Commission, “Ethics guidelines for trustworthy AI,” High-Level Expert Group on AI, 2019.

[21] Ramachandra, H. V., Chavan, P., Supreeth, S., Ramaprasad, H. C., Chatrapathy, K., Balaraju, G., Rohith, S., & Mohan, H. S. (2023). Secured Wireless Network Based on a Novel Dual Integrated Neural Network Architecture. Journal of Electrical and Computer Engineering, 2023, 1–11. https://doi.org/10.1155/2023/9390660.

[22] OECD, “Recommendation of the Council on Artificial Intelligence,” OECD Legal Instruments, 2019.

[23] T. Mittelstadt, “Principles alone cannot guarantee ethical AI,” Nature Machine Intelligence, vol. 1, pp. 501–507, 2019.

[24] K. Sonne Gowda, S. P. Smitha, G. Balaraju, B. K. Ravi and N. R. Shobha Rani, "Developing an Application for Managing and Creating Private Keys for Cryptographic Communication," 2024 Asian Conference on Intelligent Technologies (ACOIT), KOLAR, India, 2024, pp. 1-5, doi: 10.1109/ACOIT62457.2024.10941108.

Authorized licensed use limited to: PES University Bengaluru. Downloaded on October 05,2026 at 05:23:44 UTC from IEEE Xplore. Restrictions apply.